



API Reference

IAM Access Analyzer



API Version 2019-11-01

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

IAM Access Analyzer: API Reference

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
ApplyArchiveRule	4
Request Syntax	4
URI Request Parameters	4
Request Body	4
Response Syntax	5
Response Elements	5
Errors	5
See Also	6
CancelPolicyGeneration	8
Request Syntax	8
URI Request Parameters	8
Request Body	8
Response Syntax	8
Response Elements	8
Errors	8
See Also	9
CheckAccessNotGranted	11
Request Syntax	11
URI Request Parameters	11
Request Body	11
Response Syntax	12
Response Elements	12
Errors	13
See Also	14
CheckNoNewAccess	16
Request Syntax	16
URI Request Parameters	16
Request Body	16
Response Syntax	17
Response Elements	17
Errors	18
See Also	19

CheckNoPublicAccess	21
Request Syntax	21
URI Request Parameters	21
Request Body	21
Response Syntax	22
Response Elements	22
Errors	23
See Also	24
CreateAccessPreview	26
Request Syntax	26
URI Request Parameters	26
Request Body	26
Response Syntax	27
Response Elements	27
Errors	27
See Also	29
CreateAnalyzer	31
Request Syntax	31
URI Request Parameters	31
Request Body	31
Response Syntax	33
Response Elements	33
Errors	34
See Also	35
CreateArchiveRule	37
Request Syntax	37
URI Request Parameters	37
Request Body	38
Response Syntax	38
Response Elements	38
Errors	38
See Also	40
DeleteAnalyzer	42
Request Syntax	42
URI Request Parameters	42
Request Body	42

Response Syntax	42
Response Elements	42
Errors	43
See Also	44
DeleteArchiveRule	45
Request Syntax	45
URI Request Parameters	45
Request Body	45
Response Syntax	45
Response Elements	46
Errors	46
See Also	47
GenerateFindingRecommendation	48
Request Syntax	48
URI Request Parameters	48
Request Body	48
Response Syntax	48
Response Elements	48
Errors	49
See Also	49
GetAccessPreview	51
Request Syntax	51
URI Request Parameters	51
Request Body	51
Response Syntax	51
Response Elements	52
Errors	52
See Also	53
GetAnalyzedResource	55
Request Syntax	55
URI Request Parameters	55
Request Body	55
Response Syntax	55
Response Elements	56
Errors	56
See Also	57

GetAnalyzer	59
Request Syntax	59
URI Request Parameters	59
Request Body	59
Response Syntax	59
Response Elements	60
Errors	60
See Also	61
GetArchiveRule	63
Request Syntax	63
URI Request Parameters	63
Request Body	63
Response Syntax	63
Response Elements	64
Errors	64
See Also	65
GetFinding	67
Request Syntax	67
URI Request Parameters	67
Request Body	67
Response Syntax	67
Response Elements	68
Errors	69
See Also	70
GetFindingRecommendation	71
Request Syntax	71
URI Request Parameters	71
Request Body	71
Response Syntax	72
Response Elements	72
Errors	73
See Also	75
GetFindingsStatistics	76
Request Syntax	76
URI Request Parameters	76
Request Body	76

Response Syntax	76
Response Elements	77
Errors	77
See Also	78
GetFindingV2	80
Request Syntax	80
URI Request Parameters	80
Request Body	80
Response Syntax	81
Response Elements	81
Errors	83
See Also	84
GetGeneratedPolicy	86
Request Syntax	86
URI Request Parameters	86
Request Body	86
Response Syntax	87
Response Elements	87
Errors	88
See Also	89
ListAccessPreviewFindings	90
Request Syntax	90
URI Request Parameters	90
Request Body	90
Response Syntax	91
Response Elements	92
Errors	93
See Also	94
ListAccessPreviews	95
Request Syntax	95
URI Request Parameters	95
Request Body	95
Response Syntax	95
Response Elements	96
Errors	96
See Also	97

ListAnalyzedResources	99
Request Syntax	99
URI Request Parameters	99
Request Body	99
Response Syntax	100
Response Elements	100
Errors	101
See Also	102
ListAnalyzers	103
Request Syntax	103
URI Request Parameters	103
Request Body	103
Response Syntax	103
Response Elements	104
Errors	104
See Also	105
ListArchiveRules	107
Request Syntax	107
URI Request Parameters	107
Request Body	107
Response Syntax	107
Response Elements	108
Errors	108
See Also	109
ListFindings	111
Request Syntax	111
URI Request Parameters	111
Request Body	112
Response Syntax	113
Response Elements	113
Errors	114
See Also	115
ListFindingsV2	116
Request Syntax	116
URI Request Parameters	116
Request Body	116

Response Syntax	117
Response Elements	118
Errors	118
See Also	120
ListPolicyGenerations	121
Request Syntax	121
URI Request Parameters	121
Request Body	121
Response Syntax	121
Response Elements	122
Errors	122
See Also	123
ListTagsForResource	125
Request Syntax	125
URI Request Parameters	125
Request Body	125
Response Syntax	125
Response Elements	125
Errors	126
See Also	127
StartPolicyGeneration	128
Request Syntax	128
URI Request Parameters	128
Request Body	128
Response Syntax	129
Response Elements	129
Errors	130
See Also	131
StartResourceScan	133
Request Syntax	133
URI Request Parameters	133
Request Body	133
Response Syntax	134
Response Elements	134
Errors	134
See Also	135

TagResource	137
Request Syntax	137
URI Request Parameters	137
Request Body	137
Response Syntax	137
Response Elements	138
Errors	138
See Also	139
UntagResource	140
Request Syntax	140
URI Request Parameters	140
Request Body	140
Response Syntax	140
Response Elements	140
Errors	140
See Also	142
UpdateAnalyzer	143
Request Syntax	143
URI Request Parameters	143
Request Body	143
Response Syntax	144
Response Elements	144
Errors	144
See Also	146
UpdateArchiveRule	147
Request Syntax	147
URI Request Parameters	147
Request Body	148
Response Syntax	148
Response Elements	148
Errors	148
See Also	149
UpdateFindings	151
Request Syntax	151
URI Request Parameters	151
Request Body	151

Response Syntax	152
Response Elements	152
Errors	152
See Also	154
ValidatePolicy	155
Request Syntax	155
URI Request Parameters	155
Request Body	155
Response Syntax	157
Response Elements	158
Errors	158
See Also	159
Data Types	160
Access	164
Contents	164
See Also	164
AccessPreview	165
Contents	165
See Also	166
AccessPreviewFinding	167
Contents	167
See Also	170
AccessPreviewStatusReason	171
Contents	171
See Also	171
AccessPreviewSummary	172
Contents	172
See Also	173
AclGrantee	174
Contents	174
See Also	174
AnalysisRule	175
Contents	175
See Also	175
AnalysisRuleCriteria	176
Contents	176

See Also	176
AnalyzedResource	178
Contents	178
See Also	180
AnalyzedResourceSummary	181
Contents	181
See Also	182
AnalyzerConfiguration	183
Contents	183
See Also	183
AnalyzerSummary	184
Contents	184
See Also	186
ArchiveRuleSummary	187
Contents	187
See Also	188
CloudTrailDetails	189
Contents	189
See Also	190
CloudTrailProperties	191
Contents	191
See Also	191
Configuration	193
Contents	193
See Also	195
Criterion	196
Contents	196
See Also	197
DynamodbStreamConfiguration	198
Contents	198
See Also	198
DynamodbTableConfiguration	199
Contents	199
See Also	199
EbsSnapshotConfiguration	200
Contents	200

See Also	201
EcrRepositoryConfiguration	202
Contents	202
See Also	202
EfsFileSystemConfiguration	203
Contents	203
See Also	203
ExternalAccessDetails	204
Contents	204
See Also	205
ExternalAccessFindingsStatistics	206
Contents	206
See Also	207
Finding	208
Contents	208
See Also	211
FindingAggregationAccountDetails	212
Contents	212
See Also	212
FindingDetails	213
Contents	213
See Also	214
FindingSource	215
Contents	215
See Also	215
FindingSourceDetail	216
Contents	216
See Also	216
FindingsStatistics	217
Contents	217
See Also	217
FindingSummary	219
Contents	219
See Also	222
FindingSummaryV2	223
Contents	223

See Also	225
GeneratedPolicy	226
Contents	226
See Also	226
GeneratedPolicyProperties	227
Contents	227
See Also	227
GeneratedPolicyResult	229
Contents	229
See Also	229
IamRoleConfiguration	230
Contents	230
See Also	230
InlineArchiveRule	231
Contents	231
See Also	231
InternalAccessAnalysisRule	232
Contents	232
See Also	232
InternalAccessAnalysisRuleCriteria	233
Contents	233
See Also	234
InternalAccessConfiguration	235
Contents	235
See Also	235
InternalAccessDetails	236
Contents	236
See Also	238
InternalAccessFindingsStatistics	239
Contents	239
See Also	240
InternalAccessResourceTypeDetails	241
Contents	241
See Also	241
InternetConfiguration	242
Contents	242

See Also	242
JobDetails	243
Contents	243
See Also	244
JobError	245
Contents	245
See Also	245
KmsGrantConfiguration	246
Contents	246
See Also	247
KmsGrantConstraints	248
Contents	248
See Also	248
KmsKeyConfiguration	249
Contents	249
See Also	249
Location	251
Contents	251
See Also	251
NetworkOriginConfiguration	252
Contents	252
See Also	252
PathElement	254
Contents	254
See Also	255
PolicyGeneration	256
Contents	256
See Also	257
PolicyGenerationDetails	258
Contents	258
See Also	258
Position	259
Contents	259
See Also	259
RdsDbClusterSnapshotAttributeValue	260
Contents	260

See Also	260
RdsDbClusterSnapshotConfiguration	262
Contents	262
See Also	262
RdsDbSnapshotAttributeValue	264
Contents	264
See Also	264
RdsDbSnapshotConfiguration	266
Contents	266
See Also	266
ReasonSummary	268
Contents	268
See Also	268
RecommendationError	269
Contents	269
See Also	269
RecommendedStep	270
Contents	270
See Also	270
ResourceTypeDetails	271
Contents	271
See Also	271
S3AccessPointConfiguration	272
Contents	272
See Also	273
S3BucketAclGrantConfiguration	274
Contents	274
See Also	274
S3BucketConfiguration	275
Contents	275
See Also	276
S3ExpressDirectoryAccessPointConfiguration	277
Contents	277
See Also	277
S3ExpressDirectoryBucketConfiguration	279
Contents	279

See Also	279
S3PublicAccessBlockConfiguration	281
Contents	281
See Also	281
SecretsManagerSecretConfiguration	282
Contents	282
See Also	282
SnsTopicConfiguration	284
Contents	284
See Also	284
SortCriteria	285
Contents	285
See Also	285
Span	286
Contents	286
See Also	286
SqsQueueConfiguration	287
Contents	287
See Also	287
StatusReason	288
Contents	288
See Also	288
Substring	289
Contents	289
See Also	289
Trail	290
Contents	290
See Also	290
TrailProperties	292
Contents	292
See Also	292
UnusedAccessConfiguration	294
Contents	294
See Also	294
UnusedAccessFindingsStatistics	295
Contents	295

See Also	296
UnusedAccessTypeStatistics	297
Contents	297
See Also	297
UnusedAction	298
Contents	298
See Also	298
UnusedIamRoleDetails	299
Contents	299
See Also	299
UnusedIamUserAccessKeyDetails	300
Contents	300
See Also	300
UnusedIamUserPasswordDetails	301
Contents	301
See Also	301
UnusedPermissionDetails	302
Contents	302
See Also	302
UnusedPermissionsRecommendedStep	303
Contents	303
See Also	304
ValidatePolicyFinding	305
Contents	305
See Also	306
ValidationExceptionField	307
Contents	307
See Also	307
VpcConfiguration	308
Contents	308
See Also	308
Common Parameters	309
Common Error Types	312

Welcome

AWS Identity and Access Management Access Analyzer helps you to set, verify, and refine your IAM policies by providing a suite of capabilities. Its features include findings for external, internal, and unused access, basic and custom policy checks for validating policies, and policy generation to generate fine-grained policies. To start using IAM Access Analyzer to identify external, internal, or unused access, you first need to create an analyzer.

External access analyzers help you identify potential risks of accessing resources by enabling you to identify any resource policies that grant access to an external principal. It does this by using logic-based reasoning to analyze resource-based policies in your AWS environment. An external principal can be another AWS account, a root user, an IAM user or role, a federated user, an AWS service, or an anonymous user. You can also use IAM Access Analyzer to preview public and cross-account access to your resources before deploying permissions changes.

Internal access analyzers help you identify which principals within your organization or account have access to selected resources. This analysis supports implementing the principle of least privilege by ensuring that your specified resources can only be accessed by the intended principals within your organization.

Unused access analyzers help you identify potential identity access risks by enabling you to identify unused IAM roles, unused access keys, unused console passwords, and IAM principals with unused service and action-level permissions.

Beyond findings, IAM Access Analyzer provides basic and custom policy checks to validate IAM policies before deploying permissions changes. You can use policy generation to refine permissions by attaching a policy generated using access activity logged in CloudTrail logs.

This guide describes the IAM Access Analyzer operations that you can call programmatically. For general information about IAM Access Analyzer, see [Using AWS Identity and Access Management Access Analyzer](#) in the **IAM User Guide**.

This document was last published on April 5, 2026.

Actions

The following actions are supported:

- [ApplyArchiveRule](#)
- [CancelPolicyGeneration](#)
- [CheckAccessNotGranted](#)
- [CheckNoNewAccess](#)
- [CheckNoPublicAccess](#)
- [CreateAccessPreview](#)
- [CreateAnalyzer](#)
- [CreateArchiveRule](#)
- [DeleteAnalyzer](#)
- [DeleteArchiveRule](#)
- [GenerateFindingRecommendation](#)
- [GetAccessPreview](#)
- [GetAnalyzedResource](#)
- [GetAnalyzer](#)
- [GetArchiveRule](#)
- [GetFinding](#)
- [GetFindingRecommendation](#)
- [GetFindingsStatistics](#)
- [GetFindingV2](#)
- [GetGeneratedPolicy](#)
- [ListAccessPreviewFindings](#)
- [ListAccessPreviews](#)
- [ListAnalyzedResources](#)
- [ListAnalyzers](#)
- [ListArchiveRules](#)
- [ListFindings](#)
- [ListFindingsV2](#)

- [ListPolicyGenerations](#)
- [ListTagsForResource](#)
- [StartPolicyGeneration](#)
- [StartResourceScan](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateAnalyzer](#)
- [UpdateArchiveRule](#)
- [UpdateFindings](#)
- [ValidatePolicy](#)

ApplyArchiveRule

Retroactively applies the archive rule to existing findings that meet the archive rule criteria.

Request Syntax

```
PUT /archive-rule HTTP/1.1
Content-type: application/json

{
  "analyzerArn": "string",
  "clientToken": "string",
  "ruleName": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

analyzerArn

The Amazon resource name (ARN) of the analyzer.

Type: String

Pattern: `^[^:]*:[^:]*:[^:]*:[^:]*:[^:]*:analyzer/.{1,255}`

Required: Yes

clientToken

A client token.

Type: String

Required: No

ruleName

The name of the rule to apply.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[A-Za-z][A-Za-z0-9_.-]*`

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

resourceId

The ID of the resource.

resourceType

The type of the resource.

HTTP Status Code: 404

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CancelPolicyGeneration

Cancels the requested policy generation.

Request Syntax

```
PUT /policy/generation/jobId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

jobId

The JobId that is returned by the StartPolicyGeneration operation. The JobId can be used with GetGeneratedPolicy to retrieve the generated policies or used with CancelPolicyGeneration to cancel the policy generation request.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CheckAccessNotGranted

Checks whether the specified access isn't allowed by a policy.

Request Syntax

```
POST /policy/check-access-not-granted HTTP/1.1
Content-type: application/json
```

```
{
  "access": [
    {
      "actions": [ "string" ],
      "resources": [ "string" ]
    }
  ],
  "policyDocument": "string",
  "policyType": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

access

An access object containing the permissions that shouldn't be granted by the specified policy. If only actions are specified, IAM Access Analyzer checks for access to perform at least one of the actions on any resource in the policy. If only resources are specified, then IAM Access Analyzer checks for access to perform any action on at least one of the resources. If both actions and resources are specified, IAM Access Analyzer checks for access to perform at least one of the specified actions on at least one of the specified resources.

Type: Array of [Access](#) objects

Array Members: Minimum number of 0 items. Maximum number of 1 item.

Required: Yes

policyDocument

The JSON policy document to use as the content for the policy.

Type: String

Required: Yes

policyType

The type of policy. Identity policies grant permissions to IAM principals. Identity policies include managed and inline policies for IAM roles, users, and groups.

Resource policies grant permissions on AWS resources. Resource policies include trust policies for IAM roles and bucket policies for Amazon S3 buckets.

Type: String

Valid Values: IDENTITY_POLICY | RESOURCE_POLICY

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "message": "string",
  "reasons": [
    {
      "description": "string",
      "statementId": "string",
      "statementIndex": number
    }
  ],
  "result": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

message

The message indicating whether the specified access is allowed.

Type: String

reasons

A description of the reasoning of the result.

Type: Array of [ReasonSummary](#) objects

result

The result of the check for whether the access is allowed. If the result is PASS, the specified policy doesn't allow any of the specified permissions in the access object. If the result is FAIL, the specified policy might allow some or all of the permissions in the access object.

Type: String

Valid Values: PASS | FAIL

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

InvalidParameterException

The specified parameter is invalid.

HTTP Status Code: 400

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

UnprocessableEntityException

The specified entity could not be processed.

HTTP Status Code: 422

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CheckNoNewAccess

Checks whether new access is allowed for an updated policy when compared to the existing policy.

You can find examples for reference policies and learn how to set up and run a custom policy check for new access in the [IAM Access Analyzer custom policy checks samples](#) repository on GitHub. The reference policies in this repository are meant to be passed to the `existingPolicyDocument` request parameter.

Request Syntax

```
POST /policy/check-no-new-access HTTP/1.1
Content-type: application/json

{
  "existingPolicyDocument": "string",
  "newPolicyDocument": "string",
  "policyType": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

existingPolicyDocument

The JSON policy document to use as the content for the existing policy.

Type: String

Required: Yes

newPolicyDocument

The JSON policy document to use as the content for the updated policy.

Type: String

Required: Yes

policyType

The type of policy to compare. Identity policies grant permissions to IAM principals. Identity policies include managed and inline policies for IAM roles, users, and groups.

Resource policies grant permissions on AWS resources. Resource policies include trust policies for IAM roles and bucket policies for Amazon S3 buckets. You can provide a generic input such as identity policy or resource policy or a specific input such as managed policy or Amazon S3 bucket policy.

Type: String

Valid Values: IDENTITY_POLICY | RESOURCE_POLICY

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "message": "string",
  "reasons": [
    {
      "description": "string",
      "statementId": "string",
      "statementIndex": number
    }
  ],
  "result": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

message

The message indicating whether the updated policy allows new access.

Type: String

reasons

A description of the reasoning of the result.

Type: Array of [ReasonSummary](#) objects

result

The result of the check for new access. If the result is PASS, no new access is allowed by the updated policy. If the result is FAIL, the updated policy might allow new access.

Type: String

Valid Values: PASS | FAIL

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

InvalidParameterException

The specified parameter is invalid.

HTTP Status Code: 400

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

UnprocessableEntityException

The specified entity could not be processed.

HTTP Status Code: 422

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CheckNoPublicAccess

Checks whether a resource policy can grant public access to the specified resource type.

Request Syntax

```
POST /policy/check-no-public-access HTTP/1.1
Content-type: application/json
```

```
{
  "policyDocument": "string",
  "resourceType": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

policyDocument

The JSON policy document to evaluate for public access.

Type: String

Required: Yes

resourceType

The type of resource to evaluate for public access. For example, to check for public access to Amazon S3 buckets, you can choose `AWS::S3::Bucket` for the resource type.

For resource types not supported as valid values, IAM Access Analyzer will return an error.

Type: String

Valid Values: `AWS::DynamoDB::Table` | `AWS::DynamoDB::Stream` |
`AWS::EFS::FileSystem` | `AWS::OpenSearchService::Domain` |
`AWS::Kinesis::Stream` | `AWS::Kinesis::StreamConsumer` | `AWS::KMS::Key`

| AWS::Lambda::Function | AWS::S3::Bucket | AWS::S3::AccessPoint
| AWS::S3Express::DirectoryBucket | AWS::S3::Glacier |
AWS::S3Outposts::Bucket | AWS::S3Outposts::AccessPoint |
AWS::SecretsManager::Secret | AWS::SNS::Topic | AWS::SQS::Queue
| AWS::IAM::AssumeRolePolicyDocument | AWS::S3Tables::TableBucket
| AWS::ApiGateway::RestApi | AWS::CodeArtifact::Domain |
AWS::Backup::BackupVault | AWS::CloudTrail::Dashboard |
AWS::CloudTrail::EventDataStore | AWS::S3Tables::Table |
AWS::S3Express::AccessPoint

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "message": "string",
  "reasons": [
    {
      "description": "string",
      "statementId": "string",
      "statementIndex": number
    }
  ],
  "result": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

message

The message indicating whether the specified policy allows public access to resources.

Type: String

reasons

A list of reasons why the specified resource policy grants public access for the resource type.

Type: Array of [ReasonSummary](#) objects

result

The result of the check for public access to the specified resource type. If the result is PASS, the policy doesn't allow public access to the specified resource type. If the result is FAIL, the policy might allow public access to the specified resource type.

Type: String

Valid Values: PASS | FAIL

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

InvalidParameterException

The specified parameter is invalid.

HTTP Status Code: 400

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

UnprocessableEntityException

The specified entity could not be processed.

HTTP Status Code: 422

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateAccessPreview

Creates an access preview that allows you to preview IAM Access Analyzer findings for your resource before deploying resource permissions.

Request Syntax

```
PUT /access-preview HTTP/1.1
Content-type: application/json

{
  "analyzerArn": "string",
  "clientToken": "string",
  "configurations": {
    "string" : { ... }
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

analyzerArn

The [ARN of the account analyzer](#) used to generate the access preview. You can only create an access preview for analyzers with an Account type and Active status.

Type: String

Pattern: `[\^:]*:[\^:]*:[\^:]*:[\^:]*:[\^:]*:analyzer/.{1,255}`

Required: Yes

clientToken

A client token.

Type: String

Required: No

configurations

Access control configuration for your resource that is used to generate the access preview. The access preview includes findings for external access allowed to the resource with the proposed access control configuration. The configuration must contain exactly one element.

Type: String to [Configuration](#) object map

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "id": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

id

The unique ID for the access preview.

Type: String

Pattern: `[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

A conflict exception error.

resourceId

The ID of the resource.

resourceType

The resource type.

HTTP Status Code: 409

InternalServerErrorException

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

resourceId

The ID of the resource.

resourceType

The type of the resource.

HTTP Status Code: 404

ServiceQuotaExceededException

Service quote met error.

resourceId

The resource ID.

resourceType

The resource type.

HTTP Status Code: 402

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateAnalyzer

Creates an analyzer for your account.

Request Syntax

```
PUT /analyzer HTTP/1.1
Content-type: application/json

{
  "analyzerName": "string",
  "archiveRules": [
    {
      "filter": {
        "string": {
          "contains": [ "string" ],
          "eq": [ "string" ],
          "exists": boolean,
          "neq": [ "string" ]
        }
      },
      "ruleName": "string"
    }
  ],
  "clientToken": "string",
  "configuration": { ... },
  "tags": {
    "string": "string"
  },
  "type": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

analyzerName

The name of the analyzer to create.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [A-Za-z][A-Za-z0-9_.-]*

Required: Yes

archiveRules

Specifies the archive rules to add for the analyzer. Archive rules automatically archive findings that meet the criteria you define for the rule.

Type: Array of [InlineArchiveRule](#) objects

Required: No

clientToken

A client token.

Type: String

Required: No

configuration

Specifies the configuration of the analyzer. If the analyzer is an unused access analyzer, the specified scope of unused access is used for the configuration. If the analyzer is an internal access analyzer, the specified internal access analysis rules are used for the configuration.

Type: [AnalyzerConfiguration](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

tags

An array of key-value pairs to apply to the analyzer. You can use the set of Unicode letters, digits, whitespace, `_`, `.`, `/`, `=`, `+`, and `-`.

For the tag key, you can specify a value that is 1 to 128 characters in length and cannot be prefixed with `aws :`.

For the tag value, you can specify a value that is 0 to 256 characters in length.

Type: String to string map

Required: No

type

The type of analyzer to create. You can create only one analyzer per account per Region. You can create up to 5 analyzers per organization per Region.

Type: String

Valid Values: ACCOUNT | ORGANIZATION | ACCOUNT_UNUSED_ACCESS | ORGANIZATION_UNUSED_ACCESS | ACCOUNT_INTERNAL_ACCESS | ORGANIZATION_INTERNAL_ACCESS

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "arn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The ARN of the analyzer that was created by the request.

Type: String

Pattern: `[\^:]*:[\^:]*:[\^:]*:[\^:]*:[\^:]*:analyzer/.{1,255}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

A conflict exception error.

resourceId

The ID of the resource.

resourceType

The resource type.

HTTP Status Code: 409

InternalServerError

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ServiceQuotaExceededException

Service quote met error.

resourceId

The resource ID.

resourceType

The resource type.

HTTP Status Code: 402

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateArchiveRule

Creates an archive rule for the specified analyzer. Archive rules automatically archive new findings that meet the criteria you define when you create the rule.

To learn about filter keys that you can use to create an archive rule, see [IAM Access Analyzer filter keys](#) in the **IAM User Guide**.

Request Syntax

```
PUT /analyzer/analyzerName/archive-rule HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "filter": {
    "string" : {
      "contains": [ "string" ],
      "eq": [ "string" ],
      "exists": boolean,
      "neq": [ "string" ]
    }
  },
  "ruleName": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

analyzerName

The name of the created analyzer.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [A-Za-z][A-Za-z0-9_.-]*

Required: Yes

Request Body

The request accepts the following data in JSON format.

clientToken

A client token.

Type: String

Required: No

filter

The criteria for the rule.

Type: String to [Criterion](#) object map

Required: Yes

ruleName

The name of the rule to create.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[A-Za-z][A-Za-z0-9_.-]*`

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

A conflict exception error.

resourceId

The ID of the resource.

resourceType

The resource type.

HTTP Status Code: 409

InternalServerErrorException

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

resourceId

The ID of the resource.

resourceType

The type of the resource.

HTTP Status Code: 404

ServiceQuotaExceededException

Service quote met error.

resourceId

The resource ID.

resourceType

The resource type.

HTTP Status Code: 402

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteAnalyzer

Deletes the specified analyzer. When you delete an analyzer, IAM Access Analyzer is disabled for the account or organization in the current or specific Region. All findings that were generated by the analyzer are deleted. You cannot undo this action.

Request Syntax

```
DELETE /analyzer/analyzerName?clientToken=clientToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

analyzerName

The name of the analyzer to delete.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[A-Za-z][A-Za-z0-9_.-]*`

Required: Yes

clientToken

A client token.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

resourceId

The ID of the resource.

resourceType

The type of the resource.

HTTP Status Code: 404

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteArchiveRule

Deletes the specified archive rule.

Request Syntax

```
DELETE /analyzer/analyzerName/archive-rule/ruleName?clientToken=clientToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

analyzerName

The name of the analyzer that associated with the archive rule to delete.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [A-Za-z][A-Za-z0-9_.-]*

Required: Yes

clientToken

A client token.

ruleName

The name of the rule to delete.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [A-Za-z][A-Za-z0-9_.-]*

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

resourceId

The ID of the resource.

resourceType

The type of the resource.

HTTP Status Code: 404

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GenerateFindingRecommendation

Creates a recommendation for an unused permissions finding.

Request Syntax

```
POST /recommendation/id?analyzerArn=analyzerArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

analyzerArn

The [ARN of the analyzer](#) used to generate the finding recommendation.

Pattern: `[\^:]*:[\^:]*:[\^:]*:[\^:]*:[\^:]*:analyzer/.[1,255}`

Required: Yes

id

The unique ID for the finding recommendation.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetAccessPreview

Retrieves information about an access preview for the specified analyzer.

Request Syntax

```
GET /access-preview/accessPreviewId?analyzerArn=analyzerArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

accessPreviewId

The unique ID for the access preview.

Pattern: `[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}`

Required: Yes

analyzerArn

The [ARN of the analyzer](#) used to generate the access preview.

Pattern: `[\^:]*:[\^:]*:[\^:]*:[\^:]*:[\^:]*:analyzer/.{1,255}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "accessPreview": {
    "analyzerArn": "string",
```

```
  "configurations": {
    "string" : { ... }
  },
  "createdAt": "string",
  "id": "string",
  "status": "string",
  "statusReason": {
    "code": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

accessPreview

An object that contains information about the access preview.

Type: [AccessPreview](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

resourceId

The ID of the resource.

resourceType

The type of the resource.

HTTP Status Code: 404

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetAnalyzedResource

Retrieves information about a resource that was analyzed.

Note

This action is supported only for external access analyzers.

Request Syntax

```
GET /analyzed-resource?analyzerArn=analyzerArn&resourceArn=resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

analyzerArn

The [ARN of the analyzer](#) to retrieve information from.

Pattern: `[\^:]*:[\^:]*:[\^:]*:[\^:]*:[\^:]*:analyzer/.{1,255}`

Required: Yes

resourceArn

The ARN of the resource to retrieve information about.

Pattern: `arn:[\^:]*:[\^:]*:[\^:]*:[\^:]*:.*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{
  "resource": {
    "actions": [ "string" ],
    "analyzedAt": "string",
    "createdAt": "string",
    "error": "string",
    "isPublic": boolean,
    "resourceArn": "string",
    "resourceOwnerAccount": "string",
    "resourceType": "string",
    "sharedVia": [ "string" ],
    "status": "string",
    "updatedAt": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

resource

An AnalyzedResource object that contains information that IAM Access Analyzer found when it analyzed the resource.

Type: [AnalyzedResource](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

resourceId

The ID of the resource.

resourceType

The type of the resource.

HTTP Status Code: 404

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetAnalyzer

Retrieves information about the specified analyzer.

Request Syntax

```
GET /analyzer/analyzerName HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

analyzerName

The name of the analyzer retrieved.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [A-Za-z][A-Za-z0-9_.-]*

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "analyzer": {
    "arn": "string",
    "configuration": { ... },
    "createdAt": "string",
    "lastResourceAnalyzed": "string",
    "lastResourceAnalyzedAt": "string",
    "name": "string",
    "status": "string",
    "statusReason": {
```

```
    "code": "string"  
  },  
  "tags": {  
    "string" : "string"  
  },  
  "type": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

analyzer

An `AnalyzerSummary` object that contains information about the analyzer.

Type: [AnalyzerSummary](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

resourceId

The ID of the resource.

resourceType

The type of the resource.

HTTP Status Code: 404

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetArchiveRule

Retrieves information about an archive rule.

To learn about filter keys that you can use to create an archive rule, see [IAM Access Analyzer filter keys](#) in the **IAM User Guide**.

Request Syntax

```
GET /analyzer/analyzerName/archive-rule/ruleName HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

analyzerName

The name of the analyzer to retrieve rules from.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[A-Za-z][A-Za-z0-9_.-]*`

Required: Yes

ruleName

The name of the rule to retrieve.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[A-Za-z][A-Za-z0-9_.-]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{
  "archiveRule": {
    "createdAt": "string",
    "filter": {
      "string": {
        "contains": [ "string" ],
        "eq": [ "string" ],
        "exists": boolean,
        "neq": [ "string" ]
      }
    },
    "ruleName": "string",
    "updatedAt": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

archiveRule

Contains information about an archive rule. Archive rules automatically archive new findings that meet the criteria you define when you create the rule.

Type: [ArchiveRuleSummary](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

resourceId

The ID of the resource.

resourceType

The type of the resource.

HTTP Status Code: 404

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetFinding

Retrieves information about the specified finding. `GetFinding` and `GetFindingV2` both use `access-analyzer:GetFinding` in the Action element of an IAM policy statement. You must have permission to perform the `access-analyzer:GetFinding` action.

Note

`GetFinding` is supported only for external access analyzers. You must use `GetFindingV2` for internal and unused access analyzers.

Request Syntax

```
GET /finding/id?analyzerArn=analyzerArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

analyzerArn

The [ARN of the analyzer](#) that generated the finding.

Pattern: `[\^:]*:[\^:]*:[\^:]*:[\^:]*:[\^:]*:analyzer/.[1,255}`

Required: Yes

id

The ID of the finding to retrieve.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Content-type: application/json

```
{
  "finding": {
    "action": [ "string" ],
    "analyzedAt": "string",
    "condition": {
      "string" : "string"
    },
    "createdAt": "string",
    "error": "string",
    "id": "string",
    "isPublic": boolean,
    "principal": {
      "string" : "string"
    },
    "resource": "string",
    "resourceControlPolicyRestriction": "string",
    "resourceOwnerAccount": "string",
    "resourceType": "string",
    "sources": [
      {
        "detail": {
          "accessPointAccount": "string",
          "accessPointArn": "string"
        },
        "type": "string"
      }
    ],
    "status": "string",
    "updatedAt": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

finding

A finding object that contains finding details.

Type: [Finding](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

resourceId

The ID of the resource.

resourceType

The type of the resource.

HTTP Status Code: 404

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetFindingRecommendation

Retrieves information about a finding recommendation for the specified analyzer.

Request Syntax

```
GET /recommendation/id?  
analyzerArn=analyzerArn&maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

analyzerArn

The [ARN of the analyzer](#) used to generate the finding recommendation.

Pattern: `[\^:]*:[\^:]*:[\^:]*:[\^:]*:[\^:]*:analyzer/.[1,255}`

Required: Yes

id

The unique ID for the finding recommendation.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

maxResults

The maximum number of results to return in the response.

Valid Range: Minimum value of 1. Maximum value of 1000.

nextToken

A token used for pagination of results returned.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "completedAt": "string",
  "error": {
    "code": "string",
    "message": "string"
  },
  "nextToken": "string",
  "recommendationType": "string",
  "recommendedSteps": [
    { ... }
  ],
  "resourceArn": "string",
  "startedAt": "string",
  "status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

completedAt

The time at which the retrieval of the finding recommendation was completed.

Type: Timestamp

error

Detailed information about the reason that the retrieval of a recommendation for the finding failed.

Type: [RecommendationError](#) object

nextToken

A token used for pagination of results returned.

Type: String

recommendationType

The type of recommendation for the finding.

Type: String

Valid Values: UnusedPermissionRecommendation

recommendedSteps

A group of recommended steps for the finding.

Type: Array of [RecommendedStep](#) objects

resourceArn

The ARN of the resource of the finding.

Type: String

Pattern: arn:[^:]*:[^:]*:[^:]*:[^:]*:.*

startedAt

The time at which the retrieval of the finding recommendation was started.

Type: Timestamp

status

The status of the retrieval of the finding recommendation.

Type: String

Valid Values: SUCCEEDED | FAILED | IN_PROGRESS

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

resourceId

The ID of the resource.

resourceType

The type of the resource.

HTTP Status Code: 404

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetFindingsStatistics

Retrieves a list of aggregated finding statistics for an external access or unused access analyzer.

Request Syntax

```
POST /analyzer/findings/statistics HTTP/1.1
Content-type: application/json
```

```
{
  "analyzerArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[analyzerArn](#)

The [ARN of the analyzer](#) used to generate the statistics.

Type: String

Pattern: `[\^:]*:[\^:]*:[\^:]*:[\^:]*:[\^:]*:analyzer/.[1,255}`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "findingsStatistics": [
    { ... }
  ],
  "lastUpdatedAt": "string"
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

findingsStatistics

A group of external access or unused access findings statistics.

Type: Array of [FindingsStatistics](#) objects

lastUpdatedAt

The time at which the retrieval of the findings statistics was last updated. If the findings statistics have not been previously retrieved for the specified analyzer, this field will not be populated.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

resourceId

The ID of the resource.

resourceType

The type of the resource.

HTTP Status Code: 404

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetFindingV2

Retrieves information about the specified finding. `GetFinding` and `GetFindingV2` both use `access-analyzer:GetFinding` in the Action element of an IAM policy statement. You must have permission to perform the `access-analyzer:GetFinding` action.

Request Syntax

```
GET /findingv2/id?analyzerArn=analyzerArn&maxResults=maxResults&nextToken=nextToken
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

analyzerArn

The [ARN of the analyzer](#) that generated the finding.

Pattern: `[\^:]*:[\^:]*:[\^:]*:[\^:]*:[\^:]*:analyzer/.[1,255}`

Required: Yes

id

The ID of the finding to retrieve.

Required: Yes

maxResults

The maximum number of results to return in the response.

nextToken

A token used for pagination of results returned.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "analyzedAt": "string",
  "createdAt": "string",
  "error": "string",
  "findingDetails": [
    { ... }
  ],
  "findingType": "string",
  "id": "string",
  "nextToken": "string",
  "resource": "string",
  "resourceOwnerAccount": "string",
  "resourceType": "string",
  "status": "string",
  "updatedAt": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[analyzedAt](#)

The time at which the resource-based policy or IAM entity that generated the finding was analyzed.

Type: Timestamp

[createdAt](#)

The time at which the finding was created.

Type: Timestamp

[error](#)

An error.

Type: String

findingDetails

A localized message that explains the finding and provides guidance on how to address it.

Type: Array of [FindingDetails](#) objects

findingType

The type of the finding. For external access analyzers, the type is `ExternalAccess`. For unused access analyzers, the type can be `UnusedIAMRole`, `UnusedIAMUserAccessKey`, `UnusedIAMUserPassword`, or `UnusedPermission`. For internal access analyzers, the type is `InternalAccess`.

Type: String

Valid Values: `ExternalAccess` | `UnusedIAMRole` | `UnusedIAMUserAccessKey` | `UnusedIAMUserPassword` | `UnusedPermission` | `InternalAccess`

id

The ID of the finding to retrieve.

Type: String

nextToken

A token used for pagination of results returned.

Type: String

resource

The resource that generated the finding.

Type: String

resourceOwnerAccount

The AWS account ID that owns the resource.

Type: String

resourceType

The type of the resource identified in the finding.

Type: String

Valid Values: AWS::S3::Bucket | AWS::IAM::Role | AWS::SQS::Queue |
AWS::Lambda::Function | AWS::Lambda::LayerVersion | AWS::KMS::Key
| AWS::SecretsManager::Secret | AWS::EFS::FileSystem |
AWS::EC2::Snapshot | AWS::ECR::Repository | AWS::RDS::DBSnapshot
| AWS::RDS::DBClusterSnapshot | AWS::SNS::Topic |
AWS::S3Express::DirectoryBucket | AWS::DynamoDB::Table |
AWS::DynamoDB::Stream | AWS::IAM::User

status

The status of the finding.

Type: String

Valid Values: ACTIVE | ARCHIVED | RESOLVED

updatedAt

The time at which the finding was updated.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

resourceId

The ID of the resource.

resourceType

The type of the resource.

HTTP Status Code: 404

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetGeneratedPolicy

Retrieves the policy that was generated using StartPolicyGeneration.

Request Syntax

```
GET /policy/generation/jobId?  
includeResourcePlaceholders=includeResourcePlaceholders&includeServiceLevelTemplate=includeServ  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[includeResourcePlaceholders](#)

The level of detail that you want to generate. You can specify whether to generate policies with placeholders for resource ARNs for actions that support resource level granularity in policies.

For example, in the resource section of a policy, you can receive a placeholder such as "Resource": "arn:aws:s3:::\${BucketName}" instead of "*".

[includeServiceLevelTemplate](#)

The level of detail that you want to generate. You can specify whether to generate service-level policies.

IAM Access Analyzer uses iam:service:lastaccessed to identify services that have been used recently to create this service-level template.

[jobId](#)

The JobId that is returned by the StartPolicyGeneration operation. The JobId can be used with GetGeneratedPolicy to retrieve the generated policies or used with CancelPolicyGeneration to cancel the policy generation request.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "generatedPolicyResult": {
    "generatedPolicies": [
      {
        "policy": "string"
      }
    ],
    "properties": {
      "cloudTrailProperties": {
        "endTime": "string",
        "startTime": "string",
        "trailProperties": [
          {
            "allRegions": boolean,
            "cloudTrailArn": "string",
            "regions": [ "string" ]
          }
        ]
      },
      "isComplete": boolean,
      "principalArn": "string"
    }
  },
  "jobDetails": {
    "completedOn": "string",
    "jobError": {
      "code": "string",
      "message": "string"
    },
    "jobId": "string",
    "startedOn": "string",
    "status": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[generatedPolicyResult](#)

A `GeneratedPolicyResult` object that contains the generated policies and associated details.

Type: [GeneratedPolicyResult](#) object

[jobDetails](#)

A `GeneratedPolicyDetails` object that contains details about the generated policy.

Type: [JobDetails](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAccessPreviewFindings

Retrieves a list of access preview findings generated by the specified access preview.

Request Syntax

```
POST /access-preview/accessPreviewId HTTP/1.1
Content-type: application/json
```

```
{
  "analyzerArn": "string",
  "filter": {
    "string": {
      "contains": [ "string" ],
      "eq": [ "string" ],
      "exists": boolean,
      "neq": [ "string" ]
    }
  },
  "maxResults": number,
  "nextToken": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

accessPreviewId

The unique ID for the access preview.

Pattern: [a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}

Required: Yes

Request Body

The request accepts the following data in JSON format.

analyzerArn

The [ARN of the analyzer](#) used to generate the access.

Type: String

Pattern: `^[^:]*:[^:]*:[^:]*:[^:]*:[^:]*:analyzer/.{1,255}`

Required: Yes

filter

Criteria to filter the returned findings.

Type: String to [Criterion](#) object map

Required: No

maxResults

The maximum number of results to return in the response.

Type: Integer

Required: No

nextToken

A token used for pagination of results returned.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "findings": [
    {
      "action": [ "string" ],
      "changeType": "string",
      "condition": {
        "string" : "string"
      },
      "createdAt": "string",
```

```
"error": "string",
"existingFindingId": "string",
"existingFindingStatus": "string",
"id": "string",
"isPublic": boolean,
"principal": {
  "string" : "string"
},
"resource": "string",
"resourceControlPolicyRestriction": "string",
"resourceOwnerAccount": "string",
"resourceType": "string",
"sources": [
  {
    "detail": {
      "accessPointAccount": "string",
      "accessPointArn": "string"
    },
    "type": "string"
  }
],
"status": "string"
}
],
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

findings

A list of access preview findings that match the specified filter criteria.

Type: Array of [AccessPreviewFinding](#) objects

nextToken

A token used for pagination of results returned.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

A conflict exception error.

resourceId

The ID of the resource.

resourceType

The resource type.

HTTP Status Code: 409

InternalServerErrorException

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

resourceId

The ID of the resource.

resourceType

The type of the resource.

HTTP Status Code: 404

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAccessPreviews

Retrieves a list of access previews for the specified analyzer.

Request Syntax

```
GET /access-preview?analyzerArn=analyzerArn&maxResults=maxResults&nextToken=nextToken
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

analyzerArn

The [ARN of the analyzer](#) used to generate the access preview.

Pattern: `[\^:]*:[\^:]*:[\^:]*:[\^:]*:[\^:]*:analyzer/.{1,255}`

Required: Yes

maxResults

The maximum number of results to return in the response.

nextToken

A token used for pagination of results returned.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "accessPreviews": [
    {
```

```
    "analyzerArn": "string",
    "createdAt": "string",
    "id": "string",
    "status": "string",
    "statusReason": {
      "code": "string"
    }
  },
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

accessReviews

A list of access previews retrieved for the analyzer.

Type: Array of [AccessPreviewSummary](#) objects

nextToken

A token used for pagination of results returned.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

resourceId

The ID of the resource.

resourceType

The type of the resource.

HTTP Status Code: 404

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAnalyzedResources

Retrieves a list of resources of the specified type that have been analyzed by the specified analyzer.

Request Syntax

```
POST /analyzed-resource HTTP/1.1
Content-type: application/json
```

```
{
  "analyzerArn": "string",
  "maxResults": number,
  "nextToken": "string",
  "resourceType": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

analyzerArn

The [ARN of the analyzer](#) to retrieve a list of analyzed resources from.

Type: String

Pattern: `^[^:]*:[^:]*:[^:]*:[^:]*:[^:]*:analyzer/.{1,255}`

Required: Yes

maxResults

The maximum number of results to return in the response.

Type: Integer

Required: No

nextToken

A token used for pagination of results returned.

Type: String

Required: No

resourceType

The type of resource.

Type: String

Valid Values: `AWS::S3::Bucket` | `AWS::IAM::Role` | `AWS::SQS::Queue` | `AWS::Lambda::Function` | `AWS::Lambda::LayerVersion` | `AWS::KMS::Key` | `AWS::SecretsManager::Secret` | `AWS::EFS::FileSystem` | `AWS::EC2::Snapshot` | `AWS::ECR::Repository` | `AWS::RDS::DBSnapshot` | `AWS::RDS::DBClusterSnapshot` | `AWS::SNS::Topic` | `AWS::S3Express::DirectoryBucket` | `AWS::DynamoDB::Table` | `AWS::DynamoDB::Stream` | `AWS::IAM::User`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "analyzedResources": [
    {
      "resourceArn": "string",
      "resourceOwnerAccount": "string",
      "resourceType": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

analyzedResources

A list of resources that were analyzed.

Type: Array of [AnalyzedResourceSummary](#) objects

nextToken

A token used for pagination of results returned.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

resourceId

The ID of the resource.

resourceType

The type of the resource.

HTTP Status Code: 404

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAnalyzers

Retrieves a list of analyzers.

Request Syntax

```
GET /analyzer?maxResults=maxResults&nextToken=nextToken&type=type HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to return in the response.

nextToken

A token used for pagination of results returned.

type

The type of analyzer.

Valid Values: ACCOUNT | ORGANIZATION | ACCOUNT_UNUSED_ACCESS
| ORGANIZATION_UNUSED_ACCESS | ACCOUNT_INTERNAL_ACCESS |
ORGANIZATION_INTERNAL_ACCESS

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "analyzers": [
    {
      "arn": "string",
```

```
    "configuration": { ... },
    "createdAt": "string",
    "lastResourceAnalyzed": "string",
    "lastResourceAnalyzedAt": "string",
    "name": "string",
    "status": "string",
    "statusReason": {
      "code": "string"
    },
    "tags": {
      "string" : "string"
    },
    "type": "string"
  }
],
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

analyzers

The analyzers retrieved.

Type: Array of [AnalyzerSummary](#) objects

nextToken

A token used for pagination of results returned.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListArchiveRules

Retrieves a list of archive rules created for the specified analyzer.

Request Syntax

```
GET /analyzer/analyzerName/archive-rule?maxResults=maxResults&nextToken=nextToken
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

analyzerName

The name of the analyzer to retrieve rules from.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [A-Za-z][A-Za-z0-9_.-]*

Required: Yes

maxResults

The maximum number of results to return in the request.

nextToken

A token used for pagination of results returned.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"archiveRules": [
  {
    "createdAt": "string",
    "filter": {
      "string": {
        "contains": [ "string" ],
        "eq": [ "string" ],
        "exists": boolean,
        "neq": [ "string" ]
      }
    },
    "ruleName": "string",
    "updatedAt": "string"
  }
],
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

archiveRules

A list of archive rules created for the specified analyzer.

Type: Array of [ArchiveRuleSummary](#) objects

nextToken

A token used for pagination of results returned.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListFindings

Retrieves a list of findings generated by the specified analyzer. ListFindings and ListFindingsV2 both use `access-analyzer:ListFindings` in the Action element of an IAM policy statement. You must have permission to perform the `access-analyzer:ListFindings` action.

To learn about filter keys that you can use to retrieve a list of findings, see [IAM Access Analyzer filter keys](#) in the **IAM User Guide**.

Note

ListFindings is supported only for external access analyzers. You must use ListFindingsV2 for internal and unused access analyzers.

Request Syntax

```
POST /finding HTTP/1.1
Content-type: application/json

{
  "analyzerArn": "string",
  "filter": {
    "string": {
      "contains": [ "string" ],
      "eq": [ "string" ],
      "exists": boolean,
      "neq": [ "string" ]
    }
  },
  "maxResults": number,
  "nextToken": "string",
  "sort": {
    "attributeName": "string",
    "orderBy": "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

analyzerArn

The [ARN of the analyzer](#) to retrieve findings from.

Type: String

Pattern: `[\^:]*:[\^:]*:[\^:]*:[\^:]*:[\^:]*:analyzer/.{1,255}`

Required: Yes

filter

A filter to match for the findings to return.

Type: String to [Criterion](#) object map

Required: No

maxResults

The maximum number of results to return in the response.

Type: Integer

Required: No

nextToken

A token used for pagination of results returned.

Type: String

Required: No

sort

The sort order for the findings returned.

Type: [SortCriteria](#) object

Required: No

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "findings": [
    {
      "action": [ "string" ],
      "analyzedAt": "string",
      "condition": {
        "string" : "string"
      },
      "createdAt": "string",
      "error": "string",
      "id": "string",
      "isPublic": boolean,
      "principal": {
        "string" : "string"
      },
      "resource": "string",
      "resourceControlPolicyRestriction": "string",
      "resourceOwnerAccount": "string",
      "resourceType": "string",
      "sources": [
        {
          "detail": {
            "accessPointAccount": "string",
            "accessPointArn": "string"
          },
          "type": "string"
        }
      ],
      "status": "string",
      "updatedAt": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

findings

A list of findings retrieved from the analyzer that match the filter criteria specified, if any.

Type: Array of [FindingSummary](#) objects

nextToken

A token used for pagination of results returned.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

resourceId

The ID of the resource.

resourceType

The type of the resource.

HTTP Status Code: 404

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListFindingsV2

Retrieves a list of findings generated by the specified analyzer. ListFindings and ListFindingsV2 both use `access-analyzer:ListFindings` in the Action element of an IAM policy statement. You must have permission to perform the `access-analyzer:ListFindings` action.

To learn about filter keys that you can use to retrieve a list of findings, see [IAM Access Analyzer filter keys](#) in the **IAM User Guide**.

Request Syntax

```
POST /findingv2 HTTP/1.1
Content-type: application/json

{
  "analyzerArn": "string",
  "filter": {
    "string": {
      "contains": [ "string" ],
      "eq": [ "string" ],
      "exists": boolean,
      "neq": [ "string" ]
    }
  },
  "maxResults": number,
  "nextToken": "string",
  "sort": {
    "attributeName": "string",
    "orderBy": "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

analyzerArn

The [ARN of the analyzer](#) to retrieve findings from.

Type: String

Pattern: `[\^:]*:[\^:]*:[\^:]*:[\^:]*:[\^:]*:analyzer/.{1,255}`

Required: Yes

filter

A filter to match for the findings to return.

Type: String to [Criterion](#) object map

Required: No

maxResults

The maximum number of results to return in the response.

Type: Integer

Required: No

nextToken

A token used for pagination of results returned.

Type: String

Required: No

sort

The criteria used to sort.

Type: [SortCriteria](#) object

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "findings": [
    {
      "analyzedAt": "string",
      "createdAt": "string",
      "error": "string",
      "findingType": "string",
      "id": "string",
      "resource": "string",
      "resourceOwnerAccount": "string",
      "resourceType": "string",
      "status": "string",
      "updatedAt": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

findings

A list of findings retrieved from the analyzer that match the filter criteria specified, if any.

Type: Array of [FindingSummaryV2](#) objects

nextToken

A token used for pagination of results returned.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

resourceId

The ID of the resource.

resourceType

The type of the resource.

HTTP Status Code: 404

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListPolicyGenerations

Lists all of the policy generations requested in the last seven days.

Request Syntax

```
GET /policy/generation?  
maxResults=maxResults&nextToken=nextToken&principalArn=principalArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[maxResults](#)

The maximum number of results to return in the response.

Valid Range: Minimum value of 1.

[nextToken](#)

A token used for pagination of results returned.

[principalArn](#)

The ARN of the IAM entity (user or role) for which you are generating a policy. Use this with `ListGeneratedPolicies` to filter the results to only include results for a specific principal.

Pattern: `arn:[^:]*:iam:[^:]*:(role|user)/.{1,576}`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json  
  
{
```

```
"nextToken": "string",
"policyGenerations": [
  {
    "completedOn": "string",
    "jobId": "string",
    "principalArn": "string",
    "startedOn": "string",
    "status": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

A token used for pagination of results returned.

Type: String

policyGenerations

A `PolicyGeneration` object that contains details about the generated policy.

Type: Array of [PolicyGeneration](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Retrieves a list of tags applied to the specified resource.

Request Syntax

```
GET /tags/resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The ARN of the resource to retrieve tags from.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tags

The tags that are applied to the specified resource.

Type: String to string map

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

resourceId

The ID of the resource.

resourceType

The type of the resource.

HTTP Status Code: 404

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartPolicyGeneration

Starts the policy generation request.

Request Syntax

```
PUT /policy/generation HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "cloudTrailDetails": {
    "accessRole": "string",
    "endTime": "string",
    "startTime": "string",
    "trails": [
      {
        "allRegions": boolean,
        "cloudTrailArn": "string",
        "regions": [ "string" ]
      }
    ]
  },
  "policyGenerationDetails": {
    "principalArn": "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, the subsequent retries with the same client token return the result from the original successful request and they have no additional effect.

If you do not specify a client token, one is automatically generated by the AWS SDK.

Type: String

Required: No

cloudTrailDetails

A `CloudTrailDetails` object that contains details about a `Trail` that you want to analyze to generate policies.

Type: [CloudTrailDetails](#) object

Required: No

policyGenerationDetails

Contains the ARN of the IAM entity (user or role) for which you are generating a policy.

Type: [PolicyGenerationDetails](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "jobId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

jobId

The `JobId` that is returned by the `StartPolicyGeneration` operation. The `JobId` can be used with `GetGeneratedPolicy` to retrieve the generated policies or used with `CancelPolicyGeneration` to cancel the policy generation request.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

A conflict exception error.

resourceId

The ID of the resource.

resourceType

The resource type.

HTTP Status Code: 409

InternalServerError

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ServiceQuotaExceededException

Service quote met error.

resourceId

The resource ID.

resourceType

The resource type.

HTTP Status Code: 402

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartResourceScan

Immediately starts a scan of the policies applied to the specified resource.

Note

This action is supported only for external access analyzers.

Request Syntax

```
POST /resource/scan HTTP/1.1
Content-type: application/json

{
  "analyzerArn": "string",
  "resourceArn": "string",
  "resourceOwnerAccount": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

analyzerArn

The [ARN of the analyzer](#) to use to scan the policies applied to the specified resource.

Type: String

Pattern: `[\^:]*:[\^:]*:[\^:]*:[\^:]*:[\^:]*:analyzer/.{1,255}`

Required: Yes

resourceArn

The ARN of the resource to scan.

Type: String

Pattern: `arn:[^:]*:[^:]*:[^:]*:[^:]*:.*`

Required: Yes

resourceOwnerAccount

The AWS account ID that owns the resource. For most AWS resources, the owning account is the account in which the resource was created.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

resourceId

The ID of the resource.

resourceType

The type of the resource.

HTTP Status Code: 404

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Adds a tag to the specified resource.

Request Syntax

```
POST /tags/resourceArn HTTP/1.1  
Content-type: application/json
```

```
{  
  "tags": {  
    "string" : "string"  
  }  
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The ARN of the resource to add the tag to.

Required: Yes

Request Body

The request accepts the following data in JSON format.

tags

The tags to add to the resource.

Type: String to string map

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

resourceId

The ID of the resource.

resourceType

The type of the resource.

HTTP Status Code: 404

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Removes a tag from the specified resource.

Request Syntax

```
DELETE /tags/resourceArn?tagKeys=tagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The ARN of the resource to remove the tag from.

Required: Yes

tagKeys

The key for the tag to add.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

resourceId

The ID of the resource.

resourceType

The type of the resource.

HTTP Status Code: 404

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateAnalyzer

Modifies the configuration of an existing analyzer.

Note

This action is not supported for external access analyzers.

Request Syntax

```
PUT /analyzer/analyzerName HTTP/1.1
Content-type: application/json

{
  "configuration": { ... }
}
```

URI Request Parameters

The request uses the following URI parameters.

analyzerName

The name of the analyzer to modify.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[A-Za-z][A-Za-z0-9_.-]*`

Required: Yes

Request Body

The request accepts the following data in JSON format.

configuration

Contains information about the configuration of an analyzer for an AWS organization or account.

Type: [AnalyzerConfiguration](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "configuration": { ... }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[configuration](#)

Contains information about the configuration of an analyzer for an AWS organization or account.

Type: [AnalyzerConfiguration](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

A conflict exception error.

resourceId

The ID of the resource.

resourceType

The resource type.

HTTP Status Code: 409

InternalServerErrorException

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

resourceId

The ID of the resource.

resourceType

The type of the resource.

HTTP Status Code: 404

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateArchiveRule

Updates the criteria and values for the specified archive rule.

Request Syntax

```
PUT /analyzer/analyzerName/archive-rule/ruleName HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "filter": {
    "string" : {
      "contains": [ "string" ],
      "eq": [ "string" ],
      "exists": boolean,
      "neq": [ "string" ]
    }
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

[analyzerName](#)

The name of the analyzer to update the archive rules for.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [A-Za-z][A-Za-z0-9_.-]*

Required: Yes

[ruleName](#)

The name of the rule to update.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [A-Za-z][A-Za-z0-9_.-]*

Required: Yes

Request Body

The request accepts the following data in JSON format.

clientToken

A client token.

Type: String

Required: No

filter

A filter to match for the rules to update. Only rules that match the filter are updated.

Type: String to [Criterion](#) object map

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

resourceId

The ID of the resource.

resourceType

The type of the resource.

HTTP Status Code: 404

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateFindings

Updates the status for the specified findings.

Request Syntax

```
PUT /finding HTTP/1.1
Content-type: application/json

{
  "analyzerArn": "string",
  "clientToken": "string",
  "ids": [ "string" ],
  "resourceArn": "string",
  "status": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

analyzerArn

The [ARN of the analyzer](#) that generated the findings to update.

Type: String

Pattern: `[\^:]*:[\^:]*:[\^:]*:[\^:]*:[\^:]*:analyzer/.[1,255}`

Required: Yes

clientToken

A client token.

Type: String

Required: No

ids

The IDs of the findings to update.

Type: Array of strings

Required: No

resourceArn

The ARN of the resource identified in the finding.

Type: String

Pattern: `arn:[^:]*:[^:]*:[^:]*:[^:]*:.*`

Required: No

status

The state represents the action to take to update the finding Status. Use ARCHIVE to change an Active finding to an Archived finding. Use ACTIVE to change an Archived finding to an Active finding.

Type: String

Valid Values: ACTIVE | ARCHIVED

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource could not be found.

resourceId

The ID of the resource.

resourceType

The type of the resource.

HTTP Status Code: 404

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ValidatePolicy

Requests the validation of a policy and returns a list of findings. The findings help you identify issues and provide actionable recommendations to resolve the issue and enable you to author functional policies that meet security best practices.

Request Syntax

```
POST /policy/validation?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "locale": "string",
  "policyDocument": "string",
  "policyType": "string",
  "validatePolicyResourceType": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to return in the response.

nextToken

A token used for pagination of results returned.

Request Body

The request accepts the following data in JSON format.

locale

The locale to use for localizing the findings.

Type: String

Valid Values: DE | EN | ES | FR | IT | JA | KO | PT_BR | ZH_CN | ZH_TW

Required: No

policyDocument

The JSON policy document to use as the content for the policy.

Type: String

Required: Yes

policyType

The type of policy to validate. Identity policies grant permissions to IAM principals. Identity policies include managed and inline policies for IAM roles, users, and groups.

Resource policies grant permissions on AWS resources. Resource policies include trust policies for IAM roles and bucket policies for Amazon S3 buckets. You can provide a generic input such as identity policy or resource policy or a specific input such as managed policy or Amazon S3 bucket policy.

Service control policies (SCPs) are a type of organization policy attached to an AWS organization, organizational unit (OU), or an account.

Type: String

Valid Values: IDENTITY_POLICY | RESOURCE_POLICY | SERVICE_CONTROL_POLICY | RESOURCE_CONTROL_POLICY

Required: Yes

validatePolicyResourceType

The type of resource to attach to your resource policy. Specify a value for the policy validation resource type only if the policy type is RESOURCE_POLICY. For example, to validate a resource policy to attach to an Amazon S3 bucket, you can choose `AWS::S3::Bucket` for the policy validation resource type.

For resource types not supported as valid values, IAM Access Analyzer runs policy checks that apply to all resource policies. For example, to validate a resource policy to attach to a KMS key, do not specify a value for the policy validation resource type and IAM Access Analyzer will run policy checks that apply to all resource policies.

Type: String

Valid Values: AWS::S3::Bucket | AWS::S3::AccessPoint |
AWS::S3::MultiRegionAccessPoint | AWS::S3ObjectLambda::AccessPoint |
AWS::IAM::AssumeRolePolicyDocument | AWS::DynamoDB::Table

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "findings": [
    {
      "findingDetails": "string",
      "findingType": "string",
      "issueCode": "string",
      "learnMoreLink": "string",
      "locations": [
        {
          "path": [
            { ... }
          ],
          "span": {
            "end": {
              "column": number,
              "line": number,
              "offset": number
            },
            "start": {
              "column": number,
              "line": number,
              "offset": number
            }
          }
        }
      ]
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

findings

The list of findings in a policy returned by IAM Access Analyzer based on its suite of policy checks.

Type: Array of [ValidatePolicyFinding](#) objects

nextToken

A token used for pagination of results returned.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

Internal server error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 500

ThrottlingException

Throttling limit exceeded error.

retryAfterSeconds

The seconds to wait to retry.

HTTP Status Code: 429

ValidationException

Validation exception error.

fieldList

A list of fields that didn't validate.

reason

The reason for the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The IAM Access Analyzer API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [Access](#)
- [AccessPreview](#)
- [AccessPreviewFinding](#)
- [AccessPreviewStatusReason](#)
- [AccessPreviewSummary](#)
- [AclGrantee](#)
- [AnalysisRule](#)
- [AnalysisRuleCriteria](#)
- [AnalyzedResource](#)
- [AnalyzedResourceSummary](#)
- [AnalyzerConfiguration](#)
- [AnalyzerSummary](#)
- [ArchiveRuleSummary](#)
- [CloudTrailDetails](#)
- [CloudTrailProperties](#)
- [Configuration](#)
- [Criterion](#)
- [DynamodbStreamConfiguration](#)
- [DynamodbTableConfiguration](#)
- [EbsSnapshotConfiguration](#)

- [EcrRepositoryConfiguration](#)
- [EfsFileSystemConfiguration](#)
- [ExternalAccessDetails](#)
- [ExternalAccessFindingsStatistics](#)
- [Finding](#)
- [FindingAggregationAccountDetails](#)
- [FindingDetails](#)
- [FindingSource](#)
- [FindingSourceDetail](#)
- [FindingsStatistics](#)
- [FindingSummary](#)
- [FindingSummaryV2](#)
- [GeneratedPolicy](#)
- [GeneratedPolicyProperties](#)
- [GeneratedPolicyResult](#)
- [IamRoleConfiguration](#)
- [InlineArchiveRule](#)
- [InternalAccessAnalysisRule](#)
- [InternalAccessAnalysisRuleCriteria](#)
- [InternalAccessConfiguration](#)
- [InternalAccessDetails](#)
- [InternalAccessFindingsStatistics](#)
- [InternalAccessResourceTypeDetails](#)
- [InternetConfiguration](#)
- [JobDetails](#)
- [JobError](#)
- [KmsGrantConfiguration](#)
- [KmsGrantConstraints](#)
- [KmsKeyConfiguration](#)
- [Location](#)

- [NetworkOriginConfiguration](#)
- [PathElement](#)
- [PolicyGeneration](#)
- [PolicyGenerationDetails](#)
- [Position](#)
- [RdsDbClusterSnapshotAttributeValue](#)
- [RdsDbClusterSnapshotConfiguration](#)
- [RdsDbSnapshotAttributeValue](#)
- [RdsDbSnapshotConfiguration](#)
- [ReasonSummary](#)
- [RecommendationError](#)
- [RecommendedStep](#)
- [ResourceTypeDetails](#)
- [S3AccessPointConfiguration](#)
- [S3BucketAclGrantConfiguration](#)
- [S3BucketConfiguration](#)
- [S3ExpressDirectoryAccessPointConfiguration](#)
- [S3ExpressDirectoryBucketConfiguration](#)
- [S3PublicAccessBlockConfiguration](#)
- [SecretsManagerSecretConfiguration](#)
- [SnsTopicConfiguration](#)
- [SortCriteria](#)
- [Span](#)
- [SqsQueueConfiguration](#)
- [StatusReason](#)
- [Substring](#)
- [Trail](#)
- [TrailProperties](#)
- [UnusedAccessConfiguration](#)
- [UnusedAccessFindingsStatistics](#)

- [UnusedAccessTypeStatistics](#)
- [UnusedAction](#)
- [UnusedIamRoleDetails](#)
- [UnusedIamUserAccessKeyDetails](#)
- [UnusedIamUserPasswordDetails](#)
- [UnusedPermissionDetails](#)
- [UnusedPermissionsRecommendedStep](#)
- [ValidatePolicyFinding](#)
- [ValidationExceptionField](#)
- [VpcConfiguration](#)

Access

Contains information about actions and resources that define permissions to check against a policy.

Contents

actions

A list of actions for the access permissions. Any strings that can be used as an action in an IAM policy can be used in the list of actions to check.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Required: No

resources

A list of resources for the access permissions. Any strings that can be used as an Amazon Resource Name (ARN) in an IAM policy can be used in the list of resources to check. You can only use a wildcard in the portion of the ARN that specifies the resource ID.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AccessPreview

Contains information about an access preview.

Contents

analyzerArn

The ARN of the analyzer used to generate the access preview.

Type: String

Pattern: `[\^:]*:[\^:]*:[\^:]*:[\^:]*:[\^:]*:analyzer/.{1,255}`

Required: Yes

configurations

A map of resource ARNs for the proposed resource configuration.

Type: String to [Configuration](#) object map

Required: Yes

createdAt

The time at which the access preview was created.

Type: Timestamp

Required: Yes

id

The unique ID for the access preview.

Type: String

Pattern: `[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}`

Required: Yes

status

The status of the access preview.

- **Creating** - The access preview creation is in progress.
- **Completed** - The access preview is complete. You can preview findings for external access to the resource.
- **Failed** - The access preview creation has failed.

Type: String

Valid Values: COMPLETED | CREATING | FAILED

Required: Yes

statusReason

Provides more details about the current status of the access preview.

For example, if the creation of the access preview fails, a `Failed` status is returned. This failure can be due to an internal issue with the analysis or due to an invalid resource configuration.

Type: [AccessPreviewStatusReason](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AccessPreviewFinding

An access preview finding generated by the access preview.

Contents

changeType

Provides context on how the access preview finding compares to existing access identified in IAM Access Analyzer.

- New - The finding is for newly-introduced access.
- Unchanged - The preview finding is an existing finding that would remain unchanged.
- Changed - The preview finding is an existing finding with a change in status.

For example, a Changed finding with preview status Resolved and existing status Active indicates the existing Active finding would become Resolved as a result of the proposed permissions change.

Type: String

Valid Values: CHANGED | NEW | UNCHANGED

Required: Yes

createdAt

The time at which the access preview finding was created.

Type: Timestamp

Required: Yes

id

The ID of the access preview finding. This ID uniquely identifies the element in the list of access preview findings and is not related to the finding ID in Access Analyzer.

Type: String

Required: Yes

resourceOwnerAccount

The AWS account ID that owns the resource. For most AWS resources, the owning account is the account in which the resource was created.

Type: String

Required: Yes

resourceType

The type of the resource that can be accessed in the finding.

Type: String

Valid Values: `AWS::S3::Bucket` | `AWS::IAM::Role` | `AWS::SQS::Queue` | `AWS::Lambda::Function` | `AWS::Lambda::LayerVersion` | `AWS::KMS::Key` | `AWS::SecretsManager::Secret` | `AWS::EFS::FileSystem` | `AWS::EC2::Snapshot` | `AWS::ECR::Repository` | `AWS::RDS::DBSnapshot` | `AWS::RDS::DBClusterSnapshot` | `AWS::SNS::Topic` | `AWS::S3Express::DirectoryBucket` | `AWS::DynamoDB::Table` | `AWS::DynamoDB::Stream` | `AWS::IAM::User`

Required: Yes

status

The preview status of the finding. This is what the status of the finding would be after permissions deployment. For example, a Changed finding with preview status Resolved and existing status Active indicates the existing Active finding would become Resolved as a result of the proposed permissions change.

Type: String

Valid Values: `ACTIVE` | `ARCHIVED` | `RESOLVED`

Required: Yes

action

The action in the analyzed policy statement that an external principal has permission to perform.

Type: Array of strings

Required: No

condition

The condition in the analyzed policy statement that resulted in a finding.

Type: String to string map

Required: No

error

An error.

Type: String

Required: No

existingFindingId

The existing ID of the finding in IAM Access Analyzer, provided only for existing findings.

Type: String

Required: No

existingFindingStatus

The existing status of the finding, provided only for existing findings.

Type: String

Valid Values: ACTIVE | ARCHIVED | RESOLVED

Required: No

isPublic

Indicates whether the policy that generated the finding allows public access to the resource.

Type: Boolean

Required: No

principal

The external principal that has access to a resource within the zone of trust.

Type: String to string map

Required: No

resource

The resource that an external principal has access to. This is the resource associated with the access preview.

Type: String

Required: No

resourceControlPolicyRestriction

The type of restriction applied to the finding by the resource owner with an Organizations resource control policy (RCP).

Type: String

Valid Values: APPLICABLE | FAILED_TO_EVALUATE_RCP | NOT_APPLICABLE | APPLIED

Required: No

sources

The sources of the finding. This indicates how the access that generated the finding is granted. It is populated for Amazon S3 bucket findings.

Type: Array of [FindingSource](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AccessPreviewStatusReason

Provides more details about the current status of the access preview. For example, if the creation of the access preview fails, a `Failed` status is returned. This failure can be due to an internal issue with the analysis or due to an invalid proposed resource configuration.

Contents

code

The reason code for the current status of the access preview.

Type: String

Valid Values: `INTERNAL_ERROR` | `INVALID_CONFIGURATION`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AccessPreviewSummary

Contains a summary of information about an access preview.

Contents

analyzerArn

The ARN of the analyzer used to generate the access preview.

Type: String

Pattern: `[\^:]*:[\^:]*:[\^:]*:[\^:]*:[\^:]*:analyzer/.{1,255}`

Required: Yes

createdAt

The time at which the access preview was created.

Type: Timestamp

Required: Yes

id

The unique ID for the access preview.

Type: String

Pattern: `[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}`

Required: Yes

status

The status of the access preview.

- **Creating** - The access preview creation is in progress.
- **Completed** - The access preview is complete and previews the findings for external access to the resource.
- **Failed** - The access preview creation has failed.

Type: String

Valid Values: COMPLETED | CREATING | FAILED

Required: Yes

statusReason

Provides more details about the current status of the access preview. For example, if the creation of the access preview fails, a Failed status is returned. This failure can be due to an internal issue with the analysis or due to an invalid proposed resource configuration.

Type: [AccessPreviewStatusReason](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AclGrantee

You specify each grantee as a type-value pair using one of these types. You can specify only one type of grantee. For more information, see [PutBucketAcl](#).

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

id

The value specified is the canonical user ID of an AWS account.

Type: String

Required: No

uri

Used for granting permissions to a predefined group.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AnalysisRule

Contains information about analysis rules for the analyzer. Analysis rules determine which entities will generate findings based on the criteria you define when you create the rule.

Contents

exclusions

A list of rules for the analyzer containing criteria to exclude from analysis. Entities that meet the rule criteria will not generate findings.

Type: Array of [AnalysisRuleCriteria](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AnalysisRuleCriteria

The criteria for an analysis rule for an analyzer. The criteria determine which entities will generate findings.

Contents

accountIds

A list of AWS account IDs to apply to the analysis rule criteria. The accounts cannot include the organization analyzer owner account. Account IDs can only be applied to the analysis rule criteria for organization-level analyzers. The list cannot include more than 2,000 account IDs.

Type: Array of strings

Required: No

resourceTags

An array of key-value pairs to match for your resources. You can use the set of Unicode letters, digits, whitespace, `_`, `.`, `/`, `=`, `+`, and `-`.

For the tag key, you can specify a value that is 1 to 128 characters in length and cannot be prefixed with `aws :`.

For the tag value, you can specify a value that is 0 to 256 characters in length. If the specified tag value is 0 characters, the rule is applied to all principals with the specified tag key.

Type: Array of string to string maps

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AnalyzedResource

Contains details about the analyzed resource.

Contents

analyzedAt

The time at which the resource was analyzed.

Type: Timestamp

Required: Yes

createdAt

The time at which the finding was created.

Type: Timestamp

Required: Yes

isPublic

Indicates whether the policy that generated the finding grants public access to the resource.

Type: Boolean

Required: Yes

resourceArn

The ARN of the resource that was analyzed.

Type: String

Pattern: `arn:[^:]*:[^:]*:[^:]*:[^:]*:.*`

Required: Yes

resourceOwnerAccount

The AWS account ID that owns the resource.

Type: String

Required: Yes

resourceType

The type of the resource that was analyzed.

Type: String

Valid Values: `AWS::S3::Bucket` | `AWS::IAM::Role` | `AWS::SQS::Queue` | `AWS::Lambda::Function` | `AWS::Lambda::LayerVersion` | `AWS::KMS::Key` | `AWS::SecretsManager::Secret` | `AWS::EFS::FileSystem` | `AWS::EC2::Snapshot` | `AWS::ECR::Repository` | `AWS::RDS::DBSnapshot` | `AWS::RDS::DBClusterSnapshot` | `AWS::SNS::Topic` | `AWS::S3Express::DirectoryBucket` | `AWS::DynamoDB::Table` | `AWS::DynamoDB::Stream` | `AWS::IAM::User`

Required: Yes

updatedAt

The time at which the finding was updated.

Type: Timestamp

Required: Yes

actions

The actions that an external principal is granted permission to use by the policy that generated the finding.

Type: Array of strings

Required: No

error

An error message.

Type: String

Required: No

sharedVia

Indicates how the access that generated the finding is granted. This is populated for Amazon S3 bucket findings.

Type: Array of strings

Required: No

status

The current status of the finding generated from the analyzed resource.

Type: String

Valid Values: ACTIVE | ARCHIVED | RESOLVED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AnalyzedResourceSummary

Contains the ARN of the analyzed resource.

Contents

resourceArn

The ARN of the analyzed resource.

Type: String

Pattern: `arn:[^:]*:[^:]*:[^:]*:[^:]*:.*`

Required: Yes

resourceOwnerAccount

The AWS account ID that owns the resource.

Type: String

Required: Yes

resourceType

The type of resource that was analyzed.

Type: String

Valid Values: `AWS::S3::Bucket` | `AWS::IAM::Role` | `AWS::SQS::Queue` | `AWS::Lambda::Function` | `AWS::Lambda::LayerVersion` | `AWS::KMS::Key` | `AWS::SecretsManager::Secret` | `AWS::EFS::FileSystem` | `AWS::EC2::Snapshot` | `AWS::ECR::Repository` | `AWS::RDS::DBSnapshot` | `AWS::RDS::DBClusterSnapshot` | `AWS::SNS::Topic` | `AWS::S3Express::DirectoryBucket` | `AWS::DynamoDB::Table` | `AWS::DynamoDB::Stream` | `AWS::IAM::User`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AnalyzerConfiguration

Contains information about the configuration of an analyzer for an AWS organization or account.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

internalAccess

Specifies the configuration of an internal access analyzer for an AWS organization or account. This configuration determines how the analyzer evaluates access within your AWS environment.

Type: [InternalAccessConfiguration](#) object

Required: No

unusedAccess

Specifies the configuration of an unused access analyzer for an AWS organization or account.

Type: [UnusedAccessConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AnalyzerSummary

Contains information about the analyzer.

Contents

arn

The ARN of the analyzer.

Type: String

Pattern: `[\^:]*:[\^:]*:[\^:]*:[\^:]*:[\^:]*:analyzer/.{1,255}`

Required: Yes

createdAt

A timestamp for the time at which the analyzer was created.

Type: Timestamp

Required: Yes

name

The name of the analyzer.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[A-Za-z][A-Za-z0-9_.-]*`

Required: Yes

status

The status of the analyzer. An `Active` analyzer successfully monitors supported resources and generates new findings. The analyzer is `Disabled` when a user action, such as removing trusted access for AWS Identity and Access Management Access Analyzer from AWS Organizations, causes the analyzer to stop generating new findings. The status is `Creating` when the analyzer creation is in progress and `Failed` when the analyzer creation has failed.

Type: String

Valid Values: ACTIVE | CREATING | DISABLED | FAILED

Required: Yes

type

The type represents the zone of trust or scope for the analyzer.

Type: String

Valid Values: ACCOUNT | ORGANIZATION | ACCOUNT_UNUSED_ACCESS
| ORGANIZATION_UNUSED_ACCESS | ACCOUNT_INTERNAL_ACCESS |
ORGANIZATION_INTERNAL_ACCESS

Required: Yes

configuration

Specifies if the analyzer is an external access, unused access, or internal access analyzer. The [GetAnalyzer](#) action includes this property in its response if a configuration is specified, while the [ListAnalyzers](#) action omits it.

Type: [AnalyzerConfiguration](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

lastResourceAnalyzed

The resource that was most recently analyzed by the analyzer.

Type: String

Required: No

lastResourceAnalyzedAt

The time at which the most recently analyzed resource was analyzed.

Type: Timestamp

Required: No

statusReason

The `statusReason` provides more details about the current status of the analyzer. For example, if the creation for the analyzer fails, a `Failed` status is returned. For an analyzer with `organization` as the type, this failure can be due to an issue with creating the service-linked roles required in the member accounts of the AWS organization.

Type: [StatusReason](#) object

Required: No

tags

An array of key-value pairs applied to the analyzer. The key-value pairs consist of the set of Unicode letters, digits, whitespace, `_`, `.`, `/`, `=`, `+`, and `-`.

The tag key is a value that is 1 to 128 characters in length and cannot be prefixed with `aws :`.

The tag value is a value that is 0 to 256 characters in length.

Type: String to string map

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ArchiveRuleSummary

Contains information about an archive rule. Archive rules automatically archive new findings that meet the criteria you define when you create the rule.

Contents

createdAt

The time at which the archive rule was created.

Type: Timestamp

Required: Yes

filter

A filter used to define the archive rule.

Type: String to [Criterion](#) object map

Required: Yes

ruleName

The name of the archive rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[A-Za-z][A-Za-z0-9_.-]*`

Required: Yes

updatedAt

The time at which the archive rule was last updated.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CloudTrailDetails

Contains information about CloudTrail access.

Contents

accessRole

The ARN of the service role that IAM Access Analyzer uses to access your CloudTrail trail and service last accessed information.

Type: String

Pattern: `arn:[^:]*:iam:[^:]*:role/.{1,576}`

Required: Yes

startTime

The start of the time range for which IAM Access Analyzer reviews your CloudTrail events. Events with a timestamp before this time are not considered to generate a policy.

Type: Timestamp

Required: Yes

trails

A `Trail` object that contains settings for a trail.

Type: Array of [Trail](#) objects

Required: Yes

endTime

The end of the time range for which IAM Access Analyzer reviews your CloudTrail events. Events with a timestamp after this time are not considered to generate a policy. If this is not included in the request, the default value is the current time.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CloudTrailProperties

Contains information about CloudTrail access.

Contents

endTime

The end of the time range for which IAM Access Analyzer reviews your CloudTrail events. Events with a timestamp after this time are not considered to generate a policy. If this is not included in the request, the default value is the current time.

Type: Timestamp

Required: Yes

startTime

The start of the time range for which IAM Access Analyzer reviews your CloudTrail events. Events with a timestamp before this time are not considered to generate a policy.

Type: Timestamp

Required: Yes

trailProperties

A `TrailProperties` object that contains settings for trail properties.

Type: Array of [TrailProperties](#) objects

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Configuration

Access control configuration structures for your resource. You specify the configuration as a type-value pair. You can specify only one type of access control configuration.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

dynamodbStream

The access control configuration is for a DynamoDB stream.

Type: [DynamodbStreamConfiguration](#) object

Required: No

dynamodbTable

The access control configuration is for a DynamoDB table or index.

Type: [DynamodbTableConfiguration](#) object

Required: No

ebsSnapshot

The access control configuration is for an Amazon EBS volume snapshot.

Type: [EbsSnapshotConfiguration](#) object

Required: No

ecrRepository

The access control configuration is for an Amazon ECR repository.

Type: [EcrRepositoryConfiguration](#) object

Required: No

efsFileSystem

The access control configuration is for an Amazon EFS file system.

Type: [EfsFileSystemConfiguration](#) object

Required: No

iamRole

The access control configuration is for an IAM role.

Type: [IamRoleConfiguration](#) object

Required: No

kmsKey

The access control configuration is for a KMS key.

Type: [KmsKeyConfiguration](#) object

Required: No

rdsDbClusterSnapshot

The access control configuration is for an Amazon RDS DB cluster snapshot.

Type: [RdsDbClusterSnapshotConfiguration](#) object

Required: No

rdsDbSnapshot

The access control configuration is for an Amazon RDS DB snapshot.

Type: [RdsDbSnapshotConfiguration](#) object

Required: No

s3Bucket

The access control configuration is for an Amazon S3 bucket.

Type: [S3BucketConfiguration](#) object

Required: No

s3ExpressDirectoryBucket

The access control configuration is for an Amazon S3 directory bucket.

Type: [S3ExpressDirectoryBucketConfiguration](#) object

Required: No

secretsManagerSecret

The access control configuration is for a Secrets Manager secret.

Type: [SecretsManagerSecretConfiguration](#) object

Required: No

snsTopic

The access control configuration is for an Amazon SNS topic

Type: [SnsTopicConfiguration](#) object

Required: No

sqsQueue

The access control configuration is for an Amazon SQS queue.

Type: [SqsQueueConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Criterion

The criteria to use in the filter that defines the archive rule. For more information on available filter keys, see [IAM Access Analyzer filter keys](#).

Contents

contains

A "contains" operator to match for the filter used to create the rule.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Required: No

eq

An "equals" operator to match for the filter used to create the rule.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Required: No

exists

An "exists" operator to match for the filter used to create the rule.

Type: Boolean

Required: No

neq

A "not equals" operator to match for the filter used to create the rule.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DynamodbStreamConfiguration

The proposed access control configuration for a DynamoDB stream. You can propose a configuration for a new DynamoDB stream or an existing DynamoDB stream that you own by specifying the policy for the DynamoDB stream. For more information, see [PutResourcePolicy](#).

- If the configuration is for an existing DynamoDB stream and you do not specify the DynamoDB policy, then the access preview uses the existing DynamoDB policy for the stream.
- If the access preview is for a new resource and you do not specify the policy, then the access preview assumes a DynamoDB stream without a policy.
- To propose deletion of an existing DynamoDB stream policy, you can specify an empty string for the DynamoDB policy.

Contents

streamPolicy

The proposed resource policy defining who can access or manage the DynamoDB stream.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DynamodbTableConfiguration

The proposed access control configuration for a DynamoDB table or index. You can propose a configuration for a new DynamoDB table or index or an existing DynamoDB table or index that you own by specifying the policy for the DynamoDB table or index. For more information, see [PutResourcePolicy](#).

- If the configuration is for an existing DynamoDB table or index and you do not specify the DynamoDB policy, then the access preview uses the existing DynamoDB policy for the table or index.
- If the access preview is for a new resource and you do not specify the policy, then the access preview assumes a DynamoDB table without a policy.
- To propose deletion of an existing DynamoDB table or index policy, you can specify an empty string for the DynamoDB policy.

Contents

tablePolicy

The proposed resource policy defining who can access or manage the DynamoDB table.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EbsSnapshotConfiguration

The proposed access control configuration for an Amazon EBS volume snapshot. You can propose a configuration for a new Amazon EBS volume snapshot or an Amazon EBS volume snapshot that you own by specifying the user IDs, groups, and optional AWS KMS encryption key. For more information, see [ModifySnapshotAttribute](#).

Contents

groups

The groups that have access to the Amazon EBS volume snapshot. If the value `all` is specified, then the Amazon EBS volume snapshot is public.

- If the configuration is for an existing Amazon EBS volume snapshot and you do not specify the groups, then the access preview uses the existing shared groups for the snapshot.
- If the access preview is for a new resource and you do not specify the groups, then the access preview considers the snapshot without any groups.
- To propose deletion of existing shared groups, you can specify an empty list for groups.

Type: Array of strings

Required: No

kmsKeyId

The KMS key identifier for an encrypted Amazon EBS volume snapshot. The KMS key identifier is the key ARN, key ID, alias ARN, or alias name for the KMS key.

- If the configuration is for an existing Amazon EBS volume snapshot and you do not specify the `kmsKeyId`, or you specify an empty string, then the access preview uses the existing `kmsKeyId` of the snapshot.
- If the access preview is for a new resource and you do not specify the `kmsKeyId`, the access preview considers the snapshot as unencrypted.

Type: String

Required: No

userIds

The IDs of the AWS accounts that have access to the Amazon EBS volume snapshot.

- If the configuration is for an existing Amazon EBS volume snapshot and you do not specify the `userIds`, then the access preview uses the existing shared `userIds` for the snapshot.
- If the access preview is for a new resource and you do not specify the `userIds`, then the access preview considers the snapshot without any `userIds`.
- To propose deletion of existing shared `accountIds`, you can specify an empty list for `userIds`.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EcrRepositoryConfiguration

The proposed access control configuration for an Amazon ECR repository. You can propose a configuration for a new Amazon ECR repository or an existing Amazon ECR repository that you own by specifying the Amazon ECR policy. For more information, see [Repository](#).

- If the configuration is for an existing Amazon ECR repository and you do not specify the Amazon ECR policy, then the access preview uses the existing Amazon ECR policy for the repository.
- If the access preview is for a new resource and you do not specify the policy, then the access preview assumes an Amazon ECR repository without a policy.
- To propose deletion of an existing Amazon ECR repository policy, you can specify an empty string for the Amazon ECR policy.

Contents

repositoryPolicy

The JSON repository policy text to apply to the Amazon ECR repository. For more information, see [Private repository policy examples](#) in the *Amazon ECR User Guide*.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EfsFileSystemConfiguration

The proposed access control configuration for an Amazon EFS file system. You can propose a configuration for a new Amazon EFS file system or an existing Amazon EFS file system that you own by specifying the Amazon EFS policy. For more information, see [Using file systems in Amazon EFS](#).

- If the configuration is for an existing Amazon EFS file system and you do not specify the Amazon EFS policy, then the access preview uses the existing Amazon EFS policy for the file system.
- If the access preview is for a new resource and you do not specify the policy, then the access preview assumes an Amazon EFS file system without a policy.
- To propose deletion of an existing Amazon EFS file system policy, you can specify an empty string for the Amazon EFS policy.

Contents

fileSystemPolicy

The JSON policy definition to apply to the Amazon EFS file system. For more information on the elements that make up a file system policy, see [Amazon EFS Resource-based policies](#).

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ExternalAccessDetails

Contains information about an external access finding.

Contents

condition

The condition in the analyzed policy statement that resulted in an external access finding.

Type: String to string map

Required: Yes

action

The action in the analyzed policy statement that an external principal has permission to use.

Type: Array of strings

Required: No

isPublic

Specifies whether the external access finding is public.

Type: Boolean

Required: No

principal

The external principal that has access to a resource within the zone of trust.

Type: String to string map

Required: No

resourceControlPolicyRestriction

The type of restriction applied to the finding by the resource owner with an Organizations resource control policy (RCP).

- **APPLICABLE:** There is an RCP present in the organization but IAM Access Analyzer does not include it in the evaluation of effective permissions. For example, if `s3:DeleteObject` is

blocked by the RCP and the restriction is APPLICABLE, then `s3:DeleteObject` would still be included in the list of actions for the finding.

- `FAILED_TO_EVALUATE_RCP`: There was an error evaluating the RCP.
- `NOT_APPLICABLE`: There was no RCP present in the organization, or there was no RCP applicable to the resource. For example, the resource being analyzed is an Amazon RDS snapshot and there is an RCP in the organization, but the RCP only impacts Amazon S3 buckets.
- `APPLIED`: This restriction is not currently available for external access findings.

Type: String

Valid Values: `APPLICABLE` | `FAILED_TO_EVALUATE_RCP` | `NOT_APPLICABLE` | `APPLIED`

Required: No

sources

The sources of the external access finding. This indicates how the access that generated the finding is granted. It is populated for Amazon S3 bucket findings.

Type: Array of [FindingSource](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ExternalAccessFindingsStatistics

Provides aggregate statistics about the findings for the specified external access analyzer.

Contents

resourceTypeStatistics

The total number of active cross-account and public findings for each resource type of the specified external access analyzer.

Type: String to [ResourceTypeDetails](#) object map

Valid Keys: `AWS::S3::Bucket` | `AWS::IAM::Role` | `AWS::SQS::Queue` | `AWS::Lambda::Function` | `AWS::Lambda::LayerVersion` | `AWS::KMS::Key` | `AWS::SecretsManager::Secret` | `AWS::EFS::FileSystem` | `AWS::EC2::Snapshot` | `AWS::ECR::Repository` | `AWS::RDS::DBSnapshot` | `AWS::RDS::DBClusterSnapshot` | `AWS::SNS::Topic` | `AWS::S3Express::DirectoryBucket` | `AWS::DynamoDB::Table` | `AWS::DynamoDB::Stream` | `AWS::IAM::User`

Required: No

totalActiveFindings

The number of active findings for the specified external access analyzer.

Type: Integer

Required: No

totalArchivedFindings

The number of archived findings for the specified external access analyzer.

Type: Integer

Required: No

totalResolvedFindings

The number of resolved findings for the specified external access analyzer.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Finding

Contains information about a finding.

Contents

analyzedAt

The time at which the resource was analyzed.

Type: Timestamp

Required: Yes

condition

The condition in the analyzed policy statement that resulted in a finding.

Type: String to string map

Required: Yes

createdAt

The time at which the finding was generated.

Type: Timestamp

Required: Yes

id

The ID of the finding.

Type: String

Required: Yes

resourceOwnerAccount

The AWS account ID that owns the resource.

Type: String

Required: Yes

resourceType

The type of the resource identified in the finding.

Type: String

Valid Values: `AWS::S3::Bucket` | `AWS::IAM::Role` | `AWS::SQS::Queue` | `AWS::Lambda::Function` | `AWS::Lambda::LayerVersion` | `AWS::KMS::Key` | `AWS::SecretsManager::Secret` | `AWS::EFS::FileSystem` | `AWS::EC2::Snapshot` | `AWS::ECR::Repository` | `AWS::RDS::DBSnapshot` | `AWS::RDS::DBClusterSnapshot` | `AWS::SNS::Topic` | `AWS::S3Express::DirectoryBucket` | `AWS::DynamoDB::Table` | `AWS::DynamoDB::Stream` | `AWS::IAM::User`

Required: Yes

status

The current status of the finding.

Type: String

Valid Values: `ACTIVE` | `ARCHIVED` | `RESOLVED`

Required: Yes

updatedAt

The time at which the finding was updated.

Type: Timestamp

Required: Yes

action

The action in the analyzed policy statement that an external principal has permission to use.

Type: Array of strings

Required: No

error

An error.

Type: String

Required: No

isPublic

Indicates whether the policy that generated the finding allows public access to the resource.

Type: Boolean

Required: No

principal

The external principal that has access to a resource within the zone of trust.

Type: String to string map

Required: No

resource

The resource that an external principal has access to.

Type: String

Required: No

resourceControlPolicyRestriction

The type of restriction applied to the finding by the resource owner with an Organizations resource control policy (RCP).

Type: String

Valid Values: APPLICABLE | FAILED_TO_EVALUATE_RCP | NOT_APPLICABLE | APPLIED

Required: No

sources

The sources of the finding. This indicates how the access that generated the finding is granted. It is populated for Amazon S3 bucket findings.

Type: Array of [FindingSource](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FindingAggregationAccountDetails

Contains information about the findings for an AWS account in an organization unused access analyzer.

Contents

account

The ID of the AWS account for which unused access finding details are provided.

Type: String

Required: No

details

Provides the number of active findings for each type of unused access for the specified AWS account.

Type: String to integer map

Required: No

numberOfActiveFindings

The number of active unused access findings for the specified AWS account.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FindingDetails

Contains information about an external access or unused access finding. Only one parameter can be used in a `FindingDetails` object.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

externalAccessDetails

The details for an external access analyzer finding.

Type: [ExternalAccessDetails](#) object

Required: No

internalAccessDetails

The details for an internal access analyzer finding. This contains information about access patterns identified within your AWS organization or account.

Type: [InternalAccessDetails](#) object

Required: No

unusedIamRoleDetails

The details for an unused access analyzer finding with an unused IAM role finding type.

Type: [UnusedIamRoleDetails](#) object

Required: No

unusedIamUserAccessKeyDetails

The details for an unused access analyzer finding with an unused IAM user access key finding type.

Type: [UnusedIamUserAccessKeyDetails](#) object

Required: No

unusedIamUserPasswordDetails

The details for an unused access analyzer finding with an unused IAM user password finding type.

Type: [UnusedIamUserPasswordDetails](#) object

Required: No

unusedPermissionDetails

The details for an unused access analyzer finding with an unused permission finding type.

Type: [UnusedPermissionDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FindingSource

The source of the finding. This indicates how the access that generated the finding is granted. It is populated for Amazon S3 bucket findings.

Contents

type

Indicates the type of access that generated the finding.

Type: String

Valid Values: POLICY | BUCKET_ACL | S3_ACCESS_POINT | S3_ACCESS_POINT_ACCOUNT

Required: Yes

detail

Includes details about how the access that generated the finding is granted. This is populated for Amazon S3 bucket findings.

Type: [FindingSourceDetail](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FindingSourceDetail

Includes details about how the access that generated the finding is granted. This is populated for Amazon S3 bucket findings.

Contents

accessPointAccount

The account of the cross-account access point that generated the finding.

Type: String

Required: No

accessPointArn

The ARN of the access point that generated the finding. The ARN format depends on whether the ARN represents an access point or a multi-region access point.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FindingsStatistics

Contains information about the aggregate statistics for an external or unused access analyzer. Only one parameter can be used in a `FindingsStatistics` object.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

externalAccessFindingsStatistics

The aggregate statistics for an external access analyzer.

Type: [ExternalAccessFindingsStatistics](#) object

Required: No

internalAccessFindingsStatistics

The aggregate statistics for an internal access analyzer. This includes information about active, archived, and resolved findings related to internal access within your AWS organization or account.

Type: [InternalAccessFindingsStatistics](#) object

Required: No

unusedAccessFindingsStatistics

The aggregate statistics for an unused access analyzer.

Type: [UnusedAccessFindingsStatistics](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FindingSummary

Contains information about a finding.

Contents

analyzedAt

The time at which the resource-based policy that generated the finding was analyzed.

Type: Timestamp

Required: Yes

condition

The condition in the analyzed policy statement that resulted in a finding.

Type: String to string map

Required: Yes

createdAt

The time at which the finding was created.

Type: Timestamp

Required: Yes

id

The ID of the finding.

Type: String

Required: Yes

resourceOwnerAccount

The AWS account ID that owns the resource.

Type: String

Required: Yes

resourceType

The type of the resource that the external principal has access to.

Type: String

Valid Values: `AWS::S3::Bucket` | `AWS::IAM::Role` | `AWS::SQS::Queue` | `AWS::Lambda::Function` | `AWS::Lambda::LayerVersion` | `AWS::KMS::Key` | `AWS::SecretsManager::Secret` | `AWS::EFS::FileSystem` | `AWS::EC2::Snapshot` | `AWS::ECR::Repository` | `AWS::RDS::DBSnapshot` | `AWS::RDS::DBClusterSnapshot` | `AWS::SNS::Topic` | `AWS::S3Express::DirectoryBucket` | `AWS::DynamoDB::Table` | `AWS::DynamoDB::Stream` | `AWS::IAM::User`

Required: Yes

status

The status of the finding.

Type: String

Valid Values: `ACTIVE` | `ARCHIVED` | `RESOLVED`

Required: Yes

updatedAt

The time at which the finding was most recently updated.

Type: Timestamp

Required: Yes

action

The action in the analyzed policy statement that an external principal has permission to use.

Type: Array of strings

Required: No

error

The error that resulted in an Error finding.

Type: String

Required: No

isPublic

Indicates whether the finding reports a resource that has a policy that allows public access.

Type: Boolean

Required: No

principal

The external principal that has access to a resource within the zone of trust.

Type: String to string map

Required: No

resource

The resource that the external principal has access to.

Type: String

Required: No

resourceControlPolicyRestriction

The type of restriction applied to the finding by the resource owner with an Organizations resource control policy (RCP).

Type: String

Valid Values: APPLICABLE | FAILED_TO_EVALUATE_RCP | NOT_APPLICABLE | APPLIED

Required: No

sources

The sources of the finding. This indicates how the access that generated the finding is granted. It is populated for Amazon S3 bucket findings.

Type: Array of [FindingSource](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FindingSummaryV2

Contains information about a finding.

Contents

analyzedAt

The time at which the resource-based policy or IAM entity that generated the finding was analyzed.

Type: Timestamp

Required: Yes

createdAt

The time at which the finding was created.

Type: Timestamp

Required: Yes

id

The ID of the finding.

Type: String

Required: Yes

resourceOwnerAccount

The AWS account ID that owns the resource.

Type: String

Required: Yes

resourceType

The type of the resource that the external principal has access to.

Type: String

Valid Values: `AWS::S3::Bucket` | `AWS::IAM::Role` | `AWS::SQS::Queue` | `AWS::Lambda::Function` | `AWS::Lambda::LayerVersion` | `AWS::KMS::Key` | `AWS::SecretsManager::Secret` | `AWS::EFS::FileSystem` | `AWS::EC2::Snapshot` | `AWS::ECR::Repository` | `AWS::RDS::DBSnapshot` | `AWS::RDS::DBClusterSnapshot` | `AWS::SNS::Topic` | `AWS::S3Express::DirectoryBucket` | `AWS::DynamoDB::Table` | `AWS::DynamoDB::Stream` | `AWS::IAM::User`

Required: Yes

status

The status of the finding.

Type: String

Valid Values: `ACTIVE` | `ARCHIVED` | `RESOLVED`

Required: Yes

updatedAt

The time at which the finding was most recently updated.

Type: Timestamp

Required: Yes

error

The error that resulted in an Error finding.

Type: String

Required: No

findingType

The type of the access finding. For external access analyzers, the type is `ExternalAccess`. For unused access analyzers, the type can be `UnusedIAMRole`, `UnusedIAMUserAccessKey`, `UnusedIAMUserPassword`, or `UnusedPermission`. For internal access analyzers, the type is `InternalAccess`.

Type: String

Valid Values: ExternalAccess | UnusedIAMRole | UnusedIAMUserAccessKey | UnusedIAMUserPassword | UnusedPermission | InternalAccess

Required: No

resource

The resource that the external principal has access to.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GeneratedPolicy

Contains the text for the generated policy.

Contents

policy

The text to use as the content for the new policy. The policy is created using the [CreatePolicy](#) action.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GeneratedPolicyProperties

Contains the generated policy details.

Contents

principalArn

The ARN of the IAM entity (user or role) for which you are generating a policy.

Type: String

Pattern: `arn:[^:]*:iam:[^:]*:(role|user)/.{1,576}`

Required: Yes

cloudTrailProperties

Lists details about the `Trail` used to generated policy.

Type: [CloudTrailProperties](#) object

Required: No

isComplete

This value is set to `true` if the generated policy contains all possible actions for a service that IAM Access Analyzer identified from the CloudTrail trail that you specified, and `false` otherwise.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GeneratedPolicyResult

Contains the text for the generated policy and its details.

Contents

properties

A `GeneratedPolicyProperties` object that contains properties of the generated policy.

Type: [GeneratedPolicyProperties](#) object

Required: Yes

generatedPolicies

The text to use as the content for the new policy. The policy is created using the [CreatePolicy](#) action.

Type: Array of [GeneratedPolicy](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IamRoleConfiguration

The proposed access control configuration for an IAM role. You can propose a configuration for a new IAM role or an existing IAM role that you own by specifying the trust policy. If the configuration is for a new IAM role, you must specify the trust policy. If the configuration is for an existing IAM role that you own and you do not propose the trust policy, the access preview uses the existing trust policy for the role. The proposed trust policy cannot be an empty string. For more information about role trust policy limits, see [IAM and AWS STS quotas](#).

Contents

trustPolicy

The proposed trust policy for the IAM role.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InlineArchiveRule

An criterion statement in an archive rule. Each archive rule may have multiple criteria.

Contents

filter

The condition and values for a criterion.

Type: String to [Criterion](#) object map

Required: Yes

ruleName

The name of the rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[A-Za-z][A-Za-z0-9_.-]*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InternalAccessAnalysisRule

Contains information about analysis rules for the internal access analyzer. Analysis rules determine which entities will generate findings based on the criteria you define when you create the rule.

Contents

inclusions

A list of rules for the internal access analyzer containing criteria to include in analysis. Only resources that meet the rule criteria will generate findings.

Type: Array of [InternalAccessAnalysisRuleCriteria](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InternalAccessAnalysisRuleCriteria

The criteria for an analysis rule for an internal access analyzer.

Contents

accountIds

A list of AWS account IDs to apply to the internal access analysis rule criteria. Account IDs can only be applied to the analysis rule criteria for organization-level analyzers.

Type: Array of strings

Required: No

resourceArns

A list of resource ARNs to apply to the internal access analysis rule criteria. The analyzer will only generate findings for resources that match these ARNs.

Type: Array of strings

Required: No

resourceTypes

A list of resource types to apply to the internal access analysis rule criteria. The analyzer will only generate findings for resources of these types. These resource types are currently supported for internal access analyzers:

- `AWS::S3::Bucket`
- `AWS::RDS::DBSnapshot`
- `AWS::RDS::DBClusterSnapshot`
- `AWS::S3Express::DirectoryBucket`
- `AWS::DynamoDB::Table`
- `AWS::DynamoDB::Stream`

Type: Array of strings

Valid Values: `AWS::S3::Bucket` | `AWS::IAM::Role` | `AWS::SQS::Queue` | `AWS::Lambda::Function` | `AWS::Lambda::LayerVersion` | `AWS::KMS::Key`

| AWS::SecretsManager::Secret | AWS::EFS::FileSystem |
AWS::EC2::Snapshot | AWS::ECR::Repository | AWS::RDS::DBSnapshot
| AWS::RDS::DBClusterSnapshot | AWS::SNS::Topic |
AWS::S3Express::DirectoryBucket | AWS::DynamoDB::Table |
AWS::DynamoDB::Stream | AWS::IAM::User

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InternalAccessConfiguration

Specifies the configuration of an internal access analyzer for an AWS organization or account. This configuration determines how the analyzer evaluates internal access within your AWS environment.

Contents

analysisRule

Contains information about analysis rules for the internal access analyzer. These rules determine which resources and access patterns will be analyzed.

Type: [InternalAccessAnalysisRule](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InternalAccessDetails

Contains information about an internal access finding. This includes details about the access that was identified within your AWS organization or account.

Contents

accessType

The type of internal access identified in the finding. This indicates how the access is granted within your AWS environment.

Type: String

Valid Values: INTRA_ACCOUNT | INTRA_ORG

Required: No

action

The action in the analyzed policy statement that has internal access permission to use.

Type: Array of strings

Required: No

condition

The condition in the analyzed policy statement that resulted in an internal access finding.

Type: String to string map

Required: No

principal

The principal that has access to a resource within the internal environment.

Type: String to string map

Required: No

principalOwnerAccount

The AWS account ID that owns the principal identified in the internal access finding.

Type: String

Required: No

principalType

The type of principal identified in the internal access finding, such as IAM role or IAM user.

Type: String

Valid Values: IAM_ROLE | IAM_USER

Required: No

resourceControlPolicyRestriction

The type of restriction applied to the finding by the resource owner with an AWS Organizations resource control policy (RCP).

- **APPLICABLE**: There is an RCP present in the organization but IAM Access Analyzer does not include it in the evaluation of effective permissions. For example, if `s3:DeleteObject` is blocked by the RCP and the restriction is **APPLICABLE**, then `s3:DeleteObject` would still be included in the list of actions for the finding. Only applicable to internal access findings with the account as the zone of trust.
- **FAILED_TO_EVALUATE_RCP**: There was an error evaluating the RCP.
- **NOT_APPLICABLE**: There was no RCP present in the organization. For internal access findings with the account as the zone of trust, **NOT_APPLICABLE** could also indicate that there was no RCP applicable to the resource.
- **APPLIED**: An RCP is present in the organization and IAM Access Analyzer included it in the evaluation of effective permissions. For example, if `s3:DeleteObject` is blocked by the RCP and the restriction is **APPLIED**, then `s3:DeleteObject` would not be included in the list of actions for the finding. Only applicable to internal access findings with the organization as the zone of trust.

Type: String

Valid Values: APPLICABLE | FAILED_TO_EVALUATE_RCP | NOT_APPLICABLE | APPLIED

Required: No

serviceControlPolicyRestriction

The type of restriction applied to the finding by an AWS Organizations service control policy (SCP).

- **APPLICABLE:** There is an SCP present in the organization but IAM Access Analyzer does not include it in the evaluation of effective permissions. Only applicable to internal access findings with the account as the zone of trust.
- **FAILED_TO_EVALUATE_SCP:** There was an error evaluating the SCP.
- **NOT_APPLICABLE:** There was no SCP present in the organization. For internal access findings with the account as the zone of trust, **NOT_APPLICABLE** could also indicate that there was no SCP applicable to the principal.
- **APPLIED:** An SCP is present in the organization and IAM Access Analyzer included it in the evaluation of effective permissions. Only applicable to internal access findings with the organization as the zone of trust.

Type: String

Valid Values: APPLICABLE | FAILED_TO_EVALUATE_SCP | NOT_APPLICABLE | APPLIED

Required: No

sources

The sources of the internal access finding. This indicates how the access that generated the finding is granted within your AWS environment.

Type: Array of [FindingSource](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InternalAccessFindingsStatistics

Provides aggregate statistics about the findings for the specified internal access analyzer. This includes counts of active, archived, and resolved findings.

Contents

resourceTypeStatistics

The total number of active findings for each resource type of the specified internal access analyzer.

Type: String to [InternalAccessResourceTypeDetails](#) object map

Valid Keys: AWS::S3::Bucket | AWS::IAM::Role | AWS::SQS::Queue | AWS::Lambda::Function | AWS::Lambda::LayerVersion | AWS::KMS::Key | AWS::SecretsManager::Secret | AWS::EFS::FileSystem | AWS::EC2::Snapshot | AWS::ECR::Repository | AWS::RDS::DBSnapshot | AWS::RDS::DBClusterSnapshot | AWS::SNS::Topic | AWS::S3Express::DirectoryBucket | AWS::DynamoDB::Table | AWS::DynamoDB::Stream | AWS::IAM::User

Required: No

totalActiveFindings

The number of active findings for the specified internal access analyzer.

Type: Integer

Required: No

totalArchivedFindings

The number of archived findings for the specified internal access analyzer.

Type: Integer

Required: No

totalResolvedFindings

The number of resolved findings for the specified internal access analyzer.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InternalAccessResourceTypeDetails

Contains information about the total number of active, archived, and resolved findings for a resource type of an internal access analyzer.

Contents

totalActiveFindings

The total number of active findings for the resource type in the internal access analyzer.

Type: Integer

Required: No

totalArchivedFindings

The total number of archived findings for the resource type in the internal access analyzer.

Type: Integer

Required: No

totalResolvedFindings

The total number of resolved findings for the resource type in the internal access analyzer.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InternetConfiguration

This configuration sets the network origin for the Amazon S3 access point or multi-region access point to Internet.

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

JobDetails

Contains details about the policy generation request.

Contents

jobId

The JobId that is returned by the StartPolicyGeneration operation. The JobId can be used with GetGeneratedPolicy to retrieve the generated policies or used with CancelPolicyGeneration to cancel the policy generation request.

Type: String

Required: Yes

startedOn

A timestamp of when the job was started.

Type: Timestamp

Required: Yes

status

The status of the job request.

Type: String

Valid Values: IN_PROGRESS | SUCCEEDED | FAILED | CANCELED

Required: Yes

completedOn

A timestamp of when the job was completed.

Type: Timestamp

Required: No

jobError

The job error for the policy generation request.

Type: [JobError](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

JobError

Contains the details about the policy generation error.

Contents

code

The job error code.

Type: String

Valid Values: AUTHORIZATION_ERROR | RESOURCE_NOT_FOUND_ERROR | SERVICE_QUOTA_EXCEEDED_ERROR | SERVICE_ERROR

Required: Yes

message

Specific information about the error. For example, which service quota was exceeded or which resource was not found.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

KmsGrantConfiguration

A proposed grant configuration for a KMS key. For more information, see [CreateGrant](#).

Contents

granteePrincipal

The principal that is given permission to perform the operations that the grant permits.

Type: String

Required: Yes

issuingAccount

The AWS account under which the grant was issued. The account is used to propose AWS KMS grants issued by accounts other than the owner of the key.

Type: String

Required: Yes

operations

A list of operations that the grant permits.

Type: Array of strings

Valid Values: CreateGrant | Decrypt | DescribeKey | Encrypt | GenerateDataKey | GenerateDataKeyPair | GenerateDataKeyPairWithoutPlaintext | GenerateDataKeyWithoutPlaintext | GetPublicKey | ReEncryptFrom | ReEncryptTo | RetireGrant | Sign | Verify

Required: Yes

constraints

Use this structure to propose allowing [cryptographic operations](#) in the grant only when the operation request includes the specified [encryption context](#).

Type: [KmsGrantConstraints](#) object

Required: No

retiringPrincipal

The principal that is given permission to retire the grant by using [RetireGrant](#) operation.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

KmsGrantConstraints

Use this structure to propose allowing [cryptographic operations](#) in the grant only when the operation request includes the specified [encryption context](#). You can specify only one type of encryption context. An empty map is treated as not specified. For more information, see [GrantConstraints](#).

Contents

encryptionContextEquals

A list of key-value pairs that must match the encryption context in the [cryptographic operation](#) request. The grant allows the operation only when the encryption context in the request is the same as the encryption context specified in this constraint.

Type: String to string map

Required: No

encryptionContextSubset

A list of key-value pairs that must be included in the encryption context of the [cryptographic operation](#) request. The grant allows the cryptographic operation only when the encryption context in the request includes the key-value pairs specified in this constraint, although it can include additional key-value pairs.

Type: String to string map

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

KmsKeyConfiguration

Proposed access control configuration for a KMS key. You can propose a configuration for a new KMS key or an existing KMS key that you own by specifying the key policy and AWS KMS grant configuration. If the configuration is for an existing key and you do not specify the key policy, the access preview uses the existing policy for the key. If the access preview is for a new resource and you do not specify the key policy, then the access preview uses the default key policy. The proposed key policy cannot be an empty string. For more information, see [Default key policy](#). For more information about key policy limits, see [Resource quotas](#).

Contents

grants

A list of proposed grant configurations for the KMS key. If the proposed grant configuration is for an existing key, the access preview uses the proposed list of grant configurations in place of the existing grants. Otherwise, the access preview uses the existing grants for the key.

Type: Array of [KmsGrantConfiguration](#) objects

Required: No

keyPolicies

Resource policy configuration for the KMS key. The only valid value for the name of the key policy is default. For more information, see [Default key policy](#).

Type: String to string map

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Location

A location in a policy that is represented as a path through the JSON representation and a corresponding span.

Contents

path

A path in a policy, represented as a sequence of path elements.

Type: Array of [PathElement](#) objects

Required: Yes

span

A span in a policy.

Type: [Span](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NetworkOriginConfiguration

The proposed `InternetConfiguration` or `VpcConfiguration` to apply to the Amazon S3 access point. You can make the access point accessible from the internet, or you can specify that all requests made through that access point must originate from a specific virtual private cloud (VPC). You can specify only one type of network configuration. For more information, see [Creating access points](#).

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

internetConfiguration

The configuration for the Amazon S3 access point or multi-region access point with an Internet origin.

Type: [InternetConfiguration](#) object

Required: No

vpcConfiguration

The proposed virtual private cloud (VPC) configuration for the Amazon S3 access point. VPC configuration does not apply to multi-region access points. For more information, see [VpcConfiguration](#).

Type: [VpcConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PathElement

A single element in a path through the JSON representation of a policy.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

index

Refers to an index in a JSON array.

Type: Integer

Required: No

key

Refers to a key in a JSON object.

Type: String

Required: No

substring

Refers to a substring of a literal string in a JSON object.

Type: [Substring](#) object

Required: No

value

Refers to the value associated with a given key in a JSON object.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PolicyGeneration

Contains details about the policy generation status and properties.

Contents

jobId

The JobId that is returned by the StartPolicyGeneration operation. The JobId can be used with GetGeneratedPolicy to retrieve the generated policies or used with CancelPolicyGeneration to cancel the policy generation request.

Type: String

Required: Yes

principalArn

The ARN of the IAM entity (user or role) for which you are generating a policy.

Type: String

Pattern: `arn:[^:]*:iam:[^:]*:(role|user)/.{1,576}`

Required: Yes

startedOn

A timestamp of when the policy generation started.

Type: Timestamp

Required: Yes

status

The status of the policy generation request.

Type: String

Valid Values: IN_PROGRESS | SUCCEEDED | FAILED | CANCELED

Required: Yes

completedOn

A timestamp of when the policy generation was completed.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PolicyGenerationDetails

Contains the ARN details about the IAM entity for which the policy is generated.

Contents

principalArn

The ARN of the IAM entity (user or role) for which you are generating a policy.

Type: String

Pattern: `arn:[^:]*:iam:[^:]*:(role|user)/.{1,576}`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Position

A position in a policy.

Contents

column

The column of the position, starting from 0.

Type: Integer

Required: Yes

line

The line of the position, starting from 1.

Type: Integer

Required: Yes

offset

The offset within the policy that corresponds to the position, starting from 0.

Type: Integer

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RdsDbClusterSnapshotAttributeValue

The values for a manual Amazon RDS DB cluster snapshot attribute.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

accountIds

The AWS account IDs that have access to the manual Amazon RDS DB cluster snapshot. If the value `all` is specified, then the Amazon RDS DB cluster snapshot is public and can be copied or restored by all AWS accounts.

- If the configuration is for an existing Amazon RDS DB cluster snapshot and you do not specify the `accountIds` in `RdsDbClusterSnapshotAttributeValue`, then the access preview uses the existing shared `accountIds` for the snapshot.
- If the access preview is for a new resource and you do not specify the `accountIds` in `RdsDbClusterSnapshotAttributeValue`, then the access preview considers the snapshot without any attributes.
- To propose deletion of existing shared `accountIds`, you can specify an empty list for `accountIds` in the `RdsDbClusterSnapshotAttributeValue`.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

RdsDbClusterSnapshotConfiguration

The proposed access control configuration for an Amazon RDS DB cluster snapshot. You can propose a configuration for a new Amazon RDS DB cluster snapshot or an Amazon RDS DB cluster snapshot that you own by specifying the `RdsDbClusterSnapshotAttributeValue` and optional AWS KMS encryption key. For more information, see [ModifyDBClusterSnapshotAttribute](#).

Contents

attributes

The names and values of manual DB cluster snapshot attributes. Manual DB cluster snapshot attributes are used to authorize other AWS accounts to restore a manual DB cluster snapshot. The only valid value for `AttributeName` for the attribute map is `restore`

Type: String to [RdsDbClusterSnapshotAttributeValue](#) object map

Required: No

kmsKeyId

The KMS key identifier for an encrypted Amazon RDS DB cluster snapshot. The KMS key identifier is the key ARN, key ID, alias ARN, or alias name for the KMS key.

- If the configuration is for an existing Amazon RDS DB cluster snapshot and you do not specify the `kmsKeyId`, or you specify an empty string, then the access preview uses the existing `kmsKeyId` of the snapshot.
- If the access preview is for a new resource and you do not specify the `kmsKeyId`, then the access preview considers the snapshot as unencrypted.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RdsDbSnapshotAttributeValue

The name and values of a manual Amazon RDS DB snapshot attribute. Manual DB snapshot attributes are used to authorize other AWS accounts to restore a manual DB snapshot.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

accountIds

The AWS account IDs that have access to the manual Amazon RDS DB snapshot. If the value `all` is specified, then the Amazon RDS DB snapshot is public and can be copied or restored by all AWS accounts.

- If the configuration is for an existing Amazon RDS DB snapshot and you do not specify the `accountIds` in `RdsDbSnapshotAttributeValue`, then the access preview uses the existing shared `accountIds` for the snapshot.
- If the access preview is for a new resource and you do not specify the `accountIds` in `RdsDbSnapshotAttributeValue`, then the access preview considers the snapshot without any attributes.
- To propose deletion of an existing shared `accountIds`, you can specify an empty list for `accountIds` in the `RdsDbSnapshotAttributeValue`.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RdsDbSnapshotConfiguration

The proposed access control configuration for an Amazon RDS DB snapshot. You can propose a configuration for a new Amazon RDS DB snapshot or an Amazon RDS DB snapshot that you own by specifying the `RdsDbSnapshotAttributeValue` and optional AWS KMS encryption key. For more information, see [ModifyDBSnapshotAttribute](#).

Contents

attributes

The names and values of manual DB snapshot attributes. Manual DB snapshot attributes are used to authorize other AWS accounts to restore a manual DB snapshot. The only valid value for `attributeName` for the attribute map is `restore`.

Type: String to [RdsDbSnapshotAttributeValue](#) object map

Required: No

kmsKeyId

The KMS key identifier for an encrypted Amazon RDS DB snapshot. The KMS key identifier is the key ARN, key ID, alias ARN, or alias name for the KMS key.

- If the configuration is for an existing Amazon RDS DB snapshot and you do not specify the `kmsKeyId`, or you specify an empty string, then the access preview uses the existing `kmsKeyId` of the snapshot.
- If the access preview is for a new resource and you do not specify the `kmsKeyId`, then the access preview considers the snapshot as unencrypted.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ReasonSummary

Contains information about the reasoning why a check for access passed or failed.

Contents

description

A description of the reasoning of a result of checking for access.

Type: String

Required: No

statementId

The identifier for the reason statement.

Type: String

Required: No

statementIndex

The index number of the reason statement.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RecommendationError

Contains information about the reason that the retrieval of a recommendation for a finding failed.

Contents

code

The error code for a failed retrieval of a recommendation for a finding.

Type: String

Required: Yes

message

The error message for a failed retrieval of a recommendation for a finding.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RecommendedStep

Contains information about a recommended step for an unused access analyzer finding.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

unusedPermissionsRecommendedStep

A recommended step for an unused permissions finding.

Type: [UnusedPermissionsRecommendedStep](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceTypeDetails

Contains information about the total number of active cross-account and public findings for a resource type of an external access analyzer.

Contents

totalActiveCrossAccount

The total number of active cross-account findings for the resource type.

Type: Integer

Required: No

totalActiveErrors

The total number of active errors for the resource type.

Type: Integer

Required: No

totalActivePublic

The total number of active public findings for the resource type.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3AccessPointConfiguration

The configuration for an Amazon S3 access point or multi-region access point for the bucket. You can propose up to 10 access points or multi-region access points per bucket. If the proposed Amazon S3 access point configuration is for an existing bucket, the access preview uses the proposed access point configuration in place of the existing access points. To propose an access point without a policy, you can provide an empty string as the access point policy. For more information, see [Creating access points](#). For more information about access point policy limits, see [Access points restrictions and limitations](#).

Contents

accessPointPolicy

The access point or multi-region access point policy.

Type: String

Required: No

networkOrigin

The proposed Internet and VpcConfiguration to apply to this Amazon S3 access point. VpcConfiguration does not apply to multi-region access points. If the access preview is for a new resource and neither is specified, the access preview uses Internet for the network origin. If the access preview is for an existing resource and neither is specified, the access preview uses the existing network origin.

Type: [NetworkOriginConfiguration](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

publicAccessBlock

The proposed S3PublicAccessBlock configuration to apply to this Amazon S3 access point or multi-region access point.

Type: [S3PublicAccessBlockConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3BucketAclGrantConfiguration

A proposed access control list grant configuration for an Amazon S3 bucket. For more information, see [How to Specify an ACL](#).

Contents

grantee

The grantee to whom you're assigning access rights.

Type: [AclGrantee](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

permission

The permissions being granted.

Type: String

Valid Values: READ | WRITE | READ_ACP | WRITE_ACP | FULL_CONTROL

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3BucketConfiguration

Proposed access control configuration for an Amazon S3 bucket. You can propose a configuration for a new Amazon S3 bucket or an existing Amazon S3 bucket that you own by specifying the Amazon S3 bucket policy, bucket ACLs, bucket BPA settings, Amazon S3 access points, and multi-region access points attached to the bucket. If the configuration is for an existing Amazon S3 bucket and you do not specify the Amazon S3 bucket policy, the access preview uses the existing policy attached to the bucket. If the access preview is for a new resource and you do not specify the Amazon S3 bucket policy, the access preview assumes a bucket without a policy. To propose deletion of an existing bucket policy, you can specify an empty string. For more information about bucket policy limits, see [Bucket Policy Examples](#).

Contents

accessPoints

The configuration of Amazon S3 access points or multi-region access points for the bucket. You can propose up to 10 new access points per bucket.

Type: String to [S3AccessPointConfiguration](#) object map

Key Pattern: `arn:[^:]*:s3:[^:]*:[^:]*:accesspoint/.*`

Required: No

bucketAclGrants

The proposed list of ACL grants for the Amazon S3 bucket. You can propose up to 100 ACL grants per bucket. If the proposed grant configuration is for an existing bucket, the access preview uses the proposed list of grant configurations in place of the existing grants. Otherwise, the access preview uses the existing grants for the bucket.

Type: Array of [S3BucketAclGrantConfiguration](#) objects

Required: No

bucketPolicy

The proposed bucket policy for the Amazon S3 bucket.

Type: String

Required: No

bucketPublicAccessBlock

The proposed block public access configuration for the Amazon S3 bucket.

Type: [S3PublicAccessBlockConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3ExpressDirectoryAccessPointConfiguration

Proposed configuration for an access point attached to an Amazon S3 directory bucket. You can propose up to 10 access points per bucket. If the proposed access point configuration is for an existing Amazon S3 directory bucket, the access preview uses the proposed access point configuration in place of the existing access points. To propose an access point without a policy, you can provide an empty string as the access point policy. For more information about access points for Amazon S3 directory buckets, see [Managing access to directory buckets with access points](#) in the Amazon Simple Storage Service User Guide.

Contents

accessPointPolicy

The proposed access point policy for an Amazon S3 directory bucket access point.

Type: String

Required: No

networkOrigin

The proposed `InternetConfiguration` or `VpcConfiguration` to apply to the Amazon S3 access point. You can make the access point accessible from the internet, or you can specify that all requests made through that access point must originate from a specific virtual private cloud (VPC). You can specify only one type of network configuration. For more information, see [Creating access points](#).

Type: [NetworkOriginConfiguration](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3ExpressDirectoryBucketConfiguration

Proposed access control configuration for an Amazon S3 directory bucket. You can propose a configuration for a new Amazon S3 directory bucket or an existing Amazon S3 directory bucket that you own by specifying the Amazon S3 bucket policy. If the configuration is for an existing Amazon S3 directory bucket and you do not specify the Amazon S3 bucket policy, the access preview uses the existing policy attached to the directory bucket. If the access preview is for a new resource and you do not specify the Amazon S3 bucket policy, the access preview assumes an directory bucket without a policy. To propose deletion of an existing bucket policy, you can specify an empty string. For more information about Amazon S3 directory bucket policies, see [Example bucket policies for directory buckets](#) in the Amazon Simple Storage Service User Guide.

Contents

accessPoints

The proposed access points for the Amazon S3 directory bucket.

Type: String to [S3ExpressDirectoryAccessPointConfiguration](#) object map

Key Pattern: `arn:[^:]*:s3express:[^:]*:[^:]*:accesspoint/.*`

Required: No

bucketPolicy

The proposed bucket policy for the Amazon S3 directory bucket.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3PublicAccessBlockConfiguration

The `PublicAccessBlock` configuration to apply to this Amazon S3 bucket. If the proposed configuration is for an existing Amazon S3 bucket and the configuration is not specified, the access preview uses the existing setting. If the proposed configuration is for a new bucket and the configuration is not specified, the access preview uses `false`. If the proposed configuration is for a new access point or multi-region access point and the access point BPA configuration is not specified, the access preview uses `true`. For more information, see [PublicAccessBlockConfiguration](#).

Contents

`ignorePublicAcls`

Specifies whether Amazon S3 should ignore public ACLs for this bucket and objects in this bucket.

Type: Boolean

Required: Yes

`restrictPublicBuckets`

Specifies whether Amazon S3 should restrict public bucket policies for this bucket.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SecretsManagerSecretConfiguration

The configuration for a Secrets Manager secret. For more information, see [CreateSecret](#).

You can propose a configuration for a new secret or an existing secret that you own by specifying the secret policy and optional AWS KMS encryption key. If the configuration is for an existing secret and you do not specify the secret policy, the access preview uses the existing policy for the secret. If the access preview is for a new resource and you do not specify the policy, the access preview assumes a secret without a policy. To propose deletion of an existing policy, you can specify an empty string. If the proposed configuration is for a new secret and you do not specify the KMS key ID, the access preview uses the AWS managed key `aws/secretsmanager`. If you specify an empty string for the KMS key ID, the access preview uses the AWS managed key of the AWS account. For more information about secret policy limits, see [Quotas for AWS Secrets Manager](#).

Contents

`kmsKeyId`

The proposed ARN, key ID, or alias of the KMS key.

Type: String

Required: No

`secretPolicy`

The proposed resource policy defining who can access or manage the secret.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SnsTopicConfiguration

The proposed access control configuration for an Amazon SNS topic. You can propose a configuration for a new Amazon SNS topic or an existing Amazon SNS topic that you own by specifying the policy. If the configuration is for an existing Amazon SNS topic and you do not specify the Amazon SNS policy, then the access preview uses the existing Amazon SNS policy for the topic. If the access preview is for a new resource and you do not specify the policy, then the access preview assumes an Amazon SNS topic without a policy. To propose deletion of an existing Amazon SNS topic policy, you can specify an empty string for the Amazon SNS policy. For more information, see [Topic](#).

Contents

topicPolicy

The JSON policy text that defines who can access an Amazon SNS topic. For more information, see [Example cases for Amazon SNS access control](#) in the *Amazon SNS Developer Guide*.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 30720.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SortCriteria

The criteria used to sort.

Contents

attributeName

The name of the attribute to sort on.

Type: String

Required: No

orderBy

The sort order, ascending or descending.

Type: String

Valid Values: ASC | DESC

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Span

A span in a policy. The span consists of a start position (inclusive) and end position (exclusive).

Contents

end

The end position of the span (exclusive).

Type: [Position](#) object

Required: Yes

start

The start position of the span (inclusive).

Type: [Position](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SqsQueueConfiguration

The proposed access control configuration for an Amazon SQS queue. You can propose a configuration for a new Amazon SQS queue or an existing Amazon SQS queue that you own by specifying the Amazon SQS policy. If the configuration is for an existing Amazon SQS queue and you do not specify the Amazon SQS policy, the access preview uses the existing Amazon SQS policy for the queue. If the access preview is for a new resource and you do not specify the policy, the access preview assumes an Amazon SQS queue without a policy. To propose deletion of an existing Amazon SQS queue policy, you can specify an empty string for the Amazon SQS policy. For more information about Amazon SQS policy limits, see [Quotas related to policies](#).

Contents

queuePolicy

The proposed resource policy for the Amazon SQS queue.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

StatusReason

Provides more details about the current status of the analyzer. For example, if the creation for the analyzer fails, a `Failed` status is returned. For an analyzer with `organization` as the type, this failure can be due to an issue with creating the service-linked roles required in the member accounts of the AWS organization.

Contents

code

The reason code for the current status of the analyzer.

Type: String

Valid Values: `AWS_SERVICE_ACCESS_DISABLED` | `DELEGATED_ADMINISTRATOR_DEREGISTERED` | `ORGANIZATION_DELETED` | `SERVICE_LINKED_ROLE_CREATION_FAILED`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Substring

A reference to a substring of a literal string in a JSON document.

Contents

length

The length of the substring.

Type: Integer

Required: Yes

start

The start index of the substring, starting from 0.

Type: Integer

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Trail

Contains details about the CloudTrail trail being analyzed to generate a policy.

Contents

cloudTrailArn

Specifies the ARN of the trail. The format of a trail ARN is `arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail`.

Type: String

Pattern: `arn:[^:]*:cloudtrail:[^:]*:[^:]*:trail/.{1,576}`

Required: Yes

allRegions

Possible values are `true` or `false`. If set to `true`, IAM Access Analyzer retrieves CloudTrail data from all regions to analyze and generate a policy.

Type: Boolean

Required: No

regions

A list of regions to get CloudTrail data from and analyze to generate a policy.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrailProperties

Contains details about the CloudTrail trail being analyzed to generate a policy.

Contents

cloudTrailArn

Specifies the ARN of the trail. The format of a trail ARN is `arn:aws:cloudtrail:us-east-2:123456789012:trail/MyTrail`.

Type: String

Pattern: `arn:[^:]*:cloudtrail:[^:]*:[^:]*:trail/.{1,576}`

Required: Yes

allRegions

Possible values are `true` or `false`. If set to `true`, IAM Access Analyzer retrieves CloudTrail data from all regions to analyze and generate a policy.

Type: Boolean

Required: No

regions

A list of regions to get CloudTrail data from and analyze to generate a policy.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UnusedAccessConfiguration

Contains information about an unused access analyzer.

Contents

analysisRule

Contains information about analysis rules for the analyzer. Analysis rules determine which entities will generate findings based on the criteria you define when you create the rule.

Type: [AnalysisRule](#) object

Required: No

unusedAccessAge

The specified access age in days for which to generate findings for unused access. For example, if you specify 90 days, the analyzer will generate findings for IAM entities within the accounts of the selected organization for any access that hasn't been used in 90 or more days since the analyzer's last scan. You can choose a value between 1 and 365 days.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UnusedAccessFindingsStatistics

Provides aggregate statistics about the findings for the specified unused access analyzer.

Contents

topAccounts

A list of one to ten AWS accounts that have the most active findings for the unused access analyzer.

Type: Array of [FindingAggregationAccountDetails](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

totalActiveFindings

The total number of active findings for the unused access analyzer.

Type: Integer

Required: No

totalArchivedFindings

The total number of archived findings for the unused access analyzer.

Type: Integer

Required: No

totalResolvedFindings

The total number of resolved findings for the unused access analyzer.

Type: Integer

Required: No

unusedAccessTypeStatistics

A list of details about the total number of findings for each type of unused access for the analyzer.

Type: Array of [UnusedAccessTypeStatistics](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UnusedAccessTypeStatistics

Contains information about the total number of findings for a type of unused access.

Contents

total

The total number of findings for the specified unused access type.

Type: Integer

Required: No

unusedAccessType

The type of unused access.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UnusedAction

Contains information about an unused access finding for an action. IAM Access Analyzer charges for unused access analysis based on the number of IAM roles and users analyzed per month. For more details on pricing, see [IAM Access Analyzer pricing](#).

Contents

action

The action for which the unused access finding was generated.

Type: String

Required: Yes

lastAccessed

The time at which the action was last accessed.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UnusedIamRoleDetails

Contains information about an unused access finding for an IAM role. IAM Access Analyzer charges for unused access analysis based on the number of IAM roles and users analyzed per month. For more details on pricing, see [IAM Access Analyzer pricing](#).

Contents

lastAccessed

The time at which the role was last accessed.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UnusedIamUserAccessKeyDetails

Contains information about an unused access finding for an IAM user access key. IAM Access Analyzer charges for unused access analysis based on the number of IAM roles and users analyzed per month. For more details on pricing, see [IAM Access Analyzer pricing](#).

Contents

accessKeyId

The ID of the access key for which the unused access finding was generated.

Type: String

Required: Yes

lastAccessed

The time at which the access key was last accessed.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UnusedIamUserPasswordDetails

Contains information about an unused access finding for an IAM user password. IAM Access Analyzer charges for unused access analysis based on the number of IAM roles and users analyzed per month. For more details on pricing, see [IAM Access Analyzer pricing](#).

Contents

lastAccessed

The time at which the password was last accessed.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UnusedPermissionDetails

Contains information about an unused access finding for a permission. IAM Access Analyzer charges for unused access analysis based on the number of IAM roles and users analyzed per month. For more details on pricing, see [IAM Access Analyzer pricing](#).

Contents

serviceNamespace

The namespace of the AWS service that contains the unused actions.

Type: String

Required: Yes

actions

A list of unused actions for which the unused access finding was generated.

Type: Array of [UnusedAction](#) objects

Required: No

lastAccessed

The time at which the permission was last accessed.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UnusedPermissionsRecommendedStep

Contains information about the action to take for a policy in an unused permissions finding.

Contents

recommendedAction

A recommendation of whether to create or detach a policy for an unused permissions finding.

Type: String

Valid Values: CREATE_POLICY | DETACH_POLICY

Required: Yes

existingPolicyId

If the recommended action for the unused permissions finding is to detach a policy, the ID of an existing policy to be detached.

Type: String

Required: No

policyUpdatedAt

The time at which the existing policy for the unused permissions finding was last updated.

Type: Timestamp

Required: No

recommendedPolicy

If the recommended action for the unused permissions finding is to replace the existing policy, the contents of the recommended policy to replace the policy specified in the `existingPolicyId` field.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ValidatePolicyFinding

A finding in a policy. Each finding is an actionable recommendation that can be used to improve the policy.

Contents

findingDetails

A localized message that explains the finding and provides guidance on how to address it.

Type: String

Required: Yes

findingType

The impact of the finding.

Security warnings report when the policy allows access that we consider overly permissive.

Errors report when a part of the policy is not functional.

Warnings report non-security issues when a policy does not conform to policy writing best practices.

Suggestions recommend stylistic improvements in the policy that do not impact access.

Type: String

Valid Values: ERROR | SECURITY_WARNING | SUGGESTION | WARNING

Required: Yes

issueCode

The issue code provides an identifier of the issue associated with this finding.

Type: String

Required: Yes

learnMoreLink

A link to additional documentation about the type of finding.

Type: String

Required: Yes

locations

The list of locations in the policy document that are related to the finding. The issue code provides a summary of an issue identified by the finding.

Type: Array of [Location](#) objects

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ValidationExceptionField

Contains information about a validation exception.

Contents

message

A message about the validation exception.

Type: String

Required: Yes

name

The name of the validation exception.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VpcConfiguration

The proposed virtual private cloud (VPC) configuration for the Amazon S3 access point. VPC configuration does not apply to multi-region access points. For more information, see [VpcConfiguration](#).

Contents

vpclId

If this field is specified, this access point will only allow connections from the specified VPC ID.

Type: String

Pattern: vpc-([0-9a-f]){8}(([0-9a-f]){9})?

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Error Types

This section lists common error types that this AWS service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

IncompleteSignature

The request signature doesn't conform to AWS standards. Verify that you're using valid AWS credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 403

InternalFailure

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact AWS Support.

HTTP Status Code: 500

MalformedHttpRequestException

The request body can't be processed. This typically happens when the request body can't be decompressed using the specified content encoding algorithm. Verify that the content encoding header matches the compression format used.

HTTP Status Code: 400

NotAuthorized

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

OptInRequired

Your AWS account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

RequestAbortedException

The request was aborted before a response could be returned. This typically happens when the client closes the connection.

HTTP Status Code: 400

RequestEntityTooLargeException

The request entity is too large. Reduce the size of the request body and try again.

HTTP Status Code: 413

RequestTimeoutException

The request timed out. The server didn't receive the complete request within the expected time frame. Try again.

HTTP Status Code: 408

ServiceUnavailable

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

ThrottlingException

Your request rate is too high. The AWS SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

UnknownOperationException

The action or operation isn't recognized. Verify that the action name is spelled correctly and that it's supported by the API version you're using.

HTTP Status Code: 404

UnrecognizedClientException

The X.509 certificate or AWS access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

ValidationError

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400