



AgentRegistry Control Plane API Reference

AgentRegistry Control Plane API Reference



API Version 2025-12-01

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AgentRegistry Control Plane API Reference: AgentRegistry Control Plane API Reference

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
CreateRegistry	3
Request Syntax	3
URI Request Parameters	3
Request Body	3
Response Syntax	5
Response Elements	5
Errors	5
See Also	6
CreateRegistryRecord	8
Request Syntax	8
URI Request Parameters	10
Request Body	10
Response Syntax	12
Response Elements	12
Errors	13
See Also	14
DeleteRegistry	15
Request Syntax	15
URI Request Parameters	15
Request Body	15
Response Syntax	15
Response Elements	15
Errors	16
See Also	17
DeleteRegistryRecord	18
Request Syntax	18
URI Request Parameters	18
Request Body	18
Response Syntax	18
Response Elements	19
Errors	19
See Also	20

GetRegistry	21
Request Syntax	21
URI Request Parameters	21
Request Body	21
Response Syntax	21
Response Elements	22
Errors	24
See Also	24
GetRegistryRecord	26
Request Syntax	26
URI Request Parameters	26
Request Body	26
Response Syntax	26
Response Elements	28
Errors	31
See Also	32
ListRegistries	33
Request Syntax	33
URI Request Parameters	33
Request Body	33
Response Syntax	34
Response Elements	35
Errors	35
See Also	36
ListRegistryRecords	37
Request Syntax	37
URI Request Parameters	37
Request Body	37
Response Syntax	38
Response Elements	39
Errors	39
See Also	40
ListTagsForResource	42
Request Syntax	42
URI Request Parameters	42
Request Body	42

Response Syntax	42
Response Elements	42
Errors	43
See Also	44
SubmitRegistryRecordForApproval	45
Request Syntax	45
URI Request Parameters	45
Request Body	45
Response Syntax	46
Response Elements	46
Errors	47
See Also	48
TagResource	50
Request Syntax	50
URI Request Parameters	50
Request Body	50
Response Syntax	51
Response Elements	51
Errors	51
See Also	52
UntagResource	54
Request Syntax	54
URI Request Parameters	54
Request Body	54
Response Syntax	54
Response Elements	55
Errors	55
See Also	56
UpdateRegistry	57
Request Syntax	57
URI Request Parameters	57
Request Body	58
Response Syntax	58
Response Elements	59
Errors	61
See Also	62

UpdateRegistryRecord	63
Request Syntax	63
URI Request Parameters	66
Request Body	66
Response Syntax	68
Response Elements	70
Errors	72
See Also	73
UpdateRegistryRecordStatus	75
Request Syntax	75
URI Request Parameters	75
Request Body	76
Response Syntax	76
Response Elements	76
Errors	78
See Also	79
Data Types	80
A2aAgentCardDescriptor	83
Contents	83
See Also	83
AgentSkillsAdditionalData	85
Contents	85
See Also	85
AgentSkillsDefinitionDescriptor	86
Contents	86
See Also	86
AgentSkillsMdDescriptor	88
Contents	88
See Also	88
ApprovalConfiguration	90
Contents	90
See Also	90
AuthorizerConfiguration	91
Contents	91
See Also	91
AuthorizingClaimMatchValueType	92

Contents	92
See Also	92
ClaimMatchValueType	93
Contents	93
See Also	93
CustomClaimValidationType	95
Contents	95
See Also	95
CustomDescriptor	97
Contents	97
See Also	97
CustomJWTAuthorizerConfiguration	98
Contents	98
See Also	100
Descriptors	101
Contents	101
See Also	101
DescriptorSource	103
Contents	103
See Also	103
DescriptorSourceFromUrl	104
Contents	104
See Also	104
DiscoveryConfiguration	105
Contents	105
See Also	105
ManagedVpcResource	106
Contents	106
See Also	107
McpServerAdditionalData	109
Contents	109
See Also	109
McpServerDescriptor	110
Contents	110
See Also	111
McpToolsDescriptor	112

Contents	112
See Also	112
PrivateEndpoint	113
Contents	113
See Also	113
PrivateEndpointOverride	114
Contents	114
See Also	114
RegistryFilter	115
Contents	115
See Also	115
RegistryRecordCredentialProviderConfiguration	116
Contents	116
See Also	116
RegistryRecordCredentialProviderUnion	117
Contents	117
See Also	117
RegistryRecordFilter	118
Contents	118
See Also	118
RegistryRecordIamCredentialProvider	119
Contents	119
See Also	120
RegistryRecordOAuthCredentialProvider	121
Contents	121
See Also	122
RegistryRecordSummary	123
Contents	123
See Also	125
RegistrySummary	126
Contents	126
See Also	128
SelfManagedLatticeResource	129
Contents	129
See Also	129
UpdatedA2aAgentCardDescriptor	130

Contents	130
See Also	130
UpdatedA2aAgentCardDescriptorFields	131
Contents	131
See Also	131
UpdatedAgentSkillsAdditionalData	132
Contents	132
See Also	132
UpdatedAgentSkillsAdditionalDataFields	133
Contents	133
See Also	133
UpdatedAgentSkillsDefinitionDescriptor	134
Contents	134
See Also	134
UpdatedAgentSkillsDefinitionDescriptorFields	135
Contents	135
See Also	135
UpdatedAgentSkillsMdDescriptor	136
Contents	136
See Also	136
UpdatedAgentSkillsMdDescriptorFields	137
Contents	137
See Also	137
UpdatedApprovalConfiguration	138
Contents	138
See Also	138
UpdatedAuthorizerConfiguration	139
Contents	139
See Also	139
UpdatedCustomDescriptor	140
Contents	140
See Also	140
UpdatedCustomDescriptorFields	141
Contents	141
See Also	141
UpdatedDataSchemaVersion	142

Contents	142
See Also	142
UpdatedDescription	143
Contents	143
See Also	143
UpdatedDescriptorData	144
Contents	144
See Also	144
UpdatedDescriptors	145
Contents	145
See Also	145
UpdatedDescriptorsFields	146
Contents	146
See Also	146
UpdatedDescriptorSource	148
Contents	148
See Also	148
UpdatedDiscoveryConfiguration	149
Contents	149
See Also	149
UpdatedDisplayName	150
Contents	150
See Also	150
UpdatedMcpServerAdditionalData	151
Contents	151
See Also	151
UpdatedMcpServerAdditionalDataFields	152
Contents	152
See Also	152
UpdatedMcpServerDescriptor	153
Contents	153
See Also	153
UpdatedMcpServerDescriptorFields	154
Contents	154
See Also	154
UpdatedMcpToolsDescriptor	156

- Contents 156
- See Also 156
- UpdatedMcpToolsDescriptorFields 157
 - Contents 157
 - See Also 157
- ValidationExceptionField 158
 - Contents 158
 - See Also 158
- Common Parameters 159**
- Common Error Types 162**

Welcome

AWS Agent Registry is a managed catalog for publishing and discovering resources such as MCP servers, agents, and agent skills. Agent Registry Control is its control-plane API: use it to create and manage registries and the records they contain, configure discovery and authorization, govern record approval and curation workflows, and manage automatic detection of resources. Data-plane search and MCP invocation operations are provided by the companion Agent Registry API.

This document was last published on August 7, 2026.

Actions

The following actions are supported:

- [CreateRegistry](#)
- [CreateRegistryRecord](#)
- [DeleteRegistry](#)
- [DeleteRegistryRecord](#)
- [GetRegistry](#)
- [GetRegistryRecord](#)
- [ListRegistries](#)
- [ListRegistryRecords](#)
- [ListTagsForResource](#)
- [SubmitRegistryRecordForApproval](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateRegistry](#)
- [UpdateRegistryRecord](#)
- [UpdateRegistryRecordStatus](#)

CreateRegistry

Creates a new registry, a catalog that organizes registry records and defines their discovery authorization and record approval behavior. Creation is asynchronous: the registry begins in the CREATING status and becomes usable once it reaches READY.

Request Syntax

```
POST /registries HTTP/1.1
Content-type: application/json

{
  "approvalConfiguration": {
    "autoApprovalRules": [ "string" ]
  },
  "clientToken": "string",
  "description": "string",
  "discoveryConfiguration": {
    "authorizerConfiguration": { ... },
    "authorizerType": "string"
  },
  "name": "string",
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

approvalConfiguration

Approval configuration for registry records

Type: [ApprovalConfiguration](#) object

Required: No

clientToken

Client token for idempotency

Type: String

Length Constraints: Minimum length of 33. Maximum length of 256.

Pattern: `[a-zA-Z0-9](-*[a-zA-Z0-9]){0,256}`

Required: No

description

The description of the registry

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

discoveryConfiguration

Discovery configuration for the registry

Type: [DiscoveryConfiguration](#) object

Required: No

name

The name of the registry

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_-\.\|]*`

Required: Yes

tags

Tags to associate with the registry

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `[a-zA-Z0-9\s._:/=+@-]*`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `[a-zA-Z0-9\s._:/=+@-]*`

Required: No

Response Syntax

```
HTTP/1.1 202
Content-type: application/json

{
  "registryArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

registryArn

The ARN of the created registry

Type: String

Length Constraints: Minimum length of 46. Maximum length of 2048.

Pattern: `arn:aws(-[^\:]+)?:agent-registry:[a-z0-9-]+:[0-9]{12}:registry/[a-zA-Z0-9]{12,16}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The caller is not authorized to perform the requested action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource.

HTTP Status Code: 409

InternalServerError

The request failed due to an unexpected internal error; the caller may retry.

HTTP Status Code: 500

ServiceQuotaExceededException

The request would exceed a service quota.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling; the caller may retry after a delay.

HTTP Status Code: 429

ValidationException

The request failed validation of one or more input fields.

fieldList

The list of input fields that failed validation.

reason

The reason the request failed validation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateRegistryRecord

Creates a registry record within a registry. A registry record describes a discoverable resource, such as an MCP server, an agent, an agent skill, or a custom resource. Creation is asynchronous: the record is returned with the CREATING status while it is processed.

Request Syntax

POST /registries/*registryId*/records HTTP/1.1

Content-type: application/json

```
{
  "clientToken": "string",
  "description": "string",
  "descriptors": {
    "a2aAgentCard": {
      "data": "string",
      "dataSchemaVersion": "string",
      "source": {
        "fromUrl": {
          "credentialProviderConfigurations": [
            {
              "credentialProvider": { ... },
              "credentialProviderType": "string"
            }
          ],
          "url": "string"
        }
      }
    },
    "agentSkillsDefinition": {
      "additionalData": {
        "skillMd": {
          "data": "string",
          "dataSchemaVersion": "string",
          "source": {
            "fromUrl": {
              "credentialProviderConfigurations": [
                {
                  "credentialProvider": { ... },
                  "credentialProviderType": "string"
                }
              ]
            }
          }
        }
      }
    }
  }
}
```

```

        ],
        "url": "string"
      }
    }
  },
  "data": "string",
  "dataSchemaVersion": "string"
},
"custom": {
  "data": "string"
},
"mcpServer": {
  "additionalData": {
    "tools": {
      "data": "string",
      "dataSchemaVersion": "string"
    }
  },
  "data": "string",
  "dataSchemaVersion": "string",
  "source": {
    "fromUrl": {
      "credentialProviderConfigurations": [
        {
          "credentialProvider": { ... },
          "credentialProviderType": "string"
        }
      ],
      "url": "string"
    }
  }
}
},
"displayName": "string",
"name": "string",
"recordType": "string",
"recordVersion": "string",
"tags": {
  "string" : "string"
}
}

```

URI Request Parameters

The request uses the following URI parameters.

registryId

The identifier of the registry in which to create the record (ARN or ID)

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `(arn:aws(-[^\:]+)? :agent-registry:[a-z0-9-]+:[0-9]{12}:registry/)?[a-zA-Z0-9]{12,16}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

clientToken

Client token for idempotency

Type: String

Length Constraints: Minimum length of 33. Maximum length of 256.

Pattern: `[a-zA-Z0-9](-*[a-zA-Z0-9]){0,256}`

Required: No

description

The description of the registry record

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

descriptors

The typed descriptor content for the registry record

Type: [Descriptors](#) object

Required: Yes

[displayName](#)

The human-readable display name of the registry record

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

[name](#)

The name of the registry record

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_-\.\|]*`

Required: Yes

[recordType](#)

The type of the registry record, which determines the descriptor format

Type: String

Valid Values: MCP | AGENT | CUSTOM | SKILL

Required: Yes

[recordVersion](#)

The version of the registry record

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[a-zA-Z0-9.-]+`

Required: No

tags

Tags to associate with the registry record

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `[a-zA-Z0-9\s._:/=+@-]*`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `[a-zA-Z0-9\s._:/=+@-]*`

Required: No

Response Syntax

```
HTTP/1.1 202
Content-type: application/json

{
  "recordArn": "string",
  "status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

recordArn

The ARN of the created registry record

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:aws(-[^\:]+)?:agent-registry:[a-z0-9-]+:[0-9]{12}:registry/[a-zA-Z0-9]{12,16}/record/[a-zA-Z0-9]{12}`

status

The status of the registry record, set to CREATING while the asynchronous workflow is in progress

Type: String

Valid Values: DRAFT | PENDING_APPROVAL | APPROVED | REJECTED | DEPRECATED | CREATING | UPDATING | CREATE_FAILED | UPDATE_FAILED

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The caller is not authorized to perform the requested action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource.

HTTP Status Code: 409

InternalServerErrorException

The request failed due to an unexpected internal error; the caller may retry.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource was not found.

HTTP Status Code: 404

ServiceQuotaExceededException

The request would exceed a service quota.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling; the caller may retry after a delay.

HTTP Status Code: 429

ValidationException

The request failed validation of one or more input fields.

fieldList

The list of input fields that failed validation.

reason

The reason the request failed validation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteRegistry

Deletes a registry. Deletion is asynchronous: the registry transitions to the DELETING status and is removed along with its registry records.

Request Syntax

```
DELETE /registries/registryId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

registryId

The identifier of the registry to delete (ARN or ID)

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: (arn:aws(-[^\:]+)? :agent-registry:[a-z0-9-]+:[0-9]{12}:registry/)?
[a-zA-Z0-9]{12,16}

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 202
Content-type: application/json

{
  "status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

status

Current status of the registry, set to DELETING when deletion is initiated

Type: String

Valid Values: CREATING | READY | UPDATING | CREATE_FAILED | UPDATE_FAILED | DELETING | DELETE_FAILED

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The caller is not authorized to perform the requested action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource.

HTTP Status Code: 409

InternalServerError

The request failed due to an unexpected internal error; the caller may retry.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling; the caller may retry after a delay.

HTTP Status Code: 429

ValidationException

The request failed validation of one or more input fields.

fieldList

The list of input fields that failed validation.

reason

The reason the request failed validation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteRegistryRecord

Deletes a registry record

Request Syntax

```
DELETE /registries/registryId/records/recordId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

recordId

The identifier of the registry record to delete (ARN or ID)

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: (arn:aws(-[^\:]+)? :agent-registry:[a-z0-9-]+:[0-9]{12}:registry/[a-zA-Z0-9]{12,16}/record/)?[a-zA-Z0-9]{12}

Required: Yes

registryId

The identifier of the registry containing the record (ARN or ID)

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: (arn:aws(-[^\:]+)? :agent-registry:[a-z0-9-]+:[0-9]{12}:registry/)?[a-zA-Z0-9]{12,16}

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The caller is not authorized to perform the requested action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource.

HTTP Status Code: 409

InternalServerError

The request failed due to an unexpected internal error; the caller may retry.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling; the caller may retry after a delay.

HTTP Status Code: 429

ValidationException

The request failed validation of one or more input fields.

fieldList

The list of input fields that failed validation.

reason

The reason the request failed validation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetRegistry

Gets a registry by identifier (ARN or ID)

Request Syntax

```
GET /registries/registryId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

registryId

The identifier of the registry to retrieve (ARN or ID)

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: (arn:aws(-[^\:]+)? :agent-registry:[a-z0-9-]+:[0-9]{12}:registry/)?
[a-zA-Z0-9]{12,16}

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "approvalConfiguration": {
    "autoApprovalRules": [ "string" ]
  },
  "createdAt": "string",
  "description": "string",
  "discoveryConfiguration": {
    "authorizerConfiguration": { ... },
```

```
  "authorizerType": "string",
},
"name": "string",
"registryArn": "string",
"registryId": "string",
"status": "string",
"statusReason": "string",
"updatedAt": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

approvalConfiguration

Approval configuration for registry records

Type: [ApprovalConfiguration](#) object

createdAt

The timestamp when the registry was created

Type: Timestamp

description

The description of the registry

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

discoveryConfiguration

Discovery configuration for the registry

Type: [DiscoveryConfiguration](#) object

name

The name of the registry

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_\-\.\/]*`

registryArn

The ARN of the registry

Type: String

Length Constraints: Minimum length of 46. Maximum length of 2048.

Pattern: `arn:aws(-[^:]+)?:agent-registry:[a-z0-9-]+:[0-9]{12}:registry/[a-zA-Z0-9]{12,16}`

registryId

The unique identifier of the registry

Type: String

Length Constraints: Minimum length of 12. Maximum length of 16.

Pattern: `[a-zA-Z0-9]{12,16}`

status

Current status of the registry

Type: String

Valid Values: CREATING | READY | UPDATING | CREATE_FAILED | UPDATE_FAILED | DELETING | DELETE_FAILED

statusReason

The reason for the current status. Typically populated when the status indicates a failure state.

Type: String

updatedAt

The timestamp when the registry was last updated

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The caller is not authorized to perform the requested action.

HTTP Status Code: 403

InternalServerErrorException

The request failed due to an unexpected internal error; the caller may retry.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling; the caller may retry after a delay.

HTTP Status Code: 429

ValidationException

The request failed validation of one or more input fields.

fieldList

The list of input fields that failed validation.

reason

The reason the request failed validation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetRegistryRecord

Retrieves the details of a registry record

Request Syntax

```
GET /registries/registryId/records/recordId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

recordId

The identifier of the registry record to retrieve (ARN or ID)

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: (arn:aws(-[^\:]+)? :agent-registry:[a-z0-9-]+:[0-9]{12}:registry/[a-zA-Z0-9]{12,16}/record/)?[a-zA-Z0-9]{12}

Required: Yes

registryId

The identifier of the registry containing the record (ARN or ID)

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: (arn:aws(-[^\:]+)? :agent-registry:[a-z0-9-]+:[0-9]{12}:registry/)?[a-zA-Z0-9]{12,16}

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "createdAt": "string",
  "description": "string",
  "descriptors": {
    "a2aAgentCard": {
      "data": "string",
      "dataSchemaVersion": "string",
      "source": {
        "fromUrl": {
          "credentialProviderConfigurations": [
            {
              "credentialProvider": { ... },
              "credentialProviderType": "string"
            }
          ],
          "url": "string"
        }
      }
    }
  },
  "agentSkillsDefinition": {
    "additionalData": {
      "skillMd": {
        "data": "string",
        "dataSchemaVersion": "string",
        "source": {
          "fromUrl": {
            "credentialProviderConfigurations": [
              {
                "credentialProvider": { ... },
                "credentialProviderType": "string"
              }
            ],
            "url": "string"
          }
        }
      }
    }
  },
  "data": "string",
  "dataSchemaVersion": "string"
},
  "custom": {
    "data": "string"
  },
}
```

```
"mcpServer": {
  "additionalData": {
    "tools": {
      "data": "string",
      "dataSchemaVersion": "string"
    }
  },
  "data": "string",
  "dataSchemaVersion": "string",
  "source": {
    "fromUrl": {
      "credentialProviderConfigurations": [
        {
          "credentialProvider": { ... },
          "credentialProviderType": "string"
        }
      ],
      "url": "string"
    }
  }
},
"displayName": "string",
"name": "string",
"recordArn": "string",
"recordId": "string",
"recordType": "string",
"recordVersion": "string",
"registryArn": "string",
"status": "string",
"statusReason": "string",
"updatedAt": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

createdAt

The timestamp when the registry record was created.

Type: Timestamp

description

A description of the registry record.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

descriptors

The typed descriptors that define the content of the registry record.

Type: [Descriptors](#) object

displayName

The human-readable display name of the registry record.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

name

The name of the registry record. Names are unique within a registry.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_\-\.\/]*`

recordArn

The Amazon Resource Name (ARN) of the registry record.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:aws(-[^\:]+)?:agent-registry:[a-z0-9-]+:[0-9]{12}:registry/[a-zA-Z0-9]{12,16}/record/[a-zA-Z0-9]{12}`

recordId

The unique identifier of the registry record.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `[a-zA-Z0-9]{12}`

recordType

The type of the registry record, such as MCP, AGENT, SKILL, or CUSTOM.

Type: String

Valid Values: MCP | AGENT | CUSTOM | SKILL

recordVersion

The version identifier of the registry record.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[a-zA-Z0-9.-]+`

registryArn

The Amazon Resource Name (ARN) of the parent registry that owns the record.

Type: String

Length Constraints: Minimum length of 46. Maximum length of 2048.

Pattern: `arn:aws(-[:]+)?:agent-registry:[a-z0-9-]+:[0-9]{12}:registry/[a-zA-Z0-9]{12,16}`

status

The lifecycle status of the registry record.

Type: String

Valid Values: DRAFT | PENDING_APPROVAL | APPROVED | REJECTED | DEPRECATED | CREATING | UPDATING | CREATE_FAILED | UPDATE_FAILED

statusReason

The reason for the current status. Typically populated when the status indicates a failure state.

Type: String

updatedAt

The timestamp when the registry record was last updated.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The caller is not authorized to perform the requested action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource.

HTTP Status Code: 409

InternalServerError

The request failed due to an unexpected internal error; the caller may retry.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling; the caller may retry after a delay.

HTTP Status Code: 429

ValidationException

The request failed validation of one or more input fields.

fieldList

The list of input fields that failed validation.

reason

The reason the request failed validation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListRegistries

Lists the registries in the caller's account and Region, with optional filtering by status and discovery authorizer type

Request Syntax

```
POST /registries-list HTTP/1.1
Content-type: application/json

{
  "filters": [
    {
      "name": "string",
      "values": [ "string" ]
    }
  ],
  "maxResults": number,
  "nextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

filters

Filters to apply to the registry list

Type: Array of [RegistryFilter](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

maxResults

Maximum number of results to return

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

Token for pagination

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: \S*

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "registries": [
    {
      "createdAt": "string",
      "description": "string",
      "discoveryConfiguration": {
        "authorizerConfiguration": { ... },
        "authorizerType": "string"
      },
      "name": "string",
      "registryArn": "string",
      "registryId": "string",
      "status": "string",
      "statusReason": "string",
      "updatedAt": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

Token for next page of results

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: \S*

[registries](#)

List of registry summaries

Type: Array of [RegistrySummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The caller is not authorized to perform the requested action.

HTTP Status Code: 403

InternalServerError

The request failed due to an unexpected internal error; the caller may retry.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling; the caller may retry after a delay.

HTTP Status Code: 429

ValidationException

The request failed validation of one or more input fields.

fieldList

The list of input fields that failed validation.

reason

The reason the request failed validation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListRegistryRecords

Lists the registry records within a registry, with optional filtering by name, status, and record type

Request Syntax

```
POST /registries/registryId/records-list HTTP/1.1
Content-type: application/json
```

```
{
  "filters": [
    {
      "name": "string",
      "values": [ "string" ]
    }
  ],
  "maxResults": number,
  "nextToken": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

registryId

The identifier of the registry to list records from (ARN or ID)

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: (arn:aws(-[^:]+)? :agent-registry:[a-z0-9-]+:[0-9]{12}:registry/)?
[a-zA-Z0-9]{12,16}

Required: Yes

Request Body

The request accepts the following data in JSON format.

filters

Filters to apply to the registry record list

Type: Array of [RegistryRecordFilter](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

[maxResults](#)

Maximum number of records to return

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

[nextToken](#)

Token for pagination

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: \S*

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "nextToken": "string",
  "registryRecords": [
    {
      "createdAt": "string",
      "description": "string",
      "displayName": "string",
      "name": "string",
      "recordArn": "string",
      "recordId": "string",
      "recordType": "string",
```

```
    "recordVersion": "string",  
    "registryArn": "string",  
    "status": "string",  
    "updatedAt": "string"  
  }  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

Token for next page of results

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: \S*

registryRecords

List of registry record summaries

Type: Array of [RegistryRecordSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The caller is not authorized to perform the requested action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource.

HTTP Status Code: 409

InternalServerErrorException

The request failed due to an unexpected internal error; the caller may retry.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling; the caller may retry after a delay.

HTTP Status Code: 429

ValidationException

The request failed validation of one or more input fields.

fieldList

The list of input fields that failed validation.

reason

The reason the request failed validation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Lists the tags associated with the specified AWS Agent Registry resource. Returns the current tag key-value pairs on the resource.

Request Syntax

```
GET /tags/resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the resource to list tags for. Supported resources include registries and registry records.

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tags

The tags currently associated with the resource, as a map of tag keys to tag values.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `[a-zA-Z0-9\s._:/=+@-]*`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `[a-zA-Z0-9\s._:/=+@-]*`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The caller is not authorized to perform the requested action.

HTTP Status Code: 403

InternalServerError

The request failed due to an unexpected internal error; the caller may retry.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling; the caller may retry after a delay.

HTTP Status Code: 429

ValidationException

The request failed validation of one or more input fields.

fieldList

The list of input fields that failed validation.

reason

The reason the request failed validation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

SubmitRegistryRecordForApproval

Submits a DRAFT registry record for approval, moving it into the registry's approval workflow. Depending on the registry's approval configuration, the record is either auto-approved or set to PENDING_APPROVAL for a curator to approve or reject.

Request Syntax

```
POST /registries/registryId/records/recordId/submit-for-approval HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

recordId

The identifier of the registry record to submit for approval (ARN or ID)

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: (arn:aws(-[[^]:]+)? :agent-registry:[a-z0-9-]+:[0-9]{12}:registry/[a-zA-Z0-9]{12,16}/record/)?[a-zA-Z0-9]{12}

Required: Yes

registryId

The identifier of the registry containing the record (ARN or ID)

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: (arn:aws(-[[^]:]+)? :agent-registry:[a-z0-9-]+:[0-9]{12}:registry/)?[a-zA-Z0-9]{12,16}

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 202
Content-type: application/json

{
  "recordArn": "string",
  "recordId": "string",
  "registryArn": "string",
  "status": "string",
  "updatedAt": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

[recordArn](#)

The ARN of the registry record

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:aws(-[^:]+)?:agent-registry:[a-z0-9-]+:[0-9]{12}:registry/[a-zA-Z0-9]{12,16}/record/[a-zA-Z0-9]{12}`

[recordId](#)

The ID of the registry record

Type: String

Length Constraints: Fixed length of 12.

Pattern: `[a-zA-Z0-9]{12}`

[registryArn](#)

The ARN of the registry

Type: String

Length Constraints: Minimum length of 46. Maximum length of 2048.

Pattern: `arn:aws(-[^:]+)?:agent-registry:[a-z0-9-]+:[0-9]{12}:registry/[a-zA-Z0-9]{12,16}`

status

The resulting status of the registry record

Type: String

Valid Values: DRAFT | PENDING_APPROVAL | APPROVED | REJECTED | DEPRECATED | CREATING | UPDATING | CREATE_FAILED | UPDATE_FAILED

updatedAt

The timestamp when the record was last updated

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The caller is not authorized to perform the requested action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource.

HTTP Status Code: 409

InternalServerError

The request failed due to an unexpected internal error; the caller may retry.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling; the caller may retry after a delay.

HTTP Status Code: 429

ValidationException

The request failed validation of one or more input fields.

fieldList

The list of input fields that failed validation.

reason

The reason the request failed validation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Adds or overwrites one or more tags for the specified AWS Agent Registry resource. Tags are key-value pairs that you can use to categorize and manage AWS resources. If a tag with the same key already exists on the resource, the service replaces its value with the value you specify.

Request Syntax

```
POST /tags/resourceArn HTTP/1.1
Content-type: application/json
```

```
{
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the resource to tag. Supported resources include registries and registry records.

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: Yes

Request Body

The request accepts the following data in JSON format.

tags

The tags to apply to the resource, as a map of tag keys to tag values. Tag keys must be unique within the request.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `[a-zA-Z0-9\s._:/=+@-]*`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `[a-zA-Z0-9\s._:/=+@-]*`

Required: Yes

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The caller is not authorized to perform the requested action.

HTTP Status Code: 403

InternalServerError

The request failed due to an unexpected internal error; the caller may retry.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource was not found.

HTTP Status Code: 404

ServiceQuotaExceededException

The request would exceed a service quota.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling; the caller may retry after a delay.

HTTP Status Code: 429

ValidationException

The request failed validation of one or more input fields.

fieldList

The list of input fields that failed validation.

reason

The reason the request failed validation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Removes one or more tags from the specified AWS Agent Registry resource. The operation removes only the tags whose keys you supply; other tags on the resource remain unchanged.

Request Syntax

```
DELETE /tags/resourceArn?tagKeys=tagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the resource to remove tags from. Supported resources include registries and registry records.

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: Yes

tagKeys

The keys of the tags to remove from the resource. Tags with keys not included in this list remain on the resource.

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9\s._:/+=@-]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The caller is not authorized to perform the requested action.

HTTP Status Code: 403

InternalServerError

The request failed due to an unexpected internal error; the caller may retry.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling; the caller may retry after a delay.

HTTP Status Code: 429

ValidationException

The request failed validation of one or more input fields.

fieldList

The list of input fields that failed validation.

reason

The reason the request failed validation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateRegistry

Updates an existing registry. This operation uses PATCH semantics: specify only the fields you want to change, and omit the rest to leave them unchanged. Updates are applied asynchronously and the registry transitions to the UPDATING status while they are processed.

Request Syntax

```
PATCH /registries/registryId HTTP/1.1
Content-type: application/json
```

```
{
  "approvalConfiguration": {
    "optionalValue": {
      "autoApprovalRules": [ "string" ]
    }
  },
  "description": {
    "optionalValue": "string"
  },
  "discoveryConfiguration": {
    "authorizerConfiguration": {
      "optionalValue": { ... }
    }
  },
  "name": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

registryId

The identifier of the registry to update (ARN or ID)

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: (arn:aws(-[:^:]+)? :agent-registry:[a-z0-9-]+:[0-9]{12}:registry/)? [a-zA-Z0-9]{12,16}

Required: Yes

Request Body

The request accepts the following data in JSON format.

approvalConfiguration

The updated approval configuration. The change applies only to records that move to PENDING_APPROVAL after the update; records already in PENDING_APPROVAL are unaffected.

Type: [UpdatedApprovalConfiguration](#) object

Required: No

description

The updated description of the registry

Type: [UpdatedDescription](#) object

Required: No

discoveryConfiguration

The updated discovery configuration. Changing the discovery authorization can break existing consumers that rely on the previous authorization type.

Type: [UpdatedDiscoveryConfiguration](#) object

Required: No

name

The updated name of the registry

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_\-\.\/]*`

Required: No

Response Syntax

```
HTTP/1.1 202
```

Content-type: application/json

```
{
  "approvalConfiguration": {
    "autoApprovalRules": [ "string" ]
  },
  "createdAt": "string",
  "description": "string",
  "discoveryConfiguration": {
    "authorizerConfiguration": { ... },
    "authorizerType": "string"
  },
  "name": "string",
  "registryArn": "string",
  "registryId": "string",
  "status": "string",
  "statusReason": "string",
  "updatedAt": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

approvalConfiguration

Approval configuration for registry records

Type: [ApprovalConfiguration](#) object

createdAt

The timestamp when the registry was created

Type: Timestamp

description

The description of the registry

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

discoveryConfiguration

Discovery configuration for the registry

Type: [DiscoveryConfiguration](#) object

name

The name of the registry

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_\-\.\/]*`

registryArn

The ARN of the registry

Type: String

Length Constraints: Minimum length of 46. Maximum length of 2048.

Pattern: `arn:aws(-[^\:]+)?:agent-registry:[a-z0-9-]+:[0-9]{12}:registry/[a-zA-Z0-9]{12,16}`

registryId

The unique identifier of the registry

Type: String

Length Constraints: Minimum length of 12. Maximum length of 16.

Pattern: `[a-zA-Z0-9]{12,16}`

status

Current status of the registry

Type: String

Valid Values: CREATING | READY | UPDATING | CREATE_FAILED | UPDATE_FAILED | DELETING | DELETE_FAILED

statusReason

The reason for the current status. Typically populated when the status indicates a failure state.

Type: String

updatedAt

The timestamp when the registry was last updated

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The caller is not authorized to perform the requested action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource.

HTTP Status Code: 409

InternalServerError

The request failed due to an unexpected internal error; the caller may retry.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource was not found.

HTTP Status Code: 404

ServiceQuotaExceededException

The request would exceed a service quota.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling; the caller may retry after a delay.

HTTP Status Code: 429

ValidationException

The request failed validation of one or more input fields.

fieldList

The list of input fields that failed validation.

reason

The reason the request failed validation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateRegistryRecord

Updates a registry record. The update is asynchronous: the record is returned with the UPDATING status while it is processed. Fields that use update wrappers follow PATCH semantics: omit the field to leave it unchanged.

Request Syntax

```
PATCH /registries/registryId/records/recordId HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "description": {
    "optionalValue": "string"
  },
  "descriptors": {
    "optionalValue": {
      "a2aAgentCard": {
        "optionalValue": {
          "data": {
            "optionalValue": "string"
          },
          "dataSchemaVersion": {
            "optionalValue": "string"
          },
          "source": {
            "optionalValue": {
              "fromUrl": {
                "credentialProviderConfigurations": [
                  {
                    "credentialProvider": { ... },
                    "credentialProviderType": "string"
                  }
                ],
                "url": "string"
              }
            }
          }
        }
      }
    }
  },
  "agentSkillsDefinition": {
    "optionalValue": {
```

```

    "additionalData": {
      "optionalValue": {
        "skillMd": {
          "optionalValue": {
            "data": {
              "optionalValue": "string"
            },
            "dataSchemaVersion": {
              "optionalValue": "string"
            },
            "source": {
              "optionalValue": {
                "fromUrl": {
                  "credentialProviderConfigurations": [
                    {
                      "credentialProvider": { ... },
                      "credentialProviderType": "string"
                    }
                  ],
                  "url": "string"
                }
              }
            }
          }
        }
      }
    },
    "data": {
      "optionalValue": "string"
    },
    "dataSchemaVersion": {
      "optionalValue": "string"
    }
  },
  "custom": {
    "optionalValue": {
      "data": {
        "optionalValue": "string"
      }
    }
  },
  "mcpServer": {
    "optionalValue": {

```

```

    "additionalData": {
      "optionalValue": {
        "tools": {
          "optionalValue": {
            "data": {
              "optionalValue": "string"
            },
            "dataSchemaVersion": {
              "optionalValue": "string"
            }
          }
        }
      }
    },
    "data": {
      "optionalValue": "string"
    },
    "dataSchemaVersion": {
      "optionalValue": "string"
    },
    "source": {
      "optionalValue": {
        "fromUrl": {
          "credentialProviderConfigurations": [
            {
              "credentialProvider": { ... },
              "credentialProviderType": "string"
            }
          ],
          "url": "string"
        }
      }
    },
    "displayName": {
      "optionalValue": "string"
    },
    "name": "string",
    "recordType": "string",
    "recordVersion": "string",
    "triggerSynchronization": boolean

```

```
}
```

URI Request Parameters

The request uses the following URI parameters.

[recordId](#)

The identifier of the registry record to update (ARN or ID)

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `(arn:aws(-[^\:]+)? :agent-registry:[a-z0-9-]+:[0-9]{12}:registry/[a-zA-Z0-9]{12,16}/record/)?[a-zA-Z0-9]{12}`

Required: Yes

[registryId](#)

The identifier of the registry containing the record (ARN or ID)

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `(arn:aws(-[^\:]+)? :agent-registry:[a-z0-9-]+:[0-9]{12}:registry/)?[a-zA-Z0-9]{12,16}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

[description](#)

The updated description of the registry record. Omit to leave the description unchanged; provide an empty wrapper to unset it.

Type: [UpdatedDescription](#) object

Required: No

descriptors

The updated typed descriptor content for the registry record. Omit to leave the descriptors unchanged.

Type: [UpdatedDescriptors](#) object

Required: No

displayName

The updated display name of the registry record. Omit to leave the display name unchanged; provide an empty wrapper to unset it.

Type: [UpdatedDisplayName](#) object

Required: No

name

The updated name of the registry record. Omit to leave the name unchanged.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_-\.\✓]*`

Required: No

recordType

The updated type of the registry record. Omit to leave the record type unchanged.

Type: String

Valid Values: MCP | AGENT | CUSTOM | SKILL

Required: No

recordVersion

The updated version of the registry record. Omit to leave the version unchanged.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9.-]+

Required: No

triggerSynchronization

Whether to trigger synchronization of the record's descriptor content from its source

Type: Boolean

Required: No

Response Syntax

HTTP/1.1 202

Content-type: application/json

```
{
  "createdAt": "string",
  "description": "string",
  "descriptors": {
    "a2aAgentCard": {
      "data": "string",
      "dataSchemaVersion": "string",
      "source": {
        "fromUrl": {
          "credentialProviderConfigurations": [
            {
              "credentialProvider": { ... },
              "credentialProviderType": "string"
            }
          ],
          "url": "string"
        }
      }
    },
    "agentSkillsDefinition": {
      "additionalData": {
        "skillMd": {
          "data": "string",
          "dataSchemaVersion": "string",
          "source": {
            "fromUrl": {
              "credentialProviderConfigurations": [
```

```

        {
            "credentialProvider": { ... },
            "credentialProviderType": "string"
        }
    ],
    "url": "string"
}

}

},
"data": "string",
"dataSchemaVersion": "string"
},
"custom": {
    "data": "string"
},
"mcpServer": {
    "additionalData": {
        "tools": {
            "data": "string",
            "dataSchemaVersion": "string"
        }
    },
    "data": "string",
    "dataSchemaVersion": "string",
    "source": {
        "fromUrl": {
            "credentialProviderConfigurations": [
                {
                    "credentialProvider": { ... },
                    "credentialProviderType": "string"
                }
            ],
            "url": "string"
        }
    }
}

},
"displayName": "string",
"name": "string",
"recordArn": "string",
"recordId": "string",
"recordType": "string",
"recordVersion": "string",

```

```
"registryArn": "string",  
"status": "string",  
"statusReason": "string",  
"updatedAt": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

createdAt

The timestamp when the registry record was created.

Type: Timestamp

description

A description of the registry record.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

descriptors

The typed descriptors that define the content of the registry record.

Type: [Descriptors](#) object

displayName

The human-readable display name of the registry record.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

name

The name of the registry record. Names are unique within a registry.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_\-\.\/]*`

recordArn

The Amazon Resource Name (ARN) of the registry record.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:aws(-[^\:]+)?:agent-registry:[a-z0-9-]+:[0-9]{12}:registry/[a-zA-Z0-9]{12,16}/record/[a-zA-Z0-9]{12}`

recordId

The unique identifier of the registry record.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `[a-zA-Z0-9]{12}`

recordType

The type of the registry record, such as MCP, AGENT, SKILL, or CUSTOM.

Type: String

Valid Values: MCP | AGENT | CUSTOM | SKILL

recordVersion

The version identifier of the registry record.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[a-zA-Z0-9.-]+`

registryArn

The Amazon Resource Name (ARN) of the parent registry that owns the record.

Type: String

Length Constraints: Minimum length of 46. Maximum length of 2048.

Pattern: `arn:aws(-[^:]+)?:agent-registry:[a-z0-9-]+:[0-9]{12}:registry/[a-zA-Z0-9]{12,16}`

status

The lifecycle status of the registry record.

Type: String

Valid Values: DRAFT | PENDING_APPROVAL | APPROVED | REJECTED | DEPRECATED | CREATING | UPDATING | CREATE_FAILED | UPDATE_FAILED

statusReason

The reason for the current status. Typically populated when the status indicates a failure state.

Type: String

updatedAt

The timestamp when the registry record was last updated.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The caller is not authorized to perform the requested action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource.

HTTP Status Code: 409

InternalServerError

The request failed due to an unexpected internal error; the caller may retry.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling; the caller may retry after a delay.

HTTP Status Code: 429

ValidationException

The request failed validation of one or more input fields.

fieldList

The list of input fields that failed validation.

reason

The reason the request failed validation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

UpdateRegistryRecordStatus

Updates the status of a registry record as part of the registry's curation workflow, for example to approve or reject a record that is pending approval, or to deprecate an approved record so that it is no longer discoverable

Request Syntax

```
PATCH /registries/registryId/records/recordId/status HTTP/1.1
Content-type: application/json
```

```
{
  "status": "string",
  "statusReason": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

recordId

The identifier of the registry record to update the status of (ARN or ID)

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: (arn:aws(-[[^]:]+)? :agent-registry:[a-z0-9-]+:[0-9]{12}:registry/[a-zA-Z0-9]{12,16}/record/)?[a-zA-Z0-9]{12}

Required: Yes

registryId

The identifier of the registry containing the record (ARN or ID)

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: (arn:aws(-[[^]:]+)? :agent-registry:[a-z0-9-]+:[0-9]{12}:registry/)?[a-zA-Z0-9]{12,16}

Required: Yes

Request Body

The request accepts the following data in JSON format.

status

The target status for the registry record

Type: String

Valid Values: DRAFT | PENDING_APPROVAL | APPROVED | REJECTED | DEPRECATED | CREATING | UPDATING | CREATE_FAILED | UPDATE_FAILED

Required: Yes

statusReason

The reason for the status change, for example why the record was approved, rejected, or deprecated

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Required: Yes

Response Syntax

```
HTTP/1.1 202
Content-type: application/json
```

```
{
  "recordArn": "string",
  "recordId": "string",
  "registryArn": "string",
  "status": "string",
  "statusReason": "string",
  "updatedAt": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

recordArn

The ARN of the registry record

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:aws(-[^\:]+)?:agent-registry:[a-z0-9-]+:[0-9]{12}:registry/[a-zA-Z0-9]{12,16}/record/[a-zA-Z0-9]{12}`

recordId

The ID of the registry record

Type: String

Length Constraints: Fixed length of 12.

Pattern: `[a-zA-Z0-9]{12}`

registryArn

The ARN of the registry

Type: String

Length Constraints: Minimum length of 46. Maximum length of 2048.

Pattern: `arn:aws(-[^\:]+)?:agent-registry:[a-z0-9-]+:[0-9]{12}:registry/[a-zA-Z0-9]{12,16}`

status

The resulting status of the registry record

Type: String

Valid Values: DRAFT | PENDING_APPROVAL | APPROVED | REJECTED | DEPRECATED | CREATING | UPDATING | CREATE_FAILED | UPDATE_FAILED

statusReason

The reason for the status change

Type: String

updatedAt

The timestamp when the record was last updated

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The caller is not authorized to perform the requested action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource.

HTTP Status Code: 409

InternalServerError

The request failed due to an unexpected internal error; the caller may retry.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling; the caller may retry after a delay.

HTTP Status Code: 429

ValidationException

The request failed validation of one or more input fields.

fieldList

The list of input fields that failed validation.

reason

The reason the request failed validation.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The Agent Registry Control API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [A2aAgentCardDescriptor](#)
- [AgentSkillsAdditionalData](#)
- [AgentSkillsDefinitionDescriptor](#)
- [AgentSkillsMdDescriptor](#)
- [ApprovalConfiguration](#)
- [AuthorizerConfiguration](#)
- [AuthorizingClaimMatchValueType](#)
- [ClaimMatchValueType](#)
- [CustomClaimValidationType](#)
- [CustomDescriptor](#)
- [CustomJWTAuthorizerConfiguration](#)
- [Descriptors](#)
- [DescriptorSource](#)
- [DescriptorSourceFromUrl](#)
- [DiscoveryConfiguration](#)
- [ManagedVpcResource](#)
- [McpServerAdditionalData](#)
- [McpServerDescriptor](#)
- [McpToolsDescriptor](#)
- [PrivateEndpoint](#)

- [PrivateEndpointOverride](#)
- [RegistryFilter](#)
- [RegistryRecordCredentialProviderConfiguration](#)
- [RegistryRecordCredentialProviderUnion](#)
- [RegistryRecordFilter](#)
- [RegistryRecordIamCredentialProvider](#)
- [RegistryRecordOAuthCredentialProvider](#)
- [RegistryRecordSummary](#)
- [RegistrySummary](#)
- [SelfManagedLatticeResource](#)
- [UpdatedA2aAgentCardDescriptor](#)
- [UpdatedA2aAgentCardDescriptorFields](#)
- [UpdatedAgentSkillsAdditionalData](#)
- [UpdatedAgentSkillsAdditionalDataFields](#)
- [UpdatedAgentSkillsDefinitionDescriptor](#)
- [UpdatedAgentSkillsDefinitionDescriptorFields](#)
- [UpdatedAgentSkillsMdDescriptor](#)
- [UpdatedAgentSkillsMdDescriptorFields](#)
- [UpdatedApprovalConfiguration](#)
- [UpdatedAuthorizerConfiguration](#)
- [UpdatedCustomDescriptor](#)
- [UpdatedCustomDescriptorFields](#)
- [UpdatedDataSchemaVersion](#)
- [UpdatedDescription](#)
- [UpdatedDescriptorData](#)
- [UpdatedDescriptors](#)
- [UpdatedDescriptorsFields](#)
- [UpdatedDescriptorSource](#)
- [UpdatedDiscoveryConfiguration](#)
- [UpdatedDisplayName](#)

- [UpdatedMcpServerAdditionalData](#)
- [UpdatedMcpServerAdditionalDataFields](#)
- [UpdatedMcpServerDescriptor](#)
- [UpdatedMcpServerDescriptorFields](#)
- [UpdatedMcpToolsDescriptor](#)
- [UpdatedMcpToolsDescriptorFields](#)
- [ValidationExceptionField](#)

A2aAgentCardDescriptor

Descriptor that defines the content of an A2A (Agent-to-Agent) agent card registry record. The content is validated against the A2A protocol schema.

Contents

data

The A2A agent card content, serialized as descriptor payload data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 102400.

Required: No

dataSchemaVersion

The schema version of the descriptor payload.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

source

The optional source configuration used to synchronize the A2A agent card descriptor content.

Type: [DescriptorSource](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

AgentSkillsAdditionalData

Additional data associated with an agent skills definition descriptor.

Contents

skillMd

The markdown skill content associated with an agent skills definition.

Type: [AgentSkillsMdDescriptor](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AgentSkillsDefinitionDescriptor

Descriptor that defines an agent skills registry record and its associated content.

Contents

additionalData

Additional data associated with the agent skills definition descriptor.

Type: [AgentSkillsAdditionalData](#) object

Required: No

data

The agent skills definition content, serialized as descriptor payload data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 102400.

Required: No

dataSchemaVersion

The schema version of the descriptor payload.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AgentSkillsMdDescriptor

Markdown-format descriptor containing an agent skills document.

Contents

data

The agent skills markdown content, serialized as descriptor payload data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 102400.

Required: No

dataSchemaVersion

The schema version of the descriptor payload.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

source

The optional source configuration used to synchronize the agent skills markdown content.

Type: [DescriptorSource](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ApprovalConfiguration

Configuration for the registry's record approval workflow. Controls whether records submitted for approval require manual review before they become approved and discoverable, or are auto-approved. When no auto-approval rules are configured, submitted records require manual review.

Contents

autoApprovalRules

The rules that determine which registry records are automatically approved on submission. When omitted or empty, submitted records require manual review.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Valid Values: APPROVE_ALL

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AuthorizerConfiguration

The authorizer configuration for a registry. Exactly one member is set.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

customJWTAuthorizer

Configuration for a custom JWT authorizer.

Type: [CustomJWTAuthorizerConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AuthorizingClaimMatchValueType

The value and match operator used to authorize a claim during JWT validation.

Contents

claimMatchOperator

The operator used to compare the claim value against the expected value.

Type: String

Valid Values: EQUALS | CONTAINS | CONTAINS_ANY

Required: Yes

claimMatchValue

The expected value or values that the claim is compared against.

Type: [ClaimMatchValueType](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ClaimMatchValueType

The expected value used to match a claim. Exactly one member is set.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

matchValueString

A single string value to match the claim against.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [A-Za-z0-9_./-]+

Required: No

matchValueStringList

A list of string values to match the claim against.

Type: Array of strings

Array Members: Minimum number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [A-Za-z0-9_./-]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CustomClaimValidationType

A validation rule applied to a single claim of an inbound JWT.

Contents

authorizingClaimMatchValue

The value and match operator used to authorize the claim.

Type: [AuthorizingClaimMatchValueType](#) object

Required: Yes

inboundTokenClaimName

The name of the claim in the inbound token to validate.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [A-Za-z0-9_.-:]+

Required: Yes

inboundTokenClaimValueType

The value type of the claim in the inbound token, either a string or an array of strings.

Type: String

Valid Values: STRING | STRING_ARRAY

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

CustomDescriptor

Custom descriptor for user-defined content

Contents

data

The custom descriptor content, serialized as descriptor payload data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 102400.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CustomJWTAuthorizerConfiguration

Configuration for a custom JWT authorizer that validates inbound bearer tokens against an OpenID Connect identity provider.

Contents

discoveryUrl

The OpenID Connect discovery URL used to retrieve the identity provider's metadata and signing keys.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `.+/\..well-known/openid-configuration`

Required: Yes

allowedAudience

The audience values accepted during JWT validation. A token is rejected if none of its audience claims match.

Type: Array of strings

Array Members: Minimum number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

allowedClients

The client identifiers accepted during JWT validation. A token is rejected if it was not issued to one of these clients.

Type: Array of strings

Array Members: Minimum number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

allowedScopes

The scopes accepted during JWT validation. A token is rejected if it does not carry one of these scopes.

Type: Array of strings

Array Members: Minimum number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[\x21\x23-\x5B\x5D-\x7E]+`

Required: No

customClaims

Additional custom claim validations applied to the inbound JWT.

Type: Array of [CustomClaimValidationType](#) objects

Array Members: Minimum number of 1 item.

Required: No

privateEndpoint

The private endpoint used to reach the identity provider's discovery URL over a private network path.

Type: [PrivateEndpoint](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

privateEndpointOverrides

Per-domain private endpoint overrides that route specific identity provider domains through distinct private endpoints.

Type: Array of [PrivateEndpointOverride](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Descriptors

The typed set of descriptors for a registry record. Exactly one descriptor field is populated based on the record type.

Contents

a2aAgentCard

The A2A agent card descriptor, populated when the record type is AGENT.

Type: [A2aAgentCardDescriptor](#) object

Required: No

agentSkillsDefinition

The agent skills definition descriptor, populated when the record type is SKILL.

Type: [AgentSkillsDefinitionDescriptor](#) object

Required: No

custom

The custom descriptor, populated when the record type is CUSTOM.

Type: [CustomDescriptor](#) object

Required: No

mcpServer

The MCP server descriptor, populated when the record type is MCP.

Type: [McpServerDescriptor](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DescriptorSource

The source configuration that defines where descriptor content is retrieved from.

Contents

fromUrl

URL-based descriptor source, populated when descriptor content is synchronized from a URL.

Type: [DescriptorSourceFromUrl](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DescriptorSourceFromUrl

URL-based descriptor source configuration, with credential provider configurations for authenticated URL retrieval.

Contents

url

The URL from which the descriptor content is retrieved.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `https://.*`

Required: Yes

credentialProviderConfigurations

The credential providers used to authenticate when fetching descriptor content from the source URL.

Type: Array of [RegistryRecordCredentialProviderConfiguration](#) objects

Array Members: Minimum number of 0 items. Maximum number of 1 item.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DiscoveryConfiguration

Discovery configuration for the registry. Controls how consumers are authorized to search the registry and invoke its MCP endpoint.

Contents

authorizerConfiguration

The authorizer configuration for the registry. Required when `authorizerType` is `CUSTOM_JWT`.

Type: [AuthorizerConfiguration](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

authorizerType

The type of authorizer that controls how consumers access the registry's search and MCP invoke operations.

Type: String

Valid Values: `CUSTOM_JWT` | `AWS_IAM`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ManagedVpcResource

A service-managed private endpoint provisioned within a customer VPC.

Contents

endpointIpAddressType

The IP address type used by the private endpoint, either IPV4 or IPV6.

Type: String

Valid Values: IPV4 | IPV6

Required: Yes

subnetIds

The identifiers of the subnets in which the private endpoint network interfaces are placed.

Type: Array of strings

Length Constraints: Minimum length of 15. Maximum length of 24.

Pattern: subnet-[0-9a-zA-Z]{8,17}

Required: Yes

vpcIdentifier

The identifier of the VPC in which the private endpoint is provisioned.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 48.

Pattern: vpc-(((0-9a-z){8})|((0-9a-z){17}))

Required: Yes

routingDomain

The routing domain used to resolve traffic through the private endpoint.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

Required: No

securityGroupIds

The identifiers of the security groups associated with the private endpoint network interfaces.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Length Constraints: Minimum length of 10. Maximum length of 48.

Pattern: `sg-(([\0-9a-z]{8})|([\0-9a-z]{17}))`

Required: No

tags

The tags applied to the service-managed VPC resource.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `[a-zA-Z0-9\s._:/+=@-]*`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `[a-zA-Z0-9\s._:/+=@-]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

McpServerAdditionalData

Additional data for an MCP server descriptor

Contents

tools

The MCP tools descriptor that defines the tools exposed by the MCP server.

Type: [McpToolsDescriptor](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

McpServerDescriptor

Descriptor that defines the content of an MCP (Model Context Protocol) server registry record, including the server definition and its tool definitions. The content is validated against the MCP protocol schema.

Contents

additionalData

Additional data associated with the MCP server descriptor, such as tool definitions.

Type: [McpServerAdditionalData](#) object

Required: No

data

The MCP server descriptor content, serialized as descriptor payload data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 102400.

Required: No

dataSchemaVersion

The schema version of the descriptor payload.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

source

The optional source configuration used to synchronize the MCP server descriptor content.

Type: [DescriptorSource](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

McpToolsDescriptor

MCP tools descriptor containing tool definitions

Contents

data

The MCP tools descriptor content, serialized as descriptor payload data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 102400.

Required: No

dataSchemaVersion

The schema version of the descriptor payload.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PrivateEndpoint

A private network endpoint used to reach a resource over a private path. Exactly one member is set.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

managedVpcResource

A private endpoint backed by a service-managed VPC resource.

Type: [ManagedVpcResource](#) object

Required: No

selfManagedLatticeResource

A private endpoint backed by a self-managed VPC Lattice resource configuration.

Type: [SelfManagedLatticeResource](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PrivateEndpointOverride

A mapping of a domain to the private endpoint used to reach it.

Contents

domain

The domain name to which this private endpoint override applies.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 253.

Required: Yes

privateEndpoint

The private endpoint used to reach the specified domain.

Type: [PrivateEndpoint](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RegistryFilter

A single filter applied to a ListRegistries request.

Contents

name

The attribute to filter on

Type: String

Valid Values: `status` | `discoveryConfiguration.authorizerType`

Required: Yes

values

The values to match for the attribute

Type: Array of strings

Array Members: Fixed number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RegistryRecordCredentialProviderConfiguration

A credential provider configuration that specifies how to authenticate when fetching descriptor content from a registry record's source URL.

Contents

credentialProvider

The credential provider details corresponding to the specified credential provider type.

Type: [RegistryRecordCredentialProviderUnion](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

credentialProviderType

The type of credential provider.

Type: String

Valid Values: OAUTH | IAM

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RegistryRecordCredentialProviderUnion

The credential provider details for a registry record. Exactly one member is populated, matching the configured credential provider type.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

iamCredentialProvider

The IAM role credential provider details.

Type: [RegistryRecordIamCredentialProvider](#) object

Required: No

oauthCredentialProvider

The OAuth 2.0 credential provider details.

Type: [RegistryRecordOAuthCredentialProvider](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RegistryRecordFilter

A single filter applied to a ListRegistryRecords request.

Contents

name

The attribute to filter on

Type: String

Valid Values: `name` | `status` | `recordType`

Required: Yes

values

The values to match for the attribute

Type: Array of strings

Array Members: Fixed number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RegistryRecordIamCredentialProvider

The configuration for an IAM role credential provider that signs requests to a registry record's source with AWS Signature Version 4 (SigV4).

Contents

region

The AWS Region to use for request signing. If not specified, the Region is derived from the source URL hostname, falling back to the Region of the registry.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-z0-9-]+`

Required: No

roleArn

The Amazon Resource Name (ARN) of the IAM role to assume for request signing.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws(-[^\:]+)?:iam:[0-9]{12}:role/.+`

Required: No

service

The service name to use for request signing, such as `execute-api`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_-]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RegistryRecordOAuthCredentialProvider

The configuration for an OAuth 2.0 credential provider that authenticates requests to a registry record's source.

Contents

providerArn

The Amazon Resource Name (ARN) of the OAuth 2.0 credential provider resource in Amazon Bedrock AgentCore Identity.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:aws(-[^\:]+)?:bedrock-agentcore:[a-z0-9-]+:[0-9]{12}:\.*`

Required: Yes

customParameters

Additional parameters to include in the OAuth 2.0 token request.

Type: String to string map

Required: No

grantType

The OAuth 2.0 grant type used to obtain access tokens.

Type: String

Valid Values: CLIENT_CREDENTIALS

Required: No

scopes

The OAuth 2.0 scopes to request when obtaining access tokens.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RegistryRecordSummary

A summary of a registry record returned by list operations. Contains identifying and lifecycle fields but omits descriptor content.

Contents

createdAt

The timestamp when the registry record was created.

Type: Timestamp

Required: Yes

name

The name of the registry record. Names are unique within a registry.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_-\.\|]*`

Required: Yes

recordArn

The Amazon Resource Name (ARN) of the registry record.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:aws(-[^\:]+)?:agent-registry:[a-z0-9-]+:[0-9]{12}:registry/[a-zA-Z0-9]{12,16}/record/[a-zA-Z0-9]{12}`

Required: Yes

recordId

The unique identifier of the registry record.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `[a-zA-Z0-9]{12}`

Required: Yes

recordType

The type of the registry record, such as MCP, AGENT, SKILL, or CUSTOM.

Type: String

Valid Values: MCP | AGENT | CUSTOM | SKILL

Required: Yes

recordVersion

The version identifier of the registry record.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[a-zA-Z0-9.-]+`

Required: Yes

registryArn

The Amazon Resource Name (ARN) of the parent registry that owns the record.

Type: String

Length Constraints: Minimum length of 46. Maximum length of 2048.

Pattern: `arn:aws(-[^\:]+)?:agent-registry:[a-z0-9-]+:[0-9]{12}:registry/[a-zA-Z0-9]{12,16}`

Required: Yes

status

The lifecycle status of the registry record.

Type: String

Valid Values: DRAFT | PENDING_APPROVAL | APPROVED | REJECTED | DEPRECATED | CREATING | UPDATING | CREATE_FAILED | UPDATE_FAILED

Required: Yes

updatedAt

The timestamp when the registry record was last updated.

Type: Timestamp

Required: Yes

description

A description of the registry record.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

displayName

The human-readable display name of the registry record.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RegistrySummary

Registry summary for list operations

Contents

createdAt

The timestamp when the registry was created

Type: Timestamp

Required: Yes

name

Registry name

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_\-\.\/]*`

Required: Yes

registryArn

Registry Amazon Resource Name

Type: String

Length Constraints: Minimum length of 46. Maximum length of 2048.

Pattern: `arn:aws(-[^\:]+)?:agent-registry:[a-z0-9-]+:[0-9]{12}:registry/[a-zA-Z0-9]{12,16}`

Required: Yes

registryId

Unique registry identifier

Type: String

Length Constraints: Minimum length of 12. Maximum length of 16.

Pattern: `[a-zA-Z0-9]{12,16}`

Required: Yes

status

Current status of the registry

Type: String

Valid Values: CREATING | READY | UPDATING | CREATE_FAILED | UPDATE_FAILED | DELETING | DELETE_FAILED

Required: Yes

updatedAt

The timestamp when the registry was last updated

Type: Timestamp

Required: Yes

description

Registry description

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

discoveryConfiguration

Discovery configuration for the registry

Type: [DiscoveryConfiguration](#) object

Required: No

statusReason

The reason for the current status. Typically populated when the status indicates a failure state.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SelfManagedLatticeResource

A self-managed private endpoint backed by a VPC Lattice resource configuration. Exactly one member is set.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

resourceConfigurationIdentifier

The identifier of the VPC Lattice resource configuration, specified as a resource configuration ID or ARN.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `((rcfg-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:resourceconfiguration/rcfg-[0-9a-z]{17}))`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdatedA2aAgentCardDescriptor

The A2A agent card descriptor patch wrapper. Omit to leave the descriptor unchanged; supply an empty object to remove it; supply optionalValue to patch its fields.

Contents

optionalValue

The value to set for this field. Omit the wrapper to leave the field unchanged.

Type: [UpdatedA2aAgentCardDescriptorFields](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdatedA2aAgentCardDescriptorFields

The set of A2A agent card descriptor fields that can be individually updated.

Contents

data

The patch for the descriptor's data field.

Type: [UpdatedDescriptorData](#) object

Required: No

dataSchemaVersion

The patch for the descriptor's data schema version field.

Type: [UpdatedDataSchemaVersion](#) object

Required: No

source

The patch for the descriptor's source field.

Type: [UpdatedDescriptorSource](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdatedAgentSkillsAdditionalData

The agent skills additional-data patch wrapper. Omit to leave the additional data unchanged; supply an empty object to remove it; supply optionalValue to patch its fields.

Contents

optionalValue

The value to set for this field. Omit the wrapper to leave the field unchanged.

Type: [UpdatedAgentSkillsAdditionalDataFields](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdatedAgentSkillsAdditionalDataFields

The set of agent skills additional-data fields that can be individually updated.

Contents

skillMd

The patch for the agent skills markdown descriptor field.

Type: [UpdatedAgentSkillsMdDescriptor](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdatedAgentSkillsDefinitionDescriptor

The agent skills definition descriptor patch wrapper. Omit to leave the descriptor unchanged; supply an empty object to remove it; supply optionalValue to patch its fields.

Contents

optionalValue

The value to set for this field. Omit the wrapper to leave the field unchanged.

Type: [UpdatedAgentSkillsDefinitionDescriptorFields](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdatedAgentSkillsDefinitionDescriptorFields

The set of agent skills definition descriptor fields that can be individually updated.

Contents

additionalData

The patch for the descriptor's additional data field.

Type: [UpdatedAgentSkillsAdditionalData](#) object

Required: No

data

The patch for the descriptor's data field.

Type: [UpdatedDescriptorData](#) object

Required: No

dataSchemaVersion

The patch for the descriptor's data schema version field.

Type: [UpdatedDataSchemaVersion](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdatedAgentSkillsMdDescriptor

The agent skills markdown descriptor patch wrapper. Omit to leave the descriptor unchanged; supply an empty object to remove it; supply optionalValue to patch its fields.

Contents

optionalValue

The value to set for this field. Omit the wrapper to leave the field unchanged.

Type: [UpdatedAgentSkillsMdDescriptorFields](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdatedAgentSkillsMdDescriptorFields

The set of agent skills markdown descriptor fields that can be individually updated.

Contents

data

The patch for the descriptor's data field.

Type: [UpdatedDescriptorData](#) object

Required: No

dataSchemaVersion

The patch for the descriptor's data schema version field.

Type: [UpdatedDataSchemaVersion](#) object

Required: No

source

The patch for the descriptor's source field.

Type: [UpdatedDescriptorSource](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdatedApprovalConfiguration

A wrapper for updating the approval configuration of a registry. Include this wrapper to replace the approval configuration with the specified value; omit it to leave the approval configuration unchanged.

Contents

optionalValue

The value to set for this field. Omit the wrapper to leave the field unchanged.

Type: [ApprovalConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdatedAuthorizerConfiguration

Wrapper for updating an optional authorizer configuration with PATCH semantics.

Contents

optionalValue

The new authorizer configuration to set. Omit to leave the existing configuration unchanged.

Type: [AuthorizerConfiguration](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdatedCustomDescriptor

The custom descriptor patch wrapper. Omit to leave the descriptor unchanged; supply an empty object to remove it; supply optionalValue to patch its fields.

Contents

optionalValue

The value to set for this field. Omit the wrapper to leave the field unchanged.

Type: [UpdatedCustomDescriptorFields](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdatedCustomDescriptorFields

The set of custom descriptor fields that can be individually updated.

Contents

data

The patch for the descriptor's data field.

Type: [UpdatedDescriptorData](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdatedDataSchemaVersion

Leaf patch wrapper for a descriptor's data schema version. Omit to leave unchanged; supply an empty object to unset; supply optionalValue to set.

Contents

optionalValue

The value to set for this field. Omit the wrapper to leave the field unchanged.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdatedDescription

Wrapper for updating an optional Description field with PATCH semantics

Contents

optionalValue

The value to set for this field. Omit the wrapper to leave the field unchanged.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdatedDescriptorData

Leaf patch wrapper for descriptor data. Omit to leave unchanged; supply an empty object to unset; supply optionalValue to set.

Contents

optionalValue

The value to set for this field. Omit the wrapper to leave the field unchanged.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 102400.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdatedDescriptors

The top-level descriptors patch wrapper used in UpdateRegistryRecord. Omit to leave the current descriptors unchanged; supply an empty object to clear them; supply optionalValue to apply a per-field patch.

Contents

optionalValue

The value to set for this field. Omit the wrapper to leave the field unchanged.

Type: [UpdatedDescriptorsFields](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdatedDescriptorsFields

The patchable descriptor fields applied during an UpdateRegistryRecord call. Each field is independently patchable.

Contents

a2aAgentCard

The patch for the A2A agent card descriptor.

Type: [UpdatedA2aAgentCardDescriptor](#) object

Required: No

agentSkillsDefinition

The patch for the agent skills definition descriptor.

Type: [UpdatedAgentSkillsDefinitionDescriptor](#) object

Required: No

custom

The patch for the custom descriptor.

Type: [UpdatedCustomDescriptor](#) object

Required: No

mcpServer

The patch for the MCP server descriptor.

Type: [UpdatedMcpServerDescriptor](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdatedDescriptorSource

Leaf patch wrapper for a descriptor's source configuration. Omit to leave unchanged; supply an empty object to unset; supply optionalValue to set.

Contents

optionalValue

The value to set for this field. Omit the wrapper to leave the field unchanged.

Type: [DescriptorSource](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdatedDiscoveryConfiguration

The discovery configuration fields to update on a registry. Omit this structure to leave the discovery configuration unchanged.

Contents

authorizerConfiguration

Authorization configuration for the registry, with PATCH semantics

Type: [UpdatedAuthorizerConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdatedDisplayName

Leaf patch wrapper for a registry record's display name. Omit to leave unchanged; supply an empty object to unset; supply optionalValue to set.

Contents

optionalValue

The value to set for this field. Omit the wrapper to leave the field unchanged.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdatedMcpServerAdditionalData

The MCP server additional-data patch wrapper. Omit to leave the additional data unchanged; supply an empty object to remove it; supply optionalValue to patch its fields.

Contents

optionalValue

The value to set for this field. Omit the wrapper to leave the field unchanged.

Type: [UpdatedMcpServerAdditionalDataFields](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdatedMcpServerAdditionalDataFields

The set of MCP server additional-data fields that can be individually updated.

Contents

tools

The patch for the MCP tools descriptor field.

Type: [UpdatedMcpToolsDescriptor](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdatedMcpServerDescriptor

The MCP server descriptor patch wrapper. Omit to leave the descriptor unchanged; supply an empty object to remove it; supply optionalValue to patch its fields.

Contents

optionalValue

The value to set for this field. Omit the wrapper to leave the field unchanged.

Type: [UpdatedMcpServerDescriptorFields](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdatedMcpServerDescriptorFields

The set of MCP server descriptor fields that can be individually updated.

Contents

additionalData

The patch for the descriptor's additional data field.

Type: [UpdatedMcpServerAdditionalData](#) object

Required: No

data

The patch for the descriptor's data field.

Type: [UpdatedDescriptorData](#) object

Required: No

dataSchemaVersion

The patch for the descriptor's data schema version field.

Type: [UpdatedDataSchemaVersion](#) object

Required: No

source

The patch for the descriptor's source field.

Type: [UpdatedDescriptorSource](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdatedMcpToolsDescriptor

The MCP tools descriptor patch wrapper. Omit to leave the tools descriptor unchanged; supply an empty object to remove it; supply optionalValue to patch its fields.

Contents

optionalValue

The value to set for this field. Omit the wrapper to leave the field unchanged.

Type: [UpdatedMcpToolsDescriptorFields](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdatedMcpToolsDescriptorFields

The set of MCP tools descriptor fields that can be individually updated.

Contents

data

The patch for the descriptor's data field.

Type: [UpdatedDescriptorData](#) object

Required: No

dataSchemaVersion

The patch for the descriptor's data schema version field.

Type: [UpdatedDataSchemaVersion](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ValidationExceptionField

Describes a single input field that failed validation.

Contents

message

A description of why the field failed validation.

Type: String

Required: Yes

name

The name of the field that failed validation.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Error Types

This section lists common error types that this AWS service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

IncompleteSignature

The request signature doesn't conform to AWS standards. Verify that you're using valid AWS credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 403

InternalFailure

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact AWS Support.

HTTP Status Code: 500

MalformedHttpRequestException

The request body can't be processed. This typically happens when the request body can't be decompressed using the specified content encoding algorithm. Verify that the content encoding header matches the compression format used.

HTTP Status Code: 400

NotAuthorized

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

OptInRequired

Your AWS account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

RequestAbortedException

The request was aborted before a response could be returned. This typically happens when the client closes the connection.

HTTP Status Code: 400

RequestEntityTooLargeException

The request entity is too large. Reduce the size of the request body and try again.

HTTP Status Code: 413

RequestTimeoutException

The request timed out. The server didn't receive the complete request within the expected time frame. Try again.

HTTP Status Code: 408

ServiceUnavailable

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

ThrottlingException

Your request rate is too high. The AWS SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

UnknownOperationException

The action or operation isn't recognized. Verify that the action name is spelled correctly and that it's supported by the API version you're using.

HTTP Status Code: 404

UnrecognizedClientException

The X.509 certificate or AWS access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

ValidationError

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400