



API Reference

AWS App Runner



API Version 2020-05-15

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS App Runner: API Reference

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
AssociateCustomDomain	4
Request Syntax	4
Request Parameters	4
Response Syntax	5
Response Elements	6
Errors	7
Examples	7
See Also	8
CreateAutoScalingConfiguration	10
Request Syntax	10
Request Parameters	10
Response Syntax	13
Response Elements	13
Errors	13
Examples	14
See Also	15
CreateConnection	16
Request Syntax	16
Request Parameters	16
Response Syntax	17
Response Elements	17
Errors	18
Examples	18
See Also	19
CreateObservabilityConfiguration	20
Request Syntax	20
Request Parameters	20
Response Syntax	22
Response Elements	22
Errors	22
Examples	23
See Also	24

CreateService	25
Request Syntax	25
Request Parameters	27
Response Syntax	29
Response Elements	31
Errors	32
Examples	32
See Also	37
CreateVpcConnector	38
Request Syntax	38
Request Parameters	38
Response Syntax	39
Response Elements	40
Errors	40
Examples	41
See Also	41
CreateVpcIngressConnection	43
Request Syntax	43
Request Parameters	43
Response Syntax	44
Response Elements	45
Errors	45
Examples	46
See Also	47
DeleteAutoScalingConfiguration	48
Request Syntax	48
Request Parameters	48
Response Syntax	49
Response Elements	49
Errors	49
Examples	50
See Also	52
DeleteConnection	54
Request Syntax	54
Request Parameters	54
Response Syntax	54

Response Elements	55
Errors	55
Examples	55
See Also	56
DeleteObservabilityConfiguration	57
Request Syntax	57
Request Parameters	57
Response Syntax	57
Response Elements	58
Errors	58
Examples	59
See Also	61
DeleteService	62
Request Syntax	62
Request Parameters	62
Response Syntax	62
Response Elements	65
Errors	65
Examples	66
See Also	68
DeleteVpcConnector	69
Request Syntax	69
Request Parameters	69
Response Syntax	69
Response Elements	70
Errors	70
Examples	71
See Also	71
DeleteVpcIngressConnection	73
Request Syntax	73
Request Parameters	73
Response Syntax	73
Response Elements	74
Errors	74
Examples	75
See Also	76

DescribeAutoScalingConfiguration	77
Request Syntax	77
Request Parameters	77
Response Syntax	77
Response Elements	78
Errors	78
Examples	79
See Also	80
DescribeCustomDomains	82
Request Syntax	82
Request Parameters	82
Response Syntax	83
Response Elements	84
Errors	85
Examples	85
See Also	87
DescribeObservabilityConfiguration	88
Request Syntax	88
Request Parameters	88
Response Syntax	88
Response Elements	89
Errors	89
Examples	90
See Also	92
DescribeService	93
Request Syntax	93
Request Parameters	93
Response Syntax	93
Response Elements	96
Errors	96
Examples	96
See Also	98
DescribeVpcConnector	100
Request Syntax	100
Request Parameters	100
Response Syntax	100

Response Elements	101
Errors	101
Examples	102
See Also	102
DescribeVpcIngressConnection	104
Request Syntax	104
Request Parameters	104
Response Syntax	104
Response Elements	105
Errors	105
See Also	106
DisassociateCustomDomain	107
Request Syntax	107
Request Parameters	107
Response Syntax	108
Response Elements	108
Errors	109
Examples	110
See Also	111
ListAutoScalingConfigurations	112
Request Syntax	112
Request Parameters	112
Response Syntax	113
Response Elements	114
Errors	114
Examples	115
See Also	116
ListConnections	117
Request Syntax	117
Request Parameters	117
Response Syntax	118
Response Elements	118
Errors	119
Examples	119
See Also	121
ListObservabilityConfigurations	122

Request Syntax	122
Request Parameters	122
Response Syntax	123
Response Elements	124
Errors	124
Examples	125
See Also	126
ListOperations	127
Request Syntax	127
Request Parameters	127
Response Syntax	128
Response Elements	128
Errors	129
Examples	130
See Also	130
ListServices	132
Request Syntax	132
Request Parameters	132
Response Syntax	133
Response Elements	133
Errors	134
Examples	134
See Also	135
ListServicesForAutoScalingConfiguration	137
Request Syntax	137
Request Parameters	137
Response Syntax	138
Response Elements	138
Errors	139
Examples	139
See Also	140
ListTagsForResource	142
Request Syntax	142
Request Parameters	142
Response Syntax	142
Response Elements	143

Errors	143
Examples	144
See Also	144
ListVpcConnectors	146
Request Syntax	146
Request Parameters	146
Response Syntax	147
Response Elements	147
Errors	148
Examples	148
See Also	149
ListVpcIngressConnections	150
Request Syntax	150
Request Parameters	150
Response Syntax	151
Response Elements	151
Errors	152
Examples	152
See Also	153
PauseService	154
Request Syntax	154
Request Parameters	154
Response Syntax	154
Response Elements	157
Errors	157
Examples	158
See Also	160
ResumeService	161
Request Syntax	161
Request Parameters	161
Response Syntax	161
Response Elements	164
Errors	164
Examples	165
See Also	167
StartDeployment	168

Request Syntax	168
Request Parameters	168
Response Syntax	168
Response Elements	169
Errors	169
Examples	170
See Also	170
TagResource	171
Request Syntax	171
Request Parameters	171
Response Elements	172
Errors	172
Examples	172
See Also	173
UntagResource	175
Request Syntax	175
Request Parameters	175
Response Elements	176
Errors	176
Examples	176
See Also	177
UpdateDefaultAutoScalingConfiguration	178
Request Syntax	178
Request Parameters	178
Response Syntax	178
Response Elements	179
Errors	179
Examples	180
See Also	182
UpdateService	183
Request Syntax	183
Request Parameters	185
Response Syntax	186
Response Elements	189
Errors	189
Examples	190

See Also	192
UpdateVpcIngressConnection	193
Request Syntax	193
Request Parameters	193
Response Syntax	194
Response Elements	194
Errors	194
Examples	195
See Also	196
Data Types	197
AuthenticationConfiguration	199
Contents	199
See Also	199
AutoScalingConfiguration	201
Contents	201
See Also	204
AutoScalingConfigurationSummary	205
Contents	205
See Also	207
CertificateValidationRecord	208
Contents	208
See Also	209
CodeConfiguration	210
Contents	210
See Also	210
CodeConfigurationValues	212
Contents	212
See Also	214
CodeRepository	215
Contents	215
See Also	216
Connection	217
Contents	217
See Also	218
ConnectionSummary	219
Contents	219

See Also	220
CustomDomain	221
Contents	221
See Also	222
EgressConfiguration	223
Contents	223
See Also	223
EncryptionConfiguration	225
Contents	225
See Also	225
HealthCheckConfiguration	226
Contents	226
See Also	227
ImageConfiguration	229
Contents	229
See Also	230
ImageRepository	231
Contents	231
See Also	232
IngressConfiguration	233
Contents	233
See Also	233
IngressVpcConfiguration	234
Contents	234
See Also	234
InstanceConfiguration	235
Contents	235
See Also	236
ListVpcIngressConnectionsFilter	237
Contents	237
See Also	237
NetworkConfiguration	238
Contents	238
See Also	238
ObservabilityConfiguration	240
Contents	240

See Also	242
ObservabilityConfigurationSummary	243
Contents	243
See Also	244
OperationSummary	245
Contents	245
See Also	246
Service	247
Contents	247
See Also	250
ServiceObservabilityConfiguration	251
Contents	251
See Also	251
ServiceSummary	253
Contents	253
See Also	255
SourceCodeVersion	256
Contents	256
See Also	256
SourceConfiguration	258
Contents	258
See Also	259
Tag	260
Contents	260
See Also	260
TraceConfiguration	261
Contents	261
See Also	261
VpcConnector	262
Contents	262
See Also	264
VpcDNSTarget	265
Contents	265
See Also	266
VpcIngressConnection	267
Contents	267

See Also	269
VpcIngressConnectionSummary	270
Contents	270
See Also	270
Common Parameters	271
Common Errors	274

Welcome

AWS App Runner is an application service that provides a fast, simple, and cost-effective way to go directly from an existing container image or source code to a running service in the AWS Cloud in seconds. You don't need to learn new technologies, decide which compute service to use, or understand how to provision and configure AWS resources.

App Runner connects directly to your container registry or source code repository. It provides an automatic delivery pipeline with fully managed operations, high performance, scalability, and security.

For more information about App Runner, see the [AWS App Runner Developer Guide](#). For release information, see the [AWS App Runner Release Notes](#).

To install the Software Development Kits (SDKs), Integrated Development Environment (IDE) Toolkits, and command line tools that you can use to access the API, see [Tools for Amazon Web Services](#).

Endpoints

For a list of Region-specific endpoints that App Runner supports, see [AWS App Runner endpoints and quotas](#) in the *AWS General Reference*.

This document was last published on February 12, 2026.

Actions

The following actions are supported:

- [AssociateCustomDomain](#)
- [CreateAutoScalingConfiguration](#)
- [CreateConnection](#)
- [CreateObservabilityConfiguration](#)
- [CreateService](#)
- [CreateVpcConnector](#)
- [CreateVpcIngressConnection](#)
- [DeleteAutoScalingConfiguration](#)
- [DeleteConnection](#)
- [DeleteObservabilityConfiguration](#)
- [DeleteService](#)
- [DeleteVpcConnector](#)
- [DeleteVpcIngressConnection](#)
- [DescribeAutoScalingConfiguration](#)
- [DescribeCustomDomains](#)
- [DescribeObservabilityConfiguration](#)
- [DescribeService](#)
- [DescribeVpcConnector](#)
- [DescribeVpcIngressConnection](#)
- [DisassociateCustomDomain](#)
- [ListAutoScalingConfigurations](#)
- [ListConnections](#)
- [ListObservabilityConfigurations](#)
- [ListOperations](#)
- [ListServices](#)
- [ListServicesForAutoScalingConfiguration](#)
- [ListTagsForResource](#)

- [ListVpcConnectors](#)
- [ListVpcIngressConnections](#)
- [PauseService](#)
- [ResumeService](#)
- [StartDeployment](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateDefaultAutoScalingConfiguration](#)
- [UpdateService](#)
- [UpdateVpcIngressConnection](#)

AssociateCustomDomain

Associate your own domain name with the AWS App Runner subdomain URL of your App Runner service.

After you call `AssociateCustomDomain` and receive a successful response, use the information in the [CustomDomain](#) record that's returned to add CNAME records to your Domain Name System (DNS). For each mapped domain name, add a mapping to the target App Runner subdomain and one or more certificate validation records. App Runner then performs DNS validation to verify that you own or control the domain name that you associated. App Runner tracks domain validity in a certificate stored in [AWS Certificate Manager \(ACM\)](#).

Request Syntax

```
{
  "DomainName": "string",
  "EnableWWWSubdomain": boolean,
  "ServiceArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[DomainName](#)

A custom domain endpoint to associate. Specify a root domain (for example, `example.com`), a subdomain (for example, `login.example.com` or `admin.login.example.com`), or a wildcard (for example, `*.example.com`).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[A-Za-z0-9*.-]{1,255}`

Required: Yes

EnableWWWSubdomain

Set to `true` to associate the subdomain `www.DomainName` with the App Runner service in addition to the base domain.

Default: `true`

Type: Boolean

Required: No

ServiceArn

The Amazon Resource Name (ARN) of the App Runner service that you want to associate a custom domain name with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\V|-){1,1011}`

Required: Yes

Response Syntax

```
{
  "CustomDomain": {
    "CertificateValidationRecords": [
      {
        "Name": "string",
        "Status": "string",
        "Type": "string",
        "Value": "string"
      }
    ],
    "DomainName": "string",
    "EnableWWWSubdomain": boolean,
    "Status": "string"
  },
  "DNSTarget": "string",
```

```
"ServiceArn": "string",
"VpcDNSTargets": [
  {
    "DomainName": "string",
    "VpcId": "string",
    "VpcIngressConnectionArn": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CustomDomain

A description of the domain name that's being associated.

Type: [CustomDomain](#) object

DNSTarget

The App Runner subdomain of the App Runner service. The custom domain name is mapped to this target name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: .*

ServiceArn

The Amazon Resource Name (ARN) of the App Runner service with which a custom domain name is associated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\/|-){1,1011}`

VpcDNSTargets

DNS Target records for the custom domains of this Amazon VPC.

Type: Array of [VpcDNSTarget](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

InvalidStateException

You can't perform this action when the resource is in its current state.

HTTP Status Code: 400

Examples

Associate a domain name and the www subdomain with a service

This example illustrates how to associate a custom domain name that you control with an App Runner service. The domain name is the root domain `example.com`, including the special-case subdomain `www.example.com`.

Note

`CertificateValidationRecords` is an optional field and returns an empty response for `AssociateCustomDomain` APIs.

Sample Request

```
$ aws apprunner associate-custom-domain --cli-input-json "`cat`"
{
  "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/python-
app/8fe1e10304f84fd2b0df550fe98a71fa",
  "DomainName": "example.com",
  "EnableWWWSubdomain": true
}
```

Sample Response

```
{
  "DNSTarget": "zg2t7wmhi.us-east-1.awsapprunner.com",
  "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/python-
app/8fe1e10304f84fd2b0df550fe98a71fa",
  "CustomDomain": {
    "DomainName": "example.com",
    "EnableWWWSubdomain": true,
    "Status": "creating"
  },
  "VpcDNSTargets": [
    {
      "DomainName": "psbqam834h.us-east-1.awsapprunner.com",
      "VpcId": "vpc-4a5b6c7d",
      "VpcIngressConnectionArn": "arn:aws:apprunner:us-
east-1:123456789012:vpcingressconnection/my-ingress-connection-
name/3f2eb10e2c494674952026f646844e3d"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateAutoScalingConfiguration

Create an AWS App Runner automatic scaling configuration resource. App Runner requires this resource when you create or update App Runner services and you require non-default auto scaling settings. You can share an auto scaling configuration across multiple services.

Create multiple revisions of a configuration by calling this action multiple times using the same `AutoScalingConfigurationName`. The call returns incremental `AutoScalingConfigurationRevision` values. When you create a service and configure an auto scaling configuration resource, the service uses the latest active revision of the auto scaling configuration by default. You can optionally configure the service to use a specific revision.

Configure a higher `MinSize` to increase the spread of your App Runner service over more Availability Zones in the AWS Region. The tradeoff is a higher minimal cost.

Configure a lower `MaxSize` to control your cost. The tradeoff is lower responsiveness during peak demand.

Request Syntax

```
{
  "AutoScalingConfigurationName": "string",
  "MaxConcurrency": number,
  "MaxSize": number,
  "MinSize": number,
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AutoScalingConfigurationName

A name for the auto scaling configuration. When you use it for the first time in an AWS Region, App Runner creates revision number 1 of this name. When you use the same name in subsequent calls, App Runner creates incremental revisions of the configuration.

Note

Prior to the release of [Auto scale configuration enhancements](#), the name `DefaultConfiguration` was reserved.

This restriction is no longer in place. You can now manage `DefaultConfiguration` the same way you manage your custom auto scaling configurations. This means you can do the following with the `DefaultConfiguration` that App Runner provides:

- Create new revisions of the `DefaultConfiguration`.
- Delete the revisions of the `DefaultConfiguration`.
- Delete the auto scaling configuration for which the App Runner `DefaultConfiguration` was created.
- If you delete the auto scaling configuration you can create another custom auto scaling configuration with the same `DefaultConfiguration` name. The original `DefaultConfiguration` resource provided by App Runner remains in your account unless you make changes to it.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 32.

Pattern: `[A-Za-z0-9][A-Za-z0-9\-\_]{3,31}`

Required: Yes

MaxConcurrency

The maximum number of concurrent requests that you want an instance to process. If the number of concurrent requests exceeds this limit, App Runner scales up your service.

Default: 100

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 200.

Required: No

MaxSize

The maximum number of instances that your service scales up to. At most MaxSize instances actively serve traffic for your service.

Default: 25

Type: Integer

Valid Range: Minimum value of 1.

Required: No

MinSize

The minimum number of instances that App Runner provisions for your service. The service always has at least MinSize provisioned instances. Some of them actively serve traffic. The rest of them (provisioned and inactive instances) are a cost-effective compute capacity reserve and are ready to be quickly activated. You pay for memory usage of all the provisioned instances. You pay for CPU usage of only the active subset.

App Runner temporarily doubles the number of provisioned instances during deployments, to maintain the same capacity for both old and new code.

Default: 1

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

Tags

A list of metadata items that you can associate with your auto scaling configuration resource. A tag is a key-value pair.

Type: Array of [Tag](#) objects

Required: No

Response Syntax

```
{
  "AutoScalingConfiguration": {
    "AutoScalingConfigurationArn": "string",
    "AutoScalingConfigurationName": "string",
    "AutoScalingConfigurationRevision": number,
    "CreatedAt": number,
    "DeletedAt": number,
    "HasAssociatedService": boolean,
    "IsDefault": boolean,
    "Latest": boolean,
    "MaxConcurrency": number,
    "MaxSize": number,
    "MinSize": number,
    "Status": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AutoScalingConfiguration

A description of the App Runner auto scaling configuration that's created by this request.

Type: [AutoScalingConfiguration](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

ServiceQuotaExceededException

App Runner can't create this resource. You've reached your account quota for this resource type.

For App Runner per-resource quotas, see [AWS App Runner endpoints and quotas](#) in the *AWS General Reference*.

HTTP Status Code: 400

Examples

Create a high availability auto scaling configuration

This example illustrates how to create an auto scaling configuration optimized for high availability by setting `MinSize` to 5. With this configuration, App Runner attempts to spread your service instances over the most Availability Zones possible, up to five, depending on the AWS Region.

The call returns an `AutoScalingConfiguration` object with the other settings set to their defaults. In the example, this is the first call to create a configuration named `high-availability`. The revision is set to 1, and it's the latest revision.

Sample Request

```
$ aws apprunner create-auto-scaling-configuration --cli-input-json "`cat`"
{
  "AutoScalingConfigurationName": "high-availability",
  "MinSize": 5
}
```

Sample Response

```
{
  "AutoScalingConfiguration": {
```

```
    "AutoScalingConfigurationArn": "arn:aws:apprunner:us-east-1:123456789012:autoscalingconfiguration/high-availability/1/2f50e7656d7819fead0f59672e68042e",
    "AutoScalingConfigurationName": "high-availability",
    "AutoScalingConfigurationRevision": 1,
    "CreatedAt": "2020-11-03T00:29:17Z",
    "Latest": true,
    "Status": "ACTIVE",
    "MaxConcurrency": 100,
    "MaxSize": 25,
    "MinSize": 5
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateConnection

Create an AWS App Runner connection resource. App Runner requires a connection resource when you create App Runner services that access private repositories from certain third-party providers. You can share a connection across multiple services.

A connection resource is needed to access GitHub and Bitbucket repositories. Both require a user interface approval process through the App Runner console before you can use the connection.

Request Syntax

```
{
  "ConnectionName": "string",
  "ProviderType": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ConnectionName

A name for the new connection. It must be unique across all App Runner connections for the AWS account in the AWS Region.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 32.

Pattern: `[A-Za-z0-9][A-Za-z0-9\-\_]{3,31}`

Required: Yes

[ProviderType](#)

The source repository provider.

Type: String

Valid Values: GITHUB | BITBUCKET

Required: Yes

[Tags](#)

A list of metadata items that you can associate with your connection resource. A tag is a key-value pair.

Type: Array of [Tag](#) objects

Required: No

Response Syntax

```
{
  "Connection": {
    "ConnectionArn": "string",
    "ConnectionName": "string",
    "CreatedAt": number,
    "ProviderType": "string",
    "Status": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Connection](#)

A description of the App Runner connection that's created by this request.

Type: [Connection](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

ServiceQuotaExceededException

App Runner can't create this resource. You've reached your account quota for this resource type.

For App Runner per-resource quotas, see [AWS App Runner endpoints and quotas](#) in the *AWS General Reference*.

HTTP Status Code: 400

Examples

Create a GitHub connection

This example illustrates how to create a connection to a private GitHub code repository. The connection status after a successful call is `PENDING_HANDSHAKE`. This is because an authentication handshake with the provider still hasn't happened. Complete the handshake using the App Runner console. For more information, see [Managing App Runner connections](#) in the *AWS App Runner Developer Guide*.

Sample Request

```
$ aws apprunner create-connection --cli-input-json "`cat`"  
{  
  "ConnectionName": "my-github-connection",  
  "ProviderType": "GITHUB"
```



```
}
```

Sample Response

```
{
  "Connection": {
    "ConnectionArn": "arn:aws:apprunner:us-east-1:123456789012:connection/my-github-connection",
    "ConnectionName": "my-github-connection",
    "Status": "PENDING_HANDSHAKE",
    "CreatedAt": "2020-11-03T00:32:51Z",
    "ProviderType": "GITHUB"
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateObservabilityConfiguration

Create an AWS App Runner observability configuration resource. App Runner requires this resource when you create or update App Runner services and you want to enable non-default observability features. You can share an observability configuration across multiple services.

Create multiple revisions of a configuration by calling this action multiple times using the same `ObservabilityConfigurationName`. The call returns incremental `ObservabilityConfigurationRevision` values. When you create a service and configure an observability configuration resource, the service uses the latest active revision of the observability configuration by default. You can optionally configure the service to use a specific revision.

The observability configuration resource is designed to configure multiple features (currently one feature, tracing). This action takes optional parameters that describe the configuration of these features (currently one parameter, `TraceConfiguration`). If you don't specify a feature parameter, App Runner doesn't enable the feature.

Request Syntax

```
{
  "ObservabilityConfigurationName": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "TraceConfiguration": {
    "Vendor": "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ObservabilityConfigurationName

A name for the observability configuration. When you use it for the first time in an AWS Region, App Runner creates revision number 1 of this name. When you use the same name in subsequent calls, App Runner creates incremental revisions of the configuration.

Note

The name `DefaultConfiguration` is reserved. You can't use it to create a new observability configuration, and you can't create a revision of it.

When you want to use your own observability configuration for your App Runner service, *create a configuration with a different name*, and then provide it when you create or update your service.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 32.

Pattern: `[A-Za-z0-9][A-Za-z0-9\-\_]{3,31}`

Required: Yes

Tags

A list of metadata items that you can associate with your observability configuration resource. A tag is a key-value pair.

Type: Array of [Tag](#) objects

Required: No

TraceConfiguration

The configuration of the tracing feature within this observability configuration. If you don't specify it, App Runner doesn't enable tracing.

Type: [TraceConfiguration](#) object

Required: No

Response Syntax

```
{
  "ObservabilityConfiguration": {
    "CreatedAt": number,
    "DeletedAt": number,
    "Latest": boolean,
    "ObservabilityConfigurationArn": "string",
    "ObservabilityConfigurationName": "string",
    "ObservabilityConfigurationRevision": number,
    "Status": "string",
    "TraceConfiguration": {
      "Vendor": "string"
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ObservabilityConfiguration

A description of the App Runner observability configuration that's created by this request.

Type: [ObservabilityConfiguration](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

ServiceQuotaExceededException

App Runner can't create this resource. You've reached your account quota for this resource type.

For App Runner per-resource quotas, see [AWS App Runner endpoints and quotas](#) in the *AWS General Reference*.

HTTP Status Code: 400

Examples

Create an observability configuration to enable X-Ray tracing

This example illustrates how to create an observability configuration that enables tracing using AWS X-Ray.

The call returns an `ObservabilityConfiguration` object. In the example, this is the first call to create a configuration named `xray-tracing`. The revision is set to 1, and it's the latest revision.

Sample Request

```
$ aws apprunner create-observability-configuration --cli-input-json "`cat`"
{
  "ObservabilityConfigurationName": "xray-tracing",
  "TraceConfiguration": {
    "Vendor": "AWSXRAY"
  }
}
```

Sample Response

```
{
  "ObservabilityConfiguration": {
    "ObservabilityConfigurationArn": "arn:aws:apprunner:us-east-1:123456789012:observabilityconfiguration/xray-tracing/1/2f50e7656d7819fead0f59672e68042e",
    "ObservabilityConfigurationName": "xray-tracing",
    "ObservabilityConfigurationRevision": 1,
    "CreatedAt": "2020-11-03T00:29:17Z",
    "Latest": true,
```

```
"Status": "ACTIVE",
"TraceConfiguration": {
  "Vendor": "AWSXRAY"
}
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateService

Create an AWS App Runner service. After the service is created, the action also automatically starts a deployment.

This is an asynchronous operation. On a successful call, you can use the returned `OperationId` and the [ListOperations](#) call to track the operation's progress.

Request Syntax

```
{
  "AutoScalingConfigurationArn": "string",
  "EncryptionConfiguration": {
    "KmsKey": "string"
  },
  "HealthCheckConfiguration": {
    "HealthyThreshold": number,
    "Interval": number,
    "Path": "string",
    "Protocol": "string",
    "Timeout": number,
    "UnhealthyThreshold": number
  },
  "InstanceConfiguration": {
    "Cpu": "string",
    "InstanceRoleArn": "string",
    "Memory": "string"
  },
  "NetworkConfiguration": {
    "EgressConfiguration": {
      "EgressType": "string",
      "VpcConnectorArn": "string"
    },
    "IngressConfiguration": {
      "IsPubliclyAccessible": boolean
    },
    "IpAddressType": "string"
  },
  "ObservabilityConfiguration": {
    "ObservabilityConfigurationArn": "string",
    "ObservabilityEnabled": boolean
  },
  "ServiceName": "string",
```

```

"SourceConfiguration": {
  "AuthenticationConfiguration": {
    "AccessRoleArn": "string",
    "ConnectionArn": "string"
  },
  "AutoDeploymentsEnabled": boolean,
  "CodeRepository": {
    "CodeConfiguration": {
      "CodeConfigurationValues": {
        "BuildCommand": "string",
        "Port": "string",
        "Runtime": "string",
        "RuntimeEnvironmentSecrets": {
          "string" : "string"
        },
        "RuntimeEnvironmentVariables": {
          "string" : "string"
        },
        "StartCommand": "string"
      },
      "ConfigurationSource": "string"
    },
    "RepositoryUrl": "string",
    "SourceCodeVersion": {
      "Type": "string",
      "Value": "string"
    },
    "SourceDirectory": "string"
  },
  "ImageRepository": {
    "ImageConfiguration": {
      "Port": "string",
      "RuntimeEnvironmentSecrets": {
        "string" : "string"
      },
      "RuntimeEnvironmentVariables": {
        "string" : "string"
      },
      "StartCommand": "string"
    },
    "ImageIdentifier": "string",
    "ImageRepositoryType": "string"
  }
},

```



```
"Tags": [  
  {  
    "Key": "string",  
    "Value": "string"  
  }  
]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[AutoScalingConfigurationArn](#)

The Amazon Resource Name (ARN) of an App Runner automatic scaling configuration resource that you want to associate with your service. If not provided, App Runner associates the latest revision of a default auto scaling configuration.

Specify an ARN with a name and a revision number to associate that revision. For example:
`arn:aws:apprunner:us-east-1:123456789012:autoscalingconfiguration/high-availability/3`

Specify just the name to associate the latest revision. For example: `arn:aws:apprunner:us-east-1:123456789012:autoscalingconfiguration/high-availability`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\w|-){1,1011}`

Required: No

[EncryptionConfiguration](#)

An optional custom encryption key that App Runner uses to encrypt the copy of your source repository that it maintains and your service logs. By default, App Runner uses an AWS managed key.

Type: [EncryptionConfiguration](#) object

Required: No

HealthCheckConfiguration

The settings for the health check that AWS App Runner performs to monitor the health of the App Runner service.

Type: [HealthCheckConfiguration](#) object

Required: No

InstanceConfiguration

The runtime configuration of instances (scaling units) of your service.

Type: [InstanceConfiguration](#) object

Required: No

NetworkConfiguration

Configuration settings related to network traffic of the web application that the App Runner service runs.

Type: [NetworkConfiguration](#) object

Required: No

ObservabilityConfiguration

The observability configuration of your service.

Type: [ServiceObservabilityConfiguration](#) object

Required: No

ServiceName

A name for the App Runner service. It must be unique across all the running App Runner services in your AWS account in the AWS Region.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 40.

Pattern: `[A-Za-z0-9][A-Za-z0-9-_{3,39}`

Required: Yes

SourceConfiguration

The source to deploy to the App Runner service. It can be a code or an image repository.

Type: [SourceConfiguration](#) object

Required: Yes

Tags

An optional list of metadata items that you can associate with the App Runner service resource. A tag is a key-value pair.

Type: Array of [Tag](#) objects

Required: No

Response Syntax

```
{
  "OperationId": "string",
  "Service": {
    "AutoScalingConfigurationSummary": {
      "AutoScalingConfigurationArn": "string",
      "AutoScalingConfigurationName": "string",
      "AutoScalingConfigurationRevision": number,
      "CreatedAt": number,
      "HasAssociatedService": boolean,
      "IsDefault": boolean,
      "Status": "string"
    },
    "CreatedAt": number,
    "DeletedAt": number,
    "EncryptionConfiguration": {
      "KmsKey": "string"
    },
    "HealthCheckConfiguration": {
      "HealthyThreshold": number,
      "Interval": number,
      "Path": "string",
      "Protocol": "string",
      "Timeout": number,
      "UnhealthyThreshold": number
    }
  },
}
```

```

    "InstanceConfiguration": {
      "Cpu": "string",
      "InstanceRoleArn": "string",
      "Memory": "string"
    },
    "NetworkConfiguration": {
      "EgressConfiguration": {
        "EgressType": "string",
        "VpcConnectorArn": "string"
      },
      "IngressConfiguration": {
        "IsPubliclyAccessible": boolean
      },
      "IpAddressType": "string"
    },
    "ObservabilityConfiguration": {
      "ObservabilityConfigurationArn": "string",
      "ObservabilityEnabled": boolean
    },
    "ServiceArn": "string",
    "ServiceId": "string",
    "ServiceName": "string",
    "ServiceUrl": "string",
    "SourceConfiguration": {
      "AuthenticationConfiguration": {
        "AccessRoleArn": "string",
        "ConnectionArn": "string"
      },
      "AutoDeploymentsEnabled": boolean,
      "CodeRepository": {
        "CodeConfiguration": {
          "CodeConfigurationValues": {
            "BuildCommand": "string",
            "Port": "string",
            "Runtime": "string",
            "RuntimeEnvironmentSecrets": {
              "string": "string"
            },
            "RuntimeEnvironmentVariables": {
              "string": "string"
            },
            "StartCommand": "string"
          },
          "ConfigurationSource": "string"
        }
      }
    }
  }

```

```

    },
    "RepositoryUrl": "string",
    "SourceCodeVersion": {
      "Type": "string",
      "Value": "string"
    },
    "SourceDirectory": "string"
  },
  "ImageRepository": {
    "ImageConfiguration": {
      "Port": "string",
      "RuntimeEnvironmentSecrets": {
        "string" : "string"
      },
      "RuntimeEnvironmentVariables": {
        "string" : "string"
      },
      "StartCommand": "string"
    },
    "ImageIdentifier": "string",
    "ImageRepositoryType": "string"
  }
},
"Status": "string",
"UpdatedAt": number
}
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

OperationId

The unique ID of the asynchronous operation that this request started. You can use it combined with the [ListOperations](#) call to track the operation's progress.

Type: String

Length Constraints: Fixed length of 36.

Pattern: [0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[1-5][0-9a-fA-F]{3}-[89abAB][0-9a-fA-F]{3}-[0-9a-fA-F]{12}

[Service](#)

A description of the App Runner service that's created by this request.

Type: [Service](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

ServiceQuotaExceededException

App Runner can't create this resource. You've reached your account quota for this resource type.

For App Runner per-resource quotas, see [AWS App Runner endpoints and quotas](#) in the *AWS General Reference*.

HTTP Status Code: 400

Examples

Create a source code repository service

This example illustrates how to create an App Runner service based on a Python source code repository.

Sample Request

```
$ aws apprunner create-service --cli-input-json "`cat`"
{
  "ServiceName": "python-app",
  "SourceConfiguration": {
    "AuthenticationConfiguration": {
      "ConnectionArn": "arn:aws:apprunner:us-east-1:123456789012:connection/my-github-connection/e7656250f67242d7819feade6800f59e"
    },
    "AutoDeploymentsEnabled": true,
    "CodeRepository": {
      "RepositoryUrl": "https://github.com/my-account/python-hello",
      "SourceCodeVersion": {
        "Type": "BRANCH",
        "Value": "main"
      },
    },
    "CodeConfiguration": {
      "ConfigurationSource": "API",
      "CodeConfigurationValues": {
        "Runtime": "PYTHON_3",
        "BuildCommand": "pip install -r requirements.txt",
        "StartCommand": "python server.py",
        "Port": "8080",
        "RuntimeEnvironmentVariables": [
          {
            "NAME": "Jane"
          }
        ]
      }
    }
  },
  "InstanceConfiguration": {
    "CPU": "1 vCPU",
    "Memory": "3 GB"
  }
}
```

Sample Response

```
{
  "OperationId": "17fe9f55-7e91-4097-b243-fcabbb69a4cf",
```

```
"Service": {
  "CreatedAt": "2020-11-20T19:05:25Z",
  "UpdatedAt": "2020-11-20T19:05:25Z",
  "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/python-
app/8fe1e10304f84fd2b0df550fe98a71fa",
  "ServiceId": "8fe1e10304f84fd2b0df550fe98a71fa",
  "ServiceName": "python-app",
  "ServiceUrl": "psbqam834h.us-east-1.awsapprunner.com",
  "SourceConfiguration": {
    "AuthenticationConfiguration": {
      "ConnectionArn": "arn:aws:apprunner:us-east-1:123456789012:connection/my-
github-connection/e7656250f67242d7819feade6800f59e"
    },
    "AutoDeploymentsEnabled": true,
    "CodeRepository": {
      "CodeConfiguration": {
        "CodeConfigurationValues": {
          "BuildCommand": "pip install -r requirements.txt",
          "Port": "8080",
          "Runtime": "PYTHON_3",
          "RuntimeEnvironmentVariables": [
            {
              "NAME": "Jane"
            }
          ],
          "StartCommand": "python server.py"
        },
        "ConfigurationSource": "Api"
      },
      "RepositoryUrl": "https://github.com/my-account/python-hello",
      "SourceCodeVersion": {
        "Type": "BRANCH",
        "Value": "main"
      }
    }
  },
  "Status": "OPERATION_IN_PROGRESS",
  "InstanceConfiguration": {
    "CPU": "1 vCPU",
    "Memory": "3 GB"
  },
  "NetworkConfiguration": {
    "IpAddressType": "IPV4",
    "EgressConfiguration": {
```



```
    "EgressType": "DEFAULT"
  },
  "IngressConfiguration": {
    "IsPubliclyAccessible": true
  }
},
"ObservabilityConfiguration": {
  "ObservabilityEnabled": false
}
}
```

Create a source image repository service

This example illustrates how to create an App Runner service based on an image stored in Elastic Container Registry (ECR).

Sample Request

```
$ aws apprunner create-service --cli-input-json "`cat`"
{
  "ServiceName": "golang-container-app",
  "SourceConfiguration": {
    "AuthenticationConfiguration": {
      "AccessRoleArn": "arn:aws:iam::123456789012:role/my-ecr-role"
    },
    "AutoDeploymentsEnabled": true,
    "ImageRepository": {
      "ImageIdentifier": "123456789012.dkr.ecr.us-east-1.amazonaws.com/golang-
app:latest",
      "ImageConfiguration": {
        "Port": "8080",
        "RuntimeEnvironmentVariables": [
          {
            "NAME": "Jane"
          }
        ]
      },
      "ImageRepositoryType": "ECR"
    }
  },
  "InstanceConfiguration": {
    "CPU": "1 vCPU",
```

```
    "Memory": "3 GB"
  }
}
```

Sample Response

```
{
  "OperationId": "17fe9f55-7e91-4097-b243-fcabbb69a4cf",
  "Service": {
    "CreatedAt": "2020-11-06T23:15:30Z",
    "UpdatedAt": "2020-11-06T23:15:30Z",
    "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/golang-container-app/51728f8a20ce46d39b25398a6c8e9d1a",
    "ServiceId": "51728f8a20ce46d39b25398a6c8e9d1a",
    "ServiceName": "golang-container-app",
    "ServiceUrl": "psbqam834h.us-east-1.awsapprunner.com",
    "SourceConfiguration": {
      "AuthenticationConfiguration": {
        "AccessRoleArn": "arn:aws:iam::123456789012:role/my-ecr-role"
      },
      "AutoDeploymentsEnabled": true,
      "ImageRepository": {
        "ImageIdentifier": "123456789012.dkr.ecr.us-east-1.amazonaws.com/golang-app:latest",
        "ImageConfiguration": {
          "Port": "8080",
          "RuntimeEnvironmentVariables": [
            {
              "NAME": "Jane"
            }
          ]
        }
      },
      "ImageRepositoryType": "ECR"
    }
  },
  "Status": "OPERATION_IN_PROGRESS",
  "InstanceConfiguration": {
    "CPU": "1 vCPU",
    "Memory": "3 GB"
  },
  "NetworkConfiguration": {
    "IpAddressType": "IPV4",
    "EgressConfiguration": {
```

```
    "EgressType": "DEFAULT"
  },
  "IngressConfiguration": {
    "IsPubliclyAccessible": true
  }
},
"ObservabilityConfiguration": {
  "ObservabilityEnabled": false
}
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateVpcConnector

Create an AWS App Runner VPC connector resource. App Runner requires this resource when you want to associate your App Runner service to a custom Amazon Virtual Private Cloud (Amazon VPC).

Request Syntax

```
{
  "SecurityGroups": [ "string" ],
  "Subnets": [ "string" ],
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "VpcConnectorName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

SecurityGroups

A list of IDs of security groups that App Runner should use for access to AWS resources under the specified subnets. If not specified, App Runner uses the default security group of the Amazon VPC. The default security group allows all outbound traffic.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: .*

Required: No

Subnets

A list of IDs of subnets that App Runner should use when it associates your service with a custom Amazon VPC. Specify IDs of subnets of a single Amazon VPC. App Runner determines the Amazon VPC from the subnets you specify.

Note

App Runner only supports subnets of IP address type *IPv4* and *dual stack* (IPv4 and IPv6).

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: .*

Required: Yes

Tags

A list of metadata items that you can associate with your VPC connector resource. A tag is a key-value pair.

Type: Array of [Tag](#) objects

Required: No

VpcConnectorName

A name for the VPC connector.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 40.

Pattern: [A-Za-z0-9][A-Za-z0-9\-_]{3,39}

Required: Yes

Response Syntax

```
{
```

```
"VpcConnector": {  
  "CreatedAt": number,  
  "DeletedAt": number,  
  "SecurityGroups": [ "string" ],  
  "Status": "string",  
  "Subnets": [ "string" ],  
  "VpcConnectorArn": "string",  
  "VpcConnectorName": "string",  
  "VpcConnectorRevision": number  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

VpcConnector

A description of the App Runner VPC connector that's created by this request.

Type: VpcConnector object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServiceErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

ServiceQuotaExceededException

App Runner can't create this resource. You've reached your account quota for this resource type.

For App Runner per-resource quotas, see [AWS App Runner endpoints and quotas](#) in the *AWS General Reference*.

HTTP Status Code: 400

Examples

Create a VPC connector

This example illustrates how to create a VPC connector.

Sample Request

```
$ aws apprunner create-vpc-connector --cli-input-json "`cat`"
{
  "VpcConnectorName": "my-vpc-connector",
  "Subnets": ["subnet-123", "subnet-456"],
  "SecurityGroups": ["sg-123", "sg-456"]
}
```

Sample Response

```
{
  "VpcConnector": {
    "VpcConnectorArn": "arn:aws:apprunner:us-east-1:123456789012:vpccconnector/my-vpc-connector/1/3f2eb10e2c494674952026f646844e3d",
    "VpcConnectorName": "my-vpc-connector",
    "VpcConnectorRevision": 1,
    "Subnets": ["subnet-123", "subnet-456"],
    "SecurityGroups": ["sg-123", "sg-456"],
    "Status": "ACTIVE",
    "CreatedAt": "2021-08-18T23:36:45.374Z"
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateVpcIngressConnection

Create an AWS App Runner VPC Ingress Connection resource. App Runner requires this resource when you want to associate your App Runner service with an Amazon VPC endpoint.

Request Syntax

```
{
  "IngressVpcConfiguration": {
    "VpcEndpointId": "string",
    "VpcId": "string"
  },
  "ServiceArn": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "VpcIngressConnectionName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

IngressVpcConfiguration

Specifications for the customer's Amazon VPC and the related AWS PrivateLink VPC endpoint that are used to create the VPC Ingress Connection resource.

Type: [IngressVpcConfiguration](#) object

Required: Yes

ServiceArn

The Amazon Resource Name (ARN) for this App Runner service that is used to create the VPC Ingress Connection resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:([\w|\s|-]){1,1011}`

Required: Yes

Tags

An optional list of metadata items that you can associate with the VPC Ingress Connection resource. A tag is a key-value pair.

Type: Array of [Tag](#) objects

Required: No

VpcIngressConnectionName

A name for the VPC Ingress Connection resource. It must be unique across all the active VPC Ingress Connections in your AWS account in the AWS Region.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 40.

Pattern: `[A-Za-z0-9][A-Za-z0-9\-\_]{3,39}`

Required: Yes

Response Syntax

```
{
  "VpcIngressConnection": {
    "AccountId": "string",
    "CreatedAt": number,
    "DeletedAt": number,
    "DomainName": "string",
    "IngressVpcConfiguration": {
      "VpcEndpointId": "string",
      "VpcId": "string"
    }
  },
}
```

```
"ServiceArn": "string",  
"Status": "string",  
"VpcIngressConnectionArn": "string",  
"VpcIngressConnectionName": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

VpcIngressConnection

A description of the AWS App Runner VPC Ingress Connection resource that's created by this request.

Type: [VpcIngressConnection](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

InvalidStateException

You can't perform this action when the resource is in its current state.

HTTP Status Code: 400

ServiceQuotaExceededException

App Runner can't create this resource. You've reached your account quota for this resource type.

For App Runner per-resource quotas, see [AWS App Runner endpoints and quotas](#) in the *AWS General Reference*.

HTTP Status Code: 400

Examples

Create a VPC Ingress Connection

This example illustrates how to create a VPC Ingress Connection.

Sample Request

```
$ aws apprunner create-vpc-ingress-connection --cli-input-json "`cat`"
{
  "IngressVpcConfiguration": {
    "VpcEndpointId": "vpce-1a2b3c4d",
    "VpcId": "vpc-4a5b6c7d"
  },
  "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/my-service",
  "VpcIngressConnectionName": "my-ingress-connection-name"
}
```

Sample Response

```
{
  "AccountId": "123456789012",
  "CreatedAt": "2022-09-18T23:36:45.374Z",
  "DomainName": "psbqam834h.us-east-1.awsapprunner.com",
  "IngressVpcConfiguration": {
    "VpcEndpointId": "vpce-1a2b3c4d",
    "VpcId": "vpc-4a5b6c7d"
  },
  "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/my-service",
  "Status": "PENDING_CREATION",
  "VpcIngressConnectionArn": "arn:aws:apprunner:us-east-1:123456789012:vpcingressconnection/my-ingress-connection-name/3f2eb10e2c494674952026f646844e3d",
}
```

```
"VpcIngressConnectionName": "my-ingress-connection-name"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteAutoScalingConfiguration

Delete an AWS App Runner automatic scaling configuration resource. You can delete a top level auto scaling configuration, a specific revision of one, or all revisions associated with the top level configuration. You can't delete the default auto scaling configuration or a configuration that's used by one or more App Runner services.

Request Syntax

```
{  
  "AutoScalingConfigurationArn": "string",  
  "DeleteAllRevisions": boolean  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[AutoScalingConfigurationArn](#)

The Amazon Resource Name (ARN) of the App Runner auto scaling configuration that you want to delete.

The ARN can be a full auto scaling configuration ARN, or a partial ARN ending with either `.../name` or `.../name/revision`. If a revision isn't specified, the latest active revision is deleted.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\V|-){1,1011}`

Required: Yes

[DeleteAllRevisions](#)

Set to `true` to delete all of the revisions associated with the `AutoScalingConfigurationArn` parameter value.

When `DeleteAllRevisions` is set to `true`, the only valid value for the Amazon Resource Name (ARN) is a partial ARN ending with: `.../name`.

Type: Boolean

Required: No

Response Syntax

```
{
  "AutoScalingConfiguration": {
    "AutoScalingConfigurationArn": "string",
    "AutoScalingConfigurationName": "string",
    "AutoScalingConfigurationRevision": number,
    "CreatedAt": number,
    "DeletedAt": number,
    "HasAssociatedService": boolean,
    "IsDefault": boolean,
    "Latest": boolean,
    "MaxConcurrency": number,
    "MaxSize": number,
    "MinSize": number,
    "Status": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AutoScalingConfiguration](#)

A description of the App Runner auto scaling configuration that this request just deleted.

Type: [AutoScalingConfiguration](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

ResourceNotFoundException

A resource doesn't exist for the specified Amazon Resource Name (ARN) in your AWS account.

HTTP Status Code: 400

Examples

Delete the latest active revision of an auto scaling configuration

This example illustrates how to delete the latest active revision of an App Runner auto scaling configuration. To delete the latest active revision, specify an Amazon Resource Name (ARN) that ends with the configuration name, without the revision component.

In the example, two revisions exist before this action. Therefore, revision 2 (the latest) is deleted. However, it now shows "Latest": false, because, after being deleted, it isn't the latest active revision anymore.

Sample Request

```
$ aws apprunner delete-auto-scaling-configuration --cli-input-json "`cat`"  
{  
  "AutoScalingConfigurationArn": "arn:aws:apprunner:us-  
east-1:123456789012:autoscalingconfiguration/high-availability"  
}
```

Sample Response

```
{  
  "AutoScalingConfiguration": {
```



```
"AutoScalingConfigurationArn": "arn:aws:apprunner:us-east-1:123456789012:autoscalingconfiguration/high-availability/2/e76562f50d78042e819fead0f59672e6",
"AutoScalingConfigurationName": "high-availability",
"AutoScalingConfigurationRevision": 2,
"CreatedAt": "2021-02-25T17:42:59Z",
"DeletedAt": "2021-03-02T08:07:06Z",
"Latest": false,
"Status": "INACTIVE",
"MaxConcurrency": 30,
"MaxSize": 25,
"MinSize": 5
}
}
```

Delete a specific revision of an auto scaling configuration

This example illustrates how to delete a specific revision of an App Runner auto scaling configuration. To delete a specific revision, specify an ARN that includes the revision number.

In the example, several revisions exist before this action. The action deletes revision 1.

Sample Request

```
$ aws apprunner delete-auto-scaling-configuration --cli-input-json "`cat`"
{
  "AutoScalingConfigurationArn": "arn:aws:apprunner:us-east-1:123456789012:autoscalingconfiguration/high-availability/1"
}
```

Sample Response

```
{
  "AutoScalingConfiguration": {
    "AutoScalingConfigurationArn": "arn:aws:apprunner:us-east-1:123456789012:autoscalingconfiguration/high-availability/1/2f50e7656d7819fead0f59672e68042e",
    "AutoScalingConfigurationName": "high-availability",
    "AutoScalingConfigurationRevision": 1,
    "CreatedAt": "2020-11-03T00:29:17Z",
    "DeletedAt": "2021-03-02T08:07:06Z",
    "Latest": false,
    "Status": "INACTIVE",
  }
}
```

```
    "MaxConcurrency": 100,  
    "MaxSize": 25,  
    "MinSize": 5  
  }  
}
```

Delete all revisions of an auto scaling configuration

This example illustrates how to delete all of the revisions associated with an App Runner auto scaling configuration.

To delete all associated revisions set `DeleteAllRevisions` to `true`. Specify a partial ARN ending with `.../name`.

The response does not include all of the fields listed in the *Response Syntax*. It only contains the fields shown in the sample response.

Sample Request

```
$ aws apprunner delete-auto-scaling-configuration --cli-input-json "`cat`"  
{  
  "AutoScalingConfigurationArn": "arn:aws:apprunner:us-  
east-1:123456789012:autoscalingconfiguration/high-availability",  
  "DeleteAllRevisions": true  
}
```

Sample Response

```
{  
  "AutoScalingConfiguration": {  
    "AutoScalingConfigurationArn": "arn:aws:apprunner:us-  
east-1:123456789012:autoscalingconfiguration/high-availability",  
    "AutoScalingConfigurationName": "high-availability",  
    "Status": "inactive"  
  }  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteConnection

Delete an AWS App Runner connection. You must first ensure that there are no running App Runner services that use this connection. If there are any, the DeleteConnection action fails.

Request Syntax

```
{  
  "ConnectionArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ConnectionArn

The Amazon Resource Name (ARN) of the App Runner connection that you want to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\V|-){1,1011}`

Required: Yes

Response Syntax

```
{  
  "Connection": {  
    "ConnectionArn": "string",  
    "ConnectionName": "string",  
    "CreatedAt": number,  
    "ProviderType": "string",  
    "Status": "string"  
  }  
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Connection

A description of the App Runner connection that this request just deleted.

Type: [Connection](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

ResourceNotFoundException

A resource doesn't exist for the specified Amazon Resource Name (ARN) in your AWS account.

HTTP Status Code: 400

Examples

Delete a connection

This example illustrates deleting an App Runner connection. The connection status after a successful call is DELETED. This is because the connection is no longer available.

Sample Request

```
$ aws apprunner delete-connection --cli-input-json "`cat`"
{
  "ConnectionArn": "arn:aws:apprunner:us-east-1:123456789012:connection/my-github-connection"
}
```

Sample Response

```
{
  "Connection": {
    "ConnectionArn": "arn:aws:apprunner:us-east-1:123456789012:connection/my-github-connection",
    "ConnectionName": "my-github-connection",
    "Status": "DELETED",
    "CreatedAt": "2020-11-03T00:32:51Z",
    "ProviderType": "GITHUB"
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteObservabilityConfiguration

Delete an AWS App Runner observability configuration resource. You can delete a specific revision or the latest active revision. You can't delete a configuration that's used by one or more App Runner services.

Request Syntax

```
{  
  "ObservabilityConfigurationArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ObservabilityConfigurationArn](#)

The Amazon Resource Name (ARN) of the App Runner observability configuration that you want to delete.

The ARN can be a full observability configuration ARN, or a partial ARN ending with either `.../name` or `.../name/revision`. If a revision isn't specified, the latest active revision is deleted.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\V|-){1,1011}`

Required: Yes

Response Syntax

```
{  
  "ObservabilityConfiguration": {  
    "CreatedAt": number,  
    ...  
  }  
}
```

```
"DeletedAt": number,
"Latest": boolean,
"ObservabilityConfigurationArn": "string",
"ObservabilityConfigurationName": "string",
"ObservabilityConfigurationRevision": number,
"Status": "string",
"TraceConfiguration": {
  "Vendor": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ObservabilityConfiguration

A description of the App Runner observability configuration that this request just deleted.

Type: [ObservabilityConfiguration](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

ResourceNotFoundException

A resource doesn't exist for the specified Amazon Resource Name (ARN) in your AWS account.

HTTP Status Code: 400

Examples

Delete the latest active revision of an observability configuration

This example illustrates how to delete the latest active revision of an App Runner observability configuration. To delete the latest active revision, specify an Amazon Resource Name (ARN) that ends with the configuration name, without the revision component.

In the example, two revisions exist before this action. Therefore, revision 2 (the latest) is deleted. However, it now shows "Latest": false, because, after being deleted, it isn't the latest active revision anymore.

Note

The two revisions in our examples are identical, because App Runner doesn't yet support enough observability functionality to demonstrate two significantly different revisions (for example, multiple tracing vendors). We're including the two examples only to demonstrate the revisioning behavior during deletion.

Sample Request

```
$ aws apprunner delete-observability-configuration --cli-input-json "`cat`"
{
  "ObservabilityConfigurationArn": "arn:aws:apprunner:us-east-1:123456789012:observabilityconfiguration/xray-tracing"
}
```

Sample Response

```
{
  "ObservabilityConfiguration": {
    "ObservabilityConfigurationArn": "arn:aws:apprunner:us-east-1:123456789012:observabilityconfiguration/xray-tracing/2/e76562f50d78042e819fead0f59672e6",
    "ObservabilityConfigurationName": "xray-tracing",
    "ObservabilityConfigurationRevision": 2,
```

```
{
  "CreatedAt": "2021-02-25T17:42:59Z",
  "DeletedAt": "2021-03-02T08:07:06Z",
  "Latest": false,
  "Status": "INACTIVE",
  "TraceConfiguration": {
    "Vendor": "AWSXRAY"
  }
}
```

Delete a specific revision of an observability configuration

This example illustrates how to delete a specific revision of an App Runner observability configuration. To delete a specific revision, specify an ARN that includes the revision number.

In the example, several revisions exist before this action. The action deletes revision 1.

Sample Request

```
$ aws apprunner delete-observability-configuration --cli-input-json "`cat`"
{
  "ObservabilityConfigurationArn": "arn:aws:apprunner:us-
east-1:123456789012:observabilityconfiguration/xray-tracing/1"
}
```

Sample Response

```
{
  "ObservabilityConfiguration": {
    "ObservabilityConfigurationArn": "arn:aws:apprunner:us-
east-1:123456789012:observabilityconfiguration/xray-
tracing/1/2f50e7656d7819fead0f59672e68042e",
    "ObservabilityConfigurationName": "xray-tracing",
    "ObservabilityConfigurationRevision": 1,
    "CreatedAt": "2020-11-03T00:29:17Z",
    "DeletedAt": "2021-03-02T08:07:06Z",
    "Latest": false,
    "Status": "INACTIVE",
    "TraceConfiguration": {
      "Vendor": "AWSXRAY"
    }
  }
}
```

```
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteService

Delete an AWS App Runner service.

This is an asynchronous operation. On a successful call, you can use the returned `OperationId` and the [ListOperations](#) call to track the operation's progress.

Note

Make sure that you don't have any active `VPCIngressConnections` associated with the service you want to delete.

Request Syntax

```
{  
  "ServiceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ServiceArn](#)

The Amazon Resource Name (ARN) of the App Runner service that you want to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\V|-){1,1011}`

Required: Yes

Response Syntax

```
{
```

```

"OperationId": "string",
"Service": {
  "AutoScalingConfigurationSummary": {
    "AutoScalingConfigurationArn": "string",
    "AutoScalingConfigurationName": "string",
    "AutoScalingConfigurationRevision": number,
    "CreatedAt": number,
    "HasAssociatedService": boolean,
    "IsDefault": boolean,
    "Status": "string"
  },
  "CreatedAt": number,
  "DeletedAt": number,
  "EncryptionConfiguration": {
    "KmsKey": "string"
  },
  "HealthCheckConfiguration": {
    "HealthyThreshold": number,
    "Interval": number,
    "Path": "string",
    "Protocol": "string",
    "Timeout": number,
    "UnhealthyThreshold": number
  },
  "InstanceConfiguration": {
    "Cpu": "string",
    "InstanceRoleArn": "string",
    "Memory": "string"
  },
  "NetworkConfiguration": {
    "EgressConfiguration": {
      "EgressType": "string",
      "VpcConnectorArn": "string"
    },
    "IngressConfiguration": {
      "IsPubliclyAccessible": boolean
    },
    "IpAddressType": "string"
  },
  "ObservabilityConfiguration": {
    "ObservabilityConfigurationArn": "string",
    "ObservabilityEnabled": boolean
  },
  "ServiceArn": "string",

```

```

"ServiceId": "string",
"ServiceName": "string",
"ServiceUrl": "string",
"SourceConfiguration": {
  "AuthenticationConfiguration": {
    "AccessRoleArn": "string",
    "ConnectionArn": "string"
  },
  "AutoDeploymentsEnabled": boolean,
  "CodeRepository": {
    "CodeConfiguration": {
      "CodeConfigurationValues": {
        "BuildCommand": "string",
        "Port": "string",
        "Runtime": "string",
        "RuntimeEnvironmentSecrets": {
          "string" : "string"
        },
        "RuntimeEnvironmentVariables": {
          "string" : "string"
        },
        "StartCommand": "string"
      },
      "ConfigurationSource": "string"
    },
    "RepositoryUrl": "string",
    "SourceCodeVersion": {
      "Type": "string",
      "Value": "string"
    },
    "SourceDirectory": "string"
  },
  "ImageRepository": {
    "ImageConfiguration": {
      "Port": "string",
      "RuntimeEnvironmentSecrets": {
        "string" : "string"
      },
      "RuntimeEnvironmentVariables": {
        "string" : "string"
      },
      "StartCommand": "string"
    },
    "ImageIdentifier": "string",

```

```
        "ImageRepositoryType": "string"
    },
    "Status": "string",
    "UpdatedAt": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

OperationId

The unique ID of the asynchronous operation that this request started. You can use it combined with the [ListOperations](#) call to track the operation's progress.

Type: String

Length Constraints: Fixed length of 36.

Pattern: [0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[1-5][0-9a-fA-F]{3}-[89abAB][0-9a-fA-F]{3}-[0-9a-fA-F]{12}

Service

A description of the App Runner service that this request just deleted.

Type: [Service](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

InvalidStateException

You can't perform this action when the resource is in its current state.

HTTP Status Code: 400

ResourceNotFoundException

A resource doesn't exist for the specified Amazon Resource Name (ARN) in your AWS account.

HTTP Status Code: 400

Examples

Delete a service

This example illustrates how to delete an App Runner service.

Sample Request

```
$ aws apprunner delete-service --cli-input-json "`cat`"  
{  
  "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/python-  
app/8fe1e10304f84fd2b0df550fe98a71fa"  
}
```

Sample Response

```
{  
  "OperationId": "17fe9f55-7e91-4097-b243-fcabbb69a4cf",  
  "Service": {  
    "CreatedAt": "2020-11-20T19:05:25Z",  
    "UpdatedAt": "2020-11-23T12:41:37Z",  
    "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/python-  
app/8fe1e10304f84fd2b0df550fe98a71fa",  
    "ServiceId": "8fe1e10304f84fd2b0df550fe98a71fa",  
    "ServiceName": "python-app",  
  }  
}
```



```
"ServiceUrl": "psbqam834h.us-east-1.awsapprunner.com",
"SourceConfiguration": {
  "AuthenticationConfiguration": {
    "ConnectionArn": "arn:aws:apprunner:us-east-1:123456789012:connection/my-
github-connection/e7656250f67242d7819feade6800f59e"
  },
  "AutoDeploymentsEnabled": true,
  "CodeRepository": {
    "CodeConfiguration": {
      "CodeConfigurationValues": {
        "BuildCommand": "[pip install -r requirements.txt]",
        "Port": "8080",
        "Runtime": "PYTHON_3",
        "RuntimeEnvironmentVariables": [
          {
            "NAME": "Jane"
          }
        ],
        "StartCommand": "python server.py"
      },
      "ConfigurationSource": "Api"
    },
    "RepositoryUrl": "https://github.com/my-account/python-hello",
    "SourceCodeVersion": {
      "Type": "BRANCH",
      "Value": "main"
    }
  }
},
"Status": "OPERATION_IN_PROGRESS",
"InstanceConfiguration": {
  "CPU": "1 vCPU",
  "Memory": "3 GB"
},
"NetworkConfiguration": {
  "IpAddressType": "IPV4",
  "EgressConfiguration": {
    "EgressType": "DEFAULT"
  },
  "IngressConfiguration": {
    "IsPubliclyAccessible": true
  }
},
"ObservabilityConfiguration": {
```

```
    "ObservabilityEnabled": false
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteVpcConnector

Delete an AWS App Runner VPC connector resource. You can't delete a connector that's used by one or more App Runner services.

Request Syntax

```
{  
  "VpcConnectorArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

VpcConnectorArn

The Amazon Resource Name (ARN) of the App Runner VPC connector that you want to delete.

The ARN must be a full VPC connector ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\V|-){1,1011}`

Required: Yes

Response Syntax

```
{  
  "VpcConnector": {  
    "CreatedAt": number,  
    "DeletedAt": number,  
    "SecurityGroups": [ "string" ],  
  }
```

```
"Status": "string",
"Subnets": [ "string" ],
"VpcConnectorArn": "string",
"VpcConnectorName": "string",
"VpcConnectorRevision": number
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

VpcConnector

A description of the App Runner VPC connector that this request just deleted.

Type: VpcConnector object

Errors

For information about the errors that are common to all actions, see Common Errors.

InternalServiceErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

ResourceNotFoundException

A resource doesn't exist for the specified Amazon Resource Name (ARN) in your AWS account.

HTTP Status Code: 400

Examples

Delete a VPC connector

This example illustrates how to delete an App Runner VPC connector.

Sample Request

```
$ aws apprunner delete-vpc-connector --cli-input-json "`cat`"  
{  
  "VpcConnectorArn": "arn:aws:apprunner:us-east-1:123456789012:vpconnector/my-vpc-  
connector/1/3f2eb10e2c494674952026f646844e3d"  
}
```

Sample Response

```
{  
  "VpcConnector": {  
    "VpcConnectorArn": "arn:aws:apprunner:us-east-1:123456789012:vpconnector/my-vpc-  
connector/1/3f2eb10e2c494674952026f646844e3d",  
    "VpcConnectorName": "my-vpc-connector",  
    "VpcConnectorRevision": 1,  
    "Subnets": ["subnet-123", "subnet-456"],  
    "SecurityGroups": ["sg-123", "sg-456"],  
    "Status": "INACTIVE",  
    "CreatedAt": "2021-08-18T23:36:45.374Z",  
    "DeletedAt": "2021-09-23T11:42:17.545Z"  
  }  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteVpcIngressConnection

Delete an App Runner VPC Ingress Connection resource that's associated with an App Runner service. The VPC Ingress Connection must be in one of the following states to be deleted:

- AVAILABLE
- FAILED_CREATION
- FAILED_UPDATE
- FAILED_DELETION

Request Syntax

```
{  
  "VpcIngressConnectionArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

VpcIngressConnectionArn

The Amazon Resource Name (ARN) of the App Runner VPC Ingress Connection that you want to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\V|-){1,1011}`

Required: Yes

Response Syntax

```
{
```

```
"VpcIngressConnection": {
  "AccountId": "string",
  "CreatedAt": number,
  "DeletedAt": number,
  "DomainName": "string",
  "IngressVpcConfiguration": {
    "VpcEndpointId": "string",
    "VpcId": "string"
  },
  "ServiceArn": "string",
  "Status": "string",
  "VpcIngressConnectionArn": "string",
  "VpcIngressConnectionName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

VpcIngressConnection

A description of the App Runner VPC Ingress Connection that this request just deleted.

Type: [VpcIngressConnection](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

InvalidStateException

You can't perform this action when the resource is in its current state.

HTTP Status Code: 400

ResourceNotFoundException

A resource doesn't exist for the specified Amazon Resource Name (ARN) in your AWS account.

HTTP Status Code: 400

Examples

Delete a VPC Ingress Connection

This example illustrates how to delete a VPC Ingress Connection.

Sample Request

```
$ aws apprunner delete-vpc-ingress-connection --cli-input-json "`cat`"  
{  
  "VpcIngressConnectionArn": "arn:aws:apprunner:us-  
east-1:123456789012:vpcingressconnection/my-ingress-connection-  
name/3f2eb10e2c494674952026f646844e3d"  
}
```

Sample Response

```
{  
  "AccountId": "123456789012",  
  "CreatedAt": "2022-09-18T23:36:45.374Z",  
  "DeletedAt": "2022-10-18T23:36:45.374Z",  
  "DomainName": "psbqam834h.us-east-1.awsapprunner.com",  
  "IngressVpcConfiguration": {  
    "VpcEndpointId": "vpce-1a2b3c4d",  
    "VpcId": "vpc-4a5b6c7d"  
  },  
  "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/my-service",  
  "Status": "PENDING_DELETION",
```

```
"VpcIngressConnectionArn": "arn:aws:apprunner:us-east-1:123456789012:vpcingressconnection/my-ingress-connection-name/3f2eb10e2c494674952026f646844e3d",
  "VpcIngressConnectionName": "my-ingress-connection-name"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAutoScalingConfiguration

Return a full description of an AWS App Runner automatic scaling configuration resource.

Request Syntax

```
{  
  "AutoScalingConfigurationArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[AutoScalingConfigurationArn](#)

The Amazon Resource Name (ARN) of the App Runner auto scaling configuration that you want a description for.

The ARN can be a full auto scaling configuration ARN, or a partial ARN ending with either `.../name` or `.../name/revision`. If a revision isn't specified, the latest active revision is described.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:([\w|\/|-){1,1011}`

Required: Yes

Response Syntax

```
{  
  "AutoScalingConfiguration": {  
    "AutoScalingConfigurationArn": "string",  
    "AutoScalingConfigurationName": "string",
```

```
"AutoScalingConfigurationRevision": number,  
"CreatedAt": number,  
"DeletedAt": number,  
"HasAssociatedService": boolean,  
"IsDefault": boolean,  
"Latest": boolean,  
"MaxConcurrency": number,  
"MaxSize": number,  
"MinSize": number,  
"Status": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AutoScalingConfiguration

A full description of the App Runner auto scaling configuration that you specified in this request.

Type: [AutoScalingConfiguration](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

ResourceNotFoundException

A resource doesn't exist for the specified Amazon Resource Name (ARN) in your AWS account.

HTTP Status Code: 400

Examples

Describe the latest active revision of an auto scaling configuration

This example illustrates how to get a description of the latest active revision of an App Runner auto scaling configuration. To describe the latest active revision, specify an ARN that ends with the configuration name, without the revision component.

In the example, two revisions exist. Therefore, revision 2 (the latest) is described. The resulting object shows "Latest": true.

Sample Request

```
$ aws apprunner describe-auto-scaling-configuration --cli-input-json "`cat`"
{
  "AutoScalingConfigurationArn": "arn:aws:apprunner:us-
east-1:123456789012:autoscalingconfiguration/high-availability"
}
```

Sample Response

```
{
  "AutoScalingConfiguration": {
    "AutoScalingConfigurationArn": "arn:aws:apprunner:us-
east-1:123456789012:autoscalingconfiguration/high-availability/2/
e76562f50d78042e819fead0f59672e6",
    "AutoScalingConfigurationName": "high-availability",
    "AutoScalingConfigurationRevision": 2,
    "CreatedAt": "2021-02-25T17:42:59Z",
    "Latest": true,
    "Status": "ACTIVE",
    "MaxConcurrency": 30,
    "MaxSize": 25,
    "MinSize": 5
  }
}
```

```
}
```

Describe a specific revision of an auto scaling configuration

This example illustrates how to get a description of a specific revision of an App Runner auto scaling configuration. To describe a specific revision, specify an ARN that includes the revision number.

In the example, several revisions exist and revision 1 is queried. The resulting object shows "Latest": false.

Sample Request

```
$ aws apprunner describe-auto-scaling-configuration --cli-input-json "`cat`"
{
  "AutoScalingConfigurationArn": "arn:aws:apprunner:us-
east-1:123456789012:autoscalingconfiguration/high-availability/1"
}
```

Sample Response

```
{
  "AutoScalingConfiguration": {
    "AutoScalingConfigurationArn": "arn:aws:apprunner:us-
east-1:123456789012:autoscalingconfiguration/high-
availability/1/2f50e7656d7819fead0f59672e68042e",
    "AutoScalingConfigurationName": "high-availability",
    "AutoScalingConfigurationRevision": 1,
    "CreatedAt": "2020-11-03T00:29:17Z",
    "Latest": false,
    "Status": "ACTIVE",
    "MaxConcurrency": 100,
    "MaxSize": 25,
    "MinSize": 5
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeCustomDomains

Return a description of custom domain names that are associated with an AWS App Runner service.

Request Syntax

```
{  
  "MaxResults": number,  
  "NextToken": "string",  
  "ServiceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

The maximum number of results that each response (result page) can include. It's used for a paginated request.

If you don't specify `MaxResults`, the request retrieves all available results in a single response.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 5.

Required: No

NextToken

A token from a previous result page. It's used for a paginated request. The request retrieves the next result page. All other parameter values must be identical to the ones that are specified in the initial request.

If you don't specify `NextToken`, the request retrieves the first result page.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: .*

Required: No

ServiceArn

The Amazon Resource Name (ARN) of the App Runner service that you want associated custom domain names to be described for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w+]*)*: [a-z0-9-\\.]{0,63}: [a-z0-9-\\.]{0,63}: [0-9]{12}: (\w|\/|-){1,1011}`

Required: Yes

Response Syntax

```
{
  "CustomDomains": [
    {
      "CertificateValidationRecords": [
        {
          "Name": "string",
          "Status": "string",
          "Type": "string",
          "Value": "string"
        }
      ],
      "DomainName": "string",
      "EnableWWWSubdomain": boolean,
      "Status": "string"
    }
  ],
  "DNSTarget": "string",
  "NextToken": "string",
  "ServiceArn": "string",
  "VpcDNSTargets": [
    {
      "DomainName": "string",
      "VpcId": "string",
```

```
    "VpcIngressConnectionArn": "string"  
  }  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CustomDomains

A list of descriptions of custom domain names that are associated with the service. In a paginated request, the request returns up to `MaxResults` records per call.

Type: Array of [CustomDomain](#) objects

DNSTarget

The App Runner subdomain of the App Runner service. The associated custom domain names are mapped to this target name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: `.*`

NextToken

The token that you can pass in a subsequent request to get the next result page. It's returned in a paginated request.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: `.*`

ServiceArn

The Amazon Resource Name (ARN) of the App Runner service whose associated custom domain names you want to describe.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\w|-){1,1011}`

VpcDNSTargets

DNS Target records for the custom domains of this Amazon VPC.

Type: Array of [VpcDNSTarget](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServiceErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

ResourceNotFoundException

A resource doesn't exist for the specified Amazon Resource Name (ARN) in your AWS account.

HTTP Status Code: 400

Examples

Get descriptions of custom domain names associated with a service

This example illustrates how to get descriptions and status of the custom domain names associated with an App Runner service.

Sample Request

```
$ aws apprunner describe-custom-domains --cli-input-json "`cat`"
{
  "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/python-
app/8fe1e10304f84fd2b0df550fe98a71fa"
}
```

Sample Response

```
{
  "CustomDomains": [
    {
      "CertificateValidationRecords": [
        {
          "Name": "_70d3f50a94f7c72dc28784cf55db2f6b.example.com",
          "Status": "PENDING_VALIDATION",
          "Type": "CNAME",
          "Value": "_1270c137383c6307b6832db02504c4b0.bsgbmzkfwj.acm-validations.aws."
        },
        {
          "Name": "_287870d3f50a94f7c72dc4cf55db2f6b.www.example.com",
          "Status": "PENDING_VALIDATION",
          "Type": "CNAME",
          "Value": "_832db01270c137383c6307b62504c4b0.mzkbsgbfwj.acm-validations.aws."
        }
      ],
      "DomainName": "example.com",
      "EnableWWWSubdomain": true,
      "Status": "PENDING_CERTIFICATE_DNS_VALIDATION"
    },
    {
      "CertificateValidationRecords": [
        {
          "Name": "_a94f784c70d3f507c72dc28f55db2f6b.deals.example.com",
          "Status": "SUCCESS",
          "Type": "CNAME",
          "Value": "_2db02504c1270c137383c6307b6834b0.bsgbmzkfwj.acm-validations.aws."
        }
      ],
      "DomainName": "deals.example.com",
      "EnableWWWSubdomain": false,
      "Status": "ACTIVE"
    }
  ]
}
```

```
    }
  ],
  "DNSTarget": "psbqam834h.us-east-1.awsapprunner.com",
  "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/python-
app/8fe1e10304f84fd2b0df550fe98a71fa",
  "VpcDNSTargets": [
    {
      "DomainName": "psbqam834h.us-east-1.awsapprunner.com",
      "VpcId": "vpc-4a5b6c7d",
      "VpcIngressConnectionArn": "arn:aws:apprunner:us-
east-1:123456789012:vpcingressconnection/my-ingress-connection-
name/3f2eb10e2c494674952026f646844e3d"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeObservabilityConfiguration

Return a full description of an AWS App Runner observability configuration resource.

Request Syntax

```
{  
  "ObservabilityConfigurationArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ObservabilityConfigurationArn](#)

The Amazon Resource Name (ARN) of the App Runner observability configuration that you want a description for.

The ARN can be a full observability configuration ARN, or a partial ARN ending with either `.../name` or `.../name/revision`. If a revision isn't specified, the latest active revision is described.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:[\w|\/|-]{1,1011}`

Required: Yes

Response Syntax

```
{  
  "ObservabilityConfiguration": {  
    "CreatedAt": number,  
    "DeletedAt": number,  
  }
```

```
"Latest": boolean,
"ObservabilityConfigurationArn": "string",
"ObservabilityConfigurationName": "string",
"ObservabilityConfigurationRevision": number,
"Status": "string",
"TraceConfiguration": {
  "Vendor": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ObservabilityConfiguration

A full description of the App Runner observability configuration that you specified in this request.

Type: [ObservabilityConfiguration](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServiceErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

ResourceNotFoundException

A resource doesn't exist for the specified Amazon Resource Name (ARN) in your AWS account.

HTTP Status Code: 400

Examples

Describe the latest active revision of an observability configuration

This example illustrates how to get a description of the latest active revision of an App Runner observability configuration. To describe the latest active revision, specify an ARN that ends with the configuration name, without the revision component.

In the example, two revisions exist. Therefore, revision 2 (the latest) is described. The resulting object shows "Latest": true.

Note

The two revisions in our examples are identical, because App Runner doesn't yet support enough observability functionality to demonstrate two significantly different revisions (for example, multiple tracing vendors). We're including the two examples only to demonstrate the revisioning behavior during retrieval.

Sample Request

```
$ aws apprunner describe-observability-configuration --cli-input-json "`cat`"  
{  
  "ObservabilityConfigurationArn": "arn:aws:apprunner:us-  
east-1:123456789012:observabilityconfiguration/xray-tracing"  
}
```

Sample Response

```
{  
  "ObservabilityConfiguration": {  
    "ObservabilityConfigurationArn": "arn:aws:apprunner:us-  
east-1:123456789012:observabilityconfiguration/xray-tracing/2/  
e76562f50d78042e819fead0f59672e6",  
    "ObservabilityConfigurationName": "xray-tracing",  
    "ObservabilityConfigurationRevision": 2,  
    "CreatedAt": "2021-02-25T17:42:59Z",  
    "Latest": true,  
  }  
}
```



```
    "Status": "ACTIVE",
    "TraceConfiguration": {
      "Vendor": "AWSXRAY"
    }
  }
}
```

Describe a specific revision of an observability configuration

This example illustrates how to get a description of a specific revision of an App Runner observability configuration. To describe a specific revision, specify an ARN that includes the revision number.

In the example, several revisions exist and revision 1 is queried. The resulting object shows "Latest": false.

Sample Request

```
$ aws apprunner describe-observability-configuration --cli-input-json "`cat`"
{
  "ObservabilityConfigurationArn": "arn:aws:apprunner:us-
east-1:123456789012:observabilityconfiguration/xray-tracing/1"
}
```

Sample Response

```
{
  "ObservabilityConfiguration": {
    "ObservabilityConfigurationArn": "arn:aws:apprunner:us-
east-1:123456789012:observabilityconfiguration/xray-
tracing/1/2f50e7656d7819fead0f59672e68042e",
    "ObservabilityConfigurationName": "xray-tracing",
    "ObservabilityConfigurationRevision": 1,
    "CreatedAt": "2020-11-03T00:29:17Z",
    "Latest": false,
    "Status": "ACTIVE",
    "TraceConfiguration": {
      "Vendor": "AWSXRAY"
    }
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeService

Return a full description of an AWS App Runner service.

Request Syntax

```
{
  "ServiceArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ServiceArn

The Amazon Resource Name (ARN) of the App Runner service that you want a description for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\V|-){1,1011}`

Required: Yes

Response Syntax

```
{
  "Service": {
    "AutoScalingConfigurationSummary": {
      "AutoScalingConfigurationArn": "string",
      "AutoScalingConfigurationName": "string",
      "AutoScalingConfigurationRevision": number,
      "CreatedAt": number,
      "HasAssociatedService": boolean,
      "IsDefault": boolean,
      "Status": "string"
    },
  },
}
```

```

    "CreatedAt": number,
    "DeletedAt": number,
    "EncryptionConfiguration": {
        "KmsKey": "string"
    },
    "HealthCheckConfiguration": {
        "HealthyThreshold": number,
        "Interval": number,
        "Path": "string",
        "Protocol": "string",
        "Timeout": number,
        "UnhealthyThreshold": number
    },
    "InstanceConfiguration": {
        "Cpu": "string",
        "InstanceRoleArn": "string",
        "Memory": "string"
    },
    "NetworkConfiguration": {
        "EgressConfiguration": {
            "EgressType": "string",
            "VpcConnectorArn": "string"
        },
        "IngressConfiguration": {
            "IsPubliclyAccessible": boolean
        },
        "IpAddressType": "string"
    },
    "ObservabilityConfiguration": {
        "ObservabilityConfigurationArn": "string",
        "ObservabilityEnabled": boolean
    },
    "ServiceArn": "string",
    "ServiceId": "string",
    "ServiceName": "string",
    "ServiceUrl": "string",
    "SourceConfiguration": {
        "AuthenticationConfiguration": {
            "AccessRoleArn": "string",
            "ConnectionArn": "string"
        },
        "AutoDeploymentsEnabled": boolean,
        "CodeRepository": {
            "CodeConfiguration": {

```

```

    "CodeConfigurationValues": {
      "BuildCommand": "string",
      "Port": "string",
      "Runtime": "string",
      "RuntimeEnvironmentSecrets": {
        "string" : "string"
      },
      "RuntimeEnvironmentVariables": {
        "string" : "string"
      },
      "StartCommand": "string"
    },
    "ConfigurationSource": "string"
  },
  "RepositoryUrl": "string",
  "SourceCodeVersion": {
    "Type": "string",
    "Value": "string"
  },
  "SourceDirectory": "string"
},
"ImageRepository": {
  "ImageConfiguration": {
    "Port": "string",
    "RuntimeEnvironmentSecrets": {
      "string" : "string"
    },
    "RuntimeEnvironmentVariables": {
      "string" : "string"
    },
    "StartCommand": "string"
  },
  "ImageIdentifier": "string",
  "ImageRepositoryType": "string"
}
},
"Status": "string",
"UpdatedAt": number
}
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Service

A full description of the App Runner service that you specified in this request.

Type: [Service](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

ResourceNotFoundException

A resource doesn't exist for the specified Amazon Resource Name (ARN) in your AWS account.

HTTP Status Code: 400

Examples

Describe a service

This example illustrates how to get a description of an App Runner service.

Sample Request

```
$ aws apprunner describe-service --cli-input-json "`cat`"
{
  "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/python-
app/8fe1e10304f84fd2b0df550fe98a71fa"
}
```

Sample Response

```
{
  "Service": {
    "CreatedAt": "2020-11-20T19:05:25Z",
    "UpdatedAt": "2020-11-23T12:41:37Z",
    "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/python-
app/8fe1e10304f84fd2b0df550fe98a71fa",
    "ServiceId": "8fe1e10304f84fd2b0df550fe98a71fa",
    "ServiceName": "python-app",
    "ServiceUrl": "psbqam834h.us-east-1.awsapprunner.com",
    "SourceConfiguration": {
      "AuthenticationConfiguration": {
        "ConnectionArn": "arn:aws:apprunner:us-east-1:123456789012:connection/my-
github-connection/e7656250f67242d7819feade6800f59e"
      },
      "AutoDeploymentsEnabled": true,
      "CodeRepository": {
        "CodeConfiguration": {
          "CodeConfigurationValues": {
            "BuildCommand": "[pip install -r requirements.txt]",
            "Port": "8080",
            "Runtime": "PYTHON_3",
            "RuntimeEnvironmentVariables": [
              {
                "NAME": "Jane"
              }
            ],
            "StartCommand": "python server.py"
          },
          "ConfigurationSource": "Api"
        },
        "RepositoryUrl": "https://github.com/my-account/python-hello",
        "SourceCodeVersion": {
          "Type": "BRANCH",
```

```
        "Value": "main"
      }
    },
    "Status": "RUNNING",
    "InstanceConfiguration": {
      "CPU": "1 vCPU",
      "Memory": "3 GB"
    },
    "NetworkConfiguration": {
      "IpAddressType": "IPv4",
      "EgressConfiguration": {
        "EgressType": "DEFAULT"
      },
      "IngressConfiguration": {
        "IsPubliclyAccessible": true
      }
    },
    "ObservabilityConfiguration": {
      "ObservabilityEnabled": false
    }
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeVpcConnector

Return a description of an AWS App Runner VPC connector resource.

Request Syntax

```
{  
  "VpcConnectorArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

VpcConnectorArn

The Amazon Resource Name (ARN) of the App Runner VPC connector that you want a description for.

The ARN must be a full VPC connector ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\V|-){1,1011}`

Required: Yes

Response Syntax

```
{  
  "VpcConnector": {  
    "CreatedAt": number,  
    "DeletedAt": number,  
    "SecurityGroups": [ "string" ],  
  }
```

```
"Status": "string",
"Subnets": [ "string" ],
"VpcConnectorArn": "string",
"VpcConnectorName": "string",
"VpcConnectorRevision": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

VpcConnector

A description of the App Runner VPC connector that you specified in this request.

Type: [VpcConnector](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServiceErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

ResourceNotFoundException

A resource doesn't exist for the specified Amazon Resource Name (ARN) in your AWS account.

HTTP Status Code: 400

Examples

Describe a VPC connector

This example illustrates how to get a description of an App Runner VPC connector.

Sample Request

```
$ aws apprunner describe-vpc-connector --cli-input-json "`cat`"
{
  "VpcConnectorArn": "arn:aws:apprunner:us-east-1:123456789012:vpconnector/my-vpc-connector/1/3f2eb10e2c494674952026f646844e3d"
}
```

Sample Response

```
{
  "VpcConnector": {
    "VpcConnectorArn": "arn:aws:apprunner:us-east-1:123456789012:vpconnector/my-vpc-connector/1/3f2eb10e2c494674952026f646844e3d",
    "VpcConnectorName": "my-vpc-connector",
    "VpcConnectorRevision": 1,
    "Subnets": ["subnet-123", "subnet-456"],
    "SecurityGroups": ["sg-123", "sg-456"],
    "Status": "ACTIVE",
    "CreatedAt": "2021-08-18T23:36:45.374Z"
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeVpcIngressConnection

Return a full description of an AWS App Runner VPC Ingress Connection resource.

Request Syntax

```
{  
  "VpcIngressConnectionArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[VpcIngressConnectionArn](#)

The Amazon Resource Name (ARN) of the App Runner VPC Ingress Connection that you want a description for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\V|-){1,1011}`

Required: Yes

Response Syntax

```
{  
  "VpcIngressConnection": {  
    "AccountId": "string",  
    "CreatedAt": number,  
    "DeletedAt": number,  
    "DomainName": "string",  
    "IngressVpcConfiguration": {  
      "VpcEndpointId": "string",
```

```
    "VpcId": "string",
  },
  "ServiceArn": "string",
  "Status": "string",
  "VpcIngressConnectionArn": "string",
  "VpcIngressConnectionName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

VpcIngressConnection

A description of the App Runner VPC Ingress Connection that you specified in this request.

Type: [VpcIngressConnection](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServiceErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

ResourceNotFoundException

A resource doesn't exist for the specified Amazon Resource Name (ARN) in your AWS account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisassociateCustomDomain

Disassociate a custom domain name from an AWS App Runner service.

Certificates tracking domain validity are associated with a custom domain and are stored in [AWS Certificate Manager \(ACM\)](#). These certificates aren't deleted as part of this action. App Runner delays certificate deletion for 30 days after a domain is disassociated from your service.

Request Syntax

```
{  
  "DomainName": "string",  
  "ServiceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[DomainName](#)

The domain name that you want to disassociate from the App Runner service.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [A-Za-z0-9*.-]{1,255}

Required: Yes

[ServiceArn](#)

The Amazon Resource Name (ARN) of the App Runner service that you want to disassociate a custom domain name from.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\/|-){1,1011}`

Required: Yes

Response Syntax

```
{
  "CustomDomain": {
    "CertificateValidationRecords": [
      {
        "Name": "string",
        "Status": "string",
        "Type": "string",
        "Value": "string"
      }
    ],
    "DomainName": "string",
    "EnableWWWSubdomain": boolean,
    "Status": "string"
  },
  "DNSTarget": "string",
  "ServiceArn": "string",
  "VpcDNSTargets": [
    {
      "DomainName": "string",
      "VpcId": "string",
      "VpcIngressConnectionArn": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CustomDomain

A description of the domain name that's being disassociated.

Type: [CustomDomain](#) object

[DNSTarget](#)

The App Runner subdomain of the App Runner service. The disassociated custom domain name was mapped to this target name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: . *

[ServiceArn](#)

The Amazon Resource Name (ARN) of the App Runner service that a custom domain name is disassociated from.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\/|-){1,1011}`

[VpcDNSTargets](#)

DNS Target records for the custom domains of this Amazon VPC.

Type: Array of [VpcDNSTarget](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServiceErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

InvalidStateException

You can't perform this action when the resource is in its current state.

HTTP Status Code: 400

ResourceNotFoundException

A resource doesn't exist for the specified Amazon Resource Name (ARN) in your AWS account.

HTTP Status Code: 400

Examples

Disassociate a domain name from a service

This example illustrates how to disassociate the domain `example.com` from an App Runner service. The call also disassociates the subdomain `www.example.com` that was associated together with the root domain.

Note

`CertificateValidationRecords` is an optional field and returns an empty response for `AssociateCustomDomain` APIs.

Sample Request

```
$ aws apprunner disassociate-custom-domain --cli-input-json "`cat`"  
{  
  "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/python-  
app/8fe1e10304f84fd2b0df550fe98a71fa",  
  "DomainName": "example.com"  
}
```

Sample Response

```
{  
  "DNSTarget": "zg2t7wmhi.us-east-1.awsapprunner.com",  
}
```

```
{
  "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/python-
app/8fe1e10304f84fd2b0df550fe98a71fa",
  "CustomDomain": {
    "DomainName": "example.com",
    "EnableWWWSubdomain": true,
    "Status": "creating"
  },
  "VpcDNSTargets": [
    {
      "DomainName": "psbqam834h.us-east-1.awsapprunner.com",
      "VpcId": "vpc-4a5b6c7d",
      "VpcIngressConnectionArn": "arn:aws:apprunner:us-
east-1:123456789012:vpcingressconnection/my-ingress-connection-
name/3f2eb10e2c494674952026f646844e3d"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAutoScalingConfigurations

Returns a list of active AWS App Runner automatic scaling configurations in your AWS account. You can query the revisions for a specific configuration name or the revisions for all active configurations in your account. You can optionally query only the latest revision of each requested name.

To retrieve a full description of a particular configuration revision, call [DescribeAutoScalingConfiguration](#) and provide one of the ARNs returned by `ListAutoScalingConfigurations`.

Request Syntax

```
{  
  "AutoScalingConfigurationName": "string",  
  "LatestOnly": boolean,  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[AutoScalingConfigurationName](#)

The name of the App Runner auto scaling configuration that you want to list. If specified, App Runner lists revisions that share this name. If not specified, App Runner returns revisions of all active configurations.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 32.

Pattern: `[A-Za-z0-9][A-Za-z0-9\-\_]{3,31}`

Required: No

LatestOnly

Set to `true` to list only the latest revision for each requested configuration name.

Set to `false` to list all revisions for each requested configuration name.

Default: `true`

Type: Boolean

Required: No

MaxResults

The maximum number of results to include in each response (result page). It's used for a paginated request.

If you don't specify `MaxResults`, the request retrieves all available results in a single response.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

A token from a previous result page. It's used for a paginated request. The request retrieves the next result page. All other parameter values must be identical to the ones that are specified in the initial request.

If you don't specify `NextToken`, the request retrieves the first result page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `.*`

Required: No

Response Syntax

```
{
```

```
"AutoScalingConfigurationSummaryList": [  
  {  
    "AutoScalingConfigurationArn": "string",  
    "AutoScalingConfigurationName": "string",  
    "AutoScalingConfigurationRevision": number,  
    "CreatedAt": number,  
    "HasAssociatedService": boolean,  
    "IsDefault": boolean,  
    "Status": "string"  
  }  
],  
"NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AutoScalingConfigurationSummaryList](#)

A list of summary information records for auto scaling configurations. In a paginated request, the request returns up to `MaxResults` records for each call.

Type: Array of [AutoScalingConfigurationSummary](#) objects

[NextToken](#)

The token that you can pass in a subsequent request to get the next result page. It's returned in a paginated request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `.*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

Examples

Paginated listing of App Runner auto scaling configurations

This example illustrates how to list all App Runner auto scaling configurations in your AWS account. Up to five auto scaling configurations are listed in each response. `AutoScalingConfigurationName` and `LatestOnly` aren't specified. Their defaults cause the latest revision of all active configurations to be listed.

In this example, the response includes two results and there aren't additional ones, so no `NextToken` is returned.

Sample Request

```
$ aws apprunner list-auto-scaling-configurations --cli-input-json "`cat`"
{
  "MaxResults": 5
}
```

Sample Response

```
{
  "AutoScalingConfigurationSummaryList": [
    {
      "AutoScalingConfigurationArn": "arn:aws:apprunner:us-
east-1:123456789012:autoscalingconfiguration/high-availability/2/
e76562f50d78042e819fead0f59672e6",
      "AutoScalingConfigurationName": "high-availability",
```

```
    "AutoScalingConfigurationRevision": 2
  },
  {
    "AutoScalingConfigurationArn": "arn:aws:apprunner:us-
east-1:123456789012:autoscalingconfiguration/low-
cost/1/50d7804e7656fead0f59672e62f2e819",
    "AutoScalingConfigurationName": "low-cost",
    "AutoScalingConfigurationRevision": 1
  }
]
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListConnections

Returns a list of AWS App Runner connections that are associated with your AWS account.

Request Syntax

```
{  
  "ConnectionName": "string",  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ConnectionName

If specified, only this connection is returned. If not specified, the result isn't filtered by name.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 32.

Pattern: `[A-Za-z0-9][A-Za-z0-9\-\_]{3,31}`

Required: No

MaxResults

The maximum number of results to include in each response (result page). Used for a paginated request.

If you don't specify `MaxResults`, the request retrieves all available results in a single response.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

A token from a previous result page. Used for a paginated request. The request retrieves the next result page. All other parameter values must be identical to the ones specified in the initial request.

If you don't specify `NextToken`, the request retrieves the first result page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

Response Syntax

```
{
  "ConnectionSummaryList": [
    {
      "ConnectionArn": "string",
      "ConnectionName": "string",
      "CreatedAt": number,
      "ProviderType": "string",
      "Status": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ConnectionSummaryList

A list of summary information records for connections. In a paginated request, the request returns up to `MaxResults` records for each call.

Type: Array of [ConnectionSummary](#) objects

[NextToken](#)

The token that you can pass in a subsequent request to get the next result page. Returned in a paginated request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: . *

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

Examples

List all connections

This example illustrates how to list all App Runner connections in the AWS account.

Sample Request

```
$ aws apprunner list-connections --cli-input-json "`cat`"  
{  
}
```

Sample Response

```
{
  "ConnectionSummaryList": [
    {
      "ConnectionArn": "arn:aws:apprunner:us-east-1:123456789012:connection/my-github-connection",
      "ConnectionName": "my-github-connection",
      "Status": "AVAILABLE",
      "CreatedAt": "2020-11-03T00:32:51Z",
      "ProviderType": "GITHUB"
    },
    {
      "ConnectionArn": "arn:aws:apprunner:us-east-1:123456789012:connection/my-github-org-connection",
      "ConnectionName": "my-github-org-connection",
      "Status": "AVAILABLE",
      "CreatedAt": "2020-11-03T02:54:17Z",
      "ProviderType": "GITHUB"
    }
  ]
}
```

List connection by name

This example illustrates how to list a connection by its name.

Sample Request

```
$ aws apprunner list-connections --cli-input-json "`cat`"
{
  "ConnectionName": "my-github-org-connection"
}
```

Sample Response

```
{
  "ConnectionSummaryList": [
    {
      "ConnectionArn": "arn:aws:apprunner:us-east-1:123456789012:connection/my-github-org-connection",
      "ConnectionName": "my-github-org-connection",

```

```
    "Status": "AVAILABLE",  
    "CreatedAt": "2020-11-03T02:54:17Z",  
    "ProviderType": "GITHUB"  
  }  
]  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListObservabilityConfigurations

Returns a list of active AWS App Runner observability configurations in your AWS account. You can query the revisions for a specific configuration name or the revisions for all active configurations in your account. You can optionally query only the latest revision of each requested name.

To retrieve a full description of a particular configuration revision, call [DescribeObservabilityConfiguration](#) and provide one of the ARNs returned by `ListObservabilityConfigurations`.

Request Syntax

```
{  
  "LatestOnly": boolean,  
  "MaxResults": number,  
  "NextToken": "string",  
  "ObservabilityConfigurationName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[LatestOnly](#)

Set to `true` to list only the latest revision for each requested configuration name.

Set to `false` to list all revisions for each requested configuration name.

Default: `true`

Type: Boolean

Required: No

[MaxResults](#)

The maximum number of results to include in each response (result page). It's used for a paginated request.

If you don't specify `MaxResults`, the request retrieves all available results in a single response.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

A token from a previous result page. It's used for a paginated request. The request retrieves the next result page. All other parameter values must be identical to the ones that are specified in the initial request.

If you don't specify `NextToken`, the request retrieves the first result page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `. *`

Required: No

ObservabilityConfigurationName

The name of the App Runner observability configuration that you want to list. If specified, App Runner lists revisions that share this name. If not specified, App Runner returns revisions of all active configurations.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 32.

Pattern: `[A-Za-z0-9][A-Za-z0-9\-\_]{3,31}`

Required: No

Response Syntax

```
{  
  "NextToken": "string",
```

```
"ObservabilityConfigurationSummaryList": [  
  {  
    "ObservabilityConfigurationArn": "string",  
    "ObservabilityConfigurationName": "string",  
    "ObservabilityConfigurationRevision": number  
  }  
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken](#)

The token that you can pass in a subsequent request to get the next result page. It's returned in a paginated request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: . *

[ObservabilityConfigurationSummaryList](#)

A list of summary information records for observability configurations. In a paginated request, the request returns up to `MaxResults` records for each call.

Type: Array of [ObservabilityConfigurationSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServiceErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

Examples

Paginated listing of App Runner observability configurations

This example illustrates how to list all App Runner observability configurations in your AWS account. Up to five observability configurations are listed in each response. We set `LatestOnly` to `false` to get all revisions of all active configurations.

In this example, the response includes two results and there aren't additional ones, so no `NextToken` is returned.

Sample Request

```
$ aws apprunner list-observability-configurations --cli-input-json "`cat`"
{
  "LatestOnly": false,
  "MaxResults": 5
}
```

Sample Response

```
{
  "ObservabilityConfigurationSummaryList": [
    {
      "ObservabilityConfigurationArn": "arn:aws:apprunner:us-east-1:123456789012:observabilityconfiguration/xray-tracing/1/2f50e7656d7819fead0f59672e68042e",
      "ObservabilityConfigurationName": "xray-tracing",
      "ObservabilityConfigurationRevision": 1
    },
    {
      "ObservabilityConfigurationArn": "arn:aws:apprunner:us-east-1:123456789012:observabilityconfiguration/xray-tracing/2/e76562f50d78042e819fead0f59672e6",

```

```
    "ObservabilityConfigurationName": "xray-tracing",  
    "ObservabilityConfigurationRevision": 2  
  }  
]  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListOperations

Return a list of operations that occurred on an AWS App Runner service.

The resulting list of [OperationSummary](#) objects is sorted in reverse chronological order. The first object on the list represents the last started operation.

Request Syntax

```
{
  "MaxResults": number,
  "NextToken": "string",
  "ServiceArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

The maximum number of results to include in each response (result page). It's used for a paginated request.

If you don't specify `MaxResults`, the request retrieves all available results in a single response.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 20.

Required: No

NextToken

A token from a previous result page. It's used for a paginated request. The request retrieves the next result page. All other parameter values must be identical to the ones specified in the initial request.

If you don't specify `NextToken`, the request retrieves the first result page.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: . *

Required: No

ServiceArn

The Amazon Resource Name (ARN) of the App Runner service that you want a list of operations for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:([\w|\w|-){1,1011}

Required: Yes

Response Syntax

```
{
  "NextToken": "string",
  "OperationSummaryList": [
    {
      "EndedAt": number,
      "Id": "string",
      "StartedAt": number,
      "Status": "string",
      "TargetArn": "string",
      "Type": "string",
      "UpdatedAt": number
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token that you can pass in a subsequent request to get the next result page. It's returned in a paginated request.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: . *

OperationSummaryList

A list of operation summary information records. In a paginated request, the request returns up to `MaxResults` records for each call.

Type: Array of [OperationSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

ResourceNotFoundException

A resource doesn't exist for the specified Amazon Resource Name (ARN) in your AWS account.

HTTP Status Code: 400

Examples

List operations that occurred on a service

This example illustrates how to list all operations that occurred on an App Runner service so far. In this example, the service is new and only a single operation of type `CREATE_SERVICE` has occurred.

Sample Request

```
$ aws apprunner list-operations --cli-input-json "`cat`"
{
  "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/python-
app/8fe1e10304f84fd2b0df550fe98a71fa"
}
```

Sample Response

```
{
  "OperationSummaryList": [
    {
      "EndedAt": 1606156217,
      "Id": "17fe9f55-7e91-4097-b243-fcabbb69a4cf",
      "StartedAt": 1606156014,
      "Status": "SUCCEEDED",
      "TargetArn": "arn:aws:apprunner:us-east-1:123456789012:service/python-
app/8fe1e10304f84fd2b0df550fe98a71fa",
      "Type": "CREATE_SERVICE",
      "UpdatedAt": 1606156217
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListServices

Returns a list of running AWS App Runner services in your AWS account.

Request Syntax

```
{  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

The maximum number of results to include in each response (result page). It's used for a paginated request.

If you don't specify `MaxResults`, the request retrieves all available results in a single response.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 20.

Required: No

NextToken

A token from a previous result page. Used for a paginated request. The request retrieves the next result page. All other parameter values must be identical to the ones specified in the initial request.

If you don't specify `NextToken`, the request retrieves the first result page.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: . *

Required: No

Response Syntax

```
{
  "NextToken": "string",
  "ServiceSummaryList": [
    {
      "CreatedAt": number,
      "ServiceArn": "string",
      "ServiceId": "string",
      "ServiceName": "string",
      "ServiceUrl": "string",
      "Status": "string",
      "UpdatedAt": number
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token that you can pass in a subsequent request to get the next result page. It's returned in a paginated request.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: . *

ServiceSummaryList

A list of service summary information records. In a paginated request, the request returns up to `MaxResults` records for each call.

Type: Array of [ServiceSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

Examples

Paginated listing of App Runner services

This example illustrates how to list all App Runner services in the AWS account. Up to two services are listed in each response. This example shows the first request. The response includes two results and a token that can be used in the next request. When a subsequent response doesn't include a token, all services have been listed.

Sample Request

```
$ aws apprunner list-services --cli-input-json "`cat`"
{
  "MaxResults": 2
}
```

Sample Response

```
{
  "NextToken":
    "eyJDdXN0b211ckFjY291bnRJZCI6IjI3MDIwNTQwMjg0NSIsI1N1cnZpY2VTdGF0dXNDb2RlIjoiUFJPVk1TSU90SU5HI
```

```
"ServiceSummaryList": [  
  {  
    "CreatedAt": "2020-11-20T19:05:25Z",  
    "UpdatedAt": "2020-11-23T12:41:37Z",  
    "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/python-app/8fe1e10304f84fd2b0df550fe98a71fa",  
    "ServiceId": "8fe1e10304f84fd2b0df550fe98a71fa",  
    "ServiceName": "python-app",  
    "ServiceUrl": "psbqam834h.us-east-1.awsapprunner.com",  
    "Status": "RUNNING"  
  },  
  {  
    "CreatedAt": "2020-11-06T23:15:30Z",  
    "UpdatedAt": "2020-11-23T13:21:22Z",  
    "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/golang-container-app/ab8f94cfe29a460fb8760afd2ee87555",  
    "ServiceId": "ab8f94cfe29a460fb8760afd2ee87555",  
    "ServiceName": "golang-container-app",  
    "ServiceUrl": "e2m8rrrx33.us-east-1.awsapprunner.com",  
    "Status": "RUNNING"  
  }  
]  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListServicesForAutoScalingConfiguration

Returns a list of the associated App Runner services using an auto scaling configuration.

Request Syntax

```
{  
  "AutoScalingConfigurationArn": "string",  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AutoScalingConfigurationArn

The Amazon Resource Name (ARN) of the App Runner auto scaling configuration that you want to list the services for.

The ARN can be a full auto scaling configuration ARN, or a partial ARN ending with either `.../name` or `.../name/revision`. If a revision isn't specified, the latest active revision is used.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\w|-){1,1011}`

Required: Yes

MaxResults

The maximum number of results to include in each response (result page). It's used for a paginated request.

If you don't specify `MaxResults`, the request retrieves all available results in a single response.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

A token from a previous result page. It's used for a paginated request. The request retrieves the next result page. All other parameter values must be identical to the ones specified in the initial request.

If you don't specify NextToken, the request retrieves the first result page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: . *

Required: No

Response Syntax

```
{
  "NextToken": "string",
  "ServiceArnList": [ "string" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token that you can pass in a subsequent request to get the next result page. It's returned in a paginated request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: . *

ServiceArnList

A list of service ARN records. In a paginated request, the request returns up to `MaxResults` records for each call.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\w|-){1,1011}`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServiceErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

ResourceNotFoundException

A resource doesn't exist for the specified Amazon Resource Name (ARN) in your AWS account.

HTTP Status Code: 400

Examples

Paginated listing of all App Runner services associated to an auto scaling configuration

This example illustrates how to list all of the App Runner services that are associated with a specific auto scaling configuration. The response includes two results and a token that can be used in the

next request. When a subsequent response doesn't include a token, all associated services have been listed.

Sample Request

```
$ aws apprunner list-services-for-auto-scaling-configuration --cli-input-json "`cat`"  
{  
  "AutoScalingConfigurationArn": "arn:aws:apprunner:us-east-1:123456789012:autoscalingconfiguration/high-availability/2/6a4d47db94434d30a42cab9a00d21d44",  
  "MaxResults": 2  
}
```

Sample Response

```
{  
  "ServiceArnList": [  
    "arn:aws:apprunner:us-east-1:123456789012:service/golang-container-app/e598803c0a7848459f3fd978ef5ed86c",  
    "arn:aws:apprunner:us-east-1:123456789012:service/java-app/b6644b84cd04451faaad27054a70e21a"  
  ],  
  "NextToken":  
    "eyJBdXRvU2NhbgGluZ0NvbmZpZ3VyYXRpb25Bcm4iOiJhcm46YXdzOmFwcHJ1bm5lcjpwcy1lYXN0LTE6MTIzNDU2Nzg5M"  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

List tags that are associated with for an AWS App Runner resource. The response contains a list of tag key-value pairs.

Request Syntax

```
{
  "ResourceArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ResourceArn

The Amazon Resource Name (ARN) of the resource that a tag list is requested for.

It must be the ARN of an App Runner resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\V|-){1,1011}`

Required: Yes

Response Syntax

```
{
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

```
]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Tags](#)

A list of the tag key-value pairs that are associated with the resource.

Type: Array of [Tag](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

InvalidStateException

You can't perform this action when the resource is in its current state.

HTTP Status Code: 400

ResourceNotFoundException

A resource doesn't exist for the specified Amazon Resource Name (ARN) in your AWS account.

HTTP Status Code: 400

Examples

List tags associated with an App Runner service

This example illustrates how to list all the tags that are associated with an App Runner service.

Sample Request

```
$ aws apprunner list-tags-for-resource --cli-input-json "`cat`"
{
  "ResourceArn": "arn:aws:apprunner:us-east-1:123456789012:service/python-
app/8fe1e10304f84fd2b0df550fe98a71fa"
}
```

Sample Response

```
{
  "Tags": [
    {
      "Key": "Department",
      "Value": "Retail"
    },
    {
      "Key": "CustomerId",
      "Value": "56439872357912"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListVpcConnectors

Returns a list of AWS App Runner VPC connectors in your AWS account.

Request Syntax

```
{  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

The maximum number of results to include in each response (result page). It's used for a paginated request.

If you don't specify `MaxResults`, the request retrieves all available results in a single response.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

A token from a previous result page. It's used for a paginated request. The request retrieves the next result page. All other parameter values must be identical to the ones that are specified in the initial request.

If you don't specify `NextToken`, the request retrieves the first result page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `. *`

Required: No

Response Syntax

```
{
  "NextToken": "string",
  "VpcConnectors": [
    {
      "CreatedAt": number,
      "DeletedAt": number,
      "SecurityGroups": [ "string" ],
      "Status": "string",
      "Subnets": [ "string" ],
      "VpcConnectorArn": "string",
      "VpcConnectorName": "string",
      "VpcConnectorRevision": number
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token that you can pass in a subsequent request to get the next result page. It's returned in a paginated request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

VpcConnectors

A list of information records for VPC connectors. In a paginated request, the request returns up to `MaxResults` records for each call.

Type: Array of [VpcConnector](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

Examples

Paginated listing of App Runner VPC connectors

This example illustrates how to list all App Runner VPC connectors in your AWS account. Up to five VPC connectors are listed in each response.

In this example, the response includes one result and there aren't additional ones, so no `NextToken` is returned.

Sample Request

```
$ aws apprunner list-vpc-connectors --cli-input-json "`cat`"
{
  "MaxResults": 5
}
```

Sample Response

```
{
  "VpcConnectors": [
    {
```

```
    "VpcConnectorArn": "arn:aws:apprunner:us-east-1:123456789012:vpccconnector/my-vpc-connector/1/3f2eb10e2c494674952026f646844e3d",
    "VpcConnectorName": "my-vpc-connector",
    "VpcConnectorRevision": 1,
    "Subnets": ["subnet-123", "subnet-456"],
    "SecurityGroups": ["sg-123", "sg-456"],
    "Status": "ACTIVE",
    "CreatedAt": "2021-08-18T23:36:45.374Z"
  }
]
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListVpcIngressConnections

Return a list of App Runner VPC Ingress Connections in your AWS account.

Request Syntax

```
{  
  "Filter": {  
    "ServiceArn": "string",  
    "VpcEndpointId": "string"  
  },  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filter

The VPC Ingress Connections to be listed based on either the Service Arn or Vpc Endpoint Id, or both.

Type: [ListVpcIngressConnectionsFilter](#) object

Required: No

MaxResults

The maximum number of results to include in each response (result page). It's used for a paginated request.

If you don't specify `MaxResults`, the request retrieves all available results in a single response.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

A token from a previous result page. It's used for a paginated request. The request retrieves the next result page. All other parameter values must be identical to the ones that are specified in the initial request.

If you don't specify `NextToken`, the request retrieves the first result page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: . *

Required: No

Response Syntax

```
{
  "NextToken": "string",
  "VpcIngressConnectionSummaryList": [
    {
      "ServiceArn": "string",
      "VpcIngressConnectionArn": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token that you can pass in a subsequent request to get the next result page. It's returned in a paginated request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: . *

VpcIngressConnectionSummaryList

A list of summary information records for VPC Ingress Connections. In a paginated request, the request returns up to `MaxResults` records for each call.

Type: Array of [VpcIngressConnectionSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

Examples

Paginated listing of App Runner VPC Ingress Connections

This example illustrates how to list all App Runner VPC Ingress Connections in your AWS account. Up to five VPC Ingress Connections are listed in each response.

In this example, the response includes one result and there aren't additional ones, so no `NextToken` is returned.

Sample Request

```
$ aws apprunner list-vpc-ingress-connections --cli-input-json "`cat`"  
{  
    "MaxResults": 5
```

```
}
```

Sample Response

```
{
  "VpcIngressConnectionSummaryList": [
    {
      "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/my-
service",
      "VpcIngressConnectionArn": "arn:aws:apprunner:us-
east-1:123456789012:vpcingressconnection/my-ingress-connection-
name/3f2eb10e2c494674952026f646844e3d"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PauseService

Pause an active AWS App Runner service. App Runner reduces compute capacity for the service to zero and loses state (for example, ephemeral storage is removed).

This is an asynchronous operation. On a successful call, you can use the returned `OperationId` and the [ListOperations](#) call to track the operation's progress.

Request Syntax

```
{  
  "ServiceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ServiceArn](#)

The Amazon Resource Name (ARN) of the App Runner service that you want to pause.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\/|-){1,1011}`

Required: Yes

Response Syntax

```
{  
  "OperationId": "string",  
  "Service": {  
    "AutoScalingConfigurationSummary": {  
      "AutoScalingConfigurationArn": "string",  
      "AutoScalingConfigurationName": "string",
```



```

    "AutoScalingConfigurationRevision": number,
    "CreatedAt": number,
    "HasAssociatedService": boolean,
    "IsDefault": boolean,
    "Status": "string"
  },
  "CreatedAt": number,
  "DeletedAt": number,
  "EncryptionConfiguration": {
    "KmsKey": "string"
  },
  "HealthCheckConfiguration": {
    "HealthyThreshold": number,
    "Interval": number,
    "Path": "string",
    "Protocol": "string",
    "Timeout": number,
    "UnhealthyThreshold": number
  },
  "InstanceConfiguration": {
    "Cpu": "string",
    "InstanceRoleArn": "string",
    "Memory": "string"
  },
  "NetworkConfiguration": {
    "EgressConfiguration": {
      "EgressType": "string",
      "VpcConnectorArn": "string"
    },
    "IngressConfiguration": {
      "IsPubliclyAccessible": boolean
    },
    "IpAddressType": "string"
  },
  "ObservabilityConfiguration": {
    "ObservabilityConfigurationArn": "string",
    "ObservabilityEnabled": boolean
  },
  "ServiceArn": "string",
  "ServiceId": "string",
  "ServiceName": "string",
  "ServiceUrl": "string",
  "SourceConfiguration": {
    "AuthenticationConfiguration": {

```

```

    "AccessRoleArn": "string",
    "ConnectionArn": "string"
  },
  "AutoDeploymentsEnabled": boolean,
  "CodeRepository": {
    "CodeConfiguration": {
      "CodeConfigurationValues": {
        "BuildCommand": "string",
        "Port": "string",
        "Runtime": "string",
        "RuntimeEnvironmentSecrets": {
          "string" : "string"
        },
        "RuntimeEnvironmentVariables": {
          "string" : "string"
        },
        "StartCommand": "string"
      },
      "ConfigurationSource": "string"
    },
    "RepositoryUrl": "string",
    "SourceCodeVersion": {
      "Type": "string",
      "Value": "string"
    },
    "SourceDirectory": "string"
  },
  "ImageRepository": {
    "ImageConfiguration": {
      "Port": "string",
      "RuntimeEnvironmentSecrets": {
        "string" : "string"
      },
      "RuntimeEnvironmentVariables": {
        "string" : "string"
      },
      "StartCommand": "string"
    },
    "ImageIdentifier": "string",
    "ImageRepositoryType": "string"
  }
},
"Status": "string",
"UpdatedAt": number

```

```
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

OperationId

The unique ID of the asynchronous operation that this request started. You can use it combined with the [ListOperations](#) call to track the operation's progress.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[1-5][0-9a-fA-F]{3}-[89abAB][0-9a-fA-F]{3}-[0-9a-fA-F]{12}`

Service

A description of the App Runner service that this request just paused.

Type: [Service](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

InvalidStateException

You can't perform this action when the resource is in its current state.

HTTP Status Code: 400

ResourceNotFoundException

A resource doesn't exist for the specified Amazon Resource Name (ARN) in your AWS account.

HTTP Status Code: 400

Examples

Pause a service

This example illustrates pausing an App Runner service.

Sample Request

```
$ aws apprunner pause-service --cli-input-json "`cat`"
{
  "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/python-
app/8fe1e10304f84fd2b0df550fe98a71fa"
}
```

Sample Response

```
{
  "OperationId": "17fe9f55-7e91-4097-b243-fcabbb69a4cf",
  "Service": {
    "CreatedAt": "2020-11-20T19:05:25Z",
    "UpdatedAt": "2020-11-23T12:41:37Z",
    "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/python-
app/8fe1e10304f84fd2b0df550fe98a71fa",
    "ServiceId": "8fe1e10304f84fd2b0df550fe98a71fa",
    "ServiceName": "python-app",
    "ServiceUrl": "psbqam834h.us-east-1.awsapprunner.com",
    "SourceConfiguration": {
      "AuthenticationConfiguration": {
        "ConnectionArn": "arn:aws:apprunner:us-east-1:123456789012:connection/my-
github-connection/e7656250f67242d7819feade6800f59e"
      },

```

```
"AutoDeploymentsEnabled": true,
"CodeRepository": {
  "CodeConfiguration": {
    "CodeConfigurationValues": {
      "BuildCommand": "[pip install -r requirements.txt]",
      "Port": "8080",
      "Runtime": "PYTHON_3",
      "RuntimeEnvironmentVariables": [
        {
          "NAME": "Jane"
        }
      ],
      "StartCommand": "python server.py"
    },
    "ConfigurationSource": "Api"
  },
  "RepositoryUrl": "https://github.com/my-account/python-hello",
  "SourceCodeVersion": {
    "Type": "BRANCH",
    "Value": "main"
  }
},
"Status": "OPERATION_IN_PROGRESS",
"InstanceConfiguration": {
  "CPU": "1 vCPU",
  "Memory": "3 GB"
},
"NetworkConfiguration": {
  "IpAddressType": "IPV4",
  "EgressConfiguration": {
    "EgressType": "DEFAULT"
  },
  "IngressConfiguration": {
    "IsPubliclyAccessible": true
  }
},
"ObservabilityConfiguration": {
  "ObservabilityEnabled": false
}
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ResumeService

Resume an active AWS App Runner service. App Runner provisions compute capacity for the service.

This is an asynchronous operation. On a successful call, you can use the returned `OperationId` and the [ListOperations](#) call to track the operation's progress.

Request Syntax

```
{  
  "ServiceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ServiceArn](#)

The Amazon Resource Name (ARN) of the App Runner service that you want to resume.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\w|-){1,1011}`

Required: Yes

Response Syntax

```
{  
  "OperationId": "string",  
  "Service": {  
    "AutoScalingConfigurationSummary": {  
      "AutoScalingConfigurationArn": "string",  
      "AutoScalingConfigurationName": "string",
```

```

    "AutoScalingConfigurationRevision": number,
    "CreatedAt": number,
    "HasAssociatedService": boolean,
    "IsDefault": boolean,
    "Status": "string"
  },
  "CreatedAt": number,
  "DeletedAt": number,
  "EncryptionConfiguration": {
    "KmsKey": "string"
  },
  "HealthCheckConfiguration": {
    "HealthyThreshold": number,
    "Interval": number,
    "Path": "string",
    "Protocol": "string",
    "Timeout": number,
    "UnhealthyThreshold": number
  },
  "InstanceConfiguration": {
    "Cpu": "string",
    "InstanceRoleArn": "string",
    "Memory": "string"
  },
  "NetworkConfiguration": {
    "EgressConfiguration": {
      "EgressType": "string",
      "VpcConnectorArn": "string"
    },
    "IngressConfiguration": {
      "IsPubliclyAccessible": boolean
    },
    "IpAddressType": "string"
  },
  "ObservabilityConfiguration": {
    "ObservabilityConfigurationArn": "string",
    "ObservabilityEnabled": boolean
  },
  "ServiceArn": "string",
  "ServiceId": "string",
  "ServiceName": "string",
  "ServiceUrl": "string",
  "SourceConfiguration": {
    "AuthenticationConfiguration": {

```



```

    "AccessRoleArn": "string",
    "ConnectionArn": "string"
  },
  "AutoDeploymentsEnabled": boolean,
  "CodeRepository": {
    "CodeConfiguration": {
      "CodeConfigurationValues": {
        "BuildCommand": "string",
        "Port": "string",
        "Runtime": "string",
        "RuntimeEnvironmentSecrets": {
          "string" : "string"
        },
        "RuntimeEnvironmentVariables": {
          "string" : "string"
        },
        "StartCommand": "string"
      },
      "ConfigurationSource": "string"
    },
    "RepositoryUrl": "string",
    "SourceCodeVersion": {
      "Type": "string",
      "Value": "string"
    },
    "SourceDirectory": "string"
  },
  "ImageRepository": {
    "ImageConfiguration": {
      "Port": "string",
      "RuntimeEnvironmentSecrets": {
        "string" : "string"
      },
      "RuntimeEnvironmentVariables": {
        "string" : "string"
      },
      "StartCommand": "string"
    },
    "ImageIdentifier": "string",
    "ImageRepositoryType": "string"
  }
},
"Status": "string",
"UpdatedAt": number

```

```
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

OperationId

The unique ID of the asynchronous operation that this request started. You can use it combined with the [ListOperations](#) call to track the operation's progress.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[1-5][0-9a-fA-F]{3}-[89abAB][0-9a-fA-F]{3}-[0-9a-fA-F]{12}`

Service

A description of the App Runner service that this request just resumed.

Type: [Service](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

InvalidStateException

You can't perform this action when the resource is in its current state.

HTTP Status Code: 400

ResourceNotFoundException

A resource doesn't exist for the specified Amazon Resource Name (ARN) in your AWS account.

HTTP Status Code: 400

Examples

Resume a service

This example illustrates how to resume an App Runner service.

Sample Request

```
$ aws apprunner resume-service --cli-input-json "`cat`"
{
  "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/python-
app/8fe1e10304f84fd2b0df550fe98a71fa"
}
```

Sample Response

```
{
  "OperationId": "17fe9f55-7e91-4097-b243-fcabbb69a4cf",
  "Service": {
    "CreatedAt": "2020-11-20T19:05:25Z",
    "UpdatedAt": "2020-11-23T12:41:37Z",
    "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/python-
app/8fe1e10304f84fd2b0df550fe98a71fa",
    "ServiceId": "8fe1e10304f84fd2b0df550fe98a71fa",
    "ServiceName": "python-app",
    "ServiceUrl": "psbqam834h.us-east-1.awsapprunner.com",
    "SourceConfiguration": {
      "AuthenticationConfiguration": {
        "ConnectionArn": "arn:aws:apprunner:us-east-1:123456789012:connection/my-
github-connection/e7656250f67242d7819feade6800f59e"
      },

```

```
"AutoDeploymentsEnabled": true,
"CodeRepository": {
  "CodeConfiguration": {
    "CodeConfigurationValues": {
      "BuildCommand": "[pip install -r requirements.txt]",
      "Port": "8080",
      "Runtime": "PYTHON_3",
      "RuntimeEnvironmentVariables": [
        {
          "NAME": "Jane"
        }
      ],
      "StartCommand": "python server.py"
    },
    "ConfigurationSource": "Api"
  },
  "RepositoryUrl": "https://github.com/my-account/python-hello",
  "SourceCodeVersion": {
    "Type": "BRANCH",
    "Value": "main"
  }
},
"Status": "OPERATION_IN_PROGRESS",
"InstanceConfiguration": {
  "CPU": "1 vCPU",
  "Memory": "3 GB"
},
"NetworkConfiguration": {
  "IpAddressType": "IPV4",
  "EgressConfiguration": {
    "EgressType": "DEFAULT"
  },
  "IngressConfiguration": {
    "IsPubliclyAccessible": true
  }
},
"ObservabilityConfiguration": {
  "ObservabilityEnabled": false
}
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartDeployment

Initiate a manual deployment of the latest commit in a source code repository or the latest image in a source image repository to an AWS App Runner service.

For a source code repository, App Runner retrieves the commit and builds a Docker image. For a source image repository, App Runner retrieves the latest Docker image. In both cases, App Runner then deploys the new image to your service and starts a new container instance.

This is an asynchronous operation. On a successful call, you can use the returned `OperationId` and the [ListOperations](#) call to track the operation's progress.

Request Syntax

```
{  
  "ServiceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ServiceArn](#)

The Amazon Resource Name (ARN) of the App Runner service that you want to manually deploy to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\V|-){1,1011}`

Required: Yes

Response Syntax

```
{
```

```
"OperationId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[OperationId](#)

The unique ID of the asynchronous operation that this request started. You can use it combined with the [ListOperations](#) call to track the operation's progress.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[1-5][0-9a-fA-F]{3}-[89abAB][0-9a-fA-F]{3}-[0-9a-fA-F]{12}`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServiceErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

ResourceNotFoundException

A resource doesn't exist for the specified Amazon Resource Name (ARN) in your AWS account.

HTTP Status Code: 400

Examples

Initiate a manual deployment

This example illustrates how to perform a manual deployment to an App Runner service.

Sample Request

```
$ aws apprunner start-deployment --cli-input-json "`cat`"  
{  
  "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/python-  
app/8fe1e10304f84fd2b0df550fe98a71fa"  
}
```

Sample Response

```
{  
  "OperationId": "853a7d5b-fc9f-4730-831b-fd8037ab832a"  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Add tags to, or update the tag values of, an App Runner resource. A tag is a key-value pair.

Request Syntax

```
{
  "ResourceArn": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ResourceArn

The Amazon Resource Name (ARN) of the resource that you want to update tags for.

It must be the ARN of an App Runner resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\/|-){1,1011}`

Required: Yes

Tags

A list of tag key-value pairs to add or update. If a key is new to the resource, the tag is added with the provided value. If a key is already associated with the resource, the value of the tag is updated.

Type: Array of [Tag](#) objects

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

InvalidStateException

You can't perform this action when the resource is in its current state.

HTTP Status Code: 400

ResourceNotFoundException

A resource doesn't exist for the specified Amazon Resource Name (ARN) in your AWS account.

HTTP Status Code: 400

Examples

Add tags to an App Runner service

This example illustrates how to add two tags to an App Runner service.

Sample Request

```
$ aws apprunner tag-resource --cli-input-json "`cat`"
{
  "ResourceArn": "arn:aws:apprunner:us-east-1:123456789012:service/python-
app/8fe1e10304f84fd2b0df550fe98a71fa",
  "Tags": [
    {
      "Key": "Department",
      "Value": "Retail"
    },
    {
      "Key": "CustomerId",
      "Value": "56439872357912"
    }
  ]
}
```

Sample Response

```
{
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Remove tags from an App Runner resource.

Request Syntax

```
{  
  "ResourceArn": "string",  
  "TagKeys": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ResourceArn](#)

The Amazon Resource Name (ARN) of the resource that you want to remove tags from.

It must be the ARN of an App Runner resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\V|-){1,1011}`

Required: Yes

[TagKeys](#)

A list of tag keys that you want to remove.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^(?!aws:).+`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

InvalidStateException

You can't perform this action when the resource is in its current state.

HTTP Status Code: 400

ResourceNotFoundException

A resource doesn't exist for the specified Amazon Resource Name (ARN) in your AWS account.

HTTP Status Code: 400

Examples

Remove tags from an App Runner service

This example illustrates how to remove two tags from an App Runner service.

Sample Request

```
$ aws apprunner untag-resource --cli-input-json "`cat`"  
{
```

```
"ResourceArn": "arn:aws:apprunner:us-east-1:123456789012:service/python-
app/8fe1e10304f84fd2b0df550fe98a71fa",
"TagKeys": [
  "Department",
  "CustomerId"
]
```

Sample Response

```
{
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateDefaultAutoScalingConfiguration

Update an auto scaling configuration to be the default. The existing default auto scaling configuration will be set to non-default automatically.

Request Syntax

```
{  
  "AutoScalingConfigurationArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[AutoScalingConfigurationArn](#)

The Amazon Resource Name (ARN) of the App Runner auto scaling configuration that you want to set as the default.

The ARN can be a full auto scaling configuration ARN, or a partial ARN ending with either `.../name` or `.../name/revision`. If a revision isn't specified, the latest active revision is set as the default.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\V|-){1,1011}`

Required: Yes

Response Syntax

```
{
```



```
"AutoScalingConfiguration": {  
  "AutoScalingConfigurationArn": "string",  
  "AutoScalingConfigurationName": "string",  
  "AutoScalingConfigurationRevision": number,  
  "CreatedAt": number,  
  "DeletedAt": number,  
  "HasAssociatedService": boolean,  
  "IsDefault": boolean,  
  "Latest": boolean,  
  "MaxConcurrency": number,  
  "MaxSize": number,  
  "MinSize": number,  
  "Status": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AutoScalingConfiguration](#)

A description of the App Runner auto scaling configuration that was set as default.

Type: [AutoScalingConfiguration](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

ResourceNotFoundException

A resource doesn't exist for the specified Amazon Resource Name (ARN) in your AWS account.

HTTP Status Code: 400

Examples

Update the latest active revision of an auto scaling configuration to be the default

This example illustrates how to update the latest active revision of an App Runner auto scaling configuration to be the default. To designate the latest active revision as the default, specify an ARN that ends with the configuration name, without the revision component.

In the example, two revisions exist. Therefore, revision 2, (the latest revision), is set as the default. The resulting object shows "IsDefault": true and "Latest": true.

Sample Request

```
$ aws apprunner update-default-auto-scaling-configuration --cli-input-json "`cat`"  
{  
  "AutoScalingConfigurationArn": "arn:aws:apprunner:us-  
east-1:123456789012:autoscalingconfiguration/high-availability"  
}
```

Sample Response

```
{  
  "AutoScalingConfiguration": {  
    "AutoScalingConfigurationArn": "arn:aws:apprunner:us-  
east-1:123456789012:autoscalingconfiguration/high-  
availability/2/6a4d47db94434d30a42cab9a00d21d44",  
    "AutoScalingConfigurationName": "high-availability",  
    "AutoScalingConfigurationRevision": 2,  
    "Latest": true,  
    "Status": "active",  
    "MaxConcurrency": 100,  
    "MinSize": 1,  
    "MaxSize": 25,  
    "CreatedAt": "2023-09-01T00:00:00Z",
```

```
    "HasAssociatedService": false,  
    "IsDefault": true  
  }  
}
```

Update a specific revision of an auto scaling configuration to be the default

This example illustrates how to update a specific revision of an App Runner auto scaling configuration to be the default. To designate a specific revision as the default, specify an ARN that includes the revision number.

In the example, several revisions exist, and revision 1 is set as the default. The resulting object shows "IsDefault": true and "Latest": false.

Sample Request

```
$ aws apprunner update-default-auto-scaling-configuration --cli-input-json "`cat`"  
{  
  "AutoScalingConfigurationArn": "arn:aws:apprunner:us-  
east-1:123456789012:autoscalingconfiguration/high-availability/1"  
}
```

Sample Response

```
{  
  "AutoScalingConfiguration": {  
    "AutoScalingConfigurationArn": "arn:aws:apprunner:us-  
east-1:123456789012:autoscalingconfiguration/high-availability/1/  
d2321df129c8440da8c464af7ebcd887",  
    "AutoScalingConfigurationName": "high-availability",  
    "AutoScalingConfigurationRevision": 1,  
    "Latest": false,  
    "Status": "active",  
    "MaxConcurrency": 100,  
    "MinSize": 1,  
    "MaxSize": 25,  
    "CreatedAt": "2023-09-01T00:00:00Z",  
    "HasAssociatedService": false,  
    "IsDefault": true  
  }  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateService

Update an AWS App Runner service. You can update the source configuration and instance configuration of the service. You can also update the ARN of the auto scaling configuration resource that's associated with the service. However, you can't change the name or the encryption configuration of the service. These can be set only when you create the service.

To update the tags applied to your service, use the separate actions [TagResource](#) and [UntagResource](#).

This is an asynchronous operation. On a successful call, you can use the returned `OperationId` and the [ListOperations](#) call to track the operation's progress.

Request Syntax

```
{
  "AutoScalingConfigurationArn": "string",
  "HealthCheckConfiguration": {
    "HealthyThreshold": number,
    "Interval": number,
    "Path": "string",
    "Protocol": "string",
    "Timeout": number,
    "UnhealthyThreshold": number
  },
  "InstanceConfiguration": {
    "Cpu": "string",
    "InstanceRoleArn": "string",
    "Memory": "string"
  },
  "NetworkConfiguration": {
    "EgressConfiguration": {
      "EgressType": "string",
      "VpcConnectorArn": "string"
    },
    "IngressConfiguration": {
      "IsPubliclyAccessible": boolean
    },
    "IpAddressType": "string"
  },
  "ObservabilityConfiguration": {
    "ObservabilityConfigurationArn": "string",
```

```

    "ObservabilityEnabled": boolean
  },
  "ServiceArn": "string",
  "SourceConfiguration": {
    "AuthenticationConfiguration": {
      "AccessRoleArn": "string",
      "ConnectionArn": "string"
    },
    "AutoDeploymentsEnabled": boolean,
    "CodeRepository": {
      "CodeConfiguration": {
        "CodeConfigurationValues": {
          "BuildCommand": "string",
          "Port": "string",
          "Runtime": "string",
          "RuntimeEnvironmentSecrets": {
            "string" : "string"
          },
          "RuntimeEnvironmentVariables": {
            "string" : "string"
          },
          "StartCommand": "string"
        },
        "ConfigurationSource": "string"
      },
      "RepositoryUrl": "string",
      "SourceCodeVersion": {
        "Type": "string",
        "Value": "string"
      },
      "SourceDirectory": "string"
    },
    "ImageRepository": {
      "ImageConfiguration": {
        "Port": "string",
        "RuntimeEnvironmentSecrets": {
          "string" : "string"
        },
        "RuntimeEnvironmentVariables": {
          "string" : "string"
        },
        "StartCommand": "string"
      },
      "ImageIdentifier": "string",

```

```
    "ImageRepositoryType": "string"  
  }  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[AutoScalingConfigurationArn](#)

The Amazon Resource Name (ARN) of an App Runner automatic scaling configuration resource that you want to associate with the App Runner service.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\.]{0,63}:[a-z0-9-\.]{0,63}:[0-9]{12}:(\w|\/|-){1,1011}`

Required: No

[HealthCheckConfiguration](#)

The settings for the health check that AWS App Runner performs to monitor the health of the App Runner service.

Type: [HealthCheckConfiguration](#) object

Required: No

[InstanceConfiguration](#)

The runtime configuration to apply to instances (scaling units) of your service.

Type: [InstanceConfiguration](#) object

Required: No

[NetworkConfiguration](#)

Configuration settings related to network traffic of the web application that the App Runner service runs.

Type: [NetworkConfiguration](#) object

Required: No

[ObservabilityConfiguration](#)

The observability configuration of your service.

Type: [ServiceObservabilityConfiguration](#) object

Required: No

[ServiceArn](#)

The Amazon Resource Name (ARN) of the App Runner service that you want to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\/|-){1,1011}`

Required: Yes

[SourceConfiguration](#)

The source configuration to apply to the App Runner service.

You can change the configuration of the code or image repository that the service uses.

However, you can't switch from code to image or the other way around. This means that you must provide the same structure member of `SourceConfiguration` that you originally included when you created the service. Specifically, you can include either `CodeRepository` or `ImageRepository`. To update the source configuration, set the values to members of the structure that you include.

Type: [SourceConfiguration](#) object

Required: No

Response Syntax

```
{
  "OperationId": "string",
  "Service": {
```



```

    "AutoScalingConfigurationSummary": {
      "AutoScalingConfigurationArn": "string",
      "AutoScalingConfigurationName": "string",
      "AutoScalingConfigurationRevision": number,
      "CreatedAt": number,
      "HasAssociatedService": boolean,
      "IsDefault": boolean,
      "Status": "string"
    },
    "CreatedAt": number,
    "DeletedAt": number,
    "EncryptionConfiguration": {
      "KmsKey": "string"
    },
    "HealthCheckConfiguration": {
      "HealthyThreshold": number,
      "Interval": number,
      "Path": "string",
      "Protocol": "string",
      "Timeout": number,
      "UnhealthyThreshold": number
    },
    "InstanceConfiguration": {
      "Cpu": "string",
      "InstanceRoleArn": "string",
      "Memory": "string"
    },
    "NetworkConfiguration": {
      "EgressConfiguration": {
        "EgressType": "string",
        "VpcConnectorArn": "string"
      },
      "IngressConfiguration": {
        "IsPubliclyAccessible": boolean
      },
      "IpAddressType": "string"
    },
    "ObservabilityConfiguration": {
      "ObservabilityConfigurationArn": "string",
      "ObservabilityEnabled": boolean
    },
    "ServiceArn": "string",
    "ServiceId": "string",
    "ServiceName": "string",

```

```

    "ServiceUrl": "string",
    "SourceConfiguration": {
      "AuthenticationConfiguration": {
        "AccessRoleArn": "string",
        "ConnectionArn": "string"
      },
      "AutoDeploymentsEnabled": boolean,
      "CodeRepository": {
        "CodeConfiguration": {
          "CodeConfigurationValues": {
            "BuildCommand": "string",
            "Port": "string",
            "Runtime": "string",
            "RuntimeEnvironmentSecrets": {
              "string" : "string"
            },
            "RuntimeEnvironmentVariables": {
              "string" : "string"
            },
            "StartCommand": "string"
          },
          "ConfigurationSource": "string"
        },
        "RepositoryUrl": "string",
        "SourceCodeVersion": {
          "Type": "string",
          "Value": "string"
        },
        "SourceDirectory": "string"
      },
      "ImageRepository": {
        "ImageConfiguration": {
          "Port": "string",
          "RuntimeEnvironmentSecrets": {
            "string" : "string"
          },
          "RuntimeEnvironmentVariables": {
            "string" : "string"
          },
          "StartCommand": "string"
        },
        "ImageIdentifier": "string",
        "ImageRepositoryType": "string"
      }
    }
  }

```

```
    },  
    "Status": "string",  
    "UpdatedAt": number  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

OperationId

The unique ID of the asynchronous operation that this request started. You can use it combined with the [ListOperations](#) call to track the operation's progress.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[1-5][0-9a-fA-F]{3}-[89abAB][0-9a-fA-F]{3}-[0-9a-fA-F]{12}`

Service

A description of the App Runner service updated by this request. All configuration values in the returned Service structure reflect configuration changes that are being applied by this request.

Type: [Service](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServiceErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

InvalidStateException

You can't perform this action when the resource is in its current state.

HTTP Status Code: 400

ResourceNotFoundException

A resource doesn't exist for the specified Amazon Resource Name (ARN) in your AWS account.

HTTP Status Code: 400

Examples

Update memory size

This example illustrates how to update the memory size of instances (scaling units) of an App Runner service to 2048 MiB.

When the call succeeds, App Runner starts an asynchronous update process. The `Service` structure that's returned by the call reflects the new memory value that's being applied by this call.

Sample Request

```
$ aws apprunner update-service --cli-input-json "`cat`"
{
  "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/python-
app/8fe1e10304f84fd2b0df550fe98a71fa",
  "InstanceConfiguration": {
    "Memory": "4 GB"
  }
}
```

Sample Response

```
{
  "OperationId": "17fe9f55-7e91-4097-b243-fcabbb69a4cf",
```

```
"Service": {
  "CreatedAt": "2020-11-20T19:05:25Z",
  "UpdatedAt": "2020-11-23T12:41:37Z",
  "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/python-
app/8fe1e10304f84fd2b0df550fe98a71fa",
  "ServiceId": "8fe1e10304f84fd2b0df550fe98a71fa",
  "ServiceName": "python-app",
  "ServiceUrl": "psbqam834h.us-east-1.awsapprunner.com",
  "SourceConfiguration": {
    "AuthenticationConfiguration": {
      "ConnectionArn": "arn:aws:apprunner:us-east-1:123456789012:connection/my-
github-connection/e7656250f67242d7819feade6800f59e"
    },
    "AutoDeploymentsEnabled": true,
    "CodeRepository": {
      "CodeConfiguration": {
        "CodeConfigurationValues": {
          "BuildCommand": "[pip install -r requirements.txt]",
          "Port": "8080",
          "Runtime": "PYTHON_3",
          "RuntimeEnvironmentVariables": [
            {
              "NAME": "Jane"
            }
          ],
          "StartCommand": "python server.py"
        },
        "ConfigurationSource": "Api"
      },
      "RepositoryUrl": "https://github.com/my-account/python-hello",
      "SourceCodeVersion": {
        "Type": "BRANCH",
        "Value": "main"
      }
    }
  },
  "Status": "OPERATION_IN_PROGRESS",
  "InstanceConfiguration": {
    "CPU": "1 vCPU",
    "Memory": "4 GB"
  },
  "NetworkConfiguration": {
    "IpAddressType": "IPV4",
    "EgressConfiguration": {
```

```
    "EgressType": "DEFAULT"
  },
  "IngressConfiguration": {
    "IsPubliclyAccessible": true
  }
},
"ObservabilityConfiguration": {
  "ObservabilityEnabled": false
}
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateVpcIngressConnection

Update an existing App Runner VPC Ingress Connection resource. The VPC Ingress Connection must be in one of the following states to be updated:

- AVAILABLE
- FAILED_CREATION
- FAILED_UPDATE

Request Syntax

```
{  
  "IngressVpcConfiguration": {  
    "VpcEndpointId": "string",  
    "VpcId": "string"  
  },  
  "VpcIngressConnectionArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[IngressVpcConfiguration](#)

Specifications for the customer's Amazon VPC and the related AWS PrivateLink VPC endpoint that are used to update the VPC Ingress Connection resource.

Type: [IngressVpcConfiguration](#) object

Required: Yes

[VpcIngressConnectionArn](#)

The Amazon Resource Name (Arn) for the App Runner VPC Ingress Connection resource that you want to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\V|-){1,1011}`

Required: Yes

Response Syntax

```
{
  "VpcIngressConnection": {
    "AccountId": "string",
    "CreatedAt": number,
    "DeletedAt": number,
    "DomainName": "string",
    "IngressVpcConfiguration": {
      "VpcEndpointId": "string",
      "VpcId": "string"
    },
    "ServiceArn": "string",
    "Status": "string",
    "VpcIngressConnectionArn": "string",
    "VpcIngressConnectionName": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

VpcIngressConnection

A description of the AWS App Runner VPC Ingress Connection resource that's updated by this request.

Type: [VpcIngressConnection](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unexpected service exception occurred.

HTTP Status Code: 500

InvalidRequestException

One or more input parameters aren't valid. Refer to the API action's document page, correct the input parameters, and try the action again.

HTTP Status Code: 400

InvalidStateException

You can't perform this action when the resource is in its current state.

HTTP Status Code: 400

ResourceNotFoundException

A resource doesn't exist for the specified Amazon Resource Name (ARN) in your AWS account.

HTTP Status Code: 400

Examples

Updating App Runner VPC Ingress Connections

This example illustrates how to update App Runner VPC Ingress Connections.

Sample Request

```
$ aws apprunner update-vpc-ingress-connection --cli-input-json "`cat`"
{
  "IngressVpcConfiguration": {
    "VpcEndpointId": "vpce-1a2b3c4d",
    "VpcId": "vpc-4a5b6c7d"
  },
  "VpcIngressConnectionArn": "arn:aws:apprunner:us-east-1:123456789012:vpcingressconnection/my-ingress-connection-name/3f2eb10e2c494674952026f646844e3d"
}
```

Sample Response

```
{
  "VpcIngressConnection": {
    "AccountId": "123456789012",
    "CreatedAt": "2022-09-18T23:36:45.374Z",
    "DomainName": "psbqam834h.us-east-1.awsapprunner.com",
    "IngressVpcConfiguration": {
      "VpcEndpointId": "vpce-1a2b3c4d",
      "VpcId": "vpc-4a5b6c7d"
    },
    "ServiceArn": "arn:aws:apprunner:us-east-1:123456789012:service/my-service",
    "Status": "PENDING_UPDATE",
    "VpcIngressConnectionArn": "arn:aws:apprunner:us-east-1:123456789012:vpcingressconnection/my-ingress-connection-name/3f2eb10e2c494674952026f646844e3d",
    "VpcIngressConnectionName": "my-ingress-connection-name"
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS App Runner API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AuthenticationConfiguration](#)
- [AutoScalingConfiguration](#)
- [AutoScalingConfigurationSummary](#)
- [CertificateValidationRecord](#)
- [CodeConfiguration](#)
- [CodeConfigurationValues](#)
- [CodeRepository](#)
- [Connection](#)
- [ConnectionSummary](#)
- [CustomDomain](#)
- [EgressConfiguration](#)
- [EncryptionConfiguration](#)
- [HealthCheckConfiguration](#)
- [ImageConfiguration](#)
- [ImageRepository](#)
- [IngressConfiguration](#)
- [IngressVpcConfiguration](#)
- [InstanceConfiguration](#)
- [ListVpcIngressConnectionsFilter](#)
- [NetworkConfiguration](#)

- [ObservabilityConfiguration](#)
- [ObservabilityConfigurationSummary](#)
- [OperationSummary](#)
- [Service](#)
- [ServiceObservabilityConfiguration](#)
- [ServiceSummary](#)
- [SourceCodeVersion](#)
- [SourceConfiguration](#)
- [Tag](#)
- [TraceConfiguration](#)
- [VpcConnector](#)
- [VpcDNSTarget](#)
- [VpcIngressConnection](#)
- [VpcIngressConnectionSummary](#)

AuthenticationConfiguration

Describes resources needed to authenticate access to some source repositories. The specific resource depends on the repository provider.

Contents

AccessRoleArn

The Amazon Resource Name (ARN) of the IAM role that grants the App Runner service access to a source repository. It's required for ECR image repositories (but not for ECR Public repositories).

Type: String

Length Constraints: Minimum length of 29. Maximum length of 1024.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):iam::[0-9]{12}:(role|role/service-role)/[\w+=,.\@-/\]{1,1000}`

Required: No

ConnectionArn

The Amazon Resource Name (ARN) of the App Runner connection that enables the App Runner service to connect to a source repository. It's required for GitHub code repositories.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\.]{0,63}:[a-z0-9-\.]{0,63}:[0-9]{12}:([\w|\/|-]){1,1011}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AutoScalingConfiguration

Describes an AWS App Runner automatic scaling configuration resource.

A higher `MinSize` increases the spread of your App Runner service over more Availability Zones in the AWS Region. The tradeoff is a higher minimal cost.

A lower `MaxSize` controls your cost. The tradeoff is lower responsiveness during peak demand.

Multiple revisions of a configuration might have the same `AutoScalingConfigurationName` and different `AutoScalingConfigurationRevision` values.

Contents

AutoScalingConfigurationArn

The Amazon Resource Name (ARN) of this auto scaling configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\V|-){1,1011}`

Required: No

AutoScalingConfigurationName

The customer-provided auto scaling configuration name. It can be used in multiple revisions of a configuration.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 32.

Pattern: `[A-Za-z0-9][A-Za-z0-9\-\_]{3,31}`

Required: No

AutoScalingConfigurationRevision

The revision of this auto scaling configuration. It's unique among all the active configurations (`"Status": "ACTIVE"`) that share the same `AutoScalingConfigurationName`.

Type: Integer

Required: No

CreatedAt

The time when the auto scaling configuration was created. It's in Unix time stamp format.

Type: Timestamp

Required: No

DeletedAt

The time when the auto scaling configuration was deleted. It's in Unix time stamp format.

Type: Timestamp

Required: No

HasAssociatedService

Indicates if this auto scaling configuration has an App Runner service associated with it. A value of `true` indicates one or more services are associated. A value of `false` indicates no services are associated.

Type: Boolean

Required: No

IsDefault

Indicates if this auto scaling configuration should be used as the default for a new App Runner service that does not have an auto scaling configuration ARN specified during creation. Each account can have only one default `AutoScalingConfiguration` per region. The default `AutoScalingConfiguration` can be any revision under the same `AutoScalingConfigurationName`.

Type: Boolean

Required: No

Latest

It's set to `true` for the configuration with the highest `Revision` among all configurations that share the same `AutoScalingConfigurationName`. It's set to `false` otherwise.

Type: Boolean

Required: No

MaxConcurrency

The maximum number of concurrent requests that an instance processes. If the number of concurrent requests exceeds this limit, App Runner scales the service up.

Type: Integer

Required: No

MaxSize

The maximum number of instances that a service scales up to. At most MaxSize instances actively serve traffic for your service.

Type: Integer

Required: No

MinSize

The minimum number of instances that App Runner provisions for a service. The service always has at least MinSize provisioned instances. Some of them actively serve traffic. The rest of them (provisioned and inactive instances) are a cost-effective compute capacity reserve and are ready to be quickly activated. You pay for memory usage of all the provisioned instances. You pay for CPU usage of only the active subset.

App Runner temporarily doubles the number of provisioned instances during deployments, to maintain the same capacity for both old and new code.

Type: Integer

Required: No

Status

The current state of the auto scaling configuration. If the status of a configuration revision is INACTIVE, it was deleted and can't be used. Inactive configuration revisions are permanently removed some time after they are deleted.

Type: String

Valid Values: ACTIVE | INACTIVE

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AutoScalingConfigurationSummary

Provides summary information about an AWS App Runner automatic scaling configuration resource.

This type contains limited information about an auto scaling configuration. It includes only identification information, without configuration details. It's returned by the [ListAutoScalingConfigurations](#) action. Complete configuration information is returned by the [CreateAutoScalingConfiguration](#), [DescribeAutoScalingConfiguration](#), and [DeleteAutoScalingConfiguration](#) actions using the [AutoScalingConfiguration](#) type.

Contents

AutoScalingConfigurationArn

The Amazon Resource Name (ARN) of this auto scaling configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\V|-){1,1011}`

Required: No

AutoScalingConfigurationName

The customer-provided auto scaling configuration name. It can be used in multiple revisions of a configuration.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 32.

Pattern: `[A-Za-z0-9][A-Za-z0-9\_-]{3,31}`

Required: No

AutoScalingConfigurationRevision

The revision of this auto scaling configuration. It's unique among all the active configurations ("Status": "ACTIVE") with the same AutoScalingConfigurationName.

Type: Integer

Required: No

CreatedAt

The time when the auto scaling configuration was created. It's in Unix time stamp format.

Type: Timestamp

Required: No

HasAssociatedService

Indicates if this auto scaling configuration has an App Runner service associated with it. A value of `true` indicates one or more services are associated. A value of `false` indicates no services are associated.

Type: Boolean

Required: No

IsDefault

Indicates if this auto scaling configuration should be used as the default for a new App Runner service that does not have an auto scaling configuration ARN specified during creation. Each account can have only one default `AutoScalingConfiguration` per region. The default `AutoScalingConfiguration` can be any revision under the same `AutoScalingConfigurationName`.

Type: Boolean

Required: No

Status

The current state of the auto scaling configuration. If the status of a configuration revision is `INACTIVE`, it was deleted and can't be used. Inactive configuration revisions are permanently removed some time after they are deleted.

Type: String

Valid Values: `ACTIVE` | `INACTIVE`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CertificateValidationRecord

Describes a certificate CNAME record to add to your DNS. For more information, see [AssociateCustomDomain](#).

Contents

Name

The certificate CNAME record name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: . *

Required: No

Status

The current state of the certificate CNAME record validation. It should change to SUCCESS after App Runner completes validation with your DNS.

Type: String

Valid Values: PENDING_VALIDATION | SUCCESS | FAILED

Required: No

Type

The record type, always CNAME.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: . *

Required: No

Value

The certificate CNAME record value.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: . *

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CodeConfiguration

Describes the configuration that AWS App Runner uses to build and run an App Runner service from a source code repository.

Contents

ConfigurationSource

The source of the App Runner configuration. Values are interpreted as follows:

- **REPOSITORY** – App Runner reads configuration values from the `apprunner.yaml` file in the source code repository and ignores `CodeConfigurationValues`.
- **API** – App Runner uses configuration values provided in `CodeConfigurationValues` and ignores the `apprunner.yaml` file in the source code repository.

Type: String

Valid Values: REPOSITORY | API

Required: Yes

CodeConfigurationValues

The basic configuration for building and running the App Runner service. Use it to quickly launch an App Runner service without providing a `apprunner.yaml` file in the source code repository (or ignoring the file if it exists).

Type: [CodeConfigurationValues](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CodeConfigurationValues

Describes the basic configuration needed for building and running an AWS App Runner service. This type doesn't support the full set of possible configuration options. For full configuration capabilities, use a `apprunner.yaml` file in the source code repository.

Contents

Runtime

A runtime environment type for building and running an App Runner service. It represents a programming language runtime.

Type: String

Valid Values: PYTHON_3 | NODEJS_12 | NODEJS_14 | CORRETTO_8 | CORRETTO_11 | NODEJS_16 | GO_1 | DOTNET_6 | PHP_81 | RUBY_31 | PYTHON_311 | NODEJS_18 | NODEJS_22

Required: Yes

BuildCommand

The command App Runner runs to build your application.

Type: String

Pattern: `[\x0a\x0d]+`

Required: No

Port

The port that your application listens to in the container.

Default: 8080

Type: String

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: `.*`

Required: No

RuntimeEnvironmentSecrets

An array of key-value pairs representing the secrets and parameters that get referenced to your service as an environment variable. The supported values are either the full Amazon Resource Name (ARN) of the AWS Secrets Manager secret or the full ARN of the parameter in the AWS Systems Manager Parameter Store.

Note

- If the AWS Systems Manager Parameter Store parameter exists in the same AWS Region as the service that you're launching, you can use either the full ARN or name of the secret. If the parameter exists in a different Region, then the full ARN must be specified.
- Currently, cross account referencing of AWS Systems Manager Parameter Store parameter is not supported.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 2048.

Value Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

RuntimeEnvironmentVariables

The environment variables that are available to your running AWS App Runner service. An array of key-value pairs.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 51200.

Key Pattern: . *

Value Length Constraints: Minimum length of 0. Maximum length of 51200.

Value Pattern: . *

Required: No

StartCommand

The command App Runner runs to start your application.

Type: String

Pattern: `[^\x0a\x0d]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CodeRepository

Describes a source code repository.

Contents

RepositoryUrl

The location of the repository that contains the source code.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: . *

Required: Yes

SourceCodeVersion

The version that should be used within the source code repository.

Type: [SourceCodeVersion](#) object

Required: Yes

CodeConfiguration

Configuration for building and running the service from a source code repository.

Note

CodeConfiguration is required only for CreateService request.

Type: [CodeConfiguration](#) object

Required: No

SourceDirectory

The path of the directory that stores source code and configuration files. The build and start commands also execute from here. The path is absolute from root and, if not specified, defaults to the repository root.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `[^\x00]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Connection

Describes an AWS App Runner connection resource.

Contents

ConnectionArn

The Amazon Resource Name (ARN) of this connection.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\V|-){1,1011}`

Required: No

ConnectionName

The customer-provided connection name.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 32.

Pattern: `[A-Za-z0-9][A-Za-z0-9\_-]{3,31}`

Required: No

CreatedAt

The App Runner connection creation time, expressed as a Unix time stamp.

Type: Timestamp

Required: No

ProviderType

The source repository provider.

Type: String

Valid Values: GITHUB | BITBUCKET

Required: No

Status

The current state of the App Runner connection. When the state is AVAILABLE, you can use the connection to create an App Runner service.

Type: String

Valid Values: PENDING_HANDSHAKE | AVAILABLE | ERROR | DELETED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ConnectionSummary

Provides summary information about an AWS App Runner connection resource.

Contents

ConnectionArn

The Amazon Resource Name (ARN) of this connection.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\V|-){1,1011}`

Required: No

ConnectionName

The customer-provided connection name.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 32.

Pattern: `[A-Za-z0-9][A-Za-z0-9\_-]{3,31}`

Required: No

CreatedAt

The App Runner connection creation time, expressed as a Unix time stamp.

Type: Timestamp

Required: No

ProviderType

The source repository provider.

Type: String

Valid Values: GITHUB | BITBUCKET

Required: No

Status

The current state of the App Runner connection. When the state is AVAILABLE, you can use the connection to create an App Runner service.

Type: String

Valid Values: PENDING_HANDSHAKE | AVAILABLE | ERROR | DELETED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CustomDomain

Describes a custom domain that's associated with an AWS App Runner service.

Contents

DomainName

An associated custom domain endpoint. It can be a root domain (for example, `example.com`), a subdomain (for example, `login.example.com` or `admin.login.example.com`), or a wildcard (for example, `*.example.com`).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[A-Za-z0-9*.-]{1,255}`

Required: Yes

EnableWWWSubdomain

When `true`, the subdomain `www.DomainName` is associated with the App Runner service in addition to the base domain.

Type: Boolean

Required: Yes

Status

The current state of the domain name association.

Type: String

Valid Values: `CREATING` | `CREATE_FAILED` | `ACTIVE` | `DELETING` | `DELETE_FAILED` | `PENDING_CERTIFICATE_DNS_VALIDATION` | `BINDING_CERTIFICATE`

Required: Yes

CertificateValidationRecords

A list of certificate CNAME records that's used for this domain name.

Type: Array of [CertificateValidationRecord](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EgressConfiguration

Describes configuration settings related to outbound network traffic of an AWS App Runner service.

Contents

EgressType

The type of egress configuration.

Set to `DEFAULT` for access to resources hosted on public networks.

Set to `VPC` to associate your service to a custom VPC specified by `VpcConnectorArn`.

Type: String

Valid Values: `DEFAULT` | `VPC`

Required: No

VpcConnectorArn

The Amazon Resource Name (ARN) of the App Runner VPC connector that you want to associate with your App Runner service. Only valid when `EgressType` = `VPC`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\/|-){1,1011}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EncryptionConfiguration

Describes a custom encryption key that AWS App Runner uses to encrypt copies of the source repository and service logs.

Contents

KmsKey

The ARN of the KMS key that's used for encryption.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `arn:aws(-[\w]+)*:kms:[a-z\-\-]+-[0-9]{1}: [0-9]{12}:key\[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HealthCheckConfiguration

Describes the settings for the health check that AWS App Runner performs to monitor the health of a service.

Contents

HealthyThreshold

The number of consecutive checks that must succeed before App Runner decides that the service is healthy.

Default: 1

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 20.

Required: No

Interval

The time interval, in seconds, between health checks.

Default: 5

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 20.

Required: No

Path

The URL that health check requests are sent to.

Path is only applicable when you set `Protocol` to HTTP.

Default: "/"

Type: String

Length Constraints: Minimum length of 1.

Required: No

Protocol

The IP protocol that App Runner uses to perform health checks for your service.

If you set `Protocol` to HTTP, App Runner sends health check requests to the HTTP path specified by `Path`.

Default: TCP

Type: String

Valid Values: TCP | HTTP

Required: No

Timeout

The time, in seconds, to wait for a health check response before deciding it failed.

Default: 2

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 20.

Required: No

UnhealthyThreshold

The number of consecutive checks that must fail before App Runner decides that the service is unhealthy.

Default: 5

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 20.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageConfiguration

Describes the configuration that AWS App Runner uses to run an App Runner service using an image pulled from a source image repository.

Contents

Port

The port that your application listens to in the container.

Default: 8080

Type: String

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: . *

Required: No

RuntimeEnvironmentSecrets

An array of key-value pairs representing the secrets and parameters that get referenced to your service as an environment variable. The supported values are either the full Amazon Resource Name (ARN) of the AWS Secrets Manager secret or the full ARN of the parameter in the AWS Systems Manager Parameter Store.

Note

- If the AWS Systems Manager Parameter Store parameter exists in the same AWS Region as the service that you're launching, you can use either the full ARN or name of the secret. If the parameter exists in a different Region, then the full ARN must be specified.
- Currently, cross account referencing of AWS Systems Manager Parameter Store parameter is not supported.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 2048.

Value Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

RuntimeEnvironmentVariables

Environment variables that are available to your running App Runner service. An array of key-value pairs.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 51200.

Key Pattern: . *

Value Length Constraints: Minimum length of 0. Maximum length of 51200.

Value Pattern: . *

Required: No

StartCommand

An optional command that App Runner runs to start the application in the source image. If specified, this command overrides the Docker image's default start command.

Type: String

Pattern: [^\x0a\x0d]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageRepository

Describes a source image repository.

Contents

Imageldentifizier

The identifier of an image.

For an image in Amazon Elastic Container Registry (Amazon ECR), this is an image name. For the image name format, see [Pulling an image](#) in the *Amazon ECR User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: ([0-9]{12}.dkr.ecr.[a-z\-\-]+[0-9]{1}.amazonaws.com\/((?:[a-z0-9]+(?:[._-][a-z0-9]+)*\/)*[a-z0-9]+(?:[._-][a-z0-9]+)*)(:([\w\d\-\=._:\/@])|@([\w\d\:]+))?)|(^public\.ecr\.aws\/.+\/((?:[a-z0-9]+(?:[._-][a-z0-9]+)*\/)*[a-z0-9]+(?:[._-][a-z0-9]+)*)(:([\w\d\-\=._:\/@])|@([\w\d\:]+))?)

Required: Yes

ImageRepositoryType

The type of the image repository. This reflects the repository provider and whether the repository is private or public.

Type: String

Valid Values: ECR | ECR_PUBLIC

Required: Yes

ImageConfiguration

Configuration for running the identified image.

Type: **ImageConfiguration** object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IngressConfiguration

Network configuration settings for inbound network traffic.

Contents

IsPubliclyAccessible

Specifies whether your App Runner service is publicly accessible. To make the service publicly accessible set it to `True`. To make the service privately accessible, from only within an Amazon VPC set it to `False`.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IngressVpcConfiguration

The configuration of your VPC and the associated VPC endpoint. The VPC endpoint is an AWS PrivateLink resource that allows access to your App Runner services from within an Amazon VPC.

Contents

VpcEndpointId

The ID of the VPC endpoint that your App Runner service connects to.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: . *

Required: No

VpcId

The ID of the VPC that is used for the VPC endpoint.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: . *

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstanceConfiguration

Describes the runtime configuration of an AWS App Runner service instance (scaling unit).

Contents

Cpu

The number of CPU units reserved for each instance of your App Runner service.

Default: 1 vCPU

Type: String

Length Constraints: Minimum length of 3. Maximum length of 9.

Pattern: 256|512|1024|2048|4096|(0.25|0.5|1|2|4) vCPU

Required: No

InstanceRoleArn

The Amazon Resource Name (ARN) of an IAM role that provides permissions to your App Runner service. These are permissions that your code needs when it calls any AWS APIs.

Type: String

Length Constraints: Minimum length of 29. Maximum length of 1024.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):iam::[0-9]{12}:(role|role/service-role)\.[\w+=,.\@-/\]{1,1000}

Required: No

Memory

The amount of memory, in MB or GB, reserved for each instance of your App Runner service.

Default: 2 GB

Type: String

Length Constraints: Minimum length of 3. Maximum length of 6.

Pattern: 512|1024|2048|3072|4096|6144|8192|10240|12288|(0.5|1|2|3|4|6|8|10|12) GB

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListVpcIngressConnectionsFilter

Returns a list of VPC Ingress Connections based on the filter provided. It can return either ServiceArn or VpcEndpointId, or both.

Contents

ServiceArn

The Amazon Resource Name (ARN) of a service to filter by.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\V|-){1,1011}`

Required: No

VpcEndpointId

The ID of a VPC Endpoint to filter by.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: `.*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NetworkConfiguration

Describes configuration settings related to network traffic of an AWS App Runner service. Consists of embedded objects for each configurable network feature.

Contents

EgressConfiguration

Network configuration settings for outbound message traffic.

Type: [EgressConfiguration](#) object

Required: No

IngressConfiguration

Network configuration settings for inbound message traffic.

Type: [IngressConfiguration](#) object

Required: No

IpAddressType

App Runner provides you with the option to choose between *IPv4* and *dual stack* (IPv4 and IPv6). This is an optional parameter. If you do not specify an `IpAddressType`, it defaults to select IPv4.

Type: String

Valid Values: IPV4 | DUAL_STACK

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

ObservabilityConfiguration

Describes an AWS App Runner observability configuration resource. Multiple revisions of a configuration have the same `ObservabilityConfigurationName` and different `ObservabilityConfigurationRevision` values.

The resource is designed to configure multiple features (currently one feature, tracing). This type contains optional members that describe the configuration of these features (currently one member, `TraceConfiguration`). If a feature member isn't specified, the feature isn't enabled.

Contents

CreatedAt

The time when the observability configuration was created. It's in Unix time stamp format.

Type: Timestamp

Required: No

DeletedAt

The time when the observability configuration was deleted. It's in Unix time stamp format.

Type: Timestamp

Required: No

Latest

It's set to `true` for the configuration with the highest `Revision` among all configurations that share the same `ObservabilityConfigurationName`. It's set to `false` otherwise.

Type: Boolean

Required: No

ObservabilityConfigurationArn

The Amazon Resource Name (ARN) of this observability configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:([\w|\/|-]){1,1011}`

Required: No

ObservabilityConfigurationName

The customer-provided observability configuration name. It can be used in multiple revisions of a configuration.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 32.

Pattern: `[A-Za-z0-9][A-Za-z0-9\_-]{3,31}`

Required: No

ObservabilityConfigurationRevision

The revision of this observability configuration. It's unique among all the active configurations ("Status": "ACTIVE") that share the same `ObservabilityConfigurationName`.

Type: Integer

Required: No

Status

The current state of the observability configuration. If the status of a configuration revision is `INACTIVE`, it was deleted and can't be used. Inactive configuration revisions are permanently removed some time after they are deleted.

Type: String

Valid Values: `ACTIVE` | `INACTIVE`

Required: No

TraceConfiguration

The configuration of the tracing feature within this observability configuration. If not specified, tracing isn't enabled.

Type: [TraceConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ObservabilityConfigurationSummary

Provides summary information about an AWS App Runner observability configuration resource.

This type contains limited information about an observability configuration. It includes only identification information, without configuration details. It's returned by the [ListObservabilityConfigurations](#) action. Complete configuration information is returned by the [CreateObservabilityConfiguration](#), [DescribeObservabilityConfiguration](#), and [DeleteObservabilityConfiguration](#) actions using the [ObservabilityConfiguration](#) type.

Contents

ObservabilityConfigurationArn

The Amazon Resource Name (ARN) of this observability configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\w|-){1,1011}`

Required: No

ObservabilityConfigurationName

The customer-provided observability configuration name. It can be used in multiple revisions of a configuration.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 32.

Pattern: `[A-Za-z0-9][A-Za-z0-9\-\_]{3,31}`

Required: No

ObservabilityConfigurationRevision

The revision of this observability configuration. It's unique among all the active configurations ("Status": "ACTIVE") that share the same `ObservabilityConfigurationName`.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OperationSummary

Provides summary information for an operation that occurred on an AWS App Runner service.

Contents

EndedAt

The time when the operation ended. It's in the Unix time stamp format.

Type: Timestamp

Required: No

Id

A unique ID of this operation. It's unique in the scope of the App Runner service.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[1-5][0-9a-fA-F]{3}-[89abAB][0-9a-fA-F]{3}-[0-9a-fA-F]{12}`

Required: No

StartedAt

The time when the operation started. It's in the Unix time stamp format.

Type: Timestamp

Required: No

Status

The current state of the operation.

Type: String

Valid Values: PENDING | IN_PROGRESS | FAILED | SUCCEEDED |
ROLLBACK_IN_PROGRESS | ROLLBACK_FAILED | ROLLBACK_SUCCEEDED

Required: No

TargetArn

The Amazon Resource Name (ARN) of the resource that the operation acted on (for example, an App Runner service).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\V|-){1,1011}`

Required: No

Type

The type of operation. It indicates a specific action that occurred.

Type: String

Valid Values: `START_DEPLOYMENT` | `CREATE_SERVICE` | `PAUSE_SERVICE` | `RESUME_SERVICE` | `DELETE_SERVICE` | `UPDATE_SERVICE`

Required: No

UpdatedAt

The time when the operation was last updated. It's in the Unix time stamp format.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Service

Describes an AWS App Runner service. It can describe a service in any state, including deleted services.

This type contains the full information about a service, including configuration details. It's returned by the [CreateService](#), [DescribeService](#), and [DeleteService](#) actions. A subset of this information is returned by the [ListServices](#) action using the [ServiceSummary](#) type.

Contents

AutoScalingConfigurationSummary

Summary information for the App Runner automatic scaling configuration resource that's associated with this service.

Type: [AutoScalingConfigurationSummary](#) object

Required: Yes

CreatedAt

The time when the App Runner service was created. It's in the Unix time stamp format.

Type: Timestamp

Required: Yes

InstanceConfiguration

The runtime configuration of instances (scaling units) of this service.

Type: [InstanceConfiguration](#) object

Required: Yes

NetworkConfiguration

Configuration settings related to network traffic of the web application that this service runs.

Type: [NetworkConfiguration](#) object

Required: Yes

ServiceArn

The Amazon Resource Name (ARN) of this service.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\/|-){1,1011}`

Required: Yes

ServiceId

An ID that App Runner generated for this service. It's unique within the AWS Region.

Type: String

Length Constraints: Fixed length of 32.

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[1-5][0-9a-fA-F]{3}-[89abAB][0-9a-fA-F]{3}-[0-9a-fA-F]{12}`

Required: Yes

ServiceName

The customer-provided service name.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 40.

Pattern: `[A-Za-z0-9][A-Za-z0-9-_{3,39}`

Required: Yes

SourceConfiguration

The source deployed to the App Runner service. It can be a code or an image repository.

Type: [SourceConfiguration](#) object

Required: Yes

Status

The current state of the App Runner service. These particular values mean the following.

- **CREATE_FAILED** – The service failed to create. The failed service isn't usable, and still counts towards your service quota. To troubleshoot this failure, read the failure events and logs, change any parameters that need to be fixed, and rebuild your service using `UpdateService`.
- **DELETE_FAILED** – The service failed to delete and can't be successfully recovered. Retry the service deletion call to ensure that all related resources are removed.

Type: String

Valid Values: **CREATE_FAILED** | **RUNNING** | **DELETED** | **DELETE_FAILED** | **PAUSED** | **OPERATION_IN_PROGRESS**

Required: Yes

UpdatedAt

The time when the App Runner service was last updated at. It's in the Unix time stamp format.

Type: Timestamp

Required: Yes

DeletedAt

The time when the App Runner service was deleted. It's in the Unix time stamp format.

Type: Timestamp

Required: No

EncryptionConfiguration

The encryption key that App Runner uses to encrypt the service logs and the copy of the source repository that App Runner maintains for the service. It can be either a customer-provided encryption key or an AWS managed key.

Type: [EncryptionConfiguration](#) object

Required: No

HealthCheckConfiguration

The settings for the health check that App Runner performs to monitor the health of this service.

Type: [HealthCheckConfiguration](#) object

Required: No

ObservabilityConfiguration

The observability configuration of this service.

Type: [ServiceObservabilityConfiguration](#) object

Required: No

ServiceUrl

A subdomain URL that App Runner generated for this service. You can use this URL to access your service web application.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: . *

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceObservabilityConfiguration

Describes the observability configuration of an AWS App Runner service. These are additional observability features, like tracing, that you choose to enable. They're configured in a separate resource that you associate with your service.

Contents

ObservabilityEnabled

When true, an observability configuration resource is associated with the service, and an `ObservabilityConfigurationArn` is specified.

Type: Boolean

Required: Yes

ObservabilityConfigurationArn

The Amazon Resource Name (ARN) of the observability configuration that is associated with the service. Specified only when `ObservabilityEnabled` is true.

Specify an ARN with a name and a revision number to associate that revision. For example: `arn:aws:apprunner:us-east-1:123456789012:observabilityconfiguration/xray-tracing/3`

Specify just the name to associate the latest revision. For example: `arn:aws:apprunner:us-east-1:123456789012:observabilityconfiguration/xray-tracing`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\/|-){1,1011}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceSummary

Provides summary information for an AWS App Runner service.

This type contains limited information about a service. It doesn't include configuration details. It's returned by the [ListServices](#) action. Complete service information is returned by the [CreateService](#), [DescribeService](#), and [DeleteService](#) actions using the [Service](#) type.

Contents

CreatedAt

The time when the App Runner service was created. It's in the Unix time stamp format.

Type: Timestamp

Required: No

ServiceArn

The Amazon Resource Name (ARN) of this service.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\V|-){1,1011}`

Required: No

ServiceId

An ID that App Runner generated for this service. It's unique within the AWS Region.

Type: String

Length Constraints: Fixed length of 32.

Pattern: `[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[1-5][0-9a-fA-F]{3}-[89abAB][0-9a-fA-F]{3}-[0-9a-fA-F]{12}`

Required: No

ServiceName

The customer-provided service name.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 40.

Pattern: `[A-Za-z0-9][A-Za-z0-9-_{3,39}`

Required: No

ServiceUrl

A subdomain URL that App Runner generated for this service. You can use this URL to access your service web application.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: `. *`

Required: No

Status

The current state of the App Runner service. These particular values mean the following.

- **CREATE_FAILED** – The service failed to create. The failed service isn't usable, and still counts towards your service quota. To troubleshoot this failure, read the failure events and logs, change any parameters that need to be fixed, and rebuild your service using `UpdateService`.
- **DELETE_FAILED** – The service failed to delete and can't be successfully recovered. Retry the service deletion call to ensure that all related resources are removed.

Type: String

Valid Values: `CREATE_FAILED | RUNNING | DELETED | DELETE_FAILED | PAUSED | OPERATION_IN_PROGRESS`

Required: No

UpdatedAt

The time when the App Runner service was last updated. It's in the Unix time stamp format.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SourceCodeVersion

Identifies a version of code that AWS App Runner refers to within a source code repository.

Contents

Type

The type of version identifier.

For a git-based repository, branches represent versions.

Type: String

Valid Values: BRANCH

Required: Yes

Value

A source code version.

For a git-based repository, a branch name maps to a specific version. App Runner uses the most recent commit to the branch.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: .*

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SourceConfiguration

Describes the source deployed to an AWS App Runner service. It can be a code or an image repository.

Contents

AuthenticationConfiguration

Describes the resources that are needed to authenticate access to some source repositories.

Type: [AuthenticationConfiguration](#) object

Required: No

AutoDeploymentsEnabled

If `true`, continuous integration from the source repository is enabled for the App Runner service. Each repository change (including any source code commit or new image version) starts a deployment.

Default: App Runner sets to `false` for a source image that uses an ECR Public repository or an ECR repository that's in an AWS account other than the one that the service is in. App Runner sets to `true` in all other cases (which currently include a source code repository or a source image using a same-account ECR repository).

Type: Boolean

Required: No

CodeRepository

The description of a source code repository.

You must provide either this member or `ImageRepository` (but not both).

Type: [CodeRepository](#) object

Required: No

ImageRepository

The description of a source image repository.

You must provide either this member or `CodeRepository` (but not both).

Type: [ImageRepository](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

Describes a tag that is applied to an AWS App Runner resource. A tag is a metadata item consisting of a key-value pair.

Contents

Key

The key of the tag.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^(?!aws:).+`

Required: No

Value

The value of the tag.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `.*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TraceConfiguration

Describes the configuration of the tracing feature within an AWS App Runner observability configuration.

Contents

Vendor

The implementation provider chosen for tracing App Runner services.

Type: String

Valid Values: AWSXRAY

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VpcConnector

Describes an AWS App Runner VPC connector resource. A VPC connector describes the Amazon Virtual Private Cloud (Amazon VPC) that an App Runner service is associated with, and the subnets and security group that are used.

Multiple revisions of a connector might have the same Name and different Revision values.

Note

At this time, App Runner supports only one revision per name.

Contents

CreatedAt

The time when the VPC connector was created. It's in Unix time stamp format.

Type: Timestamp

Required: No

DeletedAt

The time when the VPC connector was deleted. It's in Unix time stamp format.

Type: Timestamp

Required: No

SecurityGroups

A list of IDs of security groups that App Runner uses for access to AWS resources under the specified subnets. If not specified, App Runner uses the default security group of the Amazon VPC. The default security group allows all outbound traffic.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: . *

Required: No

Status

The current state of the VPC connector. If the status of a connector revision is `INACTIVE`, it was deleted and can't be used. Inactive connector revisions are permanently removed some time after they are deleted.

Type: String

Valid Values: `ACTIVE` | `INACTIVE`

Required: No

Subnets

A list of IDs of subnets that App Runner uses for your service. All IDs are of subnets of a single Amazon VPC.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: `. *`

Required: No

VpcConnectorArn

The Amazon Resource Name (ARN) of this VPC connector.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\V|-){1,1011}`

Required: No

VpcConnectorName

The customer-provided VPC connector name.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 40.

Pattern: `[A-Za-z0-9][A-Za-z0-9\-\_]{3,39}`

Required: No

VpcConnectorRevision

The revision of this VPC connector. It's unique among all the active connectors ("Status": "ACTIVE") that share the same Name.

Note

At this time, App Runner supports only one revision per name.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VpcDNSTarget

DNS Target record for a custom domain of this Amazon VPC.

Contents

DomainName

The domain name of your target DNS that is associated with the Amazon VPC.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[A-Za-z0-9*.-]{1,255}`

Required: No

VpcId

The ID of the Amazon VPC that is associated with the custom domain name of the target DNS.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 51200.

Pattern: `.*`

Required: No

VpcIngressConnectionArn

The Amazon Resource Name (ARN) of the VPC Ingress Connection that is associated with your service.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\W|-){1,1011}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VpcIngressConnection

The AWS App Runner resource that specifies an App Runner endpoint for incoming traffic. It establishes a connection between a VPC interface endpoint and a App Runner service, to make your App Runner service accessible from only within an Amazon VPC.

Contents

AccountId

The Account Id you use to create the VPC Ingress Connection resource.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `[0-9]{12}`

Required: No

CreatedAt

The time when the VPC Ingress Connection was created. It's in the Unix time stamp format.

- Type: Timestamp
- Required: Yes

Type: Timestamp

Required: No

DeletedAt

The time when the App Runner service was deleted. It's in the Unix time stamp format.

- Type: Timestamp
- Required: No

Type: Timestamp

Required: No

DomainName

The domain name associated with the VPC Ingress Connection resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[A-Za-z0-9*.-]{1,255}`

Required: No

IngressVpcConfiguration

Specifications for the customer's VPC and related PrivateLink VPC endpoint that are used to associate with the VPC Ingress Connection resource.

Type: [IngressVpcConfiguration](#) object

Required: No

ServiceArn

The Amazon Resource Name (ARN) of the service associated with the VPC Ingress Connection.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\V|-){1,1011}`

Required: No

Status

The current status of the VPC Ingress Connection. The VPC Ingress Connection displays one of the following statuses: AVAILABLE, PENDING_CREATION, PENDING_UPDATE, PENDING_DELETION, FAILED_CREATION, FAILED_UPDATE, FAILED_DELETION, and DELETED..

Type: String

Valid Values: AVAILABLE | PENDING_CREATION | PENDING_UPDATE | PENDING_DELETION | FAILED_CREATION | FAILED_UPDATE | FAILED_DELETION | DELETED

Required: No

VpcIngressConnectionArn

The Amazon Resource Name (ARN) of the VPC Ingress Connection.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\w|-){1,1011}`

Required: No

VpcIngressConnectionName

The customer-provided VPC Ingress Connection name.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 40.

Pattern: `[A-Za-z0-9][A-Za-z0-9\-\_]{3,39}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VpcIngressConnectionSummary

Provides summary information about an VPC Ingress Connection, which includes its VPC Ingress Connection ARN and its associated Service ARN.

Contents

ServiceArn

The Amazon Resource Name (ARN) of the service associated with the VPC Ingress Connection.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\V|-){1,1011}`

Required: No

VpcIngressConnectionArn

The Amazon Resource Name (ARN) of the VPC Ingress Connection.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws(-[\w]+)*:[a-z0-9-\\.]{0,63}:[a-z0-9-\\.]{0,63}:[0-9]{12}:(\w|\V|-){1,1011}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400