



API Reference

# AWS AppSync



**API Version 2017-07-25**

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

# AWS AppSync: API Reference

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

---

# Table of Contents

Welcome .....	1
Actions .....	2
AssociateApi .....	5
Request Syntax .....	5
URI Request Parameters .....	5
Request Body .....	5
Response Syntax .....	6
Response Elements .....	6
Errors .....	6
See Also .....	7
AssociateMergedGraphqlApi .....	8
Request Syntax .....	8
URI Request Parameters .....	8
Request Body .....	8
Response Syntax .....	9
Response Elements .....	10
Errors .....	10
See Also .....	11
AssociateSourceGraphqlApi .....	12
Request Syntax .....	12
URI Request Parameters .....	12
Request Body .....	12
Response Syntax .....	13
Response Elements .....	14
Errors .....	14
See Also .....	15
CreateApi .....	16
Request Syntax .....	16
URI Request Parameters .....	17
Request Body .....	17
Response Syntax .....	18
Response Elements .....	20
Errors .....	20
See Also .....	21

CreateApiCache .....	22
Request Syntax .....	22
URI Request Parameters .....	22
Request Body .....	22
Response Syntax .....	25
Response Elements .....	25
Errors .....	25
See Also .....	26
CreateApiKey .....	28
Request Syntax .....	28
URI Request Parameters .....	28
Request Body .....	28
Response Syntax .....	29
Response Elements .....	29
Errors .....	29
See Also .....	30
CreateChannelNamespace .....	32
Request Syntax .....	32
URI Request Parameters .....	33
Request Body .....	33
Response Syntax .....	34
Response Elements .....	36
Errors .....	36
See Also .....	37
CreateDataSource .....	38
Request Syntax .....	38
URI Request Parameters .....	39
Request Body .....	39
Response Syntax .....	42
Response Elements .....	43
Errors .....	44
See Also .....	44
CreateDomainName .....	46
Request Syntax .....	46
URI Request Parameters .....	46
Request Body .....	46

Response Syntax .....	47
Response Elements .....	48
Errors .....	48
See Also .....	49
CreateFunction .....	50
Request Syntax .....	50
URI Request Parameters .....	50
Request Body .....	51
Response Syntax .....	53
Response Elements .....	54
Errors .....	54
See Also .....	55
CreateGraphqlApi .....	56
Request Syntax .....	56
URI Request Parameters .....	57
Request Body .....	57
Response Syntax .....	61
Response Elements .....	63
Errors .....	63
See Also .....	64
CreateResolver .....	66
Request Syntax .....	66
URI Request Parameters .....	67
Request Body .....	67
Response Syntax .....	70
Response Elements .....	71
Errors .....	71
See Also .....	72
CreateType .....	74
Request Syntax .....	74
URI Request Parameters .....	74
Request Body .....	74
Response Syntax .....	75
Response Elements .....	75
Errors .....	75
See Also .....	76

DeleteApi .....	78
Request Syntax .....	78
URI Request Parameters .....	78
Request Body .....	78
Response Syntax .....	78
Response Elements .....	78
Errors .....	78
See Also .....	79
DeleteApiCache .....	81
Request Syntax .....	81
URI Request Parameters .....	81
Request Body .....	81
Response Syntax .....	81
Response Elements .....	81
Errors .....	81
See Also .....	82
DeleteApiKey .....	84
Request Syntax .....	84
URI Request Parameters .....	84
Request Body .....	84
Response Syntax .....	84
Response Elements .....	84
Errors .....	84
See Also .....	85
DeleteChannelNamespace .....	87
Request Syntax .....	87
URI Request Parameters .....	87
Request Body .....	87
Response Syntax .....	87
Response Elements .....	87
Errors .....	88
See Also .....	88
DeleteDataSource .....	90
Request Syntax .....	90
URI Request Parameters .....	90
Request Body .....	90

Response Syntax .....	90
Response Elements .....	90
Errors .....	91
See Also .....	91
DeleteDomainName .....	93
Request Syntax .....	93
URI Request Parameters .....	93
Request Body .....	93
Response Syntax .....	93
Response Elements .....	93
Errors .....	93
See Also .....	94
DeleteFunction .....	96
Request Syntax .....	96
URI Request Parameters .....	96
Request Body .....	96
Response Syntax .....	96
Response Elements .....	96
Errors .....	97
See Also .....	97
DeleteGraphqlApi .....	99
Request Syntax .....	99
URI Request Parameters .....	99
Request Body .....	99
Response Syntax .....	99
Response Elements .....	99
Errors .....	99
See Also .....	100
DeleteResolver .....	102
Request Syntax .....	102
URI Request Parameters .....	102
Request Body .....	102
Response Syntax .....	103
Response Elements .....	103
Errors .....	103
See Also .....	104

DeleteType .....	105
Request Syntax .....	105
URI Request Parameters .....	105
Request Body .....	105
Response Syntax .....	105
Response Elements .....	105
Errors .....	106
See Also .....	106
DisassociateApi .....	108
Request Syntax .....	108
URI Request Parameters .....	108
Request Body .....	108
Response Syntax .....	108
Response Elements .....	108
Errors .....	108
See Also .....	109
DisassociateMergedGraphqlApi .....	111
Request Syntax .....	111
URI Request Parameters .....	111
Request Body .....	111
Response Syntax .....	111
Response Elements .....	112
Errors .....	112
See Also .....	113
DisassociateSourceGraphqlApi .....	114
Request Syntax .....	114
URI Request Parameters .....	114
Request Body .....	114
Response Syntax .....	114
Response Elements .....	115
Errors .....	115
See Also .....	116
EvaluateCode .....	117
Request Syntax .....	117
URI Request Parameters .....	117
Request Body .....	117

Response Syntax .....	118
Response Elements .....	119
Errors .....	120
See Also .....	120
EvaluateMappingTemplate .....	122
Request Syntax .....	122
URI Request Parameters .....	122
Request Body .....	122
Response Syntax .....	123
Response Elements .....	123
Errors .....	124
See Also .....	125
FlushApiCache .....	126
Request Syntax .....	126
URI Request Parameters .....	126
Request Body .....	126
Response Syntax .....	126
Response Elements .....	126
Errors .....	126
See Also .....	127
GetApi .....	129
Request Syntax .....	129
URI Request Parameters .....	129
Request Body .....	129
Response Syntax .....	129
Response Elements .....	131
Errors .....	131
See Also .....	132
GetApiAssociation .....	133
Request Syntax .....	133
URI Request Parameters .....	133
Request Body .....	133
Response Syntax .....	133
Response Elements .....	134
Errors .....	134
See Also .....	135

GetApiCache .....	136
Request Syntax .....	136
URI Request Parameters .....	136
Request Body .....	136
Response Syntax .....	136
Response Elements .....	137
Errors .....	137
See Also .....	138
GetChannelNamespace .....	139
Request Syntax .....	139
URI Request Parameters .....	139
Request Body .....	139
Response Syntax .....	139
Response Elements .....	140
Errors .....	141
See Also .....	142
GetDataSource .....	143
Request Syntax .....	143
URI Request Parameters .....	143
Request Body .....	143
Response Syntax .....	143
Response Elements .....	145
Errors .....	145
See Also .....	146
GetDataSourceIntrospection .....	147
Request Syntax .....	147
URI Request Parameters .....	147
Request Body .....	148
Response Syntax .....	148
Response Elements .....	149
Errors .....	149
See Also .....	150
GetDomainName .....	151
Request Syntax .....	151
URI Request Parameters .....	151
Request Body .....	151

Response Syntax .....	151
Response Elements .....	152
Errors .....	152
See Also .....	153
GetFunction .....	154
Request Syntax .....	154
URI Request Parameters .....	154
Request Body .....	154
Response Syntax .....	154
Response Elements .....	155
Errors .....	155
See Also .....	156
GetGraphqlApi .....	157
Request Syntax .....	157
URI Request Parameters .....	157
Request Body .....	157
Response Syntax .....	157
Response Elements .....	159
Errors .....	159
See Also .....	160
GetGraphqlApiEnvironmentVariables .....	162
Request Syntax .....	162
URI Request Parameters .....	162
Request Body .....	162
Response Syntax .....	162
Response Elements .....	162
Errors .....	163
See Also .....	164
GetIntrospectionSchema .....	165
Request Syntax .....	165
URI Request Parameters .....	165
Request Body .....	165
Response Syntax .....	165
Response Elements .....	166
Errors .....	166
See Also .....	166

GetResolver .....	168
Request Syntax .....	168
URI Request Parameters .....	168
Request Body .....	168
Response Syntax .....	169
Response Elements .....	169
Errors .....	170
See Also .....	170
GetSchemaCreationStatus .....	172
Request Syntax .....	172
URI Request Parameters .....	172
Request Body .....	172
Response Syntax .....	172
Response Elements .....	172
Errors .....	173
See Also .....	173
GetSourceApiAssociation .....	175
Request Syntax .....	175
URI Request Parameters .....	175
Request Body .....	175
Response Syntax .....	175
Response Elements .....	176
Errors .....	176
See Also .....	177
GetType .....	178
Request Syntax .....	178
URI Request Parameters .....	178
Request Body .....	178
Response Syntax .....	178
Response Elements .....	179
Errors .....	179
See Also .....	180
ListApiKeys .....	181
Request Syntax .....	181
URI Request Parameters .....	181
Request Body .....	182

Response Syntax .....	182
Response Elements .....	182
Errors .....	183
See Also .....	183
ListApis .....	185
Request Syntax .....	185
URI Request Parameters .....	185
Request Body .....	185
Response Syntax .....	185
Response Elements .....	187
Errors .....	187
See Also .....	188
ListChannelNamespaces .....	189
Request Syntax .....	189
URI Request Parameters .....	189
Request Body .....	189
Response Syntax .....	190
Response Elements .....	191
Errors .....	191
See Also .....	192
ListDataSources .....	193
Request Syntax .....	193
URI Request Parameters .....	193
Request Body .....	193
Response Syntax .....	193
Response Elements .....	195
Errors .....	195
See Also .....	196
ListDomainNames .....	198
Request Syntax .....	198
URI Request Parameters .....	198
Request Body .....	198
Response Syntax .....	198
Response Elements .....	199
Errors .....	199
See Also .....	200

ListFunctions .....	201
Request Syntax .....	201
URI Request Parameters .....	201
Request Body .....	201
Response Syntax .....	201
Response Elements .....	202
Errors .....	203
See Also .....	203
ListGraphqlApis .....	205
Request Syntax .....	205
URI Request Parameters .....	205
Request Body .....	205
Response Syntax .....	206
Response Elements .....	208
Errors .....	208
See Also .....	209
ListResolvers .....	210
Request Syntax .....	210
URI Request Parameters .....	210
Request Body .....	210
Response Syntax .....	211
Response Elements .....	212
Errors .....	212
See Also .....	213
ListResolversByFunction .....	214
Request Syntax .....	214
URI Request Parameters .....	214
Request Body .....	214
Response Syntax .....	215
Response Elements .....	216
Errors .....	216
See Also .....	217
ListSourceApiAssociations .....	218
Request Syntax .....	218
URI Request Parameters .....	218
Request Body .....	218

Response Syntax .....	218
Response Elements .....	219
Errors .....	219
See Also .....	220
ListTagsForResource .....	222
Request Syntax .....	222
URI Request Parameters .....	222
Request Body .....	222
Response Syntax .....	222
Response Elements .....	222
Errors .....	223
See Also .....	224
ListTypes .....	225
Request Syntax .....	225
URI Request Parameters .....	225
Request Body .....	226
Response Syntax .....	226
Response Elements .....	226
Errors .....	227
See Also .....	227
ListTypesByAssociation .....	229
Request Syntax .....	229
URI Request Parameters .....	229
Request Body .....	230
Response Syntax .....	230
Response Elements .....	230
Errors .....	231
See Also .....	232
PutGraphqlApiEnvironmentVariables .....	233
Request Syntax .....	233
URI Request Parameters .....	234
Request Body .....	234
Response Syntax .....	235
Response Elements .....	235
Errors .....	235
See Also .....	236

StartDataSourceIntrospection .....	238
Request Syntax .....	238
URI Request Parameters .....	238
Request Body .....	238
Response Syntax .....	238
Response Elements .....	239
Errors .....	239
See Also .....	240
StartSchemaCreation .....	242
Request Syntax .....	242
URI Request Parameters .....	242
Request Body .....	242
Response Syntax .....	242
Response Elements .....	243
Errors .....	243
See Also .....	244
StartSchemaMerge .....	245
Request Syntax .....	245
URI Request Parameters .....	245
Request Body .....	245
Response Syntax .....	245
Response Elements .....	246
Errors .....	246
See Also .....	247
TagResource .....	248
Request Syntax .....	248
URI Request Parameters .....	248
Request Body .....	248
Response Syntax .....	249
Response Elements .....	249
Errors .....	249
See Also .....	250
UntagResource .....	251
Request Syntax .....	251
URI Request Parameters .....	251
Request Body .....	251

Response Syntax .....	251
Response Elements .....	252
Errors .....	252
See Also .....	253
UpdateApi .....	254
Request Syntax .....	254
URI Request Parameters .....	255
Request Body .....	255
Response Syntax .....	256
Response Elements .....	257
Errors .....	258
See Also .....	259
UpdateApiCache .....	260
Request Syntax .....	260
URI Request Parameters .....	260
Request Body .....	260
Response Syntax .....	262
Response Elements .....	263
Errors .....	263
See Also .....	264
UpdateApiKey .....	265
Request Syntax .....	265
URI Request Parameters .....	265
Request Body .....	265
Response Syntax .....	266
Response Elements .....	266
Errors .....	266
See Also .....	267
UpdateChannelNamespace .....	269
Request Syntax .....	269
URI Request Parameters .....	270
Request Body .....	270
Response Syntax .....	271
Response Elements .....	272
Errors .....	272
See Also .....	273

UpdateDataSource .....	275
Request Syntax .....	275
URI Request Parameters .....	276
Request Body .....	276
Response Syntax .....	279
Response Elements .....	280
Errors .....	280
See Also .....	281
UpdateDomainName .....	283
Request Syntax .....	283
URI Request Parameters .....	283
Request Body .....	283
Response Syntax .....	284
Response Elements .....	284
Errors .....	284
See Also .....	285
UpdateFunction .....	287
Request Syntax .....	287
URI Request Parameters .....	287
Request Body .....	288
Response Syntax .....	290
Response Elements .....	291
Errors .....	291
See Also .....	292
UpdateGraphqlApi .....	293
Request Syntax .....	293
URI Request Parameters .....	294
Request Body .....	294
Response Syntax .....	298
Response Elements .....	299
Errors .....	300
See Also .....	301
UpdateResolver .....	302
Request Syntax .....	302
URI Request Parameters .....	302
Request Body .....	303

Response Syntax .....	306
Response Elements .....	307
Errors .....	307
See Also .....	308
UpdateSourceApiAssociation .....	309
Request Syntax .....	309
URI Request Parameters .....	309
Request Body .....	309
Response Syntax .....	310
Response Elements .....	310
Errors .....	311
See Also .....	312
UpdateType .....	313
Request Syntax .....	313
URI Request Parameters .....	313
Request Body .....	313
Response Syntax .....	314
Response Elements .....	314
Errors .....	314
See Also .....	315
<b>Data Types .....</b>	<b>317</b>
AdditionalAuthenticationProvider .....	320
Contents .....	320
See Also .....	321
Api .....	322
Contents .....	322
See Also .....	324
ApiAssociation .....	325
Contents .....	325
See Also .....	326
ApiCache .....	327
Contents .....	327
See Also .....	329
ApiKey .....	331
Contents .....	332
See Also .....	332

AppSyncRuntime .....	334
Contents .....	334
See Also .....	334
AuthMode .....	335
Contents .....	335
See Also .....	335
AuthorizationConfig .....	336
Contents .....	336
See Also .....	336
AuthProvider .....	337
Contents .....	337
See Also .....	338
AwsIamConfig .....	339
Contents .....	339
See Also .....	339
BadRequestDetail .....	340
Contents .....	340
See Also .....	340
CachingConfig .....	341
Contents .....	341
See Also .....	341
ChannelNamespace .....	342
Contents .....	342
See Also .....	344
CodeError .....	345
Contents .....	345
See Also .....	345
CodeErrorLocation .....	347
Contents .....	347
See Also .....	347
CognitoConfig .....	348
Contents .....	348
See Also .....	348
CognitoUserPoolConfig .....	349
Contents .....	349
See Also .....	349

DataSource .....	350
Contents .....	350
See Also .....	353
DataSourceIntrospectionModel .....	354
Contents .....	354
See Also .....	355
DataSourceIntrospectionModelField .....	356
Contents .....	356
See Also .....	356
DataSourceIntrospectionModelFieldType .....	357
Contents .....	357
See Also .....	358
DataSourceIntrospectionModelIndex .....	359
Contents .....	359
See Also .....	359
DataSourceIntrospectionResult .....	360
Contents .....	360
See Also .....	360
DeltaSyncConfig .....	361
Contents .....	361
See Also .....	361
DomainNameConfig .....	362
Contents .....	362
See Also .....	363
DynamodbDataSourceConfig .....	365
Contents .....	365
See Also .....	366
ElasticsearchDataSourceConfig .....	367
Contents .....	367
See Also .....	367
EnhancedMetricsConfig .....	368
Contents .....	369
See Also .....	371
ErrorDetail .....	372
Contents .....	372
See Also .....	372

EvaluateCodeErrorDetail .....	373
Contents .....	373
See Also .....	373
EventBridgeDataSourceConfig .....	374
Contents .....	374
See Also .....	374
EventConfig .....	375
Contents .....	375
See Also .....	376
EventLogConfig .....	377
Contents .....	377
See Also .....	377
FunctionConfiguration .....	378
Contents .....	378
See Also .....	380
GraphqlApi .....	382
Contents .....	382
See Also .....	387
HandlerConfig .....	388
Contents .....	388
See Also .....	388
HandlerConfigs .....	389
Contents .....	389
See Also .....	389
HttpDataSourceConfig .....	390
Contents .....	390
See Also .....	390
Integration .....	391
Contents .....	391
See Also .....	391
LambdaAuthorizerConfig .....	392
Contents .....	392
See Also .....	393
LambdaConfig .....	394
Contents .....	394
See Also .....	394

LambdaConflictHandlerConfig .....	395
Contents .....	395
See Also .....	395
LambdaDataSourceConfig .....	396
Contents .....	396
See Also .....	396
LogConfig .....	397
Contents .....	397
See Also .....	398
OpenIDConnectConfig .....	399
Contents .....	399
See Also .....	400
OpenSearchServiceDataSourceConfig .....	401
Contents .....	401
See Also .....	401
PipelineConfig .....	402
Contents .....	402
See Also .....	402
RdsDataApiConfig .....	403
Contents .....	403
See Also .....	404
RdsHttpEndpointConfig .....	405
Contents .....	405
See Also .....	406
RelationalDatabaseDataSourceConfig .....	407
Contents .....	407
See Also .....	407
Resolver .....	408
Contents .....	408
See Also .....	411
SourceApiAssociation .....	412
Contents .....	412
See Also .....	414
SourceApiAssociationConfig .....	415
Contents .....	415
See Also .....	415

SourceApiAssociationSummary .....	416
Contents .....	416
See Also .....	417
SyncConfig .....	418
Contents .....	418
See Also .....	419
Type .....	420
Contents .....	420
See Also .....	421
UserPoolConfig .....	422
Contents .....	422
See Also .....	423
<b>Common Parameters .....</b>	<b>424</b>
<b>Common Errors .....</b>	<b>427</b>

# Welcome

AWS AppSync provides API actions for creating and interacting with data sources using GraphQL from your application.

This document was last published on July 16, 2025.

# Actions

The following actions are supported:

- [AssociateApi](#)
- [AssociateMergedGraphqlApi](#)
- [AssociateSourceGraphqlApi](#)
- [CreateApi](#)
- [CreateApiCache](#)
- [CreateApiKey](#)
- [CreateChannelNamespace](#)
- [CreateDataSource](#)
- [CreateDomainName](#)
- [CreateFunction](#)
- [CreateGraphqlApi](#)
- [CreateResolver](#)
- [CreateType](#)
- [DeleteApi](#)
- [DeleteApiCache](#)
- [DeleteApiKey](#)
- [DeleteChannelNamespace](#)
- [DeleteDataSource](#)
- [DeleteDomainName](#)
- [DeleteFunction](#)
- [DeleteGraphqlApi](#)
- [DeleteResolver](#)
- [DeleteType](#)
- [DisassociateApi](#)
- [DisassociateMergedGraphqlApi](#)
- [DisassociateSourceGraphqlApi](#)
- [EvaluateCode](#)

- [EvaluateMappingTemplate](#)
- [FlushApiCache](#)
- [GetApi](#)
- [GetApiAssociation](#)
- [GetApiCache](#)
- [GetChannelNamespace](#)
- [GetDataSource](#)
- [GetDataSourceIntrospection](#)
- [GetDomainName](#)
- [GetFunction](#)
- [GetGraphqlApi](#)
- [GetGraphqlApiEnvironmentVariables](#)
- [GetIntrospectionSchema](#)
- [GetResolver](#)
- [GetSchemaCreationStatus](#)
- [GetSourceApiAssociation](#)
- [GetType](#)
- [ListApiKey](#)
- [ListApis](#)
- [ListChannelNamespaces](#)
- [ListDataSources](#)
- [ListDomainNames](#)
- [ListFunctions](#)
- [ListGraphqlApis](#)
- [ListResolvers](#)
- [ListResolversByFunction](#)
- [ListSourceApiAssociations](#)
- [ListTagsForResource](#)
- [ListTypes](#)
- [ListTypesByAssociation](#)

- [PutGraphqlApiEnvironmentVariables](#)
- [StartDataSourceIntrospection](#)
- [StartSchemaCreation](#)
- [StartSchemaMerge](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateApi](#)
- [UpdateApiCache](#)
- [UpdateApiKey](#)
- [UpdateChannelNamespace](#)
- [UpdateDataSource](#)
- [UpdateDomainName](#)
- [UpdateFunction](#)
- [UpdateGraphqlApi](#)
- [UpdateResolver](#)
- [UpdateSourceApiAssociation](#)
- [UpdateType](#)

# AssociateApi

Maps an endpoint to your custom domain.

## Request Syntax

```
POST /v1/domainnames/domainName/apiassociation HTTP/1.1
Content-type: application/json

{
  "apiIdstring"
}
```

## URI Request Parameters

The request uses the following URI parameters.

### domainName

The domain name.

Length Constraints: Minimum length of 1. Maximum length of 253.

Pattern: ^(\\*\[\w\d-\]\*\.)?([\w\d-]+\.)+[\w\d-]+\$

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### apild

The API ID. Private APIs can not be associated with custom domains.

Type: String

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "apiAssociation": {
    "apiId": "string",
    "associationStatus": "string",
    "deploymentDetail": "string",
    "domainName": "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### apiAssociation

The ApiAssociation object.

Type: [ApiAssociation](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You don't have access to perform this operation on this resource.

HTTP Status Code: 403

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

## InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# AssociateMergedGraphqlApi

Creates an association between a Merged API and source API using the source API's identifier.

## Request Syntax

```
POST /v1/sourceApis/sourceApiIdentifier/mergedApiAssociations HTTP/1.1
Content-type: application/json

{
  "description": "string",
  "mergedApiIdentifier": "string",
  "sourceApiAssociationConfig": {
    "mergeType": "string"
  }
}
```

## URI Request Parameters

The request uses the following URI parameters.

### [sourceApildentifier](#)

The identifier of the AppSync Source API. This is generated by the AppSync service. In most cases, source APIs (especially in your account) only require the API ID value or ARN of the source API. However, source APIs from other accounts (cross-account use cases) strictly require the full resource ARN of the source API.

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### [description](#)

The description field.

Type: String

Required: No

### mergedApilIdentifier

The identifier of the AppSync Merged API. This is generated by the AppSync service. In most cases, Merged APIs (especially in your account) only require the API ID value or ARN of the merged API. However, Merged APIs in other accounts (cross-account use cases) strictly require the full resource ARN of the merged API.

Type: String

Required: Yes

### sourceApiAssociationConfig

The SourceApiAssociationConfig object data.

Type: [SourceApiAssociationConfig](#) object

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "sourceApiAssociation": {
    "associationArn": "string",
    "associationId": "string",
    "description": "string",
    "lastSuccessfulMergeDate": number,
    "mergedApiArn": "string",
    "mergedApiId": "string",
    "sourceApiArn": "string",
    "sourceApiAssociationConfig": {
      "mergeType": "string"
    },
    "sourceApiAssociationStatus": "string",
    "sourceApiAssociationStatusDetail": "string",
    "sourceApiId": "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [sourceApiAssociation](#)

The SourceApiAssociation object data.

Type: [SourceApiAssociation](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **ConcurrentModificationException**

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **LimitExceededException**

The request exceeded a limit. Try your request again.

HTTP Status Code: 429

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# AssociateSourceGraphqlApi

Creates an association between a Merged API and source API using the Merged API's identifier.

## Request Syntax

```
POST /v1/mergedApis/mergedApiIdentifier/sourceApiAssociations HTTP/1.1
Content-type: application/json

{
  "description": "string",
  "sourceApiAssociationConfig": {
    "mergeType": "string"
  },
  "sourceApiIdentifier": "string"
}
```

## URI Request Parameters

The request uses the following URI parameters.

### [mergedApilIdentifier](#)

The identifier of the AppSync Merged API. This is generated by the AppSync service. In most cases, Merged APIs (especially in your account) only require the API ID value or ARN of the merged API. However, Merged APIs in other accounts (cross-account use cases) strictly require the full resource ARN of the merged API.

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### [description](#)

The description field.

Type: String

Required: No

### [sourceApiAssociationConfig](#)

The SourceApiAssociationConfig object data.

Type: [SourceApiAssociationConfig](#) object

Required: No

### [sourceApIdentifier](#)

The identifier of the AppSync Source API. This is generated by the AppSync service. In most cases, source APIs (especially in your account) only require the API ID value or ARN of the source API. However, source APIs from other accounts (cross-account use cases) strictly require the full resource ARN of the source API.

Type: String

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "sourceApiAssociation": {
    "associationArn": "string",
    "associationId": "string",
    "description": "string",
    "lastSuccessfulMergeDate": number,
    "mergedApiArn": "string",
    "mergedApiId": "string",
    "sourceApiArn": "string",
    "sourceApiAssociationConfig": {
      "mergeType": "string"
    },
    "sourceApiAssociationStatus": "string",
    "sourceApiAssociationStatusDetail": "string",
    "sourceApiId": "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [sourceApiAssociation](#)

The SourceApiAssociation object data.

Type: [SourceApiAssociation](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **ConcurrentModificationException**

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **LimitExceededException**

The request exceeded a limit. Try your request again.

HTTP Status Code: 429

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateApi

Creates an Api object. Use this operation to create an AWS AppSync API with your preferred configuration, such as an Event API that provides real-time message publishing and message subscriptions over WebSockets.

## Request Syntax

```
POST /v2/apis HTTP/1.1
Content-type: application/json

{
  "eventConfig": {
    "authProviders": [
      {
        "authType": "string",
        "cognitoConfig": {
          "appIdClientRegex": "string",
          "awsRegion": "string",
          "userPoolId": "string"
        },
        "lambdaAuthorizerConfig": {
          "authorizerResultTtlInSeconds": number,
          "authorizerUri": "string",
          "identityValidationExpression": "string"
        },
        "openIDConnectConfig": {
          "authTTL": number,
          "clientId": "string",
          "iatTTL": number,
          "issuer": "string"
        }
      }
    ],
    "connectionAuthModes": [
      {
        "authType": "string"
      }
    ],
    "defaultPublishAuthModes": [
      {
        "authType": "string"
      }
    ]
  }
}
```

```
        }
    ],
    "defaultSubscribeAuthModes": [
        {
            "authType": "string"
        }
    ],
    "logConfig": {
        "cloudWatchLogsRoleArn": "string",
        "logLevel": "string"
    }
},
"name": "string",
"ownerContact": "string",
"tags": {
    "string" : "string"
}
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### [eventConfig](#)

The Event API configuration. This includes the default authorization configuration for connecting, publishing, and subscribing to an Event API.

Type: [EventConfig](#) object

Required: No

### [name](#)

The name for the Api.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: [A-Za-z0-9\_\-\ ]+

Required: Yes

### ownerContact

The owner contact information for the Api.

Type: String

Required: No

### tags

A map with keys of TagKey objects and values of TagValue objects.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: ^(?!aws:)[ a-zA-Z+-.=:\_:/]+\$

Value Length Constraints: Maximum length of 256.

Value Pattern: ^[\s\w+-=\.:;/@]\*\$

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "api": {
    "apiArn": "string",
    "apiId": "string",
    "created": number,
    "dns": {
      "string" : "string"
    },
    "eventConfig": {
      "authProviders": [
        {
          "authType": "string",

```

```
        "cognitoConfig": {
            "appIdClientRegex": "string",
            "awsRegion": "string",
            "userPoolId": "string"
        },
        "lambdaAuthorizerConfig": {
            "authorizerResultTtlInSeconds": number,
            "authorizerUri": "string",
            "identityValidationExpression": "string"
        },
        "openIDConnectConfig": {
            "authTTL": number,
            "clientId": "string",
            "iatTTL": number,
            "issuer": "string"
        }
    }
],
"connectionAuthModes": [
    {
        "authType": "string"
    }
],
"defaultPublishAuthModes": [
    {
        "authType": "string"
    }
],
"defaultSubscribeAuthModes": [
    {
        "authType": "string"
    }
],
"logConfig": {
    "cloudWatchLogsRoleArn": "string",
    "logLevel": "string"
},
"name": "string",
"ownerContact": "string",
"tags": {
    "string" : "string"
},
"wafWebAclArn": "string",
```

```
    "xrayEnabled": boolean  
}  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [api](#)

The Api object.

Type: [Api](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **ConcurrentModificationException**

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **ServiceQuotaExceededException**

The operation exceeded the service quota for this resource.

HTTP Status Code: 402

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateApiCache

Creates a cache for the GraphQL API.

## Request Syntax

```
POST /v1/apis/apiId/ApiCaches HTTP/1.1
Content-type: application/json

{
  "apiCachingBehavioratRestEncryptionEnabledhealthMetricsConfigtransitEncryptionEnabledttltype
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The GraphQL API ID.

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### apiCachingBehavior

Caching behavior.

- **FULL\_REQUEST\_CACHING:** All requests from the same user are cached. Individual resolvers are automatically cached. All API calls will try to return responses from the cache.
- **PER\_RESOLVER\_CACHING:** Individual resolvers that you specify are cached.
- **OPERATION\_LEVEL\_CACHING:** Full requests are cached together and returned without executing resolvers.

Type: String

Valid Values: FULL\_REQUEST\_CACHING | PER\_RESOLVER\_CACHING | OPERATION\_LEVEL\_CACHING

Required: Yes

### **atRestEncryptionEnabled**

*This parameter has been deprecated.*

At-rest encryption flag for cache. You cannot update this setting after creation.

Type: Boolean

Required: No

### **healthMetricsConfig**

Controls how cache health metrics will be emitted to CloudWatch. Cache health metrics include:

- NetworkBandwidthOutAllowanceExceeded: The network packets dropped because the throughput exceeded the aggregated bandwidth limit. This is useful for diagnosing bottlenecks in a cache configuration.
- EngineCPUUtilization: The CPU utilization (percentage) allocated to the Redis process. This is useful for diagnosing bottlenecks in a cache configuration.

Metrics will be recorded by API ID. You can set the value to ENABLED or DISABLED.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

### **transitEncryptionEnabled**

*This parameter has been deprecated.*

Transit encryption flag when connecting to cache. You cannot update this setting after creation.

Type: Boolean

Required: No

### **ttl**

TTL in seconds for cache entries.

Valid values are 1–3,600 seconds.

Type: Long

Required: Yes

## type

The cache instance type. Valid values are

- SMALL
- MEDIUM
- LARGE
- XLARGE
- LARGE\_2X
- LARGE\_4X
- LARGE\_8X (not available in all regions)
- LARGE\_12X

Historically, instance types were identified by an EC2-style value. As of July 2020, this is deprecated, and the generic identifiers above should be used.

The following legacy instance types are available, but their use is discouraged:

- **T2\_SMALL**: A t2.small instance type.
- **T2\_MEDIUM**: A t2.medium instance type.
- **R4\_LARGE**: A r4.large instance type.
- **R4\_XLARGE**: A r4.xlarge instance type.
- **R4\_2XLARGE**: A r4.2xlarge instance type.
- **R4\_4XLARGE**: A r4.4xlarge instance type.
- **R4\_8XLARGE**: A r4.8xlarge instance type.

Type: String

Valid Values: T2\_SMALL | T2\_MEDIUM | R4\_LARGE | R4\_XLARGE | R4\_2XLARGE | R4\_4XLARGE | R4\_8XLARGE | SMALL | MEDIUM | LARGE | XLARGE | LARGE\_2X | LARGE\_4X | LARGE\_8X | LARGE\_12X

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "apiCache": {
    "apiCachingBehavior": "string",
    "atRestEncryptionEnabled": boolean,
    "healthMetricsConfig": "string",
    "status": "string",
    "transitEncryptionEnabled": boolean,
    "ttl": number,
    "type": "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [apiCache](#)

The ApiCache object.

Type: [ApiCache](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

## ConcurrentModificationException

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

## InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# CreateApiKey

Creates a unique key that you can distribute to clients who invoke your API.

## Request Syntax

```
POST /v1/apis/apiId/apikeys HTTP/1.1
Content-type: application/json

{
  "descriptionexpires
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The ID for your GraphQL API.

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### description

A description of the purpose of the API key.

Type: String

Required: No

### expires

From the creation time, the time after which the API key expires. The date is represented as seconds since the epoch, rounded down to the nearest hour. The default value for this parameter is 7 days from creation time. For more information, see [ApiKey](#).

Type: Long

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "apiKey": {
    "deletes": number,
    "description": "string",
    "expires": number,
    "id": "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### apiKey

The API key.

Type: [ApiKey](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ApiKeyLimitExceededException**

The API key exceeded a limit. Try your request again.

HTTP Status Code: 400

### **ApiKeyValidityOutOfBoundsException**

The API key expiration must be set to a value between 1 and 365 days from creation (for `CreateApiKey`) or from update (for `UpdateApiKey`).

HTTP Status Code: 400

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **LimitExceededException**

The request exceeded a limit. Try your request again.

HTTP Status Code: 429

### **LimitExceededException**

The request exceeded a limit. Try your request again.

HTTP Status Code: 429

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### **UnauthorizedException**

You aren't authorized to perform this operation.

HTTP Status Code: 401

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateChannelNamespace

Creates a ChannelNamespace for an Api.

## Request Syntax

```
POST /v2/apis/apiId/channelNamespaces HTTP/1.1
Content-type: application/json

{
  "codeHandlers": "string",
  "handlerConfigs": {
    "onPublish": {
      "behavior": "string",
      "integration": {
        "dataSourceName": "string",
        "lambdaConfig": {
          "invokeType": "string"
        }
      }
    },
    "onSubscribe": {
      "behavior": "string",
      "integration": {
        "dataSourceName": "string",
        "lambdaConfig": {
          "invokeType": "string"
        }
      }
    }
  },
  "name": "string",
  "publishAuthModes": [
    {
      "authType": "string"
    }
  ],
  "subscribeAuthModes": [
    {
      "authType": "string"
    }
  ],
  "tags": {
```

```
    "string" : "string"
  }
}
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The Api ID.

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### codeHandlers

The event handler functions that run custom business logic to process published events and subscribe requests.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32768.

Required: No

### handlerConfigs

The configuration for the OnPublish and OnSubscribe handlers.

Type: [HandlerConfigs](#) object

Required: No

### name

The name of the ChannelNamespace. This name must be unique within the Api

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: ([A-Za-z0-9](?:[A-Za-z0-9\-\\_]{0,48}[A-Za-z0-9])?)?

Required: Yes

### [publishAuthModes](#)

The authorization mode to use for publishing messages on the channel namespace. This configuration overrides the default Api authorization configuration.

Type: Array of [AuthMode](#) objects

Required: No

### [subscribeAuthModes](#)

The authorization mode to use for subscribing to messages on the channel namespace. This configuration overrides the default Api authorization configuration.

Type: Array of [AuthMode](#) objects

Required: No

### [tags](#)

A map with keys of TagKey objects and values of TagValue objects.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: ^(?!aws:)[ a-zA-Z+-=.\_:/]+\$

Value Length Constraints: Maximum length of 256.

Value Pattern: ^[\s\w+-=\\_.:/@]\*\$

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"channelNamespace    "apiId: "string",  
    "channelNamespaceArn: "string",  
    "codeHandlers: "string",  
    "created: number,  
    "handlerConfigs        "onPublish            "behavior: "string",  
            "integration                "dataSourceName: "string",  
                "lambdaConfig                    "invokeType: "string"  
                }  
            }  
        }  
    },  
    "onSubscribe        "behavior: "string",  
        "integration            "dataSourceName: "string",  
            "lambdaConfig                "invokeType: "string"  
            }  
        }  
    }  
},  
"lastModified: number,  
"name: "string",  
"publishAuthModes    {  
        "authType: "string"  
    }  
],  
"subscribeAuthModes    {  
        "authType: "string"  
    }  
],  
"tags    "string" : "string"  
}  
}  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [channelNamespace](#)

The ChannelNamespace object.

Type: [ChannelNamespace](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **ConcurrentModificationException**

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### **ConflictException**

A conflict with a previous successful update is detected. This typically occurs when the previous update did not have time to propagate before the next update was made. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## ServiceQuotaExceededException

The operation exceeded the service quota for this resource.

HTTP Status Code: 402

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateDataSource

Creates a DataSource object.

## Request Syntax

```
POST /v1/apis/apiId/datasources HTTP/1.1
Content-type: application/json
```

```
{
  "description": "string",
  "dynamodbConfig": {
    "awsRegion": "string",
    "deltaSyncConfig": {
      "baseTableTTL": number,
      "deltaSyncTableName": "string",
      "deltaSyncTableTTL": number
    },
    "tableName": "string",
    "useCallerCredentials": boolean,
    "versioned": boolean
  },
  "elasticsearchConfig": {
    "awsRegion": "string",
    "endpoint": "string"
  },
  "eventBridgeConfig": {
    "eventBusArn": "string"
  },
  "httpConfig": {
    "authorizationConfig": {
      "authorizationType": "string",
      "awsIamConfig": {
        "signingRegion": "string",
        "signingServiceName": "string"
      }
    },
    "endpoint": "string"
  },
  "lambdaConfig": {
    "lambdaFunctionArn": "string"
  },
  "metricsConfig": "string",
```

```
"name": "string",
"openSearchServiceConfig": {
    "awsRegion": "string",
    "endpoint": "string"
},
"relationalDatabaseConfig": {
    "rdsHttpEndpointConfig": {
        "awsRegion": "string",
        "awsSecretStoreArn": "string",
        "databaseName": "string",
        "dbClusterIdentifier": "string",
        "schema": "string"
    },
    "relationalDatabaseSourceType": "string"
},
"serviceRoleArn": "string",
"type": "string"
}
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The API ID for the GraphQL API for the DataSource.

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### description

A description of the DataSource.

Type: String

Required: No

### dynamodbConfig

Amazon DynamoDB settings.

Type: [DynamodbDataSourceConfig](#) object

Required: No

### [elasticsearchConfig](#)

Amazon OpenSearch Service settings.

As of September 2021, Amazon Elasticsearch service is Amazon OpenSearch Service. This configuration is deprecated. For new data sources, use [CreateDataSource:openSearchServiceConfig](#) to create an OpenSearch data source.

Type: [ElasticsearchDataSourceConfig](#) object

Required: No

### [eventBridgeConfig](#)

Amazon EventBridge settings.

Type: [EventBridgeDataSourceConfig](#) object

Required: No

### [httpConfig](#)

HTTP endpoint settings.

Type: [HttpDataSourceConfig](#) object

Required: No

### [lambdaConfig](#)

AWS Lambda settings.

Type: [LambdaDataSourceConfig](#) object

Required: No

### [metricsConfig](#)

Enables or disables enhanced data source metrics for specified data sources. Note that `metricsConfig` won't be used unless the `dataSourceLevelMetricsBehavior` value is set to `PER_DATA_SOURCE_METRICS`. If the `dataSourceLevelMetricsBehavior` is set to

FULL\_REQUEST\_DATA\_SOURCE\_METRICS instead, metricsConfig will be ignored. However, you can still set its value.

metricsConfig can be ENABLED or DISABLED.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

### [name](#)

A user-supplied name for the DataSource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: Yes

### [openSearchServiceConfig](#)

Amazon OpenSearch Service settings.

Type: [OpenSearchServiceDataSourceConfig](#) object

Required: No

### [relationalDatabaseConfig](#)

Relational database settings.

Type: [RelationalDatabaseDataSourceConfig](#) object

Required: No

### [serviceRoleArn](#)

The AWS Identity and Access Management (IAM) service role Amazon Resource Name (ARN) for the data source. The system assumes this role when accessing the data source.

Type: String

Required: No

### type

The type of the DataSource.

Type: String

Valid Values: AWS\_LAMBDA | AMAZON\_DYNAMODB | AMAZON\_ELASTICSEARCH | NONE | HTTP | RELATIONAL\_DATABASE | AMAZON\_OPENSEARCH\_SERVICE | AMAZON\_EVENTBRIDGE | AMAZON\_BEDROCK\_RUNTIME

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "dataSource": {
    "dataSourceArn": "string",
    "description": "string",
    "dynamodbConfig": {
      "awsRegion": "string",
      "deltaSyncConfig": {
        "baseTableTTL": number,
        "deltaSyncTableName": "string",
        "deltaSyncTableTTL": number
      },
      "tableName": "string",
      "useCallerCredentials": boolean,
      "versioned": boolean
    },
    "elasticsearchConfig": {
      "awsRegion": "string",
      "endpoint": "string"
    },
    "eventBridgeConfig": {
      "eventBusArn": "string"
    },
    "httpConfig": {
      "authorizationConfig": {
        "authorizationType": "string"
      }
    }
  }
}
```

```
        "authorizationType": "string",
        "awsIamConfig": {
            "signingRegion": "string",
            "signingServiceName": "string"
        },
        "endpoint": "string"
    },
    "lambdaConfig": {
        "lambdaFunctionArn": "string"
    },
    "metricsConfig": "string",
    "name": "string",
    "openSearchServiceConfig": {
        "awsRegion": "string",
        "endpoint": "string"
    },
    "relationalDatabaseConfig": {
        "rdsHttpEndpointConfig": {
            "awsRegion": "string",
            "awsSecretStoreArn": "string",
            "databaseName": "string",
            "dbClusterIdentifier": "string",
            "schema": "string"
        },
        "relationalDatabaseSourceType": "string"
    },
    "serviceRoleArn": "string",
    "type": "string"
}
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [dataSource](#)

The `DataSource` object.

Type: [DataSource](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **ConcurrentModificationException**

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### **UnauthorizedException**

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateDomainName

Creates a custom DomainName object.

## Request Syntax

```
POST /v1/domainnames HTTP/1.1
Content-type: application/json

{
  "certificateArn": "string",
  "description": "string",
  "domainName": "string",
  "tags": {
    "string" : "string"
  }
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### [certificateArn](#)

The Amazon Resource Name (ARN) of the certificate. This can be an AWS Certificate Manager (ACM) certificate or an AWS Identity and Access Management (IAM) server certificate.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[a-zA-Z-]\*:(acm|iam):[a-zA-Z0-9-]\*:\d{12}:(certificate|server-certificate)/[\dA-Za-z\_-/-]\*\$

Required: Yes

### [description](#)

A description of the DomainName.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: ^ . \*\$

Required: No

### domainName

The domain name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 253.

Pattern: ^(\\*\[\w\d-\]\*\.)?([\w\d-]+\.)+[\w\d-]+\$

Required: Yes

### tags

A map with keys of TagKey objects and values of TagValue objects.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: ^(?!aws:)[ a-zA-Z+-=.\_:/]+\$

Value Length Constraints: Maximum length of 256.

Value Pattern: ^[\s\w+-=\.\.:/\@]\*\$

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{  
  "domainNameConfig": {  
    "appsyncDomainName": "string",  
    "certificateArn": "string",  
    "description": "string",  
    "domainName": "string",  
    "domainNameArn": "string",  
    "hostedZoneId": "string",  
    "tags": {  
      "string" : "string"  
    }  
  }  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [domainNameConfig](#)

The configuration for the DomainName.

Type: [DomainNameConfig](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You don't have access to perform this operation on this resource.

HTTP Status Code: 403

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing.  
Check the field values, and then try again.

HTTP Status Code: 400

## InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateFunction

Creates a Function object.

A function is a reusable entity. You can use multiple functions to compose the resolver logic.

## Request Syntax

```
POST /v1/apis/apiId/functions HTTP/1.1
Content-type: application/json

{
  "code": "string",
  "dataSourceName": "string",
  "description": "string",
  "functionVersion": "string",
  "maxBatchSize": number,
  "name": "string",
  "requestMappingTemplate": "string",
  "responseMappingTemplate": "string",
  "runtime": {
    "name": "string",
    "runtimeVersion": "string"
  },
  "syncConfig": {
    "conflictDetection": "string",
    "conflictHandler": "string",
    "lambdaConflictHandlerConfig": {
      "lambdaConflictHandlerArn": "string"
    }
  }
}
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The GraphQL API ID.

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### code

The function code that contains the request and response functions. When code is used, the runtime is required. The runtime value must be APPSYNC\_JS.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32768.

Required: No

### dataSourceName

The Function DataSource name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: Yes

### description

The Function description.

Type: String

Required: No

### functionVersion

The version of the request mapping template. Currently, the supported value is 2018-05-29. Note that when using VTL and mapping templates, the functionVersion is required.

Type: String

Required: No

## maxBatchSize

The maximum batching size for a resolver.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2000.

Required: No

## name

The Function name. The function name does not have to be unique.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: Yes

## requestMappingTemplate

The Function request mapping template. Functions support only the 2018-05-29 version of the request mapping template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: ^.\*\$

Required: No

## responseMappingTemplate

The Function response mapping template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: ^.\*\$

Required: No

## runtime

Describes a runtime used by an AWS AppSync pipeline resolver or AWS AppSync function. Specifies the name and version of the runtime to use. Note that if a runtime is specified, code must also be specified.

Type: [AppSyncRuntime](#) object

Required: No

## syncConfig

Describes a Sync configuration for a resolver.

Specifies which Conflict Detection strategy and Resolution strategy to use when the resolver is invoked.

Type: [SyncConfig](#) object

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "functionConfiguration": {
    "code": "string",
    "dataSourceName": "string",
    "description": "string",
    "functionArn": "string",
    "functionId": "string",
    "functionVersion": "string",
    "maxBatchSize": number,
    "name": "string",
    "requestMappingTemplate": "string",
    "responseMappingTemplate": "string",
    "runtime": {
      "name": "string",
      "runtimeVersion": "string"
    },
    "syncConfig": {
```

```
"conflictDetection": "string",  
"conflictHandler": "string",  
"lambdaConflictHandlerConfig": {  
    "lambdaConflictHandlerArn": "string"  
}  
}  
}  
}  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### functionConfiguration

The Function object.

Type: [FunctionConfiguration object](#)

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **ConcurrentModificationException**

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateGraphqlApi

Creates a GraphqlApi object.

## Request Syntax

```
POST /v1/apis HTTP/1.1
Content-type: application/json

{
  "additionalAuthenticationProviders": [
    {
      "authenticationType": "string",
      "lambdaAuthorizerConfig": {
        "authorizerResultTtlInSeconds": number,
        "authorizerUri": "string",
        "identityValidationExpression": "string"
      },
      "openIDConnectConfig": {
        "authTTL": number,
        "clientId": "string",
        "iatTTL": number,
        "issuer": "string"
      },
      "userPoolConfig": {
        "appIdClientRegex": "string",
        "awsRegion": "string",
        "userPoolId": "string"
      }
    }
  ],
  "apiType": "string",
  "authenticationType": "string",
  "enhancedMetricsConfig": {
    "dataSourceLevelMetricsBehavior": "string",
    "operationLevelMetricsConfig": "string",
    "resolverLevelMetricsBehavior": "string"
  },
  "introspectionConfig": "string",
  "lambdaAuthorizerConfig": {
    "authorizerResultTtlInSeconds": number,
    "authorizerUri": "string",
    "identityValidationExpression": "string"
  }
}
```

```
},
"logConfig": {
  "cloudWatchLogsRoleArn": "string",
  "excludeVerboseContent": boolean,
  "fieldLogLevel": "string"
},
"mergedApiExecutionRoleArn": "string",
"name": "string",
"openIDConnectConfig": {
  "authTTL": number,
  "clientId": "string",
  "iatTTL": number,
  "issuer": "string"
},
"ownerContact": "string",
"queryDepthLimit": number,
"resolverCountLimit": number,
"tags": {
  "string" : "string"
},
"userPoolConfig": {
  "appIdClientRegex": "string",
  "awsRegion": "string",
  "defaultAction": "string",
  "userPoolId": "string"
},
"visibility": "string",
"xrayEnabled": boolean
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### [additionalAuthenticationProviders](#)

A list of additional authentication providers for the GraphqlApi API.

Type: Array of [AdditionalAuthenticationProvider](#) objects

Required: No

### apiType

The value that indicates whether the GraphQL API is a standard API (GRAPHQL) or merged API (MERGED).

Type: String

Valid Values: GRAPHQL | MERGED

Required: No

### authenticationType

The authentication type: API key, AWS Identity and Access Management (IAM), OpenID Connect (OIDC), Amazon Cognito user pools, or AWS Lambda.

Type: String

Valid Values: API\_KEY | AWS\_IAM | AMAZON\_COGNITO\_USER\_POOLS | OPENID\_CONNECT | AWS\_LAMBDA

Required: Yes

### enhancedMetricsConfig

The enhancedMetricsConfig object.

Type: [EnhancedMetricsConfig](#) object

Required: No

### introspectionConfig

Sets the value of the GraphQL API to enable (ENABLED) or disable (DISABLED) introspection. If no value is provided, the introspection configuration will be set to ENABLED by default. This field will produce an error if the operation attempts to use the introspection feature while this field is disabled.

For more information about introspection, see [GraphQL introspection](#).

Type: String

Valid Values: ENABLED | DISABLED

Required: No

## [lambdaAuthorizerConfig](#)

Configuration for AWS Lambda function authorization.

Type: [LambdaAuthorizerConfig](#) object

Required: No

## [logConfig](#)

The Amazon CloudWatch Logs configuration.

Type: [LogConfig](#) object

Required: No

## [mergedApiExecutionRoleArn](#)

The Identity and Access Management service role ARN for a merged API. The AppSync service assumes this role on behalf of the Merged API to validate access to source APIs at runtime and to prompt the AUTO\_MERGE to update the merged API endpoint with the source API changes automatically.

Type: String

Required: No

## [name](#)

A user-supplied name for the GraphqlApi.

Type: String

Required: Yes

## [openIDConnectConfig](#)

The OIDC configuration.

Type: [OpenIDConnectConfig](#) object

Required: No

## [ownerContact](#)

The owner contact information for an API resource.

This field accepts any string input with a length of 0 - 256 characters.

Type: String

Required: No

### queryDepthLimit

The maximum depth a query can have in a single request. Depth refers to the amount of nested levels allowed in the body of query. The default value is 0 (or unspecified), which indicates there's no depth limit. If you set a limit, it can be between 1 and 75 nested levels. This field will produce a limit error if the operation falls out of bounds.

Note that fields can still be set to nullable or non-nullable. If a non-nullable field produces an error, the error will be thrown upwards to the first nullable field available.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 75.

Required: No

### resolverCountLimit

The maximum number of resolvers that can be invoked in a single request. The default value is 0 (or unspecified), which will set the limit to 10000. When specified, the limit value can be between 1 and 10000. This field will produce a limit error if the operation falls out of bounds.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 10000.

Required: No

### tags

A TagMap object.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[ a-zA-Z+-=._:/]+$`

Value Length Constraints: Maximum length of 256.

Value Pattern: `^[\s\w+-=\.:/@]*$`

Required: No

### [userPoolConfig](#)

The Amazon Cognito user pool configuration.

Type: [UserPoolConfig](#) object

Required: No

### [visibility](#)

Sets the value of the GraphQL API to public (GLOBAL) or private (PRIVATE). If no value is provided, the visibility will be set to GLOBAL by default. This value cannot be changed once the API has been created.

Type: String

Valid Values: GLOBAL | PRIVATE

Required: No

### [xrayEnabled](#)

A flag indicating whether to use AWS X-Ray tracing for the GraphqlApi.

Type: Boolean

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "graphqlApi": {
    "additionalAuthenticationProviders": [
      {
        "authenticationType": "string",
        "lambdaAuthorizerConfig": {
          "authorizerResultTtlInSeconds": number,
          "authorizerUri": "string",
          "identityValidationExpression": "string"
        },
      ],
    ],
  },
}
```

```
"openIDConnectConfig": {  
    "authTTL": number,  
    "clientId": "string",  
    "iatTTL": number,  
    "issuer": "string"  
},  
"userPoolConfig": {  
    "appIdClientRegex": "string",  
    "awsRegion": "string",  
    "userPoolId": "string"  
}  
}  
]  
,"apiId": "string",  
"apiType": "string",  
"arn": "string",  
"authenticationType": "string",  
"dns": {  
    "string" : "string"  
},  
"enhancedMetricsConfig": {  
    "dataSourceLevelMetricsBehavior": "string",  
    "operationLevelMetricsConfig": "string",  
    "resolverLevelMetricsBehavior": "string"  
},  
"introspectionConfig": "string",  
"lambdaAuthorizerConfig": {  
    "authorizerResultTtlInSeconds": number,  
    "authorizerUri": "string",  
    "identityValidationExpression": "string"  
},  
"logConfig": {  
    "cloudWatchLogsRoleArn": "string",  
    "excludeVerboseContent": boolean,  
    "fieldLogLevel": "string"  
},  
"mergedApiExecutionRoleArn": "string",  
"name": "string",  
"openIDConnectConfig": {  
    "authTTL": number,  
    "clientId": "string",  
    "iatTTL": number,  
    "issuer": "string"  
},
```

```
"owner": "string",
"ownerContact": "string",
"queryDepthLimit": number,
"resolverCountLimit": number,
"tags": {
    "string" : "string"
},
"uris": {
    "string" : "string"
},
"userPoolConfig": {
    "appIdClientRegex": "string",
    "awsRegion": "string",
    "defaultAction": "string",
    "userPoolId": "string"
},
"visibility": "string",
"wafWebAclArn": "string",
"xrayEnabled": boolean
}
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [graphqlApi](#)

The GraphqlApi.

Type: [GraphqlApi](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ApiLimitExceededException**

The GraphQL API exceeded a limit. Try your request again.

HTTP Status Code: 400

## BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

## ConcurrentModificationException

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

## InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## LimitExceededException

The request exceeded a limit. Try your request again.

HTTP Status Code: 429

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateResolver

Creates a Resolver object.

A resolver converts incoming requests into a format that a data source can understand, and converts the data source's responses into GraphQL.

## Request Syntax

```
POST /v1/apis/apiId/types/typeName/resolvers HTTP/1.1
Content-type: application/json

{
  "cachingConfigcachingKeysstring" ],
    "ttlnumber
  },
  "codestring",
  "dataSourceNamestring",
  "fieldNamestring",
  "kindstring",
  "maxBatchSizenumber,
  "metricsConfigstring",
  "pipelineConfigfunctionsstring" ]
  },
  "requestMappingTemplatestring",
  "responseMappingTemplatestring",
  "runtimenamestring",
    "runtimeVersionstring"
  },
  "syncConfigconflictDetectionstring",
    "conflictHandlerstring",
    "lambdaConflictHandlerConfiglambdaConflictHandlerArnstring"
    }
  }
}
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The ID for the GraphQL API for which the resolver is being created.

Required: Yes

### typeName

The name of the Type.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### cachingConfig

The caching configuration for the resolver.

Type: [CachingConfig object](#)

Required: No

### code

The `resolver` code that contains the request and response functions. When `code` is used, the `runtime` is required. The `runtime` value must be `APPSYNC_JS`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32768.

Required: No

## [dataSourceName](#)

The name of the data source for which the resolver is being created.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: No

## [fieldName](#)

The name of the field to attach the resolver to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: Yes

## [kind](#)

The resolver type.

- **UNIT:** A UNIT resolver type. A UNIT resolver is the default resolver type. You can use a UNIT resolver to run a GraphQL query against a single data source.
- **PIPELINE:** A PIPELINE resolver type. You can use a PIPELINE resolver to invoke a series of Function objects in a serial manner. You can use a pipeline resolver to run a GraphQL query against multiple data sources.

Type: String

Valid Values: UNIT | PIPELINE

Required: No

## [maxBatchSize](#)

The maximum batching size for a resolver.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2000.

Required: No

### [metricsConfig](#)

Enables or disables enhanced resolver metrics for specified resolvers. Note that `metricsConfig` won't be used unless the `resolverLevelMetricsBehavior` value is set to `PER_RESOLVER_METRICS`. If the `resolverLevelMetricsBehavior` is set to `FULL_REQUEST_RESOLVER_METRICS` instead, `metricsConfig` will be ignored. However, you can still set its value.

`metricsConfig` can be ENABLED or DISABLED.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

### [pipelineConfig](#)

The PipelineConfig.

Type: [PipelineConfig](#) object

Required: No

### [requestMappingTemplate](#)

The mapping template to use for requests.

A resolver uses a request mapping template to convert a GraphQL expression into a format that a data source can understand. Mapping templates are written in Apache Velocity Template Language (VTL).

VTL request mapping templates are optional when using an AWS Lambda data source. For all other data sources, VTL request and response mapping templates are required.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: ^ . \*\$

Required: No

### [responseMappingTemplate](#)

The mapping template to use for responses from the data source.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: ^ . \*\$

Required: No

### [runtime](#)

Describes a runtime used by an AWS AppSync pipeline resolver or AWS AppSync function.

Specifies the name and version of the runtime to use. Note that if a runtime is specified, code must also be specified.

Type: [AppSyncRuntime](#) object

Required: No

### [syncConfig](#)

The SyncConfig for a resolver attached to a versioned data source.

Type: [SyncConfig](#) object

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "resolver": {
    "cachingConfig": {
      "cachingKeys": [ "string" ],
      "ttl": number
    },
  },
}
```

```
"code": "string",
"dataSourceName": "string",
"fieldName": "string",
"kind": "string",
"maxBatchSize": number,
"metricsConfig": "string",
"pipelineConfig": {
    "functions": [ "string" ]
},
"requestMappingTemplate": "string",
"resolverArn": "string",
"responseMappingTemplate": "string",
"runtime": {
    "name": "string",
    "runtimeVersion": "string"
},
"syncConfig": {
    "conflictDetection": "string",
    "conflictHandler": "string",
    "lambdaConflictHandlerConfig": {
        "lambdaConflictHandlerArn": "string"
    }
},
"typeName": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### resolver

The Resolver object.

Type: [Resolver](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

## ConcurrentModificationException

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

## InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateType

Creates a Type object.

## Request Syntax

```
POST /v1/apis/apiId/types HTTP/1.1
Content-type: application/json

{
  "definition": "string",
  "format": "string"
}
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The API ID.

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### definition

The type definition, in GraphQL Schema Definition Language (SDL) format.

For more information, see the [GraphQL SDL documentation](#).

Type: String

Required: Yes

### format

The type format: SDL or JSON.

Type: String

Valid Values: SDL | JSON

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "type": {
    "arn": "string",
    "definition": "string",
    "description": "string",
    "format": "string",
    "name": "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [type](#)

The Type object.

Type: [Type](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### ConcurrentModificationException

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

# DeleteApi

Deletes an Api object

## Request Syntax

```
DELETE /v2/apis/apiId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The Api ID.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

You don't have access to perform this operation on this resource.

HTTP Status Code: 403

## BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

## ConcurrentModificationException

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

## InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteApiCache

Deletes an ApiCache object.

## Request Syntax

```
DELETE /v1/apis/apiId/ApiCaches HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The API ID.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### ConcurrentModificationException

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

# DeleteApiKey

Deletes an API key.

## Request Syntax

```
DELETE /v1/apis/apiId/apikeys/id HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The API ID.

Required: Yes

### id

The ID for the API key.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

## InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# DeleteChannelNamespace

Deletes a ChannelNamespace.

## Request Syntax

```
DELETE /v2/apis/apiId/channelNamespaces/name HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The ID of the Api associated with the ChannelNamespace.

Required: Yes

### name

The name of the ChannelNamespace.

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: ([A-Za-z0-9](?:[A-Za-z0-9\-\-]{0,48}[A-Za-z0-9])?)

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

You don't have access to perform this operation on this resource.

HTTP Status Code: 403

### BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### ConcurrentModificationException

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteDataSource

Deletes a DataSource object.

## Request Syntax

```
DELETE /v1/apis/apiId/datasources/name HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The API ID.

Required: Yes

### name

The name of the data source.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **ConcurrentModificationException**

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### **UnauthorizedException**

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteDomainName

Deletes a custom DomainName object.

## Request Syntax

```
DELETE /v1/domainnames/domainName HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### [domainName](#)

The domain name.

Length Constraints: Minimum length of 1. Maximum length of 253.

Pattern:  $^(\wedge[\wedge\dash]\wedge*\.\wedge)?([\wedge\dash]+\.\wedge)+[\wedge\dash]+\$$

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## AccessDeniedException

You don't have access to perform this operation on this resource.

HTTP Status Code: 403

## BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

## ConcurrentModificationException

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

## InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteFunction

Deletes a Function.

## Request Syntax

```
DELETE /v1/apis/apiId/functions/functionId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The GraphQL API ID.

Required: Yes

### functionId

The Function ID.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **ConcurrentModificationException**

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### **UnauthorizedException**

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteGraphqlApi

Deletes a GraphqlApi object.

## Request Syntax

```
DELETE /v1/apis/apiId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The API ID.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

You don't have access to perform this operation on this resource.

HTTP Status Code: 403

## BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

## ConcurrentModificationException

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

## InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteResolver

Deletes a Resolver object.

## Request Syntax

```
DELETE /v1/apis/apiId/types/typeName/resolvers/fieldName HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The API ID.

Required: Yes

### fieldName

The resolver field name.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: Yes

### typeName

The name of the resolver type.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

HTTP/1.1 200

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **ConcurrentModificationException**

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### **UnauthorizedException**

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteType

Deletes a Type object.

## Request Syntax

```
DELETE /v1/apis/apiId/types/typeName HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The API ID.

Required: Yes

### typeName

The type name.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **ConcurrentModificationException**

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### **UnauthorizedException**

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DisassociateApi

Removes an ApiAssociation object from a custom domain.

## Request Syntax

```
DELETE /v1/domainnames/domainName/apiassociation HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### [domainName](#)

The domain name.

Length Constraints: Minimum length of 1. Maximum length of 253.

Pattern: ^(\\*\[\w\d-\]\*\.)?([\w\d-]+\.\.)\*[\w\d-]+\$

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## AccessDeniedException

You don't have access to perform this operation on this resource.

HTTP Status Code: 403

## BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

## ConcurrentModificationException

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

## InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DisassociateMergedGraphqlApi

Deletes an association between a Merged API and source API using the source API's identifier and the association ID.

## Request Syntax

```
DELETE /v1/sourceApis/sourceApiIdentifier/mergedApiAssociations/associationId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### associationId

The ID generated by the AppSync service for the source API association.

Required: Yes

### sourceApilidentifier

The identifier of the AppSync Source API. This is generated by the AppSync service. In most cases, source APIs (especially in your account) only require the API ID value or ARN of the source API. However, source APIs from other accounts (cross-account use cases) strictly require the full resource ARN of the source API.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "sourceApiAssociationStatus": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [sourceApiAssociationStatus](#)

The state of the source API association.

Type: String

Valid Values: MERGE\_SCHEDULED | MERGE\_FAILED | MERGE\_SUCCESS | MERGE\_IN\_PROGRESS | AUTO\_MERGE\_SCHEDULE\_FAILED | DELETION\_SCHEDULED | DELETION\_IN\_PROGRESS | DELETION\_FAILED

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **ConcurrentModificationException**

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DisassociateSourceGraphqlApi

Deletes an association between a Merged API and source API using the Merged API's identifier and the association ID.

## Request Syntax

```
DELETE /v1/mergedApis/mergedApiIdentifier/sourceApiAssociations/associationId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### associationId

The ID generated by the AppSync service for the source API association.

Required: Yes

### mergedApilIdentifier

The identifier of the AppSync Merged API. This is generated by the AppSync service. In most cases, Merged APIs (especially in your account) only require the API ID value or ARN of the merged API. However, Merged APIs in other accounts (cross-account use cases) strictly require the full resource ARN of the merged API.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "sourceApiAssociationStatus": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [sourceApiAssociationStatus](#)

The state of the source API association.

Type: String

Valid Values: MERGE\_SCHEDULED | MERGE\_FAILED | MERGE\_SUCCESS | MERGE\_IN\_PROGRESS | AUTO\_MERGE\_SCHEDULE\_FAILED | DELETION\_SCHEDULED | DELETION\_IN\_PROGRESS | DELETION\_FAILED

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **ConcurrentModificationException**

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# EvaluateCode

Evaluates the given code and returns the response. The code definition requirements depend on the specified runtime. For APPSYNC\_JS runtimes, the code defines the request and response functions. The request function takes the incoming request after a GraphQL operation is parsed and converts it into a request configuration for the selected data source operation. The response function interprets responses from the data source and maps it to the shape of the GraphQL field output type.

## Request Syntax

```
POST /v1/dataplane-evaluatecode HTTP/1.1
Content-type: application/json

{
  "code": "string",
  "context": "string",
  "function": "string",
  "runtime": {
    "name": "string",
    "runtimeVersion": "string"
  }
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### code

The code definition to be evaluated. Note that code and runtime are both required for this action. The runtime value must be APPSYNC\_JS.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32768.

Required: Yes

### context

The map that holds all of the contextual information for your resolver invocation. A context is required for this action.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 28000.

Pattern: ^[\s\S]\*\$

Required: Yes

### function

The function within the code to be evaluated. If provided, the valid values are request and response.

Type: String

Required: No

### runtime

The runtime to be used when evaluating the code. Currently, only the APPSYNC\_JS runtime is supported.

Type: [AppSyncRuntime](#) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "error": {
    "codeErrors": [
      {
        "errorType": "string",
        "location": {
          "column": number,
```

```
        "line": number,
        "span": number
    },
    "value": "string"
}
],
"message": "string"
},
"evaluationResult": "string",
"logs": [ "string" ],
"outErrors": "string",
"stash": "string
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### error

Contains the payload of the response error.

Type: [EvaluateCodeErrorDetail](#) object

### evaluationResult

The result of the evaluation operation.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 65536.

Pattern: ^[\s\S]\*\$

### logs

A list of logs that were generated by calls to util.log.info and util.log.error in the evaluated code.

Type: Array of strings

### outErrors

The list of runtime errors that are added to the GraphQL operation response.

Type: String

Pattern: ^[\s\S]\*\$

### stash

An object available inside each resolver and function handler. A single `stash` object lives through a single resolver run. Therefore, you can use the `stash` to pass arbitrary data across request and response handlers and across functions in a pipeline resolver.

Type: String

Pattern: ^[\s\S]\*\$

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You don't have access to perform this operation on this resource.

HTTP Status Code: 403

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# EvaluateMappingTemplate

Evaluates a given template and returns the response. The mapping template can be a request or response template.

Request templates take the incoming request after a GraphQL operation is parsed and convert it into a request configuration for the selected data source operation. Response templates interpret responses from the data source and map it to the shape of the GraphQL field output type.

Mapping templates are written in the Apache Velocity Template Language (VTL).

## Request Syntax

```
POST /v1/dataplane-evaluatetemplate HTTP/1.1
Content-type: application/json

{
    "contexttemplate
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### context

The map that holds all of the contextual information for your resolver invocation. A context is required for this action.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 28000.

Pattern: ^[\s\S]\*\$

Required: Yes

## template

The mapping template; this can be a request or response template. A template is required for this action.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 65536.

Pattern: ^[\s\S]\*\$

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "error": {
    "message": "string"
  },
  "evaluationResult": "string",
  "logs": [ "string" ],
  "outErrors": "string",
  "stash": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### error

The ErrorDetail object.

Type: [ErrorDetail](#) object

### evaluationResult

The mapping template; this can be a request or response template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 65536.

Pattern: ^[\s\S]\*\$

## logs

A list of logs that were generated by calls to `util.log.info` and `util.log.error` in the evaluated code.

Type: Array of strings

## outErrors

The list of runtime errors that are added to the GraphQL operation response.

Type: String

Pattern: ^[\s\S]\*\$

## stash

An object available inside each resolver and function handler. A single `stash` object lives through a single resolver run. Therefore, you can use the `stash` to pass arbitrary data across request and response handlers and across functions in a pipeline resolver.

Type: String

Pattern: ^[\s\S]\*\$

# Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## **AccessDeniedException**

You don't have access to perform this operation on this resource.

HTTP Status Code: 403

## **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

## InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# FlushApiCache

Flushes an ApiCache object.

## Request Syntax

```
DELETE /v1/apis/apiId/FlushCache HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The API ID.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### ConcurrentModificationException

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

# GetApi

Retrieves an Api object.

## Request Syntax

```
GET /v2/apis/apiId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The Api ID.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "api": {
    "apiArn": "string",
    "apiId": "string",
    "created": number,
    "dns": {
      "string": "string"
    },
    "eventConfig": {
      "authProviders": [
        {
          "authType": "string",
          "cognitoConfig": {
            "appIdClientRegex": "string",
            "region": "string"
          }
        }
      ]
    }
  }
}
```

```
        "awsRegion": "string",
        "userPoolId": "string"
    },
    "lambdaAuthorizerConfig": {
        "authorizerResultTtlInSeconds": number,
        "authorizerUri": "string",
        "identityValidationExpression": "string"
    },
    "openIDConnectConfig": {
        "authTTL": number,
        "clientId": "string",
        "iatTTL": number,
        "issuer": "string"
    }
}
],
"connectionAuthModes": [
    {
        "authType": "string"
    }
],
"defaultPublishAuthModes": [
    {
        "authType": "string"
    }
],
"defaultSubscribeAuthModes": [
    {
        "authType": "string"
    }
],
"logConfig": {
    "cloudWatchLogsRoleArn": "string",
    "logLevel": "string"
},
"name": "string",
"ownerContact": "string",
"tags": {
    "string" : "string"
},
"wafWebAclArn": "string",
"xrayEnabled": boolean
}
```

}

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [api](#)

The Api object.

Type: [Api](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You don't have access to perform this operation on this resource.

HTTP Status Code: 403

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetApiAssociation

Retrieves an ApiAssociation object.

## Request Syntax

```
GET /v1/domainnames/domainName/apiassociation HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### domainName

The domain name.

Length Constraints: Minimum length of 1. Maximum length of 253.

Pattern: ^(\\*\[\w\d-\]\*\.)?([\w\d-]+\.)+[\w\d-]+\$

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "apiAssociation": {
    "apiId": "string",
    "associationStatus": "string",
    "deploymentDetail": "string",
    "domainName": "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [apiAssociation](#)

The `ApiAssociation` object.

Type: [ApiAssociation](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You don't have access to perform this operation on this resource.

HTTP Status Code: 403

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetApiCache

Retrieves an ApiCache object.

## Request Syntax

```
GET /v1/apis/apiId/ApiCaches HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The API ID.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "apiCache": {
    "apiCachingBehavior": "string",
    "atRestEncryptionEnabled": boolean,
    "healthMetricsConfig": "string",
    "status": "string",
    "transitEncryptionEnabled": boolean,
    "ttl": number,
    "type": "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [apiCache](#)

The ApiCache object.

Type: [ApiCache](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **ConcurrentModificationException**

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### **UnauthorizedException**

You aren't authorized to perform this operation.

## HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetChannelNamespace

Retrieves the channel namespace for a specified Api.

## Request Syntax

```
GET /v2/apis/apiId/channelNamespaces/name HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The Api ID.

Required: Yes

### name

The name of the ChannelNamespace.

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: ([A-Za-z0-9](?:[A-Za-z0-9\-\\_]{0,48}[A-Za-z0-9])?)

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "channelNamespace": {
    "apiId": "string",
    "channelNamespaceArn": "string",
```

```
"codeHandlers": "string",
"created": number,
"handlerConfigs": {
  "onPublish": {
    "behavior": "string",
    "integration": {
      "dataSourceName": "string",
      "lambdaConfig": {
        "invokeType": "string"
      }
    }
  },
  "onSubscribe": {
    "behavior": "string",
    "integration": {
      "dataSourceName": "string",
      "lambdaConfig": {
        "invokeType": "string"
      }
    }
  }
},
"lastModified": number,
"name": "string",
"publishAuthModes": [
  {
    "authType": "string"
  }
],
"subscribeAuthModes": [
  {
    "authType": "string"
  }
],
"tags": {
  "string" : "string"
}
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## [channelNamespace](#)

The ChannelNamespace object.

Type: [ChannelNamespace](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You don't have access to perform this operation on this resource.

HTTP Status Code: 403

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### **UnauthorizedException**

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetDataSource

Retrieves a DataSource object.

## Request Syntax

```
GET /v1/apis/apiId/datasources/name HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The API ID.

Required: Yes

### name

The name of the data source.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "dataSource": {
    "dataSourceArn": "string",
    "description": "string",
    "dynamodbConfig": {
```

```
"awsRegion": "string",
"deltaSyncConfig": {
    "baseTableTTL": number,
    "deltaSyncTableName": "string",
    "deltaSyncTableTTL": number
},
"tableName": "string",
"useCallerCredentials": boolean,
"versioned": boolean
},
"elasticsearchConfig": {
    "awsRegion": "string",
    "endpoint": "string"
},
"eventBridgeConfig": {
    "eventBusArn": "string"
},
"httpConfig": {
    "authorizationConfig": {
        "authorizationType": "string",
        "awsIamConfig": {
            "signingRegion": "string",
            "signingServiceName": "string"
        }
    },
    "endpoint": "string"
},
"lambdaConfig": {
    "lambdaFunctionArn": "string"
},
"metricsConfig": "string",
"name": "string",
"openSearchServiceConfig": {
    "awsRegion": "string",
    "endpoint": "string"
},
"relationalDatabaseConfig": {
    "rdsHttpEndpointConfig": {
        "awsRegion": "string",
        "awsSecretStoreArn": "string",
        "databaseName": "string",
        "dbClusterIdentifier": "string",
        "schema": "string"
    }
},
```

```
        "relationalDatabaseSourceType": "string"
    },
    "serviceRoleArn": "string",
    "type": "string"
}
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [dataSource](#)

The DataSource object.

Type: [DataSource](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **ConcurrentModificationException**

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetDataSourceIntrospection

Retrieves the record of an existing introspection. If the retrieval is successful, the result of the introspection will also be returned. If the retrieval fails the operation, an error message will be returned instead.

## Request Syntax

```
GET /v1/datasources/introspections/introspectionId?  
includeModelsSDL=includeModelsSDL&maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### [includeModelsSDL](#)

A boolean flag that determines whether SDL should be generated for introspected types. If set to true, each model will contain an `sdl` property that contains the SDL for that type. The SDL only contains the type data and no additional metadata or directives.

### [introspectionId](#)

The introspection ID. Each introspection contains a unique ID that can be used to reference the introspection record.

Required: Yes

### [maxResults](#)

The maximum number of introspected types that will be returned in a single response.

Valid Range: Minimum value of 0. Maximum value of 25.

### [nextToken](#)

Determines the number of types to be returned in a single response before paginating. This value is typically taken from `nextToken` value from the previous response.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: `[\S]+`

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "introspectionId": "string",
  "introspectionResult": {
    "models": [
      {
        "fields": [
          {
            "length": number,
            "name": "string",
            "type": {
              "kind": "string",
              "name": "string",
              "type": "DataSourceIntrospectionModelFieldType",
              "values": [ "string" ]
            }
          }
        ],
        "indexes": [
          {
            "fields": [ "string" ],
            "name": "string"
          }
        ],
        "name": "string",
        "primaryKey": {
          "fields": [ "string" ],
          "name": "string"
        },
        "sdl": "string"
      }
    ],
    "nextToken": "string"
  },
  "introspectionStatus": "string",
```

```
    "introspectionStatusDetail": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [introspectionId](#)

The introspection ID. Each introspection contains a unique ID that can be used to reference the introspection record.

Type: String

### [introspectionResult](#)

The `DataSourceIntrospectionResult` object data.

Type: [DataSourceIntrospectionResult](#) object

### [introspectionStatus](#)

The status of the introspection during retrieval. By default, when a new introspection is being retrieved, the status will be set to PROCESSING. Once the operation has been completed, the status will change to SUCCESS or FAILED depending on how the data was parsed. A FAILED operation will return an error and its details as an `introspectionStatusDetail`.

Type: String

Valid Values: PROCESSING | FAILED | SUCCESS

### [introspectionStatusDetail](#)

The error detail field. When a FAILED `introspectionStatus` is returned, the `introspectionStatusDetail` will also return the exact error that was generated during the operation.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

## InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetDomainName

Retrieves a custom DomainName object.

## Request Syntax

```
GET /v1/domainnames/domainName HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### domainName

The domain name.

Length Constraints: Minimum length of 1. Maximum length of 253.

Pattern: ^(\\*\[\w\d-\]\*\.)?([\w\d-]+\.)+[\w\d-]+\$

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "domainNameConfig": {
    "appsyncDomainName": "string",
    "certificateArn": "string",
    "description": "string",
    "domainName": "string",
    "domainNameArn": "string",
    "hostedZoneId": "string",
    "tags": {
```

```
    "string" : "string"
}
}
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [domainNameConfig](#)

The configuration for the DomainName.

Type: [DomainNameConfig](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You don't have access to perform this operation on this resource.

HTTP Status Code: 403

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

## HTTP Status Code: 404

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetFunction

Get a Function.

## Request Syntax

```
GET /v1/apis/apiId/functions/functionId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The GraphQL API ID.

Required: Yes

### functionId

The Function ID.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "functionConfiguration": {
    "codedataSourceName": "string",
```

```
"description": "string",
"functionArn": "string",
"functionId": "string",
"functionVersion": "string",
"maxBatchSize": number,
"name": "string",
"requestMappingTemplate": "string",
"responseMappingTemplate": "string",
"runtime": {
    "name": "string",
    "runtimeVersion": "string"
},
"syncConfig": {
    "conflictDetection": "string",
    "conflictHandler": "string",
    "lambdaConflictHandlerConfig": {
        "lambdaConflictHandlerArn": "string"
    }
}
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### functionConfiguration

The Function object.

Type: [FunctionConfiguration object](#)

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ConcurrentModificationException**

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetGraphqlApi

Retrieves a GraphqlApi object.

## Request Syntax

```
GET /v1/apis/apiId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The API ID for the GraphQL API.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "graphqlApi": {
    "additionalAuthenticationProviders": [
      {
        "authenticationType": "string",
        "lambdaAuthorizerConfig": {
          "authorizerResultTtlInSeconds": number,
          "authorizerUri": "string",
          "identityValidationExpression": "string"
        },
        "openIDConnectConfig": {
          "authTTL": number,
          "clientId": "string",
          "iatTTL": number,
        }
      }
    ]
  }
}
```

```
        "issuer": "string"
    },
    "userPoolConfig": {
        "appIdClientRegex": "string",
        "awsRegion": "string",
        "userPoolId": "string"
    }
}
],
"apiId": "string",
"apiType": "string",
"arn": "string",
"authenticationType": "string",
"dns": {
    "string" : "string"
},
"enhancedMetricsConfig": {
    "dataSourceLevelMetricsBehavior": "string",
    "operationLevelMetricsConfig": "string",
    "resolverLevelMetricsBehavior": "string"
},
"introspectionConfig": "string",
"lambdaAuthorizerConfig": {
    "authorizerResultTtlInSeconds": number,
    "authorizerUri": "string",
    "identityValidationExpression": "string"
},
"logConfig": {
    "cloudWatchLogsRoleArn": "string",
    "excludeVerboseContent": boolean,
    "fieldLogLevel": "string"
},
"mergedApiExecutionRoleArn": "string",
"name": "string",
"openIDConnectConfig": {
    "authTTL": number,
    "clientId": "string",
    "iatTTL": number,
    "issuer": "string"
},
"owner": "string",
"ownerContact": "string",
"queryDepthLimit": number,
"resolverCountLimit": number,
```

```
"tags": {  
    "string": "string"  
},  
"uris": {  
    "string": "string"  
},  
"userPoolConfig": {  
    "appIdClientRegex": "string",  
    "awsRegion": "string",  
    "defaultAction": "string",  
    "userPoolId": "string"  
},  
"visibility": "string",  
"wafWebAclArn": "string",  
"xrayEnabled": boolean  
}  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [graphqlApi](#)

The GraphqlApi object.

Type: [GraphqlApi](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You don't have access to perform this operation on this resource.

HTTP Status Code: 403

## BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

## InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# GetGraphqlApiEnvironmentVariables

Retrieves the list of environmental variable key-value pairs associated with an API by its ID value.

## Request Syntax

```
GET /v1/apis/apiId/environmentVariables HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The ID of the API from which the environmental variable list will be retrieved.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "environmentVariables": [
    {
      "string": "string"
    }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## environmentVariables

The payload containing each environmental variable in the "key" : "value" format.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 2. Maximum length of 64.

Key Pattern: ^[A-Za-z]+\w\*\$

Value Length Constraints: Minimum length of 0. Maximum length of 512.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You don't have access to perform this operation on this resource.

HTTP Status Code: 403

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### **UnauthorizedException**

You aren't authorized to perform this operation.

## HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetIntrospectionSchema

Retrieves the introspection schema for a GraphQL API.

## Request Syntax

```
GET /v1/apis/apiId/schema?format=format&includeDirectives=includeDirectives HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The API ID.

Required: Yes

### format

The schema format: SDL or JSON.

Valid Values: SDL | JSON

Required: Yes

### includeDirectives

A flag that specifies whether the schema introspection should contain directives.

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

```
schema
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The response returns the following as the HTTP body.

### [schema](#)

The schema, in GraphQL Schema Definition Language (SDL) format.

For more information, see the [GraphQL SDL documentation](#).

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **GraphQLErrorException**

The GraphQL schema is not valid.

HTTP Status Code: 400

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### **UnauthorizedException**

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetResolver

Retrieves a Resolver object.

## Request Syntax

```
GET /v1/apis/apiId/types/typeName/resolvers/fieldName HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apilD

The API ID.

Required: Yes

### fieldName

The resolver field name.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: Yes

### typeName

The resolver type name.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "resolver": {
    "cachingConfig": {
      "cachingKeys": [ "string" ],
      "ttl": number
    },
    "code": "string",
    "dataSourceName": "string",
    "fieldName": "string",
    "kind": "string",
    "maxBatchSize": number,
    "metricsConfig": "string",
    "pipelineConfig": {
      "functions": [ "string" ]
    },
    "requestMappingTemplate": "string",
    "resolverArn": "string",
    "responseMappingTemplate": "string",
    "runtime": {
      "name": "string",
      "runtimeVersion": "string"
    },
    "syncConfig": {
      "conflictDetection": "string",
      "conflictHandler": "string",
      "lambdaConflictHandlerConfig": {
        "lambdaConflictHandlerArn": "string"
      }
    },
    "typeName": "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## resolver

The Resolver object.

Type: [Resolver](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ConcurrentModificationException**

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### **UnauthorizedException**

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetSchemaCreationStatus

Retrieves the current status of a schema creation operation.

## Request Syntax

```
GET /v1/apis/apiId/schemacreation HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The API ID.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "detailsstatus
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### details

Detailed information about the status of the schema creation operation.

Type: String

### **status**

The current state of the schema (PROCESSING, FAILED, SUCCESS, or NOT\_APPLICABLE). When the schema is in the ACTIVE state, you can add data.

Type: String

Valid Values: PROCESSING | ACTIVE | DELETING | FAILED | SUCCESS | NOT\_APPLICABLE

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### **UnauthorizedException**

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetSourceApiAssociation

Retrieves a SourceApiAssociation object.

## Request Syntax

```
GET /v1/mergedApis/mergedApiIdentifier/sourceApiAssociations/associationId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### associationId

The ID generated by the AppSync service for the source API association.

Required: Yes

### mergedApildentifier

The identifier of the AppSync Merged API. This is generated by the AppSync service. In most cases, Merged APIs (especially in your account) only require the API ID value or ARN of the merged API. However, Merged APIs in other accounts (cross-account use cases) strictly require the full resource ARN of the merged API.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "sourceApiAssociation": {
    "associationArn": "string",
    "associationId": "string",
```

```
"description": "string",
"lastSuccessfulMergeDatemergedApiArn": "string",
"mergedApiId": "string",
"sourceApiArn": "string",
"sourceApiAssociationConfig": {
    "mergeType": "string"
},
"sourceApiAssociationStatus": "string",
"sourceApiAssociationStatusDetail": "string",
"sourceApiId": "string"
}
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### sourceApiAssociation

The SourceApiAssociation object data.

Type: [SourceApiAssociation](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetType

Retrieves a Type object.

## Request Syntax

```
GET /v1/apis/apiId/types/typeName?format=format HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The API ID.

Required: Yes

### format

The type format: SDL or JSON.

Valid Values: SDL | JSON

Required: Yes

### typeName

The type name.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "type": {
    "arn": "string",
    "definition": "string",
    "description": "string",
    "format": "string",
    "name": "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [type](#)

The Type object.

Type: [Type](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **ConcurrentModificationException**

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

## InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListApiKeys

Lists the API keys for a given API.

## Note

API keys are deleted automatically 60 days after they expire. However, they may still be included in the response until they have actually been deleted. You can safely call `DeleteApiKey` to manually delete a key before it's automatically deleted.

## Request Syntax

```
GET /v1/apis/apiId/apikeys?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The API ID.

Required: Yes

### maxResults

The maximum number of results that you want the request to return.

Valid Range: Minimum value of 0. Maximum value of 25.

### nextToken

An identifier that was returned from the previous call to this operation, which you can use to return the next set of items in the list.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\S]+

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "apiKeys": [
    {
      "deletes": number,
      "description": "string",
      "expires": number,
      "id": "string"
    }
  ],
  "nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### apiKey

The ApiKey objects.

Type: Array of [ApiKey](#) objects

### nextToken

An identifier to pass in the next request to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\S]+

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListApis

Lists the APIs in your AWS AppSync account.

`ListApis` returns only the high level API details. For more detailed information about an API, use `GetApi`.

## Request Syntax

```
GET /v2/apis?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### maxResults

The maximum number of results that you want the request to return.

Valid Range: Minimum value of 0. Maximum value of 25.

### nextToken

An identifier that was returned from the previous call to this operation, which you can use to return the next set of items in the list.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\S]+

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "apis": [
    {
      "name": "string",
      "description": "string",
      "lastModified": "string"
    }
  ]
}
```

```
"apiArn": "string",
"apiId": "string",
"created": number,
"dns": {
    "string" : "string"
},
"eventConfig": {
    "authProviders": [
        {
            "authType": "string",
            "cognitoConfig": {
                "appIdClientRegex": "string",
                "awsRegion": "string",
                "userPoolId": "string"
            },
            "lambdaAuthorizerConfig": {
                "authorizerResultTtlInSeconds": number,
                "authorizerUri": "string",
                "identityValidationExpression": "string"
            },
            "openIDConnectConfig": {
                "authTTL": number,
                "clientId": "string",
                "iatTTL": number,
                "issuer": "string"
            }
        }
    ],
    "connectionAuthModes": [
        {
            "authType": "string"
        }
    ],
    "defaultPublishAuthModes": [
        {
            "authType": "string"
        }
    ],
    "defaultSubscribeAuthModes": [
        {
            "authType": "string"
        }
    ],
    "logConfig": {
```

```
        "cloudWatchLogsRoleArn": "string",
        "logLevel": "string"
    },
},
"name": "string",
"ownerContact": "string",
"tags": {
    "string" : "string"
},
"wafWebAclArn": "string",
"xrayEnabled": boolean
}
],
"nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [apis](#)

The Api objects.

Type: Array of [Api](#) objects

### [nextToken](#)

An identifier that was returned from the previous call to this operation, which you can use to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\S]+

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

## InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListChannelNamespaces

Lists the channel namespaces for a specified Api.

ListChannelNamespaces returns only high level details for the channel namespace. To retrieve code handlers, use GetChannelNamespace.

## Request Syntax

```
GET /v2/apis/apiId/channelNamespaces?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apiId

The Api ID.

Required: Yes

### maxResults

The maximum number of results that you want the request to return.

Valid Range: Minimum value of 0. Maximum value of 25.

### nextToken

An identifier that was returned from the previous call to this operation, which you can use to return the next set of items in the list.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\S]+

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "channelNamespaces": [
    {
      "apiId": "string",
      "channelNamespaceArn": "string",
      "codeHandlers": "string",
      "created": number,
      "handlerConfigs": {
        "onPublish": {
          "behavior": "string",
          "integration": {
            "dataSourceName": "string",
            "lambdaConfig": {
              "invokeType": "string"
            }
          }
        },
        "onSubscribe": {
          "behavior": "string",
          "integration": {
            "dataSourceName": "string",
            "lambdaConfig": {
              "invokeType": "string"
            }
          }
        }
      },
      "lastModified": number,
      "name": "string",
      "publishAuthModes": [
        {
          "authType": "string"
        }
      ],
      "subscribeAuthModes": [
        {
          "authType": "string"
        }
      ]
    }
  ]
}
```

```
        ],
        "tags": {
            "string" : "string"
        }
    },
    "nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [channelNamespaces](#)

The ChannelNamespace objects.

Type: Array of [ChannelNamespace](#) objects

### [nextToken](#)

An identifier that was returned from the previous call to this operation, which you can use to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\S]+

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

## InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListDataSources

Lists the data sources for a given API.

## Request Syntax

```
GET /v1/apis/apiId/datasources?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The API ID.

Required: Yes

### maxResults

The maximum number of results that you want the request to return.

Valid Range: Minimum value of 0. Maximum value of 25.

### nextToken

An identifier that was returned from the previous call to this operation, which you can use to return the next set of items in the list.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\S]+

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"dataSourcesdataSourceArndescriptiondynamodbConfigawsRegiondeltaSyncConfigbaseTableTTLdeltaSyncTableNamedeltaSyncTableTTLtableNameuseCallerCredentialsversionedelasticsearchConfigawsRegionendpointeventBridgeConfigeventBusArnhttpConfigauthorizationConfigauthorizationTypeawsIamConfigsigningRegionsigningServiceNameendpointlambdaConfiglambdaFunctionArnmetricsConfignameopenSearchServiceConfigawsRegionendpointrelationalDatabaseConfigrdsHttpEndpointConfigawsRegion
```

```
        "awsSecretStoreArn": "string",
        "databaseName": "string",
        "dbClusterIdentifier": "string",
        "schema": "string"
    },
    "relationalDatabaseSourceType": "string"
],
"serviceRoleArn": "string",
"type": "string"
}
],
"nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [dataSources](#)

The `DataSource` objects.

Type: Array of [DataSource](#) objects

### [nextToken](#)

An identifier to pass in the next request to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\S]+

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

## InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# ListDomainNames

Lists multiple custom domain names.

## Request Syntax

```
GET /v1/domainnames?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### maxResults

The maximum number of results that you want the request to return.

Valid Range: Minimum value of 0. Maximum value of 25.

### nextToken

An identifier that was returned from the previous call to this operation, which you can use to return the next set of items in the list.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\S]+

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "domainNameConfigs": [
    {
      "appsyncDomainName": "string",
```

```
        "certificateArn": "string",
        "description": "string",
        "domainName": "string",
        "domainNameArn": "string",
        "hostedZoneId": "string",
        "tags": {
            "string" : "string"
        }
    ],
    "nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [domainNameConfigs](#)

Lists configurations for multiple domain names.

Type: Array of [DomainNameConfig](#) objects

### [nextToken](#)

An identifier that was returned from the previous call to this operation, which you can use to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\S]+

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You don't have access to perform this operation on this resource.

HTTP Status Code: 403

## BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

## InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListFunctions

List multiple functions.

## Request Syntax

```
GET /v1/apis/apiId/functions?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The GraphQL API ID.

Required: Yes

### maxResults

The maximum number of results that you want the request to return.

Valid Range: Minimum value of 0. Maximum value of 25.

### nextToken

An identifier that was returned from the previous call to this operation, which you can use to return the next set of items in the list.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\S]+

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"functions": [  
    {  
        "code": "string",  
        "dataSourceName": "string",  
        "description": "string",  
        "functionArn": "string",  
        "functionId": "string",  
        "functionVersion": "string",  
        "maxBatchSize": number,  
        "name": "string",  
        "requestMappingTemplate": "string",  
        "responseMappingTemplate": "string",  
        "runtime": {  
            "name": "string",  
            "runtimeVersion": "string"  
        },  
        "syncConfig": {  
            "conflictDetection": "string",  
            "conflictHandler": "string",  
            "lambdaConflictHandlerConfig": {  
                "lambdaConflictHandlerArn": "string"  
            }  
        }  
    },  
    "nextToken}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### functions

A list of Function objects.

Type: Array of [FunctionConfiguration](#) objects

### nextToken

An identifier that was returned from the previous call to this operation, which you can use to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\S]+

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListGraphqlApis

Lists your GraphQL APIs.

## Request Syntax

```
GET /v1/apis?apiType=apiType&maxResults=maxResults&nextToken=nextToken&owner=owner
HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apiType

The value that indicates whether the GraphQL API is a standard API (GRAPHQL) or merged API (MERGED).

Valid Values: GRAPHQL | MERGED

### maxResults

The maximum number of results that you want the request to return.

Valid Range: Minimum value of 0. Maximum value of 25.

### nextToken

An identifier that was returned from the previous call to this operation, which you can use to return the next set of items in the list.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\S]+

### owner

The account owner of the GraphQL API.

Valid Values: CURRENT\_ACCOUNT | OTHER\_ACCOUNTS

## Request Body

The request does not have a request body.

## Response Syntax

```
        "authorizerResultTtlInSeconds": number,
        "authorizerUri": "string",
        "identityValidationExpression": "string"
    },
    "logConfig": {
        "cloudWatchLogsRoleArn": "string",
        "excludeVerboseContent": boolean,
        "fieldLogLevel": "string"
    },
    "mergedApiExecutionRoleArn": "string",
    "name": "string",
    "openIDConnectConfig": {
        "authTTL": number,
        "clientId": "string",
        "iatTTL": number,
        "issuer": "string"
    },
    "owner": "string",
    "ownerContact": "string",
    "queryDepthLimit": number,
    "resolverCountLimit": number,
    "tags": {
        "string": "string"
    },
    "uris": {
        "string": "string"
    },
    "userPoolConfig": {
        "appIdClientRegex": "string",
        "awsRegion": "string",
        "defaultAction": "string",
        "userPoolId": "string"
    },
    "visibility": "string",
    "wafWebAclArn": "string",
    "xrayEnabled": boolean
},
],
"nextToken": "string
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [graphqlApis](#)

The GraphqlApi objects.

Type: Array of [GraphqlApi](#) objects

### [nextToken](#)

An identifier to pass in the next request to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\S]+

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **UnauthorizedException**

You aren't authorized to perform this operation.

## HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListResolvers

Lists the resolvers for a given API and type.

## Request Syntax

```
GET /v1/apis/apiId/types/typeName/resolvers?maxResults=maxResults&nextToken=nextToken
HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### [apild](#)

The API ID.

Required: Yes

### [maxResults](#)

The maximum number of results that you want the request to return.

Valid Range: Minimum value of 0. Maximum value of 25.

### [nextToken](#)

An identifier that was returned from the previous call to this operation, which you can use to return the next set of items in the list.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\S]+

### [typeName](#)

The type name.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

HTTP/1.1 200  
Content-type: application/json

```
{  
    "nextToken": "string",  
    "resolvers": [  
        {  
            "cachingConfig": {  
                "cachingKeys": [ "string" ],  
                "ttl": number  
            },  
            "code": "string",  
            "dataSourceName": "string",  
            "fieldName": "string",  
            "kind": "string",  
            "maxBatchSize": number,  
            "metricsConfig": "string",  
            "pipelineConfig": {  
                "functions": [ "string" ]  
            },  
            "requestMappingTemplate": "string",  
            "resolverArn": "string",  
            "responseMappingTemplate": "string",  
            "runtime": {  
                "name": "string",  
                "runtimeVersion": "string"  
            },  
            "syncConfig": {  
                "conflictDetection": "string",  
                "conflictHandler": "string",  
                "lambdaConflictHandlerConfig": {  
                    "lambdaConflictHandlerArn": "string"  
                }  
            },  
            "typeName": "string"  
        }  
    ]  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [nextToken](#)

An identifier to pass in the next request to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\S]+

### [resolvers](#)

The Resolver objects.

Type: Array of [Resolver](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListResolversByFunction

List the resolvers that are associated with a specific function.

## Request Syntax

```
GET /v1/apis/apiId/functions/functionId/resolvers?  
maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The API ID.

Required: Yes

### functionId

The function ID.

Required: Yes

### maxResults

The maximum number of results that you want the request to return.

Valid Range: Minimum value of 0. Maximum value of 25.

### nextToken

An identifier that was returned from the previous call to this operation, which you can use to return the next set of items in the list.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\S]+

## Request Body

The request does not have a request body.

## Response Syntax

HTTP/1.1 200  
Content-type: application/json

```
{  
    "nextToken": "string",  
    "resolvers": [  
        {  
            "cachingConfig": {  
                "cachingKeys": [ "string" ],  
                "ttl": number  
            },  
            "code": "string",  
            "dataSourceName": "string",  
            "fieldName": "string",  
            "kind": "string",  
            "maxBatchSize": number,  
            "metricsConfig": "string",  
            "pipelineConfig": {  
                "functions": [ "string" ]  
            },  
            "requestMappingTemplate": "string",  
            "resolverArn": "string",  
            "responseMappingTemplate": "string",  
            "runtime": {  
                "name": "string",  
                "runtimeVersion": "string"  
            },  
            "syncConfig": {  
                "conflictDetection": "string",  
                "conflictHandler": "string",  
                "lambdaConflictHandlerConfig": {  
                    "lambdaConflictHandlerArn": "string"  
                }  
            },  
            "typeName": "string"  
        }  
    ]  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### nextToken

An identifier that you can use to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\S]+

### resolvers

The list of resolvers.

Type: Array of [Resolver](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListSourceApiAssociations

Lists the SourceApiAssociationSummary data.

## Request Syntax

```
GET /v1/apis/apiId/sourceApiAssociations?maxResults=maxResults&nextToken=nextToken
HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The API ID.

Required: Yes

### maxResults

The maximum number of results that you want the request to return.

Valid Range: Minimum value of 0. Maximum value of 25.

### nextToken

An identifier that was returned from the previous call to this operation, which you can use to return the next set of items in the list.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\S]+

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "nextToken": "string",
  "sourceApiAssociationSummaries": [
    {
      "associationArn": "string",
      "associationId": "string",
      "description": "string",
      "mergedApiArn": "string",
      "mergedApiId": "string",
      "sourceApiArn": "string",
      "sourceApiId": "string"
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [nextToken](#)

An identifier that was returned from the previous call to this operation, which you can use to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\S]+

### [sourceApiAssociationSummaries](#)

The SourceApiAssociationSummary object data.

Type: Array of [SourceApiAssociationSummary](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

## InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# ListTagsForResource

Lists the tags for a resource.

## Request Syntax

```
GET /v1/tags/resourceArn HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### resourceArn

The GraphqlApi Amazon Resource Name (ARN).

Length Constraints: Minimum length of 70. Maximum length of 75.

Pattern: ^arn:aws:appsync:[A-Za-z0-9\_/.-]{0,63}:\d{12}:apis/[0-9A-Za-z\_-]{26}\$

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "tags": [
    {
      "string" : "string"
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## tags

A TagMap object.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: ^(?!\aws:)[ a-zA-Z+-=.\_:/]+\$

Value Length Constraints: Maximum length of 256.

Value Pattern: ^[\s\w+-=\.:@]\*\$

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You don't have access to perform this operation on this resource.

HTTP Status Code: 403

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **LimitExceededException**

The request exceeded a limit. Try your request again.

HTTP Status Code: 429

### NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListTypes

Lists the types for a given API.

## Request Syntax

```
GET /v1/apis/apiId/types?format=format&maxResults=maxResults&nextToken=nextToken
HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The API ID.

Required: Yes

### format

The type format: SDL or JSON.

Valid Values: SDL | JSON

Required: Yes

### maxResults

The maximum number of results that you want the request to return.

Valid Range: Minimum value of 0. Maximum value of 25.

### nextToken

An identifier that was returned from the previous call to this operation, which you can use to return the next set of items in the list.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\S]+

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "types": [
    {
      "arn": "string",
      "definition": "string",
      "description": "string",
      "format": "string",
      "name": "string"
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [nextToken](#)

An identifier to pass in the next request to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\S]+

### [types](#)

The Type objects.

Type: Array of [Type](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### ConcurrentModificationException

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListTypesByAssociation

Lists Type objects by the source API association ID.

## Request Syntax

```
GET /v1/mergedApis/mergedApiIdentifier/sourceApiAssociations/associationId/types?  
format=format&maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### associationId

The ID generated by the AppSync service for the source API association.

Required: Yes

### format

The format type.

Valid Values: SDL | JSON

Required: Yes

### maxResults

The maximum number of results that you want the request to return.

Valid Range: Minimum value of 0. Maximum value of 25.

### mergedApieldentifier

The identifier of the AppSync Merged API. This is generated by the AppSync service. In most cases, Merged APIs (especially in your account) only require the API ID value or ARN of the merged API. However, Merged APIs in other accounts (cross-account use cases) strictly require the full resource ARN of the merged API.

Required: Yes

## nextToken

An identifier that was returned from the previous call to this operation, which you can use to return the next set of items in the list.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\S]+

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "types": [
    {
      "arn": "string",
      "definition": "string",
      "description": "string",
      "format": "string",
      "name": "string"
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## nextToken

An identifier that was returned from the previous call to this operation, which you can use to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\S]+

## [types](#)

The Type objects.

Type: Array of [Type](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **ConcurrentModificationException**

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### **UnauthorizedException**

You aren't authorized to perform this operation.

## HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# PutGraphqlApiEnvironmentVariables

Creates a list of environmental variables in an API by its ID value.

When creating an environmental variable, it must follow the constraints below:

- Both JavaScript and VTL templates support environmental variables.
- Environmental variables are not evaluated before function invocation.
- Environmental variables only support string values.
- Any defined value in an environmental variable is considered a string literal and not expanded.
- Variable evaluations should ideally be performed in the function code.

When creating an environmental variable key-value pair, it must follow the additional constraints below:

- Keys must begin with a letter.
- Keys must be at least two characters long.
- Keys can only contain letters, numbers, and the underscore character (\_).
- Values can be up to 512 characters long.
- You can configure up to 50 key-value pairs in a GraphQL API.

You can create a list of environmental variables by adding it to the environmentVariables payload as a list in the format {"key1": "value1", "key2": "value2", ...}. Note that each call of the PutGraphqlApiEnvironmentVariables action will result in the overwriting of the existing environmental variable list of that API. This means the existing environmental variables will be lost. To avoid this, you must include all existing and new environmental variables in the list each time you call this action.

## Request Syntax

```
PUT /v1/apis/apiId/environmentVariables HTTP/1.1
Content-type: application/json

{
  "environmentVariables": {
    "string": "string"
```

```
    }  
}
```

## URI Request Parameters

The request uses the following URI parameters.

### [apild](#)

The ID of the API to which the environmental variable list will be written.

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### [environmentVariables](#)

The list of environmental variables to add to the API.

When creating an environmental variable key-value pair, it must follow the additional constraints below:

- Keys must begin with a letter.
- Keys must be at least two characters long.
- Keys can only contain letters, numbers, and the underscore character (\_).
- Values can be up to 512 characters long.
- You can configure up to 50 key-value pairs in a GraphQL API.

You can create a list of environmental variables by adding it to the environmentVariables payload as a list in the format {"key1": "value1", "key2": "value2", ...}. Note that each call of the PutGraphqlApiEnvironmentVariables action will result in the overwriting of the existing environmental variable list of that API. This means the existing environmental variables will be lost. To avoid this, you must include all existing and new environmental variables in the list each time you call this action.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 2. Maximum length of 64.

Key Pattern: ^[A-Za-z]+\w\*\$

Value Length Constraints: Minimum length of 0. Maximum length of 512.

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "environmentVariables": {
    "string" : "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### environmentVariables

The payload containing each environmental variable in the "key" : "value" format.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 2. Maximum length of 64.

Key Pattern: ^[A-Za-z]+\w\*\$

Value Length Constraints: Minimum length of 0. Maximum length of 512.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## AccessDeniedException

You don't have access to perform this operation on this resource.

HTTP Status Code: 403

## BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

## ConcurrentModificationException

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

## InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# StartDataSourceIntrospection

Creates a new introspection. Returns the `introspectionId` of the new introspection after its creation.

## Request Syntax

```
POST /v1/datasources/introspections HTTP/1.1
Content-type: application/json

{
  "rdsDataApiConfig": {
    "databaseName": "string",
    "resourceArn": "string",
    "secretArn": "string"
  }
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### rdsDataApiConfig

The `rdsDataApiConfig` object data.

Type: [RdsDataApiConfig](#) object

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{  
  "introspectionId": "string",  
  "introspectionStatus": "string",  
  "introspectionStatusDetail": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [introspectionId](#)

The introspection ID. Each introspection contains a unique ID that can be used to reference the introspection record.

Type: String

### [introspectionStatus](#)

The status of the introspection during creation. By default, when a new introspection has been created, the status will be set to PROCESSING. Once the operation has been completed, the status will change to SUCCESS or FAILED depending on how the data was parsed. A FAILED operation will return an error and its details as an [introspectionStatusDetail](#).

Type: String

Valid Values: PROCESSING | FAILED | SUCCESS

### [introspectionStatusDetail](#)

The error detail field. When a FAILED [introspectionStatus](#) is returned, the [introspectionStatusDetail](#) will also return the exact error that was generated during the operation.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

## InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# StartSchemaCreation

Adds a new schema to your GraphQL API.

This operation is asynchronous. Use [GetSchemaCreationStatus](#) to determine when it has completed.

## Request Syntax

```
POST /v1/apis/apiId/schemacreation HTTP/1.1
Content-type: application/json

{
  "definitionblob
}
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The API ID.

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### definition

The schema definition, in GraphQL schema language format.

Type: Base64-encoded binary data object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "statusstring"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [status](#)

The current state of the schema (PROCESSING, FAILED, SUCCESS, or NOT\_APPLICABLE). When the schema is in the ACTIVE state, you can add data.

Type: String

Valid Values: PROCESSING | ACTIVE | DELETING | FAILED | SUCCESS | NOT\_APPLICABLE

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **ConcurrentModificationException**

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# StartSchemaMerge

Initiates a merge operation. Returns a status that shows the result of the merge operation.

## Request Syntax

```
POST /v1/mergedApis/mergedApiIdentifier/sourceApiAssociations/associationId/merge  
HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### associationId

The ID generated by the AppSync service for the source API association.

Required: Yes

### mergedApildentifier

The identifier of the AppSync Merged API. This is generated by the AppSync service. In most cases, Merged APIs (especially in your account) only require the API ID value or ARN of the merged API. However, Merged APIs in other accounts (cross-account use cases) strictly require the full resource ARN of the merged API.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200  
Content-type: application/json  
  
{  
  "sourceApiAssociationStatus": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [sourceApiAssociationStatus](#)

The state of the source API association.

Type: String

Valid Values: MERGE\_SCHEDULED | MERGE\_FAILED | MERGE\_SUCCESS | MERGE\_IN\_PROGRESS | AUTO\_MERGE\_SCHEDULE\_FAILED | DELETION\_SCHEDULED | DELETION\_IN\_PROGRESS | DELETION\_FAILED

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **ConcurrentModificationException**

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# TagResource

Tags a resource with user-supplied tags.

## Request Syntax

```
POST /v1/tags/resourceArn HTTP/1.1
Content-type: application/json

{
  "tags": {
    "string" : "string"
  }
}
```

## URI Request Parameters

The request uses the following URI parameters.

### resourceArn

The GraphqlApi Amazon Resource Name (ARN).

Length Constraints: Minimum length of 70. Maximum length of 75.

Pattern: ^arn:aws:appsync:[A-Za-z0-9\_/.-]{0,63}:\d{12}:apis/[0-9A-Za-z\_-]{26}\$

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### tags

A TagMap object.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: ^(?!aws:)[ a-zA-Z+-=.:\_:/]+\$

Value Length Constraints: Maximum length of 256.

Value Pattern: ^[\s\w+-=\.:@]\*\$

Required: Yes

## Response Syntax

HTTP/1.1 200

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

You don't have access to perform this operation on this resource.

HTTP Status Code: 403

### BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### LimitExceededException

The request exceeded a limit. Try your request again.

HTTP Status Code: 429

### NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UntagResource

Untags a resource.

## Request Syntax

```
DELETE /v1/tags/resourceArn?tagKeys=tagKeys HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### resourceArn

The GraphqlApi Amazon Resource Name (ARN).

Length Constraints: Minimum length of 70. Maximum length of 75.

Pattern: ^arn:aws:appsync:[A-Za-z0-9\_-]{0,63}:\d{12}:apis/[0-9A-Za-z\_-]{26}\$

Required: Yes

### tagKeys

A list of TagKey objects.

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^(!aws:)[ a-zA-Z+=\_.:/]+\$

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

# Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

You don't have access to perform this operation on this resource.

HTTP Status Code: 403

### BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### LimitExceededException

The request exceeded a limit. Try your request again.

HTTP Status Code: 429

### NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateApi

Updates an Api.

## Request Syntax

```
POST /v2/apis/apiId HTTP/1.1
Content-type: application/json

{
  "eventConfigauthProvidersauthTypestring",
        "cognitoConfigappIdClientRegexstring",
          "awsRegionstring",
          "userPoolIdstring"
        },
        "lambdaAuthorizerConfigauthorizerResultTtlInSecondsnumber,
          "authorizerUristring",
          "identityValidationExpressionstring"
        },
        "openIDConnectConfigauthTTLnumber,
          "clientIdstring",
          "iatTTLnumber,
          "issuerstring"
        }
      }
    ],
    "connectionAuthModesauthTypestring"
      }
    ],
    "defaultPublishAuthModesauthTypestring"
      }
    ],
    "defaultSubscribeAuthModes
```

```
{  
    "authType": "string"  
}  
,  
"logConfig": {  
    "cloudWatchLogsRoleArn": "string",  
    "logLevel": "string"  
}  
,  
"name": "string",  
"ownerContact": "string"  
}
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The Api ID.

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### eventConfig

The new event configuration. This includes the default authorization configuration for connecting, publishing, and subscribing to an Event API.

Type: [EventConfig](#) object

Required: No

### name

The name of the Api.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: [A-Za-z0-9\_\\-\\ ]<sup>+</sup>

Required: Yes

### ownerContact

The owner contact information for the Api.

Type: String

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "api": {
    "apiArn": "string",
    "apiId": "string",
    "created": number,
    "dns": {
      "string" : "string"
    },
    "eventConfig": {
      "authProviders": [
        {
          "authType": "string",
          "cognitoConfig": {
            "appIdClientRegex": "string",
            "awsRegion": "string",
            "userPoolId": "string"
          }
        },
        "lambdaAuthorizerConfig": {
          "authorizerResultTtlInSeconds": number,
          "authorizerUri": "string",
          "identityValidationExpression": "string"
        },
        "openIDConnectConfig": {
          "authTTL": number,
          "clientId": "string",
          "iatTTL": number,
          "region": "string"
        }
      ]
    }
  }
}
```

```
        "issuer": "string"
    }
],
],
"connectionAuthModes": [
{
    "authType": "string"
}
],
"defaultPublishAuthModes": [
{
    "authType": "string"
}
],
"defaultSubscribeAuthModes": [
{
    "authType": "string"
}
],
"logConfig": {
    "cloudWatchLogsRoleArn": "string",
    "logLevel": "string"
}
},
"name": "string",
"ownerContact": "string",
"tags": {
    "string" : "string"
},
"wafWebAclArn": "string",
"xrayEnabled": boolean
}
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### api

The Api object.

Type: [Api](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

You don't have access to perform this operation on this resource.

HTTP Status Code: 403

### BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### ConcurrentModificationException

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateApiCache

Updates the cache for the GraphQL API.

## Request Syntax

```
POST /v1/apis/apiId/ApiCaches/update HTTP/1.1
Content-type: application/json

{
  "apiCachingBehaviorhealthMetricsConfigttltype
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The GraphQL API ID.

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### apiCachingBehavior

Caching behavior.

- **FULL\_REQUEST\_CACHING:** All requests from the same user are cached. Individual resolvers are automatically cached. All API calls will try to return responses from the cache.
- **PER\_RESOLVER\_CACHING:** Individual resolvers that you specify are cached.
- **OPERATION\_LEVEL\_CACHING:** Full requests are cached together and returned without executing resolvers.

Type: String

Valid Values: FULL\_REQUEST\_CACHING | PER\_RESOLVER\_CACHING | OPERATION\_LEVEL\_CACHING

Required: Yes

### healthMetricsConfig

Controls how cache health metrics will be emitted to CloudWatch. Cache health metrics include:

- NetworkBandwidthOutAllowanceExceeded: The network packets dropped because the throughput exceeded the aggregated bandwidth limit. This is useful for diagnosing bottlenecks in a cache configuration.
- EngineCPUUtilization: The CPU utilization (percentage) allocated to the Redis process. This is useful for diagnosing bottlenecks in a cache configuration.

Metrics will be recorded by API ID. You can set the value to ENABLED or DISABLED.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

### ttl

TTL in seconds for cache entries.

Valid values are 1–3,600 seconds.

Type: Long

Required: Yes

### type

The cache instance type. Valid values are

- SMALL
- MEDIUM
- LARGE
- XLARGE
- LARGE\_2X

- **LARGE\_4X**
- **LARGE\_8X** (not available in all regions)
- **LARGE\_12X**

Historically, instance types were identified by an EC2-style value. As of July 2020, this is deprecated, and the generic identifiers above should be used.

The following legacy instance types are available, but their use is discouraged:

- **T2\_SMALL**: A t2.small instance type.
- **T2\_MEDIUM**: A t2.medium instance type.
- **R4\_LARGE**: A r4.large instance type.
- **R4\_XLARGE**: A r4.xlarge instance type.
- **R4\_2XLARGE**: A r4.2xlarge instance type.
- **R4\_4XLARGE**: A r4.4xlarge instance type.
- **R4\_8XLARGE**: A r4.8xlarge instance type.

Type: String

Valid Values: T2\_SMALL | T2\_MEDIUM | R4\_LARGE | R4\_XLARGE | R4\_2XLARGE | R4\_4XLARGE | R4\_8XLARGE | SMALL | MEDIUM | LARGE | XLARGE | LARGE\_2X | LARGE\_4X | LARGE\_8X | LARGE\_12X

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "apiCache": {
    "apiCachingBehavior": "string",
    "atRestEncryptionEnabled": boolean,
    "healthMetricsConfig": "string",
    "status": "string",
    "transitEncryptionEnabled": boolean,
    "ttl": number,
    "type": "string"
  }
}
```

```
    }  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [apiCache](#)

The ApiCache object.

Type: [ApiCache](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **ConcurrentModificationException**

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateApiKey

Updates an API key. You can update the key as long as it's not deleted.

## Request Syntax

```
POST /v1/apis/apiId/apikeys/id HTTP/1.1
Content-type: application/json

{
  "descriptionexpires
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The ID for the GraphQL API.

Required: Yes

### id

The API key ID.

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### description

A description of the purpose of the API key.

Type: String

Required: No

## expires

From the update time, the time after which the API key expires. The date is represented as seconds since the epoch. For more information, see [ApiKey](#).

Type: Long

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "apiKey": {
    "deletes": number,
    "description": "string",
    "expires": number,
    "id": "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### apiKey

The API key.

Type: [ApiKey](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## ApiKeyValidityOutOfBoundsException

The API key expiration must be set to a value between 1 and 365 days from creation (for CreateApiKey) or from update (for UpdateApiKey).

HTTP Status Code: 400

## BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

## InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## LimitExceededException

The request exceeded a limit. Try your request again.

HTTP Status Code: 429

## NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateChannelNamespace

Updates a ChannelNamespace associated with an Api.

## Request Syntax

```
POST /v2/apis/apiId/channelNamespaces/name HTTP/1.1
Content-type: application/json

{
  "codeHandlers": "string",
  "handlerConfigs": {
    "onPublish": {
      "behavior": "string",
      "integration": {
        "dataSourceName": "string",
        "lambdaConfig": {
          "invokeType": "string"
        }
      }
    },
    "onSubscribe": {
      "behavior": "string",
      "integration": {
        "dataSourceName": "string",
        "lambdaConfig": {
          "invokeType": "string"
        }
      }
    }
  },
  "publishAuthModes": [
    {
      "authType": "string"
    }
  ],
  "subscribeAuthModes": [
    {
      "authType": "string"
    }
  ]
}
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The Api ID.

Required: Yes

### name

The name of the ChannelNamespace.

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: ([A-Za-z0-9](?:[A-Za-z0-9\-\-]{0,48}[A-Za-z0-9])?)

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### codeHandlers

The event handler functions that run custom business logic to process published events and subscribe requests.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32768.

Required: No

### handlerConfigs

The configuration for the OnPublish and OnSubscribe handlers.

Type: [HandlerConfigs](#) object

Required: No

## [publishAuthModes](#)

The authorization mode to use for publishing messages on the channel namespace. This configuration overrides the default Api authorization configuration.

Type: Array of [AuthMode](#) objects

Required: No

## [subscribeAuthModes](#)

The authorization mode to use for subscribing to messages on the channel namespace. This configuration overrides the default Api authorization configuration.

Type: Array of [AuthMode](#) objects

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "channelNamespace": {
    "apiId": "string",
    "channelNamespaceArn": "string",
    "codeHandlers": "string",
    "created": number,
    "handlerConfigs": {
      "onPublish": {
        "behavior": "string",
        "integration": {
          "dataSourceName": "string",
          "lambdaConfig": {
            "invokeType": "string"
          }
        }
      },
      "onSubscribe": {
        "behavior": "string",
        "integration": {
          "dataSourceName": "string",
          "lambdaConfig": {
            "invokeType": "string"
          }
        }
      }
    }
  }
}
```

```
        "lambdaConfig": {
            "invokeType": "string"
        }
    }
},
"lastModified": number,
"name": "string",
"publishAuthModes": [
    {
        "authType": "string"
    }
],
"subscribeAuthModes": [
    {
        "authType": "string"
    }
],
"tags": {
    "string" : "string"
}
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [channelNamespace](#)

The ChannelNamespace object.

Type: [ChannelNamespace](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You don't have access to perform this operation on this resource.

HTTP Status Code: 403

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **ConcurrentModificationException**

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### **UnauthorizedException**

You aren't authorized to perform this operation.

HTTP Status Code: 401

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateDataSource

Updates a DataSource object.

## Request Syntax

```
POST /v1/apis/apiId/datasources/name HTTP/1.1
Content-type: application/json
```

```
{
  "descriptiondynamodbConfig: {
    "awsRegiondeltaSyncConfig: {
      "baseTableTTLdeltaSyncTableNamedeltaSyncTableTTLtableNameuseCallerCredentialsversionedelasticsearchConfig: {
    "awsRegionendpointeventBridgeConfig: {
    "eventBusArnhttpConfig: {
    "authorizationConfig: {
      "authorizationTypeawsIamConfig: {
        "signingRegionsigningServiceNameendpointlambdaConfig: {
    "lambdaFunctionArnmetricsConfig
```

```
"openSearchServiceConfig": {  
    "awsRegion": "string",  
    "endpoint": "string"  
},  
"relationalDatabaseConfig": {  
    "rdsHttpEndpointConfig": {  
        "awsRegion": "string",  
        "awsSecretStoreArn": "string",  
        "databaseName": "string",  
        "dbClusterIdentifier": "string",  
        "schema": "string"  
    },  
    "relationalDataSourceType": "string"  
},  
"serviceRoleArn": "string",  
"type": "string"  
}
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The API ID.

Required: Yes

### name

The new name for the data source.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: Yes

## Request Body

The request accepts the following data in JSON format.

## [description](#)

The new description for the data source.

Type: String

Required: No

## [dynamodbConfig](#)

The new Amazon DynamoDB configuration.

Type: [DynamodbDataSourceConfig](#) object

Required: No

## [elasticsearchConfig](#)

The new OpenSearch configuration.

As of September 2021, Amazon Elasticsearch service is Amazon OpenSearch Service. This configuration is deprecated. Instead, use [UpdateDataSource:openSearchServiceConfig](#) to update an OpenSearch data source.

Type: [ElasticsearchDataSourceConfig](#) object

Required: No

## [eventBridgeConfig](#)

The new Amazon EventBridge settings.

Type: [EventBridgeDataSourceConfig](#) object

Required: No

## [httpConfig](#)

The new HTTP endpoint configuration.

Type: [HttpDataSourceConfig](#) object

Required: No

## [lambdaConfig](#)

The new AWS Lambda configuration.

Type: [LambdaDataSourceConfig](#) object

Required: No

### metricsConfig

Enables or disables enhanced data source metrics for specified data sources. Note that `metricsConfig` won't be used unless the `dataSourceLevelMetricsBehavior` value is set to `PER_DATA_SOURCE_METRICS`. If the `dataSourceLevelMetricsBehavior` is set to `FULL_REQUEST_DATA_SOURCE_METRICS` instead, `metricsConfig` will be ignored. However, you can still set its value.

`metricsConfig` can be `ENABLED` or `DISABLED`.

Type: String

Valid Values: `ENABLED` | `DISABLED`

Required: No

### openSearchServiceConfig

The new OpenSearch configuration.

Type: [OpenSearchServiceDataSourceConfig](#) object

Required: No

### relationalDatabaseConfig

The new relational database configuration.

Type: [RelationalDatabaseDataSourceConfig](#) object

Required: No

### serviceRoleArn

The new service role Amazon Resource Name (ARN) for the data source.

Type: String

Required: No

### type

The new data source type.

Type: String

Valid Values: AWS\_LAMBDA | AMAZON\_DYNAMODB | AMAZON\_ELASTICSEARCH | NONE | HTTP | RELATIONAL\_DATABASE | AMAZON\_OPENSEARCH\_SERVICE | AMAZON\_EVENTBRIDGE | AMAZON\_BEDROCK\_RUNTIME

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "dataSource": {
    "dataSourceArn": "string",
    "description": "string",
    "dynamodbConfig": {
      "awsRegion": "string",
      "deltaSyncConfig": {
        "baseTableTTL": number,
        "deltaSyncTableName": "string",
        "deltaSyncTableTTL": number
      },
      "tableName": "string",
      "useCallerCredentials": boolean,
      "versioned": boolean
    },
    "elasticsearchConfig": {
      "awsRegion": "string",
      "endpoint": "string"
    },
    "eventBridgeConfig": {
      "eventBusArn": "string"
    },
    "httpConfig": {
      "authorizationConfig": {
        "authorizationType": "string",
        "awsIamConfig": {
          "signingRegion": "string",
          "signingServiceName": "string"
        }
      }
    }
}
```

```
        },
        "endpoint": "string"
    },
    "lambdaConfiglambdaFunctionArn": "string"
    },
    "metricsConfig": "string",
    "name": "string",
    "openSearchServiceConfig": {
        "awsRegion": "string",
        "endpoint": "string"
    },
    "relationalDatabaseConfig": {
        "rdsHttpEndpointConfig": {
            "awsRegion": "string",
            "awsSecretStoreArn": "string",
            "databaseName": "string",
            "dbClusterIdentifier": "string",
            "schema": "string"
        },
        "relationalDatabaseSourceType": "string"
    },
    "serviceRoleArn": "string",
    "type": "string"
}
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### dataSource

The updated DataSource object.

Type: [DataSource](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

## ConcurrentModificationException

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

## InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateDomainName

Updates a custom DomainName object.

## Request Syntax

```
POST /v1/domainnames/domainName HTTP/1.1
Content-type: application/json

{
  "descriptionstring"
}
```

## URI Request Parameters

The request uses the following URI parameters.

### domainName

The domain name.

Length Constraints: Minimum length of 1. Maximum length of 253.

Pattern: ^(\\*\[\w\d-\]\*\.)?([\w\d-]+\.)+[\w\d-]+\$

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### description

A description of the DomainName.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: ^.\*\$

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "domainNameConfig": {
    "appsyncDomainName": "string",
    "certificateArn": "string",
    "description": "string",
    "domainName": "string",
    "domainNameArn": "string",
    "hostedZoneId": "string",
    "tags": {
      "string" : "string"
    }
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [domainNameConfig](#)

The configuration for the DomainName.

Type: [DomainNameConfig](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You don't have access to perform this operation on this resource.

HTTP Status Code: 403

## BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

## ConcurrentModificationException

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

## InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateFunction

Updates a Function object.

## Request Syntax

```
POST /v1/apis/apiId/functions/functionId HTTP/1.1
Content-type: application/json

{
  "code": "string",
  "dataSourceName": "string",
  "description": "string",
  "functionVersion": "string",
  "maxBatchSize": number,
  "name": "string",
  "requestMappingTemplate": "string",
  "responseMappingTemplate": "string",
  "runtime": {
    "name": "string",
    "runtimeVersion": "string"
  },
  "syncConfig": {
    "conflictDetection": "string",
    "conflictHandler": "string",
    "lambdaConflictHandlerConfig": {
      "lambdaConflictHandlerArn": "string"
    }
  }
}
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The GraphQL API ID.

Required: Yes

## functionId

The function ID.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### code

The function code that contains the request and response functions. When code is used, the runtime is required. The runtime value must be APPSYNC\_JS.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32768.

Required: No

### dataSourceName

The Function DataSource name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: Yes

### description

The Function description.

Type: String

Required: No

## functionVersion

The version of the request mapping template. Currently, the supported value is 2018-05-29. Note that when using VTL and mapping templates, the functionVersion is required.

Type: String

Required: No

## maxBatchSize

The maximum batching size for a resolver.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2000.

Required: No

## name

The Function name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: Yes

## requestMappingTemplate

The Function request mapping template. Functions support only the 2018-05-29 version of the request mapping template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: ^ . \*\$

Required: No

## responseMappingTemplate

The Function request mapping template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: ^ . \*\$

Required: No

## runtime

Describes a runtime used by an AWS AppSync pipeline resolver or AWS AppSync function.

Specifies the name and version of the runtime to use. Note that if a runtime is specified, code must also be specified.

Type: [AppSyncRuntime](#) object

Required: No

## syncConfig

Describes a Sync configuration for a resolver.

Specifies which Conflict Detection strategy and Resolution strategy to use when the resolver is invoked.

Type: [SyncConfig](#) object

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "functionConfiguration": {
    "code": "string",
    "dataSourceName": "string",
    "description": "string",
    "functionArn": "string",
    "functionId": "string",
    "functionVersion": "string",
    "maxBatchSize": number,
    "name": "string",
  }
}
```

```
"requestMappingTemplate": "string",
"responseMappingTemplate": "string",
"runtime": {
    "name": "string",
    "runtimeVersion": "string"
},
"syncConfig": {
    "conflictDetection": "string",
    "conflictHandler": "string",
    "lambdaConflictHandlerConfig": {
        "lambdaConflictHandlerArn": "string"
    }
}
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [functionConfiguration](#)

The Function object.

Type: [FunctionConfiguration object](#)

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **ConcurrentModificationException**

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### **UnauthorizedException**

You aren't authorized to perform this operation.

HTTP Status Code: 401

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateGraphqlApi

Updates a GraphqlApi object.

## Request Syntax

```
POST /v1/apis/apiId HTTP/1.1
Content-type: application/json

{
  "additionalAuthenticationProvidersauthenticationTypestring",
      "lambdaAuthorizerConfigauthorizerResultTtlInSecondsnumber,
        "authorizerUristring",
        "identityValidationExpressionstring"
      },
      "openIDConnectConfigauthTTLnumber,
        "clientIdstring",
        "iatTTLnumber,
        "issuerstring"
      },
      "userPoolConfigappIdClientRegexstring",
        "awsRegionstring",
        "userPoolIdstring"
      }
    }
  ],
  "authenticationTypestring",
  "enhancedMetricsConfigdataSourceLevelMetricsBehaviorstring",
    "operationLevelMetricsConfigstring",
    "resolverLevelMetricsBehaviorstring"
  },
  "introspectionConfigstring",
  "lambdaAuthorizerConfigauthorizerResultTtlInSecondsnumber,
    "authorizerUristring",
    "identityValidationExpressionstring"
  },
}
```

```
"logConfig    "cloudWatchLogsRoleArn    "excludeVerboseContent    "fieldLogLevel},  
"mergedApiExecutionRoleArn"name"openIDConnectConfig    "authTTL    "clientId    "iatTTL    "issuer},  
"ownerContact"queryDepthLimit"resolverCountLimit"userPoolConfig    "appIdClientRegex    "awsRegion    "defaultAction    "userPoolId},  
"xrayEnabled}
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The API ID.

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### additionalAuthenticationProviders

A list of additional authentication providers for the GraphqlApi API.

Type: Array of [AdditionalAuthenticationProvider](#) objects

Required: No

### [\*\*authenticationType\*\*](#)

The new authentication type for the GraphqlApi object.

Type: String

Valid Values: API\_KEY | AWS\_IAM | AMAZON\_COGNITO\_USER\_POOLS | OPENID\_CONNECT  
| AWS\_LAMBDA

Required: Yes

### [\*\*enhancedMetricsConfig\*\*](#)

The enhancedMetricsConfig object.

Type: [EnhancedMetricsConfig](#) object

Required: No

### [\*\*introspectionConfig\*\*](#)

Sets the value of the GraphQL API to enable (ENABLED) or disable (DISABLED) introspection. If no value is provided, the introspection configuration will be set to ENABLED by default. This field will produce an error if the operation attempts to use the introspection feature while this field is disabled.

For more information about introspection, see [GraphQL introspection](#).

Type: String

Valid Values: ENABLED | DISABLED

Required: No

### [\*\*lambdaAuthorizerConfig\*\*](#)

Configuration for Lambda function authorization.

Type: [LambdaAuthorizerConfig](#) object

Required: No

## logConfig

The Amazon CloudWatch Logs configuration for the GraphqlApi object.

Type: [LogConfig](#) object

Required: No

## mergedApiExecutionRoleArn

The Identity and Access Management service role ARN for a merged API. The AppSync service assumes this role on behalf of the Merged API to validate access to source APIs at runtime and to prompt the AUTO\_MERGE to update the merged API endpoint with the source API changes automatically.

Type: String

Required: No

## name

The new name for the GraphqlApi object.

Type: String

Required: Yes

## openIDConnectConfig

The OpenID Connect configuration for the GraphqlApi object.

Type: [OpenIDConnectConfig](#) object

Required: No

## ownerContact

The owner contact information for an API resource.

This field accepts any string input with a length of 0 - 256 characters.

Type: String

Required: No

## queryDepthLimit

The maximum depth a query can have in a single request. Depth refers to the amount of nested levels allowed in the body of query. The default value is `0` (or unspecified), which indicates there's no depth limit. If you set a limit, it can be between `1` and `75` nested levels. This field will produce a limit error if the operation falls out of bounds.

Note that fields can still be set to nullable or non-nullable. If a non-nullable field produces an error, the error will be thrown upwards to the first nullable field available.

Type: Integer

Valid Range: Minimum value of `0`. Maximum value of `75`.

Required: No

## resolverCountLimit

The maximum number of resolvers that can be invoked in a single request. The default value is `0` (or unspecified), which will set the limit to `10000`. When specified, the limit value can be between `1` and `10000`. This field will produce a limit error if the operation falls out of bounds.

Type: Integer

Valid Range: Minimum value of `0`. Maximum value of `10000`.

Required: No

## userPoolConfig

The new Amazon Cognito user pool configuration for the `~GraphqlApi` object.

Type: [UserPoolConfig](#) object

Required: No

## xrayEnabled

A flag indicating whether to use AWS X-Ray tracing for the `GraphqlApi`.

Type: Boolean

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "graphqlApi": {
    "additionalAuthenticationProviders": [
      {
        "authenticationType": "string",
        "lambdaAuthorizerConfig": {
          "authorizerResultTtlInSeconds": number,
          "authorizerUri": "string",
          "identityValidationExpression": "string"
        },
        "openIDConnectConfig": {
          "authTTL": number,
          "clientId": "string",
          "iatTTL": number,
          "issuer": "string"
        },
        "userPoolConfig": {
          "appIdClientRegex": "string",
          "awsRegion": "string",
          "userPoolId": "string"
        }
      }
    ],
    "apiId": "string",
    "apiType": "string",
    "arn": "string",
    "authenticationType": "string",
    "dns": {
      "string" : "string"
    },
    "enhancedMetricsConfig": {
      "dataSourceLevelMetricsBehavior": "string",
      "operationLevelMetricsConfig": "string",
      "resolverLevelMetricsBehavior": "string"
    },
    "introspectionConfig": "string",
    "lambdaAuthorizerConfig": {
      "authorizerResultTtlInSeconds": number,
```

```
        "authorizerUri": "string",
        "identityValidationExpression": "string"
    },
    "logConfig": {
        "cloudWatchLogsRoleArn": "string",
        "excludeVerboseContent": boolean,
        "fieldLogLevel": "string"
    },
    "mergedApiExecutionRoleArn": "string",
    "name": "string",
    "openIDConnectConfig": {
        "authTTL": number,
        "clientId": "string",
        "iatTTL": number,
        "issuer": "string"
    },
    "owner": "string",
    "ownerContact": "string",
    "queryDepthLimit": number,
    "resolverCountLimit": number,
    "tags": {
        "string" : "string"
    },
    "uris": {
        "string" : "string"
    },
    "userPoolConfig": {
        "appIdClientRegex": "string",
        "awsRegion": "string",
        "defaultAction": "string",
        "userPoolId": "string"
    },
    "visibility": "string",
    "wafWebAclArn": "string",
    "xrayEnabled": boolean
}
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## [graphqlApi](#)

The updated GraphqlApi object.

Type: [GraphqlApi](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You don't have access to perform this operation on this resource.

HTTP Status Code: 403

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **ConcurrentModificationException**

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### **UnauthorizedException**

You aren't authorized to perform this operation.

## HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateResolver

Updates a Resolver object.

## Request Syntax

```
POST /v1/apis/apiId/types/typeName/resolvers/fieldName HTTP/1.1
Content-type: application/json

{
  "cachingConfig": {
    "cachingKeys": [ "string" ],
    "ttl": number
  },
  "code": "string",
  "dataSourceName": "string",
  "kind": "string",
  "maxBatchSize": number,
  "metricsConfig": "string",
  "pipelineConfig": {
    "functions": [ "string" ]
  },
  "requestMappingTemplate": "string",
  "responseMappingTemplate": "string",
  "runtime": {
    "name": "string",
    "runtimeVersion": "string"
  },
  "syncConfig": {
    "conflictDetection": "string",
    "conflictHandler": "string",
    "lambdaConflictHandlerConfig": {
      "lambdaConflictHandlerArn": "string"
    }
  }
}
```

## URI Request Parameters

The request uses the following URI parameters.

## apild

The API ID.

Required: Yes

## fieldName

The new field name.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: Yes

## typeName

The new type name.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: Yes

# Request Body

The request accepts the following data in JSON format.

## cachingConfig

The caching configuration for the resolver.

Type: [CachingConfig](#) object

Required: No

## code

The `resolver` code that contains the request and response functions. When `code` is used, the `runtime` is required. The `runtime` value must be `APPSYNC_JS`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32768.

Required: No

### [dataSourceName](#)

The new data source name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: No

### [kind](#)

The resolver type.

- **UNIT:** A UNIT resolver type. A UNIT resolver is the default resolver type. You can use a UNIT resolver to run a GraphQL query against a single data source.
- **PIPELINE:** A PIPELINE resolver type. You can use a PIPELINE resolver to invoke a series of Function objects in a serial manner. You can use a pipeline resolver to run a GraphQL query against multiple data sources.

Type: String

Valid Values: UNIT | PIPELINE

Required: No

### [maxBatchSize](#)

The maximum batching size for a resolver.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2000.

Required: No

### [metricsConfig](#)

Enables or disables enhanced resolver metrics for specified resolvers. Note that metricsConfig won't be used unless the `resolverLevelMetricsBehavior` value

is set to PER\_RESOLVER\_METRICS. If the `resolverLevelMetricsBehavior` is set to FULL\_REQUEST\_RESOLVER\_METRICS instead, `metricsConfig` will be ignored. However, you can still set its value.

`metricsConfig` can be ENABLED or DISABLED.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

### [pipelineConfig](#)

The PipelineConfig.

Type: [PipelineConfig](#) object

Required: No

### [requestMappingTemplate](#)

The new request mapping template.

A resolver uses a request mapping template to convert a GraphQL expression into a format that a data source can understand. Mapping templates are written in Apache Velocity Template Language (VTL).

VTL request mapping templates are optional when using an AWS Lambda data source. For all other data sources, VTL request and response mapping templates are required.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: ^ . \*\$

Required: No

### [responseMappingTemplate](#)

The new response mapping template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: ^.\*\$

Required: No

## runtime

Describes a runtime used by an AWS AppSync pipeline resolver or AWS AppSync function.

Specifies the name and version of the runtime to use. Note that if a runtime is specified, code must also be specified.

Type: [AppSyncRuntime](#) object

Required: No

## syncConfig

The SyncConfig for a resolver attached to a versioned data source.

Type: [SyncConfig](#) object

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "resolver": {
    "cachingConfig": {
      "cachingKeys": [ "string" ],
      "ttl": number
    },
    "code": "string",
    "dataSourceName": "string",
    "fieldName": "string",
    "kind": "string",
    "maxBatchSize": number,
    "metricsConfig": "string",
    "pipelineConfig": {
      "functions": [ "string" ]
    },
    "requestMappingTemplate": "string",
    "resolverArn": "string",
```

```
"responseMappingTemplate": "string",  
"runtime": {  
    "namestring",  
    "runtimeVersion": "string"  
},  
"syncConfig": {  
    "conflictDetection": "string",  
    "conflictHandler": "string",  
    "lambdaConflictHandlerConfig": {  
        "lambdaConflictHandlerArn": "string"  
    }  
},  
"typeName": "string"  
}  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### resolver

The updated Resolver object.

Type: [Resolver](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **ConcurrentModificationException**

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### **UnauthorizedException**

You aren't authorized to perform this operation.

HTTP Status Code: 401

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateSourceApiAssociation

Updates some of the configuration choices of a particular source API association.

## Request Syntax

```
POST /v1/mergedApis/mergedApiIdentifier/sourceApiAssociations/associationId HTTP/1.1
Content-type: application/json

{
  "descriptionsourceApiAssociationConfigmergeType
```

## URI Request Parameters

The request uses the following URI parameters.

### associationId

The ID generated by the AppSync service for the source API association.

Required: Yes

### mergedApildentifier

The identifier of the AppSync Merged API. This is generated by the AppSync service. In most cases, Merged APIs (especially in your account) only require the API ID value or ARN of the merged API. However, Merged APIs in other accounts (cross-account use cases) strictly require the full resource ARN of the merged API.

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### description

The description field.

Type: String

Required: No

### [sourceApiAssociationConfig](#)

The SourceApiAssociationConfig object data.

Type: [SourceApiAssociationConfig](#) object

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "sourceApiAssociation": {
    "associationArn": "string",
    "associationId": "string",
    "description": "string",
    "lastSuccessfulMergeDate": number,
    "mergedApiArn": "string",
    "mergedApiId": "string",
    "sourceApiArn": "string",
    "sourceApiAssociationConfig": {
      "mergeType": "string"
    },
    "sourceApiAssociationStatus": "string",
    "sourceApiAssociationStatusDetail": "string",
    "sourceApiId": "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## [sourceApiAssociation](#)

The SourceApiAssociation object data.

Type: [SourceApiAssociation](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **BadRequestException**

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

### **ConcurrentModificationException**

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

### **InternalFailureException**

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

### **NotFoundException**

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

### **UnauthorizedException**

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateType

Updates a Type object.

## Request Syntax

```
POST /v1/apis/apiId/types/typeName HTTP/1.1
Content-type: application/json

{
  "definitionformat
```

## URI Request Parameters

The request uses the following URI parameters.

### apild

The API ID.

Required: Yes

### typeName

The new type name.

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### definition

The new definition.

Type: String

Required: No

## format

The new type format: SDL or JSON.

Type: String

Valid Values: SDL | JSON

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "type": {
    "arn": "string",
    "definition": "string",
    "description": "string",
    "format": "string",
    "name": "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### type

The updated Type object.

Type: [Type](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## BadRequestException

The request is not well formed. For example, a value is invalid or a required field is missing. Check the field values, and then try again.

HTTP Status Code: 400

## ConcurrentModificationException

Another modification is in progress at this time and it must complete before you can make your change.

HTTP Status Code: 409

## InternalFailureException

An internal AWS AppSync error occurred. Try your request again.

HTTP Status Code: 500

## NotFoundException

The resource specified in the request was not found. Check the resource, and then try again.

HTTP Status Code: 404

## UnauthorizedException

You aren't authorized to perform this operation.

HTTP Status Code: 401

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# Data Types

The AWS AppSync API contains several data types that various actions use. This section describes each data type in detail.

 **Note**

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AdditionalAuthenticationProvider](#)
- [Api](#)
- [ApiAssociation](#)
- [ApiCache](#)
- [ApiKey](#)
- [AppSyncRuntime](#)
- [AuthMode](#)
- [AuthorizationConfig](#)
- [AuthProvider](#)
- [AwsIamConfig](#)
- [BadRequestDetail](#)
- [CachingConfig](#)
- [ChannelNamespace](#)
- [CodeError](#)
- [CodeErrorLocation](#)
- [CognitoConfig](#)
- [CognitoUserPoolConfig](#)
- [DataSource](#)
- [DataSourceIntrospectionModel](#)
- [DataSourceIntrospectionModelField](#)

- [DataSourceIntrospectionModelFieldType](#)
- [DataSourceIntrospectionModelIndex](#)
- [DataSourceIntrospectionResult](#)
- [DeltaSyncConfig](#)
- [DomainNameConfig](#)
- [DynamodbDataSourceConfig](#)
- [ElasticsearchDataSourceConfig](#)
- [EnhancedMetricsConfig](#)
- [ErrorDetail](#)
- [EvaluateCodeErrorDetail](#)
- [EventBridgeDataSourceConfig](#)
- [EventConfig](#)
- [EventLogConfig](#)
- [FunctionConfiguration](#)
- [GraphqlApi](#)
- [HandlerConfig](#)
- [HandlerConfigs](#)
- [HttpDataSourceConfig](#)
- [Integration](#)
- [LambdaAuthorizerConfig](#)
- [LambdaConfig](#)
- [LambdaConflictHandlerConfig](#)
- [LambdaDataSourceConfig](#)
- [LogConfig](#)
- [OpenIDConnectConfig](#)
- [OpenSearchServiceDataSourceConfig](#)
- [PipelineConfig](#)
- [RdsDataApiConfig](#)
- [RdsHttpEndpointConfig](#)
- [RelationalDatabaseDataSourceConfig](#)

- [Resolver](#)
- [SourceApiAssociation](#)
- [SourceApiAssociationConfig](#)
- [SourceApiAssociationSummary](#)
- [SyncConfig](#)
- [Type](#)
- [UserPoolConfig](#)

# AdditionalAuthenticationProvider

Describes an additional authentication provider.

## Contents

### **authenticationType**

The authentication type: API key, AWS Identity and Access Management (IAM), OpenID Connect (OIDC), Amazon Cognito user pools, or AWS Lambda.

Type: String

Valid Values: API\_KEY | AWS\_IAM | AMAZON\_COGNITO\_USER\_POOLS | OPENID\_CONNECT | AWS\_LAMBDA

Required: No

### **lambdaAuthorizerConfig**

Configuration for Lambda function authorization.

Type: [LambdaAuthorizerConfig](#) object

Required: No

### **openIDConnectConfig**

The OIDC configuration.

Type: [OpenIDConnectConfig](#) object

Required: No

### **userPoolConfig**

The Amazon Cognito user pool configuration.

Type: [CognitoUserPoolConfig](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Api

Describes an AWS AppSync API. You can use Api for an AWS AppSync API with your preferred configuration, such as an Event API that provides real-time message publishing and message subscriptions over WebSockets.

## Contents

### apiArn

The Amazon Resource Name (ARN) for the Api.

Type: String

Required: No

### apilId

The Api ID.

Type: String

Required: No

### created

The date and time that the Api was created.

Type: Timestamp

Required: No

### dns

The DNS records for the API. This will include an HTTP and a real-time endpoint.

Type: String to string map

Required: No

### eventConfig

The Event API configuration. This includes the default authorization configuration for connecting, publishing, and subscribing to an Event API.

Type: [EventConfig](#) object

Required: No

### **name**

The name of the Api.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: [A-Za-z0-9\_\-\ ]<sup>+</sup>

Required: No

### **ownerContact**

The owner contact information for the Api

Type: String

Length Constraints: Minimum length of 0. Maximum length of 250.

Pattern: [A-Za-z0-9\_\-\ \.]+

Required: No

### **tags**

A map with keys of TagKey objects and values of TagValue objects.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: ^(?!\aws:)[ a-zA-Z+-=.\_:/]+\$

Value Length Constraints: Maximum length of 256.

Value Pattern: ^[\s\w+-=\.:/@]\*\$

Required: No

## wafWebAclArn

The Amazon Resource Name (ARN) of the AWS WAF web access control list (web ACL) associated with this API, if one exists.

Type: String

Required: No

## xrayEnabled

A flag indicating whether to use AWS X-Ray tracing for this API.

Type: Boolean

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ApiAssociation

Describes an ApiAssociation object.

## Contents

### apilD

The API ID.

Type: String

Required: No

### associationStatus

Identifies the status of an association.

- **PROCESSING:** The API association is being created. You cannot modify association requests during processing.
- **SUCCESS:** The API association was successful. You can modify associations after success.
- **FAILED:** The API association has failed. You can modify associations after failure.

Type: String

Valid Values: PROCESSING | FAILED | SUCCESS

Required: No

### deploymentDetail

Details about the last deployment status.

Type: String

Required: No

### domainName

The domain name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 253.

Pattern: `^(\*\w\d-]*\.\.)?([\w\d-]+\.\.)*[\w\d-]+$`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ApiCache

The ApiCache object.

## Contents

### apiCachingBehavior

Caching behavior.

- **FULL\_REQUEST\_CACHING:** All requests from the same user are cached. Individual resolvers are automatically cached. All API calls will try to return responses from the cache.
- **PER\_RESOLVER\_CACHING:** Individual resolvers that you specify are cached.
- **OPERATION\_LEVEL\_CACHING:** Full requests are cached together and returned without executing resolvers.

Type: String

Valid Values: FULL\_REQUEST\_CACHING | PER\_RESOLVER\_CACHING | OPERATION\_LEVEL\_CACHING

Required: No

### atRestEncryptionEnabled

At-rest encryption flag for cache. You cannot update this setting after creation.

Type: Boolean

Required: No

### healthMetricsConfig

Controls how cache health metrics will be emitted to CloudWatch. Cache health metrics include:

- NetworkBandwidthOutAllowanceExceeded: The network packets dropped because the throughput exceeded the aggregated bandwidth limit. This is useful for diagnosing bottlenecks in a cache configuration.
- EngineCPUUtilization: The CPU utilization (percentage) allocated to the Redis process. This is useful for diagnosing bottlenecks in a cache configuration.

Metrics will be recorded by API ID. You can set the value to ENABLED or DISABLED.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

### **status**

The cache instance status.

- **AVAILABLE:** The instance is available for use.
- **CREATING:** The instance is currently creating.
- **DELETING:** The instance is currently deleting.
- **MODIFYING:** The instance is currently modifying.
- **FAILED:** The instance has failed creation.

Type: String

Valid Values: AVAILABLE | CREATING | DELETING | MODIFYING | FAILED

Required: No

### **transitEncryptionEnabled**

Transit encryption flag when connecting to cache. You cannot update this setting after creation.

Type: Boolean

Required: No

### **ttl**

TTL in seconds for cache entries.

Valid values are 1–3,600 seconds.

Type: Long

Required: No

### **type**

The cache instance type. Valid values are

- **SMALL**

- MEDIUM
- LARGE
- XLARGE
- LARGE\_2X
- LARGE\_4X
- LARGE\_8X (not available in all regions)
- LARGE\_12X

Historically, instance types were identified by an EC2-style value. As of July 2020, this is deprecated, and the generic identifiers above should be used.

The following legacy instance types are available, but their use is discouraged:

- **T2\_SMALL**: A t2.small instance type.
- **T2\_MEDIUM**: A t2.medium instance type.
- **R4\_LARGE**: A r4.large instance type.
- **R4\_XLARGE**: A r4.xlarge instance type.
- **R4\_2XLARGE**: A r4.2xlarge instance type.
- **R4\_4XLARGE**: A r4.4xlarge instance type.
- **R4\_8XLARGE**: A r4.8xlarge instance type.

Type: String

Valid Values: T2\_SMALL | T2\_MEDIUM | R4\_LARGE | R4\_XLARGE | R4\_2XLARGE | R4\_4XLARGE | R4\_8XLARGE | SMALL | MEDIUM | LARGE | XLARGE | LARGE\_2X | LARGE\_4X | LARGE\_8X | LARGE\_12X

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

# ApiKey

Describes an API key.

Customers invoke AWS AppSync GraphQL API operations with API keys as an identity mechanism. There are two key versions:

**da1:** We introduced this version at launch in November 2017. These keys always expire after 7 days. Amazon DynamoDB TTL manages key expiration. These keys ceased to be valid after February 21, 2018, and they should no longer be used.

- `ListApiKeys` returns the expiration time in milliseconds.
- `CreateApiKey` returns the expiration time in milliseconds.
- `UpdateApiKey` is not available for this key version.
- `DeleteApiKey` deletes the item from the table.
- Expiration is stored in DynamoDB as milliseconds. This results in a bug where keys are not automatically deleted because DynamoDB expects the TTL to be stored in seconds. As a one-time action, we deleted these keys from the table on February 21, 2018.

**da2:** We introduced this version in February 2018 when AWS AppSync added support to extend key expiration.

- `ListApiKeys` returns the expiration time and deletion time in seconds.
- `CreateApiKey` returns the expiration time and deletion time in seconds and accepts a user-provided expiration time in seconds.
- `UpdateApiKey` returns the expiration time and deletion time in seconds and accepts a user-provided expiration time in seconds. Expired API keys are kept for 60 days after the expiration time. You can update the key expiration time as long as the key isn't deleted.
- `DeleteApiKey` deletes the item from the table.
- Expiration is stored in DynamoDB as seconds. After the expiration time, using the key to authenticate will fail. However, you can reinstate the key before deletion.
- Deletion is stored in DynamoDB as seconds. The key is deleted after deletion time.

## Contents

### **deletes**

The time after which the API key is deleted. The date is represented as seconds since the epoch, rounded down to the nearest hour.

Type: Long

Required: No

### **description**

A description of the purpose of the API key.

Type: String

Required: No

### **expires**

The time after which the API key expires. The date is represented as seconds since the epoch, rounded down to the nearest hour.

Type: Long

Required: No

### **id**

The API key ID.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

# AppSyncRuntime

Describes a runtime used by an AWS AppSync pipeline resolver or AWS AppSync function. Specifies the name and version of the runtime to use. Note that if a runtime is specified, code must also be specified.

## Contents

### **name**

The name of the runtime to use. Currently, the only allowed value is APPSYNC\_JS.

Type: String

Valid Values: APPSYNC\_JS

Required: Yes

### **runtimeVersion**

The version of the runtime to use. Currently, the only allowed version is 1.0.0.

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# AuthMode

Describes an authorization configuration. Use AuthMode to specify the publishing and subscription authorization configuration for an Event API.

## Contents

### authType

The authorization type.

Type: String

Valid Values: API\_KEY | AWS\_IAM | AMAZON\_COGNITO\_USER\_POOLS | OPENID\_CONNECT  
| AWS\_LAMBDA

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# AuthorizationConfig

The authorization configuration in case the HTTP endpoint requires authorization.

## Contents

### authorizationType

The authorization type that the HTTP endpoint requires.

- **AWS\_IAM:** The authorization type is Signature Version 4 (SigV4).

Type: String

Valid Values: AWS\_IAM

Required: Yes

### awsIamConfig

The AWS Identity and Access Management (IAM) settings.

Type: [AwsIamConfig](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# AuthProvider

Describes an authorization provider.

## Contents

### authType

The authorization type.

Type: String

Valid Values: API\_KEY | AWS\_IAM | AMAZON\_COGNITO\_USER\_POOLS | OPENID\_CONNECT | AWS\_LAMBDA

Required: Yes

### cognitoConfig

Describes an Amazon Cognito user pool configuration.

Type: [CognitoConfig](#) object

Required: No

### lambdaAuthorizerConfig

A LambdaAuthorizerConfig specifies how to authorize AWS AppSync API access when using the AWS\_LAMBDA authorizer mode. Be aware that an AWS AppSync API can have only one AWS Lambda authorizer configured at a time.

Type: [LambdaAuthorizerConfig](#) object

Required: No

### openIDConnectConfig

Describes an OpenID Connect (OIDC) configuration.

Type: [OpenIDConnectConfig](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# AwsIamConfig

The AWS Identity and Access Management (IAM) configuration.

## Contents

### **signingRegion**

The signing AWS Region for IAM authorization.

Type: String

Required: No

### **signingServiceName**

The signing service name for IAM authorization.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# BadRequestDetail

Provides further details for the reason behind the bad request. For reason type CODE\_ERROR, the detail will contain a list of code errors.

## Contents

### codeErrors

Contains the list of errors in the request.

Type: Array of [CodeError](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# CachingConfig

The caching configuration for a resolver that has caching activated.

## Contents

### ttl

The TTL in seconds for a resolver that has caching activated.

Valid values are 1–3,600 seconds.

Type: Long

Required: Yes

### cachingKeys

The caching keys for a resolver that has caching activated.

Valid values are entries from the `$context.arguments`, `$context.source`, and `$context.identity` maps.

Type: Array of strings

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ChannelNamespace

Describes a channel namespace associated with an Api. The ChannelNamespace contains the definitions for code handlers for the Api.

## Contents

### apild

The Api ID.

Type: String

Required: No

### channelNamespaceArn

The Amazon Resource Name (ARN) for the ChannelNamespace.

Type: String

Required: No

### codeHandlers

The event handler functions that run custom business logic to process published events and subscribe requests.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32768.

Required: No

### created

The date and time that the ChannelNamespace was created.

Type: Timestamp

Required: No

### handlerConfigs

The configuration for the OnPublish and OnSubscribe handlers.

Type: [HandlerConfigs](#) object

Required: No

### lastModified

The date and time that the ChannelNamespace was last changed.

Type: [Timestamp](#)

Required: No

### name

The name of the channel namespace. This name must be unique within the API.

Type: [String](#)

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: ([A-Za-z0-9](?:[A-Za-z0-9\-\\_]{0,48}[A-Za-z0-9])?)

Required: No

### publishAuthModes

The authorization mode to use for publishing messages on the channel namespace. This configuration overrides the default Apiauthorization configuration.

Type: Array of [AuthMode](#) objects

Required: No

### subscribeAuthModes

The authorization mode to use for subscribing to messages on the channel namespace. This configuration overrides the default Apiauthorization configuration.

Type: Array of [AuthMode](#) objects

Required: No

### tags

A map with keys of TagKey objects and values of TagValue objects.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(!aws:)[ a-zA-Z+-=._:/]+$`

Value Length Constraints: Maximum length of 256.

Value Pattern: `^[\s\w+-=\.\:/@]*$`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# CodeError

Describes an AppSync error.

## Contents

### **errorType**

The type of code error.

Examples include, but aren't limited to: LINT\_ERROR, PARSER\_ERROR.

Type: String

Required: No

### **location**

The line, column, and span location of the error in the code.

Type: [CodeErrorLocation](#) object

Required: No

### **value**

A user presentable error.

Examples include, but aren't limited to: Parsing error: Unterminated string literal.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# CodeErrorLocation

Describes the location of the error in a code sample.

## Contents

### column

The column number in the code. Defaults to `0` if unknown.

Type: Integer

Required: No

### line

The line number in the code. Defaults to `0` if unknown.

Type: Integer

Required: No

### span

The span/length of the error. Defaults to `-1` if unknown.

Type: Integer

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# CognitoConfig

Describes an Amazon Cognito configuration.

## Contents

### awsRegion

The AWS Region in which the user pool was created.

Type: String

Required: Yes

### userPoolId

The user pool ID.

Type: String

Required: Yes

### appIdClientRegex

A regular expression for validating the incoming Amazon Cognito user pool app client ID. If this value isn't set, no filtering is applied.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# CognitoUserPoolConfig

Describes an Amazon Cognito user pool configuration.

## Contents

### **awsRegion**

The AWS Region in which the user pool was created.

Type: String

Required: Yes

### **userPoolId**

The user pool ID.

Type: String

Required: Yes

### **appIdClientRegex**

A regular expression for validating the incoming Amazon Cognito user pool app client ID. If this value isn't set, no filtering is applied.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DataSource

Describes a data source.

## Contents

### **dataSourceArn**

The data source Amazon Resource Name (ARN).

Type: String

Required: No

### **description**

The description of the data source.

Type: String

Required: No

### **dynamodbConfig**

DynamoDB settings.

Type: [DynamodbDataSourceConfig](#) object

Required: No

### **elasticsearchConfig**

Amazon OpenSearch Service settings.

Type: [ElasticsearchDataSourceConfig](#) object

Required: No

### **eventBridgeConfig**

Amazon EventBridge settings.

Type: [EventBridgeDataSourceConfig](#) object

Required: No

## httpConfig

HTTP endpoint settings.

Type: [HttpDataSourceConfig](#) object

Required: No

## lambdaConfig

Lambda settings.

Type: [LambdaDataSourceConfig](#) object

Required: No

## metricsConfig

Enables or disables enhanced data source metrics for specified data sources. Note that metricsConfig won't be used unless the dataSourceLevelMetricsBehavior value is set to PER\_DATA\_SOURCE\_METRICS. If the dataSourceLevelMetricsBehavior is set to FULL\_REQUEST\_DATA\_SOURCE\_METRICS instead, metricsConfig will be ignored. However, you can still set its value.

metricsConfig can be ENABLED or DISABLED.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

## name

The name of the data source.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [A-Za-z][0-9A-Za-z]\*

Required: No

## openSearchServiceConfig

Amazon OpenSearch Service settings.

Type: [OpenSearchServiceDataSourceConfig](#) object

Required: No

## relationalDatabaseConfig

Relational database settings.

Type: [RelationalDatabaseDataSourceConfig](#) object

Required: No

## serviceRoleArn

The AWS Identity and Access Management (IAM) service role Amazon Resource Name (ARN) for the data source. The system assumes this role when accessing the data source.

Type: String

Required: No

## type

The type of the data source.

- **AWS\_LAMBDA:** The data source is an AWS Lambda function.
- **AMAZON\_DYNAMODB:** The data source is an Amazon DynamoDB table.
- **AMAZON\_ELASTICSEARCH:** The data source is an Amazon OpenSearch Service domain.
- **AMAZON\_OPENSEARCH\_SERVICE:** The data source is an Amazon OpenSearch Service domain.
- **AMAZON\_EVENTBRIDGE:** The data source is an Amazon EventBridge configuration.
- **AMAZON\_BEDROCK\_RUNTIME:** The data source is the Amazon Bedrock runtime.
- **NONE:** There is no data source. Use this type when you want to invoke a GraphQL operation without connecting to a data source, such as when you're performing data transformation with resolvers or invoking a subscription from a mutation.
- **HTTP:** The data source is an HTTP endpoint.
- **RELATIONAL\_DATABASE:** The data source is a relational database.

Type: String

Valid Values: AWS\_LAMBDA | AMAZON\_DYNAMODB | AMAZON\_ELASTICSEARCH | NONE | HTTP | RELATIONAL\_DATABASE | AMAZON\_OPENSEARCH\_SERVICE | AMAZON\_EVENTBRIDGE | AMAZON\_BEDROCK\_RUNTIME

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DataSourceIntrospectionModel

Contains the introspected data that was retrieved from the data source.

## Contents

### fields

The DataSourceIntrospectionModelField object data.

Type: Array of [DataSourceIntrospectionModelField](#) objects

Required: No

### indexes

The array of DataSourceIntrospectionModelIndex objects.

Type: Array of [DataSourceIntrospectionModelIndex](#) objects

Required: No

### name

The name of the model. For example, this could be the name of a single table in a database.

Type: String

Required: No

### primaryKey

The primary key stored as a DataSourceIntrospectionModelIndex object.

Type: [DataSourceIntrospectionModelIndex](#) object

Required: No

### sdl

Contains the output of the SDL that was generated from the introspected types. This is controlled by the `includeModelsSDL` parameter of the `GetDataSourceIntrospection` operation.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DataSourceIntrospectionModelField

Represents the fields that were retrieved from the introspected data.

## Contents

### length

The length value of the introspected field.

Type: Long

Required: No

### name

The name of the field that was retrieved from the introspected data.

Type: String

Required: No

### type

The DataSourceIntrospectionModelFieldType object data.

Type: [DataSourceIntrospectionModelFieldType](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DataSourceIntrospectionModelFieldType

Represents the type data for each field retrieved from the introspection.

## Contents

### kind

Specifies the classification of data. For example, this could be set to values like `Scalar` or `NonNull` to indicate a fundamental property of the field.

Valid values include:

- `Scalar`: Indicates the value is a primitive type (scalar).
- `NonNull`: Indicates the field cannot be null.
- `List`: Indicates the field contains a list.

Type: String

Required: No

### name

The name of the data type that represents the field. For example, `String` is a valid name value.

Type: String

Required: No

### type

The `DataSourceIntrospectionModelFieldType` object data. The type is only present if `DataSourceIntrospectionModelFieldType.kind` is set to `NonNull` or `List`.

The type typically contains its own `kind` and `name` fields to represent the actual type data. For instance, `type` could contain a `kind` value of `Scalar` with a `name` value of `String`. The values `Scalar` and `String` will be collectively stored in the `values` field.

Type: [DataSourceIntrospectionModelFieldType](#) object

Required: No

## values

The values of the type field. This field represents the AppSync data type equivalent of the introspected field.

Type: Array of strings

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DataSourceIntrospectionModelIndex

The index that was retrieved from the introspected data.

## Contents

### fields

The fields of the index.

Type: Array of strings

Required: No

### name

The name of the index.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DataSourceIntrospectionResult

Represents the output of a `DataSourceIntrospectionResult`. This is the populated result of a `GetDataSourceIntrospection` operation.

## Contents

### models

The array of `DataSourceIntrospectionModel` objects.

Type: Array of [DataSourceIntrospectionModel](#) objects

Required: No

### nextToken

Determines the number of types to be returned in a single response before paginating. This value is typically taken from `nextToken` value from the previous response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\S]+

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DeltaSyncConfig

Describes a Delta Sync configuration.

## Contents

### baseTableTTL

The number of minutes that an Item is stored in the data source.

Type: Long

Required: No

### deltaSyncTableName

The Delta Sync table name.

Type: String

Required: No

### deltaSyncTableTTL

The number of minutes that a Delta Sync log entry is stored in the Delta Sync table.

Type: Long

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DomainNameConfig

Describes a configuration for a custom domain.

## Contents

### appsyncDomainName

The domain name that AWS AppSync provides.

Type: String

Required: No

### certificateArn

The Amazon Resource Name (ARN) of the certificate. This can be an AWS Certificate Manager (ACM) certificate or an AWS Identity and Access Management (IAM) server certificate.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[a-zA-Z-]\*:(acm|iam):[a-zA-Z0-9-]\*:\d{12}:(certificate|server-certificate)/[0-9A-Za-z\_-/-]\*\$

Required: No

### description

A description of the DomainName configuration.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: ^.\*\$

Required: No

### domainName

The domain name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 253.

Pattern:  $^(\wedge[\wedge\dash{-}]*\wedge.)?([\wedge\dash{-}]+\wedge.)+[\wedge\dash{-}]+\$$

Required: No

### domainNameArn

The Amazon Resource Name (ARN) of the domain name.

Type: String

Required: No

### hostedZoneId

The ID of your Amazon Route 53 hosted zone.

Type: String

Required: No

### tags

A map with keys of TagKey objects and values of TagValue objects.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern:  $^(\wedge[!aws:][\wedge-zA-Z+-=._:/]+)\+$$

Value Length Constraints: Maximum length of 256.

Value Pattern:  $^[\wedge[s\wedge+-=\wedge._:/@]]*\$$

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DynamodbDataSourceConfig

Describes an Amazon DynamoDB data source configuration.

## Contents

### awsRegion

The AWS Region.

Type: String

Required: Yes

### tableName

The table name.

Type: String

Required: Yes

### deltaSyncConfig

The DeltaSyncConfig for a versioned data source.

Type: [DeltaSyncConfig](#) object

Required: No

### useCallerCredentials

Set to TRUE to use Amazon Cognito credentials with this data source.

Type: Boolean

Required: No

### versioned

Set to TRUE to use Conflict Detection and Resolution with this data source.

Type: Boolean

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ElasticsearchDataSourceConfig

Describes an OpenSearch data source configuration.

As of September 2021, Amazon Elasticsearch service is Amazon OpenSearch Service. This configuration is deprecated. For new data sources, use [OpenSearchServiceDataSourceConfig](#) to specify an OpenSearch data source.

## Contents

### **awsRegion**

The AWS Region.

Type: String

Required: Yes

### **endpoint**

The endpoint.

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# EnhancedMetricsConfig

Enables and controls the enhanced metrics feature. Enhanced metrics emit granular data on API usage and performance such as AppSync request and error counts, latency, and cache hits/misses. All enhanced metric data is sent to your CloudWatch account, and you can configure the types of data that will be sent.

Enhanced metrics can be configured at the resolver, data source, and operation levels.

EnhancedMetricsConfig contains three required parameters, each controlling one of these categories:

1. `resolverLevelMetricsBehavior`: Controls how resolver metrics will be emitted to CloudWatch. Resolver metrics include:

- GraphQL errors: The number of GraphQL errors that occurred.
- Requests: The number of invocations that occurred during a request.
- Latency: The time to complete a resolver invocation.
- Cache hits: The number of cache hits during a request.
- Cache misses: The number of cache misses during a request.

These metrics can be emitted to CloudWatch per resolver or for all resolvers in the request.

Metrics will be recorded by API ID and resolver name. `resolverLevelMetricsBehavior` accepts one of these values at a time:

- FULL\_REQUEST\_RESOLVER\_METRICS: Records and emits metric data for all resolvers in the request.
- PER\_RESOLVER\_METRICS: Records and emits metric data for resolvers that have the `metricsConfig` value set to ENABLED.

2. `dataSourceLevelMetricsBehavior`: Controls how data source metrics will be emitted to CloudWatch. Data source metrics include:

- Requests: The number of invocations that occurred during a request.
- Latency: The time to complete a data source invocation.
- Errors: The number of errors that occurred during a data source invocation.

These metrics can be emitted to CloudWatch per data source or for all data sources in the request. Metrics will be recorded by API ID and data source name.

`dataSourceLevelMetricsBehavior` accepts one of these values at a time:

- **FULL\_REQUEST\_DATA\_SOURCE\_METRICS:** Records and emits metric data for all data sources in the request.
- **PER\_DATA\_SOURCE\_METRICS:** Records and emits metric data for data sources that have the `metricsConfig` value set to `ENABLED`.

3. `operationLevelMetricsConfig`: Controls how operation metrics will be emitted to CloudWatch. Operation metrics include:

- **Requests:** The number of times a specified GraphQL operation was called.
- **GraphQL errors:** The number of GraphQL errors that occurred during a specified GraphQL operation.

Metrics will be recorded by API ID and operation name. You can set the value to `ENABLED` or `DISABLED`.

## Contents

### **dataSourceLevelMetricsBehavior**

Controls how data source metrics will be emitted to CloudWatch. Data source metrics include:

- **Requests:** The number of invocations that occurred during a request.
- **Latency:** The time to complete a data source invocation.
- **Errors:** The number of errors that occurred during a data source invocation.

These metrics can be emitted to CloudWatch per data source or for all data sources in the request. Metrics will be recorded by API ID and data source name. `dataSourceLevelMetricsBehavior` accepts one of these values at a time:

- **FULL\_REQUEST\_DATA\_SOURCE\_METRICS:** Records and emits metric data for all data sources in the request.
- **PER\_DATA\_SOURCE\_METRICS:** Records and emits metric data for data sources that have the `metricsConfig` value set to `ENABLED`.

Type: String

Valid Values: `FULL_REQUEST_DATA_SOURCE_METRICS` | `PER_DATA_SOURCE_METRICS`

Required: Yes

## **operationLevelMetricsConfig**

Controls how operation metrics will be emitted to CloudWatch. Operation metrics include:

- Requests: The number of times a specified GraphQL operation was called.
- GraphQL errors: The number of GraphQL errors that occurred during a specified GraphQL operation.

Metrics will be recorded by API ID and operation name. You can set the value to ENABLED or DISABLED.

Type: String

Valid Values: ENABLED | DISABLED

Required: Yes

## **resolverLevelMetricsBehavior**

Controls how resolver metrics will be emitted to CloudWatch. Resolver metrics include:

- GraphQL errors: The number of GraphQL errors that occurred.
- Requests: The number of invocations that occurred during a request.
- Latency: The time to complete a resolver invocation.
- Cache hits: The number of cache hits during a request.
- Cache misses: The number of cache misses during a request.

These metrics can be emitted to CloudWatch per resolver or for all resolvers in the request.

Metrics will be recorded by API ID and resolver name. `resolverLevelMetricsBehavior` accepts one of these values at a time:

- `FULL_REQUEST_RESOLVER_METRICS`: Records and emits metric data for all resolvers in the request.
- `PER_RESOLVER_METRICS`: Records and emits metric data for resolvers that have the `metricsConfig` value set to ENABLED.

Type: String

Valid Values: `FULL_REQUEST_RESOLVER_METRICS` | `PER_RESOLVER_METRICS`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

## ErrorDetail

Contains the list of errors generated. When using JavaScript, this will apply to the request or response function evaluation.

### Contents

#### message

The error payload.

Type: String

Required: No

### See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# EvaluateCodeErrorDetail

Contains the list of errors from a code evaluation response.

## Contents

### codeErrors

Contains the list of CodeError objects.

Type: Array of [CodeError](#) objects

Required: No

### message

The error payload.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# EventBridgeDataSourceConfig

Describes an Amazon EventBridge bus data source configuration.

## Contents

### eventBusArn

The ARN of the event bus. For more information about event buses, see [Amazon EventBridge event buses](#).

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# EventConfig

Describes the authorization configuration for connections, message publishing, message subscriptions, and logging for an Event API.

## Contents

### authProviders

A list of authorization providers.

Type: Array of [AuthProvider](#) objects

Required: Yes

### connectionAuthModes

A list of valid authorization modes for the Event API connections.

Type: Array of [AuthMode](#) objects

Required: Yes

### defaultPublishAuthModes

A list of valid authorization modes for the Event API publishing.

Type: Array of [AuthMode](#) objects

Required: Yes

### defaultSubscribeAuthModes

A list of valid authorization modes for the Event API subscriptions.

Type: Array of [AuthMode](#) objects

Required: Yes

### logConfig

The CloudWatch Logs configuration for the Event API.

Type: [EventLogConfig](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# EventLogConfig

Describes the CloudWatch Logs configuration for the Event API.

## Contents

### cloudWatchLogsRoleArn

The IAM service role that AWS AppSync assumes to publish CloudWatch Logs in your account.

Type: String

Required: Yes

### logLevel

The type of information to log for the Event API.

Type: String

Valid Values: NONE | ERROR | ALL | INFO | DEBUG

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# FunctionConfiguration

A function is a reusable entity. You can use multiple functions to compose the resolver logic.

## Contents

### code

The function code that contains the request and response functions. When code is used, the runtime is required. The runtime value must be APPSYNC\_JS.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32768.

Required: No

### dataSourceName

The name of the DataSource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: No

### description

The Function description.

Type: String

Required: No

### functionArn

The Amazon Resource Name (ARN) of the Function object.

Type: String

Required: No

**functionId**

A unique ID representing the Function object.

Type: String

Required: No

**functionVersion**

The version of the request mapping template. Currently, only the 2018-05-29 version of the template is supported.

Type: String

Required: No

**maxBatchSize**

The maximum batching size for a resolver.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2000.

Required: No

**name**

The name of the Function object.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: No

**requestMappingTemplate**

The Function request mapping template. Functions support only the 2018-05-29 version of the request mapping template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: ^ . \*\$

Required: No

### **responseMappingTemplate**

The Function response mapping template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: ^ . \*\$

Required: No

### **runtime**

Describes a runtime used by an AWS AppSync pipeline resolver or AWS AppSync function.

Specifies the name and version of the runtime to use. Note that if a runtime is specified, code must also be specified.

Type: [AppSyncRuntime](#) object

Required: No

### **syncConfig**

Describes a Sync configuration for a resolver.

Specifies which Conflict Detection strategy and Resolution strategy to use when the resolver is invoked.

Type: [SyncConfig](#) object

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# GraphqlApi

Describes a GraphQL API.

## Contents

### additionalAuthenticationProviders

A list of additional authentication providers for the GraphqlApi API.

Type: Array of [AdditionalAuthenticationProvider](#) objects

Required: No

### apilId

The API ID.

Type: String

Required: No

### apiType

The value that indicates whether the GraphQL API is a standard API (GRAPHQL) or merged API (MERGED).

Type: String

Valid Values: GRAPHQL | MERGED

Required: No

### arn

The Amazon Resource Name (ARN).

Type: String

Required: No

### authenticationType

The authentication type.

Type: String

Valid Values: API\_KEY | AWS\_IAM | AMAZON\_COGNITO\_USER\_POOLS | OPENID\_CONNECT  
| AWS\_LAMBDA

Required: No

## dns

The DNS records for the API.

Type: String to string map

Required: No

## enhancedMetricsConfig

The enhancedMetricsConfig object.

Type: [EnhancedMetricsConfig](#) object

Required: No

## introspectionConfig

Sets the value of the GraphQL API to enable (ENABLED) or disable (DISABLED) introspection. If no value is provided, the introspection configuration will be set to ENABLED by default. This field will produce an error if the operation attempts to use the introspection feature while this field is disabled.

For more information about introspection, see [GraphQL introspection](#).

Type: String

Valid Values: ENABLED | DISABLED

Required: No

## lambdaAuthorizerConfig

Configuration for Lambda function authorization.

Type: [LambdaAuthorizerConfig](#) object

Required: No

## logConfig

The Amazon CloudWatch Logs configuration.

Type: [LogConfig](#) object

Required: No

## mergedApiExecutionRoleArn

The Identity and Access Management service role ARN for a merged API. The AppSync service assumes this role on behalf of the Merged API to validate access to source APIs at runtime and to prompt the AUTO\_MERGE to update the merged API endpoint with the source API changes automatically.

Type: String

Required: No

## name

The API name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: No

## openIDConnectConfig

The OpenID Connect configuration.

Type: [OpenIDConnectConfig](#) object

Required: No

## owner

The account owner of the GraphQL API.

Type: String

Required: No

## ownerContact

The owner contact information for an API resource.

This field accepts any string input with a length of 0 - 256 characters.

Type: String

Required: No

## queryDepthLimit

The maximum depth a query can have in a single request. Depth refers to the amount of nested levels allowed in the body of query. The default value is 0 (or unspecified), which indicates there's no depth limit. If you set a limit, it can be between 1 and 75 nested levels. This field will produce a limit error if the operation falls out of bounds.

Note that fields can still be set to nullable or non-nullable. If a non-nullable field produces an error, the error will be thrown upwards to the first nullable field available.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 75.

Required: No

## resolverCountLimit

The maximum number of resolvers that can be invoked in a single request. The default value is 0 (or unspecified), which will set the limit to 10000. When specified, the limit value can be between 1 and 10000. This field will produce a limit error if the operation falls out of bounds.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 10000.

Required: No

## tags

The tags.

Type: String to string map

Map Entries: Maximum number of 50 items.

**Key Length Constraints:** Minimum length of 1. Maximum length of 128.

**Key Pattern:** ^(?!aws:)[ a-zA-Z+-=.:\_:/]+\$

**Value Length Constraints:** Maximum length of 256.

**Value Pattern:** ^[\s\w+-=\.\:/@]\*\$

**Required:** No

## **uris**

The URIs.

**Type:** String to string map

**Required:** No

## **userPoolConfig**

The Amazon Cognito user pool configuration.

**Type:** [UserPoolConfig](#) object

**Required:** No

## **visibility**

Sets the value of the GraphQL API to public (GLOBAL) or private (PRIVATE). If no value is provided, the visibility will be set to GLOBAL by default. This value cannot be changed once the API has been created.

**Type:** String

**Valid Values:** GLOBAL | PRIVATE

**Required:** No

## **wafWebAclArn**

The ARN of the AWS WAF access control list (ACL) associated with this GraphqlApi, if one exists.

**Type:** String

**Required:** No

## xrayEnabled

A flag indicating whether to use AWS X-Ray tracing for this `GraphqlApi`.

Type: Boolean

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# HandlerConfig

The configuration for a handler.

## Contents

### behavior

The behavior for the handler.

Type: String

Valid Values: CODE | DIRECT

Required: Yes

### integration

The integration data source configuration for the handler.

Type: [Integration](#) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# HandlerConfigs

The configuration for the OnPublish and OnSubscribe handlers.

## Contents

### onPublish

The configuration for the OnPublish handler.

Type: [HandlerConfig object](#)

Required: No

### onSubscribe

The configuration for the OnSubscribe handler.

Type: [HandlerConfig object](#)

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# HttpDataSourceConfig

Describes an HTTP data source configuration.

## Contents

### authorizationConfig

The authorization configuration in case the HTTP endpoint requires authorization.

Type: [AuthorizationConfig](#) object

Required: No

### endpoint

The HTTP URL endpoint. You can specify either the domain name or IP, and port combination, and the URL scheme must be HTTP or HTTPS. If you don't specify the port, AWS AppSync uses the default port 80 for the HTTP endpoint and port 443 for HTTPS endpoints.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Integration

The integration data source configuration for the handler.

## Contents

### **dataSourceName**

The unique name of the data source that has been configured on the API.

Type: String

Required: Yes

### **lambdaConfig**

The configuration for a Lambda data source.

Type: [LambdaConfig object](#)

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# LambdaAuthorizerConfig

A LambdaAuthorizerConfig specifies how to authorize AWS AppSync API access when using the AWS\_LAMBDA authorizer mode. Be aware that an AWS AppSync API can have only one AWS Lambda authorizer configured at a time.

## Contents

### authorizerUri

The Amazon Resource Name (ARN) of the Lambda function to be called for authorization. This can be a standard Lambda ARN, a version ARN (.../v3), or an alias ARN.

**Note:** This Lambda function must have the following resource-based policy assigned to it. When configuring Lambda authorizers in the console, this is done for you. To use the AWS Command Line Interface (AWS CLI), run the following:

```
aws lambda add-permission --function-name "arn:aws:lambda:us-east-2:111122223333:function:my-function" --statement-id "appsync" --principal appsync.amazonaws.com --action lambda:InvokeFunction
```

Type: String

Required: Yes

### authorizerResultTtlInSeconds

The number of seconds a response should be cached for. The default is 0 seconds, which disables caching. If you don't specify a value for authorizerResultTtlInSeconds, the default value is used. The maximum value is one hour (3600 seconds). The Lambda function can override this by returning a ttlOverride key in its response.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 3600.

Required: No

### identityValidationExpression

A regular expression for validation of tokens before the Lambda function is called.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# LambdaConfig

The configuration for a Lambda data source.

## Contents

### invokeType

The invocation type for a Lambda data source.

Type: String

Valid Values: REQUEST\_RESPONSE | EVENT

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# LambdaConflictHandlerConfig

The LambdaConflictHandlerConfig object when configuring LAMBDA as the Conflict Handler.

## Contents

### **lambdaConflictHandlerArn**

The Amazon Resource Name (ARN) for the Lambda function to use as the Conflict Handler.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# LambdaDataSourceConfig

Describes an AWS Lambda data source configuration.

## Contents

### **lambdaFunctionArn**

The Amazon Resource Name (ARN) for the Lambda function.

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# LogConfig

The Amazon CloudWatch Logs configuration.

## Contents

### cloudWatchLogsRoleArn

The service role that AWS AppSync assumes to publish to CloudWatch logs in your account.

Type: String

Required: Yes

### fieldLogLevel

The field logging level. Values can be NONE, ERROR, or ALL.

- **NONE:** No field-level logs are captured.
- **ERROR:** Logs the following information only for the fields that are in error:
  - The error section in the server response.
  - Field-level errors.
  - The generated request/response functions that got resolved for error fields.
- **ALL:** The following information is logged for all fields in the query:
  - Field-level tracing information.
  - The generated request/response functions that got resolved for each field.

Type: String

Valid Values: NONE | ERROR | ALL | INFO | DEBUG

Required: Yes

### excludeVerboseContent

Set to TRUE to exclude sections that contain information such as headers, context, and evaluated mapping templates, regardless of logging level.

Type: Boolean

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# OpenIDConnectConfig

Describes an OpenID Connect (OIDC) configuration.

## Contents

### issuer

The issuer for the OIDC configuration. The issuer returned by discovery must exactly match the value of `iss` in the ID token.

Type: String

Required: Yes

### authTTL

The number of milliseconds that a token is valid after being authenticated.

Type: Long

Required: No

### clientId

The client identifier of the relying party at the OpenID identity provider. This identifier is typically obtained when the relying party is registered with the OpenID identity provider. You can specify a regular expression so that AWS AppSync can validate against multiple client identifiers at a time.

Type: String

Required: No

### iatTTL

The number of milliseconds that a token is valid after it's issued to a user.

Type: Long

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# OpenSearchServiceDataSourceConfig

Describes an OpenSearch data source configuration.

## Contents

### awsRegion

The AWS Region.

Type: String

Required: Yes

### endpoint

The endpoint.

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# PipelineConfig

The pipeline configuration for a resolver of kind PIPELINE.

## Contents

### functions

A list of Function objects.

Type: Array of strings

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RdsDataApiConfig

Contains the metadata required to introspect the RDS cluster.

## Contents

### databaseName

The name of the database in the cluster.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

### resourceArn

The resource ARN of the RDS cluster.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[a-z-]\*:rds:[a-z0-9-]\*:\d{12}:cluster:[0-9A-Za-z\_-/-]\*\$

Required: Yes

### secretArn

The secret's ARN that was obtained from Secrets Manager. A secret consists of secret information, the secret value, plus metadata about the secret. A secret value can be a string or binary. It typically includes the ARN, secret name and description, policies, tags, encryption key from the Key Management Service, and key rotation data.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[a-z-]\*:secretsmanager:[a-z0-9-]\*:\d{12}:secret:[0-9A-Za-z\_-+=.@!-]\*\$

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RdsHttpEndpointConfig

The Amazon Relational Database Service (Amazon RDS) HTTP endpoint configuration.

## Contents

### **awsRegion**

AWS Region for Amazon RDS HTTP endpoint.

Type: String

Required: No

### **awsSecretStoreArn**

AWS secret store Amazon Resource Name (ARN) for database credentials.

Type: String

Required: No

### **databaseName**

Logical database name.

Type: String

Required: No

### **dbClusterIdentifier**

Amazon RDS cluster Amazon Resource Name (ARN).

Type: String

Required: No

### **schema**

Logical schema name.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RelationalDatabaseDataSourceConfig

Describes a relational database data source configuration.

## Contents

### rdsHttpEndpointConfig

Amazon RDS HTTP endpoint settings.

Type: [RdsHttpEndpointConfig](#) object

Required: No

### relationalDatabaseSourceType

Source type for the relational database.

- **RDS\_HTTP\_ENDPOINT:** The relational database source type is an Amazon Relational Database Service (Amazon RDS) HTTP endpoint.

Type: String

Valid Values: RDS\_HTTP\_ENDPOINT

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Resolver

Describes a resolver.

## Contents

### cachingConfig

The caching configuration for the resolver.

Type: [CachingConfig](#) object

Required: No

### code

The `resolver` code that contains the request and response functions. When `code` is used, the `runtime` is required. The `runtime` value must be `APPSYNC_JS`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32768.

Required: No

### dataSourceName

The resolver data source name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: `[_A-Za-z][_0-9A-Za-z]*`

Required: No

### fieldName

The resolver field name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: No

### kind

The resolver type.

- **UNIT**: A UNIT resolver type. A UNIT resolver is the default resolver type. You can use a UNIT resolver to run a GraphQL query against a single data source.
- **PIPELINE**: A PIPELINE resolver type. You can use a PIPELINE resolver to invoke a series of Function objects in a serial manner. You can use a pipeline resolver to run a GraphQL query against multiple data sources.

Type: String

Valid Values: UNIT | PIPELINE

Required: No

### maxBatchSize

The maximum batching size for a resolver.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2000.

Required: No

### metricsConfig

Enables or disables enhanced resolver metrics for specified resolvers. Note that metricsConfig won't be used unless the resolverLevelMetricsBehavior value is set to PER\_RESOLVER\_METRICS. If the resolverLevelMetricsBehavior is set to FULL\_REQUEST\_RESOLVER\_METRICS instead, metricsConfig will be ignored. However, you can still set its value.

metricsConfig can be ENABLED or DISABLED.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

## pipelineConfig

The PipelineConfig.

Type: [PipelineConfig object](#)

Required: No

## requestMappingTemplate

The request mapping template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: ^ . \*\$

Required: No

## resolverArn

The resolver Amazon Resource Name (ARN).

Type: String

Required: No

## responseMappingTemplate

The response mapping template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: ^ . \*\$

Required: No

## runtime

Describes a runtime used by an AWS AppSync pipeline resolver or AWS AppSync function.

Specifies the name and version of the runtime to use. Note that if a runtime is specified, code must also be specified.

Type: [AppSyncRuntime](#) object

Required: No

### syncConfig

The SyncConfig for a resolver attached to a versioned data source.

Type: [SyncConfig](#) object

Required: No

### typeName

The resolver type name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# SourceApiAssociation

Describes the configuration of a source API. A source API is a GraphQL API that is linked to a merged API. There can be multiple source APIs attached to each merged API. When linked to a merged API, the source API's schema, data sources, and resolvers will be combined with other linked source API data to form a new, singular API.

Source APIs can originate from your account or from other accounts via AWS Resource Access Manager. For more information about sharing resources from other accounts, see [What is AWS Resource Access Manager?](#) in the *AWS Resource Access Manager* guide.

## Contents

### associationArn

The Amazon Resource Name (ARN) of the source API association.

Type: String

Required: No

### associationId

The ID generated by the AppSync service for the source API association.

Type: String

Required: No

### description

The description field.

Type: String

Required: No

### lastSuccessfulMergeDate

The datetime value of the last successful merge of the source API association. The result will be in UTC format and your local time zone.

Type: Timestamp

Required: No

### **mergedApiArn**

The Amazon Resource Name (ARN) of the AppSync Merged API.

Type: String

Required: No

### **mergedApId**

The ID of the AppSync Merged API.

Type: String

Required: No

### **sourceApiArn**

The Amazon Resource Name (ARN) of the AppSync source API.

Type: String

Required: No

### **sourceApiAssociationConfig**

The SourceApiAssociationConfig object data.

Type: [SourceApiAssociationConfig](#) object

Required: No

### **sourceApiAssociationStatus**

The state of the source API association.

Type: String

Valid Values: MERGE\_SCHEDULED | MERGE\_FAILED | MERGE\_SUCCESS |  
MERGE\_IN\_PROGRESS | AUTO\_MERGE\_SCHEDULE\_FAILED | DELETION\_SCHEDULED |  
DELETION\_IN\_PROGRESS | DELETION\_FAILED

Required: No

## sourceApiAssociationStatusDetail

The detailed message related to the current state of the source API association.

Type: String

Required: No

## sourceApild

The ID of the AppSync source API.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# SourceApiAssociationConfig

Describes properties used to specify configurations related to a source API.

## Contents

### mergeType

The property that indicates which merging option is enabled in the source API association.

Valid merge types are MANUAL\_MERGE (default) and AUTO\_MERGE. Manual merges are the default behavior and require the user to trigger any changes from the source APIs to the merged API manually. Auto merges subscribe the merged API to the changes performed on the source APIs so that any change in the source APIs are also made to the merged API. Auto merges use MergedApiExecutionRoleArn to perform merge operations.

Type: String

Valid Values: MANUAL\_MERGE | AUTO\_MERGE

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# SourceApiAssociationSummary

Describes the ARNs and IDs of associations, Merged APIs, and source APIs.

## Contents

### associationArn

The Amazon Resource Name (ARN) of the source API association.

Type: String

Required: No

### associationId

The ID generated by the AppSync service for the source API association.

Type: String

Required: No

### description

The description field.

Type: String

Required: No

### mergedApiArn

The Amazon Resource Name (ARN) of the AppSync Merged API.

Type: String

Required: No

### mergedApId

The ID of the AppSync Merged API.

Type: String

Required: No

## sourceApiArn

The Amazon Resource Name (ARN) of the AppSync Source API.

Type: String

Required: No

## sourceApilId

The ID of the AppSync source API.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# SyncConfig

Describes a Sync configuration for a resolver.

Specifies which Conflict Detection strategy and Resolution strategy to use when the resolver is invoked.

## Contents

### **conflictDetection**

The Conflict Detection strategy to use.

- **VERSION**: Detect conflicts based on object versions for this resolver.
- **NONE**: Do not detect conflicts when invoking this resolver.

Type: String

Valid Values: VERSION | NONE

Required: No

### **conflictHandler**

The Conflict Resolution strategy to perform in the event of a conflict.

- **OPTIMISTIC\_CONCURRENCY**: Resolve conflicts by rejecting mutations when versions don't match the latest version at the server.
- **AUTOMERGE**: Resolve conflicts with the Automerge conflict resolution strategy.
- **LAMBDA**: Resolve conflicts with an AWS Lambda function supplied in the LambdaConflictHandlerConfig.

Type: String

Valid Values: OPTIMISTIC\_CONCURRENCY | LAMBDA | AUTOMERGE | NONE

Required: No

### **lambdaConflictHandlerConfig**

The LambdaConflictHandlerConfig when configuring LAMBDA as the Conflict Handler.

Type: [LambdaConflictHandlerConfig](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Type

Describes a type.

## Contents

### arn

The type Amazon Resource Name (ARN).

Type: String

Required: No

### definition

The type definition.

Type: String

Required: No

### description

The type description.

Type: String

Required: No

### format

The type format: SDL or JSON.

Type: String

Valid Values: SDL | JSON

Required: No

### name

The type name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65536.

Pattern: [\_A-Za-z][\_0-9A-Za-z]\*

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# UserPoolConfig

Describes an Amazon Cognito user pool configuration.

## Contents

### **awsRegion**

The AWS Region in which the user pool was created.

Type: String

Required: Yes

### **defaultAction**

The action that you want your GraphQL API to take when a request that uses Amazon Cognito user pool authentication doesn't match the Amazon Cognito user pool configuration.

Type: String

Valid Values: ALLOW | DENY

Required: Yes

### **userPoolId**

The user pool ID.

Type: String

Required: Yes

### **appIdClientRegex**

A regular expression for validating the incoming Amazon Cognito user pool app client ID. If this value isn't set, no filtering is applied.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

## Action

The action to be performed.

Type: string

Required: Yes

## Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

## X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

## X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4\_request").

The value is expressed in the following format: *access\_key/YYYYMMDD/region/service/aws4\_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

### X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

### X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

### X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

### X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

# Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

## **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 403

## **ExpiredTokenException**

The security token included in the request is expired

HTTP Status Code: 403

## **IncompleteSignature**

The request signature does not conform to AWS standards.

HTTP Status Code: 403

## **InternalFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## **MalformedHttpRequestException**

Problems with the request at the HTTP level, e.g. we can't decompress the body according to the decompression algorithm specified by the content-encoding.

HTTP Status Code: 400

## **NotAuthorized**

You do not have permission to perform this action.

HTTP Status Code: 401

## **OptInRequired**

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

### **RequestAbortedException**

Convenient exception that can be used when a request is aborted before a reply is sent back (e.g. client closed connection).

HTTP Status Code: 400

### **RequestEntityTooLargeException**

Problems with the request at the HTTP level. The request entity is too large.

HTTP Status Code: 413

### **RequestExpired**

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

### **RequestTimeoutException**

Problems with the request at the HTTP level. Reading the Request timed out.

HTTP Status Code: 408

### **ServiceUnavailable**

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

### **ThrottlingException**

The request was denied due to request throttling.

HTTP Status Code: 400

### **UnrecognizedClientException**

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

## **UnknownOperationException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 404

## **ValidationException**

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400