

User Guide

AWS Artifact



Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS Artifact: User Guide

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

| What is AWS Artifact? | . 1 |
|---|-----|
| Pricing | . 1 |
| Getting started | . 2 |
| Prerequisites | . 2 |
| Features | . 2 |
| Downloading reports | . 3 |
| Downloading a report | . 3 |
| Viewing attachments in PDF documents | . 4 |
| Securing your documents | . 5 |
| Troubleshooting | . 5 |
| Managing agreements | . 6 |
| Accepting account agreements | . 6 |
| Terminating account agreements | . 8 |
| Accepting organization agreements | . 8 |
| Terminating organization agreements | 10 |
| Offline agreements | 11 |
| Configuring notifications | 12 |
| Prerequisite | 12 |
| Creating a configuration | 13 |
| Editing a configuration | 14 |
| Deleting a configuration | 15 |
| Identity and access management | 16 |
| Granting user access | 16 |
| Step 1: Create an IAM policy | 17 |
| Step 2: Create an IAM group and attach the policy | 17 |
| Step 3: Create IAM users and add them to the group | 18 |
| Migrating to fine-grained permissions for AWS Artifact reports | 18 |
| Migrating reports to new permissions | 19 |
| Migrating to fine-grained permissions for AWS Artifact agreements | 23 |
| Migrating to new permissions 2 | 23 |
| LegacyToFineGrainedMapping | 45 |
| Example IAM policies in commercial AWS Regions | 47 |
| Example IAM policies in AWS GovCloud (US) Regions | |
| Using AWS managed policies | 76 |

| AWSArtifactReportsReadOnlyAccess | 77 |
|---|----|
| AWSArtifactAgreementsReadOnlyAccess | 78 |
| AWSArtifactAgreementsFullAccess | 80 |
| Policy updates | 84 |
| Using service-linked roles | 85 |
| Service-linked role permissions for AWS Artifact | 86 |
| Creating a service-linked role for AWS Artifact | 86 |
| Editing a service-linked role for AWS Artifact | 86 |
| Deleting a service-linked role for AWS Artifact | 87 |
| Supported Regions for AWS Artifact service-linked roles | 87 |
| Using IAM condition keys | 89 |
| CloudTrail logging | 92 |
| | 92 |
| AWS Artifact information in CloudTrail | 92 |
| Understanding AWS Artifact log file entries | 93 |
| Document history | 96 |
| | |

What is AWS Artifact?

AWS Artifact provides on-demand downloads of AWS security and compliance documents. For example, reports on compliance with International Organization for Standardization (ISO) standards and Payment Card Industry (PCI) Security Standards, and System and Organization Controls (SOC) reports. AWS Artifact also provides downloads of certifications from accreditation bodies that validate the implementation and operating effectiveness of AWS security controls.

With AWS Artifact, you can also download security and compliance documents for independent software vendors (ISVs) who sell their products on AWS Marketplace. For more information, see <u>AWS Marketplace Vendor Insights</u>.

Additionally, you can use AWS Artifact to review, accept, and track the status of your agreements with AWS for your AWS account and for multiple AWS accounts in your organization. For more information about agreements in AWS Artifact, see <u>Managing agreements in AWS Artifact</u>.

To demonstrate the security and compliance of the AWS infrastructure and services that you use, you can submit AWS Artifact documents to your auditors or regulators as *audit artifacts*. You can also use these audit artifacts as guidelines to evaluate your own cloud architecture and to assess the effectiveness of your company's internal controls. For more information about audit artifacts, see <u>AWS Artifact FAQs</u>.

🚯 Note

AWS customers are responsible for developing or obtaining documents that demonstrate the security and compliance of their companies. For more information, see <u>Shared</u> <u>Responsibility Model</u>.

Pricing

AWS provides AWS Artifact documents and agreements to you free of charge.

Getting started with AWS Artifact

To get started using AWS Artifact, try out its key features in the AWS Artifact console. In the console, you can download AWS security and compliance reports, download and accept legal agreements, and subscribe to notifications about AWS Artifact documents.

Prerequisites

To use the features of AWS Artifact, you must have an AWS account. For setup instructions, see <u>Set</u> <u>up a new AWS account</u> in the AWS Setup User Guide.

Features

For instructions on using the features of AWS Artifact, see the following topics:

- Downloading reports
- Managing agreements
- <u>Configuring notifications</u>

Downloading reports in AWS Artifact

You can download reports from the AWS Artifact console. When you download a report from AWS Artifact, the report is generated specifically for you, and every report has a unique watermark. For this reason, you should share the reports only with those you trust. Don't email the reports as attachments, and don't share them online. To share a report, use a secure sharing service such as Amazon WorkDocs. Some reports require you to accept the **Terms and conditions** before you can download them.

Contents

- Downloading a report
- Viewing attachments in PDF documents
- Securing your documents
- Troubleshooting

Downloading a report

To download a report, you must have the required permissions. For more information, see <u>Identity</u> and access management in AWS Artifact.

When you sign up for AWS Artifact, your account is automatically granted permissions to download some reports. If you are having trouble accessing AWS Artifact, follow the guidance on <u>AWS</u> <u>Artifact Service Authorization Reference</u> page.

To download a report

- 1. Open the AWS Artifact console at https://console.aws.amazon.com/artifact/.
- 2. On the AWS Artifact home page, choose **View reports**.

On the **Reports** page, on the **AWS reports** tab, you can access AWS reports (for example, SOC 1/2/3, PCI, C5, and so on). On the **Third-party reports** tab, you can access reports from independent software vendors (ISVs) who sell their products on AWS Marketplace.

3. (Optional) To find a report, enter a keyword in the search field. You can also perform targeted searches for reports based on individual columns, including report title, category, series, and description. For example, to find the Cloud Computing Compliance Controls Catalogue (C5)

report, you can search the **Title** column using "Title", the "contains" operator (:), and the term "C5" (**Title : C5**).

- 4. (Optional) For more information about a report, choose the title of the report to open its details page.
- 5. Select a report, and then choose **Download report**.
- 6. You might be prompted to accept terms and conditions (Accept terms to download report) for the specific report that you're downloading. We recommend that you read the terms and conditions closely. When you're finished reading, select I have read and agree to the terms, and then choose Accept terms and download report.
- 7. Open the downloaded file via a PDF viewer. Review the terms and conditions for acceptance and scroll down to find the audit report. Reports could have additional information embedded as attachments within the PDF document, so make sure to check for attachments within the PDF file for supporting documentation. For instructions on how to view attachments, see Viewing attachments in PDF documents.

Viewing attachments in PDF documents

We recommend the following applications that currently support viewing PDF attachments:

Adobe Acrobat Reader

Download the latest version of Adobe Acrobat Reader from the Adobe website at <u>https://get.adobe.com/reader/</u>.

For instructions on how to view PDF attachments in Acrobat Reader, see <u>Links and attachments in</u> <u>PDFs</u> on the Adobe Support website.

Firefox Browser

- Download the latest Firefox web browser from the Mozilla website at <u>https://</u> www.mozilla.org/en-US/firefox/new/.
- Open the PDF file in Firefox's built-in PDF viewer. For instructions, see <u>View PDF files in Firefox</u> or choose another viewer on the Mozilla Support website.
- 3. To view PDF attachments in Firefox's built-in PDF viewer, choose **Toggle Sidebar**, **Show Attachments**.

Securing your documents

AWS Artifact documents are confidential and should be kept secure at all times. AWS Artifact uses the AWS shared responsibility model for its documents. This means that AWS is responsible for keeping documents secure while they are in the AWS Cloud, but you are responsible for keeping them secure after you download them. AWS Artifact might require you to accept the **Terms and conditions** before you can download documents. Each document download has a unique, traceable watermark.

You are only permitted to share documents marked as confidential within your company, with your regulators, and with your auditors. You aren't permitted to share these documents with your customers or on your website. We strongly recommend that you use a secure document sharing service, such as Amazon WorkDocs, to share documents with others. Do not send the documents through email or upload them to a site that is not secure.

Troubleshooting

If you cannot download a document or receive an error message, see <u>Troubleshooting</u> in the AWS Artifact FAQ.

Managing agreements in AWS Artifact

You can use AWS Artifact to review and manage agreements for your AWS account or organization. For example, companies that are subject to the Health Insurance Portability and Accountability Act (HIPAA) typically require a Business Associate Addendum (BAA) agreement with AWS to ensure that protected health information (PHI) is appropriately safeguarded. In the AWS Artifact console, you can review and accept such agreements, and you can designate an AWS account that can legally process PHI.

If you use AWS Organizations, you can accept agreements, such as a BAA with AWS, on behalf of all AWS accounts in your organization. All existing and subsequent member accounts are automatically covered by the agreement and can legally process PHI.

You can also use AWS Artifact to confirm that your AWS account or organization has accepted an agreement, and to review the terms of an accepted agreement to understand your obligations. If your account or organization no longer needs to use an accepted agreement, then you can use AWS Artifact to terminate the agreement. If you terminate the agreement but later realize that you need it, then you can activate the agreement again.

Contents

- <u>Accepting agreements for your AWS account in AWS Artifact</u>
- Terminating agreements for your AWS account in AWS Artifact
- <u>Accepting agreements for your organization in AWS Artifact</u>
- Terminating agreements for your organization in AWS Artifact
- Offline agreements in AWS Artifact

Accepting agreements for your AWS account in AWS Artifact

You can use the AWS Artifact console to review and accept agreements with AWS for your AWS account.

🛕 Important

Before you accept an agreement, we recommend that you consult with your legal, privacy, and compliance team.

Required permissions

If you're an administrator of an account, then you can grant IAM users and federated users with the permissions to access and manage one or more of your agreements. By default, only users with administrative privileges can accept an agreement. To accept an agreement, IAM and federated users must have the required <u>permissions</u>.

For more information, see Identity and access management in AWS Artifact.

To accept an agreement with AWS

- 1. Open the AWS Artifact console at https://console.aws.amazon.com/artifact/.
- 2. On the AWS Artifact navigation pane, choose Agreements.
- 3. Choose the **Account agreements** tab.
- 4. Open the AWS Artifact console at https://console.aws.amazon.com/artifact/.
- 5. In the navigation pane, choose **Agreements**.
- 6. On the **Agreements** page, do either of the following:
 - To accept an agreement only for your account, choose the **Account agreements** tab.
 - To accept an agreement on behalf of your organization, choose the **Organization agreements** tab.
- 7. Select an agreement, and then choose **Download agreement**.

The Accept NDA to download report dialog box appears.

- 8. Before you can download the agreement that you selected, you must first accept the terms of the AWS Artifact Nondisclosure Agreement (AWS Artifact NDA).
 - a. In the Accept NDA to download report dialog box, review the AWS Artifact NDA.
 - b. (Optional) To print a copy of the AWS Artifact NDA (or to save it as a PDF), choose Print NDA.
 - c. Select I have read and agree to all the terms of the NDA.
 - d. To accept the AWS Artifact NDA and to download a PDF of the agreement that you selected, choose **Accept NDA and download**.
- 9. In a PDF viewer, review the agreement PDF that you downloaded.
- 10. In the AWS Artifact console, with the agreement selected, choose Accept agreement.
- 11. In the **Accept agreement** dialog box, do the following:

- a. Review the agreement.
- b. Select I agree to all of these terms and conditions.
- c. Choose Accept agreement.
- 12. Choose **Accept** to accept the agreement for your account.

Terminating agreements for your AWS account in AWS Artifact

If you used the AWS Artifact console to <u>accept an agreement for a single AWS account</u>, then you can use the console to terminate that agreement. Otherwise, see <u>Offline agreements in AWS</u> <u>Artifact</u>.

Required permissions

To terminate an agreement, IAM and federated users must have the required permissions.

For more information, see Identity and access management in AWS Artifact.

To terminate your online agreement with AWS

- 1. Open the AWS Artifact console at https://console.aws.amazon.com/artifact/.
- 2. On the AWS Artifact navigation pane, choose **Agreements**.
- 3. Choose the **Account agreements** tab.
- 4. Select the agreement and choose **Terminate agreement**.
- 5. Select all checkboxes to indicate that you agree to terminate the agreement.
- 6. Choose **Terminate**. When prompted for confirmation, choose **Terminate**.

Accepting agreements for your organization in AWS Artifact

If you're the owner of the management account of an AWS Organizations organization, then you can accept an agreement with AWS on behalf of all AWS accounts in your organization.

<u> Important</u>

Before you accept an agreement, we recommend that you consult with your legal, privacy, and compliance team.

AWS Organizations has two available feature sets: *consolidated billing features* and *all features*. To use AWS Artifact for your organization, the organization that you belong to must be enabled for <u>all features</u>. If your organization is configured only for consolidated billing, see <u>Enabling all features in your organization</u> in the AWS Organizations User Guide.

To accept or terminate organization agreements, you must be signed in to the management account with the correct AWS Artifact permissions. Users of member accounts that have organizations:DescribeOrganization permissions can view the organization agreements that are accepted on their behalf.

For more information, see <u>Managing accounts in an organization with AWS Organizations</u> in the *AWS Organizations User Guide*.

Required permissions

To accept an agreement, the owner of the management account must have the required <u>permissions</u>.

For more information, see Identity and access management in AWS Artifact.

To accept an agreement for an organization

- 1. Open the AWS Artifact console at https://console.aws.amazon.com/artifact/.
- 2. On the AWS Artifact dashboard, choose Agreements.
- 3. Choose the **Organization agreements** tab.
- 4. Open the AWS Artifact console at https://console.aws.amazon.com/artifact/.
- 5. In the navigation pane, choose **Agreements**.
- 6. On the **Agreements** page, do either of the following:
 - To accept an agreement only for your account, choose the **Account agreements** tab.
 - To accept an agreement on behalf of your organization, choose the **Organization agreements** tab.
- 7. Select an agreement, and then choose **Download agreement**.

The Accept NDA to download report dialog box appears.

- 8. Before you can download the agreement that you selected, you must first accept the terms of the AWS Artifact Nondisclosure Agreement (AWS Artifact NDA).
 - a. In the **Accept NDA to download report** dialog box, review the AWS Artifact NDA.

- b. (Optional) To print a copy of the AWS Artifact NDA (or to save it as a PDF), choose **Print NDA**.
- c. Select I have read and agree to all the terms of the NDA.
- d. To accept the AWS Artifact NDA and to download a PDF of the agreement that you selected, choose **Accept NDA and download**.
- 9. In a PDF viewer, review the agreement PDF that you downloaded.
- 10. In the AWS Artifact console, with the agreement selected, choose **Accept agreement**.
- 11. In the Accept agreement dialog box, do the following:
 - a. Review the agreement.
 - b. Select I agree to all of these terms and conditions.
 - c. Choose Accept agreement.
- 12. Choose **Accept** to accept the agreement for all existing and future accounts in your organization.

Terminating agreements for your organization in AWS Artifact

If you used the AWS Artifact console to <u>accept an agreement on behalf of all member accounts in</u> <u>an organization in AWS Organizations</u>, then you can use the console to terminate that agreement. Otherwise, see <u>Offline agreements in AWS Artifact</u>.

If a member account is removed from an organization, then that member account is longer covered by organization agreements. Before removing member accounts from an organization, a management account administrator should communicate this to member accounts so that they can put new agreements in place if necessary. You can view a list of active organization agreements in the AWS Artifact console on the **Agreements** page, under <u>Organization agreements</u>.

For more information about AWS Organizations, see <u>Managing accounts in an organization with</u> <u>AWS Organizations</u> in the AWS Organizations User Guide.

Required permissions

To terminate an agreement, the owner of the management account must have the required permissions.

For more information, see Identity and access management in AWS Artifact.

To terminate your online organization agreement with AWS

- 1. Open the AWS Artifact console at https://console.aws.amazon.com/artifact/.
- 2. On the AWS Artifact dashboard, choose **Agreements**.
- 3. Choose the **Organization agreements** tab.
- 4. Select the agreement and choose **Terminate agreement**.
- 5. Select all checkboxes to indicate that you agree to terminate the agreement.
- 6. Choose **Terminate**. When prompted for confirmation, choose **Terminate**.

Offline agreements in AWS Artifact

If you have an existing offline agreement, AWS Artifact displays the agreements that you accepted offline. For example, the console might display the **Offline Business Associate Addendum (BAA)** with an **Active** status. The active status indicates that the agreement was accepted. To terminate an offline agreement, see the termination guidelines and instructions that are included in your agreement.

For more information, see Identity and access management in AWS Artifact.

Configuring email notifications in AWS Artifact

🚯 Note

The content of this page is only applicable to commercial AWS <u>Regions</u>, and does not currently apply to AWS GovCloud (US) Regions.

You can use the AWS Artifact console to configure email notifications for updates on agreements and reports in AWS Artifact. AWS Artifact sends these email notifications using AWS User Notifications. To receive AWS Artifact email notifications, you must first select AWS User Notifications notification hubs in the User Notifications console. Then, in the AWS Artifact console, you can create a configuration for notification settings, in which you specify your notification recipients and which notifications they receive.

To configure AWS Artifact email notifications, you must have the required permissions for AWS Artifact and AWS User Notifications. For more information, see <u>Identity and access management in</u> <u>AWS Artifact</u>.

Contents

- Prerequisite: Select notification hubs in User Notifications
- <u>Creating a configuration for AWS Artifact notification settings</u>
- Editing a configuration for AWS Artifact notification settings
- Deleting a configuration for AWS Artifact notification settings

Prerequisite: Select notification hubs in User Notifications

Before you can receive AWS Artifact email notifications, you must first open the User Notifications console and select the notification hubs in the AWS Regions where you want to store your User Notifications data. Selecting notification hubs is required for AWS User Notifications, which AWS Artifact uses to send notifications.

To select notification hubs

1. Open the Notification hubs page of the AWS User Notifications console.

- Select the notification hubs in the AWS Regions where you want to store your AWS User Notifications resources. By default, your User Notifications data is stored in the US East (N. Virginia) Region. User Notifications replicates your notifications data across the other Regions that you select. For more information, see the <u>notification hubs documentation</u> in the AWS User Notifications User Guide.
- 3. Choose **Save and continue**.

Creating a configuration for AWS Artifact notification settings

1 Note

The content of this page is only applicable to commercial AWS <u>Regions</u>, and does not currently apply to AWS GovCloud (US) Regions.

After you <u>select your User Notifications notification hubs</u>, you can create a configuration for notification settings in the AWS Artifact console. In the configuration that you create, you specify the recipient email addresses that you want to receive AWS Artifact notifications. You also specify which updates those recipients should receive notifications about, such as updates for AWS Artifact agreements, and updates for all (or a subset of) AWS Artifact reports.

To create a configuration

- 1. Open the <u>Notification settings</u> page of the AWS Artifact console.
- 2. Choose Create configuration.
- 3. On the **Create configuration** page, do the following:
 - To receive notifications for agreements, under Agreements, keep Updates on AWS Agreements selected.
 - To receive notifications for reports, under **Reports**, keep **Updates on AWS Reports** selected.
 - a. To receive notifications for all reports, choose All reports.
 - b. To receive notifications only for reports under specific categories and series, choose **A subset of reports**. Then, select the categories and series that you're interested in.
 - Under **Configuration name**, enter a **Name** for your configuration.

- Under **Email**, for **Recipients**, enter a comma-separated list of email addresses that you want to receive AWS Artifact notification emails.
- (Optional) To add tags to the notification configuration, expand Tags, choose Add new tag, and then enter tags as key-value pairs. For more information about tagging User Notifications resources, see <u>Tagging your AWS User Notifications resources</u> in the AWS User Notifications User Guide.
- Choose Create configuration.

User Notifications sends a verification email to each of the recipient email addresses that you provided. To verify the email address, in the verification email, the recipient must choose **Verify email**. Only verified email addresses will receive AWS Artifact notifications.

Editing a configuration for AWS Artifact notification settings

🚯 Note

The content of this page is only applicable to commercial AWS <u>Regions</u>, and does not currently apply to AWS GovCloud (US) Regions.

After you <u>create a configuration</u> for AWS Artifact notification settings, you can edit the configuration at any time to change your notification settings. For example, to add or remove recipients, change what types of notifications they receive, and add or remove tags.

To edit a configuration

- 1. Open the Notification settings page of the AWS Artifact console.
- 2. Select the configuration that you want to edit.
- 3. Choose Edit.
- 4. Edit any of the configuration selections and fields. When you're done, choose **Save changes**.

If you've added new email addresses as notification recipients, then AWS User Notifications sends a verification email those email addresses. To verify the email address, in the verification email, the recipient must choose **Verify email**. Only verified email addresses will receive AWS Artifact notifications.

Deleting a configuration for AWS Artifact notification settings

i Note

The content of this page is only applicable to commercial AWS <u>Regions</u>, and does not currently apply to AWS GovCloud (US) Regions.

If you no longer need a <u>configuration that you created</u> for AWS Artifact notification settings, then you can delete the configuration in the AWS Artifact console.

To delete a configuration

- 1. Open the <u>Notification settings</u> page of the AWS Artifact console.
- 2. Select the configuration that you want to delete.
- 3. Choose Delete.
- 4. In the **Delete configuration** dialog box, choose **Delete**.

Identity and access management in AWS Artifact

When you sign up for AWS, you provide an email address and password that are associated with your AWS account. These are your *root credentials*, and they provide complete access to all of your AWS resources, including resources for AWS Artifact. However, we strongly recommend that you don't use the root account for everyday access. We also recommend that you don't share account credentials with others to give them complete access to your account.

Instead of signing in to your AWS account with root credentials or sharing your credentials with others, you should create a special user identity called an *IAM user* for yourself and for anyone who might need access to a document or agreement in AWS Artifact. With this approach, you can provide individual sign-in information for each user, and you can grant each user only the permissions that they need to work with specific documents. You can also grant multiple IAM users the same permissions by granting the permissions to an IAM group and adding the IAM users to the group.

If you already manage user identities outside AWS, you can use IAM *identity providers* instead of creating IAM users. For more information, see <u>Identity providers and federation</u> in the *IAM User Guide*.

Contents

- Granting user access to AWS Artifact
- Migrating reports to fine-grained permissions for AWS Artifact
- Migrating to fine-grained permissions for AWS Artifact agreements
- Example IAM policies for AWS Artifact in commercial AWS Regions
- Example IAM policies for AWS Artifact in AWS GovCloud (US) Regions
- Using AWS managed policies for AWS Artifact
- Using service-linked roles for AWS Artifact
- Using IAM condition keys for AWS Artifact reports

Granting user access to AWS Artifact

Complete the following steps to grant users permissions to AWS Artifact based on the level of access they need.

Tasks

- Step 1: Create an IAM policy
- Step 2: Create an IAM group and attach the policy
- Step 3: Create IAM users and add them to the group

Step 1: Create an IAM policy

As an IAM administrator, you can create a policy that grants permissions to AWS Artifact actions and resources.

To create an IAM policy

Use the following procedure to create an IAM policy that you can use to grant permissions to your IAM users and groups.

- 1. Open the IAM console at https://console.aws.amazon.com/iam/.
- 2. In the navigation pane, choose **Policies**.
- 3. Choose **Create policy**.
- 4. Choose the **JSON** tab.
- 5. Enter a policy document. You can create you own policy, or you can use one of the policies from Example IAM policies for AWS Artifact in commercial AWS Regions.
- 6. Choose **Review Policy**. The policy validator reports any syntax errors.
- 7. On the **Review policy** page, enter a unique name that helps you remember the purpose of the policy. You can also provide a description.
- 8. Choose **Create policy**.

Step 2: Create an IAM group and attach the policy

As an IAM administrator, you can create a group and attach the policy that you created to the group. You can add IAM users to the group at any time.

To create an IAM group and attach your policy

- 1. In the navigation pane, choose **Groups** and then choose **Create New Group**.
- 2. For **Group Name**, enter a name for your group and then choose **Next Step**.

- 3. In the search field, enter the name of the policy that you created. Select the check box for your policy and then choose **Next Step**.
- 4. Review the group name and policies. When you are ready, choose **Create Group**.

Step 3: Create IAM users and add them to the group

As an IAM administrator, you can add users to a group at any time. This grants the users the permissions granted to the group.

To create an IAM user and add the user to a group

- 1. In the navigation pane, choose **Users** and then choose **Add user**.
- 2. For **User name**, enter the names for one or more users.
- Select the check box next to AWS Management Console access. Configure an auto-generated or custom password. You can optionally select User must create a new password at next signin to require a password reset when the user first signs in.
- 4. Choose Next: Permissions.
- 5. Choose **Add user to group** and then select the group that you created.
- 6. Choose Next: Tags. You can optionally add tags to your users.
- 7. Choose Next: Review. When you are ready, choose Create user.

Migrating reports to fine-grained permissions for AWS Artifact

You can now use fine-grained permissions for AWS Artifact. Through these fine-grained permissions, you have granular control on providing access to features such as accepting terms and downloading reports.

To access reports through the fine-grained permissions, you can utilize the <u>AWSArtifactReportsReadOnlyAccess</u> Managed Policy or update your permissions as per the below recommendation.

🚺 Note

The IAM action artifact: Get was deprecated in the AWS partition on March 3, 2025 and in the AWS GovCloud (US) partition on July 1, 2025.

Migrating reports to new permissions

Migrate non-resource specific permissions

Replace your existing policy containing legacy permissions with a policy containing fine-grained permissions.

Legacy policy:

AWS

JSON

```
{
    "Version": "2012-10-17",
    "Statement": [{
        "Effect": "Allow",
        "Action": [
            "artifact:Get"
        ],
        "Resource": [
            "arn:aws:artifact:::report-package/*"
        ]
    }]
}
```

AWS GovCloud (US)

```
{
    "Version": "2012-10-17",
    "Statement": [{
        "Effect": "Allow",
        "Action": [
            "artifact:Get"
    ],
```

```
"Resource": [
    "arn:aws-us-gov:artifact:::report-package/*"
]
}]
}
```

New policy with fine-grained permissions:

JSON

```
{
    "Version": "2012-10-17",
    "Statement": [{
        "Effect": "Allow",
        "Action": [
            "artifact:ListReports",
            "artifact:GetReportMetadata",
            "artifact:GetReport",
            "artifact:GetTermForReport"
        ],
        "Resource": "*"
    }]
}
```

Migrate resource-specific permissions

Replace your existing policy containing legacy permissions with a policy containing fine-grained permissions. Report resource wildcard permissions have been replaced with <u>condition keys</u>.

Legacy policy:

AWS

```
{
    "Version": "2012-10-17",
    "Statement": [{
        "Effect": "Allow",
        "Action": [
            "artifact:Get"
        ],
        "Resource": [
            "arn:aws:artifact:::report-package/Certifications and
 Attestations/SOC/*",
            "arn:aws:artifact:::report-package/Certifications and
 Attestations/PCI/*",
            "arn:aws:artifact:::report-package/Certifications and
Attestations/ISO/*"
        ]
   }]
}
```

AWS GovCloud (US)

```
{
    "Version": "2012-10-17",
    "Statement": [{
        "Effect": "Allow",
        "Action": [
            "artifact:Get"
        ],
        "Resource": [
            "arn:aws-us-gov:artifact:::report-package/Certifications and
 Attestations/SOC/*",
            "arn:aws-us-gov:artifact:::report-package/Certifications and
Attestations/PCI/*",
            "arn:aws-us-gov:artifact:::report-package/Certifications and
 Attestations/ISO/*"
        1
   }]
}
```

New policy with fine-grained permissions and condition keys:

```
{
    "Version": "2012-10-17",
    "Statement": [{
            "Effect": "Allow",
            "Action": [
                "artifact:ListReports"
            ],
            "Resource": "*"
        },
        {
            "Effect": "Allow",
            "Action": [
                "artifact:GetReportMetadata",
                "artifact:GetReport",
                "artifact:GetTermForReport"
            ],
            "Resource": "*",
            "Condition": {
                "StringEquals": {
                     "artifact:ReportSeries": [
                         "SOC",
                         "PCI",
                         "ISO"
                    ],
                    "artifact:ReportCategory": [
                         "Certifications and Attestations"
                    1
                }
            }
        }
   ]
}
```

Migrating to fine-grained permissions for AWS Artifact agreements

AWS Artifact now enables customers to use fine-grained permissions for agreements. Through these fine-grained permissions, customers have granular control on providing access to features such as viewing and accepting non-disclosure agreements, as well as accepting and terminating agreements.

To access agreements through the fine-grained permissions, you can utilize the <u>AWSArtifactAgreementsReadOnlyAccess or AWSArtifactAgreementsFullAccess</u> managed policies or update your permissions as per the below recommendation.

🚯 Note

The IAM action artifact:DownloadAgreement was deprecated in the AWS partition on March 3, 2025 and in the AWS GovCloud (US) partition on July 1, 2025.

Migrating to new permissions

The legacy IAM action "DownloadAgreement" has been replaced by the "GetAgreement" action to download unaccepted agreements and by the "GetCustomerAgreement" action for downloading accepted agreements. Additionally, more granular actions have been introduced to control access for viewing and accepting non-disclosure agreements (NDAs). To take advantage of these granular actions and maintain the ability to view and execute agreements, users must replace their existing policy containing legacy permissions with a policy containing fine-grained permissions.

Migrate permissions to download agreement at account level

Legacy Policy:

AWS

```
{
   "Version": "2012-10-17",
   "Statement": [
    {
        "Effect": "Allow",
        "Action": [
        "artifact:DownloadAgreement"
     ],
        "Resource": [
        "arn:aws:artifact::*:customer-agreement/*",
        "arn:aws:artifact:::agreement/*"
     ]
    }
]
```

AWS GovCloud (US)

JSON

```
{
   "Version": "2012-10-17",
   "Statement": [
      {
        "Effect": "Allow",
        "Action": [
           "artifact:DownloadAgreement"
      ],
        "Resource": [
           "arn:aws-us-gov:artifact::*:customer-agreement/*",
           "arn:aws-us-gov:artifact:::agreement/*"
      ]
    }
]
```

New Policy with fine-grained permissions:

AWS

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "ListAgreementsActions",
      "Effect": "Allow",
      "Action": [
        "artifact:ListAgreements",
        "artifact:ListCustomerAgreements"
      ],
      "Resource": "*"
    },
    {
      "Sid": "GetAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetCustomerAgreement",
        "artifact:GetAgreement",
        "artifact:GetNdaForAgreement",
        "artifact:AcceptNdaForAgreement"
      ],
      "Resource": [
        "arn:aws:artifact::*:customer-agreement/*",
        "arn:aws:artifact:::agreement/*"
      ]
    }
  1
}
```

AWS GovCloud (US)

```
"Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "ListAgreementsActions",
      "Effect": "Allow",
      "Action": [
        "artifact:ListAgreements",
        "artifact:ListCustomerAgreements"
      ],
      "Resource": "*"
    },
    {
      "Sid": "GetAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetCustomerAgreement",
        "artifact:GetAgreement",
        "artifact:GetNdaForAgreement",
        "artifact:AcceptNdaForAgreement"
      ],
      "Resource": [
        "arn:aws-us-gov:artifact::*:customer-agreement/*",
        "arn:aws-us-gov:artifact:::agreement/*"
      ]
    }
  ]
}
```

Migrate non-resource specific permissions to download, accept and terminate agreements at account level

Legacy Policy:

AWS

```
{
    "Version": "2012-10-17",
```

```
"Statement": [
    {
        "Effect": "Allow",
        "Action": [
            "artifact:AcceptAgreement",
            "artifact:DownloadAgreement",
            "artifact:TerminateAgreement"
        ],
        "Resource": [
            "arn:aws:artifact::*:customer-agreement/*",
            "arn:aws:artifact:::agreement/*"
        ]
     }
]
```

AWS GovCloud (US)

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "artifact:AcceptAgreement",
        "artifact:DownloadAgreement",
        "artifact:TerminateAgreement"
      ],
      "Resource": [
        "arn:aws-us-gov:artifact::*:customer-agreement/*",
        "arn:aws-us-gov:artifact:::agreement/*"
      1
    }
  ]
}
```

New Policy with fine-grained permissions:

AWS

```
{
 "Version": "2012-10-17",
 "Statement": [
   {
        "Sid": "ListAgreementActions",
        "Effect": "Allow",
        "Action": [
            "artifact:ListAgreements",
            "artifact:ListCustomerAgreements"
        ],
        "Resource": "*"
      },
      {
        "Sid": "AWSAgreementActions",
        "Effect": "Allow",
        "Action": [
          "artifact:GetAgreement",
          "artifact:AcceptNdaForAgreement",
          "artifact:GetNdaForAgreement",
          "artifact:AcceptAgreement"
        ],
        "Resource": "arn:aws:artifact:::agreement/*"
      },
      {
        "Sid": "CustomerAgreementActions",
        "Effect": "Allow",
        "Action": [
            "artifact:GetCustomerAgreement",
            "artifact:TerminateAgreement"
        ],
        "Resource": "arn:aws:artifact::*:customer-agreement/*"
      }
    ]
}
```

AWS GovCloud (US)

```
{
 "Version": "2012-10-17",
 "Statement": [
   {
        "Sid": "ListAgreementActions",
        "Effect": "Allow",
        "Action": [
            "artifact:ListAgreements",
            "artifact:ListCustomerAgreements"
        ],
        "Resource": "*"
      },
      {
        "Sid": "AWSAgreementActions",
        "Effect": "Allow",
        "Action": [
          "artifact:GetAgreement",
          "artifact:AcceptNdaForAgreement",
          "artifact:GetNdaForAgreement",
          "artifact:AcceptAgreement"
        ],
        "Resource": "arn:aws-us-gov:artifact:::agreement/*"
      },
      {
        "Sid": "CustomerAgreementActions",
        "Effect": "Allow",
        "Action": [
            "artifact:GetCustomerAgreement",
            "artifact:TerminateAgreement"
        ],
        "Resource": "arn:aws-us-gov:artifact::*:customer-agreement/*"
      }
    1
}
```

Migrate non-resource specific permissions to download, accept and terminate agreements at Organization level

Legacy Policy:

AWS

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "artifact:AcceptAgreement",
        "artifact:DownloadAgreement",
        "artifact:TerminateAgreement"
      ],
      "Resource": [
        "arn:aws:artifact::*:customer-agreement/*",
        "arn:aws:artifact:::agreement/*"
      ]
    },
    {
      "Effect": "Allow",
      "Action": "iam:ListRoles",
      "Resource": "arn:aws:iam:::role/*"
    },
    {
      "Effect": "Allow",
      "Action": "iam:CreateServiceLinkedRole",
      "Resource": "arn:aws:iam:::role/aws-service-role/artifact.amazonaws.com/
AWSServiceRoleForArtifact"
    },
    {
      "Effect": "Allow",
      "Action": [
        "organizations:DescribeOrganization",
        "organizations:EnableAWSServiceAccess",
        "organizations:ListAccounts",
```

```
"organizations:ListAWSServiceAccessForOrganization"
],
    "Resource": "*"
  }
]
```

AWS GovCloud (US)

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "artifact:AcceptAgreement",
        "artifact:DownloadAgreement",
        "artifact:TerminateAgreement"
      ],
      "Resource": [
        "arn:aws-us-gov:artifact::*:customer-agreement/*",
        "arn:aws-us-gov:artifact:::agreement/*"
      ]
   },
    {
      "Effect": "Allow",
      "Action": "iam:ListRoles",
      "Resource": "arn:aws-us-gov:iam:::role/*"
   },
    {
      "Effect": "Allow",
      "Action": "iam:CreateServiceLinkedRole",
      "Resource": "arn:aws-us-gov:iam:::role/aws-service-role/
artifact.amazonaws.com/AWSServiceRoleForArtifact"
   },
    {
      "Effect": "Allow",
      "Action": [
```

```
"organizations:DescribeOrganization",
    "organizations:EnableAWSServiceAccess",
    "organizations:ListAccounts",
    "organizations:ListAWSServiceAccessForOrganization"
    ],
    "Resource": "*"
    }
]
```

New Policy with fine-grained permissions:

AWS

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "ListAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:ListAgreements",
        "artifact:ListCustomerAgreements"
      ],
      "Resource": "*"
    },
    {
      "Sid": "AWSAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetAgreement",
        "artifact:AcceptNdaForAgreement",
        "artifact:GetNdaForAgreement",
        "artifact:AcceptAgreement"
      ],
      "Resource": "arn:aws:artifact:::agreement/*"
    },
    {
```

```
"Sid": "CustomerAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetCustomerAgreement",
        "artifact:TerminateAgreement"
      1,
      "Resource": "arn:aws:artifact::*:customer-agreement/*"
    },
    {
      "Sid": "CreateServiceLinkedRoleForOrganizationsIntegration",
      "Effect": "Allow",
      "Action": [
        "iam:CreateServiceLinkedRole"
      ],
      "Resource": "arn:aws:iam::*:role/aws-service-role/
artifact.amazonaws.com/AWSServiceRoleForArtifact",
      "Condition": {
        "StringEquals": {
          "iam:AWSServiceName": [
            "artifact.amazonaws.com"
          1
        }
      }
    },
    {
      "Sid": "GetRoleToCheckForRoleExistence",
      "Effect": "Allow",
      "Action": [
        "iam:GetRole"
      ],
      "Resource": "arn:aws:iam::*:role/aws-service-role/
artifact.amazonaws.com/AWSServiceRoleForArtifact"
    },
    {
      "Sid": "EnableServiceTrust",
      "Effect": "Allow",
      "Action": [
        "organizations:EnableAWSServiceAccess",
        "organizations:ListAWSServiceAccessForOrganization",
        "organizations:DescribeOrganization"
      ],
      "Resource": "*"
    }
  1
```

User Guide

AWS GovCloud (US)

}

```
{
 "Version": "2012-10-17",
 "Statement": [
    {
      "Sid": "ListAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:ListAgreements",
        "artifact:ListCustomerAgreements"
      ],
      "Resource": "*"
   },
    {
      "Sid": "AWSAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetAgreement",
        "artifact:AcceptNdaForAgreement",
        "artifact:GetNdaForAgreement",
        "artifact:AcceptAgreement"
      ],
      "Resource": "arn:aws-us-gov:artifact:::agreement/*"
   },
    {
      "Sid": "CustomerAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetCustomerAgreement",
        "artifact:TerminateAgreement"
      ],
      "Resource": "arn:aws-us-gov:artifact::*:customer-agreement/*"
   },
    {
      "Sid": "CreateServiceLinkedRoleForOrganizationsIntegration",
```

```
"Effect": "Allow",
      "Action": [
        "iam:CreateServiceLinkedRole"
      ],
      "Resource": "arn:aws-us-gov:iam::*:role/aws-service-role/
artifact.amazonaws.com/AWSServiceRoleForArtifact",
      "Condition": {
        "StringEquals": {
          "iam:AWSServiceName": [
            "artifact.amazonaws.com"
          1
        }
      }
    },
    {
      "Sid": "GetRoleToCheckForRoleExistence",
      "Effect": "Allow",
      "Action": [
        "iam:GetRole"
      ],
      "Resource": "arn:aws-us-gov:iam::*:role/aws-service-role/
artifact.amazonaws.com/AWSServiceRoleForArtifact"
    },
    {
      "Sid": "EnableServiceTrust",
      "Effect": "Allow",
      "Action": [
        "organizations:EnableAWSServiceAccess",
        "organizations:ListAWSServiceAccessForOrganization",
        "organizations:DescribeOrganization"
      ],
      "Resource": "*"
    }
 ]
}
```

Migrate resource specific permissions to download, accept and terminate agreements at account level

Legacy Policy:

AWS

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "artifact:AcceptAgreement",
        "artifact:DownloadAgreement"
      ],
      "Resource": [
        "arn:aws:artifact:::agreement/AWS Business Associate Addendum"
      ]
    },
    {
      "Effect": "Allow",
      "Action": [
        "artifact:TerminateAgreement"
      ],
      "Resource": [
        "arn:aws:artifact::*:customer-agreement/*"
      1
    }
  ]
}
```

AWS GovCloud (US)

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Allow",
            "
```



New Policy with fine-grained permissions:

AWS



AWS GovCloud (US)

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "ListAgreementActions",
            "Effect": "Allow",
            "Action": [
               "artifact:ListAgreements",
               "artifact:ListCustomerAgreements"
        ],
        "Resource": "*"
     },
     {
        "Sid": "AWSAgreementActions",
        "Effect": "Allow",
        "Effect": "Allow",
        "
}
```



Migrate resource specific permissions to download, accept and terminate agreements at organization level

Legacy Policy:

AWS

```
{
    "Version": "2012-10-17",
    "Statement": [
      {
        "Effect": "Allow",
        "Action": [
        "artifact:AcceptAgreement",
        "artifact:DownloadAgreement",
        "artifact:TerminateAgreement"
```



AWS GovCloud (US)

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Allow",
            "
```

```
"Action": [
        "artifact:AcceptAgreement",
        "artifact:DownloadAgreement",
        "artifact:TerminateAgreement"
      ],
      "Resource": [
        "arn:aws-us-gov:artifact::*:customer-agreement/*",
        "arn:aws-us-gov:artifact:::agreement/AWS Organizations Business
 Associate Addendum"
      1
    },
    {
      "Effect": "Allow",
      "Action": "iam:ListRoles",
      "Resource": "arn:aws-us-gov:iam:::role/*"
    },
    {
      "Effect": "Allow",
      "Action": "iam:CreateServiceLinkedRole",
      "Resource": "arn:aws-us-gov:iam:::role/aws-service-role/
artifact.amazonaws.com/AWSServiceRoleForArtifact"
    },
    {
      "Effect": "Allow",
      "Action": [
        "organizations:DescribeOrganization",
        "organizations:EnableAWSServiceAccess",
        "organizations:ListAccounts",
        "organizations:ListAWSServiceAccessForOrganization"
      ],
      "Resource": "*"
    }
  ]
}
```

New Policy with fine-grained permissions:

AWS

```
{
  "Version": "2012-10-17",
 "Statement": [
    {
      "Sid": "ListAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:ListAgreements",
        "artifact:ListCustomerAgreements"
      ],
      "Resource": "*"
   },
    {
      "Sid": "AWSAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetAgreement",
        "artifact:AcceptNdaForAgreement",
        "artifact:GetNdaForAgreement",
        "artifact:AcceptAgreement"
      ],
      "Resource": "arn:aws:artifact:::agreement/agreement-y03aUwMAEorHtqjv"
   },
    {
      "Sid": "CustomerAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetCustomerAgreement",
        "artifact:TerminateAgreement"
      ],
      "Resource": "arn:aws:artifact::*:customer-agreement/*"
   },
    {
      "Sid": "CreateServiceLinkedRoleForOrganizationsIntegration",
      "Effect": "Allow",
      "Action": [
        "iam:CreateServiceLinkedRole"
      ],
```

```
"Resource": "arn:aws:iam::*:role/aws-service-role/
artifact.amazonaws.com/AWSServiceRoleForArtifact",
      "Condition": {
        "StringEquals": {
          "iam:AWSServiceName": [
            "artifact.amazonaws.com"
          ]
        }
      }
    },
    {
      "Sid": "GetRoleToCheckForRoleExistence",
      "Effect": "Allow",
      "Action": [
        "iam:GetRole"
      ],
      "Resource": "arn:aws:iam::*:role/aws-service-role/
artifact.amazonaws.com/AWSServiceRoleForArtifact"
    },
    {
      "Sid": "EnableServiceTrust",
      "Effect": "Allow",
      "Action": [
        "organizations:EnableAWSServiceAccess",
        "organizations:ListAWSServiceAccessForOrganization",
        "organizations:DescribeOrganization"
      ],
      "Resource": "*"
    }
  1
}
```

AWS GovCloud (US)

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
```

```
"Sid": "ListAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:ListAgreements",
        "artifact:ListCustomerAgreements"
      1,
      "Resource": "*"
    },
    {
      "Sid": "AWSAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetAgreement",
        "artifact:AcceptNdaForAgreement",
        "artifact:GetNdaForAgreement",
        "artifact:AcceptAgreement"
      ],
      "Resource": "arn:aws-us-gov:artifact:::agreement/agreement-
B47fK0ArVebC9XE1"
    },
    {
      "Sid": "CustomerAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetCustomerAgreement",
        "artifact:TerminateAgreement"
      ],
      "Resource": "arn:aws-us-gov:artifact::*:customer-agreement/*"
    },
    {
      "Sid": "CreateServiceLinkedRoleForOrganizationsIntegration",
      "Effect": "Allow",
      "Action": [
        "iam:CreateServiceLinkedRole"
      ],
      "Resource": "arn:aws-us-gov:iam::*:role/aws-service-role/
artifact.amazonaws.com/AWSServiceRoleForArtifact",
      "Condition": {
        "StringEquals": {
          "iam:AWSServiceName": [
            "artifact.amazonaws.com"
          1
        }
      }
```

```
},
    {
      "Sid": "GetRoleToCheckForRoleExistence",
      "Effect": "Allow",
      "Action": [
        "iam:GetRole"
      ],
      "Resource": "arn:aws-us-gov:iam::*:role/aws-service-role/
artifact.amazonaws.com/AWSServiceRoleForArtifact"
    },
    {
      "Sid": "EnableServiceTrust",
      "Effect": "Allow",
      "Action": [
        "organizations:EnableAWSServiceAccess",
        "organizations:ListAWSServiceAccessForOrganization",
        "organizations:DescribeOrganization"
      ],
      "Resource": "*"
    }
  1
}
```

Legacy to Fine-grained resource mapping for Agreements

Agreement ARN's were updated for fine-grained permissions. Any previous references to legacy agreement resources should be replaced with new ARN's. Below is the Agreement ARN mapping between legacy to fine-grained resources.

AWS

| Agreement Name | Artifact ARN for Legacy permissions | Artifact ARN for Fine-grai ned permissions |
|------------------------------------|---|---|
| AWS Business Associate Addendum | arn:aws:artifact:::agreemen t/AWS Business Associate Addendum | arn:aws:artifact:::agreement/ agreement-9c1kBcYznTkcpRI m |

AWS Artifact

| Agreement Name | Artifact ARN for Legacy permissions | Artifact ARN for Fine-grai ned permissions |
|---|--|---|
| AWS New Zealand Notifiable Data Breach Addendum | arn:aws:artifact:::agreement/ AWS New Zealand Notifiable Data Breach Addendum | arn:aws:artifact:::agreemen t/agreement-3YRq9r GUIu72r7Gt |
| AWS Australian Notifiable Data Breach Addendum | arn:aws:artifact:::agreemen t/AWS Australian Notifiable Data Breach Addendum | arn: aws: artifact::: agreemen t/agreement-sbLSDe 8 bitmAXNr9 |
| AWS SEC Rule 17a-4 Addendum | arn:aws:artifact:::agreemen t/AWS SEC Rule 17a-4 Addendum | arn:aws:artifact:::agreemen t/agreement-bexgr7 sjvXAW4Gxu |
| AWS SEC Rule 18a-6 Addendum | arn:aws:artifact:::agreemen t/AWS SEC Rule 18a-6 Addendum | arn:aws:artifact:::agreemen t/agreement-HZTdNw JuqOKLReXC |
| AWS Organizations Business Associate Addendum | arn:aws:artifact:::agreement/ AWS Organizations Business Associate Addendum | arn:aws:artifact:::agreemen t/agreement-y03aUw MAEorHtqjv |
| AWS Organizations Australia n Notifiable Data Breach Addendum | arn:aws:artifact:::agreement/ AWS Organizations Australia n Notifiable Data Breach Addendum | arn:aws:artifact:::agreemen t/agreement-YpDMFX TePE7kEg4b |
| AWS Organizations New Zealand Notifiable Data Breach Addendum | arn:aws:artifact:::agreemen t/AWS Organizations New Zealand Notifiable Data Breach Addendum | arn:aws:artifact:::agreement/ agreement-uojEjr3vOnvrhV5 2 |

AWS GovCloud (US)

| Agreement Name | Artifact ARN for Legacy permissions | Artifact ARN for Fine-grai ned permissions |
|---|---|--|
| AWS Business Associate Addendum | arn:aws-us-gov:artifact:::a greement/AWS Business Associate Addendum | arn:aws-us-gov:artifact:::a greement/agreement- Og8HCNyYwYNp8AR1 |
| AWS Australian Notifiable Data Breach Addendum | arn:aws-us-gov:artifact:::a greement/AWS Australia n Notifiable Data Breach Addendum | arn:aws-us-gov:artifact:::a greement/agreement- G1rBS2MGYjLiCCXy |
| AWS Organizations Business Associate Addendum | arn:aws-us-gov:artifact:::a greement/AWS Organizat ions Business Associate Addendum | arn:aws-us-gov:artifact:::a greement/agreement- B47fK0ArVebC9XE1 |
| AWS Organizations Australia n Notifiable Data Breach Addendum | arn:aws-us-gov:artifact:::a greement/AWS Organizat ions Australian Notifiable Data Breach Addendum | arn:aws-us-gov:artifact:::a greement/agreement- OsnlbilP8RB73Nw5 |

Example IAM policies for AWS Artifact in commercial AWS Regions

You can create permissions policies that grant permissions to IAM users. You can grant users access to AWS Artifact reports and the ability to accept and download agreements on behalf of either a single account or an organization.

The following example policies show permissions that you can assign to IAM users based on the level of access that they need.

These policies are applicable in commercial AWS <u>Regions</u>. For policies applicable to AWS GovCloud (US) Regions, see <u>Example IAM policies for AWS Artifact in AWS GovCloud (US) Regions</u>

• Example policies to manage AWS reports with fine-grained permissions

- Example policies to manage third-party reports
- Example policies to manage agreements
- Example policies to integrate with AWS Organizations
- Example policies to manage agreements for the management account
- Example policies to manage organizational agreements
- Example policies to manage notifications

Example Example policies to manage AWS reports through fine-grained permissions

🚺 Tip

You should consider using the <u>AWSArtifactReportsReadOnlyAccess managed policy</u> instead of defining your own policy.

The following policy grants permission to download all AWS reports through fine-grained permissions.

```
{
   "Version": "2012-10-17",
   "Statement": [
     {
        "Effect": "Allow",
        "Action": [
           "artifact:ListReports",
           "artifact:GetReportMetadata",
           "artifact:GetReport",
           "artifact:GetTermForReport"
        ],
        "Resource": "*"
     }
  ]
}
```

The following policy grants permission to download only the AWS SOC, PCI, and ISO reports through fine-grained permissions.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "artifact:ListReports"
      ],
      "Resource": "*"
    },
    {
      "Effect": "Allow",
      "Action": [
        "artifact:GetReportMetadata",
        "artifact:GetReport",
        "artifact:GetTermForReport"
      ],
      "Resource": "*",
      "Condition": {
        "StringEquals": {
          "artifact:ReportSeries": [
            "SOC",
            "PCI",
            "ISO"
          ],
          "artifact:ReportCategory": [
            "Certifications and Attestations"
          ]
        }
      }
    }
  ]
}
```

Example Example policies to manage third-party reports

🚺 Tip

You should consider using the <u>AWSArtifactReportsReadOnlyAccess managed policy</u> instead of defining your own policy.

Third-party reports are denoted by the IAM resource report.

The following policy grants permission to all third-party report functionality.

JSON

```
{
   "Version": "2012-10-17",
   "Statement": [
      {
        "Effect": "Allow",
        "Action": [
           "artifact:ListReports",
           "artifact:GetReportMetadata",
           "artifact:GetReport",
           "artifact:GetTermForReport"
        ],
        "Resource": "*"
      }
   ]
}
```

The following policy grants permission to download third-party reports.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Allow",
            "Action": [
```

```
"artifact:GetReport",
    "artifact:GetTermForReport"
],
    "Resource": "*"
}
]
}
```

The following policy grants permission to list third-party reports.

JSON

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Allow",
            "Action": [
               "artifact:ListReport"
        ],
        "Resource": "*"
        }
   ]
}
```

The following policy grants permission to view a third-party report's details for all versions.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
          "Effect": "Allow",
          "Action": [
          "artifact:GetReportMetadata"
        ],
        "Resource": [
          "arn:aws:artifact:us-east-1::report/report-jRVRFP8HxUN5zpPh:*"
```

The following policy grants permission to view a third-party report's details for a specific version.

JSON

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
          "Effect": "Allow",
          "Action": [
             "artifact:GetReportMetadata"
        ],
        "Resource": [
             "arn:aws:artifact:us-east-1::report/report-jRVRFP8HxUN5zpPh:1"
        ]
        }
    ]
}
```

🚺 Tip

You should consider using the <u>AWSArtifactAgreementsReadOnlyAccess or</u> <u>AWSArtifactAgreementsFullAccess managed policy</u> instead of defining your own policy.

Example Example policies to manage agreements

The following policy grants permission to download all agreements.

```
{
    "Version": "2012-10-17",
```

```
"Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "artifact:ListAgreements",
        "artifact:ListCustomerAgreements"
      ],
      "Resource": [
        "*"
     ]
    },
    {
      "Sid": "AWSAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetAgreement",
        "artifact:AcceptNdaForAgreement",
        "artifact:GetNdaForAgreement"
      ],
      "Resource": "arn:aws:artifact:::agreement/*"
    },
    {
      "Sid": "CustomerAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetCustomerAgreement"
      ],
      "Resource": "arn:aws:artifact::*:customer-agreement/*"
    }
  ]
}
```

The following policy grants permission to accept all agreements.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Allow",
            "Action": [
```

```
"artifact:ListAgreements"
      ],
      "Resource": [
        "*"
      ]
    },
    {
      "Sid": "AWSAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetAgreement",
        "artifact:AcceptNdaForAgreement",
        "artifact:GetNdaForAgreement",
        "artifact:AcceptAgreement"
      ],
      "Resource": "arn:aws:artifact:::agreement/*"
    }
 ]
}
```

The following policy grants permission to terminate all agreements.

```
{
 "Version": "2012-10-17",
 "Statement": [
    {
     "Sid": "ListAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:ListAgreements",
        "artifact:ListCustomerAgreements"
     ],
      "Resource": "*"
    },
    {
     "Sid": "CustomerAgreementActions",
     "Effect": "Allow",
      "Action": [
        "artifact:GetCustomerAgreement",
```

```
"artifact:TerminateAgreement"
],
"Resource": "arn:aws:artifact::*:customer-agreement/*"
}
]
```

The following policy grants permissions to view and execute account level agreements.

```
{
 "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "ListAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:ListAgreements",
        "artifact:ListCustomerAgreements"
     ],
      "Resource": "*"
   },
    {
      "Sid": "AWSAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetAgreement",
        "artifact:AcceptNdaForAgreement",
        "artifact:GetNdaForAgreement",
        "artifact:AcceptAgreement"
     ],
      "Resource": "arn:aws:artifact:::agreement/*"
   },
    {
      "Sid": "CustomerAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetCustomerAgreement",
        "artifact:TerminateAgreement"
      ],
```

```
"Resource": "arn:aws:artifact::*:customer-agreement/*"
}
```

Example Example policies to integrate with AWS Organizations

The following policy grants permission to create the IAM role that AWS Artifact uses to integrate with AWS Organizations. Your organization's management account must have these permissions to get started with organizational agreements.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "CreateServiceLinkedRoleForOrganizationsIntegration",
      "Effect": "Allow",
      "Action": [
        "iam:CreateServiceLinkedRole",
        "iam:GetRole"
      ],
      "Resource": "arn:aws:iam::*:role/aws-service-role/artifact.amazonaws.com/
AWSServiceRoleForArtifact",
      "Condition": {
        "StringEquals": {
          "iam:AWSServiceName": [
            "artifact.amazonaws.com"
          1
        }
      }
    }
  1
}
```

The following policy grants permission to grant AWS Artifact the permissions to use AWS Organizations. Your organization's management account must have these permissions to get started with organizational agreements.

JSON

```
{
   "Version": "2012-10-17",
   "Statement": [
    {
        "Effect": "Allow",
        "Action": [
           "organizations:EnableAWSServiceAccess",
           "organizations:DescribeOrganization",
           "organizations:ListAWSServiceAccessForOrganization"
        ],
        "Resource": "*"
    }
]
```

Example Example policies to manage agreements for the management account

The following policy grants permissions to manage agreements for the management account.

```
{
 "Version": "2012-10-17",
 "Statement": [
    {
      "Sid": "ListAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:ListAgreements",
        "artifact:ListCustomerAgreements"
     ],
      "Resource": "*"
    },
    {
      "Sid": "AWSAgreementActions",
     "Effect": "Allow",
      "Action": [
        "artifact:GetAgreement",
```

```
"artifact:AcceptNdaForAgreement",
        "artifact:GetNdaForAgreement",
        "artifact:AcceptAgreement"
      ],
      "Resource": "arn:aws:artifact:::agreement/*"
    },
    {
      "Sid": "CustomerAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetCustomerAgreement",
        "artifact:TerminateAgreement"
      ],
      "Resource": "arn:aws:artifact::*:customer-agreement/*"
    },
    {
      "Sid": "CreateServiceLinkedRoleForOrganizationsIntegration",
      "Effect": "Allow",
      "Action": [
        "iam:CreateServiceLinkedRole",
        "iam:GetRole"
      ],
      "Resource": "arn:aws:iam::*:role/aws-service-role/artifact.amazonaws.com/
AWSServiceRoleForArtifact",
      "Condition": {
        "StringEquals": {
          "iam:AWSServiceName": [
            "artifact.amazonaws.com"
          1
        }
      }
    },
    {
      "Sid": "EnableServiceTrust",
      "Effect": "Allow",
      "Action": [
        "organizations:EnableAWSServiceAccess",
        "organizations:ListAWSServiceAccessForOrganization",
        "organizations:DescribeOrganization"
      ],
      "Resource": "*"
    }
  1
```

}

Example Example policies to manage organizational agreements

The following policy grants permissions to manage organizational agreements. Another user with the required permissions must set up the organizational agreements.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "ListAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:ListAgreements",
        "artifact:ListCustomerAgreements"
     ],
      "Resource": "*"
   },
    {
      "Sid": "AWSAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetAgreement",
        "artifact:AcceptNdaForAgreement",
        "artifact:GetNdaForAgreement",
        "artifact:AcceptAgreement"
     ],
      "Resource": "arn:aws:artifact:::agreement/*"
   },
    {
      "Sid": "CustomerAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetCustomerAgreement",
        "artifact:TerminateAgreement"
     ],
      "Resource": "arn:aws:artifact::*:customer-agreement/*"
    },
```

```
{
    "Effect": "Allow",
    "Action": [
        "organizations:DescribeOrganization"
    ],
    "Resource": "*"
    }
 ]
}
```

The following policy grants permissions to view organizational agreements.

```
{
 "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "ListAgreementActions",
     "Effect": "Allow",
     "Action": [
        "artifact:ListAgreements",
        "artifact:ListCustomerAgreements"
     ],
     "Resource": "*"
   },
    {
      "Sid": "AWSAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetAgreement",
        "artifact:AcceptNdaForAgreement",
        "artifact:GetNdaForAgreement"
     ],
      "Resource": "arn:aws:artifact:::agreement/*"
    },
    {
     "Sid": "CustomerAgreementActions",
     "Effect": "Allow",
      "Action": [
        "artifact:GetCustomerAgreement"
```

```
],
    "Resource": "arn:aws:artifact::*:customer-agreement/*"
},
    {
        "Effect": "Allow",
        "Action": [
            "organizations:DescribeOrganization"
        ],
        "Resource": "*"
    }
]
```

Example Example policies to manage notifications

The following policy grants complete permissions to use AWS Artifact notifications.

```
{
 "Version": "2012-10-17",
  "Statement": [
   {
      "Effect": "Allow",
      "Action": [
        "artifact:GetAccountSettings",
        "artifact:PutAccountSettings",
        "notifications:AssociateChannel",
        "notifications:CreateEventRule",
        "notifications:CreateNotificationConfiguration",
        "notifications:DeleteEventRule",
        "notifications:DeleteNotificationConfiguration",
        "notifications:DisassociateChannel",
        "notifications:GetEventRule",
        "notifications:GetNotificationConfiguration",
        "notifications:ListChannels",
        "notifications:ListEventRules",
        "notifications:ListNotificationConfigurations",
        "notifications:ListNotificationHubs",
        "notifications:ListTagsForResource",
        "notifications:TagResource",
```

"notifications:UntagResource", "notifications:UpdateEventRule", "notifications:UpdateNotificationConfiguration", "notifications-contacts:CreateEmailContact", "notifications-contacts:DeleteEmailContact", "notifications-contacts:GetEmailContacts", "notifications-contacts:ListEmailContacts", "notifications-contacts:SendActivationCode"], "Resource": ["*"] }]

The following policy grants permission to list all configurations.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "artifact:GetAccountSettings",
        "notifications:ListChannels",
        "notifications:ListEventRules",
        "notifications:ListNotificationConfigurations",
        "notifications:ListNotificationHubs",
        "notifications-contacts:GetEmailContact"
      ],
      "Resource": [
        "*"
      1
    }
  ]
}
```

The following policy grants permission to create a configuration.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "artifact:GetAccountSettings",
        "artifact:PutAccountSettings",
        "notifications-contacts:CreateEmailContact",
        "notifications-contacts:SendActivationCode",
        "notifications:AssociateChannel",
        "notifications:CreateEventRule",
        "notifications:CreateNotificationConfiguration",
        "notifications:ListEventRules",
        "notifications:ListNotificationHubs",
        "notifications:TagResource",
        "notifications-contacts:ListEmailContacts"
      ],
      "Resource": [
        "*"
      1
    }
  ]
}
```

The following policy grants permission to edit a configuration.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
         "Effect": "Allow",
         "Action": [
         "artifact:GetAccountSettings",
         "artifact:PutAccountSettings",
         "ar
```

"notifications:AssociateChannel", "notifications:DisassociateChannel", "notifications:GetNotificationConfiguration", "notifications:ListChannels", "notifications:ListEventRules", "notifications:ListTagsForResource", "notifications:TagResource", "notifications:UntagResource", "notifications:UpdateEventRule", "notifications:UpdateNotificationConfiguration", "notifications-contacts:GetEmailContact", "notifications-contacts:ListEmailContacts"], "Resource": ["*" 1 } 1 }

The following policy grants permission to delete a configuration.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Allow",
            "Action": [
            "notifications:DeleteNotificationConfiguration",
            "notifications:ListEventRules"
        ],
        "Resource": [
            "*"
        ]
      }
   ]
}
```

The following policy grants permission to view details of a configuration.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "notifications:GetNotificationConfiguration",
        "notifications:ListChannels",
        "notifications:ListEventRules",
        "notifications:ListTagsForResource",
        "notifications-contacts:GetEmailContact"
      ],
      "Resource": [
        "*"
      ]
    }
  ]
}
```

The following policy grants permission to register or deregister notification hubs.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Allow",
            "Action": [
               "notifications:DeregisterNotificationHub",
               "notifications:RegisterNotificationHub"
        ],
        "Resource": [
            "*"
        ]
      }
    ]
```

}

Example IAM policies for AWS Artifact in AWS GovCloud (US) Regions

These policies are ONLY applicable in AWS GovCloud (US) Regions. For policies applicable to commercial AWS Regions, see Example IAM policies for AWS Artifact in commercial AWS Regions

You can create permissions policies that grant permissions to IAM users. You can grant users access to AWS Artifact reports and the ability to accept and download agreements on behalf of either a single account or an organization.

The following example policies show permissions that you can assign to IAM users based on the level of access that they need.

- Example policies to manage AWS reports
- Example policies to manage agreements
- Example policies to integrate with AWS Organizations
- Example policies to manage agreements for the management account
- Example policies to manage organizational agreements

Example Example policies to manage reports

The following policy grants permission to download all reports.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
         "Effect": "Allow",
         "Action": [
         "artifact:ListReports",
         "artifact:GetReportMetadata",
         "artifact:GetReport",
         "artifact:GetReport",
```

```
"artifact:GetTermForReport"
],
    "Resource": "*"
}
]
```

The following policy grants permission to download only the SOC, PCI, and ISO reports.

```
{
 "Version": "2012-10-17",
 "Statement": [
    {
     "Effect": "Allow",
     "Action": [
        "artifact:ListReports"
     ],
      "Resource": "*"
   },
    {
     "Effect": "Allow",
     "Action": [
        "artifact:GetReportMetadata",
        "artifact:GetReport",
        "artifact:GetTermForReport"
     ],
      "Resource": "*",
      "Condition": {
        "StringEquals": {
          "artifact:ReportSeries": [
            "SOC",
            "PCI",
            "ISO"
          ],
          "artifact:ReportCategory": [
            "Certifications and Attestations"
          1
        }
     }
    }
```

} }

The following policy grants permission to download all agreements. IAM users must also have this permission to accept agreements.

```
{
  "Version": "2012-10-17",
 "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "artifact:ListAgreements",
        "artifact:ListCustomerAgreements"
     ],
      "Resource": [
        "*"
     1
    },
    {
      "Sid": "AWSAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetAgreement",
        "artifact:AcceptNdaForAgreement",
        "artifact:GetNdaForAgreement"
     ],
      "Resource": "arn:aws-us-gov:artifact:::agreement/*"
   },
    {
      "Sid": "CustomerAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetCustomerAgreement"
     ],
      "Resource": "arn:aws-us-gov:artifact::*:customer-agreement/*"
    }
```

] }

The following policy grants permission to accept all agreement.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "artifact:ListAgreements"
      ],
      "Resource": [
        "*"
      ]
    },
    {
      "Sid": "AWSAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetAgreement",
        "artifact:AcceptNdaForAgreement",
        "artifact:GetNdaForAgreement",
        "artifact:AcceptAgreement"
      ],
      "Resource": "arn:aws-us-gov:artifact:::agreement/*"
    }
  ]
}
```

The following policy grants permission to terminate all agreement.

```
{
    "Version": "2012-10-17",
```

```
"Statement": [
    {
      "Sid": "ListAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:ListAgreements",
        "artifact:ListCustomerAgreements"
      ],
      "Resource": "*"
    },
    {
      "Sid": "CustomerAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetCustomerAgreement",
        "artifact:TerminateAgreement"
      ],
      "Resource": "arn:aws-us-gov:artifact::*:customer-agreement/*"
    }
  ]
}
```

The following policy grants permissions to view and execute account level agreements.

```
{
 "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "ListAgreementActions",
      "Effect": "Allow",
     "Action": [
        "artifact:ListAgreements",
        "artifact:ListCustomerAgreements"
     ],
      "Resource": "*"
   },
    {
      "Sid": "AWSAgreementActions",
      "Effect": "Allow",
      "Action": [
```



Example Example policies to integrate with AWS Organizations

The following policy grants permission to create the IAM role that AWS Artifact uses to integrate with AWS Organizations. Your organization's management account must have these permissions to get started with organizational agreements.

```
{
    "Version": "2012-10-17",
    "Statement": [
    {
        "Sid": "CreateServiceLinkedRoleForOrganizationsIntegration",
        "Effect": "Allow",
        "Action": [
            "iam:CreateServiceLinkedRole",
            "iam:GetRole"
        ],
        "Resource": "arn:aws-us-gov:iam::*:role/aws-service-role/
artifact.amazonaws.com/AWSServiceRoleForArtifact",
        "Condition": {
            "StringEquals": {
```

```
"iam:AWSServiceName": [
    "artifact.amazonaws.com"
    ]
    }
}
```

The following policy grants permission to grant AWS Artifact the permissions to use AWS Organizations. Your organization's management account must have these permissions to get started with organizational agreements.

JSON

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
          "Effect": "Allow",
          "Action": [
          "organizations:EnableAWSServiceAccess",
          "organizations:DescribeOrganization",
          "organizations:ListAWSServiceAccessForOrganization"
        ],
        "Resource": "*"
        }
   ]
}
```

Example Example policies to manage agreements for the management account

The following policy grants permissions to manage agreements for the management account.

```
{
    "Version": "2012-10-17",
    "Statement": [
```

```
{
      "Sid": "ListAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:ListAgreements",
        "artifact:ListCustomerAgreements"
      ],
      "Resource": "*"
    },
    {
      "Sid": "AWSAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetAgreement",
        "artifact:AcceptNdaForAgreement",
        "artifact:GetNdaForAgreement",
        "artifact:AcceptAgreement"
      ],
      "Resource": "arn:aws-us-gov:artifact:::agreement/*"
    },
    {
      "Sid": "CustomerAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetCustomerAgreement",
        "artifact:TerminateAgreement"
      ],
      "Resource": "arn:aws-us-gov:artifact::*:customer-agreement/*"
    },
    {
      "Sid": "CreateServiceLinkedRoleForOrganizationsIntegration",
      "Effect": "Allow",
      "Action": [
        "iam:CreateServiceLinkedRole",
        "iam:GetRole"
      ],
      "Resource": "arn:aws-us-gov:iam::*:role/aws-service-role/
artifact.amazonaws.com/AWSServiceRoleForArtifact",
      "Condition": {
        "StringEquals": {
          "iam:AWSServiceName": [
            "artifact.amazonaws.com"
          ]
        }
```

```
}
},
{
    Sid": "EnableServiceTrust",
    "Effect": "Allow",
    "Action": [
        "organizations:EnableAWSServiceAccess",
        "organizations:ListAWSServiceAccessForOrganization",
        "organizations:DescribeOrganization"
    ],
    "Resource": "*"
}
```

Example Example policies to manage organizational agreements

The following policy grants permissions to manage organizational agreements. Another user with the required permissions must set up the organizational agreements.

```
{
 "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "ListAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:ListAgreements",
        "artifact:ListCustomerAgreements"
     ],
      "Resource": "*"
   },
    {
      "Sid": "AWSAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetAgreement",
        "artifact:AcceptNdaForAgreement",
        "artifact:GetNdaForAgreement",
```

```
"artifact:AcceptAgreement"
      ],
      "Resource": "arn:aws-us-gov:artifact:::agreement/*"
    },
    {
      "Sid": "CustomerAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetCustomerAgreement",
        "artifact:TerminateAgreement"
      ],
      "Resource": "arn:aws-us-gov:artifact::*:customer-agreement/*"
    },
    {
      "Effect": "Allow",
      "Action": [
        "organizations:DescribeOrganization"
      ],
      "Resource": "*"
    }
  ]
}
```

The following policy grants permissions to view organizational agreements.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "ListAgreementActions",
            "Effect": "Allow",
            "Action": [
               "artifact:ListAgreements",
               "artifact:ListCustomerAgreements"
        ],
        "Resource": "*"
     },
     {
        Sid": "AWSAgreementActions",
        "Effect": "Allow",
        "Effect": "Allow",
        "
}
```



Using AWS managed policies for AWS Artifact

An AWS managed policy is a standalone policy that is created and administered by AWS. AWS managed policies are designed to provide permissions for many common use cases so that you can start assigning permissions to users, groups, and roles.

Keep in mind that AWS managed policies might not grant least-privilege permissions for your specific use cases because they're available for all AWS customers to use. We recommend that you reduce permissions further by defining <u>customer managed policies</u> that are specific to your use cases.

You cannot change the permissions defined in AWS managed policies. If AWS updates the permissions defined in an AWS managed policy, the update affects all principal identities (users, groups, and roles) that the policy is attached to. AWS is most likely to update an AWS managed

policy when a new AWS service is launched or new API operations become available for existing services.

For more information, see <u>AWS managed policies</u> in the *IAM User Guide*.

AWS managed policy: AWSArtifactReportsReadOnlyAccess

You can attach the AWSArtifactReportsReadOnlyAccess policy to your IAM identities.

This policy grants *read-only* permissions that allow listing, viewing, and downloading reports.

Permissions details

This policy includes the following permissions.

• artifact – Allows principals to list, view, and download reports from AWS Artifact.

```
{
   "Version": "2012-10-17",
   "Statement": [
     {
        "Effect": "Allow",
        "Action": [
           "artifact:GetReport",
           "artifact:GetReportMetadata",
           "artifact:GetTermForReport",
           "artifact:ListReports"
        ],
        "Resource": "*"
     }
  ]
}
```

AWS managed policy: AWSArtifactAgreementsReadOnlyAccess

You can attach the AWSArtifactAgreementsReadOnlyAccess policy to your IAM identities.

This policy grants *read-only* access to list the AWS Artifact service agreements and to download the accepted agreements. It also includes permissions to list as well as describe the organization details. Additionally, the policy provides the ability to check if the required service-linked role exists.

Permissions details

This policy includes the following permissions.

- artifact Allows principals to list all the agreements and to view accepted agreements from AWS Artifact.
- IAM Allows principals to check if the service linked role exists using GetRole.
- organization Allows principals to describe organization and to list service access for organization.

AWS

```
{
   "Version": "2012-10-17",
   "Statement": [
    {
        "Sid": "ListAgreementsActions",
        "Effect": "Allow",
        "Action": [
            "artifact:ListAgreements",
            "artifact:ListCustomerAgreements"
        ],
        "Resource": "*"
    },
    {
        "Sid": "GetCustomerAgreementActions",
        "Effect": "Allow",
    }
}
```

```
"Action": [
        "artifact:GetCustomerAgreement"
      ],
      "Resource": "arn:aws:artifact::*:customer-agreement/*"
    },
    {
      "Sid": "AWSOrganizationActions",
      "Effect": "Allow",
      "Action": [
        "organizations:ListAWSServiceAccessForOrganization",
        "organizations:DescribeOrganization"
      ],
      "Resource": "*"
    },
    {
      "Sid": "GetRole",
      "Effect": "Allow",
      "Action": [
        "iam:GetRole"
      ],
      "Resource": "arn:aws:iam::*:role/aws-service-role/
artifact.amazonaws.com/AWSServiceRoleForArtifact"
    }
 ]
}
```

AWS GovCloud (US)

```
{
    "Version": "2012-10-17",
    "Statement": [
      {
        "Sid": "ListAgreementsActions",
        "Effect": "Allow",
        "Action": [
        "artifact:ListAgreements",
        "artifact:ListCustomerAgreements"
     ],
```

```
"Resource": "*"
    },
    {
      "Sid": "GetCustomerAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetCustomerAgreement"
      ],
      "Resource": "arn:aws-us-gov:artifact::*:customer-agreement/*"
   },
    {
      "Sid": "AWSOrganizationActions",
      "Effect": "Allow",
      "Action": [
        "organizations:ListAWSServiceAccessForOrganization",
        "organizations:DescribeOrganization"
      ],
      "Resource": "*"
   },
    {
      "Sid": "GetRole",
      "Effect": "Allow",
      "Action": [
        "iam:GetRole"
      ],
      "Resource": "arn:aws-us-gov:iam::*:role/aws-service-role/
artifact.amazonaws.com/AWSServiceRoleForArtifact"
    }
 1
}
```

AWS managed policy: AWSArtifactAgreementsFullAccess

You can attach the AWSArtifactAgreementsFullAccess policy to your IAM identities.

This policy grants *full* permissions to list, download, accept, and terminate AWS Artifact agreements. It also includes permissions to list and enable AWS service access in the Organization service, as well as describe the organization details. Additionally, the policy provides the ability to check if the required service-linked role exists and creates one if it doesn't.

Permissions details

This policy includes the following permissions.

- artifact Allows principals to list, download, accept, and terminate the agreements from AWS Artifact.
- IAM Allows principals to create service linked role and to check if the service linked role exists using GetRole.
- organization Allows principals to describe organization and to list/enable service access for organization.

AWS

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "ListAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:ListAgreements",
        "artifact:ListCustomerAgreements"
      ],
      "Resource": "*"
    },
    {
      "Sid": "AWSAgreementActions",
      "Effect": "Allow",
      "Action": [
        "artifact:GetAgreement",
        "artifact:AcceptNdaForAgreement",
        "artifact:GetNdaForAgreement",
        "artifact:AcceptAgreement"
      ],
      "Resource": "arn:aws:artifact:::agreement/*"
    },
    {
      "Sid": "CustomerAgreementActions",
```

```
"Effect": "Allow",
      "Action": [
        "artifact:GetCustomerAgreement",
        "artifact:TerminateAgreement"
      ],
      "Resource": "arn:aws:artifact::*:customer-agreement/*"
    },
    {
      "Sid": "CreateServiceLinkedRoleForOrganizationsIntegration",
      "Effect": "Allow",
      "Action": [
        "iam:CreateServiceLinkedRole"
      ],
      "Resource": "arn:aws:iam::*:role/aws-service-role/
artifact.amazonaws.com/AWSServiceRoleForArtifact",
      "Condition": {
        "StringEquals": {
          "iam:AWSServiceName": [
            "artifact.amazonaws.com"
          ]
        }
      }
    },
    {
      "Sid": "GetRoleToCheckForRoleExistence",
      "Effect": "Allow",
      "Action": [
        "iam:GetRole"
      ],
      "Resource": "arn:aws:iam::*:role/aws-service-role/
artifact.amazonaws.com/AWSServiceRoleForArtifact"
    },
    {
      "Sid": "EnableServiceTrust",
      "Effect": "Allow",
      "Action": [
        "organizations:EnableAWSServiceAccess",
        "organizations:ListAWSServiceAccessForOrganization",
        "organizations:DescribeOrganization"
      ],
      "Resource": "*"
    }
  ]
}
```

AWS GovCloud (US)

{

```
"Version": "2012-10-17",
"Statement": [
  {
    "Sid": "ListAgreementActions",
    "Effect": "Allow",
    "Action": [
      "artifact:ListAgreements",
      "artifact:ListCustomerAgreements"
    ],
    "Resource": "*"
 },
  {
    "Sid": "AWSAgreementActions",
    "Effect": "Allow",
    "Action": [
      "artifact:GetAgreement",
      "artifact:AcceptNdaForAgreement",
      "artifact:GetNdaForAgreement",
      "artifact:AcceptAgreement"
    ],
    "Resource": "arn:aws-us-gov:artifact:::agreement/*"
 },
  {
    "Sid": "CustomerAgreementActions",
    "Effect": "Allow",
    "Action": [
      "artifact:GetCustomerAgreement",
      "artifact:TerminateAgreement"
    ],
    "Resource": "arn:aws-us-gov:artifact::*:customer-agreement/*"
 },
  {
    "Sid": "CreateServiceLinkedRoleForOrganizationsIntegration",
    "Effect": "Allow",
```

```
"Action": [
        "iam:CreateServiceLinkedRole"
      ],
      "Resource": "arn:aws-us-gov:iam::*:role/aws-service-role/
artifact.amazonaws.com/AWSServiceRoleForArtifact",
      "Condition": {
        "StringEquals": {
          "iam:AWSServiceName": [
            "artifact.amazonaws.com"
          1
        }
      }
    },
    {
      "Sid": "GetRoleToCheckForRoleExistence",
      "Effect": "Allow",
      "Action": [
        "iam:GetRole"
      ],
      "Resource": "arn:aws-us-gov:iam::*:role/aws-service-role/
artifact.amazonaws.com/AWSServiceRoleForArtifact"
    },
    {
      "Sid": "EnableServiceTrust",
      "Effect": "Allow",
      "Action": [
        "organizations:EnableAWSServiceAccess",
        "organizations:ListAWSServiceAccessForOrganization",
        "organizations:DescribeOrganization"
      ],
      "Resource": "*"
    }
  1
}
```

AWS Artifact updates to AWS managed policies

View details about updates to AWS managed policies for AWS Artifact since this service began tracking these changes. For automatic alerts about changes to this page, subscribe to the RSS feed on the AWS Artifact <u>Document history</u> page.

| Change | Description | Date |
|--|---|------------|
| Updated AWS Reports managed polices | Updated AWSArtifactReports ReadOnlyAccess managed policy to remove the artifact: get permission. | 2025-03-21 |
| Introduced AWS Agreements managed polices | Introduced AWSArtifa ctAgreementsReadOnlyAccess and AWSArtifactAgreeme ntsFullAccess managed policies. | 2024-11-21 |
| AWS Artifact started tracking changes | AWS Artifact started tracking changes for its AWS managed policies and introduce d AWSArtifactReports ReadOnlyAccess. | 2023-12-15 |

Using service-linked roles for AWS Artifact

AWS Artifact uses AWS Identity and Access Management (IAM) <u>service-linked roles</u>. A service-linked role is a unique type of IAM role that is linked directly to AWS Artifact. Service-linked roles are predefined by AWS Artifact and include all the permissions that the service requires to call other AWS services on your behalf.

A service-linked role makes setting up AWS Artifact easier because you don't have to manually add the necessary permissions. AWS Artifact defines the permissions of its service-linked roles, and unless defined otherwise, only AWS Artifact can assume its roles. The defined permissions include the trust policy and the permissions policy, and that permissions policy cannot be attached to any other IAM entity.

You can delete a service-linked role only after first deleting its related resources. This protects your AWS Artifact resources because you can't inadvertently remove permission to access the resources.

For information about other services that support service-linked roles, see <u>AWS services that work</u> <u>with IAM</u> and look for the services that have **Yes** in the **Service-linked roles** column. Choose a **Yes** with a link to view the service-linked role documentation for that service.

Service-linked role permissions for AWS Artifact

AWS Artifact uses the service-linked role named **AWSServiceRoleForArtifact** – Allows AWS Artifact to gather information about an organization via AWS Organizations.

The AWSServiceRoleForArtifact service-linked role trusts the following services to assume the role:

artifact.amazonaws.com

The role permissions policy named AWSArtifactServiceRolePolicy allows AWS Artifact to complete the following actions on the organizations resource.

- DescribeOrganization
- DescribeAccount
- ListAccounts
- ListAWSServiceAccessForOrganization

Creating a service-linked role for AWS Artifact

You don't need to manually create a service-linked role. When you go to the **Organization agreements** tab in an organization management account and choose the **Get started** link in the AWS Management Console, AWS Artifact creates the service-linked role for you.

If you delete this service-linked role, and then need to create it again, you can use the same process to recreate the role in your account. When you go to the **Organization agreements** tab in an organization management account and choose the **Get started** link, AWS Artifact creates the service-linked role for you again.

Editing a service-linked role for AWS Artifact

AWS Artifact does not allow you to edit the AWSServiceRoleForArtifact service-linked role. After you create a service-linked role, you cannot change the name of the role because various entities might reference the role. However, you can edit the description of the role using IAM. For more information, see Editing a service-linked role in the *IAM User Guide*.

Deleting a service-linked role for AWS Artifact

If you no longer need to use a feature or service that requires a service-linked role, we recommend that you delete that role. That way you don't have an unused entity that is not actively monitored or maintained. However, you must clean up the resources for your service-linked role before you can manually delete it.

i Note

If the AWS Artifact service is using the role when you try to delete the resources, then the deletion might fail. If that happens, wait for a few minutes and try the operation again.

To delete AWS Artifact resources used by the AWSServiceRoleForArtifact

- 1. Visit the 'Organization Agreements' table in the AWS Artifact console
- 2. Terminate any active Organization agreements

To manually delete the service-linked role using IAM

Use the IAM console, the AWS CLI, or the AWS API to delete the AWSServiceRoleForArtifact servicelinked role. For more information, see <u>Deleting a service-linked role</u> in the *IAM User Guide*.

Supported Regions for AWS Artifact service-linked roles

AWS Artifact does not support using service-linked roles in every Region where the service is available. You can use the AWSServiceRoleForArtifact role in the following Regions.

| Region name | Region identity | Support in AWS Artifact |
|-------------------------|------------------------|-------------------------|
| US East (N. Virginia) | us-east-1 | Yes |
| US East (Ohio) | us-east-2 | No |
| US West (N. California) | us-west-1 | Νο |
| US West (Oregon) | us-west-2 | Yes |
| Africa (Cape Town) | af-south-1 | No |

| Region name | Region identity | Support in AWS Artifact |
|---------------------------|------------------------|-------------------------|
| Asia Pacific (Hong Kong) | ap-east-1 | No |
| Asia Pacific (Jakarta) | ap-southeast-3 | No |
| Asia Pacific (Mumbai) | ap-south-1 | No |
| Asia Pacific (Osaka) | ap-northeast-3 | No |
| Asia Pacific (Seoul) | ap-northeast-2 | No |
| Asia Pacific (Singapore) | ap-southeast-1 | No |
| Asia Pacific (Sydney) | ap-southeast-2 | No |
| Asia Pacific (Tokyo) | ap-northeast-1 | No |
| Canada (Central) | ca-central-1 | No |
| Europe (Frankfurt) | eu-central-1 | No |
| Europe (Ireland) | eu-west-1 | No |
| Europe (London) | eu-west-2 | No |
| Europe (Milan) | eu-south-1 | No |
| Europe (Paris) | eu-west-3 | No |
| Europe (Stockholm) | eu-north-1 | No |
| Middle East (Bahrain) | me-south-1 | No |
| Middle East (UAE) | me-central-1 | No |
| South America (São Paulo) | sa-east-1 | No |
| AWS GovCloud (US-East) | us-gov-east-1 | No |
| AWS GovCloud (US-West) | us-gov-west-1 | Yes |

Using IAM condition keys for AWS Artifact reports

You can use IAM condition keys to provide fine-grained access to reports on AWS Artifact, based on specific report categories and series.

The following example policies show permissions that you can assign to IAM users based on specific report categories and series.

Example Example policies to manage AWS reports read access

AWS Artifact reports are denoted by the IAM resource, report.

The following policy grants permission to read all AWS Artifact reports under the Certifications and Attestations category.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "artifact:ListReports"
      ],
      "Resource": "*"
   },
    {
      "Effect": "Allow",
      "Action": [
        "artifact:GetReport",
        "artifact:GetReportMetadata",
        "artifact:GetTermForReport"
      ],
      "Resource": "*",
      "Condition": {
        "StringEquals": {
          "artifact:ReportCategory": "Certifications and Attestations"
        }
      }
    }
```

User Guide

```
3
```

The following policy lets you grant permission to read all AWS Artifact reports under the SOC series.

JSON

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Allow",
            "Action": [
                "artifact:ListReports"
            ],
            "Resource": "*"
        },{
            "Effect": "Allow",
            "Action": [
                "artifact:GetReport",
                "artifact:GetReportMetadata",
                "artifact:GetTermForReport"
            ],
            "Resource": [
                "*"
            ],
            "Condition": {
                "StringEquals": {
                     "artifact:ReportSeries": "SOC",
                     "artifact:ReportCategory": "Certifications and Attestations"
                }
            }
        }
    ]
}
```

The following policy lets you grant permission to read all AWS Artifact reports under the Certifications and Attestations category, and SOC series.

```
User Guide
```

```
{
 "Version": "2012-10-17",
  "Statement": [
   {
      "Effect": "Allow",
      "Action": [
        "artifact:ListReports"
     ],
     "Resource": "*"
   },
    {
      "Effect": "Allow",
      "Action": [
        "artifact:GetReport",
        "artifact:GetReportMetadata",
        "artifact:GetTermForReport"
      ],
      "Resource": "*",
      "Condition": {
        "StringEquals": {
          "artifact:ReportSeries": "SOC",
          "artifact:ReportCategory": "Certifications and Attestations"
        }
     }
   }
 1
}
```

Logging AWS Artifact API calls with AWS CloudTrail

AWS Artifact is integrated with AWS CloudTrail, a service that provides a record of actions taken by a user, role, or an AWS service in AWS Artifact. CloudTrail captures API calls for AWS Artifact as events. The calls captured include calls from the AWS Artifact console and code calls to the AWS Artifact API operations. If you create a trail, you can enable continuous delivery of CloudTrail events to an Amazon S3 bucket, including events for AWS Artifact. If you don't configure a trail, you can still view the most recent events in the CloudTrail console in **Event history**. Using the information collected by CloudTrail, you can determine the request that was made to AWS Artifact, the IP address from which the request was made, who made the request, when it was made, and additional details.

To learn more about CloudTrail, see the AWS CloudTrail User Guide.

AWS Artifact information in CloudTrail

CloudTrail is enabled on your AWS account when you create the account. When activity occurs in AWS Artifact, that activity is recorded in a CloudTrail event along with other AWS service events in **Event history**. You can view, search, and download recent events in your AWS account. For more information, see <u>Viewing events with CloudTrail Event history</u>.

For an ongoing record of events in your AWS account, including events for AWS Artifact, create a trail. A *trail* enables CloudTrail to deliver log files to an Amazon S3 bucket. By default, when you create a trail in the console, the trail applies to all AWS Regions. The trail logs events from all Regions in the AWS partition and delivers the log files to the Amazon S3 bucket that you specify. Additionally, you can configure other AWS services to further analyze and act upon the event data collected in CloudTrail logs. For more information, see the following:

- Overview for creating a trail
- <u>CloudTrail supported services and integrations</u>
- <u>Configuring Amazon SNS notifications for CloudTrail</u>
- <u>Receiving CloudTrail log files from multiple regions</u> and <u>Receiving CloudTrail log files from</u> <u>multiple accounts</u>

AWS Artifact supports logging the following actions as events in CloudTrail log files:

ListReports

- GetAccountSettings
- GetReportMetadata
- GetReport
- GetTermForReport
- PutAccountSettings
- AcceptAgreement
- <u>AcceptNdaForAgreement</u>
- GetAgreement
- <u>GetCustomerAgreement</u>
- GetNdaForAgreement
- ListAgreements
- ListCustomerAgreements
- TerminateAgreement

Every event or log entry contains information about who generated the request. The identity information helps you determine the following:

- Whether the request was made with root or AWS Identity and Access Management (IAM) user credentials.
- Whether the request was made with temporary security credentials for a role or federated user.
- Whether the request was made by another AWS service.

For more information, see the CloudTrail userIdentity element.

Understanding AWS Artifact log file entries

A trail is a configuration that enables delivery of events as log files to an Amazon S3 bucket that you specify. CloudTrail log files contain one or more log entries. An event represents a single request from any source and includes information about the requested action, the date and time of the action, request parameters, and so on. CloudTrail log files aren't an ordered stack trace of the public API calls, so they don't appear in any specific order.

The following example shows a CloudTrail log entry that demonstrates the GetReportMetadata action.

```
{
  "Records": [
    {
      "eventVersion": "1.03",
      "userIdentity": {
        "type": "IAMUser",
        "principalId": "A1B2C3D4E5F6G7EXAMPLE",
        "arn": "arn:aws:iam::99999999999999:user/myUserName",
        "accountId": "999999999999",
        "accessKeyId": "AKIAIOSFODNN7EXAMPLE",
        "userName": "myUserName"
      },
      "eventTime": "2015-03-18T19:03:36Z",
      "eventSource": "artifact.amazonaws.com",
      "eventName": "GetReportMetadata",
      "awsRegion": "us-east-1",
      "sourceIPAddress": "127.0.0.1",
      "userAgent": "Python-httplib2/0.8 (gzip)",
      "errorCode": "AccessDenied",
      "errorMessage": "User: arn:aws:iam::999999999999:user/myUserName is not
 authorized to perform: artifact:GetReportMetadata on resource: arn:aws:artifact:us-
east-1::report/report-f1DIWBmGa2Lhsadg",
      "requestParameters": null,
      "responseElements": null,
      "requestID": "7aebcd0f-cda1-11e4-aaa2-e356da31e4ff",
      "eventID": "e92a3e85-8ecd-4d23-8074-843aabfe89bf",
      "eventType": "AwsApiCall",
      "recipientAccountId": "999999999999"
    },
    {
      "eventVersion": "1.03",
      "userIdentity": {
        "type": "IAMUser",
        "principalId": "A1B2C3D4E5F6G7EXAMPLE",
        "arn": "arn:aws:iam::99999999999999:user/myUserName",
        "accountId": "999999999999",
        "accessKeyId": "AKIAIOSFODNN7EXAMPLE",
        "userName": "myUserName"
      },
      "eventTime": "2015-03-18T19:04:42Z",
      "eventSource": "artifact.amazonaws.com",
      "eventName": "GetReportMetadata",
```

```
"awsRegion": "us-east-1",
"sourceIPAddress": "127.0.0.1",
"userAgent": "Python-httplib2/0.8 (gzip)",
"requestParameters": {
    "reportId": "report-f1DIWBmGa2Lhsadg"
    },
    "responseElements": null,
    "requestID": "a2198ecc-cda1-11e4-aaa2-e356da31e4ff",
    "eventID": "20b84ce5-730f-482e-b2b2-e8fcc87ceb22",
    "eventType": "AwsApiCall",
    "recipientAccountId": "9999999999999"
    }
]
```

Document history for AWS Artifact

The following table provides a history of AWS Artifact releases and related changes to the AWS Artifact User Guide.

| Change | Description | Date |
|--|---|-------------------|
| IAM Action Deprecation Notice Update | Updated the IAM action deprecation notice for artifact:DownloadA greement and artifact: Get in the AWS GovCloud (US) partition. | July 1, 2025 |
| Fine-grained permissions for AWS Artifact in AWS GovCloud (US) Regions | Updated and expanded policies for using AWS Artifact in AWS GovCloud (US) Regions, while removing notes about limitations as AWS Artifact functionality is now more broadly applicable across all regions. | March 31, 2025 |
| Updated AWSArtifactReportR eadOnlyAccess managed policy | Updated <u>AWSArtifactReports</u> <u>ReadOnlyAccess</u> managed policy to remove the artifact: get permission. | March 21, 2025 |
| Example policies for AWS Artifact in AWS GovCloud (US) Regions | Added example policies for using AWS Artifact in AWS GovCloud (US) Regions, and noted which pages do not apply to using AWS Artifact in AWS GovCloud (US) Regions. | December 6, 2024 |
| Fine-grained permissions for agreement execution | Enabled fine-grained access for AWS Artifact agreement | November 21, 2024 |

| <u>, AWSArtifactAgreeme</u> ntsFullAccess and AWSArtifa ctAgreementsReadOnlyAccess managed policies | execution and launched AWSArtifactAgreeme ntsFullAccess and AWSArtifa ctAgreementsReadOnlyAccess AWS managed policies. | |
|--|---|--------------------|
| Fine-grained report access and AWSArtifactReportR eadOnlyAccess managed policy | Enabled fine-grained access to AWS Artifact reports, enabled report <u>condition</u> <u>keys</u> , and launched <u>AWSArtifa</u> <u>ctReportsReadOnlyAccess</u> <u>managed policy</u> . | December 15, 2023 |
| <u>AWS Artifact service-linked</u> role | Added service-linked role documentation and updated example policies for AWS Artifact and AWS Organizat ions integration. | September 26, 2023 |
| <u>Notifications</u> | Published the documenta tion for managing notificat ions, and made relevant updates to the AWS Artifact API Reference, CloudTrai l logging documentation, and the Identity and access management page. | August 1, 2023 |
| <u>Third-party reports -</u> <u>Generally available</u> | Added API reference documentation and CloudTrai l logging documentation, and made third-party reports generally available. | January 27, 2023 |

| <u>Third-party reports (Preview)</u> | Launched compliance reports of the independent software vendors (ISVs) who sell their products on AWS Marketpla ce. Added example polic ies to Identity and access management page for third- party reports. | November 30, 2022 |
|--------------------------------------|---|-------------------|
| <u>Security</u> | Added section to Identity and access management page for confused deputy prevention. | December 20, 2021 |
| <u>Reports</u> | Removed nondisclosure agreement and introduce d terms and conditions for report downloads. | December 17, 2020 |
| Home page and search | Added service home page and search bar on the reports and agreements page. | May 15, 2020 |
| AWS GovCloud (US) launch | Launched AWS Artifact in AWS GovCloud (US) Regions. | November 7, 2019 |
| AWS Organizations agreements | Added support for managing agreements for an organizat ion. | June 20, 2018 |
| Agreements | Added support for managing AWS Artifact agreements. | June 17, 2017 |
| Initial release | This release introduces AWS Artifact. | November 30, 2016 |