



Backup gateway

AWS Backup



API Version 2021-01-01

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS Backup: Backup gateway

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
AssociateGatewayToServer	3
Request Syntax	3
Request Parameters	3
Response Syntax	4
Response Elements	4
Errors	4
See Also	5
CreateGateway	7
Request Syntax	7
Request Parameters	7
Response Syntax	8
Response Elements	8
Errors	9
See Also	9
DeleteGateway	11
Request Syntax	11
Request Parameters	11
Response Syntax	11
Response Elements	11
Errors	12
See Also	13
DeleteHypervisor	14
Request Syntax	14
Request Parameters	14
Response Syntax	14
Response Elements	14
Errors	15
See Also	16
DisassociateGatewayFromServer	18
Request Syntax	18
Request Parameters	18
Response Syntax	18

Response Elements	18
Errors	19
See Also	20
GetBandwidthRateLimitSchedule	21
Request Syntax	21
Request Parameters	21
Response Syntax	21
Response Elements	22
Errors	22
See Also	23
GetGateway	25
Request Syntax	25
Request Parameters	25
Response Syntax	25
Response Elements	26
Errors	26
See Also	27
GetHypervisor	28
Request Syntax	28
Request Parameters	28
Response Syntax	28
Response Elements	29
Errors	29
See Also	30
GetHypervisorPropertyMappings	31
Request Syntax	31
Request Parameters	31
Response Syntax	31
Response Elements	32
Errors	32
See Also	33
GetVirtualMachine	35
Request Syntax	35
Request Parameters	35
Response Syntax	35
Response Elements	36

Errors	36
See Also	37
ImportHypervisorConfiguration	38
Request Syntax	38
Request Parameters	38
Response Syntax	40
Response Elements	40
Errors	40
See Also	41
ListGateways	43
Request Syntax	43
Request Parameters	43
Response Syntax	44
Response Elements	44
Errors	44
See Also	45
ListHypervisors	47
Request Syntax	47
Request Parameters	47
Response Syntax	48
Response Elements	48
Errors	48
See Also	49
ListTagsForResource	51
Request Syntax	51
Request Parameters	51
Response Syntax	51
Response Elements	52
Errors	52
See Also	53
ListVirtualMachines	54
Request Syntax	54
Request Parameters	54
Response Syntax	55
Response Elements	55
Errors	56

See Also	57
PutBandwidthRateLimitSchedule	58
Request Syntax	58
Request Parameters	58
Response Syntax	59
Response Elements	59
Errors	59
See Also	60
PutHypervisorPropertyMappings	62
Request Syntax	62
Request Parameters	62
Response Syntax	63
Response Elements	63
Errors	63
See Also	65
PutMaintenanceStartTime	66
Request Syntax	66
Request Parameters	66
Response Syntax	67
Response Elements	67
Errors	68
See Also	69
StartVirtualMachinesMetadataSync	70
Request Syntax	70
Request Parameters	70
Response Syntax	70
Response Elements	70
Errors	71
See Also	72
TagResource	73
Request Syntax	73
Request Parameters	73
Response Syntax	74
Response Elements	74
Errors	74
See Also	75

TestHypervisorConfiguration	76
Request Syntax	76
Request Parameters	76
Response Elements	77
Errors	77
See Also	78
UntagResource	80
Request Syntax	80
Request Parameters	80
Response Syntax	81
Response Elements	81
Errors	81
See Also	82
UpdateGatewayInformation	83
Request Syntax	83
Request Parameters	83
Response Syntax	84
Response Elements	84
Errors	84
See Also	85
UpdateGatewaySoftwareNow	87
Request Syntax	87
Request Parameters	87
Response Syntax	87
Response Elements	88
Errors	88
See Also	89
UpdateHypervisor	90
Request Syntax	90
Request Parameters	90
Response Syntax	92
Response Elements	92
Errors	92
See Also	94
Data Types	95
BandwidthRateLimitInterval	96

Contents	96
See Also	97
Gateway	99
Contents	99
See Also	100
GatewayDetails	101
Contents	101
See Also	103
Hypervisor	104
Contents	104
See Also	105
HypervisorDetails	106
Contents	106
See Also	108
MaintenanceStartTime	109
Contents	109
See Also	110
Tag	111
Contents	111
See Also	111
VirtualMachine	112
Contents	112
See Also	113
VirtualMachineDetails	114
Contents	114
See Also	115
VmwareTag	117
Contents	117
See Also	117
VmwareToAwsTagMapping	119
Contents	119
See Also	120
Common Parameters	121
Common Error Types	124

Welcome

AWS Backup gateway connects AWS Backup to your hypervisor, so you can create, store, and restore backups of your virtual machines (VMs) anywhere, whether on-premises or in the VMware Cloud (VMC) on AWS.

Add on-premises resources by connecting to a hypervisor through a gateway. AWS Backup will automatically discover the resources in your hypervisor.

Use AWS Backup to assign virtual or on-premises resources to a backup plan, or run on-demand backups. Once you have backed up your resources, you can view them and restore them like any resource supported by AWS Backup.

To download the AWS software to get started, navigate to the AWS Backup console, choose **Gateways**, then choose **Create gateway**.

This document was last published on July 13, 2026.

Actions

The following actions are supported:

- [AssociateGatewayToServer](#)
- [CreateGateway](#)
- [DeleteGateway](#)
- [DeleteHypervisor](#)
- [DisassociateGatewayFromServer](#)
- [GetBandwidthRateLimitSchedule](#)
- [GetGateway](#)
- [GetHypervisor](#)
- [GetHypervisorPropertyMappings](#)
- [GetVirtualMachine](#)
- [ImportHypervisorConfiguration](#)
- [ListGateways](#)
- [ListHypervisors](#)
- [ListTagsForResource](#)
- [ListVirtualMachines](#)
- [PutBandwidthRateLimitSchedule](#)
- [PutHypervisorPropertyMappings](#)
- [PutMaintenanceStartTime](#)
- [StartVirtualMachinesMetadataSync](#)
- [TagResource](#)
- [TestHypervisorConfiguration](#)
- [UntagResource](#)
- [UpdateGatewayInformation](#)
- [UpdateGatewaySoftwareNow](#)
- [UpdateHypervisor](#)

AssociateGatewayToServer

Associates a backup gateway with your server. After you complete the association process, you can back up and restore your VMs through the gateway.

Request Syntax

```
{  
  "GatewayArn": "string",  
  "ServerArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[GatewayArn](#)

The Amazon Resource Name (ARN) of the gateway. Use the `ListGateways` operation to return a list of gateways for your account and AWS Region.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 180.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})\[/code>`

Required: Yes

[ServerArn](#)

The Amazon Resource Name (ARN) of the server that hosts your virtual machines.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})\[/code>`

Required: Yes

Response Syntax

```
{
  "GatewayArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[GatewayArn](#)

The Amazon Resource Name (ARN) of a gateway.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 180.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]+){3}\/[a-zA-Z-0-9]+`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ConflictException

The operation cannot proceed because it is not supported.

ErrorCode

A description of why the operation is not supported.

HTTP Status Code: 400

InternalServerErrorException

The operation did not succeed because an internal error occurred. Try again later.

ErrorCode

A description of which internal error occurred.

HTTP Status Code: 500

ThrottlingException

TPS has been limited to protect against intentional or unintentional high request volumes.

ErrorCode

Error: TPS has been limited to protect against intentional or unintentional high request volumes.

HTTP Status Code: 400

ValidationException

The operation did not succeed because a validation error occurred.

ErrorCode

A description of what caused the validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

CreateGateway

Creates a backup gateway. After you create a gateway, you can associate it with a server using the `AssociateGatewayToServer` operation.

Request Syntax

```
{
  "ActivationKey": "string",
  "GatewayDisplayName": "string",
  "GatewayType": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ActivationKey

The activation key of the created gateway.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[0-9a-zA-Z\-\-]+`

Required: Yes

GatewayDisplayName

The display name of the created gateway.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[a-zA-Z0-9-]*`

Required: Yes

GatewayType

The type of created gateway.

Type: String

Valid Values: BACKUP_VM

Required: Yes

Tags

A list of up to 50 tags to assign to the gateway. Each tag is a key-value pair.

Type: Array of [Tag](#) objects

Required: No

Response Syntax

```
{
  "GatewayArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

GatewayArn

The Amazon Resource Name (ARN) of the gateway you create.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 180.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})\/[a-zA-Z-0-9]{3}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalServerError

The operation did not succeed because an internal error occurred. Try again later.

ErrorCode

A description of which internal error occurred.

HTTP Status Code: 500

ThrottlingException

TPS has been limited to protect against intentional or unintentional high request volumes.

ErrorCode

Error: TPS has been limited to protect against intentional or unintentional high request volumes.

HTTP Status Code: 400

ValidationException

The operation did not succeed because a validation error occurred.

ErrorCode

A description of what caused the validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteGateway

Deletes a backup gateway.

Request Syntax

```
{  
  "GatewayArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[GatewayArn](#)

The Amazon Resource Name (ARN) of the gateway to delete.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 180.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})\/[a-zA-Z-0-9]{3}`

Required: Yes

Response Syntax

```
{  
  "GatewayArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

GatewayArn

The Amazon Resource Name (ARN) of the gateway you deleted.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 180.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]+){3}\/[a-zA-Z-0-9]+`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalServerError

The operation did not succeed because an internal error occurred. Try again later.

ErrorCode

A description of which internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

A resource that is required for the action wasn't found.

ErrorCode

A description of which resource wasn't found.

HTTP Status Code: 400

ThrottlingException

TPS has been limited to protect against intentional or unintentional high request volumes.

ErrorCode

Error: TPS has been limited to protect against intentional or unintentional high request volumes.

HTTP Status Code: 400

ValidationException

The operation did not succeed because a validation error occurred.

ErrorCode

A description of what caused the validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteHypervisor

Deletes a hypervisor.

Request Syntax

```
{  
  "HypervisorArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[HypervisorArn](#)

The Amazon Resource Name (ARN) of the hypervisor to delete.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{1,20}){3}/[a-zA-Z-0-9]{1,20}`

Required: Yes

Response Syntax

```
{  
  "HypervisorArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

HypervisorArn

The Amazon Resource Name (ARN) of the hypervisor you deleted.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})\.[a-zA-Z-0-9]{3}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The operation cannot proceed because you have insufficient permissions.

ErrorCode

A description of why you have insufficient permissions.

HTTP Status Code: 400

ConflictException

The operation cannot proceed because it is not supported.

ErrorCode

A description of why the operation is not supported.

HTTP Status Code: 400

InternalServerError

The operation did not succeed because an internal error occurred. Try again later.

ErrorCode

A description of which internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

A resource that is required for the action wasn't found.

ErrorCode

A description of which resource wasn't found.

HTTP Status Code: 400

ThrottlingException

TPS has been limited to protect against intentional or unintentional high request volumes.

ErrorCode

Error: TPS has been limited to protect against intentional or unintentional high request volumes.

HTTP Status Code: 400

ValidationException

The operation did not succeed because a validation error occurred.

ErrorCode

A description of what caused the validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisassociateGatewayFromServer

Disassociates a backup gateway from the specified server. After the disassociation process finishes, the gateway can no longer access the virtual machines on the server.

Request Syntax

```
{  
  "GatewayArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

GatewayArn

The Amazon Resource Name (ARN) of the gateway to disassociate.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 180.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})/[a-zA-Z-0-9]{+}`

Required: Yes

Response Syntax

```
{  
  "GatewayArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

GatewayArn

The Amazon Resource Name (ARN) of the gateway you disassociated.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 180.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})\/[a-zA-Z-0-9]{+}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ConflictException

The operation cannot proceed because it is not supported.

ErrorCode

A description of why the operation is not supported.

HTTP Status Code: 400

InternalServerErrorException

The operation did not succeed because an internal error occurred. Try again later.

ErrorCode

A description of which internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

A resource that is required for the action wasn't found.

ErrorCode

A description of which resource wasn't found.

HTTP Status Code: 400

ThrottlingException

TPS has been limited to protect against intentional or unintentional high request volumes.

ErrorCode

Error: TPS has been limited to protect against intentional or unintentional high request volumes.

HTTP Status Code: 400

ValidationException

The operation did not succeed because a validation error occurred.

ErrorCode

A description of what caused the validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetBandwidthRateLimitSchedule

Retrieves the bandwidth rate limit schedule for a specified gateway. By default, gateways do not have bandwidth rate limit schedules, which means no bandwidth rate limiting is in effect. Use this to get a gateway's bandwidth rate limit schedule.

Request Syntax

```
{  
  "GatewayArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[GatewayArn](#)

The Amazon Resource Name (ARN) of the gateway. Use the [ListGateways](#) operation to return a list of gateways for your account and AWS Region.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 180.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]+){3}\/[a-zA-Z-0-9]+`

Required: Yes

Response Syntax

```
{  
  "BandwidthRateLimitIntervals": [  
    {  
      "AverageUploadRateLimitInBitsPerSec": number,  
      "DaysOfWeek": [ number ],  
      "EndHourOfDay": number,  
    }  
  ]  
}
```

```
    "EndMinuteOfHour": number,  
    "StartHourOfDay": number,  
    "StartMinuteOfHour": number  
  }  
],  
"GatewayArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

BandwidthRateLimitIntervals

An array containing bandwidth rate limit schedule intervals for a gateway. When no bandwidth rate limit intervals have been scheduled, the array is empty.

Type: Array of [BandwidthRateLimitInterval](#) objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

GatewayArn

The Amazon Resource Name (ARN) of the gateway. Use the [ListGateways](#) operation to return a list of gateways for your account and AWS Region.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 180.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{1,30}){3}\/[a-zA-Z-0-9]{1,30}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalServerError

The operation did not succeed because an internal error occurred. Try again later.

ErrorCode

A description of which internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

A resource that is required for the action wasn't found.

ErrorCode

A description of which resource wasn't found.

HTTP Status Code: 400

ThrottlingException

TPS has been limited to protect against intentional or unintentional high request volumes.

ErrorCode

Error: TPS has been limited to protect against intentional or unintentional high request volumes.

HTTP Status Code: 400

ValidationException

The operation did not succeed because a validation error occurred.

ErrorCode

A description of what caused the validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetGateway

By providing the ARN (Amazon Resource Name), this API returns the gateway.

Request Syntax

```
{  
  "GatewayArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

GatewayArn

The Amazon Resource Name (ARN) of the gateway.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 180.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]+){3}\/[a-zA-Z-0-9]+`

Required: Yes

Response Syntax

```
{  
  "Gateway": {  
    "DeprecationDate": number,  
    "GatewayArn": "string",  
    "GatewayDisplayName": "string",  
    "GatewayType": "string",  
    "HypervisorId": "string",  
    "LastSeenTime": number,  
    "MaintenanceStartTime": {
```

```
    "DayOfMonth": number,
    "DayOfWeek": number,
    "HourOfDay": number,
    "MinuteOfHour": number
  },
  "NextUpdateAvailabilityTime": number,
  "SoftwareVersion": "string",
  "VpcEndpoint": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Gateway

By providing the ARN (Amazon Resource Name), this API returns the gateway.

Type: [GatewayDetails](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalServerError

The operation did not succeed because an internal error occurred. Try again later.

ErrorCode

A description of which internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

A resource that is required for the action wasn't found.

ErrorCode

A description of which resource wasn't found.

HTTP Status Code: 400

ThrottlingException

TPS has been limited to protect against intentional or unintentional high request volumes.

ErrorCode

Error: TPS has been limited to protect against intentional or unintentional high request volumes.

HTTP Status Code: 400

ValidationException

The operation did not succeed because a validation error occurred.

ErrorCode

A description of what caused the validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetHypervisor

This action requests information about the specified hypervisor to which the gateway will connect. A hypervisor is hardware, software, or firmware that creates and manages virtual machines, and allocates resources to them.

Request Syntax

```
{  
  "HypervisorArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[HypervisorArn](#)

The Amazon Resource Name (ARN) of the hypervisor.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})\[/code>`

Required: Yes

Response Syntax

```
{  
  "Hypervisor": {  
    "Host": "string",  
    "HypervisorArn": "string",  
    "KmsKeyArn": "string",  
    "LastSuccessfulMetadataSyncTime": number,  
  }
```

```
"LatestMetadataSyncStatus": "string",  
"LatestMetadataSyncStatusMessage": "string",  
"LogGroupArn": "string",  
"Name": "string",  
"State": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Hypervisor](#)

Details about the requested hypervisor.

Type: [HypervisorDetails](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalServerError

The operation did not succeed because an internal error occurred. Try again later.

ErrorCode

A description of which internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

A resource that is required for the action wasn't found.

ErrorCode

A description of which resource wasn't found.

HTTP Status Code: 400

ThrottlingException

TPS has been limited to protect against intentional or unintentional high request volumes.

ErrorCode

Error: TPS has been limited to protect against intentional or unintentional high request volumes.

HTTP Status Code: 400

ValidationException

The operation did not succeed because a validation error occurred.

ErrorCode

A description of what caused the validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetHypervisorPropertyMappings

This action retrieves the property mappings for the specified hypervisor. A hypervisor property mapping displays the relationship of entity properties available from the hypervisor to the properties available in AWS.

Request Syntax

```
{
  "HypervisorArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[HypervisorArn](#)

The Amazon Resource Name (ARN) of the hypervisor.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})\[/code>`

Required: Yes

Response Syntax

```
{
  "HypervisorArn": "string",
  "IamRoleArn": "string",
  "VmwareToAwsTagMappings": [
    {
      "AwsTagKey": "string",
      "AwsTagValue": "string",

```

```
    "VmwareCategory": "string",  
    "VmwareTagName": "string"  
  }  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

HypervisorArn

The Amazon Resource Name (ARN) of the hypervisor.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})\[/code>`

IamRoleArn

The Amazon Resource Name (ARN) of the IAM role.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:(aws|aws-cn|aws-us-gov):iam::([0-9]+):role/(\\S+)`

VmwareToAwsTagMappings

This is a display of the mappings of VMware tags to the AWS tags.

Type: Array of [VmwareToAwsTagMapping](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalServerError

The operation did not succeed because an internal error occurred. Try again later.

ErrorCode

A description of which internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

A resource that is required for the action wasn't found.

ErrorCode

A description of which resource wasn't found.

HTTP Status Code: 400

ThrottlingException

TPS has been limited to protect against intentional or unintentional high request volumes.

ErrorCode

Error: TPS has been limited to protect against intentional or unintentional high request volumes.

HTTP Status Code: 400

ValidationException

The operation did not succeed because a validation error occurred.

ErrorCode

A description of what caused the validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetVirtualMachine

By providing the ARN (Amazon Resource Name), this API returns the virtual machine.

Request Syntax

```
{  
  "ResourceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ResourceArn](#)

The Amazon Resource Name (ARN) of the virtual machine.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]+){3}\/[a-zA-Z-0-9]+`

Required: Yes

Response Syntax

```
{  
  "VirtualMachine": {  
    "HostName": "string",  
    "HypervisorId": "string",  
    "LastBackupDate": number,  
    "Name": "string",  
    "Path": "string",  
    "ResourceArn": "string",  
    "VmwareTags": [  

```

```
{
  {
    "VmwareCategory": "string",
    "VmwareTagDescription": "string",
    "VmwareTagName": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

VirtualMachine

This object contains the basic attributes of VirtualMachine contained by the output of GetVirtualMachine

Type: [VirtualMachineDetails](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalServerError

The operation did not succeed because an internal error occurred. Try again later.

ErrorCode

A description of which internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

A resource that is required for the action wasn't found.

ErrorCode

A description of which resource wasn't found.

HTTP Status Code: 400

ThrottlingException

TPS has been limited to protect against intentional or unintentional high request volumes.

ErrorCode

Error: TPS has been limited to protect against intentional or unintentional high request volumes.

HTTP Status Code: 400

ValidationException

The operation did not succeed because a validation error occurred.

ErrorCode

A description of what caused the validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ImportHypervisorConfiguration

Connect to a hypervisor by importing its configuration.

Request Syntax

```
{
  "Host": "string",
  "KmsKeyArn": "string",
  "Name": "string",
  "Password": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "Username": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Host

The server host of the hypervisor. This can be either an IP address or a fully-qualified domain name (FQDN).

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: . +

Required: Yes

KmsKeyArn

The AWS Key Management Service for the hypervisor.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: `(^arn:(aws|aws-cn|aws-us-gov):kms:([a-zA-Z0-9-]+):([0-9]+):(key|alias))/(\S+)$)|(^alias/(\S+)$)`

Required: No

Name

The name of the hypervisor.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[a-zA-Z0-9-]*`

Required: Yes

Password

The password for the hypervisor.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[ -~]+`

Required: No

Tags

The tags of the hypervisor configuration to import.

Type: Array of [Tag](#) objects

Required: No

Username

The username for the hypervisor.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [-\.0-\[\]-~]*[!-\.0-\[\]-~][-\.0-\[\]-~]*

Required: No

Response Syntax

```
{  
  "HypervisorArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[HypervisorArn](#)

The Amazon Resource Name (ARN) of the hypervisor you disassociated.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})\[/a-zA-Z-0-9]{3}

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The operation cannot proceed because you have insufficient permissions.

ErrorCode

A description of why you have insufficient permissions.

HTTP Status Code: 400

ConflictException

The operation cannot proceed because it is not supported.

ErrorCode

A description of why the operation is not supported.

HTTP Status Code: 400

InternalServerErrorException

The operation did not succeed because an internal error occurred. Try again later.

ErrorCode

A description of which internal error occurred.

HTTP Status Code: 500

ThrottlingException

TPS has been limited to protect against intentional or unintentional high request volumes.

ErrorCode

Error: TPS has been limited to protect against intentional or unintentional high request volumes.

HTTP Status Code: 400

ValidationException

The operation did not succeed because a validation error occurred.

ErrorCode

A description of what caused the validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListGateways

Lists backup gateways owned by an AWS account in an AWS Region. The returned list is ordered by gateway Amazon Resource Name (ARN).

Request Syntax

```
{  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

The maximum number of gateways to list.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The next item following a partial list of returned resources. For example, if a request is made to return `MaxResults` number of resources, `NextToken` allows you to return more items in your list starting at the location pointed to by the next token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: . +

Required: No

Response Syntax

```
{
  "Gateways": [
    {
      "GatewayArn": "string",
      "GatewayDisplayName": "string",
      "GatewayType": "string",
      "HypervisorId": "string",
      "LastSeenTime": number
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Gateways

A list of your gateways.

Type: Array of [Gateway](#) objects

NextToken

The next item following a partial list of returned resources. For example, if a request is made to return `maxResults` number of resources, `NextToken` allows you to return more items in your list starting at the location pointed to by the next token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: . +

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalServerError

The operation did not succeed because an internal error occurred. Try again later.

ErrorCode

A description of which internal error occurred.

HTTP Status Code: 500

ThrottlingException

TPS has been limited to protect against intentional or unintentional high request volumes.

ErrorCode

Error: TPS has been limited to protect against intentional or unintentional high request volumes.

HTTP Status Code: 400

ValidationException

The operation did not succeed because a validation error occurred.

ErrorCode

A description of what caused the validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListHypervisors

Lists your hypervisors.

Request Syntax

```
{  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

The maximum number of hypervisors to list.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The next item following a partial list of returned resources. For example, if a request is made to return `maxResults` number of resources, `NextToken` allows you to return more items in your list starting at the location pointed to by the next token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: . +

Required: No

Response Syntax

```
{
  "Hypervisors": [
    {
      "Host": "string",
      "HypervisorArn": "string",
      "KmsKeyArn": "string",
      "Name": "string",
      "State": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Hypervisors](#)

A list of your Hypervisor objects, ordered by their Amazon Resource Names (ARNs).

Type: Array of [Hypervisor](#) objects

[NextToken](#)

The next item following a partial list of returned resources. For example, if a request is made to return `maxResults` number of resources, `NextToken` allows you to return more items in your list starting at the location pointed to by the next token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: . +

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalServerError

The operation did not succeed because an internal error occurred. Try again later.

ErrorCode

A description of which internal error occurred.

HTTP Status Code: 500

ThrottlingException

TPS has been limited to protect against intentional or unintentional high request volumes.

ErrorCode

Error: TPS has been limited to protect against intentional or unintentional high request volumes.

HTTP Status Code: 400

ValidationException

The operation did not succeed because a validation error occurred.

ErrorCode

A description of what caused the validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Lists the tags applied to the resource identified by its Amazon Resource Name (ARN).

Request Syntax

```
{  
  "ResourceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ResourceArn

The Amazon Resource Name (ARN) of the resource's tags to list.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})\.[a-zA-Z-0-9]{3}`

Required: Yes

Response Syntax

```
{  
  "ResourceArn": "string",  
  "Tags": [  
    {  
      "Key": "string",  
      "Value": "string"  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ResourceArn

The Amazon Resource Name (ARN) of the resource's tags that you listed.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})\[/code>`

Tags

A list of the resource's tags.

Type: Array of [Tag](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalServerError

The operation did not succeed because an internal error occurred. Try again later.

ErrorCode

A description of which internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

A resource that is required for the action wasn't found.

ErrorCode

A description of which resource wasn't found.

HTTP Status Code: 400

ThrottlingException

TPS has been limited to protect against intentional or unintentional high request volumes.

ErrorCode

Error: TPS has been limited to protect against intentional or unintentional high request volumes.

HTTP Status Code: 400

ValidationException

The operation did not succeed because a validation error occurred.

ErrorCode

A description of what caused the validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListVirtualMachines

Lists your virtual machines.

Request Syntax

```
{  
  "HypervisorArn": "string",  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

HypervisorArn

The Amazon Resource Name (ARN) of the hypervisor connected to your virtual machine.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]+){3}[/[a-zA-Z-0-9]+`

Required: No

MaxResults

The maximum number of virtual machines to list.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The next item following a partial list of returned resources. For example, if a request is made to return `maxResults` number of resources, `NextToken` allows you to return more items in your list starting at the location pointed to by the next token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: . +

Required: No

Response Syntax

```
{
  "NextToken": "string",
  "VirtualMachines": [
    {
      "HostName": "string",
      "HypervisorId": "string",
      "LastBackupDate": number,
      "Name": "string",
      "Path": "string",
      "ResourceArn": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The next item following a partial list of returned resources. For example, if a request is made to return `maxResults` number of resources, `NextToken` allows you to return more items in your list starting at the location pointed to by the next token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: . +

VirtualMachines

A list of your VirtualMachine objects, ordered by their Amazon Resource Names (ARNs).

Type: Array of [VirtualMachine](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalServerError

The operation did not succeed because an internal error occurred. Try again later.

ErrorCode

A description of which internal error occurred.

HTTP Status Code: 500

ThrottlingException

TPS has been limited to protect against intentional or unintentional high request volumes.

ErrorCode

Error: TPS has been limited to protect against intentional or unintentional high request volumes.

HTTP Status Code: 400

ValidationException

The operation did not succeed because a validation error occurred.

ErrorCode

A description of what caused the validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutBandwidthRateLimitSchedule

This action sets the bandwidth rate limit schedule for a specified gateway. By default, gateways do not have a bandwidth rate limit schedule, which means no bandwidth rate limiting is in effect. Use this to initiate a gateway's bandwidth rate limit schedule.

Request Syntax

```
{
  "BandwidthRateLimitIntervals": [
    {
      "AverageUploadRateLimitInBitsPerSec": number,
      "DaysOfWeek": [ number ],
      "EndHourOfDay": number,
      "EndMinuteOfHour": number,
      "StartHourOfDay": number,
      "StartMinuteOfHour": number
    }
  ],
  "GatewayArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[BandwidthRateLimitIntervals](#)

An array containing bandwidth rate limit schedule intervals for a gateway. When no bandwidth rate limit intervals have been scheduled, the array is empty.

Type: Array of [BandwidthRateLimitInterval](#) objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: Yes

[GatewayArn](#)

The Amazon Resource Name (ARN) of the gateway. Use the [ListGateways](#) operation to return a list of gateways for your account and AWS Region.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 180.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3}){3}\[a-zA-Z-0-9]{3}`

Required: Yes

Response Syntax

```
{
  "GatewayArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

GatewayArn

The Amazon Resource Name (ARN) of the gateway. Use the [ListGateways](#) operation to return a list of gateways for your account and AWS Region.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 180.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3}){3}\[a-zA-Z-0-9]{3}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalServerError

The operation did not succeed because an internal error occurred. Try again later.

ErrorCode

A description of which internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

A resource that is required for the action wasn't found.

ErrorCode

A description of which resource wasn't found.

HTTP Status Code: 400

ThrottlingException

TPS has been limited to protect against intentional or unintentional high request volumes.

ErrorCode

Error: TPS has been limited to protect against intentional or unintentional high request volumes.

HTTP Status Code: 400

ValidationException

The operation did not succeed because a validation error occurred.

ErrorCode

A description of what caused the validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutHypervisorPropertyMappings

This action sets the property mappings for the specified hypervisor. A hypervisor property mapping displays the relationship of entity properties available from the hypervisor to the properties available in AWS.

Request Syntax

```
{
  "HypervisorArn": "string",
  "IamRoleArn": "string",
  "VmwareToAwsTagMappings": [
    {
      "AwsTagKey": "string",
      "AwsTagValue": "string",
      "VmwareCategory": "string",
      "VmwareTagName": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

HypervisorArn

The Amazon Resource Name (ARN) of the hypervisor.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})\[/code>`

Required: Yes

IamRoleArn

The Amazon Resource Name (ARN) of the IAM role.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:(aws|aws-cn|aws-us-gov):iam:([0-9]+):role/(\S+)`

Required: Yes

[VmwareToAwsTagMappings](#)

This action requests the mappings of VMware tags to the AWS tags.

Type: Array of [VmwareToAwsTagMapping](#) objects

Required: Yes

Response Syntax

```
{  
  "HypervisorArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[HypervisorArn](#)

The Amazon Resource Name (ARN) of the hypervisor.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]+){3}\/[a-zA-Z-0-9]+`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The operation cannot proceed because you have insufficient permissions.

ErrorCode

A description of why you have insufficient permissions.

HTTP Status Code: 400

ConflictException

The operation cannot proceed because it is not supported.

ErrorCode

A description of why the operation is not supported.

HTTP Status Code: 400

InternalServerError

The operation did not succeed because an internal error occurred. Try again later.

ErrorCode

A description of which internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

A resource that is required for the action wasn't found.

ErrorCode

A description of which resource wasn't found.

HTTP Status Code: 400

ThrottlingException

TPS has been limited to protect against intentional or unintentional high request volumes.

ErrorCode

Error: TPS has been limited to protect against intentional or unintentional high request volumes.

HTTP Status Code: 400

ValidationException

The operation did not succeed because a validation error occurred.

ErrorCode

A description of what caused the validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutMaintenanceStartTime

Set the maintenance start time for a gateway.

Request Syntax

```
{  
  "DayOfMonth": number,  
  "DayOfWeek": number,  
  "GatewayArn": "string",  
  "HourOfDay": number,  
  "MinuteOfHour": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

DayOfMonth

The day of the month start maintenance on a gateway.

Valid values range from Sunday to Saturday.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 31.

Required: No

DayOfWeek

The day of the week to start maintenance on a gateway.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 6.

Required: No

GatewayArn

The Amazon Resource Name (ARN) for the gateway, used to specify its maintenance start time.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 180.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})?/[a-zA-Z-0-9]{50,180}`

Required: Yes

HourOfDay

The hour of the day to start maintenance on a gateway.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 23.

Required: Yes

MinuteOfHour

The minute of the hour to start maintenance on a gateway.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 59.

Required: Yes

Response Syntax

```
{  
  "GatewayArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

GatewayArn

The Amazon Resource Name (ARN) of a gateway for which you set the maintenance start time.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 180.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})\/[a-zA-Z-0-9]{+}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ConflictException

The operation cannot proceed because it is not supported.

ErrorCode

A description of why the operation is not supported.

HTTP Status Code: 400

InternalServerErrorException

The operation did not succeed because an internal error occurred. Try again later.

ErrorCode

A description of which internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

A resource that is required for the action wasn't found.

ErrorCode

A description of which resource wasn't found.

HTTP Status Code: 400

ThrottlingException

TPS has been limited to protect against intentional or unintentional high request volumes.

ErrorCode

Error: TPS has been limited to protect against intentional or unintentional high request volumes.

HTTP Status Code: 400

ValidationException

The operation did not succeed because a validation error occurred.

ErrorCode

A description of what caused the validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartVirtualMachinesMetadataSync

This action sends a request to sync metadata across the specified virtual machines.

Request Syntax

```
{  
  "HypervisorArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[HypervisorArn](#)

The Amazon Resource Name (ARN) of the hypervisor.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})\[/code>`

Required: Yes

Response Syntax

```
{  
  "HypervisorArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

HypervisorArn

The Amazon Resource Name (ARN) of the hypervisor.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})\[/code>`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The operation cannot proceed because you have insufficient permissions.

ErrorCode

A description of why you have insufficient permissions.

HTTP Status Code: 400

InternalServerError

The operation did not succeed because an internal error occurred. Try again later.

ErrorCode

A description of which internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

A resource that is required for the action wasn't found.

ErrorCode

A description of which resource wasn't found.

HTTP Status Code: 400

ThrottlingException

TPS has been limited to protect against intentional or unintentional high request volumes.

ErrorCode

Error: TPS has been limited to protect against intentional or unintentional high request volumes.

HTTP Status Code: 400

ValidationException

The operation did not succeed because a validation error occurred.

ErrorCode

A description of what caused the validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Tag the resource.

Request Syntax

```
{
  "ResourceARN": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ResourceARN](#)

The Amazon Resource Name (ARN) of the resource to tag.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})\[/code>`

Required: Yes

[Tags](#)

A list of tags to assign to the resource.

Type: Array of [Tag](#) objects

Required: Yes

Response Syntax

```
{  
  "ResourceARN": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ResourceARN](#)

The Amazon Resource Name (ARN) of the resource you tagged.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]+){3}\/[a-zA-Z-0-9]+`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalServerError

The operation did not succeed because an internal error occurred. Try again later.

ErrorCode

A description of which internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

A resource that is required for the action wasn't found.

ErrorCode

A description of which resource wasn't found.

HTTP Status Code: 400

ThrottlingException

TPS has been limited to protect against intentional or unintentional high request volumes.

ErrorCode

Error: TPS has been limited to protect against intentional or unintentional high request volumes.

HTTP Status Code: 400

ValidationException

The operation did not succeed because a validation error occurred.

ErrorCode

A description of what caused the validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TestHypervisorConfiguration

Tests your hypervisor configuration to validate that backup gateway can connect with the hypervisor and its resources.

Request Syntax

```
{
  "GatewayArn": "string",
  "Host": "string",
  "Password": "string",
  "Username": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[GatewayArn](#)

The Amazon Resource Name (ARN) of the gateway to the hypervisor to test.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 180.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]+){3}\/[a-zA-Z-0-9]+`

Required: Yes

[Host](#)

The server host of the hypervisor. This can be either an IP address or a fully-qualified domain name (FQDN).

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: . +

Required: Yes

Password

The password for the hypervisor.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [-~] +

Required: No

Username

The username for the hypervisor.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [-\.\0-\[\] -~] * [!-\.\0-\[\] -~] [-\.\0-\[\] -~] *

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ConflictException

The operation cannot proceed because it is not supported.

ErrorCode

A description of why the operation is not supported.

HTTP Status Code: 400

InternalServerErrorException

The operation did not succeed because an internal error occurred. Try again later.

ErrorCode

A description of which internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

A resource that is required for the action wasn't found.

ErrorCode

A description of which resource wasn't found.

HTTP Status Code: 400

ThrottlingException

TPS has been limited to protect against intentional or unintentional high request volumes.

ErrorCode

Error: TPS has been limited to protect against intentional or unintentional high request volumes.

HTTP Status Code: 400

ValidationException

The operation did not succeed because a validation error occurred.

ErrorCode

A description of what caused the validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Removes tags from the resource.

Request Syntax

```
{  
  "ResourceARN": "string",  
  "TagKeys": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ResourceARN

The Amazon Resource Name (ARN) of the resource from which to remove tags.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})\[/code>`

Required: Yes

TagKeys

The list of tag keys specifying which tags to remove.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `([\p{L}\p{Z}\p{N}_.: /+=\ -@]*)`

Required: Yes

Response Syntax

```
{  
  "ResourceARN": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ResourceARN](#)

The Amazon Resource Name (ARN) of the resource from which you removed tags.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]+){3}\/[a-zA-Z-0-9]+`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalServerError

The operation did not succeed because an internal error occurred. Try again later.

ErrorCode

A description of which internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

A resource that is required for the action wasn't found.

ErrorCode

A description of which resource wasn't found.

HTTP Status Code: 400

ThrottlingException

TPS has been limited to protect against intentional or unintentional high request volumes.

ErrorCode

Error: TPS has been limited to protect against intentional or unintentional high request volumes.

HTTP Status Code: 400

ValidationException

The operation did not succeed because a validation error occurred.

ErrorCode

A description of what caused the validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateGatewayInformation

Updates a gateway's name. Specify which gateway to update using the Amazon Resource Name (ARN) of the gateway in your request.

Request Syntax

```
{  
  "GatewayArn": "string",  
  "GatewayDisplayName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[GatewayArn](#)

The Amazon Resource Name (ARN) of the gateway to update.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 180.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})\.[a-zA-Z-0-9]{3}`

Required: Yes

[GatewayDisplayName](#)

The updated display name of the gateway.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[a-zA-Z0-9-]*`

Required: No

Response Syntax

```
{  
  "GatewayArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[GatewayArn](#)

The Amazon Resource Name (ARN) of the gateway you updated.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 180.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})\/[a-zA-Z-0-9]{+}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ConflictException

The operation cannot proceed because it is not supported.

ErrorCode

A description of why the operation is not supported.

HTTP Status Code: 400

InternalServerErrorException

The operation did not succeed because an internal error occurred. Try again later.

ErrorCode

A description of which internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

A resource that is required for the action wasn't found.

ErrorCode

A description of which resource wasn't found.

HTTP Status Code: 400

ThrottlingException

TPS has been limited to protect against intentional or unintentional high request volumes.

ErrorCode

Error: TPS has been limited to protect against intentional or unintentional high request volumes.

HTTP Status Code: 400

ValidationException

The operation did not succeed because a validation error occurred.

ErrorCode

A description of what caused the validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateGatewaySoftwareNow

Updates the gateway virtual machine (VM) software. The request immediately triggers the software update.

Note

When you make this request, you get a 200 OK success response immediately. However, it might take some time for the update to complete.

Request Syntax

```
{  
  "GatewayArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

GatewayArn

The Amazon Resource Name (ARN) of the gateway to be updated.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 180.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})\/[a-zA-Z-0-9]{+}`

Required: Yes

Response Syntax

```
{
```

```
"GatewayArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

GatewayArn

The Amazon Resource Name (ARN) of the gateway you updated.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 180.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})\[/code>`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalServerError

The operation did not succeed because an internal error occurred. Try again later.

ErrorCode

A description of which internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

A resource that is required for the action wasn't found.

ErrorCode

A description of which resource wasn't found.

HTTP Status Code: 400

ThrottlingException

TPS has been limited to protect against intentional or unintentional high request volumes.

ErrorCode

Error: TPS has been limited to protect against intentional or unintentional high request volumes.

HTTP Status Code: 400

ValidationException

The operation did not succeed because a validation error occurred.

ErrorCode

A description of what caused the validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateHypervisor

Updates a hypervisor metadata, including its host, username, and password. Specify which hypervisor to update using the Amazon Resource Name (ARN) of the hypervisor in your request.

Request Syntax

```
{  
  "Host": "string",  
  "HypervisorArn": "string",  
  "LogGroupArn": "string",  
  "Name": "string",  
  "Password": "string",  
  "Username": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Host

The updated host of the hypervisor. This can be either an IP address or a fully-qualified domain name (FQDN).

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: . +

Required: No

HypervisorArn

The Amazon Resource Name (ARN) of the hypervisor to update.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})\/[a-zA-Z-0-9]{3}`

Required: Yes

LogGroupArn

The Amazon Resource Name (ARN) of the group of gateways within the requested log.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `^\$arn:(aws|aws-cn|aws-us-gov):logs:([a-zA-Z0-9-]{1,63}):([0-9-]{1,63}):log-group:[a-zA-Z0-9-_.\+]{1,63}`

Required: No

Name

The updated name for the hypervisor

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[a-zA-Z0-9-]{1,100}`

Required: No

Password

The updated password for the hypervisor.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[-~]{1,100}`

Required: No

Username

The updated username for the hypervisor.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [-\.0-\[\]-~]*[!-\.0-\[\]-~][-\.0-\[\]-~]*

Required: No

Response Syntax

```
{  
  "HypervisorArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[HypervisorArn](#)

The Amazon Resource Name (ARN) of the hypervisor you updated.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})\/[a-zA-Z-0-9]{+}

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The operation cannot proceed because you have insufficient permissions.

ErrorCode

A description of why you have insufficient permissions.

HTTP Status Code: 400

ConflictException

The operation cannot proceed because it is not supported.

ErrorCode

A description of why the operation is not supported.

HTTP Status Code: 400

InternalServerErrorException

The operation did not succeed because an internal error occurred. Try again later.

ErrorCode

A description of which internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

A resource that is required for the action wasn't found.

ErrorCode

A description of which resource wasn't found.

HTTP Status Code: 400

ThrottlingException

TPS has been limited to protect against intentional or unintentional high request volumes.

ErrorCode

Error: TPS has been limited to protect against intentional or unintentional high request volumes.

HTTP Status Code: 400

ValidationException

The operation did not succeed because a validation error occurred.

ErrorCode

A description of what caused the validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS Backup API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [BandwidthRateLimitInterval](#)
- [Gateway](#)
- [GatewayDetails](#)
- [Hypervisor](#)
- [HypervisorDetails](#)
- [MaintenanceStartTime](#)
- [Tag](#)
- [VirtualMachine](#)
- [VirtualMachineDetails](#)
- [VmwareTag](#)
- [VmwareToAwsTagMapping](#)

BandwidthRateLimitInterval

Describes a bandwidth rate limit interval for a gateway. A bandwidth rate limit schedule consists of one or more bandwidth rate limit intervals. A bandwidth rate limit interval defines a period of time on one or more days of the week, during which bandwidth rate limits are specified for uploading.

Contents

DaysOfWeek

The days of the week component of the bandwidth rate limit interval, represented as ordinal numbers from 0 to 6, where 0 represents Sunday and 6 represents Saturday.

Type: Array of integers

Array Members: Minimum number of 1 item. Maximum number of 7 items.

Valid Range: Minimum value of 0. Maximum value of 6.

Required: Yes

EndHourOfDay

The hour of the day to end the bandwidth rate limit interval.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 23.

Required: Yes

EndMinuteOfHour

The minute of the hour to end the bandwidth rate limit interval.

Important

The bandwidth rate limit interval ends at the end of the minute. To end an interval at the end of an hour, use the value 59.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 59.

Required: Yes

StartHourOfDay

The hour of the day to start the bandwidth rate limit interval.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 23.

Required: Yes

StartMinuteOfHour

The minute of the hour to start the bandwidth rate limit interval. The interval begins at the start of that minute. To begin an interval exactly at the start of the hour, use the value 0.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 59.

Required: Yes

AverageUploadRateLimitInBitsPerSec

The average upload rate limit component of the bandwidth rate limit interval, in bits per second. This field does not appear in the response if the upload rate limit is not set.

Type: Long

Valid Range: Minimum value of 51200. Maximum value of 8000000000000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

Gateway

A gateway is an AWS Backup Gateway appliance that runs on the customer's network to provide seamless connectivity to backup storage in the AWS Cloud.

Contents

GatewayArn

The Amazon Resource Name (ARN) of the gateway. Use the `ListGateways` operation to return a list of gateways for your account and AWS Region.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 180.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})/[a-zA-Z-0-9]{+}`

Required: No

GatewayDisplayName

The display name of the gateway.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[a-zA-Z0-9-]*`

Required: No

GatewayType

The type of the gateway.

Type: String

Valid Values: `BACKUP_VM`

Required: No

HypervisorId

The hypervisor ID of the gateway.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

LastSeenTime

The last time AWS Backup gateway communicated with the gateway, in Unix format and UTC time.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GatewayDetails

The details of gateway.

Contents

DeprecationDate

Date after which this gateway will not receive software updates for new features and bug fixes.

Type: Timestamp

Required: No

GatewayArn

The Amazon Resource Name (ARN) of the gateway. Use the `ListGateways` operation to return a list of gateways for your account and AWS Region.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 180.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]+){3}\/[a-zA-Z-0-9]+`

Required: No

GatewayDisplayName

The display name of the gateway.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[a-zA-Z0-9-]*`

Required: No

GatewayType

The type of the gateway type.

Type: String

Valid Values: BACKUP_VM

Required: No

HypervisorId

The hypervisor ID of the gateway.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

LastSeenTime

Details showing the last time AWS Backup gateway communicated with the cloud, in Unix format and UTC time.

Type: Timestamp

Required: No

MaintenanceStartTime

Returns your gateway's weekly maintenance start time including the day and time of the week. Note that values are in terms of the gateway's time zone. Can be weekly or monthly.

Type: [MaintenanceStartTime](#) object

Required: No

NextUpdateAvailabilityTime

Details showing the next update availability time of the gateway.

Type: Timestamp

Required: No

SoftwareVersion

The version number of the software running on the gateway appliance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9-]*

Required: No

VpcEndpoint

The DNS name for the virtual private cloud (VPC) endpoint the gateway uses to connect to the cloud for backup gateway.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Hypervisor

Represents the hypervisor's permissions to which the gateway will connect.

A hypervisor is hardware, software, or firmware that creates and manages virtual machines, and allocates resources to them.

Contents

Host

The server host of the hypervisor. This can be either an IP address or a fully-qualified domain name (FQDN).

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: . +

Required: No

HypervisorArn

The Amazon Resource Name (ARN) of the hypervisor.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})\[/code>`

Required: No

KmsKeyArn

The Amazon Resource Name (ARN) of the AWS Key Management Service used to encrypt the hypervisor.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: (^arn:(aws|aws-cn|aws-us-gov):kms:([a-zA-Z0-9-]+):([0-9]+):(key|alias))/(\S+)\$)|(^alias/(\S+)\$)

Required: No

Name

The name of the hypervisor.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9-]*

Required: No

State

The state of the hypervisor.

Type: String

Valid Values: PENDING | ONLINE | OFFLINE | ERROR

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HypervisorDetails

These are the details of the specified hypervisor. A hypervisor is hardware, software, or firmware that creates and manages virtual machines, and allocates resources to them.

Contents

Host

The server host of the hypervisor. This can be either an IP address or a fully-qualified domain name (FQDN).

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: . +

Required: No

HypervisorArn

The Amazon Resource Name (ARN) of the hypervisor.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3})\[/code>`

Required: No

KmsKeyArn

The Amazon Resource Name (ARN) of the AWS KMS used to encrypt the hypervisor.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: `(^arn:(aws|aws-cn|aws-us-gov):kms:([a-zA-Z0-9-]{3}):([0-9-]{3}):([key|alias])/(\S+)$)|(^alias/(\S+)$)`

Required: No

LastSuccessfulMetadataSyncTime

This is the time when the most recent successful sync of metadata occurred.

Type: Timestamp

Required: No

LatestMetadataSyncStatus

This is the most recent status for the indicated metadata sync.

Type: String

Valid Values: CREATED | RUNNING | FAILED | PARTIALLY_FAILED | SUCCEEDED

Required: No

LatestMetadataSyncStatusMessage

This is the most recent status for the indicated metadata sync.

Type: String

Required: No

LogGroupArn

The Amazon Resource Name (ARN) of the group of gateways within the requested log.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `$|^arn:(aws|aws-cn|aws-us-gov):logs:([a-zA-Z0-9-]+):([0-9]+):log-group:[a-zA-Z0-9_\-\/\.]+:\*`

Required: No

Name

This is the name of the specified hypervisor.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[a-zA-Z0-9-]*`

Required: No

State

This is the current state of the specified hypervisor.

The possible states are PENDING, ONLINE, OFFLINE, or ERROR.

Type: String

Valid Values: PENDING | ONLINE | OFFLINE | ERROR

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MaintenanceStartTime

This is your gateway's weekly maintenance start time including the day and time of the week. Note that values are in terms of the gateway's time zone. Can be weekly or monthly.

Contents

HourOfDay

The hour component of the maintenance start time represented as *hh*, where *hh* is the hour (0 to 23). The hour of the day is in the time zone of the gateway.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 23.

Required: Yes

MinuteOfHour

The minute component of the maintenance start time represented as *mm*, where *mm* is the minute (0 to 59). The minute of the hour is in the time zone of the gateway.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 59.

Required: Yes

DayOfMonth

The day of the month component of the maintenance start time represented as an ordinal number from 1 to 28, where 1 represents the first day of the month and 28 represents the last day of the month.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 31.

Required: No

DayOfWeek

An ordinal number between 0 and 6 that represents the day of the week, where 0 represents Sunday and 6 represents Saturday. The day of week is in the time zone of the gateway.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 6.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

A key-value pair you can use to manage, filter, and search for your resources. Allowed characters include UTF-8 letters, numbers, and the following characters: + - = . _ : /. Spaces are not allowed in tag values.

Contents

Key

The key part of a tag's key-value pair. The key can't start with `aws :`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `( [\p{L}\p{Z}\p{N}_.: /+=\ -@] * )`

Required: Yes

Value

The value part of a tag's key-value pair.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[^\x00]*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualMachine

A virtual machine that is on a hypervisor.

Contents

HostName

The host name of the virtual machine.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9-]*

Required: No

HypervisorId

The ID of the virtual machine's hypervisor.

Type: String

Required: No

LastBackupDate

The most recent date a virtual machine was backed up, in Unix format and UTC time.

Type: Timestamp

Required: No

Name

The name of the virtual machine.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9-]*

Required: No

Path

The path of the virtual machine.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `[^\x00]+`

Required: No

ResourceArn

The Amazon Resource Name (ARN) of the virtual machine. For example, `arn:aws:backup-gateway:us-west-1:0000000000000000:vm/vm-0000ABCDEFGHIJKL`.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3}){3}\/[a-zA-Z-0-9]{3}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualMachineDetails

Your VirtualMachine objects, ordered by their Amazon Resource Names (ARNs).

Contents

HostName

The host name of the virtual machine.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9-]*

Required: No

HypervisorId

The ID of the virtual machine's hypervisor.

Type: String

Required: No

LastBackupDate

The most recent date a virtual machine was backed up, in Unix format and UTC time.

Type: Timestamp

Required: No

Name

The name of the virtual machine.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9-]*

Required: No

Path

The path of the virtual machine.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `[^\x00]+`

Required: No

ResourceArn

The Amazon Resource Name (ARN) of the virtual machine. For example, `arn:aws:backup-gateway:us-west-1:0000000000000000:vm/vm-0000ABCDEFGHIJKL`.

Type: String

Length Constraints: Minimum length of 50. Maximum length of 500.

Pattern: `arn:(aws|aws-cn|aws-us-gov):backup-gateway(:[a-zA-Z-0-9]{3}){3}\/[a-zA-Z-0-9]{3}`

Required: No

VmwareTags

These are the details of the VMware tags associated with the specified virtual machine.

Type: Array of [VmwareTag](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VmwareTag

A VMware tag is a tag attached to a specific virtual machine. A [tag](#) is a key-value pair you can use to manage, filter, and search for your resources.

The content of VMware tags can be matched to AWS tags.

Contents

VmwareCategory

This is the category of VMware.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 80.

Required: No

VmwareTagDescription

This is a user-defined description of a VMware tag.

Type: String

Required: No

VmwareTagName

This is the user-defined name of a VMware tag.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 80.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VmwareToAwsTagMapping

This displays the mapping of VMware tags to the corresponding AWS tags.

Contents

AwsTagKey

The key part of the AWS tag's key-value pair.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ([\p{L}\p{Z}\p{N}_ . : / = + \ - @] *)

Required: Yes

AwsTagValue

The value part of the AWS tag's key-value pair.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: [^ \ x 0 0] *

Required: Yes

VmwareCategory

The is the category of VMware.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 80.

Required: Yes

VmwareTagName

This is the user-defined name of a VMware tag.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 80.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Error Types

This section lists common error types that this AWS service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

IncompleteSignature

The request signature doesn't conform to AWS standards. Verify that you're using valid AWS credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 403

InternalFailure

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact AWS Support.

HTTP Status Code: 500

MalformedHttpRequestException

The request body can't be processed. This typically happens when the request body can't be decompressed using the specified content encoding algorithm. Verify that the content encoding header matches the compression format used.

HTTP Status Code: 400

NotAuthorized

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

OptInRequired

Your AWS account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

RequestAbortedException

The request was aborted before a response could be returned. This typically happens when the client closes the connection.

HTTP Status Code: 400

RequestEntityTooLargeException

The request entity is too large. Reduce the size of the request body and try again.

HTTP Status Code: 413

RequestTimeoutException

The request timed out. The server didn't receive the complete request within the expected time frame. Try again.

HTTP Status Code: 408

ServiceUnavailable

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

ThrottlingException

Your request rate is too high. The AWS SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

UnknownOperationException

The action or operation isn't recognized. Verify that the action name is spelled correctly and that it's supported by the API version you're using.

HTTP Status Code: 404

UnrecognizedClientException

The X.509 certificate or AWS access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

ValidationError

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400