



API Reference

AWS Billing Conductor



API Version 2021-07-30

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS Billing Conductor: API Reference

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
AssociateAccounts	4
Request Syntax	4
URI Request Parameters	4
Request Body	4
Response Syntax	5
Response Elements	5
Errors	5
See Also	7
AssociatePricingRules	9
Request Syntax	9
URI Request Parameters	9
Request Body	9
Response Syntax	10
Response Elements	10
Errors	10
See Also	12
BatchAssociateResourcesToCustomLineItem	14
Request Syntax	14
URI Request Parameters	14
Request Body	14
Response Syntax	15
Response Elements	15
Errors	16
See Also	18
BatchDisassociateResourcesFromCustomLineItem	19
Request Syntax	19
URI Request Parameters	19
Request Body	19
Response Syntax	20
Response Elements	20
Errors	21
See Also	22

CreateBillingGroup	24
Request Syntax	24
URI Request Parameters	24
Request Body	25
Response Syntax	26
Response Elements	26
Errors	27
See Also	28
CreateCustomLineItem	30
Request Syntax	30
URI Request Parameters	31
Request Body	31
Response Syntax	33
Response Elements	33
Errors	34
Examples	36
See Also	36
CreatePricingPlan	38
Request Syntax	38
URI Request Parameters	38
Request Body	38
Response Syntax	40
Response Elements	40
Errors	40
See Also	42
CreatePricingRule	44
Request Syntax	44
URI Request Parameters	44
Request Body	45
Response Syntax	48
Response Elements	48
Errors	48
See Also	50
DeleteBillingGroup	51
Request Syntax	51
URI Request Parameters	51

Request Body	51
Response Syntax	51
Response Elements	52
Errors	52
See Also	53
DeleteCustomLineItem	54
Request Syntax	54
URI Request Parameters	54
Request Body	54
Response Syntax	55
Response Elements	55
Errors	55
See Also	56
DeletePricingPlan	58
Request Syntax	58
URI Request Parameters	58
Request Body	58
Response Syntax	58
Response Elements	59
Errors	59
See Also	60
DeletePricingRule	62
Request Syntax	62
URI Request Parameters	62
Request Body	62
Response Syntax	62
Response Elements	63
Errors	63
See Also	64
DisassociateAccounts	66
Request Syntax	66
URI Request Parameters	66
Request Body	66
Response Syntax	67
Response Elements	67
Errors	67

See Also	69
DisassociatePricingRules	70
Request Syntax	70
URI Request Parameters	70
Request Body	70
Response Syntax	71
Response Elements	71
Errors	71
See Also	73
GetBillingGroupCostReport	74
Request Syntax	74
URI Request Parameters	74
Request Body	74
Response Syntax	75
Response Elements	76
Errors	76
See Also	78
ListAccountAssociations	79
Request Syntax	79
URI Request Parameters	79
Request Body	79
Response Syntax	80
Response Elements	80
Errors	81
See Also	82
ListBillingGroupCostReports	83
Request Syntax	83
URI Request Parameters	83
Request Body	83
Response Syntax	84
Response Elements	84
Errors	85
See Also	86
ListBillingGroups	87
Request Syntax	87
URI Request Parameters	87

Request Body	87
Response Syntax	88
Response Elements	89
Errors	89
See Also	91
ListCustomLineItems	92
Request Syntax	92
URI Request Parameters	92
Request Body	92
Response Syntax	93
Response Elements	94
Errors	95
See Also	96
ListCustomLineItemVersions	97
Request Syntax	97
URI Request Parameters	97
Request Body	97
Response Syntax	98
Response Elements	99
Errors	100
See Also	101
ListPricingPlans	102
Request Syntax	102
URI Request Parameters	102
Request Body	102
Response Syntax	103
Response Elements	103
Errors	104
See Also	105
ListPricingPlansAssociatedWithPricingRule	106
Request Syntax	106
URI Request Parameters	106
Request Body	106
Response Syntax	107
Response Elements	107
Errors	108

See Also	109
ListPricingRules	111
Request Syntax	111
URI Request Parameters	111
Request Body	111
Response Syntax	112
Response Elements	113
Errors	113
See Also	114
ListPricingRulesAssociatedToPricingPlan	116
Request Syntax	116
URI Request Parameters	116
Request Body	116
Response Syntax	117
Response Elements	117
Errors	118
See Also	119
ListResourcesAssociatedToCustomLineItem	121
Request Syntax	121
URI Request Parameters	121
Request Body	121
Response Syntax	122
Response Elements	123
Errors	123
See Also	125
ListTagsForResource	126
Request Syntax	126
URI Request Parameters	126
Request Body	126
Response Syntax	126
Response Elements	127
Errors	127
See Also	128
TagResource	130
Request Syntax	130
URI Request Parameters	130

Request Body	130
Response Syntax	131
Response Elements	131
Errors	131
See Also	132
UntagResource	134
Request Syntax	134
URI Request Parameters	134
Request Body	134
Response Syntax	135
Response Elements	135
Errors	135
See Also	136
UpdateBillingGroup	137
Request Syntax	137
URI Request Parameters	137
Request Body	137
Response Syntax	139
Response Elements	139
Errors	141
See Also	142
UpdateCustomLineItem	144
Request Syntax	144
URI Request Parameters	144
Request Body	144
Response Syntax	146
Response Elements	146
Errors	148
See Also	149
UpdatePricingPlan	151
Request Syntax	151
URI Request Parameters	151
Request Body	151
Response Syntax	152
Response Elements	152
Errors	153

See Also	155
UpdatePricingRule	156
Request Syntax	156
URI Request Parameters	156
Request Body	156
Response Syntax	158
Response Elements	158
Errors	161
See Also	162
Data Types	164
AccountAssociationsListElement	166
Contents	166
See Also	167
AccountGrouping	168
Contents	168
See Also	169
AssociateResourceError	170
Contents	170
See Also	170
AssociateResourceResponseElement	171
Contents	171
See Also	171
Attribute	172
Contents	172
See Also	172
BillingGroupCostReportElement	173
Contents	173
See Also	174
BillingGroupCostReportResultElement	175
Contents	175
See Also	176
BillingGroupListElement	177
Contents	177
See Also	179
BillingPeriodRange	180
Contents	180

See Also	180
ComputationPreference	181
Contents	181
See Also	181
CreateFreeTierConfig	182
Contents	182
See Also	182
CreateTieringInput	183
Contents	183
See Also	183
CustomLineItemBillingPeriodRange	184
Contents	184
See Also	184
CustomLineItemChargeDetails	185
Contents	185
See Also	186
CustomLineItemFlatChargeDetails	187
Contents	187
See Also	187
CustomLineItemListElement	188
Contents	188
See Also	191
CustomLineItemPercentageChargeDetails	192
Contents	192
See Also	192
CustomLineItemVersionListElement	193
Contents	193
See Also	196
DisassociateResourceResponseElement	197
Contents	197
See Also	197
FreeTierConfig	198
Contents	198
See Also	198
LineItemFilter	199
Contents	199

See Also	200
ListAccountAssociationsFilter	201
Contents	201
See Also	202
ListBillingGroupAccountGrouping	203
Contents	203
See Also	203
ListBillingGroupCostReportsFilter	204
Contents	204
See Also	204
ListBillingGroupsFilter	205
Contents	205
See Also	207
ListCustomLineItemChargeDetails	208
Contents	208
See Also	209
ListCustomLineItemFlatChargeDetails	210
Contents	210
See Also	210
ListCustomLineItemPercentageChargeDetails	211
Contents	211
See Also	211
ListCustomLineItemsFilter	212
Contents	212
See Also	213
ListCustomLineItemVersionsBillingPeriodRangeFilter	214
Contents	214
See Also	214
ListCustomLineItemVersionsFilter	215
Contents	215
See Also	215
ListPricingPlansFilter	216
Contents	216
See Also	216
ListPricingRulesFilter	217
Contents	217

See Also	217
ListResourcesAssociatedToCustomLineItemFilter	218
Contents	218
See Also	218
ListResourcesAssociatedToCustomLineItemResponseElement	219
Contents	219
See Also	219
PresentationObject	221
Contents	221
See Also	221
PricingPlanListElement	222
Contents	222
See Also	223
PricingRuleListElement	224
Contents	224
See Also	227
StringSearch	228
Contents	228
See Also	228
Tiering	229
Contents	229
See Also	229
UpdateBillingGroupAccountGrouping	230
Contents	230
See Also	230
UpdateCustomLineItemChargeDetails	231
Contents	231
See Also	231
UpdateCustomLineItemFlatChargeDetails	233
Contents	233
See Also	233
UpdateCustomLineItemPercentageChargeDetails	234
Contents	234
See Also	234
UpdateFreeTierConfig	235
Contents	235

See Also	235
UpdateTieringInput	236
Contents	236
See Also	236
ValidationExceptionField	237
Contents	237
See Also	237
Common Parameters	238
Common Error Types	241

Welcome

AWS Billing Conductor is a fully managed service that you can use to customize a [pro forma](#) version of your billing data each month, to accurately show or chargeback your end customers. AWS Billing Conductor doesn't change the way you're billed by AWS each month by design. Instead, it provides you with a mechanism to configure, generate, and display rates to certain customers over a given billing period. You can also analyze the difference between the rates you apply to your accounting groupings relative to your actual rates from AWS. As a result of your Billing Conductor configuration, the payer account can also see the custom rate applied on the billing details page of the [Billing console](#), or configure a cost and usage report per billing group.

This documentation shows how you can configure Billing Conductor by using its API. For more information about using the [Billing Conductor](#) user interface, see the [AWS Billing Conductor User Guide](#).

This document was last published on May 21, 2026.

Actions

The following actions are supported:

- [AssociateAccounts](#)
- [AssociatePricingRules](#)
- [BatchAssociateResourcesToCustomLineItem](#)
- [BatchDisassociateResourcesFromCustomLineItem](#)
- [CreateBillingGroup](#)
- [CreateCustomLineItem](#)
- [CreatePricingPlan](#)
- [CreatePricingRule](#)
- [DeleteBillingGroup](#)
- [DeleteCustomLineItem](#)
- [DeletePricingPlan](#)
- [DeletePricingRule](#)
- [DisassociateAccounts](#)
- [DisassociatePricingRules](#)
- [GetBillingGroupCostReport](#)
- [ListAccountAssociations](#)
- [ListBillingGroupCostReports](#)
- [ListBillingGroups](#)
- [ListCustomLineItems](#)
- [ListCustomLineItemVersions](#)
- [ListPricingPlans](#)
- [ListPricingPlansAssociatedWithPricingRule](#)
- [ListPricingRules](#)
- [ListPricingRulesAssociatedToPricingPlan](#)
- [ListResourcesAssociatedToCustomLineItem](#)
- [ListTagsForResource](#)
- [TagResource](#)

- [UntagResource](#)
- [UpdateBillingGroup](#)
- [UpdateCustomLineItem](#)
- [UpdatePricingPlan](#)
- [UpdatePricingRule](#)

AssociateAccounts

Connects an array of account IDs in a consolidated billing family to a predefined billing group. The account IDs must be a part of the consolidated billing family during the current month, and not already associated with another billing group. The maximum number of accounts that can be associated in one call is 30.

Request Syntax

```
POST /associate-accounts HTTP/1.1
Content-type: application/json

{
  "AccountIds": [ "string" ],
  "Arn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

AccountIds

The associating array of account IDs.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 30 items.

Pattern: [0-9]{12}

Required: Yes

Arn

The Amazon Resource Name (ARN) of the billing group that associates the array of account IDs.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:billinggroup/)?[a-zA-Z0-9]{10,12}

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the billing group that associates the array of account IDs.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:billinggroup/)?[a-zA-Z0-9]{10,12}

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

You can cause an inconsistent state by updating or deleting a resource.

Reason

Reason for the inconsistent state.

ResourceId

Identifier of the resource in use.

ResourceType

Type of the resource in use.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

ResourceId

Resource identifier that was not found.

ResourceType

Resource type that was not found.

HTTP Status Code: 404

ServiceLimitExceededException

The request would cause a service limit to exceed.

LimitCode

The unique code identifier of the service limit that is being exceeded.

ResourceId

Identifier of the resource affected.

ResourceType

Type of the resource affected.

ServiceCode

The unique code for the service of the limit that is being exceeded.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

AssociatePricingRules

Connects an array of `PricingRuleArns` to a defined `PricingPlan`. The maximum number `PricingRuleArn` that can be associated in one call is 30.

Request Syntax

```
PUT /associate-pricing-rules HTTP/1.1
Content-type: application/json
```

```
{
  "Arn": "string",
  "PricingRuleArns": [ "string" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Arn

The `PricingPlanArn` that the `PricingRuleArns` are associated with.

Type: String

Pattern: `(arn:aws(-cn)?:billingconductor::(aws|[0-9]{12}):pricingplan/)?(BasicPricingPlan|Passthrough|[a-zA-Z0-9]{10})`

Required: Yes

PricingRuleArns

The `PricingRuleArns` that are associated with the Pricing Plan.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 30 items.

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:pricingrule/)?[a-zA-Z0-9]{10}

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The PricingPlanArn that the PricingRuleArns are associated with.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::(aws|[0-9]{12}):pricingplan/)?
(BasicPricingPlan|Passthrough|[a-zA-Z0-9]{10})

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

You can cause an inconsistent state by updating or deleting a resource.

Reason

Reason for the inconsistent state.

ResourceId

Identifier of the resource in use.

ResourceType

Type of the resource in use.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

ResourceId

Resource identifier that was not found.

ResourceType

Resource type that was not found.

HTTP Status Code: 404

ServiceLimitExceededException

The request would cause a service limit to exceed.

LimitCode

The unique code identifier of the service limit that is being exceeded.

ResourceId

Identifier of the resource affected.

ResourceType

Type of the resource affected.

ServiceCode

The unique code for the service of the limit that is being exceeded.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

BatchAssociateResourcesToCustomLineItem

Associates a batch of resources to a percentage custom line item.

Request Syntax

```
PUT /batch-associate-resources-to-custom-line-item HTTP/1.1
Content-type: application/json

{
  "BillingPeriodRange": {
    "ExclusiveEndBillingPeriod": "string",
    "InclusiveStartBillingPeriod": "string"
  },
  "ResourceArns": [ "string" ],
  "TargetArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

BillingPeriodRange

The billing period range in which the custom line item request will be applied.

Type: [CustomLineItemBillingPeriodRange](#) object

Required: No

ResourceArns

A list containing the ARNs of the resources to be associated.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 30 items.

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:(customlineitem|billinggroup)/)?[a-zA-Z0-9]{10,12}

Required: Yes

TargetArn

A percentage custom line item ARN to associate the resources to.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:customlineitem/)?[a-zA-Z0-9]{10}

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "FailedAssociatedResources": [
    {
      "Arn": "string",
      "Error": {
        "Message": "string",
        "Reason": "string"
      }
    }
  ],
  "SuccessfullyAssociatedResources": [
    {
      "Arn": "string",
      "Error": {
        "Message": "string",
        "Reason": "string"
      }
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

FailedAssociatedResources

A list of `AssociateResourceResponseElement` for each resource that failed association to a percentage custom line item.

Type: Array of [AssociateResourceResponseElement](#) objects

SuccessfullyAssociatedResources

A list of `AssociateResourceResponseElement` for each resource that's been associated to a percentage custom line item successfully.

Type: Array of [AssociateResourceResponseElement](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

You can cause an inconsistent state by updating or deleting a resource.

Reason

Reason for the inconsistent state.

ResourceId

Identifier of the resource in use.

ResourceType

Type of the resource in use.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

ResourceId

Resource identifier that was not found.

ResourceType

Resource type that was not found.

HTTP Status Code: 404

ServiceLimitExceededException

The request would cause a service limit to exceed.

LimitCode

The unique code identifier of the service limit that is being exceeded.

ResourceId

Identifier of the resource affected.

ResourceType

Type of the resource affected.

ServiceCode

The unique code for the service of the limit that is being exceeded.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

BatchDisassociateResourcesFromCustomLineItem

Disassociates a batch of resources from a percentage custom line item.

Request Syntax

```
PUT /batch-disassociate-resources-from-custom-line-item HTTP/1.1
Content-type: application/json

{
  "BillingPeriodRange": {
    "ExclusiveEndBillingPeriod": "string",
    "InclusiveStartBillingPeriod": "string"
  },
  "ResourceArns": [ "string" ],
  "TargetArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

BillingPeriodRange

The billing period range in which the custom line item request will be applied.

Type: [CustomLineItemBillingPeriodRange](#) object

Required: No

ResourceArns

A list containing the ARNs of resources to be disassociated.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 30 items.

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:(customlineitem|billinggroup)/)?[a-zA-Z0-9]{10,12}

Required: Yes

TargetArn

A percentage custom line item ARN to disassociate the resources from.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:customlineitem/)?[a-zA-Z0-9]{10}

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "FailedDisassociatedResources": [
    {
      "Arn": "string",
      "Error": {
        "Message": "string",
        "Reason": "string"
      }
    }
  ],
  "SuccessfullyDisassociatedResources": [
    {
      "Arn": "string",
      "Error": {
        "Message": "string",
        "Reason": "string"
      }
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

FailedDisassociatedResources

A list of `DisassociateResourceResponseElement` for each resource that failed disassociation from a percentage custom line item.

Type: Array of [DisassociateResourceResponseElement](#) objects

SuccessfullyDisassociatedResources

A list of `DisassociateResourceResponseElement` for each resource that's been disassociated from a percentage custom line item successfully.

Type: Array of [DisassociateResourceResponseElement](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

You can cause an inconsistent state by updating or deleting a resource.

Reason

Reason for the inconsistent state.

ResourceId

Identifier of the resource in use.

ResourceType

Type of the resource in use.

HTTP Status Code: 409

InternalServerError

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

ResourceId

Resource identifier that was not found.

ResourceType

Resource type that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateBillingGroup

Creates a billing group that resembles a consolidated billing family that AWS charges, based off of the predefined pricing plan computation.

Request Syntax

```
POST /create-billing-group HTTP/1.1
X-Amzn-Client-Token: ClientToken
Content-type: application/json

{
  "AccountGrouping": {
    "AutoAssociate": boolean,
    "LinkedAccountIds": [ "string" ],
    "ResponsibilityTransferArn": "string"
  },
  "ComputationPreference": {
    "PricingPlanArn": "string"
  },
  "Description": "string",
  "Name": "string",
  "PrimaryAccountId": "string",
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

ClientToken

A unique, case-sensitive identifier that you specify to ensure idempotency of the request. Idempotency ensures that an API request completes no more than one time. With an idempotent request, if the original request completes successfully, any subsequent retries complete successfully without performing any further actions.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9-]+

Request Body

The request accepts the following data in JSON format.

AccountGrouping

The set of accounts that will be under the billing group. The set of accounts resemble the linked accounts in a consolidated billing family.

Type: [AccountGrouping](#) object

Required: Yes

ComputationPreference

The preferences and settings that will be used to compute the AWS charges for a billing group.

Type: [ComputationPreference](#) object

Required: Yes

Description

The description of the billing group.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

Name

The billing group name. The names must be unique.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_\\+=\\.\\-@]+`

Required: Yes

PrimaryAccountId

The account ID that serves as the main account in a billing group.

Type: String

Pattern: [0-9]{12}

Required: No

Tags

A map that contains tag keys and tag values that are attached to a billing group. This feature isn't available during the beta.

Type: String to string map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Arn](#)

The Amazon Resource Name (ARN) of the created billing group.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:billinggroup/)?[a-zA-Z0-9]{10,12}

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

You can cause an inconsistent state by updating or deleting a resource.

Reason

Reason for the inconsistent state.

ResourceId

Identifier of the resource in use.

ResourceType

Type of the resource in use.

HTTP Status Code: 409

InternalServerError

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ServiceLimitExceededException

The request would cause a service limit to exceed.

LimitCode

The unique code identifier of the service limit that is being exceeded.

ResourceId

Identifier of the resource affected.

ResourceType

Type of the resource affected.

ServiceCode

The unique code for the service of the limit that is being exceeded.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateCustomLineItem

Creates a custom line item that can be used to create a one-time fixed charge that can be applied to a single billing group for the current or previous billing period. The one-time fixed charge is either a fee or discount.

Request Syntax

```
POST /create-custom-line-item HTTP/1.1
```

```
X-Amzn-Client-Token: ClientToken
```

```
Content-type: application/json
```

```
{
  "AccountId": "string",
  "BillingGroupArn": "string",
  "BillingPeriodRange": {
    "ExclusiveEndBillingPeriod": "string",
    "InclusiveStartBillingPeriod": "string"
  },
  "ChargeDetails": {
    "Flat": {
      "ChargeValue": number
    },
    "LineItemFilters": [
      {
        "Attribute": "string",
        "AttributeValues": [ "string" ],
        "MatchOption": "string",
        "Values": [ "string" ]
      }
    ],
    "Percentage": {
      "AssociatedValues": [ "string" ],
      "PercentageValue": number
    },
    "Type": "string"
  },
  "ComputationRule": "string",
  "Description": "string",
  "Name": "string",
  "PresentationDetails": {
    "Service": "string"
  }
}
```

```
},
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

ClientToken

A unique, case-sensitive identifier that you specify to ensure idempotency of the request. Idempotency ensures that an API request completes no more than one time. With an idempotent request, if the original request completes successfully, any subsequent retries complete successfully without performing any further actions.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9-]+

Request Body

The request accepts the following data in JSON format.

AccountId

The AWS account in which this custom line item will be applied to.

Type: String

Pattern: [0-9]{12}

Required: No

BillingGroupArn

The Amazon Resource Name (ARN) that references the billing group where the custom line item applies to.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:billinggroup/)?[a-zA-Z0-9]{10,12}

Required: Yes

BillingPeriodRange

A time range for which the custom line item is effective.

Type: [CustomLineItemBillingPeriodRange](#) object

Required: No

ChargeDetails

A CustomLineItemChargeDetails that describes the charge details for a custom line item.

Type: [CustomLineItemChargeDetails](#) object

Required: Yes

ComputationRule

Specifies how the custom line item charges are computed.

Type: String

Valid Values: ITEMIZED | CONSOLIDATED

Required: No

Description

The description of the custom line item. This is shown on the Bills page in association with the charge value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Name

The name of the custom line item.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_+=\.\-@]+`

Required: Yes

PresentationDetails

Details controlling how the custom line item charges are presented in the bill. Contains specifications for which service the charges will be shown under.

Type: [PresentationObject](#) object

Required: No

Tags

A map that contains tag keys and tag values that are attached to a custom line item.

Type: String to string map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the created custom line item.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:customlineitem/)?[a-zA-Z0-9]{10}

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

You can cause an inconsistent state by updating or deleting a resource.

Reason

Reason for the inconsistent state.

ResourceId

Identifier of the resource in use.

ResourceType

Type of the resource in use.

HTTP Status Code: 409

InternalServerError

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ServiceLimitExceededException

The request would cause a service limit to exceed.

LimitCode

The unique code identifier of the service limit that is being exceeded.

ResourceId

Identifier of the resource affected.

ResourceType

Type of the resource affected.

ServiceCode

The unique code for the service of the limit that is being exceeded.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

Examples

The following example applies a custom line item to another linked account (55555555555) in the billing group.

This example illustrates one usage of `CreateCustomLineItem`.

Sample Request

```
POST /create-custom-line-item HTTP/1.1
X-Amzn-Client-Token: ClientToken
Content-type: application/json
{
  "BillingGroupArn":
  "arn:aws:billingconductor::123456789012:billinggroup/111122223333",
  "ChargeDetails": {
    "Flat": {
      "ChargeValue":10
    },
    "Type": "FEE"
  },
  "Description": "My custom line item",
  "Name": "MyCustomLineItem",
  "AccountId": "55555555555"
}
```

Sample Response

```
HTTP/1.1 200
Content-type: application/json
{
  "Arn": "arn:aws:billingconductor::123456789012:customlineitem/55555555555"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreatePricingPlan

Creates a pricing plan that is used for computing AWS charges for billing groups.

Request Syntax

```
POST /create-pricing-plan HTTP/1.1
X-Amzn-Client-Token: ClientToken
Content-type: application/json

{
  "Description": "string",
  "Name": "string",
  "PricingRuleArns": [ "string" ],
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

ClientToken

A unique, case-sensitive identifier that you specify to ensure idempotency of the request. Idempotency ensures that an API request completes no more than one time. With an idempotent request, if the original request completes successfully, any subsequent retries complete successfully without performing any further actions.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9-]+

Request Body

The request accepts the following data in JSON format.

Description

The description of the pricing plan.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

Name

The name of the pricing plan. The names must be unique to each pricing plan.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_+=\.\\-@]+`

Required: Yes

PricingRuleArns

A list of Amazon Resource Names (ARNs) that define the pricing plan parameters.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 30 items.

Pattern: `(arn:aws(-cn)?:billingconductor::[0-9]{12}:pricingrule/)?[a-zA-Z0-9]{10}`

Required: No

Tags

A map that contains tag keys and tag values that are attached to a pricing plan.

Type: String to string map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the created pricing plan.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::(aws|[0-9]{12}):pricingplan/)?
(BasicPricingPlan|Passthrough|[a-zA-Z0-9]{10})

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

You can cause an inconsistent state by updating or deleting a resource.

Reason

Reason for the inconsistent state.

ResourceId

Identifier of the resource in use.

ResourceType

Type of the resource in use.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

ResourceId

Resource identifier that was not found.

ResourceType

Resource type that was not found.

HTTP Status Code: 404

ServiceLimitExceededException

The request would cause a service limit to exceed.

LimitCode

The unique code identifier of the service limit that is being exceeded.

ResourceId

Identifier of the resource affected.

ResourceType

Type of the resource affected.

ServiceCode

The unique code for the service of the limit that is being exceeded.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreatePricingRule

Creates a pricing rule can be associated to a pricing plan, or a set of pricing plans.

Request Syntax

```
POST /create-pricing-rule HTTP/1.1
X-Amzn-Client-Token: ClientToken
Content-type: application/json
```

```
{
  "BillingEntity": "string",
  "Description": "string",
  "ModifierPercentage": number,
  "Name": "string",
  "Operation": "string",
  "Scope": "string",
  "Service": "string",
  "Tags": {
    "string" : "string"
  },
  "Tiering": {
    "FreeTier": {
      "Activated": boolean
    }
  },
  "Type": "string",
  "UsageType": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

ClientToken

A unique, case-sensitive identifier that you specify to ensure idempotency of the request. Idempotency ensures that an API request completes no more than one time. With an idempotent request, if the original request completes successfully, any subsequent retries complete successfully without performing any further actions.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9-]+

Request Body

The request accepts the following data in JSON format.

BillingEntity

The seller of services provided by AWS, their affiliates, or third-party providers selling services via AWS Marketplace.

Type: String

Pattern: [a-zA-Z0-9()]+

Required: No

Description

The pricing rule description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

ModifierPercentage

A percentage modifier that's applied on the public pricing rates. Your entry will be rounded to the nearest 2 decimal places.

Type: Double

Valid Range: Minimum value of 0.

Required: No

Name

The pricing rule name. The names must be unique to each pricing rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_+=\.\-@]+`

Required: Yes

Operation

Operation is the specific AWS action covered by this line item. This describes the specific usage of the line item.

If the Scope attribute is set to SKU, this attribute indicates which operation the `PricingRule` is modifying. For example, a value of `RunInstances:0202` indicates the operation of running an Amazon EC2 instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `\S+`

Required: No

Scope

The scope of pricing rule that indicates if it's globally applicable, or it's service-specific.

Type: String

Valid Values: GLOBAL | SERVICE | BILLING_ENTITY | SKU

Required: Yes

Service

If the Scope attribute is set to SERVICE or SKU, the attribute indicates which service the `PricingRule` is applicable for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9]+`

Required: No

Tags

A map that contains tag keys and tag values that are attached to a pricing rule.

Type: String to string map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Tiering

The set of tiering configurations for the pricing rule.

Type: [CreateTieringInput](#) object

Required: No

Type

The type of pricing rule.

Type: String

Valid Values: MARKUP | DISCOUNT | TIERING

Required: Yes

UsageType

Usage type is the unit that each service uses to measure the usage of a specific type of resource.

If the Scope attribute is set to SKU, this attribute indicates which usage type the PricingRule is modifying. For example, USW2-BoxUsage:m2.2xlarge describes an M2 High Memory Double Extra Large instance in the US West (Oregon) Region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: \S+

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the created pricing rule.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:pricingrule/)?[a-zA-Z0-9]{10}

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

You can cause an inconsistent state by updating or deleting a resource.

Reason

Reason for the inconsistent state.

ResourceId

Identifier of the resource in use.

ResourceType

Type of the resource in use.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ServiceLimitExceededException

The request would cause a service limit to exceed.

LimitCode

The unique code identifier of the service limit that is being exceeded.

ResourceId

Identifier of the resource affected.

ResourceType

Type of the resource affected.

ServiceCode

The unique code for the service of the limit that is being exceeded.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteBillingGroup

Deletes a billing group.

Request Syntax

```
POST /delete-billing-group HTTP/1.1
Content-type: application/json
```

```
{
  "Arn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Arn

The Amazon Resource Name (ARN) of the billing group that you're deleting.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:billinggroup/)?[a-zA-Z0-9]{10,12}

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "Arn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the deleted billing group.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:billinggroup/)?[a-zA-Z0-9]{10,12}

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteCustomLineItem

Deletes the custom line item identified by the given ARN in the current, or previous billing period.

Request Syntax

```
POST /delete-custom-line-item HTTP/1.1
Content-type: application/json

{
  "Arn": "string",
  "BillingPeriodRange": {
    "ExclusiveEndBillingPeriod": "string",
    "InclusiveStartBillingPeriod": "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Arn

The ARN of the custom line item to be deleted.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:customlineitem/)?[a-zA-Z0-9]{10}

Required: Yes

BillingPeriodRange

The billing period range in which the custom line item request will be applied.

Type: [CustomLineItemBillingPeriodRange](#) object

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The ARN of the deleted custom line item.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:customlineitem/)?[a-zA-Z0-9]{10}

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

You can cause an inconsistent state by updating or deleting a resource.

Reason

Reason for the inconsistent state.

ResourceId

Identifier of the resource in use.

ResourceType

Type of the resource in use.

HTTP Status Code: 409

InternalServerError

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeletePricingPlan

Deletes a pricing plan. The pricing plan must not be associated with any billing groups to delete successfully.

Request Syntax

```
POST /delete-pricing-plan HTTP/1.1
Content-type: application/json

{
  "Arn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Arn

The Amazon Resource Name (ARN) of the pricing plan that you're deleting.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::(aws|[0-9]{12}):pricingplan/)?
(BasicPricingPlan|Passthrough|[a-zA-Z0-9]{10})

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string"
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the deleted pricing plan.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::(aws|[0-9]{12}):pricingplan/)?
(BasicPricingPlan|Passthrough|[a-zA-Z0-9]{10})

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

You can cause an inconsistent state by updating or deleting a resource.

Reason

Reason for the inconsistent state.

ResourceId

Identifier of the resource in use.

ResourceType

Type of the resource in use.

HTTP Status Code: 409

InternalServerError

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeletePricingRule

Deletes the pricing rule that's identified by the input Amazon Resource Name (ARN).

Request Syntax

```
POST /delete-pricing-rule HTTP/1.1
Content-type: application/json
```

```
{
  "Arn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Arn

The Amazon Resource Name (ARN) of the pricing rule that you are deleting.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:pricingrule/)?[a-zA-Z0-9]{10}

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "Arn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the deleted pricing rule.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:pricingrule/)?[a-zA-Z0-9]{10}

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

You can cause an inconsistent state by updating or deleting a resource.

Reason

Reason for the inconsistent state.

ResourceId

Identifier of the resource in use.

ResourceType

Type of the resource in use.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisassociateAccounts

Removes the specified list of account IDs from the given billing group.

Request Syntax

```
POST /disassociate-accounts HTTP/1.1
Content-type: application/json
```

```
{
  "AccountIds": [ "string" ],
  "Arn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

AccountIds

The array of account IDs to disassociate.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 30 items.

Pattern: [0-9]{12}

Required: Yes

Arn

The Amazon Resource Name (ARN) of the billing group that the array of account IDs will disassociate from.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:billinggroup/)?[a-zA-Z0-9]{10,12}

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the billing group that the array of account IDs is disassociated from.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:billinggroup/)?[a-zA-Z0-9]{10,12}

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

You can cause an inconsistent state by updating or deleting a resource.

Reason

Reason for the inconsistent state.

ResourceId

Identifier of the resource in use.

ResourceType

Type of the resource in use.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

ResourceId

Resource identifier that was not found.

ResourceType

Resource type that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisassociatePricingRules

Disassociates a list of pricing rules from a pricing plan.

Request Syntax

```
PUT /disassociate-pricing-rules HTTP/1.1
Content-type: application/json

{
  "Arn": "string",
  "PricingRuleArns": [ "string" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Arn

The pricing plan Amazon Resource Name (ARN) to disassociate pricing rules from.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::(aws|[0-9]{12}):pricingplan/)?
(BasicPricingPlan|Passthrough|[a-zA-Z0-9]{10})

Required: Yes

PricingRuleArns

A list containing the Amazon Resource Name (ARN) of the pricing rules that will be disassociated.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 30 items.

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:pricingrule/)?[a-zA-Z0-9]{10}

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the pricing plan that the pricing rules successfully disassociated from.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::(aws|[0-9]{12}):pricingplan/)?(BasicPricingPlan|Passthrough|[a-zA-Z0-9]{10})

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

You can cause an inconsistent state by updating or deleting a resource.

Reason

Reason for the inconsistent state.

ResourceId

Identifier of the resource in use.

ResourceType

Type of the resource in use.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

ResourceId

Resource identifier that was not found.

ResourceType

Resource type that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetBillingGroupCostReport

Retrieves the margin summary report, which includes the AWS cost and charged amount (pro forma cost) by AWS service for a specific billing group.

Request Syntax

```
POST /get-billing-group-cost-report HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "Arn": "string",
  "BillingPeriodRange": {
    "ExclusiveEndBillingPeriod": "string",
    "InclusiveStartBillingPeriod": "string"
  },
  "GroupBy": [ "string" ],
  "MaxResults": number,
  "NextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Arn

The Amazon Resource Number (ARN) that uniquely identifies the billing group.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:billinggroup/)?[a-zA-Z0-9]{10,12}

Required: Yes

BillingPeriodRange

A time range for which the margin summary is effective. You can specify up to 12 months.

Type: [BillingPeriodRange](#) object

Required: No

[GroupBy](#)

A list of strings that specify the attributes that are used to break down costs in the margin summary reports for the billing group. For example, you can view your costs by the AWS service name or the billing period.

Type: Array of strings

Valid Values: PRODUCT_NAME | BILLING_PERIOD

Required: No

[MaxResults](#)

The maximum number of margin summary reports to retrieve.

Type: Integer

Valid Range: Minimum value of 200. Maximum value of 300.

Required: No

[NextToken](#)

The pagination token used on subsequent calls to get reports.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "BillingGroupCostReportResults": [
    {
      "Arn": "string",
```

```
    "Attributes": [  
      {  
        "Key": "string",  
        "Value": "string"  
      }  
    ],  
    "AWSCost": "string",  
    "Currency": "string",  
    "Margin": "string",  
    "MarginPercentage": "string",  
    "ProformaCost": "string"  
  }  
],  
"NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

BillingGroupCostReportResults

The list of margin summary reports.

Type: Array of [BillingGroupCostReportResultElement](#) objects

NextToken

The pagination token used on subsequent calls to get reports.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

ResourceId

Resource identifier that was not found.

ResourceType

Resource type that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAccountAssociations

This is a paginated call to list linked accounts that are linked to the payer account for the specified time period. If no information is provided, the current billing period is used. The response will optionally include the billing group that's associated with the linked account.

Request Syntax

```
POST /list-account-associations HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "BillingPeriod": "string",
  "Filters": {
    "AccountId": "string",
    "AccountIds": [ "string" ],
    "Association": "string"
  },
  "NextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

BillingPeriod

The preferred billing period to get account associations.

Type: String

Pattern: `\d{4}-(0?[1-9]|1[012])`

Required: No

Filters

The filter on the account ID of the linked account, or any of the following:

MONITORED: linked accounts that are associated to billing groups.

UNMONITORED: linked accounts that aren't associated to billing groups.

Billing Group Arn: linked accounts that are associated to the provided billing group Arn.

Type: [ListAccountAssociationsFilter](#) object

Required: No

[NextToken](#)

The pagination token that's used on subsequent calls to retrieve accounts.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "LinkedAccounts": [
    {
      "AccountEmail": "string",
      "AccountId": "string",
      "AccountName": "string",
      "BillingGroupArn": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[LinkedAccounts](#)

The list of linked accounts in the payer account.

Type: Array of [AccountAssociationsListElement](#) objects

NextToken

The pagination token that's used on subsequent calls to get accounts.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

ResourceId

Resource identifier that was not found.

ResourceType

Resource type that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListBillingGroupCostReports

A paginated call to retrieve a summary report of actual AWS charges and the calculated AWS charges based on the associated pricing plan of a billing group.

Request Syntax

```
POST /list-billing-group-cost-reports HTTP/1.1
Content-type: application/json

{
  "BillingPeriod": "string",
  "Filters": {
    "BillingGroupArns": [ "string" ]
  },
  "MaxResults": number,
  "NextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

BillingPeriod

The preferred billing period for your report.

Type: String

Pattern: `\d{4}-(0?[1-9]|1[012])`

Required: No

Filters

A `ListBillingGroupCostReportsFilter` to specify billing groups to retrieve reports from.

Type: [ListBillingGroupCostReportsFilter](#) object

Required: No

MaxResults

The maximum number of reports to retrieve.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The pagination token that's used on subsequent calls to get reports.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "BillingGroupCostReports": [
    {
      "Arn": "string",
      "AWSCost": "string",
      "Currency": "string",
      "Margin": "string",
      "MarginPercentage": "string",
      "ProformaCost": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

BillingGroupCostReports

A list of `BillingGroupCostReportElement` retrieved.

Type: Array of [BillingGroupCostReportElement](#) objects

NextToken

The pagination token that's used on subsequent calls to get reports.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

ResourceId

Resource identifier that was not found.

ResourceType

Resource type that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListBillingGroups

A paginated call to retrieve a list of billing groups for the given billing period. If you don't provide a billing group, the current billing period is used.

Request Syntax

```
POST /list-billing-groups HTTP/1.1
Content-type: application/json

{
  "BillingPeriod": "string",
  "Filters": {
    "Arns": [ "string" ],
    "AutoAssociate": boolean,
    "BillingGroupTypes": [ "string" ],
    "Names": [
      {
        "SearchOption": "string",
        "SearchValue": "string"
      }
    ],
    "PricingPlan": "string",
    "PrimaryAccountIds": [ "string" ],
    "ResponsibilityTransferArns": [ "string" ],
    "Statuses": [ "string" ]
  },
  "MaxResults": number,
  "NextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

BillingPeriod

The preferred billing period to get billing groups.

Type: String

Pattern: `\d{4}-(0?[1-9]|1[012])`

Required: No

Filters

A `ListBillingGroupsFilter` that specifies the billing group and pricing plan to retrieve billing group information.

Type: [ListBillingGroupsFilter](#) object

Required: No

MaxResults

The maximum number of billing groups to retrieve.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The pagination token that's used on subsequent calls to get billing groups.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "BillingGroups": [
    {
      "AccountGrouping": {
        "AutoAssociate": boolean,
        "ResponsibilityTransferArn": "string"
      },

```

```
    "Arn": "string",
    "BillingGroupType": "string",
    "ComputationPreference": {
      "PricingPlanArn": "string"
    },
    "CreationTime": number,
    "Description": "string",
    "LastModifiedTime": number,
    "Name": "string",
    "PrimaryAccountId": "string",
    "Size": number,
    "Status": "string",
    "StatusReason": "string"
  }
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

BillingGroups

A list of `BillingGroupListElement` retrieved.

Type: Array of [BillingGroupListElement](#) objects

NextToken

The pagination token that's used on subsequent calls to get billing groups.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

ResourceId

Resource identifier that was not found.

ResourceType

Resource type that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListCustomLineItems

A paginated call to get a list of all custom line items (FFLIs) for the given billing period. If you don't provide a billing period, the current billing period is used.

Request Syntax

```
POST /list-custom-line-items HTTP/1.1
Content-type: application/json

{
  "BillingPeriod": "string",
  "Filters": {
    "AccountIds": [ "string" ],
    "Arns": [ "string" ],
    "BillingGroups": [ "string" ],
    "Names": [ "string" ]
  },
  "MaxResults": number,
  "NextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

BillingPeriod

The preferred billing period to get custom line items (FFLIs).

Type: String

Pattern: `\d{4}-(0?[1-9]|1[012])`

Required: No

Filters

A `ListCustomLineItemsFilter` that specifies the custom line item names and/or billing group Amazon Resource Names (ARNs) to retrieve FFLI information.

Type: [ListCustomLineItemsFilter](#) object

Required: No

MaxResults

The maximum number of billing groups to retrieve.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The pagination token that's used on subsequent calls to get custom line items (FFLIs).

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CustomLineItems": [
    {
      "AccountId": "string",
      "Arn": "string",
      "AssociationSize": number,
      "BillingGroupArn": "string",
      "ChargeDetails": {
        "Flat": {
          "ChargeValue": number
        },
        "LineItemFilters": [
```

```

    {
      "Attribute": "string",
      "AttributeValues": [ "string" ],
      "MatchOption": "string",
      "Values": [ "string" ]
    }
  ],
  "Percentage": {
    "PercentageValue": number
  },
  "Type": "string"
},
"ComputationRule": "string",
"CreationTime": number,
"CurrencyCode": "string",
"Description": "string",
"LastModifiedTime": number,
"Name": "string",
"PresentationDetails": {
  "Service": "string"
},
"ProductCode": "string"
}
],
"NextToken": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CustomLineItems

A list of FreeFormLineItemListElements received.

Type: Array of [CustomLineItemListElement](#) objects

NextToken

The pagination token that's used on subsequent calls to get custom line items (FFLIs).

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

ResourceId

Resource identifier that was not found.

ResourceType

Resource type that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListCustomLineItemVersions

A paginated call to get a list of all custom line item versions.

Request Syntax

```
POST /list-custom-line-item-versions HTTP/1.1
Content-type: application/json
```

```
{
  "Arn": "string",
  "Filters": {
    "BillingPeriodRange": {
      "EndBillingPeriod": "string",
      "StartBillingPeriod": "string"
    }
  },
  "MaxResults": number,
  "NextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Arn

The Amazon Resource Name (ARN) for the custom line item.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:customlineitem/)?[a-zA-Z0-9]{10}

Required: Yes

Filters

A `ListCustomLineItemVersionsFilter` that specifies the billing period range in which the custom line item versions are applied.

Type: [ListCustomLineItemVersionsFilter](#) object

Required: No

MaxResults

The maximum number of custom line item versions to retrieve.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The pagination token that's used on subsequent calls to retrieve custom line item versions.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CustomLineItemVersions": [
    {
      "AccountId": "string",
      "Arn": "string",
      "AssociationSize": number,
      "BillingGroupArn": "string",
      "ChargeDetails": {
        "Flat": {
          "ChargeValue": number
        },
        "LineItemFilters": [
          {
```

```

        "Attribute": "string",
        "AttributeValues": [ "string" ],
        "MatchOption": "string",
        "Values": [ "string" ]
    }
],
  "Percentage": {
    "PercentageValue": number
  },
  "Type": "string"
},
"ComputationRule": "string",
"CreationTime": number,
"CurrencyCode": "string",
"Description": "string",
"EndBillingPeriod": "string",
"LastModifiedTime": number,
"Name": "string",
"PresentationDetails": {
  "Service": "string"
},
"ProductCode": "string",
"StartBillingPeriod": "string",
"StartTime": number
}
],
"NextToken": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CustomLineItemVersions

A list of CustomLineItemVersionListElements that are received.

Type: Array of [CustomLineItemVersionListElement](#) objects

NextToken

The pagination token that's used on subsequent calls to retrieve custom line item versions.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListPricingPlans

A paginated call to get pricing plans for the given billing period. If you don't provide a billing period, the current billing period is used.

Request Syntax

```
POST /list-pricing-plans HTTP/1.1
Content-type: application/json

{
  "BillingPeriod": "string",
  "Filters": {
    "Arns": [ "string" ]
  },
  "MaxResults": number,
  "NextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

BillingPeriod

The preferred billing period to get pricing plan.

Type: String

Pattern: `\d{4}-(0?[1-9]|1[012])`

Required: No

Filters

A `ListPricingPlansFilter` that specifies the Amazon Resource Name (ARNs) of pricing plans to retrieve pricing plans information.

Type: [ListPricingPlansFilter](#) object

Required: No

MaxResults

The maximum number of pricing plans to retrieve.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The pagination token that's used on subsequent call to get pricing plans.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "BillingPeriod": "string",
  "NextToken": "string",
  "PricingPlans": [
    {
      "Arn": "string",
      "CreationTime": number,
      "Description": "string",
      "LastModifiedTime": number,
      "Name": "string",
      "Size": number
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

BillingPeriod

The billing period for which the described pricing plans are applicable.

Type: String

Pattern: `\d{4}-(0?[1-9]|1[012])`

NextToken

The pagination token that's used on subsequent calls to get pricing plans.

Type: String

PricingPlans

A list of `PricingPlanListElement` retrieved.

Type: Array of [PricingPlanListElement](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListPricingPlansAssociatedWithPricingRule

A list of the pricing plans that are associated with a pricing rule.

Request Syntax

```
POST /list-pricing-plans-associated-with-pricing-rule HTTP/1.1
Content-type: application/json
```

```
{
  "BillingPeriod": "string",
  "MaxResults": number,
  "NextToken": "string",
  "PricingRuleArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

BillingPeriod

The pricing plan billing period for which associations will be listed.

Type: String

Pattern: `\d{4}-(0?[1-9]|1[012])`

Required: No

MaxResults

The optional maximum number of pricing rule associations to retrieve.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The optional pagination token returned by a previous call.

Type: String

Required: No

PricingRuleArn

The pricing rule Amazon Resource Name (ARN) for which associations will be listed.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:pricingrule/)?[a-zA-Z0-9]{10}

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "BillingPeriod": "string",
  "NextToken": "string",
  "PricingPlanArns": [ "string" ],
  "PricingRuleArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

BillingPeriod

The pricing plan billing period for which associations will be listed.

Type: String

Pattern: `\d{4}-(0?[1-9]|1[012])`

NextToken

The pagination token to be used on subsequent calls.

Type: String

PricingPlanArns

The list containing pricing plans that are associated with the requested pricing rule.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Pattern: `(arn:aws(-cn)?:billingconductor::(aws|[0-9]{12}):pricingplan/)?(BasicPricingPlan|Passthrough|[a-zA-Z0-9]{10})`

PricingRuleArn

The pricing rule Amazon Resource Name (ARN) for which associations will be listed.

Type: String

Pattern: `(arn:aws(-cn)?:billingconductor::[0-9]{12}:pricingrule/)?[a-zA-Z0-9]{10}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

ResourceId

Resource identifier that was not found.

ResourceType

Resource type that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListPricingRules

Describes a pricing rule that can be associated to a pricing plan, or set of pricing plans.

Request Syntax

```
POST /list-pricing-rules HTTP/1.1
Content-type: application/json
```

```
{
  "BillingPeriod": "string",
  "Filters": {
    "Arns": [ "string" ]
  },
  "MaxResults": number,
  "NextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

BillingPeriod

The preferred billing period to get the pricing plan.

Type: String

Pattern: `\d{4}-(0?[1-9]|1[012])`

Required: No

Filters

A `DescribePricingRuleFilter` that specifies the Amazon Resource Name (ARNs) of pricing rules to retrieve pricing rules information.

Type: [ListPricingRulesFilter](#) object

Required: No

MaxResults

The maximum number of pricing rules to retrieve.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The pagination token that's used on subsequent call to get pricing rules.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "BillingPeriod": "string",
  "NextToken": "string",
  "PricingRules": [
    {
      "Arn": "string",
      "AssociatedPricingPlanCount": number,
      "BillingEntity": "string",
      "CreationTime": number,
      "Description": "string",
      "LastModifiedTime": number,
      "ModifierPercentage": number,
      "Name": "string",
      "Operation": "string",
      "Scope": "string",
      "Service": "string",
      "Tiering": {
        "FreeTier": {
          "Activated": boolean
        }
      }
    }
  ]
}
```

```
    }
  },
  "Type": "string",
  "UsageType": "string"
}
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

BillingPeriod

The billing period for which the described pricing rules are applicable.

Type: String

Pattern: `\d{4}-(0?[1-9]|1[012])`

NextToken

The pagination token that's used on subsequent calls to get pricing rules.

Type: String

PricingRules

A list containing the described pricing rules.

Type: Array of [PricingRuleListElement](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListPricingRulesAssociatedToPricingPlan

Lists the pricing rules that are associated with a pricing plan.

Request Syntax

```
POST /list-pricing-rules-associated-to-pricing-plan HTTP/1.1
Content-type: application/json
```

```
{
  "BillingPeriod": "string",
  "MaxResults": number,
  "NextToken": "string",
  "PricingPlanArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

BillingPeriod

The billing period for which the pricing rule associations are to be listed.

Type: String

Pattern: `\d{4}-(0?[1-9]|1[012])`

Required: No

MaxResults

The optional maximum number of pricing rule associations to retrieve.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The optional pagination token returned by a previous call.

Type: String

Required: No

PricingPlanArn

The Amazon Resource Name (ARN) of the pricing plan for which associations are to be listed.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::(aws|[0-9]{12}):pricingplan/)?
(BasicPricingPlan|Passthrough|[a-zA-Z0-9]{10})

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "BillingPeriod": "string",
  "NextToken": "string",
  "PricingPlanArn": "string",
  "PricingRuleArns": [ "string" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

BillingPeriod

The billing period for which the pricing rule associations are listed.

Type: String

Pattern: `\d{4}-(0?[1-9]|1[012])`

NextToken

The pagination token to be used on subsequent calls.

Type: String

PricingPlanArn

The Amazon Resource Name (ARN) of the pricing plan for which associations are listed.

Type: String

Pattern: `(arn:aws(-cn)?:billingconductor::(aws|[0-9]{12}):pricingplan/)?(BasicPricingPlan|Passthrough|[a-zA-Z0-9]{10})`

PricingRuleArns

A list containing pricing rules that are associated with the requested pricing plan.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Pattern: `(arn:aws(-cn)?:billingconductor::[0-9]{12}:pricingrule/)?[a-zA-Z0-9]{10}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

ResourceId

Resource identifier that was not found.

ResourceType

Resource type that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListResourcesAssociatedToCustomLineItem

List the resources that are associated to a custom line item.

Request Syntax

```
POST /list-resources-associated-to-custom-line-item HTTP/1.1
Content-type: application/json
```

```
{
  "Arn": "string",
  "BillingPeriod": "string",
  "Filters": {
    "Relationship": "string"
  },
  "MaxResults": number,
  "NextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Arn

The ARN of the custom line item for which the resource associations will be listed.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:customlineitem/)?[a-zA-Z0-9]{10}

Required: Yes

BillingPeriod

The billing period for which the resource associations will be listed.

Type: String

Pattern: `\d{4}-(0?[1-9]|1[012])`

Required: No

Filters

(Optional) A `ListResourcesAssociatedToCustomLineItemFilter` that can specify the types of resources that should be retrieved.

Type: [ListResourcesAssociatedToCustomLineItemFilter](#) object

Required: No

MaxResults

(Optional) The maximum number of resource associations to be retrieved.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

(Optional) The pagination token that's returned by a previous request.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "AssociatedResources": [
    {
      "Arn": "string",
```

```
        "EndBillingPeriod": "string",
        "Relationship": "string"
    }
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The custom line item ARN for which the resource associations are listed.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:customlineitem/)?[a-zA-Z0-9]{10}

AssociatedResources

A list of `ListResourcesAssociatedToCustomLineItemResponseElement` for each resource association retrieved.

Type: Array of [ListResourcesAssociatedToCustomLineItemResponseElement](#) objects

NextToken

The pagination token to be used in subsequent requests to retrieve additional results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

ResourceId

Resource identifier that was not found.

ResourceType

Resource type that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

A list the tags for a resource.

Request Syntax

```
GET /tags/ResourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ResourceArn

The Amazon Resource Name (ARN) that identifies the resource to list the tags.

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws(-cn)?:billingconductor::[0-9]{12}:billinggroup/?[0-9]{12}$|^arn:aws(-cn)?:billingconductor::[0-9]{12}:pricingplan/[a-zA-Z0-9]{10}$|^arn:aws(-cn)?:billingconductor::[0-9]{12}:pricingrule/[a-zA-Z0-9]{10}$|^(arn:aws(-cn)?:billingconductor::[0-9]{12}:customlineitem/)?[a-zA-Z0-9]{10}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
Content-type: application/json

{
  "Tags": {
    "string" : "string"
  }
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response.

The following data is returned in JSON format by the service.

Tags

The tags for the resource.

Type: String to string map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

ResourceId

Resource identifier that was not found.

ResourceType

Resource type that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Associates the specified tags to a resource with the specified `resourceArn`. If existing tags on a resource are not specified in the request parameters, they are not changed.

Request Syntax

```
POST /tags/ResourceArn HTTP/1.1
Content-type: application/json
```

```
{
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

ResourceArn

The Amazon Resource Name (ARN) of the resource to which to add tags.

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws(-cn)?:billingconductor::[0-9]{12}:billinggroup/?[0-9]{12}$|^arn:aws(-cn)?:billingconductor::[0-9]{12}:pricingplan/[a-zA-Z0-9]{10}$|^arn:aws(-cn)?:billingconductor::[0-9]{12}:pricingrule/[a-zA-Z0-9]{10}$|^(arn:aws(-cn)?:billingconductor::[0-9]{12}:customlineitem/)?[a-zA-Z0-9]{10}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

Tags

The tags to add to the resource as a list of key-value pairs.

Type: String to string map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

ResourceId

Resource identifier that was not found.

ResourceType

Resource type that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Deletes specified tags from a resource.

Request Syntax

```
DELETE /tags/ResourceArn?tagKeys=TagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ResourceArn

The Amazon Resource Name (ARN) of the resource to which to delete tags.

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws(-cn)?:billingconductor::[0-9]{12}:billinggroup/?[0-9]{12}$|^arn:aws(-cn)?:billingconductor::[0-9]{12}:pricingplan/[a-zA-Z0-9]{10}$|^arn:aws(-cn)?:billingconductor::[0-9]{12}:pricingrule/[a-zA-Z0-9]{10}$|^(arn:aws(-cn)?:billingconductor::[0-9]{12}:customlineitem/)?[a-zA-Z0-9]{10}`

Required: Yes

TagKeys

The tags to delete from the resource as a list of key-value pairs.

Array Members: Minimum number of 1 item. Maximum number of 200 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

ResourceId

Resource identifier that was not found.

ResourceType

Resource type that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateBillingGroup

This updates an existing billing group.

Request Syntax

```
POST /update-billing-group HTTP/1.1
Content-type: application/json

{
  "AccountGrouping": {
    "AutoAssociate": boolean,
    "ResponsibilityTransferArn": "string"
  },
  "Arn": "string",
  "ComputationPreference": {
    "PricingPlanArn": "string"
  },
  "Description": "string",
  "Name": "string",
  "Status": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

AccountGrouping

Specifies if the billing group has automatic account association (AutoAssociate) enabled.

Type: [UpdateBillingGroupAccountGrouping](#) object

Required: No

Arn

The Amazon Resource Name (ARN) of the billing group being updated.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:billinggroup/)?[a-zA-Z0-9]{10,12}

Required: Yes

ComputationPreference

The preferences and settings that will be used to compute the AWS charges for a billing group.

Type: [ComputationPreference](#) object

Required: No

Description

A description of the billing group.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

Name

The name of the billing group. The names must be unique to each billing group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [a-zA-Z0-9_+=\.\-@]+

Required: No

Status

The status of the billing group. Only one of the valid values can be used.

Type: String

Valid Values: ACTIVE | PRIMARY_ACCOUNT_MISSING | PENDING

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AccountGrouping": {
    "AutoAssociate": boolean,
    "ResponsibilityTransferArn": "string"
  },
  "Arn": "string",
  "Description": "string",
  "LastModifiedTime": number,
  "Name": "string",
  "PricingPlanArn": "string",
  "PrimaryAccountId": "string",
  "Size": number,
  "Status": "string",
  "StatusReason": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AccountGrouping

Specifies if the billing group has automatic account association (AutoAssociate) enabled.

Type: [UpdateBillingGroupAccountGrouping](#) object

Arn

The Amazon Resource Name (ARN) of the billing group that was updated.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:billinggroup/)?[a-zA-Z0-9]{10,12}

Description

A description of the billing group.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

LastModifiedTime

The most recent time when the billing group was modified.

Type: Long

Name

The name of the billing group. The names must be unique to each billing group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_\\+=\\.\\-@]+`

PricingPlanArn

The Amazon Resource Name (ARN) of the pricing plan to compute AWS charges for the billing group.

Type: String

Pattern: `(arn:aws(-cn)?:billingconductor::(aws|[0-9]{12}):pricingplan/)?(BasicPricingPlan|Passthrough|[a-zA-Z0-9]{10})`

PrimaryAccountId

The account ID that serves as the main account in a billing group.

Type: String

Pattern: `[0-9]{12}`

Size

The number of accounts in the particular billing group.

Type: Long

Valid Range: Minimum value of 0.

Status

The status of the billing group. Only one of the valid values can be used.

Type: String

Valid Values: ACTIVE | PRIMARY_ACCOUNT_MISSING | PENDING

StatusReason

The reason why the billing group is in its current status.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

You can cause an inconsistent state by updating or deleting a resource.

Reason

Reason for the inconsistent state.

ResourceId

Identifier of the resource in use.

ResourceType

Type of the resource in use.

HTTP Status Code: 409

InternalServerError

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

ResourceId

Resource identifier that was not found.

ResourceType

Resource type that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateCustomLineItem

Update an existing custom line item in the current or previous billing period.

Request Syntax

```
POST /update-custom-line-item HTTP/1.1
Content-type: application/json

{
  "Arn": "string",
  "BillingPeriodRange": {
    "ExclusiveEndBillingPeriod": "string",
    "InclusiveStartBillingPeriod": "string"
  },
  "ChargeDetails": {
    "Flat": {
      "ChargeValue": number
    },
    "LineItemFilters": [
      {
        "Attribute": "string",
        "AttributeValues": [ "string" ],
        "MatchOption": "string",
        "Values": [ "string" ]
      }
    ],
    "Percentage": {
      "PercentageValue": number
    }
  },
  "Description": "string",
  "Name": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Arn

The ARN of the custom line item to be updated.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:customlineitem/)?[a-zA-Z0-9]{10}

Required: Yes

BillingPeriodRange

The billing period range in which the custom line item request will be applied.

Type: [CustomLineItemBillingPeriodRange](#) object

Required: No

ChargeDetails

A `ListCustomLineItemChargeDetails` containing the new charge details for the custom line item.

Type: [UpdateCustomLineItemChargeDetails](#) object

Required: No

Description

The new line item description of the custom line item.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

Name

The new name for the custom line item.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [a-zA-Z0-9_\\+=\\.\\-@]+

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "AssociationSize": number,
  "BillingGroupArn": "string",
  "ChargeDetails": {
    "Flat": {
      "ChargeValue": number
    },
    "LineItemFilters": [
      {
        "Attribute": "string",
        "AttributeValues": [ "string" ],
        "MatchOption": "string",
        "Values": [ "string" ]
      }
    ],
    "Percentage": {
      "PercentageValue": number
    },
    "Type": "string"
  },
  "Description": "string",
  "LastModifiedTime": number,
  "Name": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The ARN of the successfully updated custom line item.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:customlineitem/)?[a-zA-Z0-9]{10}

AssociationSize

The number of resources that are associated to the custom line item.

Type: Long

Valid Range: Minimum value of 0.

BillingGroupArn

The ARN of the billing group that the custom line item is applied to.

Type: String

Pattern: arn:aws(-cn)?:billingconductor::[0-9]{12}:billinggroup/[a-zA-Z0-9]{10,12}

ChargeDetails

A `ListCustomLineItemChargeDetails` containing the charge details of the successfully updated custom line item.

Type: [ListCustomLineItemChargeDetails](#) object

Description

The description of the successfully updated custom line item.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

LastModifiedTime

The most recent time when the custom line item was modified.

Type: Long

Name

The name of the successfully updated custom line item.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [a-zA-Z0-9_+=\.\-@]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

You can cause an inconsistent state by updating or deleting a resource.

Reason

Reason for the inconsistent state.

ResourceId

Identifier of the resource in use.

ResourceType

Type of the resource in use.

HTTP Status Code: 409

InternalServerError

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

ResourceId

Resource identifier that was not found.

ResourceType

Resource type that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdatePricingPlan

This updates an existing pricing plan.

Request Syntax

```
PUT /update-pricing-plan HTTP/1.1
Content-type: application/json
```

```
{
  "Arn": "string",
  "Description": "string",
  "Name": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Arn

The Amazon Resource Name (ARN) of the pricing plan that you're updating.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::(aws|[0-9]{12}):pricingplan/)?
(BasicPricingPlan|Passthrough|[a-zA-Z0-9]{10})

Required: Yes

Description

The description of the pricing plan.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

Name

The name of the pricing plan. The name must be unique to each pricing plan.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_\\+=\\.\\-@]+`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "Description": "string",
  "LastModifiedTime": number,
  "Name": "string",
  "Size": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the updated pricing plan.

Type: String

Pattern: `(arn:aws(-cn)?:billingconductor::(aws|[0-9]{12}):pricingplan/)?(BasicPricingPlan|Passthrough|[a-zA-Z0-9]{10})`

Description

The new description for the pricing rule.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

LastModifiedTime

The most recent time when the pricing plan was modified.

Type: Long

Name

The name of the pricing plan. The name must be unique to each pricing plan.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [a-zA-Z0-9_+=\. \-@]+

Size

The pricing rules count that's currently associated with this pricing plan list.

Type: Long

Valid Range: Minimum value of 1.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

You can cause an inconsistent state by updating or deleting a resource.

Reason

Reason for the inconsistent state.

ResourceId

Identifier of the resource in use.

ResourceType

Type of the resource in use.

HTTP Status Code: 409

InternalServerError

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

ResourceId

Resource identifier that was not found.

ResourceType

Resource type that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdatePricingRule

Updates an existing pricing rule.

Request Syntax

```
PUT /update-pricing-rule HTTP/1.1
Content-type: application/json
```

```
{
  "Arn": "string",
  "Description": "string",
  "ModifierPercentage": number,
  "Name": "string",
  "Tiering": {
    "FreeTier": {
      "Activated": boolean
    }
  },
  "Type": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Arn

The Amazon Resource Name (ARN) of the pricing rule to update.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:pricingrule/)?[a-zA-Z0-9]{10}

Required: Yes

Description

The new description for the pricing rule.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

ModifierPercentage

The new modifier to show pricing plan rates as a percentage. Your entry will be rounded to the nearest 2 decimal places.

Type: Double

Valid Range: Minimum value of 0.

Required: No

Name

The new name of the pricing rule. The name must be unique to each pricing rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_+=\.\-@]+`

Required: No

Tiering

The set of tiering configurations for the pricing rule.

Type: [UpdateTieringInput](#) object

Required: No

Type

The new pricing rule type.

Type: String

Valid Values: MARKUP | DISCOUNT | TIERING

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "AssociatedPricingPlanCount": number,
  "BillingEntity": "string",
  "Description": "string",
  "LastModifiedTime": number,
  "ModifierPercentage": number,
  "Name": "string",
  "Operation": "string",
  "Scope": "string",
  "Service": "string",
  "Tiering": {
    "FreeTier": {
      "Activated": boolean
    }
  },
  "Type": "string",
  "UsageType": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the successfully updated pricing rule.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:pricingrule/)?[a-zA-Z0-9]{10}

AssociatedPricingPlanCount

The pricing plans count that this pricing rule is associated with.

Type: Long

Valid Range: Minimum value of 0.

BillingEntity

The seller of services provided by AWS, their affiliates, or third-party providers selling services via AWS Marketplace.

Type: String

Pattern: [a-zA-Z0-9()]+

Description

The new description for the pricing rule.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

LastModifiedTime

The most recent time the pricing rule was modified.

Type: Long

ModifierPercentage

The new modifier to show pricing plan rates as a percentage.

Type: Double

Valid Range: Minimum value of 0.

Name

The new name of the pricing rule. The name must be unique to each pricing rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_\\+=\\.\\-@]+`

Operation

Operation refers to the specific AWS covered by this line item. This describes the specific usage of the line item.

If the Scope attribute is set to SKU, this attribute indicates which operation the `PricingRule` is modifying. For example, a value of `RunInstances:0202` indicates the operation of running an Amazon EC2 instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `\\S+`

Scope

The scope of pricing rule that indicates if it's globally applicable, or it's service-specific.

Type: String

Valid Values: GLOBAL | SERVICE | BILLING_ENTITY | SKU

Service

If the Scope attribute is set to SERVICE, the attribute indicates which service the `PricingRule` is applicable for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9]+`

Tiering

The set of tiering configurations for the pricing rule.

Type: [UpdateTieringInput](#) object

Type

The new pricing rule type.

Type: String

Valid Values: MARKUP | DISCOUNT | TIERING

UsageType

Usage type is the unit that each service uses to measure the usage of a specific type of resource.

If the Scope attribute is set to SKU, this attribute indicates which usage type the PricingRule is modifying. For example, USW2-BoxUsage:m2.2xlarge describes an M2 High Memory Double Extra Large instance in the US West (Oregon) Region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: \S+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

You can cause an inconsistent state by updating or deleting a resource.

Reason

Reason for the inconsistent state.

ResourceId

Identifier of the resource in use.

ResourceType

Type of the resource in use.

HTTP Status Code: 409

InternalServerError

An unexpected error occurred while processing a request.

RetryAfterSeconds

Number of seconds you can retry after the call.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that doesn't exist.

ResourceId

Resource identifier that was not found.

ResourceType

Resource type that was not found.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

RetryAfterSeconds

Number of seconds you can safely retry after the call.

HTTP Status Code: 429

ValidationException

The input doesn't match with the constraints specified by AWS services.

Fields

The fields that caused the error, if applicable.

Reason

The reason the request's validation failed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS Billing Conductor API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AccountAssociationsListElement](#)
- [AccountGrouping](#)
- [AssociateResourceError](#)
- [AssociateResourceResponseElement](#)
- [Attribute](#)
- [BillingGroupCostReportElement](#)
- [BillingGroupCostReportResultElement](#)
- [BillingGroupListElement](#)
- [BillingPeriodRange](#)
- [ComputationPreference](#)
- [CreateFreeTierConfig](#)
- [CreateTieringInput](#)
- [CustomLineItemBillingPeriodRange](#)
- [CustomLineItemChargeDetails](#)
- [CustomLineItemFlatChargeDetails](#)
- [CustomLineItemListElement](#)
- [CustomLineItemPercentageChargeDetails](#)
- [CustomLineItemVersionListElement](#)
- [DisassociateResourceResponseElement](#)
- [FreeTierConfig](#)

- [LineItemFilter](#)
- [ListAccountAssociationsFilter](#)
- [ListBillingGroupAccountGrouping](#)
- [ListBillingGroupCostReportsFilter](#)
- [ListBillingGroupsFilter](#)
- [ListCustomLineItemChargeDetails](#)
- [ListCustomLineItemFlatChargeDetails](#)
- [ListCustomLineItemPercentageChargeDetails](#)
- [ListCustomLineItemsFilter](#)
- [ListCustomLineItemVersionsBillingPeriodRangeFilter](#)
- [ListCustomLineItemVersionsFilter](#)
- [ListPricingPlansFilter](#)
- [ListPricingRulesFilter](#)
- [ListResourcesAssociatedToCustomLineItemFilter](#)
- [ListResourcesAssociatedToCustomLineItemResponseElement](#)
- [PresentationObject](#)
- [PricingPlanListElement](#)
- [PricingRuleListElement](#)
- [StringSearch](#)
- [Tiering](#)
- [UpdateBillingGroupAccountGrouping](#)
- [UpdateCustomLineItemChargeDetails](#)
- [UpdateCustomLineItemFlatChargeDetails](#)
- [UpdateCustomLineItemPercentageChargeDetails](#)
- [UpdateFreeTierConfig](#)
- [UpdateTieringInput](#)
- [ValidationExceptionField](#)

AccountAssociationsListElement

A representation of a linked account.

Contents

AccountEmail

The AWS account email.

Type: String

Required: No

AccountId

The associating array of account IDs.

Type: String

Pattern: `[0-9]{12}`

Required: No

AccountName

The AWS account name.

Type: String

Required: No

BillingGroupArn

The Billing Group Arn that the linked account is associated to.

Type: String

Pattern: `(arn:aws(-cn)?:billingconductor::[0-9]{12}:billinggroup/)?[a-zA-Z0-9]{10,12}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AccountGrouping

The set of accounts that will be under the billing group. The set of accounts resemble the linked accounts in a consolidated billing family.

Contents

AutoAssociate

Specifies if this billing group will automatically associate newly added AWS accounts that join your consolidated billing family.

Type: Boolean

Required: No

LinkedAccountIds

The account IDs that make up the billing group. Account IDs must be a part of the consolidated billing family, and not associated with another billing group.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 30 items.

Pattern: `[0-9]{12}`

Required: No

ResponsibilityTransferArn

The Amazon Resource Name (ARN) that identifies the transfer relationship owned by the Bill Transfer account (caller account). When specified, the PrimaryAccountId is no longer required.

Type: String

Pattern: `arn:[a-z0-9][a-z0-9-.\]{0,62}:organizations::\d{12}:transfer/o-[a-z0-9]{10,32}/(billing)/(inbound|outbound)/rt-[0-9a-z]{8,32}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssociateResourceError

A representation of a resource association error.

Contents

Message

The reason why the resource association failed.

Type: String

Required: No

Reason

A static error code that's used to classify the type of failure.

Type: String

Valid Values: INVALID_ARN | SERVICE_LIMIT_EXCEEDED | ILLEGAL_CUSTOMLINEITEM
| INTERNAL_SERVER_EXCEPTION | INVALID_BILLING_PERIOD_RANGE

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssociateResourceResponseElement

A resource association result for a percentage custom line item.

Contents

Arn

The resource ARN that was associated to the custom line item.

Type: String

Pattern: `(arn:aws(-cn)?:billingconductor::[0-9]{12}:(customlineitem|billinggroup)/)?[a-zA-Z0-9]{10,12}`

Required: No

Error

An `AssociateResourceError` that will populate if the resource association fails.

Type: [AssociateResourceError](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Attribute

The key-value pair that represents the attribute by which the `BillingGroupCostReportResults` are grouped. For example, if you want a service-level breakdown for Amazon Simple Storage Service (Amazon S3) of the billing group, the attribute will be a key-value pair of "PRODUCT_NAME" and "S3".

Contents

Key

The key in a key-value pair that describes the margin summary.

Type: String

Required: No

Value

The value in a key-value pair that describes the margin summary.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BillingGroupCostReportElement

A summary report of actual AWS charges and calculated AWS charges, based on the associated pricing plan of a billing group.

Contents

Arn

The Amazon Resource Name (ARN) of a billing group.

Type: String

Pattern: `(arn:aws(-cn)?:billingconductor::[0-9]{12}:billinggroup/)?[a-zA-Z0-9]{10,12}`

Required: No

AWSCost

The actual AWS charges for the billing group.

Type: String

Required: No

Currency

The displayed currency.

Type: String

Required: No

Margin

The billing group margin.

Type: String

Required: No

MarginPercentage

The percentage of billing group margin.

Type: String

Required: No

ProformaCost

The hypothetical AWS charges based on the associated pricing plan of a billing group.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BillingGroupCostReportResultElement

A paginated call to retrieve a list of summary reports of actual AWS charges and the calculated AWS charges, broken down by attributes.

Contents

Arn

The Amazon Resource Number (ARN) that uniquely identifies the billing group.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:billinggroup/)?[a-zA-Z0-9]{10,12}

Required: No

Attributes

The list of key-value pairs that represent the attributes by which the `BillingGroupCostReportResults` are grouped. For example, if you want the Amazon S3 service-level breakdown of a billing group for November 2023, the attributes list will contain a key-value pair of "PRODUCT_NAME" and "S3" and a key-value pair of "BILLING_PERIOD" and "Nov 2023".

Type: Array of [Attribute](#) objects

Required: No

AWSCost

The actual AWS charges for the billing group.

Type: String

Required: No

Currency

The displayed currency.

Type: String

Required: No

Margin

The billing group margin.

Type: String

Required: No

MarginPercentage

The percentage of the billing group margin.

Type: String

Required: No

ProformaCost

The hypothetical AWS charges based on the associated pricing plan of a billing group.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BillingGroupListElement

A representation of a billing group.

Contents

AccountGrouping

Specifies if the billing group has automatic account association (`AutoAssociate`) enabled.

Type: [ListBillingGroupAccountGrouping](#) object

Required: No

Arn

The Amazon Resource Number (ARN) that can be used to uniquely identify the billing group.

Type: String

Pattern: `(arn:aws(-cn)?:billingconductor::[0-9]{12}:billinggroup/)?[a-zA-Z0-9]{10,12}`

Required: No

BillingGroupType

The type of billing group.

Type: String

Valid Values: STANDARD | TRANSFER_BILLING

Required: No

ComputationPreference

The preferences and settings that will be used to compute the AWS charges for a billing group.

Type: [ComputationPreference](#) object

Required: No

CreationTime

The time when the billing group was created.

Type: Long

Required: No

Description

The description of the billing group.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

LastModifiedTime

The most recent time when the billing group was modified.

Type: Long

Required: No

Name

The name of the billing group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_+=\.\-@]+`

Required: No

PrimaryAccountId

The account ID that serves as the main account in a billing group.

Type: String

Pattern: `[0-9]{12}`

Required: No

Size

The number of accounts in the particular billing group.

Type: Long

Valid Range: Minimum value of 0.

Required: No

Status

The billing group status. Only one of the valid values can be used.

Type: String

Valid Values: ACTIVE | PRIMARY_ACCOUNT_MISSING | PENDING

Required: No

StatusReason

The reason why the billing group is in its current status.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BillingPeriodRange

A time range for which the margin summary is effective. The time range can be up to 12 months.

Contents

ExclusiveEndBillingPeriod

The exclusive end billing period that defines a billing period range for the margin summary. For example, if you choose a billing period that starts in October 2023 and ends in December 2023, the margin summary will only include data from October 2023 and November 2023.

Type: String

Pattern: `\d{4}-(0?[1-9]|1[012])`

Required: Yes

InclusiveStartBillingPeriod

The inclusive start billing period that defines a billing period range for the margin summary.

Type: String

Pattern: `\d{4}-(0?[1-9]|1[012])`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ComputationPreference

The preferences and settings that will be used to compute the AWS charges for a billing group.

Contents

PricingPlanArn

The Amazon Resource Name (ARN) of the pricing plan that's used to compute the AWS charges for a billing group.

Type: String

Pattern: `arn:aws(-cn)?:billingconductor::(aws|[0-9]{12}):pricingplan/(BasicPricingPlan|Passthrough|[a-zA-Z0-9]{10})`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CreateFreeTierConfig

The possible AWS Free Tier configurations.

Contents

Activated

Activate or deactivate AWS Free Tier.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CreateTieringInput

The set of tiering configurations for the pricing rule.

Contents

FreeTier

The possible AWS Free Tier configurations.

Type: [CreateFreeTierConfig](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CustomLineItemBillingPeriodRange

The billing period range in which the custom line item request will be applied.

Contents

InclusiveStartBillingPeriod

The inclusive start billing period that defines a billing period range where a custom line is applied.

Type: String

Pattern: `\d{4}-(0?[1-9]|1[012])`

Required: Yes

ExclusiveEndBillingPeriod

The inclusive end billing period that defines a billing period range where a custom line is applied.

Type: String

Pattern: `\d{4}-(0?[1-9]|1[012])`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CustomLineItemChargeDetails

The charge details of a custom line item. It should contain only one of Flat or Percentage.

Contents

Type

The type of the custom line item that indicates whether the charge is a fee or credit.

Type: String

Valid Values: CREDIT | FEE

Required: Yes

Flat

A `CustomLineItemFlatChargeDetails` that describes the charge details of a flat custom line item.

Type: [CustomLineItemFlatChargeDetails](#) object

Required: No

LineItemFilters

A representation of the line item filter.

Type: Array of [LineItemFilter](#) objects

Array Members: Minimum number of 0 items. Maximum number of 1 item.

Required: No

Percentage

A `CustomLineItemPercentageChargeDetails` that describes the charge details of a percentage custom line item.

Type: [CustomLineItemPercentageChargeDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CustomLineItemFlatChargeDetails

A representation of the charge details that are associated with a flat custom line item.

Contents

ChargeValue

The custom line item's fixed charge value in USD.

Type: Double

Valid Range: Minimum value of 0. Maximum value of 1000000.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CustomLineItemListElement

A representation of a custom line item.

Contents

AccountId

The AWS account in which this custom line item will be applied to.

Type: String

Pattern: `[0-9]{12}`

Required: No

Arn

The Amazon Resource Names (ARNs) for custom line items.

Type: String

Pattern: `(arn:aws(-cn)?:billingconductor::[0-9]{12}:customlineitem/)?[a-zA-Z0-9]{10}`

Required: No

AssociationSize

The number of resources that are associated to the custom line item.

Type: Long

Valid Range: Minimum value of 0.

Required: No

BillingGroupArn

The Amazon Resource Name (ARN) that references the billing group where the custom line item applies to.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:billinggroup/)?[a-zA-Z0-9]{10,12}

Required: No

ChargeDetails

A `ListCustomLineItemChargeDetails` that describes the charge details of a custom line item.

Type: [ListCustomLineItemChargeDetails](#) object

Required: No

ComputationRule

The computation rule that determines how the custom line item charges are computed and reflected in the bill.

Type: String

Valid Values: ITEMIZED | CONSOLIDATED

Required: No

CreationTime

The time created.

Type: Long

Required: No

CurrencyCode

The custom line item's charge value currency. Only one of the valid values can be used.

Type: String

Valid Values: USD | CNY

Required: No

Description

The custom line item's description. This is shown on the Bills page in association with the charge value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

LastModifiedTime

The most recent time when the custom line item was modified.

Type: Long

Required: No

Name

The custom line item's name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_+=\.\-@]+`

Required: No

PresentationDetails

Configuration details specifying how the custom line item charges are presented, including which service the charges are shown under.

Type: [PresentationObject](#) object

Required: No

ProductCode

The product code that's associated with the custom line item.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 29.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CustomLineItemPercentageChargeDetails

A representation of the charge details that are associated with a percentage custom line item.

Contents

PercentageValue

The custom line item's percentage value. This will be multiplied against the combined value of its associated resources to determine its charge value.

Type: Double

Valid Range: Minimum value of 0. Maximum value of 10000.

Required: Yes

AssociatedValues

A list of resource ARNs to associate to the percentage custom line item.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Pattern: `(arn:aws(-cn)?:billingconductor::[0-9]{12}:(customlineitem|billinggroup)/)?[a-zA-Z0-9]{10,12}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CustomLineItemVersionListElement

A representation of a custom line item version.

Contents

AccountId

The AWS account in which this custom line item will be applied to.

Type: String

Pattern: `[0-9]{12}`

Required: No

Arn

A list of custom line item Amazon Resource Names (ARNs) to retrieve information.

Type: String

Pattern: `(arn:aws(-cn)?:billingconductor::[0-9]{12}:customlineitem/)?[a-zA-Z0-9]{10}`

Required: No

AssociationSize

The number of resources that are associated with the custom line item.

Type: Long

Valid Range: Minimum value of 0.

Required: No

BillingGroupArn

The Amazon Resource Name (ARN) of the billing group that the custom line item applies to.

Type: String

Pattern: `(arn:aws(-cn)?:billingconductor::[0-9]{12}:billinggroup/)?[a-zA-Z0-9]{10,12}`

Required: No

ChargeDetails

A representation of the charge details of a custom line item.

Type: [ListCustomLineItemChargeDetails](#) object

Required: No

ComputationRule

The computation rule for a specific version of a custom line item, determining how charges are computed and reflected in the bill.

Type: String

Valid Values: ITEMIZED | CONSOLIDATED

Required: No

CreationTime

The time when the custom line item version was created.

Type: Long

Required: No

CurrencyCode

The charge value currency of the custom line item.

Type: String

Valid Values: USD | CNY

Required: No

Description

The description of the custom line item.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

EndBillingPeriod

The end billing period of the custom line item version.

Type: String

Pattern: `\d{4}-(0?[1-9]|1[012])`

Required: No

LastModifiedTime

The most recent time that the custom line item version was modified.

Type: Long

Required: No

Name

The name of the custom line item.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_+=\.\-@]+`

Required: No

PresentationDetails

Presentation configuration for a specific version of a custom line item, specifying how charges are displayed in the bill.

Type: [PresentationObject](#) object

Required: No

ProductCode

The product code that's associated with the custom line item.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 29.

Required: No

StartBillingPeriod

The start billing period of the custom line item version.

Type: String

Pattern: `\d{4}-(0?[1-9]|1[012])`

Required: No

StartTime

The inclusive start time.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DisassociateResourceResponseElement

A resource disassociation result for a percentage custom line item.

Contents

Arn

The resource ARN that was disassociated from the custom line item.

Type: String

Pattern: `(arn:aws(-cn)?:billingconductor::[0-9]{12}:(customlineitem|billinggroup)/)?[a-zA-Z0-9]{10,12}`

Required: No

Error

An `AssociateResourceError` that's shown if the resource disassociation fails.

Type: [AssociateResourceError](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FreeTierConfig

The possible AWS Free Tier configurations.

Contents

Activated

Activate or deactivate AWS Free Tier application.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LineItemFilter

A representation of the line item filter for your custom line item. You can use line item filters to include or exclude specific resource values from the billing group's total cost. For example, if you create a custom line item and you want to filter out a value, such as Savings Plans discounts, you can update `LineItemFilter` to exclude it.

Contents

Attribute

The attribute of the line item filter. This specifies what attribute that you can filter on.

Type: String

Valid Values: `LINE_ITEM_TYPE` | `SERVICE`

Required: Yes

MatchOption

The match criteria of the line item filter. This parameter specifies whether not to include the resource value from the billing group total cost.

Type: String

Valid Values: `NOT_EQUAL` | `EQUAL`

Required: Yes

AttributeValues

The values of the line item filter. This specifies the values to filter on.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9]+`

Required: No

Values

The values of the line item filter. This specifies the values to filter on. Currently, you can only exclude Savings Plans discounts.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 1 item.

Valid Values: SAVINGS_PLAN_NEGATION

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListAccountAssociationsFilter

The filter on the account ID of the linked account, or any of the following:

MONITORED: linked accounts that are associated to billing groups.

UNMONITORED: linked accounts that are not associated to billing groups.

Billing Group Arn: linked accounts that are associated to the provided Billing Group Arn.

Contents

AccountId

The AWS account ID to filter on.

Type: String

Pattern: [0-9]{12}

Required: No

AccountIds

The list of AWS IDs to retrieve their associated billing group for a given time range.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 30 items.

Pattern: [0-9]{12}

Required: No

Association

MONITORED: linked accounts that are associated to billing groups.

UNMONITORED: linked accounts that are not associated to billing groups.

Billing Group Arn: linked accounts that are associated to the provided Billing Group Arn.

Type: String

Pattern: ((arn:aws(-cn)?:billingconductor::[0-9]{12}:billinggroup/)?[a-zA-Z0-9]{10,12}|MONITORED|UNMONITORED)

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListBillingGroupAccountGrouping

Specifies if the billing group has the following features enabled.

Contents

AutoAssociate

Specifies if this billing group will automatically associate newly added AWS accounts that join your consolidated billing family.

Type: Boolean

Required: No

ResponsibilityTransferArn

The Amazon Resource Name (ARN) that identifies the transfer relationship for the billing group.

Type: String

Pattern: `arn:[a-z0-9][a-z0-9-.]{0,62}:organizations::\d{12}:transfer/o-[a-z0-9]{10,32}/(billing)/(inbound|outbound)/rt-[0-9a-z]{8,32}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListBillingGroupCostReportsFilter

The filter used to retrieve specific BillingGroupCostReportElements.

Contents

BillingGroupArns

The list of Amazon Resource Names (ARNs) used to filter billing groups to retrieve reports.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Pattern: (arn:aws(-cn)?:billingconductor::[0-9]{12}:billinggroup/)?[a-zA-Z0-9]{10,12}

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListBillingGroupsFilter

The filter that specifies the billing groups and pricing plans to retrieve billing group information.

Contents

Arns

The list of billing group Amazon Resource Names (ARNs) to retrieve information.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Pattern: `(arn:aws(-cn)?:billingconductor::[0-9]{12}:billinggroup/)?[a-zA-Z0-9]{10,12}`

Required: No

AutoAssociate

Specifies if this billing group will automatically associate newly added AWS accounts that join your consolidated billing family.

Type: Boolean

Required: No

BillingGroupTypes

Filter billing groups by their type.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 2 items.

Valid Values: STANDARD | TRANSFER_BILLING

Required: No

Names

Filter billing groups by their names.

Type: Array of [StringSearch](#) objects

Array Members: Fixed number of 1 item.

Required: No

PricingPlan

The pricing plan Amazon Resource Names (ARNs) to retrieve information.

Type: String

Pattern: `arn:aws(-cn)?:billingconductor::(aws|[0-9]{12}):pricingplan/(BasicPricingPlan|Passthrough|[a-zA-Z0-9]{10})`

Required: No

PrimaryAccountIds

A list of primary account IDs to filter the billing groups.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Pattern: `[0-9]{12}`

Required: No

ResponsibilityTransferArns

Filter billing groups by their responsibility transfer ARNs.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 30 items.

Pattern: `arn:[a-z0-9][a-z0-9-]{0,62}:organizations::\d{12}:transfer/o-[a-z0-9]{10,32}/(billing)/(inbound|outbound)/rt-[0-9a-z]{8,32}`

Required: No

Statuses

A list of billing groups to retrieve their current status for a specific time range

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 2 items.

Valid Values: ACTIVE | PRIMARY_ACCOUNT_MISSING | PENDING

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListCustomLineItemChargeDetails

A representation of the charge details of a custom line item.

Contents

Type

The type of the custom line item that indicates whether the charge is a fee or credit.

Type: String

Valid Values: CREDIT | FEE

Required: Yes

Flat

A `ListCustomLineItemFlatChargeDetails` that describes the charge details of a flat custom line item.

Type: [ListCustomLineItemFlatChargeDetails](#) object

Required: No

LineItemFilters

A representation of the line item filter.

Type: Array of [LineItemFilter](#) objects

Array Members: Minimum number of 0 items. Maximum number of 1 item.

Required: No

Percentage

A `ListCustomLineItemPercentageChargeDetails` that describes the charge details of a percentage custom line item.

Type: [ListCustomLineItemPercentageChargeDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListCustomLineItemFlatChargeDetails

A representation of the charge details that are associated with a flat custom line item.

Contents

ChargeValue

The custom line item's fixed charge value in USD.

Type: Double

Valid Range: Minimum value of 0. Maximum value of 1000000.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListCustomLineItemPercentageChargeDetails

A representation of the charge details that are associated with a percentage custom line item.

Contents

PercentageValue

The custom line item's percentage value. This will be multiplied against the combined value of its associated resources to determine its charge value.

Type: Double

Valid Range: Minimum value of 0. Maximum value of 10000.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListCustomLineItemsFilter

A filter that specifies the custom line items and billing groups to retrieve FFLI information.

Contents

AccountIds

The AWS accounts in which this custom line item will be applied to.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 30 items.

Pattern: `[0-9]{12}`

Required: No

Arns

A list of custom line item ARNs to retrieve information.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Pattern: `(arn:aws(-cn)?:billingconductor::[0-9]{12}:customlineitem/)?[a-zA-Z0-9]{10}`

Required: No

BillingGroups

The billing group Amazon Resource Names (ARNs) to retrieve information.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Pattern: `(arn:aws(-cn)?:billingconductor::[0-9]{12}:billinggroup/)?[a-zA-Z0-9]{10,12}`

Required: No

Names

A list of custom line items to retrieve information.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_+=\.\\-@]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListCustomLineItemVersionsBillingPeriodRangeFilter

A billing period filter that specifies the custom line item versions to retrieve.

Contents

EndBillingPeriod

The exclusive end billing period that defines a billing period range where a custom line item version is applied.

Type: String

Pattern: `\d{4}-(0?[1-9]|1[012])`

Required: No

StartBillingPeriod

The inclusive start billing period that defines a billing period range where a custom line item version is applied.

Type: String

Pattern: `\d{4}-(0?[1-9]|1[012])`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListCustomLineItemVersionsFilter

A filter that specifies the billing period range where the custom line item versions reside.

Contents

BillingPeriodRange

The billing period range in which the custom line item version is applied.

Type: [ListCustomLineItemVersionsBillingPeriodRangeFilter](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListPricingPlansFilter

The filter that specifies the Amazon Resource Names (ARNs) of pricing plans, to retrieve pricing plan information.

Contents

Arns

A list of pricing plan Amazon Resource Names (ARNs) to retrieve information.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Pattern: (arn:aws(-cn)?:billingconductor::(aws|[0-9]{12}):pricingplan/)?
(BasicPricingPlan|Passthrough|[a-zA-Z0-9]{10})

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListPricingRulesFilter

The filter that specifies criteria that the pricing rules returned by the `ListPricingRules` API will adhere to.

Contents

Arns

A list containing the pricing rule Amazon Resource Names (ARNs) to include in the API response.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Pattern: `(arn:aws(-cn)?:billingconductor::[0-9]{12}:pricingrule/)?[a-zA-Z0-9]{10}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListResourcesAssociatedToCustomLineItemFilter

A filter that specifies the type of resource associations that should be retrieved for a custom line item.

Contents

Relationship

The type of relationship between the custom line item and the associated resource.

Type: String

Valid Values: PARENT | CHILD

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListResourcesAssociatedToCustomLineItemResponseElement

A representation of a resource association for a custom line item.

Contents

Arn

The ARN of the associated resource.

Type: String

Pattern: `(arn:aws(-cn)?:billingconductor::[0-9]{12}:(customlineitem|billinggroup)/)?[a-zA-Z0-9]{10,12}`

Required: No

EndBillingPeriod

The end billing period of the associated resource.

Type: String

Pattern: `\d{4}-(0?[1-9]|1[012])`

Required: No

Relationship

The type of relationship between the custom line item and the associated resource.

Type: String

Valid Values: PARENT | CHILD

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PresentationObject

An object that defines how custom line item charges are presented in the bill, containing specifications for service presentation.

Contents

Service

The service under which the custom line item charges will be presented. Must be a string between 1 and 128 characters matching the pattern "[a-zA-Z0-9]+\$".

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [a-zA-Z0-9]+

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PricingPlanListElement

A representation of a pricing plan.

Contents

Arn

The pricing plan Amazon Resource Names (ARN). This can be used to uniquely identify a pricing plan.

Type: String

Pattern: (arn:aws(-cn)?:billingconductor::(aws|[0-9]{12}):pricingplan/)?(BasicPricingPlan|Passthrough|[a-zA-Z0-9]{10})

Required: No

CreationTime

The time when the pricing plan was created.

Type: Long

Required: No

Description

The pricing plan description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

LastModifiedTime

The most recent time when the pricing plan was modified.

Type: Long

Required: No

Name

The name of a pricing plan.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_+=\.\\-@]+`

Required: No

Size

The pricing rules count that's currently associated with this pricing plan list element.

Type: Long

Valid Range: Minimum value of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PricingRuleListElement

A representation of a pricing rule.

Contents

Arn

The Amazon Resource Name (ARN) used to uniquely identify a pricing rule.

Type: String

Pattern: `(arn:aws(-cn)?:billingconductor::[0-9]{12}:pricingrule/)?[a-zA-Z0-9]{10}`

Required: No

AssociatedPricingPlanCount

The pricing plans count that this pricing rule is associated with.

Type: Long

Valid Range: Minimum value of 0.

Required: No

BillingEntity

The seller of services provided by AWS, their affiliates, or third-party providers selling services via AWS Marketplace.

Type: String

Pattern: `[a-zA-Z0-9()]+`

Required: No

CreationTime

The time when the pricing rule was created.

Type: Long

Required: No

Description

The pricing rule description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

LastModifiedTime

The most recent time when the pricing rule was modified.

Type: Long

Required: No

ModifierPercentage

A percentage modifier applied on the public pricing rates.

Type: Double

Valid Range: Minimum value of 0.

Required: No

Name

The name of a pricing rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_+=\.\-@]+`

Required: No

Operation

Operation is the specific AWS action covered by this line item. This describes the specific usage of the line item.

If the `Scope` attribute is set to `SKU`, this attribute indicates which operation the `PricingRule` is modifying. For example, a value of `RunInstances:0202` indicates the operation of running an Amazon EC2 instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `\S+`

Required: No

Scope

The scope of pricing rule that indicates if it is globally applicable, or if it is service-specific.

Type: String

Valid Values: `GLOBAL` | `SERVICE` | `BILLING_ENTITY` | `SKU`

Required: No

Service

If the `Scope` attribute is `SERVICE`, this attribute indicates which service the `PricingRule` is applicable for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9]+`

Required: No

Tiering

The set of tiering configurations for the pricing rule.

Type: [Tiering](#) object

Required: No

Type

The type of pricing rule.

Type: String

Valid Values: MARKUP | DISCOUNT | TIERING

Required: No

UsageType

Usage type is the unit that each service uses to measure the usage of a specific type of resource.

If the Scope attribute is set to SKU, this attribute indicates which usage type the PricingRule is modifying. For example, USW2-BoxUsage:m2.2xlarge describes an M2 High Memory Double Extra Large instance in the US West (Oregon) Region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: \S+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

StringSearch

A structure that defines string search parameters.

Contents

SearchOption

The search option to be applied when performing the string search.

Type: String

Valid Values: STARTS_WITH

Required: Yes

SearchValue

The value to search for within the specified string field.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [a-zA-Z0-9_\+=\. \-@]+

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tiering

The set of tiering configurations for the pricing rule.

Contents

FreeTier

The possible AWS Free Tier configurations.

Type: [FreeTierConfig](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdateBillingGroupAccountGrouping

Specifies if the billing group has the following features enabled.

Contents

AutoAssociate

Specifies if this billing group will automatically associate newly added AWS accounts that join your consolidated billing family.

Type: Boolean

Required: No

ResponsibilityTransferArn

The Amazon Resource Name (ARN) that identifies the transfer relationship. Note: Modifications to the ResponsibilityTransferArn are not permitted for existing billing groups.

Type: String

Pattern: `arn:[a-z0-9][a-z0-9-.]{0,62}:organizations::\d{12}:transfer/o-[a-z0-9]{10,32}/(billing)/(inbound|outbound)/rt-[0-9a-z]{8,32}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdateCustomLineItemChargeDetails

A representation of the new charge details of a custom line item. This should contain only one of Flat or Percentage.

Contents

Flat

An `UpdateCustomLineItemFlatChargeDetails` that describes the new charge details of a flat custom line item.

Type: [UpdateCustomLineItemFlatChargeDetails](#) object

Required: No

LineItemFilters

A representation of the line item filter.

Type: Array of [LineItemFilter](#) objects

Array Members: Minimum number of 0 items. Maximum number of 1 item.

Required: No

Percentage

An `UpdateCustomLineItemPercentageChargeDetails` that describes the new charge details of a percentage custom line item.

Type: [UpdateCustomLineItemPercentageChargeDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

UpdateCustomLineItemFlatChargeDetails

A representation of the new charge details that are associated with a flat custom line item.

Contents

ChargeValue

The custom line item's new fixed charge value in USD.

Type: Double

Valid Range: Minimum value of 0. Maximum value of 1000000.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdateCustomLineItemPercentageChargeDetails

A representation of the new charge details that are associated with a percentage custom line item.

Contents

PercentageValue

The custom line item's new percentage value. This will be multiplied against the combined value of its associated resources to determine its charge value.

Type: Double

Valid Range: Minimum value of 0. Maximum value of 10000.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdateFreeTierConfig

The possible AWS Free Tier configurations.

Contents

Activated

Activate or deactivate application of AWS Free Tier.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdateTieringInput

The set of tiering configurations for the pricing rule.

Contents

FreeTier

The possible AWS Free Tier configurations.

Type: [UpdateFreeTierConfig](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ValidationExceptionField

The field's information of a request that resulted in an exception.

Contents

Message

The message describing why the field failed validation.

Type: String

Required: Yes

Name

The field name.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Error Types

This section lists common error types that this AWS service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

IncompleteSignature

The request signature doesn't conform to AWS standards. Verify that you're using valid AWS credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 403

InternalFailure

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact AWS Support.

HTTP Status Code: 500

MalformedHttpRequestException

The request body can't be processed. This typically happens when the request body can't be decompressed using the specified content encoding algorithm. Verify that the content encoding header matches the compression format used.

HTTP Status Code: 400

NotAuthorized

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

OptInRequired

Your AWS account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

RequestAbortedException

The request was aborted before a response could be returned. This typically happens when the client closes the connection.

HTTP Status Code: 400

RequestEntityTooLargeException

The request entity is too large. Reduce the size of the request body and try again.

HTTP Status Code: 413

RequestTimeoutException

The request timed out. The server didn't receive the complete request within the expected time frame. Try again.

HTTP Status Code: 408

ServiceUnavailable

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

ThrottlingException

Your request rate is too high. The AWS SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

UnknownOperationException

The action or operation isn't recognized. Verify that the action name is spelled correctly and that it's supported by the API version you're using.

HTTP Status Code: 404

UnrecognizedClientException

The X.509 certificate or AWS access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

ValidationError

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400