



API Reference

Amazon Cloud Directory



Amazon Cloud Directory: API Reference

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

.....	xxviii
Welcome	1
Actions	2
AddFacetToObject	5
Request Syntax	5
URI Request Parameters	5
Request Body	6
Response Syntax	6
Response Elements	6
Errors	7
Examples	8
See Also	9
ApplySchema	10
Request Syntax	10
URI Request Parameters	10
Request Body	10
Response Syntax	11
Response Elements	11
Errors	11
Examples	13
See Also	14
AttachObject	15
Request Syntax	15
URI Request Parameters	15
Request Body	15
Response Syntax	16
Response Elements	16
Errors	17
Examples	19
See Also	20
AttachPolicy	21
Request Syntax	21
URI Request Parameters	21
Request Body	21

Response Syntax	22
Response Elements	22
Errors	22
Examples	23
See Also	24
AttachToIndex	26
Request Syntax	26
URI Request Parameters	26
Request Body	26
Response Syntax	27
Response Elements	27
Errors	27
Examples	29
See Also	30
AttachTypedLink	32
Request Syntax	32
URI Request Parameters	32
Request Body	33
Response Syntax	33
Response Elements	34
Errors	35
Examples	36
See Also	38
BatchRead	40
Request Syntax	40
URI Request Parameters	45
Request Body	45
Response Syntax	45
Response Elements	51
Errors	51
Examples	52
See Also	53
BatchWrite	55
Request Syntax	55
URI Request Parameters	61
Request Body	61

Response Syntax	61
Response Elements	63
Errors	63
Examples	64
See Also	65
CreateDirectory	67
Request Syntax	67
URI Request Parameters	67
Request Body	67
Response Syntax	68
Response Elements	68
Errors	69
Examples	70
See Also	71
CreateFacet	73
Request Syntax	73
URI Request Parameters	74
Request Body	74
Response Syntax	75
Response Elements	75
Errors	75
Examples	77
See Also	78
CreateIndex	79
Request Syntax	79
URI Request Parameters	79
Request Body	79
Response Syntax	80
Response Elements	80
Errors	81
Examples	82
See Also	84
CreateObject	85
Request Syntax	85
URI Request Parameters	86
Request Body	86

Response Syntax	87
Response Elements	87
Errors	87
Examples	89
See Also	90
CreateSchema	91
Request Syntax	91
URI Request Parameters	91
Request Body	91
Response Syntax	92
Response Elements	92
Errors	92
Examples	93
See Also	94
CreateTypedLinkFacet	96
Request Syntax	96
URI Request Parameters	97
Request Body	97
Response Syntax	97
Response Elements	97
Errors	97
Examples	99
See Also	100
DeleteDirectory	101
Request Syntax	101
URI Request Parameters	101
Request Body	101
Response Syntax	101
Response Elements	101
Errors	102
Examples	103
See Also	104
DeleteFacet	105
Request Syntax	105
URI Request Parameters	105
Request Body	105

Response Syntax	106
Response Elements	106
Errors	106
Examples	107
See Also	108
DeleteObject	109
Request Syntax	109
URI Request Parameters	109
Request Body	109
Response Syntax	110
Response Elements	110
Errors	110
Examples	111
See Also	112
DeleteSchema	114
Request Syntax	114
URI Request Parameters	114
Request Body	114
Response Syntax	114
Response Elements	114
Errors	115
Examples	116
See Also	117
DeleteTypedLinkFacet	118
Request Syntax	118
URI Request Parameters	118
Request Body	118
Response Syntax	119
Response Elements	119
Errors	119
Examples	120
See Also	121
DetachFromIndex	122
Request Syntax	122
URI Request Parameters	122
Request Body	122

Response Syntax	123
Response Elements	123
Errors	123
Examples	125
See Also	126
DetachObject	127
Request Syntax	127
URI Request Parameters	127
Request Body	127
Response Syntax	128
Response Elements	128
Errors	128
Examples	130
See Also	131
DetachPolicy	132
Request Syntax	132
URI Request Parameters	132
Request Body	132
Response Syntax	133
Response Elements	133
Errors	133
Examples	134
See Also	135
DetachTypedLink	137
Request Syntax	137
URI Request Parameters	137
Request Body	138
Response Syntax	138
Response Elements	138
Errors	138
Examples	140
See Also	141
DisableDirectory	142
Request Syntax	142
URI Request Parameters	142
Request Body	142

Response Syntax	142
Response Elements	142
Errors	143
Examples	144
See Also	145
EnableDirectory	146
Request Syntax	146
URI Request Parameters	146
Request Body	146
Response Syntax	146
Response Elements	146
Errors	147
Examples	148
See Also	149
GetAppliedSchemaVersion	150
Request Syntax	150
URI Request Parameters	150
Request Body	150
Response Syntax	150
Response Elements	150
Errors	151
See Also	152
GetDirectory	153
Request Syntax	153
URI Request Parameters	153
Request Body	153
Response Syntax	153
Response Elements	153
Errors	154
Examples	155
See Also	156
GetFacet	157
Request Syntax	157
URI Request Parameters	157
Request Body	157
Response Syntax	158

Response Elements	158
Errors	158
Examples	159
See Also	160
GetLinkAttributes	162
Request Syntax	162
URI Request Parameters	162
Request Body	163
Response Syntax	163
Response Elements	164
Errors	164
See Also	166
GetObjectAttributes	167
Request Syntax	167
URI Request Parameters	167
Request Body	167
Response Syntax	168
Response Elements	169
Errors	169
See Also	170
GetObjectInformation	172
Request Syntax	172
URI Request Parameters	172
Request Body	172
Response Syntax	173
Response Elements	173
Errors	173
Examples	175
See Also	176
GetSchemaAsJson	177
Request Syntax	177
URI Request Parameters	177
Request Body	177
Response Syntax	177
Response Elements	177
Errors	178

Examples	179
See Also	182
GetTypedLinkFacetInformation	183
Request Syntax	183
URI Request Parameters	183
Request Body	183
Response Syntax	184
Response Elements	184
Errors	184
Examples	186
See Also	187
ListAppliedSchemaArns	188
Request Syntax	188
URI Request Parameters	188
Request Body	188
Response Syntax	189
Response Elements	189
Errors	190
Examples	191
See Also	192
ListAttachedIndices	193
Request Syntax	193
URI Request Parameters	193
Request Body	193
Response Syntax	194
Response Elements	195
Errors	195
Examples	196
See Also	198
ListDevelopmentSchemaArns	199
Request Syntax	199
URI Request Parameters	199
Request Body	199
Response Syntax	199
Response Elements	200
Errors	200

Examples	201
See Also	202
ListDirectories	204
Request Syntax	204
URI Request Parameters	204
Request Body	204
Response Syntax	205
Response Elements	205
Errors	206
Examples	207
See Also	208
ListFacetAttributes	210
Request Syntax	210
URI Request Parameters	210
Request Body	210
Response Syntax	211
Response Elements	212
Errors	212
Examples	214
See Also	219
ListFacetNames	220
Request Syntax	220
URI Request Parameters	220
Request Body	220
Response Syntax	221
Response Elements	221
Errors	221
Examples	223
See Also	224
ListIncomingTypedLinks	225
Request Syntax	225
URI Request Parameters	226
Request Body	226
Response Syntax	227
Response Elements	228
Errors	228

Examples	230
See Also	232
ListIndex	234
Request Syntax	234
URI Request Parameters	235
Request Body	235
Response Syntax	236
Response Elements	237
Errors	237
Examples	239
See Also	240
ListManagedSchemaArns	242
Request Syntax	242
URI Request Parameters	242
Request Body	242
Response Syntax	243
Response Elements	243
Errors	243
See Also	245
ListObjectAttributes	246
Request Syntax	246
URI Request Parameters	246
Request Body	247
Response Syntax	247
Response Elements	248
Errors	248
Examples	250
See Also	252
ListObjectChildren	253
Request Syntax	253
URI Request Parameters	253
Request Body	253
Response Syntax	254
Response Elements	254
Errors	255
Examples	257

See Also	258
ListObjectParentPaths	259
Request Syntax	259
URI Request Parameters	259
Request Body	259
Response Syntax	260
Response Elements	260
Errors	261
See Also	262
ListObjectParents	264
Request Syntax	264
URI Request Parameters	264
Request Body	264
Response Syntax	265
Response Elements	266
Errors	266
See Also	268
ListObjectPolicies	269
Request Syntax	269
URI Request Parameters	269
Request Body	269
Response Syntax	270
Response Elements	270
Errors	271
See Also	272
ListOutgoingTypedLinks	274
Request Syntax	274
URI Request Parameters	275
Request Body	275
Response Syntax	276
Response Elements	277
Errors	277
See Also	279
ListPolicyAttachments	280
Request Syntax	280
URI Request Parameters	280

Request Body	280
Response Syntax	281
Response Elements	281
Errors	282
See Also	283
ListPublishedSchemaArns	285
Request Syntax	285
URI Request Parameters	285
Request Body	285
Response Syntax	286
Response Elements	286
Errors	286
See Also	288
ListTagsForResource	289
Request Syntax	289
URI Request Parameters	289
Request Body	289
Response Syntax	290
Response Elements	290
Errors	291
See Also	292
ListTypedLinkFacetAttributes	293
Request Syntax	293
URI Request Parameters	293
Request Body	293
Response Syntax	294
Response Elements	295
Errors	295
See Also	297
ListTypedLinkFacetNames	298
Request Syntax	298
URI Request Parameters	298
Request Body	298
Response Syntax	299
Response Elements	299
Errors	299

See Also	301
LookupPolicy	302
Request Syntax	302
URI Request Parameters	302
Request Body	302
Response Syntax	303
Response Elements	304
Errors	304
See Also	305
PublishSchema	307
Request Syntax	307
URI Request Parameters	307
Request Body	307
Response Syntax	308
Response Elements	308
Errors	309
See Also	310
PutSchemaFromJson	311
Request Syntax	311
URI Request Parameters	311
Request Body	311
Response Syntax	311
Response Elements	312
Errors	312
See Also	313
RemoveFacetFromObject	315
Request Syntax	315
URI Request Parameters	315
Request Body	315
Response Syntax	316
Response Elements	316
Errors	316
See Also	317
TagResource	319
Request Syntax	319
URI Request Parameters	319

Request Body	319
Response Syntax	320
Response Elements	320
Errors	320
See Also	321
UntagResource	323
Request Syntax	323
URI Request Parameters	323
Request Body	323
Response Syntax	323
Response Elements	324
Errors	324
See Also	325
UpdateFacet	326
Request Syntax	326
URI Request Parameters	327
Request Body	327
Response Syntax	328
Response Elements	328
Errors	328
See Also	330
UpdateLinkAttributes	331
Request Syntax	331
URI Request Parameters	332
Request Body	332
Response Syntax	333
Response Elements	333
Errors	333
See Also	334
UpdateObjectAttributes	336
Request Syntax	336
URI Request Parameters	336
Request Body	337
Response Syntax	337
Response Elements	337
Errors	338

See Also	339
UpdateSchema	341
Request Syntax	341
URI Request Parameters	341
Request Body	341
Response Syntax	342
Response Elements	342
Errors	342
See Also	343
UpdateTypedLinkFacet	345
Request Syntax	345
URI Request Parameters	346
Request Body	346
Response Syntax	347
Response Elements	347
Errors	347
See Also	349
UpgradeAppliedSchema	350
Request Syntax	350
URI Request Parameters	350
Request Body	350
Response Syntax	351
Response Elements	351
Errors	351
See Also	353
UpgradePublishedSchema	354
Request Syntax	354
URI Request Parameters	354
Request Body	354
Response Syntax	355
Response Elements	355
Errors	356
See Also	357
Data Types	358
AttributeKey	362
Contents	362

See Also	362
AttributeKeyAndValue	364
Contents	364
See Also	364
AttributeNameAndValue	365
Contents	365
See Also	365
BatchAddFacetToObject	366
Contents	366
See Also	366
BatchAddFacetToObjectResponse	367
Contents	367
See Also	367
BatchAttachObject	368
Contents	368
See Also	368
BatchAttachObjectResponse	370
Contents	370
See Also	370
BatchAttachPolicy	371
Contents	371
See Also	371
BatchAttachPolicyResponse	372
Contents	372
See Also	372
BatchAttachToIndex	373
Contents	373
See Also	373
BatchAttachToIndexResponse	374
Contents	374
See Also	374
BatchAttachTypedLink	375
Contents	375
See Also	375
BatchAttachTypedLinkResponse	377
Contents	377

See Also	377
BatchCreateIndex	378
Contents	378
See Also	379
BatchCreateIndexResponse	380
Contents	380
See Also	380
BatchCreateObject	381
Contents	381
See Also	382
BatchCreateObjectResponse	383
Contents	383
See Also	383
BatchDeleteObject	384
Contents	384
See Also	384
BatchDeleteObjectResponse	385
Contents	385
See Also	385
BatchDetachFromIndex	386
Contents	386
See Also	386
BatchDetachFromIndexResponse	387
Contents	387
See Also	387
BatchDetachObject	388
Contents	388
See Also	388
BatchDetachObjectResponse	390
Contents	390
See Also	390
BatchDetachPolicy	391
Contents	391
See Also	391
BatchDetachPolicyResponse	392
Contents	392

See Also	392
BatchDetachTypedLink	393
Contents	393
See Also	393
BatchDetachTypedLinkResponse	394
Contents	394
See Also	394
BatchGetLinkAttributes	395
Contents	395
See Also	395
BatchGetLinkAttributesResponse	396
Contents	396
See Also	396
BatchGetObjectAttributes	397
Contents	397
See Also	397
BatchGetObjectAttributesResponse	399
Contents	399
See Also	399
BatchGetObjectInformation	400
Contents	400
See Also	400
BatchGetObjectInformationResponse	401
Contents	401
See Also	401
BatchListAttachedIndices	402
Contents	402
See Also	402
BatchListAttachedIndicesResponse	404
Contents	404
See Also	404
BatchListIncomingTypedLinks	405
Contents	405
See Also	406
BatchListIncomingTypedLinksResponse	407
Contents	407

See Also	407
BatchListIndex	408
Contents	408
See Also	408
BatchListIndexResponse	410
Contents	410
See Also	410
BatchListObjectAttributes	411
Contents	411
See Also	411
BatchListObjectAttributesResponse	413
Contents	413
See Also	413
BatchListObjectChildren	414
Contents	414
See Also	414
BatchListObjectChildrenResponse	415
Contents	415
See Also	415
BatchListObjectParentPaths	416
Contents	416
See Also	416
BatchListObjectParentPathsResponse	418
Contents	418
See Also	418
BatchListObjectParents	419
Contents	419
See Also	419
BatchListObjectParentsResponse	420
Contents	420
See Also	420
BatchListObjectPolicies	421
Contents	421
See Also	421
BatchListObjectPoliciesResponse	423
Contents	423

See Also	423
BatchListOutgoingTypedLinks	424
Contents	424
See Also	425
BatchListOutgoingTypedLinksResponse	426
Contents	426
See Also	426
BatchListPolicyAttachments	427
Contents	427
See Also	427
BatchListPolicyAttachmentsResponse	429
Contents	429
See Also	429
BatchLookupPolicy	430
Contents	430
See Also	430
BatchLookupPolicyResponse	432
Contents	432
See Also	432
BatchReadException	433
Contents	433
See Also	433
BatchReadOperation	434
Contents	434
See Also	436
BatchReadOperationResponse	437
Contents	437
See Also	437
BatchReadSuccessfulResponse	438
Contents	438
See Also	440
BatchRemoveFacetFromObject	441
Contents	441
See Also	441
BatchRemoveFacetFromObjectResponse	442
Contents	442

See Also	442
BatchUpdateLinkAttributes	443
Contents	443
See Also	443
BatchUpdateLinkAttributesResponse	444
Contents	444
See Also	444
BatchUpdateObjectAttributes	445
Contents	445
See Also	445
BatchUpdateObjectAttributesResponse	446
Contents	446
See Also	446
BatchWriteOperation	447
Contents	447
See Also	449
BatchWriteOperationResponse	451
Contents	451
See Also	453
Directory	455
Contents	455
See Also	456
Facet	457
Contents	457
See Also	458
FacetAttribute	459
Contents	459
See Also	460
FacetAttributeDefinition	461
Contents	461
See Also	462
FacetAttributeReference	463
Contents	463
See Also	463
FacetAttributeUpdate	465
Contents	465

See Also	465
IndexAttachment	466
Contents	466
See Also	466
LinkAttributeAction	467
Contents	467
See Also	467
LinkAttributeUpdate	468
Contents	468
See Also	468
ObjectAttributeAction	469
Contents	469
See Also	469
ObjectAttributeRange	470
Contents	470
See Also	470
ObjectAttributeUpdate	471
Contents	471
See Also	471
ObjectIdentifierAndLinkNameTuple	472
Contents	472
See Also	472
ObjectReference	473
Contents	473
See Also	473
PathToObjectIdentifiers	474
Contents	474
See Also	474
PolicyAttachment	475
Contents	475
See Also	475
PolicyToPath	476
Contents	476
See Also	476
Rule	477
Contents	477

See Also	477
SchemaFacet	478
Contents	478
See Also	478
Tag	479
Contents	479
See Also	479
TypedAttributeValue	480
Contents	480
See Also	481
TypedAttributeValueRange	482
Contents	482
See Also	483
TypedLinkAttributeDefinition	484
Contents	484
See Also	485
TypedLinkAttributeRange	486
Contents	486
See Also	486
TypedLinkFacet	487
Contents	487
See Also	488
TypedLinkFacetAttributeUpdate	489
Contents	489
See Also	489
TypedLinkSchemaAndFacetName	490
Contents	490
See Also	490
TypedLinkSpecifier	491
Contents	491
See Also	492
Arn Examples	493
Schema Arns	493
Directory Arns	494
CloudTrail Logging	496
Cloud Directory Information in CloudTrail	496

Understanding Cloud Directory Log File Entries	498
Common Parameters	502
Common Error Types	505
Document History	508

Amazon Cloud Directory will no longer be open to new customers starting on November 7, 2025. For alternatives to Cloud Directory, explore [Amazon DynamoDB](#) and [Amazon Neptune](#). If you need help choosing the right alternative for your use case, or for any other questions, contact [AWS Support](#).

Welcome to the Amazon Cloud Directory API Reference

Amazon Cloud Directory is a highly scalable, high performance, multitenant directory service in the cloud. Its web-based directories make it easy for you to organize and manage application resources such as users, groups, locations, devices, policies, and the rich relationships between them. Cloud Directory is a foundational building block for developers to create directory-based solutions easily and without having to worry about deployment, global scale, availability, and performance.

With Cloud Directory, you can organize directory objects into multiple hierarchies to support multiple organizational pivots and relationships across directory information. For example, a directory of users could provide a hierarchical view based on reporting structure, location, and project affiliation. Similarly, a directory of devices might have multiple hierarchical views based on its manufacturer, current owner, and physical location. For more information, see [Amazon Cloud Directory](#) in the *AWS Directory Service Admin Guide*.

This guide describes the Cloud Directory operations that you can call programmatically and includes detailed information on data types and errors.

Note

AWS provides SDKs that consist of libraries and sample code for various programming languages and platforms (Java, Ruby, .Net, iOS, Android, etc.). The SDKs provide a convenient way to create programmatic access to Directory Service and other AWS services. For more information about the AWS SDKs, including how to download and install them, see [Tools for Amazon Web Services](#).

Actions

The following actions are supported:

- [AddFacetToObject](#)
- [ApplySchema](#)
- [AttachObject](#)
- [AttachPolicy](#)
- [AttachToIndex](#)
- [AttachTypedLink](#)
- [BatchRead](#)
- [BatchWrite](#)
- [CreateDirectory](#)
- [CreateFacet](#)
- [CreateIndex](#)
- [CreateObject](#)
- [CreateSchema](#)
- [CreateTypedLinkFacet](#)
- [DeleteDirectory](#)
- [DeleteFacet](#)
- [DeleteObject](#)
- [DeleteSchema](#)
- [DeleteTypedLinkFacet](#)
- [DetachFromIndex](#)
- [DetachObject](#)
- [DetachPolicy](#)
- [DetachTypedLink](#)
- [DisableDirectory](#)
- [EnableDirectory](#)
- [GetAppliedSchemaVersion](#)
- [GetDirectory](#)

- [GetFacet](#)
- [GetLinkAttributes](#)
- [GetObjectAttributes](#)
- [GetObjectInformation](#)
- [GetSchemaAsJson](#)
- [GetTypedLinkFacetInformation](#)
- [ListAppliedSchemaArns](#)
- [ListAttachedIndices](#)
- [ListDevelopmentSchemaArns](#)
- [ListDirectories](#)
- [ListFacetAttributes](#)
- [ListFacetNames](#)
- [ListIncomingTypedLinks](#)
- [ListIndex](#)
- [ListManagedSchemaArns](#)
- [ListObjectAttributes](#)
- [ListObjectChildren](#)
- [ListObjectParentPaths](#)
- [ListObjectParents](#)
- [ListObjectPolicies](#)
- [ListOutgoingTypedLinks](#)
- [ListPolicyAttachments](#)
- [ListPublishedSchemaArns](#)
- [ListTagsForResource](#)
- [ListTypedLinkFacetAttributes](#)
- [ListTypedLinkFacetNames](#)
- [LookupPolicy](#)
- [PublishSchema](#)
- [PutSchemaFromJson](#)
- [RemoveFacetFromObject](#)

- [TagResource](#)
- [UntagResource](#)
- [UpdateFacet](#)
- [UpdateLinkAttributes](#)
- [UpdateObjectAttributes](#)
- [UpdateSchema](#)
- [UpdateTypedLinkFacet](#)
- [UpgradeAppliedSchema](#)
- [UpgradePublishedSchema](#)

AddFacetToObject

Adds a new [Facet](#) to an object. An object can have more than one facet applied on it.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/object/facets HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json
```

```
{
  "ObjectAttributeList": [
    {
      "Key": {
        "FacetName": "string",
        "Name": "string",
        "SchemaArn": "string"
      },
      "Value": {
        "BinaryValue": blob,
        "BooleanValue": boolean,
        "DatetimeValue": number,
        "NumberValue": "string",
        "StringValue": "string"
      }
    }
  ],
  "ObjectReference": {
    "Selector": "string"
  },
  "SchemaFacet": {
    "FacetName": "string",
    "SchemaArn": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

DirectoryArn

The Amazon Resource Name (ARN) that is associated with the [Directory](#) where the object resides. For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

ObjectAttributeList

Attributes on the facet that you are adding to the object.

Type: Array of [AttributeKeyAndValue](#) objects

Required: No

ObjectReference

A reference to the object you are adding the specified facet to.

Type: [ObjectReference](#) object

Required: Yes

SchemaFacet

Identifiers for the facet that you are adding to the object. See [SchemaFacet](#) for details.

Type: [SchemaFacet](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

FacetValidationException

The [Facet](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of AddFacetToObject.

```
PUT /amazonclouddirectory/2017-01-11/object/facets HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 232
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171009/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=2cf0b34e6e7305c27f7ec762255196d937ef036d0e665e452a0e1bd79ae25106
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY
X-Amz-Date: 20171009T164125Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "ObjectReference": {
    "Selector": "$AQQG_AD1fNZBzYHY_JgDt3TWmspn1fxfQmSQaaVKSbvEiQ"
  },
  "SchemaFacet": {
```

```
"SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY/schema/org/1",
"FacetName": "node1"
}
}
```

Example Response

This example illustrates one usage of `AddFacetToObject`.

```
HTTP/1.1 200 OK
x-amzn-RequestId: b21ee371-ad10-11e7-9e13-5b6a00750e59
Date: Mon, 09 Oct 2017 16:41:26 GMT
x-amzn-RequestId: b21ee371-ad10-11e7-9e13-5b6a00750e59
Content-Type: application/json
Content-Length: 2

{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ApplySchema

Copies the input published schema, at the specified version, into the [Directory](#) with the same name and version as that of the published schema.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/schema/apply HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json

{
  "PublishedSchemaArn": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

DirectoryArn

The Amazon Resource Name (ARN) that is associated with the [Directory](#) into which the schema is copied. For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

PublishedSchemaArn

Published schema Amazon Resource Name (ARN) that needs to be copied. For more information, see [Arn Examples](#).

Type: String

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AppliedSchemaArn": "string",
  "DirectoryArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AppliedSchemaArn](#)

The applied schema ARN that is associated with the copied schema in the [Directory](#). You can use this ARN to describe the schema information applied on this directory. For more information, see [Arn Examples](#).

Type: String

[DirectoryArn](#)

The ARN that is associated with the [Directory](#). For more information, see [Arn Examples](#).

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidAttachmentException

Indicates that an attempt to make an attachment was invalid. For example, attaching two nodes with a link type that is not applicable to the nodes or attempting to apply a schema to a directory a second time.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

SchemaAlreadyExistsException

Indicates that a schema could not be created due to a naming conflict. Please select a different name and then try again.

HTTP Status Code: 400

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of `ApplySchema`.

```
PUT /amazonclouddirectory/2017-01-11/schema/apply HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 94
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171003/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=ac58e3d2d25b85cd1869f7a845a0e97cebfce28d15e8f8df34c0ee89a197f042
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AfMr4qym1kZTvwq0afAYfqI
X-Amz-Date: 20171003T201513Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "PublishedSchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:schema/published/
org/1"
}
```

Example Response

This example illustrates one usage of `ApplySchema`.

```
HTTP/1.1 200 OK
```

```
x-amzn-RequestId: 90d60895-a877-11e7-81c0-7b48a7696e76
Date: Tue, 03 Oct 2017 20:15:13 GMT
x-amzn-RequestId: 90d60895-a877-11e7-81c0-7b48a7696e76
Content-Type: application/json
Content-Length: 212

{
  "AppliedSchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AfMr4qym1kZTvwq0afAYfqI/schema/org/1",
  "DirectoryArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AfMr4qym1kZTvwq0afAYfqI"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

AttachObject

Attaches an existing object to another object. An object can be accessed in two ways:

1. Using the path
2. Using `ObjectIdentifier`

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/object/attach HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json

{
  "ChildReference": {
    "Selector": "string"
  },
  "LinkName": "string",
  "ParentReference": {
    "Selector": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

DirectoryArn

Amazon Resource Name (ARN) that is associated with the [Directory](#) where both objects reside. For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

ChildReference

The child object reference to be attached to the object.

Type: [ObjectReference](#) object

Required: Yes

LinkName

The link name with which the child object is attached to the parent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[^\v[\]\(\):\{\}\#\@!\?\s\\;]+`

Required: Yes

ParentReference

The parent object reference.

Type: [ObjectReference](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AttachedObjectIdentifier": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AttachedObjectIdentifier

The attached `ObjectIdentifier`, which is the child `ObjectIdentifier`.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

FacetValidationException

The [Facet](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidAttachmentException

Indicates that an attempt to make an attachment was invalid. For example, attaching two nodes with a link type that is not applicable to the nodes or attempting to apply a schema to a directory a second time.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

LinkNameAlreadyInUseException

Indicates that a link could not be created due to a naming conflict. Choose a different name and then try again.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of AttachObject.

```
PUT /amazonclouddirectory/2017-01-11/object/attach HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 188
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171003/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=2ce97afc4ac4d1fd4826861fa366d6d8674d1399b1a666e59cc53b8310aacf6a
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY
X-Amz-Date: 20171003T195605Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "ParentReference": {
    "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWcU7IARv0TeaR09zme1sVsw"
  },
  "LinkName": "link2",
  "ChildReference": {
    "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWSvfuEnDqTdmeCuTs6YBNUA"
  }
}
```

Example Response

This example illustrates one usage of AttachObject.

```
HTTP/1.1 200 OK
x-amzn-RequestId: e4be5146-a874-11e7-a169-c5bf0acd39f4
Date: Tue, 03 Oct 2017 19:56:06 GMT
x-amzn-RequestId: e4be5146-a874-11e7-a169-c5bf0acd39f4
Content-Type: application/json
Content-Length: 77
```

```
{  
  "AttachedObjectIdentifier": "AQGG_AD1fNZBzYHY_JgDt3TWSvfuEnDqTdmeCuTs6YBNUA"  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

AttachPolicy

Attaches a policy object to a regular object. An object can have a limited number of attached policies.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/policy/attach HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json

{
  "ObjectReference": {
    "Selector": "string"
  },
  "PolicyReference": {
    "Selector": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

DirectoryArn

The Amazon Resource Name (ARN) that is associated with the [Directory](#) where both objects reside. For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

ObjectReference

The reference that identifies the object to which the policy will be attached.

Type: [ObjectReference](#) object

Required: Yes

[PolicyReference](#)

The reference that is associated with the policy object.

Type: [ObjectReference](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

NotPolicyException

Indicates that the requested operation can only operate on policy objects.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of AttachPolicy.

```
PUT /amazonclouddirectory/2017-01-11/policy/attach HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 168
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171017/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=d6ba55fbae53295150b69a92946e542ad08f7557492c5862d70d6a8c62fa24b0
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY
X-Amz-Date: 20171017T185436Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "PolicyReference": {
    "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWgcBsTVmcQEws6jlygfhuew"
  },
  "ObjectReference": {
    "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWQoovm1s3Ts2v0NKrzdVnPw"
  }
}
```

Example Response

This example illustrates one usage of AttachPolicy.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 9ff9d709-b36c-11e7-843e-9fad359f817f
Date: Tue, 17 Oct 2017 18:54:37 GMT
x-amzn-RequestId: 9ff9d709-b36c-11e7-843e-9fad359f817f
Content-Type: application/json
Content-Length: 2

{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

AttachToIndex

Attaches the specified object to the specified index.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/index/attach HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json

{
  "IndexReference": {
    "Selector": "string"
  },
  "TargetReference": {
    "Selector": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

DirectoryArn

The Amazon Resource Name (ARN) of the directory where the object and index exist.

Required: Yes

Request Body

The request accepts the following data in JSON format.

IndexReference

A reference to the index that you are attaching the object to.

Type: [ObjectReference](#) object

Required: Yes

TargetReference

A reference to the object that you are attaching to the index.

Type: [ObjectReference](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AttachedObjectIdentifier": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AttachedObjectIdentifier

The `ObjectIdentifier` of the object that was attached to the index.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

IndexedAttributeMissingException

An object has been attempted to be attached to an object that does not have the appropriate attribute value.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidAttachmentException

Indicates that an attempt to make an attachment was invalid. For example, attaching two nodes with a link type that is not applicable to the nodes or attempting to apply a schema to a directory a second time.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

LinkNameAlreadyInUseException

Indicates that a link could not be created due to a naming conflict. Choose a different name and then try again.

HTTP Status Code: 400

NotIndexException

Indicates that the requested operation can only operate on index objects.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of AttachToIndex.

```
PUT /amazonclouddirectory/2017-01-11/index/attach HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 167
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20170927/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=78d785ce666b33aa8624c62c59be1dca60c49062f91eb216909450ea214c5a56
```

```
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY
X-Amz-Date: 20170927T171118Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "IndexReference": {
    "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TW45F26R1HTY2z-stwKBte_Q"
  },
  "TargetReference": {
    "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWcU7IARv0TeaR09zme1sVsw"
  }
}
```

Example Response

This example illustrates one usage of `AttachToIndex`.

```
HTTP/1.1 200 OK
x-amzn-RequestId: e1458e29-a3a6-11e7-a169-c5bf0acd39f4
Date: Wed, 27 Sep 2017 17:11:18 GMT
x-amzn-RequestId: e1458e29-a3a6-11e7-a169-c5bf0acd39f4
Content-Type: application/json
Content-Length: 77

{
  "AttachedObjectIdentifier": "AQGG_AD1fNZBzYHY_JgDt3TWcU7IARv0TeaR09zme1sVsw"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

AttachTypedLink

Attaches a typed link to a specified source and target object. For more information, see [Typed Links](#).

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/typedlink/attach HTTP/1.1
```

```
x-amz-data-partition: DirectoryArn
```

```
Content-type: application/json
```

```
{
  "Attributes": [
    {
      "AttributeName": "string",
      "Value": {
        "BinaryValue": blob,
        "BooleanValue": boolean,
        "DatetimeValue": number,
        "NumberValue": "string",
        "StringValue": "string"
      }
    }
  ],
  "SourceObjectReference": {
    "Selector": "string"
  },
  "TargetObjectReference": {
    "Selector": "string"
  },
  "TypedLinkFacet": {
    "SchemaArn": "string",
    "TypedLinkName": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

DirectoryArn

The Amazon Resource Name (ARN) of the directory where you want to attach the typed link.

Required: Yes

Request Body

The request accepts the following data in JSON format.

Attributes

A set of attributes that are associated with the typed link.

Type: Array of [AttributeNameAndValue](#) objects

Required: Yes

SourceObjectReference

Identifies the source object that the typed link will attach to.

Type: [ObjectReference](#) object

Required: Yes

TargetObjectReference

Identifies the target object that the typed link will attach to.

Type: [ObjectReference](#) object

Required: Yes

TypedLinkFacet

Identifies the typed link facet that is associated with the typed link.

Type: [TypedLinkSchemaAndFacetName](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Content-type: application/json

```
{
  "TypedLinkSpecifier": {
    "IdentityAttributeValues": [
      {
        "AttributeName": "string",
        "Value": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        }
      }
    ],
    "SourceObjectReference": {
      "Selector": "string"
    },
    "TargetObjectReference": {
      "Selector": "string"
    },
    "TypedLinkFacet": {
      "SchemaArn": "string",
      "TypedLinkName": "string"
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

TypedLinkSpecifier

Returns a typed link specifier as output.

Type: [TypedLinkSpecifier](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

FacetValidationException

The [Facet](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidAttachmentException

Indicates that an attempt to make an attachment was invalid. For example, attaching two nodes with a link type that is not applicable to the nodes or attempting to apply a schema to a directory a second time.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of AttachTypedLink.

```
PUT /amazonclouddirectory/2017-01-11/typedlink/attach HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
```

```

Accept-Encoding: identity
Content-Length: 422
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20170928/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=d1b63e72fd13cafb5af77d621891a58849c146c2654d046366d420527a659b48
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY
X-Amz-Date: 20170928T003543Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

```

```

{
  "SourceObjectReference": {
    "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWSvfuEnDqTdmeCuTs6YBNUA"
  },
  "Attributes": [{
    "AttributeName": "22",
    "Value": {
      "BinaryValue": "c3Ry"
    }
  }],
  "TargetObjectReference": {
    "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWcU7IARv0TeaR09zme1sVsw"
  },
  "TypedLinkFacet": {
    "TypedLinkName": "exampletypedlink8",
    "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY/schema/org/1"
  }
}

```

Example Response

This example illustrates one usage of `AttachTypedLink`.

```

HTTP/1.1 200 OK
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Date: Thu, 28 Sep 2017 00:35:44 GMT
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Content-Type: application/json
Content-Length: 521

{
  "TypedLinkSpecifier": {

```

```
"IdentityAttributeValues": [{
  "AttributeName": "22",
  "Value": {
    "BinaryValue": "c3Ry",
    "BooleanValue": null,
    "DatetimeValue": null,
    "NumberValue": null,
    "StringValue": null
  }
}],
"SourceObjectReference": {
  "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWSvfuEnDqTdmeCuTs6YBNUA"
},
"TargetObjectReference": {
  "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWcU7IARv0Tear09zme1sVsw"
},
"TypedLinkFacet": {
  "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY/schema/org/1",
  "TypedLinkName": "exampletypedlink8"
}
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

BatchRead

Performs all the read operations in a batch.

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/batchread HTTP/1.1
```

```
x-amz-data-partition: DirectoryArn
```

```
x-amz-consistency-level: ConsistencyLevel
```

```
Content-type: application/json
```

```
{
  "Operations": [
    {
      "GetLinkAttributes": {
        "AttributeNames": [ "string" ],
        "TypedLinkSpecifier": {
          "IdentityAttributeValues": [
            {
              "AttributeName": "string",
              "Value": {
                "BinaryValue": blob,
                "BooleanValue": boolean,
                "DatetimeValue": number,
                "NumberValue": "string",
                "StringValue": "string"
              }
            }
          ]
        },
        "SourceObjectReference": {
          "Selector": "string"
        },
        "TargetObjectReference": {
          "Selector": "string"
        },
        "TypedLinkFacet": {
          "SchemaArn": "string",
          "TypedLinkName": "string"
        }
      },
      "GetObjectAttributes": {
        "AttributeNames": [ "string" ],
```

```
    "ObjectReference": {
      "Selector": "string"
    },
    "SchemaFacet": {
      "FacetName": "string",
      "SchemaArn": "string"
    }
  },
  "GetObjectInformation": {
    "ObjectReference": {
      "Selector": "string"
    }
  },
  "ListAttachedIndices": {
    "MaxResults": number,
    "NextToken": "string",
    "TargetReference": {
      "Selector": "string"
    }
  },
  "ListIncomingTypedLinks": {
    "FilterAttributeRanges": [
      {
        "AttributeName": "string",
        "Range": {
          "EndMode": "string",
          "EndValue": {
            "BinaryValue": blob,
            "BooleanValue": boolean,
            "DatetimeValue": number,
            "NumberValue": "string",
            "StringValue": "string"
          },
          "StartMode": "string",
          "StartValue": {
            "BinaryValue": blob,
            "BooleanValue": boolean,
            "DatetimeValue": number,
            "NumberValue": "string",
            "StringValue": "string"
          }
        }
      }
    ]
  },
],
```

```

    "FilterTypedLink": {
      "SchemaArn": "string",
      "TypedLinkName": "string"
    },
    "MaxResults": number,
    "NextToken": "string",
    "ObjectReference": {
      "Selector": "string"
    }
  },
  "ListIndex": {
    "IndexReference": {
      "Selector": "string"
    },
    "MaxResults": number,
    "NextToken": "string",
    "RangesOnIndexedValues": [
      {
        "AttributeKey": {
          "FacetName": "string",
          "Name": "string",
          "SchemaArn": "string"
        },
        "Range": {
          "EndMode": "string",
          "EndValue": {
            "BinaryValue": blob,
            "BooleanValue": boolean,
            "DatetimeValue": number,
            "NumberValue": "string",
            "StringValue": "string"
          },
          "StartMode": "string",
          "StartValue": {
            "BinaryValue": blob,
            "BooleanValue": boolean,
            "DatetimeValue": number,
            "NumberValue": "string",
            "StringValue": "string"
          }
        }
      }
    ]
  },
],
},

```

```
"ListObjectAttributes": {
  "FacetFilter": {
    "FacetName": "string",
    "SchemaArn": "string"
  },
  "MaxResults": number,
  "NextToken": "string",
  "ObjectReference": {
    "Selector": "string"
  }
},
"ListObjectChildren": {
  "MaxResults": number,
  "NextToken": "string",
  "ObjectReference": {
    "Selector": "string"
  }
},
"ListObjectParentPaths": {
  "MaxResults": number,
  "NextToken": "string",
  "ObjectReference": {
    "Selector": "string"
  }
},
"ListObjectParents": {
  "MaxResults": number,
  "NextToken": "string",
  "ObjectReference": {
    "Selector": "string"
  }
},
"ListObjectPolicies": {
  "MaxResults": number,
  "NextToken": "string",
  "ObjectReference": {
    "Selector": "string"
  }
},
"ListOutgoingTypedLinks": {
  "FilterAttributeRanges": [
    {
      "AttributeName": "string",
      "Range": {
```

```
    "EndMode": "string",
    "EndValue": {
      "BinaryValue": blob,
      "BooleanValue": boolean,
      "DatetimeValue": number,
      "NumberValue": "string",
      "StringValue": "string"
    },
    "StartMode": "string",
    "StartValue": {
      "BinaryValue": blob,
      "BooleanValue": boolean,
      "DatetimeValue": number,
      "NumberValue": "string",
      "StringValue": "string"
    }
  }
},
],
"FilterTypedLink": {
  "SchemaArn": "string",
  "TypedLinkName": "string"
},
"MaxResults": number,
"NextToken": "string",
"ObjectReference": {
  "Selector": "string"
}
},
"ListPolicyAttachments": {
  "MaxResults": number,
  "NextToken": "string",
  "PolicyReference": {
    "Selector": "string"
  }
},
"LookupPolicy": {
  "MaxResults": number,
  "NextToken": "string",
  "ObjectReference": {
    "Selector": "string"
  }
}
}
```

```
]
}
```

URI Request Parameters

The request uses the following URI parameters.

ConsistencyLevel

Represents the manner and timing in which the successful write or update of an object is reflected in a subsequent read operation of that same object.

Valid Values: `SERIALIZABLE` | `EVENTUAL`

DirectoryArn

The Amazon Resource Name (ARN) that is associated with the [Directory](#). For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

Operations

A list of operations that are part of the batch.

Type: Array of [BatchReadOperation](#) objects

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Responses": [
    {
      "ExceptionResponse": {
```

```
    "Message": "string",
    "Type": "string"
  },
  "SuccessfulResponse": {
    "GetLinkAttributes": {
      "Attributes": [
        {
          "Key": {
            "FacetName": "string",
            "Name": "string",
            "SchemaArn": "string"
          },
          "Value": {
            "BinaryValue": blob,
            "BooleanValue": boolean,
            "DatetimeValue": number,
            "NumberValue": "string",
            "StringValue": "string"
          }
        }
      ]
    },
    "GetObjectAttributes": {
      "Attributes": [
        {
          "Key": {
            "FacetName": "string",
            "Name": "string",
            "SchemaArn": "string"
          },
          "Value": {
            "BinaryValue": blob,
            "BooleanValue": boolean,
            "DatetimeValue": number,
            "NumberValue": "string",
            "StringValue": "string"
          }
        }
      ]
    },
    "GetObjectInformation": {
      "ObjectIdentifier": "string",
      "SchemaFacets": [
        {
```

```

        "FacetName": "string",
        "SchemaArn": "string"
    }
]
},
"ListAttachedIndices": {
    "IndexAttachments": [
        {
            "IndexedAttributes": [
                {
                    "Key": {
                        "FacetName": "string",
                        "Name": "string",
                        "SchemaArn": "string"
                    },
                    "Value": {
                        "BinaryValue": blob,
                        "BooleanValue": boolean,
                        "DatetimeValue": number,
                        "NumberValue": "string",
                        "StringValue": "string"
                    }
                }
            ],
            "ObjectIdentifier": "string"
        }
    ],
    "NextToken": "string"
},
"ListIncomingTypedLinks": {
    "LinkSpecifiers": [
        {
            "IdentityAttributeValues": [
                {
                    "AttributeName": "string",
                    "Value": {
                        "BinaryValue": blob,
                        "BooleanValue": boolean,
                        "DatetimeValue": number,
                        "NumberValue": "string",
                        "StringValue": "string"
                    }
                }
            ]
        }
    ],

```

```

    "SourceObjectReference": {
      "Selector": "string"
    },
    "TargetObjectReference": {
      "Selector": "string"
    },
    "TypedLinkFacet": {
      "SchemaArn": "string",
      "TypedLinkName": "string"
    }
  }
],
"NextToken": "string"
},
"ListIndex": {
  "IndexAttachments": [
    {
      "IndexedAttributes": [
        {
          "Key": {
            "FacetName": "string",
            "Name": "string",
            "SchemaArn": "string"
          },
          "Value": {
            "BinaryValue": blob,
            "BooleanValue": boolean,
            "DatetimeValue": number,
            "NumberValue": "string",
            "StringValue": "string"
          }
        }
      ],
      "ObjectIdentifier": "string"
    }
  ],
  "NextToken": "string"
},
"ListObjectAttributes": {
  "Attributes": [
    {
      "Key": {
        "FacetName": "string",
        "Name": "string",

```

```

        "SchemaArn": "string"
    },
    "Value": {
        "BinaryValue": blob,
        "BooleanValue": boolean,
        "DatetimeValue": number,
        "NumberValue": "string",
        "StringValue": "string"
    }
}
],
"NextToken": "string"
},
"ListObjectChildren": {
    "Children": {
        "string" : "string"
    },
    "NextToken": "string"
},
"ListObjectParentPaths": {
    "NextToken": "string",
    "PathToObjectIdentifiersList": [
        {
            "ObjectIdentifiers": [ "string" ],
            "Path": "string"
        }
    ]
},
"ListObjectParents": {
    "NextToken": "string",
    "ParentLinks": [
        {
            "LinkName": "string",
            "ObjectIdentifier": "string"
        }
    ]
},
"ListObjectPolicies": {
    "AttachedPolicyIds": [ "string" ],
    "NextToken": "string"
},
"ListOutgoingTypedLinks": {
    "NextToken": "string",
    "TypedLinkSpecifiers": [

```

```

    {
      "IdentityAttributeValues": [
        {
          "AttributeName": "string",
          "Value": {
            "BinaryValue": blob,
            "BooleanValue": boolean,
            "DatetimeValue": number,
            "NumberValue": "string",
            "StringValue": "string"
          }
        }
      ],
      "SourceObjectReference": {
        "Selector": "string"
      },
      "TargetObjectReference": {
        "Selector": "string"
      },
      "TypedLinkFacet": {
        "SchemaArn": "string",
        "TypedLinkName": "string"
      }
    }
  ],
  "ListPolicyAttachments": {
    "NextToken": "string",
    "ObjectIdentifiers": [ "string" ]
  },
  "LookupPolicy": {
    "NextToken": "string",
    "PolicyToPathList": [
      {
        "Path": "string",
        "Policies": [
          {
            "ObjectIdentifier": "string",
            "PolicyId": "string",
            "PolicyType": "string"
          }
        ]
      }
    ]
  }
]

```

```
    }  
  }  
}  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Responses](#)

A list of all the responses for each batch read.

Type: Array of [BatchReadOperationResponse](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of BatchRead.

```
POST /amazonclouddirectory/2017-01-11/batchread HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 18
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8
```

```
x-amz-consistency-level: EVENTUAL
X-Amz-Date: 20170922T233414Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20170922/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-consistency-level;x-amz-data-
partition;x-amz-date,
  Signature=dcf33d791a3f742d04edde6107c4795918d7e034c32f0029a49c95a9fe79cd40

{
  "Operations": []
}
```

Example Response

This example illustrates one usage of BatchRead.

```
HTTP/1.1 200 OK
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Date: Thu, 22 Sep 2017 00:35:44 GMT
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Content-Type: application/json
Content-Length: 521

{
  "Responses": []
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

BatchWrite

Performs all the write operations in a batch. Either all the operations succeed or none.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/batchwrite HTTP/1.1
```

```
x-amz-data-partition: DirectoryArn
```

```
Content-type: application/json
```

```
{
  "Operations": [
    {
      "AddFacetToObject": {
        "ObjectAttributeList": [
          {
            "Key": {
              "FacetName": "string",
              "Name": "string",
              "SchemaArn": "string"
            },
            "Value": {
              "BinaryValue": blob,
              "BooleanValue": boolean,
              "DatetimeValue": number,
              "NumberValue": "string",
              "StringValue": "string"
            }
          }
        ],
        "ObjectReference": {
          "Selector": "string"
        },
        "SchemaFacet": {
          "FacetName": "string",
          "SchemaArn": "string"
        }
      },
      "AttachObject": {
        "ChildReference": {
          "Selector": "string"
        },
        "LinkName": "string",
```

```
    "ParentReference": {
      "Selector": "string"
    }
  },
  "AttachPolicy": {
    "ObjectReference": {
      "Selector": "string"
    },
    "PolicyReference": {
      "Selector": "string"
    }
  },
  "AttachToIndex": {
    "IndexReference": {
      "Selector": "string"
    },
    "TargetReference": {
      "Selector": "string"
    }
  },
  "AttachTypedLink": {
    "Attributes": [
      {
        "AttributeName": "string",
        "Value": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        }
      }
    ],
    "SourceObjectReference": {
      "Selector": "string"
    },
    "TargetObjectReference": {
      "Selector": "string"
    },
    "TypedLinkFacet": {
      "SchemaArn": "string",
      "TypedLinkName": "string"
    }
  },
},
```

```
"CreateIndex": {
  "BatchReferenceName": "string",
  "IsUnique": boolean,
  "LinkName": "string",
  "OrderedIndexedAttributeList": [
    {
      "FacetName": "string",
      "Name": "string",
      "SchemaArn": "string"
    }
  ],
  "ParentReference": {
    "Selector": "string"
  }
},
"CreateObject": {
  "BatchReferenceName": "string",
  "LinkName": "string",
  "ObjectAttributeList": [
    {
      "Key": {
        "FacetName": "string",
        "Name": "string",
        "SchemaArn": "string"
      },
      "Value": {
        "BinaryValue": blob,
        "BooleanValue": boolean,
        "DatetimeValue": number,
        "NumberValue": "string",
        "StringValue": "string"
      }
    }
  ],
  "ParentReference": {
    "Selector": "string"
  },
  "SchemaFacet": [
    {
      "FacetName": "string",
      "SchemaArn": "string"
    }
  ]
},
```

```

"DeleteObject": {
  "ObjectReference": {
    "Selector": "string"
  }
},
"DetachFromIndex": {
  "IndexReference": {
    "Selector": "string"
  },
  "TargetReference": {
    "Selector": "string"
  }
},
"DetachObject": {
  "BatchReferenceName": "string",
  "LinkName": "string",
  "ParentReference": {
    "Selector": "string"
  }
},
"DetachPolicy": {
  "ObjectReference": {
    "Selector": "string"
  },
  "PolicyReference": {
    "Selector": "string"
  }
},
"DetachTypedLink": {
  "TypedLinkSpecifier": {
    "IdentityAttributeValues": [
      {
        "AttributeName": "string",
        "Value": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        }
      }
    ]
  },
  "SourceObjectReference": {
    "Selector": "string"
  }
}

```

```

    },
    "TargetObjectReference": {
      "Selector": "string"
    },
    "TypedLinkFacet": {
      "SchemaArn": "string",
      "TypedLinkName": "string"
    }
  }
},
"RemoveFacetFromObject": {
  "ObjectReference": {
    "Selector": "string"
  },
  "SchemaFacet": {
    "FacetName": "string",
    "SchemaArn": "string"
  }
},
"UpdateLinkAttributes": {
  "AttributeUpdates": [
    {
      "AttributeAction": {
        "AttributeActionType": "string",
        "AttributeUpdateValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        }
      },
      "AttributeKey": {
        "FacetName": "string",
        "Name": "string",
        "SchemaArn": "string"
      }
    }
  ],
  "TypedLinkSpecifier": {
    "IdentityAttributeValues": [
      {
        "AttributeName": "string",
        "Value": {

```

```

        "BinaryValue": blob,
        "BooleanValue": boolean,
        "DatetimeValue": number,
        "NumberValue": "string",
        "StringValue": "string"
    }
}
],
"SourceObjectReference": {
    "Selector": "string"
},
"TargetObjectReference": {
    "Selector": "string"
},
"TypedLinkFacet": {
    "SchemaArn": "string",
    "TypedLinkName": "string"
}
}
},
"UpdateObjectAttributes": {
    "AttributeUpdates": [
        {
            "ObjectAttributeAction": {
                "ObjectAttributeActionType": "string",
                "ObjectAttributeUpdateValue": {
                    "BinaryValue": blob,
                    "BooleanValue": boolean,
                    "DatetimeValue": number,
                    "NumberValue": "string",
                    "StringValue": "string"
                }
            },
            "ObjectAttributeKey": {
                "FacetName": "string",
                "Name": "string",
                "SchemaArn": "string"
            }
        }
    ],
    "ObjectReference": {
        "Selector": "string"
    }
}
}

```

```
    }  
  ]  
}
```

URI Request Parameters

The request uses the following URI parameters.

DirectoryArn

The Amazon Resource Name (ARN) that is associated with the [Directory](#). For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

Operations

A list of operations that are part of the batch.

Type: Array of [BatchWriteOperation](#) objects

Required: Yes

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json  
  
{  
  "Responses": [  
    {  
      "AddFacetToObject": {  
      },  
      "AttachObject": {  
        "attachedObjectIdentifier": "string"  
      },  
      "AttachPolicy": {  
      },  
    }  
  ]  
}
```

```

"AttachToIndex": {
  "AttachedObjectIdentifier": "string"
},
"AttachTypedLink": {
  "TypedLinkSpecifier": {
    "IdentityAttributeValues": [
      {
        "AttributeName": "string",
        "Value": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        }
      }
    ],
    "SourceObjectReference": {
      "Selector": "string"
    },
    "TargetObjectReference": {
      "Selector": "string"
    },
    "TypedLinkFacet": {
      "SchemaArn": "string",
      "TypedLinkName": "string"
    }
  }
},
"CreateIndex": {
  "ObjectIdentifier": "string"
},
"CreateObject": {
  "ObjectIdentifier": "string"
},
"DeleteObject": {
},
"DetachFromIndex": {
  "DetachedObjectIdentifier": "string"
},
"DetachObject": {
  "detachedObjectIdentifier": "string"
},
"DetachPolicy": {

```

```
    },
    "DetachTypedLink": {
    },
    "RemoveFacetFromObject": {
    },
    "UpdateLinkAttributes": {
    },
    "UpdateObjectAttributes": {
      "ObjectIdentifier": "string"
    }
  }
]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Responses

A list of all the responses for each batch write.

Type: Array of [BatchWriteOperationResponse](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

BatchWriteException

A BatchWrite exception has occurred.

HTTP Status Code: 400

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of BatchWrite.

```
PUT /amazonclouddirectory/2017-01-11/batchwrite HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 18
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20170922/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=e539506cd67ac7a753fa37aa58272f4c7bda369fc0f6b4f7bff6bea0f0fcd4af
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mAO3dNY
X-Amz-Date: 20170922T232444Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "Operations": []
}
```

Example Response

This example illustrates one usage of BatchWrite.

```
HTTP/1.1 200 OK
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Date: Thu, 22 Sep 2017 00:35:44 GMT
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Content-Type: application/json
Content-Length: 521

{
  "Responses": []
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateDirectory

Creates a [Directory](#) by copying the published schema into the directory. A directory cannot be created without a schema.

You can also quickly create a directory using a managed schema, called the QuickStartSchema. For more information, see [Managed Schema](#) in the *Amazon Cloud Directory Developer Guide*.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/directory/create HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json

{
  "Name": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

[SchemaArn](#)

The Amazon Resource Name (ARN) of the published schema that will be copied into the data [Directory](#). For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

[Name](#)

The name of the [Directory](#). Should be unique per account, per region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AppliedSchemaArn": "string",
  "DirectoryArn": "string",
  "Name": "string",
  "ObjectIdentifier": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AppliedSchemaArn

The ARN of the published schema in the [Directory](#). Once a published schema is copied into the directory, it has its own ARN, which is referred to as applied schema ARN. For more information, see [Arn Examples](#).

Type: String

DirectoryArn

The ARN that is associated with the [Directory](#). For more information, see [Arn Examples](#).

Type: String

Name

The name of the [Directory](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._-]*$`

ObjectIdentifier

The root object node of the created directory.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryAlreadyExistsException

Indicates that a [Directory](#) could not be created due to a naming conflict. Choose a different name and try again.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of CreateDirectory.

```
PUT /amazonclouddirectory/2017-01-11/directory/create HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 22
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20170922/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=f347d3f8d6ceccbfd47738ab11fe0194b5efd329b4e0431f7221ee80c672fd9a
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:schema/published/
person/1
X-Amz-Date: 20170922T220642Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
```

```
"Name": "ExampleCD"
}
```

Example Response

This example illustrates one usage of `CreateDirectory`.

```
HTTP/1.1 200 OK
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Date: Thu, 22 Sep 2017 00:35:44 GMT
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Content-Type: application/json
Content-Length: 521

{
  "AppliedSchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AfMr4qym1kZTvwq0afAYfqI/schema/person/1",
  "DirectoryArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AfMr4qym1kZTvwq0afAYfqI",
  "Name": "ExampleCD",
  "ObjectIdentifier": "AQHzK-KsptZGU78KjmnwGH6i-4guCM3uQFOTA9_NjeHDrg"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateFacet

Creates a new [Facet](#) in a schema. Facet creation is allowed only in development or applied schemas.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/facet/create HTTP/1.1
```

```
x-amz-data-partition: SchemaArn
```

```
Content-type: application/json
```

```
{
  "Attributes": [
    {
      "AttributeDefinition": {
        "DefaultValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        },
        "IsImmutable": boolean,
        "Rules": {
          "string" : {
            "Parameters": {
              "string" : "string"
            },
            "Type": "string"
          }
        },
        "Type": "string"
      },
      "AttributeReference": {
        "TargetAttributeName": "string",
        "TargetFacetName": "string"
      },
      "Name": "string",
      "RequiredBehavior": "string"
    }
  ],
  "FacetStyle": "string",
  "Name": "string",
  "ObjectType": "string"
}
```

```
}
```

URI Request Parameters

The request uses the following URI parameters.

SchemaArn

The schema ARN in which the new [Facet](#) will be created. For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

Attributes

The attributes that are associated with the [Facet](#).

Type: Array of [FacetAttribute](#) objects

Required: No

FacetStyle

There are two different styles that you can define on any given facet, `Static` and `Dynamic`. For static facets, all attributes must be defined in the schema. For dynamic facets, attributes can be defined during data plane operations.

Type: String

Valid Values: `STATIC` | `DYNAMIC`

Required: No

Name

The name of the [Facet](#), which is unique for a given schema.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

ObjectType

Specifies whether a given object created from this facet is of type node, leaf node, policy or index.

- Node: Can have multiple children but one parent.
- Leaf node: Cannot have children but can have multiple parents.
- Policy: Allows you to store a policy document and policy type. For more information, see [Policies](#).
- Index: Can be created with the Index API.

Type: String

Valid Values: NODE | LEAF_NODE | POLICY | INDEX

Required: No

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

FacetAlreadyExistsException

A facet with the same name already exists.

HTTP Status Code: 400

FacetValidationException

The [Facet](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidRuleException

Occurs when any of the rule parameter keys or values are invalid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using

“SERIALIZABLE” consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of CreateFacet.

```
PUT /amazonclouddirectory/2017-01-11/facet/create HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 39
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20170922/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=d6b41d921e64be7413abf9bd9036289cb34ace20275ed17dee45e594622ced4b
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY/schema/org/1
X-Amz-Date: 20170922T214008Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "Name": "node1",
  "ObjectType": "NODE"
}
```

Example Response

This example illustrates one usage of CreateFacet.

```
HTTP/1.1 200 OK
```

```
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Date: Thu, 22 Sep 2017 00:35:44 GMT
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Content-Type: application/json
Content-Length: 521
```

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateIndex

Creates an index object. See [Indexing and search](#) for more information.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/index HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json
```

```
{
  "IsUnique": boolean,
  "LinkName": "string",
  "OrderedIndexedAttributeList": [
    {
      "FacetName": "string",
      "Name": "string",
      "SchemaArn": "string"
    }
  ],
  "ParentReference": {
    "Selector": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

[DirectoryArn](#)

The ARN of the directory where the index should be created.

Required: Yes

Request Body

The request accepts the following data in JSON format.

[IsUnique](#)

Indicates whether the attribute that is being indexed has unique values or not.

Type: Boolean

Required: Yes

LinkName

The name of the link between the parent object and the index object.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[^\\\/\[\]\(\):\{\}\#\@!\?\s\\;]+`

Required: No

OrderedIndexedAttributeList

Specifies the attributes that should be indexed on. Currently only a single attribute is supported.

Type: Array of [AttributeKey](#) objects

Required: Yes

ParentReference

A reference to the parent object that contains the index object.

Type: [ObjectReference](#) object

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ObjectIdentifier": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ObjectIdentifier

The `ObjectIdentifier` of the index created by this operation.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

FacetValidationException

The [Facet](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

LinkNameAlreadyInUseException

Indicates that a link could not be created due to a naming conflict. Choose a different name and then try again.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

UnsupportedIndexTypeException

Indicates that the requested index type is not supported.

HTTP Status Code: 400

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of CreateIndex.

```
PUT /amazonclouddirectory/2017-01-11/index HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 290
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20170913/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=dc93fb34cd655e125aa748b8747d99bef78c7c5785e30327cf151d74accbbcf0
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AXQDXvdgk0WktRXV4HnRa8
X-Amz-Date: 20170913T012153Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "ParentReference":{
    "Selector":"/"
  },
  "OrderedIndexedAttributeList":[
    {
      "SchemaArn":"arn:aws:clouddirectory:us-west-2:45132example:directory/
AXQDXvdgk0WktRXV4HnRa8/schema/Examplepersonschema/1",
      "FacetName":"Organization_Person",
      "Name":"manager"
    }
  ],
  "IsUnique":true,
  "LinkName":"Examplelink"
}
```

Example Response

This example illustrates one usage of CreateIndex.

```
HTTP/1.1 200 OK
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Date: Thu, 13 Sep 2017 00:35:44 GMT
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Content-Type: application/json
Content-Length: 521
```

```
{
  "ObjectIdentifier": "AQF0Fw173YJD1pLUV1eB50Wv4vU99HjyQIShCCUeVob2fw"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateObject

Creates an object in a [Directory](#). Additionally attaches the object to a parent, if a parent reference and LinkName is specified. An object is simply a collection of [Facet](#) attributes. You can also use this API call to create a policy object, if the facet from which you create the object is a policy facet.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/object HTTP/1.1
```

```
x-amz-data-partition: DirectoryArn
```

```
Content-type: application/json
```

```
{
  "LinkName": "string",
  "ObjectAttributeList": [
    {
      "Key": {
        "FacetName": "string",
        "Name": "string",
        "SchemaArn": "string"
      },
      "Value": {
        "BinaryValue": blob,
        "BooleanValue": boolean,
        "DatetimeValue": number,
        "NumberValue": "string",
        "StringValue": "string"
      }
    }
  ],
  "ParentReference": {
    "Selector": "string"
  },
  "SchemaFacets": [
    {
      "FacetName": "string",
      "SchemaArn": "string"
    }
  ]
}
```

URI Request Parameters

The request uses the following URI parameters.

[DirectoryArn](#)

The Amazon Resource Name (ARN) that is associated with the [Directory](#) in which the object will be created. For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

[LinkName](#)

The name of link that is used to attach this object to a parent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[^\\\/\[\]\(\):\{\}\#\@!\?\s\\;]+`

Required: No

[ObjectAttributeList](#)

The attribute map whose attribute ARN contains the key and attribute value as the map value.

Type: Array of [AttributeKeyAndValue](#) objects

Required: No

[ParentReference](#)

If specified, the parent reference to which this object will be attached.

Type: [ObjectReference](#) object

Required: No

SchemaFacets

A list of schema facets to be associated with the object. Do not provide minor version components. See [SchemaFacet](#) for details.

Type: Array of [SchemaFacet](#) objects

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ObjectIdentifier": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ObjectIdentifier

The identifier that is associated with the object.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

FacetValidationException

The [Facet](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

LinkNameAlreadyInUseException

Indicates that a link could not be created due to a naming conflict. Choose a different name and then try again.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using

“SERIALIZABLE” consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

UnsupportedIndexTypeException

Indicates that the requested index type is not supported.

HTTP Status Code: 400

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of `CreateObject`.

```
PUT /amazonclouddirectory/2017-01-11/object HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 196
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20170912/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=af5780db69f39c02593f384e0ad70528f9c833e67d47e8e37ac456c10c994aa0
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AXQXDXvdgk0WktRXV4HnRa8
X-Amz-Date: 20170912T184134Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "SchemaFacets": [
    {
      "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AXQXDXvdgk0WktRXV4HnRa8/schema/Examplepersonschema/1",
```

```
        "FacetName": "Organization_Person"
    }
]
}
```

Example Response

This example illustrates one usage of `CreateObject`.

```
HTTP/1.1 200 OK
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Date: Thu, 12 Sep 2017 00:35:44 GMT
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Content-Type: application/json
Content-Length: 521

{
  "ObjectIdentifier": "AQF0Fw173YJD1pLUV1eB50WvP1K49muETy2xCqhXZK2s-A"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateSchema

Creates a new schema in a development state. A schema can exist in three phases:

- *Development*: This is a mutable phase of the schema. All new schemas are in the development phase. Once the schema is finalized, it can be published.
- *Published*: Published schemas are immutable and have a version associated with them.
- *Applied*: Applied schemas are mutable in a way that allows you to add new schema facets. You can also add new, nonrequired attributes to existing schema facets. You can apply only published schemas to directories.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/schema/create HTTP/1.1
Content-type: application/json

{
  "Name": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Name

The name that is associated with the schema. This is unique to each account and in each region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "SchemaArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[SchemaArn](#)

The Amazon Resource Name (ARN) that is associated with the schema. For more information, see [Arn Examples](#).

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

SchemaAlreadyExistsException

Indicates that a schema could not be created due to a naming conflict. Please select a different name and then try again.

HTTP Status Code: 400

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of CreateSchema.

```
PUT /amazonclouddirectory/2017-01-11/schema/create HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 21
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20170927/
us-west-2/clouddirectory/aws4_request, SignedHeaders=host;x-amz-date,
Signature=92b2be88dd90f3e789ff651f5ae897b35f601e2f6a4d08addb07993ef8399e29
X-Amz-Date: 20170927T164420Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "Name": "Customers"
}
```

Example Response

This example illustrates one usage of CreateSchema.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 2c3050f1-a3a3-11e7-bd9d-f9e3493b0666
Date: Wed, 27 Sep 2017 16:44:47 GMT
x-amzn-RequestId: 2c3050f1-a3a3-11e7-bd9d-f9e3493b0666
Content-Type: application/json
Content-Length: 90

{
  "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:schema/development/
Customers"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateTypedLinkFacet

Creates a [TypedLinkFacet](#). For more information, see [Typed Links](#).

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/typedlink/facet/create HTTP/1.1
```

```
x-amz-data-partition: SchemaArn
```

```
Content-type: application/json
```

```
{
  "Facet": {
    "Attributes": [
      {
        "DefaultValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        },
        "IsImmutable": boolean,
        "Name": "string",
        "RequiredBehavior": "string",
        "Rules": {
          "string" : {
            "Parameters": {
              "string" : "string"
            },
            "Type": "string"
          }
        },
        "Type": "string"
      }
    ],
    "IdentityAttributeOrder": [ "string" ],
    "Name": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

SchemaArn

The Amazon Resource Name (ARN) that is associated with the schema. For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

Facet

[Facet](#) structure that is associated with the typed link facet.

Type: [TypedLinkFacet](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

FacetAlreadyExistsException

A facet with the same name already exists.

HTTP Status Code: 400

FacetValidationException

The [Facet](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidRuleException

Occurs when any of the rule parameter keys or values are invalid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using

“SERIALIZABLE” consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of `CreateTypedLinkFacet`.

```
PUT /amazonclouddirectory/2017-01-11/typedlink/facet/create HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 156
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20170923/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=b174c239b7f8e0ef63f16c7755d3655a16f7b812e2f93008eb0447fb611cfefa
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:schema/development/
typedlinkschema
X-Amz-Date: 20170923T004008Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "Facet": {
    "Attributes": [{
      "RequiredBehavior": "REQUIRED_ALWAYS",
      "Type": "BINARY",
      "Name": "1"
    }],
    "IdentityAttributeOrder": ["1"],
    "Name": "FacetExample"
  }
}
```

```
}
```

Example Response

This example illustrates one usage of `CreateTypedLinkFacet`.

```
HTTP/1.1 200 OK
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Date: Thu, 23 Sep 2017 00:35:44 GMT
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Content-Type: application/json
Content-Length: 521
```

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteDirectory

Deletes a directory. Only disabled directories can be deleted. A deleted directory cannot be undone. Exercise extreme caution when deleting directories.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/directory HTTP/1.1
x-amz-data-partition: DirectoryArn
```

URI Request Parameters

The request uses the following URI parameters.

DirectoryArn

The ARN of the directory to delete.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "DirectoryArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DirectoryArn

The ARN of the deleted directory.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryDeletedException

A directory that has been deleted and to which access has been attempted. Note: The requested resource will eventually cease to exist.

HTTP Status Code: 400

DirectoryNotDisabledException

An operation can only operate on a disabled directory.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of DeleteDirectory.

```
PUT /amazonclouddirectory/2017-01-11/directory HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 0
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171009/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=671e5a6db08c16becf5a59a956690cbdf3da4a089022e919d1f185ae3365c46a
```

```
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/  
AXQXDXvdgk0WktRXV4HnRa8  
X-Amz-Date: 20171009T173437Z  
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8
```

Example Response

This example illustrates one usage of DeleteDirectory.

```
HTTP/1.1 200 OK  
x-amzn-RequestId: 2061f3c0-ad18-11e7-8502-0566a31305cf  
Date: Mon, 09 Oct 2017 17:34:39 GMT  
x-amzn-RequestId: 2061f3c0-ad18-11e7-8502-0566a31305cf  
Content-Type: application/json  
Content-Length: 98  
  
{  
  "DirectoryArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/  
AXQXDXvdgk0WktRXV4HnRa8"  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteFacet

Deletes a given [Facet](#). All attributes and [Rules](#) that are associated with the facet will be deleted. Only development schema facets are allowed deletion.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/facet/delete HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json

{
  "Name": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

[SchemaArn](#)

The Amazon Resource Name (ARN) that is associated with the [Facet](#). For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

[Name](#)

The name of the facet to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

FacetInUseException

Occurs when deleting a facet that contains an attribute that is a target to an attribute reference in a different facet.

HTTP Status Code: 400

FacetNotFoundException

The specified [Facet](#) could not be found.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of DeleteFacet.

```
PUT /amazonclouddirectory/2017-01-11/facet/delete HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 24
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171009/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=67a330fb824e90451da06dd85e94ac37865044e9c933657a298457bd46660b07
```

```
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:schema/development/
exampleorgtest
X-Amz-Date: 20171009T182210Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "Name": "Organization"
}
```

Example Response

This example illustrates one usage of DeleteFacet.

```
HTTP/1.1 200 OK
x-amzn-RequestId: c4f739ec-ad1e-11e7-a6de-b54884d62153
Date: Mon, 09 Oct 2017 18:22:11 GMT
x-amzn-RequestId: c4f739ec-ad1e-11e7-a6de-b54884d62153
Content-Type: application/json
Content-Length: 2

{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteObject

Deletes an object and its associated attributes. Only objects with no children and no parents can be deleted. The maximum number of attributes that can be deleted during an object deletion is 30. For more information, see [Amazon Cloud Directory Limits](#).

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/object/delete HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json

{
  "ObjectReference": {
    "Selector": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

[DirectoryArn](#)

The Amazon Resource Name (ARN) that is associated with the [Directory](#) where the object resides. For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

[ObjectReference](#)

A reference that identifies the object.

Type: [ObjectReference](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ObjectNotDetachedException

Indicates that the requested operation cannot be completed because the object has not been detached from the tree.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of DeleteObject.

```
PUT /amazonclouddirectory/2017-01-11/object/delete HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 84
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171009/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=7b16ec6d1d54f36672cb2d39f1e975925e5222208ff8c6a8cd4e1a63dd17df70
```

```
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AfMr4qym1kZTvwq0afAYfqI
X-Amz-Date: 20171009T183947Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "ObjectReference": {
    "Selector": "$AQHzK-KsptZGU78KjmnwGH6i8H-voMZDNCqfx-fRUcBFg"
  }
}
```

Example Response

This example illustrates one usage of DeleteObject.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 3b1928f3-ad21-11e7-81c0-7b48a7696e76
Date: Mon, 09 Oct 2017 18:39:48 GMT
x-amzn-RequestId: 3b1928f3-ad21-11e7-81c0-7b48a7696e76
Content-Type: application/json
Content-Length: 2

{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

DeleteSchema

Deletes a given schema. Schemas in a development and published state can only be deleted.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/schema HTTP/1.1
x-amz-data-partition: SchemaArn
```

URI Request Parameters

The request uses the following URI parameters.

SchemaArn

The Amazon Resource Name (ARN) of the development schema. For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "SchemaArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

SchemaArn

The input ARN that is returned as part of the response. For more information, see [Arn Examples](#).

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using

“SERIALIZABLE” consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

StillContainsLinksException

The object could not be deleted because links still exist. Remove the links and then try the operation again.

HTTP Status Code: 400

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of DeleteSchema.

```
PUT /amazonclouddirectory/2017-01-11/schema HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 0
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171009/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=f2ac3f0780f6e0fa9115c1a7e19353dbc607eac30420fceacba09a189d057b44
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:schema/development/
exampleorgtest
X-Amz-Date: 20171009T185055Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8
```

Example Response

This example illustrates one usage of DeleteSchema.

```
HTTP/1.1 200 OK
x-amzn-RequestId: c92b705e-ad22-11e7-8502-0566a31305cf
Date: Mon, 09 Oct 2017 18:50:57 GMT
x-amzn-RequestId: c92b705e-ad22-11e7-8502-0566a31305cf
Content-Type: application/json
Content-Length: 95

{
  "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:schema/development/
exampleorgtest"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteTypedLinkFacet

Deletes a [TypedLinkFacet](#). For more information, see [Typed Links](#).

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/typedlink/facet/delete HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json
```

```
{
  "Name": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

[SchemaArn](#)

The Amazon Resource Name (ARN) that is associated with the schema. For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

[Name](#)

The unique name of the typed link facet.

Type: String

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

FacetNotFoundException

The specified [Facet](#) could not be found.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of DeleteTypedLinkFacet.

```
PUT /amazonclouddirectory/2017-01-11/typedlink/facet/delete HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 24
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171009/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=a8d2e25d4f3051fb3820effa2fc21cfe3327bea088e45c53199a5d2a2db9e1d6
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:schema/development/
typedlinkschematest
X-Amz-Date: 20171009T190948Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
```

```
"Name": "ExampleFacet"  
}
```

Example Response

This example illustrates one usage of DeleteTypedLinkFacet.

```
HTTP/1.1 200 OK  
x-amzn-RequestId: 6cbc3bb3-ad25-11e7-98a0-81d6fbb0fa15  
Date: Mon, 09 Oct 2017 19:09:50 GMT  
x-amzn-RequestId: 6cbc3bb3-ad25-11e7-98a0-81d6fbb0fa15  
Content-Type: application/json  
Content-Length: 2  
  
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DetachFromIndex

Detaches the specified object from the specified index.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/index/detach HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json

{
  "IndexReference": {
    "Selector": "string"
  },
  "TargetReference": {
    "Selector": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

DirectoryArn

The Amazon Resource Name (ARN) of the directory the index and object exist in.

Required: Yes

Request Body

The request accepts the following data in JSON format.

IndexReference

A reference to the index object.

Type: [ObjectReference](#) object

Required: Yes

TargetReference

A reference to the object being detached from the index.

Type: [ObjectReference](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "DetachedObjectIdentifier": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DetachedObjectIdentifier

The `ObjectIdentifier` of the object that was detached from the index.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

NotIndexException

Indicates that the requested operation can only operate on index objects.

HTTP Status Code: 400

ObjectAlreadyDetachedException

Indicates that the object is not attached to the index.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous

write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of `DetachFromIndex`.

```
PUT /amazonclouddirectory/2017-01-11/index/detach HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 167
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171009/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=78a7d77e2d49bc312be21f048fd10742dc50c838314696f2f58e99658137773b
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY
X-Amz-Date: 20171009T195357Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "IndexReference": {
    "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TW45F26R1HTY2z-stwKBte_Q"
  },
  "TargetReference": {
    "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWcU7IARv0TearR09zme1sVsw"
  }
}
```

Example Response

This example illustrates one usage of `DetachFromIndex`.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 9746ae70-ad2b-11e7-81c0-7b48a7696e76
Date: Mon, 09 Oct 2017 19:53:59 GMT
x-amzn-RequestId: 9746ae70-ad2b-11e7-81c0-7b48a7696e76
Content-Type: application/json
Content-Length: 77

{
  "DetachedObjectIdentifier": "AQGG_AD1fNZBzYHY_JgDt3TWcU7IARv0TeaR09zme1sVsw"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DetachObject

Detaches a given object from the parent object. The object that is to be detached from the parent is specified by the link name.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/object/detach HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json

{
  "LinkName": "string",
  "ParentReference": {
    "Selector": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

DirectoryArn

The Amazon Resource Name (ARN) that is associated with the [Directory](#) where objects reside. For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

LinkName

The link name associated with the object that needs to be detached.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[^\\\/[\]\(\):\{\}\#\@!\?\s\\;]+`

Required: Yes

[ParentReference](#)

The parent reference from which the object with the specified link name is detached.

Type: [ObjectReference](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "DetachedObjectIdentifier": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[DetachedObjectIdentifier](#)

The `ObjectIdentifier` that was detached from the object.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

NotNodeException

Occurs when any invalid operations are performed on an object that is not a node, such as calling `ListObjectChildren` for a leaf node object.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of `DetachObject`.

```
PUT /amazonclouddirectory/2017-01-11/object/detach HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 105
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171016/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=e994ca925acaa6fc6d03c9bc505e5f634fc0847563f32025ed500ea05bc5f389
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY
X-Amz-Date: 20171016T231940Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "ParentReference": {
    "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWcU7IARv0TeaR09zme1sVsw"
  },
  "LinkName": "link2"
}
```

Example Response

This example illustrates one usage of `DetachObject`.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 7d42c361-b2c8-11e7-81c0-7b48a7696e76
Date: Mon, 16 Oct 2017 23:19:41 GMT
```

```
x-amzn-RequestId: 7d42c361-b2c8-11e7-81c0-7b48a7696e76
Content-Type: application/json
Content-Length: 77

{
  "DetachedObjectIdentifier": "AQGG_AD1fNZBzYHY_JgDt3TWSvfuEnDqTdmeCuTs6YBNUA"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DetachPolicy

Detaches a policy from an object.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/policy/detach HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json

{
  "ObjectReference": {
    "Selector": "string"
  },
  "PolicyReference": {
    "Selector": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

DirectoryArn

The Amazon Resource Name (ARN) that is associated with the [Directory](#) where both objects reside. For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

ObjectReference

Reference that identifies the object whose policy object will be detached.

Type: [ObjectReference](#) object

Required: Yes

PolicyReference

Reference that identifies the policy object.

Type: [ObjectReference](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

NotPolicyException

Indicates that the requested operation can only operate on policy objects.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of DetachPolicy.

```
PUT /amazonclouddirectory/2017-01-11/policy/detach HTTP/1.1
```

```
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 168
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171017/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=c4e16e1a1fae26ec2a5531e95ea261c6f7255e5639438bd56af0c0ce9dafc700
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY
X-Amz-Date: 20171017T185834Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "PolicyReference": {
    "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWgcBsTVmcQEws6jlygfhuew"
  },
  "ObjectReference": {
    "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWQoovm1s3Ts2v0NKrzdVnPw"
  }
}
```

Example Response

This example illustrates one usage of DetachPolicy.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 2d7a5bcf-b36d-11e7-81c0-7b48a7696e76
Date: Tue, 17 Oct 2017 18:58:34 GMT
x-amzn-RequestId: 2d7a5bcf-b36d-11e7-81c0-7b48a7696e76
Content-Type: application/json
Content-Length: 2

{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DetachTypedLink

Detaches a typed link from a specified source and target object. For more information, see [Typed Links](#).

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/typedlink/detach HTTP/1.1
```

```
x-amz-data-partition: DirectoryArn
```

```
Content-type: application/json
```

```
{
  "TypedLinkSpecifier": {
    "IdentityAttributeValues": [
      {
        "AttributeName": "string",
        "Value": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        }
      }
    ],
    "SourceObjectReference": {
      "Selector": "string"
    },
    "TargetObjectReference": {
      "Selector": "string"
    },
    "TypedLinkFacet": {
      "SchemaArn": "string",
      "TypedLinkName": "string"
    }
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

DirectoryArn

The Amazon Resource Name (ARN) of the directory where you want to detach the typed link.

Required: Yes

Request Body

The request accepts the following data in JSON format.

TypedLinkSpecifier

Used to accept a typed link specifier as input.

Type: [TypedLinkSpecifier](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

FacetValidationException

The [Facet](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of `DetachTypedLink`.

```

PUT /amazonclouddirectory/2017-01-11/typedlink/detach HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 459
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20170927/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=f2b55a0895ed644a5acfa07e793f5b2d25166c91c5f3be765004cd0b1c1613c1
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY
X-Amz-Date: 20170927T191638Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "TypedLinkSpecifier": {
    "SourceObjectReference": {
      "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWSvfuEnDqTdmeCuTs6YBNUA"
    },
    "IdentityAttributeValues": [{
      "AttributeName": "22",
      "Value": {
        "BinaryValue": "c3Ry"
      }
    }],
    "TargetObjectReference": {
      "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWcU7IARv0TearR09zme1sVsw"
    },
    "TypedLinkFacet": {
      "TypedLinkName": "exampltypedlink8",
      "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY/schema/org/1"
    }
  }
}

```

```
}
```

Example Response

This example illustrates one usage of `DetachTypedLink`.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 6340a418-a3b8-11e7-8502-0566a31305cf
Date: Wed, 27 Sep 2017 19:16:38 GMT
x-amzn-RequestId: 6340a418-a3b8-11e7-8502-0566a31305cf
Content-Type: application/json
Content-Length: 0
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisableDirectory

Disables the specified directory. Disabled directories cannot be read or written to. Only enabled directories can be disabled. Disabled directories may be reenabled.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/directory/disable HTTP/1.1
x-amz-data-partition: DirectoryArn
```

URI Request Parameters

The request uses the following URI parameters.

DirectoryArn

The ARN of the directory to disable.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "DirectoryArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DirectoryArn

The ARN of the directory that has been disabled.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryDeletedException

A directory that has been deleted and to which access has been attempted. Note: The requested resource will eventually cease to exist.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of DisableDirectory.

```
PUT /amazonclouddirectory/2017-01-11/directory/disable HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 0
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171006/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=2d3c51c700aee56ce68f0c2981c6dc08a413cd771ec9349b5190519c2c2d8a87
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AXQXDxvdgk0WktRXV4HnRa8
X-Amz-Date: 20171006T011145Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8
```

Example Response

This example illustrates one usage of `DisableDirectory`.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 51db4cc5-aa33-11e7-98a0-81d6fbb0fa15
Date: Fri, 06 Oct 2017 01:11:45 GMT
x-amzn-RequestId: 51db4cc5-aa33-11e7-98a0-81d6fbb0fa15
Content-Type: application/json
Content-Length: 98

{
  "DirectoryArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AXQXDXvdgk0WktRXV4HnRa8"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

EnableDirectory

Enables the specified directory. Only disabled directories can be enabled. Once enabled, the directory can then be read and written to.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/directory/enable HTTP/1.1
x-amz-data-partition: DirectoryArn
```

URI Request Parameters

The request uses the following URI parameters.

DirectoryArn

The ARN of the directory to enable.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "DirectoryArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DirectoryArn

The ARN of the enabled directory.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryDeletedException

A directory that has been deleted and to which access has been attempted. Note: The requested resource will eventually cease to exist.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of EnableDirectory.

```
PUT /amazonclouddirectory/2017-01-11/directory/enable HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 0
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171006/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=1399f0fdfbcd70640c9d5f2ddd91f8722645721bb30cbd9f6487d091de54bda0
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AXQXDxvdgk0WktRXV4HnRa8
X-Amz-Date: 20171006T011313Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8
```

Example Response

This example illustrates one usage of EnableDirectory.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 85ee2468-aa33-11e7-98a0-81d6fbb0fa15
Date: Fri, 06 Oct 2017 01:13:12 GMT
x-amzn-RequestId: 85ee2468-aa33-11e7-98a0-81d6fbb0fa15
Content-Type: application/json
Content-Length: 98

{
  "DirectoryArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AXQXDXvdgk0WktRXV4HnRa8"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetAppliedSchemaVersion

Returns current applied schema version ARN, including the minor version in use.

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/schema/getappliedschema HTTP/1.1
Content-type: application/json
```

```
{
  "SchemaArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[SchemaArn](#)

The ARN of the applied schema.

Type: String

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "AppliedSchemaArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AppliedSchemaArn

Current applied schema ARN, including the minor version in use if one was provided.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using “SERIALIZABLE” consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetDirectory

Retrieves metadata about a directory.

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/directory/get HTTP/1.1
x-amz-data-partition: DirectoryArn
```

URI Request Parameters

The request uses the following URI parameters.

DirectoryArn

The ARN of the directory.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Directory": {
    "CreationDateTime": number,
    "DirectoryArn": "string",
    "Name": "string",
    "State": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Directory

Metadata about the directory.

Type: [Directory](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous

write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of GetDirectory.

```
POST /amazonclouddirectory/2017-01-11/directory/get HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 0
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171005/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=255eceb681267d8e41de7eb8983269fb61aa76fe56e2b36a4d0c4f855d9ae237
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY
X-Amz-Date: 20171005T202329Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8
```

Example Response

This example illustrates one usage of GetDirectory.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 0d9489ee-aa0b-11e7-a169-c5bf0acd39f4
Date: Thu, 05 Oct 2017 20:23:30 GMT
x-amzn-RequestId: 0d9489ee-aa0b-11e7-a169-c5bf0acd39f4
Content-Type: application/json
Content-Length: 185
```

```
{
  "Directory": {
    "CreationDateTime": 1.506115781186E9,
    "DirectoryArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY",
    "Name": "ExampleCD",
    "State": "ENABLED"
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetFacet

Gets details of the [Facet](#), such as facet name, attributes, [Rules](#), or ObjectType. You can call this on all kinds of schema facets -- published, development, or applied.

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/facet HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json

{
  "Name": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

[SchemaArn](#)

The Amazon Resource Name (ARN) that is associated with the [Facet](#). For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

[Name](#)

The name of the facet to retrieve.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Facet": {
    "FacetStyle": "string",
    "Name": "string",
    "ObjectType": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Facet

The [Facet](#) structure that is associated with the facet.

Type: [Facet](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

FacetNotFoundException

The specified [Facet](#) could not be found.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of GetFacet.

```
POST /amazonclouddirectory/2017-01-11/facet HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 17
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171005/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=70251faa630aeb0c6ca6375eefdde5fb0f956289eaf4a6fbb48ad7a34926aa6
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY/schema/org/1
X-Amz-Date: 20171005T195712Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "Name": "node2"
}
```

Example Response

This example illustrates one usage of GetFacet.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 614b09f0-aa07-11e7-843e-9fad359f817f
Date: Thu, 05 Oct 2017 19:57:13 GMT
x-amzn-RequestId: 614b09f0-aa07-11e7-843e-9fad359f817f
Content-Type: application/json
Content-Length: 46

{
  "Facet": {
    "Name": "node2",
    "ObjectType": "NODE"
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetLinkAttributes

Retrieves attributes that are associated with a typed link.

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/typedlink/attributes/get HTTP/1.1
```

```
x-amz-data-partition: DirectoryArn
```

```
Content-type: application/json
```

```
{
  "AttributeNames": [ "string" ],
  "ConsistencyLevel": "string",
  "TypedLinkSpecifier": {
    "IdentityAttributeValues": [
      {
        "AttributeName": "string",
        "Value": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        }
      }
    ],
    "SourceObjectReference": {
      "Selector": "string"
    },
    "TargetObjectReference": {
      "Selector": "string"
    },
    "TypedLinkFacet": {
      "SchemaArn": "string",
      "TypedLinkName": "string"
    }
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

DirectoryArn

The Amazon Resource Name (ARN) that is associated with the Directory where the typed link resides. For more information, see [Arn Examples](#) or [Typed Links](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

AttributeNames

A list of attribute names whose values will be retrieved.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 230.

Pattern: `^[a-zA-Z0-9._: -]*$`

Required: Yes

ConsistencyLevel

The consistency level at which to retrieve the attributes on a typed link.

Type: String

Valid Values: SERIALIZABLE | EVENTUAL

Required: No

TypedLinkSpecifier

Allows a typed link specifier to be accepted as input.

Type: [TypedLinkSpecifier](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Content-type: application/json

```
{
  "Attributes": [
    {
      "Key": {
        "FacetName": "string",
        "Name": "string",
        "SchemaArn": "string"
      },
      "Value": {
        "BinaryValue": blob,
        "BooleanValue": boolean,
        "DatetimeValue": number,
        "NumberValue": "string",
        "StringValue": "string"
      }
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Attributes

The attributes that are associated with the typed link.

Type: Array of [AttributeKeyAndValue](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

FacetValidationException

The [Facet](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetObjectAttributes

Retrieves attributes within a facet that are associated with an object.

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/object/attributes/get HTTP/1.1
x-amz-data-partition: DirectoryArn
x-amz-consistency-level: ConsistencyLevel
Content-type: application/json

{
  "AttributeNames": [ "string" ],
  "ObjectReference": {
    "Selector": "string"
  },
  "SchemaFacet": {
    "FacetName": "string",
    "SchemaArn": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

ConsistencyLevel

The consistency level at which to retrieve the attributes on an object.

Valid Values: SERIALIZABLE | EVENTUAL

DirectoryArn

The Amazon Resource Name (ARN) that is associated with the [Directory](#) where the object resides.

Required: Yes

Request Body

The request accepts the following data in JSON format.

AttributeNames

List of attribute names whose values will be retrieved.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 230.

Pattern: `^[a-zA-Z0-9._: -]*$`

Required: Yes

ObjectReference

Reference that identifies the object whose attributes will be retrieved.

Type: [ObjectReference](#) object

Required: Yes

SchemaFacet

Identifier for the facet whose attributes will be retrieved. See [SchemaFacet](#) for details.

Type: [SchemaFacet](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AttributeNames": [
    {
      "Key": {
        "FacetName": "string",
        "Name": "string",
        "SchemaArn": "string"
      },
      "Value": {
        "BinaryValue": blob,

```

```
    "BooleanValue": boolean,
    "DatetimeValue": number,
    "NumberValue": "string",
    "StringValue": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Attributes

The attributes that are associated with the object.

Type: Array of [AttributeKeyAndValue](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

FacetValidationException

The [Facet](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetObjectInformation

Retrieves metadata about an object.

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/object/information HTTP/1.1
x-amz-data-partition: DirectoryArn
x-amz-consistency-level: ConsistencyLevel
Content-type: application/json
```

```
{
  "ObjectReference": {
    "Selector": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

ConsistencyLevel

The consistency level at which to retrieve the object information.

Valid Values: SERIALIZABLE | EVENTUAL

DirectoryArn

The ARN of the directory being retrieved.

Required: Yes

Request Body

The request accepts the following data in JSON format.

ObjectReference

A reference to the object.

Type: ObjectReference object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ObjectIdentifier": "string",
  "SchemaFacets": [
    {
      "FacetName": "string",
      "SchemaArn": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ObjectIdentifier

The `ObjectIdentifier` of the specified object.

Type: String

SchemaFacets

The facets attached to the specified object. Although the response does not include minor version information, the most recently applied minor version of each Facet is in effect. See [GetAppliedSchemaVersion](#) for details.

Type: Array of [SchemaFacet](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of `GetObjectInformation`.

```
POST /amazonclouddirectory/2017-01-11/object/information HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 84
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171005/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=6afad99dfe7c5c8152ec38e7ff206dc0c6c6060ed24624ea5654f24ab1392086
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY
X-Amz-Date: 20171005T182528Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "ObjectReference": {
    "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWmspn1fxfQmSQaaVKSbvEiQ"
  }
}
```

Example Response

This example illustrates one usage of `GetObjectInformation`.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 90f2f915-a9fa-11e7-bd9d-f9e3493b0666
Date: Thu, 05 Oct 2017 18:25:29 GMT
x-amzn-RequestId: 90f2f915-a9fa-11e7-bd9d-f9e3493b0666
```

Content-Type: application/json

Content-Length: 215

```
{
  "ObjectIdentifier": "AQGG_AD1fNZBzYHY_JgDt3TWmspn1fxfQmSQaaVKSbvEiQ",
  "SchemaFacets": [{
    "FacetName": "node2",
    "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY/schema/org/1"
  }]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetSchemaAsJson

Retrieves a JSON representation of the schema. See [JSON Schema Format](#) for more information.

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/schema/json HTTP/1.1
x-amz-data-partition: SchemaArn
```

URI Request Parameters

The request uses the following URI parameters.

[SchemaArn](#)

The ARN of the schema to retrieve.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Document": "string",
  "Name": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Document

The JSON representation of the schema document.

Type: String

Name

The name of the retrieved schema.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^[a-zA-Z0-9._-]*$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using “SERIALIZABLE” consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of GetSchemaAsJson.

```
POST /amazonclouddirectory/2017-01-11/schema/json HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 0
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171005/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=1cac388e2c4c4fb13c1fa5d0dfceaffc827acddf559c1706168a5fd84932e4d6
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY/schema/org/1
```

```
X-Amz-Date: 20171005T204308Z
```

```
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8
```

Example Response

This example illustrates one usage of GetSchemaAsJson.

```
HTTP/1.1 200 OK
x-amzn-RequestId: cc541a4e-aa0d-11e7-9e13-5b6a00750e59
Date: Thu, 05 Oct 2017 20:43:09 GMT
x-amzn-RequestId: cc541a4e-aa0d-11e7-9e13-5b6a00750e59
Content-Type: application/json
Content-Length: 6938

{
  "Document": "{\"sourceSchemaArn\":\"arn:aws:clouddirectory:us-
west-2:45132example:schema/published/org/1\", \"facets\": {\"node2\": {\"facetAttributes
\": {}, \"objectType\": \"NODE\"}, \"Organization\": {\"facetAttributes\": {\"account_id
\": {\"attributeDefinition\": {\"attributeType\": \"STRING\", \"isImmutable\": false,
\"attributeRules\": {\"nameLength\": {\"parameters\": {\"min\": \"1\", \"max\":
\"1024\"}, \"ruleType\": \"STRING_LENGTH\"}}}, \"requiredBehavior\": \"NOT_REQUIRED\"},
\"account_name\": {\"attributeDefinition\": {\"attributeType\": \"STRING\", \"isImmutable
\": false, \"attributeRules\": {\"nameLength\": {\"parameters\": {\"min\": \"1\", \"max
\": \"1024\"}, \"ruleType\": \"STRING_LENGTH\"}}}, \"requiredBehavior\": \"NOT_REQUIRED
\"}, \"telephone_number\": {\"attributeDefinition\": {\"attributeType\": \"STRING\",
\"isImmutable\": false, \"attributeRules\": {\"nameLength\": {\"parameters\": {\"min
\": \"1\", \"max\": \"1024\"}, \"ruleType\": \"STRING_LENGTH\"}}}, \"requiredBehavior\":
\"NOT_REQUIRED\"}, \"description\": {\"attributeDefinition\": {\"attributeType\": \"STRING
\", \"isImmutable\": false, \"attributeRules\": {\"nameLength\": {\"parameters\": {\"min
\": \"1\", \"max\": \"1024\"}, \"ruleType\": \"STRING_LENGTH\"}}}, \"requiredBehavior
\": \"NOT_REQUIRED\"}, \"mailing_address (country)\": {\"attributeDefinition
\": {\"attributeType\": \"STRING\", \"isImmutable\": false, \"attributeRules\":
{\"nameLength\": {\"parameters\": {\"min\": \"1\", \"max\": \"1024\"}, \"ruleType\":
\"STRING_LENGTH\"}}}, \"requiredBehavior\": \"NOT_REQUIRED\"}, \"mailing_address
(state)\": {\"attributeDefinition\": {\"attributeType\": \"STRING\", \"isImmutable
\": false, \"attributeRules\": {\"nameLength\": {\"parameters\": {\"min\": \"1\", \"max\":
\"1024\"}, \"ruleType\": \"STRING_LENGTH\"}}}, \"requiredBehavior\": \"NOT_REQUIRED\"},
\"mailing_address (street2)\": {\"attributeDefinition\": {\"attributeType\": \"STRING
\", \"isImmutable\": false, \"attributeRules\": {\"nameLength\": {\"parameters\": {\"min
\": \"1\", \"max\": \"1024\"}, \"ruleType\": \"STRING_LENGTH\"}}}, \"requiredBehavior
\": \"NOT_REQUIRED\"}, \"mailing_address (street1)\": {\"attributeDefinition\":
{\"attributeType\": \"STRING\", \"isImmutable\": false, \"attributeRules\": {\"nameLength
```

```

\":"parameters\":"{\\"min\\":\\"1\\",\\"max\\":\\"1024\\"},\\"ruleType\\":\\"STRING_LENGTH
\\"}}},\\"requiredBehavior\\":\\"NOT_REQUIRED\\"},\\"web_site\\":{\\"attributeDefinition\\":
{\\"attributeType\\":\\"STRING\\",\\"isImmutable\\":false,\\"attributeRules\\":{\\"nameLength
\\":{\\"parameters\\":{\\"min\\":\\"1\\",\\"max\\":\\"1024\\"},\\"ruleType\\":\\"STRING_LENGTH
\\"}}},\\"requiredBehavior\\":\\"NOT_REQUIRED\\"},\\"email\\":{\\"attributeDefinition
\\":{\\"attributeType\\":\\"STRING\\",\\"isImmutable\\":false,\\"attributeRules\\":
{\\"nameLength\\":{\\"parameters\\":{\\"min\\":\\"1\\",\\"max\\":\\"1024\\"},\\"ruleType\\":
\\"STRING_LENGTH\\"}}},\\"requiredBehavior\\":\\"NOT_REQUIRED\\"},\\"mailing_address
(city)\\":{\\"attributeDefinition\\":{\\"attributeType\\":\\"STRING\\",\\"isImmutable
\\":false,\\"attributeRules\\":{\\"nameLength\\":{\\"parameters\\":{\\"min\\":\\"1\\",\\"max
\\":\\"1024\\"},\\"ruleType\\":\\"STRING_LENGTH\\"}}},\\"requiredBehavior\\":\\"NOT_REQUIRED
\\"},\\"organization_status\\":{\\"attributeDefinition\\":{\\"attributeType\\":\\"STRING
\\",\\"isImmutable\\":false,\\"attributeRules\\":{\\"nameLength\\":{\\"parameters\\":{\\"min
\\":\\"1\\",\\"max\\":\\"1024\\"},\\"ruleType\\":\\"STRING_LENGTH\\"}}},\\"requiredBehavior
\\":\\"NOT_REQUIRED\\"},\\"mailing_address (postal_code)\\":{\\"attributeDefinition\\":
{\\"attributeType\\":\\"STRING\\",\\"isImmutable\\":false,\\"attributeRules\\":{\\"nameLength
\\":{\\"parameters\\":{\\"min\\":\\"1\\",\\"max\\":\\"1024\\"},\\"ruleType\\":\\"STRING_LENGTH
\\"}}},\\"requiredBehavior\\":\\"NOT_REQUIRED\\"}},\\"objectType\\":\\"LEAF_NODE\\"},\\"nodex\\":
{\\"facetAttributes\\":{\},\\"objectType\\":\\"NODE\\"},\\"Legal_Entity\\":{\\"facetAttributes
\\":{\\"industry_vertical\\":{\\"attributeDefinition\\":{\\"attributeType\\":\\"STRING\\",
\\"isImmutable\\":false,\\"attributeRules\\":{\\"nameLength\\":{\\"parameters\\":{\\"min
\\":\\"1\\",\\"max\\":\\"1024\\"},\\"ruleType\\":\\"STRING_LENGTH\\"}}},\\"requiredBehavior
\\":\\"NOT_REQUIRED\\"},\\"registered_company_name\\":{\\"attributeDefinition\\":
{\\"attributeType\\":\\"STRING\\",\\"isImmutable\\":false,\\"attributeRules\\":{\\"nameLength
\\":{\\"parameters\\":{\\"min\\":\\"1\\",\\"max\\":\\"1024\\"},\\"ruleType\\":\\"STRING_LENGTH\\"}}},
\\"requiredBehavior\\":\\"NOT_REQUIRED\\"},\\"billing_currency\\":{\\"attributeDefinition
\\":{\\"attributeType\\":\\"STRING\\",\\"isImmutable\\":false,\\"attributeRules\\":
{\\"nameLength\\":{\\"parameters\\":{\\"min\\":\\"1\\",\\"max\\":\\"1024\\"},\\"ruleType\\":
\\"STRING_LENGTH\\"}}},\\"requiredBehavior\\":\\"NOT_REQUIRED\\"},\\"mailing_address
(country)\\":{\\"attributeDefinition\\":{\\"attributeType\\":\\"STRING\\",\\"isImmutable
\\":false,\\"attributeRules\\":{\\"nameLength\\":{\\"parameters\\":{\\"min\\":\\"1\\",\\"max\\":
\\"1024\\"},\\"ruleType\\":\\"STRING_LENGTH\\"}}},\\"requiredBehavior\\":\\"NOT_REQUIRED\\"},
\\"mailing_address (state)\\":{\\"attributeDefinition\\":{\\"attributeType\\":\\"STRING
\\",\\"isImmutable\\":false,\\"attributeRules\\":{\\"nameLength\\":{\\"parameters\\":{\\"min
\\":\\"1\\",\\"max\\":\\"1024\\"},\\"ruleType\\":\\"STRING_LENGTH\\"}}},\\"requiredBehavior
\\":\\"NOT_REQUIRED\\"},\\"mailing_address (street2)\\":{\\"attributeDefinition\\":
{\\"attributeType\\":\\"STRING\\",\\"isImmutable\\":false,\\"attributeRules\\":{\\"nameLength
\\":{\\"parameters\\":{\\"min\\":\\"1\\",\\"max\\":\\"1024\\"},\\"ruleType\\":\\"STRING_LENGTH
\\"}}},\\"requiredBehavior\\":\\"NOT_REQUIRED\\"},\\"mailing_address (street1)\\":
{\\"attributeDefinition\\":{\\"attributeType\\":\\"STRING\\",\\"isImmutable\\":false,
\\"attributeRules\\":{\\"nameLength\\":{\\"parameters\\":{\\"min\\":\\"1\\",\\"max\\":
\\"1024\\"},\\"ruleType\\":\\"STRING_LENGTH\\"}}},\\"requiredBehavior\\":\\"NOT_REQUIRED
\\"},\\"tax_id\\":{\\"attributeDefinition\\":{\\"attributeType\\":\\"STRING\\",\\"isImmutable
\\":false,\\"attributeRules\\":{\\"nameLength\\":{\\"parameters\\":{\\"min\\":\\"1\\",\\"max

```

```

\":"1024\"},"ruleType\":"STRING_LENGTH\}}},\requiredBehavior\":"NOT_REQUIRED
\"},"mailing_address (city)\":{"attributeDefinition\":{"attributeType\":"STRING
\","isImmutable\":false,\attributeRules\":{"nameLength\":{"parameters\":{"min
\":"1\","max\":"1024\"},"ruleType\":"STRING_LENGTH\}}},\requiredBehavior
\":"NOT_REQUIRED\"},"mailing_address (postal_code)\":{"attributeDefinition\":
{"attributeType\":"STRING\","isImmutable\":false,\attributeRules\":{"nameLength
\":{"parameters\":{"min\":"1\","max\":"1024\"},"ruleType\":"STRING_LENGTH\}}},
\requiredBehavior\":"NOT_REQUIRED\}}},\objectType\":"LEAF_NODE\"},"policyfacet
\":{"facetAttributes\":{},\objectType\":"POLICY\"},"node1\":{"facetAttributes
\":{},\objectType\":"NODE\}}},\typedLinkFacets\":{"exampletypedlink\":
{"facetAttributes\":{"1\":{"attributeDefinition\":{"attributeType\":"BINARY\","
isImmutable\":false,\attributeRules\":{}},\requiredBehavior\":"REQUIRED_ALWAYS
\}}},\identityAttributeOrder\":["1"]},\exampletypedlink8\":{"facetAttributes
\":{"22\":{"attributeDefinition\":{"attributeType\":"BINARY\","isImmutable
\":false,\attributeRules\":{}},\requiredBehavior\":"REQUIRED_ALWAYS\}}},
\identityAttributeOrder\":["22"]}}}],
  "Name": "org"
}

```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTypedLinkFacetInformation

Returns the identity attribute order for a specific [TypedLinkFacet](#). For more information, see [Typed Links](#).

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/typedlink/facet/get HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json

{
  "Name": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

[SchemaArn](#)

The Amazon Resource Name (ARN) that is associated with the schema. For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

[Name](#)

The unique name of the typed link facet.

Type: String

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "IdentityAttributeOrder": [ "string" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[IdentityAttributeOrder](#)

The order of identity attributes for the facet, from most significant to least significant. The ability to filter typed links considers the order that the attributes are defined on the typed link facet. When providing ranges to typed link selection, any inexact ranges must be specified at the end. Any attributes that do not have a range specified are presumed to match the entire range. Filters are interpreted in the order of the attributes on the typed link facet, not the order in which they are supplied to any API calls. For more information about identity attributes, see [Typed Links](#).

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 230.

Pattern: `^[a-zA-Z0-9._:-]*$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

FacetNotFound

The specified [Facet](#) could not be found.

HTTP Status Code: 400

InternalServerError

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArn

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidNextToken

Indicates that the NextToken value is not valid.

HTTP Status Code: 400

LimitExceeded

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFound

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflict

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of `GetTypedLinkFacetInformation`.

```
POST /amazonclouddirectory/2017-01-11/typedlink/facet/get HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 29
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171006/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=6561b457b066c8458961d43944ad116fc7d3a8b2fdb1a07a08cb4a5273a10b14
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY/schema/org/1
X-Amz-Date: 20171006T005026Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "Name": "exampltypedlink8"
}
```

Example Response

This example illustrates one usage of `GetTypedLinkFacetInformation`.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 57471e31-aa30-11e7-8502-0566a31305cf
Date: Fri, 06 Oct 2017 00:50:25 GMT
x-amzn-RequestId: 57471e31-aa30-11e7-8502-0566a31305cf
Content-Type: application/json
Content-Length: 33

{
```

```
"IdentityAttributeOrder": ["22"]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAppliedSchemaArns

Lists schema major versions applied to a directory. If SchemaArn is provided, lists the minor version.

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/schema/applied HTTP/1.1
Content-type: application/json
```

```
{
  "DirectoryArn": "string",
  "MaxResults": number,
  "NextToken": "string",
  "SchemaArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

DirectoryArn

The ARN of the directory you are listing.

Type: String

Required: Yes

MaxResults

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The pagination token.

Type: String

Required: No

SchemaArn

The response for `ListAppliedSchemaArns` when this parameter is used will list all minor version ARNs for a major version.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "SchemaArns": [ "string" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token.

Type: String

SchemaArns

The ARNs of schemas that are applied to the directory.

Type: Array of strings

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidNextTokenException

Indicates that the NextToken value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of ListAppliedSchemaArns.

```
POST /amazonclouddirectory/2017-01-11/schema/applied HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 99
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171016/
us-west-2/clouddirectory/aws4_request, SignedHeaders=host;x-amz-date,
Signature=9263dc9a99c8cd1178f6305dfb28c6d95f9c273b4d7cab78aaf1d7934b1dce9f
X-Amz-Date: 20171016T225524Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "DirectoryArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY"
}
```

Example Response

This example illustrates one usage of ListAppliedSchemaArns.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 1920f0d5-b2c5-11e7-a973-b71cf1107b43
Date: Mon, 16 Oct 2017 22:55:25 GMT
x-amzn-RequestId: 1920f0d5-b2c5-11e7-a973-b71cf1107b43
Content-Type: application/json
Content-Length: 128

{
  "NextToken": null,
  "SchemaArns": ["arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY/schema/org/1"]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAttachedIndices

Lists indices attached to the specified object.

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/object/indices HTTP/1.1
```

```
x-amz-data-partition: DirectoryArn
```

```
x-amz-consistency-level: ConsistencyLevel
```

```
Content-type: application/json
```

```
{
  "MaxResults": number,
  "NextToken": "string",
  "TargetReference": {
    "Selector": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

ConsistencyLevel

The consistency level to use for this operation.

Valid Values: SERIALIZABLE | EVENTUAL

DirectoryArn

The ARN of the directory.

Required: Yes

Request Body

The request accepts the following data in JSON format.

MaxResults

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The pagination token.

Type: String

Required: No

TargetReference

A reference to the object that has indices attached.

Type: [ObjectReference](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "IndexAttachments": [
    {
      "IndexedAttributes": [
        {
          "Key": {
            "FacetName": "string",
            "Name": "string",
            "SchemaArn": "string"
          },
          "Value": {
            "BinaryValue": blob,
            "BooleanValue": boolean,
            "DatetimeValue": number,
            "NumberValue": "string",
            "StringValue": "string"
          }
        }
      ]
    }
  ]
}
```

```
    }
  },
  ],
  "ObjectIdentifier": "string"
}
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

IndexAttachments

The indices attached to the specified object.

Type: Array of [IndexAttachment](#) objects

NextToken

The pagination token.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of ListAttachedIndices.

```
POST /amazonclouddirectory/2017-01-11/object/indices HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 84
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171009/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=0dd23d46d0aa37f61649857fafdafa5a9d52305b03bcda0de2027c074efce9d1
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY
X-Amz-Date: 20171009T194908Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "TargetReference": {
    "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWcU7IARv0TeaR09zme1sVsw"
  }
}
```

Example Response

This example illustrates one usage of ListAttachedIndices.

```
HTTP/1.1 200 OK
x-amzn-RequestId: eb40bf46-ad2a-11e7-9e13-5b6a00750e59
Date: Mon, 09 Oct 2017 19:49:10 GMT
x-amzn-RequestId: eb40bf46-ad2a-11e7-9e13-5b6a00750e59
Content-Type: application/json
Content-Length: 132

{
  "IndexAttachments": [{
    "IndexedAttributes": [],
    "ObjectIdentifier": "AQGG_AD1fNZBzYHY_JgDt3TW45F26R1HTY2z-stwKBte_Q"
  }],
  "NextToken": null
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListDevelopmentSchemaArns

Retrieves each Amazon Resource Name (ARN) of schemas in the development state.

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/schema/development HTTP/1.1
Content-type: application/json
```

```
{
  "MaxResults": number,
  "NextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

MaxResults

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The pagination token.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "NextToken": "string",
  "SchemaArns": [ "string" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token.

Type: String

SchemaArns

The ARNs of retrieved development schemas.

Type: Array of strings

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidNextTokenException

Indicates that the NextToken value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using “SERIALIZABLE” consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of ListDevelopmentSchemaArns.

```
POST /amazonclouddirectory/2017-01-11/schema/development HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 0
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171016/
us-west-2/clouddirectory/aws4_request, SignedHeaders=host;x-amz-date,
Signature=ff097f28605d8f60239f2ae4c0c3600741e772e10dfef76c61b2a16a8f36a8fe
X-Amz-Date: 20171016T233712Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8
```

Example Response

This example illustrates one usage of ListDevelopmentSchemaArns.

```
HTTP/1.1 200 OK
x-amzn-RequestId: f01c6580-b2ca-11e7-81c0-7b48a7696e76
Date: Mon, 16 Oct 2017 23:37:13 GMT
x-amzn-RequestId: f01c6580-b2ca-11e7-81c0-7b48a7696e76
Content-Type: application/json
Content-Length: 510

{
  "NextToken": null,
  "SchemaArns": ["arn:aws:clouddirectory:us-west-2:45132example:schema/development/
typedlinkschematest", "arn:aws:clouddirectory:us-west-2:45132example:schema/
development/asdfsdfdf", "arn:aws:clouddirectory:us-west-2:45132example:schema/
development/Customers", "arn:aws:clouddirectory:us-west-2:45132example:schema/
development/CourseCatalog", "arn:aws:clouddirectory:us-west-2:45132example:schema/
development/Consumers", "arn:aws:clouddirectory:us-west-2:45132example:schema/
development/exampleorg"]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListDirectories

Lists directories created within an account.

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/directory/list HTTP/1.1
Content-type: application/json
```

```
{
  "MaxResults": number,
  "NextToken": "string",
  "state": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

MaxResults

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The pagination token.

Type: String

Required: No

state

The state of the directories in the list. Can be either Enabled, Disabled, or Deleted.

Type: String

Valid Values: ENABLED | DISABLED | DELETED

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Directories": [
    {
      "CreationDateTime": number,
      "DirectoryArn": "string",
      "Name": "string",
      "State": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Directories

Lists all directories that are associated with your account in pagination fashion.

Type: Array of [Directory](#) objects

NextToken

The pagination token.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidNextTokenException

Indicates that the NextToken value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous

write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of ListDirectories.

```
POST /amazonclouddirectory/2017-01-11/directory/list HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 0
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171016/
us-west-2/clouddirectory/aws4_request, SignedHeaders=host;x-amz-date,
Signature=3e25d9a79eca5d22f81ae7ef6ed3d3b1a7280201839584196e680029893b8694
X-Amz-Date: 20171016T233810Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8
```

Example Response

This example illustrates one usage of ListDirectories.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 12ade21c-b2cb-11e7-bd9d-f9e3493b0666
Date: Mon, 16 Oct 2017 23:38:11 GMT
x-amzn-RequestId: 12ade21c-b2cb-11e7-bd9d-f9e3493b0666
Content-Type: application/json
Content-Length: 893

{
```

```
"Directories": [{
  "CreationDateTime": 1.506121791167E9,
  "DirectoryArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
Ae89h0Kmw0bRpvYgW8EAsus",
  "Name": "ExampleCD4",
  "State": "ENABLED"
}, {
  "CreationDateTime": 1.485473189746E9,
  "DirectoryArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AXQDXvdgk0WktRXV4HnRa8",
  "Name": "testCD",
  "State": "DELETED"
}, {
  "CreationDateTime": 1.506115781186E9,
  "DirectoryArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY",
  "Name": "ExampleCD",
  "State": "ENABLED"
}, {
  "CreationDateTime": 1.506118003859E9,
  "DirectoryArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AfMr4qym1kZTvwq0afAYfqI",
  "Name": "ExampleCD2",
  "State": "ENABLED"
}, {
  "CreationDateTime": 1.485477107925E9,
  "DirectoryArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AWeI1yjiB0SylWVTvQk1CD0",
  "Name": "testCD2",
  "State": "DELETED"
}],
"NextToken": null
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListFacetAttributes

Retrieves attributes attached to the facet.

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/facet/attributes HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json

{
  "MaxResults": number,
  "Name": "string",
  "NextToken": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

SchemaArn

The ARN of the schema where the facet resides.

Required: Yes

Request Body

The request accepts the following data in JSON format.

MaxResults

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

Name

The name of the facet whose attributes will be retrieved.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

NextToken

The pagination token.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Attributes": [
    {
      "AttributeDefinition": {
        "DefaultValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        },
        "IsImmutable": boolean,
        "Rules": {
          "string" : {
            "Parameters": {
              "string" : "string"
            },
            "Type": "string"
          }
        },
        "Type": "string"
      },
      "AttributeReference": {
```

```
        "TargetAttributeName": "string",
        "TargetFacetName": "string"
    },
    "Name": "string",
    "RequiredBehavior": "string"
}
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Attributes

The attributes attached to the facet.

Type: Array of [FacetAttribute](#) objects

NextToken

The pagination token.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

FacetNotFound

The specified [Facet](#) could not be found.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidNextTokenException

Indicates that the NextToken value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of ListFacetAttributes.

```
POST /amazonclouddirectory/2017-01-11/facet/attributes HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 24
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171017/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=729cd6edffd57814ab2e2a671da29fc3c57f277c440cc331c2dfd2a3dd35f71b
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY/schema/org/1
X-Amz-Date: 20171017T202437Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "Name": "Organization"
}
```

Example Response

This example illustrates one usage of ListFacetAttributes.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 330cefed-b379-11e7-a6de-b54884d62153
Date: Tue, 17 Oct 2017 20:24:38 GMT
x-amzn-RequestId: 330cefed-b379-11e7-a6de-b54884d62153
Content-Type: application/json
Content-Length: 2628

{
  "Attributes": [{
    "AttributeDefinition": {
      "DefaultValue": null,
      "IsImmutable": false,
      "Rules": {
        "nameLength": {
          "Parameters": {
```

```
    "max": "1024",
    "min": "1"
  },
  "Type": "STRING_LENGTH"
}
},
"Type": "STRING"
},
"AttributeReference": null,
"Name": "account_id",
"RequiredBehavior": "NOT_REQUIRED"
}, {
"AttributeDefinition": {
  "DefaultValue": null,
  "IsImmutable": false,
  "Rules": {
    "nameLength": {
      "Parameters": {
        "max": "1024",
        "min": "1"
      },
      "Type": "STRING_LENGTH"
    }
  },
  "Type": "STRING"
},
"AttributeReference": null,
"Name": "account_name",
"RequiredBehavior": "NOT_REQUIRED"
}, {
"AttributeDefinition": {
  "DefaultValue": null,
  "IsImmutable": false,
  "Rules": {
    "nameLength": {
      "Parameters": {
        "max": "1024",
        "min": "1"
      },
      "Type": "STRING_LENGTH"
    }
  },
  "Type": "STRING"
},
```

```
"AttributeReference": null,
"Name": "description",
"RequiredBehavior": "NOT_REQUIRED"
}, {
"AttributeDefinition": {
  "DefaultValue": null,
  "IsImmutable": false,
  "Rules": {
    "nameLength": {
      "Parameters": {
        "max": "1024",
        "min": "1"
      },
      "Type": "STRING_LENGTH"
    }
  },
  "Type": "STRING"
},
"AttributeReference": null,
"Name": "email",
"RequiredBehavior": "NOT_REQUIRED"
}, {
"AttributeDefinition": {
  "DefaultValue": null,
  "IsImmutable": false,
  "Rules": {
    "nameLength": {
      "Parameters": {
        "max": "1024",
        "min": "1"
      },
      "Type": "STRING_LENGTH"
    }
  },
  "Type": "STRING"
},
"AttributeReference": null,
"Name": "mailing_address (city)",
"RequiredBehavior": "NOT_REQUIRED"
}, {
"AttributeDefinition": {
  "DefaultValue": null,
  "IsImmutable": false,
  "Rules": {
```



```
    "Type": "STRING"
  },
  "AttributeReference": null,
  "Name": "mailing_address (state)",
  "RequiredBehavior": "NOT_REQUIRED"
}, {
  "AttributeDefinition": {
    "DefaultValue": null,
    "IsImmutable": false,
    "Rules": {
      "nameLength": {
        "Parameters": {
          "max": "1024",
          "min": "1"
        }
      },
      "Type": "STRING_LENGTH"
    }
  },
  "Type": "STRING"
},
  "AttributeReference": null,
  "Name": "mailing_address (street1)",
  "RequiredBehavior": "NOT_REQUIRED"
}, {
  "AttributeDefinition": {
    "DefaultValue": null,
    "IsImmutable": false,
    "Rules": {
      "nameLength": {
        "Parameters": {
          "max": "1024",
          "min": "1"
        }
      },
      "Type": "STRING_LENGTH"
    }
  },
  "Type": "STRING"
},
  "AttributeReference": null,
  "Name": "mailing_address (street2)",
  "RequiredBehavior": "NOT_REQUIRED"
}],
"NextToken": "V0b3JnYW5pemF0aW9uX3N0YXR1cw=="
```

```
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListFacetNames

Retrieves the names of facets that exist in a schema.

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/facet/list HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json

{
  "MaxResults": number,
  "NextToken": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

SchemaArn

The Amazon Resource Name (ARN) to retrieve facet names from.

Required: Yes

Request Body

The request accepts the following data in JSON format.

MaxResults

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The pagination token.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "FacetNames": [ "string" ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[FacetNames](#)

The names of facets that exist within the schema.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._-]*$`

[NextToken](#)

The pagination token.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidNextTokenException

Indicates that the NextToken value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of ListFacetNames.

```
POST /amazonclouddirectory/2017-01-11/facet/list HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 0
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171017/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=e29fa5e564697e1912f34bd1d1437f78be8e8ebbd4f31fce6d300f5be5c814bd
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY/schema/org/1
X-Amz-Date: 20171017T202730Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8
```

Example Response

This example illustrates one usage of ListFacetNames.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 9a69f750-b379-11e7-bd9d-f9e3493b0666
Date: Tue, 17 Oct 2017 20:27:32 GMT
x-amzn-RequestId: 9a69f750-b379-11e7-bd9d-f9e3493b0666
Content-Type: application/json
Content-Length: 101

{
  "FacetNames": ["Legal_Entity", "Organization", "node1", "node2", "nodex",
    "policyfacet"],
```

```
"NextToken": null
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListIncomingTypedLinks

Returns a paginated list of all the incoming [TypedLinkSpecifier](#) information for an object. It also supports filtering by typed link facet and identity attributes. For more information, see [Typed Links](#).

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/typedlink/incoming HTTP/1.1
```

```
x-amz-data-partition: DirectoryArn
```

```
Content-type: application/json
```

```
{
  "ConsistencyLevel": "string",
  "FilterAttributeRanges": [
    {
      "AttributeName": "string",
      "Range": {
        "EndMode": "string",
        "EndValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        },
        "StartMode": "string",
        "StartValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        }
      }
    }
  ],
  "FilterTypedLink": {
    "SchemaArn": "string",
    "TypedLinkName": "string"
  },
  "MaxResults": number,
```

```
"NextToken": "string",  
"ObjectReference": {  
  "Selector": "string"  
}  
}
```

URI Request Parameters

The request uses the following URI parameters.

DirectoryArn

The Amazon Resource Name (ARN) of the directory where you want to list the typed links.

Required: Yes

Request Body

The request accepts the following data in JSON format.

ConsistencyLevel

The consistency level to execute the request at.

Type: String

Valid Values: SERIALIZABLE | EVENTUAL

Required: No

FilterAttributeRanges

Provides range filters for multiple attributes. When providing ranges to typed link selection, any inexact ranges must be specified at the end. Any attributes that do not have a range specified are presumed to match the entire range.

Type: Array of [TypedLinkAttributeRange](#) objects

Required: No

FilterTypedLink

Filters are interpreted in the order of the attributes on the typed link facet, not the order in which they are supplied to any API calls.

Type: [TypedLinkSchemaAndFacetName](#) object

Required: No

[MaxResults](#)

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

[NextToken](#)

The pagination token.

Type: String

Required: No

[ObjectReference](#)

Reference that identifies the object whose attributes will be listed.

Type: [ObjectReference](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "LinkSpecifiers": [
    {
      "IdentityAttributeValues": [
        {
          "AttributeName": "string",
          "Value": {
            "BinaryValue": blob,
            "BooleanValue": boolean,
```

```
        "DatettimeValue": number,
        "NumberValue": "string",
        "StringValue": "string"
    }
}
],
"SourceObjectReference": {
    "Selector": "string"
},
"TargetObjectReference": {
    "Selector": "string"
},
"TypedLinkFacet": {
    "SchemaArn": "string",
    "TypedLinkName": "string"
}
}
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

LinkSpecifiers

Returns one or more typed link specifiers as output.

Type: Array of [TypedLinkSpecifier](#) objects

NextToken

The pagination token.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

FacetValidationException

The [Facet](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidNextTokenException

Indicates that the NextToken value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of ListIncomingTypedLinks.

```
POST /amazonclouddirectory/2017-01-11/typedlink/incoming HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 84
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171017/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=fc13e2c9fb358918b87ada72c9dca32938fc33cf83e7774394fce55d755001dc
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY
X-Amz-Date: 20171017T204458Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "ObjectReference": {
    "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWcU7IARv0TearR09zme1sVsw"
  }
}
```

Example Response

This example illustrates one usage of ListIncomingTypedLinks.

```

HTTP/1.1 200 OK
x-amzn-RequestId: 0b1ebdf5-b37c-11e7-9e13-5b6a00750e59
Date: Tue, 17 Oct 2017 20:45:00 GMT
x-amzn-RequestId: 0b1ebdf5-b37c-11e7-9e13-5b6a00750e59
Content-Type: application/json
Content-Length: 1530

{
  "LinkSpecifiers": [{
    "IdentityAttributeValues": [{
      "AttributeName": "22",
      "Value": {
        "BinaryValue": "",
        "BooleanValue": null,
        "DatetimeValue": null,
        "NumberValue": null,
        "StringValue": null
      }
    }
  ]},
  "SourceObjectReference": {
    "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWSvfuEnDqTdmeCuTs6YBNUA"
  },
  "TargetObjectReference": {
    "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWcU7IARv0TeaR09zme1sVsw"
  },
  "TypedLinkFacet": {
    "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/AYb8A0V81kHNgdj8mA03dNY/schema/org/1",
    "TypedLinkName": "exampltypedlink8"
  }
}, {
  "IdentityAttributeValues": [{
    "AttributeName": "22",
    "Value": {
      "BinaryValue": "MA==",
      "BooleanValue": null,
      "DatetimeValue": null,
      "NumberValue": null,
      "StringValue": null
    }
  ]
}

```

```

    ]],
    "SourceObjectReference": {
      "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWSvfuEnDqTdmeCuTs6YBNUA"
    },
    "TargetObjectReference": {
      "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWcU7IARv0TeaR09zme1sVsw"
    },
    "TypedLinkFacet": {
      "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY/schema/org/1",
      "TypedLinkName": "exampletypedlink8"
    }
  }, {
    "IdentityAttributeValues": [{
      "AttributeName": "22",
      "Value": {
        "BinaryValue": "c3Ry",
        "BooleanValue": null,
        "DatetimeValue": null,
        "NumberValue": null,
        "StringValue": null
      }
    }],
    "SourceObjectReference": {
      "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWSvfuEnDqTdmeCuTs6YBNUA"
    },
    "TargetObjectReference": {
      "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWcU7IARv0TeaR09zme1sVsw"
    },
    "TypedLinkFacet": {
      "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY/schema/org/1",
      "TypedLinkName": "exampletypedlink8"
    }
  }],
  "NextToken": null
}

```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListIndex

Lists objects attached to the specified index.

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/index/targets HTTP/1.1
```

```
x-amz-data-partition: DirectoryArn
```

```
x-amz-consistency-level: ConsistencyLevel
```

```
Content-type: application/json
```

```
{
  "IndexReference": {
    "Selector": "string"
  },
  "MaxResults": number,
  "NextToken": "string",
  "RangesOnIndexedValues": [
    {
      "AttributeKey": {
        "FacetName": "string",
        "Name": "string",
        "SchemaArn": "string"
      },
      "Range": {
        "EndMode": "string",
        "EndValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        },
        "StartMode": "string",
        "StartValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        }
      }
    }
  ]
}
```

```
]
}
```

URI Request Parameters

The request uses the following URI parameters.

ConsistencyLevel

The consistency level to execute the request at.

Valid Values: SERIALIZABLE | EVENTUAL

DirectoryArn

The ARN of the directory that the index exists in.

Required: Yes

Request Body

The request accepts the following data in JSON format.

IndexReference

The reference to the index to list.

Type: [ObjectReference](#) object

Required: Yes

MaxResults

The maximum number of objects in a single page to retrieve from the index during a request. For more information, see [Amazon Cloud Directory Limits](#).

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The pagination token.

Type: String

Required: No

RangesOnIndexedValues

Specifies the ranges of indexed values that you want to query.

Type: Array of [ObjectAttributeRange](#) objects

Required: No

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "IndexAttachments": [
    {
      "IndexedAttributes": [
        {
          "Key": {
            "FacetName": "string",
            "Name": "string",
            "SchemaArn": "string"
          },
          "Value": {
            "BinaryValue": blob,
            "BooleanValue": boolean,
            "DatetimeValue": number,
            "NumberValue": "string",
            "StringValue": "string"
          }
        }
      ],
      "ObjectIdentifier": "string"
    }
  ],
}
```

```
"NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

IndexAttachments

The objects and indexed values attached to the index.

Type: Array of [IndexAttachment](#) objects

NextToken

The pagination token.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

FacetValidationException

The [Facet](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidNextTokenException

Indicates that the NextToken value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

NotIndexException

Indicates that the requested operation can only operate on index objects.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of ListIndex.

```
POST /amazonclouddirectory/2017-01-11/index/targets HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 83
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171017/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=e10557e84c0fb9fd30e6a018a02b51ecbac72a389e2dd20090e516d3023872e4
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY
X-Amz-Date: 20171017T221341Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "IndexReference": {
    "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TW45F26R1HTY2z-stwKBte_Q"
  }
}
```

Example Response

This example illustrates one usage of ListIndex.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 2920690c-b38d-11e7-bd9d-f9e3493b0666
Date: Tue, 17 Oct 2017 22:47:31 GMT
x-amzn-RequestId: 2920690c-b38d-11e7-bd9d-f9e3493b0666
Content-Type: application/json
```

Content-Length: 404

```
{
  "IndexAttachments": [{
    "IndexedAttributes": [{
      "Key": {
        "FacetName": "Organization",
        "Name": "description",
        "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY/schema/org/1"
      },
      "Value": {
        "BinaryValue": null,
        "BooleanValue": null,
        "DatetimeValue": null,
        "NumberValue": null,
        "StringValue": null
      }
    }],
    "ObjectIdentifier": "AQGG_AD1fNZBzYHY_JgDt3TWcU7IARv0TeaR09zme1sVsw"
  }],
  "NextToken": null
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListManagedSchemaArns

Lists the major version families of each managed schema. If a major version ARN is provided as SchemaArn, the minor version revisions in that family are listed instead.

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/schema/managed HTTP/1.1
Content-type: application/json
```

```
{
  "MaxResults": number,
  "NextToken": "string",
  "SchemaArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

MaxResults

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The pagination token.

Type: String

Required: No

SchemaArn

The response for ListManagedSchemaArns. When this parameter is used, all minor version ARNs for a major version are listed.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "SchemaArns": [ "string" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token.

Type: String

SchemaArns

The ARNs for all AWS managed schemas.

Type: Array of strings

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidNextTokenException

Indicates that the NextToken value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListObjectAttributes

Lists all attributes that are associated with an object.

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/object/attributes HTTP/1.1
x-amz-data-partition: DirectoryArn
x-amz-consistency-level: ConsistencyLevel
Content-type: application/json

{
  "FacetFilter": {
    "FacetName": "string",
    "SchemaArn": "string"
  },
  "MaxResults": number,
  "NextToken": "string",
  "ObjectReference": {
    "Selector": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

ConsistencyLevel

Represents the manner and timing in which the successful write or update of an object is reflected in a subsequent read operation of that same object.

Valid Values: SERIALIZABLE | EVENTUAL

DirectoryArn

The Amazon Resource Name (ARN) that is associated with the [Directory](#) where the object resides. For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

FacetFilter

Used to filter the list of object attributes that are associated with a certain facet.

Type: [SchemaFacet](#) object

Required: No

MaxResults

The maximum number of items to be retrieved in a single call. This is an approximate number.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The pagination token.

Type: String

Required: No

ObjectReference

The reference that identifies the object whose attributes will be listed.

Type: [ObjectReference](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "Attributes": [
    {
      "Key": {
        "FacetName": "string",
        "Name": "string",
        "SchemaArn": "string"
      },
      "Value": {
        "BinaryValue": blob,
        "BooleanValue": boolean,
        "DatetimeValue": number,
        "NumberValue": "string",
        "StringValue": "string"
      }
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Attributes

Attributes map that is associated with the object. `AttributeArn` is the key, and attribute value is the value.

Type: Array of [AttributeKeyAndValue](#) objects

NextToken

The pagination token.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

FacetValidationException

The [Facet](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidNextTokenException

Indicates that the NextToken value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of `ListObjectAttributes`.

```
POST /amazonclouddirectory/2017-01-11/object/attributes HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 84
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171017/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=192bfef84370989cc0ccc0760a138e2e49e4454e467f2247d98112507bee7ed7
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY
X-Amz-Date: 20171017T221819Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "ObjectReference": {
    "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TW45F26R1HTY2z-stwKBte_Q"
  }
}
```

```
}
```

Example Response

This example illustrates one usage of ListObjectAttributes.

```
HTTP/1.1 200 OK
x-amzn-RequestId: 151ad236-b389-11e7-a6de-b54884d62153
Date: Tue, 17 Oct 2017 22:18:19 GMT
x-amzn-RequestId: 151ad236-b389-11e7-a6de-b54884d62153
Content-Type: application/json
Content-Length: 725

{
  "Attributes": [{
    "Key": {
      "FacetName": "INDEX",
      "Name": "index_is_unique",
      "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY/schema/CloudDirectory/1.0"
    },
    "Value": {
      "BinaryValue": null,
      "BooleanValue": true,
      "DatetimeValue": null,
      "NumberValue": null,
      "StringValue": null
    }
  }, {
    "Key": {
      "FacetName": "INDEX",
      "Name": "ordered_indexed_attributes",
      "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY/schema/CloudDirectory/1.0"
    },
    "Value": {
      "BinaryValue": null,
      "BooleanValue": null,
      "DatetimeValue": null,
      "NumberValue": null,
      "StringValue": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY/schema/org/1*Organization*description"
    }
  }
}
```

```
  }],  
  "NextToken": null  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListObjectChildren

Returns a paginated list of child objects that are associated with a given object.

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/object/children HTTP/1.1
x-amz-data-partition: DirectoryArn
x-amz-consistency-level: ConsistencyLevel
Content-type: application/json
```

```
{
  "MaxResults": number,
  "NextToken": "string",
  "ObjectReference": {
    "Selector": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

ConsistencyLevel

Represents the manner and timing in which the successful write or update of an object is reflected in a subsequent read operation of that same object.

Valid Values: SERIALIZABLE | EVENTUAL

DirectoryArn

The Amazon Resource Name (ARN) that is associated with the [Directory](#) where the object resides. For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

MaxResults

The maximum number of items to be retrieved in a single call. This is an approximate number.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The pagination token.

Type: String

Required: No

ObjectReference

The reference that identifies the object for which child objects are being listed.

Type: [ObjectReference](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Children": {
    "string" : "string"
  },
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Children

Children structure, which is a map with key as the `LinkName` and `ObjectIdentifier` as the value.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Key Pattern: `[^\\\[\\]\(\):\{\}\#\@!\?\s\\;]+`

NextToken

The pagination token.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidNextTokenException

Indicates that the NextToken value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

NotNodeException

Occurs when any invalid operations are performed on an object that is not a node, such as calling ListObjectChildren for a leaf node object.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

Examples

The following examples are formatted for legibility.

Example Request

This example illustrates one usage of `ListObjectChildren`.

```
POST /amazonclouddirectory/2017-01-11/object/children HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 84
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171017/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=8c56f415f53f259c6c7a7ba5c5d8b9924ba5341dbb17eb84e23235f5fd3eca0e
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8A0V81kHNgdj8mA03dNY
X-Amz-Date: 20171017T223103Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "ObjectReference": {
    "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWcU7IARv0TearR09zme1sVsw"
  }
}
```

Example Response

This example illustrates one usage of `ListObjectChildren`.

```
HTTP/1.1 200 OK
x-amzn-RequestId: dcafb249-b38a-11e7-a973-b71cf1107b43
Date: Tue, 17 Oct 2017 22:31:04 GMT
x-amzn-RequestId: dcafb249-b38a-11e7-a973-b71cf1107b43
Content-Type: application/json
Content-Length: 88

{
  "Children": {
    "link2": "AQGG_AD1fNZBzYHY_JgDt3TWSvfuEnDqTdmeCuTs6YBNUA"
  },
  "NextToken": null
}
```

```
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListObjectParentPaths

Retrieves all available parent paths for any object type such as node, leaf node, policy node, and index node objects. For more information about objects, see [Directory Structure](#).

Use this API to evaluate all parents for an object. The call returns all objects from the root of the directory up to the requested object. The API returns the number of paths based on user-defined `MaxResults`, in case there are multiple paths to the parent. The order of the paths and nodes returned is consistent among multiple API calls unless the objects are deleted or moved. Paths not leading to the directory root are ignored from the target object.

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/object/parentpaths HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json

{
  "MaxResults": number,
  "NextToken": "string",
  "ObjectReference": {
    "Selector": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

[DirectoryArn](#)

The ARN of the directory to which the parent path applies.

Required: Yes

Request Body

The request accepts the following data in JSON format.

MaxResults

The maximum number of items to be retrieved in a single call. This is an approximate number.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The pagination token.

Type: String

Required: No

ObjectReference

The reference that identifies the object whose parent paths are listed.

Type: [ObjectReference](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "PathToObjectIdentifiersList": [
    {
      "ObjectIdentifiers": [ "string" ],
      "Path": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token.

Type: String

PathToObjectIdentifiersList

Returns the path to the `ObjectIdentifiers` that are associated with the directory.

Type: Array of [PathToObjectIdentifiers](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidNextTokenException

Indicates that the NextToken value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using “SERIALIZABLE” consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListObjectParents

Lists parent objects that are associated with a given object in pagination fashion.

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/object/parent HTTP/1.1
x-amz-data-partition: DirectoryArn
x-amz-consistency-level: ConsistencyLevel
Content-type: application/json

{
  "IncludeAllLinksToEachParent": boolean,
  "MaxResults": number,
  "NextToken": "string",
  "ObjectReference": {
    "Selector": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

ConsistencyLevel

Represents the manner and timing in which the successful write or update of an object is reflected in a subsequent read operation of that same object.

Valid Values: SERIALIZABLE | EVENTUAL

DirectoryArn

The Amazon Resource Name (ARN) that is associated with the [Directory](#) where the object resides. For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

IncludeAllLinksToEachParent

When set to True, returns all [ListObjectParents:ParentLinks](#). There could be multiple links between a parent-child pair.

Type: Boolean

Required: No

MaxResults

The maximum number of items to be retrieved in a single call. This is an approximate number.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The pagination token.

Type: String

Required: No

ObjectReference

The reference that identifies the object for which parent objects are being listed.

Type: [ObjectReference](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "ParentLinks": [
```

```
{
  {
    "LinkName": "string",
    "ObjectIdentifier": "string"
  }
],
"Parents": {
  "string" : "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token.

Type: String

ParentLinks

Returns a list of parent reference and LinkName Tuples.

Type: Array of [ObjectIdentifierAndLinkNameTuple](#) objects

Parents

The parent structure, which is a map with key as the `ObjectIdentifier` and `LinkName` as the value.

Type: String to string map

Value Length Constraints: Minimum length of 1. Maximum length of 64.

Value Pattern: `[^\\\[\\]\\\(\):\\{\}#\@!?\s\\;]+`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

CannotListParentOfRootException

Cannot list the parents of a [Directory](#) root.

HTTP Status Code: 400

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidNextTokenException

Indicates that the NextToken value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListObjectPolicies

Returns policies attached to an object in pagination fashion.

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/object/policy HTTP/1.1
x-amz-data-partition: DirectoryArn
x-amz-consistency-level: ConsistencyLevel
Content-type: application/json
```

```
{
  "MaxResults": number,
  "NextToken": "string",
  "ObjectReference": {
    "Selector": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

ConsistencyLevel

Represents the manner and timing in which the successful write or update of an object is reflected in a subsequent read operation of that same object.

Valid Values: SERIALIZABLE | EVENTUAL

DirectoryArn

The Amazon Resource Name (ARN) that is associated with the [Directory](#) where objects reside. For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

MaxResults

The maximum number of items to be retrieved in a single call. This is an approximate number.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The pagination token.

Type: String

Required: No

ObjectReference

Reference that identifies the object for which policies will be listed.

Type: [ObjectReference](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AttachedPolicyIds": [ "string" ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AttachedPolicyIds

A list of policy `ObjectIdentifiers`, that are attached to the object.

Type: Array of strings

NextToken

The pagination token.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidNextTokenException

Indicates that the `NextToken` value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListOutgoingTypedLinks

Returns a paginated list of all the outgoing [TypedLinkSpecifier](#) information for an object. It also supports filtering by typed link facet and identity attributes. For more information, see [Typed Links](#).

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/typedlink/outgoing HTTP/1.1
```

```
x-amz-data-partition: DirectoryArn
```

```
Content-type: application/json
```

```
{
  "ConsistencyLevel": "string",
  "FilterAttributeRanges": [
    {
      "AttributeName": "string",
      "Range": {
        "EndMode": "string",
        "EndValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        },
        "StartMode": "string",
        "StartValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        }
      }
    }
  ],
  "FilterTypedLink": {
    "SchemaArn": "string",
    "TypedLinkName": "string"
  },
  "MaxResults": number,
```

```
"NextToken": "string",
"ObjectReference": {
  "Selector": "string"
}
}
```

URI Request Parameters

The request uses the following URI parameters.

DirectoryArn

The Amazon Resource Name (ARN) of the directory where you want to list the typed links.

Required: Yes

Request Body

The request accepts the following data in JSON format.

ConsistencyLevel

The consistency level to execute the request at.

Type: String

Valid Values: SERIALIZABLE | EVENTUAL

Required: No

FilterAttributeRanges

Provides range filters for multiple attributes. When providing ranges to typed link selection, any inexact ranges must be specified at the end. Any attributes that do not have a range specified are presumed to match the entire range.

Type: Array of [TypedLinkAttributeRange](#) objects

Required: No

FilterTypedLink

Filters are interpreted in the order of the attributes defined on the typed link facet, not the order they are supplied to any API calls.

Type: [TypedLinkSchemaAndFacetName](#) object

Required: No

[MaxResults](#)

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

[NextToken](#)

The pagination token.

Type: String

Required: No

[ObjectReference](#)

A reference that identifies the object whose attributes will be listed.

Type: [ObjectReference](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "TypedLinkSpecifiers": [
    {
      "IdentityAttributeValues": [
        {
          "AttributeName": "string",
          "Value": {
            "BinaryValue": blob,

```

```
        "BooleanValue": boolean,
        "DatetimeValue": number,
        "NumberValue": "string",
        "StringValue": "string"
    }
}
],
"SourceObjectReference": {
    "Selector": "string"
},
"TargetObjectReference": {
    "Selector": "string"
},
"TypedLinkFacet": {
    "SchemaArn": "string",
    "TypedLinkName": "string"
}
}
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token.

Type: String

TypedLinkSpecifiers

Returns a typed link specifier as output.

Type: Array of [TypedLinkSpecifier](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

FacetValidationException

The [Facet](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidNextTokenException

Indicates that the NextToken value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using “SERIALIZABLE” consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListPolicyAttachments

Returns all of the `ObjectIdentifiers` to which a given policy is attached.

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/policy/attachment HTTP/1.1
x-amz-data-partition: DirectoryArn
x-amz-consistency-level: ConsistencyLevel
Content-type: application/json
```

```
{
  "MaxResults": number,
  "NextToken": "string",
  "PolicyReference": {
    "Selector": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

ConsistencyLevel

Represents the manner and timing in which the successful write or update of an object is reflected in a subsequent read operation of that same object.

Valid Values: SERIALIZABLE | EVENTUAL

DirectoryArn

The Amazon Resource Name (ARN) that is associated with the [Directory](#) where objects reside. For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

MaxResults

The maximum number of items to be retrieved in a single call. This is an approximate number.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The pagination token.

Type: String

Required: No

PolicyReference

The reference that identifies the policy object.

Type: [ObjectReference](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "ObjectIdentifiers": [ "string" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token.

Type: String

ObjectIdentifiers

A list of `ObjectIdentifiers` to which the policy is attached.

Type: Array of strings

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidNextTokenException

Indicates that the `NextToken` value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

NotPolicyException

Indicates that the requested operation can only operate on policy objects.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListPublishedSchemaArns

Lists the major version families of each published schema. If a major version ARN is provided as `SchemaArn`, the minor version revisions in that family are listed instead.

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/schema/published HTTP/1.1
Content-type: application/json
```

```
{
  "MaxResults": number,
  "NextToken": "string",
  "SchemaArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

MaxResults

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The pagination token.

Type: String

Required: No

SchemaArn

The response for `ListPublishedSchemaArns` when this parameter is used will list all minor version ARNs for a major version.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "SchemaArns": [ "string" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token.

Type: String

SchemaArns

The ARNs of published schemas.

Type: Array of strings

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidNextTokenException

Indicates that the NextToken value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Returns tags for a resource. Tagging is currently supported only for directories with a limit of 50 tags per directory. All 50 tags are returned for a given directory with this API call.

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/tags HTTP/1.1
Content-type: application/json
```

```
{
  "MaxResults": number,
  "NextToken": "string",
  "ResourceArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

MaxResults

The `MaxResults` parameter sets the maximum number of results returned in a single page. This is for future use and is not supported currently.

Type: Integer

Valid Range: Minimum value of 50.

Required: No

NextToken

The pagination token. This is for future use. Currently pagination is not supported for tagging.

Type: String

Required: No

ResourceArn

The Amazon Resource Name (ARN) of the resource. Tagging is only supported for directories.

Type: String

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token to use to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

Tags

A list of tag key value pairs that are associated with the response.

Type: Array of [Tag](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidTaggingRequestException

Can occur for multiple reasons such as when you tag a resource that doesn't exist or if you specify a higher number of tags for a resource than the allowed limit. Allowed limit is 50 tags per resource.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using “SERIALIZABLE” consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTypedLinkFacetAttributes

Returns a paginated list of all attribute definitions for a particular [TypedLinkFacet](#). For more information, see [Typed Links](#).

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/typedlink/facet/attributes HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json

{
  "MaxResults": number,
  "Name": "string",
  "NextToken": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

[SchemaArn](#)

The Amazon Resource Name (ARN) that is associated with the schema. For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

[MaxResults](#)

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

Name

The unique name of the typed link facet.

Type: String

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

NextToken

The pagination token.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Attributes": [
    {
      "DefaultValue": {
        "BinaryValue": blob,
        "BooleanValue": boolean,
        "DatetimeValue": number,
        "NumberValue": "string",
        "StringValue": "string"
      },
      "IsImmutable": boolean,
      "Name": "string",
      "RequiredBehavior": "string",
      "Rules": {
        "string" : {
          "Parameters": {
            "string" : "string"
          },
        },
        "Type": "string"
      }
    }
  ]
}
```

```
    }
    },
    "Type": "string"
  }
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Attributes

An ordered set of attributes associate with the typed link.

Type: Array of [TypedLinkAttributeDefinition](#) objects

NextToken

The pagination token.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

FacetNotFoundException

The specified [Facet](#) could not be found.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidNextTokenException

Indicates that the NextToken value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTypedLinkFacetNames

Returns a paginated list of TypedLink facet names for a particular schema. For more information, see [Typed Links](#).

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/typedlink/facet/list HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json

{
  "MaxResults": number,
  "NextToken": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

[SchemaArn](#)

The Amazon Resource Name (ARN) that is associated with the schema. For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

[MaxResults](#)

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The pagination token.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "FacetNames": [ "string" ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

FacetNames

The names of typed link facets that exist within the schema.

Type: Array of strings

Pattern: `^[a-zA-Z0-9._-]*$`

NextToken

The pagination token.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidNextTokenException

Indicates that the NextToken value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

LookupPolicy

Lists all policies from the root of the [Directory](#) to the object specified. If there are no policies present, an empty list is returned. If policies are present, and if some objects don't have the policies attached, it returns the `ObjectIdentifier` for such objects. If policies are present, it returns `ObjectIdentifier`, `policyId`, and `policyType`. Paths that don't lead to the root from the target object are ignored. For more information, see [Policies](#).

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/policy/lookup HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json

{
  "MaxResults": number,
  "NextToken": "string",
  "ObjectReference": {
    "Selector": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

[DirectoryArn](#)

The Amazon Resource Name (ARN) that is associated with the [Directory](#). For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

[MaxResults](#)

The maximum number of items to be retrieved in a single call. This is an approximate number.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The token to request the next page of results.

Type: String

Required: No

ObjectReference

Reference that identifies the object whose policies will be looked up.

Type: [ObjectReference](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "PolicyToPathList": [
    {
      "Path": "string",
      "Policies": [
        {
          "ObjectIdentifier": "string",
          "PolicyId": "string",
          "PolicyType": "string"
        }
      ]
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token.

Type: String

PolicyToPathList

Provides list of path to policies. Policies contain `PolicyId`, `ObjectIdentifier`, and `PolicyType`. For more information, see [Policies](#).

Type: Array of [PolicyToPath](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidNextTokenException

Indicates that the NextToken value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PublishSchema

Publishes a development schema with a major version and a recommended minor version.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/schema/publish HTTP/1.1
x-amz-data-partition: DevelopmentSchemaArn
Content-type: application/json

{
  "MinorVersion": "string",
  "Name": "string",
  "Version": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

DevelopmentSchemaArn

The Amazon Resource Name (ARN) that is associated with the development schema. For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

MinorVersion

The minor version under which the schema will be published. This parameter is recommended. Schemas have both a major and minor version associated with them.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: No

Name

The new name under which the schema will be published. If this is not provided, the development schema is considered.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: No

Version

The major version under which the schema will be published. Schemas have both a major and minor version associated with them.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "PublishedSchemaArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

PublishedSchemaArn

The ARN that is associated with the published schema. For more information, see [Arn Examples](#).

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using “SERIALIZABLE” consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

SchemaAlreadyPublishedException

Indicates that a schema is already published.

HTTP Status Code: 400

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutSchemaFromJson

Allows a schema to be updated using JSON upload. Only available for development schemas. See [JSON Schema Format](#) for more information.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/schema/json HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json

{
  "Document": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

SchemaArn

The ARN of the schema to update.

Required: Yes

Request Body

The request accepts the following data in JSON format.

Document

The replacement JSON schema.

Type: String

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "Arn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The ARN of the schema to update.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidRuleException

Occurs when any of the rule parameter keys or values are invalid.

HTTP Status Code: 400

InvalidSchemaDocException

Indicates that the provided SchemaDoc value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RemoveFacetFromObject

Removes the specified facet from the specified object.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/object/facets/delete HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json

{
  "ObjectReference": {
    "Selector": "string"
  },
  "SchemaFacet": {
    "FacetName": "string",
    "SchemaArn": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

DirectoryArn

The ARN of the directory in which the object resides.

Required: Yes

Request Body

The request accepts the following data in JSON format.

ObjectReference

A reference to the object to remove the facet from.

Type: ObjectReference object

Required: Yes

[SchemaFacet](#)

The facet to remove. See [SchemaFacet](#) for details.

Type: [SchemaFacet](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

FacetValidationException

The [Facet](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

An API operation for adding tags to a resource.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/tags/add HTTP/1.1
Content-type: application/json

{
  "ResourceArn": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ResourceArn

The Amazon Resource Name (ARN) of the resource. Tagging is only supported for directories.

Type: String

Required: Yes

Tags

A list of tag key-value pairs.

Type: Array of [Tag](#) objects

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidTaggingRequestException

Can occur for multiple reasons such as when you tag a resource that doesn't exist or if you specify a higher number of tags for a resource than the allowed limit. Allowed limit is 50 tags per resource.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

An API operation for removing tags from a resource.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/tags/remove HTTP/1.1
Content-type: application/json
```

```
{
  "ResourceArn": "string",
  "TagKeys": [ "string" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ResourceArn

The Amazon Resource Name (ARN) of the resource. Tagging is only supported for directories.

Type: String

Required: Yes

TagKeys

Keys of the tag that need to be removed from the resource.

Type: Array of strings

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidTaggingRequestException

Can occur for multiple reasons such as when you tag a resource that doesn't exist or if you specify a higher number of tags for a resource than the allowed limit. Allowed limit is 50 tags per resource.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using “SERIALIZABLE” consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateFacet

Does the following:

1. Adds new Attributes, Rules, or ObjectTypes.
2. Updates existing Attributes, Rules, or ObjectTypes.
3. Deletes existing Attributes, Rules, or ObjectTypes.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/facet HTTP/1.1
```

```
x-amz-data-partition: SchemaArn
```

```
Content-type: application/json
```

```
{
  "AttributeUpdates": [
    {
      "Action": "string",
      "Attribute": {
        "AttributeDefinition": {
          "DefaultValue": {
            "BinaryValue": blob,
            "BooleanValue": boolean,
            "DatetimeValue": number,
            "NumberValue": "string",
            "StringValue": "string"
          },
          "IsImmutable": boolean,
          "Rules": {
            "string" : {
              "Parameters": {
                "string" : "string"
              },
              "Type": "string"
            }
          },
          "Type": "string"
        },
        "AttributeReference": {
          "TargetAttributeName": "string",
          "TargetFacetName": "string"
        }
      }
    }
  ]
}
```

```
    },
    "Name": "string",
    "RequiredBehavior": "string"
  }
},
"Name": "string",
"ObjectType": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

SchemaArn

The Amazon Resource Name (ARN) that is associated with the [Facet](#). For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

AttributeUpdates

List of attributes that need to be updated in a given schema [Facet](#). Each attribute is followed by `AttributeAction`, which specifies the type of update operation to perform.

Type: Array of [FacetAttributeUpdate](#) objects

Required: No

Name

The name of the facet.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

ObjectType

The object type that is associated with the facet. See [CreateFacet:ObjectType](#) for more details.

Type: String

Valid Values: NODE | LEAF_NODE | POLICY | INDEX

Required: No

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

FacetNotFoundException

The specified [Facet](#) could not be found.

HTTP Status Code: 400

FacetValidationException

The [Facet](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidFacetUpdateException

An attempt to modify a [Facet](#) resulted in an invalid schema exception.

HTTP Status Code: 400

InvalidRuleException

Occurs when any of the rule parameter keys or values are invalid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateLinkAttributes

Updates a given typed link's attributes. Attributes to be updated must not contribute to the typed link's identity, as defined by its IdentityAttributeOrder.

Request Syntax

```
POST /amazonclouddirectory/2017-01-11/typedlink/attributes/update HTTP/1.1
```

```
x-amz-data-partition: DirectoryArn
```

```
Content-type: application/json
```

```
{
  "AttributeUpdates": [
    {
      "AttributeAction": {
        "AttributeActionType": "string",
        "AttributeUpdateValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        }
      },
      "AttributeKey": {
        "FacetName": "string",
        "Name": "string",
        "SchemaArn": "string"
      }
    }
  ],
  "TypedLinkSpecifier": {
    "IdentityAttributeValues": [
      {
        "AttributeName": "string",
        "Value": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        }
      }
    ]
  }
}
```

```
    ],
    "SourceObjectReference": {
      "Selector": "string"
    },
    "TargetObjectReference": {
      "Selector": "string"
    },
    "TypedLinkFacet": {
      "SchemaArn": "string",
      "TypedLinkName": "string"
    }
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

DirectoryArn

The Amazon Resource Name (ARN) that is associated with the Directory where the updated typed link resides. For more information, see [Arn Examples](#) or [Typed Links](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

AttributeUpdates

The attributes update structure.

Type: Array of [LinkAttributeUpdate](#) objects

Required: Yes

TypedLinkSpecifier

Allows a typed link specifier to be accepted as input.

Type: [TypedLinkSpecifier](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

FacetValidationException

The [Facet](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateObjectAttributes

Updates a given object's attributes.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/object/update HTTP/1.1
```

```
x-amz-data-partition: DirectoryArn
```

```
Content-type: application/json
```

```
{
  "AttributeUpdates": [
    {
      "ObjectAttributeAction": {
        "ObjectAttributeActionType": "string",
        "ObjectAttributeUpdateValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        }
      },
      "ObjectAttributeKey": {
        "FacetName": "string",
        "Name": "string",
        "SchemaArn": "string"
      }
    }
  ],
  "ObjectReference": {
    "Selector": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

DirectoryArn

The Amazon Resource Name (ARN) that is associated with the [Directory](#) where the object resides. For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

AttributeUpdates

The attributes update structure.

Type: Array of [ObjectAttributeUpdate](#) objects

Required: Yes

ObjectReference

The reference that identifies the object.

Type: [ObjectReference](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ObjectIdentifier": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ObjectIdentifier

The `ObjectIdentifier` of the updated object.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

FacetValidationException

The [Facet](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

LinkNameAlreadyInUseException

Indicates that a link could not be created due to a naming conflict. Choose a different name and then try again.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateSchema

Updates the schema name with a new name. Only development schema names can be updated.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/schema/update HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json

{
  "Name": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

SchemaArn

The Amazon Resource Name (ARN) of the development schema. For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

Name

The name of the schema.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "SchemaArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[SchemaArn](#)

The ARN that is associated with the updated schema. For more information, see [Arn Examples](#).

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

SchemaAlreadyExistsException

Indicates that a schema could not be created due to a naming conflict. Please select a different name and then try again.

HTTP Status Code: 400

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateTypedLinkFacet

Updates a [TypedLinkFacet](#). For more information, see [Typed Links](#).

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/typedlink/facet HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json
```

```
{
  "AttributeUpdates": [
    {
      "Action": "string",
      "Attribute": {
        "DefaultValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        },
        "IsImmutable": boolean,
        "Name": "string",
        "RequiredBehavior": "string",
        "Rules": {
          "string" : {
            "Parameters": {
              "string" : "string"
            },
            "Type": "string"
          }
        },
        "Type": "string"
      }
    }
  ],
  "IdentityAttributeOrder": [ "string" ],
  "Name": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

SchemaArn

The Amazon Resource Name (ARN) that is associated with the schema. For more information, see [Arn Examples](#).

Required: Yes

Request Body

The request accepts the following data in JSON format.

AttributeUpdates

Attributes update structure.

Type: Array of [TypedLinkFacetAttributeUpdate](#) objects

Required: Yes

IdentityAttributeOrder

The order of identity attributes for the facet, from most significant to least significant. The ability to filter typed links considers the order that the attributes are defined on the typed link facet. When providing ranges to a typed link selection, any inexact ranges must be specified at the end. Any attributes that do not have a range specified are presumed to match the entire range. Filters are interpreted in the order of the attributes on the typed link facet, not the order in which they are supplied to any API calls. For more information about identity attributes, see [Typed Links](#).

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 230.

Pattern: `^[a-zA-Z0-9._: -]*$`

Required: Yes

Name

The unique name of the typed link facet.

Type: String

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

FacetNotFoundException

The specified [Facet](#) could not be found.

HTTP Status Code: 400

FacetValidationException

The [Facet](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidFacetUpdateException

An attempt to modify a [Facet](#) resulted in an invalid schema exception.

HTTP Status Code: 400

InvalidRuleException

Occurs when any of the rule parameter keys or values are invalid.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpgradeAppliedSchema

Upgrades a single directory in-place using the `PublishedSchemaArn` with schema updates found in `MinorVersion`. Backwards-compatible minor version upgrades are instantaneously available for readers on all objects in the directory. Note: This is a synchronous API call and upgrades only one schema on a given directory per call. To upgrade multiple directories from one schema, you would need to call this API on each directory.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/schema/upgradeapplied HTTP/1.1
Content-type: application/json
```

```
{
  "DirectoryArn": "string",
  "DryRun": boolean,
  "PublishedSchemaArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[DirectoryArn](#)

The ARN for the directory to which the upgraded schema will be applied.

Type: String

Required: Yes

[DryRun](#)

Used for testing whether the major version schemas are backward compatible or not. If schema compatibility fails, an exception would be thrown else the call would succeed but no changes will be saved. This parameter is optional.

Type: Boolean

Required: No

PublishedSchemaArn

The revision of the published schema to upgrade the directory to.

Type: String

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "DirectoryArn": "string",
  "UpgradedSchemaArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DirectoryArn

The ARN of the directory that is returned as part of the response.

Type: String

UpgradedSchemaArn

The ARN of the upgraded schema that is returned as part of the response.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

IncompatibleSchemaException

Indicates a failure occurred while performing a check for backward compatibility between the specified schema and the schema that is currently applied to the directory.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidAttachmentException

Indicates that an attempt to make an attachment was invalid. For example, attaching two nodes with a link type that is not applicable to the nodes or attempting to apply a schema to a directory a second time.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using

“SERIALIZABLE” consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

SchemaAlreadyExistsException

Indicates that a schema could not be created due to a naming conflict. Please select a different name and then try again.

HTTP Status Code: 400

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpgradePublishedSchema

Upgrades a published schema under a new minor version revision using the current contents of `DevelopmentSchemaArn`.

Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/schema/upgradepublished HTTP/1.1
Content-type: application/json
```

```
{
  "DevelopmentSchemaArn": "string",
  "DryRun": boolean,
  "MinorVersion": "string",
  "PublishedSchemaArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

DevelopmentSchemaArn

The ARN of the development schema with the changes used for the upgrade.

Type: String

Required: Yes

DryRun

Used for testing whether the Development schema provided is backwards compatible, or not, with the publish schema provided by the user to be upgraded. If schema compatibility fails, an exception would be thrown else the call would succeed. This parameter is optional and defaults to false.

Type: Boolean

Required: No

MinorVersion

Identifies the minor version of the published schema that will be created. This parameter is NOT optional.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

PublishedSchemaArn

The ARN of the published schema to be upgraded.

Type: String

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "UpgradedSchemaArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

UpgradedSchemaArn

The ARN of the upgraded schema that is returned as part of the response.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) and check your permissions.

HTTP Status Code: 403

IncompatibleSchemaException

Indicates a failure occurred while performing a check for backward compatibility between the specified schema and the schema that is currently applied to the directory.

HTTP Status Code: 400

InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

InvalidAttachmentException

Indicates that an attempt to make an attachment was invalid. For example, attaching two nodes with a link type that is not applicable to the nodes or attempting to apply a schema to a directory a second time.

HTTP Status Code: 400

LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using “SERIALIZABLE” consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The Amazon CloudDirectory API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AttributeKey](#)
- [AttributeKeyAndValue](#)
- [AttributeNameAndValue](#)
- [BatchAddFacetToObject](#)
- [BatchAddFacetToObjectResponse](#)
- [BatchAttachObject](#)
- [BatchAttachObjectResponse](#)
- [BatchAttachPolicy](#)
- [BatchAttachPolicyResponse](#)
- [BatchAttachToIndex](#)
- [BatchAttachToIndexResponse](#)
- [BatchAttachTypedLink](#)
- [BatchAttachTypedLinkResponse](#)
- [BatchCreateIndex](#)
- [BatchCreateIndexResponse](#)
- [BatchCreateObject](#)
- [BatchCreateObjectResponse](#)
- [BatchDeleteObject](#)
- [BatchDeleteObjectResponse](#)
- [BatchDetachFromIndex](#)

- [BatchDetachFromIndexResponse](#)
- [BatchDetachObject](#)
- [BatchDetachObjectResponse](#)
- [BatchDetachPolicy](#)
- [BatchDetachPolicyResponse](#)
- [BatchDetachTypedLink](#)
- [BatchDetachTypedLinkResponse](#)
- [BatchGetLinkAttributes](#)
- [BatchGetLinkAttributesResponse](#)
- [BatchGetObjectAttributes](#)
- [BatchGetObjectAttributesResponse](#)
- [BatchGetObjectInformation](#)
- [BatchGetObjectInformationResponse](#)
- [BatchListAttachedIndices](#)
- [BatchListAttachedIndicesResponse](#)
- [BatchListIncomingTypedLinks](#)
- [BatchListIncomingTypedLinksResponse](#)
- [BatchListIndex](#)
- [BatchListIndexResponse](#)
- [BatchListObjectAttributes](#)
- [BatchListObjectAttributesResponse](#)
- [BatchListObjectChildren](#)
- [BatchListObjectChildrenResponse](#)
- [BatchListObjectParentPaths](#)
- [BatchListObjectParentPathsResponse](#)
- [BatchListObjectParents](#)
- [BatchListObjectParentsResponse](#)
- [BatchListObjectPolicies](#)
- [BatchListObjectPoliciesResponse](#)
- [BatchListOutgoingTypedLinks](#)

- [BatchListOutgoingTypedLinksResponse](#)
- [BatchListPolicyAttachments](#)
- [BatchListPolicyAttachmentsResponse](#)
- [BatchLookupPolicy](#)
- [BatchLookupPolicyResponse](#)
- [BatchReadException](#)
- [BatchReadOperation](#)
- [BatchReadOperationResponse](#)
- [BatchReadSuccessfulResponse](#)
- [BatchRemoveFacetFromObject](#)
- [BatchRemoveFacetFromObjectResponse](#)
- [BatchUpdateLinkAttributes](#)
- [BatchUpdateLinkAttributesResponse](#)
- [BatchUpdateObjectAttributes](#)
- [BatchUpdateObjectAttributesResponse](#)
- [BatchWriteOperation](#)
- [BatchWriteOperationResponse](#)
- [Directory](#)
- [Facet](#)
- [FacetAttribute](#)
- [FacetAttributeDefinition](#)
- [FacetAttributeReference](#)
- [FacetAttributeUpdate](#)
- [IndexAttachment](#)
- [LinkAttributeAction](#)
- [LinkAttributeUpdate](#)
- [ObjectAttributeAction](#)
- [ObjectAttributeRange](#)
- [ObjectAttributeUpdate](#)
- [ObjectIdentifierAndLinkNameTuple](#)

- [ObjectReference](#)
- [PathToObjectIdentifiers](#)
- [PolicyAttachment](#)
- [PolicyToPath](#)
- [Rule](#)
- [SchemaFacet](#)
- [Tag](#)
- [TypedAttributeValue](#)
- [TypedAttributeValueRange](#)
- [TypedLinkAttributeDefinition](#)
- [TypedLinkAttributeRange](#)
- [TypedLinkFacet](#)
- [TypedLinkFacetAttributeUpdate](#)
- [TypedLinkSchemaAndFacetName](#)
- [TypedLinkSpecifier](#)

AttributeKey

A unique identifier for an attribute.

Contents

FacetName

The name of the facet that the attribute exists within.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

Name

The name of the attribute.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 230.

Pattern: `^[a-zA-Z0-9._:-]*$`

Required: Yes

SchemaArn

The Amazon Resource Name (ARN) of the schema that contains the facet and attribute.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AttributeKeyAndValue

The combination of an attribute key and an attribute value.

Contents

Key

The key of the attribute.

Type: [AttributeKey](#) object

Required: Yes

Value

The value of the attribute.

Type: [TypedAttributeValue](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AttributeNameAndValue

Identifies the attribute name and value for a typed link.

Contents

AttributeName

The attribute name of the typed link.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 230.

Pattern: `^[a-zA-Z0-9._: -]*$`

Required: Yes

Value

The value for the typed link.

Type: [TypedAttributeValue](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchAddFacetToObject

Represents the output of a batch add facet to object operation.

Contents

ObjectAttributeList

The attributes to set on the object.

Type: Array of [AttributeKeyAndValue](#) objects

Required: Yes

ObjectReference

A reference to the object being mutated.

Type: [ObjectReference](#) object

Required: Yes

SchemaFacet

Represents the facet being added to the object.

Type: [SchemaFacet](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchAddFacetToObjectResponse

The result of a batch add facet to object operation.

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchAttachObject

Represents the output of an [AttachObject](#) operation.

Contents

ChildReference

The child object reference that is to be attached to the object.

Type: [ObjectReference](#) object

Required: Yes

LinkName

The name of the link.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[^\\\/\[\]\(\):\{\}\#\@!\?\s\\;]+`

Required: Yes

ParentReference

The parent object reference.

Type: [ObjectReference](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchAttachObjectResponse

Represents the output batch [AttachObject](#) response operation.

Contents

attachedObjectIdentifier

The `ObjectIdentifier` of the object that has been attached.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchAttachPolicy

Attaches a policy object to a regular object inside a [BatchRead](#) operation. For more information, see [AttachPolicy](#) and [BatchRead:Operations](#).

Contents

ObjectReference

The reference that identifies the object to which the policy will be attached.

Type: [ObjectReference](#) object

Required: Yes

PolicyReference

The reference that is associated with the policy object.

Type: [ObjectReference](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchAttachPolicyResponse

Represents the output of an [AttachPolicy](#) response operation.

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchAttachToIndex

Attaches the specified object to the specified index inside a [BatchRead](#) operation. For more information, see [AttachToIndex](#) and [BatchRead:Operations](#).

Contents

IndexReference

A reference to the index that you are attaching the object to.

Type: [ObjectReference](#) object

Required: Yes

TargetReference

A reference to the object that you are attaching to the index.

Type: [ObjectReference](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchAttachToIndexResponse

Represents the output of a [AttachToIndex](#) response operation.

Contents

AttachedObjectIdentifier

The `ObjectIdentifier` of the object that was attached to the index.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchAttachTypedLink

Attaches a typed link to a specified source and target object inside a [BatchRead](#) operation. For more information, see [AttachTypedLink](#) and [BatchRead:Operations](#).

Contents

Attributes

A set of attributes that are associated with the typed link.

Type: Array of [AttributeNameAndValue](#) objects

Required: Yes

SourceObjectReference

Identifies the source object that the typed link will attach to.

Type: [ObjectReference](#) object

Required: Yes

TargetObjectReference

Identifies the target object that the typed link will attach to.

Type: [ObjectReference](#) object

Required: Yes

TypedLinkFacet

Identifies the typed link facet that is associated with the typed link.

Type: [TypedLinkSchemaAndFacetName](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchAttachTypedLinkResponse

Represents the output of a [AttachTypedLink](#) response operation.

Contents

TypedLinkSpecifier

Returns a typed link specifier as output.

Type: [TypedLinkSpecifier](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchCreateIndex

Creates an index object inside of a [BatchRead](#) operation. For more information, see [CreateIndex](#) and [BatchRead:Operations](#).

Contents

IsUnique

Indicates whether the attribute that is being indexed has unique values or not.

Type: Boolean

Required: Yes

OrderedIndexedAttributeList

Specifies the attributes that should be indexed on. Currently only a single attribute is supported.

Type: Array of [AttributeKey](#) objects

Required: Yes

BatchReferenceName

The batch reference name. See [Transaction Support](#) for more information.

Type: String

Required: No

LinkName

The name of the link between the parent object and the index object.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[^\\\/[\]\(\):\{\}\#\@!\?\s\\;]+`

Required: No

ParentReference

A reference to the parent object that contains the index object.

Type: [ObjectReference](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchCreateIndexResponse

Represents the output of a [CreateIndex](#) response operation.

Contents

ObjectIdentifier

The `ObjectIdentifier` of the index created by this operation.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchCreateObject

Represents the output of a [CreateObject](#) operation.

Contents

ObjectAttributeList

An attribute map, which contains an attribute ARN as the key and attribute value as the map value.

Type: Array of [AttributeKeyAndValue](#) objects

Required: Yes

SchemaFacet

A list of FacetArns that will be associated with the object. For more information, see [Arn Examples](#).

Type: Array of [SchemaFacet](#) objects

Required: Yes

BatchReferenceName

The batch reference name. See [Transaction Support](#) for more information.

Type: String

Required: No

LinkName

The name of the link.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[^\v[\]\(\):\{\}\#\@!?\s\\;]+`

Required: No

ParentReference

If specified, the parent reference to which this object will be attached.

Type: [ObjectReference](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchCreateObjectResponse

Represents the output of a [CreateObject](#) response operation.

Contents

ObjectIdentifier

The ID that is associated with the object.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchDeleteObject

Represents the output of a [DeleteObject](#) operation.

Contents

ObjectReference

The reference that identifies the object.

Type: [ObjectReference](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchDeleteObjectResponse

Represents the output of a [DeleteObject](#) response operation.

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchDetachFromIndex

Detaches the specified object from the specified index inside a [BatchRead](#) operation. For more information, see [DetachFromIndex](#) and [BatchRead:Operations](#).

Contents

IndexReference

A reference to the index object.

Type: [ObjectReference](#) object

Required: Yes

TargetReference

A reference to the object being detached from the index.

Type: [ObjectReference](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchDetachFromIndexResponse

Represents the output of a [DetachFromIndex](#) response operation.

Contents

DetachedObjectIdentifier

The `ObjectIdentifier` of the object that was detached from the index.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchDetachObject

Represents the output of a [DetachObject](#) operation.

Contents

LinkName

The name of the link.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[^\V\[\]\(\):\{\}\#\@!\?\s\\;]+`

Required: Yes

ParentReference

Parent reference from which the object with the specified link name is detached.

Type: [ObjectReference](#) object

Required: Yes

BatchReferenceName

The batch reference name. See [Transaction Support](#) for more information.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchDetachObjectResponse

Represents the output of a [DetachObject](#) response operation.

Contents

`detachedObjectIdentifier`

The `ObjectIdentifier` of the detached object.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchDetachPolicy

Detaches the specified policy from the specified directory inside a [BatchWrite](#) operation. For more information, see [DetachPolicy](#) and [BatchWrite:Operations](#).

Contents

ObjectReference

Reference that identifies the object whose policy object will be detached.

Type: [ObjectReference](#) object

Required: Yes

PolicyReference

Reference that identifies the policy object.

Type: [ObjectReference](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchDetachPolicyResponse

Represents the output of a [DetachPolicy](#) response operation.

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchDetachTypedLink

Detaches a typed link from a specified source and target object inside a [BatchRead](#) operation. For more information, see [DetachTypedLink](#) and [BatchRead:Operations](#).

Contents

TypedLinkSpecifier

Used to accept a typed link specifier as input.

Type: [TypedLinkSpecifier](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchDetachTypedLinkResponse

Represents the output of a [DetachTypedLink](#) response operation.

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchGetLinkAttributes

Retrieves attributes that are associated with a typed link inside a [BatchRead](#) operation. For more information, see [GetLinkAttributes](#) and [BatchRead:Operations](#).

Contents

AttributeNames

A list of attribute names whose values will be retrieved.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 230.

Pattern: `^[a-zA-Z0-9._: -]*$`

Required: Yes

TypedLinkSpecifier

Allows a typed link specifier to be accepted as input.

Type: [TypedLinkSpecifier](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchGetLinkAttributesResponse

Represents the output of a [GetLinkAttributes](#) response operation.

Contents

Attributes

The attributes that are associated with the typed link.

Type: Array of [AttributeKeyAndValue](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchGetObjectAttributes

Retrieves attributes within a facet that are associated with an object inside an [BatchRead](#) operation. For more information, see [GetObjectAttributes](#) and [BatchRead:Operations](#).

Contents

AttributeNames

List of attribute names whose values will be retrieved.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 230.

Pattern: `^[a-zA-Z0-9._: -]*$`

Required: Yes

ObjectReference

Reference that identifies the object whose attributes will be retrieved.

Type: [ObjectReference](#) object

Required: Yes

SchemaFacet

Identifier for the facet whose attributes will be retrieved. See [SchemaFacet](#) for details.

Type: [SchemaFacet](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

BatchGetObjectAttributesResponse

Represents the output of a [GetObjectAttributes](#) response operation.

Contents

Attributes

The attribute values that are associated with an object.

Type: Array of [AttributeKeyAndValue](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchGetObjectInformation

Retrieves metadata about an object inside a [BatchRead](#) operation. For more information, see [GetObjectInformation](#) and [BatchRead:Operations](#).

Contents

ObjectReference

A reference to the object.

Type: [ObjectReference](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchGetObjectInformationResponse

Represents the output of a [GetObjectInformation](#) response operation.

Contents

ObjectIdentifier

The `ObjectIdentifier` of the specified object.

Type: String

Required: No

SchemaFacets

The facets attached to the specified object.

Type: Array of [SchemaFacet](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchListAttachedIndices

Lists indices attached to an object inside a [BatchRead](#) operation. For more information, see [ListAttachedIndices](#) and [BatchRead:Operations](#).

Contents

TargetReference

A reference to the object that has indices attached.

Type: [ObjectReference](#) object

Required: Yes

MaxResults

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The pagination token.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchListAttachedIndicesResponse

Represents the output of a [ListAttachedIndices](#) response operation.

Contents

IndexAttachments

The indices attached to the specified object.

Type: Array of [IndexAttachment](#) objects

Required: No

NextToken

The pagination token.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchListIncomingTypedLinks

Returns a paginated list of all the incoming [TypedLinkSpecifier](#) information for an object inside a [BatchRead](#) operation. For more information, see [ListIncomingTypedLinks](#) and [BatchRead:Operations](#).

Contents

ObjectReference

The reference that identifies the object whose attributes will be listed.

Type: [ObjectReference](#) object

Required: Yes

FilterAttributeRanges

Provides range filters for multiple attributes. When providing ranges to typed link selection, any inexact ranges must be specified at the end. Any attributes that do not have a range specified are presumed to match the entire range.

Type: Array of [TypedLinkAttributeRange](#) objects

Required: No

FilterTypedLink

Filters are interpreted in the order of the attributes on the typed link facet, not the order in which they are supplied to any API calls.

Type: [TypedLinkSchemaAndFacetName](#) object

Required: No

MaxResults

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The pagination token.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchListIncomingTypedLinksResponse

Represents the output of a [ListIncomingTypedLinks](#) response operation.

Contents

LinkSpecifiers

Returns one or more typed link specifiers as output.

Type: Array of [TypedLinkSpecifier](#) objects

Required: No

NextToken

The pagination token.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchListIndex

Lists objects attached to the specified index inside a [BatchRead](#) operation. For more information, see [ListIndex](#) and [BatchRead:Operations](#).

Contents

IndexReference

The reference to the index to list.

Type: [ObjectReference](#) object

Required: Yes

MaxResults

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The pagination token.

Type: String

Required: No

RangesOnIndexedValues

Specifies the ranges of indexed values that you want to query.

Type: Array of [ObjectAttributeRange](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchListIndexResponse

Represents the output of a [ListIndex](#) response operation.

Contents

IndexAttachments

The objects and indexed values attached to the index.

Type: Array of [IndexAttachment](#) objects

Required: No

NextToken

The pagination token.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchListObjectAttributes

Represents the output of a [ListObjectAttributes](#) operation.

Contents

ObjectReference

Reference of the object whose attributes need to be listed.

Type: [ObjectReference](#) object

Required: Yes

FacetFilter

Used to filter the list of object attributes that are associated with a certain facet.

Type: [SchemaFacet](#) object

Required: No

MaxResults

The maximum number of items to be retrieved in a single call. This is an approximate number.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The pagination token.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchListObjectAttributesResponse

Represents the output of a [ListObjectAttributes](#) response operation.

Contents

Attributes

The attributes map that is associated with the object. `AttributeArn` is the key; attribute value is the value.

Type: Array of [AttributeKeyAndValue](#) objects

Required: No

NextToken

The pagination token.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchListObjectChildren

Represents the output of a [ListObjectChildren](#) operation.

Contents

ObjectReference

Reference of the object for which child objects are being listed.

Type: [ObjectReference](#) object

Required: Yes

MaxResults

Maximum number of items to be retrieved in a single call. This is an approximate number.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The pagination token.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchListObjectChildrenResponse

Represents the output of a [ListObjectChildren](#) response operation.

Contents

Children

The children structure, which is a map with the key as the `LinkName` and `ObjectIdentifier` as the value.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Key Pattern: `[^\v[\]\(\):\{\}\#\@!\?\s\\;]+`

Required: No

NextToken

The pagination token.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchListObjectParentPaths

Retrieves all available parent paths for any object type such as node, leaf node, policy node, and index node objects inside a [BatchRead](#) operation. For more information, see [ListObjectParentPaths](#) and [BatchRead:Operations](#).

Contents

ObjectReference

The reference that identifies the object whose attributes will be listed.

Type: [ObjectReference](#) object

Required: Yes

MaxResults

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The pagination token.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchListObjectParentPathsResponse

Represents the output of a [ListObjectParentPaths](#) response operation.

Contents

NextToken

The pagination token.

Type: String

Required: No

PathToObjectIdentifiersList

Returns the path to the `ObjectIdentifiers` that are associated with the directory.

Type: Array of [PathToObjectIdentifiers](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchListObjectParents

Lists parent objects that are associated with a given object in pagination fashion.

Contents

ObjectReference

The reference that identifies an object.

Type: [ObjectReference](#) object

Required: Yes

MaxResults

The maximum number of items to be retrieved in a single call. This is an approximate number.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The pagination token.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchListObjectParentsResponse

Represents the output of a [ListObjectParents](#) response operation.

Contents

NextToken

The pagination token.

Type: String

Required: No

ParentLinks

Returns a list of parent reference and LinkName Tuples.

Type: Array of [ObjectIdentifierAndLinkNameTuple](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchListObjectPolicies

Returns policies attached to an object in pagination fashion inside a [BatchRead](#) operation. For more information, see [ListObjectPolicies](#) and [BatchRead:Operations](#).

Contents

ObjectReference

The reference that identifies the object whose attributes will be listed.

Type: [ObjectReference](#) object

Required: Yes

MaxResults

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The pagination token.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchListObjectPoliciesResponse

Represents the output of a [ListObjectPolicies](#) response operation.

Contents

AttachedPolicyIds

A list of policy `ObjectIdentifiers`, that are attached to the object.

Type: Array of strings

Required: No

NextToken

The pagination token.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchListOutgoingTypedLinks

Returns a paginated list of all the outgoing [TypedLinkSpecifier](#) information for an object inside a [BatchRead](#) operation. For more information, see [ListOutgoingTypedLinks](#) and [BatchRead:Operations](#).

Contents

ObjectReference

The reference that identifies the object whose attributes will be listed.

Type: [ObjectReference](#) object

Required: Yes

FilterAttributeRanges

Provides range filters for multiple attributes. When providing ranges to typed link selection, any inexact ranges must be specified at the end. Any attributes that do not have a range specified are presumed to match the entire range.

Type: Array of [TypedLinkAttributeRange](#) objects

Required: No

FilterTypedLink

Filters are interpreted in the order of the attributes defined on the typed link facet, not the order they are supplied to any API calls.

Type: [TypedLinkSchemaAndFacetName](#) object

Required: No

MaxResults

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The pagination token.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchListOutgoingTypedLinksResponse

Represents the output of a [ListOutgoingTypedLinks](#) response operation.

Contents

NextToken

The pagination token.

Type: String

Required: No

TypedLinkSpecifiers

Returns a typed link specifier as output.

Type: Array of [TypedLinkSpecifier](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchListPolicyAttachments

Returns all of the `ObjectIdentifiers` to which a given policy is attached inside a [BatchRead](#) operation. For more information, see [ListPolicyAttachments](#) and [BatchRead:Operations](#).

Contents

PolicyReference

The reference that identifies the policy object.

Type: [ObjectReference](#) object

Required: Yes

MaxResults

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The pagination token.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchListPolicyAttachmentsResponse

Represents the output of a [ListPolicyAttachments](#) response operation.

Contents

NextToken

The pagination token.

Type: String

Required: No

ObjectIdentifiers

A list of `ObjectIdentifiers` to which the policy is attached.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchLookupPolicy

Lists all policies from the root of the Directory to the object specified inside a [BatchRead](#) operation. For more information, see [LookupPolicy](#) and [BatchRead:Operations](#).

Contents

ObjectReference

Reference that identifies the object whose policies will be looked up.

Type: [ObjectReference](#) object

Required: Yes

MaxResults

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

NextToken

The pagination token.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchLookupPolicyResponse

Represents the output of a [LookupPolicy](#) response operation.

Contents

NextToken

The pagination token.

Type: String

Required: No

PolicyToPathList

Provides list of path to policies. Policies contain `PolicyId`, `ObjectIdentifier`, and `PolicyType`. For more information, see [Policies](#).

Type: Array of [PolicyToPath](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchReadException

The batch read exception structure, which contains the exception type and message.

Contents

Message

An exception message that is associated with the failure.

Type: String

Required: No

Type

A type of exception, such as `InvalidArnException`.

Type: String

Valid Values: `ValidationException` | `InvalidArnException` | `ResourceNotFoundException` | `InvalidNextTokenException` | `AccessDeniedException` | `NotNodeException` | `FacetValidationException` | `CannotListParentOfRootException` | `NotIndexException` | `NotPolicyException` | `DirectoryNotEnabledException` | `LimitExceededException` | `InternalServiceException`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchReadOperation

Represents the output of a BatchRead operation.

Contents

GetLinkAttributes

Retrieves attributes that are associated with a typed link.

Type: [BatchGetLinkAttributes](#) object

Required: No

GetObjectAttributes

Retrieves attributes within a facet that are associated with an object.

Type: [BatchGetObjectAttributes](#) object

Required: No

GetObjectInformation

Retrieves metadata about an object.

Type: [BatchGetObjectInformation](#) object

Required: No

ListAttachedIndices

Lists indices attached to an object.

Type: [BatchListAttachedIndices](#) object

Required: No

ListIncomingTypedLinks

Returns a paginated list of all the incoming [TypedLinkSpecifier](#) information for an object. It also supports filtering by typed link facet and identity attributes. For more information, see [Typed Links](#).

Type: [BatchListIncomingTypedLinks](#) object

Required: No

ListIndex

Lists objects attached to the specified index.

Type: [BatchListIndex](#) object

Required: No

ListObjectAttributes

Lists all attributes that are associated with an object.

Type: [BatchListObjectAttributes](#) object

Required: No

ListObjectChildren

Returns a paginated list of child objects that are associated with a given object.

Type: [BatchListObjectChildren](#) object

Required: No

ListObjectParentPaths

Retrieves all available parent paths for any object type such as node, leaf node, policy node, and index node objects. For more information about objects, see [Directory Structure](#).

Type: [BatchListObjectParentPaths](#) object

Required: No

ListObjectParents

Lists parent objects that are associated with a given object in pagination fashion.

Type: [BatchListObjectParents](#) object

Required: No

ListObjectPolicies

Returns policies attached to an object in pagination fashion.

Type: [BatchListObjectPolicies](#) object

Required: No

ListOutgoingTypedLinks

Returns a paginated list of all the outgoing [TypedLinkSpecifier](#) information for an object. It also supports filtering by typed link facet and identity attributes. For more information, see [Typed Links](#).

Type: [BatchListOutgoingTypedLinks](#) object

Required: No

ListPolicyAttachments

Returns all of the `ObjectIdentifiers` to which a given policy is attached.

Type: [BatchListPolicyAttachments](#) object

Required: No

LookupPolicy

Lists all policies from the root of the [Directory](#) to the object specified. If there are no policies present, an empty list is returned. If policies are present, and if some objects don't have the policies attached, it returns the `ObjectIdentifier` for such objects. If policies are present, it returns `ObjectIdentifier`, `policyId`, and `policyType`. Paths that don't lead to the root from the target object are ignored. For more information, see [Policies](#).

Type: [BatchLookupPolicy](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchReadOperationResponse

Represents the output of a BatchRead response operation.

Contents

ExceptionResponse

Identifies which operation in a batch has failed.

Type: [BatchReadException](#) object

Required: No

SuccessfulResponse

Identifies which operation in a batch has succeeded.

Type: [BatchReadSuccessfulResponse](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchReadSuccessfulResponse

Represents the output of a `BatchRead` success response operation.

Contents

GetLinkAttributes

The list of attributes to retrieve from the typed link.

Type: [BatchGetLinkAttributesResponse](#) object

Required: No

GetObjectAttributes

Retrieves attributes within a facet that are associated with an object.

Type: [BatchGetObjectAttributesResponse](#) object

Required: No

GetObjectInformation

Retrieves metadata about an object.

Type: [BatchGetObjectInformationResponse](#) object

Required: No

ListAttachedIndices

Lists indices attached to an object.

Type: [BatchListAttachedIndicesResponse](#) object

Required: No

ListIncomingTypedLinks

Returns a paginated list of all the incoming [TypedLinkSpecifier](#) information for an object. It also supports filtering by typed link facet and identity attributes. For more information, see [Typed Links](#).

Type: [BatchListIncomingTypedLinksResponse](#) object

Required: No

ListIndex

Lists objects attached to the specified index.

Type: [BatchListIndexResponse](#) object

Required: No

ListObjectAttributes

Lists all attributes that are associated with an object.

Type: [BatchListObjectAttributesResponse](#) object

Required: No

ListObjectChildren

Returns a paginated list of child objects that are associated with a given object.

Type: [BatchListObjectChildrenResponse](#) object

Required: No

ListObjectParentPaths

Retrieves all available parent paths for any object type such as node, leaf node, policy node, and index node objects. For more information about objects, see [Directory Structure](#).

Type: [BatchListObjectParentPathsResponse](#) object

Required: No

ListObjectParents

The list of parent objects to retrieve.

Type: [BatchListObjectParentsResponse](#) object

Required: No

ListObjectPolicies

Returns policies attached to an object in pagination fashion.

Type: [BatchListObjectPoliciesResponse](#) object

Required: No

ListOutgoingTypedLinks

Returns a paginated list of all the outgoing [TypedLinkSpecifier](#) information for an object. It also supports filtering by typed link facet and identity attributes. For more information, see [Typed Links](#).

Type: [BatchListOutgoingTypedLinksResponse](#) object

Required: No

ListPolicyAttachments

Returns all of the `ObjectIdentifiers` to which a given policy is attached.

Type: [BatchListPolicyAttachmentsResponse](#) object

Required: No

LookupPolicy

Lists all policies from the root of the [Directory](#) to the object specified. If there are no policies present, an empty list is returned. If policies are present, and if some objects don't have the policies attached, it returns the `ObjectIdentifier` for such objects. If policies are present, it returns `ObjectIdentifier`, `policyId`, and `policyType`. Paths that don't lead to the root from the target object are ignored. For more information, see [Policies](#).

Type: [BatchLookupPolicyResponse](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchRemoveFacetFromObject

A batch operation to remove a facet from an object.

Contents

ObjectReference

A reference to the object whose facet will be removed.

Type: [ObjectReference](#) object

Required: Yes

SchemaFacet

The facet to remove from the object.

Type: [SchemaFacet](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchRemoveFacetFromObjectResponse

An empty result that represents success.

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchUpdateLinkAttributes

Updates a given typed link's attributes inside a [BatchRead](#) operation. Attributes to be updated must not contribute to the typed link's identity, as defined by its IdentityAttributeOrder. For more information, see [UpdateLinkAttributes](#) and [BatchRead:Operations](#).

Contents

AttributeUpdates

The attributes update structure.

Type: Array of [LinkAttributeUpdate](#) objects

Required: Yes

TypedLinkSpecifier

Allows a typed link specifier to be accepted as input.

Type: [TypedLinkSpecifier](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchUpdateLinkAttributesResponse

Represents the output of a [UpdateLinkAttributes](#) response operation.

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchUpdateObjectAttributes

Represents the output of a BatchUpdate operation.

Contents

AttributeUpdates

Attributes update structure.

Type: Array of [ObjectAttributeUpdate](#) objects

Required: Yes

ObjectReference

Reference that identifies the object.

Type: [ObjectReference](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchUpdateObjectAttributesResponse

Represents the output of a BatchUpdate response operation.

Contents

ObjectIdentifier

ID that is associated with the object.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchWriteOperation

Represents the output of a BatchWrite operation.

Contents

AddFacetToObject

A batch operation that adds a facet to an object.

Type: [BatchAddFacetToObject](#) object

Required: No

AttachObject

Attaches an object to a [Directory](#).

Type: [BatchAttachObject](#) object

Required: No

AttachPolicy

Attaches a policy object to a regular object. An object can have a limited number of attached policies.

Type: [BatchAttachPolicy](#) object

Required: No

AttachToIndex

Attaches the specified object to the specified index.

Type: [BatchAttachToIndex](#) object

Required: No

AttachTypedLink

Attaches a typed link to a specified source and target object. For more information, see [Typed Links](#).

Type: [BatchAttachTypedLink](#) object

Required: No

CreateIndex

Creates an index object. See [Indexing and search](#) for more information.

Type: [BatchCreateIndex](#) object

Required: No

CreateObject

Creates an object.

Type: [BatchCreateObject](#) object

Required: No

DeleteObject

Deletes an object in a [Directory](#).

Type: [BatchDeleteObject](#) object

Required: No

DetachFromIndex

Detaches the specified object from the specified index.

Type: [BatchDetachFromIndex](#) object

Required: No

DetachObject

Detaches an object from a [Directory](#).

Type: [BatchDetachObject](#) object

Required: No

DetachPolicy

Detaches a policy from a [Directory](#).

Type: [BatchDetachPolicy](#) object

Required: No

DetachTypedLink

Detaches a typed link from a specified source and target object. For more information, see [Typed Links](#).

Type: [BatchDetachTypedLink](#) object

Required: No

RemoveFacetFromObject

A batch operation that removes a facet from an object.

Type: [BatchRemoveFacetFromObject](#) object

Required: No

UpdateLinkAttributes

Updates a given object's attributes.

Type: [BatchUpdateLinkAttributes](#) object

Required: No

UpdateObjectAttributes

Updates a given object's attributes.

Type: [BatchUpdateObjectAttributes](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchWriteOperationResponse

Represents the output of a BatchWrite response operation.

Contents

AddFacetToObject

The result of an add facet to object batch operation.

Type: [BatchAddFacetToObjectResponse](#) object

Required: No

AttachObject

Attaches an object to a [Directory](#).

Type: [BatchAttachObjectResponse](#) object

Required: No

AttachPolicy

Attaches a policy object to a regular object. An object can have a limited number of attached policies.

Type: [BatchAttachPolicyResponse](#) object

Required: No

AttachToIndex

Attaches the specified object to the specified index.

Type: [BatchAttachToIndexResponse](#) object

Required: No

AttachTypedLink

Attaches a typed link to a specified source and target object. For more information, see [Typed Links](#).

Type: [BatchAttachTypedLinkResponse](#) object

Required: No

CreateIndex

Creates an index object. See [Indexing and search](#) for more information.

Type: [BatchCreateIndexResponse](#) object

Required: No

CreateObject

Creates an object in a [Directory](#).

Type: [BatchCreateObjectResponse](#) object

Required: No

DeleteObject

Deletes an object in a [Directory](#).

Type: [BatchDeleteObjectResponse](#) object

Required: No

DetachFromIndex

Detaches the specified object from the specified index.

Type: [BatchDetachFromIndexResponse](#) object

Required: No

DetachObject

Detaches an object from a [Directory](#).

Type: [BatchDetachObjectResponse](#) object

Required: No

DetachPolicy

Detaches a policy from a [Directory](#).

Type: [BatchDetachPolicyResponse](#) object

Required: No

DetachTypedLink

Detaches a typed link from a specified source and target object. For more information, see [Typed Links](#).

Type: [BatchDetachTypedLinkResponse](#) object

Required: No

RemoveFacetFromObject

The result of a batch remove facet from object operation.

Type: [BatchRemoveFacetFromObjectResponse](#) object

Required: No

UpdateLinkAttributes

Represents the output of a BatchWrite response operation.

Type: [BatchUpdateLinkAttributesResponse](#) object

Required: No

UpdateObjectAttributes

Updates a given object's attributes.

Type: [BatchUpdateObjectAttributesResponse](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Directory

Directory structure that includes the directory name and directory ARN.

Contents

CreationDateTime

The date and time when the directory was created.

Type: Timestamp

Required: No

DirectoryArn

The Amazon Resource Name (ARN) that is associated with the directory. For more information, see [Arn Examples](#).

Type: String

Required: No

Name

The name of the directory.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: No

State

The state of the directory. Can be either Enabled, Disabled, or Deleted.

Type: String

Valid Values: ENABLED | DISABLED | DELETED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Facet

A structure that contains Name, ARN, Attributes, [Rules](#), and ObjectTypes. See [Facets](#) for more information.

Contents

FacetStyle

There are two different styles that you can define on any given facet, `Static` and `Dynamic`. For static facets, all attributes must be defined in the schema. For dynamic facets, attributes can be defined during data plane operations.

Type: String

Valid Values: `STATIC` | `DYNAMIC`

Required: No

Name

The name of the [Facet](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: No

ObjectType

The object type that is associated with the facet. See [CreateFacet:ObjectType](#) for more details.

Type: String

Valid Values: `NODE` | `LEAF_NODE` | `POLICY` | `INDEX`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FacetAttribute

An attribute that is associated with the [Facet](#).

Contents

Name

The name of the facet attribute.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 230.

Pattern: `^[a-zA-Z0-9._: -]*$`

Required: Yes

AttributeDefinition

A facet attribute consists of either a definition or a reference. This structure contains the attribute definition. See [Attribute References](#) for more information.

Type: [FacetAttributeDefinition](#) object

Required: No

AttributeReference

An attribute reference that is associated with the attribute. See [Attribute References](#) for more information.

Type: [FacetAttributeReference](#) object

Required: No

RequiredBehavior

The required behavior of the FacetAttribute.

Type: String

Valid Values: REQUIRED_ALWAYS | NOT_REQUIRED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FacetAttributeDefinition

A facet attribute definition. See [Attribute References](#) for more information.

Contents

Type

The type of the attribute.

Type: String

Valid Values: STRING | BINARY | BOOLEAN | NUMBER | DATETIME | VARIANT

Required: Yes

DefaultValue

The default value of the attribute (if configured).

Type: [TypedAttributeValue](#) object

Required: No

Immutable

Whether the attribute is mutable or not.

Type: Boolean

Required: No

Rules

Validation rules attached to the attribute definition.

Type: String to [Rule](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Key Pattern: `^[a-zA-Z0-9._-]*$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FacetAttributeReference

The facet attribute reference that specifies the attribute definition that contains the attribute facet name and attribute name.

Contents

TargetAttributeName

The target attribute name that is associated with the facet reference. See [Attribute References](#) for more information.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 230.

Pattern: `^[a-zA-Z0-9._:-]*$`

Required: Yes

TargetFacetName

The target facet name that is associated with the facet reference. See [Attribute References](#) for more information.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FacetAttributeUpdate

A structure that contains information used to update an attribute.

Contents

Action

The action to perform when updating the attribute.

Type: String

Valid Values: CREATE_OR_UPDATE | DELETE

Required: No

Attribute

The attribute to update.

Type: [FacetAttribute](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IndexAttachment

Represents an index and an attached object.

Contents

IndexedAttributes

The indexed attribute values.

Type: Array of [AttributeKeyAndValue](#) objects

Required: No

ObjectIdentifier

In response to [ListIndex](#), the `ObjectIdentifier` of the object attached to the index. In response to [ListAttachedIndices](#), the `ObjectIdentifier` of the index attached to the object. This field will always contain the `ObjectIdentifier` of the object on the opposite side of the attachment specified in the query.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LinkAttributeAction

The action to take on a typed link attribute value. Updates are only supported for attributes which don't contribute to link identity.

Contents

AttributeActionType

A type that can be either UPDATE_OR_CREATE or DELETE.

Type: String

Valid Values: CREATE_OR_UPDATE | DELETE

Required: No

AttributeUpdateValue

The value that you want to update to.

Type: [TypedAttributeValue](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LinkAttributeUpdate

Structure that contains attribute update information.

Contents

AttributeAction

The action to perform as part of the attribute update.

Type: [LinkAttributeAction](#) object

Required: No

AttributeKey

The key of the attribute being updated.

Type: [AttributeKey](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ObjectAttributeAction

The action to take on the object attribute.

Contents

ObjectAttributeActionType

A type that can be either Update or Delete.

Type: String

Valid Values: CREATE_OR_UPDATE | DELETE

Required: No

ObjectAttributeUpdateValue

The value that you want to update to.

Type: [TypedAttributeValue](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ObjectAttributeRange

A range of attributes.

Contents

AttributeKey

The key of the attribute that the attribute range covers.

Type: [AttributeKey](#) object

Required: No

Range

The range of attribute values being selected.

Type: [TypedAttributeValueRange](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ObjectAttributeUpdate

Structure that contains attribute update information.

Contents

ObjectAttributeAction

The action to perform as part of the attribute update.

Type: [ObjectAttributeAction](#) object

Required: No

ObjectAttributeKey

The key of the attribute being updated.

Type: [AttributeKey](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ObjectIdentifierAndLinkNameTuple

A pair of ObjectIdentifier and LinkName.

Contents

LinkName

The name of the link between the parent and the child object.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[^\v[\]\(\):\{\}\#\@!\?\s\\;]+`

Required: No

ObjectIdentifier

The ID that is associated with the object.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ObjectReference

The reference that identifies an object.

Contents

Selector

A path selector supports easy selection of an object by the parent/child links leading to it from the directory root. Use the link names from each parent/child link to construct the path. Path selectors start with a slash (/) and link names are separated by slashes. For more information about paths, see [Access Objects](#). You can identify an object in one of the following ways:

- *\$ObjectIdentifier* - An object identifier is an opaque string provided by Amazon Cloud Directory. When creating objects, the system will provide you with the identifier of the created object. An object's identifier is immutable and no two objects will ever share the same object identifier. To identify an object with ObjectIdentifier, the ObjectIdentifier must be wrapped in double quotes.
- */some/path* - Identifies the object based on path
- *#SomeBatchReference* - Identifies the object in a batch call

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PathToObjectIdentifiers

Returns the path to the `ObjectIdentifiers` that is associated with the directory.

Contents

ObjectIdentifiers

Lists `ObjectIdentifiers` starting from directory root to the object in the request.

Type: Array of strings

Required: No

Path

The path that is used to identify the object starting from directory root.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PolicyAttachment

Contains the `PolicyType`, `PolicyId`, and the `ObjectIdentifier` to which it is attached. For more information, see [Policies](#).

Contents

ObjectIdentifier

The `ObjectIdentifier` that is associated with `PolicyAttachment`.

Type: String

Required: No

PolicyId

The ID of `PolicyAttachment`.

Type: String

Required: No

PolicyType

The type of policy that can be associated with `PolicyAttachment`.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PolicyToPath

Used when a regular object exists in a [Directory](#) and you want to find all of the policies that are associated with that object and the parent to that object.

Contents

Path

The path that is referenced from the root.

Type: String

Required: No

Policies

List of policy objects.

Type: Array of [PolicyAttachment](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Rule

Contains an Amazon Resource Name (ARN) and parameters that are associated with the rule.

Contents

Parameters

The minimum and maximum parameters that are associated with the rule.

Type: String to string map

Required: No

Type

The type of attribute validation rule.

Type: String

Valid Values: BINARY_LENGTH | NUMBER_COMPARISON | STRING_FROM_SET |
STRING_LENGTH

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SchemaFacet

A facet.

Contents

FacetName

The name of the facet. If this value is set, SchemaArn must also be set.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: No

SchemaArn

The ARN of the schema that contains the facet with no minor component. See [Arn Examples](#) and [In-Place Schema Upgrade](#) for a description of when to provide minor versions. If this value is set, FacetName must also be set.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

The tag structure that contains a tag key and value.

Contents

Key

The key that is associated with the tag.

Type: String

Required: Yes

Value

The value that is associated with the tag.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TypedAttributeValue

Represents the data for a typed attribute. You can set one, and only one, of the elements. Each attribute in an item is a name-value pair. Attributes have a single value.

Contents

BinaryValue

A binary data value.

Type: Base64-encoded binary data object

Required: No

BooleanValue

A Boolean data value.

Type: Boolean

Required: No

DatetimeValue

A date and time value.

Type: Timestamp

Required: No

NumberValue

A number data value.

Type: String

Required: No

StringValue

A string data value.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TypedAttributeValueRange

A range of attribute values. For more information, see [Range Filters](#).

Contents

EndMode

The inclusive or exclusive range end.

Type: String

Valid Values: FIRST | LAST | LAST_BEFORE_MISSING_VALUES | INCLUSIVE | EXCLUSIVE

Required: Yes

StartMode

The inclusive or exclusive range start.

Type: String

Valid Values: FIRST | LAST | LAST_BEFORE_MISSING_VALUES | INCLUSIVE | EXCLUSIVE

Required: Yes

EndValue

The attribute value to terminate the range at.

Type: [TypedAttributeValue](#) object

Required: No

StartValue

The value to start the range at.

Type: [TypedAttributeValue](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TypedLinkAttributeDefinition

A typed link attribute definition.

Contents

Name

The unique name of the typed link attribute.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 230.

Pattern: `^[a-zA-Z0-9._: -]*$`

Required: Yes

RequiredBehavior

The required behavior of the `TypedLinkAttributeDefinition`.

Type: String

Valid Values: `REQUIRED_ALWAYS` | `NOT_REQUIRED`

Required: Yes

Type

The type of the attribute.

Type: String

Valid Values: `STRING` | `BINARY` | `BOOLEAN` | `NUMBER` | `DATETIME` | `VARIANT`

Required: Yes

DefaultValue

The default value of the attribute (if configured).

Type: [TypedAttributeValue](#) object

Required: No

IsImmutable

Whether the attribute is mutable or not.

Type: Boolean

Required: No

Rules

Validation rules that are attached to the attribute definition.

Type: String to [Rule](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Key Pattern: `^[a-zA-Z0-9._-]*$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TypedLinkAttributeRange

Identifies the range of attributes that are used by a specified filter.

Contents

Range

The range of attribute values that are being selected.

Type: [TypedAttributeValueRange](#) object

Required: Yes

AttributeName

The unique name of the typed link attribute.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 230.

Pattern: `^[a-zA-Z0-9._: -]*$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TypedLinkFacet

Defines the typed links structure and its attributes. To create a typed link facet, use the [CreateTypedLinkFacet](#) API.

Contents

Attributes

A set of key-value pairs associated with the typed link. Typed link attributes are used when you have data values that are related to the link itself, and not to one of the two objects being linked. Identity attributes also serve to distinguish the link from others of the same type between the same objects.

Type: Array of [TypedLinkAttributeDefinition](#) objects

Required: Yes

IdentityAttributeOrder

The set of attributes that distinguish links made from this facet from each other, in the order of significance. Listing typed links can filter on the values of these attributes. See [ListOutgoingTypedLinks](#) and [ListIncomingTypedLinks](#) for details.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 230.

Pattern: `^[a-zA-Z0-9._: -]*$`

Required: Yes

Name

The unique name of the typed link facet.

Type: String

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TypedLinkFacetAttributeUpdate

A typed link facet attribute update.

Contents

Action

The action to perform when updating the attribute.

Type: String

Valid Values: CREATE_OR_UPDATE | DELETE

Required: Yes

Attribute

The attribute to update.

Type: [TypedLinkAttributeDefinition](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TypedLinkSchemaAndFacetName

Identifies the schema Amazon Resource Name (ARN) and facet name for the typed link.

Contents

SchemaArn

The Amazon Resource Name (ARN) that is associated with the schema. For more information, see [Arn Examples](#).

Type: String

Required: Yes

TypedLinkName

The unique name of the typed link facet.

Type: String

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TypedLinkSpecifier

Contains all the information that is used to uniquely identify a typed link. The parameters discussed in this topic are used to uniquely specify the typed link being operated on. The [AttachTypedLink](#) API returns a typed link specifier while the [DetachTypedLink](#) API accepts one as input. Similarly, the [ListIncomingTypedLinks](#) and [ListOutgoingTypedLinks](#) API operations provide typed link specifiers as output. You can also construct a typed link specifier from scratch.

Contents

IdentityAttributeValues

Identifies the attribute value to update.

Type: Array of [AttributeNameAndValue](#) objects

Required: Yes

SourceObjectReference

Identifies the source object that the typed link will attach to.

Type: [ObjectReference](#) object

Required: Yes

TargetObjectReference

Identifies the target object that the typed link will attach to.

Type: [ObjectReference](#) object

Required: Yes

TypedLinkFacet

Identifies the typed link facet that is associated with the typed link.

Type: [TypedLinkSchemaAndFacetName](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Arn Examples

The following examples are separated by ARN types and show how they can be constructed for each schema state (where applicable). A schema can exist in three states:

- *Development*: This is a mutable state of the schema. All new schemas are in the development state. Once the schema is finalized, it can be published. All development schemas are under the development sub root of the schema metadata container.
- *Published*: Published schemas are immutable and have a version associated with them. All published schemas are under the published sub root of the schema container.
- *Applied*: Applied schemas are mutable in a way that allows you to add new schema facets. However, existing schema facets cannot be changed. You can apply only published schemas to directories. You can't apply schemas at the node level, but only at the directory root level.

Schema Arns

State	Format or Example	Schema Arn
Development	Format	arn:aws:clouddirectory:us-west-2: <i>accountId</i> :schema/development/ <i>SchemaName</i>
	Example	arn:aws:clouddirectory:us-west-2:12345678910:schema/development/cognito
Published	Format	arn:aws:clouddirectory:us-west-2: <i>accountId</i> :schema/published/ <i>SchemaName</i> / <i>SchemaVersion</i>
	Example	arn:aws:clouddirectory:us-west-2:12345678910:schema/published/cognito/1.0
	Format	arn:aws:clouddirectory:us-west-2: <i>accountId</i> :schema/pu

State	Format or Example	Schema Arn
		blished/ <i>SchemaName</i> / <i>SchemaVersion</i> / <i>SchemaMinorVersion</i>
	Example	arn:aws:clouddirectory:us-west-2:12345678910:schema/published/cognito/1.0/XYZ
Applied	Format	arn:aws:clouddirectory:us-west-2: <i>accountId</i> :directory/ <i>directoryId</i> / <i>SchemaName</i> / <i>SchemaVersion</i>
	Example	arn:aws:clouddirectory:us-west-2:12345678910:directory/ARIqk1HD-UjdtmcIrJHEvPI/schema/cognito/1.0
	Format	arn:aws:clouddirectory:us-west-2: <i>accountId</i> :directory/ <i>directoryId</i> / <i>SchemaName</i> / <i>SchemaVersion</i> / <i>SchemaMinorVersion</i>
	Example	arn:aws:clouddirectory:us-west-2:12345678910:directory/ARIqk1HD-UjdtmcIrJHEvPI/schema/cognito/1.0/XYZ

Directory Arns

Arn Type	Format or example	Arn
Directory Arn	Format	arn:aws:clouddirectory:us-west-2: <i>Directory owner accountId</i> :directory/ <i>directoryId</i>

Arn Type	Format or example	Arn
	Example	arn:aws:clouddirectory:us-west-2:12345678910:directory/ARIqk1HD-UjdtmcIrJHEvPI

Logging Cloud Directory API Calls with CloudTrail

Amazon Cloud Directory is integrated with AWS CloudTrail, a service that captures all of the Cloud Directory API calls and delivers the log files to an Amazon S3 bucket that you specify. CloudTrail captures API calls from the Cloud Directory section of the Directory Service console or from your code to the Cloud Directory APIs. Using the information collected by CloudTrail, you can determine the request that was made to Cloud Directory, the source IP address from which the request was made, who made the request, when it was made, and so on. To learn more about CloudTrail, see the [AWS CloudTrail User Guide](#).

Cloud Directory Information in CloudTrail

CloudTrail is enabled on your AWS account when you create the account. When supported event activity occurs in Cloud Directory, that activity is recorded in a CloudTrail event along with other AWS service events in **Event history**. You can view, search, and download recent events in your AWS account. For more information, see [Viewing Events with CloudTrail Event History](#).

For an ongoing record of events in your AWS account, including events for Cloud Directory, create a trail. A *trail* enables CloudTrail to deliver log files to an Amazon S3 bucket. By default, when you create a trail in the console, the trail applies to all AWS Regions. The trail logs events from all Regions in the AWS partition and delivers the log files to the Amazon S3 bucket that you specify. Additionally, you can configure other AWS services to further analyze and act upon the event data collected in CloudTrail logs. For more information, see the following:

- [Overview for Creating a Trail](#)
- [CloudTrail Supported Services and Integrations](#)
- [Configuring Amazon SNS Notifications for CloudTrail](#)
- [Receiving CloudTrail Log Files from Multiple Regions](#) and [Receiving CloudTrail Log Files from Multiple Accounts](#)

When CloudTrail logging is enabled in your AWS account, API calls made to Cloud Directory actions are tracked in CloudTrail log files, where they are written with other AWS service records. CloudTrail determines when to create and write to a new file based on a time period and file size.

The following Cloud Directory actions are logged by CloudTrail and are documented in this API Reference guide.

- [ApplySchema](#)
- [CreateDirectory](#)
- [CreateFacet](#)
- [CreateSchema](#)
- [DeleteDirectory](#)
- [DeleteFacet](#)
- [DeleteSchema](#)
- [DisableDirectory](#)
- [EnableDirectory](#)
- [GetDirectory](#)
- [GetFacet](#)
- [GetSchemaAsJson](#)
- [ListAppliedSchemaArns](#)
- [ListDevelopmentSchemaArns](#)
- [ListDirectories](#)
- [ListFacetAttributes](#)
- [ListFacetNames](#)
- [ListManagedSchemaArns](#)
- [ListPublishedSchemaArns](#)
- [ListTagsForResource](#)
- [PublishSchema](#)
- [PutSchemaFromJson](#)
- [TagResource](#)
- [UpdateFacet](#)
- [UpdateSchema](#)
- [UntagResource](#)

For example, calls to the **ApplySchema**, **ListDirectories** and **CreateSchema** sections generate entries in the CloudTrail log files.

Every log entry contains information about who generated the request. The user identity information in the log entry helps you determine the following:

- Whether the request was made with root or IAM user credentials
- Whether the request was made with temporary security credentials for a role or federated user
- Whether the request was made by another AWS service

For more information, see the [CloudTrail userIdentity Element](#).

You can store your log files in your Amazon S3 bucket for as long as you want, but you can also define Amazon S3 lifecycle rules to archive or delete log files automatically. By default, your log files are encrypted with Amazon S3 server-side encryption (SSE).

If you want to be notified upon log file delivery, you can configure CloudTrail to publish Amazon SNS notifications when new log files are delivered. For more information, see [Configuring Amazon SNS Notifications for CloudTrail](#).

You can also aggregate Cloud Directory log files from multiple AWS regions and multiple AWS accounts into a single Amazon S3 bucket. For more information, see [Receiving CloudTrail Log Files from Multiple Regions](#) and [Receiving CloudTrail Log Files from Multiple Accounts](#).

Understanding Cloud Directory Log File Entries

CloudTrail log files can contain one or more log entries. Each entry lists multiple JSON-formatted events. A log entry represents a single request from any source and includes information about the requested action, the date and time of the action, request parameters, and so on. Log entries are not an ordered stack trace of the public API calls, so they do not appear in any specific order.

Sensitive information, such as passwords, authentication tokens, file comments, and file contents are redacted in the log entries.

The following example shows a CloudTrail log entry that demonstrates the following Cloud Directory actions:

- ApplySchema
- ListDirectories
- CreateSchema

```
ApplySchema:
{
  "eventVersion": "1.05",
```

```

"userIdentity": {
  "type": "IAMUser",
  "principalId": "ASDFLKJHEXAMPLE1QWERT",
  "arn": "arn:aws:iam::11223Example:user/nickpi",
  "accountId": "11223Example",
  "accessKeyId": "ALSKDJFHGQPW0Example",
  "userName": "nickpi"
},
"eventTime": "2017-01-06T00:09:08Z",
"eventSource": "clouddirectory.amazonaws.com",
"eventName": "ApplySchema",
"awsRegion": "us-east-1",
"sourceIPAddress": "192.0.2.92",
"userAgent": "Apache-HttpClient/4.3 (java 1.5)",
"requestParameters": {
  "directoryArn": "arn:aws:clouddirectory:us-east-1:11223Example:directory/
AsCGClGIkIqweR836u9pyU",
  "publishedSchemaArn": "arn:aws:clouddirectory:us-east-1:11223Example:schema/
published/simple_org-123456/1.0"
},
"responseElements": {
  "directoryArn": "arn:aws:clouddirectory:us-east-1:11223Example:directory/
AsCGClGIkIqweR836u9pyU",
  "appliedSchemaArn": "arn:aws:clouddirectory:us-east-1:11223Example:directory/
AsCGClGIkIqweR836u9pyU/schema/simple_org-123456/1.0"
},
"requestID": "12j45lk0-a1s2-00ie-b180-2b70510bd66f",
"eventID": "733409ba-a869-4e7b-95a1-4d5d204e697c",
"eventType": "AwsApiCall",
"recipientAccountId": "11223Example"
}

```

ListDirectories:

```

{
  "eventVersion": "1.05",
  "userIdentity": {
    "type": "IAMUser",
    "principalId": "ASDFLKJHEXAMPLE1QWERT",
    "arn": "arn:aws:iam::11223Example:user/nickpi",
    "accountId": "11223Example",
    "accessKeyId": "ALSKDJFHGQPW0Example",
    "userName": "nickpi"
  },
  "eventTime": "2017-01-06T00:09:54Z",

```

```
"eventSource": "clouddirectory.amazonaws.com",
"eventName": "ListDirectories",
"awsRegion": "us-east-1",
"sourceIPAddress": "192.0.2.92",
"userAgent": "Apache-HttpClient/4.3 (java 1.5)",
"requestParameters": {
  "maxResults": 10
},
"responseElements": null,
"requestID": "56j45100-a1s2-00ie-b180-2b70660bd66f",
"eventID": "uwjdf8-f003-4ef7-b15d-8a34149479ac",
"eventType": "AwsApiCall",
"recipientAccountId": "11223Example"
}

CreateSchema:
{
  "eventVersion": "1.05",
  "userIdentity": {
    "type": "IAMUser",
    "principalId": "ASDFLKJHEXAMPLE1QWERT",
    "arn": "arn:aws:iam::11223Example:user/nickpi",
    "accountId": "11223Example",
    "accessKeyId": "ALSKDJFHGQPW0Example",
    "userName": "nickpi"
  },
  "eventTime": "2017-01-06T00:08:54Z",
  "eventSource": "clouddirectory.amazonaws.com",
  "eventName": "CreateSchema",
  "awsRegion": "us-east-1",
  "sourceIPAddress": "192.0.2.92",
  "userAgent": "Apache-HttpClient/4.3 (java 1.5)",
  "requestParameters": {
    "name": "newName-111"
  },
  "responseElements": {
    "schemaArn": "arn:aws:clouddirectory:us-east-1:11223Example:schema/development/newName-111"
  },
  "requestID": "4jshkjsg-d3a4-11e6-b180-dfhkasdh",
  "eventID": "skdjf-0acb-426c-b64b-fsaj",
  "eventType": "AwsApiCall",
  "recipientAccountId": "11223Example"
}
```

```
}
```

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Error Types

This section lists common error types that this AWS service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

IncompleteSignature

The request signature doesn't conform to AWS standards. Verify that you're using valid AWS credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 403

InternalFailure

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact AWS Support.

HTTP Status Code: 500

MalformedHttpRequestException

The request body can't be processed. This typically happens when the request body can't be decompressed using the specified content encoding algorithm. Verify that the content encoding header matches the compression format used.

HTTP Status Code: 400

NotAuthorized

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

OptInRequired

Your AWS account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

RequestAbortedException

The request was aborted before a response could be returned. This typically happens when the client closes the connection.

HTTP Status Code: 400

RequestEntityTooLargeException

The request entity is too large. Reduce the size of the request body and try again.

HTTP Status Code: 413

RequestTimeoutException

The request timed out. The server didn't receive the complete request within the expected time frame. Try again.

HTTP Status Code: 408

ServiceUnavailable

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

ThrottlingException

Your request rate is too high. The AWS SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

UnknownOperationException

The action or operation isn't recognized. Verify that the action name is spelled correctly and that it's supported by the API version you're using.

HTTP Status Code: 404

UnrecognizedClientException

The X.509 certificate or AWS access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

ValidationError

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400

Document History

The following table describes the important changes to the documentation in this release of the Amazon Cloud Directory API Reference.

- **Latest documentation update:** May 23, 2018

Change	Description	Release Date
Typed links	Added the GetLinkAttributes and UpdateLinkAttributes APIs for Typed Links .	May 23, 2018
New API	Added the GetObjectAttributes API.	April 10, 2018
In-Place Schema Upgrade	Added new APIs to support In-Place Schema Upgrade feature.	December 6, 2017
Batch updates	Added several new Read and Write batch operation APIs	July 25, 2017
Typed links	Additional APIs for new Typed Links feature	May 31, 2017
New guide	This is the first release of the Amazon Cloud Directory API Reference Guide.	January 26, 2017