



API Reference

Amazon CodeGuru Security



API Version 2018-05-10

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon CodeGuru Security: API Reference

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
BatchGetFindings	3
Request Syntax	3
URI Request Parameters	3
Request Body	3
Response Syntax	3
Response Elements	5
Errors	5
See Also	6
CreateScan	7
Request Syntax	7
URI Request Parameters	7
Request Body	7
Response Syntax	9
Response Elements	9
Errors	10
See Also	11
CreateUploadUrl	13
Request Syntax	13
URI Request Parameters	13
Request Body	13
Response Syntax	13
Response Elements	14
Errors	15
See Also	15
GetAccountConfiguration	17
Request Syntax	17
URI Request Parameters	17
Request Body	17
Response Syntax	17
Response Elements	17
Errors	18
See Also	18

GetFindings	20
Request Syntax	20
URI Request Parameters	20
Request Body	21
Response Syntax	21
Response Elements	22
Errors	23
See Also	24
GetMetricsSummary	25
Request Syntax	25
URI Request Parameters	25
Request Body	25
Response Syntax	25
Response Elements	26
Errors	26
See Also	27
GetScan	28
Request Syntax	28
URI Request Parameters	28
Request Body	28
Response Syntax	28
Response Elements	29
Errors	30
See Also	31
ListFindingsMetrics	33
Request Syntax	33
URI Request Parameters	33
Request Body	34
Response Syntax	34
Response Elements	35
Errors	35
See Also	36
ListScans	37
Request Syntax	37
URI Request Parameters	37
Request Body	37

Response Syntax	37
Response Elements	38
Errors	38
See Also	39
ListTagsForResource	40
Request Syntax	40
URI Request Parameters	40
Request Body	40
Response Syntax	40
Response Elements	40
Errors	41
See Also	42
TagResource	43
Request Syntax	43
URI Request Parameters	43
Request Body	43
Response Syntax	44
Response Elements	44
Errors	44
See Also	45
UntagResource	46
Request Syntax	46
URI Request Parameters	46
Request Body	46
Response Syntax	46
Response Elements	47
Errors	47
See Also	48
UpdateAccountConfiguration	49
Request Syntax	49
URI Request Parameters	49
Request Body	49
Response Syntax	49
Response Elements	50
Errors	50
See Also	51

Data Types	52
AccountFindingsMetric	53
Contents	53
See Also	54
BatchGetFindingsError	55
Contents	55
See Also	56
CategoryWithFindingNum	57
Contents	57
See Also	57
CodeLine	58
Contents	58
See Also	58
EncryptionConfig	59
Contents	59
See Also	59
FilePath	60
Contents	60
See Also	61
Finding	62
Contents	62
See Also	65
FindingIdentifier	66
Contents	66
See Also	66
FindingMetricsValuePerSeverity	67
Contents	67
See Also	68
MetricsSummary	69
Contents	69
See Also	70
Recommendation	71
Contents	71
See Also	71
Remediation	72
Contents	72

See Also	72
Resource	73
Contents	73
See Also	73
ResourceId	74
Contents	74
See Also	74
ScanNameWithFindingNum	75
Contents	75
See Also	75
ScanSummary	76
Contents	76
See Also	77
SuggestedFix	78
Contents	78
See Also	78
ValidationExceptionField	79
Contents	79
See Also	79
Vulnerability	80
Contents	80
See Also	81
Service-specific Errors	82
AccessDeniedException	83
Contents	83
See Also	83
ConflictException	85
Contents	85
See Also	85
InternalServerError	87
Contents	87
See Also	87
ResourceNotFoundException	88
Contents	88
See Also	88
ThrottlingException	90

Contents	90
See Also	90
ValidationException	92
Contents	92
See Also	93
Common Parameters	94
Common Errors	97

Welcome

Note

Amazon CodeGuru Security is in preview release and is subject to change.

This section provides documentation for the Amazon CodeGuru Security API operations. CodeGuru Security is a service that uses program analysis and machine learning to detect security policy violations and vulnerabilities, and recommends ways to address these security risks.

By proactively detecting and providing recommendations for addressing security risks, CodeGuru Security improves the overall security of your application code. For more information about CodeGuru Security, see the [Amazon CodeGuru Security User Guide](#).

This document was last published on June 16, 2025.

Actions

The following actions are supported:

- [BatchGetFindings](#)
- [CreateScan](#)
- [CreateUploadUrl](#)
- [GetAccountConfiguration](#)
- [GetFindings](#)
- [GetMetricsSummary](#)
- [GetScan](#)
- [ListFindingsMetrics](#)
- [ListScans](#)
- [ListTagsForResource](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateAccountConfiguration](#)

BatchGetFindings

Returns a list of requested findings from standard scans.

Request Syntax

```
POST /batchGetFindings HTTP/1.1
Content-type: application/json
```

```
{
  "findingIdentifiers": [
    {
      "findingId": "string",
      "scanName": "string"
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

findingIdentifiers

A list of finding identifiers. Each identifier consists of a scanName and a findingId. You retrieve the findingId when you call GetFindings.

Type: Array of [FindingIdentifier](#) objects

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "failedFindings": [
    {
      "errorCode": "string",
      "findingId": "string",
      "message": "string",
      "scanName": "string"
    }
  ],
  "findings": [
    {
      "createdAt": number,
      "description": "string",
      "detectorId": "string",
      "detectorName": "string",
      "detectorTags": [ "string" ],
      "generatorId": "string",
      "id": "string",
      "remediation": {
        "recommendation": {
          "text": "string",
          "url": "string"
        },
        "suggestedFixes": [
          {
            "code": "string",
            "description": "string"
          }
        ]
      },
      "resource": {
        "id": "string",
        "subResourceId": "string"
      },
      "ruleId": "string",
      "severity": "string",
      "status": "string",
      "title": "string",
      "type": "string",
      "updatedAt": number,
      "vulnerability": {
        "filePath": {
          "codeSnippet": [
```

```
        {
            "content": "string",
            "number": number
        }
    ],
    "endLine": number,
    "name": "string",
    "path": "string",
    "startLine": number
},
"id": "string",
"itemCount": number,
"referenceUrls": [ "string" ],
"relatedVulnerabilities": [ "string" ]
}
}
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[failedFindings](#)

A list of errors for individual findings which were not fetched. Each `BatchGetFindingsError` contains the `scanName`, `findingId`, `errorCode` and error message.

Type: Array of [BatchGetFindingsError](#) objects

[findings](#)

A list of all findings which were successfully fetched.

Type: Array of [Finding](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[AccessDeniedException](#)

You do not have sufficient access to perform this action.

HTTP Status Code: 403

[InternalServerErrorException](#)

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 500

[ThrottlingException](#)

The request was denied due to request throttling.

HTTP Status Code: 429

[ValidationException](#)

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateScan

Use to create a scan using code uploaded to an Amazon S3 bucket.

Request Syntax

```
POST /scans HTTP/1.1
Content-type: application/json

{
  "analysisType": "string",
  "clientToken": "string",
  "resourceId": { ... },
  "scanName": "string",
  "scanType": "string",
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

analysisType

The type of analysis you want CodeGuru Security to perform in the scan, either `Security` or `All`. The `Security` type only generates findings related to security. The `All` type generates both security findings and quality findings. Defaults to `Security` type if missing.

Type: String

Valid Values: `Security` | `All`

Required: No

clientToken

The idempotency token for the request. Amazon CodeGuru Security uses this value to prevent the accidental creation of duplicate scans if there are failures and retries.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\S]+`

Required: No

resourceId

The identifier for the resource object to be scanned.

Type: [ResourceId](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

scanName

The unique name that CodeGuru Security uses to track revisions across multiple scans of the same resource. Only allowed for a STANDARD scan type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Pattern: `[a-zA-Z0-9-_$.]*`

Required: Yes

scanType

The type of scan, either Standard or Express. Defaults to Standard type if missing.

Express scans run on limited resources and use a limited set of detectors to analyze your code in near-real time. Standard scans have standard resource limits and use the full set of detectors to analyze your code.

Type: String

Valid Values: Standard | Express

Required: No

tags

An array of key-value pairs used to tag a scan. A tag is a custom attribute label with two parts:

- A tag key. For example, CostCenter, Environment, or Secret. Tag keys are case sensitive.
- An optional tag value field. For example, 111122223333, Production, or a team name. Omitting the tag value is the same as using an empty string. Tag values are case sensitive.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "resourceId": { ... },
  "runId": "string",
  "scanName": "string",
  "scanNameArn": "string",
  "scanState": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

resourceId

The identifier for the resource object that contains resources that were scanned.

Type: [ResourceId](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

runId

UUID that identifies the individual scan run.

Type: String

Pattern: `[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}`

scanName

The name of the scan.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Pattern: `[a-zA-Z0-9-_$:.]*`

scanNameArn

The ARN for the scan name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Pattern: `arn:aws:codeguru-security:[\S]+:[\d]{12}:scans\[a-zA-Z0-9-_$:.]*`

scanState

The current state of the scan. Returns either `InProgress`, `Successful`, or `Failed`.

Type: String

Valid Values: `InProgress` | `Successful` | `Failed`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[AccessDeniedException](#)

You do not have sufficient access to perform this action.

HTTP Status Code: 403

[ConflictException](#)

The requested operation would cause a conflict with the current state of a service resource associated with the request. Resolve the conflict before retrying this request.

HTTP Status Code: 409

[InternalServerErrorException](#)

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 500

[ResourceNotFoundException](#)

The resource specified in the request was not found.

HTTP Status Code: 404

[ThrottlingException](#)

The request was denied due to request throttling.

HTTP Status Code: 429

[ValidationException](#)

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateUploadUrl

Generates a pre-signed URL, request headers used to upload a code resource, and code artifact identifier for the uploaded resource.

You can upload your code resource to the URL with the request headers using any HTTP client.

Request Syntax

```
POST /uploadUrl HTTP/1.1
Content-type: application/json

{
  "scanName": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

scanName

The name of the scan that will use the uploaded resource. CodeGuru Security uses the unique scan name to track revisions across multiple scans of the same resource. Use this scanName when you call CreateScan on the code resource you upload to this URL.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Pattern: [a-zA-Z0-9-_\$:.]*

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "codeArtifactId": "string",
  "requestHeaders": {
    "string" : "string"
  },
  "s3Url": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[codeArtifactId](#)

The identifier for the uploaded code resource. Pass this to CreateScan to use the uploaded resources.

Type: String

Pattern: [a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}

[requestHeaders](#)

A set of key-value pairs that contain the required headers when uploading your resource.

Type: String to string map

Key Length Constraints: Minimum length of 1.

Value Length Constraints: Minimum length of 1.

[s3Url](#)

A pre-signed S3 URL. You can upload the code file you want to scan with the required requestHeaders using any HTTP client.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[AccessDeniedException](#)

You do not have sufficient access to perform this action.

HTTP Status Code: 403

[InternalServerErrorException](#)

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 500

[ThrottlingException](#)

The request was denied due to request throttling.

HTTP Status Code: 429

[ValidationException](#)

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetAccountConfiguration

Use to get the encryption configuration for an account.

Request Syntax

```
GET /accountConfiguration/get HTTP/1.1
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "encryptionConfig": {
    "kmsKeyArn": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

encryptionConfig

An EncryptionConfig object that contains the KMS key ARN that is used for encryption. By default, CodeGuru Security uses an AWS-managed key for encryption. To specify your own key, call UpdateAccountConfiguration. If you do not specify a customer-managed key, returns empty.

Type: [EncryptionConfig](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[AccessDeniedException](#)

You do not have sufficient access to perform this action.

HTTP Status Code: 403

[InternalServerErrorException](#)

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 500

[ThrottlingException](#)

The request was denied due to request throttling.

HTTP Status Code: 429

[ValidationException](#)

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetFindings

Returns a list of all findings generated by a particular scan.

Request Syntax

```
GET /findings/scanName?maxResults=maxResults&nextToken=nextToken&status=status HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to return in the response. Use this parameter when paginating results. If additional results exist beyond the number you specify, the `nextToken` element is returned in the response. Use `nextToken` in a subsequent request to retrieve additional results. If not specified, returns 1000 results.

Valid Range: Minimum value of 1. Maximum value of 1000.

nextToken

A token to use for paginating results that are returned in the response. Set the value of this parameter to null for the first request. For subsequent calls, use the `nextToken` value returned from the previous request to continue listing results after the first page.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[\S]+`

scanName

The name of the scan you want to retrieve findings from.

Length Constraints: Minimum length of 1. Maximum length of 140.

Pattern: `[a-zA-Z0-9-_$.]*`

Required: Yes

status

The status of the findings you want to get. Pass either Open, Closed, or All.

Valid Values: Closed | Open | All

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "findings": [
    {
      "createdAt": number,
      "description": "string",
      "detectorId": "string",
      "detectorName": "string",
      "detectorTags": [ "string" ],
      "generatorId": "string",
      "id": "string",
      "remediation": {
        "recommendation": {
          "text": "string",
          "url": "string"
        },
        "suggestedFixes": [
          {
            "code": "string",
            "description": "string"
          }
        ]
      },
      "resource": {
        "id": "string",
        "subResourceId": "string"
      },
      "ruleId": "string",
```

```

    "severity": "string",
    "status": "string",
    "title": "string",
    "type": "string",
    "updatedAt": number,
    "vulnerability": {
      "filePath": {
        "codeSnippet": [
          {
            "content": "string",
            "number": number
          }
        ],
        "endLine": number,
        "name": "string",
        "path": "string",
        "startLine": number
      },
      "id": "string",
      "itemCount": number,
      "referenceUrls": [ "string" ],
      "relatedVulnerabilities": [ "string" ]
    }
  ],
  "nextToken": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

findings

A list of findings generated by the specified scan.

Type: Array of [Finding](#) objects

nextToken

A pagination token. You can use this in future calls to `GetFindings` to continue listing results after the current page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[\S]+`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[AccessDeniedException](#)

You do not have sufficient access to perform this action.

HTTP Status Code: 403

[ConflictException](#)

The requested operation would cause a conflict with the current state of a service resource associated with the request. Resolve the conflict before retrying this request.

HTTP Status Code: 409

[InternalServerException](#)

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 500

[ResourceNotFoundException](#)

The resource specified in the request was not found.

HTTP Status Code: 404

[ThrottlingException](#)

The request was denied due to request throttling.

HTTP Status Code: 429

[ValidationException](#)

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetMetricsSummary

Returns a summary of metrics for an account from a specified date, including number of open findings, the categories with most findings, the scans with most open findings, and scans with most open critical findings.

Request Syntax

```
GET /metrics/summary?date=date HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

date

The date you want to retrieve summary metrics from, rounded to the nearest day. The date must be within the past two years.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "metricsSummary": {
    "categoriesWithMostFindings": [
      {
        "categoryName": "string",
        "findingNumber": number
      }
    ],
    "date": number,
    "openFindings": {
```

```
    "critical": number,
    "high": number,
    "info": number,
    "low": number,
    "medium": number
  },
  "scansWithMostOpenCriticalFindings": [
    {
      "findingNumber": number,
      "scanName": "string"
    }
  ],
  "scansWithMostOpenFindings": [
    {
      "findingNumber": number,
      "scanName": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[metricsSummary](#)

The summary metrics from the specified date.

Type: [MetricsSummary](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[AccessDeniedException](#)

You do not have sufficient access to perform this action.

HTTP Status Code: 403

[InternalServerErrorException](#)

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 500

[ThrottlingException](#)

The request was denied due to request throttling.

HTTP Status Code: 429

[ValidationException](#)

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetScan

Returns details about a scan, including whether or not a scan has completed.

Request Syntax

```
GET /scans/scanName?runId=runId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

runId

UUID that identifies the individual scan run you want to view details about. You retrieve this when you call the CreateScan operation. Defaults to the latest scan run if missing.

Pattern: `[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}`

scanName

The name of the scan you want to view details about.

Length Constraints: Minimum length of 1. Maximum length of 140.

Pattern: `[a-zA-Z0-9-_$:.]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "analysisType": "string",
```

```
"createdAt": number,  
"errorMessage": "string",  
"numberOfRevisions": number,  
"runId": "string",  
"scanName": "string",  
"scanNameArn": "string",  
"scanState": "string",  
"updatedAt": number  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[analysisType](#)

The type of analysis CodeGuru Security performed in the scan, either `Security` or `All`. The `Security` type only generates findings related to security. The `All` type generates both security findings and quality findings.

Type: String

Valid Values: `Security` | `All`

[createdAt](#)

The time the scan was created.

Type: Timestamp

[errorMessage](#)

Details about the error that causes a scan to fail to be retrieved.

Type: String

Length Constraints: Minimum length of 1.

[numberOfRevisions](#)

The number of times a scan has been re-run on a revised resource.

Type: Long

runId

UUID that identifies the individual scan run.

Type: String

Pattern: `[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}`

scanName

The name of the scan.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Pattern: `[a-zA-Z0-9-_$:.*]*`

scanNameArn

The ARN for the scan name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Pattern: `arn:aws:codeguru-security:[\S]+:[\d]{12}:scans\[a-zA-Z0-9-_$:.*\]`

scanState

The current state of the scan. Returns either `InProgress`, `Successful`, or `Failed`.

Type: String

Valid Values: `InProgress` | `Successful` | `Failed`

updatedAt

The time when the scan was last updated. Only available for STANDARD scan types.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[AccessDeniedException](#)

You do not have sufficient access to perform this action.

HTTP Status Code: 403

[InternalServerError](#)

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 500

[ResourceNotFoundException](#)

The resource specified in the request was not found.

HTTP Status Code: 404

[ThrottlingException](#)

The request was denied due to request throttling.

HTTP Status Code: 429

[ValidationException](#)

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListFindingsMetrics

Returns metrics about all findings in an account within a specified time range.

Request Syntax

```
GET /metrics/findings?  
endDate=endDate&maxResults=maxResults&nextToken=nextToken&startDate=startDate HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

endDate

The end date of the interval which you want to retrieve metrics from. Round to the nearest day.

Required: Yes

maxResults

The maximum number of results to return in the response. Use this parameter when paginating results. If additional results exist beyond the number you specify, the `nextToken` element is returned in the response. Use `nextToken` in a subsequent request to retrieve additional results. If not specified, returns 1000 results.

Valid Range: Minimum value of 1. Maximum value of 1000.

nextToken

A token to use for paginating results that are returned in the response. Set the value of this parameter to null for the first request. For subsequent calls, use the `nextToken` value returned from the previous request to continue listing results after the first page.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[\S]+`

startDate

The start date of the interval which you want to retrieve metrics from. Rounds to the nearest day.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "findingsMetrics": [
    {
      "closedFindings": {
        "critical": number,
        "high": number,
        "info": number,
        "low": number,
        "medium": number
      },
      "date": number,
      "meanTimeToClose": {
        "critical": number,
        "high": number,
        "info": number,
        "low": number,
        "medium": number
      },
      "newFindings": {
        "critical": number,
        "high": number,
        "info": number,
        "low": number,
        "medium": number
      },
      "openFindings": {
        "critical": number,
        "high": number,
        "info": number,
        "low": number,
        "medium": number
      }
    }
  ],
}
```

```
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[findingsMetrics](#)

A list of `AccountFindingsMetric` objects retrieved from the specified time interval.

Type: Array of [AccountFindingsMetric](#) objects

[nextToken](#)

A pagination token. You can use this in future calls to `ListFindingMetrics` to continue listing results after the current page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[\S]+`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[AccessDeniedException](#)

You do not have sufficient access to perform this action.

HTTP Status Code: 403

[InternalServerException](#)

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 500

[ThrottlingException](#)

The request was denied due to request throttling.

HTTP Status Code: 429

[ValidationException](#)

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListScans

Returns a list of all scans in an account. Does not return EXPRESS scans.

Request Syntax

```
GET /scans?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[maxResults](#)

The maximum number of results to return in the response. Use this parameter when paginating results. If additional results exist beyond the number you specify, the `nextToken` element is returned in the response. Use `nextToken` in a subsequent request to retrieve additional results. If not specified, returns 100 results.

Valid Range: Minimum value of 1. Maximum value of 100.

[nextToken](#)

A token to use for paginating results that are returned in the response. Set the value of this parameter to null for the first request. For subsequent calls, use the `nextToken` value returned from the previous request to continue listing results after the first page.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[\S]+`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"nextToken": "string",
"summaries": [
  {
    "createdAt": number,
    "runId": "string",
    "scanName": "string",
    "scanNameArn": "string",
    "scanState": "string",
    "updatedAt": number
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

A pagination token. You can use this in future calls to `ListScans` to continue listing results after the current page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[\S]+`

[summaries](#)

A list of `ScanSummary` objects with information about all scans in an account.

Type: Array of [ScanSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[AccessDeniedException](#)

You do not have sufficient access to perform this action.

HTTP Status Code: 403

[InternalServerErrorException](#)

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 500

[ThrottlingException](#)

The request was denied due to request throttling.

HTTP Status Code: 429

[ValidationException](#)

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Returns a list of all tags associated with a scan.

Request Syntax

```
GET /tags/resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The ARN of the ScanName object. You can retrieve this ARN by calling CreateScan, ListScans, or GetScan.

Length Constraints: Minimum length of 1. Maximum length of 300.

Pattern: `arn:aws:codeguru-security:[\S]+:[\d]{12}:scans\[a-zA-Z0-9-_$:.*\]`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tags

An array of key-value pairs used to tag an existing scan. A tag is a custom attribute label with two parts:

- A tag key. For example, `CostCenter`, `Environment`, or `Secret`. Tag keys are case sensitive.
- An optional tag value field. For example, `111122223333`, `Production`, or a team name. Omitting the tag value is the same as using an empty string. Tag values are case sensitive.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The requested operation would cause a conflict with the current state of a service resource associated with the request. Resolve the conflict before retrying this request.

HTTP Status Code: 409

InternalServerError

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 500

ResourceNotFoundException

The resource specified in the request was not found.

HTTP Status Code: 404

[ThrottlingException](#)

The request was denied due to request throttling.

HTTP Status Code: 429

[ValidationException](#)

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Use to add one or more tags to an existing scan.

Request Syntax

```
POST /tags/resourceArn HTTP/1.1
Content-type: application/json
```

```
{
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The ARN of the ScanName object. You can retrieve this ARN by calling CreateScan, ListScans, or GetScan.

Length Constraints: Minimum length of 1. Maximum length of 300.

Pattern: `arn:aws:codeguru-security:[\S]+:[\d]{12}:scans\[a-zA-Z0-9-_$:.*\]`

Required: Yes

Request Body

The request accepts the following data in JSON format.

tags

An array of key-value pairs used to tag an existing scan. A tag is a custom attribute label with two parts:

- A tag key. For example, CostCenter, Environment, or Secret. Tag keys are case sensitive.

- An optional tag value field. For example, 111122223333, Production, or a team name. Omitting the tag value is the same as using an empty string. Tag values are case sensitive.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[AccessDeniedException](#)

You do not have sufficient access to perform this action.

HTTP Status Code: 403

[ConflictException](#)

The requested operation would cause a conflict with the current state of a service resource associated with the request. Resolve the conflict before retrying this request.

HTTP Status Code: 409

[InternalServerException](#)

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 500

[ResourceNotFoundException](#)

The resource specified in the request was not found.

HTTP Status Code: 404

[ThrottlingException](#)

The request was denied due to request throttling.

HTTP Status Code: 429

[ValidationException](#)

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Use to remove one or more tags from an existing scan.

Request Syntax

```
DELETE /tags/resourceArn?tagKeys=tagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The ARN of the ScanName object. You can retrieve this ARN by calling CreateScan, ListScans, or GetScan.

Length Constraints: Minimum length of 1. Maximum length of 300.

Pattern: `arn:aws:codeguru-security:[\S]+:[\d]{12}:scans\[a-zA-Z0-9-_$:.*\]`

Required: Yes

tagKeys

A list of keys for each tag you want to remove from a scan.

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[AccessDeniedException](#)

You do not have sufficient access to perform this action.

HTTP Status Code: 403

[ConflictException](#)

The requested operation would cause a conflict with the current state of a service resource associated with the request. Resolve the conflict before retrying this request.

HTTP Status Code: 409

[InternalServerError](#)

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 500

[ResourceNotFoundException](#)

The resource specified in the request was not found.

HTTP Status Code: 404

[ThrottlingException](#)

The request was denied due to request throttling.

HTTP Status Code: 429

[ValidationException](#)

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateAccountConfiguration

Use to update the encryption configuration for an account.

Request Syntax

```
PUT /updateAccountConfiguration HTTP/1.1
Content-type: application/json
```

```
{
  "encryptionConfig": {
    "kmsKeyArn": "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[encryptionConfig](#)

The customer-managed KMS key ARN you want to use for encryption. If not specified, CodeGuru Security will use an AWS-managed key for encryption. If you previously specified a customer-managed KMS key and want CodeGuru Security to use an AWS-managed key for encryption instead, pass nothing.

Type: [EncryptionConfig](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
```

```
"encryptionConfig": {  
  "kmsKeyArn": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[encryptionConfig](#)

An EncryptionConfig object that contains the KMS key ARN that is used for encryption. If you did not specify a customer-managed KMS key in the request, returns empty.

Type: [EncryptionConfig](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[AccessDeniedException](#)

You do not have sufficient access to perform this action.

HTTP Status Code: 403

[InternalServerError](#)

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 500

[ResourceNotFoundException](#)

The resource specified in the request was not found.

HTTP Status Code: 404

[ThrottlingException](#)

The request was denied due to request throttling.

HTTP Status Code: 429

[ValidationException](#)

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The Amazon CodeGuru Security API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AccountFindingsMetric](#)
- [BatchGetFindingsError](#)
- [CategoryWithFindingNum](#)
- [CodeLine](#)
- [EncryptionConfig](#)
- [FilePath](#)
- [Finding](#)
- [FindingIdentifier](#)
- [FindingMetricsValuePerSeverity](#)
- [MetricsSummary](#)
- [Recommendation](#)
- [Remediation](#)
- [Resource](#)
- [ResourceId](#)
- [ScanNameWithFindingNum](#)
- [ScanSummary](#)
- [SuggestedFix](#)
- [ValidationExceptionField](#)
- [Vulnerability](#)

AccountFindingsMetric

A summary of findings metrics for an account on a specified date.

Contents

closedFindings

The number of closed findings of each severity on the specified date.

Type: [FindingMetricsValuePerSeverity](#) object

Required: No

date

The date from which the findings metrics were retrieved.

Type: Timestamp

Required: No

meanTimeToClose

The average time in days it takes to close findings of each severity as of a specified date.

Type: [FindingMetricsValuePerSeverity](#) object

Required: No

newFindings

The number of new findings of each severity on the specified date.

Type: [FindingMetricsValuePerSeverity](#) object

Required: No

openFindings

The number of open findings of each severity as of the specified date.

Type: [FindingMetricsValuePerSeverity](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchGetFindingsError

Contains information about the error that caused a finding to fail to be retrieved.

Contents

errorCode

A code associated with the type of error.

Type: String

Valid Values: DUPLICATE_IDENTIFIER | ITEM_DOES_NOT_EXIST | INTERNAL_ERROR | INVALID_FINDING_ID | INVALID_SCAN_NAME

Required: Yes

findingId

The finding ID of the finding that was not fetched.

Type: String

Required: Yes

message

Describes the error.

Type: String

Required: Yes

scanName

The name of the scan that generated the finding.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Pattern: [a-zA-Z0-9-_\$:.*]*

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CategoryWithFindingNum

Information about a finding category with open findings.

Contents

categoryName

The name of the finding category. A finding category is determined by the detector that detected the finding.

Type: String

Required: No

findingNumber

The number of open findings in the category.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CodeLine

The line of code where a finding was detected.

Contents

content

The code that contains a vulnerability.

Type: String

Required: No

number

The code line number.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EncryptionConfig

Information about the encryption configuration for an account. Required to call `UpdateAccountConfiguration`.

Contents

kmsKeyArn

The KMS key ARN that is used for encryption. If an AWS-managed key is used for encryption, returns empty.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:aws:kms:[\S]+:[\d]{12}:key\/((([a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}))|(mrk-[0-9a-zA-Z]{32}))`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FilePath

Information about the location of security vulnerabilities that Amazon CodeGuru Security detected in your code.

Contents

codeSnippet

A list of [CodeLine](#) objects that describe where the security vulnerability appears in your code.

Type: Array of [CodeLine](#) objects

Required: No

endLine

The last line number of the code snippet where the security vulnerability appears in your code.

Type: Integer

Required: No

name

The name of the file.

Type: String

Required: No

path

The path to the resource with the security vulnerability.

Type: String

Required: No

startLine

The first line number of the code snippet where the security vulnerability appears in your code.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Finding

Information about a finding that was detected in your code.

Contents

createdAt

The time when the finding was created.

Type: Timestamp

Required: No

description

A description of the finding.

Type: String

Required: No

detectorId

The identifier for the detector that detected the finding in your code. A detector is a defined rule based on industry standards and AWS best practices.

Type: String

Required: No

detectorName

The name of the detector that identified the security vulnerability in your code.

Type: String

Required: No

detectorTags

One or more tags or categorizations that are associated with a detector. These tags are defined by type, programming language, or other classification such as maintainability or consistency.

Type: Array of strings

Required: No

generatorId

The identifier for the component that generated a finding such as AmazonCodeGuruSecurity.

Type: String

Required: No

id

The identifier for a finding.

Type: String

Required: No

remediation

An object that contains the details about how to remediate a finding.

Type: [Remediation](#) object

Required: No

resource

The resource where Amazon CodeGuru Security detected a finding.

Type: [Resource](#) object

Required: No

ruleId

The identifier for the rule that generated the finding.

Type: String

Required: No

severity

The severity of the finding. Severity can be critical, high, medium, low, or informational. For information on severity levels, see [Finding severity](#) in the *Amazon CodeGuru Security User Guide*.

Type: String

Valid Values: Critical | High | Medium | Low | Info

Required: No

status

The status of the finding. A finding status can be open or closed.

Type: String

Valid Values: Closed | Open | All

Required: No

title

The title of the finding.

Type: String

Required: No

type

The type of finding.

Type: String

Required: No

updatedAt

The time when the finding was last updated. Findings are updated when you remediate them or when the finding code location changes.

Type: Timestamp

Required: No

vulnerability

An object that describes the detected security vulnerability.

Type: [Vulnerability](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FindingIdentifier

An object that contains information about a finding and the scan that generated it.

Contents

findingId

The identifier for a finding.

Type: String

Required: Yes

scanName

The name of the scan that generated the finding.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FindingMetricsValuePerSeverity

A numeric value corresponding to the severity of a finding, such as the number of open findings or the average time it takes to close findings of a given severity.

Contents

critical

A numeric value corresponding to a critical finding.

Type: Double

Required: No

high

A numeric value corresponding to a high severity finding.

Type: Double

Required: No

info

A numeric value corresponding to an informational finding.

Type: Double

Required: No

low

A numeric value corresponding to a low severity finding.

Type: Double

Required: No

medium

A numeric value corresponding to a medium severity finding.

Type: Double

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MetricsSummary

A summary of metrics for an account as of a specified date.

Contents

categoriesWithMostFindings

A list of `CategoryWithFindingNum` objects for the top 5 finding categories with the most findings.

Type: Array of [CategoryWithFindingNum](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

date

The date from which the metrics summary information was retrieved.

Type: Timestamp

Required: No

openFindings

The number of open findings of each severity.

Type: [FindingMetricsValuePerSeverity](#) object

Required: No

scansWithMostOpenCriticalFindings

A list of `ScanNameWithFindingNum` objects for the top 3 scans with the most number of open critical findings.

Type: Array of [ScanNameWithFindingNum](#) objects

Array Members: Minimum number of 0 items. Maximum number of 3 items.

Required: No

scansWithMostOpenFindings

A list of `ScanNameWithFindingNum` objects for the top 3 scans with the most number of open findings.

Type: Array of [ScanNameWithFindingNum](#) objects

Array Members: Minimum number of 0 items. Maximum number of 3 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Recommendation

Information about the recommended course of action to remediate a finding.

Contents

text

The recommended course of action to remediate the finding.

Type: String

Required: No

url

The URL address to the recommendation for remediating the finding.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Remediation

Information about how to remediate a finding.

Contents

recommendation

An object that contains information about the recommended course of action to remediate a finding.

Type: [Recommendation](#) object

Required: No

suggestedFixes

A list of SuggestedFix objects. Each object contains information about a suggested code fix to remediate the finding.

Type: Array of [SuggestedFix](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Resource

Information about a resource that contains a finding.

Contents

id

The scanName of the scan that was run on the resource.

Type: String

Required: No

subResourceId

The identifier for a section of the resource.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceId

The identifier for a resource object that contains resources to scan. Specifying a `codeArtifactId` is required to create a scan.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

`codeArtifactId`

The identifier for the code file uploaded to the resource object. Returned by `CreateUploadUrl` when you upload resources to be scanned.

Type: String

Pattern: `[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ScanNameWithFindingNum

Information about the number of findings generated by a scan.

Contents

findingNumber

The number of findings generated by a scan.

Type: Integer

Required: No

scanName

The name of the scan.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ScanSummary

Information about a scan.

Contents

createdAt

The time when the scan was created.

Type: Timestamp

Required: Yes

runId

The identifier for the scan run.

Type: String

Pattern: `[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}`

Required: Yes

scanName

The name of the scan.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Pattern: `[a-zA-Z0-9-_$.]*`

Required: Yes

scanState

The state of the scan. A scan can be In Progress, Complete, or Failed.

Type: String

Valid Values: `InProgress` | `Successful` | `Failed`

Required: Yes

scanNameArn

The ARN for the scan name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Pattern: `arn:aws:codeguru-security:[\S]+:[\d]{12}:scans\[a-zA-Z0-9-_$:.*\]`

Required: No

updatedAt

The time the scan was last updated. A scan is updated when it is re-run.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SuggestedFix

Information about the suggested code fix to remediate a finding.

Contents

code

The suggested code fix. If applicable, includes code patch to replace your source code.

Type: String

Required: No

description

A description of the suggested code fix and why it is being suggested.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ValidationExceptionField

Information about a validation exception.

Contents

message

Describes the exception.

Type: String

Required: Yes

name

The name of the exception.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Vulnerability

Information about a security vulnerability that Amazon CodeGuru Security detected.

Contents

filePath

An object that describes the location of the detected security vulnerability in your code.

Type: [FilePath](#) object

Required: No

id

The identifier for the vulnerability.

Type: String

Required: No

itemCount

This member has been deprecated.

The number of times the vulnerability appears in your code.

Type: Integer

Required: No

referenceUrls

One or more URL addresses that contain details about a vulnerability.

Type: Array of strings

Required: No

relatedVulnerabilities

One or more vulnerabilities that are related to the vulnerability being described.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Service-specific Errors

The Amazon CodeGuru Security API contains service-specific exceptions that various actions return. This section describes each exception in detail.

The following service-specific exceptions are returned:

- [AccessDeniedException](#)
- [ConflictException](#)
- [InternalServerErrorException](#)
- [ResourceNotFoundException](#)
- [ThrottlingException](#)
- [ValidationException](#)

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code returned: 403

Contents

errorCode

The identifier for the error.

Type: String

Required: Yes

message

Description of the error.

Type: String

Required: Yes

resourceId

The identifier for the resource you don't have access to.

Type: String

Required: No

resourceType

The type of resource you don't have access to.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for Ruby V3](#)

ConflictException

The requested operation would cause a conflict with the current state of a service resource associated with the request. Resolve the conflict before retrying this request.

HTTP Status Code returned: 409

Contents

errorCode

The identifier for the error.

Type: String

Required: Yes

message

Description of the error.

Type: String

Required: Yes

resourceId

The identifier for the service resource associated with the request.

Type: String

Required: Yes

resourceType

The type of resource associated with the request.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for Ruby V3](#)

InternalServerErrorException

The server encountered an internal error and is unable to complete the request.

HTTP Status Code returned: 500

Contents

error

The internal error encountered by the server.

Type: String

Required: No

message

Description of the error.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for Ruby V3](#)

ResourceNotFoundException

The resource specified in the request was not found.

HTTP Status Code returned: 404

Contents

errorCode

The identifier for the error.

Type: String

Required: Yes

message

Description of the error.

Type: String

Required: Yes

resourceId

The identifier for the resource that was not found.

Type: String

Required: Yes

resourceType

The type of resource that was not found.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for Ruby V3](#)

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code returned: 429

Contents

errorCode

The identifier for the error.

Type: String

Required: Yes

message

Description of the error.

Type: String

Required: Yes

quotaCode

The identifier for the originating quota.

Type: String

Required: No

serviceCode

The identifier for the originating service.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for Ruby V3](#)

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code returned: 400

Contents

errorCode

The identifier for the error.

Type: String

Required: Yes

message

Description of the error.

Type: String

Required: Yes

reason

The reason the request failed validation.

Type: String

Valid Values: `unknownOperation` | `cannotParse` | `fieldValidationFailed` | `other`
| `lambdaCodeShaMismatch`

Required: Yes

fieldList

The field that caused the error, if applicable.

Type: Array of [ValidationExceptionField](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request is expired

HTTP Status Code: 403

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 403

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

MalformedHttpRequestException

Problems with the request at the HTTP level, e.g. we can't decompress the body according to the decompression algorithm specified by the content-encoding.

HTTP Status Code: 400

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 401

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestAbortedException

Convenient exception that can be used when a request is aborted before a reply is sent back (e.g. client closed connection).

HTTP Status Code: 400

RequestEntityTooLargeException

Problems with the request at the HTTP level. The request entity is too large.

HTTP Status Code: 413

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

RequestTimeoutException

Problems with the request at the HTTP level. Reading the Request timed out.

HTTP Status Code: 408

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

UnrecognizedClientException

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

UnknownOperationException

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 404

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400