



API Reference

# Amazon Cognito Sync



**API Version 2014-06-30**

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

# Amazon Cognito Sync: API Reference

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

---

# Table of Contents

<b>Welcome</b> .....	<b>1</b>
<b>Actions</b> .....	<b>2</b>
BulkPublish .....	3
Request Syntax .....	3
URI Request Parameters .....	3
Request Body .....	3
Response Syntax .....	3
Response Elements .....	4
Errors .....	4
See Also .....	5
DeleteDataset .....	7
Request Syntax .....	7
URI Request Parameters .....	7
Request Body .....	8
Response Syntax .....	8
Response Elements .....	8
Errors .....	9
See Also .....	10
DescribeDataset .....	11
Request Syntax .....	11
URI Request Parameters .....	11
Request Body .....	12
Response Syntax .....	12
Response Elements .....	12
Errors .....	13
See Also .....	14
DescribeIdentityPoolUsage .....	15
Request Syntax .....	15
URI Request Parameters .....	15
Request Body .....	15
Response Syntax .....	15
Response Elements .....	16
Errors .....	16
Examples .....	17

---

See Also .....	18
DescribeIdentityUsage .....	20
Request Syntax .....	20
URI Request Parameters .....	20
Request Body .....	20
Response Syntax .....	21
Response Elements .....	21
Errors .....	21
Examples .....	22
See Also .....	23
GetBulkPublishDetails .....	25
Request Syntax .....	25
URI Request Parameters .....	25
Request Body .....	25
Response Syntax .....	25
Response Elements .....	26
Errors .....	27
See Also .....	28
GetCognitoEvents .....	29
Request Syntax .....	29
URI Request Parameters .....	29
Request Body .....	29
Response Syntax .....	29
Response Elements .....	30
Errors .....	30
See Also .....	31
GetIdentityPoolConfiguration .....	32
Request Syntax .....	32
URI Request Parameters .....	32
Request Body .....	32
Response Syntax .....	32
Response Elements .....	33
Errors .....	33
Examples .....	35
See Also .....	36
ListDatasets .....	37

---

Request Syntax .....	37
URI Request Parameters .....	37
Request Body .....	38
Response Syntax .....	38
Response Elements .....	38
Errors .....	39
Examples .....	40
See Also .....	41
ListIdentityPoolUsage .....	42
Request Syntax .....	42
URI Request Parameters .....	42
Request Body .....	42
Response Syntax .....	42
Response Elements .....	43
Errors .....	43
Examples .....	44
See Also .....	46
ListRecords .....	47
Request Syntax .....	47
URI Request Parameters .....	47
Request Body .....	48
Response Syntax .....	48
Response Elements .....	49
Errors .....	50
Examples .....	51
See Also .....	52
RegisterDevice .....	54
Request Syntax .....	54
URI Request Parameters .....	54
Request Body .....	55
Response Syntax .....	55
Response Elements .....	55
Errors .....	56
Examples .....	57
See Also .....	58
SetCognitoEvents .....	59

---

Request Syntax .....	59
URI Request Parameters .....	59
Request Body .....	59
Response Syntax .....	60
Response Elements .....	60
Errors .....	60
See Also .....	61
SetIdentityPoolConfiguration .....	63
Request Syntax .....	63
URI Request Parameters .....	63
Request Body .....	64
Response Syntax .....	64
Response Elements .....	64
Errors .....	65
Examples .....	66
See Also .....	68
SubscribeToDataset .....	69
Request Syntax .....	69
URI Request Parameters .....	69
Request Body .....	70
Response Syntax .....	70
Response Elements .....	70
Errors .....	70
Examples .....	71
See Also .....	72
UnsubscribeFromDataset .....	74
Request Syntax .....	74
URI Request Parameters .....	74
Request Body .....	75
Response Syntax .....	75
Response Elements .....	75
Errors .....	75
Examples .....	76
See Also .....	77
UpdateRecords .....	79
Request Syntax .....	79

---

URI Request Parameters .....	79
Request Body .....	80
Response Syntax .....	81
Response Elements .....	81
Errors .....	82
See Also .....	84
<b>Data Types .....</b>	<b>85</b>
CognitoStreams .....	86
Contents .....	86
See Also .....	87
Dataset .....	88
Contents .....	88
See Also .....	89
IdentityPoolUsage .....	90
Contents .....	90
See Also .....	91
IdentityUsage .....	92
Contents .....	92
See Also .....	93
PushSync .....	94
Contents .....	94
See Also .....	94
Record .....	95
Contents .....	95
See Also .....	96
RecordPatch .....	97
Contents .....	97
See Also .....	98
<b>Common Parameters .....</b>	<b>99</b>
<b>Common Error Types .....</b>	<b>102</b>

# Welcome

Amazon Cognito Sync provides an AWS service and client library that enable cross-device syncing of application-related user data. High-level client libraries are available for both iOS and Android. You can use these libraries to persist data locally so that it's available even if the device is offline. Developer credentials don't need to be stored on the mobile device to access the service. You can use Amazon Cognito to obtain a normalized user ID and credentials. User data is persisted in a dataset that can store up to 1 MB of key-value pairs, and you can have up to 20 datasets per user identity.

With Amazon Cognito Sync, the data stored for each identity is accessible only to credentials assigned to that identity. In order to use the Cognito Sync service, you need to make API calls using credentials retrieved with [Amazon Cognito Identity service](#).

You can work with Amazon Cognito Sync in the following SDKs.

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

This document was last published on April 24, 2026.

# Actions

The following actions are supported:

- [BulkPublish](#)
- [DeleteDataset](#)
- [DescribeDataset](#)
- [DescribeIdentityPoolUsage](#)
- [DescribeIdentityUsage](#)
- [GetBulkPublishDetails](#)
- [GetCognitoEvents](#)
- [GetIdentityPoolConfiguration](#)
- [ListDatasets](#)
- [ListIdentityPoolUsage](#)
- [ListRecords](#)
- [RegisterDevice](#)
- [SetCognitoEvents](#)
- [SetIdentityPoolConfiguration](#)
- [SubscribeToDataset](#)
- [UnsubscribeFromDataset](#)
- [UpdateRecords](#)

# BulkPublish

Initiates a bulk publish of all existing datasets for an Identity Pool to the configured stream. Customers are limited to one successful bulk publish per 24 hours. Bulk publish is an asynchronous request, customers can see the status of the request via the `GetBulkPublishDetails` operation.

This API can only be called with developer credentials. You cannot call this API with the temporary user credentials provided by Cognito Identity.

## Request Syntax

```
POST /identitypools/IdentityPoolId/bulkpublish HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### IdentityPoolId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito. GUID generation is unique within a region.

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w- ]+ : [0-9a-f- ]+`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "IdentityPoolId": "string"
}
```

```
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### IdentityPoolId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito. GUID generation is unique within a region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w- ]+ : [0-9a-f- ]+`

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **AlreadyStreamedException**

An exception thrown when a bulk publish operation is requested less than 24 hours after a previous bulk publish operation completed successfully.

#### **message**

The message associated with the `AlreadyStreamedException` exception.

HTTP Status Code: 400

### **DuplicateRequestException**

An exception thrown when there is an `IN_PROGRESS` bulk publish operation for the given identity pool.

#### **message**

The message associated with the `DuplicateRequestException` exception.

HTTP Status Code: 400

## InternalErrorException

Indicates an internal service error.

### message

Message returned by InternalErrorException.

HTTP Status Code: 500

## InvalidParameterException

Thrown when a request parameter does not comply with the associated constraints.

### message

Message returned by InvalidParameterException.

HTTP Status Code: 400

## NotAuthorizedException

Thrown when a user is not authorized to access the requested resource.

### message

The message returned by a NotAuthorizedException.

HTTP Status Code: 403

## ResourceNotFoundException

Thrown if the resource doesn't exist.

### message

Message returned by a ResourceNotFoundException.

HTTP Status Code: 404

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteDataset

Deletes the specific dataset. The dataset will be deleted permanently, and the action can't be undone. Datasets that this dataset was merged with will no longer report the merge. Any subsequent operation on this dataset will result in a `ResourceNotFoundException`.

This API can be called with temporary user credentials provided by Cognito Identity or with developer credentials.

## Request Syntax

```
DELETE /identitypools/IdentityPoolId/identities/IdentityId/datasets/DatasetName
HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### DatasetName

A string of up to 128 characters. Allowed characters are a-z, A-Z, 0-9, '\_' (underscore), '-' (dash), and '.' (dot).

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

### IdentityId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito. GUID generation is unique within a region.

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w-]+:[0-9a-f-]+`

Required: Yes

### IdentityPoolId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito. GUID generation is unique within a region.

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w- ]+ : [0-9a-f- ]+`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Dataset": {
    "CreationDate": number,
    "DatasetName": "string",
    "DataStorage": number,
    "IdentityId": "string",
    "LastModifiedBy": "string",
    "LastModifiedDate": number,
    "NumRecords": number
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### Dataset

A collection of data for an identity pool. An identity pool can have multiple datasets. A dataset is per identity and can be general or associated with a particular entity in an application (like a saved game). Datasets are automatically created if they don't exist. Data is synced by dataset, and a dataset can hold up to 1MB of key-value pairs.

Type: [Dataset](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InternalErrorException**

Indicates an internal service error.

#### **message**

Message returned by InternalErrorException.

HTTP Status Code: 500

### **InvalidParameterException**

Thrown when a request parameter does not comply with the associated constraints.

#### **message**

Message returned by InvalidParameterException.

HTTP Status Code: 400

### **NotAuthorizedException**

Thrown when a user is not authorized to access the requested resource.

#### **message**

The message returned by a NotAuthorizedException.

HTTP Status Code: 403

### **ResourceConflictException**

Thrown if an update can't be applied because the resource was changed by another call and this would result in a conflict.

#### **message**

The message returned by a ResourceConflictException.

HTTP Status Code: 409

### **ResourceNotFoundException**

Thrown if the resource doesn't exist.

**message**

Message returned by a `ResourceNotFoundException`.

HTTP Status Code: 404

**TooManyRequestsException**

Thrown if the request is throttled.

**message**

Message returned by a `TooManyRequestsException`.

HTTP Status Code: 429

**See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DescribeDataset

Gets meta data about a dataset by identity and dataset name. With Amazon Cognito Sync, each identity has access only to its own data. Thus, the credentials used to make this API call need to have access to the identity data.

This API can be called with temporary user credentials provided by Cognito Identity or with developer credentials. You should use Cognito Identity credentials to make this API call.

## Request Syntax

```
GET /identitypools/IdentityPoolId/identities/IdentityId/datasets/DatasetName HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### DatasetName

A string of up to 128 characters. Allowed characters are a-z, A-Z, 0-9, '\_' (underscore), '-' (dash), and '.' (dot).

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

### IdentityId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito. GUID generation is unique within a region.

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w-]+:[0-9a-f-]+`

Required: Yes

### IdentityPoolId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito. GUID generation is unique within a region.

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w-]+:[0-9a-f-]+`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Dataset": {
    "CreationDate": number,
    "DatasetName": "string",
    "DataStorage": number,
    "IdentityId": "string",
    "LastModifiedBy": "string",
    "LastModifiedDate": number,
    "NumRecords": number
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### Dataset

Metadata for a collection of data for an identity. An identity can have multiple datasets. A dataset can be general or associated with a particular entity in an application (like a saved game). Datasets are automatically created if they don't exist. Data is synced by dataset, and a dataset can hold up to 1MB of key-value pairs

Type: [Dataset](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### InternalErrorException

Indicates an internal service error.

#### message

Message returned by InternalErrorException.

HTTP Status Code: 500

### InvalidParameterException

Thrown when a request parameter does not comply with the associated constraints.

#### message

Message returned by InvalidParameterException.

HTTP Status Code: 400

### NotAuthorizedException

Thrown when a user is not authorized to access the requested resource.

#### message

The message returned by a NotAuthorizedException.

HTTP Status Code: 403

### ResourceNotFoundException

Thrown if the resource doesn't exist.

#### message

Message returned by a ResourceNotFoundException.

HTTP Status Code: 404

### TooManyRequestsException

Thrown if the request is throttled.

## message

Message returned by a TooManyRequestsException.

HTTP Status Code: 429

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DescribeIdentityPoolUsage

Gets usage details (for example, data storage) about a particular identity pool.

This API can only be called with developer credentials. You cannot call this API with the temporary user credentials provided by Cognito Identity.

## Request Syntax

```
GET /identitypools/IdentityPoolId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### IdentityPoolId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito. GUID generation is unique within a region.

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w- ]+ : [0-9a-f- ]+`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "IdentityPoolUsage": {
    "DataStorage": number,
    "IdentityPoolId": "string",
```

```
    "LastModifiedDate": number,  
    "SyncSessionsCount": number  
  }  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### IdentityPoolUsage

Information about the usage of the identity pool.

Type: [IdentityPoolUsage](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InternalErrorException**

Indicates an internal service error.

#### **message**

Message returned by InternalErrorException.

HTTP Status Code: 500

### **InvalidParameterException**

Thrown when a request parameter does not comply with the associated constraints.

#### **message**

Message returned by InvalidParameterException.

HTTP Status Code: 400

### **NotAuthorizedException**

Thrown when a user is not authorized to access the requested resource.

**message**

The message returned by a `NotAuthorizedException`.

HTTP Status Code: 403

**ResourceNotFoundException**

Thrown if the resource doesn't exist.

**message**

Message returned by a `ResourceNotFoundException`.

HTTP Status Code: 404

**TooManyRequestsException**

Thrown if the request is throttled.

**message**

Message returned by a `TooManyRequestsException`.

HTTP Status Code: 429

## Examples

### DescribeIdentityPoolUsage

The following examples have been edited for readability.

#### Sample Request

```
POST / HTTP/1.1
CONTENT-TYPE: application/json
X-AMZN-REQUESTID: 8dc0e749-c8cd-48bd-8520-da6be00d528b
X-AMZ-TARGET:
  com.amazonaws.cognito.sync.model.AWSognitoSyncService.DescribeIdentityPoolUsage
HOST: cognito-sync.us-east-1.amazonaws.com:443
X-AMZ-DATE: 20141111T205737Z
AUTHORIZATION: AWS4-HMAC-SHA256 Credential=<credential>, SignedHeaders=content-
type;host;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<signature>
```

```
{
  "IdentityPoolId": "IDENTITY_POOL_ID"
}
```

## Sample Response

```
1.1 200 OK
x-amzn-requestid: 8dc0e749-c8cd-48bd-8520-da6be00d528b
content-type: application/json
content-length: 271
date: Tue, 11 Nov 2014 20:57:37 GMT
```

```
{
  "IdentityPoolUsage":
  {
    "DataStorage": 0,
    "IdentityPoolId": "IDENTITY_POOL_ID",
    "LastModifiedDate": 1.413231134115E9,
    "SyncSessionsCount": null
  }
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

# DescribeIdentityUsage

Gets usage information for an identity, including number of datasets and data usage.

This API can be called with temporary user credentials provided by Cognito Identity or with developer credentials.

## Request Syntax

```
GET /identitypools/IdentityPoolId/identities/IdentityId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### IdentityId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito. GUID generation is unique within a region.

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w-]+:[0-9a-f-]+`

Required: Yes

### IdentityPoolId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito. GUID generation is unique within a region.

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w-]+:[0-9a-f-]+`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "IdentityUsage": {
    "DatasetCount": number,
    "DataStorage": number,
    "IdentityId": "string",
    "IdentityPoolId": "string",
    "LastModifiedDate": number
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### IdentityUsage

Usage information for the identity.

Type: [IdentityUsage](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InternalErrorException**

Indicates an internal service error.

#### **message**

Message returned by InternalErrorException.

HTTP Status Code: 500

### **InvalidParameterException**

Thrown when a request parameter does not comply with the associated constraints.

**message**

Message returned by `InvalidParameterException`.

HTTP Status Code: 400

**NotAuthorizedException**

Thrown when a user is not authorized to access the requested resource.

**message**

The message returned by a `NotAuthorizedException`.

HTTP Status Code: 403

**ResourceNotFoundException**

Thrown if the resource doesn't exist.

**message**

Message returned by a `ResourceNotFoundException`.

HTTP Status Code: 404

**TooManyRequestsException**

Thrown if the request is throttled.

**message**

Message returned by a `TooManyRequestsException`.

HTTP Status Code: 429

## Examples

### DescribeIdentityUsage

The following examples have been edited for readability.

#### Sample Request

```
POST / HTTP/1.1
CONTENT-TYPE: application/json
```

```
X-AMZN-REQUESTID: 33f9b4e4-a177-4aad-a3bb-6edb7980b283
X-AMZ-TARGET:
  com.amazonaws.cognito.sync.model.AWSCognitoSyncService.DescribeIdentityUsage
HOST: cognito-sync.us-east-1.amazonaws.com:443
X-AMZ-DATE: 20141111T215129Z
AUTHORIZATION: AWS4-HMAC-SHA256 Credential=<credential>, SignedHeaders=content-
type;host;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<signature>

{
  "IdentityPoolId": "IDENTITY_POOL_ID",
  "IdentityId": "IDENTITY_ID"
}
```

## Sample Response

```
1.1 200 OK
x-amzn-requestid: 33f9b4e4-a177-4aad-a3bb-6edb7980b283
content-type: application/json
content-length: 318
date: Tue, 11 Nov 2014 21:51:29 GMT

{
  "IdentityUsage":
  {
    "DataStorage": 16,
    "DatasetCount": 1,
    "IdentityId": "IDENTITY_ID",
    "IdentityPoolId": "IDENTITY_POOL_ID",
    "LastModifiedDate": 1.412974081336E9
  }
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetBulkPublishDetails

Get the status of the last BulkPublish operation for an identity pool.

This API can only be called with developer credentials. You cannot call this API with the temporary user credentials provided by Cognito Identity.

## Request Syntax

```
POST /identitypools/IdentityPoolId/getBulkPublishDetails HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### IdentityPoolId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito. GUID generation is unique within a region.

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w-]+:[0-9a-f-]+`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "BulkPublishCompleteTime": number,
  "BulkPublishStartTime": number,
  "BulkPublishStatus": "string",
  "FailureMessage": "string",
```

```
"IdentityPoolId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### BulkPublishCompleteTime

If BulkPublishStatus is SUCCEEDED, the time the last bulk publish operation completed.

Type: Timestamp

### BulkPublishStartTime

The date/time at which the last bulk publish was initiated.

Type: Timestamp

### BulkPublishStatus

Status of the last bulk publish operation, valid values are:

- NOT\_STARTED - No bulk publish has been requested for this identity pool
- IN\_PROGRESS - Data is being published to the configured stream
- SUCCEEDED - All data for the identity pool has been published to the configured stream
- FAILED - Some portion of the data has failed to publish, check FailureMessage for the cause.

Type: String

Valid Values: NOT\_STARTED | IN\_PROGRESS | FAILED | SUCCEEDED

### FailureMessage

If BulkPublishStatus is FAILED this field will contain the error message that caused the bulk publish to fail.

Type: String

### IdentityPoolId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito. GUID generation is unique within a region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w- ]+ : [0-9a-f- ]+`

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### InternalErrorException

Indicates an internal service error.

#### message

Message returned by InternalErrorException.

HTTP Status Code: 500

### InvalidParameterException

Thrown when a request parameter does not comply with the associated constraints.

#### message

Message returned by InvalidParameterException.

HTTP Status Code: 400

### NotAuthorizedException

Thrown when a user is not authorized to access the requested resource.

#### message

The message returned by a NotAuthorizedException.

HTTP Status Code: 403

### ResourceNotFoundException

Thrown if the resource doesn't exist.

#### message

Message returned by a ResourceNotFoundException.

## HTTP Status Code: 404

### See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetCognitoEvents

Gets the events and the corresponding Lambda functions associated with an identity pool.

This API can only be called with developer credentials. You cannot call this API with the temporary user credentials provided by Cognito Identity.

## Request Syntax

```
GET /identitypools/IdentityPoolId/events HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### IdentityPoolId

The Cognito Identity Pool ID for the request

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w-]+:[0-9a-f-]+`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Events": {
    "string" : "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### Events

The Cognito Events returned from the `GetCognitoEvents` request

Type: String to string map

Map Entries: Maximum number of 1 item.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InternalErrorException**

Indicates an internal service error.

#### **message**

Message returned by `InternalErrorException`.

HTTP Status Code: 500

### **InvalidParameterException**

Thrown when a request parameter does not comply with the associated constraints.

#### **message**

Message returned by `InvalidParameterException`.

HTTP Status Code: 400

### **NotAuthorizedException**

Thrown when a user is not authorized to access the requested resource.

#### **message**

The message returned by a `NotAuthorizedException`.

HTTP Status Code: 403

### **ResourceNotFoundException**

Thrown if the resource doesn't exist.

#### **message**

Message returned by a ResourceNotFoundException.

HTTP Status Code: 404

### **TooManyRequestsException**

Thrown if the request is throttled.

#### **message**

Message returned by a TooManyRequestsException.

HTTP Status Code: 429

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetIdentityPoolConfiguration

Gets the configuration settings of an identity pool.

This API can only be called with developer credentials. You cannot call this API with the temporary user credentials provided by Cognito Identity.

## Request Syntax

```
GET /identitypools/IdentityPoolId/configuration HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### IdentityPoolId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito. This is the ID of the pool for which to return a configuration.

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w- ]+ : [0-9a-f- ]+`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CognitoStreams": {
    "DisabledReason": "string",
    "RoleArn": "string",
```

```
    "StreamingStatus": "string",
    "StreamName": "string"
  },
  "IdentityPoolId": "string",
  "PushSync": {
    "ApplicationArns": [ "string" ],
    "RoleArn": "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### CognitoStreams

Options to apply to this identity pool for Amazon Cognito streams.

Type: [CognitoStreams](#) object

### IdentityPoolId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w-]+:[0-9a-f-]+`

### PushSync

Options to apply to this identity pool for push synchronization.

Type: [PushSync](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

## InternalErrorException

Indicates an internal service error.

### message

Message returned by InternalErrorException.

HTTP Status Code: 500

## InvalidParameterException

Thrown when a request parameter does not comply with the associated constraints.

### message

Message returned by InvalidParameterException.

HTTP Status Code: 400

## NotAuthorizedException

Thrown when a user is not authorized to access the requested resource.

### message

The message returned by a NotAuthorizedException.

HTTP Status Code: 403

## ResourceNotFoundException

Thrown if the resource doesn't exist.

### message

Message returned by a ResourceNotFoundException.

HTTP Status Code: 404

## TooManyRequestsException

Thrown if the request is throttled.

### message

Message returned by a TooManyRequestsException.

HTTP Status Code: 429

## Examples

### GetIdentityPoolConfiguration

The following examples have been edited for readability.

#### Sample Request

```
POST / HTTP/1.1
CONTENT-TYPE: application/json
X-AMZN-REQUESTID: b1cfdd4b-f620-4fe4-be0f-02024a1d33da
X-AMZ-TARGET:
  com.amazonaws.cognito.sync.model.AWSCognitoSyncService.GetIdentityPoolConfiguration
HOST: cognito-sync.us-east-1.amazonaws.com
X-AMZ-DATE: 20141004T195722Z
AUTHORIZATION: AWS4-HMAC-SHA256 Credential=<credential>, SignedHeaders=content-
type;content-length;host;x-amz-date;x-amz-target, Signature=<signature>

{
  "IdentityPoolId": "ID_POOL_ID"
}
```

#### Sample Response

```
1.1 200 OK
x-amzn-requestid: b1cfdd4b-f620-4fe4-be0f-02024a1d33da
date: Sat, 04 Oct 2014 19:57:22 GMT
content-type: application/json
content-length: 332

{
  "IdentityPoolId": "ID_POOL_ID",
  "PushSync":
  {
    "ApplicationArns": ["PLATFORMARN1", "PLATFORMARN2"],
    "RoleArn": "ROLEARN"
  }
}
```

```
}  
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## ListDatasets

Lists datasets for an identity. With Amazon Cognito Sync, each identity has access only to its own data. Thus, the credentials used to make this API call need to have access to the identity data.

ListDatasets can be called with temporary user credentials provided by Cognito Identity or with developer credentials. You should use the Cognito Identity credentials to make this API call.

### Request Syntax

```
GET /identitypools/IdentityPoolId/identities/IdentityId/datasets?  
maxResults=MaxResults&nextToken=NextToken HTTP/1.1
```

### URI Request Parameters

The request uses the following URI parameters.

#### IdentityId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito. GUID generation is unique within a region.

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w-]+:[0-9a-f-]+`

Required: Yes

#### IdentityPoolId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito. GUID generation is unique within a region.

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w-]+:[0-9a-f-]+`

Required: Yes

#### MaxResults

The maximum number of results to be returned.

Length Constraints: Maximum length of 19.

Pattern: `^[1-9]\d*`

### NextToken

A pagination token for obtaining the next page of results.

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Count": number,
  "Datasets": [
    {
      "CreationDate": number,
      "DatasetName": "string",
      "DataStorage": number,
      "IdentityId": "string",
      "LastModifiedBy": "string",
      "LastModifiedDate": number,
      "NumRecords": number
    }
  ],
  "NextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### Count

Number of datasets returned.

Type: Integer

### Datasets

A set of datasets.

Type: Array of [Dataset](#) objects

### NextToken

A pagination token for obtaining the next page of results.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InternalErrorException**

Indicates an internal service error.

#### **message**

Message returned by InternalErrorException.

HTTP Status Code: 500

### **InvalidParameterException**

Thrown when a request parameter does not comply with the associated constraints.

#### **message**

Message returned by InvalidParameterException.

HTTP Status Code: 400

### **NotAuthorizedException**

Thrown when a user is not authorized to access the requested resource.

#### **message**

The message returned by a NotAuthorizedException.

HTTP Status Code: 403

## TooManyRequestsException

Thrown if the request is throttled.

### message

Message returned by a TooManyRequestsException.

HTTP Status Code: 429

## Examples

### ListDatasets

The following examples have been edited for readability.

#### Sample Request

```
POST / HTTP/1.1
CONTENT-TYPE: application/json
X-AMZN-REQUESTID: 15225768-209f-4078-aaed-7494ace9f2db
X-AMZ-TARGET: com.amazonaws.cognito.sync.model.AWSCognitoSyncService.ListDatasets
HOST: cognito-sync.us-east-1.amazonaws.com:443
X-AMZ-DATE: 20141111T215640Z
AUTHORIZATION: AWS4-HMAC-SHA256 Credential=<credential>, SignedHeaders=content-type;host;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<signature>

{
  "IdentityPoolId": "IDENTITY_POOL_ID",
  "IdentityId": "IDENTITY_ID",
  "MaxResults": "3"
}
```

#### Sample Response

```
1.1 200 OK
x-amzn-requestid: 15225768-209f-4078-aaed-7494ace9f2db, 15225768-209f-4078-aaed-7494ace9f2db
content-type: application/json
```

```
content-length: 355
date: Tue, 11 Nov 2014 21:56:40 GMT

{
  "Count": 1,
  "Datasets": [
    {
      "CreationDate": 1.412974057151E9,
      "DataStorage": 16,
      "DatasetName": "my_list",
      "IdentityId": "IDENTITY_ID",
      "LastModifiedBy": "123456789012",
      "LastModifiedDate": 1.412974057244E9,
      "NumRecords": 1
    }
  ],
  "NextToken": null
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListIdentityPoolUsage

Gets a list of identity pools registered with Cognito.

ListIdentityPoolUsage can only be called with developer credentials. You cannot make this API call with the temporary user credentials provided by Cognito Identity.

## Request Syntax

```
GET /identitypools?maxResults=MaxResults&nextToken=NextToken HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### MaxResults

The maximum number of results to be returned.

### NextToken

A pagination token for obtaining the next page of results.

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Count": number,
  "IdentityPoolUsages": [
    {
      "DataStorage": number,
      "IdentityPoolId": "string",
      "LastModifiedDate": number,
      "SyncSessionsCount": number
    }
  ]
}
```

```
    }  
  ],  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### Count

Total number of identities for the identity pool.

Type: Integer

### IdentityPoolUsages

Usage information for the identity pools.

Type: Array of [IdentityPoolUsage](#) objects

### MaxResults

The maximum number of results to be returned.

Type: Integer

### NextToken

A pagination token for obtaining the next page of results.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InternalErrorException**

Indicates an internal service error.

**message**

Message returned by `InternalErrorException`.

HTTP Status Code: 500

**InvalidParameterException**

Thrown when a request parameter does not comply with the associated constraints.

**message**

Message returned by `InvalidParameterException`.

HTTP Status Code: 400

**NotAuthorizedException**

Thrown when a user is not authorized to access the requested resource.

**message**

The message returned by a `NotAuthorizedException`.

HTTP Status Code: 403

**TooManyRequestsException**

Thrown if the request is throttled.

**message**

Message returned by a `TooManyRequestsException`.


HTTP Status Code: 429

## Examples

### ListIdentityPoolUsage

The following examples have been edited for readability.

#### Sample Request



```
POST / HTTP/1.1
CONTENT-TYPE: application/json
X-AMZN-REQUESTID: 9be7c425-ef05-48c0-aef3-9f0ff2fe17d3
X-AMZ-TARGET:
  com.amazonaws.cognito.sync.model.AWSCognitoSyncService.ListIdentityPoolUsage
HOST: cognito-sync.us-east-1.amazonaws.com:443
X-AMZ-DATE: 20141111T211414Z
AUTHORIZATION: AWS4-HMAC-SHA256 Credential=<credential>, SignedHeaders=content-
type;host;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<signature>

{
  "MaxResults": "2"
}
```

## Sample Response

```
1.1 200 OK
x-amzn-requestid: 9be7c425-ef05-48c0-aef3-9f0ff2fe17d3
content-type: application/json
content-length: 519
date: Tue, 11 Nov 2014 21:14:14 GMT

{
  "Count": 2,
  "IdentityPoolUsages": [
    {
      "DataStorage": 0,
      "IdentityPoolId": "IDENTITY_POOL_ID",
      "LastModifiedDate": 1.413836234607E9,
      "SyncSessionsCount": null
    },
    {
      "DataStorage": 0,
      "IdentityPoolId": "IDENTITY_POOL_ID",
      "LastModifiedDate": 1.410892165601E9,
      "SyncSessionsCount": null
    }
  ],
  "MaxResults": 2,
  "NextToken": "dXMtZWZzdC0x0jBjMwJhMDUyLWUwOTgtNDFmYS1hNzZlLWVhYTJjMTI1Zjg2MQ=="
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListRecords

Gets paginated records, optionally changed after a particular sync count for a dataset and identity. With Amazon Cognito Sync, each identity has access only to its own data. Thus, the credentials used to make this API call need to have access to the identity data.

ListRecords can be called with temporary user credentials provided by Cognito Identity or with developer credentials. You should use Cognito Identity credentials to make this API call.

## Request Syntax

```
GET /identitypools/IdentityPoolId/identities/IdentityId/datasets/DatasetName/records?
lastSyncCount=LastSyncCount&maxResults=MaxResults&nextToken=NextToken&syncSessionToken=SyncSessionToken
HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### DatasetName

A string of up to 128 characters. Allowed characters are a-z, A-Z, 0-9, '\_' (underscore), '-' (dash), and '.' (dot).

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

### IdentityId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito. GUID generation is unique within a region.

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w-]+:[0-9a-f-]+`

Required: Yes

## IdentityPoolId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito. GUID generation is unique within a region.

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w- ]+ : [0-9a-f- ]+`

Required: Yes

## LastSyncCount

The last server sync count for this record.

## MaxResults

The maximum number of results to be returned.

## NextToken

A pagination token for obtaining the next page of results.

## SyncSessionToken

A token containing a session ID, identity ID, and expiration.

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Count": number,
  "DatasetDeletedAfterRequestedSyncCount": boolean,
  "DatasetExists": boolean,
  "DatasetSyncCount": number,
  "LastModifiedBy": "string",
  "MergedDatasetNames": [ "string" ],
  "NextToken": "string",
```

```
"Records": [  
  {  
    "DeviceLastModifiedDate": number,  
    "Key": "string",  
    "LastModifiedBy": "string",  
    "LastModifiedDate": number,  
    "SyncCount": number,  
    "Value": "string"  
  }  
],  
"SyncSessionToken": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### Count

Total number of records.

Type: Integer

### DatasetDeletedAfterRequestedSyncCount

A boolean value specifying whether to delete the dataset locally.

Type: Boolean

### DatasetExists

Indicates whether the dataset exists.

Type: Boolean

### DatasetSyncCount

Server sync count for this dataset.

Type: Long

### LastModifiedBy

The user/device that made the last change to this record.

Type: String

### MergedDatasetNames

Names of merged datasets.

Type: Array of strings

### NextToken

A pagination token for obtaining the next page of results.

Type: String

### Records

A list of all records.

Type: Array of [Record](#) objects

### SyncSessionToken

A token containing a session ID, identity ID, and expiration.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **InternalErrorException**

Indicates an internal service error.

#### **message**

Message returned by InternalErrorException.

HTTP Status Code: 500

### **InvalidParameterException**

Thrown when a request parameter does not comply with the associated constraints.

#### **message**

Message returned by InvalidParameterException.

HTTP Status Code: 400

### **NotAuthorizedException**

Thrown when a user is not authorized to access the requested resource.

#### **message**

The message returned by a NotAuthorizedException.

HTTP Status Code: 403

### **TooManyRequestsException**

Thrown if the request is throttled.

#### **message**

Message returned by a TooManyRequestsException.

HTTP Status Code: 429

## **Examples**

### **ListRecords**

The following examples have been edited for readability.

#### **Sample Request**

```
POST / HTTP/1.1
CONTENT-TYPE: application/json
X-AMZN-REQUESTID: b3d2e31e-d6b7-4612-8e84-c9ba288dab5d
X-AMZ-TARGET: com.amazonaws.cognito.sync.model.AWSCognitoSyncService.ListRecords
HOST: cognito-sync.us-east-1.amazonaws.com:443
X-AMZ-DATE: 20141111T183230Z
AUTHORIZATION: AWS4-HMAC-SHA256 Credential=<credential>, SignedHeaders=content-type;host;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<signature>

{
  "IdentityPoolId": "IDENTITY_POOL_ID",
  "IdentityId": "IDENTITY_ID",
  "DatasetName": "newDataSet"
```

```
}
```

## Sample Response

```
1.1 200 OK
x-amzn-requestid: b3d2e31e-d6b7-4612-8e84-c9ba288dab5d
content-type: application/json
content-length: 623
date: Tue, 11 Nov 2014 18:32:30 GMT
```

```
{
  "Count": 0,
  "DatasetDeletedAfterRequestedSyncCount": false,
  "DatasetExists": false,
  "DatasetSyncCount": 0,
  "LastModifiedBy": null,
  "MergedDatasetNames": null,
  "NextToken": null,
  "Records": [],
  "SyncSessionToken": "SYNC_SESSION_TOKEN"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

# RegisterDevice

Registers a device to receive push sync notifications.

This API can only be called with temporary credentials provided by Cognito Identity. You cannot call this API with developer credentials.

## Request Syntax

```
POST /identitypools/IdentityPoolId/identity/IdentityId/device HTTP/1.1
Content-type: application/json

{
  "Platform": "string",
  "Token": "string"
}
```

## URI Request Parameters

The request uses the following URI parameters.

### IdentityId

The unique ID for this identity.

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w-]+:[0-9a-f-]+`

Required: Yes

### IdentityPoolId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito. Here, the ID of the pool that the identity belongs to.

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w-]+:[0-9a-f-]+`

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### Platform

The SNS platform type (e.g. GCM, SDM, APNS, APNS\_SANDBOX).

Type: String

Valid Values: APNS | APNS\_SANDBOX | GCM | ADM

Required: Yes

### Token

The push token.

Type: String

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "DeviceId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### DeviceId

The unique ID generated for this device by Cognito.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### InternalErrorException

Indicates an internal service error.

#### message

Message returned by InternalErrorException.

HTTP Status Code: 500

### InvalidConfigurationException

This exception is thrown when Amazon Cognito detects an invalid configuration.

#### message

Message returned by InvalidConfigurationException.

HTTP Status Code: 400

### InvalidParameterException

Thrown when a request parameter does not comply with the associated constraints.

#### message

Message returned by InvalidParameterException.

HTTP Status Code: 400

### NotAuthorizedException

Thrown when a user is not authorized to access the requested resource.

#### message

The message returned by a NotAuthorizedException.

HTTP Status Code: 403

## ResourceNotFoundException

Thrown if the resource doesn't exist.

### message

Message returned by a ResourceNotFoundException.

HTTP Status Code: 404

## TooManyRequestsException

Thrown if the request is throttled.

### message

Message returned by a TooManyRequestsException.

HTTP Status Code: 429

## Examples

### RegisterDevice

The following examples have been edited for readability.

#### Sample Request

```
POST / HTTP/1.1
CONTENT-TYPE: application/json
X-AMZN-REQUESTID: 368f9200-3eca-449e-93b3-7b9c08d8e185
X-AMZ-TARGET: com.amazonaws.cognito.sync.model.AWSCognitoSyncService.RegisterDevice
HOST: cognito-sync.us-east-1.amazonaws.com
X-AMZ-DATE: 20141004T194643Z
X-AMZ-SECURITY-TOKEN: <securitytoken>
AUTHORIZATION: AWS4-HMAC-SHA256 Credential=<credential>, SignedHeaders=content-type;content-length;host;x-amz-date;x-amz-target, Signature=<signature>

{
  "IdentityPoolId": "ID_POOL_ID",
  "IdentityId": "IDENTITY_ID",
  "Platform": "GCM",
  "Token": "PUSH_TOKEN"
```

```
}
```

## Sample Response

```
1.1 200 OK
x-amzn-requestid: 368f9200-3eca-449e-93b3-7b9c08d8e185
date: Sat, 04 Oct 2014 19:46:44 GMT
content-type: application/json
content-length: 145

{
  "DeviceId": "5cd28fbe-dd83-47ab-9f83-19093a5fb014"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# SetCognitoEvents

Sets the AWS Lambda function for a given event type for an identity pool. This request only updates the key/value pair specified. Other key/values pairs are not updated. To remove a key value pair, pass a empty value for the particular key.

This API can only be called with developer credentials. You cannot call this API with the temporary user credentials provided by Cognito Identity.

## Request Syntax

```
POST /identitypools/IdentityPoolId/events HTTP/1.1
Content-type: application/json
```

```
{
  "Events": {
    "string" : "string"
  }
}
```

## URI Request Parameters

The request uses the following URI parameters.

### IdentityPoolId

The Cognito Identity Pool to use when configuring Cognito Events

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w-]+:[0-9a-f-]+`

Required: Yes

## Request Body

The request accepts the following data in JSON format.

## Events

The AWS Lambda Amazon Resource Name (ARN) that you want to set as your Cognito Events trigger. For example, "SyncTrigger" : "arn:aws:lambda:us-east-1:123456789012:function:my-function".

Type: String to string map

Map Entries: Maximum number of 1 item.

Required: Yes

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### InternalErrorException

Indicates an internal service error.

#### message

Message returned by InternalErrorException.

HTTP Status Code: 500

### InvalidParameterException

Thrown when a request parameter does not comply with the associated constraints.

#### message

Message returned by InvalidParameterException.

HTTP Status Code: 400

## NotAuthorizedException

Thrown when a user is not authorized to access the requested resource.

### message

The message returned by a NotAuthorizedException.

HTTP Status Code: 403

## ResourceNotFoundException

Thrown if the resource doesn't exist.

### message

Message returned by a ResourceNotFoundException.

HTTP Status Code: 404

## TooManyRequestsException

Thrown if the request is throttled.

### message

Message returned by a TooManyRequestsException.

HTTP Status Code: 429

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# SetIdentityPoolConfiguration

Sets the necessary configuration for push sync.

This API can only be called with developer credentials. You cannot call this API with the temporary user credentials provided by Cognito Identity.

## Request Syntax

```
POST /identitypools/IdentityPoolId/configuration HTTP/1.1
Content-type: application/json
```

```
{
  "CognitoStreams": {
    "DisabledReason": "string",
    "RoleArn": "string",
    "StreamingStatus": "string",
    "StreamName": "string"
  },
  "PushSync": {
    "ApplicationArns": [ "string" ],
    "RoleArn": "string"
  }
}
```

## URI Request Parameters

The request uses the following URI parameters.

### IdentityPoolId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito. This is the ID of the pool to modify.

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w- ]+ : [0-9a-f- ]+`

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### CognitoStreams

Options to apply to this identity pool for Amazon Cognito streams.

Type: [CognitoStreams](#) object

Required: No

### PushSync

Options to apply to this identity pool for push synchronization.

Type: [PushSync](#) object

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CognitoStreams": {
    "DisabledReason": "string",
    "RoleArn": "string",
    "StreamingStatus": "string",
    "StreamName": "string"
  },
  "IdentityPoolId": "string",
  "PushSync": {
    "ApplicationArns": [ "string" ],
    "RoleArn": "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### CognitoStreams

Options to apply to this identity pool for Amazon Cognito streams.

Type: [CognitoStreams](#) object

### IdentityPoolId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w-]+:[0-9a-f-]+`

### PushSync

Options to apply to this identity pool for push synchronization.

Type: [PushSync](#) object

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### **ConcurrentModificationException**

Thrown if there are parallel requests to modify a resource.

#### **message**

The message returned by a ConcurrentModificationException.

HTTP Status Code: 400

### **InternalErrorException**

Indicates an internal service error.

#### **message**

Message returned by InternalErrorException.

HTTP Status Code: 500

### **InvalidParameterException**

Thrown when a request parameter does not comply with the associated constraints.

#### **message**

Message returned by InvalidParameterException.

HTTP Status Code: 400

### **NotAuthorizedException**

Thrown when a user is not authorized to access the requested resource.

#### **message**

The message returned by a NotAuthorizedException.

HTTP Status Code: 403

### **ResourceNotFoundException**

Thrown if the resource doesn't exist.

#### **message**

Message returned by a ResourceNotFoundException.

HTTP Status Code: 404

### **TooManyRequestsException**

Thrown if the request is throttled.

#### **message**

Message returned by a TooManyRequestsException.

HTTP Status Code: 429

## **Examples**

### **SetIdentityPoolConfiguration**

The following examples have been edited for readability.

## Sample Request

```
POST / HTTP/1.1
CONTENT-TYPE: application/json
X-AMZN-REQUESTID: a46db021-f5dd-45d6-af5b-7069fa4a211b
X-AMZ-TARGET:
  com.amazonaws.cognito.sync.model.AWSCognitoSyncService.SetIdentityPoolConfiguration
HOST: cognito-sync.us-east-1.amazonaws.com
X-AMZ-DATE: 20141004T200006Z
AUTHORIZATION: AWS4-HMAC-SHA256 Credential=<credential>, SignedHeaders=content-
type;content-length;host;x-amz-date;x-amz-target, Signature=<signature>

{
  "IdentityPoolId": "ID_POOL_ID",
  "PushSync":
  {
    "ApplicationArns": ["PLATFORMARN1", "PLATFORMARN2"],
    "RoleArn": "ROLEARN"
  }
}
```

## Sample Response

```
1.1 200 OK
x-amzn-requestid: a46db021-f5dd-45d6-af5b-7069fa4a211b
date: Sat, 04 Oct 2014 20:00:06 GMT
content-type: application/json
content-length: 332

{
  "IdentityPoolId": "ID_POOL_ID",
  "PushSync":
  {
    "ApplicationArns": ["PLATFORMARN1", "PLATFORMARN2"],
    "RoleArn": "ROLEARN"
  }
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# SubscribeToDataset

Subscribes to receive notifications when a dataset is modified by another device.

This API can only be called with temporary credentials provided by Cognito Identity. You cannot call this API with developer credentials.

## Request Syntax

```
POST /identitypools/IdentityPoolId/identities/IdentityId/datasets/DatasetName/subscriptions/DeviceId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### DatasetName

The name of the dataset to subscribe to.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [a-zA-Z0-9\_ . :- ]+

Required: Yes

### DeviceId

The unique ID generated for this device by Cognito.

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

### IdentityId

Unique ID for this identity.

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: [\w- ]+ : [0-9a-f- ]+

Required: Yes

## IdentityPoolId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito. The ID of the pool to which the identity belongs.

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w- ]+ : [\0-9a-f- ]+`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### InternalErrorException

Indicates an internal service error.

#### message

Message returned by InternalErrorException.

HTTP Status Code: 500

### InvalidConfigurationException

This exception is thrown when Amazon Cognito detects an invalid configuration.

#### message

Message returned by InvalidConfigurationException.

HTTP Status Code: 400

### **InvalidParameterException**

Thrown when a request parameter does not comply with the associated constraints.

#### **message**

Message returned by InvalidParameterException.

HTTP Status Code: 400

### **NotAuthorizedException**

Thrown when a user is not authorized to access the requested resource.

#### **message**

The message returned by a NotAuthorizedException.

HTTP Status Code: 403

### **ResourceNotFoundException**

Thrown if the resource doesn't exist.

#### **message**

Message returned by a ResourceNotFoundException.

HTTP Status Code: 404

### **TooManyRequestsException**

Thrown if the request is throttled.

#### **message**

Message returned by a TooManyRequestsException.

HTTP Status Code: 429

## **Examples**

### **SubscribeToDataset**

The following examples have been edited for readability.

## Sample Request

```
POST / HTTP/1.1
CONTENT-TYPE: application/json
X-AMZN-REQUESTID: 8b9932b7-201d-4418-a960-0a470e11de9f
X-AMZ-TARGET: com.amazonaws.cognito.sync.model.AWSCognitoSyncService.SubscribeToDataset
HOST: cognito-sync.us-east-1.amazonaws.com
X-AMZ-DATE: 20141004T195350Z
X-AMZ-SECURITY-TOKEN: <securitytoken>
AUTHORIZATION: AWS4-HMAC-SHA256 Credential=<credential>, SignedHeaders=content-type;content-length;host;x-amz-date;x-amz-target, Signature=<signature>

{
  "IdentityPoolId": "ID_POOL_ID",
  "IdentityId": "IDENTITY_ID",
  "DatasetName": "Rufus",
  "DeviceId": "5cd28fbe-dd83-47ab-9f83-19093a5fb014"
}
```

## Sample Response

```
1.1 200 OK
x-amzn-requestid: 8b9932b7-201d-4418-a960-0a470e11de9f
date: Sat, 04 Oct 2014 19:53:50 GMT
content-type: application/json
content-length: 99

{
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UnsubscribeFromDataset

Unsubscribes from receiving notifications when a dataset is modified by another device.

This API can only be called with temporary credentials provided by Cognito Identity. You cannot call this API with developer credentials.

## Request Syntax

```
DELETE /identitypools/IdentityPoolId/identities/IdentityId/datasets/DatasetName/
subscriptions/DeviceId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### DatasetName

The name of the dataset from which to unsubscribe.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [a-zA-Z0-9\_ . :- ]+

Required: Yes

### DeviceId

The unique ID generated for this device by Cognito.

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

### IdentityId

Unique ID for this identity.

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: [\w- ]+ : [0-9a-f- ]+

Required: Yes

## IdentityPoolId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito. The ID of the pool to which this identity belongs.

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w- ]+ : [\0-9a-f- ]+`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### InternalErrorException

Indicates an internal service error.

#### message

Message returned by InternalErrorException.

HTTP Status Code: 500

### InvalidConfigurationException

This exception is thrown when Amazon Cognito detects an invalid configuration.

#### message

Message returned by InvalidConfigurationException.

HTTP Status Code: 400

### **InvalidParameterException**

Thrown when a request parameter does not comply with the associated constraints.

#### **message**

Message returned by InvalidParameterException.

HTTP Status Code: 400

### **NotAuthorizedException**

Thrown when a user is not authorized to access the requested resource.

#### **message**

The message returned by a NotAuthorizedException.

HTTP Status Code: 403

### **ResourceNotFoundException**

Thrown if the resource doesn't exist.

#### **message**

Message returned by a ResourceNotFoundException.

HTTP Status Code: 404

### **TooManyRequestsException**

Thrown if the request is throttled.

#### **message**

Message returned by a TooManyRequestsException.

HTTP Status Code: 429

## **Examples**

### **UnsubscribeFromDataset**

The following examples have been edited for readability.

## Sample Request

```
POST / HTTP/1.1
CONTENT-TYPE: application/json
X-AMZ-REQUESTSUPERTRACE: true
X-AMZN-REQUESTID: 676896d6-14ca-45b1-8029-6d36b10a077e
X-AMZ-TARGET:
  com.amazonaws.cognito.sync.model.AWSCognitoSyncService.UnsubscribeFromDataset
HOST: cognito-sync.us-east-1.amazonaws.com
X-AMZ-DATE: 20141004T195446Z
X-AMZ-SECURITY-TOKEN: <securitytoken>
AUTHORIZATION: AWS4-HMAC-SHA256 Credential=<credential>, SignedHeaders=content-type;content-length;host;x-amz-date;x-amz-target, Signature=<signature>

{
  "IdentityPoolId": "ID_POOL_ID",
  "IdentityId": "IDENTITY_ID",
  "DatasetName": "Rufus",
  "DeviceId": "5cd28fbe-dd83-47ab-9f83-19093a5fb014"
}
```

## Sample Response

```
1.1 200 OK
x-amzn-requestid: 676896d6-14ca-45b1-8029-6d36b10a077e
date: Sat, 04 Oct 2014 19:54:46 GMT
content-type: application/json
content-length: 103

{
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateRecords

Posts updates to records and adds and deletes records for a dataset and user.

The sync count in the record patch is your last known sync count for that record. The server will reject an UpdateRecords request with a ResourceConflictException if you try to patch a record with a new value but a stale sync count.

For example, if the sync count on the server is 5 for a key called highScore and you try and submit a new highScore with sync count of 4, the request will be rejected. To obtain the current sync count for a record, call ListRecords. On a successful update of the record, the response returns the new sync count for that record. You should present that sync count the next time you try to update that same record. When the record does not exist, specify the sync count as 0.

This API can be called with temporary user credentials provided by Cognito Identity or with developer credentials.

## Request Syntax

```
POST /identitypools/IdentityPoolId/identities/IdentityId/datasets/DatasetName HTTP/1.1
x-amz-Client-Context: ClientContext
Content-type: application/json
```

```
{
  "DeviceId": "string",
  "RecordPatches": [
    {
      "DeviceLastModifiedDate": number,
      "Key": "string",
      "Op": "string",
      "SyncCount": number,
      "Value": "string"
    }
  ],
  "SyncSessionToken": "string"
}
```

## URI Request Parameters

The request uses the following URI parameters.

## ClientContext

Intended to supply a device ID that will populate the lastModifiedBy field referenced in other methods. The ClientContext field is not yet implemented.

## DatasetName

A string of up to 128 characters. Allowed characters are a-z, A-Z, 0-9, '\_' (underscore), '-' (dash), and '.' (dot).

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [a-zA-Z0-9\_.-]+

Required: Yes

## IdentityId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito. GUID generation is unique within a region.

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: [\w-]+:[0-9a-f-]+

Required: Yes

## IdentityPoolId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito. GUID generation is unique within a region.

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: [\w-]+:[0-9a-f-]+

Required: Yes

## **Request Body**

The request accepts the following data in JSON format.

## DeviceId

The unique ID generated for this device by Cognito.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

### RecordPatches

A list of patch operations.

Type: Array of [RecordPatch](#) objects

Required: No

### SyncSessionToken

The SyncSessionToken returned by a previous call to ListRecords for this dataset and identity.

Type: String

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Records": [
    {
      "DeviceLastModifiedDate": number,
      "Key": "string",
      "LastModifiedBy": "string",
      "LastModifiedDate": number,
      "SyncCount": number,
      "Value": "string"
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## Records

A list of records that have been updated.

Type: Array of [Record](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

### InternalErrorException

Indicates an internal service error.

#### **message**

Message returned by InternalErrorException.

HTTP Status Code: 500

### InvalidLambdaFunctionOutputException

The AWS Lambda function returned invalid output or an exception.

#### **message**

A message returned when an InvalidLambdaFunctionOutputException occurs

HTTP Status Code: 400

### InvalidParameterException

Thrown when a request parameter does not comply with the associated constraints.

#### **message**

Message returned by InvalidParameterException.

HTTP Status Code: 400

### LambdaSocketTimeoutException

This exception is thrown when your Lambda function fails to respond within 5 seconds. For more information, see [Amazon Cognito Events](#).

HTTP Status Code: 400

### **LambdaThrottledException**

AWS Lambda throttled your account, please contact AWS Support

#### **message**

A message returned when an LambdaThrottledException is thrown

HTTP Status Code: 429

### **LimitExceededException**

Thrown when the limit on the number of objects or operations has been exceeded.

#### **message**

Message returned by LimitExceededException.

HTTP Status Code: 400

### **NotAuthorizedException**

Thrown when a user is not authorized to access the requested resource.

#### **message**

The message returned by a NotAuthorizedException.

HTTP Status Code: 403

### **ResourceConflictException**

Thrown if an update can't be applied because the resource was changed by another call and this would result in a conflict.

#### **message**

The message returned by a ResourceConflictException.

HTTP Status Code: 409

### **ResourceNotFoundException**

Thrown if the resource doesn't exist.

#### **message**

Message returned by a ResourceNotFoundException.

HTTP Status Code: 404

## TooManyRequestsException

Thrown if the request is throttled.

### message

Message returned by a TooManyRequestsException.

HTTP Status Code: 429


## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# Data Types

The Amazon Cognito Sync API contains several data types that various actions use. This section describes each data type in detail.

 **Note**

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [CognitoStreams](#)
- [Dataset](#)
- [IdentityPoolUsage](#)
- [IdentityUsage](#)
- [PushSync](#)
- [Record](#)
- [RecordPatch](#)

# CognitoStreams

Configuration options for configure Cognito streams.

## Contents

### DisabledReason

A string containing the reason why streaming of updates to the identity pool was disabled.

Type: String

Required: No

### RoleArn

The ARN of the role Amazon Cognito can assume in order to publish to the stream. This role must grant access to Amazon Cognito (cognito-sync) to invoke PutRecord on your Cognito stream.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws:iam::\d+:role/.*`

Required: No

### StreamingStatus

Status of the Cognito streams. Valid values are:

- **ENABLED** - Streaming of updates to identity pool is enabled.
- **DISABLED** - Streaming of updates to identity pool is disabled. Bulk publish will also fail if StreamingStatus is DISABLED.

Type: String

Valid Values: **ENABLED** | **DISABLED**

Required: No

### StreamName

The name of the Cognito stream to receive updates. This stream must be in the developers account and in the same region as the identity pool.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Dataset

A collection of data for an identity pool. An identity pool can have multiple datasets. A dataset is per identity and can be general or associated with a particular entity in an application (like a saved game). Datasets are automatically created if they don't exist. Data is synced by dataset, and a dataset can hold up to 1MB of key-value pairs.

## Contents

### CreationDate

Date on which the dataset was created.

Type: Timestamp

Required: No

### DatasetName

A string of up to 128 characters. Allowed characters are a-z, A-Z, 0-9, '\_' (underscore), '-' (dash), and '.' (dot).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [a-zA-Z0-9\_ . : - ]+

Required: No

### DataStorage

Total size in bytes of the records in this dataset.

Type: Long

Required: No

### IdentityId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito. GUID generation is unique within a region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w-]+:[0-9a-f-]+`

Required: No

### **LastModifiedBy**

The device that made the last change to this dataset.

Type: String

Required: No

### **LastModifiedDate**

Date when the dataset was last modified.

Type: Timestamp

Required: No

### **NumRecords**

Number of records in this dataset.

Type: Long

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# IdentityPoolUsage

Usage information for the identity pool.

## Contents

### DataStorage

Data storage information for the identity pool.

Type: Long

Required: No

### IdentityPoolId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito. GUID generation is unique within a region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w- ]+ : [0-9a-f- ]+`

Required: No

### LastModifiedDate

Date on which the identity pool was last modified.

Type: Timestamp

Required: No

### SyncSessionsCount

Number of sync sessions for the identity pool.

Type: Long

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# IdentityUsage

Usage information for the identity.

## Contents

### DatasetCount

Number of datasets for the identity.

Type: Integer

Required: No

### DataStorage

Total data storage for this identity.

Type: Long

Required: No

### IdentityId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito. GUID generation is unique within a region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w-]+:[0-9a-f-]+`

Required: No

### IdentityPoolId

A name-spaced GUID (for example, us-east-1:23EC4050-6AEA-7089-A2DD-08002EXAMPLE) created by Amazon Cognito. GUID generation is unique within a region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 55.

Pattern: `[\w-]+:[0-9a-f-]+`

Required: No

## **LastModifiedDate**

Date on which the identity was last modified.

Type: Timestamp

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# PushSync

Configuration options to be applied to the identity pool.

## Contents

### ApplicationArns

List of SNS platform application ARNs that could be used by clients.

Type: Array of strings

Pattern: `arn:aws:sns:[-0-9a-z]+:\d+:app/[A-Z_]+/[a-zA-Z0-9_.-]+`

Required: No

### RoleArn

A role configured to allow Cognito to call SNS on behalf of the developer.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws:iam::\d+:role/.*`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Record

The basic data structure of a dataset.

## Contents

### DeviceLastModifiedDate

The last modified date of the client device.

Type: Timestamp

Required: No

### Key

The key for the record.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

### LastModifiedBy

The user/device that made the last change to this record.

Type: String

Required: No

### LastModifiedDate

The date on which the record was last modified.

Type: Timestamp

Required: No

### SyncCount

The server sync count for this record.

Type: Long

Required: No

## Value

The value for the record.

Type: String

Length Constraints: Maximum length of 4194304.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RecordPatch

An update operation for a record.

## Contents

### Key

The key associated with the record patch.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

### Op

An operation, either replace or remove.

Type: String

Valid Values: `replace` | `remove`

Required: Yes

### SyncCount

Last known server sync count for this record. Set to 0 if unknown.

Type: Long

Required: Yes

### DeviceLastModifiedDate

The last modified date of the client device.

Type: Timestamp

Required: No

### Value

The value associated with the record patch.

Type: String

Length Constraints: Maximum length of 4194304.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

## X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

## X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4\_request"). The value is expressed in the following format: *access\_key/YYYYMMDD/region/service/aws4\_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

## X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

### **X-Amz-Security-Token**

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

### **X-Amz-Signature**

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

### **X-Amz-SignedHeaders**

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

## Required: Conditional

# Common Error Types

This section lists common error types that this AWS service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

## **AccessDeniedException**

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

## **ExpiredTokenException**

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

## **IncompleteSignature**

The request signature doesn't conform to AWS standards. Verify that you're using valid AWS credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 403

## **InternalFailure**

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact AWS Support.

HTTP Status Code: 500

## **MalformedHttpRequestException**

The request body can't be processed. This typically happens when the request body can't be decompressed using the specified content encoding algorithm. Verify that the content encoding header matches the compression format used.

HTTP Status Code: 400

**NotAuthorized**

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

**OptInRequired**

Your AWS account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

**RequestAbortedException**

The request was aborted before a response could be returned. This typically happens when the client closes the connection.

HTTP Status Code: 400

**RequestEntityTooLargeException**

The request entity is too large. Reduce the size of the request body and try again.

HTTP Status Code: 413

**RequestTimeoutException**

The request timed out. The server didn't receive the complete request within the expected time frame. Try again.

HTTP Status Code: 408

**ServiceUnavailable**

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

**ThrottlingException**

Your request rate is too high. The AWS SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

## **UnknownOperationException**

The action or operation isn't recognized. Verify that the action name is spelled correctly and that it's supported by the API version you're using.

HTTP Status Code: 404

## **UnrecognizedClientException**

The X.509 certificate or AWS access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

## **ValidationError**

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400