



API Reference

AWS Device Farm Documentation



API Version 2015-06-23

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS Device Farm Documentation: API Reference

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
CreateDevicePool	5
Request Syntax	5
Request Parameters	5
Response Syntax	6
Response Elements	7
Errors	7
See Also	8
CreateInstanceProfile	9
Request Syntax	9
Request Parameters	9
Response Syntax	10
Response Elements	10
Errors	11
See Also	11
CreateNetworkProfile	13
Request Syntax	13
Request Parameters	13
Response Syntax	16
Response Elements	16
Errors	16
See Also	17
CreateProject	18
Request Syntax	18
Request Parameters	18
Response Syntax	19
Response Elements	19
Errors	19
See Also	20
CreateRemoteAccessSession	21
Request Syntax	21
Request Parameters	21
Response Syntax	25

Response Elements	27
Errors	27
See Also	28
CreateTestGridProject	29
Request Syntax	29
Request Parameters	29
Response Syntax	30
Response Elements	30
Errors	30
See Also	31
CreateTestGridUrl	32
Request Syntax	32
Request Parameters	32
Response Syntax	32
Response Elements	33
Errors	33
See Also	34
CreateUpload	35
Request Syntax	35
Request Parameters	35
Response Syntax	38
Response Elements	38
Errors	38
See Also	39
CreateVPCEConfiguration	40
Request Syntax	40
Request Parameters	40
Response Syntax	41
Response Elements	41
Errors	42
See Also	42
DeleteDevicePool	43
Request Syntax	43
Request Parameters	43
Response Elements	43
Errors	43

See Also	44
DeleteInstanceProfile	45
Request Syntax	45
Request Parameters	45
Response Elements	45
Errors	45
See Also	46
DeleteNetworkProfile	47
Request Syntax	47
Request Parameters	47
Response Elements	47
Errors	47
See Also	48
DeleteProject	49
Request Syntax	49
Request Parameters	49
Response Elements	49
Errors	49
See Also	50
DeleteRemoteAccessSession	51
Request Syntax	51
Request Parameters	51
Response Elements	51
Errors	51
See Also	52
DeleteRun	53
Request Syntax	53
Request Parameters	53
Response Elements	53
Errors	53
See Also	54
DeleteTestGridProject	55
Request Syntax	55
Request Parameters	55
Response Elements	56
Errors	56

See Also	56
DeleteUpload	58
Request Syntax	58
Request Parameters	58
Response Elements	58
Errors	58
See Also	59
DeleteVPCEConfiguration	60
Request Syntax	60
Request Parameters	60
Response Elements	60
Errors	60
See Also	61
GetAccountSettings	62
Response Syntax	62
Response Elements	62
Errors	63
See Also	63
GetDevice	65
Request Syntax	65
Request Parameters	65
Response Syntax	65
Response Elements	66
Errors	67
See Also	67
GetDeviceInstance	69
Request Syntax	69
Request Parameters	69
Response Syntax	69
Response Elements	70
Errors	70
See Also	71
GetDevicePool	72
Request Syntax	72
Request Parameters	72
Response Syntax	72

Response Elements	73
Errors	73
See Also	74
GetDevicePoolCompatibility	75
Request Syntax	75
Request Parameters	76
Response Syntax	78
Response Elements	80
Errors	81
See Also	81
GetInstanceProfile	83
Request Syntax	83
Request Parameters	83
Response Syntax	83
Response Elements	84
Errors	84
See Also	84
GetJob	86
Request Syntax	86
Request Parameters	86
Response Syntax	86
Response Elements	88
Errors	88
See Also	89
GetNetworkProfile	90
Request Syntax	90
Request Parameters	90
Response Syntax	90
Response Elements	91
Errors	91
See Also	92
GetOfferingStatus	93
Request Syntax	93
Request Parameters	93
Response Syntax	93
Response Elements	94

Errors	95
Examples	96
See Also	97
GetProject	98
Request Syntax	98
Request Parameters	98
Response Syntax	98
Response Elements	99
Errors	99
See Also	100
GetRemoteAccessSession	101
Request Syntax	101
Request Parameters	101
Response Syntax	101
Response Elements	103
Errors	104
See Also	104
GetRun	106
Request Syntax	106
Request Parameters	106
Response Syntax	106
Response Elements	108
Errors	109
See Also	109
GetSuite	111
Request Syntax	111
Request Parameters	111
Response Syntax	111
Response Elements	112
Errors	112
See Also	113
GetTest	114
Request Syntax	114
Request Parameters	114
Response Syntax	114
Response Elements	115

Errors	115
See Also	116
GetTestGridProject	117
Request Syntax	117
Request Parameters	117
Response Syntax	117
Response Elements	118
Errors	118
See Also	118
GetTestGridSession	120
Request Syntax	120
Request Parameters	120
Response Syntax	121
Response Elements	121
Errors	122
See Also	122
GetUpload	124
Request Syntax	124
Request Parameters	124
Response Syntax	124
Response Elements	125
Errors	125
See Also	126
GetVPCEConfiguration	127
Request Syntax	127
Request Parameters	127
Response Syntax	127
Response Elements	128
Errors	128
See Also	128
InstallToRemoteAccessSession	130
Request Syntax	130
Request Parameters	130
Response Syntax	131
Response Elements	131
Errors	131

See Also	132
ListArtifacts	133
Request Syntax	133
Request Parameters	133
Response Syntax	134
Response Elements	134
Errors	135
See Also	135
ListDeviceInstances	137
Request Syntax	137
Request Parameters	137
Response Syntax	137
Response Elements	138
Errors	138
See Also	139
ListDevicePools	140
Request Syntax	140
Request Parameters	140
Response Syntax	141
Response Elements	141
Errors	142
See Also	142
ListDevices	144
Request Syntax	144
Request Parameters	144
Response Syntax	146
Response Elements	147
Errors	148
See Also	148
ListInstanceProfiles	150
Request Syntax	150
Request Parameters	150
Response Syntax	150
Response Elements	151
Errors	151
See Also	152

ListJobs	153
Request Syntax	153
Request Parameters	153
Response Syntax	153
Response Elements	155
Errors	156
See Also	156
ListNetworkProfiles	158
Request Syntax	158
Request Parameters	158
Response Syntax	159
Response Elements	159
Errors	160
See Also	160
ListOfferingPromotions	162
Request Syntax	162
Request Parameters	162
Response Syntax	162
Response Elements	163
Errors	163
See Also	164
ListOfferings	165
Request Syntax	165
Request Parameters	165
Response Syntax	165
Response Elements	166
Errors	166
Examples	167
See Also	168
ListOfferingTransactions	169
Request Syntax	169
Request Parameters	169
Response Syntax	169
Response Elements	170
Errors	171
Examples	171

See Also	179
ListProjects	181
Request Syntax	181
Request Parameters	181
Response Syntax	182
Response Elements	182
Errors	183
See Also	183
ListRemoteAccessSessions	185
Request Syntax	185
Request Parameters	185
Response Syntax	185
Response Elements	188
Errors	188
See Also	189
ListRuns	190
Request Syntax	190
Request Parameters	190
Response Syntax	190
Response Elements	193
Errors	193
See Also	194
ListSamples	195
Request Syntax	195
Request Parameters	195
Response Syntax	195
Response Elements	196
Errors	196
See Also	197
ListSuites	198
Request Syntax	198
Request Parameters	198
Response Syntax	198
Response Elements	199
Errors	200
See Also	200

ListTagsForResource	202
Request Syntax	202
Request Parameters	202
Response Syntax	202
Response Elements	203
Errors	203
See Also	203
ListTestGridProjects	205
Request Syntax	205
Request Parameters	205
Response Syntax	205
Response Elements	206
Errors	206
See Also	207
ListTestGridSessionActions	208
Request Syntax	208
Request Parameters	208
Response Syntax	209
Response Elements	209
Errors	209
See Also	210
ListTestGridSessionArtifacts	211
Request Syntax	211
Request Parameters	211
Response Syntax	212
Response Elements	212
Errors	213
See Also	213
ListTestGridSessions	215
Request Syntax	215
Request Parameters	215
Response Syntax	217
Response Elements	217
Errors	217
See Also	218
ListTests	219

Request Syntax	219
Request Parameters	219
Response Syntax	219
Response Elements	220
Errors	221
See Also	221
ListUniqueProblems	223
Request Syntax	223
Request Parameters	223
Response Syntax	224
Response Elements	225
Errors	226
See Also	227
ListUploads	228
Request Syntax	228
Request Parameters	228
Response Syntax	230
Response Elements	231
Errors	231
See Also	232
ListVPCEConfigurations	233
Request Syntax	233
Request Parameters	233
Response Syntax	233
Response Elements	234
Errors	234
See Also	235
PurchaseOffering	236
Request Syntax	236
Request Parameters	236
Response Syntax	237
Response Elements	237
Errors	238
Examples	239
See Also	240
RenewOffering	241

Request Syntax	241
Request Parameters	241
Response Syntax	241
Response Elements	242
Errors	243
Examples	243
See Also	244
ScheduleRun	246
Request Syntax	246
Request Parameters	247
Response Syntax	249
Response Elements	251
Errors	251
See Also	252
StopJob	253
Request Syntax	253
Request Parameters	253
Response Syntax	253
Response Elements	255
Errors	255
See Also	256
StopRemoteAccessSession	257
Request Syntax	257
Request Parameters	257
Response Syntax	257
Response Elements	259
Errors	260
See Also	260
StopRun	262
Request Syntax	262
Request Parameters	262
Response Syntax	262
Response Elements	264
Errors	265
See Also	265
TagResource	267

Request Syntax	267
Request Parameters	267
Response Elements	268
Errors	268
See Also	269
UntagResource	270
Request Syntax	270
Request Parameters	270
Response Elements	271
Errors	271
See Also	271
UpdateDeviceInstance	273
Request Syntax	273
Request Parameters	273
Response Syntax	274
Response Elements	274
Errors	274
See Also	275
UpdateDevicePool	276
Request Syntax	276
Request Parameters	276
Response Syntax	278
Response Elements	278
Errors	279
See Also	279
UpdateInstanceProfile	281
Request Syntax	281
Request Parameters	281
Response Syntax	282
Response Elements	283
Errors	283
See Also	284
UpdateNetworkProfile	285
Request Syntax	285
Request Parameters	285
Response Syntax	288

Response Elements	288
Errors	288
See Also	289
UpdateProject	290
Request Syntax	290
Request Parameters	290
Response Syntax	291
Response Elements	291
Errors	292
See Also	292
UpdateTestGridProject	294
Request Syntax	294
Request Parameters	294
Response Syntax	295
Response Elements	295
Errors	296
See Also	296
UpdateUpload	298
Request Syntax	298
Request Parameters	298
Response Syntax	299
Response Elements	299
Errors	300
See Also	300
UpdateVPCEConfiguration	302
Request Syntax	302
Request Parameters	302
Response Syntax	303
Response Elements	304
Errors	304
See Also	305
Data Types	306
AccountSettings	309
Contents	309
See Also	310
Artifact	312

Contents	312
See Also	314
Counters	315
Contents	315
See Also	316
CPU	317
Contents	317
See Also	317
CreateRemoteAccessSessionConfiguration	318
Contents	318
See Also	318
CustomerArtifactPaths	320
Contents	320
See Also	320
Device	322
Contents	322
See Also	326
DeviceFilter	327
Contents	327
See Also	330
DeviceInstance	331
Contents	331
See Also	332
DeviceMinutes	333
Contents	333
See Also	333
DevicePool	334
Contents	334
See Also	335
DevicePoolCompatibilityResult	336
Contents	336
See Also	336
DeviceProxy	337
Contents	337
See Also	337
DeviceSelectionConfiguration	338

Contents	338
See Also	340
DeviceSelectionResult	341
Contents	341
See Also	341
ExecutionConfiguration	342
Contents	342
See Also	343
IncompatibilityMessage	344
Contents	344
See Also	345
InstanceProfile	346
Contents	346
See Also	347
Job	348
Contents	348
See Also	352
ListTestGridProjectsRequest	353
Contents	353
See Also	353
ListTestGridSessionsRequest	354
Contents	354
See Also	355
Location	356
Contents	356
See Also	356
MonetaryAmount	357
Contents	357
See Also	357
NetworkProfile	358
Contents	358
See Also	360
Offering	361
Contents	361
See Also	362
OfferingPromotion	363

Contents	363
See Also	363
OfferingStatus	364
Contents	364
See Also	364
OfferingTransaction	366
Contents	366
See Also	367
Problem	368
Contents	368
See Also	369
ProblemDetail	371
Contents	371
See Also	371
Project	372
Contents	372
See Also	373
Radios	374
Contents	374
See Also	374
RecurringCharge	376
Contents	376
See Also	376
RemoteAccessSession	377
Contents	377
See Also	382
Resolution	384
Contents	384
See Also	384
Rule	385
Contents	385
See Also	387
Run	388
Contents	388
See Also	396
Sample	397

Contents	397
See Also	398
ScheduleRunConfiguration	399
Contents	399
See Also	401
ScheduleRunTest	402
Contents	402
See Also	404
Suite	406
Contents	406
See Also	409
Tag	410
Contents	410
See Also	410
Test	411
Contents	411
See Also	414
TestGridProject	415
Contents	415
See Also	416
TestGridSession	417
Contents	417
See Also	418
TestGridSessionAction	419
Contents	419
See Also	420
TestGridSessionArtifact	421
Contents	421
See Also	421
TestGridVpcConfig	423
Contents	423
See Also	424
TrialMinutes	425
Contents	425
See Also	425
UniqueProblem	426

Contents	426
See Also	426
Upload	427
Contents	427
See Also	431
VpcConfig	432
Contents	432
See Also	433
VPCEConfiguration	434
Contents	434
See Also	435
Common Parameters	436
Common Errors	439

Welcome

Welcome to the AWS Device Farm API documentation, which contains APIs for:

- Testing on desktop browsers

Device Farm makes it possible for you to test your web applications on desktop browsers using Selenium. The APIs for desktop browser testing contain TestGrid in their names. For more information, see [Testing Web Applications on Selenium with Device Farm](#).

- Testing on real mobile devices

Device Farm makes it possible for you to test apps on physical phones, tablets, and other devices in the cloud. For more information, see the [Device Farm Developer Guide](#).

This document was last published on August 6, 2025.

Actions

The following actions are supported:

- [CreateDevicePool](#)
- [CreateInstanceProfile](#)
- [CreateNetworkProfile](#)
- [CreateProject](#)
- [CreateRemoteAccessSession](#)
- [CreateTestGridProject](#)
- [CreateTestGridUrl](#)
- [CreateUpload](#)
- [CreateVPCEConfiguration](#)
- [DeleteDevicePool](#)
- [DeleteInstanceProfile](#)
- [DeleteNetworkProfile](#)
- [DeleteProject](#)
- [DeleteRemoteAccessSession](#)
- [DeleteRun](#)
- [DeleteTestGridProject](#)
- [DeleteUpload](#)
- [DeleteVPCEConfiguration](#)
- [GetAccountSettings](#)
- [GetDevice](#)
- [GetDeviceInstance](#)
- [GetDevicePool](#)
- [GetDevicePoolCompatibility](#)
- [GetInstanceProfile](#)
- [GetJob](#)
- [GetNetworkProfile](#)
- [GetOfferingStatus](#)

- [GetProject](#)
- [GetRemoteAccessSession](#)
- [GetRun](#)
- [GetSuite](#)
- [GetTest](#)
- [GetTestGridProject](#)
- [GetTestGridSession](#)
- [GetUpload](#)
- [GetVPCEConfiguration](#)
- [InstallToRemoteAccessSession](#)
- [ListArtifacts](#)
- [ListDeviceInstances](#)
- [ListDevicePools](#)
- [ListDevices](#)
- [ListInstanceProfiles](#)
- [ListJobs](#)
- [ListNetworkProfiles](#)
- [ListOfferingPromotions](#)
- [ListOfferings](#)
- [ListOfferingTransactions](#)
- [ListProjects](#)
- [ListRemoteAccessSessions](#)
- [ListRuns](#)
- [ListSamples](#)
- [ListSuites](#)
- [ListTagsForResource](#)
- [ListTestGridProjects](#)
- [ListTestGridSessionActions](#)
- [ListTestGridSessionArtifacts](#)
- [ListTestGridSessions](#)

- [ListTests](#)
- [ListUniqueProblems](#)
- [ListUploads](#)
- [ListVPCEConfigurations](#)
- [PurchaseOffering](#)
- [RenewOffering](#)
- [ScheduleRun](#)
- [StopJob](#)
- [StopRemoteAccessSession](#)
- [StopRun](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateDeviceInstance](#)
- [UpdateDevicePool](#)
- [UpdateInstanceProfile](#)
- [UpdateNetworkProfile](#)
- [UpdateProject](#)
- [UpdateTestGridProject](#)
- [UpdateUpload](#)
- [UpdateVPCEConfiguration](#)

CreateDevicePool

Creates a device pool.

Request Syntax

```
{
  "description": "string",
  "maxDevices": number,
  "name": "string",
  "projectArn": "string",
  "rules": [
    {
      "attribute": "string",
      "operator": "string",
      "value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

description

The device pool's description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

maxDevices

The number of devices that Device Farm can add to your device pool. Device Farm adds devices that are available and meet the criteria that you assign for the `rules` parameter. Depending on how many devices meet these constraints, your device pool might contain fewer devices than the value for this parameter.

By specifying the maximum number of devices, you can control the costs that you incur by running tests.

Type: Integer

Required: No

name

The device pool's name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

projectArn

The ARN of the project for the device pool.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: Yes

rules

The device pool's rules.

Type: Array of [Rule](#) objects

Required: Yes

Response Syntax

```
{
  "devicePool": {
    "arn": "string",
    "description": "string",
    "maxDevices": number,
```

```
  "name": "string",
  "rules": [
    {
      "attribute": "string",
      "operator": "string",
      "value": "string"
    }
  ],
  "type": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

devicePool

The newly created device pool.

Type: [DevicePool](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateInstanceProfile

Creates a profile that can be applied to one or more private fleet device instances.

Request Syntax

```
{
  "description": "string",
  "excludeAppPackagesFromCleanup": [ "string" ],
  "name": "string",
  "packageCleanup": boolean,
  "rebootAfterUse": boolean
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

description

The description of your instance profile.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

excludeAppPackagesFromCleanup

An array of strings that specifies the list of app packages that should not be cleaned up from the device after a test run.

The list of packages is considered only if you set packageCleanup to true.

Type: Array of strings

Required: No

name

The name of your instance profile.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

[packageCleanup](#)

When set to `true`, Device Farm removes app packages after a test run. The default value is `false` for private devices.

Type: Boolean

Required: No

[rebootAfterUse](#)

When set to `true`, Device Farm reboots the instance after a test run. The default value is `true`.

Type: Boolean

Required: No

Response Syntax

```
{
  "instanceProfile": {
    "arn": "string",
    "description": "string",
    "excludeAppPackagesFromCleanup": [ "string" ],
    "name": "string",
    "packageCleanup": boolean,
    "rebootAfterUse": boolean
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

instanceProfile

An object that contains information about your instance profile.

Type: [InstanceProfile](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateNetworkProfile

Creates a network profile.

Request Syntax

```
{  
  "description": "string",  
  "downlinkBandwidthBits": number,  
  "downlinkDelayMs": number,  
  "downlinkJitterMs": number,  
  "downlinkLossPercent": number,  
  "name": "string",  
  "projectArn": "string",  
  "type": "string",  
  "uplinkBandwidthBits": number,  
  "uplinkDelayMs": number,  
  "uplinkJitterMs": number,  
  "uplinkLossPercent": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

description

The description of the network profile.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

downlinkBandwidthBits

The data throughput rate in bits per second, as an integer from 0 to 104857600.

Type: Long

Required: No

[downlinkDelayMs](#)

Delay time for all packets to destination in milliseconds as an integer from 0 to 2000.

Type: Long

Required: No

[downlinkJitterMs](#)

Time variation in the delay of received packets in milliseconds as an integer from 0 to 2000.

Type: Long

Required: No

[downlinkLossPercent](#)

Proportion of received packets that fail to arrive from 0 to 100 percent.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

[name](#)

The name for the new network profile.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

[projectArn](#)

The Amazon Resource Name (ARN) of the project for which you want to create a network profile.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: Yes

type

The type of network profile to create. Valid values are listed here.

Type: String

Valid Values: CURATED | PRIVATE

Required: No

uplinkBandwidthBits

The data throughput rate in bits per second, as an integer from 0 to 104857600.

Type: Long

Required: No

uplinkDelayMs

Delay time for all packets to destination in milliseconds as an integer from 0 to 2000.

Type: Long

Required: No

uplinkJitterMs

Time variation in the delay of received packets in milliseconds as an integer from 0 to 2000.

Type: Long

Required: No

uplinkLossPercent

Proportion of transmitted packets that fail to arrive from 0 to 100 percent.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

Response Syntax

```
{
  "networkProfile": {
    "arn": "string",
    "description": "string",
    "downlinkBandwidthBits": number,
    "downlinkDelayMs": number,
    "downlinkJitterMs": number,
    "downlinkLossPercent": number,
    "name": "string",
    "type": "string",
    "uplinkBandwidthBits": number,
    "uplinkDelayMs": number,
    "uplinkJitterMs": number,
    "uplinkLossPercent": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

networkProfile

The network profile that is returned by the create network profile request.

Type: [NetworkProfile](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateProject

Creates a project.

Request Syntax

```
{  
  "defaultJobTimeoutMinutes": number,  
  "name": "string",  
  "vpcConfig": {  
    "securityGroupIds": [ "string" ],  
    "subnetIds": [ "string" ],  
    "vpcId": "string"  
  }  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

defaultJobTimeoutMinutes

Sets the execution timeout value (in minutes) for a project. All test runs in this project use the specified execution timeout value unless overridden when scheduling a run.

Type: Integer

Required: No

name

The project's name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

vpcConfig

The VPC security groups and subnets that are attached to a project.

Type: [VpcConfig](#) object

Required: No

Response Syntax

```
{
  "project": {
    "arn": "string",
    "created": number,
    "defaultJobTimeoutMinutes": number,
    "name": "string",
    "vpcConfig": {
      "securityGroupIds": [ "string" ],
      "subnetIds": [ "string" ],
      "vpcId": "string"
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[project](#)

The newly created project.

Type: [Project](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

TagOperationException

The operation was not successful. Try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateRemoteAccessSession

Specifies and starts a remote access session.

Request Syntax

```
{
  "clientId": "string",
  "configuration": {
    "billingMethod": "string",
    "deviceProxy": {
      "host": "string",
      "port": number
    },
    "vpceConfigurationArns": [ "string" ]
  },
  "deviceArn": "string",
  "instanceArn": "string",
  "interactionMode": "string",
  "name": "string",
  "projectArn": "string",
  "remoteDebugEnabled": boolean,
  "remoteRecordAppArn": "string",
  "remoteRecordEnabled": boolean,
  "skipAppResign": boolean,
  "sshPublicKey": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

clientId

Unique identifier for the client. If you want access to multiple devices on the same client, you should pass the same `clientId` value in each call to `CreateRemoteAccessSession`. This identifier is required only if `remoteDebugEnabled` is set to `true`.

Remote debugging is [no longer supported](#).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 64.

Required: No

configuration

The configuration information for the remote access session request.

Type: [CreateRemoteAccessSessionConfiguration](#) object

Required: No

deviceArn

The ARN of the device for which you want to create a remote access session.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: Yes

instanceArn

The Amazon Resource Name (ARN) of the device instance for which you want to create a remote access session.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

interactionMode

The interaction mode of the remote access session. Valid values are:

- **INTERACTIVE:** You can interact with the iOS device by viewing, touching, and rotating the screen. You cannot run XCUITest framework-based tests in this mode.

- **NO_VIDEO**: You are connected to the device, but cannot interact with it or view the screen. This mode has the fastest test execution speed. You can run XCUITest framework-based tests in this mode.
- **VIDEO_ONLY**: You can view the screen, but cannot touch or rotate it. You can run XCUITest framework-based tests and watch the screen in this mode.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 64.

Valid Values: INTERACTIVE | NO_VIDEO | VIDEO_ONLY

Required: No

name

The name of the remote access session to create.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

projectArn

The Amazon Resource Name (ARN) of the project for which you want to create a remote access session.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*

Required: Yes

remoteDebugEnabled

Set to `true` if you want to access devices remotely for debugging in your remote access session.

Remote debugging is [no longer supported](#).

Type: Boolean

Required: No

remoteRecordAppArn

The Amazon Resource Name (ARN) for the app to be recorded in the remote access session.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

remoteRecordEnabled

Set to `true` to enable remote recording for the remote access session.

Type: Boolean

Required: No

skipAppResign

When set to `true`, for private devices, Device Farm does not sign your app again. For public devices, Device Farm always signs your apps again.

For more information on how Device Farm modifies your uploads during tests, see [Do you modify my app?](#)

Type: Boolean

Required: No

sshPublicKey

Ignored. The public key of the ssh key pair you want to use for connecting to remote devices in your remote debugging session. This key is required only if `remoteDebugEnabled` is set to `true`.

Remote debugging is [no longer supported](#).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 8192.

Required: No

Response Syntax

```
{
  "remoteAccessSession": {
    "arn": "string",
    "billingMethod": "string",
    "clientId": "string",
    "created": number,
    "device": {
      "arn": "string",
      "availability": "string",
      "carrier": "string",
      "cpu": {
        "architecture": "string",
        "clock": number,
        "frequency": "string"
      },
      "fleetName": "string",
      "fleetType": "string",
      "formFactor": "string",
      "heapSize": number,
      "image": "string",
      "instances": [
        {
          "arn": "string",
          "deviceArn": "string",
          "instanceProfile": {
            "arn": "string",
            "description": "string",
            "excludeAppPackagesFromCleanup": [ "string" ],
            "name": "string",
            "packageCleanup": boolean,
            "rebootAfterUse": boolean
          },
          "labels": [ "string" ],
          "status": "string",
          "udid": "string"
        }
      ],
      "manufacturer": "string",
      "memory": number,
      "model": "string",
      "modelId": "string",
```

```
    "name": "string",
    "os": "string",
    "platform": "string",
    "radio": "string",
    "remoteAccessEnabled": boolean,
    "remoteDebugEnabled": boolean,
    "resolution": {
      "height": number,
      "width": number
    }
  },
  "deviceMinutes": {
    "metered": number,
    "total": number,
    "unmetered": number
  },
  "deviceProxy": {
    "host": "string",
    "port": number
  },
  "deviceUdid": "string",
  "endpoint": "string",
  "hostAddress": "string",
  "instanceArn": "string",
  "interactionMode": "string",
  "message": "string",
  "name": "string",
  "remoteDebugEnabled": boolean,
  "remoteRecordAppArn": "string",
  "remoteRecordEnabled": boolean,
  "result": "string",
  "skipAppResign": boolean,
  "started": number,
  "status": "string",
  "stopped": number,
  "vpcConfig": {
    "securityGroupIds": [ "string" ],
    "subnetIds": [ "string" ],
    "vpcId": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

remoteAccessSession

A container that describes the remote access session when the request to create a remote access session is sent.

Type: [RemoteAccessSession](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateTestGridProject

Creates a Selenium testing project. Projects are used to track [TestGridSession](#) instances.

Request Syntax

```
{
  "description": "string",
  "name": "string",
  "vpcConfig": {
    "securityGroupIds": [ "string" ],
    "subnetIds": [ "string" ],
    "vpcId": "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[description](#)

Human-readable description of the project.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `.*\S.*`

Required: No

[name](#)

Human-readable name of the Selenium testing project.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `.*\S.*`

Required: Yes

vpcConfig

The VPC security groups and subnets that are attached to a project.

Type: [TestGridVpcConfig](#) object

Required: No

Response Syntax

```
{
  "testGridProject": {
    "arn": "string",
    "created": number,
    "description": "string",
    "name": "string",
    "vpcConfig": {
      "securityGroupIds": [ "string" ],
      "subnetIds": [ "string" ],
      "vpcId": "string"
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

testGridProject

ARN of the Selenium testing project that was created.

Type: [TestGridProject](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

InternalServiceException

An internal exception was raised in the service. Contact aws-devicefarm-support@amazon.com if you see this error.

HTTP Status Code: 500

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateTestGridUrl

Creates a signed, short-term URL that can be passed to a Selenium RemoteWebDriver constructor.

Request Syntax

```
{  
  "expiresInSeconds": number,  
  "projectArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

expiresInSeconds

Lifetime, in seconds, of the URL.

Type: Integer

Valid Range: Minimum value of 60. Maximum value of 86400.

Required: Yes

projectArn

ARN (from [CreateTestGridProject](#) or [ListTestGridProjects](#)) to associate with the short-term URL.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{
```

```
"expires": number,  
"url": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[expires](#)

The number of seconds the URL from [CreateTestGridUrl:url](#) stays active.

Type: Timestamp

[url](#)

A signed URL, expiring in [CreateTestGridUrl:expiresInSeconds](#) seconds, to be passed to a RemoteWebDriver.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

InternalServiceException

An internal exception was raised in the service. Contact aws-devicefarm-support@amazon.com if you see this error.

HTTP Status Code: 500

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateUpload

Uploads an app or test scripts.

Request Syntax

```
{  
  "contentType": "string",  
  "name": "string",  
  "projectArn": "string",  
  "type": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

contentType

The upload's content type (for example, `application/octet-stream`).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 64.

Required: No

name

The upload's file name. The name should not contain any forward slashes (/). If you are uploading an iOS app, the file name must end with the `.ipa` extension. If you are uploading an Android app, the file name must end with the `.apk` extension. For all others, the file name must end with the `.zip` file extension.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

projectArn

The ARN of the project for the upload.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: Yes

type

The upload's upload type.

Must be one of the following values:

- ANDROID_APP
- IOS_APP
- WEB_APP
- EXTERNAL_DATA
- APPIUM_JAVA_JUNIT_TEST_PACKAGE
- APPIUM_JAVA_TESTNG_TEST_PACKAGE
- APPIUM_PYTHON_TEST_PACKAGE
- APPIUM_NODE_TEST_PACKAGE
- APPIUM_RUBY_TEST_PACKAGE
- APPIUM_WEB_JAVA_JUNIT_TEST_PACKAGE
- APPIUM_WEB_JAVA_TESTNG_TEST_PACKAGE
- APPIUM_WEB_PYTHON_TEST_PACKAGE
- APPIUM_WEB_NODE_TEST_PACKAGE
- APPIUM_WEB_RUBY_TEST_PACKAGE
- INSTRUMENTATION_TEST_PACKAGE
- XCTEST_TEST_PACKAGE
- XCTEST_UI_TEST_PACKAGE

- `APPIUM_JAVA_JUNIT_TEST_SPEC`
- `APPIUM_JAVA_TESTNG_TEST_SPEC`
- `APPIUM_PYTHON_TEST_SPEC`
- `APPIUM_NODE_TEST_SPEC`
- `APPIUM_RUBY_TEST_SPEC`
- `APPIUM_WEB_JAVA_JUNIT_TEST_SPEC`
- `APPIUM_WEB_JAVA_TESTNG_TEST_SPEC`
- `APPIUM_WEB_PYTHON_TEST_SPEC`
- `APPIUM_WEB_NODE_TEST_SPEC`
- `APPIUM_WEB_RUBY_TEST_SPEC`
- `INSTRUMENTATION_TEST_SPEC`
- `XCTEST_UI_TEST_SPEC`

If you call `CreateUpload` with `WEB_APP` specified, AWS Device Farm throws an `ArgumentException` error.

Type: String

Valid Values: `ANDROID_APP` | `IOS_APP` | `WEB_APP` | `EXTERNAL_DATA` | `APPIUM_JAVA_JUNIT_TEST_PACKAGE` | `APPIUM_JAVA_TESTNG_TEST_PACKAGE` | `APPIUM_PYTHON_TEST_PACKAGE` | `APPIUM_NODE_TEST_PACKAGE` | `APPIUM_RUBY_TEST_PACKAGE` | `APPIUM_WEB_JAVA_JUNIT_TEST_PACKAGE` | `APPIUM_WEB_JAVA_TESTNG_TEST_PACKAGE` | `APPIUM_WEB_PYTHON_TEST_PACKAGE` | `APPIUM_WEB_NODE_TEST_PACKAGE` | `APPIUM_WEB_RUBY_TEST_PACKAGE` | `CALABASH_TEST_PACKAGE` | `INSTRUMENTATION_TEST_PACKAGE` | `UIAUTOMATION_TEST_PACKAGE` | `UIAUTOMATOR_TEST_PACKAGE` | `XCTEST_TEST_PACKAGE` | `XCTEST_UI_TEST_PACKAGE` | `APPIUM_JAVA_JUNIT_TEST_SPEC` | `APPIUM_JAVA_TESTNG_TEST_SPEC` | `APPIUM_PYTHON_TEST_SPEC` | `APPIUM_NODE_TEST_SPEC` | `APPIUM_RUBY_TEST_SPEC` | `APPIUM_WEB_JAVA_JUNIT_TEST_SPEC` | `APPIUM_WEB_JAVA_TESTNG_TEST_SPEC` | `APPIUM_WEB_PYTHON_TEST_SPEC` | `APPIUM_WEB_NODE_TEST_SPEC` | `APPIUM_WEB_RUBY_TEST_SPEC` | `INSTRUMENTATION_TEST_SPEC` | `XCTEST_UI_TEST_SPEC`

Required: Yes

Response Syntax

```
{
  "upload": {
    "arn": "string",
    "category": "string",
    "contentType": "string",
    "created": number,
    "message": "string",
    "metadata": "string",
    "name": "string",
    "status": "string",
    "type": "string",
    "url": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

upload

The newly created upload.

Type: [Upload](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateVPCEConfiguration

Creates a configuration record in Device Farm for your Amazon Virtual Private Cloud (VPC) endpoint.

Request Syntax

```
{  
  "serviceDnsName": "string",  
  "vpceConfigurationDescription": "string",  
  "vpceConfigurationName": "string",  
  "vpceServiceName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[serviceDnsName](#)

The DNS name of the service running in your VPC that you want Device Farm to test.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: Yes

[vpceConfigurationDescription](#)

An optional description that provides details about your VPC endpoint configuration.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

[vpceConfigurationName](#)

The friendly name you give to your VPC endpoint configuration, to manage your configurations more easily.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: Yes

vpceServiceName

The name of the VPC endpoint service running in your AWS account that you want Device Farm to test.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: Yes

Response Syntax

```
{
  "vpceConfiguration": {
    "arn": "string",
    "serviceDnsName": "string",
    "vpceConfigurationDescription": "string",
    "vpceConfigurationName": "string",
    "vpceServiceName": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

vpceConfiguration

An object that contains information about your VPC endpoint configuration.

Type: VPCEConfiguration object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteDevicePool

Deletes a device pool given the pool ARN. Does not allow deletion of curated pools owned by the system.

Request Syntax

```
{
  "arn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

Represents the Amazon Resource Name (ARN) of the Device Farm device pool to delete.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteInstanceProfile

Deletes a profile that can be applied to one or more private device instances.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the instance profile you are requesting to delete.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteNetworkProfile

Deletes a network profile.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The ARN of the network profile to delete.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteProject

Deletes an AWS Device Farm project, given the project ARN.

Deleting this resource does not stop an in-progress run.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

Represents the Amazon Resource Name (ARN) of the Device Farm project to delete.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteRemoteAccessSession

Deletes a completed remote access session and its results.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the session for which you want to delete remote access.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteRun

Deletes the run, given the run ARN.

Deleting this resource does not stop an in-progress run.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) for the run to delete.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteTestGridProject

Deletes a Selenium testing project and all content generated under it.

Important

You cannot undo this operation.

Note

You cannot delete a project if it has active sessions.

Request Syntax

```
{  
  "projectArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

projectArn

The ARN of the project to delete, from [CreateTestGridProject](#) or [ListTestGridProjects](#).

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

CannotDeleteException

The requested object could not be deleted.

HTTP Status Code: 400

InternalServiceException

An internal exception was raised in the service. Contact aws-devicefarm-support@amazon.com if you see this error.

HTTP Status Code: 500

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteUpload

Deletes an upload given the upload ARN.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

Represents the Amazon Resource Name (ARN) of the Device Farm upload to delete.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteVPCEConfiguration

Deletes a configuration for your Amazon Virtual Private Cloud (VPC) endpoint.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the VPC endpoint configuration you want to delete.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

InvalidOperationException

There was an error with the update request, or you do not have sufficient permissions to update this VPC endpoint configuration.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetAccountSettings

Returns the number of unmetered iOS or unmetered Android devices that have been purchased by the account.

Response Syntax

```
{
  "accountSettings": {
    "awsAccountNumber": "string",
    "defaultJobTimeoutMinutes": number,
    "maxJobTimeoutMinutes": number,
    "maxSlots": {
      "string" : number
    },
    "skipAppResign": boolean,
    "trialMinutes": {
      "remaining": number,
      "total": number
    },
    "unmeteredDevices": {
      "string" : number
    },
    "unmeteredRemoteAccessDevices": {
      "string" : number
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

accountSettings

The account settings.

Type: [AccountSettings](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetDevice

Gets information about a unique device type.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The device type's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "device": {  
    "arn": "string",  
    "availability": "string",  
    "carrier": "string",  
    "cpu": {  
      "architecture": "string",  
      "clock": number,  
      "frequency": "string"  
    },  
    "fleetName": "string",  
  },  
}
```

```

    "fleetType": "string",
    "formFactor": "string",
    "heapSize": number,
    "image": "string",
    "instances": [
      {
        "arn": "string",
        "deviceArn": "string",
        "instanceProfile": {
          "arn": "string",
          "description": "string",
          "excludeAppPackagesFromCleanup": [ "string" ],
          "name": "string",
          "packageCleanup": boolean,
          "rebootAfterUse": boolean
        },
        "labels": [ "string" ],
        "status": "string",
        "udid": "string"
      }
    ],
    "manufacturer": "string",
    "memory": number,
    "model": "string",
    "modelId": "string",
    "name": "string",
    "os": "string",
    "platform": "string",
    "radio": "string",
    "remoteAccessEnabled": boolean,
    "remoteDebugEnabled": boolean,
    "resolution": {
      "height": number,
      "width": number
    }
  }
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

device

An object that contains information about the requested device.

Type: [Device](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetDeviceInstance

Returns information about a device instance that belongs to a private device fleet.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the instance you're requesting information about.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "deviceInstance": {  
    "arn": "string",  
    "deviceArn": "string",  
    "instanceProfile": {  
      "arn": "string",  
      "description": "string",  
      "excludeAppPackagesFromCleanup": [ "string" ],  
      "name": "string",  
      "packageCleanup": boolean,  
      "rebootAfterUse": boolean  
    }  
  }  
}
```

```
    },  
    "labels": [ "string" ],  
    "status": "string",  
    "udid": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

deviceInstance

An object that contains information about your device instance.

Type: [DeviceInstance](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetDevicePool

Gets information about a device pool.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The device pool's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*

Required: Yes

Response Syntax

```
{  
  "devicePool": {  
    "arn": "string",  
    "description": "string",  
    "maxDevices": number,  
    "name": "string",  
    "rules": [  
      {  
        "attribute": "string",  
        "operator": "string",
```

```
        "value": "string"
      },
    ],
    "type": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

devicePool

An object that contains information about the requested device pool.

Type: [DevicePool](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetDevicePoolCompatibility

Gets information about compatibility with a device pool.

Request Syntax

```
{  
  "appArn": "string",  
  "configuration": {  
    "auxiliaryApps": [ "string" ],  
    "billingMethod": "string",  
    "customerArtifactPaths": {  
      "androidPaths": [ "string" ],  
      "deviceHostPaths": [ "string" ],  
      "iosPaths": [ "string" ]  
    },  
    "deviceProxy": {  
      "host": "string",  
      "port": number  
    },  
    "extraDataPackageArn": "string",  
    "locale": "string",  
    "location": {  
      "latitude": number,  
      "longitude": number  
    },  
    "networkProfileArn": "string",  
    "radios": {  
      "bluetooth": boolean,  
      "gps": boolean,  
      "nfc": boolean,  
      "wifi": boolean  
    },  
    "vpceConfigurationArns": [ "string" ]  
  },  
  "devicePoolArn": "string",  
  "projectArn": "string",  
  "test": {  
    "filter": "string",  
    "parameters": {  
      "string": "string"  
    },  
    "testPackageArn": "string",  
  },  
}
```

```
    "testSpecArn": "string",  
    "type": "string"  
  },  
  "testType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[appArn](#)

The ARN of the app that is associated with the specified device pool.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

[configuration](#)

An object that contains information about the settings for a run.

Type: [ScheduleRunConfiguration](#) object

Required: No

[devicePoolArn](#)

The device pool's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: Yes

[projectArn](#)

The ARN of the project for which you want to check device pool compatibility.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*+`

Required: No

test

Information about the uploaded test to be run against the device pool.

Type: [ScheduleRunTest](#) object

Required: No

testType

The test type for the specified device pool.

Allowed values include the following:

- BUILTIN_FUZZ.
- APPIUM_JAVA_JUNIT.
- APPIUM_JAVA_TESTNG.
- APPIUM_PYTHON.
- APPIUM_NODE.
- APPIUM_RUBY.
- APPIUM_WEB_JAVA_JUNIT.
- APPIUM_WEB_JAVA_TESTNG.
- APPIUM_WEB_PYTHON.
- APPIUM_WEB_NODE.
- APPIUM_WEB_RUBY.
- INSTRUMENTATION.
- XCTEST.
- XCTEST_UI.

Type: String

Valid Values: BUILTIN_FUZZ | APPIUM_JAVA_JUNIT | APPIUM_JAVA_TESTNG | APPIUM_PYTHON | APPIUM_NODE | APPIUM_RUBY | APPIUM_WEB_JAVA_JUNIT | APPIUM_WEB_JAVA_TESTNG | APPIUM_WEB_PYTHON | APPIUM_WEB_NODE | APPIUM_WEB_RUBY | INSTRUMENTATION | XCTEST | XCTEST_UI

Required: No

Response Syntax

```
{
  "compatibleDevices": [
    {
      "compatible": boolean,
      "device": {
        "arn": "string",
        "availability": "string",
        "carrier": "string",
        "cpu": {
          "architecture": "string",
          "clock": number,
          "frequency": "string"
        },
        "fleetName": "string",
        "fleetType": "string",
        "formFactor": "string",
        "heapSize": number,
        "image": "string",
        "instances": [
          {
            "arn": "string",
            "deviceArn": "string",
            "instanceProfile": {
              "arn": "string",
              "description": "string",
              "excludeAppPackagesFromCleanup": [ "string" ],
              "name": "string",
              "packageCleanup": boolean,
              "rebootAfterUse": boolean
            },
            "labels": [ "string" ],
            "status": "string",
            "udid": "string"
          }
        ]
      }
    }
  ]
}
```

```

    }
  ],
  "manufacturer": "string",
  "memory": number,
  "model": "string",
  "modelId": "string",
  "name": "string",
  "os": "string",
  "platform": "string",
  "radio": "string",
  "remoteAccessEnabled": boolean,
  "remoteDebugEnabled": boolean,
  "resolution": {
    "height": number,
    "width": number
  }
},
"incompatibilityMessages": [
  {
    "message": "string",
    "type": "string"
  }
]
}
],
"incompatibleDevices": [
  {
    "compatible": boolean,
    "device": {
      "arn": "string",
      "availability": "string",
      "carrier": "string",
      "cpu": {
        "architecture": "string",
        "clock": number,
        "frequency": "string"
      },
      "fleetName": "string",
      "fleetType": "string",
      "formFactor": "string",
      "heapSize": number,
      "image": "string",
      "instances": [
        {

```

```

        "arn": "string",
        "deviceArn": "string",
        "instanceProfile": {
            "arn": "string",
            "description": "string",
            "excludeAppPackagesFromCleanup": [ "string" ],
            "name": "string",
            "packageCleanup": boolean,
            "rebootAfterUse": boolean
        },
        "labels": [ "string" ],
        "status": "string",
        "udid": "string"
    }
],
"manufacturer": "string",
"memory": number,
"model": "string",
"modelId": "string",
"name": "string",
"os": "string",
"platform": "string",
"radio": "string",
"remoteAccessEnabled": boolean,
"remoteDebugEnabled": boolean,
"resolution": {
    "height": number,
    "width": number
}
},
"incompatibilityMessages": [
    {
        "message": "string",
        "type": "string"
    }
]
}
]
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[compatibleDevices](#)

Information about compatible devices.

Type: Array of [DevicePoolCompatibilityResult](#) objects

[incompatibleDevices](#)

Information about incompatible devices.

Type: Array of [DevicePoolCompatibilityResult](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetInstanceProfile

Returns information about the specified instance profile.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of an instance profile.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "instanceProfile": {  
    "arn": "string",  
    "description": "string",  
    "excludeAppPackagesFromCleanup": [ "string" ],  
    "name": "string",  
    "packageCleanup": boolean,  
    "rebootAfterUse": boolean  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

instanceProfile

An object that contains information about an instance profile.

Type: [InstanceProfile](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetJob

Gets information about a job.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[arn](#)

The job's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "job": {  
    "arn": "string",  
    "counters": {  
      "errored": number,  
      "failed": number,  
      "passed": number,  
      "skipped": number,  
      "stopped": number,  
      "total": number,  
      "warned": number  
    },  
  },  
}
```

```
"created": number,
"device": {
  "arn": "string",
  "availability": "string",
  "carrier": "string",
  "cpu": {
    "architecture": "string",
    "clock": number,
    "frequency": "string"
  },
  "fleetName": "string",
  "fleetType": "string",
  "formFactor": "string",
  "heapSize": number,
  "image": "string",
  "instances": [
    {
      "arn": "string",
      "deviceArn": "string",
      "instanceProfile": {
        "arn": "string",
        "description": "string",
        "excludeAppPackagesFromCleanup": [ "string" ],
        "name": "string",
        "packageCleanup": boolean,
        "rebootAfterUse": boolean
      },
      "labels": [ "string" ],
      "status": "string",
      "udid": "string"
    }
  ],
  "manufacturer": "string",
  "memory": number,
  "model": "string",
  "modelId": "string",
  "name": "string",
  "os": "string",
  "platform": "string",
  "radio": "string",
  "remoteAccessEnabled": boolean,
  "remoteDebugEnabled": boolean,
  "resolution": {
    "height": number,
```

```
        "width": number
    },
    "deviceMinutes": {
        "metered": number,
        "total": number,
        "unmetered": number
    },
    "instanceArn": "string",
    "message": "string",
    "name": "string",
    "result": "string",
    "started": number,
    "status": "string",
    "stopped": number,
    "type": "string",
    "videoCapture": boolean,
    "videoEndpoint": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

job

An object that contains information about the requested job.

Type: [Job](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetNetworkProfile

Returns information about a network profile.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The ARN of the network profile to return information about.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "networkProfile": {  
    "arn": "string",  
    "description": "string",  
    "downloadBandwidthBits": number,  
    "downloadDelayMs": number,  
    "downloadJitterMs": number,  
    "downloadLossPercent": number,  
    "name": "string",  
    "type": "string",  
  }  
}
```

```
"uplinkBandwidthBits": number,  
"uplinkDelayMs": number,  
"uplinkJitterMs": number,  
"uplinkLossPercent": number  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

networkProfile

The network profile.

Type: [NetworkProfile](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetOfferingStatus

Gets the current status and future status of all offerings purchased by an AWS account. The response indicates how many offerings are currently available and the offerings that will be available in the next period. The API returns a `NotEligible` error if the user is not permitted to invoke the operation. If you must be able to invoke this operation, contact aws-devicefarm-support@amazon.com.

Request Syntax

```
{  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{  
  "current": {  
    "string" : {  
      "effectiveOn": number,  
      "offering": {  
        "description": "string",  
        "id": "string",  
        "platform": "string",
```

```

    "recurringCharges": [
      {
        "cost": {
          "amount": number,
          "currencyCode": "string"
        },
        "frequency": "string"
      }
    ],
    "type": "string"
  },
  "quantity": number,
  "type": "string"
}
},
"nextPeriod": {
  "string" : {
    "effectiveOn": number,
    "offering": {
      "description": "string",
      "id": "string",
      "platform": "string",
      "recurringCharges": [
        {
          "cost": {
            "amount": number,
            "currencyCode": "string"
          },
          "frequency": "string"
        }
      ],
      "type": "string"
    },
    "quantity": number,
    "type": "string"
  }
},
"nextToken": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

current

When specified, gets the offering status for the current period.

Type: String to [OfferingStatus](#) object map

Key Length Constraints: Minimum length of 32.

nextPeriod

When specified, gets the offering status for the next period.

Type: String to [OfferingStatus](#) object map

Key Length Constraints: Minimum length of 32.

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotEligibleException

Exception gets thrown when a user is not eligible to perform the specified transaction.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

Examples

Example

The following example checks the current and renewal status.

Sample Response

```
{
  "current": {
    "offering-id-ios": {
      "offering": {
        "platform": "IOS",
        "type": "RECURRING",
        "id": "offering-id-ios",
        "description": "iOS Unmetered Device Slot"
      },
      "quantity": 1
    }
  },
  "nextPeriod": {
    "offering-id-ios": {
      "effectiveOn": 1459468800.0,
      "offering": {
        "platform": "IOS",
        "type": "RECURRING",
        "id": "offering-id-ios",
        "description": "iOS Unmetered Device Slot"
      },
      "quantity": 1
    }
  }
}
```

```
    }  
  }  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetProject

Gets information about a project.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The project's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "project": {  
    "arn": "string",  
    "created": number,  
    "defaultJobTimeoutMinutes": number,  
    "name": "string",  
    "vpcConfig": {  
      "securityGroupIds": [ "string" ],  
      "subnetIds": [ "string" ],  
      "vpcId": "string"  
    }  
  }  
}
```

```
}  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

project

The project to get information about.

Type: [Project](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetRemoteAccessSession

Returns a link to a currently running remote access session.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the remote access session about which you want to get session information.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "remoteAccessSession": {  
    "arn": "string",  
    "billingMethod": "string",  
    "clientId": "string",  
    "created": number,  
    "device": {  
      "arn": "string",  
      "availability": "string",  
      "carrier": "string",  
      "cpu": {
```

```

    "architecture": "string",
    "clock": number,
    "frequency": "string"
  },
  "fleetName": "string",
  "fleetType": "string",
  "formFactor": "string",
  "heapSize": number,
  "image": "string",
  "instances": [
    {
      "arn": "string",
      "deviceArn": "string",
      "instanceProfile": {
        "arn": "string",
        "description": "string",
        "excludeAppPackagesFromCleanup": [ "string" ],
        "name": "string",
        "packageCleanup": boolean,
        "rebootAfterUse": boolean
      },
      "labels": [ "string" ],
      "status": "string",
      "udid": "string"
    }
  ],
  "manufacturer": "string",
  "memory": number,
  "model": "string",
  "modelId": "string",
  "name": "string",
  "os": "string",
  "platform": "string",
  "radio": "string",
  "remoteAccessEnabled": boolean,
  "remoteDebugEnabled": boolean,
  "resolution": {
    "height": number,
    "width": number
  }
},
"deviceMinutes": {
  "metered": number,
  "total": number,

```

```
    "unmetered": number
  },
  "deviceProxy": {
    "host": "string",
    "port": number
  },
  "deviceUdid": "string",
  "endpoint": "string",
  "hostAddress": "string",
  "instanceArn": "string",
  "interactionMode": "string",
  "message": "string",
  "name": "string",
  "remoteDebugEnabled": boolean,
  "remoteRecordAppArn": "string",
  "remoteRecordEnabled": boolean,
  "result": "string",
  "skipAppResign": boolean,
  "started": number,
  "status": "string",
  "stopped": number,
  "vpcConfig": {
    "securityGroupIds": [ "string" ],
    "subnetIds": [ "string" ],
    "vpcId": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[remoteAccessSession](#)

A container that lists detailed information about the remote access session.

Type: [RemoteAccessSession](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetRun

Gets information about a run.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The run's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "run": {  
    "appUpload": "string",  
    "arn": "string",  
    "billingMethod": "string",  
    "completedJobs": number,  
    "counters": {  
      "errored": number,  
      "failed": number,  
      "passed": number,  
      "skipped": number,  
      "stopped": number,  
    }  
  }  
}
```

```
    "total": number,
    "warned": number
  },
  "created": number,
  "customerArtifactPaths": {
    "androidPaths": [ "string" ],
    "deviceHostPaths": [ "string" ],
    "iosPaths": [ "string" ]
  },
  "deviceMinutes": {
    "metered": number,
    "total": number,
    "unmetered": number
  },
  "devicePoolArn": "string",
  "deviceProxy": {
    "host": "string",
    "port": number
  },
  "deviceSelectionResult": {
    "filters": [
      {
        "attribute": "string",
        "operator": "string",
        "values": [ "string" ]
      }
    ],
    "matchedDevicesCount": number,
    "maxDevices": number
  },
  "eventCount": number,
  "jobTimeoutMinutes": number,
  "locale": "string",
  "location": {
    "latitude": number,
    "longitude": number
  },
  "message": "string",
  "name": "string",
  "networkProfile": {
    "arn": "string",
    "description": "string",
    "downlinkBandwidthBits": number,
    "downlinkDelayMs": number,
```

```

    "downlinkJitterMs": number,
    "downlinkLossPercent": number,
    "name": "string",
    "type": "string",
    "uplinkBandwidthBits": number,
    "uplinkDelayMs": number,
    "uplinkJitterMs": number,
    "uplinkLossPercent": number
  },
  "parsingResultUrl": "string",
  "platform": "string",
  "radios": {
    "bluetooth": boolean,
    "gps": boolean,
    "nfc": boolean,
    "wifi": boolean
  },
  "result": "string",
  "resultCode": "string",
  "seed": number,
  "skipAppResign": boolean,
  "started": number,
  "status": "string",
  "stopped": number,
  "testSpecArn": "string",
  "totalJobs": number,
  "type": "string",
  "vpcConfig": {
    "securityGroupIds": [ "string" ],
    "subnetIds": [ "string" ],
    "vpcId": "string"
  },
  "webUrl": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[run](#)

The run to get results from.

Type: [Run](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetSuite

Gets information about a suite.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The suite's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "suite": {  
    "arn": "string",  
    "counters": {  
      "errored": number,  
      "failed": number,  
      "passed": number,  
      "skipped": number,  
      "stopped": number,  
      "total": number,  
    }  
  }  
}
```

```
    "warned": number
  },
  "created": number,
  "deviceMinutes": {
    "metered": number,
    "total": number,
    "unmetered": number
  },
  "message": "string",
  "name": "string",
  "result": "string",
  "started": number,
  "status": "string",
  "stopped": number,
  "type": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

suite

A collection of one or more tests.

Type: [Suite](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTest

Gets information about a test.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The test's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "test": {  
    "arn": "string",  
    "counters": {  
      "errored": number,  
      "failed": number,  
      "passed": number,  
      "skipped": number,  
      "stopped": number,  
      "total": number,  
    }  
  }  
}
```

```
    "warned": number
  },
  "created": number,
  "deviceMinutes": {
    "metered": number,
    "total": number,
    "unmetered": number
  },
  "message": "string",
  "name": "string",
  "result": "string",
  "started": number,
  "status": "string",
  "stopped": number,
  "type": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

test

A test condition that is evaluated.

Type: [Test](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTestGridProject

Retrieves information about a Selenium testing project.

Request Syntax

```
{  
  "projectArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[projectArn](#)

The ARN of the Selenium testing project, from either [CreateTestGridProject](#) or [ListTestGridProjects](#).

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "testGridProject": {  
    "arn": "string",  
    "created": number,  
    "description": "string",  
    "name": "string",  
    "vpcConfig": {  
      "securityGroupIds": [ "string" ],  
      "subnetIds": [ "string" ],  
      "vpcId": "string"  
    }  
  }  
}
```

```
}  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

testGridProject

A [TestGridProject](#).

Type: [TestGridProject](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

InternalServiceException

An internal exception was raised in the service. Contact aws-devicefarm-support@amazon.com if you see this error.

HTTP Status Code: 500

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTestGridSession

A session is an instance of a browser created through a `RemoteWebDriver` with the URL from [CreateTestGridUrl:url](#). You can use the following to look up sessions:

- The session ARN ([GetTestGridSession:sessionArn](#)).
- The project ARN and a session ID ([GetTestGridSession:projectArn](#) and [GetTestGridSession:sessionId](#)).

Request Syntax

```
{  
  "projectArn": "string",  
  "sessionArn": "string",  
  "sessionId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[projectArn](#)

The ARN for the project that this session belongs to. See [CreateTestGridProject](#) and [ListTestGridProjects](#).

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

[sessionArn](#)

An ARN that uniquely identifies a [TestGridSession](#).

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

sessionId

An ID associated with this session.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `.*\S.*`

Required: No

Response Syntax

```
{
  "testGridSession": {
    "arn": "string",
    "billingMinutes": number,
    "created": number,
    "ended": number,
    "seleniumProperties": "string",
    "status": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

testGridSession

The [TestGridSession](#) that was requested.

Type: [TestGridSession](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

InternalServiceException

An internal exception was raised in the service. Contact aws-devicefarm-support@amazon.com if you see this error.

HTTP Status Code: 500

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

GetUpload

Gets information about an upload.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The upload's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "upload": {  
    "arn": "string",  
    "category": "string",  
    "contentType": "string",  
    "created": number,  
    "message": "string",  
    "metadata": "string",  
    "name": "string",  
    "status": "string",
```

```
    "type": "string",  
    "url": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

upload

An app or a set of one or more tests to upload or that have been uploaded.

Type: Upload object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetVPCEConfiguration

Returns information about the configuration settings for your Amazon Virtual Private Cloud (VPC) endpoint.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the VPC endpoint configuration you want to describe.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*

Required: Yes

Response Syntax

```
{  
  "vpceConfiguration": {  
    "arn": "string",  
    "serviceDnsName": "string",  
    "vpceConfigurationDescription": "string",  
    "vpceConfigurationName": "string",  
    "vpceServiceName": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[vpceConfiguration](#)

An object that contains information about your VPC endpoint configuration.

Type: [VPCEConfiguration](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

InstallToRemoteAccessSession

Installs an application to the device in a remote access session. For Android applications, the file must be in .apk format. For iOS applications, the file must be in .ipa format.

Request Syntax

```
{  
  "appArn": "string",  
  "remoteAccessSessionArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

appArn

The ARN of the app about which you are requesting information.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: Yes

remoteAccessSessionArn

The Amazon Resource Name (ARN) of the remote access session about which you are requesting information.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: Yes

Response Syntax

```
{
  "appUpload": {
    "arn": "string",
    "category": "string",
    "contentType": "string",
    "created": number,
    "message": "string",
    "metadata": "string",
    "name": "string",
    "status": "string",
    "type": "string",
    "url": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[appUpload](#)

An app to upload or that has been uploaded.

Type: [Upload](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListArtifacts

Gets information about artifacts.

Request Syntax

```
{  
  "arn": "string",  
  "nextToken": "string",  
  "type": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The run, job, suite, or test ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

type

The artifacts' type.

Allowed values include:

- FILE
- LOG
- SCREENSHOT

Type: String

Valid Values: SCREENSHOT | FILE | LOG

Required: Yes

Response Syntax

```
{
  "artifacts": [
    {
      "arn": "string",
      "extension": "string",
      "name": "string",
      "type": "string",
      "url": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

artifacts

Information about the artifacts.

Type: Array of [Artifact](#) objects

nextToken

If the number of items that are returned is significantly large, this is an identifier that is also returned. It can be used in a subsequent call to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListDeviceInstances

Returns information about the private device instances associated with one or more AWS accounts.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

An integer that specifies the maximum number of items you want to return in the API response.

Type: Integer

Required: No

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{  
  "deviceInstances": [  
    {  
      ...  
    }  
  ]  
}
```

```
"arn": "string",
"deviceArn": "string",
"instanceProfile": {
  "arn": "string",
  "description": "string",
  "excludeAppPackagesFromCleanup": [ "string" ],
  "name": "string",
  "packageCleanup": boolean,
  "rebootAfterUse": boolean
},
"labels": [ "string" ],
"status": "string",
"udid": "string"
},
],
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[deviceInstances](#)

An object that contains information about your device instances.

Type: Array of [DeviceInstance](#) objects

[nextToken](#)

An identifier that can be used in the next call to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListDevicePools

Gets information about device pools.

Request Syntax

```
{  
  "arn": "string",  
  "nextToken": "string",  
  "type": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The project ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*

Required: Yes

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

type

The device pools' type.

Allowed values include:

- **CURATED**: A device pool that is created and managed by AWS Device Farm.
- **PRIVATE**: A device pool that is created and managed by the device pool developer.

Type: String

Valid Values: CURATED | PRIVATE

Required: No

Response Syntax

```
{
  "devicePools": [
    {
      "arn": "string",
      "description": "string",
      "maxDevices": number,
      "name": "string",
      "rules": [
        {
          "attribute": "string",
          "operator": "string",
          "value": "string"
        }
      ],
      "type": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

devicePools

Information about the device pools.

Type: Array of [DevicePool](#) objects

[nextToken](#)

If the number of items that are returned is significantly large, this is an identifier that is also returned. It can be used in a subsequent call to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListDevices

Gets information about unique device types.

Request Syntax

```
{
  "arn": "string",
  "filters": [
    {
      "attribute": "string",
      "operator": "string",
      "values": [ "string" ]
    }
  ],
  "nextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the project.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*

Required: No

filters

Used to select a set of devices. A filter is made up of an attribute, an operator, and one or more values.

- **Attribute:** The aspect of a device such as platform or model used as the selection criteria in a device filter.

Allowed values include:

- **ARN:** The Amazon Resource Name (ARN) of the device (for example, `arn:aws:devicefarm:us-west-2::device:12345Example`).
- **PLATFORM:** The device platform. Valid values are `ANDROID` or `IOS`.
- **OS_VERSION:** The operating system version (for example, `10.3.2`).
- **MODEL:** The device model (for example, `iPad 5th Gen`).
- **AVAILABILITY:** The current availability of the device. Valid values are `AVAILABLE`, `HIGHLY_AVAILABLE`, `BUSY`, or `TEMPORARY_NOT_AVAILABLE`.
- **FORM_FACTOR:** The device form factor. Valid values are `PHONE` or `TABLET`.
- **MANUFACTURER:** The device manufacturer (for example, `Apple`).
- **REMOTE_ACCESS_ENABLED:** Whether the device is enabled for remote access. Valid values are `TRUE` or `FALSE`.
- **REMOTE_DEBUG_ENABLED:** Whether the device is enabled for remote debugging. Valid values are `TRUE` or `FALSE`. Because remote debugging is [no longer supported](#), this attribute is ignored.
- **INSTANCE_ARN:** The Amazon Resource Name (ARN) of the device instance.
- **INSTANCE_LABELS:** The label of the device instance.
- **FLEET_TYPE:** The fleet type. Valid values are `PUBLIC` or `PRIVATE`.
- **Operator:** The filter operator.
 - The `EQUALS` operator is available for every attribute except `INSTANCE_LABELS`.
 - The `CONTAINS` operator is available for the `INSTANCE_LABELS` and `MODEL` attributes.
 - The `IN` and `NOT_IN` operators are available for the `ARN`, `OS_VERSION`, `MODEL`, `MANUFACTURER`, and `INSTANCE_ARN` attributes.
 - The `LESS_THAN`, `GREATER_THAN`, `LESS_THAN_OR_EQUALS`, and `GREATER_THAN_OR_EQUALS` operators are also available for the `OS_VERSION` attribute.
- **Values:** An array of one or more filter values.
 - The `IN` and `NOT_IN` operators take a values array that has one or more elements.
 - The other operators require an array with a single element.
 - In a request, the `AVAILABILITY` attribute takes the following values: `AVAILABLE`, `HIGHLY_AVAILABLE`, `BUSY`, or `TEMPORARY_NOT_AVAILABLE`.

Required: No

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{
  "devices": [
    {
      "arn": "string",
      "availability": "string",
      "carrier": "string",
      "cpu": {
        "architecture": "string",
        "clock": number,
        "frequency": "string"
      },
      "fleetName": "string",
      "fleetType": "string",
      "formFactor": "string",
      "heapSize": number,
      "image": "string",
      "instances": [
        {
          "arn": "string",
          "deviceArn": "string",
          "instanceProfile": {
            "arn": "string",
            "description": "string",
            "excludeAppPackagesFromCleanup": [ "string" ],
            "name": "string",
            "packageCleanup": boolean,
            "rebootAfterUse": boolean
          },

```

```
        "labels": [ "string" ],
        "status": "string",
        "udid": "string"
    }
],
"manufacturer": "string",
"memory": number,
"model": "string",
"modelId": "string",
"name": "string",
"os": "string",
"platform": "string",
"radio": "string",
"remoteAccessEnabled": boolean,
"remoteDebugEnabled": boolean,
"resolution": {
    "height": number,
    "width": number
}
}
],
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

devices

Information about the devices.

Type: Array of [Device](#) objects

nextToken

If the number of items that are returned is significantly large, this is an identifier that is also returned. It can be used in a subsequent call to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListInstanceProfiles

Returns information about all the instance profiles in an AWS account.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

An integer that specifies the maximum number of items you want to return in the API response.

Type: Integer

Required: No

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{  
  "instanceProfiles": [  
    {  
      "Name": "string",  
      "Id": "string",  
      "Path": "string",  
      "CreateDate": "string",  
      "LastModifiedDate": "string",  
      "MaxSessionDuration": "string",  
      "AssumeRoleSessionName": "string",  
      "PermissionsBoundary": "string",  
      "Tags": {  
        "key": "string",  
        "value": "string"  
      },  
      "CreateDateAsString": "string",  
      "LastModifiedDateAsString": "string",  
      "MaxSessionDurationAsString": "string",  
      "AssumeRoleSessionNameAsString": "string",  
      "PermissionsBoundaryAsString": "string"  
    }  
  ]  
}
```

```
{
  "arn": "string",
  "description": "string",
  "excludeAppPackagesFromCleanup": [ "string" ],
  "name": "string",
  "packageCleanup": boolean,
  "rebootAfterUse": boolean
},
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

instanceProfiles

An object that contains information about your instance profiles.

Type: Array of [InstanceProfile](#) objects

nextToken

An identifier that can be used in the next call to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListJobs

Gets information about jobs for a given test run.

Request Syntax

```
{  
  "arn": "string",  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The run's Amazon Resource Name (ARN).

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{
```

```
"jobs": [  
  {  
    "arn": "string",  
    "counters": {  
      "errored": number,  
      "failed": number,  
      "passed": number,  
      "skipped": number,  
      "stopped": number,  
      "total": number,  
      "warned": number  
    },  
    "created": number,  
    "device": {  
      "arn": "string",  
      "availability": "string",  
      "carrier": "string",  
      "cpu": {  
        "architecture": "string",  
        "clock": number,  
        "frequency": "string"  
      },  
      "fleetName": "string",  
      "fleetType": "string",  
      "formFactor": "string",  
      "heapSize": number,  
      "image": "string",  
      "instances": [  
        {  
          "arn": "string",  
          "deviceArn": "string",  
          "instanceProfile": {  
            "arn": "string",  
            "description": "string",  
            "excludeAppPackagesFromCleanup": [ "string" ],  
            "name": "string",  
            "packageCleanup": boolean,  
            "rebootAfterUse": boolean  
          },  
          "labels": [ "string" ],  
          "status": "string",  
          "udid": "string"  
        }  
      ],  
    },  
  ],  
]
```

```

    "manufacturer": "string",
    "memory": number,
    "model": "string",
    "modelId": "string",
    "name": "string",
    "os": "string",
    "platform": "string",
    "radio": "string",
    "remoteAccessEnabled": boolean,
    "remoteDebugEnabled": boolean,
    "resolution": {
        "height": number,
        "width": number
    }
},
"deviceMinutes": {
    "metered": number,
    "total": number,
    "unmetered": number
},
"instanceArn": "string",
"message": "string",
"name": "string",
"result": "string",
"started": number,
"status": "string",
"stopped": number,
"type": "string",
"videoCapture": boolean,
"videoEndpoint": "string"
}
],
"nextToken": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

jobs

Information about the jobs.

Type: Array of [Job](#) objects

nextToken

If the number of items that are returned is significantly large, this is an identifier that is also returned. It can be used in a subsequent call to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListNetworkProfiles

Returns the list of available network profiles.

Request Syntax

```
{  
  "arn": "string",  
  "nextToken": "string",  
  "type": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the project for which you want to list network profiles.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

type

The type of network profile to return information about. Valid values are listed here.

Type: String

Valid Values: CURATED | PRIVATE

Required: No

Response Syntax

```
{
  "networkProfiles": [
    {
      "arn": "string",
      "description": "string",
      "downlinkBandwidthBits": number,
      "downlinkDelayMs": number,
      "downlinkJitterMs": number,
      "downlinkLossPercent": number,
      "name": "string",
      "type": "string",
      "uplinkBandwidthBits": number,
      "uplinkDelayMs": number,
      "uplinkJitterMs": number,
      "uplinkLossPercent": number
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

networkProfiles

A list of the available network profiles.

Type: Array of [NetworkProfile](#) objects

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListOfferingPromotions

Returns a list of offering promotions. Each offering promotion record contains the ID and description of the promotion. The API returns a `NotEligible` error if the caller is not permitted to invoke the operation. Contact aws-devicefarm-support@amazon.com if you must be able to invoke this operation.

Request Syntax

```
{  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{  
  "nextToken": "string",  
  "offeringPromotions": [  
    {  
      "description": "string",  
      "id": "string"  
    }  
  ]  
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

An identifier to be used in the next call to this operation, to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

offeringPromotions

Information about the offering promotions.

Type: Array of [OfferingPromotion](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotEligibleException

Exception gets thrown when a user is not eligible to perform the specified transaction.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListOfferings

Returns a list of products or offerings that the user can manage through the API. Each offering record indicates the recurring price per unit and the frequency for that offering. The API returns a `NotEligible` error if the user is not permitted to invoke the operation. If you must be able to invoke this operation, contact aws-devicefarm-support@amazon.com.

Request Syntax

```
{  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{  
  "nextToken": "string",  
  "offerings": [  
    {  
      "description": "string",  
      "id": "string",  
      "platform": "string",  
      "recurringCharges": [  

```

```
{
  "cost": {
    "amount": number,
    "currencyCode": "string"
  },
  "frequency": "string"
},
"type": "string"
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

offerings

A value that represents the list offering results.

Type: Array of [Offering](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotEligibleException

Exception gets thrown when a user is not eligible to perform the specified transaction.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

Examples

Example

The following example response shows a list of device offerings for the user's account.

Sample Response

```
{
  "offerings": [
    {
      "recurringCharges": [
        {
          "cost": {
            "amount": 250.0,
            "currencyCode": "USD"
          },
          "frequency": "MONTHLY"
        }
      ],
      "platform": "IOS",
```

```
        "type": "RECURRING",
        "id": "offering-id-ios",
        "description": "iOS Unmetered Device Slot"
    },
    {
        "recurringCharges": [
            {
                "cost": {
                    "amount": 250.0,
                    "currencyCode": "USD"
                },
                "frequency": "MONTHLY"
            }
        ],
        "platform": "ANDROID",
        "type": "RECURRING",
        "id": "offering-id-android",
        "description": "Android Unmetered Device Slot"
    }
]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListOfferingTransactions

Returns a list of all historical purchases, renewals, and system renewal transactions for an AWS account. The list is paginated and ordered by a descending timestamp (most recent transactions are first). The API returns a `NotEligible` error if the user is not permitted to invoke the operation. If you must be able to invoke this operation, contact aws-devicefarm-support@amazon.com.

Request Syntax

```
{  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{  
  "nextToken": "string",  
  "offeringTransactions": [  
    {  
      "cost": {  
        "amount": number,  
        "currencyCode": "string"  
      },  
      "createdOn": number,
```

```
    "offeringPromotionId": "string",
    "offeringStatus": {
      "effectiveOn": number,
      "offering": {
        "description": "string",
        "id": "string",
        "platform": "string",
        "recurringCharges": [
          {
            "cost": {
              "amount": number,
              "currencyCode": "string"
            },
            "frequency": "string"
          }
        ],
        "type": "string"
      },
      "quantity": number,
      "type": "string"
    },
    "transactionId": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

offeringTransactions

The audit log of subscriptions you have purchased and modified through AWS Device Farm.

Type: Array of [OfferingTransaction](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotEligibleException

Exception gets thrown when a user is not eligible to perform the specified transaction.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

Examples

Example

The following example response contains all the transactions that the customer has made.

Sample Response

```
{
```

```
"offeringTransactions": [  
  {  
    "createdOn": 1458596241.001,  
    "offeringStatus": {  
      "effectiveOn": 1458596240.974,  
      "type": "PURCHASE",  
      "offering": {  
        "platform": "IOS",  
        "type": "RECURRING",  
        "id": "offering-id-ios",  
        "description": "iOS Unmetered Device Slot"  
      },  
      "quantity": 1  
    },  
    "cost": {  
      "amount": 80.65,  
      "currencyCode": "USD"  
    },  
    "transactionId": "transaction-id"  
  },  
  {  
    "createdOn": 1458587590.308,  
    "offeringStatus": {  
      "effectiveOn": 1458587590.24,  
      "type": "PURCHASE",  
      "offering": {  
        "platform": "IOS",  
        "type": "RECURRING",  
        "id": "offering-id-ios",  
        "description": "iOS Unmetered Device Slot"  
      },  
      "quantity": 1  
    },  
    "cost": {  
      "amount": 80.65,  
      "currencyCode": "USD"  
    },  
    "transactionId": "transaction-id"  
  },  
  {  
    "createdOn": 1458541943.395,  
    "offeringStatus": {  
      "effectiveOn": 1458541943.34,  
      "type": "PURCHASE",
```

```
        "offering": {
            "platform": "ANDROID",
            "type": "RECURRING",
            "id": "offering-id-android",
            "description": "Android Unmetered Device Slot"
        },
        "quantity": 10
    },
    "cost": {
        "amount": 806.45,
        "currencyCode": "USD"
    },
    "transactionId": "transaction-id"
},
{
    "createdOn": 1458584276.849,
    "offeringStatus": {
        "effectiveOn": 1458584276.811,
        "type": "PURCHASE",
        "offering": {
            "platform": "ANDROID",
            "type": "RECURRING",
            "id": "offering-id-android",
            "description": "Android Unmetered Device Slot"
        },
        "quantity": 2
    },
    "cost": {
        "amount": 161.29,
        "currencyCode": "USD"
    },
    "transactionId": "transaction-id"
},
{
    "createdOn": 1458592981.171,
    "offeringStatus": {
        "effectiveOn": 1458592981.137,
        "type": "PURCHASE",
        "offering": {
            "platform": "IOS",
            "type": "RECURRING",
            "id": "offering-id-ios",
            "description": "iOS Unmetered Device Slot"
        },
    },
}
```

```
        "quantity": 1
      },
      "cost": {
        "amount": 80.65,
        "currencyCode": "USD"
      },
      "transactionId": "transaction-id"
    },
    {
      "createdOn": 1458591927.511,
      "offeringStatus": {
        "effectiveOn": 1458591927.468,
        "type": "PURCHASE",
        "offering": {
          "platform": "IOS",
          "type": "RECURRING",
          "id": "offering-id-ios",
          "description": "iOS Unmetered Device Slot"
        },
        "quantity": 1
      },
      "cost": {
        "amount": 80.65,
        "currencyCode": "USD"
      },
      "transactionId": "transaction-id"
    },
    {
      "createdOn": 1458581880.117,
      "offeringStatus": {
        "effectiveOn": 1459468800.0,
        "type": "RENEW",
        "offering": {
          "platform": "IOS",
          "type": "RECURRING",
          "id": "offering-id-ios",
          "description": "iOS Unmetered Device Slot"
        },
        "quantity": 0
      },
      "cost": {
        "amount": 0.0,
        "currencyCode": "USD"
      },
    },
```

```
    "transactionId": "transaction-id"
  },
  {
    "createdOn": 1458587390.031,
    "offeringStatus": {
      "effectiveOn": 1458587390.008,
      "type": "PURCHASE",
      "offering": {
        "platform": "ANDROID",
        "type": "RECURRING",
        "id": "offering-id-android",
        "description": "Android Unmetered Device Slot"
      },
      "quantity": 1
    },
    "cost": {
      "amount": 80.65,
      "currencyCode": "USD"
    },
    "transactionId": "transaction-id"
  },
  {
    "createdOn": 1458591927.99,
    "offeringStatus": {
      "effectiveOn": 1459468800.0,
      "type": "RENEW",
      "offering": {
        "platform": "ANDROID",
        "type": "RECURRING",
        "id": "offering-id-android",
        "description": "Android Unmetered Device Slot"
      },
      "quantity": 3
    },
    "cost": {
      "amount": 750.0,
      "currencyCode": "USD"
    },
    "transactionId": "transaction-id"
  },
  {
    "createdOn": 1458581580.426,
    "offeringStatus": {
      "effectiveOn": 1458581580.377,
```

```
        "type": "PURCHASE",
        "offering": {
            "platform": "ANDROID",
            "type": "RECURRING",
            "id": "offering-id-android",
            "description": "Android Unmetered Device Slot"
        },
        "quantity": 1
    },
    "cost": {
        "amount": 80.65,
        "currencyCode": "USD"
    },
    "transactionId": "transaction-id"
},
{
    "createdOn": 1458582235.794,
    "offeringStatus": {
        "effectiveOn": 1459468800.0,
        "type": "RENEW",
        "offering": {
            "platform": "ANDROID",
            "type": "RECURRING",
            "id": "offering-id-android",
            "description": "Android Unmetered Device Slot"
        },
        "quantity": 1
    },
    "cost": {
        "amount": 250.0,
        "currencyCode": "USD"
    },
    "transactionId": "transaction-id"
},
{
    "createdOn": 1458581580.429,
    "offeringStatus": {
        "effectiveOn": 1458581580.372,
        "type": "PURCHASE",
        "offering": {
            "platform": "IOS",
            "type": "RECURRING",
            "id": "offering-id-ios",
            "description": "iOS Unmetered Device Slot"
```

```
    },
    "quantity": 1
  },
  "cost": {
    "amount": 80.65,
    "currencyCode": "USD"
  },
  "transactionId": "transaction-id"
},
{
  "createdOn": 1458593014.881,
  "offeringStatus": {
    "effectiveOn": 1458593014.856,
    "type": "PURCHASE",
    "offering": {
      "platform": "IOS",
      "type": "RECURRING",
      "id": "offering-id-ios",
      "description": "iOS Unmetered Device Slot"
    },
    "quantity": 2
  },
  "cost": {
    "amount": 161.29,
    "currencyCode": "USD"
  },
  "transactionId": "transaction-id"
},
{
  "createdOn": 1458581880.415,
  "offeringStatus": {
    "effectiveOn": 1459468800.0,
    "type": "RENEW",
    "offering": {
      "platform": "ANDROID",
      "type": "RECURRING",
      "id": "offering-id-android",
      "description": "Android Unmetered Device Slot"
    },
    "quantity": 0
  },
  "cost": {
    "amount": 0.0,
    "currencyCode": "USD"
  }
}
```

```
    },
    "transactionId": "transaction-id"
  },
  {
    "createdOn": 1458591927.662,
    "offeringStatus": {
      "effectiveOn": 1458591927.491,
      "type": "PURCHASE",
      "offering": {
        "platform": "ANDROID",
        "type": "RECURRING",
        "id": "offering-id-android",
        "description": "Android Unmetered Device Slot"
      },
      "quantity": 1
    },
    "cost": {
      "amount": 80.65,
      "currencyCode": "USD"
    },
    "transactionId": "transaction-id"
  },
  {
    "createdOn": 1458582235.834,
    "offeringStatus": {
      "effectiveOn": 1459468800.0,
      "type": "RENEW",
      "offering": {
        "platform": "IOS",
        "type": "RECURRING",
        "id": "offering-id-ios",
        "description": "iOS Unmetered Device Slot"
      },
      "quantity": 1
    },
    "cost": {
      "amount": 250.0,
      "currencyCode": "USD"
    },
    "transactionId": "transaction-id"
  },
  {
    "createdOn": 1458583642.184,
    "offeringStatus": {
```

```

        "effectiveOn": 1459468800.0,
        "type": "RENEW",
        "offering": {
            "platform": "IOS",
            "type": "RECURRING",
            "id": "offering-id-ios",
            "description": "iOS Unmetered Device Slot"
        },
        "quantity": 0
    },
    "cost": {
        "amount": 0.0,
        "currencyCode": "USD"
    },
    "transactionId": "transaction-id"
},
{
    "createdOn": 1458581880.007,
    "offeringStatus": {
        "effectiveOn": 1458581879.937,
        "type": "PURCHASE",
        "offering": {
            "platform": "ANDROID",
            "type": "RECURRING",
            "id": "offering-id-android",
            "description": "Android Unmetered Device Slot"
        },
        "quantity": 1
    },
    "cost": {
        "amount": 80.65,
        "currencyCode": "USD"
    },
    "transactionId": "transaction-id"
}
]
}

```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListProjects

Gets information about projects.

Request Syntax

```
{  
  "arn": "string",  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

Optional. If no Amazon Resource Name (ARN) is specified, then AWS Device Farm returns a list of all projects for the AWS account. You can also specify a project ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: No

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "projects": [
    {
      "arn": "string",
      "created": number,
      "defaultJobTimeoutMinutes": number,
      "name": "string",
      "vpcConfig": {
        "securityGroupIds": [ "string" ],
        "subnetIds": [ "string" ],
        "vpcId": "string"
      }
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

If the number of items that are returned is significantly large, this is an identifier that is also returned. It can be used in a subsequent call to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

projects

Information about the projects.

Type: Array of [Project](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListRemoteAccessSessions

Returns a list of all currently running remote access sessions.

Request Syntax

```
{  
  "arn": "string",  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the project about which you are requesting information.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{
```

```
"nextToken": "string",
"remoteAccessSessions": [
  {
    "arn": "string",
    "billingMethod": "string",
    "clientId": "string",
    "created": number,
    "device": {
      "arn": "string",
      "availability": "string",
      "carrier": "string",
      "cpu": {
        "architecture": "string",
        "clock": number,
        "frequency": "string"
      },
    },
    "fleetName": "string",
    "fleetType": "string",
    "formFactor": "string",
    "heapSize": number,
    "image": "string",
    "instances": [
      {
        "arn": "string",
        "deviceArn": "string",
        "instanceProfile": {
          "arn": "string",
          "description": "string",
          "excludeAppPackagesFromCleanup": [ "string" ],
          "name": "string",
          "packageCleanup": boolean,
          "rebootAfterUse": boolean
        },
        "labels": [ "string" ],
        "status": "string",
        "udid": "string"
      }
    ],
    "manufacturer": "string",
    "memory": number,
    "model": "string",
    "modelId": "string",
    "name": "string",
    "os": "string",
```

```

    "platform": "string",
    "radio": "string",
    "remoteAccessEnabled": boolean,
    "remoteDebugEnabled": boolean,
    "resolution": {
      "height": number,
      "width": number
    }
  },
  "deviceMinutes": {
    "metered": number,
    "total": number,
    "unmetered": number
  },
  "deviceProxy": {
    "host": "string",
    "port": number
  },
  "deviceUdid": "string",
  "endpoint": "string",
  "hostAddress": "string",
  "instanceArn": "string",
  "interactionMode": "string",
  "message": "string",
  "name": "string",
  "remoteDebugEnabled": boolean,
  "remoteRecordAppArn": "string",
  "remoteRecordEnabled": boolean,
  "result": "string",
  "skipAppResign": boolean,
  "started": number,
  "status": "string",
  "stopped": number,
  "vpcConfig": {
    "securityGroupIds": [ "string" ],
    "subnetIds": [ "string" ],
    "vpcId": "string"
  }
}
]
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

[remoteAccessSessions](#)

A container that represents the metadata from the service about each remote access session you are requesting.

Type: Array of [RemoteAccessSession](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListRuns

Gets information about runs, given an AWS Device Farm project ARN.

Request Syntax

```
{  
  "arn": "string",  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the project for which you want to list runs.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: Yes

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{
```

```
"nextToken": "string",
"runs": [
  {
    "appUpload": "string",
    "arn": "string",
    "billingMethod": "string",
    "completedJobs": number,
    "counters": {
      "errored": number,
      "failed": number,
      "passed": number,
      "skipped": number,
      "stopped": number,
      "total": number,
      "warned": number
    },
    "created": number,
    "customerArtifactPaths": {
      "androidPaths": [ "string" ],
      "deviceHostPaths": [ "string" ],
      "iosPaths": [ "string" ]
    },
    "deviceMinutes": {
      "metered": number,
      "total": number,
      "unmetered": number
    },
    "devicePoolArn": "string",
    "deviceProxy": {
      "host": "string",
      "port": number
    },
    "deviceSelectionResult": {
      "filters": [
        {
          "attribute": "string",
          "operator": "string",
          "values": [ "string" ]
        }
      ],
      "matchedDevicesCount": number,
      "maxDevices": number
    },
    "eventCount": number,
```

```
"jobTimeoutMinutes": number,
"locale": "string",
"location": {
  "latitude": number,
  "longitude": number
},
"message": "string",
"name": "string",
"networkProfile": {
  "arn": "string",
  "description": "string",
  "downlinkBandwidthBits": number,
  "downlinkDelayMs": number,
  "downlinkJitterMs": number,
  "downlinkLossPercent": number,
  "name": "string",
  "type": "string",
  "uplinkBandwidthBits": number,
  "uplinkDelayMs": number,
  "uplinkJitterMs": number,
  "uplinkLossPercent": number
},
"parsingResultUrl": "string",
"platform": "string",
"radios": {
  "bluetooth": boolean,
  "gps": boolean,
  "nfc": boolean,
  "wifi": boolean
},
"result": "string",
"resultCode": "string",
"seed": number,
"skipAppResign": boolean,
"started": number,
"status": "string",
"stopped": number,
"testSpecArn": "string",
"totalJobs": number,
"type": "string",
"vpcConfig": {
  "securityGroupIds": [ "string" ],
  "subnetIds": [ "string" ],
  "vpcId": "string"
}
```

```
    },  
    "webUrl": "string"  
  }  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

If the number of items that are returned is significantly large, this is an identifier that is also returned. It can be used in a subsequent call to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

[runs](#)

Information about the runs.

Type: Array of [Run](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListSamples

Gets information about samples, given an AWS Device Farm job ARN.

Request Syntax

```
{  
  "arn": "string",  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the job used to list samples.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: Yes

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{
```

```
"nextToken": "string",
"samples": [
  {
    "arn": "string",
    "type": "string",
    "url": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

If the number of items that are returned is significantly large, this is an identifier that is also returned. It can be used in a subsequent call to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

samples

Information about the samples.

Type: Array of [Sample](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListSuites

Gets information about test suites for a given job.

Request Syntax

```
{  
  "arn": "string",  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[arn](#)

The job's Amazon Resource Name (ARN).

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

[nextToken](#)

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{
```

```
"nextToken": "string",
"suites": [
  {
    "arn": "string",
    "counters": {
      "errored": number,
      "failed": number,
      "passed": number,
      "skipped": number,
      "stopped": number,
      "total": number,
      "warned": number
    },
    "created": number,
    "deviceMinutes": {
      "metered": number,
      "total": number,
      "unmetered": number
    },
    "message": "string",
    "name": "string",
    "result": "string",
    "started": number,
    "status": "string",
    "stopped": number,
    "type": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

If the number of items that are returned is significantly large, this is an identifier that is also returned. It can be used in a subsequent call to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

[suites](#)

Information about the suites.

Type: Array of [Suite](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

List the tags for an AWS Device Farm resource.

Request Syntax

```
{  
  "ResourceARN": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ResourceARN

The Amazon Resource Name (ARN) of the resource or resources for which to list tags. You can associate tags with the following Device Farm resources: PROJECT, RUN, NETWORK_PROFILE, INSTANCE_PROFILE, DEVICE_INSTANCE, SESSION, DEVICE_POOL, DEVICE, and VPCE_CONFIGURATION.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "Tags": [  
    {  
      "Key": "string",  
      "Value": "string"  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Tags](#)

The tags to add to the resource. A tag is an array of key-value pairs. Tag keys can have a maximum character length of 128 characters. Tag values can have a maximum length of 256 characters.

Type: Array of [Tag](#) objects

Array Members: Maximum number of 150 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

TagOperationException

The operation was not successful. Try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Gets a list of all Selenium testing projects in your account.

```
{
  "maxResult": number,
  "nextToken": "string"
}
```

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Return no more than this number of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

From a response, used to continue a paginated listing.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

```
{
  "nextToken": "string",
  "testGridProjects": [
```

```
{
  "arn": "string",
  "created": number,
  "description": "string",
  "name": "string",
  "vpcConfig": {
    "securityGroupIds": [ "string" ],
    "subnetIds": [ "string" ],
    "vpcId": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

Used for pagination. Pass into [ListTestGridProjects](#) to get more results in a paginated request.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

testGridProjects

The list of TestGridProjects, based on a [ListTestGridProjectsRequest](#).

Type: Array of [TestGridProject](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

InternalServerErrorException

An internal exception was raised in the service. Contact aws-devicefarm-support@amazon.com if you see this error.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTestGridSessionActions

Returns a list of the actions taken in a [TestGridSession](#).

Request Syntax

```
{  
  "maxResult": number,  
  "nextToken": "string",  
  "sessionArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[maxResult](#)

The maximum number of sessions to return per response.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

[nextToken](#)

Pagination token.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

[sessionArn](#)

The ARN of the session to retrieve.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: Yes

Response Syntax

```
{
  "actions": [
    {
      "action": "string",
      "duration": number,
      "requestMethod": "string",
      "started": number,
      "statusCode": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

actions

The action taken by the session.

Type: Array of [TestGridSessionAction](#) objects

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

InternalServiceException

An internal exception was raised in the service. Contact aws-devicefarm-support@amazon.com if you see this error.

HTTP Status Code: 500

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTestGridSessionArtifacts

Retrieves a list of artifacts created during the session.

Request Syntax

```
{  
  "maxResult": number,  
  "nextToken": "string",  
  "sessionArn": "string",  
  "type": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[maxResult](#)

The maximum number of results to be returned by a request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

[nextToken](#)

Pagination token.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

[sessionArn](#)

The ARN of a [TestGridSession](#).

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: Yes

type

Limit results to a specified type of artifact.

Type: String

Valid Values: VIDEO | LOG

Required: No

Response Syntax

```
{
  "artifacts": [
    {
      "filename": "string",
      "type": "string",
      "url": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

artifacts

A list of test grid session artifacts for a [TestGridSession](#).

Type: Array of [TestGridSessionArtifact](#) objects

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

InternalServiceException

An internal exception was raised in the service. Contact aws-devicefarm-support@amazon.com if you see this error.

HTTP Status Code: 500

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTestGridSessions

Retrieves a list of sessions for a [TestGridProject](#).

Request Syntax

```
{
  "creationTimeAfter": number,
  "creationTimeBefore": number,
  "endTimeAfter": number,
  "endTimeBefore": number,
  "maxResult": number,
  "nextToken": "string",
  "projectArn": "string",
  "status": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[creationTimeAfter](#)

Return only sessions created after this time.

Type: Timestamp

Required: No

[creationTimeBefore](#)

Return only sessions created before this time.

Type: Timestamp

Required: No

[endTimeAfter](#)

Return only sessions that ended after this time.

Type: Timestamp

Required: No

endTimeBefore

Return only sessions that ended before this time.

Type: Timestamp

Required: No

maxResult

Return only this many results at a time.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

projectArn

ARN of a [TestGridProject](#).

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

status

Return only sessions in this state.

Type: String

Valid Values: ACTIVE | CLOSED | ERRORRED

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "testGridSessions": [
    {
      "arn": "string",
      "billingMinutes": number,
      "created": number,
      "ended": number,
      "seleniumProperties": "string",
      "status": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

testGridSessions

The sessions that match the criteria in a [ListTestGridSessionsRequest](#).

Type: Array of [TestGridSession](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

InternalServiceException

An internal exception was raised in the service. Contact aws-devicefarm-support@amazon.com if you see this error.

HTTP Status Code: 500

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTests

Gets information about tests in a given test suite.

Request Syntax

```
{  
  "arn": "string",  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The test suite's Amazon Resource Name (ARN).

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{
```

```
"nextToken": "string",
"tests": [
  {
    "arn": "string",
    "counters": {
      "errored": number,
      "failed": number,
      "passed": number,
      "skipped": number,
      "stopped": number,
      "total": number,
      "warned": number
    },
    "created": number,
    "deviceMinutes": {
      "metered": number,
      "total": number,
      "unmetered": number
    },
    "message": "string",
    "name": "string",
    "result": "string",
    "started": number,
    "status": "string",
    "stopped": number,
    "type": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

If the number of items that are returned is significantly large, this is an identifier that is also returned. It can be used in a subsequent call to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

[tests](#)

Information about the tests.

Type: Array of [Test](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListUniqueProblems

Gets information about unique problems, such as exceptions or crashes.

Unique problems are defined as a single instance of an error across a run, job, or suite. For example, if a call in your application consistently raises an exception (`OutOfBoundsException` in `MyActivity.java:386`), `ListUniqueProblems` returns a single entry instead of many individual entries for that exception.

Request Syntax

```
{
  "arn": "string",
  "nextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The unique problems' ARNs.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: Yes

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "uniqueProblems": {
    "string" : [
      {
        "message": "string",
        "problems": [
          {
            "device": {
              "arn": "string",
              "availability": "string",
              "carrier": "string",
              "cpu": {
                "architecture": "string",
                "clock": number,
                "frequency": "string"
              },
              "fleetName": "string",
              "fleetType": "string",
              "formFactor": "string",
              "heapSize": number,
              "image": "string",
              "instances": [
                {
                  "arn": "string",
                  "deviceArn": "string",
                  "instanceProfile": {
                    "arn": "string",
                    "description": "string",
                    "excludeAppPackagesFromCleanup": [ "string" ],
                    "name": "string",
                    "packageCleanup": boolean,
                    "rebootAfterUse": boolean
                  },
                  "labels": [ "string" ],
                  "status": "string",
                  "udid": "string"
                }
              ],
              "manufacturer": "string",
              "memory": number,
```

```

    "model": "string",
    "modelId": "string",
    "name": "string",
    "os": "string",
    "platform": "string",
    "radio": "string",
    "remoteAccessEnabled": boolean,
    "remoteDebugEnabled": boolean,
    "resolution": {
        "height": number,
        "width": number
    }
},
"job": {
    "arn": "string",
    "name": "string"
},
"message": "string",
"result": "string",
"run": {
    "arn": "string",
    "name": "string"
},
"suite": {
    "arn": "string",
    "name": "string"
},
"test": {
    "arn": "string",
    "name": "string"
}
}
]
}
]
}
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

If the number of items that are returned is significantly large, this is an identifier that is also returned. It can be used in a subsequent call to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

[uniqueProblems](#)

Information about the unique problems.

Allowed values include:

- PENDING
- PASSED
- WARNED
- FAILED
- SKIPPED
- ERRORED
- STOPPED

Type: String to array of [UniqueProblem](#) objects map

Valid Keys: PENDING | PASSED | WARNED | FAILED | SKIPPED | ERRORED | STOPPED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListUploads

Gets information about uploads, given an AWS Device Farm project ARN.

Request Syntax

```
{  
  "arn": "string",  
  "nextToken": "string",  
  "type": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the project for which you want to list uploads.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*

Required: Yes

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

type

The type of upload.

Must be one of the following values:

- `ANDROID_APP`
- `IOS_APP`
- `WEB_APP`
- `EXTERNAL_DATA`
- `APPIUM_JAVA_JUNIT_TEST_PACKAGE`
- `APPIUM_JAVA_TESTNG_TEST_PACKAGE`
- `APPIUM_PYTHON_TEST_PACKAGE`
- `APPIUM_NODE_TEST_PACKAGE`
- `APPIUM_RUBY_TEST_PACKAGE`
- `APPIUM_WEB_JAVA_JUNIT_TEST_PACKAGE`
- `APPIUM_WEB_JAVA_TESTNG_TEST_PACKAGE`
- `APPIUM_WEB_PYTHON_TEST_PACKAGE`
- `APPIUM_WEB_NODE_TEST_PACKAGE`
- `APPIUM_WEB_RUBY_TEST_PACKAGE`
- `INSTRUMENTATION_TEST_PACKAGE`
- `XCTEST_TEST_PACKAGE`
- `XCTEST_UI_TEST_PACKAGE`
- `APPIUM_JAVA_JUNIT_TEST_SPEC`
- `APPIUM_JAVA_TESTNG_TEST_SPEC`
- `APPIUM_PYTHON_TEST_SPEC`
- `APPIUM_NODE_TEST_SPEC`
- `APPIUM_RUBY_TEST_SPEC`
- `APPIUM_WEB_JAVA_JUNIT_TEST_SPEC`
- `APPIUM_WEB_JAVA_TESTNG_TEST_SPEC`
- `APPIUM_WEB_PYTHON_TEST_SPEC`
- `APPIUM_WEB_NODE_TEST_SPEC`
- `APPIUM_WEB_RUBY_TEST_SPEC`
- `INSTRUMENTATION_TEST_SPEC`
- `XCTEST_UI_TEST_SPEC`

Type: String

Valid Values: ANDROID_APP | IOS_APP | WEB_APP | EXTERNAL_DATA |
APPIUM_JAVA_JUNIT_TEST_PACKAGE | APPIUM_JAVA_TESTNG_TEST_PACKAGE
| APPIUM_PYTHON_TEST_PACKAGE | APPIUM_NODE_TEST_PACKAGE |
APPIUM_RUBY_TEST_PACKAGE | APPIUM_WEB_JAVA_JUNIT_TEST_PACKAGE |
APPIUM_WEB_JAVA_TESTNG_TEST_PACKAGE | APPIUM_WEB_PYTHON_TEST_PACKAGE
| APPIUM_WEB_NODE_TEST_PACKAGE | APPIUM_WEB_RUBY_TEST_PACKAGE
| CALABASH_TEST_PACKAGE | INSTRUMENTATION_TEST_PACKAGE
| UIAUTOMATION_TEST_PACKAGE | UIAUTOMATOR_TEST_PACKAGE
| XCTEST_TEST_PACKAGE | XCTEST_UI_TEST_PACKAGE |
APPIUM_JAVA_JUNIT_TEST_SPEC | APPIUM_JAVA_TESTNG_TEST_SPEC |
APPIUM_PYTHON_TEST_SPEC | APPIUM_NODE_TEST_SPEC | APPIUM_RUBY_TEST_SPEC
| APPIUM_WEB_JAVA_JUNIT_TEST_SPEC | APPIUM_WEB_JAVA_TESTNG_TEST_SPEC
| APPIUM_WEB_PYTHON_TEST_SPEC | APPIUM_WEB_NODE_TEST_SPEC
| APPIUM_WEB_RUBY_TEST_SPEC | INSTRUMENTATION_TEST_SPEC |
XCTEST_UI_TEST_SPEC

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "uploads": [
    {
      "arn": "string",
      "category": "string",
      "contentType": "string",
      "created": number,
      "message": "string",
      "metadata": "string",
      "name": "string",
      "status": "string",
      "type": "string",
      "url": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

If the number of items that are returned is significantly large, this is an identifier that is also returned. It can be used in a subsequent call to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

[uploads](#)

Information about the uploads.

Type: Array of [Upload](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListVPCEConfigurations

Returns information about all Amazon Virtual Private Cloud (VPC) endpoint configurations in the AWS account.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

An integer that specifies the maximum number of items you want to return in the API response.

Type: Integer

Required: No

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{  
  "nextToken": "string",  
}
```

```
"vpceConfigurations": [  
  {  
    "arn": "string",  
    "serviceDnsName": "string",  
    "vpceConfigurationDescription": "string",  
    "vpceConfigurationName": "string",  
    "vpceServiceName": "string"  
  }  
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

[vpceConfigurations](#)

An array of VPCEConfiguration objects that contain information about your VPC endpoint configuration.

Type: Array of [VPCEConfiguration](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PurchaseOffering

Immediately purchases offerings for an AWS account. Offerings renew with the latest total purchased quantity for an offering, unless the renewal was overridden. The API returns a `NotEligible` error if the user is not permitted to invoke the operation. If you must be able to invoke this operation, contact aws-devicefarm-support@amazon.com.

Request Syntax

```
{  
  "offeringId": "string",  
  "offeringPromotionId": "string",  
  "quantity": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[offeringId](#)

The ID of the offering.

Type: String

Length Constraints: Minimum length of 32.

Required: Yes

[offeringPromotionId](#)

The ID of the offering promotion to be applied to the purchase.

Type: String

Length Constraints: Minimum length of 4.

Required: No

[quantity](#)

The number of device slots to purchase in an offering request.

Type: Integer

Required: Yes

Response Syntax

```
{
  "offeringTransaction": {
    "cost": {
      "amount": number,
      "currencyCode": "string"
    },
    "createdOn": number,
    "offeringPromotionId": "string",
    "offeringStatus": {
      "effectiveOn": number,
      "offering": {
        "description": "string",
        "id": "string",
        "platform": "string",
        "recurringCharges": [
          {
            "cost": {
              "amount": number,
              "currencyCode": "string"
            },
            "frequency": "string"
          }
        ],
        "type": "string"
      },
      "quantity": number,
      "type": "string"
    },
    "transactionId": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

offeringTransaction

Represents the offering transaction for the purchase result.

Type: [OfferingTransaction](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotEligibleException

Exception gets thrown when a user is not eligible to perform the specified transaction.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

Examples

Example

The following example purchases one unmetered iOS device.

Sample Request

```
{
  "transactions": [
    "purchase": {
      "offeringId": "offering-id-ios",
      "quantity": 1
    }
  ]
}
```

Sample Response

```
{
  "offeringTransaction": {
    "createdOn": 1458587590.308,
    "offeringStatus": {
      "effectiveOn": 1458587590.24,
      "type": "RECURRING",
      "offering": {
        "platform": "IOS",
        "type": "RECURRING",
        "id": "offering-id-ios",
        "description": "iOS Unmetered Device Slot"
      },
      "quantity": 1
    },
    "cost": {
      "amount": 80.65,
      "currencyCode": "USD"
    },
    "transactionId": "transaction-id"
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RenewOffering

Explicitly sets the quantity of devices to renew for an offering, starting from the `effectiveDate` of the next period. The API returns a `NotEligible` error if the user is not permitted to invoke the operation. If you must be able to invoke this operation, contact aws-devicefarm-support@amazon.com.

Request Syntax

```
{
  "offeringId": "string",
  "quantity": number
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[offeringId](#)

The ID of a request to renew an offering.

Type: String

Length Constraints: Minimum length of 32.

Required: Yes

[quantity](#)

The quantity requested in an offering renewal.

Type: Integer

Required: Yes

Response Syntax

```
{
```

```
"offeringTransaction": {
  "cost": {
    "amount": number,
    "currencyCode": "string"
  },
  "createdOn": number,
  "offeringPromotionId": "string",
  "offeringStatus": {
    "effectiveOn": number,
    "offering": {
      "description": "string",
      "id": "string",
      "platform": "string",
      "recurringCharges": [
        {
          "cost": {
            "amount": number,
            "currencyCode": "string"
          },
          "frequency": "string"
        }
      ],
      "type": "string"
    },
    "quantity": number,
    "type": "string"
  },
  "transactionId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

offeringTransaction

Represents the status of the offering transaction for the renewal.

Type: [OfferingTransaction](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotEligibleException

Exception gets thrown when a user is not eligible to perform the specified transaction.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

Examples

Example

The following example renews the offering for one unmetered iOS device.

Sample Request

```
{
```

```
"transactions": [  
  "renew": {  
    "offeringId": "offering-id-ios",  
    "quantity": 1,  
  }  
]  
}
```

Sample Response

```
{  
  "offeringTransaction": {  
    "createdOn": 1458596930.431,  
    "offeringStatus": {  
      "effectiveOn": 1459468800.0,  
      "type": "RECURRING",  
      "offering": {  
        "platform": "IOS",  
        "type": "RECURRING",  
        "id": "offering-id-ios",  
        "description": "iOS Unmetered Device Slot"  
      },  
      "quantity": 1  
    },  
    "cost": {  
      "amount": 250.0,  
      "currencyCode": "USD"  
    },  
    "transactionId": "transaction-id"  
  }  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ScheduleRun

Schedules a run.

Request Syntax

```
{
  "appArn": "string",
  "configuration": {
    "auxiliaryApps": [ "string" ],
    "billingMethod": "string",
    "customerArtifactPaths": {
      "androidPaths": [ "string" ],
      "deviceHostPaths": [ "string" ],
      "iosPaths": [ "string" ]
    },
    "deviceProxy": {
      "host": "string",
      "port": number
    },
    "extraDataPackageArn": "string",
    "locale": "string",
    "location": {
      "latitude": number,
      "longitude": number
    },
    "networkProfileArn": "string",
    "radios": {
      "bluetooth": boolean,
      "gps": boolean,
      "nfc": boolean,
      "wifi": boolean
    },
    "vpceConfigurationArns": [ "string" ]
  },
  "devicePoolArn": "string",
  "deviceSelectionConfiguration": {
    "filters": [
      {
        "attribute": "string",
        "operator": "string",
        "values": [ "string" ]
      }
    ]
  }
}
```

```
    ],
    "maxDevices": number
  },
  "executionConfiguration": {
    "accountsCleanup": boolean,
    "appPackagesCleanup": boolean,
    "jobTimeoutMinutes": number,
    "skipAppResign": boolean,
    "videoCapture": boolean
  },
  "name": "string",
  "projectArn": "string",
  "test": {
    "filter": "string",
    "parameters": {
      "string": "string"
    },
    "testPackageArn": "string",
    "testSpecArn": "string",
    "type": "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[appArn](#)

The ARN of an application package to run tests against, created with [CreateUpload](#). See [ListUploads](#).

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

[configuration](#)

Information about the settings for the run to be scheduled.

Type: [ScheduleRunConfiguration](#) object

Required: No

[devicePoolArn](#)

The ARN of the device pool for the run to be scheduled.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

[deviceSelectionConfiguration](#)

The filter criteria used to dynamically select a set of devices for a test run and the maximum number of devices to be included in the run.

Either **devicePoolArn** or **deviceSelectionConfiguration** is required in a request.

Type: [DeviceSelectionConfiguration](#) object

Required: No

[executionConfiguration](#)

Specifies configuration information about a test run, such as the execution timeout (in minutes).

Type: [ExecutionConfiguration](#) object

Required: No

[name](#)

The name for the run to be scheduled.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

[projectArn](#)

The ARN of the project for the run to be scheduled.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

test

Information about the test for the run to be scheduled.

Type: [ScheduleRunTest](#) object

Required: Yes

Response Syntax

```
{
  "run": {
    "appUpload": "string",
    "arn": "string",
    "billingMethod": "string",
    "completedJobs": number,
    "counters": {
      "errored": number,
      "failed": number,
      "passed": number,
      "skipped": number,
      "stopped": number,
      "total": number,
      "warned": number
    },
    "created": number,
    "customerArtifactPaths": {
      "androidPaths": [ "string" ],
      "deviceHostPaths": [ "string" ],
      "iosPaths": [ "string" ]
    },
    "deviceMinutes": {
      "metered": number,
      "total": number,
      "unmetered": number
    }
  },
}
```

```
"devicePoolArn": "string",
"deviceProxy": {
  "host": "string",
  "port": number
},
"deviceSelectionResult": {
  "filters": [
    {
      "attribute": "string",
      "operator": "string",
      "values": [ "string" ]
    }
  ],
  "matchedDevicesCount": number,
  "maxDevices": number
},
"eventCount": number,
"jobTimeoutMinutes": number,
"locale": "string",
"location": {
  "latitude": number,
  "longitude": number
},
"message": "string",
"name": "string",
"networkProfile": {
  "arn": "string",
  "description": "string",
  "downlinkBandwidthBits": number,
  "downlinkDelayMs": number,
  "downlinkJitterMs": number,
  "downlinkLossPercent": number,
  "name": "string",
  "type": "string",
  "uplinkBandwidthBits": number,
  "uplinkDelayMs": number,
  "uplinkJitterMs": number,
  "uplinkLossPercent": number
},
"parsingResultUrl": "string",
"platform": "string",
"radios": {
  "bluetooth": boolean,
  "gps": boolean,
```

```
    "nfc": boolean,
    "wifi": boolean
  },
  "result": "string",
  "resultCode": "string",
  "seed": number,
  "skipAppResign": boolean,
  "started": number,
  "status": "string",
  "stopped": number,
  "testSpecArn": "string",
  "totalJobs": number,
  "type": "string",
  "vpcConfig": {
    "securityGroupIds": [ "string" ],
    "subnetIds": [ "string" ],
    "vpcId": "string"
  },
  "webUrl": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

run

Information about the scheduled run.

Type: [Run](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

IdempotencyException

An entity with the same name already exists.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StopJob

Initiates a stop request for the current job. AWS Device Farm immediately stops the job on the device where tests have not started. You are not billed for this device. On the device where tests have started, setup suite and teardown suite tests run to completion on the device. You are billed for setup, teardown, and any tests that were in progress or already completed.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

Represents the Amazon Resource Name (ARN) of the Device Farm job to stop.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*

Required: Yes

Response Syntax

```
{  
  "job": {  
    "arn": "string",  
    "counters": {  
      "errored": number,  
      "failed": number,  
      "passed": number,  
      "skipped": number,  
    }  
  }  
}
```

```

    "stopped": number,
    "total": number,
    "warned": number
  },
  "created": number,
  "device": {
    "arn": "string",
    "availability": "string",
    "carrier": "string",
    "cpu": {
      "architecture": "string",
      "clock": number,
      "frequency": "string"
    },
    "fleetName": "string",
    "fleetType": "string",
    "formFactor": "string",
    "heapSize": number,
    "image": "string",
    "instances": [
      {
        "arn": "string",
        "deviceArn": "string",
        "instanceProfile": {
          "arn": "string",
          "description": "string",
          "excludeAppPackagesFromCleanup": [ "string" ],
          "name": "string",
          "packageCleanup": boolean,
          "rebootAfterUse": boolean
        },
        "labels": [ "string" ],
        "status": "string",
        "udid": "string"
      }
    ],
    "manufacturer": "string",
    "memory": number,
    "model": "string",
    "modelId": "string",
    "name": "string",
    "os": "string",
    "platform": "string",
    "radio": "string",

```

```
    "remoteAccessEnabled": boolean,
    "remoteDebugEnabled": boolean,
    "resolution": {
      "height": number,
      "width": number
    }
  },
  "deviceMinutes": {
    "metered": number,
    "total": number,
    "unmetered": number
  },
  "instanceArn": "string",
  "message": "string",
  "name": "string",
  "result": "string",
  "started": number,
  "status": "string",
  "stopped": number,
  "type": "string",
  "videoCapture": boolean,
  "videoEndpoint": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[job](#)

The job that was stopped.

Type: [Job](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StopRemoteAccessSession

Ends a specified remote access session.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the remote access session to stop.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "remoteAccessSession": {  
    "arn": "string",  
    "billingMethod": "string",  
    "clientId": "string",  
    "created": number,  
    "device": {  
      "arn": "string",  
      "availability": "string",  
      "carrier": "string",  
      "cpu": {  
        "architecture": "string",
```

```
    "clock": number,
    "frequency": "string"
  },
  "fleetName": "string",
  "fleetType": "string",
  "formFactor": "string",
  "heapSize": number,
  "image": "string",
  "instances": [
    {
      "arn": "string",
      "deviceArn": "string",
      "instanceProfile": {
        "arn": "string",
        "description": "string",
        "excludeAppPackagesFromCleanup": [ "string" ],
        "name": "string",
        "packageCleanup": boolean,
        "rebootAfterUse": boolean
      },
      "labels": [ "string" ],
      "status": "string",
      "udid": "string"
    }
  ],
  "manufacturer": "string",
  "memory": number,
  "model": "string",
  "modelId": "string",
  "name": "string",
  "os": "string",
  "platform": "string",
  "radio": "string",
  "remoteAccessEnabled": boolean,
  "remoteDebugEnabled": boolean,
  "resolution": {
    "height": number,
    "width": number
  }
},
"deviceMinutes": {
  "metered": number,
  "total": number,
  "unmetered": number
}
```

```
    },
    "deviceProxy": {
      "host": "string",
      "port": number
    },
    "deviceUdid": "string",
    "endpoint": "string",
    "hostAddress": "string",
    "instanceArn": "string",
    "interactionMode": "string",
    "message": "string",
    "name": "string",
    "remoteDebugEnabled": boolean,
    "remoteRecordAppArn": "string",
    "remoteRecordEnabled": boolean,
    "result": "string",
    "skipAppResign": boolean,
    "started": number,
    "status": "string",
    "stopped": number,
    "vpcConfig": {
      "securityGroupIds": [ "string" ],
      "subnetIds": [ "string" ],
      "vpcId": "string"
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

remoteAccessSession

A container that represents the metadata from the service about the remote access session you are stopping.

Type: [RemoteAccessSession](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StopRun

Initiates a stop request for the current test run. AWS Device Farm immediately stops the run on devices where tests have not started. You are not billed for these devices. On devices where tests have started executing, setup suite and teardown suite tests run to completion on those devices. You are billed for setup, teardown, and any tests that were in progress or already completed.

Request Syntax

```
{
  "arn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

Represents the Amazon Resource Name (ARN) of the Device Farm run to stop.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{
  "run": {
    "appUpload": "string",
    "arn": "string",
    "billingMethod": "string",
    "completedJobs": number,
    "counters": {
      "errored": number,
```

```
    "failed": number,
    "passed": number,
    "skipped": number,
    "stopped": number,
    "total": number,
    "warned": number
  },
  "created": number,
  "customerArtifactPaths": {
    "androidPaths": [ "string" ],
    "deviceHostPaths": [ "string" ],
    "iosPaths": [ "string" ]
  },
  "deviceMinutes": {
    "metered": number,
    "total": number,
    "unmetered": number
  },
  "devicePoolArn": "string",
  "deviceProxy": {
    "host": "string",
    "port": number
  },
  "deviceSelectionResult": {
    "filters": [
      {
        "attribute": "string",
        "operator": "string",
        "values": [ "string" ]
      }
    ],
    "matchedDevicesCount": number,
    "maxDevices": number
  },
  "eventCount": number,
  "jobTimeoutMinutes": number,
  "locale": "string",
  "location": {
    "latitude": number,
    "longitude": number
  },
  "message": "string",
  "name": "string",
  "networkProfile": {
```

```

    "arn": "string",
    "description": "string",
    "downlinkBandwidthBits": number,
    "downlinkDelayMs": number,
    "downlinkJitterMs": number,
    "downlinkLossPercent": number,
    "name": "string",
    "type": "string",
    "uplinkBandwidthBits": number,
    "uplinkDelayMs": number,
    "uplinkJitterMs": number,
    "uplinkLossPercent": number
  },
  "parsingResultUrl": "string",
  "platform": "string",
  "radios": {
    "bluetooth": boolean,
    "gps": boolean,
    "nfc": boolean,
    "wifi": boolean
  },
  "result": "string",
  "resultCode": "string",
  "seed": number,
  "skipAppResign": boolean,
  "started": number,
  "status": "string",
  "stopped": number,
  "testSpecArn": "string",
  "totalJobs": number,
  "type": "string",
  "vpcConfig": {
    "securityGroupIds": [ "string" ],
    "subnetIds": [ "string" ],
    "vpcId": "string"
  },
  "webUrl": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[run](#)

The run that was stopped.

Type: [Run](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Associates the specified tags to a resource with the specified `resourceArn`. If existing tags on a resource are not specified in the request parameters, they are not changed. When a resource is deleted, the tags associated with that resource are also deleted.

Request Syntax

```
{
  "ResourceARN": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ResourceARN

The Amazon Resource Name (ARN) of the resource or resources to which to add tags. You can associate tags with the following Device Farm resources: PROJECT, RUN, NETWORK_PROFILE, INSTANCE_PROFILE, DEVICE_INSTANCE, SESSION, DEVICE_POOL, DEVICE, and VPCE_CONFIGURATION.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: Yes

Tags

The tags to add to the resource. A tag is an array of key-value pairs. Tag keys can have a maximum character length of 128 characters. Tag values can have a maximum length of 256 characters.

Type: Array of [Tag](#) objects

Array Members: Maximum number of 150 items.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

TagOperationException

The operation was not successful. Try again.

HTTP Status Code: 400

TagPolicyException

The request doesn't comply with the AWS Identity and Access Management (IAM) tag policy. Correct your request and then retry it.

HTTP Status Code: 400

TooManyTagsException

The list of tags on the repository is over the limit. The maximum number of tags that can be applied to a repository is 50.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Deletes the specified tags from a resource.

Request Syntax

```
{  
  "ResourceARN": "string",  
  "TagKeys": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ResourceARN](#)

The Amazon Resource Name (ARN) of the resource or resources from which to delete tags. You can associate tags with the following Device Farm resources: PROJECT, RUN, NETWORK_PROFILE, INSTANCE_PROFILE, DEVICE_INSTANCE, SESSION, DEVICE_POOL, DEVICE, and VPCE_CONFIGURATION.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

[TagKeys](#)

The keys of the tags to be removed.

Type: Array of strings

Array Members: Maximum number of 150 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

TagOperationException

The operation was not successful. Try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateDeviceInstance

Updates information about a private device instance.

Request Syntax

```
{  
  "arn": "string",  
  "labels": [ "string" ],  
  "profileArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the device instance.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

labels

An array of strings that you want to associate with the device instance.

Type: Array of strings

Required: No

profileArn

The ARN of the profile that you want to associate with the device instance.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

Response Syntax

```
{
  "deviceInstance": {
    "arn": "string",
    "deviceArn": "string",
    "instanceProfile": {
      "arn": "string",
      "description": "string",
      "excludeAppPackagesFromCleanup": [ "string" ],
      "name": "string",
      "packageCleanup": boolean,
      "rebootAfterUse": boolean
    },
    "labels": [ "string" ],
    "status": "string",
    "udid": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

deviceInstance

An object that contains information about your device instance.

Type: [DeviceInstance](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateDevicePool

Modifies the name, description, and rules in a device pool given the attributes and the pool ARN. Rule updates are all-or-nothing, meaning they can only be updated as a whole (or not at all).

Request Syntax

```
{
  "arn": "string",
  "clearMaxDevices": boolean,
  "description": "string",
  "maxDevices": number,
  "name": "string",
  "rules": [
    {
      "attribute": "string",
      "operator": "string",
      "value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the Device Farm device pool to update.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*

Required: Yes

clearMaxDevices

Sets whether the maxDevices parameter applies to your device pool. If you set this parameter to true, the maxDevices parameter does not apply, and Device Farm does not limit the

number of devices that it adds to your device pool. In this case, Device Farm adds all available devices that meet the criteria specified in the `rules` parameter.

If you use this parameter in your request, you cannot use the `maxDevices` parameter in the same request.

Type: Boolean

Required: No

description

A description of the device pool to update.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

maxDevices

The number of devices that Device Farm can add to your device pool. Device Farm adds devices that are available and that meet the criteria that you assign for the `rules` parameter. Depending on how many devices meet these constraints, your device pool might contain fewer devices than the value for this parameter.

By specifying the maximum number of devices, you can control the costs that you incur by running tests.

If you use this parameter in your request, you cannot use the `clearMaxDevices` parameter in the same request.

Type: Integer

Required: No

name

A string that represents the name of the device pool to update.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

[rules](#)

Represents the rules to modify for the device pool. Updating rules is optional. If you update rules for your request, the update replaces the existing rules.

Type: Array of [Rule](#) objects

Required: No

Response Syntax

```
{
  "devicePool": {
    "arn": "string",
    "description": "string",
    "maxDevices": number,
    "name": "string",
    "rules": [
      {
        "attribute": "string",
        "operator": "string",
        "value": "string"
      }
    ],
    "type": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[devicePool](#)

The device pool you just updated.

Type: [DevicePool](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateInstanceProfile

Updates information about an existing private device instance profile.

Request Syntax

```
{  
  "arn": "string",  
  "description": "string",  
  "excludeAppPackagesFromCleanup": [ "string" ],  
  "name": "string",  
  "packageCleanup": boolean,  
  "rebootAfterUse": boolean  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the instance profile.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

description

The updated description for your instance profile.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

excludeAppPackagesFromCleanup

An array of strings that specifies the list of app packages that should not be cleaned up from the device after a test run is over.

The list of packages is only considered if you set `packageCleanup` to `true`.

Type: Array of strings

Required: No

name

The updated name for your instance profile.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

packageCleanup

The updated choice for whether you want to specify package cleanup. The default value is `false` for private devices.

Type: Boolean

Required: No

rebootAfterUse

The updated choice for whether you want to reboot the device after use. The default value is `true`.

Type: Boolean

Required: No

Response Syntax

```
{
  "instanceProfile": {
    "arn": "string",
    "description": "string",
```

```
"excludeAppPackagesFromCleanup": [ "string" ],  
"name": "string",  
"packageCleanup": boolean,  
"rebootAfterUse": boolean  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[instanceProfile](#)

An object that contains information about your instance profile.

Type: [InstanceProfile](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateNetworkProfile

Updates the network profile.

Request Syntax

```
{
  "arn": "string",
  "description": "string",
  "downlinkBandwidthBits": number,
  "downlinkDelayMs": number,
  "downlinkJitterMs": number,
  "downlinkLossPercent": number,
  "name": "string",
  "type": "string",
  "uplinkBandwidthBits": number,
  "uplinkDelayMs": number,
  "uplinkJitterMs": number,
  "uplinkLossPercent": number
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the project for which you want to update network profile settings.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

description

The description of the network profile about which you are returning information.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

[downlinkBandwidthBits](#)

The data throughput rate in bits per second, as an integer from 0 to 104857600.

Type: Long

Required: No

[downlinkDelayMs](#)

Delay time for all packets to destination in milliseconds as an integer from 0 to 2000.

Type: Long

Required: No

[downlinkJitterMs](#)

Time variation in the delay of received packets in milliseconds as an integer from 0 to 2000.

Type: Long

Required: No

[downlinkLossPercent](#)

Proportion of received packets that fail to arrive from 0 to 100 percent.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

[name](#)

The name of the network profile about which you are returning information.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

type

The type of network profile to return information about. Valid values are listed here.

Type: String

Valid Values: CURATED | PRIVATE

Required: No

uplinkBandwidthBits

The data throughput rate in bits per second, as an integer from 0 to 104857600.

Type: Long

Required: No

uplinkDelayMs

Delay time for all packets to destination in milliseconds as an integer from 0 to 2000.

Type: Long

Required: No

uplinkJitterMs

Time variation in the delay of received packets in milliseconds as an integer from 0 to 2000.

Type: Long

Required: No

uplinkLossPercent

Proportion of transmitted packets that fail to arrive from 0 to 100 percent.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

Response Syntax

```
{
  "networkProfile": {
    "arn": "string",
    "description": "string",
    "downlinkBandwidthBits": number,
    "downlinkDelayMs": number,
    "downlinkJitterMs": number,
    "downlinkLossPercent": number,
    "name": "string",
    "type": "string",
    "uplinkBandwidthBits": number,
    "uplinkDelayMs": number,
    "uplinkJitterMs": number,
    "uplinkLossPercent": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

networkProfile

A list of the available network profiles.

Type: [NetworkProfile](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateProject

Modifies the specified project name, given the project ARN and a new name.

Request Syntax

```
{
  "arn": "string",
  "defaultJobTimeoutMinutes": number,
  "name": "string",
  "vpcConfig": {
    "securityGroupIds": [ "string" ],
    "subnetIds": [ "string" ],
    "vpcId": "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the project whose name to update.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

defaultJobTimeoutMinutes

The number of minutes a test run in the project executes before it times out.

Type: Integer

Required: No

name

A string that represents the new name of the project that you are updating.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

vpcConfig

The VPC security groups and subnets that are attached to a project.

Type: [VpcConfig](#) object

Required: No

Response Syntax

```
{
  "project": {
    "arn": "string",
    "created": number,
    "defaultJobTimeoutMinutes": number,
    "name": "string",
    "vpcConfig": {
      "securityGroupIds": [ "string" ],
      "subnetIds": [ "string" ],
      "vpcId": "string"
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

project

The project to update.

Type: [Project](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateTestGridProject

Change details of a project.

Request Syntax

```
{
  "description": "string",
  "name": "string",
  "projectArn": "string",
  "vpcConfig": {
    "securityGroupIds": [ "string" ],
    "subnetIds": [ "string" ],
    "vpcId": "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

description

Human-readable description for the project.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `.*\S.*`

Required: No

name

Human-readable name for the project.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `.*\S.*`

Required: No

[projectArn](#)

ARN of the project to update.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*+`

Required: Yes

[vpcConfig](#)

The VPC security groups and subnets that are attached to a project.

Type: [TestGridVpcConfig](#) object

Required: No

Response Syntax

```
{
  "testGridProject": {
    "arn": "string",
    "created": number,
    "description": "string",
    "name": "string",
    "vpcConfig": {
      "securityGroupIds": [ "string" ],
      "subnetIds": [ "string" ],
      "vpcId": "string"
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

testGridProject

The project, including updated information.

Type: [TestGridProject](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

InternalServiceException

An internal exception was raised in the service. Contact aws-devicefarm-support@amazon.com if you see this error.

HTTP Status Code: 500

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateUpload

Updates an uploaded test spec.

Request Syntax

```
{  
  "arn": "string",  
  "contentType": "string",  
  "editContent": boolean,  
  "name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the uploaded test spec.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

contentType

The upload's content type (for example, application/x-yaml).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 64.

Required: No

editContent

Set to true if the YAML file has changed and must be updated. Otherwise, set to false.

Type: Boolean

Required: No

name

The upload's test spec file name. The name must not contain any forward slashes (/). The test spec file name must end with the .yaml or .yml file extension.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
{
  "upload": {
    "arn": "string",
    "category": "string",
    "contentType": "string",
    "created": number,
    "message": "string",
    "metadata": "string",
    "name": "string",
    "status": "string",
    "type": "string",
    "url": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

upload

A test spec uploaded to Device Farm.

Type: Upload object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateVPCEConfiguration

Updates information about an Amazon Virtual Private Cloud (VPC) endpoint configuration.

Request Syntax

```
{  
  "arn": "string",  
  "serviceDnsName": "string",  
  "vpceConfigurationDescription": "string",  
  "vpceConfigurationName": "string",  
  "vpceServiceName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the VPC endpoint configuration you want to update.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*

Required: Yes

serviceDnsName

The DNS (domain) name used to connect to your private service in your VPC. The DNS name must not already be in use on the internet.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

vpceConfigurationDescription

An optional description that provides details about your VPC endpoint configuration.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

vpceConfigurationName

The friendly name you give to your VPC endpoint configuration to manage your configurations more easily.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

vpceServiceName

The name of the VPC endpoint service running in your AWS account that you want Device Farm to test.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

Response Syntax

```
{
  "vpceConfiguration": {
    "arn": "string",
    "serviceDnsName": "string",
    "vpceConfigurationDescription": "string",
    "vpceConfigurationName": "string",
    "vpceServiceName": "string"
  }
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

vpceConfiguration

An object that contains information about your VPC endpoint configuration.

Type: [VPCEConfiguration](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ArgumentException

An invalid argument was specified.

HTTP Status Code: 400

InvalidOperationException

There was an error with the update request, or you do not have sufficient permissions to update this VPC endpoint configuration.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS Device Farm API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AccountSettings](#)
- [Artifact](#)
- [Counters](#)
- [CPU](#)
- [CreateRemoteAccessSessionConfiguration](#)
- [CustomerArtifactPaths](#)
- [Device](#)
- [DeviceFilter](#)
- [DeviceInstance](#)
- [DeviceMinutes](#)
- [DevicePool](#)
- [DevicePoolCompatibilityResult](#)
- [DeviceProxy](#)
- [DeviceSelectionConfiguration](#)
- [DeviceSelectionResult](#)
- [ExecutionConfiguration](#)
- [IncompatibilityMessage](#)
- [InstanceProfile](#)
- [Job](#)
- [ListTestGridProjectsRequest](#)

- [ListTestGridSessionsRequest](#)
- [Location](#)
- [MonetaryAmount](#)
- [NetworkProfile](#)
- [Offering](#)
- [OfferingPromotion](#)
- [OfferingStatus](#)
- [OfferingTransaction](#)
- [Problem](#)
- [ProblemDetail](#)
- [Project](#)
- [Radios](#)
- [RecurringCharge](#)
- [RemoteAccessSession](#)
- [Resolution](#)
- [Rule](#)
- [Run](#)
- [Sample](#)
- [ScheduleRunConfiguration](#)
- [ScheduleRunTest](#)
- [Suite](#)
- [Tag](#)
- [Test](#)
- [TestGridProject](#)
- [TestGridSession](#)
- [TestGridSessionAction](#)
- [TestGridSessionArtifact](#)
- [TestGridVpcConfig](#)
- [TrialMinutes](#)
- [UniqueProblem](#)

- [Upload](#)
- [VpcConfig](#)
- [VPCEConfiguration](#)

AccountSettings

A container for account-level settings in AWS Device Farm.

Contents

awsAccountNumber

The AWS account number specified in the AccountSettings container.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 16.

Required: No

defaultJobTimeoutMinutes

The default number of minutes (at the account level) a test run executes before it times out.
The default value is 150 minutes.

Type: Integer

Required: No

maxJobTimeoutMinutes

The maximum number of minutes a test run executes before it times out.

Type: Integer

Required: No

maxSlots

The maximum number of device slots that the AWS account can purchase. Each maximum is expressed as an `offering-id:number` pair, where the `offering-id` represents one of the IDs returned by the `ListOfferings` command.

Type: String to integer map

Required: No

skipAppResign

When set to `true`, for private devices, Device Farm does not sign your app again. For public devices, Device Farm always signs your apps again.

For more information about how Device Farm re-signs your apps, see [Do you modify my app?](#) in the *AWS Device Farm FAQs*.

Type: Boolean

Required: No

trialMinutes

Information about an AWS account's usage of free trial device minutes.

Type: [TrialMinutes](#) object

Required: No

unmeteredDevices

Returns the unmetered devices you have purchased or want to purchase.

Type: String to integer map

Valid Keys: ANDROID | IOS

Required: No

unmeteredRemoteAccessDevices

Returns the unmetered remote access devices you have purchased or want to purchase.

Type: String to integer map

Valid Keys: ANDROID | IOS

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Artifact

Represents the output of a test. Examples of artifacts include logs and screenshots.

Contents

arn

The artifact's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

extension

The artifact's file extension.

Type: String

Required: No

name

The artifact's name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

type

The artifact's type.

Allowed values include the following:

- UNKNOWN
- SCREENSHOT

- `DEVICE_LOG`
- `MESSAGE_LOG`
- `VIDEO_LOG`
- `RESULT_LOG`
- `SERVICE_LOG`
- `WEBKIT_LOG`
- `INSTRUMENTATION_OUTPUT`
- `EXERCISER_MONKEY_OUTPUT`: the artifact (log) generated by an Android fuzz test.
- `APPIUM_SERVER_OUTPUT`
- `APPIUM_JAVA_OUTPUT`
- `APPIUM_JAVA_XML_OUTPUT`
- `APPIUM_PYTHON_OUTPUT`
- `APPIUM_PYTHON_XML_OUTPUT`
- `APPLICATION_CRASH_REPORT`
- `XCTEST_LOG`
- `VIDEO`
- `CUSTOMER_ARTIFACT`
- `CUSTOMER_ARTIFACT_LOG`
- `TESTSPEC_OUTPUT`

Type: String

Valid Values: `UNKNOWN` | `SCREENSHOT` | `DEVICE_LOG` | `MESSAGE_LOG` | `VIDEO_LOG` | `RESULT_LOG` | `SERVICE_LOG` | `WEBKIT_LOG` | `INSTRUMENTATION_OUTPUT` | `EXERCISER_MONKEY_OUTPUT` | `CALABASH_JSON_OUTPUT` | `CALABASH_PRETTY_OUTPUT` | `CALABASH_STANDARD_OUTPUT` | `CALABASH_JAVA_XML_OUTPUT` | `AUTOMATION_OUTPUT` | `APPIUM_SERVER_OUTPUT` | `APPIUM_JAVA_OUTPUT` | `APPIUM_JAVA_XML_OUTPUT` | `APPIUM_PYTHON_OUTPUT` | `APPIUM_PYTHON_XML_OUTPUT` | `EXPLORER_EVENT_LOG` | `EXPLORER_SUMMARY_LOG` | `APPLICATION_CRASH_REPORT` | `XCTEST_LOG` | `VIDEO` | `CUSTOMER_ARTIFACT` | `CUSTOMER_ARTIFACT_LOG` | `TESTSPEC_OUTPUT`

Required: No

url

The presigned Amazon S3 URL that can be used with a GET request to download the artifact's file.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Counters

Represents entity counters.

Contents

errored

The number of errored entities.

Type: Integer

Required: No

failed

The number of failed entities.

Type: Integer

Required: No

passed

The number of passed entities.

Type: Integer

Required: No

skipped

The number of skipped entities.

Type: Integer

Required: No

stopped

The number of stopped entities.

Type: Integer

Required: No

total

The total number of entities.

Type: Integer

Required: No

warned

The number of warned entities.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CPU

Represents the amount of CPU that an app is using on a physical device. Does not represent system-wide CPU usage.

Contents

architecture

The CPU's architecture (for example, x86 or ARM).

Type: String

Required: No

clock

The clock speed of the device's CPU, expressed in hertz (Hz). For example, a 1.2 GHz CPU is expressed as 1200000000.

Type: Double

Required: No

frequency

The CPU's frequency.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CreateRemoteAccessSessionConfiguration

Configuration settings for a remote access session, including billing method.

Contents

billingMethod

The billing method for the remote access session.

Type: String

Valid Values: METERED | UNMETERED

Required: No

deviceProxy

The device proxy to be configured on the device for the remote access session.

Type: [DeviceProxy](#) object

Required: No

vpceConfigurationArns

An array of ARNs included in the VPC endpoint configuration.

Type: Array of strings

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

CustomerArtifactPaths

A JSON object that specifies the paths where the artifacts generated by the customer's tests, on the device or in the test environment, are pulled from.

Specify `deviceHostPaths` and optionally specify either `iosPaths` or `androidPaths`.

For web app tests, you can specify both `iosPaths` and `androidPaths`.

Contents

androidPaths

Comma-separated list of paths on the Android device where the artifacts generated by the customer's tests are pulled from.

Type: Array of strings

Required: No

deviceHostPaths

Comma-separated list of paths in the test execution environment where the artifacts generated by the customer's tests are pulled from.

Type: Array of strings

Required: No

iosPaths

Comma-separated list of paths on the iOS device where the artifacts generated by the customer's tests are pulled from.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Device

Represents a device type that an app is tested against.

Contents

arn

The device's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

availability

Indicates how likely a device is available for a test run. Currently available in the [ListDevices](#) and [GetDevice](#) API methods.

Type: String

Valid Values: `TEMPORARY_NOT_AVAILABLE` | `BUSY` | `AVAILABLE` | `HIGHLY_AVAILABLE`

Required: No

carrier

The device's carrier.

Type: String

Required: No

cpu

Information about the device's CPU.

Type: [CPU](#) object

Required: No

fleetName

The name of the fleet to which this device belongs.

Type: String

Required: No

fleetType

The type of fleet to which this device belongs. Possible values are PRIVATE and PUBLIC.

Type: String

Required: No

formFactor

The device's form factor.

Allowed values include:

- PHONE
- TABLET

Type: String

Valid Values: PHONE | TABLET

Required: No

heapSize

The device's heap size, expressed in bytes.

Type: Long

Required: No

image

The device's image name.

Type: String

Required: No

instances

The instances that belong to this device.

Type: Array of [DeviceInstance](#) objects

Required: No

manufacturer

The device's manufacturer name.

Type: String

Required: No

memory

The device's total memory size, expressed in bytes.

Type: Long

Required: No

model

The device's model name.

Type: String

Required: No

modelId

The device's model ID.

Type: String

Required: No

name

The device's display name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

os

The device's operating system type.

Type: String

Required: No

platform

The device's platform.

Allowed values include:

- ANDROID
- IOS

Type: String

Valid Values: ANDROID | IOS

Required: No

radio

The device's radio.

Type: String

Required: No

remoteAccessEnabled

Specifies whether remote access has been enabled for the specified device.

Type: Boolean

Required: No

remoteDebugEnabled

This flag is set to `true` if remote debugging is enabled for the device.

Remote debugging is [no longer supported](#).

Type: Boolean

Required: No

resolution

The resolution of the device.

Type: [Resolution](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeviceFilter

Represents a device filter used to select a set of devices to be included in a test run. This data structure is passed in as the `deviceSelectionConfiguration` parameter to `ScheduleRun`. For an example of the JSON request syntax, see [ScheduleRun](#).

It is also passed in as the `filters` parameter to `ListDevices`. For an example of the JSON request syntax, see [ListDevices](#).

Contents

attribute

The aspect of a device such as platform or model used as the selection criteria in a device filter.

The supported operators for each attribute are provided in the following list.

ARN

The Amazon Resource Name (ARN) of the device (for example, `arn:aws:devicefarm:us-west-2::device:12345Example`).

Supported operators: `EQUALS`, `IN`, `NOT_IN`

PLATFORM

The device platform. Valid values are `ANDROID` or `IOS`.

Supported operators: `EQUALS`

OS_VERSION

The operating system version (for example, `10.3.2`).

Supported operators: `EQUALS`, `GREATER_THAN`, `GREATER_THAN_OR_EQUALS`, `IN`, `LESS_THAN`, `LESS_THAN_OR_EQUALS`, `NOT_IN`

MODEL

The device model (for example, `iPad 5th Gen`).

Supported operators: `CONTAINS`, `EQUALS`, `IN`, `NOT_IN`

AVAILABILITY

The current availability of the device. Valid values are AVAILABLE, HIGHLY_AVAILABLE, BUSY, or TEMPORARY_NOT_AVAILABLE.

Supported operators: EQUALS

FORM_FACTOR

The device form factor. Valid values are PHONE or TABLET.

Supported operators: EQUALS

MANUFACTURER

The device manufacturer (for example, Apple).

Supported operators: EQUALS, IN, NOT_IN

REMOTE_ACCESS_ENABLED

Whether the device is enabled for remote access. Valid values are TRUE or FALSE.

Supported operators: EQUALS

REMOTE_DEBUG_ENABLED

Whether the device is enabled for remote debugging. Valid values are TRUE or FALSE.

Supported operators: EQUALS

Because remote debugging is [no longer supported](#), this filter is ignored.

INSTANCE_ARN

The Amazon Resource Name (ARN) of the device instance.

Supported operators: EQUALS, IN, NOT_IN

INSTANCE_LABELS

The label of the device instance.

Supported operators: CONTAINS

FLEET_TYPE

The fleet type. Valid values are PUBLIC or PRIVATE.

Supported operators: EQUALS

Type: String

Valid Values: ARN | PLATFORM | OS_VERSION | MODEL | AVAILABILITY
| FORM_FACTOR | MANUFACTURER | REMOTE_ACCESS_ENABLED |
REMOTE_DEBUG_ENABLED | INSTANCE_ARN | INSTANCE_LABELS | FLEET_TYPE

Required: Yes

operator

Specifies how Device Farm compares the filter's attribute to the value. See the attribute descriptions.

Type: String

Valid Values: EQUALS | LESS_THAN | LESS_THAN_OR_EQUALS | GREATER_THAN |
GREATER_THAN_OR_EQUALS | IN | NOT_IN | CONTAINS

Required: Yes

values

An array of one or more filter values used in a device filter.

Operator Values

- The IN and NOT_IN operators can take a values array that has more than one element.
- The other operators require an array with a single element.

Attribute Values

- The PLATFORM attribute can be set to ANDROID or IOS.
- The AVAILABILITY attribute can be set to AVAILABLE, HIGHLY_AVAILABLE, BUSY, or TEMPORARY_NOT_AVAILABLE.
- The FORM_FACTOR attribute can be set to PHONE or TABLET.
- The FLEET_TYPE attribute can be set to PUBLIC or PRIVATE.

Type: Array of strings

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeviceInstance

Represents the device instance.

Contents

arn

The Amazon Resource Name (ARN) of the device instance.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

deviceArn

The ARN of the device.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

instanceProfile

A object that contains information about the instance profile.

Type: [InstanceProfile](#) object

Required: No

labels

An array of strings that describe the device instance.

Type: Array of strings

Required: No

status

The status of the device instance. Valid values are listed here.

Type: String

Valid Values: IN_USE | PREPARING | AVAILABLE | NOT_AVAILABLE

Required: No

udid

Unique device identifier for the device instance.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeviceMinutes

Represents the total (metered or unmetered) minutes used by the resource to run tests. Contains the sum of minutes consumed by all children.

Contents

metered

When specified, represents only the sum of metered minutes used by the resource to run tests.

Type: Double

Required: No

total

When specified, represents the total minutes used by the resource to run tests.

Type: Double

Required: No

unmetered

When specified, represents only the sum of unmetered minutes used by the resource to run tests.

Type: Double

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DevicePool

Represents a collection of device types.

Contents

arn

The device pool's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

description

The device pool's description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

maxDevices

The number of devices that Device Farm can add to your device pool. Device Farm adds devices that are available and meet the criteria that you assign for the `rules` parameter. Depending on how many devices meet these constraints, your device pool might contain fewer devices than the value for this parameter.

By specifying the maximum number of devices, you can control the costs that you incur by running tests.

Type: Integer

Required: No

name

The device pool's name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

rules

Information about the device pool's rules.

Type: Array of [Rule](#) objects

Required: No

type

The device pool's type.

Allowed values include:

- CURATED: A device pool that is created and managed by AWS Device Farm.
- PRIVATE: A device pool that is created and managed by the device pool developer.

Type: String

Valid Values: CURATED | PRIVATE

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DevicePoolCompatibilityResult

Represents a device pool compatibility result.

Contents

compatible

Whether the result was compatible with the device pool.

Type: Boolean

Required: No

device

The device (phone or tablet) to return information about.

Type: [Device](#) object

Required: No

incompatibilityMessages

Information about the compatibility.

Type: Array of [IncompatibilityMessage](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeviceProxy

Represents the http/s proxy configuration that will be applied to a device during a run.

Contents

host

Hostname or IPv4 address of the proxy.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^([a-zA-Z0-9])([a-zA-Z0-9- .]+)([a-zA-Z0-9])$`

Required: Yes

port

The port number on which the http/s proxy is listening.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeviceSelectionConfiguration

Represents the device filters used in a test run and the maximum number of devices to be included in the run. It is passed in as the `deviceSelectionConfiguration` request parameter in [ScheduleRun](#).

Contents

filters

Used to dynamically select a set of devices for a test run. A filter is made up of an attribute, an operator, and one or more values.

- **Attribute**

The aspect of a device such as platform or model used as the selection criteria in a device filter.

Allowed values include:

- **ARN**: The Amazon Resource Name (ARN) of the device (for example, `arn:aws:devicefarm:us-west-2::device:12345Example`).
- **PLATFORM**: The device platform. Valid values are `ANDROID` or `IOS`.
- **OS_VERSION**: The operating system version (for example, `10.3.2`).
- **MODEL**: The device model (for example, `iPad 5th Gen`).
- **AVAILABILITY**: The current availability of the device. Valid values are `AVAILABLE`, `HIGHLY_AVAILABLE`, `BUSY`, or `TEMPORARY_NOT_AVAILABLE`.
- **FORM_FACTOR**: The device form factor. Valid values are `PHONE` or `TABLET`.
- **MANUFACTURER**: The device manufacturer (for example, `Apple`).
- **REMOTE_ACCESS_ENABLED**: Whether the device is enabled for remote access. Valid values are `TRUE` or `FALSE`.
- **REMOTE_DEBUG_ENABLED**: Whether the device is enabled for remote debugging. Valid values are `TRUE` or `FALSE`. Because remote debugging is [no longer supported](#), this filter is ignored.
- **INSTANCE_ARN**: The Amazon Resource Name (ARN) of the device instance.
- **INSTANCE_LABELS**: The label of the device instance.

- **Operator**

The filter operator.

- The EQUALS operator is available for every attribute except INSTANCE_LABELS.
- The CONTAINS operator is available for the INSTANCE_LABELS and MODEL attributes.
- The IN and NOT_IN operators are available for the ARN, OS_VERSION, MODEL, MANUFACTURER, and INSTANCE_ARN attributes.
- The LESS_THAN, GREATER_THAN, LESS_THAN_OR_EQUALS, and GREATER_THAN_OR_EQUALS operators are also available for the OS_VERSION attribute.

- **Values**

An array of one or more filter values.

Operator Values

- The IN and NOT_IN operators can take a values array that has more than one element.
- The other operators require an array with a single element.

Attribute Values

- The PLATFORM attribute can be set to ANDROID or IOS.
- The AVAILABILITY attribute can be set to AVAILABLE, HIGHLY_AVAILABLE, BUSY, or TEMPORARY_NOT_AVAILABLE.
- The FORM_FACTOR attribute can be set to PHONE or TABLET.
- The FLEET_TYPE attribute can be set to PUBLIC or PRIVATE.

Type: Array of [DeviceFilter](#) objects

Required: Yes

maxDevices

The maximum number of devices to be included in a test run.

Type: Integer

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeviceSelectionResult

Contains the run results requested by the device selection configuration and how many devices were returned. For an example of the JSON response syntax, see [ScheduleRun](#).

Contents

filters

The filters in a device selection result.

Type: Array of [DeviceFilter](#) objects

Required: No

matchedDevicesCount

The number of devices that matched the device filter selection criteria.

Type: Integer

Required: No

maxDevices

The maximum number of devices to be selected by a device filter and included in a test run.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ExecutionConfiguration

Represents configuration information about a test run, such as the execution timeout (in minutes).

Contents

accountsCleanup

True if account cleanup is enabled at the beginning of the test. Otherwise, false.

Type: Boolean

Required: No

appPackagesCleanup

True if app package cleanup is enabled at the beginning of the test. Otherwise, false.

Type: Boolean

Required: No

jobTimeoutMinutes

The number of minutes a test run executes before it times out.

Type: Integer

Required: No

skipAppResign

When set to `true`, for private devices, Device Farm does not sign your app again. For public devices, Device Farm always signs your apps again.

For more information about how Device Farm re-signs your apps, see [Do you modify my app?](#) in the *AWS Device Farm FAQs*.

Type: Boolean

Required: No

videoCapture

Set to `true` to enable video capture. Otherwise, set to `false`. The default is `true`.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IncompatibilityMessage

Represents information about incompatibility.

Contents

message

A message about the incompatibility.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

type

The type of incompatibility.

Allowed values include:

- ARN
- FORM_FACTOR (for example, phone or tablet)
- MANUFACTURER
- PLATFORM (for example, Android or iOS)
- REMOTE_ACCESS_ENABLED
- APPIUM_VERSION

Type: String

Valid Values: ARN | PLATFORM | FORM_FACTOR | MANUFACTURER |
REMOTE_ACCESS_ENABLED | REMOTE_DEBUG_ENABLED | APPIUM_VERSION |
INSTANCE_ARN | INSTANCE_LABELS | FLEET_TYPE | OS_VERSION | MODEL |
AVAILABILITY

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstanceProfile

Represents the instance profile.

Contents

arn

The Amazon Resource Name (ARN) of the instance profile.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

description

The description of the instance profile.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

excludeAppPackagesFromCleanup

An array of strings containing the list of app packages that should not be cleaned up from the device after a test run completes.

The list of packages is considered only if you set `packageCleanup` to `true`.

Type: Array of strings

Required: No

name

The name of the instance profile.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

packageCleanup

When set to `true`, Device Farm removes app packages after a test run. The default value is `false` for private devices.

Type: Boolean

Required: No

rebootAfterUse

When set to `true`, Device Farm reboots the instance after a test run. The default value is `true`.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Job

Represents a device.

Contents

arn

The job's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

counters

The job's result counters.

Type: [Counters](#) object

Required: No

created

When the job was created.

Type: Timestamp

Required: No

device

The device (phone or tablet).

Type: [Device](#) object

Required: No

deviceMinutes

Represents the total (metered or unmetered) minutes used by the job.

Type: [DeviceMinutes](#) object

Required: No

instanceArn

The ARN of the instance.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: No

message

A message about the job's result.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

name

The job's name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

result

The job's result.

Allowed values include:

- PENDING
- PASSED
- WARNED

- FAILED
- SKIPPED
- ERRORED
- STOPPED

Type: String

Valid Values: PENDING | PASSED | WARNED | FAILED | SKIPPED | ERRORED | STOPPED

Required: No

started

The job's start time.

Type: Timestamp

Required: No

status

The job's status.

Allowed values include:

- PENDING
- PENDING_CONCURRENCY
- PENDING_DEVICE
- PROCESSING
- SCHEDULING
- PREPARING
- RUNNING
- COMPLETED
- STOPPING

Type: String

Valid Values: PENDING | PENDING_CONCURRENCY | PENDING_DEVICE | PROCESSING | SCHEDULING | PREPARING | RUNNING | COMPLETED | STOPPING

Required: No

stopped

The job's stop time.

Type: Timestamp

Required: No

type

The job's type.

Allowed values include the following:

- BUILTIN_FUZZ
- APPIUM_JAVA_JUNIT
- APPIUM_JAVA_TESTNG
- APPIUM_PYTHON
- APPIUM_NODE
- APPIUM_RUBY
- APPIUM_WEB_JAVA_JUNIT
- APPIUM_WEB_JAVA_TESTNG
- APPIUM_WEB_PYTHON
- APPIUM_WEB_NODE
- APPIUM_WEB_RUBY
- INSTRUMENTATION
- XCTEST
- XCTEST_UI

Type: String

Valid Values: BUILTIN_FUZZ | APPIUM_JAVA_JUNIT | APPIUM_JAVA_TESTNG | APPIUM_PYTHON | APPIUM_NODE | APPIUM_RUBY | APPIUM_WEB_JAVA_JUNIT | APPIUM_WEB_JAVA_TESTNG | APPIUM_WEB_PYTHON | APPIUM_WEB_NODE | APPIUM_WEB_RUBY | INSTRUMENTATION | XCTEST | XCTEST_UI

Required: No

videoCapture

This value is set to true if video capture is enabled. Otherwise, it is set to false.

Type: Boolean

Required: No

videoEndpoint

The endpoint for streaming device video.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListTestGridProjectsRequest

Contents

maxResult

Return no more than this number of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

nextToken

From a response, used to continue a paginated listing.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListTestGridSessionsRequest

Contents

projectArn

ARN of a [TestGridProject](#).

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

creationTimeAfter

Return only sessions created after this time.

Type: Timestamp

Required: No

creationTimeBefore

Return only sessions created before this time.

Type: Timestamp

Required: No

endTimeAfter

Return only sessions that ended after this time.

Type: Timestamp

Required: No

endTimeBefore

Return only sessions that ended before this time.

Type: Timestamp

Required: No

maxResult

Return only this many results at a time.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

status

Return only sessions in this state.

Type: String

Valid Values: ACTIVE | CLOSED | ERRORRED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Location

Represents a latitude and longitude pair, expressed in geographic coordinate system degrees (for example, 47.6204, -122.3491).

Elevation is currently not supported.

Contents

latitude

The latitude.

Type: Double

Required: Yes

longitude

The longitude.

Type: Double

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MonetaryAmount

A number that represents the monetary amount for an offering or transaction.

Contents

amount

The numerical amount of an offering or transaction.

Type: Double

Required: No

currencyCode

The currency code of a monetary amount. For example, USD means U.S. dollars.

Type: String

Valid Values: USD

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NetworkProfile

An array of settings that describes characteristics of a network profile.

Contents

arn

The Amazon Resource Name (ARN) of the network profile.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

description

The description of the network profile.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

downlinkBandwidthBits

The data throughput rate in bits per second, as an integer from 0 to 104857600.

Type: Long

Required: No

downlinkDelayMs

Delay time for all packets to destination in milliseconds as an integer from 0 to 2000.

Type: Long

Required: No

downlinkJitterMs

Time variation in the delay of received packets in milliseconds as an integer from 0 to 2000.

Type: Long

Required: No

downlinkLossPercent

Proportion of received packets that fail to arrive from 0 to 100 percent.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

name

The name of the network profile.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

type

The type of network profile. Valid values are listed here.

Type: String

Valid Values: CURATED | PRIVATE

Required: No

uplinkBandwidthBits

The data throughput rate in bits per second, as an integer from 0 to 104857600.

Type: Long

Required: No

uplinkDelayMs

Delay time for all packets to destination in milliseconds as an integer from 0 to 2000.

Type: Long

Required: No

uplinkJitterMs

Time variation in the delay of received packets in milliseconds as an integer from 0 to 2000.

Type: Long

Required: No

uplinkLossPercent

Proportion of transmitted packets that fail to arrive from 0 to 100 percent.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Offering

Represents the metadata of a device offering.

Contents

description

A string that describes the offering.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

id

The ID that corresponds to a device offering.

Type: String

Length Constraints: Minimum length of 32.

Required: No

platform

The platform of the device (for example, ANDROID or IOS).

Type: String

Valid Values: ANDROID | IOS

Required: No

recurringCharges

Specifies whether there are recurring charges for the offering.

Type: Array of [RecurringCharge](#) objects

Required: No

type

The type of offering (for example, RECURRING) for a device.

Type: String

Valid Values: RECURRING

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OfferingPromotion

Represents information about an offering promotion.

Contents

description

A string that describes the offering promotion.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

id

The ID of the offering promotion.

Type: String

Length Constraints: Minimum length of 4.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OfferingStatus

The status of the offering.

Contents

effectiveOn

The date on which the offering is effective.

Type: Timestamp

Required: No

offering

Represents the metadata of an offering status.

Type: [Offering](#) object

Required: No

quantity

The number of available devices in the offering.

Type: Integer

Required: No

type

The type specified for the offering status.

Type: String

Valid Values: PURCHASE | RENEW | SYSTEM

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OfferingTransaction

Represents the metadata of an offering transaction.

Contents

cost

The cost of an offering transaction.

Type: [MonetaryAmount](#) object

Required: No

createdOn

The date on which an offering transaction was created.

Type: Timestamp

Required: No

offeringPromotionId

The ID that corresponds to a device offering promotion.

Type: String

Length Constraints: Minimum length of 4.

Required: No

offeringStatus

The status of an offering transaction.

Type: [OfferingStatus](#) object

Required: No

transactionId

The transaction ID of the offering transaction.

Type: String

Length Constraints: Minimum length of 32.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Problem

Represents a specific warning or failure.

Contents

device

Information about the associated device.

Type: [Device](#) object

Required: No

job

Information about the associated job.

Type: [ProblemDetail](#) object

Required: No

message

A message about the problem's result.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

result

The problem's result.

Allowed values include:

- PENDING
- PASSED
- WARNED
- FAILED
- SKIPPED

- ERRORED
- STOPPED

Type: String

Valid Values: PENDING | PASSED | WARNED | FAILED | SKIPPED | ERRORED | STOPPED

Required: No

run

Information about the associated run.

Type: [ProblemDetail](#) object

Required: No

suite

Information about the associated suite.

Type: [ProblemDetail](#) object

Required: No

test

Information about the associated test.

Type: [ProblemDetail](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ProblemDetail

Information about a problem detail.

Contents

arn

The problem detail's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*+`

Required: No

name

The problem detail's name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Project

Represents an operating-system neutral workspace for running and managing tests.

Contents

arn

The project's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

created

When the project was created.

Type: Timestamp

Required: No

defaultJobTimeoutMinutes

The default number of minutes (at the project level) a test run executes before it times out. The default value is 150 minutes.

Type: Integer

Required: No

name

The project's name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

vpcConfig

The VPC security groups and subnets that are attached to a project.

Type: [VpcConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Radios

Represents the set of radios and their states on a device. Examples of radios include Wi-Fi, GPS, Bluetooth, and NFC.

Contents

bluetooth

True if Bluetooth is enabled at the beginning of the test. Otherwise, false.

Type: Boolean

Required: No

gps

True if GPS is enabled at the beginning of the test. Otherwise, false.

Type: Boolean

Required: No

nfc

True if NFC is enabled at the beginning of the test. Otherwise, false.

Type: Boolean

Required: No

wifi

True if Wi-Fi is enabled at the beginning of the test. Otherwise, false.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RecurringCharge

Specifies whether charges for devices are recurring.

Contents

cost

The cost of the recurring charge.

Type: [MonetaryAmount](#) object

Required: No

frequency

The frequency in which charges recur.

Type: String

Valid Values: MONTHLY

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RemoteAccessSession

Represents information about the remote access session.

Contents

arn

The Amazon Resource Name (ARN) of the remote access session.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

billingMethod

The billing method of the remote access session. Possible values include `METERED` or `UNMETERED`. For more information about metered devices, see [AWS Device Farm terminology](#).

Type: String

Valid Values: `METERED` | `UNMETERED`

Required: No

clientId

Unique identifier of your client for the remote access session. Only returned if remote debugging is enabled for the remote access session.

Remote debugging is [no longer supported](#).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 64.

Required: No

created

The date and time the remote access session was created.

Type: Timestamp

Required: No

device

The device (phone or tablet) used in the remote access session.

Type: [Device](#) object

Required: No

deviceMinutes

The number of minutes a device is used in a remote access session (including setup and teardown minutes).

Type: [DeviceMinutes](#) object

Required: No

deviceProxy

The device proxy configured for the remote access session.

Type: [DeviceProxy](#) object

Required: No

deviceUdid

Unique device identifier for the remote device. Only returned if remote debugging is enabled for the remote access session.

Remote debugging is [no longer supported](#).

Type: String

Required: No

endpoint

The endpoint for the remote access session.

Type: String

Required: No

hostAddress

IP address of the EC2 host where you need to connect to remotely debug devices. Only returned if remote debugging is enabled for the remote access session.

Remote debugging is [no longer supported](#).

Type: String

Length Constraints: Maximum length of 1024.

Required: No

instanceArn

The ARN of the instance.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*+`

Required: No

interactionMode

The interaction mode of the remote access session. Valid values are:

- **INTERACTIVE**: You can interact with the iOS device by viewing, touching, and rotating the screen. You cannot run XCUITest framework-based tests in this mode.
- **NO_VIDEO**: You are connected to the device, but cannot interact with it or view the screen. This mode has the fastest test execution speed. You can run XCUITest framework-based tests in this mode.
- **VIDEO_ONLY**: You can view the screen, but cannot touch or rotate it. You can run XCUITest framework-based tests and watch the screen in this mode.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 64.

Valid Values: `INTERACTIVE` | `NO_VIDEO` | `VIDEO_ONLY`

Required: No

message

A message about the remote access session.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

name

The name of the remote access session.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

remoteDebugEnabled

This flag is set to `true` if remote debugging is enabled for the remote access session.

Remote debugging is [no longer supported](#).

Type: Boolean

Required: No

remoteRecordAppArn

The ARN for the app to be recorded in the remote access session.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

remoteRecordEnabled

This flag is set to `true` if remote recording is enabled for the remote access session.

Type: Boolean

Required: No

result

The result of the remote access session. Can be any of the following:

- PENDING.
- PASSED.
- WARNED.
- FAILED.
- SKIPPED.
- ERRORED.
- STOPPED.

Type: String

Valid Values: PENDING | PASSED | WARNED | FAILED | SKIPPED | ERRORED | STOPPED

Required: No

skipAppResign

When set to `true`, for private devices, Device Farm does not sign your app again. For public devices, Device Farm always signs your apps again.

For more information about how Device Farm re-signs your apps, see [Do you modify my app?](#) in the *AWS Device Farm FAQs*.

Type: Boolean

Required: No

started

The date and time the remote access session was started.

Type: Timestamp

Required: No

status

The status of the remote access session. Can be any of the following:

- PENDING.
- PENDING_CONCURRENCY.
- PENDING_DEVICE.
- PROCESSING.
- SCHEDULING.
- PREPARING.
- RUNNING.
- COMPLETED.
- STOPPING.

Type: String

Valid Values: PENDING | PENDING_CONCURRENCY | PENDING_DEVICE | PROCESSING | SCHEDULING | PREPARING | RUNNING | COMPLETED | STOPPING

Required: No

stopped

The date and time the remote access session was stopped.

Type: Timestamp

Required: No

vpcConfig

The VPC security groups and subnets that are attached to a project.

Type: [VpcConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

Resolution

Represents the screen resolution of a device in height and width, expressed in pixels.

Contents

height

The screen resolution's height, expressed in pixels.

Type: Integer

Required: No

width

The screen resolution's width, expressed in pixels.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Rule

Represents a condition for a device pool.

Contents

attribute

The rule's stringified attribute. For example, specify the value as `"\"abc\""`.

The supported operators for each attribute are provided in the following list.

APPIUM_VERSION

The Appium version for the test.

Supported operators: CONTAINS

ARN

The Amazon Resource Name (ARN) of the device (for example, `arn:aws:devicefarm:us-west-2::device:12345Example`).

Supported operators: EQUALS, IN, NOT_IN

AVAILABILITY

The current availability of the device. Valid values are AVAILABLE, HIGHLY_AVAILABLE, BUSY, or TEMPORARY_NOT_AVAILABLE.

Supported operators: EQUALS

FLEET_TYPE

The fleet type. Valid values are PUBLIC or PRIVATE.

Supported operators: EQUALS

FORM_FACTOR

The device form factor. Valid values are PHONE or TABLET.

Supported operators: EQUALS, IN, NOT_IN

INSTANCE_ARN

The Amazon Resource Name (ARN) of the device instance.

Supported operators: IN, NOT_IN

INSTANCE_LABELS

The label of the device instance.

Supported operators: CONTAINS

MANUFACTURER

The device manufacturer (for example, Apple).

Supported operators: EQUALS, IN, NOT_IN

MODEL

The device model, such as Apple iPad Air 2 or Google Pixel.

Supported operators: CONTAINS, EQUALS, IN, NOT_IN

OS_VERSION

The operating system version (for example, 10.3.2).

Supported operators: EQUALS, GREATER_THAN, GREATER_THAN_OR_EQUALS, IN, LESS_THAN, LESS_THAN_OR_EQUALS, NOT_IN

PLATFORM

The device platform. Valid values are ANDROID or IOS.

Supported operators: EQUALS, IN, NOT_IN

REMOTE_ACCESS_ENABLED

Whether the device is enabled for remote access. Valid values are TRUE or FALSE.

Supported operators: EQUALS

REMOTE_DEBUG_ENABLED

Whether the device is enabled for remote debugging. Valid values are TRUE or FALSE.

Supported operators: EQUALS

Because remote debugging is [no longer supported](#), this filter is ignored.

Type: String

Valid Values: ARN | PLATFORM | FORM_FACTOR | MANUFACTURER | REMOTE_ACCESS_ENABLED | REMOTE_DEBUG_ENABLED | APPIUM_VERSION | INSTANCE_ARN | INSTANCE_LABELS | FLEET_TYPE | OS_VERSION | MODEL | AVAILABILITY

Required: No

operator

Specifies how Device Farm compares the rule's attribute to the value. For the operators that are supported by each attribute, see the attribute descriptions.

Type: String

Valid Values: EQUALS | LESS_THAN | LESS_THAN_OR_EQUALS | GREATER_THAN | GREATER_THAN_OR_EQUALS | IN | NOT_IN | CONTAINS

Required: No

value

The rule's value.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Run

Represents a test run on a set of devices with a given app package, test parameters, and so on.

Contents

appUpload

An app to upload or that has been uploaded.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

arn

The run's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

billingMethod

Specifies the billing method for a test run: `metered` or `unmetered`. If the parameter is not specified, the default value is `metered`.

Note

If you have unmetered device slots, you must set this to `unmetered` to use them. Otherwise, the run is counted toward metered device minutes.

Type: String

Valid Values: METERED | UNMETERED

Required: No

completedJobs

The total number of completed jobs.

Type: Integer

Required: No

counters

The run's result counters.

Type: [Counters](#) object

Required: No

created

When the run was created.

Type: Timestamp

Required: No

customerArtifactPaths

Output CustomerArtifactPaths object for the test run.

Type: [CustomerArtifactPaths](#) object

Required: No

deviceMinutes

Represents the total (metered or unmetered) minutes used by the test run.

Type: [DeviceMinutes](#) object

Required: No

devicePoolArn

The ARN of the device pool for the run.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

deviceProxy

The device proxy configured for the devices in the run.

Type: [DeviceProxy](#) object

Required: No

deviceSelectionResult

The results of a device filter used to select the devices for a test run.

Type: [DeviceSelectionResult](#) object

Required: No

eventCount

For fuzz tests, this is the number of events, between 1 and 10000, that the UI fuzz test should perform.

Type: Integer

Required: No

jobTimeoutMinutes

The number of minutes the job executes before it times out.

Type: Integer

Required: No

locale

Information about the locale that is used for the run.

Type: String

Required: No

location

Information about the location that is used for the run.

Type: [Location](#) object

Required: No

message

A message about the run's result.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

name

The run's name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

networkProfile

The network profile being used for a test run.

Type: [NetworkProfile](#) object

Required: No

parsingResultUrl

Read-only URL for an object in an S3 bucket where you can get the parsing results of the test package. If the test package doesn't parse, the reason why it doesn't parse appears in the file that this URL points to.

Type: String

Required: No

platform

The run's platform.

Allowed values include:

- ANDROID
- IOS

Type: String

Valid Values: ANDROID | IOS

Required: No

radios

Information about the radio states for the run.

Type: [Radios](#) object

Required: No

result

The run's result.

Allowed values include:

- PENDING
- PASSED
- WARNED
- FAILED
- SKIPPED
- ERRORED
- STOPPED

Type: String

Valid Values: PENDING | PASSED | WARNED | FAILED | SKIPPED | ERRORED | STOPPED

Required: No

resultCode

Supporting field for the result field. Set only if `result` is `SKIPPED`. `PARSING_FAILED` if the result is skipped because of test package parsing failure.

Type: String

Valid Values: `PARSING_FAILED` | `VPC_ENDPOINT_SETUP_FAILED`

Required: No

seed

For fuzz tests, this is a seed to use for randomizing the UI fuzz test. Using the same seed value between tests ensures identical event sequences.

Type: Integer

Required: No

skipAppResign

When set to `true`, for private devices, Device Farm does not sign your app again. For public devices, Device Farm always signs your apps again.

For more information about how Device Farm re-signs your apps, see [Do you modify my app?](#) in the *AWS Device Farm FAQs*.

Type: Boolean

Required: No

started

The run's start time.

Type: Timestamp

Required: No

status

The run's status.

Allowed values include:

- PENDING
- PENDING_CONCURRENCY
- PENDING_DEVICE
- PROCESSING
- SCHEDULING
- PREPARING
- RUNNING
- COMPLETED
- STOPPING

Type: String

Valid Values: PENDING | PENDING_CONCURRENCY | PENDING_DEVICE | PROCESSING | SCHEDULING | PREPARING | RUNNING | COMPLETED | STOPPING

Required: No

stopped

The run's stop time.

Type: Timestamp

Required: No

testSpecArn

The ARN of the YAML-formatted test specification for the run.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: No

totalJobs

The total number of jobs for the run.

Type: Integer

Required: No

type

The run's type.

Must be one of the following values:

- BUILTIN_FUZZ
- APPIUM_JAVA_JUNIT
- APPIUM_JAVA_TESTNG
- APPIUM_PYTHON
- APPIUM_NODE
- APPIUM_RUBY
- APPIUM_WEB_JAVA_JUNIT
- APPIUM_WEB_JAVA_TESTNG
- APPIUM_WEB_PYTHON
- APPIUM_WEB_NODE
- APPIUM_WEB_RUBY
- INSTRUMENTATION
- XCTEST
- XCTEST_UI

Type: String

Valid Values: BUILTIN_FUZZ | APPIUM_JAVA_JUNIT | APPIUM_JAVA_TESTNG | APPIUM_PYTHON | APPIUM_NODE | APPIUM_RUBY | APPIUM_WEB_JAVA_JUNIT | APPIUM_WEB_JAVA_TESTNG | APPIUM_WEB_PYTHON | APPIUM_WEB_NODE | APPIUM_WEB_RUBY | INSTRUMENTATION | XCTEST | XCTEST_UI

Required: No

vpcConfig

The VPC security groups and subnets that are attached to a project.

Type: [VpcConfig](#) object

Required: No

webUrl

The Device Farm console URL for the recording of the run.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Sample

Represents a sample of performance data.

Contents

arn

The sample's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

type

The sample's type.

Must be one of the following values:

- CPU: A CPU sample type. This is expressed as the app processing CPU time (including child processes) as reported by process, as a percentage.
- MEMORY: A memory usage sample type. This is expressed as the total proportional set size of an app process, in kilobytes.
- NATIVE_AVG_DRAWTIME
- NATIVE_FPS
- NATIVE_FRAMES
- NATIVE_MAX_DRAWTIME
- NATIVE_MIN_DRAWTIME
- OPENGGL_AVG_DRAWTIME
- OPENGGL_FPS
- OPENGGL_FRAMES
- OPENGGL_MAX_DRAWTIME
- OPENGGL_MIN_DRAWTIME
- RX

- **RX_RATE**: The total number of bytes per second (TCP and UDP) that are sent, by app process.
- **THREADS**: A threads sample type. This is expressed as the total number of threads per app process.
- **TX**
- **TX_RATE**: The total number of bytes per second (TCP and UDP) that are received, by app process.

Type: String

Valid Values: CPU | MEMORY | THREADS | RX_RATE | TX_RATE | RX | TX |
NATIVE_FRAMES | NATIVE_FPS | NATIVE_MIN_DRAWTIME | NATIVE_AVG_DRAWTIME |
NATIVE_MAX_DRAWTIME | OPENGL_FRAMES | OPENGL_FPS | OPENGL_MIN_DRAWTIME |
OPENGL_AVG_DRAWTIME | OPENGL_MAX_DRAWTIME

Required: No

url

The presigned Amazon S3 URL that can be used with a GET request to download the sample's file.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ScheduleRunConfiguration

Represents the settings for a run. Includes things like location, radio states, auxiliary apps, and network profiles.

Contents

auxiliaryApps

A list of upload ARNs for app packages to be installed with your app.

Type: Array of strings

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

billingMethod

Specifies the billing method for a test run: `metered` or `unmetered`. If the parameter is not specified, the default value is `metered`.

Note

If you have purchased unmetered device slots, you must set this parameter to `unmetered` to make use of them. Otherwise, your run counts against your metered time.

Type: String

Valid Values: `METERED` | `UNMETERED`

Required: No

customerArtifactPaths

Input `CustomerArtifactPaths` object for the scheduled run configuration.

Type: [CustomerArtifactPaths](#) object

Required: No

deviceProxy

The device proxy to be configured on the device for the run.

Type: [DeviceProxy](#) object

Required: No

extraDataPackageArn

The ARN of the extra data for the run. The extra data is a .zip file that AWS Device Farm extracts to external data for Android or the app's sandbox for iOS.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

locale

Information about the locale that is used for the run.

Type: String

Required: No

location

Information about the location that is used for the run.

Type: [Location](#) object

Required: No

networkProfileArn

Reserved for internal use.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

radios

Information about the radio states for the run.

Type: [Radios](#) object

Required: No

vpceConfigurationArns

An array of ARNs for your VPC endpoint configurations.

Type: Array of strings

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ScheduleRunTest

Represents test settings. This data structure is passed in as the test parameter to ScheduleRun. For an example of the JSON request syntax, see [ScheduleRun](#).

Contents

type

The test's type.

Must be one of the following values:

- BUILTIN_FUZZ
- APPIUM_JAVA_JUNIT
- APPIUM_JAVA_TESTNG
- APPIUM_PYTHON
- APPIUM_NODE
- APPIUM_RUBY
- APPIUM_WEB_JAVA_JUNIT
- APPIUM_WEB_JAVA_TESTNG
- APPIUM_WEB_PYTHON
- APPIUM_WEB_NODE
- APPIUM_WEB_RUBY
- INSTRUMENTATION
- XCTEST
- XCTEST_UI

Type: String

Valid Values: BUILTIN_FUZZ | APPIUM_JAVA_JUNIT | APPIUM_JAVA_TESTNG | APPIUM_PYTHON | APPIUM_NODE | APPIUM_RUBY | APPIUM_WEB_JAVA_JUNIT | APPIUM_WEB_JAVA_TESTNG | APPIUM_WEB_PYTHON | APPIUM_WEB_NODE | APPIUM_WEB_RUBY | INSTRUMENTATION | XCTEST | XCTEST_UI

Required: Yes

filter

The test's filter.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 8192.

Required: No

parameters

The test's parameters, such as test framework parameters and fixture settings. Parameters are represented by name-value pairs of strings.

For all tests:

- `app_performance_monitoring`: Performance monitoring is enabled by default. Set this parameter to false to disable it.

For Appium tests (all types):

- `appium_version`: The Appium version. Currently supported values are 1.6.5 (and later), latest, and default.
 - latest runs the latest Appium version supported by Device Farm (1.9.1).
 - For default, Device Farm selects a compatible version of Appium for the device. The current behavior is to run 1.7.2 on Android devices and iOS 9 and earlier and 1.7.2 for iOS 10 and later.
 - This behavior is subject to change.

For fuzz tests (Android only):

- `event_count`: The number of events, between 1 and 10000, that the UI fuzz test should perform.
- `throttle`: The time, in ms, between 0 and 1000, that the UI fuzz test should wait between events.
- `seed`: A seed to use for randomizing the UI fuzz test. Using the same seed value between tests ensures identical event sequences.

For Instrumentation:

- `filter`: A test filter string. Examples:
 - Running a single test case: `com.android.abc.Test1`

- Running a single test: `com.android.abc.Test1#smoke`
- Running multiple tests: `com.android.abc.Test1,com.android.abc.Test2`

For XCTest and XCTestUI:

- filter: A test filter string. Examples:
 - Running a single test class: `LoginTests`
 - Running a multiple test classes: `LoginTests,SmokeTests`
 - Running a single test: `LoginTests/testValid`
 - Running multiple tests: `LoginTests/testValid,LoginTests/testInvalid`

Type: String to string map

Required: No

testPackageArn

The ARN of the uploaded test to be run.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

testSpecArn

The ARN of the YAML-formatted test specification.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Suite

Represents a collection of one or more tests.

Contents

arn

The suite's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

counters

The suite's result counters.

Type: [Counters](#) object

Required: No

created

When the suite was created.

Type: Timestamp

Required: No

deviceMinutes

Represents the total (metered or unmetered) minutes used by the test suite.

Type: [DeviceMinutes](#) object

Required: No

message

A message about the suite's result.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

name

The suite's name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

result

The suite's result.

Allowed values include:

- PENDING
- PASSED
- WARNED
- FAILED
- SKIPPED
- ERRORED
- STOPPED

Type: String

Valid Values: PENDING | PASSED | WARNED | FAILED | SKIPPED | ERRORED | STOPPED

Required: No

started

The suite's start time.

Type: Timestamp

Required: No

status

The suite's status.

Allowed values include:

- PENDING
- PENDING_CONCURRENCY
- PENDING_DEVICE
- PROCESSING
- SCHEDULING
- PREPARING
- RUNNING
- COMPLETED
- STOPPING

Type: String

Valid Values: PENDING | PENDING_CONCURRENCY | PENDING_DEVICE | PROCESSING | SCHEDULING | PREPARING | RUNNING | COMPLETED | STOPPING

Required: No

stopped

The suite's stop time.

Type: Timestamp

Required: No

type

The suite's type.

Must be one of the following values:

- BUILTIN_FUZZ
- APPIUM_JAVA_JUNIT
- APPIUM_JAVA_TESTNG
- APPIUM_PYTHON

- APPIUM_NODE
- APPIUM_RUBY
- APPIUM_WEB_JAVA_JUNIT
- APPIUM_WEB_JAVA_TESTNG
- APPIUM_WEB_PYTHON
- APPIUM_WEB_NODE
- APPIUM_WEB_RUBY
- INSTRUMENTATION
- XCTEST
- XCTEST_UI

Type: String

Valid Values: BUILTIN_FUZZ | APPIUM_JAVA_JUNIT | APPIUM_JAVA_TESTNG | APPIUM_PYTHON | APPIUM_NODE | APPIUM_RUBY | APPIUM_WEB_JAVA_JUNIT | APPIUM_WEB_JAVA_TESTNG | APPIUM_WEB_PYTHON | APPIUM_WEB_NODE | APPIUM_WEB_RUBY | INSTRUMENTATION | XCTEST | XCTEST_UI

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

The metadata that you apply to a resource to help you categorize and organize it. Each tag consists of a key and an optional value, both of which you define. Tag keys can have a maximum character length of 128 characters. Tag values can have a maximum length of 256 characters.

Contents

Key

One part of a key-value pair that makes up a tag. A key is a general label that acts like a category for more specific tag values.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Value

The optional part of a key-value pair that makes up a tag. A value acts as a descriptor in a tag category (key).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Test

Represents a condition that is evaluated.

Contents

arn

The test's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

counters

The test's result counters.

Type: [Counters](#) object

Required: No

created

When the test was created.

Type: Timestamp

Required: No

deviceMinutes

Represents the total (metered or unmetered) minutes used by the test.

Type: [DeviceMinutes](#) object

Required: No

message

A message about the test's result.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

name

The test's name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

result

The test's result.

Allowed values include:

- PENDING
- PASSED
- WARNED
- FAILED
- SKIPPED
- ERRORED
- STOPPED

Type: String

Valid Values: PENDING | PASSED | WARNED | FAILED | SKIPPED | ERRORED | STOPPED

Required: No

started

The test's start time.

Type: Timestamp

Required: No

status

The test's status.

Allowed values include:

- PENDING
- PENDING_CONCURRENCY
- PENDING_DEVICE
- PROCESSING
- SCHEDULING
- PREPARING
- RUNNING
- COMPLETED
- STOPPING

Type: String

Valid Values: PENDING | PENDING_CONCURRENCY | PENDING_DEVICE | PROCESSING | SCHEDULING | PREPARING | RUNNING | COMPLETED | STOPPING

Required: No

stopped

The test's stop time.

Type: Timestamp

Required: No

type

The test's type.

Must be one of the following values:

- BUILTIN_FUZZ
- APPIUM_JAVA_JUNIT
- APPIUM_JAVA_TESTNG
- APPIUM_PYTHON

- APPIUM_NODE
- APPIUM_RUBY
- APPIUM_WEB_JAVA_JUNIT
- APPIUM_WEB_JAVA_TESTNG
- APPIUM_WEB_PYTHON
- APPIUM_WEB_NODE
- APPIUM_WEB_RUBY
- INSTRUMENTATION
- XCTEST
- XCTEST_UI

Type: String

Valid Values: BUILTIN_FUZZ | APPIUM_JAVA_JUNIT | APPIUM_JAVA_TESTNG | APPIUM_PYTHON | APPIUM_NODE | APPIUM_RUBY | APPIUM_WEB_JAVA_JUNIT | APPIUM_WEB_JAVA_TESTNG | APPIUM_WEB_PYTHON | APPIUM_WEB_NODE | APPIUM_WEB_RUBY | INSTRUMENTATION | XCTEST | XCTEST_UI

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestGridProject

A Selenium testing project. Projects are used to collect and collate sessions.

Contents

arn

The ARN for the project.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

created

When the project was created.

Type: Timestamp

Required: No

description

A human-readable description for the project.

Type: String

Required: No

name

A human-readable name for the project.

Type: String

Required: No

vpcConfig

The VPC security groups and subnets that are attached to a project.

Type: [TestGridVpcConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestGridSession

A [TestGridSession](#) is a single instance of a browser launched from the URL provided by a call to [CreateTestGridUrl](#).

Contents

arn

The ARN of the session.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: No

billingMinutes

The number of billed minutes that were used for this session.

Type: Double

Required: No

created

The time that the session was started.

Type: Timestamp

Required: No

ended

The time the session ended.

Type: Timestamp

Required: No

seleniumProperties

A JSON object of options and parameters passed to the Selenium WebDriver.

Type: String

Required: No

status

The state of the session.

Type: String

Valid Values: ACTIVE | CLOSED | ERRORRED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestGridSessionAction

An action taken by a [TestGridSession](#) browser instance.

Contents

action

The action taken by the session.

Type: String

Required: No

duration

The time, in milliseconds, that the action took to complete in the browser.

Type: Long

Required: No

requestMethod

HTTP method that the browser used to make the request.

Type: String

Required: No

started

The time that the session invoked the action.

Type: Timestamp

Required: No

statusCode

HTTP status code returned to the browser when the action was taken.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestGridSessionArtifact

Artifacts are video and other files that are produced in the process of running a browser in an automated context.

Note

Video elements might be broken up into multiple artifacts as they grow in size during creation.

Contents

filename

The file name of the artifact.

Type: String

Required: No

type

The kind of artifact.

Type: String

Valid Values: UNKNOWN | VIDEO | SELENIUM_LOG

Required: No

url

A semi-stable URL to the content of the object.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestGridVpcConfig

The VPC security groups and subnets that are attached to a project.

Contents

securityGroupIds

A list of VPC security group IDs in your Amazon VPC.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `.*\S.*`

Required: Yes

subnetIds

A list of VPC subnet IDs in your Amazon VPC.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 8 items.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `.*\S.*`

Required: Yes

vpcId

The ID of the Amazon VPC.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `.*\S.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrialMinutes

Represents information about free trial device minutes for an AWS account.

Contents

remaining

The number of free trial minutes remaining in the account.

Type: Double

Required: No

total

The total number of free trial minutes that the account started with.

Type: Double

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UniqueProblem

A collection of one or more problems, grouped by their result.

Contents

message

A message about the unique problems' result.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

problems

Information about the problems.

Type: Array of [Problem](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Upload

An app or a set of one or more tests to upload or that have been uploaded.

Contents

arn

The upload's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

category

The upload's category. Allowed values include:

- **CURATED**: An upload managed by AWS Device Farm.
- **PRIVATE**: An upload managed by the AWS Device Farm customer.

Type: String

Valid Values: `CURATED` | `PRIVATE`

Required: No

contentType

The upload's content type (for example, `application/octet-stream`).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 64.

Required: No

created

When the upload was created.

Type: Timestamp

Required: No

message

A message about the upload's result.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

metadata

The upload's metadata. For example, for Android, this contains information that is parsed from the manifest and is displayed in the AWS Device Farm console after the associated app is uploaded.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 8192.

Required: No

name

The upload's file name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

status

The upload's status.

Must be one of the following values:

- FAILED
- INITIALIZED
- PROCESSING

- SUCCEEDED

Type: String

Valid Values: INITIALIZED | PROCESSING | SUCCEEDED | FAILED

Required: No

type

The upload's type.

Must be one of the following values:

- ANDROID_APP
- IOS_APP
- WEB_APP
- EXTERNAL_DATA
- APPIUM_JAVA_JUNIT_TEST_PACKAGE
- APPIUM_JAVA_TESTNG_TEST_PACKAGE
- APPIUM_PYTHON_TEST_PACKAGE
- APPIUM_NODE_TEST_PACKAGE
- APPIUM_RUBY_TEST_PACKAGE
- APPIUM_WEB_JAVA_JUNIT_TEST_PACKAGE
- APPIUM_WEB_JAVA_TESTNG_TEST_PACKAGE
- APPIUM_WEB_PYTHON_TEST_PACKAGE
- APPIUM_WEB_NODE_TEST_PACKAGE
- APPIUM_WEB_RUBY_TEST_PACKAGE
- INSTRUMENTATION_TEST_PACKAGE
- XCTEST_TEST_PACKAGE
- XCTEST_UI_TEST_PACKAGE
- APPIUM_JAVA_JUNIT_TEST_SPEC
- APPIUM_JAVA_TESTNG_TEST_SPEC
- APPIUM_PYTHON_TEST_SPEC
- APPIUM_NODE_TEST_SPEC

- APPIUM_RUBY_TEST_SPEC
- APPIUM_WEB_JAVA_JUNIT_TEST_SPEC
- APPIUM_WEB_JAVA_TESTNG_TEST_SPEC
- APPIUM_WEB_PYTHON_TEST_SPEC
- APPIUM_WEB_NODE_TEST_SPEC
- APPIUM_WEB_RUBY_TEST_SPEC
- INSTRUMENTATION_TEST_SPEC
- XCTEST_UI_TEST_SPEC

Type: String

Valid Values: ANDROID_APP | IOS_APP | WEB_APP | EXTERNAL_DATA |
APPIUM_JAVA_JUNIT_TEST_PACKAGE | APPIUM_JAVA_TESTNG_TEST_PACKAGE
| APPIUM_PYTHON_TEST_PACKAGE | APPIUM_NODE_TEST_PACKAGE |
APPIUM_RUBY_TEST_PACKAGE | APPIUM_WEB_JAVA_JUNIT_TEST_PACKAGE |
APPIUM_WEB_JAVA_TESTNG_TEST_PACKAGE | APPIUM_WEB_PYTHON_TEST_PACKAGE
| APPIUM_WEB_NODE_TEST_PACKAGE | APPIUM_WEB_RUBY_TEST_PACKAGE
| CALABASH_TEST_PACKAGE | INSTRUMENTATION_TEST_PACKAGE
| UIAUTOMATION_TEST_PACKAGE | UIAUTOMATOR_TEST_PACKAGE
| XCTEST_TEST_PACKAGE | XCTEST_UI_TEST_PACKAGE |
APPIUM_JAVA_JUNIT_TEST_SPEC | APPIUM_JAVA_TESTNG_TEST_SPEC |
APPIUM_PYTHON_TEST_SPEC | APPIUM_NODE_TEST_SPEC | APPIUM_RUBY_TEST_SPEC
| APPIUM_WEB_JAVA_JUNIT_TEST_SPEC | APPIUM_WEB_JAVA_TESTNG_TEST_SPEC
| APPIUM_WEB_PYTHON_TEST_SPEC | APPIUM_WEB_NODE_TEST_SPEC
| APPIUM_WEB_RUBY_TEST_SPEC | INSTRUMENTATION_TEST_SPEC |
XCTEST_UI_TEST_SPEC

Required: No

url

The presigned Amazon S3 URL that was used to store a file using a PUT request.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VpcConfig

Contains the VPC configuration data necessary to interface with AWS Device Farm's services.

Contents

securityGroupIds

An array of one or more security groups IDs in your Amazon VPC.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `^sg-[0-9a-fA-F]{8,}$`

Required: Yes

subnetIds

An array of one or more subnet IDs in your Amazon VPC.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 8 items.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `^subnet-[0-9a-fA-F]{8,}$`

Required: Yes

vpId

The ID of the Amazon VPC.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `.*\S.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VPCEConfiguration

Represents an Amazon Virtual Private Cloud (VPC) endpoint configuration.

Contents

arn

The Amazon Resource Name (ARN) of the VPC endpoint configuration.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

serviceDnsName

The DNS name that maps to the private IP address of the service you want to access.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

vpceConfigurationDescription

An optional description that provides details about your VPC endpoint configuration.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

vpceConfigurationName

The friendly name you give to your VPC endpoint configuration to manage your configurations more easily.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

vpceServiceName

The name of the VPC endpoint service running in your AWS account that you want Device Farm to test.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400