



API Reference

Elastic Load Balancing



API Version 2015-12-01

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Elastic Load Balancing: API Reference

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	3
AddListenerCertificates	5
Request Parameters	5
Response Elements	5
Errors	6
See Also	6
AddTags	8
Request Parameters	8
Errors	8
Examples	9
See Also	10
AddTrustStoreRevocations	11
Request Parameters	11
Response Elements	11
Errors	11
Examples	12
See Also	12
CreateListener	14
Request Parameters	14
Response Elements	16
Errors	17
Examples	19
See Also	24
CreateLoadBalancer	25
Request Parameters	25
Response Elements	29
Errors	29
Examples	31
See Also	34
CreateRule	35
Request Parameters	35
Response Elements	36
Errors	36

Examples	38
See Also	40
CreateTargetGroup	42
Request Parameters	42
Response Elements	47
Errors	47
Examples	48
See Also	50
CreateTrustStore	52
Request Parameters	52
Response Elements	53
Errors	53
Examples	54
See Also	54
DeleteListener	56
Request Parameters	56
Errors	56
Examples	56
See Also	57
DeleteLoadBalancer	58
Request Parameters	58
Errors	58
Examples	59
See Also	59
DeleteRule	60
Request Parameters	60
Errors	60
Examples	60
See Also	61
DeleteSharedTrustStoreAssociation	62
Request Parameters	62
Errors	62
See Also	63
DeleteTargetGroup	64
Request Parameters	64
Errors	64

Examples	64
See Also	65
DeleteTrustStore	66
Request Parameters	66
Errors	66
Examples	66
See Also	67
DeregisterTargets	68
Request Parameters	68
Errors	68
Examples	69
See Also	70
DescribeAccountLimits	71
Request Parameters	71
Response Elements	71
Errors	72
See Also	72
DescribeCapacityReservation	73
Request Parameters	73
Response Elements	73
Errors	74
See Also	74
DescribeListenerAttributes	75
Request Parameters	75
Response Elements	75
Errors	75
Examples	75
See Also	76
DescribeListenerCertificates	77
Request Parameters	77
Response Elements	77
Errors	78
Examples	78
See Also	79
DescribeListeners	81
Request Parameters	81

Response Elements	82
Errors	82
Examples	83
See Also	86
DescribeLoadBalancerAttributes	88
Request Parameters	88
Response Elements	88
Errors	88
Examples	89
See Also	90
DescribeLoadBalancers	91
Request Parameters	91
Response Elements	92
Errors	92
Examples	92
See Also	94
DescribeRules	95
Request Parameters	95
Response Elements	95
Errors	96
Examples	96
See Also	99
DescribeSSLPolicies	100
Request Parameters	100
Response Elements	101
Errors	101
Examples	101
See Also	103
DescribeTags	104
Request Parameters	104
Response Elements	104
Errors	104
Examples	105
See Also	106
DescribeTargetGroupAttributes	107
Request Parameters	107

Response Elements	107
Errors	107
Examples	108
See Also	108
DescribeTargetGroups	110
Request Parameters	110
Response Elements	111
Errors	111
Examples	112
See Also	113
DescribeTargetHealth	115
Request Parameters	115
Response Elements	115
Errors	116
Examples	116
See Also	118
DescribeTrustStoreAssociations	120
Request Parameters	120
Response Elements	120
Errors	121
Examples	121
See Also	121
DescribeTrustStoreRevocations	123
Request Parameters	123
Response Elements	123
Errors	124
Examples	124
See Also	125
DescribeTrustStores	126
Request Parameters	126
Response Elements	127
Errors	127
Examples	127
See Also	128
GetResourcePolicy	129
Request Parameters	129

Response Elements	129
Errors	129
Examples	130
See Also	130
GetTrustStoreCaCertificatesBundle	131
Request Parameters	131
Response Elements	131
Errors	131
See Also	132
GetTrustStoreRevocationContent	133
Request Parameters	133
Response Elements	133
Errors	133
Examples	134
See Also	134
ModifyCapacityReservation	136
Request Parameters	136
Response Elements	136
Errors	137
See Also	138
ModifyIpPools	139
Request Parameters	139
Response Elements	139
Errors	140
See Also	140
ModifyListener	141
Request Parameters	141
Response Elements	143
Errors	143
Examples	146
See Also	149
ModifyListenerAttributes	151
Request Parameters	151
Response Elements	151
Errors	151
See Also	152

ModifyLoadBalancerAttributes	153
Request Parameters	153
Response Elements	153
Errors	154
Examples	154
See Also	158
ModifyRule	160
Request Parameters	160
Response Elements	161
Errors	161
See Also	163
ModifyTargetGroup	164
Request Parameters	164
Response Elements	166
Errors	166
Examples	167
See Also	168
ModifyTargetGroupAttributes	169
Request Parameters	169
Response Elements	169
Errors	169
Examples	170
See Also	171
ModifyTrustStore	172
Request Parameters	172
Response Elements	172
Errors	173
Examples	173
See Also	174
RegisterTargets	175
Request Parameters	175
Errors	175
Examples	176
See Also	178
RemoveListenerCertificates	179
Request Parameters	179

Errors	179
See Also	180
RemoveTags	181
Request Parameters	181
Errors	181
Examples	182
See Also	183
RemoveTrustStoreRevocations	184
Request Parameters	184
Errors	184
Examples	185
See Also	185
SetIpAddressType	186
Request Parameters	186
Response Elements	186
Errors	187
Examples	187
See Also	188
SetRulePriorities	189
Request Parameters	189
Response Elements	189
Errors	189
Examples	190
See Also	191
SetSecurityGroups	192
Request Parameters	192
Response Elements	193
Errors	193
Examples	194
See Also	194
SetSubnets	196
Request Parameters	196
Response Elements	198
Errors	198
Examples	199
See Also	200

Data Types	201
Action	204
Contents	204
See Also	206
AdministrativeOverride	207
Contents	207
See Also	207
AnomalyDetection	209
Contents	209
See Also	209
AuthenticateCognitoActionConfig	210
Contents	210
See Also	211
AuthenticateOidcActionConfig	213
Contents	213
See Also	215
AvailabilityZone	216
Contents	216
See Also	217
CapacityReservationStatus	218
Contents	218
See Also	218
Certificate	219
Contents	219
See Also	219
Cipher	220
Contents	220
See Also	220
DescribeTrustStoreRevocation	221
Contents	221
See Also	221
FixedResponseActionConfig	223
Contents	223
See Also	223
ForwardActionConfig	225
Contents	225

See Also	225
HostHeaderConditionConfig	226
Contents	226
See Also	226
HostHeaderRewriteConfig	227
Contents	227
See Also	227
HttpHeaderConditionConfig	228
Contents	228
See Also	229
HttpRequestMethodConditionConfig	230
Contents	230
See Also	230
IpamPools	231
Contents	231
See Also	231
JwtValidationActionAdditionalClaim	232
Contents	232
See Also	232
JwtValidationActionConfig	234
Contents	234
See Also	234
Limit	236
Contents	236
See Also	236
Listener	237
Contents	237
See Also	238
ListenerAttribute	240
Contents	240
See Also	242
LoadBalancer	243
Contents	243
See Also	246
LoadBalancerAddress	247
Contents	247

See Also	247
LoadBalancerAttribute	249
Contents	249
See Also	252
LoadBalancerState	253
Contents	253
See Also	253
Matcher	254
Contents	254
See Also	254
MinimumLoadBalancerCapacity	256
Contents	256
See Also	256
MutualAuthenticationAttributes	257
Contents	257
See Also	258
PathPatternConditionConfig	259
Contents	259
See Also	259
QueryStringConditionConfig	260
Contents	260
See Also	260
QueryStringKeyValuePair	261
Contents	261
See Also	261
RedirectActionConfig	262
Contents	262
See Also	263
RevocationContent	265
Contents	265
See Also	265
RewriteConfig	267
Contents	267
See Also	267
Rule	268
Contents	268

See Also	269
RuleCondition	270
Contents	270
See Also	272
RulePriorityPair	273
Contents	273
See Also	273
RuleTransform	274
Contents	274
See Also	274
SourceIpConditionConfig	276
Contents	276
See Also	276
SslPolicy	277
Contents	277
See Also	277
SubnetMapping	279
Contents	279
See Also	280
Tag	281
Contents	281
See Also	281
TagDescription	282
Contents	282
See Also	282
TargetDescription	283
Contents	283
See Also	284
TargetGroup	285
Contents	285
See Also	289
TargetGroupAttribute	290
Contents	290
See Also	293
TargetGroupStickinessConfig	294
Contents	294

See Also	294
TargetGroupTuple	295
Contents	295
See Also	295
TargetHealth	296
Contents	296
See Also	297
TargetHealthDescription	299
Contents	299
See Also	300
TrustStore	301
Contents	301
See Also	302
TrustStoreAssociation	303
Contents	303
See Also	303
TrustStoreRevocation	304
Contents	304
See Also	304
UrlRewriteConfig	306
Contents	306
See Also	306
ZonalCapacityReservationState	307
Contents	307
See Also	307
Common Parameters	308
Common Error Types	311

Welcome

A load balancer distributes incoming traffic across targets, such as your EC2 instances. This enables you to increase the availability of your application. The load balancer also monitors the health of its registered targets and ensures that it routes traffic only to healthy targets. You configure your load balancer to accept incoming traffic by specifying one or more listeners, which are configured with a protocol and port number for connections from clients to the load balancer. You configure a target group with a protocol and port number for connections from the load balancer to the targets, and with health check settings to be used when checking the health status of the targets.

Elastic Load Balancing supports the following types of load balancers: Application Load Balancers, Network Load Balancers, Gateway Load Balancers, and Classic Load Balancers. This reference covers the following load balancer types:

- Application Load Balancer - Operates at the application layer (layer 7) and supports HTTP and HTTPS.
- Network Load Balancer - Operates at the transport layer (layer 4) and supports TCP, TLS, UDP, and QUIC.
- Gateway Load Balancer - Operates at the network layer (layer 3).

For more information, see the [Elastic Load Balancing User Guide](#).

To get started, complete the following tasks:

1. Create a load balancer using [CreateLoadBalancer](#).
2. Create target groups using [CreateTargetGroup](#).
3. Register targets with the target groups using [RegisterTargets](#).
4. Create listeners for your load balancer using [CreateListener](#).

To delete a load balancer and its related resources, complete the following tasks:

1. Delete the load balancer using [DeleteLoadBalancer](#).
2. Delete the target group using [DeleteTargetGroup](#).

All Elastic Load Balancing operations are idempotent, which means that they complete at most one time. If you repeat an operation, it succeeds.

This document was last published on May 1, 2026.

Actions

The following actions are supported:

- [AddListenerCertificates](#)
- [AddTags](#)
- [AddTrustStoreRevocations](#)
- [CreateListener](#)
- [CreateLoadBalancer](#)
- [CreateRule](#)
- [CreateTargetGroup](#)
- [CreateTrustStore](#)
- [DeleteListener](#)
- [DeleteLoadBalancer](#)
- [DeleteRule](#)
- [DeleteSharedTrustStoreAssociation](#)
- [DeleteTargetGroup](#)
- [DeleteTrustStore](#)
- [DeregisterTargets](#)
- [DescribeAccountLimits](#)
- [DescribeCapacityReservation](#)
- [DescribeListenerAttributes](#)
- [DescribeListenerCertificates](#)
- [DescribeListeners](#)
- [DescribeLoadBalancerAttributes](#)
- [DescribeLoadBalancers](#)
- [DescribeRules](#)
- [DescribeSSLPolicies](#)
- [DescribeTags](#)
- [DescribeTargetGroupAttributes](#)
- [DescribeTargetGroups](#)

- [DescribeTargetHealth](#)
- [DescribeTrustStoreAssociations](#)
- [DescribeTrustStoreRevocations](#)
- [DescribeTrustStores](#)
- [GetResourcePolicy](#)
- [GetTrustStoreCaCertificatesBundle](#)
- [GetTrustStoreRevocationContent](#)
- [ModifyCapacityReservation](#)
- [ModifyIpPools](#)
- [ModifyListener](#)
- [ModifyListenerAttributes](#)
- [ModifyLoadBalancerAttributes](#)
- [ModifyRule](#)
- [ModifyTargetGroup](#)
- [ModifyTargetGroupAttributes](#)
- [ModifyTrustStore](#)
- [RegisterTargets](#)
- [RemoveListenerCertificates](#)
- [RemoveTags](#)
- [RemoveTrustStoreRevocations](#)
- [SetIpAddressType](#)
- [SetRulePriorities](#)
- [SetSecurityGroups](#)
- [SetSubnets](#)

AddListenerCertificates

Adds the specified SSL server certificate to the certificate list for the specified HTTPS or TLS listener.

If the certificate is already in the certificate list, the call is successful but the certificate is not added again.

To get the certificate list for a listener, use [DescribeListenerCertificates](#). To remove certificates from the certificate list for a listener, use [RemoveListenerCertificates](#). To replace the default certificate for a listener, use [ModifyListener](#).

For more information, see [SSL certificates](#) in the *Application Load Balancers Guide* or [Server certificates](#) in the *Network Load Balancers Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

Certificates.member.N

The certificate to add. You can specify one certificate per call. Set `CertificateArn` to the certificate ARN but do not set `IsDefault`.

Type: Array of [Certificate](#) objects

Required: Yes

ListenerArn

The Amazon Resource Name (ARN) of the listener.

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

Certificates.member.N

Information about the certificates in the certificate list.

Type: Array of [Certificate](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CertificateNotFound

The specified certificate does not exist.

HTTP Status Code: 400

ListenerNotFound

The specified listener does not exist.

HTTP Status Code: 400

TooManyCertificates

You've reached the limit on the number of certificates per load balancer.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

AddTags

Adds the specified tags to the specified Elastic Load Balancing resource. You can tag your Application Load Balancers, Network Load Balancers, Gateway Load Balancers, target groups, trust stores, listeners, and rules.

Each tag consists of a key and an optional value. If a resource already has a tag with the same key, AddTags updates its value.

To list the current tags for your resources, use [DescribeTags](#). To remove tags from your resources, use [RemoveTags](#).

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

ResourceArns.member.N

The Amazon Resource Name (ARN) of the resource.

Type: Array of strings

Required: Yes

Tags.member.N

The tags.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item.

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

DuplicateTagKeys

A tag key was specified more than once.

HTTP Status Code: 400

ListenerNotFound

The specified listener does not exist.

HTTP Status Code: 400

LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

RuleNotFound

The specified rule does not exist.

HTTP Status Code: 400

TargetGroupNotFound

The specified target group does not exist.

HTTP Status Code: 400

TooManyTags

You've reached the limit on the number of tags for this resource.

HTTP Status Code: 400

TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

Examples

Add tags to a load balancer

This example adds the specified tags to the specified load balancer.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=AddTags
```

```
&ResourceArns.member.1=arn:aws:elasticloadbalancing:us-  
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188  
&Tags.member.1.Key=project  
&Tags.member.1.Value=lima  
&Tags.member.2.Key=department  
&Tags.member.2.Value=digital-media  
&Version=2015-12-01  
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

AddTrustStoreRevocations

Adds the specified revocation file to the specified trust store.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

RevocationContents.member.N

The revocation file to add.

Type: Array of [RevocationContent](#) objects

Required: No

TrustStoreArn

The Amazon Resource Name (ARN) of the trust store.

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

TrustStoreRevocations.member.N

Information about the revocation file added to the trust store.

Type: Array of [TrustStoreRevocation](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidRevocationContent

The provided revocation file is an invalid format, or uses an incorrect algorithm.

HTTP Status Code: 400

RevocationContentNotFound

The specified revocation file does not exist.

HTTP Status Code: 400

TooManyTrustStoreRevocationEntries

The specified trust store has too many revocation entries.

HTTP Status Code: 400

TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

Examples

Add a revocation file to a trust store.

This example adds the specified certificate revocation list to the specified trust store.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=AddTrustStoreRevocations
&TrustStoreArn=arn:aws:elasticloadbalancing:us-east-1:111122223333:truststore/my-trust-
store/3ym756xh7yj
&RevocationContents.member.1.RevocationType=CRL
&RevocationContents.member.1.S3Bucket=amzn-s3-demo-bucket
&RevocationContents.member.1.S3Key=my-crl.pem
&Version=2015-12-01
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateListener

Creates a listener for the specified Application Load Balancer, Network Load Balancer, or Gateway Load Balancer.

To update a listener, use [ModifyListener](#). When you are finished with a listener, you can delete it using [DeleteListener](#). If you are finished with both the listener and the load balancer, you can delete them both using [DeleteLoadBalancer](#).

For more information, see the following:

- [Listeners for your Application Load Balancers](#)
- [Listeners for your Network Load Balancers](#)
- [Listeners for your Gateway Load Balancers](#)

This operation is idempotent, which means that it completes at most one time. If you attempt to create multiple listeners with the same settings, each call succeeds.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

AlpnPolicy.member.N

[TLS listeners] The name of the Application-Layer Protocol Negotiation (ALPN) policy. You can specify one policy name. The following are the possible values:

- HTTP10nly
- HTTP20nly
- HTTP2Optional
- HTTP2Preferred
- None

For more information, see [ALPN policies](#) in the *Network Load Balancers Guide*.

Type: Array of strings

Required: No

Certificates.member.N

[HTTPS and TLS listeners] The default certificate for the listener. You must provide exactly one certificate. Set `CertificateArn` to the certificate ARN but do not set `IsDefault`.

To create a certificate list for the listener, use [AddListenerCertificates](#).

Type: Array of [Certificate](#) objects

Required: No

DefaultActions.member.N

The actions for the default rule.

Type: Array of [Action](#) objects

Required: Yes

LoadBalancerArn

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: Yes

MutualAuthentication

[HTTPS listeners] The mutual authentication configuration information.

Type: [MutualAuthenticationAttributes](#) object

Required: No

Port

The port on which the load balancer is listening. You can't specify a port for a Gateway Load Balancer.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

Protocol

The protocol for connections from clients to the load balancer. For Application Load Balancers, the supported protocols are HTTP and HTTPS. For Network Load Balancers, the supported protocols are TCP, TLS, UDP, TCP_UDP, QUIC, and TCP_QUIC. You can't specify the UDP, TCP_UDP, QUIC, or TCP_QUIC protocol if dual-stack mode is enabled. You can't specify a protocol for a Gateway Load Balancer.

Type: String

Valid Values: HTTP | HTTPS | TCP | TLS | UDP | TCP_UDP | GENEVE | QUIC | TCP_QUIC

Required: No

SslPolicy

[HTTPS and TLS listeners] The security policy that defines which protocols and ciphers are supported.

For more information, see [Security policies](#) in the *Application Load Balancers Guide* and [Security policies](#) in the *Network Load Balancers Guide*.

Type: String

Required: No

Tags.member.N

The tags to assign to the listener.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item.

Required: No

Response Elements

The following element is returned by the service.

Listeners.member.N

Information about the listener.

Type: Array of [Listener](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ALPNPolicyNotFound

The specified ALPN policy is not supported.

HTTP Status Code: 400

CertificateNotFound

The specified certificate does not exist.

HTTP Status Code: 400

DuplicateListener

A listener with the specified port already exists.

HTTP Status Code: 400

IncompatibleProtocols

The specified configuration is not valid with this protocol.

HTTP Status Code: 400

InvalidConfigurationRequest

The requested configuration is not valid.

HTTP Status Code: 400

InvalidLoadBalancerAction

The requested action is not valid.

HTTP Status Code: 400

LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

SSLPolicyNotFound

The specified SSL policy does not exist.

HTTP Status Code: 400

TargetGroupAssociationLimit

You've reached the limit on the number of load balancers per target group.

HTTP Status Code: 400

TargetGroupNotFound

The specified target group does not exist.

HTTP Status Code: 400

TooManyActions

You've reached the limit on the number of actions per rule.

HTTP Status Code: 400

TooManyCertificates

You've reached the limit on the number of certificates per load balancer.

HTTP Status Code: 400

TooManyListeners

You've reached the limit on the number of listeners per load balancer.

HTTP Status Code: 400

TooManyRegistrationsForTargetId

You've reached the limit on the number of times a target can be registered with a load balancer.

HTTP Status Code: 400

TooManyTags

You've reached the limit on the number of tags for this resource.

HTTP Status Code: 400

TooManyTargets

You've reached the limit on the number of targets.

HTTP Status Code: 400

TooManyUniqueTargetGroupsPerLoadBalancer

You've reached the limit on the number of unique target groups per load balancer across all listeners. If a target group is used by multiple actions for a load balancer, it is counted as only one use.

HTTP Status Code: 400

TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

TrustStoreNotReady

The specified trust store is not active.

HTTP Status Code: 400

UnsupportedProtocol

The specified protocol is not supported.

HTTP Status Code: 400

Examples

Create an HTTP listener

This example creates an HTTP listener for the specified Application Load Balancer that forwards requests to the specified target group.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateListener
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/
my-load-balancer/50dc6c495c0c9188
```

```
&Protocol=HTTP
&Port=80
&DefaultActions.member.1.Type=forward
&DefaultActions.member.1.TargetGroupArn=arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<CreateListenerResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <CreateListenerResult>
    <Listeners>
      <member>
        <LoadBalancerArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188</
LoadBalancerArn>
        <Protocol>HTTP</Protocol>
        <Port>80</Port>
        <ListenerArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/
my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2</ListenerArn>
        <DefaultActions>
          <member>
            <Type>forward</Type>
            <TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
          </member>
        </DefaultActions>
      </member>
    </Listeners>
  </CreateListenerResult>
  <ResponseMetadata>
    <RequestId>883c84bb-f387-11e5-ae48-cff02092876b</RequestId>
  </ResponseMetadata>
</CreateListenerResponse>
```

Create an HTTPS listener

This example creates an HTTPS listener for the specified Application Load Balancer that forwards requests to the specified target group. Note that you must specify a default certificate for an HTTPS listener. You can create and manage your certificates using AWS Certificate Manager (ACM).

Alternatively, you can create a certificate using SSL/TLS tools, get the certificate signed by a certificate authority (CA), and upload the certificate to AWS Identity and Access Management (IAM).

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateListener
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188
&Protocol=HTTPS
&Port=443
&Certificates.member.1.CertificateArn=arn:aws:iam::123456789012:server-certificate/my-server-cert
&SslPolicy=ELBSecurityPolicy-2016-08
&DefaultActions.member.1.Type=forward
&DefaultActions.member.1.TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<CreateListenerResponse xmlns="http://elasticloadbalancing.amazonaws.com/doc/2015-12-01/">
  <CreateListenerResult>
    <Listeners>
      <member>
        <LoadBalancerArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188</LoadBalancerArn>
        <Protocol>HTTPS</Protocol>
        <Certificates>
          <member>
            <CertificateArn>arn:aws:iam::123456789012:server-certificate/my-server-cert</CertificateArn>
          </member>
        </Certificates>
        <Port>443</Port>
        <SslPolicy>ELBSecurityPolicy-2016-08</SslPolicy>
        <ListenerArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2</ListenerArn>
        <DefaultActions>
          <member>
            <Type>forward</Type>
```

```

        <TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
    </member>
</DefaultActions>
</member>
</Listeners>
</CreateListenerResult>
<ResponseMetadata>
  <RequestId>97f1bb38-f390-11e5-b95d-3b2c1831fc26</RequestId>
</ResponseMetadata>
</CreateListenerResponse>

```

Create a TCP listener

This example creates a TCP listener for the specified Network Load Balancer that forwards requests to the specified target group.

```

https://elasticloadbalancing.amazonaws.com/?Action=CreateListener
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/net/
my-network-load-balancer/2d7b630a7815dda2
&Protocol=TCP
&Port=80
&DefaultActions.member.1.Type=forward
&DefaultActions.member.1.TargetGroupArn=arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-tcp-targets/b7fce90c666d892a
&Version=2015-12-01
&AUTHPARAMS

```

Create a TLS listener

This example creates a TLS listener for the specified Network Load Balancer that forwards requests to the specified target group.

```

https://elasticloadbalancing.amazonaws.com/?Action=CreateListener
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/net/
my-network-load-balancer/2d7b630a7815dda2
&Protocol=TLS
&Port=443
&Certificates.member.1.CertificateArn=arn:aws:acm::123456789012:server-certificate/my-
server-cert
&SslPolicy=ELBSecurityPolicy-2016-08
&DefaultActions.member.1.Type=forward

```

```
&DefaultActions.member.1.TargetGroupArn=arn:aws:elasticloadbalancing:us-  
west-2:123456789012:targetgroup/my-tls-targets/b7fce90c666d892a  
&Version=2015-12-01  
&AUTHPARAMS
```

Create a UDP listener

This example creates a UDP listener for the specified Network Load Balancer that forwards requests to the specified target group.

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateListener  
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/net/  
my-network-load-balancer/2d7b630a7815dda2  
&Protocol=UDP  
&Port=53  
&DefaultActions.member.1.Type=forward  
&DefaultActions.member.1.TargetGroupArn=arn:aws:elasticloadbalancing:us-  
west-2:123456789012:targetgroup/my-udp-targets/b7fce90c666d892a  
&Version=2015-12-01  
&AUTHPARAMS
```

Create a TCP_UDP listener

This example creates a TCP_UDP listener for the specified Network Load Balancer that forwards requests to the specified target group. The target group must use the TCP_UDP protocol.

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateListener  
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/net/  
my-network-load-balancer/2d7b630a7815dda2  
&Protocol=TCP_UDP  
&Port=80  
&DefaultActions.member.1.Type=forward  
&DefaultActions.member.1.TargetGroupArn=arn:aws:elasticloadbalancing:us-  
west-2:123456789012:targetgroup/my-tcp-udp-targets/b7fce90c666d892a  
&Version=2015-12-01  
&AUTHPARAMS
```

Create a listener for your Gateway Load Balancer

This example creates a listener for the specified Gateway Load Balancer that forwards requests to the specified target group. You can't specify a port or protocol.

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateListener
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/gwy/
my-gateway-load-balancer/2d7b630a7815dda2
&DefaultActions.member.1.Type=forward
&DefaultActions.member.1.TargetGroupArn=arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-appliance-targets/b7fce90c666d892a
&Version=2015-12-01
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateLoadBalancer

Creates an Application Load Balancer, Network Load Balancer, or Gateway Load Balancer.

To create listeners for your load balancer, use [CreateListener](#). To describe your current load balancers, see [DescribeLoadBalancers](#). When you are finished with a load balancer, you can delete it using [DeleteLoadBalancer](#).

For more information, see the following:

- [Application Load Balancers](#)
- [Network Load Balancers](#)
- [Gateway Load Balancers](#)

This operation is idempotent, which means that it completes at most one time. If you attempt to create multiple load balancers with the same settings, each call succeeds.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

CustomerOwnedIpv4Pool

[Application Load Balancers on Outposts] The ID of the customer-owned address pool (CoIP pool).

Type: String

Length Constraints: Maximum length of 256.

Pattern: `^(ipv4pool-coip-)[a-zA-Z0-9]+$`

Required: No

EnablePrefixForIpv6SourceNat

[Network Load Balancers with UDP listeners] Indicates whether to use an IPv6 prefix from each subnet for source NAT. The IP address type must be `dualstack`. The default value is `off`.

Type: String

Valid Values: `on` | `off`

Required: No

IpAddressType

The IP address type. Internal load balancers must use `ipv4`.

[Application Load Balancers] The possible values are `ipv4` (IPv4 addresses), `dualstack` (IPv4 and IPv6 addresses), and `dualstack-without-public-ipv4` (public IPv6 addresses and private IPv4 and IPv6 addresses).

[Network Load Balancers and Gateway Load Balancers] The possible values are `ipv4` (IPv4 addresses) and `dualstack` (IPv4 and IPv6 addresses).

Type: String

Valid Values: `ipv4` | `dualstack` | `dualstack-without-public-ipv4`

Required: No

IpamPools

[Application Load Balancers] The IPAM pools to use with the load balancer.

Type: [IpamPools](#) object

Required: No

Name

The name of the load balancer.

This name must be unique per region per account, can have a maximum of 32 characters, must contain only alphanumeric characters or hyphens, must not begin or end with a hyphen, and must not begin with "internal-".

Type: String

Required: Yes

Scheme

The nodes of an Internet-facing load balancer have public IP addresses. The DNS name of an Internet-facing load balancer is publicly resolvable to the public IP addresses of the nodes. Therefore, Internet-facing load balancers can route requests from clients over the internet.

The nodes of an internal load balancer have only private IP addresses. The DNS name of an internal load balancer is publicly resolvable to the private IP addresses of the nodes. Therefore, internal load balancers can route requests only from clients with access to the VPC for the load balancer.

The default is an Internet-facing load balancer.

You can't specify a scheme for a Gateway Load Balancer.

Type: String

Valid Values: `internet-facing` | `internal`

Required: No

SecurityGroups.member.N

[Application Load Balancers and Network Load Balancers] The IDs of the security groups for the load balancer.

Type: Array of strings

Required: No

SubnetMappings.member.N

The IDs of the subnets. You can specify only one subnet per Availability Zone. You must specify either subnets or subnet mappings, but not both.

[Application Load Balancers] You must specify subnets from at least two Availability Zones. You can't specify Elastic IP addresses for your subnets.

[Application Load Balancers on Outposts] You must specify one Outpost subnet.

[Application Load Balancers on Local Zones] You can specify subnets from one or more Local Zones.

[Network Load Balancers] You can specify subnets from one or more Availability Zones. You can specify one Elastic IP address per subnet if you need static IP addresses for your internet-facing load balancer. For internal load balancers, you can specify one private IP address per subnet from the IPv4 range of the subnet. For internet-facing load balancer, you can specify one IPv6 address per subnet.

[Gateway Load Balancers] You can specify subnets from one or more Availability Zones. You can't specify Elastic IP addresses for your subnets.

Type: Array of [SubnetMapping](#) objects

Required: No

Subnets.member.N

The IDs of the subnets. You can specify only one subnet per Availability Zone. You must specify either subnets or subnet mappings, but not both. To specify an Elastic IP address, specify subnet mappings instead of subnets.

[Application Load Balancers] You must specify subnets from at least two Availability Zones.

[Application Load Balancers on Outposts] You must specify one Outpost subnet.

[Application Load Balancers on Local Zones] You can specify subnets from one or more Local Zones.

[Network Load Balancers and Gateway Load Balancers] You can specify subnets from one or more Availability Zones.

Type: Array of strings

Required: No

Tags.member.N

The tags to assign to the load balancer.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item.

Required: No

Type

The type of load balancer. The default is `application`.

Type: String

Valid Values: `application` | `network` | `gateway`

Required: No

Response Elements

The following element is returned by the service.

LoadBalancers.member.N

Information about the load balancer.

Type: Array of [LoadBalancer](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AllocationIdNotFound

The specified allocation ID does not exist.

HTTP Status Code: 400

AvailabilityZoneNotSupported

The specified Availability Zone is not supported.

HTTP Status Code: 400

DuplicateLoadBalancerName

A load balancer with the specified name already exists.

HTTP Status Code: 400

DuplicateTagKeys

A tag key was specified more than once.

HTTP Status Code: 400

InvalidConfigurationRequest

The requested configuration is not valid.

HTTP Status Code: 400

InvalidScheme

The requested scheme is not valid.

HTTP Status Code: 400

InvalidSecurityGroup

The specified security group does not exist.

HTTP Status Code: 400

InvalidSubnet

The specified subnet is out of available addresses.

HTTP Status Code: 400

OperationNotPermitted

This operation is not allowed.

HTTP Status Code: 400

ResourceInUse

A specified resource is in use.

HTTP Status Code: 400

SubnetNotFound

The specified subnet does not exist.

HTTP Status Code: 400

TooManyLoadBalancers

You've reached the limit on the number of load balancers for your AWS account.

HTTP Status Code: 400

TooManyTags

You've reached the limit on the number of tags for this resource.

HTTP Status Code: 400

Examples

Create an Internet-facing load balancer

This example creates an Internet-facing load balancer and enables the Availability Zones for the specified subnets.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateLoadBalancer
&Name=my-load-balancer
&Subnets.member.1=subnet-8360a9e7
&Subnets.member.2=subnet-b7d581c0
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<CreateLoadBalancerResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <CreateLoadBalancerResult>
    <LoadBalancers>
      <member>
        <LoadBalancerArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-internal-load-balancer/50dc6c495c0c9188</
LoadBalancerArn>
        <Scheme>internet-facing</Scheme>
        <LoadBalancerName>my-load-balancer</LoadBalancerName>
        <VpcId>vpc-3ac0fb5f</VpcId>
        <CanonicalHostedZoneId>Z2P70J7EXAMPLE</CanonicalHostedZoneId>
        <CreatedTime>2016-03-25T21:29:48.850Z</CreatedTime>
        <AvailabilityZones>
          <member>
            <SubnetId>subnet-8360a9e7</SubnetId>
            <ZoneName>us-west-2a</ZoneName>
          </member>
          <member>
            <SubnetId>subnet-b7d581c0</SubnetId>
            <ZoneName>us-west-2b</ZoneName>
          </member>
        </AvailabilityZones>
        <SecurityGroups>
```

```

    <member>sg-5943793c</member>
  </SecurityGroups>
  <DNSName>my-load-balancer-424835706.us-west-2.elb.amazonaws.com</DNSName>
  <State>
    <Code>provisioning</Code>
  </State>
  <Type>application</Type>
</member>
</LoadBalancers>
</CreateLoadBalancerResult>
<ResponseMetadata>
  <RequestId>32d531b2-f2d0-11e5-9192-3fff33344cfa</RequestId>
</ResponseMetadata>
</CreateLoadBalancerResponse>

```

Create an internal load balancer

This example creates an internal load balancer and enables the Availability Zones for the specified subnets.

Sample Request

```

https://elasticloadbalancing.amazonaws.com/?Action=CreateLoadBalancer
&Name=my-internal-load-balancer
&Scheme=internal
&Subnets.member.1=subnet-8360a9e7
&Subnets.member.2=subnet-b7d581c0
&Version=2015-12-01
&AUTHPARAMS

```

Sample Response

```

<CreateLoadBalancerResponse xmlns="http://elasticloadbalancing.amazonaws.com/doc/2015-12-01/">
  <CreateLoadBalancerResult>
    <LoadBalancers>
      <member>
        <LoadBalancerArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/my-internal-load-balancer/5b49b8d4303115c2</LoadBalancerArn>
        <Scheme>internal</Scheme>
        <LoadBalancerName>my-internal-load-balancer</LoadBalancerName>
      </member>
    </LoadBalancers>
  </CreateLoadBalancerResult>
</CreateLoadBalancerResponse>

```

```
<VpcId>vpc-3ac0fb5f</VpcId>
<CanonicalHostedZoneId>Z2P70J7EXAMPLE</CanonicalHostedZoneId>
<CreatedTime>2016-03-25T21:29:48.850Z</CreatedTime>
<AvailabilityZones>
  <member>
    <SubnetId>subnet-8360a9e7</SubnetId>
    <ZoneName>us-west-2a</ZoneName>
  </member>
  <member>
    <SubnetId>subnet-b7d581c0</SubnetId>
    <ZoneName>us-west-2b</ZoneName>
  </member>
</AvailabilityZones>
<SecurityGroups>
  <member>sg-5943793c</member>
</SecurityGroups>
<DNSName>internal-my-internal-load-balancer-1529930873.us-
west-2.elb.amazonaws.com</DNSName>
<State>
  <Code>provisioning</Code>
</State>
<Type>application</Type>
</member>
</LoadBalancers>
</CreateLoadBalancerResult>
<ResponseMetadata>
  <RequestId>b37b9c3e-f2d0-11e5-a53c-67205c0d10fd</RequestId>
</ResponseMetadata>
</CreateLoadBalancerResponse>
```

Create a Network Load Balancer

This example creates a Network Load Balancer and associates an Elastic IP address with each of the specified subnets.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateLoadBalancer
&Name=my-network-load-balancer
&Type=network
&SubnetMappings.member.1.SubnetId=subnet-8360a9e7
&SubnetMappings.member.1.AllocationId=eipalloc-5723d13e
&SubnetMappings.member.2.SubnetId=subnet-b7d581c0
```

```
&SubnetMappings.member.2.AllocationId=eipalloc-fc5ca095  
&Version=2015-12-01  
&AUTHPARAMS
```

Create a Gateway Load Balancer

This example creates a Gateway Load Balancer.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateLoadBalancer  
&Name=my-gateway-load-balancer  
&Type=gateway  
&Subnets.member.1.SubnetId=subnet-066877671789bd71b  
&Subnets.member.2.SubnetId=subnet-09ed24a70bc19bbe4  
&Version=2015-12-01  
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateRule

Creates a rule for the specified listener. The listener must be associated with an Application Load Balancer.

Each rule consists of a priority, one or more actions, one or more conditions, and up to two optional transforms. Rules are evaluated in priority order, from the lowest value to the highest value. When the conditions for a rule are met, its actions are performed. If the conditions for no rules are met, the actions for the default rule are performed. For more information, see [Listener rules](#) in the *Application Load Balancers Guide*.

To view your current rules, use [DescribeRules](#). To update a rule, use [ModifyRule](#). To set the priorities of your rules, use [SetRulePriorities](#). To delete a rule, use [DeleteRule](#).

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

Actions.member.N

The actions.

Type: Array of [Action](#) objects

Required: Yes

Conditions.member.N

The conditions.

Type: Array of [RuleCondition](#) objects

Required: Yes

ListenerArn

The Amazon Resource Name (ARN) of the listener.

Type: String

Required: Yes

Priority

The rule priority. A listener can't have multiple rules with the same priority.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50000.

Required: Yes

Tags.member.N

The tags to assign to the rule.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item.

Required: No

Transforms.member.N

The transforms to apply to requests that match this rule. You can add one host header rewrite transform and one URL rewrite transform.

Type: Array of [RuleTransform](#) objects

Required: No

Response Elements

The following element is returned by the service.

Rules.member.N

Information about the rule.

Type: Array of [Rule](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

IncompatibleProtocols

The specified configuration is not valid with this protocol.

HTTP Status Code: 400

InvalidConfigurationRequest

The requested configuration is not valid.

HTTP Status Code: 400

InvalidLoadBalancerAction

The requested action is not valid.

HTTP Status Code: 400

ListenerNotFound

The specified listener does not exist.

HTTP Status Code: 400

PriorityInUse

The specified priority is in use.

HTTP Status Code: 400

TargetGroupAssociationLimit

You've reached the limit on the number of load balancers per target group.

HTTP Status Code: 400

TargetGroupNotFound

The specified target group does not exist.

HTTP Status Code: 400

TooManyActions

You've reached the limit on the number of actions per rule.

HTTP Status Code: 400

TooManyRegistrationsForTargetId

You've reached the limit on the number of times a target can be registered with a load balancer.

HTTP Status Code: 400

TooManyRules

You've reached the limit on the number of rules per load balancer.

HTTP Status Code: 400

TooManyTags

You've reached the limit on the number of tags for this resource.

HTTP Status Code: 400

TooManyTargetGroups

You've reached the limit on the number of target groups for your AWS account.

HTTP Status Code: 400

TooManyTargets

You've reached the limit on the number of targets.

HTTP Status Code: 400

TooManyUniqueTargetGroupsPerLoadBalancer

You've reached the limit on the number of unique target groups per load balancer across all listeners. If a target group is used by multiple actions for a load balancer, it is counted as only one use.

HTTP Status Code: 400

UnsupportedProtocol

The specified protocol is not supported.

HTTP Status Code: 400

Examples

Create a rule that forwards to a target group if a condition is met

This example creates a rule that forwards requests to the specified target group if the URL contains the specified pattern (for example, /img/*).

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateRule
&ListenerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/my-load-
balancer/50dc6c495c0c9188/f2f7dc8efc522ab2
&Priority=10
&Conditions.member.1.Field=path-pattern
&Conditions.member.1.Values.member.1=/img/*
&Actions.member.1.Type=forward
&Actions.member.1.TargetGroupArn=arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<CreateRuleResponse xmlns="http://elasticloadbalancing.amazonaws.com/doc/2015-12-01/">
  <CreateRuleResult>
    <Rules>
      <member>
        <IsDefault>>false</IsDefault>
        <Conditions>
          <member>
            <Field>path-pattern</Field>
            <Values>
              <member>/img/*</member>
            </Values>
          </member>
        </Conditions>
        <Priority>10</Priority>
        <Actions>
          <member>
            <Type>forward</Type>
            <TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
          </member>
        </Actions>
        <RuleArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener-rule/app/
my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2/9683b2d02a6cabee</RuleArn>
      </member>
    </Rules>
  </CreateRuleResult>
  <ResponseMetadata>
```

```
<RequestId>c5478c83-f397-11e5-bb98-57195a6eb84a</RequestId>
</ResponseMetadata>
</CreateRuleResponse>
```

Create a rule with a forward rule and an authenticate-oidc rule

This example creates a rule that first authenticates the user and then forwards the request if the user is authenticated.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateRule
&ListenerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/my-load-
balancer/50dc6c495c0c9188/f2f7dc8efc522ab2
&Priority=10
&Actions.member.1.Type=authenticate-oidc
&Actions.member.1.AuthenticateOidcConfig.Issuer="https://idp-issuer.com"
&Actions.member.1.AuthenticateOidcConfig.AuthorizationEndpoint="https://authorization-
endpoint.com"
&Actions.member.1.AuthenticateOidcConfig.TokenEndpoint="https://token-endpoint.com"
&Actions.member.1.AuthenticateOidcConfig.UserInfoEndpoint="https://user-info-
endpoint.com"
&Actions.member.1.AuthenticateOidcConfig.ClientId="abcdefghijklmnopqrstuvwxy123456789"
&Actions.member.1.AuthenticateOidcConfig.ClientSecret="123456789012345678901234567890"
&Actions.member.1.AuthenticateOidcConfig.SessionTimeout=3600
&Actions.member.1.AuthenticateOidcConfig.Scope="email"
&Actions.member.1.AuthenticateOidcConfig.OnUnauthenticatedRequest="authenticate"
&Actions.member.1.Order=1
&Actions.member.2.Type=forward
&Actions.member.2.TargetGroupArn=arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067
&Actions.member.2.Order=2
&Version=2015-12-01
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateTargetGroup

Creates a target group.

To register targets with the target group, use [RegisterTargets](#). To update the health check settings for the target group, use [ModifyTargetGroup](#). To monitor the health of targets in the target group, use [DescribeTargetHealth](#).

To route traffic to the targets in a target group, specify the target group in an action using [CreateListener](#) or [CreateRule](#).

To delete a target group, use [DeleteTargetGroup](#).

For more information, see the following:

- [Target groups for your Application Load Balancers](#)
- [Target groups for your Network Load Balancers](#)
- [Target groups for your Gateway Load Balancers](#)

This operation is idempotent, which means that it completes at most one time. If you attempt to create multiple target groups with the same settings, each call succeeds.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

HealthCheckEnabled

Indicates whether health checks are enabled. If the target type is `lambda`, health checks are disabled by default but can be enabled. If the target type is `instance`, `ip`, or `alb`, health checks are always enabled and can't be disabled.

Type: Boolean

Required: No

HealthCheckIntervalSeconds

The approximate amount of time, in seconds, between health checks of an individual target. The range is 5-300. If the target group protocol is `TCP`, `TLS`, `UDP`, `TCP_UDP`, `QUIC`, `TCP_QUIC`,

HTTP or HTTPS, the default is 30 seconds. If the target group protocol is GENEVE, the default is 10 seconds. If the target type is `lambda`, the default is 35 seconds.

Type: Integer

Valid Range: Minimum value of 5. Maximum value of 300.

Required: No

HealthCheckPath

[HTTP/HTTPS health checks] The destination for health checks on the targets.

[HTTP1 or HTTP2 protocol version] The ping path. The default is `/`.

[GRPC protocol version] The path of a custom health check method with the format `/package.service/method`. The default is `/AWS.ALB/healthcheck`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

HealthCheckPort

The port the load balancer uses when performing health checks on targets. If the protocol is HTTP, HTTPS, TCP, TLS, UDP, TCP_UDP, QUIC, or TCP_QUIC the default is `traffic-port`, which is the port on which each target receives traffic from the load balancer. If the protocol is GENEVE, the default is port 80.

Type: String

Required: No

HealthCheckProtocol

The protocol the load balancer uses when performing health checks on targets. For Application Load Balancers, the default is HTTP. For Network Load Balancers and Gateway Load Balancers, the default is TCP. The TCP protocol is not supported for health checks if the protocol of the target group is HTTP or HTTPS. The GENEVE, TLS, UDP, TCP_UDP, QUIC, and TCP_QUIC protocols are not supported for health checks.

Type: String

Valid Values: HTTP | HTTPS | TCP | TLS | UDP | TCP_UDP | GENEVE | QUIC | TCP_QUIC

Required: No

HealthCheckTimeoutSeconds

The amount of time, in seconds, during which no response from a target means a failed health check. The range is 2–120 seconds. For target groups with a protocol of HTTP, the default is 6 seconds. For target groups with a protocol of TCP, TLS or HTTPS, the default is 10 seconds. For target groups with a protocol of GENEVE, the default is 5 seconds. If the target type is `lambda`, the default is 30 seconds.

Type: Integer

Valid Range: Minimum value of 2. Maximum value of 120.

Required: No

HealthyThresholdCount

The number of consecutive health check successes required before considering a target healthy. The range is 2-10. If the target group protocol is TCP, TCP_UDP, UDP, TLS, HTTP or HTTPS, the default is 5. For target groups with a protocol of GENEVE, the default is 5. If the target type is `lambda`, the default is 5.

Type: Integer

Valid Range: Minimum value of 2. Maximum value of 10.

Required: No

IpAddressType

The IP address type. The default value is `ipv4`.

Type: String

Valid Values: `ipv4` | `ipv6`

Required: No

Matcher

[HTTP/HTTPS health checks] The HTTP or gRPC codes to use when checking for a successful response from a target. For target groups with a protocol of TCP, TCP_UDP, UDP, QUIC,

TCP_QUIC, or TLS the range is 200-599. For target groups with a protocol of HTTP or HTTPS, the range is 200-499. For target groups with a protocol of GENEVE, the range is 200-399.

Type: [Matcher](#) object

Required: No

Name

The name of the target group.

This name must be unique per region per account, can have a maximum of 32 characters, must contain only alphanumeric characters or hyphens, and must not begin or end with a hyphen.

Type: String

Required: Yes

Port

The port on which the targets receive traffic. This port is used unless you specify a port override when registering the target. If the target is a Lambda function, this parameter does not apply. If the protocol is GENEVE, the supported port is 6081.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

Protocol

The protocol to use for routing traffic to the targets. For Application Load Balancers, the supported protocols are HTTP and HTTPS. For Network Load Balancers, the supported protocols are TCP, TLS, UDP, TCP_UDP, QUIC, or TCP_QUIC. For Gateway Load Balancers, the supported protocol is GENEVE. A TCP_UDP listener must be associated with a TCP_UDP target group. A TCP_QUIC listener must be associated with a TCP_QUIC target group. If the target is a Lambda function, this parameter does not apply.

Type: String

Valid Values: HTTP | HTTPS | TCP | TLS | UDP | TCP_UDP | GENEVE | QUIC | TCP_QUIC

Required: No

ProtocolVersion

[HTTP/HTTPS protocol] The protocol version. Specify GRPC to send requests to targets using gRPC. Specify HTTP2 to send requests to targets using HTTP/2. The default is HTTP1, which sends requests to targets using HTTP/1.1.

Type: String

Required: No

Tags.member.N

The tags to assign to the target group.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item.

Required: No

TargetControlPort

The port on which the target control agent and application load balancer exchange management traffic for the target optimizer feature.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

TargetType

The type of target that you must specify when registering targets with this target group. You can't specify targets for a target group using more than one target type.

- `instance` - Register targets by instance ID. This is the default value.
- `ip` - Register targets by IP address. You can specify IP addresses from the subnets of the virtual private cloud (VPC) for the target group, the RFC 1918 range (10.0.0.0/8, 172.16.0.0/12, and 192.168.0.0/16), and the RFC 6598 range (100.64.0.0/10). You can't specify publicly routable IP addresses.
- `lambda` - Register a single Lambda function as a target.

- `alb` - Register a single Application Load Balancer as a target.

Type: String

Valid Values: `instance` | `ip` | `lambda` | `alb`

Required: No

UnhealthyThresholdCount

The number of consecutive health check failures required before considering a target unhealthy. The range is 2-10. If the target group protocol is TCP, TCP_UDP, UDP, TLS, QUIC, TCP_QUIC, HTTP or HTTPS, the default is 2. For target groups with a protocol of GENEVE, the default is 2. If the target type is `lambda`, the default is 5.

Type: Integer

Valid Range: Minimum value of 2. Maximum value of 10.

Required: No

VpcId

The identifier of the virtual private cloud (VPC). If the target is a Lambda function, this parameter does not apply. Otherwise, this parameter is required.

Type: String

Required: No

Response Elements

The following element is returned by the service.

TargetGroups.member.N

Information about the target group.

Type: Array of [TargetGroup](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

DuplicateTargetGroupName

A target group with the specified name already exists.

HTTP Status Code: 400

InvalidConfigurationRequest

The requested configuration is not valid.

HTTP Status Code: 400

TooManyTags

You've reached the limit on the number of tags for this resource.

HTTP Status Code: 400

TooManyTargetGroups

You've reached the limit on the number of target groups for your AWS account.

HTTP Status Code: 400

Examples

Create a target group to route traffic to instances registered by instance ID

This example creates a target group for an Application Load Balancer that you can use to route traffic to instances using HTTP on port 80. You register the instances by instance ID. This target group uses the default health check settings.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateTargetGroup
&Name=my-targets
&Protocol=HTTP
&Port=80
&VpcId=vpc-3ac0fb5f
&TargetType=instance
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<CreateTargetGroupResponse xmlns="http://elasticloadbalancing.amazonaws.com/doc/2015-12-01/">
  <CreateTargetGroupResult>
    <TargetGroups>
      <member>
        <TargetGroupArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
        <HealthCheckTimeoutSeconds>5</HealthCheckTimeoutSeconds>
        <HealthCheckPort>traffic-port</HealthCheckPort>
        <Matcher>
          <HttpCode>200</HttpCode>
        </Matcher>
        <TargetGroupName>my-targets</TargetGroupName>
        <HealthCheckProtocol>HTTP</HealthCheckProtocol>
        <HealthCheckPath>/</HealthCheckPath>
        <Protocol>HTTP</Protocol>
        <Port>80</Port>
        <VpcId>vpc-3ac0fb5f</VpcId>
        <HealthyThresholdCount>5</HealthyThresholdCount>
        <HealthCheckIntervalSeconds>30</HealthCheckIntervalSeconds>
        <UnhealthyThresholdCount>2</UnhealthyThresholdCount>
      </member>
    </TargetGroups>
  </CreateTargetGroupResult>
  <ResponseMetadata>
    <RequestId>b83fe90e-f2d5-11e5-b95d-3b2c1831fc26</RequestId>
  </ResponseMetadata>
</CreateTargetGroupResponse>
```

Create a target group to route traffic to IP addresses

This example creates a target group for a Network Load Balancer that you can use to route traffic to IP addresses using TCP on port 80. This target group uses the default health check settings.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateTargetGroup
&Name=my-ip-targets
&Protocol=TCP
&Port=80
&VpcId=vpc-09e5e2c5ef7e38ae7
```

```
&TargetType=ip
&Version=2015-12-01
&AUTHPARAMS
```

Create a target group to route traffic to a Lambda function

This example creates a target group for an Application Load Balancer that you can use to route traffic to a Lambda function. This target group uses the default health check settings. For more information, see [Lambda functions as targets](#) in the *Application Load Balancers Guide*.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateTargetGroup
&Name=my-lambda-target
&TargetType=lambda
&Version=2015-12-01
&AUTHPARAMS
```

Create a target group for your Gateway Load Balancer

This example creates a target group for a Gateway Load Balancer. The protocol must be GENEVE and the port must be 6081.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateTargetGroup
&Name=my-appliance-targets
&Protocol=GENEVE
&Port=6081
&VpcId=vpc-09e5e2c5ef7e38ae7
&TargetType=ip
&Version=2015-12-01
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateTrustStore

Creates a trust store.

For more information, see [Mutual TLS for Application Load Balancers](#).

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

CaCertificatesBundleS3Bucket

The Amazon S3 bucket for the ca certificates bundle.

Type: String

Required: Yes

CaCertificatesBundleS3Key

The Amazon S3 path for the ca certificates bundle.

Type: String

Required: Yes

CaCertificatesBundleS3ObjectVersion

The Amazon S3 object version for the ca certificates bundle. If undefined the current version is used.

Type: String

Required: No

Name

The name of the trust store.

This name must be unique per region and can't be changed after creation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: $^([a-zA-Z0-9]+-)^*[a-zA-Z0-9]+\$$

Required: Yes

Tags.member.N

The tags to assign to the trust store.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item.

Required: No

Response Elements

The following element is returned by the service.

TrustStores.member.N

Information about the trust store created.

Type: Array of [TrustStore](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CaCertificatesBundleNotFound

The specified ca certificate bundle does not exist.

HTTP Status Code: 400

DuplicateTagKeys

A tag key was specified more than once.

HTTP Status Code: 400

DuplicateTrustStoreName

A trust store with the specified name already exists.

HTTP Status Code: 400

InvalidCaCertificatesBundle

The specified ca certificate bundle is in an invalid format, or corrupt.

HTTP Status Code: 400

TooManyTags

You've reached the limit on the number of tags for this resource.

HTTP Status Code: 400

TooManyTrustStores

You've reached the limit on the number of trust stores for your AWS account.

HTTP Status Code: 400

Examples

Create a trust store.

This example creates a trust store using the current version of the specified ca certificate bundle.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateTrustStore
&Name=my-trust-store
&CaCertificatesBundleS3Bucket=amzn-s3-demo-bucket
&CaCertificatesBundleS3Key=CACertBundle.pem
&Version=2015-12-01
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteListener

Deletes the specified listener.

Alternatively, your listener is deleted when you delete the load balancer to which it is attached, using [DeleteLoadBalancer](#).

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

ListenerArn

The Amazon Resource Name (ARN) of the listener.

Type: String

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ListenerNotFound

The specified listener does not exist.

HTTP Status Code: 400

ResourceInUse

A specified resource is in use.

HTTP Status Code: 400

Examples

Delete a listener

This example deletes the specified listener.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DeleteListener
&ListenerArn=arn:aws:elasticloadbalancing:ua-west-2:123456789012:listener/app/my-load-
balancer/50dc6c495c0c9188/f2f7dc8efc522ab2
&Version=2015-12-01
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteLoadBalancer

Deletes the specified Application Load Balancer, Network Load Balancer, or Gateway Load Balancer. Deleting a load balancer also deletes its listeners.

You can't delete a load balancer if deletion protection is enabled. If the load balancer does not exist or has already been deleted, the call succeeds.

Deleting a load balancer does not affect its registered targets. For example, your EC2 instances continue to run and are still registered to their target groups. If you no longer need these EC2 instances, you can stop or terminate them.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

LoadBalancerArn

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

OperationNotPermitted

This operation is not allowed.

HTTP Status Code: 400

ResourceInUse

A specified resource is in use.

HTTP Status Code: 400

Examples

Delete a load balancer

This example deletes the specified load balancer.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DeleteLoadBalancer
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/
my-load-balancer/50dc6c495c0c9188
&Version=2015-12-01
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteRule

Deletes the specified rule.

You can't delete the default rule.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

RuleArn

The Amazon Resource Name (ARN) of the rule.

Type: String

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

OperationNotPermitted

This operation is not allowed.

HTTP Status Code: 400

RuleNotFound

The specified rule does not exist.

HTTP Status Code: 400

Examples

Delete a rule

This example deletes the specified rule.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DeleteRule
```

```
&RuleArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:listener-rule/app/my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2/1291d13826f405c3
&Version=2015-12-01
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteSharedTrustStoreAssociation

Deletes a shared trust store association.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

ResourceArn

The Amazon Resource Name (ARN) of the resource.

Type: String

Required: Yes

TrustStoreArn

The Amazon Resource Name (ARN) of the trust store.

Type: String

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AssociationNotFound

The specified association does not exist.

HTTP Status Code: 400

DeleteAssociationSameAccount

The specified association can't be within the same account.

HTTP Status Code: 400

TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteTargetGroup

Deletes the specified target group.

You can delete a target group if it is not referenced by any actions. Deleting a target group also deletes any associated health checks. Deleting a target group does not affect its registered targets. For example, any EC2 instances continue to run until you stop or terminate them.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

TargetGroupArn

The Amazon Resource Name (ARN) of the target group.

Type: String

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ResourceInUse

A specified resource is in use.

HTTP Status Code: 400

Examples

Delete a target group

This example deletes the specified target group.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DeleteTargetGroup
```

```
&TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-  
targets/73e2d6bc24d8a067  
&Version=2015-12-01  
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteTrustStore

Deletes a trust store.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

TrustStoreArn

The Amazon Resource Name (ARN) of the trust store.

Type: String

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

TrustStoreInUse

The specified trust store is currently in use.

HTTP Status Code: 400

TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

Examples

Delete a trust store.

This example deletes the specified trust store.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DeleteTrustStore
```

```
&TrustStoreArn=arn:aws:elasticloadbalancing:us-east-1:111122223333:truststore/my-trust-  
store/3ym756xh7yj  
&Version=2015-12-01  
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeregisterTargets

Deregisters the specified targets from the specified target group. After the targets are deregistered, they no longer receive traffic from the load balancer.

The load balancer stops sending requests to targets that are deregistering, but uses connection draining to ensure that in-flight traffic completes on the existing connections. This deregistration delay is configured by default but can be updated for each target group.

For more information, see the following:

- [Deregistration delay](#) in the *Application Load Balancers User Guide*
- [Deregistration delay](#) in the *Network Load Balancers User Guide*
- [Deregistration delay](#) in the *Gateway Load Balancers User Guide*

Note: If the specified target does not exist, the action returns successfully.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

TargetGroupArn

The Amazon Resource Name (ARN) of the target group.

Type: String

Required: Yes

Targets.member.N

The targets. If you specified a port override when you registered a target, you must specify both the target ID and the port when you deregister it.

Type: Array of [TargetDescription](#) objects

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidTarget

The specified target does not exist, is not in the same VPC as the target group, or has an unsupported instance type.

HTTP Status Code: 400

TargetGroupNotFound

The specified target group does not exist.

HTTP Status Code: 400

Examples

Deregister an instance from a target group

This example deregisters the specified instance from the specified target group.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DeregisterTargets
&TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-
targets/73e2d6bc24d8a067
&Targets.member.1.Id=i-0f76fade435676abd
&Version=2015-12-01
&AUTHPARAMS
```

Deregister an IP address from a target group

This example deregisters the specified IP address from the specified target group.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DeregisterTargets
&TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-
targets/73e2d6bc24d8a067
&Targets.member.1.Id=10.0.1.238
&Version=2015-12-01
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAccountLimits

Describes the current Elastic Load Balancing resource limits for your AWS account.

For more information, see the following:

- [Quotas for your Application Load Balancers](#)
- [Quotas for your Network Load Balancers](#)
- [Quotas for your Gateway Load Balancers](#)

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

Marker

The marker for the next set of results. (You received this marker from a previous call.)

Type: String

Required: No

PageSize

The maximum number of results to return with this call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 400.

Required: No

Response Elements

The following elements are returned by the service.

Limits.member.N

Information about the limits.

Type: Array of [Limit](#) objects

NextMarker

If there are additional results, this is the marker for the next set of results. Otherwise, this is null.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeCapacityReservation

Describes the capacity reservation status for the specified load balancer.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

LoadBalancerArn

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: Yes

Response Elements

The following elements are returned by the service.

CapacityReservationState.member.N

The state of the capacity reservation.

Type: Array of [ZonalCapacityReservationState](#) objects

DecreaseRequestsRemaining

The amount of daily capacity decreases remaining.

Type: Integer

LastModifiedTime

The last time the capacity reservation was modified.

Type: Timestamp

MinimumLoadBalancerCapacity

The requested minimum capacity reservation for the load balancer

Type: [MinimumLoadBalancerCapacity](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeListenerAttributes

Describes the attributes for the specified listener.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

ListenerArn

The Amazon Resource Name (ARN) of the listener.

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

Attributes.member.N

Information about the listener attributes.

Type: Array of [ListenerAttribute](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ListenerNotFound

The specified listener does not exist.

HTTP Status Code: 400

Examples

Describe listener attributes

This example describes the attributes of the specified listener.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeListenerAttributes
&ListenerArn=arn:aws:elasticloadbalancing:us-east-1:123456789012:listener/net/my-
listener/73e2d6bc24d8a067/d5dc06411fa5bcea
&Version=2015-12-01
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeListenerCertificates

Describes the default certificate and the certificate list for the specified HTTPS or TLS listener.

If the default certificate is also in the certificate list, it appears twice in the results (once with `IsDefault` set to true and once with `IsDefault` set to false).

For more information, see [SSL certificates](#) in the *Application Load Balancers Guide* or [Server certificates](#) in the *Network Load Balancers Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

ListenerArn

The Amazon Resource Names (ARN) of the listener.

Type: String

Required: Yes

Marker

The marker for the next set of results. (You received this marker from a previous call.)

Type: String

Required: No

PageSize

The maximum number of results to return with this call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 400.

Required: No

Response Elements

The following elements are returned by the service.

Certificates.member.N

Information about the certificates.

Type: Array of [Certificate](#) objects

NextMarker

If there are additional results, this is the marker for the next set of results. Otherwise, this is null.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ListenerNotFound

The specified listener does not exist.

HTTP Status Code: 400

Examples

Describe the certificate list for a listener

This example describes the certificate list for the specified listener.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeListenerCertificates
&ListenerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/my-load-
balancer/50dc6c495c0c9188/f2f7dc8efc522ab2
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<DescribeListenerCertificatesResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
```

```
<DescribeListenerCertificatesResult>
  <Certificates>
    <member>
      <CertificateArn>arn:aws:acm:us-
west-2:123456789012:certificate/1bf70a25-6914-495a-92f8-e27feEXAMPLE</CertificateArn>
      <IsDefault>true</IsDefault>
    </member>
    <member>
      <CertificateArn>arn:aws:acm:us-
west-2:123456789012:certificate/68c11a12-39de-44dd-b329-fe64aEXAMPLE</CertificateArn>
      <IsDefault>>false</IsDefault>
    </member>
    <member>
      <CertificateArn>arn:aws:acm:us-
west-2:123456789012:certificate/1bf70a25-6914-495a-92f8-e27feEXAMPLE</CertificateArn>
      <IsDefault>>false</IsDefault>
    </member>
  </Certificates>
</DescribeListenerCertificatesResult>
<ResponseMetadata>
  <RequestId>18e470d3-f39c-11e5-a53c-67205c0d10fd</RequestId>
</ResponseMetadata>
</DescribeListenerCertificatesResponse>
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeListeners

Describes the specified listeners or the listeners for the specified Application Load Balancer, Network Load Balancer, or Gateway Load Balancer. You must specify either a load balancer or one or more listeners.

For an HTTPS or TLS listener, the output includes the default certificate for the listener. To describe the certificate list for the listener, use [DescribeListenerCertificates](#).

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

ListenerArns.member.N

The Amazon Resource Names (ARN) of the listeners.

Type: Array of strings

Required: No

LoadBalancerArn

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: No

Marker

The marker for the next set of results. (You received this marker from a previous call.)

Type: String

Required: No

PageSize

The maximum number of results to return with this call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 400.

Required: No

Response Elements

The following elements are returned by the service.

Listeners.member.N

Information about the listeners.

Type: Array of [Listener](#) objects

NextMarker

If there are additional results, this is the marker for the next set of results. Otherwise, this is null.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ListenerNotFound

The specified listener does not exist.

HTTP Status Code: 400

LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

UnsupportedProtocol

The specified protocol is not supported.

HTTP Status Code: 400

Examples

Describe an HTTP listener

This example describes the specified HTTP listener.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeListeners
&ListenerArns.member.1=arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/
app/my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<DescribeListenersResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <DescribeListenersResult>
    <Listeners>
      <member>
        <LoadBalancerArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188</
LoadBalancerArn>
        <Protocol>HTTP</Protocol>
        <Port>80</Port>
        <ListenerArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/
my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2</ListenerArn>
        <DefaultActions>
          <member>
            <Type>forward</Type>
            <TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
          </member>
        </DefaultActions>
      </member>
    </Listeners>
  </DescribeListenersResult>
  <ResponseMetadata>
    <RequestId>18e470d3-f39c-11e5-a53c-67205c0d10fd</RequestId>
  </ResponseMetadata>
</DescribeListenersResponse>
```

Describe an HTTPS listener

This example describes the specified HTTPS listener.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeListeners
&ListenerArns.member.1=arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/
app/my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<DescribeListenersResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <DescribeListenersResult>
    <Listeners>
      <member>
        <Port>443</Port>
        <Protocol>HTTPS</Protocol>
        <LoadBalancerArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188</
LoadBalancerArn>
        <ListenerArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/
my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2</ListenerArn>
        <DefaultActions>
          <member>
            <Type>forward</Type>
            <TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
          </member>
        </DefaultActions>
        <SslPolicy>ELBSecurityPolicy-2016-08</SslPolicy>
        <Certificates>
          <member>
            <CertificateArn>arn:aws:acm:us-
west-2:123456789012:certificate/68c11a12-39de-44dd-b329-fe64aEXAMPLE</CertificateArn>
          </member>
        </Certificates>
      </member>
    </Listeners>
  </DescribeListenersResult>
```

```
<ResponseMetadata>
  <RequestId>18e470d3-f39c-11e5-a53c-67205c0d10fd</RequestId>
</ResponseMetadata>
</DescribeListenersResponse>
```

Describe the listeners for a load balancer

This example describe the listeners for the specified load balancer.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeListeners
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/my-
load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<DescribeLoadBalancersResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <DescribeListenersResult>
    <Listeners>
      <member>
        <LoadBalancerArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188</
LoadBalancerArn>
        <Protocol>HTTPS</Protocol>
        <Certificates>
          <member>
            <CertificateArn>arn:aws:iam::123456789012:server-certificate/my-server-
cert</CertificateArn>
          </member>
        </Certificates>
        <Port>443</Port>
        <SslPolicy>ELBSecurityPolicy-2016-08</SslPolicy>
        <ListenerArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/
my-load-balancer/50dc6c495c0c9188/0467ef3c8400ae65</ListenerArn>
        <DefaultActions>
          <member>
            <Type>forward</Type>
            <TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
```

```
        </member>
    </DefaultActions>
</member>
<member>
    <LoadBalancerArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188</
LoadBalancerArn>
    <Protocol>HTTP</Protocol>
    <Port>80</Port>
    <ListenerArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/
my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2</ListenerArn>
    <DefaultActions>
        <member>
            <Type>forward</Type>
            <TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
        </member>
    </DefaultActions>
</member>
</Listeners>
</DescribeListenersResult>
<ResponseMetadata>
    <RequestId>65a3a7ea-f39c-11e5-b543-9f2c3fbb9bee</RequestId>
</ResponseMetadata>
</DescribeLoadBalancersResponse>
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeLoadBalancerAttributes

Describes the attributes for the specified Application Load Balancer, Network Load Balancer, or Gateway Load Balancer.

For more information, see the following:

- [Load balancer attributes](#) in the *Application Load Balancers Guide*
- [Load balancer attributes](#) in the *Network Load Balancers Guide*
- [Load balancer attributes](#) in the *Gateway Load Balancers Guide*

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

LoadBalancerArn

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

Attributes.member.N

Information about the load balancer attributes.

Type: Array of [LoadBalancerAttribute](#) objects

Array Members: Maximum number of 20 items.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

Examples

Describe load balancer attributes

This example describes the attributes of the specified load balancer.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeLoadBalancerAttributes
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/
my-load-balancer/50dc6c495c0c9188
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<DescribeLoadBalancerAttributesResponse xmlns="http://
elasticloadbalancing.amazonaws.com/doc/2015-12-01/">
  <DescribeLoadBalancerAttributesResult>
    <Attributes>
      <member>
        <Value>>false</Value>
        <Key>access_logs.s3.enabled</Key>
      </member>
      <member>
        <Value>60</Value>
        <Key>idle_timeout.timeout_seconds</Key>
      </member>
      <member>
        <Value />
        <Key>access_logs.s3.prefix</Key>
      </member>
      <member>
        <Value>>false</Value>
        <Key>deletion_protection.enabled</Key>
      </member>
    </Attributes>
  </DescribeLoadBalancerAttributesResult>
</DescribeLoadBalancerAttributesResponse>
```

```
<member>
  <Value />
  <Key>access_logs.s3.bucket</Key>
</member>
</Attributes>
</DescribeLoadBalancerAttributesResult>
<ResponseMetadata>
  <RequestId>1528a9a4-f38e-11e5-8ead-f1e91be31786</RequestId>
</ResponseMetadata>
</DescribeLoadBalancerAttributesResponse>
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeLoadBalancers

Describes the specified load balancers or all of your load balancers.

To describe the listeners for a load balancer, use [DescribeListeners](#). To describe the attributes for a load balancer, use [DescribeLoadBalancerAttributes](#).

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

LoadBalancerArns.member.N

The Amazon Resource Names (ARN) of the load balancers. You can specify up to 20 load balancers in a single call.

Type: Array of strings

Required: No

Marker

The marker for the next set of results. (You received this marker from a previous call.)

Type: String

Required: No

Names.member.N

The names of the load balancers.

Type: Array of strings

Required: No

PageSize

The maximum number of results to return with this call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 400.

Required: No

Response Elements

The following elements are returned by the service.

LoadBalancers.member.N

Information about the load balancers.

Type: Array of [LoadBalancer](#) objects

NextMarker

If there are additional results, this is the marker for the next set of results. Otherwise, this is null.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

Examples

Describe a load balancer

This example describes the specified load balancer.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeLoadBalancers
&LoadBalancerArns.member.1=arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188
```

```
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<DescribeLoadBalancersResponse xmlns="http://elasticloadbalancing.amazonaws.com/doc/2015-12-01/">
  <DescribeLoadBalancersResult>
    <LoadBalancers>
      <member>
        <LoadBalancerArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188</LoadBalancerArn>
        <Scheme>internet-facing</Scheme>
        <LoadBalancerName>my-load-balancer</LoadBalancerName>
        <VpcId>vpc-3ac0fb5f</VpcId>
        <CanonicalHostedZoneId>Z2P70J7EXAMPLE</CanonicalHostedZoneId>
        <CreatedTime>2016-03-25T21:26:12.920Z</CreatedTime>
        <AvailabilityZones>
          <member>
            <SubnetId>subnet-8360a9e7</SubnetId>
            <ZoneName>us-west-2a</ZoneName>
          </member>
          <member>
            <SubnetId>subnet-b7d581c0</SubnetId>
            <ZoneName>us-west-2b</ZoneName>
          </member>
        </AvailabilityZones>
        <SecurityGroups>
          <member>sg-5943793c</member>
        </SecurityGroups>
        <DNSName>my-load-balancer-424835706.us-west-2.elb.amazonaws.com</DNSName>
        <State>
          <Code>active</Code>
        </State>
        <Type>application</Type>
      </member>
    </LoadBalancers>
  </DescribeLoadBalancersResult>
  <ResponseMetadata>
    <RequestId>6581c0ac-f39f-11e5-bb98-57195a6eb84a</RequestId>
  </ResponseMetadata>
</DescribeLoadBalancersResponse>
```

Describe all load balancers

This example describes all of your load balancers.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeLoadBalancers
&Version=2015-12-01
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeRules

Describes the specified rules or the rules for the specified listener. You must specify either a listener or rules.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

ListenerArn

The Amazon Resource Name (ARN) of the listener.

Type: String

Required: No

Marker

The marker for the next set of results. (You received this marker from a previous call.)

Type: String

Required: No

PageSize

The maximum number of results to return with this call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 400.

Required: No

RuleArns.member.N

The Amazon Resource Names (ARN) of the rules.

Type: Array of strings

Required: No

Response Elements

The following elements are returned by the service.

NextMarker

If there are additional results, this is the marker for the next set of results. Otherwise, this is null.

Type: String

Rules.member.N

Information about the rules.

Type: Array of [Rule](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ListenerNotFound

The specified listener does not exist.

HTTP Status Code: 400

RuleNotFound

The specified rule does not exist.

HTTP Status Code: 400

UnsupportedProtocol

The specified protocol is not supported.

HTTP Status Code: 400

Examples

Describe a rule

This example describes the specified rule.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeRules
```

```
&RuleArns.member.1=arn:aws:elasticloadbalancing:us-west-2:123456789012:listener-rule/
app/my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2/9683b2d02a6cabee
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<DescribeRulesResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <DescribeRulesResult>
    <Rules>
      <member>
        <IsDefault>>false</IsDefault>
        <Conditions>
          <member>
            <Field>path-pattern</Field>
            <Values>
              <member>/img/*</member>
            </Values>
          </member>
        </Conditions>
        <Priority>10</Priority>
        <Actions>
          <member>
            <Type>forward</Type>
            <TargetGroupArn>arn:aws:elasticloadbalancing:ua-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
          </member>
        </Actions>
        <RuleArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener-rule/app/
my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2/9683b2d02a6cabee</RuleArn>
      </member>
    </Rules>
  </DescribeRulesResult>
  <ResponseMetadata>
    <RequestId>74926cf3-f3a3-11e5-b543-9f2c3fbb9bee</RequestId>
  </ResponseMetadata>
</DescribeRulesResponse>
```

Describe the rules for a listener

This example describes the rules for the specified listener. The output includes the default rule and any other rules that you've defined.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeRules
&ListenerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/my-load-
balancer/50dc6c495c0c9188/f2f7dc8efc522ab2
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<DescribeRulesResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <DescribeRulesResult>
    <Rules>
      <member>
        <IsDefault>>false</IsDefault>
        <Conditions>
          <member>
            <Field>path-pattern</Field>
            <Values>
              <member>/img/*</member>
            </Values>
          </member>
        </Conditions>
        <Priority>10</Priority>
        <Actions>
          <member>
            <Type>forward</Type>
            <TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
          </member>
        </Actions>
        <RuleArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener-rule/app/
my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2/9683b2d02a6cabee</RuleArn>
      </member>
      <member>
        <IsDefault>>true</IsDefault>
        <Conditions />
        <Priority>default</Priority>
        <Actions>
          <member>
            <Type>forward</Type>
```

```
<TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
  </member>
</Actions>
  <RuleArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener-rule/app/
my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2/fd906cf3d7a9d36d</RuleArn>
  </member>
</Rules>
</DescribeRulesResult>
<ResponseMetadata>
  <RequestId>d8581c8d-f3a3-11e5-8a24-ffe2bf8623ae</RequestId>
</ResponseMetadata>
</DescribeRulesResponse>
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeSSLPolicies

Describes the specified policies or all policies used for SSL negotiation.

For more information, see [Security policies](#) in the *Application Load Balancers Guide* and [Security policies](#) in the *Network Load Balancers Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

LoadBalancerType

The type of load balancer. The default lists the SSL policies for all load balancers.

Type: String

Valid Values: `application` | `network` | `gateway`

Required: No

Marker

The marker for the next set of results. (You received this marker from a previous call.)

Type: String

Required: No

Names.member.N

The names of the policies.

Type: Array of strings

Required: No

PageSize

The maximum number of results to return with this call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 400.

Required: No

Response Elements

The following elements are returned by the service.

NextMarker

If there are additional results, this is the marker for the next set of results. Otherwise, this is null.

Type: String

SslPolicies.member.N

Information about the security policies.

Type: Array of [SslPolicy](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

SSLPolicyNotFound

The specified SSL policy does not exist.

HTTP Status Code: 400

Examples

Describe the specified policy used for SSL negotiation

This example describes the specified policy used for SSL negotiation.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeSSLPolicies
&Names.member.1=ELBSecurityPolicy-2016-08
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<DescribeSSLPoliciesResponse xmlns="http://elasticloadbalancing.amazonaws.com/doc/2015-12-01/">
  <DescribeSSLPoliciesResult>
    <SslPolicies>
      <member>
        <Ciphers>
          <member>
            <Name>ECDHE-ECDSA-AES128-GCM-SHA256</Name>
            <Priority>1</Priority>
          </member>
          <member>
            <Name>ECDHE-RSA-AES128-GCM-SHA256</Name>
            <Priority>2</Priority>
          </member>
          <member>
            <Name>ECDHE-ECDSA-AES128-SHA256</Name>
            <Priority>3</Priority>
          </member>
          ...
          <member>
            <Name>AES256-SHA</Name>
            <Priority>19</Priority>
          </member>
        </Ciphers>
        <Name>ELBSecurityPolicy-2016-08</Name>
        <SslProtocols>
          <member>TLSv1</member>
          <member>TLSv1.1</member>
          <member>TLSv1.2</member>
        </SslProtocols>
      </member>
    </SslPolicies>
  </DescribeSSLPoliciesResult>
  <ResponseMetadata>
    <RequestId>a78c9aee-f2aa-11e5-8a24-ffe2bf8623ae</RequestId>
  </ResponseMetadata>
</DescribeSSLPoliciesResponse>
```

Describe all policies used for SSL negotiation

This example describes all the policies that you can use for SSL negotiation.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeSSLPolicies
&Version=2015-12-01
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeTags

Describes the tags for the specified Elastic Load Balancing resources. You can describe the tags for one or more Application Load Balancers, Network Load Balancers, Gateway Load Balancers, target groups, listeners, or rules.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

ResourceArns.member.N

The Amazon Resource Names (ARN) of the resources. You can specify up to 20 resources in a single call.

Type: Array of strings

Required: Yes

Response Elements

The following element is returned by the service.

TagDescriptions.member.N

Information about the tags.

Type: Array of [TagDescription](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ListenerNotFound

The specified listener does not exist.

HTTP Status Code: 400

LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

RuleNotFound

The specified rule does not exist.

HTTP Status Code: 400

TargetGroupNotFound

The specified target group does not exist.

HTTP Status Code: 400

TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

Examples

Describe the tags assigned to a load balancer

This example describes the tags assigned to the specified load balancer.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeTags
&ResourceArns.member.1=arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<DescribeTagsResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <DescribeTagsResult>
    <TagDescriptions>
      <member>
        <ResourceArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/
app/my-load-balancer/50dc6c495c0c9188</ResourceArn>
```

```
<Tags>
  <member>
    <Value>lima</Value>
    <Key>project</Key>
  </member>
  <member>
    <Value>digital-media</Value>
    <Key>department</Key>
  </member>
</Tags>
</member>
</TagDescriptions>
</DescribeTagsResult>
<ResponseMetadata>
  <RequestId>34f144db-f2d9-11e5-a53c-67205c0d10fd</RequestId>
</ResponseMetadata>
</DescribeTagsResponse>
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeTargetGroupAttributes

Describes the attributes for the specified target group.

For more information, see the following:

- [Target group attributes](#) in the *Application Load Balancers Guide*
- [Target group attributes](#) in the *Network Load Balancers Guide*
- [Target group attributes](#) in the *Gateway Load Balancers Guide*

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

TargetGroupArn

The Amazon Resource Name (ARN) of the target group.

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

Attributes.member.N

Information about the target group attributes

Type: Array of [TargetGroupAttribute](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

TargetGroupNotFound

The specified target group does not exist.

HTTP Status Code: 400

Examples

Describe target group attributes

This example describes the attributes of the specified target group.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeTargetGroupAttributes
&TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-
targets/73e2d6bc24d8a067
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<DescribeTargetGroupAttributesResponse xmlns="http://
elasticloadbalancing.amazonaws.com/doc/2015-12-01/">
  <DescribeTargetGroupAttributesResult>
    <Attributes>
      <member>
        <Value>300</Value>
        <Key>deregistration_delay.timeout_seconds</Key>
      </member>
    </Attributes>
  </DescribeTargetGroupAttributesResult>
  <ResponseMetadata>
    <RequestId>54618294-f3a8-11e5-bb98-57195a6eb84a</RequestId>
  </ResponseMetadata>
</DescribeTargetGroupAttributesResponse>
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeTargetGroups

Describes the specified target groups or all of your target groups. By default, all target groups are described. Alternatively, you can specify one of the following to filter the results: the ARN of the load balancer, the names of one or more target groups, or the ARNs of one or more target groups.

To describe the targets for a target group, use [DescribeTargetHealth](#). To describe the attributes of a target group, use [DescribeTargetGroupAttributes](#).

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

LoadBalancerArn

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: No

Marker

The marker for the next set of results. (You received this marker from a previous call.)

Type: String

Required: No

Names.member.N

The names of the target groups.

Type: Array of strings

Required: No

PageSize

The maximum number of results to return with this call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 400.

Required: No

TargetGroupArns.member.N

The Amazon Resource Names (ARN) of the target groups.

Type: Array of strings

Required: No

Response Elements

The following elements are returned by the service.

NextMarker

If there are additional results, this is the marker for the next set of results. Otherwise, this is null.

Type: String

TargetGroups.member.N

Information about the target groups.

Type: Array of [TargetGroup](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

TargetGroupNotFound

The specified target group does not exist.

HTTP Status Code: 400

Examples

Describe a target group

This example describes the specified target group.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeTargetGroups
&TargetGroupArns.member.1=arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<DescribeTargetGroupsResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <DescribeTargetGroupsResult>
    <TargetGroups>
      <member>
        <TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
        <HealthCheckTimeoutSeconds>5</HealthCheckTimeoutSeconds>
        <HealthCheckPort>traffic-port</HealthCheckPort>
        <Matcher>
          <HttpCode>200</HttpCode>
        </Matcher>
        <TargetGroupName>my-targets</TargetGroupName>
        <HealthCheckProtocol>HTTP</HealthCheckProtocol>
        <HealthCheckPath>/</HealthCheckPath>
        <Protocol>HTTP</Protocol>
        <Port>80</Port>
        <VpcId>vpc-3ac0fb5f</VpcId>
        <HealthyThresholdCount>5</HealthyThresholdCount>
        <HealthCheckIntervalSeconds>30</HealthCheckIntervalSeconds>
        <LoadBalancerArns>
          <member>arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/
my-load-balancer/50dc6c495c0c9188</member>
        </LoadBalancerArns>
        <UnhealthyThresholdCount>2</UnhealthyThresholdCount>
      </member>
    </TargetGroups>
```

```
</DescribeTargetGroupsResult>
<ResponseMetadata>
  <RequestId>70092c0e-f3a9-11e5-ae48-cff02092876b</RequestId>
</ResponseMetadata>
</DescribeTargetGroupsResponse>
```

Describe all target groups for a load balancer

This example describes all target groups for the specified load balancer.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeTargetGroups
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/
my-load-balancer/50dc6c495c0c9188
&Version=2015-12-01
&AUTHPARAMS
```

Describe all target groups

This example describes all of your target groups.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeTargetGroups
&Version=2015-12-01
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeTargetHealth

Describes the health of the specified targets or all of your targets.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

Include.member.N

Used to include anomaly detection information.

Type: Array of strings

Valid Values: AnomalyDetection | All

Required: No

TargetGroupArn

The Amazon Resource Name (ARN) of the target group.

Type: String

Required: Yes

Targets.member.N

The targets.

Type: Array of [TargetDescription](#) objects

Required: No

Response Elements

The following element is returned by the service.

TargetHealthDescriptions.member.N

Information about the health of the targets.

Type: Array of [TargetHealthDescription](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

HealthUnavailable

The health of the specified targets could not be retrieved due to an internal error.

HTTP Status Code: 500

InvalidTarget

The specified target does not exist, is not in the same VPC as the target group, or has an unsupported instance type.

HTTP Status Code: 400

TargetGroupNotFound

The specified target group does not exist.

HTTP Status Code: 400

Examples

Describe the health of the targets for a target group

This example describes the health of the targets for the specified target group. These targets are healthy.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeTargetHealth
&TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-
targets/73e2d6bc24d8a067
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<DescribeTargetHealthResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
```

```
<DescribeTargetHealthResult>
  <TargetHealthDescriptions>
    <member>
      <HealthCheckPort>80</HealthCheckPort>
      <TargetHealth>
        <State>healthy</State>
      </TargetHealth>
      <Target>
        <Port>80</Port>
        <Id>i-0f76fade</Id>
      </Target>
    </member>
    <member>
      <HealthCheckPort>80</HealthCheckPort>
      <TargetHealth>
        <State>healthy</State>
      </TargetHealth>
      <Target>
        <Port>80</Port>
        <Id>i-0f76fade</Id>
      </Target>
    </member>
  </TargetHealthDescriptions>
</DescribeTargetHealthResult>
<ResponseMetadata>
  <RequestId>c534f810-f389-11e5-9192-3fff33344cfa</RequestId>
</ResponseMetadata>
</DescribeTargetHealthResponse>
```

Describe the health of the specified target

This example describes the health of the specified target. This target is healthy.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeTargetHealth
&TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-
targets/73e2d6bc24d8a067
&Targets.member.1.Id=i-0f76fade
&Targets.member.1.Port=80
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<DescribeTargetHealthResponse xmlns="http://elasticloadbalancing.amazonaws.com/doc/2015-12-01/">
  <DescribeTargetHealthResult>
    <TargetHealthDescriptions>
      <member>
        <HealthCheckPort>80</HealthCheckPort>
        <TargetHealth>
          <State>healthy</State>
        </TargetHealth>
        <Target>
          <Port>80</Port>
          <Id>i-0f76fade</Id>
        </Target>
      </member>
    </TargetHealthDescriptions>
  </DescribeTargetHealthResult>
  <ResponseMetadata>
    <RequestId>c534f810-f389-11e5-9192-3fff33344cfa</RequestId>
  </ResponseMetadata>
</DescribeTargetHealthResponse>
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeTrustStoreAssociations

Describes all resources associated with the specified trust store.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

Marker

The marker for the next set of results. (You received this marker from a previous call.)

Type: String

Required: No

PageSize

The maximum number of results to return with this call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 400.

Required: No

TrustStoreArn

The Amazon Resource Name (ARN) of the trust store.

Type: String

Required: Yes

Response Elements

The following elements are returned by the service.

NextMarker

If there are additional results, this is the marker for the next set of results. Otherwise, this is null.

Type: String

TrustStoreAssociations.member.N

Information about the resources the trust store is associated to.

Type: Array of [TrustStoreAssociation](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

Examples

Describe all resources associated with a trust store.

This example describes all resources associated to the specified trust store.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeTrustStoreAssociations
&TrustStoreArn=arn:aws:elasticloadbalancing:us-east-1:111122223333:truststore/my-trust-
store/3ym756xh7yj
&Version=2015-12-01
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeTrustStoreRevocations

Describes the revocation files in use by the specified trust store or revocation files.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

Marker

The marker for the next set of results. (You received this marker from a previous call.)

Type: String

Required: No

PageSize

The maximum number of results to return with this call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 400.

Required: No

RevocationIds.member.N

The revocation IDs of the revocation files you want to describe.

Type: Array of longs

Required: No

TrustStoreArn

The Amazon Resource Name (ARN) of the trust store.

Type: String

Required: Yes

Response Elements

The following elements are returned by the service.

NextMarker

If there are additional results, this is the marker for the next set of results. Otherwise, this is null.

Type: String

TrustStoreRevocations.member.N

Information about the revocation file in the trust store.

Type: Array of [DescribeTrustStoreRevocation](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

RevocationIdNotFound

The specified revocation ID does not exist.

HTTP Status Code: 400

TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

Examples

Describe revocation file contents from a trust store.

This example describes the specified certificate revocation IDs list contents from the specified trust store.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeTrustStoreRevocations
&TrustStoreArn=arn:aws:elasticloadbalancing:us-east-1:111122223333:truststore/my-trust-
store/3ym756xh7yj
&RevocationIds.member.1.RevocationId=1
```

```
&Version=2015-12-01  
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeTrustStores

Describes all trust stores for the specified account.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

Marker

The marker for the next set of results. (You received this marker from a previous call.)

Type: String

Required: No

Names.member.N

The names of the trust stores.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: $^([a-zA-Z0-9]+-)*[a-zA-Z0-9]+\$$

Required: No

PageSize

The maximum number of results to return with this call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 400.

Required: No

TrustStoreArns.member.N

The Amazon Resource Name (ARN) of the trust store.

Type: Array of strings

Required: No

Response Elements

The following elements are returned by the service.

NextMarker

If there are additional results, this is the marker for the next set of results. Otherwise, this is null.

Type: String

TrustStores.member.N

Information about the trust stores.

Type: Array of [TrustStore](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

Examples

Describe a trust store.

This example describes the specified trust store.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeTrustStores
&TrustStoreArns.member.1.TrustStoreArn=arn:aws:elasticloadbalancing:us-
east-1:111122223333:truststore/my-trust-store/3ym756xh7yj
&Version=2015-12-01
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetResourcePolicy

Retrieves the resource policy for a specified resource.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

ResourceArn

The Amazon Resource Name (ARN) of the resource.

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

Policy

The content of the resource policy.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ResourceNotFound

The specified resource does not exist.

HTTP Status Code: 400

Examples

Retrieve a resource policy

This example retrieves the resource policy for the specified trust store.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=GetResourcePolicy
&ResourceArn=arn:aws:elasticloadbalancing:us-east-1:123456789012:truststore/my-trust-
store/73e2d6bc24d8a067
&Version=2015-12-01
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTrustStoreCaCertificatesBundle

Retrieves the ca certificate bundle.

This action returns a pre-signed S3 URI which is active for ten minutes.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

TrustStoreArn

The Amazon Resource Name (ARN) of the trust store.

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

Location

The ca certificate bundles Amazon S3 URI.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTrustStoreRevocationContent

Retrieves the specified revocation file.

This action returns a pre-signed S3 URI which is active for ten minutes.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

RevocationId

The revocation ID of the revocation file.

Type: Long

Required: Yes

TrustStoreArn

The Amazon Resource Name (ARN) of the trust store.

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

Location

The revocation files Amazon S3 URI.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

RevocationIdNotFound

The specified revocation ID does not exist.

HTTP Status Code: 400

TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

Examples

Retrieve a certificate revocation list.

This example retrieves the specified certificate revocation IDs list contents from the specified trust store and provides a pre-signed S3 URI.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=GetTrustStoreRevocationContent
&TrustStoreArn=arn:aws:elasticloadbalancing:us-east-1:111122223333:truststore/my-trust-
store/3ym756xh7yj
&RevocationId=1
&Version=2015-12-01
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

ModifyCapacityReservation

Modifies the capacity reservation of the specified load balancer.

When modifying capacity reservation, you must include at least one `MinimumLoadBalancerCapacity` or `ResetCapacityReservation`.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

LoadBalancerArn

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: Yes

MinimumLoadBalancerCapacity

The minimum load balancer capacity reserved.

Type: [MinimumLoadBalancerCapacity](#) object

Required: No

ResetCapacityReservation

Resets the capacity reservation.

Type: Boolean

Required: No

Response Elements

The following elements are returned by the service.

CapacityReservationState.member.N

The state of the capacity reservation.

Type: Array of [ZonalCapacityReservationState](#) objects

DecreaseRequestsRemaining

The amount of daily capacity decreases remaining.

Type: Integer

LastModifiedTime

The last time the capacity reservation was modified.

Type: Timestamp

MinimumLoadBalancerCapacity

The requested minimum capacity reservation for the load balancer

Type: [MinimumLoadBalancerCapacity](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CapacityDecreaseRequestLimitExceeded

You've exceeded the daily capacity decrease limit for this reservation.

HTTP Status Code: 400

CapacityReservationPending

There is a pending capacity reservation.

HTTP Status Code: 400

CapacityUnitsLimitExceeded

You've exceeded the capacity units limit.

HTTP Status Code: 400

InsufficientCapacity

There is insufficient capacity to reserve.

HTTP Status Code: 500

InvalidConfigurationRequest

The requested configuration is not valid.

HTTP Status Code: 400

LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

OperationNotPermitted

This operation is not allowed.

HTTP Status Code: 400

PriorRequestNotComplete

This operation is not allowed while a prior request has not been completed.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ModifyIpPools

[Application Load Balancers] Modify the IP pool associated to a load balancer.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

IpamPools

The IPAM pools to be modified.

Type: [IpamPools](#) object

Required: No

LoadBalancerArn

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: Yes

RemoveIpamPools.member.N

Remove the IP pools in use by the load balancer.

Type: Array of strings

Valid Values: ipv4

Required: No

Response Elements

The following element is returned by the service.

IpamPools

The IPAM pool ID.

Type: [IpamPools](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ModifyListener

Replaces the specified properties of the specified listener. Any properties that you do not specify remain unchanged.

Changing the protocol from HTTPS to HTTP, or from TLS to TCP, removes the security policy and default certificate properties. If you change the protocol from HTTP to HTTPS, or from TCP to TLS, you must add the security policy and default certificate properties.

To add an item to a list, remove an item from a list, or update an item in a list, you must provide the entire list. For example, to add an action, specify a list with the current actions plus the new action.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

AlpnPolicy.member.N

[TLS listeners] The name of the Application-Layer Protocol Negotiation (ALPN) policy. You can specify one policy name. The following are the possible values:

- HTTP10nly
- HTTP20nly
- HTTP2Optional
- HTTP2Preferred
- None

For more information, see [ALPN policies](#) in the *Network Load Balancers Guide*.

Type: Array of strings

Required: No

Certificates.member.N

[HTTPS and TLS listeners] The default certificate for the listener. You must provide exactly one certificate. Set `CertificateArn` to the certificate ARN but do not set `IsDefault`.

To create a certificate list, use [AddListenerCertificates](#).

Type: Array of [Certificate](#) objects

Required: No

DefaultActions.member.N

The actions for the default rule.

Type: Array of [Action](#) objects

Required: No

ListenerArn

The Amazon Resource Name (ARN) of the listener.

Type: String

Required: Yes

MutualAuthentication

[HTTPS listeners] The mutual authentication configuration information.

Type: [MutualAuthenticationAttributes](#) object

Required: No

Port

The port for connections from clients to the load balancer. You can't specify a port for a Gateway Load Balancer.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

Protocol

The protocol for connections from clients to the load balancer. Application Load Balancers support the HTTP and HTTPS protocols. Network Load Balancers support the TCP, TLS, UDP, TCP_UDP, QUIC, and TCP_QUIC protocols. You can't change the protocol to UDP, TCP_UDP, QUIC, or TCP_QUIC if dual-stack mode is enabled. You can't specify a protocol for a Gateway Load Balancer.

Type: String

Valid Values: HTTP | HTTPS | TCP | TLS | UDP | TCP_UDP | GENEVE | QUIC | TCP_QUIC

Required: No

SslPolicy

[HTTPS and TLS listeners] The security policy that defines which protocols and ciphers are supported.

For more information, see [Security policies](#) in the *Application Load Balancers Guide* or [Security policies](#) in the *Network Load Balancers Guide*.

Type: String

Required: No

Response Elements

The following element is returned by the service.

Listeners.member.N

Information about the modified listener.

Type: Array of [Listener](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ALPNPolicyNotFound

The specified ALPN policy is not supported.

HTTP Status Code: 400

CertificateNotFound

The specified certificate does not exist.

HTTP Status Code: 400

DuplicateListener

A listener with the specified port already exists.

HTTP Status Code: 400

IncompatibleProtocols

The specified configuration is not valid with this protocol.

HTTP Status Code: 400

InvalidConfigurationRequest

The requested configuration is not valid.

HTTP Status Code: 400

InvalidLoadBalancerAction

The requested action is not valid.

HTTP Status Code: 400

ListenerNotFound

The specified listener does not exist.

HTTP Status Code: 400

SSLPolicyNotFound

The specified SSL policy does not exist.

HTTP Status Code: 400

TargetGroupAssociationLimit

You've reached the limit on the number of load balancers per target group.

HTTP Status Code: 400

TargetGroupNotFound

The specified target group does not exist.

HTTP Status Code: 400

TooManyActions

You've reached the limit on the number of actions per rule.

HTTP Status Code: 400

TooManyCertificates

You've reached the limit on the number of certificates per load balancer.

HTTP Status Code: 400

TooManyListeners

You've reached the limit on the number of listeners per load balancer.

HTTP Status Code: 400

TooManyRegistrationsForTargetId

You've reached the limit on the number of times a target can be registered with a load balancer.

HTTP Status Code: 400

TooManyTargets

You've reached the limit on the number of targets.

HTTP Status Code: 400

TooManyUniqueTargetGroupsPerLoadBalancer

You've reached the limit on the number of unique target groups per load balancer across all listeners. If a target group is used by multiple actions for a load balancer, it is counted as only one use.

HTTP Status Code: 400

TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

TrustStoreNotReady

The specified trust store is not active.

HTTP Status Code: 400

UnsupportedProtocol

The specified protocol is not supported.

HTTP Status Code: 400

Examples

Change the default action

This example changes the default action for the specified listener.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=ModifyListener
&ListenerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/my-load-
balancer/50dc6c495c0c9188/f2f7dc8efc522ab2
&DefaultActions.member.1.Type=forward
&DefaultActions.member.1.TargetGroupArn=arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-new-targets/2453ed029918f21f
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<ModifyListenerResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <ModifyListenerResult>
    <Listeners>
      <member>
        <LoadBalancerArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188</
LoadBalancerArn>
        <Protocol>HTTP</Protocol>
        <Port>80</Port>
        <ListenerArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/
my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2</ListenerArn>
        <DefaultActions>
          <member>
            <Type>forward</Type>
```

```

        <TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-new-targets/2453ed029918f21f</TargetGroupArn>
    </member>
</DefaultActions>
</member>
</Listeners>
</ModifyListenerResult>
<ResponseMetadata>
    <RequestId>9759b8df-f462-11e5-8a24-ffe2bf8623ae</RequestId>
</ResponseMetadata>
</ModifyListenerResponse>

```

Change the default certificate

This example changes the default certificate for the specified HTTPS listener.

Sample Request

```

https://elasticloadbalancing.amazonaws.com/?Action=ModifyListener
&ListenerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/my-load-
balancer/50dc6c495c0c9188/0467ef3c8400ae65
&Certificates.member.1.CertificateArn=arn:aws:iam::123456789012:server-certificate/my-
new-server-cert
&Version=2015-12-01
&AUTHPARAMS

```

Sample Response

```

<ModifyListenerResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
    <ModifyListenerResult>
        <Listeners>
            <member>
                <LoadBalancerArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188</
LoadBalancerArn>
                <Protocol>HTTPS</Protocol>
                <Certificates>
                    <member>
                        <CertificateArn>arn:aws:iam::123456789012:server-certificate/my-new-server-
cert</CertificateArn>
                    </member>
                </Certificates>
            </member>
        </Listeners>
    </ModifyListenerResult>
</ModifyListenerResponse>

```

```

    <Port>443</Port>
    <SslPolicy>ELBSecurityPolicy-2016-08</SslPolicy>
    <ListenerArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/my-load-balancer/50dc6c495c0c9188/0467ef3c8400ae65</ListenerArn>
    <DefaultActions>
      <member>
        <Type>forward</Type>
        <TargetGroupArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
      </member>
    </DefaultActions>
  </member>
</Listeners>
</ModifyListenerResult>
<ResponseMetadata>
  <RequestId>3f72dcb2-f463-11e5-b95d-3b2c1831fc26</RequestId>
</ResponseMetadata> </ModifyListenerResponse>

```

Change the security policy

This example changes the security policy for the specified HTTPS listener.

Sample Request

```

https://elasticloadbalancing.amazonaws.com/?Action=ModifyListener
&ListenerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/my-load-balancer/50dc6c495c0c9188/0467ef3c8400ae65
&SslPolicy=ELBSecurityPolicy-2016-08
&Version=2015-12-01
&AUTHPARAMS

```

Sample Response

```

<ModifyListenerResponse xmlns="http://elasticloadbalancing.amazonaws.com/doc/2015-12-01/">
  <ModifyListenerResult>
    <Listeners>
      <member>
        <LoadBalancerArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188</LoadBalancerArn>
        <Protocol>HTTPS</Protocol>
        <Certificates>

```

```
<member>
  <CertificateArn>arn:aws:iam::123456789012:server-certificate/my-server-
cert</CertificateArn>
</member>
</Certificates>
<Port>443</Port>
<SslPolicy>ELBSecurityPolicy-2016-08</SslPolicy>
<ListenerArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/
my-load-balancer/50dc6c495c0c9188/0467ef3c8400ae65</ListenerArn>
<DefaultActions>
  <member>
    <Type>forward</Type>
    <TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
  </member>
</DefaultActions>
</member>
</Listeners>
</ModifyListenerResult>
<ResponseMetadata>
  <RequestId>3f72dcb2-f463-11e5-b95d-3b2c1831fc26</RequestId>
</ResponseMetadata>
</ModifyListenerResponse>
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ModifyListenerAttributes

Modifies the specified attributes of the specified listener.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

Attributes.member.N

The listener attributes.

Type: Array of [ListenerAttribute](#) objects

Required: Yes

ListenerArn

The Amazon Resource Name (ARN) of the listener.

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

Attributes.member.N

Information about the listener attributes.

Type: Array of [ListenerAttribute](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidConfigurationRequest

The requested configuration is not valid.

HTTP Status Code: 400

ListenerNotFound

The specified listener does not exist.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ModifyLoadBalancerAttributes

Modifies the specified attributes of the specified Application Load Balancer, Network Load Balancer, or Gateway Load Balancer.

If any of the specified attributes can't be modified as requested, the call fails. Any existing attributes that you do not modify retain their current values.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

Attributes.member.N

The load balancer attributes.

Type: Array of [LoadBalancerAttribute](#) objects

Array Members: Maximum number of 20 items.

Required: Yes

LoadBalancerArn

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

Attributes.member.N

Information about the load balancer attributes.

Type: Array of [LoadBalancerAttribute](#) objects

Array Members: Maximum number of 20 items.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidConfigurationRequest

The requested configuration is not valid.

HTTP Status Code: 400

LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

Examples

Enable deletion protection

This example enables deletion protection for the specified load balancer.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=ModifyLoadBalancerAttributes
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/
my-load-balancer/50dc6c495c0c9188
&Attributes.member.1.Key=deletion_protection.enabled
&Attributes.member.1.Value=true
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<ModifyLoadBalancerAttributesResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <ModifyLoadBalancerAttributesResult>
    <Attributes>
      <member>
        <Value>true</Value>
        <Key>deletion_protection.enabled</Key>
      </member>
      <member>
```

```

    <Value>>false</Value>
    <Key>access_logs.s3.enabled</Key>
  </member>
  <member>
    <Value>60</Value>
    <Key>idle_timeout.timeout_seconds</Key>
  </member>
  <member>
    <Value />
    <Key>access_logs.s3.prefix</Key>
  </member>
  <member>
    <Value />
    <Key>access_logs.s3.bucket</Key>
  </member>
</Attributes>
</ModifyLoadBalancerAttributesResult>
<ResponseMetadata>
  <RequestId>b2066529-f42c-11e5-b543-9f2c3fbb9bee</RequestId>
</ResponseMetadata>
</ModifyLoadBalancerAttributesResponse>

```

Change the idle timeout

This example changes the idle timeout value for the specified Application Load Balancer.

Sample Request

```

https://elasticloadbalancing.amazonaws.com/?Action=ModifyLoadBalancerAttributes
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/
my-load-balancer/50dc6c495c0c9188
&Attributes.member.1.Key=idle_timeout.timeout_seconds
&Attributes.member.1.Value=30
&Version=2015-12-01
&AUTHPARAMS

```

Sample Response

```

<ModifyLoadBalancerAttributesResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <ModifyLoadBalancerAttributesResult>
    <Attributes>
      <member>

```

```
<Value>30</Value>
  <Key>idle_timeout.timeout_seconds</Key>
</member>
<member>
  <Value>>false</Value>
  <Key>access_logs.s3.enabled</Key>
</member>
<member>
  <Value />
  <Key>access_logs.s3.prefix</Key>
</member>
<member>
  <Value>>false</Value>
  <Key>deletion_protection.enabled</Key>
</member>
<member>
  <Value />
  <Key>access_logs.s3.bucket</Key>
</member>
</Attributes>
</ModifyLoadBalancerAttributesResult>
<ResponseMetadata>
  <RequestId>d3f6e6dc-f42c-11e5-b5ae-8bfaf16614ac</RequestId>
</ResponseMetadata>
</ModifyLoadBalancerAttributesResponse>
```

Enable access logs

This example enables access logs for the specified Application Load Balancer. The S3 bucket must exist in the same Region as the load balancer and must have a bucket policy that grants Elastic Load Balancing permissions to write to the bucket.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=ModifyLoadBalancerAttributes
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/
my-load-balancer/50dc6c495c0c9188
&Attributes.member.1.Key=access_logs.s3.enabled
&Attributes.member.1.Value=true
&Attributes.member.2.Key=access_logs.s3.bucket
&Attributes.member.2.Value=my-loadbalancer-logs
&Attributes.member.3.Key=access_logs.s3.prefix
&Attributes.member.3.Value=myapp
```

```
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<ModifyLoadBalancerAttributesResponse xmlns="http://elasticloadbalancing.amazonaws.com/doc/2015-12-01/">
  <ModifyLoadBalancerAttributesResult>
    <Attributes>
      <member>
        <Value>>true</Value>
        <Key>access_logs.s3.enabled</Key>
      </member>
      <member>
        <Value>my-loadbalancer-logs</Value>
        <Key>access_logs.s3.bucket</Key>
      </member>
      <member>
        <Value>myapp</Value>
        <Key>access_logs.s3.prefix</Key>
      </member>
      <member>
        <Value>60</Value>
        <Key>idle_timeout.timeout_seconds</Key>
      </member>
      <member>
        <Value>>false</Value>
        <Key>deletion_protection.enabled</Key>
      </member>
    </Attributes>
  </ModifyLoadBalancerAttributesResult>
  <ResponseMetadata>
    <RequestId>095cb76d-f52e-11e5-bb98-57195a6eb84a</RequestId>
  </ResponseMetadata>
</ModifyLoadBalancerAttributesResponse>
```

Enable connection logs.

This example enables connection logs, setting the specified S3 bucket and prefix location.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=ModifyLoadBalancerAttributes
```

```
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188
&Attributes.member.1.Key=connection_logs.s3.enabled
&Attributes.member.1.Value=true
&Attributes.member.2.Key=connection_logs.s3.bucket
&Attributes.member.2.Value=my-loadbalancer-connection-logs
&Attributes.member.3.Key=connection_logs.s3.prefix
&Attributes.member.3.Value=myapp-connections
&Version=2015-12-01
&AUTHPARAMS
```

Enable health check logs.

This example enables health check logs, setting the specified S3 bucket and prefix location.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=ModifyLoadBalancerAttributes
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188
&Attributes.member.1.Key=health_check_logs.s3.enabled
&Attributes.member.1.Value=true
&Attributes.member.2.Key=health_check_logs.s3.bucket
&Attributes.member.2.Value=my-loadbalancer-connection-logs
&Attributes.member.3.Key=health_check_logs.s3.prefix
&Attributes.member.3.Value=mylb-health
&Version=2015-12-01
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ModifyRule

Replaces the specified properties of the specified rule. Any properties that you do not specify are unchanged.

To add an item to a list, remove an item from a list, or update an item in a list, you must provide the entire list. For example, to add an action, specify a list with the current actions plus the new action.

To modify the actions for the default rule, use [ModifyListener](#).

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

Actions.member.N

The actions.

Type: Array of [Action](#) objects

Required: No

Conditions.member.N

The conditions.

Type: Array of [RuleCondition](#) objects

Required: No

ResetTransforms

Indicates whether to remove all transforms from the rule. If you specify `ResetTransforms`, you can't specify `Transforms`.

Type: Boolean

Required: No

RuleArn

The Amazon Resource Name (ARN) of the rule.

Type: String

Required: Yes

Transforms.member.N

The transforms to apply to requests that match this rule. You can add one host header rewrite transform and one URL rewrite transform. If you specify `Transforms`, you can't specify `ResetTransforms`.

Type: Array of [RuleTransform](#) objects

Required: No

Response Elements

The following element is returned by the service.

Rules.member.N

Information about the modified rule.

Type: Array of [Rule](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

IncompatibleProtocols

The specified configuration is not valid with this protocol.

HTTP Status Code: 400

InvalidLoadBalancerAction

The requested action is not valid.

HTTP Status Code: 400

OperationNotPermitted

This operation is not allowed.

HTTP Status Code: 400

RuleNotFound

The specified rule does not exist.

HTTP Status Code: 400

TargetGroupAssociationLimit

You've reached the limit on the number of load balancers per target group.

HTTP Status Code: 400

TargetGroupNotFound

The specified target group does not exist.

HTTP Status Code: 400

TooManyActions

You've reached the limit on the number of actions per rule.

HTTP Status Code: 400

TooManyRegistrationsForTargetId

You've reached the limit on the number of times a target can be registered with a load balancer.

HTTP Status Code: 400

TooManyTargets

You've reached the limit on the number of targets.

HTTP Status Code: 400

TooManyUniqueTargetGroupsPerLoadBalancer

You've reached the limit on the number of unique target groups per load balancer across all listeners. If a target group is used by multiple actions for a load balancer, it is counted as only one use.

HTTP Status Code: 400

UnsupportedProtocol

The specified protocol is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ModifyTargetGroup

Modifies the health checks used when evaluating the health state of the targets in the specified target group.

To monitor the health of the targets, use [DescribeTargetHealth](#).

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

HealthCheckEnabled

Indicates whether health checks are enabled. If the target type is `lambda`, health checks are disabled by default but can be enabled. If the target type is `instance`, `ip`, or `alb`, health checks are always enabled and can't be disabled.

Type: Boolean

Required: No

HealthCheckIntervalSeconds

The approximate amount of time, in seconds, between health checks of an individual target.

Type: Integer

Valid Range: Minimum value of 5. Maximum value of 300.

Required: No

HealthCheckPath

[HTTP/HTTPS health checks] The destination for health checks on the targets.

[HTTP1 or HTTP2 protocol version] The ping path. The default is `/`.

[GRPC protocol version] The path of a custom health check method with the format `/package.service/method`. The default is `/AWS.ALB/healthcheck`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

HealthCheckPort

The port the load balancer uses when performing health checks on targets.

Type: String

Required: No

HealthCheckProtocol

The protocol the load balancer uses when performing health checks on targets. For Application Load Balancers, the default is HTTP. For Network Load Balancers and Gateway Load Balancers, the default is TCP. The TCP protocol is not supported for health checks if the protocol of the target group is HTTP or HTTPS. It is supported for health checks only if the protocol of the target group is TCP, TLS, UDP, or TCP_UDP. The GENEVE, TLS, UDP, TCP_UDP, QUIC, and TCP_QUIC protocols are not supported for health checks.

Type: String

Valid Values: HTTP | HTTPS | TCP | TLS | UDP | TCP_UDP | GENEVE | QUIC | TCP_QUIC

Required: No

HealthCheckTimeoutSeconds

[HTTP/HTTPS health checks] The amount of time, in seconds, during which no response means a failed health check.

Type: Integer

Valid Range: Minimum value of 2. Maximum value of 120.

Required: No

HealthyThresholdCount

The number of consecutive health checks successes required before considering an unhealthy target healthy.

Type: Integer

Valid Range: Minimum value of 2. Maximum value of 10.

Required: No

Matcher

[HTTP/HTTPS health checks] The HTTP or gRPC codes to use when checking for a successful response from a target. For target groups with a protocol of TCP, TCP_UDP, UDP or TLS the range is 200-599. For target groups with a protocol of HTTP or HTTPS, the range is 200-499. For target groups with a protocol of GENEVE, the range is 200-399.

Type: [Matcher](#) object

Required: No

TargetGroupArn

The Amazon Resource Name (ARN) of the target group.

Type: String

Required: Yes

UnhealthyThresholdCount

The number of consecutive health check failures required before considering the target unhealthy.

Type: Integer

Valid Range: Minimum value of 2. Maximum value of 10.

Required: No

Response Elements

The following element is returned by the service.

TargetGroups.member.N

Information about the modified target group.

Type: Array of [TargetGroup](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidConfigurationRequest

The requested configuration is not valid.

HTTP Status Code: 400

TargetGroupNotFound

The specified target group does not exist.

HTTP Status Code: 400

Examples

Modify the health check configuration for a target group

This example changes the configuration of the health checks used to evaluate the health of the targets for the specified target group.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=ModifyTargetGroup
&TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-
https-targets/2453ed029918f21f
&HealthCheckProtocol=HTTPS
&HealthCheckPort=443
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<ModifyTargetGroupResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <ModifyTargetGroupResult>
    <TargetGroups>
      <member>
        <TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-https-targets/2453ed029918f21f</TargetGroupArn>
        <HealthCheckTimeoutSeconds>5</HealthCheckTimeoutSeconds>
        <HealthCheckPort>443</HealthCheckPort>
        <Matcher>
          <HttpCode>200</HttpCode>
```

```
</Matcher>
<TargetGroupName>my-https-targets</TargetGroupName>
<HealthCheckProtocol>HTTPS</HealthCheckProtocol>
<Protocol>HTTPS</Protocol>
<Port>443</Port>
<HealthyThresholdCount>5</HealthyThresholdCount>
<VpcId>vpc-3ac0fb5f</VpcId>
<HealthCheckIntervalSeconds>30</HealthCheckIntervalSeconds>
<LoadBalancerArns>
  <member>arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/
my-load-balancer/50dc6c495c0c9188</member>
</LoadBalancerArns>
<UnhealthyThresholdCount>2</UnhealthyThresholdCount>
</member>
</TargetGroups>
</ModifyTargetGroupResult>
<ResponseMetadata>
  <RequestId>8525b334-f466-11e5-aa04-33bf366f62e2</RequestId>
</ResponseMetadata>
</ModifyTargetGroupResponse>
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ModifyTargetGroupAttributes

Modifies the specified attributes of the specified target group.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

Attributes.member.N

The target group attributes.

Type: Array of [TargetGroupAttribute](#) objects

Required: Yes

TargetGroupArn

The Amazon Resource Name (ARN) of the target group.

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

Attributes.member.N

Information about the target group attributes.

Type: Array of [TargetGroupAttribute](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidConfigurationRequest

The requested configuration is not valid.

HTTP Status Code: 400

TargetGroupNotFound

The specified target group does not exist.

HTTP Status Code: 400

Examples

Modify the deregistration delay timeout

This example sets the deregistration delay timeout for the specified target group to the specified value.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=ModifyTargetGroupAttributes
&TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-
targets/73e2d6bc24d8a067
&Attributes.member.1.Key=deregistration_delay.timeout_seconds
&Attributes.member.1.Value=600
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<ModifyTargetGroupAttributesResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <ModifyTargetGroupAttributesResult>
    <Attributes>
      <member>
        <Value>600</Value>
        <Key>deregistration_delay.timeout_seconds</Key>
      </member>
    </Attributes>
  </ModifyTargetGroupAttributesResult>
  <ResponseMetadata>
    <RequestId>bb8c272b-f455-11e5-a53c-67205c0d10fd</RequestId>
  </ResponseMetadata>
</ModifyTargetGroupAttributesResponse>
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ModifyTrustStore

Update the ca certificate bundle for the specified trust store.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

CaCertificatesBundleS3Bucket

The Amazon S3 bucket for the ca certificates bundle.

Type: String

Required: Yes

CaCertificatesBundleS3Key

The Amazon S3 path for the ca certificates bundle.

Type: String

Required: Yes

CaCertificatesBundleS3ObjectVersion

The Amazon S3 object version for the ca certificates bundle. If undefined the current version is used.

Type: String

Required: No

TrustStoreArn

The Amazon Resource Name (ARN) of the trust store.

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

TrustStores.member.N

Information about the modified trust store.

Type: Array of [TrustStore](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CaCertificatesBundleNotFound

The specified ca certificate bundle does not exist.

HTTP Status Code: 400

InvalidCaCertificatesBundle

The specified ca certificate bundle is in an invalid format, or corrupt.

HTTP Status Code: 400

TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

Examples

Modify a trust store.

This example replaces the ca certificate bundle in the specified trust store.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=ModifyTrustStore
&TrustStoreArn=arn:aws:elasticloadbalancing:us-east-1:111122223333:truststore/my-trust-
store/d5f637c79df8c943
&CaCertificatesBundleS3Bucket=amzn-s3-demo-bucket
&CaCertificatesBundleS3Key=CACertBundle.pem
&Version=2015-12-01
```

&AUTHPARAMS

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RegisterTargets

Registers the specified targets with the specified target group.

If the target is an EC2 instance, it must be in the `running` state when you register it.

By default, the load balancer routes requests to registered targets using the protocol and port for the target group. Alternatively, you can override the port for a target when you register it. You can register each EC2 instance or IP address with the same target group multiple times using different ports.

For more information, see the following:

- [Register targets for your Application Load Balancer](#)
- [Register targets for your Network Load Balancer](#)
- [Register targets for your Gateway Load Balancer](#)

To remove a target from a target group, use [DeregisterTargets](#).

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

TargetGroupArn

The Amazon Resource Name (ARN) of the target group.

Type: String

Required: Yes

Targets.member.N

The targets.

Type: Array of [TargetDescription](#) objects

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidTarget

The specified target does not exist, is not in the same VPC as the target group, or has an unsupported instance type.

HTTP Status Code: 400

TargetGroupNotFound

The specified target group does not exist.

HTTP Status Code: 400

TooManyRegistrationsForTargetId

You've reached the limit on the number of times a target can be registered with a load balancer.

HTTP Status Code: 400

TooManyTargets

You've reached the limit on the number of targets.

HTTP Status Code: 400

Examples

Register targets by instance ID

This example registers the specified instance IDs with the specified target group.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=RegisterTargets
&TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-
targets/73e2d6bc24d8a067
&Targets.member.1.Id=i-80c8dd94
&Targets.member.2.Id=i-ceddc4d
&Version=2015-12-01
&AUTHPARAMS
```

Register targets by IP address

This example registers the specified IP addresses with the specified target group.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=RegisterTargets
&TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-
targets/73e2d6bc24d8a067
&Targets.member.1.Id=10.0.42.17
&Targets.member.2.Id=192.168.0.3
&Targets.member.2.AvailabilityZone=all
&Version=2015-12-01
&AUTHPARAMS
```

Register targets by instance ID using port overrides

This example registers the specified instance with the specified target group using multiple ports. This enables you to register microservices on the same instance as targets in the target group.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=RegisterTargets
&TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-
targets/73e2d6bc24d8a067
&Targets.member.1.Id=i-80c8dd94
&Targets.member.1.Port=80
&Targets.member.2.Id=i-80c8dd94
&Targets.member.2.Port=766
&Version=2015-12-01
&AUTHPARAMS
```

Register a Lambda function as a target

This example registers the specified Lambda function with the specified target group. You must grant Elastic Load Balancing permission to invoke the Lambda function. For more information, see [Lambda functions as targets](#) in the *Application Load Balancers Guide*.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=RegisterTargets
&TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-
targets/73e2d6bc24d8a067
&Targets.member.1.Id=aws:lambda:us-west-2:123456789012:function:my-function
&Version=2015-12-01
```

&AUTHPARAMS

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RemoveListenerCertificates

Removes the specified certificate from the certificate list for the specified HTTPS or TLS listener.

You can't remove the default certificate for a listener. To replace the default certificate, call [ModifyListener](#).

To list the certificates for your listener, use [DescribeListenerCertificates](#).

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

Certificates.member.N

The certificate to remove. You can specify one certificate per call. Set `CertificateArn` to the certificate ARN but do not set `IsDefault`.

Type: Array of [Certificate](#) objects

Required: Yes

ListenerArn

The Amazon Resource Name (ARN) of the listener.

Type: String

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ListenerNotFound

The specified listener does not exist.

HTTP Status Code: 400

OperationNotPermitted

This operation is not allowed.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RemoveTags

Removes the specified tags from the specified Elastic Load Balancing resources. You can remove the tags for one or more Application Load Balancers, Network Load Balancers, Gateway Load Balancers, target groups, listeners, or rules.

To list the current tags for your resources, use [DescribeTags](#).

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

ResourceArns.member.N

The Amazon Resource Name (ARN) of the resource.

Type: Array of strings

Required: Yes

TagKeys.member.N

The tag keys for the tags to remove.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^([\p{L}\p{Z}\p{N}_ . : / = + \ - @] *)$`

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ListenerNotFound

The specified listener does not exist.

HTTP Status Code: 400

LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

RuleNotFound

The specified rule does not exist.

HTTP Status Code: 400

TargetGroupNotFound

The specified target group does not exist.

HTTP Status Code: 400

TooManyTags

You've reached the limit on the number of tags for this resource.

HTTP Status Code: 400

TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

Examples

Remove tags from a load balancer

This example removes the specified tags from the specified load balancer.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=RemoveTags
&ResourceArns.member.1=arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188
&TagKeys.member.1=project
&TagKeys.member.2=department
&Version=2015-12-01
```

&AUTHPARAMS

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RemoveTrustStoreRevocations

Removes the specified revocation file from the specified trust store.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

RevocationIds.member.N

The revocation IDs of the revocation files you want to remove.

Type: Array of longs

Required: Yes

TrustStoreArn

The Amazon Resource Name (ARN) of the trust store.

Type: String

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

RevocationIdNotFound

The specified revocation ID does not exist.

HTTP Status Code: 400

TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

Examples

Remove a revocation file from a trust store.

This example removes the specified certificate revocation ID from the specified trust store.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=RemoveTrustStoreRevocations
&TrustStoreArn=arn:aws:elasticloadbalancing:us-east-1:111122223333:truststore/my-trust-
store/3ym756xh7yj
&RevocationIds.member.1.RevocationID=1
&Version=2015-12-01
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

SetIpAddressType

Sets the type of IP addresses used by the subnets of the specified load balancer.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

IpAddressType

The IP address type. Internal load balancers must use `ipv4`.

[Application Load Balancers] The possible values are `ipv4` (IPv4 addresses), `dualstack` (IPv4 and IPv6 addresses), and `dualstack-without-public-ipv4` (public IPv6 addresses and private IPv4 and IPv6 addresses).

Application Load Balancer authentication supports IPv4 addresses only when connecting to an Identity Provider (IdP) or Amazon Cognito endpoint. Without a public IPv4 address the load balancer can't complete the authentication process, resulting in HTTP 500 errors.

[Network Load Balancers and Gateway Load Balancers] The possible values are `ipv4` (IPv4 addresses) and `dualstack` (IPv4 and IPv6 addresses).

Type: String

Valid Values: `ipv4` | `dualstack` | `dualstack-without-public-ipv4`

Required: Yes

LoadBalancerArn

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

IpAddressType

The IP address type.

Type: String

Valid Values: `ipv4` | `dualstack` | `dualstack-without-public-ipv4`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidConfigurationRequest

The requested configuration is not valid.

HTTP Status Code: 400

InvalidSubnet

The specified subnet is out of available addresses.

HTTP Status Code: 400

LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

Examples

Set the IP address type of a load balancer

This example sets the IP address type of the specified load balancer to `dualstack` to support IPv4 and IPv6 addresses. The load balancer subnets must have associated IPv6 CIDR blocks.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=SetIpAddressType
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/
my-load-balancer/50dc6c495c0c9188
```

```
&IpAddressType=dualstack
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<SetIpAddressTypeResponse xmlns="http://elasticloadbalancing.amazonaws.com/doc/2015-12-01/">
  <SetIpAddressTypeResult>
    <IpAddressType>dualstack</IpAddressType>
  </SetIpAddressTypeResult>
  <ResponseMetadata>
    <RequestId>a127426b-f3ab-11e5-9192-3fff33344cfa</RequestId>
  </ResponseMetadata>
</SetIpAddressTypeResponse>
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

SetRulePriorities

Sets the priorities of the specified rules.

You can reorder the rules as long as there are no priority conflicts in the new order. Any existing rules that you do not specify retain their current priority.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

RulePriorities.member.N

The rule priorities.

Type: Array of [RulePriorityPair](#) objects

Required: Yes

Response Elements

The following element is returned by the service.

Rules.member.N

Information about the rules.

Type: Array of [Rule](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

OperationNotPermitted

This operation is not allowed.

HTTP Status Code: 400

PriorityInUse

The specified priority is in use.

HTTP Status Code: 400

RuleNotFound

The specified rule does not exist.

HTTP Status Code: 400

Examples

Set the rule priority

This example sets the priority of the specified rule.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=SetRulePriorities
&RulePriorities.member.1.RuleArn=arn:aws:elasticloadbalancing:us-
west-2:123456789012:listener-rule/app/my-load-balancer/50dc6c495c0c9188/
f2f7dc8efc522ab2/1291d13826f405c3
&RulePriorities.member.1.Priority=5
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<SetRulePrioritiesResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <SetRulePrioritiesResult>
    <Rules>
      <member>
        <IsDefault>>false</IsDefault>
        <Conditions>
          <member>
            <Field>path-pattern</Field>
            <Values>
              <member>/img/*</member>
            </Values>
          </member>
        </Conditions>
        <Priority>5</Priority>
        <Actions>
```

```
<member>
  <Type>forward</Type>
  <TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
</member>
</Actions>
<RuleArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener-rule/app/
my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2/1291d13826f405c3</RuleArn>
</member>
</Rules>
</SetRulePrioritiesResult>
<ResponseMetadata>
  <RequestId>4d7a8036-f3a7-11e5-9c02-8fd20490d5a6</RequestId>
</ResponseMetadata>
</SetRulePrioritiesResponse>
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

SetSecurityGroups

Associates the specified security groups with the specified Application Load Balancer or Network Load Balancer. The specified security groups override the previously associated security groups.

You can't perform this operation on a Network Load Balancer unless you specified a security group for the load balancer when you created it.

You can't associate a security group with a Gateway Load Balancer.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

EnforceSecurityGroupInboundRulesOnPrivateLinkTraffic

Indicates whether to evaluate inbound security group rules for traffic sent to a Network Load Balancer through AWS PrivateLink. Applies only if the load balancer has an associated security group. The default is on.

Type: String

Valid Values: on | off

Required: No

LoadBalancerArn

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: Yes

SecurityGroups.member.N

The IDs of the security groups.

Type: Array of strings

Required: Yes

Response Elements

The following elements are returned by the service.

EnforceSecurityGroupInboundRulesOnPrivateLinkTraffic

Indicates whether to evaluate inbound security group rules for traffic sent to a Network Load Balancer through AWS PrivateLink.

Type: String

Valid Values: on | off

SecurityGroupIds.member.N

The IDs of the security groups associated with the load balancer.

Type: Array of strings

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidConfigurationRequest

The requested configuration is not valid.

HTTP Status Code: 400

InvalidSecurityGroup

The specified security group does not exist.

HTTP Status Code: 400

LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

Examples

Associate a security group with a load balancer

This example associates the specified security group with the specified load balancer.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=SetSecurityGroups
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/
my-load-balancer/50dc6c495c0c9188
&SecurityGroups.member.1=sg-5943793c
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<SetSecurityGroupsResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <SetSecurityGroupsResult>
    <SecurityGroupIds>
      <member>sg-5943793c</member>
    </SecurityGroupIds>
  </SetSecurityGroupsResult>
  <ResponseMetadata>
    <RequestId>a127426b-f3ab-11e5-9192-3fff33344cfa</RequestId>
  </ResponseMetadata>
</SetSecurityGroupsResponse>
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

SetSubnets

Enables the Availability Zones for the specified public subnets for the specified Application Load Balancer, Network Load Balancer or Gateway Load Balancer. The specified subnets replace the previously enabled subnets.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

EnablePrefixForIpv6SourceNat

[Network Load Balancers with UDP listeners] Indicates whether to use an IPv6 prefix from each subnet for source NAT. The IP address type must be `dualstack`. The default value is `off`.

Type: String

Valid Values: `on` | `off`

Required: No

IpAddressType

The IP address type.

[Application Load Balancers] The possible values are `ipv4` (IPv4 addresses), `dualstack` (IPv4 and IPv6 addresses), and `dualstack-without-public-ipv4` (public IPv6 addresses and private IPv4 and IPv6 addresses).

[Network Load Balancers and Gateway Load Balancers] The possible values are `ipv4` (IPv4 addresses) and `dualstack` (IPv4 and IPv6 addresses).

Type: String

Valid Values: `ipv4` | `dualstack` | `dualstack-without-public-ipv4`

Required: No

LoadBalancerArn

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: Yes

SubnetMappings.member.N

The IDs of the public subnets. You can specify only one subnet per Availability Zone. You must specify either subnets or subnet mappings.

[Application Load Balancers] You must specify subnets from at least two Availability Zones. You can't specify Elastic IP addresses for your subnets.

[Application Load Balancers on Outposts] You must specify one Outpost subnet.

[Application Load Balancers on Local Zones] You can specify subnets from one or more Local Zones.

[Network Load Balancers] You can specify subnets from one or more Availability Zones. You can specify one Elastic IP address per subnet if you need static IP addresses for your internet-facing load balancer. For internal load balancers, you can specify one private IP address per subnet from the IPv4 range of the subnet. For internet-facing load balancer, you can specify one IPv6 address per subnet.

[Gateway Load Balancers] You can specify subnets from one or more Availability Zones.

Type: Array of [SubnetMapping](#) objects

Required: No

Subnets.member.N

The IDs of the public subnets. You can specify only one subnet per Availability Zone. You must specify either subnets or subnet mappings.

[Application Load Balancers] You must specify subnets from at least two Availability Zones.

[Application Load Balancers on Outposts] You must specify one Outpost subnet.

[Application Load Balancers on Local Zones] You can specify subnets from one or more Local Zones.

[Network Load Balancers] You can specify subnets from one or more Availability Zones.

[Gateway Load Balancers] You can specify subnets from one or more Availability Zones. You must include all subnets that were enabled previously, with their existing configurations, plus any additional subnets.

Type: Array of strings

Required: No

Response Elements

The following elements are returned by the service.

AvailabilityZones.member.N

Information about the subnets.

Type: Array of [AvailabilityZone](#) objects

EnablePrefixForIpv6SourceNat

[Network Load Balancers] Indicates whether to use an IPv6 prefix from each subnet for source NAT.

Type: String

Valid Values: on | off

IpAddressType

The IP address type.

Type: String

Valid Values: ipv4 | dualstack | dualstack-without-public-ipv4

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AllocationIdNotFound

The specified allocation ID does not exist.

HTTP Status Code: 400

AvailabilityZoneNotSupported

The specified Availability Zone is not supported.

HTTP Status Code: 400

CapacityReservationPending

There is a pending capacity reservation.

HTTP Status Code: 400

InvalidConfigurationRequest

The requested configuration is not valid.

HTTP Status Code: 400

InvalidSubnet

The specified subnet is out of available addresses.

HTTP Status Code: 400

LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

SubnetNotFound

The specified subnet does not exist.

HTTP Status Code: 400

Examples

Enable Availability Zones for a load balancer

This example enables the Availability Zone for the specified subnet for the specified load balancer.

Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=SetSubnets
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/
my-load-balancer/50dc6c495c0c9188
&Subnets.member.1=subnet-8360a9e7
&Subnets.member.2=subnet-b7d581c0
```

```
&Version=2015-12-01
&AUTHPARAMS
```

Sample Response

```
<SetSubnetsResponse xmlns="http://elasticloadbalancing.amazonaws.com/doc/2015-12-01/">
  <SetSubnetsResult>
    <AvailabilityZones>
      <member>
        <SubnetId>subnet-8360a9e7</SubnetId>
        <ZoneName>us-west-2a</ZoneName>
      </member>
      <member>
        <SubnetId>subnet-b7d581c0</SubnetId>
        <ZoneName>us-west-2b</ZoneName>
      </member>
    </AvailabilityZones>
  </SetSubnetsResult>
  <ResponseMetadata>
    <RequestId>c1a80803-f3ab-11e5-b673-8d4a8a9e6f48</RequestId>
  </ResponseMetadata>
</SetSubnetsResponse>
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The Elastic Load Balancing API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [Action](#)
- [AdministrativeOverride](#)
- [AnomalyDetection](#)
- [AuthenticateCognitoActionConfig](#)
- [AuthenticateOidcActionConfig](#)
- [AvailabilityZone](#)
- [CapacityReservationStatus](#)
- [Certificate](#)
- [Cipher](#)
- [DescribeTrustStoreRevocation](#)
- [FixedResponseActionConfig](#)
- [ForwardActionConfig](#)
- [HostHeaderConditionConfig](#)
- [HostHeaderRewriteConfig](#)
- [HTTPHeaderConditionConfig](#)
- [HttpRequestMethodConditionConfig](#)
- [IpamPools](#)
- [JwtValidationActionAdditionalClaim](#)
- [JwtValidationActionConfig](#)
- [Limit](#)

- [Listener](#)
- [ListenerAttribute](#)
- [LoadBalancer](#)
- [LoadBalancerAddress](#)
- [LoadBalancerAttribute](#)
- [LoadBalancerState](#)
- [Matcher](#)
- [MinimumLoadBalancerCapacity](#)
- [MutualAuthenticationAttributes](#)
- [PathPatternConditionConfig](#)
- [QueryStringConditionConfig](#)
- [QueryStringKeyValuePair](#)
- [RedirectActionConfig](#)
- [RevocationContent](#)
- [RewriteConfig](#)
- [Rule](#)
- [RuleCondition](#)
- [RulePriorityPair](#)
- [RuleTransform](#)
- [SourceIpConditionConfig](#)
- [SslPolicy](#)
- [SubnetMapping](#)
- [Tag](#)
- [TagDescription](#)
- [TargetDescription](#)
- [TargetGroup](#)
- [TargetGroupAttribute](#)
- [TargetGroupStickinessConfig](#)
- [TargetGroupTuple](#)
- [TargetHealth](#)

- [TargetHealthDescription](#)
- [TrustStore](#)
- [TrustStoreAssociation](#)
- [TrustStoreRevocation](#)
- [UrlRewriteConfig](#)
- [ZonalCapacityReservationState](#)

Action

Information about an action.

Each rule must include exactly one of the following routing actions: `forward`, `fixed-response`, or `redirect`, and it must be the last action to be performed.

Optionally, a rule for an HTTPS listener can also include one of the following user authentication actions: `authenticate-oidc`, `authenticate-cognito`, or `jwt-validation`.

Contents

Type

The type of action.

Type: String

Valid Values: `forward` | `authenticate-oidc` | `authenticate-cognito` | `redirect` | `fixed-response` | `jwt-validation`

Required: Yes

AuthenticateCognitoConfig

[HTTPS listeners] Information for using Amazon Cognito to authenticate users. Specify only when Type is `authenticate-cognito`.

Type: [AuthenticateCognitoActionConfig](#) object

Required: No

AuthenticateOidcConfig

[HTTPS listeners] Information about an identity provider that is compliant with OpenID Connect (OIDC). Specify only when Type is `authenticate-oidc`.

Type: [AuthenticateOidcActionConfig](#) object

Required: No

FixedResponseConfig

[Application Load Balancer] Information for creating an action that returns a custom HTTP response. Specify only when Type is `fixed-response`.

Type: [FixedResponseActionConfig](#) object

Required: No

ForwardConfig

Information for creating an action that distributes requests among multiple target groups. Specify only when Type is forward.

If you specify both ForwardConfig and TargetGroupArn, you can specify only one target group using ForwardConfig and it must be the same target group specified in TargetGroupArn.

Type: [ForwardActionConfig](#) object

Required: No

JwtValidationConfig

[HTTPS listeners] Information for validating JWT access tokens in client requests. Specify only when Type is jwt-validation.

Type: [JwtValidationActionConfig](#) object

Required: No

Order

The order for the action. This value is required for rules with multiple actions. The action with the lowest value for order is performed first.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50000.

Required: No

RedirectConfig

[Application Load Balancer] Information for creating a redirect action. Specify only when Type is redirect.

Type: [RedirectActionConfig](#) object

Required: No

TargetGroupArn

The Amazon Resource Name (ARN) of the target group. Specify only when Type is forward and you want to route to a single target group. To route to multiple target groups, you must use ForwardConfig instead.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AdministrativeOverride

Information about the override status applied to a target.

Contents

Description

A description of the override state that provides additional details.

Type: String

Required: No

Reason

The reason code for the state.

Type: String

Valid Values: `AdministrativeOverride.Unknown` |
`AdministrativeOverride.NoOverride` |
`AdministrativeOverride.ZonalShiftActive` |
`AdministrativeOverride.ZonalShiftDelegatedToDns`

Required: No

State

The state of the override.

Type: String

Valid Values: `unknown` | `no_override` | `zonal_shift_active` |
`zonal_shift_delegated_to_dns`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AnomalyDetection

Information about anomaly detection and mitigation.

Contents

MitigationInEffect

Indicates whether anomaly mitigation is in progress.

Type: String

Valid Values: yes | no

Required: No

Result

The latest anomaly detection result.

Type: String

Valid Values: anomalous | normal

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AuthenticateCognitoActionConfig

Request parameters to use when integrating with Amazon Cognito to authenticate users.

Contents

UserPoolArn

The Amazon Resource Name (ARN) of the Amazon Cognito user pool.

Type: String

Required: Yes

UserPoolClientId

The ID of the Amazon Cognito user pool client.

Type: String

Required: Yes

UserPoolDomain

The domain prefix or fully-qualified domain name of the Amazon Cognito user pool.

Type: String

Required: Yes

AuthenticationRequestExtraParams , AuthenticationRequestExtraParams.entry.N.key (key) , AuthenticationRequestExtraParams.entry.N.value (value)

The query parameters (up to 10) to include in the redirect request to the authorization endpoint.

Type: String to string map

Required: No

OnUnauthenticatedRequest

The behavior if the user is not authenticated. The following are possible values:

- deny - Return an HTTP 401 Unauthorized error.

- **allow** - Allow the request to be forwarded to the target.
- **authenticate** - Redirect the request to the IdP authorization endpoint. This is the default value.

Type: String

Valid Values: deny | allow | authenticate

Required: No

Scope

The set of user claims to be requested from the IdP. The default is `openid`.

To verify which scope values your IdP supports and how to separate multiple values, see the documentation for your IdP.

Type: String

Required: No

SessionCookieName

The name of the cookie used to maintain session information. The default is `AWSELBAuthSessionCookie`.

Type: String

Required: No

SessionTimeout

The maximum duration of the authentication session, in seconds. The default is 604800 seconds (7 days).

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AuthenticateOidcActionConfig

Request parameters when using an identity provider (IdP) that is compliant with OpenID Connect (OIDC) to authenticate users.

Contents

AuthorizationEndpoint

The authorization endpoint of the IdP. This must be a full URL, including the HTTPS protocol, the domain, and the path.

Type: String

Required: Yes

ClientId

The OAuth 2.0 client identifier.

Type: String

Required: Yes

Issuer

The OIDC issuer identifier of the IdP. This must be a full URL, including the HTTPS protocol, the domain, and the path.

Type: String

Required: Yes

TokenEndpoint

The token endpoint of the IdP. This must be a full URL, including the HTTPS protocol, the domain, and the path.

Type: String

Required: Yes

UserInfoEndpoint

The user info endpoint of the IdP. This must be a full URL, including the HTTPS protocol, the domain, and the path.

Type: String

Required: Yes

AuthenticationRequestExtraParams , AuthenticationRequestExtraParams.entry.N.key (key) , AuthenticationRequestExtraParams.entry.N.value (value)

The query parameters (up to 10) to include in the redirect request to the authorization endpoint.

Type: String to string map

Required: No

ClientSecret

The OAuth 2.0 client secret. This parameter is required if you are creating a rule. If you are modifying a rule, you can omit this parameter if you set `UseExistingClientSecret` to true.

Type: String

Required: No

OnUnauthenticatedRequest

The behavior if the user is not authenticated. The following are possible values:

- deny - Return an HTTP 401 Unauthorized error.
- allow - Allow the request to be forwarded to the target.
- authenticate - Redirect the request to the IdP authorization endpoint. This is the default value.

Type: String

Valid Values: deny | allow | authenticate

Required: No

Scope

The set of user claims to be requested from the IdP. The default is `openid`.

To verify which scope values your IdP supports and how to separate multiple values, see the documentation for your IdP.

Type: String

Required: No

SessionCookieName

The name of the cookie used to maintain session information. The default is AWSELBAuthSessionCookie.

Type: String

Required: No

SessionTimeout

The maximum duration of the authentication session, in seconds. The default is 604800 seconds (7 days).

Type: Long

Required: No

UseExistingClientSecret

Indicates whether to use the existing client secret when modifying a rule. If you are creating a rule, you can omit this parameter or set it to false.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AvailabilityZone

Information about an Availability Zone.

Contents

LoadBalancerAddresses.member.N

[Network Load Balancers] If you need static IP addresses for your load balancer, you can specify one Elastic IP address per Availability Zone when you create an internal-facing load balancer. For internal load balancers, you can specify a private IP address from the IPv4 range of the subnet.

Type: Array of [LoadBalancerAddress](#) objects

Required: No

OutpostId

[Application Load Balancers on Outposts] The ID of the Outpost.

Type: String

Required: No

SourceNatIpv6Prefixes.member.N

[Network Load Balancers with UDP listeners] The IPv6 prefixes to use for source NAT. For each subnet, specify an IPv6 prefix (/80 netmask) from the subnet CIDR block or `auto_assigned` to use an IPv6 prefix selected at random from the subnet CIDR block.

Type: Array of strings

Required: No

SubnetId

The ID of the subnet. You can specify one subnet per Availability Zone.

Type: String

Required: No

ZoneName

The name of the Availability Zone.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CapacityReservationStatus

The status of a capacity reservation.

Contents

Code

The status code.

Type: String

Valid Values: `provisioned` | `pending` | `rebalancing` | `failed`

Required: No

Reason

The reason code for the status.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Certificate

Information about an SSL server certificate.

Contents

CertificateArn

The Amazon Resource Name (ARN) of the certificate.

Type: String

Required: No

IsDefault

Indicates whether the certificate is the default certificate. Do not set this value when specifying a certificate as an input. This value is not included in the output when describing a listener, but is included when describing listener certificates.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Cipher

Information about a cipher used in a policy.

Contents

Name

The name of the cipher.

Type: String

Required: No

Priority

The priority of the cipher.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DescribeTrustStoreRevocation

Information about the revocations used by a trust store.

Contents

NumberOfRevokedEntries

The number of revoked certificates.

Type: Long

Required: No

RevocationId

The revocation ID of a revocation file in use.

Type: Long

Required: No

RevocationType

The type of revocation file.

Type: String

Valid Values: CRL

Required: No

TrustStoreArn

The Amazon Resource Name (ARN) of the trust store.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FixedResponseActionConfig

Information about an action that returns a custom HTTP response.

Contents

StatusCode

The HTTP response code (2XX, 4XX, or 5XX).

Type: String

Pattern: `^(2|4|5)\d\d$`

Required: Yes

ContentType

The content type.

Valid Values: `text/plain | text/css | text/html | application/javascript | application/json`

Type: String

Length Constraints: Minimum length of 0. Maximum length of 32.

Required: No

MessageBody

The message.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ForwardActionConfig

Information about a forward action.

Contents

TargetGroups.member.N

The target groups.

Type: Array of [TargetGroupTuple](#) objects

Required: No

TargetGroupStickinessConfig

The target group stickiness for the rule.

Type: [TargetGroupStickinessConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HostHeaderConditionConfig

Information about a host header condition.

Contents

RegexValues.member.N

The regular expressions to compare against the host header. The maximum length of each string is 128 characters.

Type: Array of strings

Required: No

Values.member.N

The host names. The maximum length of each string is 128 characters. The comparison is case insensitive. The following wildcard characters are supported: * (matches 0 or more characters) and ? (matches exactly 1 character). You must include at least one "." character. You can include only alphabetical characters after the final "." character.

If you specify multiple strings, the condition is satisfied if one of the strings matches the host name.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HostHeaderRewriteConfig

Information about a host header rewrite transform. This transform matches a pattern in the host header in an HTTP request and replaces it with the specified string.

Contents

Rewrites.member.N

The host header rewrite transform. Each transform consists of a regular expression to match and a replacement string.

Type: Array of [RewriteConfig](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HTTPHeaderConditionConfig

Information about an HTTP header condition.

There is a set of standard HTTP header fields. You can also define custom HTTP header fields.

Contents

HTTPHeaderName

The name of the HTTP header field. The maximum length is 40 characters. The header name is case insensitive. The allowed characters are specified by RFC 7230. Wildcards are not supported.

You can't use an HTTP header condition to specify the host header. Instead, use a [host condition](#).

Type: String

Required: No

RegexValues.member.N

The regular expression to compare against the HTTP header. The maximum length of each string is 128 characters.

Type: Array of strings

Required: No

Values.member.N

The strings to compare against the value of the HTTP header. The maximum length of each string is 128 characters. The comparison strings are case insensitive. The following wildcard characters are supported: * (matches 0 or more characters) and ? (matches exactly 1 character).

If the same header appears multiple times in the request, we search them in order until a match is found.

If you specify multiple strings, the condition is satisfied if one of the strings matches the value of the HTTP header. To require that all of the strings are a match, create one condition per string.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HttpRequestMethodConditionConfig

Information about an HTTP method condition.

HTTP defines a set of request methods, also referred to as HTTP verbs. For more information, see the [HTTP Method Registry](#). You can also define custom HTTP methods.

Contents

Values.member.N

The name of the request method. The maximum length is 40 characters. The allowed characters are A-Z, hyphen (-), and underscore (_). The comparison is case sensitive. Wildcards are not supported; therefore, the method name must be an exact match.

If you specify multiple strings, the condition is satisfied if one of the strings matches the HTTP request method. We recommend that you route GET and HEAD requests in the same way, because the response to a HEAD request may be cached.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IpamPools

An IPAM pool is a collection of IP address CIDRs. IPAM pools enable you to organize your IP addresses according to your routing and security needs.

Contents

Ipv4IpamPoolId

The ID of the IPv4 IPAM pool.

Type: String

Length Constraints: Maximum length of 1000.

Pattern: `^(ipam-pool-)[a-zA-Z0-9]+$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

JwtValidationActionAdditionalClaim

Information about an additional claim to validate.

Contents

Format

The format of the claim value.

Type: String

Valid Values: `single-string` | `string-array` | `space-separated-values`

Required: Yes

Name

The name of the claim. You can't specify `exp`, `iss`, `nbf`, or `iat` because we validate them by default.

Type: String

Required: Yes

Values.member.N

The claim value. The maximum size of the list is 10. Each value can be up to 256 characters in length. If the format is `space-separated-values`, the values can't include spaces.

Type: Array of strings

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

JwtValidationActionConfig

Information about a JSON Web Token (JWT) validation action.

Contents

Issuer

The issuer of the JWT. The maximum length is 256 characters.

Type: String

Required: Yes

JwksEndpoint

The JSON Web Key Set (JWKS) endpoint. This endpoint contains JSON Web Keys (JWK) that are used to validate signatures from the provider.

This must be a full URL, including the HTTPS protocol, the domain, and the path. The maximum length is 256 characters.

Type: String

Required: Yes

AdditionalClaims.member.N

Additional claims to validate. The maximum size of the list is 10. We validate the `exp`, `iss`, `nbf`, and `iat` claims by default.

Type: Array of [JwtValidationActionAdditionalClaim](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

Limit

Information about an Elastic Load Balancing resource limit for your AWS account.

For more information, see the following:

- [Quotas for your Application Load Balancers](#)
- [Quotas for your Network Load Balancers](#)
- [Quotas for your Gateway Load Balancers](#)

Contents

Max

The maximum value of the limit.

Type: String

Required: No

Name

The name of the limit.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Listener

Information about a listener.

Contents

AlpnPolicy.member.N

[TLS listener] The name of the Application-Layer Protocol Negotiation (ALPN) policy.

Type: Array of strings

Required: No

Certificates.member.N

[HTTPS or TLS listener] The default certificate for the listener.

Type: Array of [Certificate](#) objects

Required: No

DefaultActions.member.N

The default actions for the listener.

Type: Array of [Action](#) objects

Required: No

ListenerArn

The Amazon Resource Name (ARN) of the listener.

Type: String

Required: No

LoadBalancerArn

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: No

MutualAuthentication

The mutual authentication configuration information.

Type: [MutualAuthenticationAttributes](#) object

Required: No

Port

The port on which the load balancer is listening.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

Protocol

The protocol for connections from clients to the load balancer.

Type: String

Valid Values: HTTP | HTTPS | TCP | TLS | UDP | TCP_UDP | GENEVE | QUIC | TCP_QUIC

Required: No

SslPolicy

[HTTPS or TLS listener] The security policy that defines which protocols and ciphers are supported.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListenerAttribute

Information about a listener attribute.

Contents

Key

The name of the attribute.

The following attribute is supported by Network Load Balancers, and Gateway Load Balancers.

- `tcp.idle_timeout.seconds` - The tcp idle timeout value, in seconds. The valid range is 60-6000 seconds. The default is 350 seconds.

The following attributes are only supported by Application Load Balancers.

- `routing.http.request.x_amzn_mtls_clientcert_serial_number.header_name` - Enables you to modify the header name of the **X-Amzn-Mtls-Clientcert-Serial-Number** HTTP request header.
- `routing.http.request.x_amzn_mtls_clientcert_issuer.header_name` - Enables you to modify the header name of the **X-Amzn-Mtls-Clientcert-Issuer** HTTP request header.
- `routing.http.request.x_amzn_mtls_clientcert_subject.header_name` - Enables you to modify the header name of the **X-Amzn-Mtls-Clientcert-Subject** HTTP request header.
- `routing.http.request.x_amzn_mtls_clientcert_validity.header_name` - Enables you to modify the header name of the **X-Amzn-Mtls-Clientcert-Validity** HTTP request header.
- `routing.http.request.x_amzn_mtls_clientcert_leaf.header_name` - Enables you to modify the header name of the **X-Amzn-Mtls-Clientcert-Leaf** HTTP request header.
- `routing.http.request.x_amzn_mtls_clientcert.header_name` - Enables you to modify the header name of the **X-Amzn-Mtls-Clientcert** HTTP request header.
- `routing.http.request.x_amzn_tls_version.header_name` - Enables you to modify the header name of the **X-Amzn-Tls-Version** HTTP request header.
- `routing.http.request.x_amzn_tls_cipher_suite.header_name` - Enables you to modify the header name of the **X-Amzn-Tls-Cipher-Suite** HTTP request header.
- `routing.http.response.server.enabled` - Enables you to allow or remove the HTTP response server header.

- `routing.http.response.strict_transport_security.header_value` - Informs browsers that the site should only be accessed using HTTPS, and that any future attempts to access it using HTTP should automatically be converted to HTTPS.
- `routing.http.response.access_control_allow_origin.header_value` - Specifies which origins are allowed to access the server.
- `routing.http.response.access_control_allow_methods.header_value` - Returns which HTTP methods are allowed when accessing the server from a different origin.
- `routing.http.response.access_control_allow_headers.header_value` - Specifies which headers can be used during the request.
- `routing.http.response.access_control_allow_credentials.header_value` - Indicates whether the browser should include credentials such as cookies or authentication when making requests.
- `routing.http.response.access_control_expose_headers.header_value` - Returns which headers the browser can expose to the requesting client.
- `routing.http.response.access_control_max_age.header_value` - Specifies how long the results of a preflight request can be cached, in seconds.
- `routing.http.response.content_security_policy.header_value` - Specifies restrictions enforced by the browser to help minimize the risk of certain types of security threats.
- `routing.http.response.x_content_type_options.header_value` - Indicates whether the MIME types advertised in the **Content-Type** headers should be followed and not be changed.
- `routing.http.response.x_frame_options.header_value` - Indicates whether the browser is allowed to render a page in a **frame**, **iframe**, **embed** or **object**.

Type: String

Length Constraints: Maximum length of 256.

Pattern: `^[a-zA-Z0-9._]+$`

Required: No

Value

The value of the attribute.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LoadBalancer

Information about a load balancer.

Contents

AvailabilityZones.member.N

The subnets for the load balancer.

Type: Array of [AvailabilityZone](#) objects

Required: No

CanonicalHostedZoneId

The ID of the Amazon Route 53 hosted zone associated with the load balancer.

Type: String

Required: No

CreatedTime

The date and time the load balancer was created.

Type: Timestamp

Required: No

CustomerOwnedIpv4Pool

[Application Load Balancers on Outposts] The ID of the customer-owned address pool.

Type: String

Length Constraints: Maximum length of 256.

Pattern: `^(ipv4pool-coip-)[a-zA-Z0-9]+$`

Required: No

DNSName

The public DNS name of the load balancer.

Type: String

Required: No

EnablePrefixForIpv6SourceNat

[Network Load Balancers with UDP listeners] Indicates whether to use an IPv6 prefix from each subnet for source NAT. The IP address type must be `dualstack`. The default value is `off`.

Type: String

Valid Values: `on` | `off`

Required: No

EnforceSecurityGroupInboundRulesOnPrivateLinkTraffic

Indicates whether to evaluate inbound security group rules for traffic sent to a Network Load Balancer through AWS PrivateLink.

Type: String

Required: No

IpAddressType

The type of IP addresses used for public or private connections by the subnets attached to your load balancer.

[Application Load Balancers] The possible values are `ipv4` (IPv4 addresses), `dualstack` (IPv4 and IPv6 addresses), and `dualstack-without-public-ipv4` (public IPv6 addresses and private IPv4 and IPv6 addresses).

[Network Load Balancers and Gateway Load Balancers] The possible values are `ipv4` (IPv4 addresses) and `dualstack` (IPv4 and IPv6 addresses).

Type: String

Valid Values: `ipv4` | `dualstack` | `dualstack-without-public-ipv4`

Required: No

IpamPools

[Application Load Balancers] The IPAM pool in use by the load balancer, if configured.

Type: [IpamPools](#) object

Required: No

LoadBalancerArn

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: No

LoadBalancerName

The name of the load balancer.

Type: String

Required: No

Scheme

The nodes of an Internet-facing load balancer have public IP addresses. The DNS name of an Internet-facing load balancer is publicly resolvable to the public IP addresses of the nodes. Therefore, Internet-facing load balancers can route requests from clients over the internet.

The nodes of an internal load balancer have only private IP addresses. The DNS name of an internal load balancer is publicly resolvable to the private IP addresses of the nodes. Therefore, internal load balancers can route requests only from clients with access to the VPC for the load balancer.

Type: String

Valid Values: `internet-facing` | `internal`

Required: No

SecurityGroups.member.N

The IDs of the security groups for the load balancer.

Type: Array of strings

Required: No

State

The state of the load balancer.

Type: [LoadBalancerState](#) object

Required: No

Type

The type of load balancer.

Type: String

Valid Values: `application` | `network` | `gateway`

Required: No

VpcId

The ID of the VPC for the load balancer.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LoadBalancerAddress

Information about a static IP address for a load balancer.

Contents

AllocationId

[Network Load Balancers] The allocation ID of the Elastic IP address for an internal-facing load balancer.

Type: String

Required: No

IpAddress

The static IP address.

Type: String

Required: No

IPv6Address

[Network Load Balancers] The IPv6 address.

Type: String

Required: No

PrivateIPv4Address

[Network Load Balancers] The private IPv4 address for an internal load balancer.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LoadBalancerAttribute

Information about a load balancer attribute.

Contents

Key

The name of the attribute.

The following attributes are supported by all load balancers:

- `deletion_protection.enabled` - Indicates whether deletion protection is enabled. The value is `true` or `false`. The default is `false`.
- `load_balancing.cross_zone.enabled` - Indicates whether cross-zone load balancing is enabled. The possible values are `true` and `false`. The default for Network Load Balancers and Gateway Load Balancers is `false`. The default for Application Load Balancers is `true`, and can't be changed.

The following attributes are supported by both Application Load Balancers and Network Load Balancers:

- `access_logs.s3.enabled` - Indicates whether access logs are enabled. The value is `true` or `false`. The default is `false`.
- `access_logs.s3.bucket` - The name of the S3 bucket for the access logs. This attribute is required if access logs are enabled. The bucket must exist in the same region as the load balancer and have a bucket policy that grants Elastic Load Balancing permissions to write to the bucket.
- `access_logs.s3.prefix` - The prefix for the location in the S3 bucket for the access logs.
- `ipv6.deny_all_igw_traffic` - Blocks internet gateway (IGW) access to the load balancer. It is set to `false` for internet-facing load balancers and `true` for internal load balancers, preventing unintended access to your internal load balancer through an internet gateway.
- `zonal_shift.config.enabled` - Indicates whether zonal shift is enabled. The possible values are `true` and `false`. The default is `false`.

The following attributes are supported by only Application Load Balancers:

- `idle_timeout.timeout_seconds` - The idle timeout value, in seconds. The valid range is 1-4000 seconds. The default is 60 seconds.

- `client_keep_alive.seconds` - The client keep alive value, in seconds. The valid range is 60-604800 seconds. The default is 3600 seconds.
- `connection_logs.s3.enabled` - Indicates whether connection logs are enabled. The value is `true` or `false`. The default is `false`.
- `connection_logs.s3.bucket` - The name of the S3 bucket for the connection logs. This attribute is required if connection logs are enabled. The bucket must exist in the same region as the load balancer and have a bucket policy that grants Elastic Load Balancing permissions to write to the bucket.
- `connection_logs.s3.prefix` - The prefix for the location in the S3 bucket for the connection logs.
- `health_check_logs.s3.enabled` - Indicates whether health check logs are enabled. The value is `true` or `false`. The default is `false`.
- `health_check_logs.s3.bucket` - The name of the S3 bucket for the health check logs. This attribute is required if health check logs are enabled. The bucket must exist in the same region as the load balancer and have a bucket policy that grants Elastic Load Balancing permissions to write to the bucket.
- `health_check_logs.s3.prefix` - The prefix for the location in the S3 bucket for the health check logs.
- `routing.http.desync_mitigation_mode` - Determines how the load balancer handles requests that might pose a security risk to your application. The possible values are `monitor`, `defensive`, and `strictest`. The default is `defensive`.
- `routing.http.drop_invalid_header_fields.enabled` - Indicates whether HTTP headers with invalid header fields are removed by the load balancer (`true`) or routed to targets (`false`). The default is `false`.
- `routing.http.preserve_host_header.enabled` - Indicates whether the Application Load Balancer should preserve the Host header in the HTTP request and send it to the target without any change. The possible values are `true` and `false`. The default is `false`.
- `routing.http.x_amzn_tls_version_and_cipher_suite.enabled` - Indicates whether the two headers (`x-amzn-tls-version` and `x-amzn-tls-cipher-suite`), which contain information about the negotiated TLS version and cipher suite, are added to the client request before sending it to the target. The `x-amzn-tls-version` header has information about the TLS protocol version negotiated with the client, and the `x-amzn-tls-cipher-suite` header has information about the cipher suite negotiated with the client.

Both headers are in OpenSSL format. The possible values for the attribute are `true` and `false`. The default is `false`.

- `routing.http.xff_client_port.enabled` - Indicates whether the X-Forwarded-For header should preserve the source port that the client used to connect to the load balancer. The possible values are `true` and `false`. The default is `false`.
- `routing.http.xff_header_processing.mode` - Enables you to modify, preserve, or remove the X-Forwarded-For header in the HTTP request before the Application Load Balancer sends the request to the target. The possible values are `append`, `preserve`, and `remove`. The default is `append`.
 - If the value is `append`, the Application Load Balancer adds the client IP address (of the last hop) to the X-Forwarded-For header in the HTTP request before it sends it to targets.
 - If the value is `preserve` the Application Load Balancer preserves the X-Forwarded-For header in the HTTP request, and sends it to targets without any change.
 - If the value is `remove`, the Application Load Balancer removes the X-Forwarded-For header in the HTTP request before it sends it to targets.
- `routing.http2.enabled` - Indicates whether clients can connect to the load balancer using HTTP/2. If `true`, clients can connect using HTTP/2 or HTTP/1.1. However, all client requests are subject to the stricter HTTP/2 header validation rules. For example, message header names must contain only alphanumeric characters and hyphens. If `false`, clients must connect using HTTP/1.1. The default is `true`.
- `waf.fail_open.enabled` - Indicates whether to allow a WAF-enabled load balancer to route requests to targets if it is unable to forward the request to AWS WAF. The possible values are `true` and `false`. The default is `false`.

The following attributes are supported by only Network Load Balancers:

- `dns_record.client_routing_policy` - Indicates how traffic is distributed among the load balancer Availability Zones. The possible values are `availability_zone_affinity` with 100 percent zonal affinity, `partial_availability_zone_affinity` with 85 percent zonal affinity, and `any_availability_zone` with 0 percent zonal affinity.
- `secondary_ips.auto_assigned.per_subnet` - The number of secondary IP addresses to configure for your load balancer nodes. Use to address port allocation errors if you can't add targets. The valid range is 0 to 7. The default is 0. After you set this value, you can't decrease it.

Type: String

Length Constraints: Maximum length of 256.

Pattern: `^[a-zA-Z0-9._]+$`

Required: No

Value

The value of the attribute.

Type: String

Length Constraints: Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LoadBalancerState

Information about the state of the load balancer.

Contents

Code

The state code. The initial state of the load balancer is provisioning. After the load balancer is fully set up and ready to route traffic, its state is active. If load balancer is routing traffic but does not have the resources it needs to scale, its state is `active_impaired`. If the load balancer could not be set up, its state is failed.

Type: String

Valid Values: `active` | `provisioning` | `active_impaired` | `failed`

Required: No

Reason

A description of the state.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Matcher

The codes to use when checking for a successful response from a target. If the protocol version is gRPC, these are gRPC codes. Otherwise, these are HTTP codes.

Contents

GrpcCode

You can specify values between 0 and 99. You can specify multiple values (for example, "0,1") or a range of values (for example, "0-5"). The default value is 12.

Type: String

Required: No

HttpCode

For Application Load Balancers, you can specify values between 200 and 499, with the default value being 200. You can specify multiple values (for example, "200,202") or a range of values (for example, "200-299").

For Network Load Balancers, you can specify values between 200 and 599, with the default value being 200-399. You can specify multiple values (for example, "200,202") or a range of values (for example, "200-299").

For Gateway Load Balancers, this must be "200-399".

Note that when using shorthand syntax, some values such as commas need to be escaped.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

MinimumLoadBalancerCapacity

The minimum capacity for a load balancer.

Contents

CapacityUnits

The number of capacity units.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MutualAuthenticationAttributes

Information about the mutual authentication attributes of a listener.

Contents

AdvertiseTrustStoreCaNames

Indicates whether trust store CA certificate names are advertised.

Type: String

Valid Values: on | off

Required: No

IgnoreClientCertificateExpiry

Indicates whether expired client certificates are ignored.

Type: Boolean

Required: No

Mode

The client certificate handling method. Options are off, passthrough or verify. The default value is off.

Type: String

Required: No

TrustStoreArn

The Amazon Resource Name (ARN) of the trust store.

Type: String

Required: No

TrustStoreAssociationStatus

Indicates a shared trust stores association status.

Type: String

Valid Values: active | removed

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PathPatternConditionConfig

Information about a path pattern condition.

Contents

RegexValues.member.N

The regular expressions to compare against the request URL. The maximum length of each string is 128 characters.

Type: Array of strings

Required: No

Values.member.N

The path patterns to compare against the request URL. The maximum length of each string is 128 characters. The comparison is case sensitive. The following wildcard characters are supported: * (matches 0 or more characters) and ? (matches exactly 1 character).

If you specify multiple strings, the condition is satisfied if one of them matches the request URL. The path pattern is compared only to the path of the URL, not to its query string. To compare against the query string, use a [query string condition](#).

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

QueryStringConditionConfig

Information about a query string condition.

The query string component of a URI starts after the first '?' character and is terminated by either a '#' character or the end of the URI. A typical query string contains key/value pairs separated by '&' characters. The allowed characters are specified by RFC 3986. Any character can be percentage encoded.

Contents

Values.member.N

The key/value pairs or values to find in the query string. The maximum length of each string is 128 characters. The comparison is case insensitive. The following wildcard characters are supported: * (matches 0 or more characters) and ? (matches exactly 1 character). To search for a literal '*' or '?' character in a query string, you must escape these characters in `Values` using a '\' character.

If you specify multiple key/value pairs or values, the condition is satisfied if one of them is found in the query string.

Type: Array of [QueryStringKeyValuePair](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

QueryStringKeyValuePair

Information about a key/value pair.

Contents

Key

The key. You can omit the key.

Type: String

Required: No

Value

The value.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RedirectActionConfig

Information about a redirect action.

A URI consists of the following components: protocol://hostname:port/path?query. You must modify at least one of the following components to avoid a redirect loop: protocol, hostname, port, or path. Any components that you do not modify retain their original values.

You can reuse URI components using the following reserved keywords:

- `{protocol}`
- `{host}`
- `{port}`
- `{path}` (the leading "/" is removed)
- `{query}`

For example, you can change the path to `/new/{path}`, the hostname to `example.{host}`, or the query to `{query}&value=xyz`.

Contents

StatusCode

The HTTP redirect code. The redirect is either permanent (HTTP 301) or temporary (HTTP 302).

Type: String

Valid Values: HTTP_301 | HTTP_302

Required: Yes

Host

The hostname. This component is not percent-encoded. The hostname can contain `{host}`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Path

The absolute path, starting with the leading "/". This component is not percent-encoded. The path can contain `{host}`, `{path}`, and `{port}`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Port

The port. You can specify a value from 1 to 65535 or `{port}`.

Type: String

Required: No

Protocol

The protocol. You can specify HTTP, HTTPS, or `{protocol}`. You can redirect HTTP to HTTP, HTTP to HTTPS, and HTTPS to HTTPS. You can't redirect HTTPS to HTTP.

Type: String

Pattern: `^(HTTPS?|#{protocol\})$`

Required: No

Query

The query parameters, URL-encoded when necessary, but not percent-encoded. Do not include the leading "?", as it is automatically added. You can specify any of the reserved keywords.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RevocationContent

Information about a revocation file.

Contents

RevocationType

The type of revocation file.

Type: String

Valid Values: CRL

Required: No

S3Bucket

The Amazon S3 bucket for the revocation file.

Type: String

Required: No

S3Key

The Amazon S3 path for the revocation file.

Type: String

Required: No

S3ObjectVersion

The Amazon S3 object version of the revocation file.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RewriteConfig

Information about a rewrite transform. This transform matches a pattern and replaces it with the specified string.

Contents

Regex

The regular expression to match in the input string. The maximum length of the string is 1,024 characters.

Type: String

Required: Yes

Replace

The replacement string to use when rewriting the matched input. The maximum length of the string is 1,024 characters. You can specify capture groups in the regular expression (for example, \$1 and \$2).

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Rule

Information about a rule.

Contents

Actions.member.N

The actions. Each rule must include exactly one of the following types of actions: `forward`, `redirect`, or `fixed-response`, and it must be the last action to be performed.

Type: Array of [Action](#) objects

Required: No

Conditions.member.N

The conditions. Each rule can include zero or one of the following conditions: `http-request-method`, `host-header`, `path-pattern`, and `source-ip`, and zero or more of the following conditions: `http-header` and `query-string`.

Type: Array of [RuleCondition](#) objects

Required: No

IsDefault

Indicates whether this is the default rule.

Type: Boolean

Required: No

Priority

The priority.

Type: String

Required: No

RuleArn

The Amazon Resource Name (ARN) of the rule.

Type: String

Required: No

Transforms.member.N

The transforms for the rule.

Type: Array of [RuleTransform](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RuleCondition

Information about a condition for a rule.

Each rule can optionally include up to one of each of the following conditions: `http-request-method`, `host-header`, `path-pattern`, and `source-ip`. Each rule can also optionally include one or more of each of the following conditions: `http-header` and `query-string`. Note that the value for a condition can't be empty.

For more information, see [Quotas for your Application Load Balancers](#).

Contents

Field

The field in the HTTP request. The following are the possible values:

- `http-header`
- `http-request-method`
- `host-header`
- `path-pattern`
- `query-string`
- `source-ip`

Type: String

Length Constraints: Maximum length of 64.

Required: No

HostHeaderConfig

Information for a host header condition. Specify only when `Field` is `host-header`.

Type: [HostHeaderConditionConfig](#) object

Required: No

HTTPHeaderConfig

Information for an HTTP header condition. Specify only when `Field` is `http-header`.

Type: [HTTPHeaderConditionConfig](#) object

Required: No

HttpRequestMethodConfig

Information for an HTTP method condition. Specify only when `Field` is `http-request-method`.

Type: [HttpRequestMethodConditionConfig](#) object

Required: No

PathPatternConfig

Information for a path pattern condition. Specify only when `Field` is `path-pattern`.

Type: [PathPatternConditionConfig](#) object

Required: No

QueryStringConfig

Information for a query string condition. Specify only when `Field` is `query-string`.

Type: [QueryStringConditionConfig](#) object

Required: No

RegexValues.member.N

The regular expressions to match against the condition field. The maximum length of each string is 128 characters. Specify only when `Field` is `http-header`, `host-header`, or `path-pattern`.

Type: Array of strings

Required: No

SourceIpConfig

Information for a source IP condition. Specify only when `Field` is `source-ip`.

Type: [SourceIpConditionConfig](#) object

Required: No

Values.member.N

The condition value. Specify only when `Field` is `host-header` or `path-pattern`. Alternatively, to specify multiple host names or multiple path patterns, use `HostHeaderConfig` or `PathPatternConfig`.

If `Field` is `host-header` and you are not using `HostHeaderConfig`, you can specify a single host name (for example, `my.example.com`) in `Values`. A host name is case insensitive, can be up to 128 characters in length, and can contain any of the following characters.

- A-Z, a-z, 0-9
- - .
- * (matches 0 or more characters)
- ? (matches exactly 1 character)

If `Field` is `path-pattern` and you are not using `PathPatternConfig`, you can specify a single path pattern (for example, `/img/*`) in `Values`. A path pattern is case-sensitive, can be up to 128 characters in length, and can contain any of the following characters.

- A-Z, a-z, 0-9
- _ - . \$ / ~ " ' @ : +
- & (using `&`)
- * (matches 0 or more characters)
- ? (matches exactly 1 character)

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RulePriorityPair

Information about the priorities for the rules for a listener.

Contents

Priority

The rule priority.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50000.

Required: No

RuleArn

The Amazon Resource Name (ARN) of the rule.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RuleTransform

Information about a transform to apply to requests that match a rule. Transforms are applied to requests before they are sent to targets.

Contents

Type

The type of transform.

- `host-header-rewrite` - Rewrite the host header.
- `url-rewrite` - Rewrite the request URL.

Type: String

Valid Values: `host-header-rewrite` | `url-rewrite`

Required: Yes

HostHeaderRewriteConfig

Information about a host header rewrite transform. This transform modifies the host header in an HTTP request. Specify only when Type is `host-header-rewrite`.

Type: [HostHeaderRewriteConfig](#) object

Required: No

UrlRewriteConfig

Information about a URL rewrite transform. This transform modifies the request URL. Specify only when Type is `url-rewrite`.

Type: [UrlRewriteConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SourceIpConditionConfig

Information about a source IP condition.

You can use this condition to route based on the IP address of the source that connects to the load balancer. If a client is behind a proxy, this is the IP address of the proxy not the IP address of the client.

Contents

Values.member.N

The source IP addresses, in CIDR format. You can use both IPv4 and IPv6 addresses. Wildcards are not supported.

If you specify multiple addresses, the condition is satisfied if the source IP address of the request matches one of the CIDR blocks. This condition is not satisfied by the addresses in the X-Forwarded-For header. To search for addresses in the X-Forwarded-For header, use an [HTTP header condition](#).

The total number of values must be less than, or equal to five.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SslPolicy

Information about a policy used for SSL negotiation.

Contents

Ciphers.member.N

The ciphers.

Type: Array of [Cipher](#) objects

Required: No

Name

The name of the policy.

Type: String

Required: No

SslProtocols.member.N

The protocols.

Type: Array of strings

Required: No

SupportedLoadBalancerTypes.member.N

The supported load balancers.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SubnetMapping

Information about a subnet mapping.

Contents

AllocationId

[Network Load Balancers] The allocation ID of the Elastic IP address for an internet-facing load balancer.

Type: String

Required: No

IPv6Address

[Network Load Balancers] The IPv6 address.

Type: String

Required: No

PrivateIPv4Address

[Network Load Balancers] The private IPv4 address for an internal load balancer.

Type: String

Required: No

SourceNatIPv6Prefix

[Network Load Balancers with UDP listeners] The IPv6 prefix to use for source NAT. Specify an IPv6 prefix (/80 netmask) from the subnet CIDR block or `auto_assigned` to use an IPv6 prefix selected at random from the subnet CIDR block.

Type: String

Required: No

SubnetId

The ID of the subnet.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

Information about a tag.

Contents

Key

The key of the tag.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: $^([\p{L}\p{Z}\p{N}_\p{.}:/=\+\-\@]^*)\$$

Required: Yes

Value

The value of the tag.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: $^([\p{L}\p{Z}\p{N}_\p{.}:/=\+\-\@]^*)\$$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TagDescription

The tags associated with a resource.

Contents

ResourceArn

The Amazon Resource Name (ARN) of the resource.

Type: String

Required: No

Tags.member.N

Information about the tags.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TargetDescription

Information about a target.

Contents

Id

The ID of the target. If the target type of the target group is `instance`, specify an instance ID. If the target type is `ip`, specify an IP address. If the target type is `lambda`, specify the ARN of the Lambda function. If the target type is `alb`, specify the ARN of the Application Load Balancer target.

Type: String

Required: Yes

AvailabilityZone

An Availability Zone or `all`. This determines whether the target receives traffic from the load balancer nodes in the specified Availability Zone or from all enabled Availability Zones for the load balancer.

For Application Load Balancer target groups, the specified Availability Zone value is only applicable when cross-zone load balancing is off. Otherwise the parameter is ignored and treated as `all`.

This parameter is not supported if the target type of the target group is `instance` or `alb`.

If the target type is `ip` and the IP address is in a subnet of the VPC for the target group, the Availability Zone is automatically detected and this parameter is optional. If the IP address is outside the VPC, this parameter is required.

For Application Load Balancer target groups with cross-zone load balancing off, if the target type is `ip` and the IP address is outside of the VPC for the target group, this should be an Availability Zone inside the VPC for the target group.

If the target type is `lambda`, this parameter is optional and the only supported value is `all`.

Type: String

Required: No

Port

The port on which the target is listening. If the target group protocol is GENEVE, the supported port is 6081. If the target type is `alb`, the targeted Application Load Balancer must have at least one listener whose port matches the target group port. This parameter is not used if the target is a Lambda function.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

QuicServerId

The server ID for the targets. This value is required if the protocol is QUIC or TCP_QUIC and can't be used with other protocols.

The ID consists of the `0x` prefix followed by 16 hexadecimal characters. Any letters must be lowercase. The value must be unique at the listener level. You can't modify the server ID for a registered target. You must deregister the target and then provide a new server ID when you register the target again.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TargetGroup

Information about a target group.

Contents

HealthCheckEnabled

Indicates whether health checks are enabled.

Type: Boolean

Required: No

HealthCheckIntervalSeconds

The approximate amount of time, in seconds, between health checks of an individual target.

Type: Integer

Valid Range: Minimum value of 5. Maximum value of 300.

Required: No

HealthCheckPath

The destination for health checks on the targets.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

HealthCheckPort

The port to use to connect with the target.

Type: String

Required: No

HealthCheckProtocol

The protocol to use to connect with the target. The GENEVE, TLS, UDP, and TCP_UDP protocols are not supported for health checks.

Type: String

Valid Values: HTTP | HTTPS | TCP | TLS | UDP | TCP_UDP | GENEVE | QUIC | TCP_QUIC

Required: No

HealthCheckTimeoutSeconds

The amount of time, in seconds, during which no response means a failed health check.

Type: Integer

Valid Range: Minimum value of 2. Maximum value of 120.

Required: No

HealthyThresholdCount

The number of consecutive health checks successes required before considering an unhealthy target healthy.

Type: Integer

Valid Range: Minimum value of 2. Maximum value of 10.

Required: No

IpAddressType

The IP address type. The default value is ipv4.

Type: String

Valid Values: ipv4 | ipv6

Required: No

LoadBalancerArns.member.N

The Amazon Resource Name (ARN) of the load balancer that routes traffic to this target group. You can use each target group with only one load balancer.

Type: Array of strings

Required: No

Matcher

The HTTP or gRPC codes to use when checking for a successful response from a target.

Type: [Matcher](#) object

Required: No

Port

The port on which the targets are listening. This parameter is not used if the target is a Lambda function.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

Protocol

The protocol to use for routing traffic to the targets.

Type: String

Valid Values: HTTP | HTTPS | TCP | TLS | UDP | TCP_UDP | GENEVE | QUIC | TCP_QUIC

Required: No

ProtocolVersion

[HTTP/HTTPS protocol] The protocol version. The possible values are GRPC, HTTP1, and HTTP2.

Type: String

Required: No

TargetControlPort

The port on which the target control agent and application load balancer exchange management traffic for the target optimizer feature.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

TargetGroupArn

The Amazon Resource Name (ARN) of the target group.

Type: String

Required: No

TargetGroupName

The name of the target group.

Type: String

Required: No

TargetType

The type of target that you must specify when registering targets with this target group. The possible values are `instance` (register targets by instance ID), `ip` (register targets by IP address), `lambda` (register a single Lambda function as a target), or `alb` (register a single Application Load Balancer as a target).

Type: String

Valid Values: `instance` | `ip` | `lambda` | `alb`

Required: No

UnhealthyThresholdCount

The number of consecutive health check failures required before considering the target unhealthy.

Type: Integer

Valid Range: Minimum value of 2. Maximum value of 10.

Required: No

VpcId

The ID of the VPC for the targets.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TargetGroupAttribute

Information about a target group attribute.

Contents

Key

The name of the attribute.

The following attributes are supported by all load balancers:

- `deregistration_delay.timeout_seconds` - The amount of time, in seconds, for Elastic Load Balancing to wait before changing the state of a deregistering target from draining to unused. The range is 0-3600 seconds. The default value is 300 seconds. If the target is a Lambda function, this attribute is not supported.
- `stickiness.enabled` - Indicates whether target stickiness is enabled. The value is `true` or `false`. The default is `false`.
- `stickiness.type` - Indicates the type of stickiness. The possible values are:
 - `lb_cookie` and `app_cookie` for Application Load Balancers.
 - `source_ip` for Network Load Balancers.
 - `source_ip_dest_ip` and `source_ip_dest_ip_proto` for Gateway Load Balancers.

The following attributes are supported by Application Load Balancers and Network Load Balancers:

- `load_balancing.cross_zone.enabled` - Indicates whether cross zone load balancing is enabled. The value is `true`, `false` or `use_load_balancer_configuration`. The default is `use_load_balancer_configuration`.
- `target_group_health.dns_failover.minimum_healthy_targets.count` - The minimum number of targets that must be healthy. If the number of healthy targets is below this value, mark the zone as unhealthy in DNS, so that traffic is routed only to healthy zones. The possible values are `off` or an integer from 1 to the maximum number of targets. The default is 1.
- `target_group_health.dns_failover.minimum_healthy_targets.percentage` - The minimum percentage of targets that must be healthy. If the percentage of healthy targets is below this value, mark the zone as unhealthy in DNS, so that traffic is routed only to healthy zones. The possible values are `off` or an integer from 1 to 100. The default is `off`.

- `target_group_health.unhealthy_state_routing.minimum_healthy_targets.count`
 - The minimum number of targets that must be healthy. If the number of healthy targets is below this value, send traffic to all targets, including unhealthy targets. The possible values are 1 to the maximum number of targets. The default is 1.
- `target_group_health.unhealthy_state_routing.minimum_healthy_targets.percenta`
 - The minimum percentage of targets that must be healthy. If the percentage of healthy targets is below this value, send traffic to all targets, including unhealthy targets. The possible values are off or an integer from 1 to 100. The default is off.

The following attributes are supported only if the load balancer is an Application Load Balancer and the target is an instance or an IP address:

- `load_balancing.algorithm.type` - The load balancing algorithm determines how the load balancer selects targets when routing requests. The value is `round_robin`, `least_outstanding_requests`, or `weighted_random`. The default is `round_robin`.
- `load_balancing.algorithm.anomaly_mitigation` - Only available when `load_balancing.algorithm.type` is `weighted_random`. Indicates whether anomaly mitigation is enabled. The value is `on` or `off`. The default is `off`.
- `slow_start.duration_seconds` - The time period, in seconds, during which a newly registered target receives an increasing share of the traffic to the target group. After this time period ends, the target receives its full share of traffic. The range is 30-900 seconds (15 minutes). The default is 0 seconds (disabled).
- `stickiness.app_cookie.cookie_name` - Indicates the name of the application-based cookie. Names that start with the following prefixes are not allowed: `AWSALB`, `AWSALBAPP`, and `AWSALBTG`; they're reserved for use by the load balancer.
- `stickiness.app_cookie.duration_seconds` - The time period, in seconds, during which requests from a client should be routed to the same target. After this time period expires, the application-based cookie is considered stale. The range is 1 second to 1 week (604800 seconds). The default value is 1 day (86400 seconds).
- `stickiness.lb_cookie.duration_seconds` - The time period, in seconds, during which requests from a client should be routed to the same target. After this time period expires, the load balancer-generated cookie is considered stale. The range is 1 second to 1 week (604800 seconds). The default value is 1 day (86400 seconds).

The following attribute is supported only if the load balancer is an Application Load Balancer and the target is a Lambda function:

- `lambda.multi_value_headers.enabled` - Indicates whether the request and response headers that are exchanged between the load balancer and the Lambda function include arrays of values or strings. The value is `true` or `false`. The default is `false`. If the value is `false` and the request contains a duplicate header field name or query parameter key, the load balancer uses the last value sent by the client.

The following attributes are supported only by Network Load Balancers:

- `deregistration_delay.connection_termination.enabled` - Indicates whether the load balancer terminates connections at the end of the deregistration timeout. The value is `true` or `false`. For new UDP/TCP_UDP target groups the default is `true`. Otherwise, the default is `false`.
- `preserve_client_ip.enabled` - Indicates whether client IP preservation is enabled. The value is `true` or `false`. The default is disabled if the target group type is IP address and the target group protocol is TCP or TLS. Otherwise, the default is enabled. Client IP preservation can't be disabled for UDP and TCP_UDP target groups.
- `proxy_protocol_v2.enabled` - Indicates whether Proxy Protocol version 2 is enabled. The value is `true` or `false`. The default is `false`.
- `target_health_state.unhealthy.connection_termination.enabled` - Indicates whether the load balancer terminates connections to unhealthy targets. The value is `true` or `false`. The default is `true`. This attribute can't be enabled for UDP and TCP_UDP target groups.
- `target_health_state.unhealthy.draining_interval_seconds` - The amount of time for Elastic Load Balancing to wait before changing the state of an unhealthy target from `unhealthy.draining` to `unhealthy`. The range is 0-360000 seconds. The default value is 0 seconds.

Note: This attribute can only be configured when `target_health_state.unhealthy.connection_termination.enabled` is `false`.

The following attributes are supported only by Gateway Load Balancers:

- `target_failover.on_deregistration` - Indicates how the Gateway Load Balancer handles existing flows when a target is deregistered. The possible values are `rebalance` and `no_rebalance`. The default is `no_rebalance`. The two attributes (`target_failover.on_deregistration` and `target_failover.on_unhealthy`) can't be set independently. The value you set for both attributes must be the same.

- `target_failover.on_unhealthy` - Indicates how the Gateway Load Balancer handles existing flows when a target is unhealthy. The possible values are `rebalance` and `no_rebalance`. The default is `no_rebalance`. The two attributes (`target_failover.on_deregistration` and `target_failover.on_unhealthy`) can't be set independently. The value you set for both attributes must be the same.

Type: String

Length Constraints: Maximum length of 256.

Pattern: `^[a-zA-Z0-9._]+$`

Required: No

Value

The value of the attribute.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TargetGroupStickinessConfig

Information about the target group stickiness for a rule.

Contents

DurationSeconds

[Application Load Balancers] The time period, in seconds, during which requests from a client should be routed to the same target group. The range is 1-604800 seconds (7 days). You must specify this value when enabling target group stickiness.

Type: Integer

Required: No

Enabled

Indicates whether target group stickiness is enabled.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TargetGroupTuple

Information about how traffic will be distributed between multiple target groups in a forward rule.

Contents

TargetGroupArn

The Amazon Resource Name (ARN) of the target group.

Type: String

Required: No

Weight

The weight. The range is 0 to 999.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TargetHealth

Information about the current health of a target.

Contents

Description

A description of the target health that provides additional details. If the state is `healthy`, a description is not provided.

Type: String

Required: No

Reason

The reason code.

If the target state is `healthy`, a reason code is not provided.

If the target state is `initial`, the reason code can be one of the following values:

- `Elb.RegistrationInProgress` - The target is in the process of being registered with the load balancer.
- `Elb.InitialHealthChecking` - The load balancer is still sending the target the minimum number of health checks required to determine its health status.

If the target state is `unhealthy`, the reason code can be one of the following values:

- `Target.ResponseCodeMismatch` - The health checks did not return an expected HTTP code.
- `Target.Timeout` - The health check requests timed out.
- `Target.FailedHealthChecks` - The load balancer received an error while establishing a connection to the target or the target response was malformed.
- `Elb.InternalError` - The health checks failed due to an internal error.

If the target state is `unused`, the reason code can be one of the following values:

- `Target.NotRegistered` - The target is not registered with the target group.
- `Target.NotInUse` - The target group is not used by any load balancer or the target is in an Availability Zone that is not enabled for its load balancer.

- `Target.InvalidState` - The target is in the stopped or terminated state.
- `Target.IpUnusable` - The target IP address is reserved for use by a load balancer.

If the target state is `draining`, the reason code can be the following value:

- `Target.DeregistrationInProgress` - The target is in the process of being deregistered and the deregistration delay period has not expired.

If the target state is `unavailable`, the reason code can be the following value:

- `Target.HealthCheckDisabled` - Health checks are disabled for the target group.
- `Elb.InternalError` - Target health is unavailable due to an internal error.

Type: String

Valid Values: `Elb.RegistrationInProgress` | `Elb.InitialHealthChecking` | `Target.ResponseCodeMismatch` | `Target.Timeout` | `Target.FailedHealthChecks` | `Target.NotRegistered` | `Target.NotInUse` | `Target.DeregistrationInProgress` | `Target.InvalidState` | `Target.IpUnusable` | `Target.HealthCheckDisabled` | `Elb.InternalError`

Required: No

State

The state of the target.

Type: String

Valid Values: `initial` | `healthy` | `unhealthy` | `unhealthy.draining` | `unused` | `draining` | `unavailable`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

TargetHealthDescription

Information about the health of a target.

Contents

AdministrativeOverride

The administrative override information for the target.

Type: [AdministrativeOverride](#) object

Required: No

AnomalyDetection

The anomaly detection result for the target.

If no anomalies were detected, the result is normal.

If anomalies were detected, the result is anomalous.

Type: [AnomalyDetection](#) object

Required: No

HealthCheckPort

The port to use to connect with the target.

Type: String

Required: No

Target

The description of the target.

Type: [TargetDescription](#) object

Required: No

TargetHealth

The health information for the target.

Type: [TargetHealth](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrustStore

Information about a trust store.

Contents

Name

The name of the trust store.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: $^{\wedge}([a-zA-Z0-9]+-)^*[a-zA-Z0-9]+\$$

Required: No

NumberOfCaCertificates

The number of ca certificates in the trust store.

Type: Integer

Required: No

Status

The current status of the trust store.

Type: String

Valid Values: ACTIVE | CREATING

Required: No

TotalRevokedEntries

The number of revoked certificates in the trust store.

Type: Long

Required: No

TrustStoreArn

The Amazon Resource Name (ARN) of the trust store.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrustStoreAssociation

Information about the resources a trust store is associated with.

Contents

ResourceArn

The Amazon Resource Name (ARN) of the resource.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrustStoreRevocation

Information about a revocation file in use by a trust store.

Contents

NumberOfRevokedEntries

The number of revoked certificates.

Type: Long

Required: No

RevocationId

The revocation ID of the revocation file.

Type: Long

Required: No

RevocationType

The type of revocation file.

Type: String

Valid Values: CRL

Required: No

TrustStoreArn

The Amazon Resource Name (ARN) of the trust store.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UrlRewriteConfig

Information about a URL rewrite transform. This transform matches a pattern in the request URL and replaces it with the specified string.

Contents

Rewrites.member.N

The URL rewrite transform to apply to the request. The transform consists of a regular expression to match and a replacement string.

Type: Array of [RewriteConfig](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ZonalCapacityReservationState

The capacity reservation status for each Availability Zone.

Contents

AvailabilityZone

Information about the Availability Zone.

Type: String

Required: No

EffectiveCapacityUnits

The number of effective capacity units.

Type: Double

Required: No

State

The state of the capacity reservation.

Type: [CapacityReservationStatus](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Error Types

This section lists common error types that this AWS service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

IncompleteSignature

The request signature doesn't conform to AWS standards. Verify that you're using valid AWS credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 400

InternalFailure

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact AWS Support.

HTTP Status Code: 500

InvalidParameterCombination

Parameters that must not be used together were used together. Remove one of the conflicting parameters and try again.

HTTP Status Code: 400

InvalidParameterValue

A value that you provided for a parameter isn't valid. Check the parameter constraints and try again.

HTTP Status Code: 400

InvalidQueryParameter

The AWS query string is malformed or doesn't adhere to AWS standards. Verify the query string format and try again.

HTTP Status Code: 400

MalformedQueryString

The query string contains a syntax error. Verify the query string and try again.

HTTP Status Code: 404

MissingAction

The request is missing the Action parameter. Add the Action parameter and try again.

HTTP Status Code: 400

MissingAuthenticationToken

The request must contain a valid AWS access key ID or X.509 certificate. Verify that your credentials are included in the request.

HTTP Status Code: 403

MissingParameter

A required parameter for the specified action isn't included in the request. Add the missing parameter and try again.

HTTP Status Code: 400

NotAuthorized

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

OptInRequired

Your AWS account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

RequestExpired

The request has expired. This can happen if the request took more than 15 minutes to reach the service, the date stamp is more than 15 minutes in the future, or a pre-signed URL has expired. Generate a new request with a current timestamp and try again.

HTTP Status Code: 400

ServiceUnavailable

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

ThrottlingException

Your request rate is too high. The AWS SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

UnrecognizedClientException

The X.509 certificate or AWS access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

ValidationError

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400