



Welcome

# Amazon Fraud Detector



**API Version 2019-11-15**

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

## Amazon Fraud Detector: Welcome

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

---

# Table of Contents

Welcome .....	1
Actions .....	2
BatchCreateVariable .....	5
Request Syntax .....	5
Request Parameters .....	5
Response Syntax .....	6
Response Elements .....	6
Errors .....	6
See Also .....	7
BatchGetVariable .....	8
Request Syntax .....	8
Request Parameters .....	8
Response Syntax .....	8
Response Elements .....	9
Errors .....	9
See Also .....	10
CancelBatchImportJob .....	11
Request Syntax .....	11
Request Parameters .....	11
Response Elements .....	11
Errors .....	11
See Also .....	12
CancelBatchPredictionJob .....	14
Request Syntax .....	14
Request Parameters .....	14
Response Elements .....	14
Errors .....	14
See Also .....	15
CreateBatchImportJob .....	17
Request Syntax .....	17
Request Parameters .....	17
Response Elements .....	19
Errors .....	19
See Also .....	20

CreateBatchPredictionJob .....	21
Request Syntax .....	21
Request Parameters .....	21
Response Elements .....	23
Errors .....	23
See Also .....	24
CreateDetectorVersion .....	26
Request Syntax .....	26
Request Parameters .....	26
Response Syntax .....	28
Response Elements .....	28
Errors .....	29
See Also .....	30
CreateList .....	31
Request Syntax .....	31
Request Parameters .....	31
Response Elements .....	33
Errors .....	33
See Also .....	33
CreateModel .....	35
Request Syntax .....	35
Request Parameters .....	35
Response Elements .....	36
Errors .....	36
See Also .....	37
CreateModelError .....	39
Request Syntax .....	39
Request Parameters .....	39
Response Syntax .....	41
Response Elements .....	41
Errors .....	42
See Also .....	43
CreateRule .....	44
Request Syntax .....	44
Request Parameters .....	44
Response Syntax .....	46

Response Elements .....	46
Errors .....	46
See Also .....	47
CreateVariable .....	48
Request Syntax .....	48
Request Parameters .....	48
Response Elements .....	50
Errors .....	50
See Also .....	51
DeleteBatchImportJob .....	52
Request Syntax .....	52
Request Parameters .....	52
Response Elements .....	52
Errors .....	52
See Also .....	53
DeleteBatchPredictionJob .....	54
Request Syntax .....	54
Request Parameters .....	54
Response Elements .....	54
Errors .....	54
See Also .....	55
DeleteDetector .....	56
Request Syntax .....	56
Request Parameters .....	56
Response Elements .....	56
Errors .....	56
See Also .....	57
DeleteDetectorVersion .....	59
Request Syntax .....	59
Request Parameters .....	59
Response Elements .....	60
Errors .....	60
See Also .....	61
DeleteEntityType .....	62
Request Syntax .....	62
Request Parameters .....	62

Response Elements .....	62
Errors .....	62
See Also .....	63
DeleteEvent .....	65
Request Syntax .....	65
Request Parameters .....	65
Response Elements .....	66
Errors .....	66
See Also .....	67
DeleteEventsByEventType .....	68
Request Syntax .....	68
Request Parameters .....	68
Response Syntax .....	68
Response Elements .....	68
Errors .....	69
See Also .....	70
DeleteEventType .....	71
Request Syntax .....	71
Request Parameters .....	71
Response Elements .....	71
Errors .....	71
See Also .....	72
DeleteExternalModel .....	74
Request Syntax .....	74
Request Parameters .....	74
Response Elements .....	74
Errors .....	74
See Also .....	75
DeleteLabel .....	77
Request Syntax .....	77
Request Parameters .....	77
Response Elements .....	77
Errors .....	77
See Also .....	78
DeleteList .....	79
Request Syntax .....	79

Request Parameters .....	79
Response Elements .....	79
Errors .....	79
See Also .....	80
<b>DeleteModel .....</b>	<b>82</b>
Request Syntax .....	82
Request Parameters .....	82
Response Elements .....	83
Errors .....	83
See Also .....	84
<b>DeleteModelError .....</b>	<b>85</b>
Request Syntax .....	85
Request Parameters .....	85
Response Elements .....	86
Errors .....	86
See Also .....	87
<b>DeleteOutcome .....</b>	<b>88</b>
Request Syntax .....	88
Request Parameters .....	88
Response Elements .....	88
Errors .....	88
See Also .....	89
<b>DeleteRule .....</b>	<b>91</b>
Request Syntax .....	91
Request Parameters .....	91
Response Elements .....	91
Errors .....	91
See Also .....	92
<b>DeleteVariable .....</b>	<b>94</b>
Request Syntax .....	94
Request Parameters .....	94
Response Elements .....	94
Errors .....	94
See Also .....	95
<b>DescribeDetector .....</b>	<b>97</b>
Request Syntax .....	97

Request Parameters .....	97
Response Syntax .....	98
Response Elements .....	98
Errors .....	99
See Also .....	100
<b>DescribeModelVersions .....</b>	<b>101</b>
Request Syntax .....	101
Request Parameters .....	101
Response Syntax .....	102
Response Elements .....	106
Errors .....	106
See Also .....	107
<b>GetBatchImportJobs .....</b>	<b>109</b>
Request Syntax .....	109
Request Parameters .....	109
Response Syntax .....	110
Response Elements .....	110
Errors .....	111
See Also .....	112
<b>GetBatchPredictionJobs .....</b>	<b>113</b>
Request Syntax .....	113
Request Parameters .....	113
Response Syntax .....	114
Response Elements .....	114
Errors .....	115
See Also .....	116
<b>GetDeleteEventsByEventTypeStatus .....</b>	<b>117</b>
Request Syntax .....	117
Request Parameters .....	117
Response Syntax .....	117
Response Elements .....	117
Errors .....	118
See Also .....	119
<b>GetDetectors .....</b>	<b>120</b>
Request Syntax .....	120
Request Parameters .....	120

Response Syntax .....	121
Response Elements .....	121
Errors .....	122
See Also .....	122
GetDetectorVersion .....	124
Request Syntax .....	124
Request Parameters .....	124
Response Syntax .....	125
Response Elements .....	125
Errors .....	127
See Also .....	128
GetEntityTypes .....	130
Request Syntax .....	130
Request Parameters .....	130
Response Syntax .....	131
Response Elements .....	131
Errors .....	132
See Also .....	132
GetEvent .....	134
Request Syntax .....	134
Request Parameters .....	134
Response Syntax .....	134
Response Elements .....	135
Errors .....	135
See Also .....	136
GetEventPrediction .....	137
Request Syntax .....	137
Request Parameters .....	137
Response Syntax .....	140
Response Elements .....	141
Errors .....	141
See Also .....	142
GetEventPredictionMetadata .....	144
Request Syntax .....	144
Request Parameters .....	144
Response Syntax .....	145

Response Elements .....	147
Errors .....	150
See Also .....	150
GetEventTypes .....	152
Request Syntax .....	152
Request Parameters .....	152
Response Syntax .....	153
Response Elements .....	153
Errors .....	154
See Also .....	155
GetExternalModels .....	156
Request Syntax .....	156
Request Parameters .....	156
Response Syntax .....	157
Response Elements .....	157
Errors .....	158
See Also .....	159
GetKMSEncryptionKey .....	160
Response Syntax .....	160
Response Elements .....	160
Errors .....	160
See Also .....	161
GetLabels .....	162
Request Syntax .....	162
Request Parameters .....	162
Response Syntax .....	163
Response Elements .....	163
Errors .....	164
See Also .....	164
GetListElements .....	166
Request Syntax .....	166
Request Parameters .....	166
Response Syntax .....	167
Response Elements .....	167
Errors .....	168
See Also .....	168

GetListsMetadata .....	170
Request Syntax .....	170
Request Parameters .....	170
Response Syntax .....	171
Response Elements .....	171
Errors .....	172
See Also .....	172
GetModels .....	174
Request Syntax .....	174
Request Parameters .....	174
Response Syntax .....	175
Response Elements .....	175
Errors .....	176
See Also .....	177
GetModelVersion .....	178
Request Syntax .....	178
Request Parameters .....	178
Response Syntax .....	179
Response Elements .....	179
Errors .....	182
See Also .....	182
GetOutcomes .....	184
Request Syntax .....	184
Request Parameters .....	184
Response Syntax .....	185
Response Elements .....	185
Errors .....	186
See Also .....	186
GetRules .....	188
Request Syntax .....	188
Request Parameters .....	188
Response Syntax .....	189
Response Elements .....	190
Errors .....	190
See Also .....	191
GetVariables .....	192

Request Syntax .....	192
Request Parameters .....	192
Response Syntax .....	193
Response Elements .....	193
Errors .....	194
See Also .....	194
<b>ListEventPredictions .....</b>	<b>196</b>
Request Syntax .....	196
Request Parameters .....	196
Response Syntax .....	198
Response Elements .....	198
Errors .....	199
See Also .....	199
<b>ListTagsForResource .....</b>	<b>201</b>
Request Syntax .....	201
Request Parameters .....	201
Response Syntax .....	202
Response Elements .....	202
Errors .....	202
See Also .....	203
<b>PutDetector .....</b>	<b>205</b>
Request Syntax .....	205
Request Parameters .....	205
Response Elements .....	206
Errors .....	206
See Also .....	207
<b>PutEntityType .....</b>	<b>208</b>
Request Syntax .....	208
Request Parameters .....	208
Response Elements .....	209
Errors .....	209
See Also .....	210
<b>PutEventType .....</b>	<b>211</b>
Request Syntax .....	211
Request Parameters .....	211
Response Elements .....	213

Errors .....	213
See Also .....	214
PutExternalModel .....	215
Request Syntax .....	215
Request Parameters .....	215
Response Elements .....	217
Errors .....	217
See Also .....	218
PutKMSEncryptionKey .....	219
Request Syntax .....	219
Request Parameters .....	219
Response Elements .....	219
Errors .....	219
See Also .....	220
PutLabel .....	222
Request Syntax .....	222
Request Parameters .....	222
Response Elements .....	223
Errors .....	223
See Also .....	224
PutOutcome .....	225
Request Syntax .....	225
Request Parameters .....	225
Response Elements .....	226
Errors .....	226
See Also .....	227
SendEvent .....	228
Request Syntax .....	228
Request Parameters .....	228
Response Elements .....	230
Errors .....	230
See Also .....	231
TagResource .....	232
Request Syntax .....	232
Request Parameters .....	232
Response Elements .....	233

Errors .....	233
See Also .....	233
UntagResource .....	235
Request Syntax .....	235
Request Parameters .....	235
Response Elements .....	236
Errors .....	236
See Also .....	236
UpdateDetectorVersion .....	238
Request Syntax .....	238
Request Parameters .....	238
Response Elements .....	240
Errors .....	240
See Also .....	241
UpdateDetectorVersionMetadata .....	243
Request Syntax .....	243
Request Parameters .....	243
Response Elements .....	244
Errors .....	244
See Also .....	245
UpdateDetectorVersionStatus .....	246
Request Syntax .....	246
Request Parameters .....	246
Response Elements .....	247
Errors .....	247
See Also .....	248
UpdateEventLabel .....	249
Request Syntax .....	249
Request Parameters .....	249
Response Elements .....	250
Errors .....	250
See Also .....	251
UpdateList .....	252
Request Syntax .....	252
Request Parameters .....	252
Response Elements .....	254

Errors .....	254
See Also .....	255
UpdateModel .....	256
Request Syntax .....	256
Request Parameters .....	256
Response Elements .....	257
Errors .....	257
See Also .....	258
UpdateModelVersion .....	259
Request Syntax .....	259
Request Parameters .....	259
Response Syntax .....	261
Response Elements .....	261
Errors .....	262
See Also .....	263
UpdateModelVersionStatus .....	264
Request Syntax .....	264
Request Parameters .....	264
Response Elements .....	265
Errors .....	265
See Also .....	266
UpdateRuleMetadata .....	268
Request Syntax .....	268
Request Parameters .....	268
Response Elements .....	268
Errors .....	269
See Also .....	269
UpdateRuleVersion .....	271
Request Syntax .....	271
Request Parameters .....	271
Response Syntax .....	272
Response Elements .....	273
Errors .....	273
See Also .....	274
UpdateVariable .....	275
Request Syntax .....	275

Request Parameters .....	275
Response Elements .....	276
Errors .....	276
See Also .....	277
<b>Data Types .....</b>	<b>278</b>
AggregatedLogOddsMetric .....	281
Contents .....	281
See Also .....	281
AggregatedVariablesImpactExplanation .....	282
Contents .....	282
See Also .....	282
AggregatedVariablesImportanceMetrics .....	284
Contents .....	284
See Also .....	284
AllowDenyList .....	285
Contents .....	285
See Also .....	286
ATIMetricDataPoint .....	287
Contents .....	287
See Also .....	288
ATIModelPerformance .....	289
Contents .....	289
See Also .....	289
ATITrainingMetricsValue .....	290
Contents .....	290
See Also .....	290
BatchCreateVariableError .....	291
Contents .....	291
See Also .....	291
BatchGetVariableError .....	292
Contents .....	292
See Also .....	292
BatchImport .....	293
Contents .....	293
See Also .....	296
BatchPrediction .....	297

Contents .....	297
See Also .....	300
DataValidationMetrics .....	301
Contents .....	301
See Also .....	301
Detector .....	302
Contents .....	302
See Also .....	303
DetectorVersionSummary .....	304
Contents .....	304
See Also .....	305
Entity .....	306
Contents .....	306
See Also .....	306
EntityType .....	307
Contents .....	307
See Also .....	308
EvaluatedExternalModel .....	309
Contents .....	309
See Also .....	309
EvaluatedModelVersion .....	311
Contents .....	311
See Also .....	311
EvaluatedRule .....	313
Contents .....	313
See Also .....	314
Event .....	315
Contents .....	315
See Also .....	316
EventOrchestration .....	317
Contents .....	317
See Also .....	317
EventPredictionSummary .....	318
Contents .....	318
See Also .....	319
EventType .....	320

Contents .....	320
See Also .....	322
EventVariableSummary .....	323
Contents .....	323
See Also .....	323
ExternalEventsDetail .....	324
Contents .....	324
See Also .....	324
ExternalModel .....	325
Contents .....	325
See Also .....	327
ExternalModelOutputs .....	328
Contents .....	328
See Also .....	328
ExternalModelSummary .....	329
Contents .....	329
See Also .....	329
FieldValidationMessage .....	330
Contents .....	330
See Also .....	331
FileValidationMessage .....	332
Contents .....	332
See Also .....	332
FilterCondition .....	333
Contents .....	333
See Also .....	333
IngestedEventsDetail .....	334
Contents .....	334
See Also .....	334
IngestedEventStatistics .....	335
Contents .....	335
See Also .....	336
IngestedEventsTimeWindow .....	337
Contents .....	337
See Also .....	337
KMSKey .....	338

Contents .....	338
See Also .....	338
Label .....	339
Contents .....	339
See Also .....	340
LabelSchema .....	341
Contents .....	341
See Also .....	342
LogOddsMetric .....	343
Contents .....	343
See Also .....	343
MetricDataPoint .....	344
Contents .....	344
See Also .....	345
Model .....	346
Contents .....	346
See Also .....	347
ModelEndpointDataBlob .....	349
Contents .....	349
See Also .....	349
ModelInputConfiguration .....	350
Contents .....	350
See Also .....	351
ModelOutputConfiguration .....	352
Contents .....	352
See Also .....	352
ModelScores .....	353
Contents .....	353
See Also .....	353
ModelVersion .....	354
Contents .....	354
See Also .....	355
ModelVersionDetail .....	356
Contents .....	356
See Also .....	358
ModelVersionEvaluation .....	360

Contents .....	360
See Also .....	360
OFIMetricDataPoint .....	361
Contents .....	361
See Also .....	362
OFIModelPerformance .....	363
Contents .....	363
See Also .....	363
OFITrainingMetricsValue .....	364
Contents .....	364
See Also .....	364
Outcome .....	365
Contents .....	365
See Also .....	366
PredictionExplanations .....	367
Contents .....	367
See Also .....	367
PredictionTimeRange .....	368
Contents .....	368
See Also .....	368
Rule .....	369
Contents .....	369
See Also .....	370
RuleDetail .....	371
Contents .....	371
See Also .....	373
RuleResult .....	374
Contents .....	374
See Also .....	374
Tag .....	375
Contents .....	375
See Also .....	375
TFIMetricDataPoint .....	376
Contents .....	376
See Also .....	377
TFIModelPerformance .....	378

Contents .....	378
See Also .....	378
<b>TFITrainingMetricsValue</b> .....	379
Contents .....	379
See Also .....	379
<b>TrainingDataSchema</b> .....	380
Contents .....	380
See Also .....	380
<b>TrainingMetrics</b> .....	381
Contents .....	381
See Also .....	381
<b>TrainingMetricsV2</b> .....	382
Contents .....	382
See Also .....	382
<b>TrainingResult</b> .....	383
Contents .....	383
See Also .....	383
<b>TrainingResultV2</b> .....	384
Contents .....	384
See Also .....	385
<b>UncertaintyRange</b> .....	386
Contents .....	386
See Also .....	386
<b>Variable</b> .....	387
Contents .....	387
See Also .....	389
<b>VariableEntry</b> .....	390
Contents .....	390
See Also .....	391
<b>VariableImpactExplanation</b> .....	392
Contents .....	392
See Also .....	392
<b>VariableImportanceMetrics</b> .....	394
Contents .....	394
See Also .....	394
<b>Common Parameters</b> .....	395

---

<b>Common Errors .....</b>	<b>398</b>
----------------------------	------------

# Welcome

This is the Amazon Fraud Detector API Reference. This guide is for developers who need detailed information about Amazon Fraud Detector API actions, data types, and errors. For more information about Amazon Fraud Detector features, see the [Amazon Fraud Detector User Guide](#).

We provide the Query API as well as AWS software development kits (SDK) for Amazon Fraud Detector in Java and Python programming languages.

The Amazon Fraud Detector Query API provides HTTPS requests that use the HTTP verb GET or POST and a Query parameter Action. AWS SDK provides libraries, sample code, tutorials, and other resources for software developers who prefer to build applications using language-specific APIs instead of submitting a request over HTTP or HTTPS. These libraries provide basic functions that automatically take care of tasks such as cryptographically signing your requests, retrying requests, and handling error responses, so that it is easier for you to get started. For more information about the AWS SDKs, go to [Tools to build on AWS](#) page, scroll down to the **SDK** section, and choose plus (+) sign to expand the section.

This document was last published on July 18, 2025.

# Actions

The following actions are supported:

- [BatchCreateVariable](#)
- [BatchGetVariable](#)
- [CancelBatchImportJob](#)
- [CancelBatchPredictionJob](#)
- [CreateBatchImportJob](#)
- [CreateBatchPredictionJob](#)
- [CreateDetectorVersion](#)
- [CreateList](#)
- [CreateModel](#)
- [CreateModelVersion](#)
- [CreateRule](#)
- [CreateVariable](#)
- [DeleteBatchImportJob](#)
- [DeleteBatchPredictionJob](#)
- [DeleteDetector](#)
- [DeleteDetectorVersion](#)
- [DeleteEntityType](#)
- [DeleteEvent](#)
- [DeleteEventsByEventType](#)
- [DeleteEventType](#)
- [DeleteExternalModel](#)
- [DeleteLabel](#)
- [DeleteList](#)
- [DeleteModel](#)
- [DeleteModelVersion](#)
- [DeleteOutcome](#)
- [DeleteRule](#)

- [DeleteVariable](#)
- [DescribeDetector](#)
- [DescribeModelVersions](#)
- [GetBatchImportJobs](#)
- [GetBatchPredictionJobs](#)
- [GetDeleteEventsByEventTypeStatus](#)
- [GetDetectors](#)
- [GetDetectorVersion](#)
- [GetEntityTypes](#)
- [GetEvent](#)
- [GetEventPrediction](#)
- [GetEventPredictionMetadata](#)
- [GetEventTypes](#)
- [GetExternalModels](#)
- [GetKMSEncryptionKey](#)
- [GetLabels](#)
- [GetListElements](#)
- [GetListsMetadata](#)
- [GetModels](#)
- [GetModelVersion](#)
- [GetOutcomes](#)
- [GetRules](#)
- [GetVariables](#)
- [ListEventPredictions](#)
- [ListTagsForResource](#)
- [PutDetector](#)
- [PutEntityType](#)
- [PutEventType](#)
- [PutExternalModel](#)
- [PutKMSEncryptionKey](#)

- [PutLabel](#)
- [PutOutcome](#)
- [SendEvent](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateDetectorVersion](#)
- [UpdateDetectorVersionMetadata](#)
- [UpdateDetectorVersionStatus](#)
- [UpdateEventLabel](#)
- [UpdateList](#)
- [UpdateModel](#)
- [UpdateModelVersion](#)
- [UpdateModelVersionStatus](#)
- [UpdateRuleMetadata](#)
- [UpdateRuleVersion](#)
- [UpdateVariable](#)

# BatchCreateVariable

Creates a batch of variables.

## Request Syntax

```
{  
    "tags": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ],  
    "variableEntries": [  
        {  
            "dataSource": "string",  
            "dataType": "string",  
            "defaultValue": "string",  
            "description": "string",  
            "name": "string",  
            "variableType": "string"  
        }  
    ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### tags

A collection of key and value pairs.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

### variableEntries

The list of variables for the batch create variable request.

Type: Array of [VariableEntry](#) objects

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Required: Yes

## Response Syntax

```
{  
    "errors": [  
        {  
            "code": number,  
            "message": "string",  
            "name": "string"  
        }  
    ]  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [errors](#)

Provides the errors for the BatchCreateVariable request.

Type: Array of [BatchCreateVariableError](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

## InternalServerError

An exception indicating an internal server error.

HTTP Status Code: 500

## ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# BatchGetVariable

Gets a batch of variables.

## Request Syntax

```
{  
    "names": [ "string" ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### names

The list of variable names to get.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: Yes

## Response Syntax

```
{  
    "errors": [  
        {  
            "code": number,  
            "message": "string",  
            "name": "string"  
        }  
    ],  
    "variables": [  
        {  
            "arn": "string",  
            "createdTime": "string",  
            "dataSource": "string",  
            "name": "string",  
            "value": "string"  
        }  
    ]  
}
```

```
    "dataType": "string",
    "defaultValue": "string",
    "description": "string",
    "lastUpdatedTime": "string",
    "name": "string",
    "variableType": "string"
}
]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### errors

The errors from the request.

Type: Array of [BatchGetVariableError](#) objects

### variables

The returned variables.

Type: Array of [Variable](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CancelBatchImportJob

Cancels an in-progress batch import job.

## Request Syntax

```
{  
    "jobId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### jobId

The ID of an in-progress batch import job to cancel.

Amazon Fraud Detector will throw an error if the batch import job is in FAILED, CANCELED, or COMPLETED state.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

## InternalServerException

An exception indicating an internal server error.

HTTP Status Code: 500

## ResourceNotFoundException

An exception indicating the specified resource was not found.

HTTP Status Code: 400

## ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CancelBatchPredictionJob

Cancels the specified batch prediction job.

## Request Syntax

```
{  
    "jobId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### jobId

The ID of the batch prediction job to cancel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **InternalServerException**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# CreateBatchImportJob

Creates a batch import job.

## Request Syntax

```
{  
    "eventTypeName": "string",  
    "iamRoleArn": "string",  
    "inputPath": "string",  
    "jobId": "string",  
    "outputPath": "string",  
    "tags": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### eventTypeName

The name of the event type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

### iamRoleArn

The ARN of the IAM role created for Amazon S3 bucket that holds your data file.

The IAM role must have read permissions to your input S3 bucket and write permissions to your output S3 bucket. For more information about bucket permissions, see [User policy examples](#) in the *Amazon S3 User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^arn\aws[a-z-]{0,15}\iam\:[0-9]{12}\role\[^s]{2,64}\$

Required: Yes

### inputPath

The URI that points to the Amazon S3 location of your data file.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: ^s3:\//(.+)\$

Required: Yes

### jobId

The ID of the batch import job. The ID cannot be of a past job, unless the job exists in CREATE\_FAILED state.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

### outputPath

The URI that points to the Amazon S3 location for storing your results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: ^s3:\//(.+)\$

Required: Yes

### **tags**

A collection of key-value pairs associated with this request.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

## **Response Elements**

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## **Errors**

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateBatchPredictionJob

Creates a batch prediction job.

## Request Syntax

```
{  
    "detectorName": "string",  
    "detectorVersion": "string",  
    "eventTypeName": "string",  
    "iamRoleArn": "string",  
    "inputPath": "string",  
    "jobId": "string",  
    "outputPath": "string",  
    "tags": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### detectorName

The name of the detector.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

### detectorVersion

The detector version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 5.

Pattern: ^([1-9][0-9]\*)\$

Required: No

### eventTypeName

The name of the event type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

### iamRoleArn

The ARN of the IAM role to use for this job request.

The IAM Role must have read permissions to your input S3 bucket and write permissions to your output S3 bucket. For more information about bucket permissions, see [User policy examples](#) in the *Amazon S3 User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^arn\aws[a-z-]{0,15}\iam\:[0-9]{12}\role\[^\s]{2,64}\$

Required: Yes

### inputPath

The Amazon S3 location of your training file.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: ^s3:\//(.+)\$

Required: Yes

### jobId

The ID of the batch prediction job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

### outputPath

The Amazon S3 location of your output file.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: ^s3://^(.+)\$

Required: Yes

### tags

A collection of key and value pairs.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

## InternalServerException

An exception indicating an internal server error.

HTTP Status Code: 500

## ResourceNotFoundException

An exception indicating the specified resource was not found.

HTTP Status Code: 400

## ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateDetectorVersion

Creates a detector version. The detector version starts in a DRAFT status.

## Request Syntax

```
{  
    "description": "string",  
    "detectorId": "string",  
    "externalModelEndpoints": [ "string" ],  
    "modelVersions": [  
        {  
            "arn": "string",  
            "modelId": "string",  
            "modelType": "string",  
            "modelVersionNumber": "string"  
        }  
    ],  
    "ruleExecutionMode": "string",  
    "rules": [  
        {  
            "detectorId": "string",  
            "ruleId": "string",  
            "ruleVersion": "string"  
        }  
    ],  
    "tags": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [description](#)

The description of the detector version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### detectorId

The ID of the detector under which you want to create a new version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

### externalModelEndpoints

The Amazon Sagemaker model endpoints to include in the detector version.

Type: Array of strings

Required: No

### modelVersions

The model versions to include in the detector version.

Type: Array of [ModelVersion](#) objects

Required: No

### ruleExecutionMode

The rule execution mode for the rules included in the detector version.

You can define and edit the rule mode at the detector version level, when it is in draft status.

If you specify FIRST\_MATCHED, Amazon Fraud Detector evaluates rules sequentially, first to last, stopping at the first matched rule. Amazon Fraud dectector then provides the outcomes for that single rule.

If you specifiy ALL\_MATCHED, Amazon Fraud Detector evaluates all rules and returns the outcomes for all matched rules.

The default behavior is FIRST\_MATCHED.

Type: String

Valid Values: ALL\_MATCHED | FIRST\_MATCHED

Required: No

### rules

The rules to include in the detector version.

Type: Array of [Rule](#) objects

Required: Yes

### tags

A collection of key and value pairs.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

## Response Syntax

```
{  
  "detectorId": "string",  
  "detectorVersionId": "string",  
  "status": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### detectorId

The ID for the created version's parent detector.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

### detectorVersionId

The ID for the created detector.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 5.

Pattern: ^([1-9][0-9]\*\$)

### status

The status of the detector version.

Type: String

Valid Values: DRAFT | ACTIVE | INACTIVE

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateList

Creates a list.

List is a set of input data for a variable in your event dataset. You use the input data in a rule that's associated with your detector. For more information, see [Lists](#).

## Request Syntax

```
{  
    "description": "string",  
    "elements": [ "string" ],  
    "name": "string",  
    "tags": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ],  
    "variableType": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### description

The description of the list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### elements

The names of the elements, if providing. You can also create an empty list and add elements later using the [UpdateList](#) API.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100000 items.

Length Constraints: Minimum length of 1. Maximum length of 320.

Pattern: `^\$S+( +\$S+)*$`

Required: No

### [name](#)

The name of the list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[\$0-9a-zA-Z_]+$`

Required: Yes

### [tags](#)

A collection of the key and value pairs.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

### [variableType](#)

The variable type of the list. You can only assign the variable type with String data type. For more information, see [Variable types](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[A-Z_]{1,64}$`

Required: No

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### InternalServerError

An exception indicating an internal server error.

HTTP Status Code: 500

### ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

### ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateModel

Creates a model using the specified model type.

## Request Syntax

```
{  
    "description": "string",  
    "eventTypeName": "string",  
    "modelId": "string",  
    "modelType": "string",  
    "tags": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [description](#)

The model description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### [eventTypeName](#)

The name of the event type.

Type: String

Required: Yes

## modelId

The model ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_]+\$

Required: Yes

## modelType

The model type.

Type: String

Valid Values: ONLINE\_FRAUD\_INSIGHTS | TRANSACTION\_FRAUD\_INSIGHTS | ACCOUNT\_TAKEOVER\_INSIGHTS

Required: Yes

## tags

A collection of key and value pairs.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

## InternalServerException

An exception indicating an internal server error.

HTTP Status Code: 500

## ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

# CreateModelVersion

Creates a version of the model using the specified model type and model id.

## Request Syntax

```
{  
    "externalEventsDetail": {  
        "dataAccessRoleArn": "string",  
        "dataLocation": "string"  
    },  
    "ingestedEventsDetail": {  
        "ingestedEventsTimeWindow": {  
            "endTime": "string",  
            "startTime": "string"  
        }  
    },  
    "modelId": "string",  
    "modelType": "string",  
    "tags": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ],  
    "trainingDataSchema": {  
        "labelSchema": {  
            "labelMapper": {  
                "string" : [ "string" ]  
            },  
            "unlabeledEventsTreatment": "string"  
        },  
        "modelVariables": [ "string" ]  
    },  
    "trainingDataSource": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

## externalEventsDetail

Details of the external events data used for model version training. Required if `trainingDataSource` is `EXTERNAL_EVENTS`.

Type: [ExternalEventsDetail](#) object

Required: No

## ingestedEventsDetail

Details of the ingested events data used for model version training. Required if `trainingDataSource` is `INGESTED_EVENTS`.

Type: [IngestedEventsDetail](#) object

Required: No

## modelId

The model ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[0-9a-z_]+$`

Required: Yes

## modelType

The model type.

Type: String

Valid Values: `ONLINE_FRAUD_INSIGHTS` | `TRANSACTION_FRAUD_INSIGHTS` | `ACCOUNT_TAKEOVER_INSIGHTS`

Required: Yes

## tags

A collection of key and value pairs.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

### [trainingDataSchema](#)

The training data schema.

Type: [TrainingDataSchema](#) object

Required: Yes

### [trainingDataSource](#)

The training data source location in Amazon S3.

Type: String

Valid Values: EXTERNAL\_EVENTS | INGESTED\_EVENTS

Required: Yes

## Response Syntax

```
{  
  "modelId": "string",  
  "modelType": "string",  
  "modelVersionNumber": "string",  
  "status": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [modelId](#)

The model ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[0-9a-zA-Z_]+$`

### [modelType](#)

The model type.

Type: String

Valid Values: ONLINE\_FRAUD\_INSIGHTS | TRANSACTION\_FRAUD\_INSIGHTS | ACCOUNT\_TAKEOVER\_INSIGHTS

### [modelVersionNumber](#)

The model version number of the model version created.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 7.

Pattern: `^[1-9][0-9]{0,3}\.[0-9]{1,2}$`

### [status](#)

The model version status.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateRule

Creates a rule for use with the specified detector.

## Request Syntax

```
{  
    "description": "string",  
    "detectorId": "string",  
    "expression": "string",  
    "language": "string",  
    "outcomes": [ "string" ],  
    "ruleId": "string",  
    "tags": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [description](#)

The rule description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### [detectorId](#)

The detector ID for the rule's parent detector.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[0-9a-zA-Z_-]+$`

Required: Yes

### expression

The rule expression.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: Yes

### language

The language of the rule.

Type: String

Valid Values: DETECTORPL

Required: Yes

### outcomes

The outcome or outcomes returned when the rule expression matches.

Type: Array of strings

Array Members: Minimum number of 1 item.

Required: Yes

### ruleId

The rule ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[0-9a-zA-Z_-]+$`

Required: Yes

## tags

A collection of key and value pairs.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

## Response Syntax

```
{
  "rule": {
    "detectorId": "string",
    "ruleId": "string",
    "ruleVersion": "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### rule

The created rule.

Type: [Rule](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **InternalServerException**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateVariable

Creates a variable.

## Request Syntax

```
{  
    "dataSource": "string",  
    "dataType": "string",  
    "defaultValue": "string",  
    "description": "string",  
    "name": "string",  
    "tags": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ],  
    "variableType": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### dataSource

The source of the data.

Type: String

Valid Values: EVENT | MODEL\_SCORE | EXTERNAL\_MODEL\_SCORE

Required: Yes

### dataType

The data type of the variable.

Type: String

Valid Values: STRING | INTEGER | FLOAT | BOOLEAN | DATETIME

Required: Yes

### defaultValue

The default value for the variable when no value is received.

Type: String

Required: Yes

### description

The description.

Type: String

Required: No

### name

The name of the variable.

Type: String

Required: Yes

### tags

A collection of key and value pairs.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

### variableType

The variable type. For more information see [Variable types](#).

Valid Values: AUTH\_CODE | AVS | BILLING\_ADDRESS\_L1 | BILLING\_ADDRESS\_L2  
| BILLING\_CITY | BILLING\_COUNTRY | BILLING\_NAME | BILLING\_PHONE |  
BILLING\_STATE | BILLING\_ZIP | CARD\_BIN | CATEGORICAL | CURRENCY\_CODE

| EMAIL\_ADDRESS | FINGERPRINT | FRAUD\_LABEL | FREE\_FORM\_TEXT |  
IP\_ADDRESS | NUMERIC | ORDER\_ID | PAYMENT\_TYPE | PHONE\_NUMBER | PRICE  
| PRODUCT\_CATEGORY | SHIPPING\_ADDRESS\_L1 | SHIPPING\_ADDRESS\_L2 |  
SHIPPING\_CITY | SHIPPING\_COUNTRY | SHIPPING\_NAME | SHIPPING\_PHONE |  
SHIPPING\_STATE | SHIPPING\_ZIP | USERAGENT

Type: String

Required: No

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### InternalServerError

An exception indicating an internal server error.

HTTP Status Code: 500

### ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

### ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteBatchImportJob

Deletes the specified batch import job ID record. This action does not delete the data that was batch imported.

## Request Syntax

```
{  
    "jobId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### jobId

The ID of the batch import job to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **InternalServerException**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteBatchPredictionJob

Deletes a batch prediction job.

## Request Syntax

```
{  
    "jobId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### jobId

The ID of the batch prediction job to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **InternalServerException**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteDetector

Deletes the detector. Before deleting a detector, you must first delete all detector versions and rule versions associated with the detector.

When you delete a detector, Amazon Fraud Detector permanently deletes the detector and the data is no longer stored in Amazon Fraud Detector.

## Request Syntax

```
{  
    "detectorId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### detectorId

The ID of the detector to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

## ConflictException

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

## InternalServerException

An exception indicating an internal server error.

HTTP Status Code: 500

## ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteDetectorVersion

Deletes the detector version. You cannot delete detector versions that are in ACTIVE status.

When you delete a detector version, Amazon Fraud Detector permanently deletes the detector and the data is no longer stored in Amazon Fraud Detector.

## Request Syntax

```
{  
  "detectorId": "string",  
  "detectorVersionId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [detectorId](#)

The ID of the parent detector for the detector version to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

### [detectorVersionId](#)

The ID of the detector version to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 5.

Pattern: ^([1-9][0-9]\*)\$

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **ConflictException**

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

### **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteEntityType

Deletes an entity type.

You cannot delete an entity type that is included in an event type.

When you delete an entity type, Amazon Fraud Detector permanently deletes that entity type and the data is no longer stored in Amazon Fraud Detector.

## Request Syntax

```
{  
    "name": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### name

The name of the entity type to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-zA-Z\_-]+\$

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

## ConflictException

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

## InternalServerException

An exception indicating an internal server error.

HTTP Status Code: 500

## ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteEvent

Deletes the specified event.

When you delete an event, Amazon Fraud Detector permanently deletes that event and the event data is no longer stored in Amazon Fraud Detector. If `deleteAuditHistory` is `True`, event data is available through search for up to 30 seconds after the delete operation is completed.

## Request Syntax

```
{  
    "deleteAuditHistory": boolean,  
    "eventId": "string",  
    "eventTypeName": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [deleteAuditHistory](#)

Specifies whether or not to delete any predictions associated with the event. If set to `True`,

Type: Boolean

Required: No

### [eventId](#)

The ID of the event to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

## eventTypeName

The name of the event type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteEventsByEventType

Deletes all events of a particular event type.

## Request Syntax

```
{  
  "eventTypeName": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### eventTypeName

The name of the event type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

## Response Syntax

```
{  
  "eventsDeletionStatus": "string",  
  "eventTypeName": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## eventsDeletionStatus

The status of the delete request.

Type: String

## eventTypeName

Name of event type for which to delete the events.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-zA-Z\_-]+\$

# Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **ConflictException**

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

### **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

## ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteEventType

Deletes an event type.

You cannot delete an event type that is used in a detector or a model.

When you delete an event type, Amazon Fraud Detector permanently deletes that event type and the data is no longer stored in Amazon Fraud Detector.

## Request Syntax

```
{  
    "name": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### name

The name of the event type to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-zA-Z\_-]+\$

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

## ConflictException

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

## InternalServerException

An exception indicating an internal server error.

HTTP Status Code: 500

## ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteExternalModel

Removes a SageMaker model from Amazon Fraud Detector.

You can remove an Amazon SageMaker model if it is not associated with a detector version. Removing a SageMaker model disconnects it from Amazon Fraud Detector, but the model remains available in SageMaker.

## Request Syntax

```
{  
    "modelEndpoint": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### modelEndpoint

The endpoint of the Amazon Sagemaker model to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: ^[0-9A-Za-z\_-]+\$

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

## ConflictException

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

## InternalServerException

An exception indicating an internal server error.

HTTP Status Code: 500

## ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## DeleteLabel

Deletes a label.

You cannot delete labels that are included in an event type in Amazon Fraud Detector.

You cannot delete a label assigned to an event ID. You must first delete the relevant event ID.

When you delete a label, Amazon Fraud Detector permanently deletes that label and the data is no longer stored in Amazon Fraud Detector.

## Request Syntax

```
{  
    "name": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### name

The name of the label to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-zA-Z\_-]+\$

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## ConflictException

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

## InternalServerException

An exception indicating an internal server error.

HTTP Status Code: 500

## ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## DeleteList

Deletes the list, provided it is not used in a rule.

When you delete a list, Amazon Fraud Detector permanently deletes that list and the elements in the list.

### Request Syntax

```
{  
    "name": "string"  
}
```

### Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

#### name

The name of the list to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-zA-Z\_]+\$

Required: Yes

### Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

### Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

## ConflictException

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

## InternalServerException

An exception indicating an internal server error.

HTTP Status Code: 500

## ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteModel

Deletes a model.

You can delete models and model versions in Amazon Fraud Detector, provided that they are not associated with a detector version.

When you delete a model, Amazon Fraud Detector permanently deletes that model and the data is no longer stored in Amazon Fraud Detector.

## Request Syntax

```
{  
    "modelId": "string",  
    "modelType": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### modelId

The model ID of the model to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-zA-Z\_]+\$

Required: Yes

### modelType

The model type of the model to delete.

Type: String

Valid Values: ONLINE\_FRAUD\_INSIGHTS | TRANSACTION\_FRAUD\_INSIGHTS | ACCOUNT\_TAKEOVER\_INSIGHTS

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### ConflictException

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

### InternalServerError

An exception indicating an internal server error.

HTTP Status Code: 500

### ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

### ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteModelVersion

Deletes a model version.

You can delete models and model versions in Amazon Fraud Detector, provided that they are not associated with a detector version.

When you delete a model version, Amazon Fraud Detector permanently deletes that model version and the data is no longer stored in Amazon Fraud Detector.

## Request Syntax

```
{  
    "modelId": "string",  
    "modelType": "string",  
    "modelVersionNumber": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [modelId](#)

The model ID of the model version to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-zA-Z\_]+\$

Required: Yes

### [modelType](#)

The model type of the model version to delete.

Type: String

Valid Values: ONLINE\_FRAUD\_INSIGHTS | TRANSACTION\_FRAUD\_INSIGHTS | ACCOUNT\_TAKEOVER\_INSIGHTS

Required: Yes

### **modelVersionNumber**

The model version number of the model version to delete.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 7.

Pattern: ^[1-9][0-9]{0,3}\.[0-9]{1,2}\$

Required: Yes

## **Response Elements**

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## **Errors**

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **ConflictException**

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

### **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

## ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteOutcome

Deletes an outcome.

You cannot delete an outcome that is used in a rule version.

When you delete an outcome, Amazon Fraud Detector permanently deletes that outcome and the data is no longer stored in Amazon Fraud Detector.

## Request Syntax

```
{  
    "name": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### name

The name of the outcome to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-zA-Z\_-]+\$

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

## ConflictException

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

## InternalServerException

An exception indicating an internal server error.

HTTP Status Code: 500

## ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## DeleteRule

Deletes the rule. You cannot delete a rule if it is used by an ACTIVE or INACTIVE detector version.

When you delete a rule, Amazon Fraud Detector permanently deletes that rule and the data is no longer stored in Amazon Fraud Detector.

## Request Syntax

```
{  
    "rule": {  
        "detectorId": "string",  
        "ruleId": "string",  
        "ruleVersion": "string"  
    }  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### rule

A rule.

Type: [Rule](#) object

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

## ConflictException

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

## InternalServerException

An exception indicating an internal server error.

HTTP Status Code: 500

## ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteVariable

Deletes a variable.

You can't delete variables that are included in an event type in Amazon Fraud Detector.

Amazon Fraud Detector automatically deletes model output variables and SageMaker model output variables when you delete the model. You can't delete these variables manually.

When you delete a variable, Amazon Fraud Detector permanently deletes that variable and the data is no longer stored in Amazon Fraud Detector.

## Request Syntax

```
{  
    "name": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### name

The name of the variable to delete.

Type: String

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

## ConflictException

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

## InternalServerException

An exception indicating an internal server error.

HTTP Status Code: 500

## ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DescribeDetector

Gets all versions for a specified detector.

## Request Syntax

```
{  
    "detectorId": "string",  
    "maxResults": number,  
    "nextToken": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### detectorId

The detector ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

### maxResults

The maximum number of results to return for the request.

Type: Integer

Valid Range: Minimum value of 1000. Maximum value of 2500.

Required: No

### nextToken

The next token from the previous response.

Type: String

Required: No

## Response Syntax

```
{  
    "arn": "string",  
    "detectorId": "string",  
    "detectorVersionSummaries": [  
        {  
            "description": "string",  
            "detectorVersionId": "string",  
            "lastUpdatedTime": "string",  
            "status": "string"  
        }  
    ],  
    "nextToken": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### arn

The detector ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^arn\aws[a-z-]{0,15}\frauddetector\:[a-z0-9-]{3,20}\:[0-9]{12}\:[^\s]{2,128}\$

### detectorId

The detector ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

### [detectorVersionSummaries](#)

The status and description for each detector version.

Type: Array of [DetectorVersionSummary](#) objects

### [nextToken](#)

The next token to be used for subsequent requests.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DescribeModelVersions

Gets all of the model versions for the specified model type or for the specified model type and model ID. You can also get details for a single, specified model version.

## Request Syntax

```
{  
    "maxResults": number,  
    "modelId": "string",  
    "modelType": "string",  
    "modelVersionNumber": "string",  
    "nextToken": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### maxResults

The maximum number of results to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 10.

Required: No

### modelId

The model ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_]+\$

Required: No

## [modelType](#)

The model type.

Type: String

Valid Values: ONLINE\_FRAUD\_INSIGHTS | TRANSACTION\_FRAUD\_INSIGHTS | ACCOUNT\_TAKEOVER\_INSIGHTS

Required: No

## [modelVersionNumber](#)

The model version number.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 7.

Pattern: ^[1-9][0-9]{0,3}\.[0-9]{1,2}\$

Required: No

## [nextToken](#)

The next token from the previous results.

Type: String

Required: No

# Response Syntax

```
{  
  "modelVersionDetails": [  
    {  
      "arn": "string",  
      "createdTime": "string",  
      "externalEventsDetail": {  
        "dataAccessRoleArn": "string",  
        "dataLocation": "string"  
      },  
      "ingestedEventsDetail": {  
        "ingestedEventsTimeWindow": {  
          "endTime": "string",  
          "startTime": "string"  
        }  
      }  
    }  
  ]  
}
```

```
        "startTime": "string"
    },
},
"lastUpdatedTime": "string",
"modelId": "string",
"modelType": "string",
"modelVersionNumber": "string",
"status": "string",
"trainingDataSchema": {
    "labelSchema": {
        "labelMapper": {
            "string" : [ "string" ]
        },
        "unlabeledEventsTreatment": "string"
    },
    "modelVariables": [ "string" ]
},
"trainingDataSource": "string",
"trainingResult": {
    "dataValidationMetrics": {
        "fieldLevelMessages": [
            {
                "content": "string",
                "fieldName": "string",
                "identifier": "string",
                "title": "string",
                "type": "string"
            }
        ],
        "fileLevelMessages": [
            {
                "content": "string",
                "title": "string",
                "type": "string"
            }
        ]
    },
    "trainingMetrics": {
        "auc": number,
        "metricDataPoints": [
            {
                "fpr": number,
                "precision": number,
                "threshold": number,
            }
        ]
    }
}
```

```
        "tpr": number
    }
]
},
"variableImportanceMetrics": {
    "logOddsMetrics": [
        {
            "variableImportance": number,
            "variableName": "string",
            "variableType": "string"
        }
    ]
},
"trainingResultV2": {
    "aggregatedVariablesImportanceMetrics": {
        "logOddsMetrics": [
            {
                "aggregatedVariablesImportance": number,
                "variableNames": [ "string" ]
            }
        ]
    },
    "dataValidationMetrics": {
        "fieldLevelMessages": [
            {
                "content": "string",
                "fieldName": "string",
                "identifier": "string",
                "title": "string",
                "type": "string"
            }
        ],
        "fileLevelMessages": [
            {
                "content": "string",
                "title": "string",
                "type": "string"
            }
        ]
    },
    "trainingMetricsV2": {
        "ati": {
            "metricDataPoints": [

```

```
{  
    "adr": number,  
    "atodr": number,  
    "cr": number,  
    "threshold": number  
}  
],  
"modelPerformance": {  
    "asi": number  
}  

```

```
        }
    },
    "variableImportanceMetrics": {
        "logOddsMetrics": [
            {
                "variableImportance": number,
                "variableName": "string",
                "variableType": "string"
            }
        ]
    }
},
"nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [modelVersionDetails](#)

The model version details.

Type: Array of [ModelVersionDetail](#) objects

### [nextToken](#)

The next token.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

## InternalServerException

An exception indicating an internal server error.

HTTP Status Code: 500

## ResourceNotFoundException

An exception indicating the specified resource was not found.

HTTP Status Code: 400

## ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetBatchImportJobs

Gets all batch import jobs or a specific job of the specified ID. This is a paginated API. If you provide a null maxResults, this action retrieves a maximum of 50 records per page. If you provide a maxResults, the value must be between 1 and 50. To get the next page results, provide the pagination token from the GetBatchImportJobsResponse as part of your request. A null pagination token fetches the records from the beginning.

## Request Syntax

```
{  
    "jobId": "string",  
    "maxResults": number,  
    "nextToken": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### jobId

The ID of the batch import job to get.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: No

### maxResults

The maximum number of objects to return for request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

### nextToken

The next token from the previous request.

Type: String

Required: No

## Response Syntax

```
{  
    "batchImports": [  
        {  
            "arn": "string",  
            "completionTime": "string",  
            "eventTypeName": "string",  
            "failedRecordsCount": number,  
            "failureReason": "string",  
            "iamRoleArn": "string",  
            "inputPath": "string",  
            "jobId": "string",  
            "outputPath": "string",  
            "processedRecordsCount": number,  
            "startTime": "string",  
            "status": "string",  
            "totalRecordsCount": number  
        }  
    ],  
    "nextToken": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### batchImports

An array containing the details of each batch import job.

Type: Array of [BatchImport](#) objects

### nextToken

The next token for the subsequent request.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetBatchPredictionJobs

Gets all batch prediction jobs or a specific job if you specify a job ID. This is a paginated API. If you provide a null maxResults, this action retrieves a maximum of 50 records per page. If you provide a maxResults, the value must be between 1 and 50. To get the next page results, provide the pagination token from the GetBatchPredictionJobsResponse as part of your request. A null pagination token fetches the records from the beginning.

## Request Syntax

```
{  
  "jobId": "string",  
  "maxResults": number,  
  "nextToken": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### jobId

The batch prediction job for which to get the details.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: No

### maxResults

The maximum number of objects to return for the request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

## nextToken

The next token from the previous request.

Type: String

Required: No

## Response Syntax

```
{  
    "batchPredictions": [  
        {  
            "arn": "string",  
            "completionTime": "string",  
            "detectorName": "string",  
            "detectorVersion": "string",  
            "eventTypeName": "string",  
            "failureReason": "string",  
            "iamRoleArn": "string",  
            "inputPath": "string",  
            "jobId": "string",  
            "lastHeartbeatTime": "string",  
            "outputPath": "string",  
            "processedRecordsCount": number,  
            "startTime": "string",  
            "status": "string",  
            "totalRecordsCount": number  
        }  
    ],  
    "nextToken": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### batchPredictions

An array containing the details of each batch prediction job.

Type: Array of [BatchPrediction](#) objects

### nextToken

The next token for the subsequent request.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetDeleteEventsByEventTypeStatus

Retrieves the status of a DeleteEventsByEventType action.

## Request Syntax

```
{  
  "eventTypeName": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### eventTypeName

Name of event type for which to get the deletion status.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

## Response Syntax

```
{  
  "eventsDeletionStatus": "string",  
  "eventTypeName": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## eventsDeletionStatus

The deletion status.

Type: String

Valid Values: IN\_PROGRESS\_INITIALIZING | IN\_PROGRESS | CANCEL\_IN\_PROGRESS | CANCELED | COMPLETE | FAILED

## eventTypeName

The event type name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## GetDetectors

Gets all detectors or a single detector if a detectorId is specified. This is a paginated API. If you provide a null maxResults, this action retrieves a maximum of 10 records per page. If you provide a maxResults, the value must be between 5 and 10. To get the next page results, provide the pagination token from the GetDetectorsResponse as part of your request. A null pagination token fetches the records from the beginning.

## Request Syntax

```
{  
  "detectorId": "string",  
  "maxResults": number,  
  "nextToken": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### detectorId

The detector ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: No

### maxResults

The maximum number of objects to return for the request.

Type: Integer

Valid Range: Minimum value of 5. Maximum value of 10.

Required: No

### nextToken

The next token for the subsequent request.

Type: String

Required: No

## Response Syntax

```
{  
  "detectors": [  
    {  
      "arn": "string",  
      "createdTime": "string",  
      "description": "string",  
      "detectorId": "string",  
      "eventTypeName": "string",  
      "lastUpdatedTime": "string"  
    }  
  ],  
  "nextToken": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### detectors

The detectors.

Type: Array of [Detector](#) objects

### nextToken

The next page token.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **InternalServerException**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetDetectorVersion

Gets a particular detector version.

## Request Syntax

```
{  
  "detectorId": "string",  
  "detectorVersionId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### detectorId

The detector ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

### detectorVersionId

The detector version ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 5.

Pattern: ^([1-9][0-9]\*)\$

Required: Yes

## Response Syntax

```
{  
    "arn": "string",  
    "createdTime": "string",  
    "description": "string",  
    "detectorId": "string",  
    "detectorVersionId": "string",  
    "externalModelEndpoints": [ "string" ],  
    "lastUpdatedTime": "string",  
    "modelVersions": [  
        {  
            "arn": "string",  
            "modelId": "string",  
            "modelType": "string",  
            "modelVersionNumber": "string"  
        }  
    ],  
    "ruleExecutionMode": "string",  
    "rules": [  
        {  
            "detectorId": "string",  
            "ruleId": "string",  
            "ruleVersion": "string"  
        }  
    ],  
    "status": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### arn

The detector version ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^arn\aws[a-z-]{0,15}\frauddetector\:[a-z0-9-]{3,20}\:[0-9]{12}\:[^\s]{2,128}\$

### [createdTime](#)

The timestamp when the detector version was created.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

### [description](#)

The detector version description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

### [detectorId](#)

The detector ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

### [detectorVersionId](#)

The detector version ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 5.

Pattern: ^([1-9][0-9]\*)\$

### [externalModelEndpoints](#)

The Amazon SageMaker model endpoints included in the detector version.

Type: Array of strings

### [lastUpdatedTime](#)

The timestamp when the detector version was last updated.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

### **modelVersions**

The model versions included in the detector version.

Type: Array of [ModelVersion](#) objects

### **ruleExecutionMode**

The execution mode of the rule in the detector

FIRST\_MATCHED indicates that Amazon Fraud Detector evaluates rules sequentially, first to last, stopping at the first matched rule. Amazon Fraud detector then provides the outcomes for that single rule.

ALL\_MATCHED indicates that Amazon Fraud Detector evaluates all rules and returns the outcomes for all matched rules. You can define and edit the rule mode at the detector version level, when it is in draft status.

Type: String

Valid Values: ALL\_MATCHED | FIRST\_MATCHED

### **rules**

The rules included in the detector version.

Type: Array of [Rule](#) objects

### **status**

The status of the detector version.

Type: String

Valid Values: DRAFT | ACTIVE | INACTIVE

## **Errors**

For information about the errors that are common to all actions, see [Common Errors](#).

## AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

## InternalServerException

An exception indicating an internal server error.

HTTP Status Code: 500

## ResourceNotFoundException

An exception indicating the specified resource was not found.

HTTP Status Code: 400

## ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetEntityTypes

Gets all entity types or a specific entity type if a name is specified. This is a paginated API. If you provide a null maxResults, this action retrieves a maximum of 10 records per page. If you provide a maxResults, the value must be between 5 and 10. To get the next page results, provide the pagination token from the GetEntityTypesResponse as part of your request. A null pagination token fetches the records from the beginning.

## Request Syntax

```
{  
    "maxResults": number,  
    "name": "string",  
    "nextToken": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### maxResults

The maximum number of objects to return for the request.

Type: Integer

Valid Range: Minimum value of 5. Maximum value of 10.

Required: No

### name

The name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: No

### nextToken

The next token for the subsequent request.

Type: String

Required: No

## Response Syntax

```
{  
    "entityTypes": [  
        {  
            "arn": "string",  
            "createdTime": "string",  
            "description": "string",  
            "lastUpdatedTime": "string",  
            "name": "string"  
        }  
    ],  
    "nextToken": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### entityTypes

An array of entity types.

Type: Array of [EntityType](#) objects

### nextToken

The next page token.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **InternalServerException**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetEvent

Retrieves details of events stored with Amazon Fraud Detector. This action does not retrieve prediction results.

## Request Syntax

```
{  
  "eventId": "string",  
  "eventTypeName": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### eventId

The ID of the event to retrieve.

Type: String

Required: Yes

### eventTypeName

The event type of the event to retrieve.

Type: String

Required: Yes

## Response Syntax

```
{  
  "event": {  
    "currentLabel": "string",  
    "entities": [  
      {  
        "entityType": "string",  
        "label": "string",  
        "score": 123  
      }  
    ]  
  }  
}
```

```
        "entityId": "string",
        "entityType": "string"
    },
],
"eventId": "string",
"eventTimestamp": "string",
"eventTypeName": "string",
"eventVariables": {
    "string" : "string"
},
"labelTimestamp": "string"
}
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### event

The details of the event.

Type: [Event](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

## ResourceNotFoundException

An exception indicating the specified resource was not found.

HTTP Status Code: 400

## ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetEventPrediction

Evaluates an event against a detector version. If a version ID is not provided, the detector's (ACTIVE) version is used.

## Request Syntax

```
{  
    "detectorId": "string",  
    "detectorVersionId": "string",  
    "entities": [  
        {  
            "entityId": "string",  
            "entityType": "string"  
        }  
    ],  
    "eventId": "string",  
    "eventTimestamp": "string",  
    "eventTypeName": "string",  
    "eventVariables": {  
        "string" : "string"  
    },  
    "externalModelEndpointDataBlobs": {  
        "string" : {  
            "byteBuffer": blob,  
            "contentType": "string"  
        }  
    }  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### detectorId

The detector ID.

Type: String

Required: Yes

### [detectorVersionId](#)

The detector version ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 5.

Pattern: ^([1-9][0-9]\*)\$

Required: No

### [entities](#)

The entity type (associated with the detector's event type) and specific entity ID representing who performed the event. If an entity id is not available, use "UNKNOWN."

Type: Array of [Entity](#) objects

Required: Yes

### [eventId](#)

The unique ID used to identify the event.

Type: String

Required: Yes

### [eventTimestamp](#)

Timestamp that defines when the event under evaluation occurred. The timestamp must be specified using ISO 8601 standard in UTC.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 30.

Required: Yes

### [eventTypeName](#)

The event type associated with the detector specified for the prediction.

Type: String

Required: Yes

### eventVariables

Names of the event type's variables you defined in Amazon Fraud Detector to represent data elements and their corresponding values for the event you are sending for evaluation.

#### **⚠ Important**

You must provide at least one eventVariable

To ensure most accurate fraud prediction and to simplify your data preparation, Amazon Fraud Detector will replace all missing variables or values as follows:

#### **For Amazon Fraud Detector trained models:**

If a null value is provided explicitly for a variable or if a variable is missing, model will replace the null value or the missing variable (no variable name in the eventVariables map) with calculated default mean/medians for numeric variables and with special values for categorical variables.

#### **For imported SageMaker models:**

If a null value is provided explicitly for a variable, the model and rules will use "null" as the value. If a variable is not provided (no variable name in the eventVariables map), model and rules will use the default value that is provided for the variable.

Type: String to string map

Map Entries: Maximum number of items.

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Value Length Constraints: Minimum length of 1. Maximum length of 8192.

Required: Yes

### externalModelEndpointDataBlobs

The Amazon SageMaker model endpoint input data blobs.

Type: String to [ModelEndpointDataBlob](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 63.

Key Pattern: ^[0-9A-Za-z\_-]+\$

Required: No

## Response Syntax

```
{  
    "externalModelOutputs": [  
        {  
            "externalModel": {  
                "modelEndpoint": "string",  
                "modelSource": "string"  
            },  
            "outputs": {  
                "string" : "string"  
            }  
        }  
    ],  
    "modelScores": [  
        {  
            "modelVersion": {  
                "arn": "string",  
                "modelId": "string",  
                "modelType": "string",  
                "modelVersionNumber": "string"  
            },  
            "scores": {  
                "string" : number  
            }  
        }  
    ],  
    "ruleResults": [  
        {  
            "outcomes": [ "string" ],  
            "ruleId": "string"  
        }  
    ]  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [externalModelOutputs](#)

The model scores for Amazon SageMaker models.

Type: Array of [ExternalModelOutputs](#) objects

### [modelScores](#)

The model scores. Amazon Fraud Detector generates model scores between 0 and 1000, where 0 is low fraud risk and 1000 is high fraud risk. Model scores are directly related to the false positive rate (FPR). For example, a score of 600 corresponds to an estimated 10% false positive rate whereas a score of 900 corresponds to an estimated 2% false positive rate.

Type: Array of [ModelScores](#) objects

### [ruleResults](#)

The results from the rules.

Type: Array of [RuleResult](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **ConflictException**

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

## **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

## **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

## **ResourceUnavailableException**

An exception indicating that the attached customer-owned (external) model threw an exception when Amazon Fraud Detector invoked the model.

HTTP Status Code: 400

## **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

## **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetEventPredictionMetadata

Gets details of the past fraud predictions for the specified event ID, event type, detector ID, and detector version ID that was generated in the specified time period.

## Request Syntax

```
{  
    "detectorId": "string",  
    "detectorVersionId": "string",  
    "eventId": "string",  
    "eventTypeName": "string",  
    "predictionTimestamp": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### detectorId

The detector ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

### detectorVersionId

The detector version ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 5.

Pattern: ^([1-9][0-9]\*\$)

Required: Yes

## eventId

The event ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

## eventTypeName

The event type associated with the detector specified for the prediction.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

## predictionTimestamp

The timestamp that defines when the prediction was generated. The timestamp must be specified using ISO 8601 standard in UTC.

We recommend calling [ListEventPredictions](#) first, and using the predictionTimestamp value in the response to provide an accurate prediction timestamp value.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: Yes

## Response Syntax

```
{  
  "detectorId": "string",  
  "detectorVersionId": "string",  
  "detectorVersionStatus": "string",  
  "entityId": "string",  
}
```

```
"entityType": "string",
"evaluatedExternalModels": [
  {
    "inputVariables": {
      "string" : "string"
    },
    "modelEndpoint": "string",
    "outputVariables": {
      "string" : "string"
    },
    "useEventVariables": boolean
  }
],
"evaluatedModelVersions": [
  {
    "evaluations": [
      {
        "evaluationScore": "string",
        "outputVariableName": "string",
        "predictionExplanations": {
          "aggregatedVariablesImpactExplanations": [
            {
              "eventVariableNames": [ "string" ],
              "logOddsImpact": number,
              "relativeImpact": "string"
            }
          ],
          "variableImpactExplanations": [
            {
              "eventVariableName": "string",
              "logOddsImpact": number,
              "relativeImpact": "string"
            }
          ]
        }
      }
    ],
    "modelId": "string",
    "modelType": "string",
    "modelVersion": "string"
  }
],
"eventId": "string",
"eventTimestamp": "string",
```

```
"eventType": "string",
"eventVariables": [
  {
    "namesource": "string",
    "value": "string"
  }
],
"outcomes": [ "string" ],
"predictionTimestamp": "string",
"ruleExecutionMode": "string",
"rules": [
  {
    "evaluated": boolean,
    "expression": "string",
    "expressionWithValues": "string",
    "matched": boolean,
    "outcomes": [ "string" ],
    "ruleId": "string",
    "ruleVersion": "string"
  }
]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### detectorId

The detector ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

### detectorVersionId

The detector version ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 5.

Pattern: ^([1-9][0-9]\*\$)

### detectorVersionStatus

The status of the detector version.

Type: String

### entityId

The entity ID.

Type: String

### entityType

The entity type.

Type: String

### evaluatedExternalModels

External (Amazon SageMaker) models that were evaluated for generating predictions.

Type: Array of [EvaluatedExternalModel](#) objects

### evaluatedModelVersions

Model versions that were evaluated for generating predictions.

Type: Array of [EvaluatedModelVersion](#) objects

### eventId

The event ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

### eventTimestamp

The timestamp for when the prediction was generated for the associated event ID.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

### eventTypeName

The event type associated with the detector specified for this prediction.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-zA-Z\_-]+\$

### eventVariables

A list of event variables that influenced the prediction scores.

Type: Array of [EventVariableSummary](#) objects

### outcomes

The outcomes of the matched rule, based on the rule execution mode.

Type: Array of strings

### predictionTimestamp

The timestamp that defines when the prediction was generated.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

### ruleExecutionMode

The execution mode of the rule used for evaluating variable values.

Type: String

Valid Values: ALL\_MATCHED | FIRST\_MATCHED

### rules

List of rules associated with the detector version that were used for evaluating variable values.

Type: Array of [EvaluatedRule](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **InternalServerException**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetEventTypes

Gets all event types or a specific event type if name is provided. This is a paginated API. If you provide a null maxResults, this action retrieves a maximum of 10 records per page. If you provide a maxResults, the value must be between 5 and 10. To get the next page results, provide the pagination token from the GetEventTypesResponse as part of your request. A null pagination token fetches the records from the beginning.

## Request Syntax

```
{  
    "maxResults": number,  
    "name": "string",  
    "nextToken": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### maxResults

The maximum number of objects to return for the request.

Type: Integer

Valid Range: Minimum value of 5. Maximum value of 10.

Required: No

### name

The name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-zA-Z\_-]+\$

Required: No

## nextToken

The next token for the subsequent request.

Type: String

Required: No

## Response Syntax

```
{  
  "eventTypes": [  
    {  
      "arn": "string",  
      "createdTime": "string",  
      "description": "string",  
      "entityTypes": [ "string" ],  
      "eventIngestion": "string",  
      "eventOrchestration": {  
        "eventBridgeEnabled": boolean  
      },  
      "eventVariables": [ "string" ],  
      "ingestedEventStatistics": {  
        "eventDataSizeInBytes": number,  
        "lastUpdatedTime": "string",  
        "leastRecentEvent": "string",  
        "mostRecentEvent": "string",  
        "numberOfEvents": number  
      },  
      "labels": [ "string" ],  
      "lastUpdatedTime": "string",  
      "name": "string"  
    }  
  ],  
  "nextToken": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## eventTypes

An array of event types.

Type: Array of [EventType](#) objects

## nextToken

The next page token.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetExternalModels

Gets the details for one or more Amazon SageMaker models that have been imported into the service. This is a paginated API. If you provide a null maxResults, this actions retrieves a maximum of 10 records per page. If you provide a maxResults, the value must be between 5 and 10. To get the next page results, provide the pagination token from the GetExternalModelsResult as part of your request. A null pagination token fetches the records from the beginning.

## Request Syntax

```
{  
    "maxResults": number,  
    "modelEndpoint": "string",  
    "nextToken": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### maxResults

The maximum number of objects to return for the request.

Type: Integer

Valid Range: Minimum value of 5. Maximum value of 10.

Required: No

### modelEndpoint

The Amazon SageMaker model endpoint.

Type: String

Required: No

### nextToken

The next page token for the request.

Type: String

Required: No

## Response Syntax

```
{  
  "externalModels": [  
    {  
      "arn": "string",  
      "createdTime": "string",  
      "inputConfiguration": {  
        "csvInputTemplate": "string",  
        "eventTypeName": "string",  
        "format": "string",  
        "jsonInputTemplate": "string",  
        "useEventVariables": boolean  
      },  
      "invokeModelEndpointRoleArn": "string",  
      "lastUpdatedTime": "string",  
      "modelEndpoint": "string",  
      "modelEndpointStatus": "string",  
      "modelSource": "string",  
      "outputConfiguration": {  
        "csvIndexToVariableMap": {  
          "string" : "string"  
        },  
        "format": "string",  
        "jsonKeyToVariableMap": {  
          "string" : "string"  
        }  
      }  
    },  
    "nextToken  ]  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## externalModels

Gets the Amazon SageMaker models.

Type: Array of [ExternalModel](#) objects

## nextToken

The next page token to be used in subsequent requests.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetKMSEncryptionKey

Gets the encryption key if a KMS key has been specified to be used to encrypt content in Amazon Fraud Detector.

## Response Syntax

```
{  
  "kmsKey": {  
    "kmsEncryptionKeyArn": "string"  
  }  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### kmsKey

The KMS encryption key.

Type: [KMSKey](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### InternalServerError

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## GetLabels

Gets all labels or a specific label if name is provided. This is a paginated API. If you provide a null maxResults, this action retrieves a maximum of 50 records per page. If you provide a maxResults, the value must be between 10 and 50. To get the next page results, provide the pagination token from the GetGetLabelsResponse as part of your request. A null pagination token fetches the records from the beginning.

## Request Syntax

```
{  
    "maxResults": number,  
    "name": "string",  
    "nextToken": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### maxResults

The maximum number of objects to return for the request.

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 50.

Required: No

### name

The name of the label or labels to get.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: No

### nextToken

The next token for the subsequent request.

Type: String

Required: No

## Response Syntax

```
{  
    "labels": [  
        {  
            "arn": "string",  
            "createdTime": "string",  
            "description": "string",  
            "lastUpdatedTime": "string",  
            "name": "string"  
        }  
    ],  
    "nextToken": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### labels

An array of labels.

Type: Array of [Label](#) objects

### nextToken

The next page token.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **InternalServerException**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetListElements

Gets all the elements in the specified list.

## Request Syntax

```
{  
    "maxResults": number,  
    "name": "string",  
    "nextToken": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### maxResults

The maximum number of objects to return for the request.

Type: Integer

Valid Range: Minimum value of 500. Maximum value of 5000.

Required: No

### name

The name of the list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-zA-Z\_]+\$

Required: Yes

### nextToken

The next token for the subsequent request.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 8192.

Pattern: .\*

Required: No

## Response Syntax

```
{  
  "elements  "nextToken}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### elements

The list elements.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100000 items.

Length Constraints: Minimum length of 1. Maximum length of 320.

Pattern: ^\S+( +\S+)\*\$

### nextToken

The next page token.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 8192.

Pattern: .\*

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **InternalServerException**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetListsMetadata

Gets the metadata of either all the lists under the account or the specified list.

## Request Syntax

```
{  
    "maxResults": number,  
    "name": "string",  
    "nextToken": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### maxResults

The maximum number of objects to return for the request.

Type: Integer

Valid Range: Minimum value of 5. Maximum value of 50.

Required: No

### name

The name of the list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-zA-Z\_]+\$

Required: No

### nextToken

The next token for the subsequent request.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 8192.

Pattern: .\*

Required: No

## Response Syntax

```
{  
  "lists": [  
    {  
      "arn": "string",  
      "createdTime": "string",  
      "description": "string",  
      "name": "string",  
      "updatedTime": "string",  
      "variableType": "string"  
    }  
  ],  
  "nextToken": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### lists

The metadata of the specified list or all lists under the account.

Type: Array of [AllowDenyList](#) objects

### nextToken

The next page token.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 8192.

Pattern: .\*

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### InternalServerError

An exception indicating an internal server error.

HTTP Status Code: 500

### ResourceNotFoundException

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

### ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## GetModels

Gets one or more models. Gets all models for the AWS account if no model type and no model id provided. Gets all models for the AWS account and model type, if the model type is specified but model id is not provided. Gets a specific model if (model type, model id) tuple is specified.

This is a paginated API. If you provide a null maxResults, this action retrieves a maximum of 10 records per page. If you provide a maxResults, the value must be between 1 and 10. To get the next page results, provide the pagination token from the response as part of your request. A null pagination token fetches the records from the beginning.

## Request Syntax

```
{  
    "maxResults": number,  
    "modelId": "string",  
    "modelType": "string",  
    "nextToken": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### maxResults

The maximum number of objects to return for the request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 10.

Required: No

### modelId

The model ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_]+\$

Required: No

### [modelType](#)

The model type.

Type: String

Valid Values: ONLINE\_FRAUD\_INSIGHTS | TRANSACTION\_FRAUD\_INSIGHTS | ACCOUNT\_TAKEOVER\_INSIGHTS

Required: No

### [nextToken](#)

The next token for the subsequent request.

Type: String

Required: No

## Response Syntax

```
{  
  "models": [  
    {  
      "arn": "string",  
      "createdTime": "string",  
      "description": "string",  
      "eventTypeName": "string",  
      "lastUpdatedTime": "string",  
      "modelId": "string",  
      "modelType": "string"  
    }  
  ],  
  "nextToken": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## models

The array of models.

Type: Array of [Model](#) objects

## nextToken

The next page token to be used in subsequent requests.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetModelVersion

Gets the details of the specified model version.

## Request Syntax

```
{  
    "modelId": "string",  
    "modelType": "string",  
    "modelVersionNumber": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### modelId

The model ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_]+\$

Required: Yes

### modelType

The model type.

Type: String

Valid Values: ONLINE\_FRAUD\_INSIGHTS | TRANSACTION\_FRAUD\_INSIGHTS | ACCOUNT\_TAKEOVER\_INSIGHTS

Required: Yes

### modelVersionNumber

The model version number.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 7.

Pattern: ^[1-9][0-9]{0,3}\.[0-9]{1,2}\$

Required: Yes

## Response Syntax

```
{  
    "arn": "string",  
    "externalEventsDetail": {  
        "dataAccessRoleArn": "string",  
        "dataLocation": "string"  
    },  
    "ingestedEventsDetail": {  
        "ingestedEventsTimeWindow": {  
            "endTime": "string",  
            "startTime": "string"  
        }  
    },  
    "modelId": "string",  
    "modelType": "string",  
    "modelVersionNumber": "string",  
    "status": "string",  
    "trainingDataSchema": {  
        "labelSchema": {  
            "labelMapper": {  
                "string" : [ "string" ]  
            },  
            "unlabeledEventsTreatment": "string"  
        },  
        "modelVariables": [ "string" ]  
    },  
    "trainingDataSource": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### arn

The model version ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^arn\aws[a-z-]{0,15}\frauddetector\:[a-z0-9-]{3,20}\:[0-9]{12}\[^\\s]{2,128}\$

### externalEventsDetail

The details of the external events data used for training the model version. This will be populated if the `trainingDataSource` is EXTERNAL\_EVENTS

Type: [ExternalEventsDetail](#) object

### ingestedEventsDetail

The details of the ingested events data used for training the model version. This will be populated if the `trainingDataSource` is INGESTED\_EVENTS.

Type: [IngestedEventsDetail](#) object

### modelId

The model ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_]+\$

### modelType

The model type.

Type: String

Valid Values: ONLINE\_FRAUD\_INSIGHTS | TRANSACTION\_FRAUD\_INSIGHTS | ACCOUNT\_TAKEOVER\_INSIGHTS

## [modelVersionNumber](#)

The model version number.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 7.

Pattern: ^[1-9][0-9]{0,3}\.[0-9]{1,2}\$

## [status](#)

The model version status.

Possible values are:

- TRAINING\_IN\_PROGRESS
- TRAINING\_COMPLETE
- ACTIVATE\_REQUESTED
- ACTIVATE\_IN\_PROGRESS
- ACTIVE
- INACTIVATE\_REQUESTED
- INACTIVATE\_IN\_PROGRESS
- INACTIVE
- ERROR

Type: String

## [trainingDataSchema](#)

The training data schema.

Type: [TrainingDataSchema](#) object

## [trainingDataSource](#)

The training data source.

Type: String

Valid Values: EXTERNAL\_EVENTS | INGESTED\_EVENTS

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **InternalServerException**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetOutcomes

Gets one or more outcomes. This is a paginated API. If you provide a null maxResults, this action retrieves a maximum of 100 records per page. If you provide a maxResults, the value must be between 50 and 100. To get the next page results, provide the pagination token from the GetOutcomesResult as part of your request. A null pagination token fetches the records from the beginning.

## Request Syntax

```
{  
    "maxResults": number,  
    "name": "string",  
    "nextToken": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### maxResults

The maximum number of objects to return for the request.

Type: Integer

Valid Range: Minimum value of 50. Maximum value of 100.

Required: No

### name

The name of the outcome or outcomes to get.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: No

### nextToken

The next page token for the request.

Type: String

Required: No

## Response Syntax

```
{  
    "nextToken": "string",  
    "outcomes": [  
        {  
            "arn": "string",  
            "createdTime": "string",  
            "description": "string",  
            "lastUpdatedTime": "string",  
            "name": "string"  
        }  
    ]  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### nextToken

The next page token for subsequent requests.

Type: String

### outcomes

The outcomes.

Type: Array of [Outcome](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **InternalServerException**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## GetRules

Get all rules for a detector (paginated) if ruleId and ruleVersion are not specified. Gets all rules for the detector and the ruleId if present (paginated). Gets a specific rule if both the ruleId and the ruleVersion are specified.

This is a paginated API. Providing null maxResults results in retrieving maximum of 100 records per page. If you provide maxResults the value must be between 50 and 100. To get the next page result, provide a pagination token from GetRulesResult as part of your request. Null pagination token fetches the records from the beginning.

### Request Syntax

```
{  
    "detectorId": "string",  
    "maxResults": number,  
    "nextToken": "string",  
    "ruleId": "string",  
    "ruleVersion": "string"  
}
```

### Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

#### detectorId

The detector ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

#### maxResults

The maximum number of rules to return for the request.

Type: Integer

Valid Range: Minimum value of 50. Maximum value of 100.

Required: No

### nextToken

The next page token.

Type: String

Required: No

### ruleId

The rule ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: No

### ruleVersion

The rule version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 5.

Pattern: ^([1-9][0-9]\*)\$

Required: No

## Response Syntax

```
{  
    "nextToken": "string",  
    "ruleDetails": [  
        {  
            "arn": "string",  
            "ruleId": "string",  
            "ruleName": "string",  
            "ruleVersion": "string",  
            "ruleType": "string",  
            "status": "string",  
            "version": "string"  
        }  
    ]  
}
```

```
    "createdTime": "string",
    "description": "string",
    "detectorId": "string",
    "expression": "string",
    "language": "string",
    "lastUpdatedTime": "string",
    "outcomes": [ "string" ],
    "ruleId": "string",
    "ruleVersion": "string"
}
]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [nextToken](#)

The next page token to be used in subsequent requests.

Type: String

### [ruleDetails](#)

The details of the requested rule.

Type: Array of [RuleDetail](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

## **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

## **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

## **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

## **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetVariables

Gets all of the variables or the specific variable. This is a paginated API. Providing null maxSizePerPage results in retrieving maximum of 100 records per page. If you provide maxSizePerPage the value must be between 50 and 100. To get the next page result, a provide a pagination token from GetVariablesResult as part of your request. Null pagination token fetches the records from the beginning.

## Request Syntax

```
{  
    "maxResults": number,  
    "name": "string",  
    "nextToken": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### maxResults

The max size per page determined for the get variable request.

Type: Integer

Valid Range: Minimum value of 50. Maximum value of 100.

Required: No

### name

The name of the variable.

Type: String

Required: No

### nextToken

The next page token of the get variable request.

Type: String

Required: No

## Response Syntax

```
{  
    "nextToken": "string",  
    "variables": [  
        {  
            "arn": "string",  
            "createdTime": "string",  
            "dataSource": "string",  
            "dataType": "string",  
            "defaultValue": "string",  
            "description": "string",  
            "lastUpdatedTime": "string",  
            "name": "string",  
            "variableType": "string"  
        }  
    ]  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### nextToken

The next page token to be used in subsequent requests.

Type: String

### variables

The names of the variables returned.

Type: Array of [Variable](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **InternalServerException**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListEventPredictions

Gets a list of past predictions. The list can be filtered by detector ID, detector version ID, event ID, event type, or by specifying a time period. If filter is not specified, the most recent prediction is returned.

For example, the following filter lists all past predictions for xyz event type - { "eventType": { "value": "xyz" } }

This is a paginated API. If you provide a null maxResults, this action will retrieve a maximum of 10 records per page. If you provide a maxResults, the value must be between 50 and 100. To get the next page results, provide the nextToken from the response as part of your request. A null nextToken fetches the records from the beginning.

## Request Syntax

```
{  
    "detectorId": {  
        "value": "string"  
    },  
    "detectorVersionId": {  
        "value": "string"  
    },  
    "eventId": {  
        "value": "string"  
    },  
    "eventType": {  
        "value": "string"  
    },  
    "maxResults": number,  
    "nextToken": "string",  
    "predictionTimeRange": {  
        "endTime": "string",  
        "startTime": "string"  
    }  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### **detectorId**

The detector ID.

Type: [FilterCondition](#) object

Required: No

### **detectorVersionId**

The detector version ID.

Type: [FilterCondition](#) object

Required: No

### **eventId**

The event ID.

Type: [FilterCondition](#) object

Required: No

### **eventType**

The event type associated with the detector.

Type: [FilterCondition](#) object

Required: No

### **maxResults**

The maximum number of predictions to return for the request.

Type: Integer

Valid Range: Minimum value of 50. Maximum value of 100.

Required: No

### **nextToken**

Identifies the next page of results to return. Use the token to make the call again to retrieve the next page. Keep all other arguments unchanged. Each pagination token expires after 24 hours.

Type: String

Required: No

### [predictionTimeRange](#)

The time period for when the predictions were generated.

Type: [PredictionTimeRange](#) object

Required: No

## Response Syntax

```
{  
  "eventPredictionSummaries": [  
    {  
      "detectorId": "string",  
      "detectorVersionId": "string",  
      "eventId": "string",  
      "eventTimestamp": "string",  
      "eventTypeName": "string",  
      "predictionTimestamp": "string"  
    }  
  ],  
  "nextToken": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [eventPredictionSummaries](#)

The summary of the past predictions.

Type: Array of [EventPredictionSummary](#) objects

### [nextToken](#)

Identifies the next page of results to return. Use the token to make the call again to retrieve the next page. Keep all other arguments unchanged. Each pagination token expires after 24 hours.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### InternalServerError

An exception indicating an internal server error.

HTTP Status Code: 500

### ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

### ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListTagsForResource

Lists all tags associated with the resource. This is a paginated API. To get the next page results, provide the pagination token from the response as part of your request. A null pagination token fetches the records from the beginning.

## Request Syntax

```
{  
    "maxResults": number,  
    "nextToken": "string",  
    "resourceARN": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### maxResults

The maximum number of objects to return for the request.

Type: Integer

Valid Range: Fixed value of 50.

Required: No

### nextToken

The next token from the previous results.

Type: String

Required: No

### resourceARN

The ARN that specifies the resource whose tags you want to list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^arn\aws[a-z-]{0,15}\frauddetector\:[a-z0-9-]{3,20}\:[0-9]{12}\:[^\s]{2,128}\$

Required: Yes

## Response Syntax

```
{  
    "nextToken": "string",  
    "tags": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ]  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### nextToken

The next token for subsequent requests.

Type: String

### tags

A collection of key and value pairs.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

## ResourceNotFoundException

An exception indicating the specified resource was not found.

HTTP Status Code: 400

## ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

# PutDetector

Creates or updates a detector.

## Request Syntax

```
{  
    "description": "string",  
    "detectorId": "string",  
    "eventTypeName": "string",  
    "tags": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [description](#)

The description of the detector.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### [detectorId](#)

The detector ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

### [eventTypeName](#)

The name of the event type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-zA-Z\_-]+\$

Required: Yes

### [tags](#)

A collection of key and value pairs.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **ConflictException**

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

### **InternalServerException**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# PutEntityType

Creates or updates an entity type. An entity represents who is performing the event. As part of a fraud prediction, you pass the entity ID to indicate the specific entity who performed the event. An entity type classifies the entity. Example classifications include customer, merchant, or account.

## Request Syntax

```
{  
    "description": "string",  
    "name": "string",  
    "tags": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### description

The description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### name

The name of the entity type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

### tags

A collection of key and value pairs.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **ConflictException**

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

### **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# PutEventType

Creates or updates an event type. An event is a business activity that is evaluated for fraud risk. With Amazon Fraud Detector, you generate fraud predictions for events. An event type defines the structure for an event sent to Amazon Fraud Detector. This includes the variables sent as part of the event, the entity performing the event (such as a customer), and the labels that classify the event. Example event types include online payment transactions, account registrations, and authentications.

## Request Syntax

```
{  
    "description": "string",  
    "entityTypes": [ "string" ],  
    "eventIngestion": "string",  
    "eventOrchestration": {  
        "eventBridgeEnabled": boolean  
    },  
    "eventVariables": [ "string" ],  
    "labels": [ "string" ],  
    "name": "string",  
    "tags": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [description](#)

The description of the event type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### [entityTypes](#)

The entity type for the event type. Example entity types: customer, merchant, account.

Type: Array of strings

Array Members: Minimum number of 1 item.

Required: Yes

### [eventIngestion](#)

Specifies if ingestion is enabled or disabled.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

### [eventOrchestration](#)

Enables or disables event orchestration. If enabled, you can send event predictions to select AWS services for downstream processing of the events.

Type: [EventOrchestration](#) object

Required: No

### [eventVariables](#)

The event type variables.

Type: Array of strings

Array Members: Minimum number of 1 item.

Required: Yes

### [labels](#)

The event type labels.

Type: Array of strings

Required: No

### [name](#)

The name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

### [tags](#)

A collection of key and value pairs.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **ConflictException**

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

### **InternalServerException**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# PutExternalModel

Creates or updates an Amazon SageMaker model endpoint. You can also use this action to update the configuration of the model endpoint, including the IAM role and/or the mapped variables.

## Request Syntax

```
{  
    "inputConfiguration": {  
        "csvInputTemplate": "string",  
        "eventTypeName": "string",  
        "format": "string",  
        "jsonInputTemplate": "string",  
        "useEventVariables": boolean  
    },  
    "invokeModelEndpointRoleArn": "string",  
    "modelEndpoint": "string",  
    "modelEndpointStatus": "string",  
    "modelSource": "string",  
    "outputConfiguration": {  
        "csvIndexToVariableMap": {  
            "string" : "string"  
        },  
        "format": "string",  
        "jsonKeyToVariableMap": {  
            "string" : "string"  
        }  
    },  
    "tags": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

## [inputConfiguration](#)

The model endpoint input configuration.

Type: [ModelInputConfiguration](#) object

Required: Yes

## [invokeModelEndpointRoleArn](#)

The IAM role used to invoke the model endpoint.

Type: String

Required: Yes

## [modelEndpoint](#)

The model endpoints name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: ^[0-9A-Za-z\_-]+\$

Required: Yes

## [modelEndpointStatus](#)

The model endpoint's status in Amazon Fraud Detector.

Type: String

Valid Values: ASSOCIATED | DISSOCIATED

Required: Yes

## [modelSource](#)

The source of the model.

Type: String

Valid Values: SAGEMAKER

Required: Yes

## [outputConfiguration](#)

The model endpoint output configuration.

Type: [ModelOutputConfiguration](#) object

Required: Yes

## [tags](#)

A collection of key and value pairs.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **ConflictException**

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

### **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# PutKMSEncryptionKey

Specifies the KMS key to be used to encrypt content in Amazon Fraud Detector.

## Request Syntax

```
{  
    "kmsEncryptionKeyArn": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### kmsEncryptionKeyArn

The KMS encryption key ARN.

The KMS key must be single-Region key. Amazon Fraud Detector does not support multi-Region KMS key.

Type: String

Length Constraints: Minimum length of 7. Maximum length of 90.

Pattern: ^DEFAULT|arn:[a-zA-Z0-9-]+:kms:[a-zA-Z0-9-]+:\d{12}:key\w{8}-\w{4}-\w{4}-\w{4}-\w{12}\$

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

## ConflictException

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

## InternalServerError

An exception indicating an internal server error.

HTTP Status Code: 500

## ResourceNotFoundException

An exception indicating the specified resource was not found.

HTTP Status Code: 400

## ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# PutLabel

Creates or updates label. A label classifies an event as fraudulent or legitimate. Labels are associated with event types and used to train supervised machine learning models in Amazon Fraud Detector.

## Request Syntax

```
{  
    "description": "string",  
    "name": "string",  
    "tags": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### description

The label description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### name

The label name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

### tags

A collection of key and value pairs.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **ConflictException**

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

### **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# PutOutcome

Creates or updates an outcome.

## Request Syntax

```
{  
    "description": "string",  
    "name": "string",  
    "tags": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### description

The outcome description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### name

The name of the outcome.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

### **tags**

A collection of key and value pairs.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

## **Response Elements**

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## **Errors**

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **ConflictException**

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

### **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# SendEvent

Stores events in Amazon Fraud Detector without generating fraud predictions for those events. For example, you can use SendEvent to upload a historical dataset, which you can then later use to train a model.

## Request Syntax

```
{  
    "assignedLabel": "string",  
    "entities": [  
        {  
            "entityId": "string",  
            "entityType": "string"  
        }  
    ],  
    "eventId": "string",  
    "eventTimestamp": "string",  
    "eventTypeName": "string",  
    "eventVariables": {  
        "string" : "string"  
    },  
    "labelTimestamp": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### assignedLabel

The label to associate with the event. Required if specifying labelTimestamp.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-zA-Z\_-]+\$

Required: No

## entities

An array of entities.

Type: Array of [Entity](#) objects

Required: Yes

## eventId

The event ID to upload.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

## eventTimestamp

The timestamp that defines when the event under evaluation occurred. The timestamp must be specified using ISO 8601 standard in UTC.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 30.

Required: Yes

## eventTypeName

The event type name of the event.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

## eventVariables

Names of the event type's variables you defined in Amazon Fraud Detector to represent data elements and their corresponding values for the event you are sending for evaluation.

Type: String to string map

Map Entries: Maximum number of items.

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Value Length Constraints: Minimum length of 1. Maximum length of 8192.

Required: Yes

### **labelTimestamp**

The timestamp associated with the label. Required if specifying assignedLabel.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 30.

Required: No

## **Response Elements**

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## **Errors**

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **ConflictException**

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

### **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# TagResource

Assigns tags to a resource.

## Request Syntax

```
{  
    "resourceARN": "string",  
    "tags": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### resourceARN

The resource ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^arn\aws[a-z-]{0,15}\frauddetector\:[a-z0-9-]{3,20}\:[0-9]{12}\:[^\s]{2,128}\$

Required: Yes

### tags

The tags to assign to the resource.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### ResourceNotFoundException

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

### ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UntagResource

Removes tags from a resource.

## Request Syntax

```
{  
    "resourceARN": "string",  
    "tagKeys": [ "string" ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### resourceARN

The ARN of the resource from which to remove the tag.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^arn\aws[a-z-]{0,15}\frauddetector\:[a-z0-9-]{3,20}\:[0-9]{12}\:[^\s]{2,128}\$

Required: Yes

### tagKeys

The resource ARN.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^([\p{L}\p{Z}\p{N}\_.:/=+\-@\"]\*)\$

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### ResourceNotFoundException

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

### ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateDetectorVersion

Updates a detector version. The detector version attributes that you can update include models, external model endpoints, rules, rule execution mode, and description. You can only update a DRAFT detector version.

## Request Syntax

```
{  
    "description": "string",  
    "detectorId": "string",  
    "detectorVersionId": "string",  
    "externalModelEndpoints": [ "string" ],  
    "modelVersions": [  
        {  
            "arn": "string",  
            "modelId": "string",  
            "modelType": "string",  
            "modelVersionNumber": "string"  
        }  
    ],  
    "ruleExecutionMode": "string",  
    "rules": [  
        {  
            "detectorId": "string",  
            "ruleId": "string",  
            "ruleVersion": "string"  
        }  
    ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### description

The detector version description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### [detectorId](#)

The parent detector ID for the detector version you want to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

### [detectorVersionId](#)

The detector version ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 5.

Pattern: ^([1-9][0-9]\*\$)

Required: Yes

### [externalModelEndpoints](#)

The Amazon SageMaker model endpoints to include in the detector version.

Type: Array of strings

Required: Yes

### [modelVersions](#)

The model versions to include in the detector version.

Type: Array of [ModelVersion](#) objects

Required: No

### [ruleExecutionMode](#)

The rule execution mode to add to the detector.

If you specify FIRST\_MATCHED, Amazon Fraud Detector evaluates rules sequentially, first to last, stopping at the first matched rule. Amazon Fraud detector then provides the outcomes for that single rule.

If you specify ALL\_MATCHED, Amazon Fraud Detector evaluates all rules and returns the outcomes for all matched rules. You can define and edit the rule mode at the detector version level, when it is in draft status.

The default behavior is FIRST\_MATCHED.

Type: String

Valid Values: ALL\_MATCHED | FIRST\_MATCHED

Required: No

## rules

The rules to include in the detector version.

Type: Array of [Rule](#) objects

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### ConflictException

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

### **InternalServerException**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# UpdateDetectorVersionMetadata

Updates the detector version's description. You can update the metadata for any detector version (DRAFT, ACTIVE, or INACTIVE).

## Request Syntax

```
{  
  "description": "string",  
  "detectorId": "string",  
  "detectorVersionId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [description](#)

The description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

### [detectorId](#)

The detector ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

### [detectorVersionId](#)

The detector version ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 5.

Pattern: ^([1-9][0-9]\*)\$

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### ConflictException

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

### InternalServerError

An exception indicating an internal server error.

HTTP Status Code: 500

### ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

### ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateDetectorVersionStatus

Updates the detector version's status. You can perform the following promotions or demotions using `UpdateDetectorVersionStatus`: DRAFT to ACTIVE, ACTIVE to INACTIVE, and INACTIVE to ACTIVE.

## Request Syntax

```
{  
    "detectorId": "string",  
    "detectorVersionId": "string",  
    "status": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [detectorId](#)

The detector ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

### [detectorVersionId](#)

The detector version ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 5.

Pattern: ^([1-9][0-9]\*)\$

Required: Yes

## **status**

The new status.

Type: String

Valid Values: ACTIVE | INACTIVE

Required: Yes

## **Response Elements**

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## **Errors**

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **ConflictException**

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

### **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

## ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateEventLabel

Updates the specified event with a new label.

## Request Syntax

```
{  
    "assignedLabel": "string",  
    "eventId": "string",  
    "eventTypeName": "string",  
    "labelTimestamp": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### assignedLabel

The new label to assign to the event.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

### eventId

The ID of the event associated with the label to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: Yes

## eventTypeName

The event type of the event associated with the label to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-zA-Z\_-]+\$

Required: Yes

## labelTimestamp

The timestamp associated with the label. The timestamp must be specified using ISO 8601 standard in UTC.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 30.

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### ConflictException

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

## **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

## **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

## **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

## **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateList

Updates a list.

## Request Syntax

```
{  
    "description": "string",  
    "elements": [ "string" ],  
    "name": "string",  
    "updateMode": "string",  
    "variableType": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### description

The new description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### elements

One or more list elements to add or replace. If you are providing the elements, make sure to specify the updateMode to use.

If you are deleting all elements from the list, use REPLACE for the updateMode and provide an empty list (0 elements).

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100000 items.

Length Constraints: Minimum length of 1. Maximum length of 320.

Pattern: `^\$+( +\$+)*$`

Required: No

### name

The name of the list to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[\w{0-9a-z}_]+$`

Required: Yes

### updateMode

The update mode (type).

- Use APPEND if you are adding elements to the list.
- Use REPLACE if you replacing existing elements in the list.
- Use REMOVE if you are removing elements from the list.

Type: String

Valid Values: REPLACE | APPEND | REMOVE

Required: No

### variableType

The variable type you want to assign to the list.

#### Note

You cannot update a variable type of a list that already has a variable type assigned to it. You can assign a variable type to a list only if the list does not already have a variable type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[A-Z\_]{1,64}\$

Required: No

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### ConflictException

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

### InternalServerError

An exception indicating an internal server error.

HTTP Status Code: 500

### ResourceNotFoundException

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateModel

Updates model description.

## Request Syntax

```
{  
    "description": "string",  
    "modelId": "string",  
    "modelType": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [description](#)

The new model description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### [modelId](#)

The model ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_]+\$

Required: Yes

### [modelType](#)

The model type.

Type: String

Valid Values: ONLINE\_FRAUD\_INSIGHTS | TRANSACTION\_FRAUD\_INSIGHTS | ACCOUNT\_TAKEOVER\_INSIGHTS

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### ConflictException

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

### InternalServerError

An exception indicating an internal server error.

HTTP Status Code: 500

### ResourceNotFoundException

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateModelVersion

Updates a model version. Updating a model version retrains an existing model version using updated training data and produces a new minor version of the model. You can update the training data set location and data access role attributes using this action. This action creates and trains a new minor version of the model, for example version 1.01, 1.02, 1.03.

## Request Syntax

```
{
  "externalEventsDetail": {
    "dataAccessRoleArn": "string",
    "dataLocation": "string"
  },
  "ingestedEventsDetail": {
    "ingestedEventsTimeWindow": {
      "endTime": "string",
      "startTime": "string"
    }
  },
  "majorVersionNumber": "string",
  "modelId": "string",
  "modelType": "string",
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [externalEventsDetail](#)

The details of the external events data used for training the model version. Required if `trainingDataSource` is EXTERNAL\_EVENTS.

Type: [ExternalEventsDetail](#) object

Required: No

### [ingestedEventsDetail](#)

The details of the ingested event used for training the model version. Required if your `trainingDataSource` is `INGESTED_EVENTS`.

Type: [IngestedEventsDetail](#) object

Required: No

### [majorVersionNumber](#)

The major version number.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 5.

Pattern: `^([1-9][0-9]*)$`

Required: Yes

### [modelId](#)

The model ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[0-9a-z_]+$`

Required: Yes

### [modelType](#)

The model type.

Type: String

Valid Values: `ONLINE_FRAUD_INSIGHTS` | `TRANSACTION_FRAUD_INSIGHTS` | `ACCOUNT_TAKEOVER_INSIGHTS`

Required: Yes

## tags

A collection of key and value pairs.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

## Response Syntax

```
{  
  "modelId": "string",  
  "modelType": "string",  
  "modelVersionNumber": "string",  
  "status": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### modelId

The model ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_]+\$

### modelType

The model type.

Type: String

Valid Values: ONLINE\_FRAUD\_INSIGHTS | TRANSACTION\_FRAUD\_INSIGHTS | ACCOUNT\_TAKEOVER\_INSIGHTS

## **modelVersionNumber**

The model version number of the model version updated.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 7.

Pattern: ^[1-9][0-9]{0,3}\.[0-9]{1,2}\$

## **status**

The status of the updated model version.

Type: String

# Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **ConflictException**

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

### **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

## ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateModelVersionStatus

Updates the status of a model version.

You can perform the following status updates:

1. Change the TRAINING\_IN\_PROGRESS status to TRAINING\_CANCELLED.
2. Change the TRAINING\_COMPLETE status to ACTIVE.
3. Change ACTIVE to INACTIVE.

## Request Syntax

```
{  
    "modelId": "string",  
    "modelType": "string",  
    "modelVersionNumber": "string",  
    "status": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [modelId](#)

The model ID of the model version to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_]+\$

Required: Yes

### [modelType](#)

The model type.

Type: String

Valid Values: ONLINE\_FRAUD\_INSIGHTS | TRANSACTION\_FRAUD\_INSIGHTS | ACCOUNT\_TAKEOVER\_INSIGHTS

Required: Yes

### **modelVersionNumber**

The model version number.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 7.

Pattern: ^[1-9][0-9]{0,3}\.[0-9]{1,2}\$

Required: Yes

### **status**

The model version status.

Type: String

Valid Values: ACTIVE | INACTIVE | TRAINING\_CANCELLED

Required: Yes

## **Response Elements**

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## **Errors**

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **ConflictException**

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

### **InternalServerException**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateRuleMetadata

Updates a rule's metadata. The description attribute can be updated.

## Request Syntax

```
{  
    "description": "string",  
    "rule": {  
        "detectorId": "string",  
        "ruleId": "string",  
        "ruleVersion": "string"  
    }  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [description](#)

The rule description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

### [rule](#)

The rule to update.

Type: [Rule](#) object

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **ConflictException**

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

### **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

### **ValidationException**

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateRuleVersion

Updates a rule version resulting in a new rule version. Updates a rule version resulting in a new rule version (version 1, 2, 3 ...).

## Request Syntax

```
{  
    "description": "string",  
    "expression": "string",  
    "language": "string",  
    "outcomes": [ "string" ],  
    "rule": {  
        "detectorId": "string",  
        "ruleId": "string",  
        "ruleVersion": "string"  
    },  
    "tags": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [description](#)

The description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### [expression](#)

The rule expression.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: Yes

### language

The language.

Type: String

Valid Values: DETECTORPL

Required: Yes

### outcomes

The outcomes.

Type: Array of strings

Array Members: Minimum number of 1 item.

Required: Yes

### rule

The rule to update.

Type: [Rule](#) object

Required: Yes

### tags

The tags to assign to the rule version.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

## Response Syntax

```
{
```

```
"rule": {  
    "detectorId": "string",  
    "ruleId": "string",  
    "ruleVersion": "string"  
}  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### rule

The new rule version that was created.

Type: [Rule](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **ConflictException**

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

### **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

## ResourceNotFoundException

An exception indicating the specified resource was not found.

HTTP Status Code: 400

## ThrottlingException

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateVariable

Updates a variable.

## Request Syntax

```
{  
    "defaultValue": "string",  
    "description": "string",  
    "name": "string",  
    "variableType": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### defaultValue

The new default value of the variable.

Type: String

Required: No

### description

The new description.

Type: String

Required: No

### name

The name of the variable.

Type: String

Required: Yes

## variableType

The variable type. For more information see [Variable types](#).

Type: String

Required: No

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

An exception indicating Amazon Fraud Detector does not have the needed permissions. This can occur if you submit a request, such as PutExternalModel, that specifies a role that is not in your account.

HTTP Status Code: 400

### **ConflictException**

An exception indicating there was a conflict during a delete operation.

HTTP Status Code: 400

### **InternalServerError**

An exception indicating an internal server error.

HTTP Status Code: 500

### **ResourceNotFoundException**

An exception indicating the specified resource was not found.

HTTP Status Code: 400

### **ThrottlingException**

An exception indicating a throttling error.

HTTP Status Code: 400

## ValidationException

An exception indicating a specified value is not allowed.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# Data Types

The Amazon Fraud Detector API contains several data types that various actions use. This section describes each data type in detail.

 **Note**

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AggregatedLogOddsMetric](#)
- [AggregatedVariablesImpactExplanation](#)
- [AggregatedVariablesImportanceMetrics](#)
- [AllowDenyList](#)
- [ATIMetricDataPoint](#)
- [ATIModelPerformance](#)
- [ATITrainingMetricsValue](#)
- [BatchCreateVariableError](#)
- [BatchGetVariableError](#)
- [BatchImport](#)
- [BatchPrediction](#)
- [DataValidationMetrics](#)
- [Detector](#)
- [DetectorVersionSummary](#)
- [Entity](#)
- [EntityType](#)
- [EvaluatedExternalModel](#)
- [EvaluatedModelVersion](#)
- [EvaluatedRule](#)
- [Event](#)

- [EventOrchestration](#)
- [EventPredictionSummary](#)
- [EventType](#)
- [EventVariableSummary](#)
- [ExternalEventsDetail](#)
- [ExternalModel](#)
- [ExternalModelOutputs](#)
- [ExternalModelSummary](#)
- [FieldValidationMessage](#)
- [FileValidationMessage](#)
- [FilterCondition](#)
- [IngestedEventsDetail](#)
- [IngestedEventStatistics](#)
- [IngestedEventsTimeWindow](#)
- [KMSKey](#)
- [Label](#)
- [LabelSchema](#)
- [LogOddsMetric](#)
- [MetricDataPoint](#)
- [Model](#)
- [ModelEndpointDataBlob](#)
- [ModelInputConfiguration](#)
- [ModelOutputConfiguration](#)
- [ModelScores](#)
- [ModelVersion](#)
- [ModelVersionDetail](#)
- [ModelVersionEvaluation](#)
- [OFIMetricDataPoint](#)
- [OFIModelPerformance](#)
- [OFITrainingMetricsValue](#)

- [Outcome](#)
- [PredictionExplanations](#)
- [PredictionTimeRange](#)
- [Rule](#)
- [RuleDetail](#)
- [RuleResult](#)
- [Tag](#)
- [TFIMetricDataPoint](#)
- [TFIModelPerformance](#)
- [TFITrainingMetricsValue](#)
- [TrainingDataSchema](#)
- [TrainingMetrics](#)
- [TrainingMetricsV2](#)
- [TrainingResult](#)
- [TrainingResultV2](#)
- [UncertaintyRange](#)
- [Variable](#)
- [VariableEntry](#)
- [VariableImpactExplanation](#)
- [VariableImportanceMetrics](#)

# AggregatedLogOddsMetric

The log odds metric details.

Account Takeover Insights (ATI) model uses event variables from the login data you provide to continuously calculate a set of variables (aggregated variables) based on historical events. For example, your ATI model might calculate the number of times an user has logged in using the same IP address. In this case, event variables used to derive the aggregated variables are IP address and user.

## Contents

### aggregatedVariablesImportance

The relative importance of the variables in the list to the other event variable.

Type: Float

Required: Yes

### variableNames

The names of all the variables.

Type: Array of strings

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# AggregatedVariablesImpactExplanation

The details of the impact of aggregated variables on the prediction score.

Account Takeover Insights (ATI) model uses the login data you provide to continuously calculate a set of variables (aggregated variables) based on historical events. For example, the model might calculate the number of times an user has logged in using the same IP address. In this case, event variables used to derive the aggregated variables are IP address and user.

## Contents

### eventVariableNames

The names of all the event variables that were used to derive the aggregated variables.

Type: Array of strings

Required: No

### logOddsImpact

The raw, uninterpreted value represented as log-odds of the fraud. These values are usually between -10 to +10, but range from -infinity to +infinity.

- A positive value indicates that the variables drove the risk score up.
- A negative value indicates that the variables drove the risk score down.

Type: Float

Required: No

### relativeImpact

The relative impact of the aggregated variables in terms of magnitude on the prediction scores.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# AggregatedVariablesImportanceMetrics

The details of the relative importance of the aggregated variables.

Account Takeover Insights (ATI) model uses event variables from the login data you provide to continuously calculate a set of variables (aggregated variables) based on historical events. For example, your ATI model might calculate the number of times an user has logged in using the same IP address. In this case, event variables used to derive the aggregated variables are IP address and user.

## Contents

### logOddsMetrics

List of variables' metrics.

Type: Array of [AggregatedLogOddsMetric](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# AllowDenyList

The metadata of a list.

## Contents

### **name**

The name of the list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-zA-Z\_]+\$

Required: Yes

### **arn**

The ARN of the list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^arn\aws[a-zA-Z]{0,15}\frauddetector\:[a-zA-Z0-9-]{3,20}\:[0-9]{12}\:[^\s]{2,128}\$

Required: No

### **createdTime**

The time the list was created.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

### **description**

The description of the list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### **updatedTime**

The time the list was last updated.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

### **variableType**

The variable type of the list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[A-Z\_]{1,64}\$

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ATIMetricDataPoint

The Account Takeover Insights (ATI) model performance metrics data points.

## Contents

### adr

The anomaly discovery rate. This metric quantifies the percentage of anomalies that can be detected by the model at the selected score threshold. A lower score threshold increases the percentage of anomalies captured by the model, but would also require challenging a larger percentage of login events, leading to a higher customer friction.

Type: Float

Required: No

### atodr

The account takeover discovery rate. This metric quantifies the percentage of account compromise events that can be detected by the model at the selected score threshold. This metric is only available if 50 or more entities with at-least one labeled account takeover event is present in the ingested dataset.

Type: Float

Required: No

### cr

The challenge rate. This indicates the percentage of login events that the model recommends to challenge such as one-time password, multi-factor authentication, and investigations.

Type: Float

Required: No

### threshold

The model's threshold that specifies an acceptable fraud capture rate. For example, a threshold of 500 means any model score 500 or above is labeled as fraud.

Type: Float

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ATIModelPerformance

The Account Takeover Insights (ATI) model performance score.

## Contents

### asi

The anomaly separation index (ASI) score. This metric summarizes the overall ability of the model to separate anomalous activities from the normal behavior. Depending on the business, a large fraction of these anomalous activities can be malicious and correspond to the account takeover attacks. A model with no separability power will have the lowest possible ASI score of 0.5, whereas a model with a high separability power will have the highest possible ASI score of 1.0

Type: Float

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ATITrainingMetricsValue

The Account Takeover Insights (ATI) model training metric details.

## Contents

### **metricDataPoints**

The model's performance metrics data points.

Type: Array of [ATIMetricDataPoint](#) objects

Required: No

### **modelPerformance**

The model's overall performance scores.

Type: [ATIModelPerformance](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# BatchCreateVariableError

Provides the error of the batch create variable API.

## Contents

### code

The error code.

Type: Integer

Required: No

### message

The error message.

Type: String

Required: No

### name

The name.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# BatchGetVariableError

Provides the error of the batch get variable API.

## Contents

### code

The error code.

Type: Integer

Required: No

### message

The error message.

Type: String

Required: No

### name

The error name.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# BatchImport

The batch import job details.

## Contents

### arn

The ARN of the batch import job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^arn\aws[a-z-]{0,15}\frauddetector\:[a-z0-9-]{3,20}\:[0-9]{12}\:[^\s]{2,128}\$

Required: No

### completionTime

Timestamp of when batch import job completed.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

### eventTypeName

The name of the event type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: No

### failedRecordsCount

The number of records that failed to import.

Type: Integer

Required: No

### **failureReason**

The reason batch import job failed.

Type: String

Required: No

### **iamRoleArn**

The ARN of the IAM role to use for this job request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^arn\aws[a-z-]{0,15}\iam\:[0-9]{12}\role\[^s]{2,64}\$

Required: No

### **inputPath**

The Amazon S3 location of your data file for batch import.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: ^s3:\//(.+)\$

Required: No

### **jobId**

The ID of the batch import job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: No

**outputPath**

The Amazon S3 location of your output file.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: ^s3://^(.+)\$

Required: No

**processedRecordsCount**

The number of records processed by batch import job.

Type: Integer

Required: No

**startTime**

Timestamp of when the batch import job started.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

**status**

The status of the batch import job.

Type: String

Valid Values: IN\_PROGRESS\_INITIALIZING | IN\_PROGRESS | CANCEL\_IN\_PROGRESS | CANCELED | COMPLETE | FAILED

Required: No

**totalRecordsCount**

The total number of records in the batch import job.

Type: Integer

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# BatchPrediction

The batch prediction details.

## Contents

### arn

The ARN of batch prediction job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^arn\aws[a-z-]{0,15}\frauddetector\:[a-z0-9-]{3,20}\:[0-9]{12}\:[^\s]{2,128}\$

Required: No

### completionTime

Timestamp of when the batch prediction job completed.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

### detectorName

The name of the detector.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: No

### detectorVersion

The detector version.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 7.

Pattern: ^[1-9][0-9]{0,3}\.[0-9]{1,2}\$

Required: No

### **eventTypeName**

The name of the event type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: No

### **failureReason**

The reason a batch prediction job failed.

Type: String

Required: No

### **iamRoleArn**

The ARN of the IAM role to use for this job request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^arn\aws[a-z-]{0,15}\iam\:[0-9]{12}\role\[^s]{2,64}\$

Required: No

### **inputPath**

The Amazon S3 location of your training file.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: ^s3://( .+)\$

Required: No

### **jobId**

The job ID for the batch prediction.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: No

### **lastHeartbeatTime**

Timestamp of most recent heartbeat indicating the batch prediction job was making progress.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

### **outputPath**

The Amazon S3 location of your output file.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: ^s3://( .+)\$

Required: No

### **processedRecordsCount**

The number of records processed by the batch prediction job.

Type: Integer

Required: No

**startTime**

Timestamp of when the batch prediction job started.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

**status**

The batch prediction status.

Type: String

Valid Values: IN\_PROGRESS\_INITIALIZING | IN\_PROGRESS | CANCEL\_IN\_PROGRESS | CANCELED | COMPLETE | FAILED

Required: No

**totalRecordsCount**

The total number of records in the batch prediction job.

Type: Integer

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DataValidationMetrics

The model training data validation metrics.

## Contents

### **fieldLevelMessages**

The field-specific model training validation messages.

Type: Array of [FieldValidationMessage](#) objects

Required: No

### **fileLevelMessages**

The file-specific model training data validation messages.

Type: Array of [FileValidationMessage](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Detector

The detector.

## Contents

### arn

The detector ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^arn\aws[a-z-]{0,15}\frauddetector\:[a-z0-9-]{3,20}\:[0-9]{12}\:[^\s]{2,128}\$

Required: No

### createdTime

Timestamp of when the detector was created.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

### description

The detector description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### detectorId

The detector ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[0-9a-zA-Z_-]+$`

Required: No

### **eventTypeName**

The name of the event type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[0-9a-zA-Z_-]+$`

Required: No

### **lastUpdatedTime**

Timestamp of when the detector was last updated.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DetectorVersionSummary

The summary of the detector version.

## Contents

### **description**

The detector version description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### **detectorVersionId**

The detector version ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 5.

Pattern: ^([1-9][0-9]\*\$)

Required: No

### **lastUpdatedTime**

Timestamp of when the detector version was last updated.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

### **status**

The detector version status.

Type: String

Valid Values: DRAFT | ACTIVE | INACTIVE

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Entity

The entity details.

## Contents

### entityId

The entity ID. If you do not know the entityId, you can pass unknown, which is a reserved string literal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^[0-9A-Za-z\_.@+-]+\$

Required: Yes

### entityType

The entity type.

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# EntityType

The entity type details.

## Contents

### arn

The entity type ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^arn\aws[a-z-]{0,15}\frauddetector\:[a-z0-9-]{3,20}\:[0-9]{12}\:[^\s]{2,128}\$

Required: No

### createdTime

Timestamp of when the entity type was created.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

### description

The entity type description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### lastUpdatedTime

Timestamp of when the entity type was last updated.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

### **name**

The entity type name.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# EvaluatedExternalModel

The details of the external (Amazon Sagemaker) model evaluated for generating predictions.

## Contents

### **inputVariables**

Input variables use for generating predictions.

Type: String to string map

Required: No

### **modelEndpoint**

The endpoint of the external (Amazon Sagemaker) model.

Type: String

Required: No

### **outputVariables**

Output variables.

Type: String to string map

Required: No

### **useEventVariables**

Indicates whether event variables were used to generate predictions.

Type: Boolean

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# EvaluatedModelVersion

The model version evaluated for generating prediction.

## Contents

### **evaluations**

Evaluations generated for the model version.

Type: Array of [ModelVersionEvaluation](#) objects

Required: No

### **modelId**

The model ID.

Type: String

Required: No

### **modelType**

The model type.

Valid values: ONLINE\_FRAUD\_INSIGHTS | TRANSACTION\_FRAUD\_INSIGHTS

Type: String

Required: No

### **modelVersion**

The model version.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# EvaluatedRule

The details of the rule used for evaluating variable values.

## Contents

### **evaluated**

Indicates whether the rule was evaluated.

Type: Boolean

Required: No

### **expression**

The rule expression.

Type: String

Required: No

### **expressionWithValues**

The rule expression value.

Type: String

Required: No

### **matched**

Indicates whether the rule matched.

Type: Boolean

Required: No

### **outcomes**

The rule outcome.

Type: Array of strings

Required: No

**ruleId**

The rule ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-zA-Z\_-]+\$

Required: No

**ruleVersion**

The rule version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 5.

Pattern: ^([1-9][0-9]\*\$)

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Event

The event details.

## Contents

### **currentLabel**

The label associated with the event.

Type: String

Required: No

### **entities**

The event entities.

Type: Array of [Entity](#) objects

Required: No

### **eventId**

The event ID.

Type: String

Required: No

### **eventTimestamp**

The timestamp that defines when the event under evaluation occurred. The timestamp must be specified using ISO 8601 standard in UTC.

Type: String

Required: No

### **eventTypeName**

The event type.

Type: String

Required: No

## eventVariables

Names of the event type's variables you defined in Amazon Fraud Detector to represent data elements and their corresponding values for the event you are sending for evaluation.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Value Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

## labelTimestamp

The timestamp associated with the label to update. The timestamp must be specified using ISO 8601 standard in UTC.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# EventOrchestration

The event orchestration status.

## Contents

### **eventBridgeEnabled**

Specifies if event orchestration is enabled through Amazon EventBridge.

Type: Boolean

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# EventPredictionSummary

Information about the summary of an event prediction.

## Contents

### **detectorId**

The detector ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-zA-Z\_-]+\$

Required: No

### **detectorVersionId**

The detector version ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 5.

Pattern: ^([1-9][0-9]\*\$)

Required: No

### **eventId**

The event ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-zA-Z\_-]+\$

Required: No

### **eventTimestamp**

The timestamp of the event.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

### **eventTypeName**

The event type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-zA-Z\_-]+\$

Required: No

### **predictionTimestamp**

The timestamp when the prediction was generated.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# EventType

The event type details.

## Contents

### arn

The entity type ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^arn\aws[a-z-]{0,15}\frauddetector\:[a-z0-9-]{3,20}\:[0-9]{12}\:[^\s]{2,128}\$

Required: No

### createdTime

Timestamp of when the event type was created.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

### description

The event type description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### entityTypes

The event type entity types.

Type: Array of strings

Array Members: Minimum number of 1 item.

Required: No

### **eventIngestion**

If Enabled, Amazon Fraud Detector stores event data when you generate a prediction and uses that data to update calculated variables in near real-time. Amazon Fraud Detector uses this data, known as INGESTED\_EVENTS, to train your model and improve fraud predictions.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

### **eventOrchestration**

The event orchestration status.

Type: [EventOrchestration](#) object

Required: No

### **eventVariables**

The event type event variables.

Type: Array of strings

Required: No

### **ingestedEventStatistics**

Data about the stored events.

Type: [IngestedEventStatistics](#) object

Required: No

### **labels**

The event type labels.

Type: Array of strings

Required: No

## lastUpdatedTime

Timestamp of when the event type was last updated.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

## name

The event type name.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# EventVariableSummary

Information about the summary of an event variable that was evaluated for generating prediction.

## Contents

### **name**

The event variable name.

Type: String

Required: No

### **source**

The event variable source.

Type: String

Required: No

### **value**

The value of the event variable.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ExternalEventsDetail

Details for the external events data used for model version training.

## Contents

### **dataAccessRoleArn**

The ARN of the role that provides Amazon Fraud Detector access to the data location.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^arn\aws[a-z-]{0,15}\iam\:[0-9]{12}\role\[^s]{2,64}\$

Required: Yes

### **dataLocation**

The Amazon S3 bucket location for the data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: ^s3:\//(.+)\$

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ExternalModel

The Amazon SageMaker model.

## Contents

### arn

The model ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^arn\aws[a-z-]{0,15}\frauddetector\:[a-z0-9-]{3,20}\:[0-9]{12}\:[^\s]{2,128}\$

Required: No

### createdTime

Timestamp of when the model was last created.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

### inputConfiguration

The input configuration.

Type: [ModelInputConfiguration](#) object

Required: No

### invokeModelEndpointRoleArn

The role used to invoke the model.

Type: String

Required: No

**lastUpdatedTime**

Timestamp of when the model was last updated.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

**modelEndpoint**

The Amazon SageMaker model endpoints.

Type: String

Required: No

**modelEndpointStatus**

The Amazon Fraud Detector status for the external model endpoint

Type: String

Valid Values: ASSOCIATED | DISSOCIATED

Required: No

**modelSource**

The source of the model.

Type: String

Valid Values: SAGEMAKER

Required: No

**outputConfiguration**

The output configuration.

Type: [ModelOutputConfiguration](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ExternalModelOutputs

The fraud prediction scores from Amazon SageMaker model.

## Contents

### externalModel

The Amazon SageMaker model.

Type: [ExternalModelSummary](#) object

Required: No

### outputs

The fraud prediction scores from Amazon SageMaker model.

Type: String to string map

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ExternalModelSummary

The Amazon SageMaker model.

## Contents

### **modelEndpoint**

The endpoint of the Amazon SageMaker model.

Type: String

Required: No

### **modelSource**

The source of the model.

Type: String

Valid Values: SAGEMAKER

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# FieldValidationMessage

The message details.

## Contents

### content

The message content.

Type: String

Required: No

### fieldName

The field name.

Type: String

Required: No

### identifier

The message ID.

Type: String

Required: No

### title

The message title.

Type: String

Required: No

### type

The message type.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# FileValidationMessage

The message details.

## Contents

### **content**

The message content.

Type: String

Required: No

### **title**

The message title.

Type: String

Required: No

### **type**

The message type.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# FilterCondition

A conditional statement for filtering a list of past predictions.

## Contents

### value

A statement containing a resource property and a value to specify filter condition.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^[0-9A-Za-z\_-]+\$

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# IngestedEventsDetail

The details of the ingested event.

## Contents

### ingestedEventsTimeWindow

The start and stop time of the ingested events.

Type: [IngestedEventsTimeWindow](#) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# IngestedEventStatistics

Data about the stored events.

## Contents

### **eventDataSizeInBytes**

The total size of the stored events.

Type: Long

Required: No

### **lastUpdatedTime**

Timestamp of when the stored event was last updated.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

### **leastRecentEvent**

The oldest stored event.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

### **mostRecentEvent**

The newest stored event.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

### **numberOfEvents**

The number of stored events.

Type: Long

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# IngestedEventsTimeWindow

The start and stop time of the ingested events.

## Contents

### **endTime**

Timestamp of the final ingested event.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: Yes

### **startTime**

Timestamp of the first ingested event.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# KMSKey

The KMS key details.

## Contents

### kmsEncryptionKeyArn

The encryption key ARN.

Type: String

Length Constraints: Minimum length of 7. Maximum length of 90.

Pattern: ^DEFAULT | arn:[a-zA-Z0-9-]+:kms:[a-zA-Z0-9-]+\:\d{12}:key\/\w{8}-\w{4}-\w{4}-\w{4}-\w{12}\\$

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Label

The label details.

## Contents

### arn

The label ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^arn\aws[a-z-]{0,15}\frauddetector\:[a-z0-9-]{3,20}\:[0-9]{12}\:[^\s]{2,128}\$

Required: No

### createdTime

Timestamp of when the event type was created.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

### description

The label description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### lastUpdatedTime

Timestamp of when the label was last updated.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

#### **name**

The label name.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# LabelSchema

The label schema.

## Contents

### labelMapper

The label mapper maps the Amazon Fraud Detector supported model classification labels (FRAUD, LEGIT) to the appropriate event type labels. For example, if "FRAUD" and "LEGIT" are Amazon Fraud Detector supported labels, this mapper could be: {"FRAUD" => ["0"], "LEGIT" => ["1"]} or {"FRAUD" => ["false"], "LEGIT" => ["true"]} or {"FRAUD" => ["fraud", "abuse"], "LEGIT" => ["legit", "safe"]}. The value part of the mapper is a list, because you may have multiple label variants from your event type for a single Amazon Fraud Detector label.

Type: String to array of strings map

Required: No

### unlabeledEventsTreatment

The action to take for unlabeled events.

- Use IGNORE if you want the unlabeled events to be ignored. This is recommended when the majority of the events in the dataset are labeled.
- Use FRAUD if you want to categorize all unlabeled events as "Fraud". This is recommended when most of the events in your dataset are fraudulent.
- Use LEGIT if you want to categorize all unlabeled events as "Legit". This is recommended when most of the events in your dataset are legitimate.
- Use AUTO if you want Amazon Fraud Detector to decide how to use the unlabeled data. This is recommended when there is significant unlabeled events in the dataset.

By default, Amazon Fraud Detector ignores the unlabeled data.

Type: String

Valid Values: IGNORE | FRAUD | LEGIT | AUTO

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# LogOddsMetric

The log odds metric details.

## Contents

### variableImportance

The relative importance of the variable. For more information, see [Model variable importance](#).

Type: Float

Required: Yes

### variableName

The name of the variable.

Type: String

Required: Yes

### variableType

The type of variable.

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# MetricDataPoint

Model performance metrics data points.

## Contents

### fpr

The false positive rate. This is the percentage of total legitimate events that are incorrectly predicted as fraud.

Type: Float

Required: No

### precision

The percentage of fraud events correctly predicted as fraudulent as compared to all events predicted as fraudulent.

Type: Float

Required: No

### threshold

The model threshold that specifies an acceptable fraud capture rate. For example, a threshold of 500 means any model score 500 or above is labeled as fraud.

Type: Float

Required: No

### tpr

The true positive rate. This is the percentage of total fraud the model detects. Also known as capture rate.

Type: Float

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Model

The model.

## Contents

### arn

The ARN of the model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^arn\aws[a-z-]{0,15}\frauddetector\:[a-z0-9-]{3,20}\:[0-9]{12}\:[^\s]{2,128}\$

Required: No

### createdTime

Timestamp of when the model was created.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

### description

The model description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### eventTypeName

The name of the event type.

Type: String

Required: No

### **lastUpdatedTime**

Timestamp of last time the model was updated.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

### **modelId**

The model ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_]+\$

Required: No

### **modelType**

The model type.

Type: String

Valid Values: ONLINE\_FRAUD\_INSIGHTS | TRANSACTION\_FRAUD\_INSIGHTS | ACCOUNT\_TAKEOVER\_INSIGHTS

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# ModelEndpointDataBlob

A pre-formed Amazon SageMaker model input you can include if your detector version includes an imported Amazon SageMaker model endpoint with pass-through input configuration.

## Contents

### byteBuffer

The byte buffer of the Amazon SageMaker model endpoint input data blob.

Type: Base64-encoded binary data object

Required: No

### contentType

The content type of the Amazon SageMaker model endpoint input data blob.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ModelInputConfiguration

The Amazon SageMaker model input configuration.

## Contents

### **useEventVariables**

The event variables.

Type: Boolean

Required: Yes

### **csvInputTemplate**

Template for constructing the CSV input-data sent to SageMaker. At event-evaluation, the placeholders for variable-names in the template will be replaced with the variable values before being sent to SageMaker.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Required: No

### **eventTypeName**

The event type name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: No

### **format**

The format of the model input configuration. The format differs depending on if it is passed through to SageMaker or constructed by Amazon Fraud Detector.

Type: String

Valid Values: TEXT\_CSV | APPLICATION\_JSON

Required: No

### **jsonInputTemplate**

Template for constructing the JSON input-data sent to SageMaker. At event-evaluation, the placeholders for variable names in the template will be replaced with the variable values before being sent to SageMaker.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ModelOutputConfiguration

Provides the Amazon Sagemaker model output configuration.

## Contents

### **format**

The format of the model output configuration.

Type: String

Valid Values: TEXT\_CSV | APPLICATION\_JSONLINES

Required: Yes

### **csvIndexToVariableMap**

A map of CSV index values in the SageMaker response to the Amazon Fraud Detector variables.

Type: String to string map

Required: No

### **jsonKeyToVariableMap**

A map of JSON keys in response from SageMaker to the Amazon Fraud Detector variables.

Type: String to string map

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ModelScores

The fraud prediction scores.

## Contents

### **modelVersion**

The model version.

Type: [ModelVersion](#) object

Required: No

### **scores**

The model's fraud prediction scores.

Type: String to float map

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ModelVersion

The model version.

## Contents

### **modelId**

The model ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-zA-Z\_]+\$

Required: Yes

### **modelType**

The model type.

Type: String

Valid Values: ONLINE\_FRAUD\_INSIGHTS | TRANSACTION\_FRAUD\_INSIGHTS | ACCOUNT\_TAKEOVER\_INSIGHTS

Required: Yes

### **modelVersionNumber**

The model version number.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 7.

Pattern: ^[1-9][0-9]{0,3}\.[0-9]{1,2}\$

Required: Yes

### **arn**

The model version ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^arn\aws[a-z-]{0,15}\frauddetector\:[a-z0-9-]{3,20}\:[0-9]{12}\:[^\s]{2,128}\$

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ModelVersionDetail

The details of the model version.

## Contents

### arn

The model version ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^arn\aws[a-z-]{0,15}\frauddetector\:[a-z0-9-]{3,20}\:[0-9]{12}\[^s]{2,128}\$

Required: No

### createdTime

The timestamp when the model was created.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

### externalEventsDetail

The external events data details. This will be populated if the `trainingDataSource` for the model version is specified as `EXTERNAL_EVENTS`.

Type: [ExternalEventsDetail](#) object

Required: No

### ingestedEventsDetail

The ingested events data details. This will be populated if the `trainingDataSource` for the model version is specified as `INGESTED_EVENTS`.

Type: [IngestedEventsDetail](#) object

Required: No

### **lastUpdatedTime**

The timestamp when the model was last updated.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

### **modelId**

The model ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_]+\$

Required: No

### **modelType**

The model type.

Type: String

Valid Values: ONLINE\_FRAUD\_INSIGHTS | TRANSACTION\_FRAUD\_INSIGHTS | ACCOUNT\_TAKEOVER\_INSIGHTS

Required: No

### **modelVersionNumber**

The model version number.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 7.

Pattern: ^[1-9][0-9]{0,3}\.[0-9]{1,2}\$

Required: No

**status**

The status of the model version.

Type: String

Required: No

**trainingDataSchema**

The training data schema.

Type: [TrainingDataSchema](#) object

Required: No

**trainingDataSource**

The model version training data source.

Type: String

Valid Values: EXTERNAL\_EVENTS | INGESTED\_EVENTS

Required: No

**trainingResult**

The training results.

Type: [TrainingResult](#) object

Required: No

**trainingResultV2**

The training result details. The details include the relative importance of the variables.

Type: [TrainingResultV2](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ModelVersionEvaluation

The model version evalutions.

## Contents

### **evaluationScore**

The evaluation score generated for the model version.

Type: String

Required: No

### **outputVariableName**

The output variable name.

Type: String

Required: No

### **predictionExplanations**

The prediction explanations generated for the model version.

Type: [PredictionExplanations](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# OFIMetricDataPoint

The Online Fraud Insights (OFI) model performance metrics data points.

## Contents

### fpr

The false positive rate. This is the percentage of total legitimate events that are incorrectly predicted as fraud.

Type: Float

Required: No

### precision

The percentage of fraud events correctly predicted as fraudulent as compared to all events predicted as fraudulent.

Type: Float

Required: No

### threshold

The model threshold that specifies an acceptable fraud capture rate. For example, a threshold of 500 means any model score 500 or above is labeled as fraud.

Type: Float

Required: No

### tpr

The true positive rate. This is the percentage of total fraud the model detects. Also known as capture rate.

Type: Float

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# OFIModelPerformance

The Online Fraud Insights (OFI) model performance score.

## Contents

### auc

The area under the curve (auc). This summarizes the total positive rate (tpr) and false positive rate (FPR) across all possible model score thresholds.

Type: Float

Required: No

### uncertaintyRange

Indicates the range of area under curve (auc) expected from the OFI model. A range greater than 0.1 indicates higher model uncertainty.

Type: [UncertaintyRange](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# OFITrainingMetricsValue

The Online Fraud Insights (OFI) model training metric details.

## Contents

### **metricDataPoints**

The model's performance metrics data points.

Type: Array of [OFIMetricDataPoint](#) objects

Required: No

### **modelPerformance**

The model's overall performance score.

Type: [OFIModelPerformance](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Outcome

The outcome.

## Contents

### arn

The outcome ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^arn\aws[a-z-]{0,15}\frauddetector\:[a-z0-9-]{3,20}\:[0-9]{12}\:[^\s]{2,128}\$

Required: No

### createdTime

The timestamp when the outcome was created.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

### description

The outcome description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### lastUpdatedTime

The timestamp when the outcome was last updated.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

#### **name**

The outcome name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-z\_-]+\$

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# PredictionExplanations

The prediction explanations that provide insight into how each event variable impacted the model version's fraud prediction score.

## Contents

### aggregatedVariablesImpactExplanations

The details of the aggregated variables impact on the prediction score.

Account Takeover Insights (ATI) model uses event variables from the login data you provide to continuously calculate a set of variables (aggregated variables) based on historical events. For example, your ATI model might calculate the number of times an user has logged in using the same IP address. In this case, event variables used to derive the aggregated variables are IP address and user.

Type: Array of [AggregatedVariablesImpactExplanation](#) objects

Required: No

### variableImpactExplanations

The details of the event variable's impact on the prediction score.

Type: Array of [VariableImpactExplanation](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# PredictionTimeRange

The time period for when the predictions were generated.

## Contents

### **endTime**

The end time of the time period for when the predictions were generated.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: Yes

### **startTime**

The start time of the time period for when the predictions were generated.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Rule

A rule.

## Contents

### **detectorId**

The detector for which the rule is associated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-zA-Z\_-]+\$

Required: Yes

### **ruleId**

The rule ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-zA-Z\_-]+\$

Required: Yes

### **ruleVersion**

The rule version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 5.

Pattern: ^([1-9][0-9]\*)\$

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RuleDetail

The details of the rule.

## Contents

### arn

The rule ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^arn\aws[a-z-]{0,15}\frauddetector\:[a-z0-9-]{3,20}\:[0-9]{12}\:[^\s]{2,128}\$

Required: No

### createdTime

The timestamp of when the rule was created.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

### description

The rule description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### detectorId

The detector for which the rule is associated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-zA-Z\_-]+\$

Required: No

### **expression**

The rule expression.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

### **language**

The rule language.

Type: String

Valid Values: DETECTORPL

Required: No

### **lastUpdatedTime**

Timestamp of the last time the rule was updated.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

### **outcomes**

The rule outcomes.

Type: Array of strings

Array Members: Minimum number of 1 item.

Required: No

**ruleId**

The rule ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[0-9a-zA-Z\_-]+\$

Required: No

**ruleVersion**

The rule version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 5.

Pattern: ^([1-9][0-9]\*\$)

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RuleResult

The rule results.

## Contents

### **outcomes**

The outcomes of the matched rule, based on the rule execution mode.

Type: Array of strings

Required: No

### **ruleId**

The rule ID that was matched, based on the rule execution mode.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Tag

A key and value pair.

## Contents

### key

A tag key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^([\p{L}\p{Z}\p{N}\_.:/-@]+)\$

Required: Yes

### value

A value assigned to a tag key.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# TFIMetricDataPoint

The performance metrics data points for Transaction Fraud Insights (TFI) model.

## Contents

### fpr

The false positive rate. This is the percentage of total legitimate events that are incorrectly predicted as fraud.

Type: Float

Required: No

### precision

The percentage of fraud events correctly predicted as fraudulent as compared to all events predicted as fraudulent.

Type: Float

Required: No

### threshold

The model threshold that specifies an acceptable fraud capture rate. For example, a threshold of 500 means any model score 500 or above is labeled as fraud.

Type: Float

Required: No

### tpr

The true positive rate. This is the percentage of total fraud the model detects. Also known as capture rate.

Type: Float

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# TFIModelPerformance

The Transaction Fraud Insights (TFI) model performance score.

## Contents

### auc

The area under the curve (auc). This summarizes the total positive rate (tpr) and false positive rate (FPR) across all possible model score thresholds.

Type: Float

Required: No

### uncertaintyRange

Indicates the range of area under curve (auc) expected from the TFI model. A range greater than 0.1 indicates higher model uncertainty.

Type: [UncertaintyRange](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# TFITrainingMetricsValue

The Transaction Fraud Insights (TFI) model training metric details.

## Contents

### **metricDataPoints**

The model's performance metrics data points.

Type: Array of [TFIMetricDataPoint](#) objects

Required: No

### **modelPerformance**

The model performance score.

Type: [TFIModelPerformance](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# TrainingDataSchema

The training data schema.

## Contents

### **modelVariables**

The training data schema variables.

Type: Array of strings

Required: Yes

### **labelSchema**

The label schema.

Type: [LabelSchema](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# TrainingMetrics

The training metric details.

## Contents

### auc

The area under the curve. This summarizes true positive rate (TPR) and false positive rate (FPR) across all possible model score thresholds. A model with no predictive power has an AUC of 0.5, whereas a perfect model has a score of 1.0.

Type: Float

Required: No

### metricDataPoints

The data points details.

Type: Array of [MetricDataPoint](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# TrainingMetricsV2

The training metrics details.

## Contents

### ati

The Account Takeover Insights (ATI) model training metric details.

Type: [ATITrainingMetricsValue](#) object

Required: No

### ofi

The Online Fraud Insights (OFI) model training metric details.

Type: [OFITrainingMetricsValue](#) object

Required: No

### tfi

The Transaction Fraud Insights (TFI) model training metric details.

Type: [TFITrainingMetricsValue](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# TrainingResult

The training result details.

## Contents

### **dataValidationMetrics**

The validation metrics.

Type: [DataValidationMetrics](#) object

Required: No

### **trainingMetrics**

The training metric details.

Type: [TrainingMetrics](#) object

Required: No

### **variableImportanceMetrics**

The variable importance metrics.

Type: [VariableImportanceMetrics](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# TrainingResultV2

The training result details.

## Contents

### aggregatedVariablesImportanceMetrics

The variable importance metrics of the aggregated variables.

Account Takeover Insights (ATI) model uses event variables from the login data you provide to continuously calculate a set of variables (aggregated variables) based on historical events. For example, your ATI model might calculate the number of times an user has logged in using the same IP address. In this case, event variables used to derive the aggregated variables are IP address and user.

Type: [AggregatedVariablesImportanceMetrics](#) object

Required: No

### dataValidationMetrics

The model training data validation metrics.

Type: [DataValidationMetrics](#) object

Required: No

### trainingMetricsV2

The training metric details.

Type: [TrainingMetricsV2](#) object

Required: No

### variableImportanceMetrics

The variable importance metrics details.

Type: [VariableImportanceMetrics](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# UncertaintyRange

Range of area under curve (auc) expected from the model. A range greater than 0.1 indicates higher model uncertainty. A range is the difference between upper and lower bound of auc.

## Contents

### **lowerBoundValue**

The lower bound value of the area under curve (auc).

Type: Float

Required: Yes

### **upperBoundValue**

The upper bound value of the area under curve (auc).

Type: Float

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Variable

The variable.

## Contents

### arn

The ARN of the variable.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^arn\aws[a-z-]{0,15}\frauddetector\:[a-z0-9-]{3,20}\:[0-9]{12}\:[^\s]{2,128}\$

Required: No

### createdTime

The time when the variable was created.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

### dataSource

The data source of the variable.

Type: String

Valid Values: EVENT | MODEL\_SCORE | EXTERNAL\_MODEL\_SCORE

Required: No

### dataType

The data type of the variable. For more information see [Variable types](#).

Type: String

Valid Values: STRING | INTEGER | FLOAT | BOOLEAN | DATETIME

Required: No

### **defaultValue**

The default value of the variable.

Type: String

Required: No

### **description**

The description of the variable.

Type: String

Required: No

### **lastUpdatedTime**

The time when variable was last updated.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 30.

Required: No

### **name**

The name of the variable.

Type: String

Required: No

### **variableType**

The variable type of the variable.

Valid Values: AUTH\_CODE | AVS | BILLING\_ADDRESS\_L1 | BILLING\_ADDRESS\_L2  
| BILLING\_CITY | BILLING\_COUNTRY | BILLING\_NAME | BILLING\_PHONE |  
BILLING\_STATE | BILLING\_ZIP | CARD\_BIN | CATEGORICAL | CURRENCY\_CODE  
| EMAIL\_ADDRESS | FINGERPRINT | FRAUD\_LABEL | FREE\_FORM\_TEXT |

IP\_ADDRESS | NUMERIC | ORDER\_ID | PAYMENT\_TYPE | PHONE\_NUMBER | PRICE  
| PRODUCT\_CATEGORY | SHIPPING\_ADDRESS\_L1 | SHIPPING\_ADDRESS\_L2 |  
SHIPPING\_CITY | SHIPPING\_COUNTRY | SHIPPING\_NAME | SHIPPING\_PHONE |  
SHIPPING\_STATE | SHIPPING\_ZIP | USERAGENT

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# VariableEntry

A variable in the list of variables for the batch create variable request.

## Contents

### **dataSource**

The data source of the variable.

Type: String

Required: No

### **dataType**

The data type of the variable.

Type: String

Required: No

### **defaultValue**

The default value of the variable.

Type: String

Required: No

### **description**

The description of the variable.

Type: String

Required: No

### **name**

The name of the variable.

Type: String

Required: No

## variableType

The type of the variable. For more information see [Variable types](#).

Valid Values: AUTH\_CODE | AVS | BILLING\_ADDRESS\_L1 | BILLING\_ADDRESS\_L2 | BILLING\_CITY | BILLING\_COUNTRY | BILLING\_NAME | BILLING\_PHONE | BILLING\_STATE | BILLING\_ZIP | CARD\_BIN | CATEGORICAL | CURRENCY\_CODE | EMAIL\_ADDRESS | FINGERPRINT | FRAUD\_LABEL | FREE\_FORM\_TEXT | IP\_ADDRESS | NUMERIC | ORDER\_ID | PAYMENT\_TYPE | PHONE\_NUMBER | PRICE | PRODUCT\_CATEGORY | SHIPPING\_ADDRESS\_L1 | SHIPPING\_ADDRESS\_L2 | SHIPPING\_CITY | SHIPPING\_COUNTRY | SHIPPING\_NAME | SHIPPING\_PHONE | SHIPPING\_STATE | SHIPPING\_ZIP | USERAGENT

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# VariableImpactExplanation

The details of the event variable's impact on the prediction score.

## Contents

### eventVariableName

The event variable name.

Type: String

Required: No

### logOddsImpact

The raw, uninterpreted value represented as log-odds of the fraud. These values are usually between -10 to +10, but range from - infinity to + infinity.

- A positive value indicates that the variable drove the risk score up.
- A negative value indicates that the variable drove the risk score down.

Type: Float

Required: No

### relativeImpact

The event variable's relative impact in terms of magnitude on the prediction scores. The relative impact values consist of a numerical rating (0-5, 5 being the highest) and direction (increased/decreased) impact of the fraud risk.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# VariableImportanceMetrics

The variable importance metrics details.

## Contents

### logOddsMetrics

List of variable metrics.

Type: Array of [LogOddsMetric](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests in the IAM User Guide](#).

## Action

The action to be performed.

Type: string

Required: Yes

## Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

## X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

## X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4\_request"). The value is expressed in the following format: *access\_key/YYYYMMDD/region/service/aws4\_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

### X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

### X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

### X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

### X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

# Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

## **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

## **IncompleteSignature**

The request signature does not conform to AWS standards.

HTTP Status Code: 400

## **InternalFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## **InvalidAction**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

## **InvalidClientTokenId**

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

## **NotAuthorized**

You do not have permission to perform this action.

HTTP Status Code: 400

## **OptInRequired**

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

## **RequestExpired**

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

## **ServiceUnavailable**

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

## **ThrottlingException**

The request was denied due to request throttling.

HTTP Status Code: 400

## **ValidationException**

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400