



API Reference

AWS HealthImaging



API Version 2023-07-19

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS HealthImaging: API Reference

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
CopyImageSet	3
Request Syntax	3
URI Request Parameters	3
Request Body	4
Response Syntax	4
Response Elements	5
Errors	6
See Also	7
CreateDatastore	8
Request Syntax	8
URI Request Parameters	8
Request Body	8
Response Syntax	10
Response Elements	10
Errors	11
See Also	12
DeleteDatastore	13
Request Syntax	13
URI Request Parameters	13
Request Body	13
Response Syntax	13
Response Elements	14
Errors	14
See Also	15
DeleteImageSet	16
Request Syntax	16
URI Request Parameters	16
Request Body	16
Response Syntax	16
Response Elements	17
Errors	18
See Also	18

GetDatastore	20
Request Syntax	20
URI Request Parameters	20
Request Body	20
Response Syntax	20
Response Elements	21
Errors	21
See Also	22
GetDICOMImportJob	23
Request Syntax	23
URI Request Parameters	23
Request Body	24
Response Syntax	24
Response Elements	24
Errors	24
See Also	25
GetImageFrame	27
Request Syntax	27
URI Request Parameters	27
Request Body	27
Response Syntax	28
Response Elements	28
Errors	29
See Also	30
GetImageSet	32
Request Syntax	32
URI Request Parameters	32
Request Body	32
Response Syntax	32
Response Elements	33
Errors	35
See Also	36
GetImageSetMetadata	38
Request Syntax	38
URI Request Parameters	38
Request Body	38

Response Syntax	38
Response Elements	39
Errors	39
See Also	40
ListDatastores	41
Request Syntax	41
URI Request Parameters	41
Request Body	41
Response Syntax	41
Response Elements	42
Errors	42
See Also	43
ListDICOMImportJobs	44
Request Syntax	44
URI Request Parameters	44
Request Body	44
Response Syntax	45
Response Elements	45
Errors	46
See Also	46
ListImageSetVersions	48
Request Syntax	48
URI Request Parameters	48
Request Body	49
Response Syntax	49
Response Elements	49
Errors	50
See Also	51
ListTagsForResource	52
Request Syntax	52
URI Request Parameters	52
Request Body	52
Response Syntax	52
Response Elements	52
Errors	53
See Also	54

SearchImageSets	55
Request Syntax	55
URI Request Parameters	55
Request Body	56
Response Syntax	56
Response Elements	57
Errors	58
See Also	59
StartDICOMImportJob	60
Request Syntax	60
URI Request Parameters	60
Request Body	60
Response Syntax	62
Response Elements	63
Errors	63
See Also	64
TagResource	66
Request Syntax	66
URI Request Parameters	66
Request Body	66
Response Syntax	67
Response Elements	67
Errors	67
See Also	68
UntagResource	69
Request Syntax	69
URI Request Parameters	69
Request Body	69
Response Syntax	69
Response Elements	70
Errors	70
See Also	70
UpdateImageSetMetadata	72
Request Syntax	72
URI Request Parameters	72
Request Body	73

Response Syntax	74
Response Elements	74
Errors	76
See Also	77
Data Types	78
CopyDestinationImageSet	80
Contents	80
See Also	80
CopyDestinationImageSetProperties	81
Contents	81
See Also	82
CopyImageSetInformation	83
Contents	83
See Also	83
CopySourceImageSetInformation	84
Contents	84
See Also	84
CopySourceImageSetProperties	85
Contents	85
See Also	86
DatastoreProperties	87
Contents	87
See Also	89
DatastoreSummary	90
Contents	90
See Also	91
DICOMImportJobProperties	92
Contents	92
See Also	94
DICOMImportJobSummary	95
Contents	95
See Also	97
DicomJsonMetadataImportConfiguration	98
Contents	98
See Also	98
DicomMetadataMapping	99

Contents	99
See Also	100
DICOMStudyDateAndTime	101
Contents	101
See Also	101
DICOMTags	102
Contents	102
See Also	105
DICOMUpdates	106
Contents	106
See Also	106
ImageFrameInformation	107
Contents	107
See Also	107
ImageSetProperties	108
Contents	108
See Also	110
ImageSetsMetadataSummary	111
Contents	111
See Also	112
ImportConfiguration	113
Contents	113
See Also	113
MetadataCopies	114
Contents	114
See Also	114
MetadataUpdates	115
Contents	115
See Also	115
Overrides	117
Contents	117
See Also	117
SearchByAttributeValue	118
Contents	118
See Also	120
SearchCriteria	121

- Contents 121
- See Also 121
- SearchFilter 122
 - Contents 122
 - See Also 122
- Sort 123
 - Contents 123
 - See Also 123
- Common Parameters 124**
- Common Error Types 127**

Welcome

This is the *AWS HealthImaging API Reference*. For an introduction to the service, see [What is AWS HealthImaging?](#) in the *AWS HealthImaging Developer Guide*.

This document was last published on August 7, 2026.

Actions

The following actions are supported:

- [CopyImageSet](#)
- [CreateDatastore](#)
- [DeleteDatastore](#)
- [DeleteImageSet](#)
- [GetDatastore](#)
- [GetDICOMImportJob](#)
- [GetImageFrame](#)
- [GetImageSet](#)
- [GetImageSetMetadata](#)
- [ListDatastores](#)
- [ListDICOMImportJobs](#)
- [ListImageSetVersions](#)
- [ListTagsForResource](#)
- [SearchImageSets](#)
- [StartDICOMImportJob](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateImageSetMetadata](#)

CopyImageSet

Copy an image set.

Request Syntax

```
POST /datastore/datastoreId/imageSet/sourceImageSetId/copyImageSet?  
force=force&promoteToPrimary=promoteToPrimary HTTP/1.1  
Content-type: application/json
```

```
{  
  "destinationImageSet": {  
    "imageSetId": "string",  
    "latestVersionId": "string"  
  },  
  "sourceImageSet": {  
    "DICOMCopies": {  
      "copiableAttributes": "string"  
    },  
    "latestVersionId": "string"  
  }  
}
```

URI Request Parameters

The request uses the following URI parameters.

datastoreId

The data store identifier.

Pattern: `[0-9a-z]{32}`

Required: Yes

force

Providing this parameter will force completion of the CopyImageSet operation, even if there are inconsistent Patient, Study, and/or Series level metadata elements between the sourceImageSet and destinationImageSet.

[promoteToPrimary](#)

Providing this parameter will configure the CopyImageSet operation to promote the given image set to the primary DICOM hierarchy. If successful, a new primary image set ID will be returned as the destination image set.

[sourceImageSetId](#)

The source image set identifier.

Pattern: `[0-9a-z]{32}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

[destinationImageSet](#)

The destination image set.

Type: [CopyDestinationImageSet](#) object

Required: No

[sourceImageSet](#)

The source image set.

Type: [CopySourceImageSetInformation](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "datastoreId": "string",
  "destinationImageSetProperties": {
```

```
    "createdAt": number,
    "imageSetArn": "string",
    "imageSetId": "string",
    "imageSetState": "string",
    "imageSetWorkflowStatus": "string",
    "latestVersionId": "string",
    "updatedAt": number
  },
  "sourceImageSetProperties": {
    "createdAt": number,
    "imageSetArn": "string",
    "imageSetId": "string",
    "imageSetState": "string",
    "imageSetWorkflowStatus": "string",
    "latestVersionId": "string",
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

datastoreId

The data store identifier.

Type: String

Pattern: [0-9a-z]{32}

destinationImageSetProperties

The properties of the destination image set.

Type: [CopyDestinationImageSetProperties](#) object

sourceImageSetProperties

The properties of the source image set.

Type: [CopySourceImageSetProperties](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request caused a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateDatastore

Create a data store.

Request Syntax

```
POST /datastore HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "datastoreName": "string",
  "kmsKeyArn": "string",
  "lambdaAuthorizerArn": "string",
  "losslessStorageFormat": "string",
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique identifier for API idempotency.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9._-]+

Required: Yes

datastoreName

The data store name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [A-Za-z0-9._/#-]+

Required: No

kmsKeyArn

The Amazon Resource Name (ARN) assigned to the Key Management Service (KMS) key for accessing encrypted data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: arn:aws[a-zA-Z-]{0,16}:kms:[a-z]{2}(-[a-z]{1,16}){1,3}-\d{1}:\d{12}:((key/[a-fA-F0-9]{8}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{12})|(alias/[a-zA-Z0-9:/_-]{1,256}))

Required: No

lambdaAuthorizerArn

The ARN of the authorizer's Lambda function.

Type: String

Pattern: arn:(aws[a-zA-Z-]*)?:lambda:[a-z]{2}((-gov)|(-iso(b?)))?-[a-z]+\d{1}:\d{12}:function:[a-zA-Z0-9-_-]+(:(\\$LATEST|[a-zA-Z0-9-_-]+))?

Required: No

losslessStorageFormat

The lossless storage format for the datastore.

Type: String

Valid Values: HTJ2K | JPEG_2000_LOSSLESS

Required: No

tags

The tags provided when creating a data store.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: (?!aws:)[a-zA-Z+-. _:/]+

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "datastoreId": "string",
  "datastoreStatus": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

datastoreId

The data store identifier.

Type: String

Pattern: [0-9a-z]{32}

datastoreStatus

The data store status.

Type: String

Valid Values: CREATING | CREATE_FAILED | ACTIVE | DELETING | DELETED

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request caused a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteDatastore

Delete a data store.

Note

Before a data store can be deleted, you must first delete all image sets within it.

Request Syntax

```
DELETE /datastore/datastoreId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

datastoreId

The data store identifier.

Pattern: `[0-9a-z]{32}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "datastoreId": "string",
  "datastoreStatus": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

datastoreId

The data store identifier.

Type: String

Pattern: `[0-9a-z]{32}`

datastoreStatus

The data store status.

Type: String

Valid Values: `CREATING` | `CREATE_FAILED` | `ACTIVE` | `DELETING` | `DELETED`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteImageSet

Delete an image set.

Request Syntax

```
POST /datastore/datastoreId/imageSet/imageSetId/deleteImageSet HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

datastoreId

The data store identifier.

Pattern: `[0-9a-z]{32}`

Required: Yes

imageSetId

The image set identifier.

Pattern: `[0-9a-z]{32}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "datastoreId": "string",
  "imageSetId": "string",
```

```
"imageSetState": "string",  
"imageSetWorkflowStatus": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

datastoreId

The data store identifier.

Type: String

Pattern: [0-9a-z]{32}

imageSetId

The image set identifier.

Type: String

Pattern: [0-9a-z]{32}

imageSetState

The image set state.

Type: String

Valid Values: ACTIVE | LOCKED | DELETED

imageSetWorkflowStatus

The image set workflow status.

Type: String

Valid Values: CREATED | COPIED | COPYING | COPYING_WITH_READ_ONLY_ACCESS
| COPY_FAILED | UPDATING | UPDATING_FOR_STUDY_CONSISTENCY | UPDATED
| UPDATE_FAILED | DELETING | DELETED | IMPORTING | IMPORTED |
IMPORT_FAILED

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetDatastore

Get data store properties.

Request Syntax

```
GET /datastore/datastoreId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

datastoreId

The data store identifier.

Pattern: `[0-9a-z]{32}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "datastoreProperties": {
    "createdAt": number,
    "datastoreArn": "string",
    "datastoreId": "string",
    "datastoreName": "string",
    "datastoreStatus": "string",
    "kmsKeyArn": "string",
    "lambdaAuthorizerArn": "string",
    "losslessStorageFormat": "string",
    "updatedAt": number
  }
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

datastoreProperties

The data store properties.

Type: [DatastoreProperties](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetDICOMImportJob

Get the import job properties to learn more about the job or job progress.

Note

The `jobStatus` refers to the execution of the import job. Therefore, an import job can return a `jobStatus` as `COMPLETED` even if validation issues are discovered during the import process. If a `jobStatus` returns as `COMPLETED`, we still recommend you review the output manifests written to S3, as they provide details on the success or failure of individual P10 object imports.

Request Syntax

```
GET /getDICOMImportJob/datastore/datastoreId/job/jobId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

datastoreId

The data store identifier.

Pattern: `[0-9a-z]{32}`

Required: Yes

jobId

The import job identifier.

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `[0-9a-z]+`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "jobProperties": {
    "dataAccessRoleArn": "string",
    "datastoreId": "string",
    "endedAt": number,
    "importConfiguration": { ... },
    "inputS3Uri": "string",
    "jobId": "string",
    "jobName": "string",
    "jobStatus": "string",
    "message": "string",
    "outputS3Uri": "string",
    "submittedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[jobProperties](#)

The properties of the import job.

Type: [DICOMImportJobProperties](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetImageFrame

Get an image frame (pixel data) for an image set.

Request Syntax

```
POST /datastore/datastoreId/imageSet/imageSetId/getImageFrame HTTP/1.1
Content-type: application/json
```

```
{
  "imageFrameId": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

datastoreId

The data store identifier.

Pattern: `[0-9a-z]{32}`

Required: Yes

imageSetId

The image set identifier.

Pattern: `[0-9a-z]{32}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

imageFrameId

The image frame (pixel data) identifier.

Type: String

Pattern: [0-9a-z]{32}

Required: Yes

Response Syntax

HTTP/1.1 200

Content-Type: *contentType*

imageFrameBlob

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The response returns the following HTTP headers.

contentType

The format in which the image frame information is returned to the customer. Default is application/octet-stream.

Note

- If the stored transfer syntax is 1.2.840.10008.1.2.1, the returned contentType is application/octet-stream.
- If the stored transfer syntax is 1.2.840.10008.1.2.4.50, the returned contentType is image/jpeg.
- If the stored transfer syntax is 1.2.840.10008.1.2.4.91, the returned contentType is image/j2c.
- If the stored transfer syntax is MPEG2, 1.2.840.10008.1.2.4.100, 1.2.840.10008.1.2.4.100.1, 1.2.840.10008.1.2.4.101, or 1.2.840.10008.1.2.4.101.1, the returned contentType is video/mpeg.
- If the stored transfer syntax is MPEG-4 AVC/H.264, UID 1.2.840.10008.1.2.4.102, 1.2.840.10008.1.2.4.102.1, 1.2.840.10008.1.2.4.103, 1.2.840.10008.1.2.4.103.1, 1.2.840.10008.1.2.4.104, 1.2.840.10008.1.2.4.104.1,

1.2.840.10008.1.2.4.105, 1.2.840.10008.1.2.4.105.1, 1.2.840.10008.1.2.4.106, or 1.2.840.10008.1.2.4.106.1, the returned `contentType` is `video/mp4`.

- If the stored transfer syntax is HEVC/H.265, UID 1.2.840.10008.1.2.4.107 or 1.2.840.10008.1.2.4.108, the returned `contentType` is `video/H256`.
- If the stored transfer syntax is 1.2.840.10008.1.2.4.202 or if the stored transfer syntax is *missing*, the returned `contentType` is `image/jph`.
- If the stored transfer syntax is 1.2.840.10008.1.2.4.203, the returned `contentType` is `image/jphc`.
- If the stored transfer syntax is 1.2.840.10008.1.2.4.112 the returned `contentType` is `image/jxl`.

The response returns the following as the HTTP body.

imageFrameBlob

The blob containing the aggregated image frame information.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

BadRequestException

The request is invalid or malformed.

HTTP Status Code: 400

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

NotAcceptableException

The request content type or accept header is not supported.

HTTP Status Code: 406

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetImageSet

Get image set properties.

Request Syntax

```
POST /datastore/datastoreId/imageSet/imageSetId/getImageSet?version=versionId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

datastoreId

The data store identifier.

Pattern: `[0-9a-z]{32}`

Required: Yes

imageSetId

The image set identifier.

Pattern: `[0-9a-z]{32}`

Required: Yes

versionId

The image set version identifier.

Pattern: `\d+`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Content-type: application/json

```
{
  "createdAt": number,
  "datastoreId": "string",
  "deletedAt": number,
  "imageSetArn": "string",
  "imageSetId": "string",
  "imageSetState": "string",
  "imageSetWorkflowStatus": "string",
  "isPrimary": boolean,
  "lastAccessedAt": number,
  "message": "string",
  "overrides": {
    "forced": boolean
  },
  "storageTier": "string",
  "updatedAt": number,
  "versionId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

createdAt

The timestamp when image set properties were created.

Type: Timestamp

datastoreId

The data store identifier.

Type: String

Pattern: [0-9a-z]{32}

deletedAt

The timestamp when the image set properties were deleted.

Type: Timestamp

imageSetArn

The Amazon Resource Name (ARN) assigned to the image set.

Type: String

Pattern: `arn:aws((-us-gov)|(-iso)|(-iso-b)|(-cn))?:medical-imaging:[a-z0-9-]+:[0-9]{12}:datastore/[0-9a-z]{32}(/imageset/[0-9a-z]{32})?`

imageSetId

The image set identifier.

Type: String

Pattern: `[0-9a-z]{32}`

imageSetState

The image set state.

Type: String

Valid Values: ACTIVE | LOCKED | DELETED

imageSetWorkflowStatus

The image set workflow status.

Type: String

Valid Values: CREATED | COPIED | COPYING | COPYING_WITH_READ_ONLY_ACCESS | COPY_FAILED | UPDATING | UPDATING_FOR_STUDY_CONSISTENCY | UPDATED | UPDATE_FAILED | DELETING | DELETED | IMPORTING | IMPORTED | IMPORT_FAILED

isPrimary

The flag to determine whether the image set is primary or not.

Type: Boolean

lastAccessedAt

When the image set was last accessed.

Type: Timestamp

message

The error message thrown if an image set action fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[\w - : `]+`

overrides

This object contains the details of any overrides used while creating a specific image set version. If an image set was copied or updated using the force flag, this object will contain the forced flag.

Type: [Overrides](#) object

storageTier

The storage tier of the image set.

Type: String

Valid Values: FREQUENT_ACCESS | ARCHIVE_INSTANT_ACCESS

updatedAt

The timestamp when image set properties were updated.

Type: Timestamp

versionId

The image set version identifier.

Type: String

Pattern: `\d+`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetImageSetMetadata

Get metadata attributes for an image set.

Request Syntax

```
POST /datastore/datastoreId/imageSet/imageSetId/getImageSetMetadata?version=versionId
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

datastoreId

The data store identifier.

Pattern: `[0-9a-z]{32}`

Required: Yes

imageSetId

The image set identifier.

Pattern: `[0-9a-z]{32}`

Required: Yes

versionId

The image set version identifier.

Pattern: `\d+`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Content-Type: *contentType*
Content-Encoding: *contentEncoding*

imageSetMetadataBlob

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The response returns the following HTTP headers.

contentEncoding

The compression format in which image set metadata attributes are returned.

contentType

The format in which the study metadata is returned to the customer. Default is text/plain.

The response returns the following as the HTTP body.

imageSetMetadataBlob

The blob containing the aggregated metadata information for the image set.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListDatastores

List data stores.

Request Syntax

```
GET /datastore?  
datastoreStatus=datastoreStatus&maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

datastoreStatus

The data store status.

Valid Values: CREATING | CREATE_FAILED | ACTIVE | DELETING | DELETED

maxResults

Valid Range: Minimum value of 1. Maximum value of 50.

Valid Range: Minimum value of 1. Maximum value of 50.

nextToken

The pagination token used to request the list of data stores on the next page.

Length Constraints: Minimum length of 1. Maximum length of 8192.

Pattern: \p{ASCII}{0,8192}

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{
  "datastoreSummaries": [
    {
      "createdAt": number,
      "datastoreArn": "string",
      "datastoreId": "string",
      "datastoreName": "string",
      "datastoreStatus": "string",
      "updatedAt": number
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

datastoreSummaries

The list of summaries of data stores.

Type: Array of [DatastoreSummary](#) objects

nextToken

The pagination token used to retrieve the list of data stores on the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8192.

Pattern: \p{ASCII}{0,8192}

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListDICOMImportJobs

List import jobs created for a specific data store.

Request Syntax

```
GET /listDICOMImportJobs/datastore/datastoreId?  
jobStatus=jobStatus&maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

datastoreId

The data store identifier.

Pattern: `[0-9a-z]{32}`

Required: Yes

jobStatus

The filters for listing import jobs based on status.

Valid Values: SUBMITTED | IN_PROGRESS | COMPLETED | FAILED

maxResults

The max results count. The upper bound is determined by load testing.

Valid Range: Minimum value of 1. Maximum value of 50.

nextToken

The pagination token used to request the list of import jobs on the next page.

Length Constraints: Minimum length of 1. Maximum length of 8192.

Pattern: `\p{ASCII}{0,8192}`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "jobSummaries": [
    {
      "dataAccessRoleArn": "string",
      "datastoreId": "string",
      "endedAt": number,
      "jobId": "string",
      "jobName": "string",
      "jobStatus": "string",
      "message": "string",
      "submittedAt": number
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

jobSummaries

A list of job summaries.

Type: Array of [DICOMImportJobSummary](#) objects

nextToken

The pagination token used to retrieve the list of import jobs on the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8192.

Pattern: \p{ASCII}{0,8192}

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListImageSetVersions

List image set versions.

Request Syntax

```
POST /datastore/datastoreId/imageSet/imageSetId/listImageSetVersions?  
maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

datastoreId

The data store identifier.

Pattern: `[0-9a-z]{32}`

Required: Yes

imageSetId

The image set identifier.

Pattern: `[0-9a-z]{32}`

Required: Yes

maxResults

The max results count.

Valid Range: Minimum value of 1. Maximum value of 50.

nextToken

The pagination token used to request the list of image set versions on the next page.

Length Constraints: Minimum length of 1. Maximum length of 8192.

Pattern: `\p{ASCII}{0,8192}`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "imageSetPropertiesList": [
    {
      "createdAt": number,
      "deletedAt": number,
      "imageSetId": "string",
      "imageSetState": "string",
      "ImageSetWorkflowStatus": "string",
      "isPrimary": boolean,
      "message": "string",
      "overrides": {
        "forced": boolean
      },
      "updatedAt": number,
      "versionId": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

imageSetPropertiesList

Lists all properties associated with an image set.

Type: Array of [ImageSetProperties](#) objects

nextToken

The pagination token used to retrieve the list of image set versions on the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8192.

Pattern: \p{ASCII}{0,8192}

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Lists all tags associated with a medical imaging resource.

Request Syntax

```
GET /tags/resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the medical imaging resource to list tags for.

Pattern: `arn:aws((-us-gov)|(-iso)|(-iso-b)|(-cn))?:medical-imaging:[a-z0-9-]+:[0-9]{12}:datastore/[0-9a-z]{32}(/imageset/[0-9a-z]{32})?`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tags

A list of all tags associated with a medical imaging resource.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: (?!aws:)[a-zA-Z+-. _:/]+

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

SearchImageSets

Search image sets based on defined input attributes.

Note

SearchImageSets accepts a single search query parameter and returns a paginated response of all image sets that have the matching criteria. All date range queries must be input as (lowerBound, upperBound).

By default, SearchImageSets uses the updatedAt field for sorting in descending order from newest to oldest.

Request Syntax

```
POST /datastore/datastoreId/searchImageSets?maxResults=maxResults&nextToken=nextToken
```

```
HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "filters": [
    {
      "operator": "string",
      "values": [
        { ... }
      ]
    }
  ],
  "sort": {
    "sortField": "string",
    "sortOrder": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

datastoreId

The identifier of the data store where the image sets reside.

Pattern: `[0-9a-z]{32}`

Required: Yes

[maxResults](#)

The maximum number of results that can be returned in a search.

Valid Range: Minimum value of 1. Maximum value of 50.

[nextToken](#)

The token used for pagination of results returned in the response. Use the token returned from the previous request to continue results where the previous request ended.

Length Constraints: Minimum length of 1. Maximum length of 8192.

Pattern: `\p{ASCII}{0,8192}`

Request Body

The request accepts the following data in JSON format.

[filters](#)

The filters for the search criteria.

Type: Array of [SearchFilter](#) objects

Array Members: Minimum number of 1 item. Maximum number of 2 items.

Required: No

[sort](#)

The sort input for search criteria.

Type: [Sort](#) object

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```

{
  "imageSetsMetadataSummaries": [
    {
      "createdAt": number,
      "DICOMTags": {
        "DICOMAccessionNumber": "string",
        "DICOMNumberOfStudyRelatedInstances": number,
        "DICOMNumberOfStudyRelatedSeries": number,
        "DICOMPatientBirthDate": "string",
        "DICOMPatientId": "string",
        "DICOMPatientName": "string",
        "DICOMPatientSex": "string",
        "DICOMSeriesBodyPart": "string",
        "DICOMSeriesInstanceUID": "string",
        "DICOMSeriesModality": "string",
        "DICOMSeriesNumber": number,
        "DICOMStudyDate": "string",
        "DICOMStudyDescription": "string",
        "DICOMStudyId": "string",
        "DICOMStudyInstanceUID": "string",
        "DICOMStudyTime": "string"
      },
      "imageSetId": "string",
      "isPrimary": boolean,
      "lastAccessedAt": number,
      "storageTier": "string",
      "updatedAt": number,
      "version": number
    }
  ],
  "nextToken": "string",
  "sort": {
    "sortField": "string",
    "sortOrder": "string"
  }
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[imageSetsMetadataSummaries](#)

The model containing the image set results.

Type: Array of [ImageSetsMetadataSummary](#) objects

[nextToken](#)

The token for pagination results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8192.

Pattern: \p{ASCII}{0,8192}

[sort](#)

The sort order for image set search results.

Type: [Sort](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartDICOMImportJob

Start importing bulk data into an ACTIVE data store. The import job imports DICOM P10 files or enhances existing DICOM files with JSON metadata. The `importConfiguration` parameter specifies the import type. The data is found in the S3 prefix specified by the `inputS3Uri` parameter. The import job stores processing results in the file specified by the `outputS3Uri` parameter.

Request Syntax

```
POST /startDICOMImportJob/datastore/datastoreId HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "dataAccessRoleArn": "string",
  "importConfiguration": { ... },
  "inputOwnerAccountId": "string",
  "inputS3Uri": "string",
  "jobName": "string",
  "outputS3Uri": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

datastoreId

The data store identifier.

Pattern: `[0-9a-z]{32}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

clientToken

A unique identifier for API idempotency.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9._-]+

Required: Yes

dataAccessRoleArn

The Amazon Resource Name (ARN) of the IAM role that grants permission to access medical imaging resources.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: arn:aws(-[^:]+)?:iam::[0-9]{12}:role/.+

Required: Yes

importConfiguration

The import configuration for the import job.

Type: [ImportConfiguration](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

inputOwnerAccountId

The account ID of the source S3 bucket owner.

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d+

Required: No

inputS3Uri

The input prefix path for the S3 bucket that contains the DICOM files to be imported.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `s3://[a-z0-9][\.\-a-z0-9]{1,61}[a-z0-9](/.*)?`

Required: Yes

jobName

The import job name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[A-Za-z0-9._/#- ]+`

Required: No

outputS3Uri

The output prefix of the S3 bucket to upload the results of the DICOM import job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `s3://[a-z0-9][\.\-a-z0-9]{1,61}[a-z0-9](/.*)?`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "datastoreId": "string",
  "jobId": "string",
```

```
"jobStatus": "string",  
"submittedAt": number  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[datastoreId](#)

The data store identifier.

Type: String

Pattern: `[0-9a-z]{32}`

[jobId](#)

The import job identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `[0-9a-z]+`

[jobStatus](#)

The import job status.

Type: String

Valid Values: SUBMITTED | IN_PROGRESS | COMPLETED | FAILED

[submittedAt](#)

The timestamp when the import job was submitted.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request caused a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Adds a user-specified key and value tag to a medical imaging resource.

Request Syntax

```
POST /tags/resourceArn HTTP/1.1
Content-type: application/json

{
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the medical imaging resource that tags are being added to.

Pattern: `arn:aws((-us-gov)|(-iso)|(-iso-b)|(-cn))?:medical-imaging:[a-z0-9-]+:[0-9]{12}:datastore/[0-9a-z]{32}(/imageset/[0-9a-z]{32})?`

Required: Yes

Request Body

The request accepts the following data in JSON format.

tags

The user-specified key and value tag pairs added to a medical imaging resource.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: (?!aws:)[a-zA-Z+-._: /]+

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Removes tags from a medical imaging resource.

Request Syntax

```
DELETE /tags/resourceArn?tagKeys=tagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the medical imaging resource that tags are being removed from.

Pattern: `arn:aws((-us-gov)|(-iso)|(-iso-b)|(-cn)):medical-imaging:[a-z0-9-]+:[0-9]{12}:datastore/[0-9a-z]{32}(/imageset/[0-9a-z]{32})?`

Required: Yes

tagKeys

The keys for the tags to be removed from the medical imaging resource.

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `(?!aws:)[a-zA-Z+ -=._:/]+`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateImageSetMetadata

Update image set metadata attributes.

Request Syntax

```
POST /datastore/datastoreId/imageSet/imageSetId/updateImageSetMetadata?
force=force&includeStudyImageSets=includeStudyImageSets&latestVersion=latestVersionId
HTTP/1.1
Content-type: application/json

{
  "DICOMUpdates": {
    "removableAttributes": blob,
    "updatableAttributes": blob
  },
  "revertToVersionId": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

datastoreId

The data store identifier.

Pattern: [0-9a-z]{32}

Required: Yes

force

Setting this flag will force the UpdateImageSetMetadata operation for the following attributes:

- Tag.StudyInstanceUID, Tag.SeriesInstanceUID, Tag.SOPInstanceUID, and Tag.StudyID
- Adding, removing, or updating private tags for an individual SOP Instance

imageSetId

The image set identifier.

Pattern: `[0-9a-z]{32}`

Required: Yes

[includeStudyImageSets](#)

Flag to apply the metadata updates to all image sets in the same Study as the requested image set ID.

[latestVersionId](#)

The latest image set version identifier.

Pattern: `\d+`

Required: Yes

Request Body

The request accepts the following data in JSON format.

[DICOMUpdates](#)

The object containing `removableAttributes` and `updatableAttributes`.

Type: [DICOMUpdates](#) object

Required: No

[revertToVersionId](#)

Specifies the previous image set version ID to revert the current image set back to.

Note

You must provide either `revertToVersionId` or `DICOMUpdates` in your request. A `ValidationException` error is thrown if both parameters are provided at the same time.

Type: String

Pattern: `\d+`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "createdAt": number,
  "datastoreId": "string",
  "imageSetId": "string",
  "imageSetState": "string",
  "imageSetWorkflowStatus": "string",
  "latestVersionId": "string",
  "message": "string",
  "updatedAt": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[createdAt](#)

The timestamp when image set metadata was created.

Type: Timestamp

[datastoreId](#)

The data store identifier.

Type: String

Pattern: `[0-9a-z]{32}`

[imageSetId](#)

The image set identifier.

Type: String

Pattern: `[0-9a-z]{32}`

imageSetState

The image set state.

Type: String

Valid Values: ACTIVE | LOCKED | DELETED

imageSetWorkflowStatus

The image set workflow status.

Type: String

Valid Values: CREATED | COPIED | COPYING | COPYING_WITH_READ_ONLY_ACCESS
| COPY_FAILED | UPDATING | UPDATING_FOR_STUDY_CONSISTENCY | UPDATED
| UPDATE_FAILED | DELETING | DELETED | IMPORTING | IMPORTED |
IMPORT_FAILED

latestVersionId

The latest image set version identifier.

Type: String

Pattern: `\d+`

message

The error message thrown if an update image set metadata action fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[\w - : `]+`

updatedAt

The timestamp when image set metadata was updated.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request caused a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS Health Imaging API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [CopyDestinationImageSet](#)
- [CopyDestinationImageSetProperties](#)
- [CopyImageSetInformation](#)
- [CopySourceImageSetInformation](#)
- [CopySourceImageSetProperties](#)
- [DatastoreProperties](#)
- [DatastoreSummary](#)
- [DICOMImportJobProperties](#)
- [DICOMImportJobSummary](#)
- [DicomJsonMetadataImportConfiguration](#)
- [DicomMetadataMapping](#)
- [DICOMStudyDateAndTime](#)
- [DICOMTags](#)
- [DICOMUpdates](#)
- [ImageFrameInformation](#)
- [ImageSetProperties](#)
- [ImageSetsMetadataSummary](#)
- [ImportConfiguration](#)
- [MetadataCopies](#)
- [MetadataUpdates](#)

- [Overrides](#)
- [SearchByAttributeValue](#)
- [SearchCriteria](#)
- [SearchFilter](#)
- [Sort](#)

CopyDestinationImageSet

Copy the destination image set.

Contents

imageSetId

The image set identifier for the destination image set.

Type: String

Pattern: `[0-9a-z]{32}`

Required: Yes

latestVersionId

The latest version identifier for the destination image set.

Type: String

Pattern: `\d+`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CopyDestinationImageSetProperties

Copy the image set properties of the destination image set.

Contents

imageSetId

The image set identifier of the copied image set properties.

Type: String

Pattern: `[0-9a-z]{32}`

Required: Yes

latestVersionId

The latest version identifier for the destination image set properties.

Type: String

Pattern: `\d+`

Required: Yes

createdAt

The timestamp when the destination image set properties were created.

Type: Timestamp

Required: No

imageSetArn

The Amazon Resource Name (ARN) assigned to the destination image set.

Type: String

Pattern: `arn:aws((-us-gov)|(-iso)|(-iso-b)|(-cn))?:medical-imaging:[a-z0-9-]+:[0-9]{12}:datastore/[0-9a-z]{32}(/imageset/[0-9a-z]{32})?`

Required: No

imageSetState

The image set state of the destination image set properties.

Type: String

Valid Values: ACTIVE | LOCKED | DELETED

Required: No

imageSetWorkflowStatus

The image set workflow status of the destination image set properties.

Type: String

Valid Values: CREATED | COPIED | COPYING | COPYING_WITH_READ_ONLY_ACCESS
| COPY_FAILED | UPDATING | UPDATING_FOR_STUDY_CONSISTENCY | UPDATED
| UPDATE_FAILED | DELETING | DELETED | IMPORTING | IMPORTED |
IMPORT_FAILED

Required: No

updatedAt

The timestamp when the destination image set properties were last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CopyImageSetInformation

Copy image set information.

Contents

sourceImageSet

The source image set.

Type: [CopySourceImageSetInformation](#) object

Required: Yes

destinationImageSet

The destination image set.

Type: [CopyDestinationImageSet](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CopySourceImageSetInformation

Copy source image set information.

Contents

latestVersionId

The latest version identifier for the source image set.

Type: String

Pattern: \d+

Required: Yes

DICOMCopies

Contains MetadataCopies structure and wraps information related to specific copy use cases. For example, when copying subsets.

Type: [MetadataCopies](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CopySourceImageSetProperties

Copy source image set properties.

Contents

imageSetId

The image set identifier for the copied source image set.

Type: String

Pattern: `[0-9a-z]{32}`

Required: Yes

latestVersionId

The latest version identifier for the copied source image set.

Type: String

Pattern: `\d+`

Required: Yes

createdAt

The timestamp when the source image set properties were created.

Type: Timestamp

Required: No

imageSetArn

The Amazon Resource Name (ARN) assigned to the source image set.

Type: String

Pattern: `arn:aws((-us-gov)|(-iso)|(-iso-b)|(-cn))?:medical-imaging:[a-z0-9-]+:[0-9]{12}:datastore/[0-9a-z]{32}(/imageset/[0-9a-z]{32})?`

Required: No

imageSetState

The image set state of the copied source image set.

Type: String

Valid Values: ACTIVE | LOCKED | DELETED

Required: No

imageSetWorkflowStatus

The workflow status of the copied source image set.

Type: String

Valid Values: CREATED | COPIED | COPYING | COPYING_WITH_READ_ONLY_ACCESS
| COPY_FAILED | UPDATING | UPDATING_FOR_STUDY_CONSISTENCY | UPDATED
| UPDATE_FAILED | DELETING | DELETED | IMPORTING | IMPORTED |
IMPORT_FAILED

Required: No

updatedAt

The timestamp when the source image set properties were updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DatastoreProperties

The properties associated with the data store.

Contents

datastoreId

The data store identifier.

Type: String

Pattern: `[0-9a-z]{32}`

Required: Yes

datastoreName

The data store name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[A-Za-z0-9._/#- ]+`

Required: Yes

datastoreStatus

The data store status.

Type: String

Valid Values: `CREATING` | `CREATE_FAILED` | `ACTIVE` | `DELETING` | `DELETED`

Required: Yes

createdAt

The timestamp when the data store was created.

Type: Timestamp

Required: No

datastoreArn

The Amazon Resource Name (ARN) for the data store.

Type: String

Pattern: `arn:aws((-us-gov)|(-iso)|(-iso-b)|(-cn))?:medical-imaging:[a-z0-9-]+:[0-9]{12}:datastore/[0-9a-z]{32}(/imageset/[0-9a-z]{32})?`

Required: No

kmsKeyArn

The Amazon Resource Name (ARN) assigned to the Key Management Service (KMS) key for accessing encrypted data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:aws[a-zA-Z-]{0,16}:kms:[a-z]{2}(-[a-z]{1,16}){1,3}-\d{1}:\d{12}:((key/[a-fA-F0-9]{8}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{12})|(alias/[a-zA-Z0-9:/_-]{1,256}))`

Required: No

lambdaAuthorizerArn

The ARN of the authorizer's Lambda function.

Type: String

Pattern: `arn:(aws[a-zA-Z-]*)?:lambda:[a-z]{2}((-gov)|(-iso(b?)))?-[a-z]+\d{1}:\d{12}:function:[a-zA-Z0-9-_\+](:(\$\{LATEST|[a-zA-Z0-9-_\+])?)?`

Required: No

losslessStorageFormat

The datastore's lossless storage format.

Type: String

Valid Values: HTJ2K | JPEG_2000_LOSSLESS

Required: No

updatedAt

The timestamp when the data store was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DatastoreSummary

List of summaries of data stores.

Contents

datastoreId

The data store identifier.

Type: String

Pattern: `[0-9a-z]{32}`

Required: Yes

datastoreName

The data store name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[A-Za-z0-9._/#- ]+`

Required: Yes

datastoreStatus

The data store status.

Type: String

Valid Values: CREATING | CREATE_FAILED | ACTIVE | DELETING | DELETED

Required: Yes

createdAt

The timestamp when the data store was created.

Type: Timestamp

Required: No

datastoreArn

The Amazon Resource Name (ARN) for the data store.

Type: String

Pattern: `arn:aws((-us-gov)|(-iso)|(-iso-b)|(-cn))?:medical-imaging:[a-z0-9-]+:[0-9]{12}:datastore/[0-9a-z]{32}(/imageset/[0-9a-z]{32})?`

Required: No

updatedAt

The timestamp when the data store was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DICOMImportJobProperties

Properties of the import job.

Contents

dataAccessRoleArn

The Amazon Resource Name (ARN) that grants permissions to access medical imaging resources.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws(-[^\:]+)?:iam::[0-9]{12}:role/.+`

Required: Yes

datastoreId

The data store identifier.

Type: String

Pattern: `[0-9a-z]{32}`

Required: Yes

inputS3Uri

The input prefix path for the S3 bucket that contains the DICOM P10 files to be imported.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `s3://[a-z0-9][\.\-a-z0-9]{1,61}[a-z0-9](/.*)?`

Required: Yes

jobId

The import job identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `[0-9a-z]+`

Required: Yes

jobName

The import job name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[A-Za-z0-9._/#-]+`

Required: Yes

jobStatus

The filters for listing import jobs based on status.

Type: String

Valid Values: SUBMITTED | IN_PROGRESS | COMPLETED | FAILED

Required: Yes

outputS3Uri

The output prefix of the S3 bucket to upload the results of the DICOM import job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `s3://[a-z0-9][\.-a-z0-9]{1,61}[a-z0-9](/.*)?`

Required: Yes

endedAt

The timestamp for when the import job was ended.

Type: Timestamp

Required: No

importConfiguration

The object containing DicomJsonMetadataImportConfiguration.

Type: [ImportConfiguration](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

message

The error message thrown if an import job fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[\w - : `]+`

Required: No

submittedAt

The timestamp for when the import job was submitted.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DICOMImportJobSummary

Summary of import job.

Contents

datastoreId

The data store identifier.

Type: String

Pattern: `[0-9a-z]{32}`

Required: Yes

jobId

The import job identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `[0-9a-z]+`

Required: Yes

jobName

The import job name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[A-Za-z0-9._/#-]+`

Required: Yes

jobStatus

The filters for listing import jobs based on status.

Type: String

Valid Values: SUBMITTED | IN_PROGRESS | COMPLETED | FAILED

Required: Yes

dataAccessRoleArn

The Amazon Resource Name (ARN) that grants permissions to access medical imaging resources.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws(-[^\:]+)?:iam::[0-9]{12}:role/.+`

Required: No

endedAt

The timestamp when an import job ended.

Type: Timestamp

Required: No

message

The error message thrown if an import job fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[\w - : `]+`

Required: No

submittedAt

The timestamp when an import job was submitted.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DicomJsonMetadataImportConfiguration

The configuration parameters that are specific to DICOM JSON metadata import operations.

Contents

dicomMetadataMappings

Maps DCM files to their metadata.

Type: Array of [DicomMetadataMapping](#) objects

Array Members: Minimum number of 1 item. Maximum number of 1000 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DicomMetadataMapping

Maps DCM files to their metadata.

Contents

metadataFilePath

The path to the JSON metadata file relative to inputS3Uri.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[a-zA-Z0-9!-~]+([a-zA-Z0-9!-~ ]*[a-zA-Z0-9!-~]+)*`

Required: Yes

studyInstanceUID

The Study Instance UID that identifies the study.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 512.

Pattern: `[0-9. ]+`

Required: Yes

seriesInstanceUID

The Series Instance UID that identifies the series. This parameter is optional because the mapping might be at the study level.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 512.

Pattern: `[0-9. ]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DICOMStudyDateAndTime

The aggregated structure to store DICOM study date and study time for search capabilities.

Contents

DICOMStudyDate

The DICOM study date provided in yyMMdd format.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 36.

Required: Yes

DICOMStudyTime

The DICOM study time provided in HHmmss.FFFFFFF format.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 56.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DICOMTags

The DICOM attributes returned as a part of a response. Each image set has these properties as part of a search result.

Contents

DICOMAccessionNumber

The accession number for the DICOM study.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 512.

Required: No

DICOMNumberOfStudyRelatedInstances

The total number of instances in the DICOM study.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 1000000.

Required: No

DICOMNumberOfStudyRelatedSeries

The total number of series in the DICOM study.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 1000000.

Required: No

DICOMPatientBirthDate

The patient birth date.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 36.

Required: No

DICOMPatientId

The unique identifier for a patient in a DICOM Study.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 512.

Required: No

DICOMPatientName

The patient name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 512.

Required: No

DICOMPatientSex

The patient sex.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16.

Required: No

DICOMSeriesBodyPart

The DICOM provided identifier for the series Body Part Examined.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Required: No

DICOMSeriesInstanceUID

The DICOM provided identifier for the Series Instance UID.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 512.

Pattern: [0-9.]+

Required: No

DICOMSeriesModality

The DICOM provided identifier for the series Modality.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 32.

Required: No

DICOMSeriesNumber

The DICOM provided identifier for the Series Number.

Type: Integer

Valid Range: Minimum value of -2147483648. Maximum value of 2147483647.

Required: No

DICOMStudyDate

The study date.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 36.

Required: No

DICOMStudyDescription

The DICOM provided Study Description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 512.

Required: No

DICOMStudyId

The DICOM provided identifier for the Study ID.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 512.

Required: No

DICOMStudyInstanceUID

The DICOM provided identifier for the Study Instance UID.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 512.

Pattern: [0-9.]+

Required: No

DICOMStudyTime

The study time.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 56.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DICOMUpdates

The object containing `removableAttributes` and `updatableAttributes`.

Contents

removableAttributes

The DICOM tags to be removed from `ImageSetMetadata`.

Type: Base64-encoded binary data object

Length Constraints: Minimum length of 1. Maximum length of 10000.

Required: No

updatableAttributes

The DICOM tags that need to be updated in `ImageSetMetadata`.

Type: Base64-encoded binary data object

Length Constraints: Minimum length of 1. Maximum length of 10000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageFrameInformation

Information about the image frame (pixel data) identifier.

Contents

imageFrameId

The image frame (pixel data) identifier.

Type: String

Pattern: `[0-9a-z]{32}`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageSetProperties

The image set properties.

Contents

imageSetId

The image set identifier.

Type: String

Pattern: `[0-9a-z]{32}`

Required: Yes

imageSetState

The image set state.

Type: String

Valid Values: ACTIVE | LOCKED | DELETED

Required: Yes

versionId

The image set version identifier.

Type: String

Pattern: `\d+`

Required: Yes

createdAt

The timestamp when the image set properties were created.

Type: Timestamp

Required: No

deletedAt

The timestamp when the image set properties were deleted.

Type: Timestamp

Required: No

ImageSetWorkflowStatus

The image set workflow status.

Type: String

Valid Values: CREATED | COPIED | COPYING | COPYING_WITH_READ_ONLY_ACCESS | COPY_FAILED | UPDATING | UPDATING_FOR_STUDY_CONSISTENCY | UPDATED | UPDATE_FAILED | DELETING | DELETED | IMPORTING | IMPORTED | IMPORT_FAILED

Required: No

isPrimary

The flag to determine whether the image set is primary or not.

Type: Boolean

Required: No

message

The error message thrown if an image set action fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[\w - : `]+`

Required: No

overrides

Contains details on overrides used when creating the returned version of an image set. For example, if forced exists, the forced flag was used when creating the image set.

Type: [Overrides](#) object

Required: No

updatedAt

The timestamp when the image set properties were updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageSetsMetadataSummary

Summary of the image set metadata.

Contents

imageSetId

The image set identifier.

Type: String

Pattern: `[0-9a-z]{32}`

Required: Yes

createdAt

The time an image set is created. Sample creation date is provided in `1985-04-12T23:20:50.52Z` format.

Type: Timestamp

Required: No

DICOMTags

The DICOM tags associated with the image set.

Type: [DICOMTags](#) object

Required: No

isPrimary

The flag to determine whether the image set is primary or not.

Type: Boolean

Required: No

lastAccessedAt

When the image set was last accessed.

Type: Timestamp

Required: No

storageTier

The image set's storage tier.

Type: String

Valid Values: FREQUENT_ACCESS | ARCHIVE_INSTANT_ACCESS

Required: No

updatedAt

The time an image set was last updated.

Type: Timestamp

Required: No

version

The image set version.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImportConfiguration

The configuration options for different types of import operations.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

dicomJsonMetadataImportConfiguration

The configuration parameters that are specific to DICOM JSON metadata import operations.

Type: [DicomJsonMetadataImportConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MetadataCopies

Contains copiable `Attributes` structure and wraps information related to specific copy use cases. For example, when copying subsets.

Contents

`copiableAttributes`

The JSON string used to specify a subset of SOP Instances to copy from source to destination image set.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 260000.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MetadataUpdates

Contains DICOMUpdates.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

DICOMUpdates

The object containing removableAttributes and updatableAttributes.

Type: [DICOMUpdates](#) object

Required: No

revertToVersionId

Specifies the previous image set version ID to revert the current image set back to.

Note

You must provide either revertToVersionId or DICOMUpdates in your request. A ValidationException error is thrown if both parameters are provided at the same time.

Type: String

Pattern: \d+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Overrides

Specifies the overrides used in image set modification calls to CopyImageSet and UpdateImageSetMetadata.

Contents

forced

Providing this parameter will force completion of the CopyImageSet and UpdateImageSetMetadata actions, even if metadata is inconsistent at the Patient, Study, and/or Series levels.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SearchByAttributeValue

The search input attribute value.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

createdAt

The created at time of the image set provided for search.

Type: Timestamp

Required: No

DICOMAccessionNumber

The DICOM accession number for search.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 512.

Required: No

DICOMPatientId

The patient ID input for search.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 512.

Required: No

DICOMSeriesInstanceUID

The Series Instance UID input for search.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 512.

Pattern: [0-9.]+

Required: No

DICOMStudyDateAndTime

The aggregated structure containing DICOM study date and study time for search.

Type: [DICOMStudyDateAndTime](#) object

Required: No

DICOMStudyId

The DICOM study ID for search.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 512.

Required: No

DICOMStudyInstanceUID

The DICOM study instance UID for search.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 512.

Pattern: [0-9.]+

Required: No

isPrimary

The primary image set flag provided for search.

Type: Boolean

Required: No

updatedAt

The timestamp input for search.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SearchCriteria

The search criteria.

Contents

filters

The filters for the search criteria.

Type: Array of [SearchFilter](#) objects

Array Members: Minimum number of 1 item. Maximum number of 2 items.

Required: No

sort

The sort input for search criteria.

Type: [Sort](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SearchFilter

The search filter.

Contents

operator

The search filter operator for `imageSetDateTime`.

Type: String

Valid Values: EQUAL | BETWEEN

Required: Yes

values

The search filter values.

Type: Array of [SearchByAttributeValue](#) objects

Array Members: Minimum number of 1 item. Maximum number of 2 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Sort

Sort search results.

Contents

sortField

The sort field for search criteria.

Type: String

Valid Values: updatedAt | createdAt | DICOMStudyDateAndTime

Required: Yes

sortOrder

The sort order for search criteria.

Type: String

Valid Values: ASC | DESC

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Error Types

This section lists common error types that this AWS service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

IncompleteSignature

The request signature doesn't conform to AWS standards. Verify that you're using valid AWS credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 403

InternalFailure

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact AWS Support.

HTTP Status Code: 500

MalformedHttpRequestException

The request body can't be processed. This typically happens when the request body can't be decompressed using the specified content encoding algorithm. Verify that the content encoding header matches the compression format used.

HTTP Status Code: 400

NotAuthorized

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

OptInRequired

Your AWS account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

RequestAbortedException

The request was aborted before a response could be returned. This typically happens when the client closes the connection.

HTTP Status Code: 400

RequestEntityTooLargeException

The request entity is too large. Reduce the size of the request body and try again.

HTTP Status Code: 413

RequestTimeoutException

The request timed out. The server didn't receive the complete request within the expected time frame. Try again.

HTTP Status Code: 408

ServiceUnavailable

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

ThrottlingException

Your request rate is too high. The AWS SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

UnknownOperationException

The action or operation isn't recognized. Verify that the action name is spelled correctly and that it's supported by the API version you're using.

HTTP Status Code: 404

UnrecognizedClientException

The X.509 certificate or AWS access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

ValidationError

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400