



API Reference

AWS HealthImaging



API Version 2023-07-19

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS HealthImaging: API Reference

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
CopyImageSet	3
Request Syntax	3
URI Request Parameters	3
Request Body	4
Response Syntax	4
Response Elements	5
Errors	6
See Also	7
CreateDatastore	8
Request Syntax	8
URI Request Parameters	8
Request Body	8
Response Syntax	9
Response Elements	10
Errors	10
See Also	11
DeleteDatastore	12
Request Syntax	12
URI Request Parameters	12
Request Body	12
Response Syntax	12
Response Elements	13
Errors	13
See Also	14
DeleteImageSet	15
Request Syntax	15
URI Request Parameters	15
Request Body	15
Response Syntax	15
Response Elements	16
Errors	16
See Also	17

GetDatastore	19
Request Syntax	19
URI Request Parameters	19
Request Body	19
Response Syntax	19
Response Elements	20
Errors	20
See Also	21
GetDICOMImportJob	22
Request Syntax	22
URI Request Parameters	22
Request Body	23
Response Syntax	23
Response Elements	23
Errors	23
See Also	24
GetImageFrame	26
Request Syntax	26
URI Request Parameters	26
Request Body	26
Response Syntax	27
Response Elements	27
Errors	28
See Also	29
GetImageSet	30
Request Syntax	30
URI Request Parameters	30
Request Body	30
Response Syntax	30
Response Elements	31
Errors	33
See Also	34
GetImageSetMetadata	35
Request Syntax	35
URI Request Parameters	35
Request Body	35

Response Syntax	35
Response Elements	36
Errors	36
See Also	37
ListDatastores	38
Request Syntax	38
URI Request Parameters	38
Request Body	38
Response Syntax	38
Response Elements	39
Errors	39
See Also	40
ListDICOMImportJobs	41
Request Syntax	41
URI Request Parameters	41
Request Body	41
Response Syntax	42
Response Elements	42
Errors	43
See Also	43
ListImageSetVersions	45
Request Syntax	45
URI Request Parameters	45
Request Body	46
Response Syntax	46
Response Elements	46
Errors	47
See Also	48
ListTagsForResource	49
Request Syntax	49
URI Request Parameters	49
Request Body	49
Response Syntax	49
Response Elements	49
Errors	50
See Also	51

SearchImageSets	52
Request Syntax	52
URI Request Parameters	52
Request Body	53
Response Syntax	53
Response Elements	54
Errors	55
See Also	56
StartDICOMImportJob	57
Request Syntax	57
URI Request Parameters	57
Request Body	57
Response Syntax	59
Response Elements	59
Errors	60
See Also	61
TagResource	63
Request Syntax	63
URI Request Parameters	63
Request Body	63
Response Syntax	64
Response Elements	64
Errors	64
See Also	65
UntagResource	66
Request Syntax	66
URI Request Parameters	66
Request Body	66
Response Syntax	66
Response Elements	67
Errors	67
See Also	67
UpdateImageSetMetadata	69
Request Syntax	69
URI Request Parameters	69
Request Body	70

Response Syntax	70
Response Elements	71
Errors	72
See Also	73
Data Types	75
CopyDestinationImageSet	77
Contents	77
See Also	77
CopyDestinationImageSetProperties	78
Contents	78
See Also	79
CopyImageSetInformation	80
Contents	80
See Also	80
CopySourceImageSetInformation	81
Contents	81
See Also	81
CopySourceImageSetProperties	82
Contents	82
See Also	83
DatastoreProperties	84
Contents	84
See Also	85
DatastoreSummary	87
Contents	87
See Also	88
DICOMImportJobProperties	89
Contents	89
See Also	91
DICOMImportJobSummary	92
Contents	92
See Also	94
DICOMStudyDateAndTime	95
Contents	95
See Also	95
DICOMTags	96

Contents	96
See Also	99
DICOMUpdates	100
Contents	100
See Also	100
ImageFrameInformation	101
Contents	101
See Also	101
ImageSetProperties	102
Contents	102
See Also	104
ImageSetsMetadataSummary	105
Contents	105
See Also	106
MetadataCopies	107
Contents	107
See Also	107
MetadataUpdates	108
Contents	108
See Also	108
Overrides	110
Contents	110
See Also	110
SearchByAttributeValue	111
Contents	111
See Also	113
SearchCriteria	114
Contents	114
See Also	114
SearchFilter	115
Contents	115
See Also	115
Sort	116
Contents	116
See Also	116
Common Parameters	117

Common Errors	120
----------------------------	------------

Welcome

This is the *AWS HealthImaging API Reference*. For an introduction to the service, see [What is AWS HealthImaging?](#) in the *AWS HealthImaging Developer Guide*.

This document was last published on July 19, 2025.

Actions

The following actions are supported:

- [CopyImageSet](#)
- [CreateDatastore](#)
- [DeleteDatastore](#)
- [DeleteImageSet](#)
- [GetDatastore](#)
- [GetDICOMImportJob](#)
- [GetImageFrame](#)
- [GetImageSet](#)
- [GetImageSetMetadata](#)
- [ListDatastores](#)
- [ListDICOMImportJobs](#)
- [ListImageSetVersions](#)
- [ListTagsForResource](#)
- [SearchImageSets](#)
- [StartDICOMImportJob](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateImageSetMetadata](#)

CopyImageSet

Copy an image set.

Request Syntax

```
POST /datastore/datastoreId/imageSet/sourceImageSetId/copyImageSet?  
force=force&promoteToPrimary=promoteToPrimary HTTP/1.1  
Content-type: application/json  
  
{  
    "destinationImageSet        "imageSetId": "string",  
        "latestVersionId": "string"  
    },  
    "sourceImageSet        "DICOMCopies            "copiableAttributes": "string"  
        },  
        "latestVersionId": "string"  
    }  
}
```

URI Request Parameters

The request uses the following URI parameters.

datastoreId

The data store identifier.

Pattern: [0-9a-z]{32}

Required: Yes

force

Providing this parameter will force completion of the CopyImageSet operation, even if there are inconsistent Patient, Study, and/or Series level metadata elements between the sourceImageSet and destinationImageSet.

[promoteToPrimary](#)

Providing this parameter will configure the CopyImageSet operation to promote the given image set to the primary DICOM hierarchy. If successful, a new primary image set ID will be returned as the destination image set.

[sourceImageSetId](#)

The source image set identifier.

Pattern: [0-9a-z]{32}

Required: Yes

Request Body

The request accepts the following data in JSON format.

[destinationImageSet](#)

The destination image set.

Type: [CopyDestinationImageSet](#) object

Required: No

[sourceImageSet](#)

The source image set.

Type: [CopySourceImageSetInformation](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "datastoreId": "string",
  "destinationImageSetProperties": {
```

```
"createdAt": number,
"imageSetArn": "string",
"imageSetId": "string",
"imageSetState": "string",
"imageSetWorkflowStatus": "string",
"latestVersionId": "string",
"updatedAt": number
},
"sourceImageSetProperties": {
  "createdAt": number,
  "imageSetArn": "string",
  "imageSetId": "string",
  "imageSetState": "string",
  "imageSetWorkflowStatus": "string",
  "latestVersionId": "string",
  "updatedAt": number
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[datastoreId](#)

The data store identifier.

Type: String

Pattern: [0-9a-z]{32}

[destinationImageSetProperties](#)

The properties of the destination image set.

Type: [CopyDestinationImageSetProperties](#) object

[sourceImageSetProperties](#)

The properties of the source image set.

Type: [CopySourceImageSetProperties](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request caused a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateDatastore

Create a data store.

Request Syntax

```
POST /datastore HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "datastoreName": "string",
  "kmsKeyArn": "string",
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique identifier for API idempotency.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9._-]+

Required: Yes

datastoreName

The data store name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [A-Za-z0-9._/#-]+

Required: No

kmsKeyArn

The Amazon Resource Name (ARN) assigned to the Key Management Service (KMS) key for accessing encrypted data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: arn:aws[a-zA-Z-]{0,16}:kms:[a-z]{2}(-[a-z]{1,16}){1,3}-\d{1}:\d{12}:((key/[a-fA-F0-9]{8}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{12})|(alias/[a-zA-Z0-9:_-]{1,256}))

Required: No

tags

The tags provided when creating a data store.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: (?!aws:)[a-zA-Z+-.=:_:/]+

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "datastoreId": "string",
  "datastoreStatus": "string"
```

}

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[datastoreId](#)

The data store identifier.

Type: String

Pattern: [0-9a-z]{32}

[datastoreStatus](#)

The data store status.

Type: String

Valid Values: CREATING | CREATE_FAILED | ACTIVE | DELETING | DELETED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ServiceQuotaExceededException

The request caused a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteDatastore

Delete a data store.

Note

Before a data store can be deleted, you must first delete all image sets within it.

Request Syntax

```
DELETE /datastore/datastoreId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[datastoreId](#)

The data store identifier.

Pattern: [0-9a-z]{32}

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "datastoreId": "string",
  "datastoreStatus": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[datastoreId](#)

The data store identifier.

Type: String

Pattern: [0-9a-z]{32}

[datastoreStatus](#)

The data store status.

Type: String

Valid Values: CREATING | CREATE_FAILED | ACTIVE | DELETING | DELETED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerError

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteImageSet

Delete an image set.

Request Syntax

```
POST /datastore/datastoreId/imageSet/imageSetId/deleteImageSet HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[datastoreId](#)

The data store identifier.

Pattern: [0-9a-z]{32}

Required: Yes

[imageSetId](#)

The image set identifier.

Pattern: [0-9a-z]{32}

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "datastoreId": "string",
  "imageSetId": "string",
  "imageSetState": "string",
```

```
    "imageSetWorkflowStatus": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[datastoreId](#)

The data store identifier.

Type: String

Pattern: [0-9a-z]{32}

[imageSetId](#)

The image set identifier.

Type: String

Pattern: [0-9a-z]{32}

[imageSetState](#)

The image set state.

Type: String

Valid Values: ACTIVE | LOCKED | DELETED

[imageSetWorkflowStatus](#)

The image set workflow status.

Type: String

Valid Values: CREATED | COPIED | COPYING | COPYING_WITH_READONLY_ACCESS | COPY_FAILED | UPDATING | UPDATED | UPDATE_FAILED | DELETING | DELETED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetDatastore

Get data store properties.

Request Syntax

```
GET /datastore/datastoreId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[datastoreId](#)

The data store identifier.

Pattern: [0-9a-z]{32}

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "datastoreProperties": {
    "createdAtdatastoreArn": "string",
    "datastoreId": "string",
    "datastoreName": "string",
    "datastoreStatus": "string",
    "kmsKeyArn": "string",
    "updatedAt": "number"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[datastoreProperties](#)

The data store properties.

Type: [DatastoreProperties](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetDICOMImportJob

Get the import job properties to learn more about the job or job progress.

Note

The jobStatus refers to the execution of the import job. Therefore, an import job can return a jobStatus as COMPLETED even if validation issues are discovered during the import process. If a jobStatus returns as COMPLETED, we still recommend you review the output manifests written to S3, as they provide details on the success or failure of individual P10 object imports.

Request Syntax

```
GET /getDICOMImportJob/datastore/datastoreId/job/jobId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[datastoreId](#)

The data store identifier.

Pattern: [0-9a-z]{32}

Required: Yes

[jobId](#)

The import job identifier.

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: [0-9a-z]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
    "jobProperties": {
        "dataAccessRoleArn": "string",
        "datastoreId": "string",
        "endedAt": number,
        "inputS3Uri": "string",
        "jobId": "string",
        "jobName": "string",
        "jobStatus": "string",
        "message": "string",
        "outputS3Uri": "string",
        "submittedAt": number
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[jobProperties](#)

The properties of the import job.

Type: [DICOMImportJobProperties](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetImageFrame

Get an image frame (pixel data) for an image set.

Request Syntax

```
POST /datastore/datastoreId/imageSet/imageSetId/getImageFrame HTTP/1.1
Content-type: application/json

{
    "imageFrameId
```

URI Request Parameters

The request uses the following URI parameters.

datastoreId

The data store identifier.

Pattern: [0-9a-z]{32}

Required: Yes

imageSetId

The image set identifier.

Pattern: [0-9a-z]{32}

Required: Yes

Request Body

The request accepts the following data in JSON format.

imageFrameId

The image frame (pixel data) identifier.

Type: String

Pattern: [0-9a-z]{32}

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-Type: contentType

imageFrameBlob
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The response returns the following HTTP headers.

[contentType](#)

The format in which the image frame information is returned to the customer. Default is application/octet-stream.

Note

- If the stored transfer syntax is 1.2.840.10008.1.2.1, the returned contentType is application/octet-stream.
- If the stored transfer syntax is 1.2.840.10008.1.2.4.50, the returned contentType is image/jpeg.
- If the stored transfer syntax is 1.2.840.10008.1.2.4.91, the returned contentType is image/j2c.
- If the stored transfer syntax is MPEG2, 1.2.840.10008.1.2.4.100, 1.2.840.10008.1.2.4.100.1, 1.2.840.10008.1.2.4.101, or 1.2.840.10008.1.2.4.101.1, the returned contentType is video/mpeg.
- If the stored transfer syntax is MPEG-4 AVC/H.264, UID 1.2.840.10008.1.2.4.102, 1.2.840.10008.1.2.4.102.1, 1.2.840.10008.1.2.4.103, 1.2.840.10008.1.2.4.103.1, 1.2.840.10008.1.2.4.104, 1.2.840.10008.1.2.4.104.1, 1.2.840.10008.1.2.4.105, 1.2.840.10008.1.2.4.105.1,

1.2.840.10008.1.2.4.106, or 1.2.840.10008.1.2.4.106.1, the returned contentType is video/mp4.

- If the stored transfer syntax is HEVC/H.265, UID 1.2.840.10008.1.2.4.107 or 1.2.840.10008.1.2.4.108, the returned contentType is video/H265.
- If the stored transfer syntax is 1.2.840.10008.1.2.4.202 or if the stored transfer syntax is *missing*, the returned contentType is image/jph.
- If the stored transfer syntax is 1.2.840.10008.1.2.4.203, the returned contentType is image/jphc.

The response returns the following as the HTTP body.

imageFrameBlob

The blob containing the aggregated image frame information.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetImageSet

Get image set properties.

Request Syntax

```
POST /datastore/datastoreId/imageSet/imageSetId/getImageSet?version=versionId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[datastoreId](#)

The data store identifier.

Pattern: [0-9a-z]{32}

Required: Yes

[imageSetId](#)

The image set identifier.

Pattern: [0-9a-z]{32}

Required: Yes

[versionId](#)

The image set version identifier.

Pattern: \d+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Content-type: application/json

```
{  
  "createdAt": number,  
  "datastoreId": "string",  
  "deletedAt": number,  
  "imageSetArn": "string",  
  "imageSetId": "string",  
  "imageSetState": "string",  
  "imageSetWorkflowStatus": "string",  
  "isPrimary": boolean,  
  "message": "string",  
  "overrides": {  
    "forced": boolean  
  },  
  "updatedAt": number,  
  "versionId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[createdAt](#)

The timestamp when image set properties were created.

Type: Timestamp

[datastoreId](#)

The data store identifier.

Type: String

Pattern: [0-9a-z]{32}

[deletedAt](#)

The timestamp when the image set properties were deleted.

Type: Timestamp

[imageSetArn](#)

The Amazon Resource Name (ARN) assigned to the image set.

Type: String

Pattern: arn:aws((-us-gov)|(-iso)|(-iso-b)|(-cn))?:medical-imaging:[a-zA-Z0-9-]+:[0-9]{12}:datastore/[0-9a-z]{32}(/imageset/[0-9a-z]{32})?

[imageSetId](#)

The image set identifier.

Type: String

Pattern: [0-9a-z]{32}

[imageSetState](#)

The image set state.

Type: String

Valid Values: ACTIVE | LOCKED | DELETED

[imageSetWorkflowStatus](#)

The image set workflow status.

Type: String

Valid Values: CREATED | COPIED | COPYING | COPYING_WITH_READ_ONLY_ACCESS | COPY_FAILED | UPDATING | UPDATED | UPDATE_FAILED | DELETING | DELETED

[isPrimary](#)

The flag to determine whether the image set is primary or not.

Type: Boolean

[message](#)

The error message thrown if an image set action fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[\w - :]+`

overrides

This object contains the details of any overrides used while creating a specific image set version. If an image set was copied or updated using the `force` flag, this object will contain the `forced` flag.

Type: [Overrides](#) object

updatedAt

The timestamp when image set properties were updated.

Type: Timestamp

versionId

The image set version identifier.

Type: String

Pattern: `\d+`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetImageSetMetadata

Get metadata attributes for an image set.

Request Syntax

```
POST /datastore/datastoreId/imageSet/imageSetId/getImageSetMetadata?version=versionId
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[datastoreId](#)

The data store identifier.

Pattern: [0-9a-z]{32}

Required: Yes

[imageSetId](#)

The image set identifier.

Pattern: [0-9a-z]{32}

Required: Yes

[versionId](#)

The image set version identifier.

Pattern: \d+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Content-Type: *contentType*
Content-Encoding: *contentEncoding*

imageSetMetadataBlob

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The response returns the following HTTP headers.

[contentEncoding](#)

The compression format in which image set metadata attributes are returned.

[contentType](#)

The format in which the study metadata is returned to the customer. Default is text/plain.

The response returns the following as the HTTP body.

[imageSetMetadataBlob](#)

The blob containing the aggregated metadata information for the image set.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerError

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListDatastores

List data stores.

Request Syntax

```
GET /datastore?  
datastoreStatus=datastoreStatus&maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[datastoreStatus](#)

The data store status.

Valid Values: CREATING | CREATE_FAILED | ACTIVE | DELETING | DELETED

[maxResults](#)

Valid Range: Minimum value of 1. Maximum value of 50.

Valid Range: Minimum value of 1. Maximum value of 50.

[nextToken](#)

The pagination token used to request the list of data stores on the next page.

Length Constraints: Minimum length of 1. Maximum length of 8192.

Pattern: \p{ASCII}{0,8192}

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{  
    "datastoreSummaries": [  
        {  
            "createdAt": number,  
            "datastoreArn": "string",  
            "datastoreId": "string",  
            "datastoreName": "string",  
            "datastoreStatus": "string",  
            "updatedAt": number  
        }  
    ],  
    "nextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[datastoreSummaries](#)

The list of summaries of data stores.

Type: Array of [DatastoreSummary](#) objects

[nextToken](#)

The pagination token used to retrieve the list of data stores on the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8192.

Pattern: \p{ASCII}{0,8192}

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListDICOMImportJobs

List import jobs created for a specific data store.

Request Syntax

```
GET /listDICOMImportJobs/datastore/datastoreId?  
jobStatus=jobStatus&maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[datastoreId](#)

The data store identifier.

Pattern: [0-9a-z]{32}

Required: Yes

[jobStatus](#)

The filters for listing import jobs based on status.

Valid Values: SUBMITTED | IN_PROGRESS | COMPLETED | FAILED

[maxResults](#)

The max results count. The upper bound is determined by load testing.

Valid Range: Minimum value of 1. Maximum value of 50.

[nextToken](#)

The pagination token used to request the list of import jobs on the next page.

Length Constraints: Minimum length of 1. Maximum length of 8192.

Pattern: \p{ASCII}{0,8192}

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
    "jobSummaries": [
        {
            "dataAccessRoleArn": "string",
            "datastoreId": "string",
            "endedAt": number,
            "jobId": "string",
            "jobName": "string",
            "jobStatus": "string",
            "message": "string",
            "submittedAt": number
        }
    ],
    "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[jobSummaries](#)

A list of job summaries.

Type: Array of [DICOMImportJobSummary](#) objects

[nextToken](#)

The pagination token used to retrieve the list of import jobs on the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8192.

Pattern: \p{ASCII}{0,8192}

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListImageSetVersions

List image set versions.

Request Syntax

```
POST /datastore/datastoreId/imageSet/imageSetId/listImageSetVersions?  
maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[datastoreId](#)

The data store identifier.

Pattern: [0-9a-z]{32}

Required: Yes

[imageSetId](#)

The image set identifier.

Pattern: [0-9a-z]{32}

Required: Yes

[maxResults](#)

The max results count.

Valid Range: Minimum value of 1. Maximum value of 50.

[nextToken](#)

The pagination token used to request the list of image set versions on the next page.

Length Constraints: Minimum length of 1. Maximum length of 8192.

Pattern: \p{ASCII}{0,8192}

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
    "imageSetPropertiesList": [
        {
            "createdAt": number,
            "deletedAt": number,
            "imageSetId": "string",
            "imageSetState": "string",
            "ImageSetWorkflowStatus": "string",
            "isPrimary": boolean,
            "message": "string",
            "overrides": {
                "forced": boolean
            },
            "updatedAt": number,
            "versionId": "string"
        }
    ],
    "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[imageSetPropertiesList](#)

Lists all properties associated with an image set.

Type: Array of [ImageSetProperties](#) objects

[nextToken](#)

The pagination token used to retrieve the list of image set versions on the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8192.

Pattern: \p{ASCII}{0,8192}

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Lists all tags associated with a medical imaging resource.

Request Syntax

```
GET /tags/resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the medical imaging resource to list tags for.

Pattern: arn:aws((-us-gov)|(-iso)|(-iso-b)|(-cn))?:medical-imaging:[a-zA-Z0-9-]+:[0-9]{12}:datastore/[0-9a-z]{32}(/imageset/[0-9a-z]{32})?

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "tags": {
    "string": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tags

A list of all tags associated with a medical imaging resource.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: (? !aws :)[a-zA-Z+-=._:/]+

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

SearchImageSets

Search image sets based on defined input attributes.

Note

SearchImageSets accepts a single search query parameter and returns a paginated response of all image sets that have the matching criteria. All date range queries must be input as (lowerBound, upperBound).

By default, SearchImageSets uses the updatedAt field for sorting in descending order from newest to oldest.

Request Syntax

```
POST /datastore/datastoreId/searchImageSets?maxResults=maxResults&nextToken=nextToken
HTTP/1.1
Content-type: application/json

{
  "filtersoperatorvaluessortsortFieldsortOrder
```

URI Request Parameters

The request uses the following URI parameters.

[datastoreId](#)

The identifier of the data store where the image sets reside.

Pattern: [0-9a-z]{32}

Required: Yes

maxResults

The maximum number of results that can be returned in a search.

Valid Range: Minimum value of 1. Maximum value of 50.

nextToken

The token used for pagination of results returned in the response. Use the token returned from the previous request to continue results where the previous request ended.

Length Constraints: Minimum length of 1. Maximum length of 8192.

Pattern: \p{ASCII}{0,8192}

Request Body

The request accepts the following data in JSON format.

filters

The filters for the search criteria.

Type: Array of [SearchFilter](#) objects

Array Members: Minimum number of 1 item. Maximum number of 2 items.

Required: No

sort

The sort input for search criteria.

Type: [Sort](#) object

Required: No

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{  
    "imageSetsMetadataSummaries": [  
        {  
            "createdAt": number,  
            "DICOMTags": {  
                "DICOMAccessionNumber": "string",  
                "DICOMNumberOfStudyRelatedInstances": number,  
                "DICOMNumberOfStudyRelatedSeries": number,  
                "DICOMPatientBirthDate": "string",  
                "DICOMPatientId": "string",  
                "DICOMPatientName": "string",  
                "DICOMPatientSex": "string",  
                "DICOMSeriesBodyPart": "string",  
                "DICOMSeriesInstanceUID": "string",  
                "DICOMSeriesModality": "string",  
                "DICOMSeriesNumber": number,  
                "DICOMStudyDate": "string",  
                "DICOMStudyDescription": "string",  
                "DICOMStudyId": "string",  
                "DICOMStudyInstanceUID": "string",  
                "DICOMStudyTime": "string"  
            },  
            "imageSetId": "string",  
            "isPrimary": boolean,  
            "updatedAt": number,  
            "version": number  
        },  
        ],  
        "nextToken": "string",  
        "sort": {  
            "sortField": "string",  
            "sortOrder": "string"  
        }  
    }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[imageSetsMetadataSummaries](#)

The model containing the image set results.

Type: Array of [ImageSetsMetadataSummary](#) objects

[nextToken](#)

The token for pagination results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8192.

Pattern: \p{ASCII}{0,8192}

[sort](#)

The sort order for image set search results.

Type: [Sort](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerError

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartDICOMImportJob

Start importing bulk data into an ACTIVE data store. The import job imports DICOM P10 files found in the S3 prefix specified by the `inputS3Uri` parameter. The import job stores processing results in the file specified by the `outputS3Uri` parameter.

Request Syntax

```
POST /startDICOMImportJob/datastore/datastoreId HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "dataAccessRoleArn": "string",
  "inputOwnerAccountId": "string",
  "inputS3Uri": "string",
  "jobName": "string",
  "outputS3Uri": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

[datastoreId](#)

The data store identifier.

Pattern: [0-9a-z]{32}

Required: Yes

Request Body

The request accepts the following data in JSON format.

[clientToken](#)

A unique identifier for API idempotency.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9._-]+

Required: Yes

[dataAccessRoleArn](#)

The Amazon Resource Name (ARN) of the IAM role that grants permission to access medical imaging resources.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: arn:aws(-[^:]*)?:iam::[0-9]{12}:role/.+

Required: Yes

[inputOwnerAccountId](#)

The account ID of the source S3 bucket owner.

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d+

Required: No

[inputS3Uri](#)

The input prefix path for the S3 bucket that contains the DICOM files to be imported.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: s3://[a-zA-Z0-9][\.\-\a-zA-Z0-9]{1,61}[a-zA-Z0-9](/.*)?

Required: Yes

[jobName](#)

The import job name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9._/-]+

Required: No

outputS3Uri

The output prefix of the S3 bucket to upload the results of the DICOM import job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: s3://[a-zA-Z0-9][\.\-_a-zA-Z0-9]{1,61}[a-zA-Z0-9](/.*)?

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "datastoreId": "string",
  "jobId": "string",
  "jobStatus": "string",
  "submittedAt": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

datastoreId

The data store identifier.

Type: String

Pattern: [0-9a-z]{32}

jobId

The import job identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: [0-9a-z]+

jobStatus

The import job status.

Type: String

Valid Values: SUBMITTED | IN_PROGRESS | COMPLETED | FAILED

submittedAt

The timestamp when the import job was submitted.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerError

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request caused a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Adds a user-specified key and value tag to a medical imaging resource.

Request Syntax

```
POST /tags/resourceArn HTTP/1.1
Content-type: application/json

{
  "tags": {
    "string": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the medical imaging resource that tags are being added to.

Pattern: arn:aws((-us-gov)|(-iso)|(-iso-b)|(-cn))?:medical-imaging:[a-z0-9-]+:[0-9]{12}:datastore/[0-9a-z]{32}(/imageset/[0-9a-z]{32})?

Required: Yes

Request Body

The request accepts the following data in JSON format.

tags

The user-specified key and value tag pairs added to a medical imaging resource.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: (? !aws :)[a-zA-Z+-=._:/]+

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

Response Syntax

HTTP/1.1 200

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Removes tags from a medical imaging resource.

Request Syntax

```
DELETE /tags/resourceArn?tagKeys=tagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the medical imaging resource that tags are being removed from.

Pattern: arn:aws((-us-gov)|(-iso)|(-iso-b)|(-cn))?:medical-imaging:[a-z0-9-]+:[0-9]{12}:datastore/[0-9a-z]{32}(/imageset/[0-9a-z]{32})?

Required: Yes

tagKeys

The keys for the tags to be removed from the medical imaging resource.

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (?!aws:)[a-zA-Z+-.=:_:/]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateImageSetMetadata

Update image set metadata attributes.

Request Syntax

```
POST /datastore/datastoreId/imageSet/imageSetId/updateImageSetMetadata?  
force=force&latestVersion=latestVersionId HTTP/1.1  
Content-type: application/json  
  
{  
    "DICOMUpdates": {  
        "removableAttributes": blob,  
        "updatableAttributes": blob  
    },  
    "revertToVersionId": "string"  
}
```

URI Request Parameters

The request uses the following URI parameters.

[datastoreId](#)

The data store identifier.

Pattern: [0-9a-z]{32}

Required: Yes

[force](#)

Setting this flag will force the UpdateImageSetMetadata operation for the following attributes:

- Tag.StudyInstanceUID, Tag.SeriesInstanceUID, Tag.SOPInstanceUID, and Tag.StudyID
- Adding, removing, or updating private tags for an individual SOP Instance

[imageSetId](#)

The image set identifier.

Pattern: [0-9a-z]{32}

Required: Yes

latestVersionId

The latest image set version identifier.

Pattern: \d+

Required: Yes

Request Body

The request accepts the following data in JSON format.

DICOMUpdates

The object containing removableAttributes and updatableAttributes.

Type: [DICOMUpdates](#) object

Required: No

revertToVersionId

Specifies the previous image set version ID to revert the current image set back to.

Note

You must provide either revertToVersionId or DICOMUpdates in your request. A ValidationException error is thrown if both parameters are provided at the same time.

Type: String

Pattern: \d+

Required: No

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{  
    "createdAt": number,  
    "datastoreId": "string",  
    "imageSetId": "string",  
    "imageSetState": "string",  
    "imageSetWorkflowStatus": "string",  
    "latestVersionId": "string",  
    "message": "string",  
    "updatedAt": number  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

createdAt

The timestamp when image set metadata was created.

Type: Timestamp

datastoreId

The data store identifier.

Type: String

Pattern: [0-9a-z]{32}

imageSetId

The image set identifier.

Type: String

Pattern: [0-9a-z]{32}

imageSetState

The image set state.

Type: String

Valid Values: ACTIVE | LOCKED | DELETED

[imageSetWorkflowStatus](#)

The image set workflow status.

Type: String

Valid Values: CREATED | COPIED | COPYING | COPYING_WITH_READONLY_ACCESS | COPY_FAILED | UPDATING | UPDATED | UPDATE_FAILED | DELETING | DELETED

[latestVersionId](#)

The latest image set version identifier.

Type: String

Pattern: \d+

[message](#)

The error message thrown if an update image set metadata action fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: [\w - :]+

[updatedAt](#)

The timestamp when image set metadata was updated.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

An unexpected error occurred during processing of the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource which does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request caused a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The request was denied due to throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints set by the service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS Health Imaging API contains several data types that various actions use. This section describes each data type in detail.

 **Note**

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [CopyDestinationImageSet](#)
- [CopyDestinationImageSetProperties](#)
- [CopyImageSetInformation](#)
- [CopySourceImageSetInformation](#)
- [CopySourceImageSetProperties](#)
- [DatastoreProperties](#)
- [DatastoreSummary](#)
- [DICOMImportJobProperties](#)
- [DICOMImportJobSummary](#)
- [DICOMStudyDateAndTime](#)
- [DICOMTags](#)
- [DICOMUpdates](#)
- [ImageFrameInformation](#)
- [ImageSetProperties](#)
- [ImageSetsMetadataSummary](#)
- [MetadataCopies](#)
- [MetadataUpdates](#)
- [Overrides](#)
- [SearchByAttributeValue](#)
- [SearchCriteria](#)

- [SearchFilter](#)
- [Sort](#)

CopyDestinationImageSet

Copy the destination image set.

Contents

imageSetId

The image set identifier for the destination image set.

Type: String

Pattern: [0-9a-z]{32}

Required: Yes

latestVersionId

The latest version identifier for the destination image set.

Type: String

Pattern: \d+

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CopyDestinationImageSetProperties

Copy the image set properties of the destination image set.

Contents

imageSetId

The image set identifier of the copied image set properties.

Type: String

Pattern: [0-9a-z]{32}

Required: Yes

latestVersionId

The latest version identifier for the destination image set properties.

Type: String

Pattern: \d+

Required: Yes

createdAt

The timestamp when the destination image set properties were created.

Type: Timestamp

Required: No

imageSetArn

The Amazon Resource Name (ARN) assigned to the destination image set.

Type: String

Pattern: arn:aws((-us-gov)|(-iso)|(-iso-b)|(-cn))?:medical-imaging:[a-zA-Z0-9-]+:[0-9]{12}:datastore/[0-9a-z]{32}(/imageset/[0-9a-z]{32})?

Required: No

imageSetState

The image set state of the destination image set properties.

Type: String

Valid Values: ACTIVE | LOCKED | DELETED

Required: No

imageSetWorkflowStatus

The image set workflow status of the destination image set properties.

Type: String

Valid Values: CREATED | COPIED | COPYING | COPYING_WITH_READONLY_ACCESS | COPY_FAILED | UPDATING | UPDATED | UPDATE_FAILED | DELETING | DELETED

Required: No

updatedAt

The timestamp when the destination image set properties were last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CopyImageSetInformation

Copy image set information.

Contents

sourceImageSet

The source image set.

Type: [CopySourceImageSetInformation](#) object

Required: Yes

destinationImageSet

The destination image set.

Type: [CopyDestinationImageSet](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CopySourceImageSetInformation

Copy source image set information.

Contents

latestVersionId

The latest version identifier for the source image set.

Type: String

Pattern: \d+

Required: Yes

DICOMCopies

Contains MetadataCopies structure and wraps information related to specific copy use cases.
For example, when copying subsets.

Type: [MetadataCopies](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CopySourceImageSetProperties

Copy source image set properties.

Contents

imageSetId

The image set identifier for the copied source image set.

Type: String

Pattern: [0-9a-z]{32}

Required: Yes

latestVersionId

The latest version identifier for the copied source image set.

Type: String

Pattern: \d+

Required: Yes

createdAt

The timestamp when the source image set properties were created.

Type: Timestamp

Required: No

imageSetArn

The Amazon Resource Name (ARN) assigned to the source image set.

Type: String

Pattern: arn:aws((-us-gov)|(-iso)|(-iso-b)|(-cn))?:medical-imaging:[a-zA-Z0-9-]+:[0-9]{12}:datastore/[0-9a-z]{32}(/imageset/[0-9a-z]{32})?

Required: No

imageSetState

The image set state of the copied source image set.

Type: String

Valid Values: ACTIVE | LOCKED | DELETED

Required: No

imageSetWorkflowStatus

The workflow status of the copied source image set.

Type: String

Valid Values: CREATED | COPIED | COPYING | COPYING_WITH_READONLY_ACCESS | COPY_FAILED | UPDATING | UPDATED | UPDATE_FAILED | DELETING | DELETED

Required: No

updatedAt

The timestamp when the source image set properties were updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DatastoreProperties

The properties associated with the data store.

Contents

datastoreId

The data store identifier.

Type: String

Pattern: [0-9a-z]{32}

Required: Yes

datastoreName

The data store name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [A-Za-z0-9._/#-]+

Required: Yes

datastoreStatus

The data store status.

Type: String

Valid Values: CREATING | CREATE_FAILED | ACTIVE | DELETING | DELETED

Required: Yes

createdAt

The timestamp when the data store was created.

Type: Timestamp

Required: No

datastoreArn

The Amazon Resource Name (ARN) for the data store.

Type: String

Pattern: `arn:aws((-us-gov)|(-iso)|(-iso-b)|(-cn))?:medical-imaging:[a-zA-Z0-9-]+:[0-9]{12}:datastore/[0-9a-z]{32}(/imageset/[0-9a-z]{32})?`

Required: No

kmsKeyArn

The Amazon Resource Name (ARN) assigned to the Key Management Service (KMS) key for accessing encrypted data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:aws[a-zA-Z-]{0,16}:kms:[a-z]{2}(-[a-z]{1,16}){1,3}-\d{1}:\d{12}:((key/[a-fA-F0-9]{8}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{12})|(alias/[a-zA-Z0-9:_-]{1,256}))`

Required: No

updatedAt

The timestamp when the data store was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DatastoreSummary

List of summaries of data stores.

Contents

datastoreId

The data store identifier.

Type: String

Pattern: [0-9a-z]{32}

Required: Yes

datastoreName

The data store name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [A-Za-z0-9._/#-]+

Required: Yes

datastoreStatus

The data store status.

Type: String

Valid Values: CREATING | CREATE_FAILED | ACTIVE | DELETING | DELETED

Required: Yes

createdAt

The timestamp when the data store was created.

Type: Timestamp

Required: No

datastoreArn

The Amazon Resource Name (ARN) for the data store.

Type: String

Pattern: `arn:aws((-us-gov)|(-iso)|(-iso-b)|(-cn))?:medical-imaging:[a-zA-Z0-9-]+:[0-9]{12}:datastore/[0-9a-z]{32}(/imageset/[0-9a-z]{32})?`

Required: No

updatedAt

The timestamp when the data store was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DICOMImportJobProperties

Properties of the import job.

Contents

dataAccessRoleArn

The Amazon Resource Name (ARN) that grants permissions to access medical imaging resources.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws(-[:.]+)?:iam::[0-9]{12}:role/.+`

Required: Yes

datastoreId

The data store identifier.

Type: String

Pattern: `[0-9a-z]{32}`

Required: Yes

inputS3Uri

The input prefix path for the S3 bucket that contains the DICOM P10 files to be imported.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `s3://[a-zA-Z0-9][\.\-\w]{1,61}[a-zA-Z0-9](/.*)?`

Required: Yes

jobId

The import job identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: [0-9a-z]+

Required: Yes

jobName

The import job name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9._/#-]+

Required: Yes

jobStatus

The filters for listing import jobs based on status.

Type: String

Valid Values: SUBMITTED | IN_PROGRESS | COMPLETED | FAILED

Required: Yes

outputS3Uri

The output prefix of the S3 bucket to upload the results of the DICOM import job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: s3://[a-z0-9][\.\-\a-z0-9]{1,61}[a-z0-9](/.*)?

Required: Yes

endedAt

The timestamp for when the import job was ended.

Type: Timestamp

Required: No

message

The error message thrown if an import job fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: [\w - :]+

Required: No

submittedAt

The timestamp for when the import job was submitted.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DICOMImportJobSummary

Summary of import job.

Contents

datastoreId

The data store identifier.

Type: String

Pattern: [0-9a-z]{32}

Required: Yes

jobId

The import job identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: [0-9a-z]+

Required: Yes

jobName

The import job name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9._/#-]+

Required: Yes

jobStatus

The filters for listing import jobs based on status.

Type: String

Valid Values: SUBMITTED | IN_PROGRESS | COMPLETED | FAILED

Required: Yes

dataAccessRoleArn

The Amazon Resource Name (ARN) that grants permissions to access medical imaging resources.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: arn:aws(-[^:]+)?:iam::[0-9]{12}:role/.+

Required: No

endedAt

The timestamp when an import job ended.

Type: Timestamp

Required: No

message

The error message thrown if an import job fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: [\w - :]+

Required: No

submittedAt

The timestamp when an import job was submitted.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DICOMStudyDateAndTime

The aggregated structure to store DICOM study date and study time for search capabilities.

Contents

DICOMStudyDate

The DICOM study date provided in yyMMdd format.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 18.

Required: Yes

DICOMStudyTime

The DICOM study time provided in HHmmss . FFFFFF format.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 28.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DICOMTags

The DICOM attributes returned as a part of a response. Each image set has these properties as part of a search result.

Contents

DICOMAccessionNumber

The accession number for the DICOM study.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

DICOMNumberOfStudyRelatedInstances

The total number of instances in the DICOM study.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 10000.

Required: No

DICOMNumberOfStudyRelatedSeries

The total number of series in the DICOM study.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 1000000.

Required: No

DICOMPatientBirthDate

The patient birth date.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 18.

Required: No

DICOPatientId

The unique identifier for a patient in a DICOM Study.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

DICOPatientName

The patient name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

DICOPatientSex

The patient sex.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16.

Required: No

DICOMSeriesBodyPart

The DICOM provided identifier for the series Body Part Examined.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 64.

Required: No

DICOMSeriesInstanceUID

The DICOM provided identifier for the Series Instance UID.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: (?:[0-9][0-9]*|0)(\.(?:[1-9][0-9]*|0))*

Required: No

DICOMSeriesModality

The DICOM provided identifier for the series Modality.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16.

Required: No

DICOMSeriesNumber

The DICOM provided identifier for the Series Number.

Type: Integer

Valid Range: Minimum value of -2147483648. Maximum value of 2147483647.

Required: No

DICOMStudyDate

The study date.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 18.

Required: No

DICOMStudyDescription

The DICOM provided Study Description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 64.

Required: No

DICOMStudyId

The DICOM provided identifier for the Study ID.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16.

Required: No

DICOMStudyInstanceUID

The DICOM provided identifier for the Study Instance UID.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: (?:[0-9][0-9]*|0)(\.(?:[1-9][0-9]*|0))*

Required: No

DICOMStudyTime

The study time.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 28.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DICOMUpdates

The object containing `removableAttributes` and `updatableAttributes`.

Contents

removableAttributes

The DICOM tags to be removed from `ImageSetMetadata`.

Type: Base64-encoded binary data object

Length Constraints: Minimum length of 1. Maximum length of 10000.

Required: No

updatableAttributes

The DICOM tags that need to be updated in `ImageSetMetadata`.

Type: Base64-encoded binary data object

Length Constraints: Minimum length of 1. Maximum length of 10000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageFrameInformation

Information about the image frame (pixel data) identifier.

Contents

imageFrameId

The image frame (pixel data) identifier.

Type: String

Pattern: [0-9a-z]{32}

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageSetProperties

The image set properties.

Contents

imageSetId

The image set identifier.

Type: String

Pattern: [0-9a-z]{32}

Required: Yes

imageSetState

The image set state.

Type: String

Valid Values: ACTIVE | LOCKED | DELETED

Required: Yes

versionId

The image set version identifier.

Type: String

Pattern: \d+

Required: Yes

createdAt

The timestamp when the image set properties were created.

Type: Timestamp

Required: No

deletedAt

The timestamp when the image set properties were deleted.

Type: Timestamp

Required: No

ImageSetWorkflowStatus

The image set workflow status.

Type: String

Valid Values: CREATED | COPIED | COPYING | COPYING_WITH_READONLY_ACCESS | COPY_FAILED | UPDATING | UPDATED | UPDATE_FAILED | DELETING | DELETED

Required: No

isPrimary

The flag to determine whether the image set is primary or not.

Type: Boolean

Required: No

message

The error message thrown if an image set action fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: [\w - :]+

Required: No

overrides

Contains details on overrides used when creating the returned version of an image set. For example, if forced exists, the forced flag was used when creating the image set.

Type: [Overrides](#) object

Required: No

updatedAt

The timestamp when the image set properties were updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageSetsMetadataSummary

Summary of the image set metadata.

Contents

imageSetId

The image set identifier.

Type: String

Pattern: [0-9a-z]{32}

Required: Yes

createdAt

The time an image set is created. Sample creation date is provided in 1985-04-12T23:20:50.52Z format.

Type: Timestamp

Required: No

DICOMTags

The DICOM tags associated with the image set.

Type: [DICOMTags](#) object

Required: No

isPrimary

The flag to determine whether the image set is primary or not.

Type: Boolean

Required: No

updatedAt

The time an image set was last updated.

Type: Timestamp

Required: No

version

The image set version.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MetadataCopies

Contains copiable Attributes structure and wraps information related to specific copy use cases. For example, when copying subsets.

Contents

copiableAttributes

The JSON string used to specify a subset of SOP Instances to copy from source to destination image set.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 260000.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MetadataUpdates

Contains DICOMUpdates.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

DICOMUpdates

The object containing removableAttributes and updatableAttributes.

Type: [DICOMUpdates object](#)

Required: No

revertToVersionId

Specifies the previous image set version ID to revert the current image set back to.

Note

You must provide either revertToVersionId or DICOMUpdates in your request. A ValidationException error is thrown if both parameters are provided at the same time.

Type: String

Pattern: \d+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Overrides

Specifies the overrides used in image set modification calls to CopyImageSet and UpdateImageSetMetadata.

Contents

forced

Providing this parameter will force completion of the CopyImageSet and UpdateImageSetMetadata actions, even if metadata is inconsistent at the Patient, Study, and/or Series levels.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SearchByAttributeValue

The search input attribute value.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

createdAt

The created at time of the image set provided for search.

Type: Timestamp

Required: No

DICOMAccessionNumber

The DICOM accession number for search.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

DICOMPatientId

The patient ID input for search.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

DICOMSeriesInstanceUID

The Series Instance UID input for search.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: (?:[0-9][0-9]*|0)(\.(?:[1-9][0-9]*|0))*

Required: No

DICOMStudyDateAndTime

The aggregated structure containing DICOM study date and study time for search.

Type: [DICOMStudyDateAndTime](#) object

Required: No

DICOMStudyId

The DICOM study ID for search.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16.

Required: No

DICOMStudyInstanceUID

The DICOM study instance UID for search.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: (?:[0-9][0-9]*|0)(\.(?:[1-9][0-9]*|0))*

Required: No

isPrimary

The primary image set flag provided for search.

Type: Boolean

Required: No

updatedAt

The timestamp input for search.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SearchCriteria

The search criteria.

Contents

filters

The filters for the search criteria.

Type: Array of [SearchFilter](#) objects

Array Members: Minimum number of 1 item. Maximum number of 2 items.

Required: No

sort

The sort input for search criteria.

Type: [Sort](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SearchFilter

The search filter.

Contents

operator

The search filter operator for `imageSetDateTime`.

Type: String

Valid Values: EQUAL | BETWEEN

Required: Yes

values

The search filter values.

Type: Array of [SearchByAttributeValue](#) objects

Array Members: Minimum number of 1 item. Maximum number of 2 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Sort

Sort search results.

Contents

sortField

The sort field for search criteria.

Type: String

Valid Values: updatedAt | createdAt | DICOMStudyDateAndTime

Required: Yes

sortOrder

The sort order for search criteria.

Type: String

Valid Values: ASC | DESC

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests in the IAM User Guide](#).

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request").

The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request is expired

HTTP Status Code: 403

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 403

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

MalformedHttpRequestException

Problems with the request at the HTTP level, e.g. we can't decompress the body according to the decompression algorithm specified by the content-encoding.

HTTP Status Code: 400

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 401

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestAbortedException

Convenient exception that can be used when a request is aborted before a reply is sent back (e.g. client closed connection).

HTTP Status Code: 400

RequestEntityTooLargeException

Problems with the request at the HTTP level. The request entity is too large.

HTTP Status Code: 413

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

RequestTimeoutException

Problems with the request at the HTTP level. Reading the Request timed out.

HTTP Status Code: 408

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

UnrecognizedClientException

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

UnknownOperationException

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 404

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400