



API Reference

AWS HealthLake



API Version 2017-07-01

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS HealthLake: API Reference

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
CreateFHIRDatastore	3
Request Syntax	3
Request Parameters	3
Response Syntax	5
Response Elements	5
Errors	6
See Also	7
DeleteFHIRDatastore	8
Request Syntax	8
Request Parameters	8
Response Syntax	8
Response Elements	8
Errors	9
See Also	10
DescribeFHIRDatastore	12
Request Syntax	12
Request Parameters	12
Response Syntax	12
Response Elements	13
Errors	13
See Also	14
DescribeFHIRExportJob	15
Request Syntax	15
Request Parameters	15
Response Syntax	16
Response Elements	16
Errors	16
See Also	17
DescribeFHIRImportJob	18
Request Syntax	18
Request Parameters	18
Response Syntax	19

Response Elements	19
Errors	19
See Also	20
ListFHIRDatastores	21
Request Syntax	21
Request Parameters	21
Response Syntax	22
Response Elements	23
Errors	23
See Also	24
ListFHIRExportJobs	25
Request Syntax	25
Request Parameters	25
Response Syntax	27
Response Elements	27
Errors	28
See Also	28
ListFHIRImportJobs	30
Request Syntax	30
Request Parameters	30
Response Syntax	32
Response Elements	32
Errors	33
See Also	34
ListTagsForResource	35
Request Syntax	35
Request Parameters	35
Response Syntax	35
Response Elements	36
Errors	36
See Also	36
StartFHIRExportJob	38
Request Syntax	38
Request Parameters	38
Response Syntax	39
Response Elements	40

Errors	40
See Also	41
StartFHIRImportJob	43
Request Syntax	43
Request Parameters	43
Response Syntax	45
Response Elements	45
Errors	46
See Also	46
TagResource	48
Request Syntax	48
Request Parameters	48
Response Elements	49
Errors	49
See Also	49
UntagResource	51
Request Syntax	51
Request Parameters	51
Response Elements	52
Errors	52
See Also	52
Data Types	53
DatastoreFilter	54
Contents	54
See Also	55
DatastoreProperties	56
Contents	56
See Also	58
ErrorCause	59
Contents	59
See Also	59
ExportJobProperties	60
Contents	60
See Also	62
IdentityProviderConfiguration	63
Contents	63

See Also	64
ImportJobProperties	66
Contents	66
See Also	68
InputDataConfig	69
Contents	69
See Also	69
JobProgressReport	70
Contents	70
See Also	71
KmsEncryptionConfig	72
Contents	72
See Also	72
OutputDataConfig	74
Contents	74
See Also	74
PreloadDataConfig	75
Contents	75
See Also	75
S3Configuration	76
Contents	76
See Also	76
SseConfiguration	78
Contents	78
See Also	78
Tag	79
Contents	79
See Also	79
Common Parameters	80
Common Errors	83

Welcome

This is the *AWS HealthLake API Reference*. For an introduction to the service, see [What is AWS HealthLake?](#) in the *AWS HealthLake Developer Guide*.

This document was last published on July 22, 2025.

Actions

The following actions are supported:

- [CreateFHIRDatastore](#)
- [DeleteFHIRDatastore](#)
- [DescribeFHIRDatastore](#)
- [DescribeFHIRExportJob](#)
- [DescribeFHIRImportJob](#)
- [ListFHIRDatastores](#)
- [ListFHIRExportJobs](#)
- [ListFHIRImportJobs](#)
- [ListTagsForResource](#)
- [StartFHIRExportJob](#)
- [StartFHIRImportJob](#)
- [TagResource](#)
- [UntagResource](#)

CreateFHIRDatastore

Create a FHIR-enabled data store.

Request Syntax

```
{
  "ClientToken": "string",
  "DatastoreName": "string",
  "DatastoreTypeVersion": "string",
  "IdentityProviderConfiguration": {
    "AuthorizationStrategy": "string",
    "FineGrainedAuthorizationEnabled": boolean,
    "IdpLambdaArn": "string",
    "Metadata": "string"
  },
  "PreloadDataConfig": {
    "PreloadDataType": "string"
  },
  "SseConfiguration": {
    "KmsEncryptionConfig": {
      "CmkType": "string",
      "KmsKeyId": "string"
    }
  },
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClientToken

An optional user-provided token to ensure API idempotency.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9-]+$`

Required: No

DatastoreName

The data store name (user-generated).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

Required: No

DatastoreTypeVersion

The FHIR release version supported by the data store. Current support is for version R4.

Type: String

Valid Values: R4

Required: Yes

IdentityProviderConfiguration

The identity provider configuration to use for the data store.

Type: [IdentityProviderConfiguration](#) object

Required: No

PreloadDataConfig

An optional parameter to preload (import) open source Synthea FHIR data upon creation of the data store.

Type: [PreloadDataConfig](#) object

Required: No

SseConfiguration

The server-side encryption key configuration for a customer-provided encryption key specified for creating a data store.

Type: [SseConfiguration](#) object

Required: No

Tags

The resource tags applied to a data store when it is created.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

Response Syntax

```
{
  "DatastoreArn": "string",
  "DatastoreEndpoint": "string",
  "DatastoreId": "string",
  "DatastoreStatus": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DatastoreArn

The Amazon Resource Name (ARN) for the data store.

Type: String

Pattern: `^arn:aws((-us-gov)|(-iso)|(-iso-b)|(-cn))?:healthlake:[a-zA-Z0-9-]+:[0-9]{12}:datastore/.+?`

DatastoreEndpoint

The AWS endpoint created for the data store.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 5000.

Pattern: `[\P{M}\p{M}]{1,5000}`

DatastoreId

The data store identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

DatastoreStatus

The data store status.

Type: String

Valid Values: CREATING | ACTIVE | DELETING | DELETED | CREATE_FAILED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied. Your account is not authorized to perform this operation.

HTTP Status Code: 400

InternalServerError

An unknown internal error occurred in the service.

HTTP Status Code: 500

ThrottlingException

The user has exceeded their maximum number of allowed calls to the given API.

HTTP Status Code: 400

ValidationException

The user input parameter was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteFHIRDatastore

Delete a FHIR-enabled data store.

Request Syntax

```
{
  "DatastoreId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[DatastoreId](#)

The AWS-generated identifier for the data store to be deleted.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

Required: Yes

Response Syntax

```
{
  "DatastoreArn": "string",
  "DatastoreEndpoint": "string",
  "DatastoreId": "string",
  "DatastoreStatus": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DatastoreArn

The Amazon Resource Name (ARN) that grants access permission to AWS HealthLake.

Type: String

Pattern: `^arn:aws((-us-gov)|(-iso)|(-iso-b)|(-cn))?:healthlake:[a-zA-Z0-9-]+:[0-9]{12}:datastore/.+?`

DatastoreEndpoint

The AWS endpoint of the data store to be deleted.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 5000.

Pattern: `[\P{M}\p{M}]{1,5000}`

DatastoreId

The AWS-generated ID for the deleted data store.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

DatastoreStatus

The data store status.

Type: String

Valid Values: CREATING | ACTIVE | DELETING | DELETED | CREATE_FAILED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied. Your account is not authorized to perform this operation.

HTTP Status Code: 400

ConflictException

The data store is in a transition state and the user requested action cannot be performed.

HTTP Status Code: 400

InternalServerErrorException

An unknown internal error occurred in the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested data store was not found.

HTTP Status Code: 400

ThrottlingException

The user has exceeded their maximum number of allowed calls to the given API.

HTTP Status Code: 400

ValidationException

The user input parameter was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeFHIRDatastore

Get properties for a FHIR-enabled data store.

Request Syntax

```
{  
  "DatastoreId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[DatastoreId](#)

The data store identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

Required: Yes

Response Syntax

```
{  
  "DatastoreProperties": {  
    "CreatedAt": number,  
    "DatastoreArn": "string",  
    "DatastoreEndpoint": "string",  
    "DatastoreId": "string",  
    "DatastoreName": "string",  
    "DatastoreStatus": "string",  
    "DatastoreTypeVersion": "string",  
    "ErrorCause": {
```

```
    "ErrorCategory": "string",
    "ErrorMessage": "string"
  },
  "IdentityProviderConfiguration": {
    "AuthorizationStrategy": "string",
    "FineGrainedAuthorizationEnabled": boolean,
    "IdpLambdaArn": "string",
    "Metadata": "string"
  },
  "PreloadDataConfig": {
    "PreloadDataType": "string"
  },
  "SseConfiguration": {
    "KmsEncryptionConfig": {
      "CmkType": "string",
      "KmsKeyId": "string"
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DatastoreProperties

The data store properties.

Type: [DatastoreProperties](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

An unknown internal error occurred in the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested data store was not found.

HTTP Status Code: 400

ThrottlingException

The user has exceeded their maximum number of allowed calls to the given API.

HTTP Status Code: 400

ValidationException

The user input parameter was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeFHIRExportJob

Get FHIR export job properties.

Request Syntax

```
{  
  "DatastoreId": "string",  
  "JobId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

DatastoreId

The data store identifier from which FHIR data is being exported from.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

Required: Yes

JobId

The export job identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

Required: Yes

Response Syntax

```
{
  "ExportJobProperties": {
    "DataAccessRoleArn": "string",
    "DatastoreId": "string",
    "EndTime": number,
    "JobId": "string",
    "JobName": "string",
    "JobStatus": "string",
    "Message": "string",
    "OutputDataConfig": { ... },
    "SubmitTime": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ExportJobProperties](#)

The export job properties.

Type: [ExportJobProperties](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

An unknown internal error occurred in the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested data store was not found.

HTTP Status Code: 400

ThrottlingException

The user has exceeded their maximum number of allowed calls to the given API.

HTTP Status Code: 400

ValidationException

The user input parameter was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeFHIRImportJob

Get the import job properties to learn more about the job or job progress.

Request Syntax

```
{  
  "DatastoreId": "string",  
  "JobId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

DatastoreId

The data store identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

Required: Yes

JobId

The import job identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

Required: Yes

Response Syntax

```
{
  "ImportJobProperties": {
    "DataAccessRoleArn": "string",
    "DatastoreId": "string",
    "EndTime": number,
    "InputDataConfig": { ... },
    "JobId": "string",
    "JobName": "string",
    "JobOutputDataConfig": { ... },
    "JobProgressReport": {
      "Throughput": number,
      "TotalNumberOfFilesReadWithCustomerError": number,
      "TotalNumberOfImportedFiles": number,
      "TotalNumberOfResourcesImported": number,
      "TotalNumberOfResourcesScanned": number,
      "TotalNumberOfResourcesWithCustomerError": number,
      "TotalNumberOfScannedFiles": number,
      "TotalSizeOfScannedFilesInMB": number
    },
    "JobStatus": "string",
    "Message": "string",
    "SubmitTime": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ImportJobProperties

The import job properties.

Type: [ImportJobProperties](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An unknown internal error occurred in the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested data store was not found.

HTTP Status Code: 400

ThrottlingException

The user has exceeded their maximum number of allowed calls to the given API.

HTTP Status Code: 400

ValidationException

The user input parameter was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListFHIRDatastores

List all FHIR-enabled data stores in a user's account, regardless of data store status.

Request Syntax

```
{
  "Filter": {
    "CreatedAfter": number,
    "CreatedBefore": number,
    "DatastoreName": "string",
    "DatastoreStatus": "string"
  },
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filter

List all filters associated with a FHIR data store request.

Type: [DatastoreFilter](#) object

Required: No

MaxResults

The maximum number of data stores returned on a page.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 500.

Required: No

NextToken

The token used to retrieve the next page of data stores when results are paginated.

Type: String

Length Constraints: Maximum length of 8192.

Pattern: \p{ASCII}{0,8192}

Required: No

Response Syntax

```
{
  "DatastorePropertiesList": [
    {
      "CreatedAt": number,
      "DatastoreArn": "string",
      "DatastoreEndpoint": "string",
      "DatastoreId": "string",
      "DatastoreName": "string",
      "DatastoreStatus": "string",
      "DatastoreTypeVersion": "string",
      "ErrorCause": {
        "ErrorCategory": "string",
        "ErrorMessage": "string"
      },
      "IdentityProviderConfiguration": {
        "AuthorizationStrategy": "string",
        "FineGrainedAuthorizationEnabled": boolean,
        "IdpLambdaArn": "string",
        "Metadata": "string"
      },
      "PreloadDataConfig": {
        "PreloadDataType": "string"
      },
      "SseConfiguration": {
        "KmsEncryptionConfig": {
          "CmkType": "string",
          "KmsKeyId": "string"
        }
      }
    }
  ],
  "NextToken": "string"
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[DatastorePropertiesList](#)

The properties associated with all listed data stores.

Type: Array of [DatastoreProperties](#) objects

[NextToken](#)

The pagination token used to retrieve the next page of results.

Type: String

Length Constraints: Maximum length of 8192.

Pattern: \p{ASCII}{0,8192}

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

An unknown internal error occurred in the service.

HTTP Status Code: 500

ThrottlingException

The user has exceeded their maximum number of allowed calls to the given API.

HTTP Status Code: 400

ValidationException

The user input parameter was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListFHIRExportJobs

Lists all FHIR export jobs associated with an account and their statuses.

Request Syntax

```
{
  "DatastoreId": "string",
  "JobName": "string",
  "JobStatus": "string",
  "MaxResults": number,
  "NextToken": "string",
  "SubmittedAfter": number,
  "SubmittedBefore": number
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

DatastoreId

Limits the response to the export job with the specified data store ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

Required: Yes

JobName

Limits the response to the export job with the specified job name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

Required: No

JobStatus

Limits the response to export jobs with the specified job status.

Type: String

Valid Values: SUBMITTED | QUEUED | IN_PROGRESS | COMPLETED_WITH_ERRORS
| COMPLETED | FAILED | CANCEL_SUBMITTED | CANCEL_IN_PROGRESS |
CANCEL_COMPLETED | CANCEL_FAILED

Required: No

MaxResults

Limits the number of results returned for a ListFHIRExportJobs to a maximum quantity specified by the user.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 500.

Required: No

NextToken

A pagination token used to identify the next page of results to return.

Type: String

Length Constraints: Maximum length of 8192.

Pattern: \p{ASCII}{0,8192}

Required: No

SubmittedAfter

Limits the response to FHIR export jobs submitted after a user-specified date.

Type: Timestamp

Required: No

SubmittedBefore

Limits the response to FHIR export jobs submitted before a user- specified date.

Type: Timestamp

Required: No

Response Syntax

```
{
  "ExportJobPropertiesList": [
    {
      "DataAccessRoleArn": "string",
      "DatastoreId": "string",
      "EndTime": number,
      "JobId": "string",
      "JobName": "string",
      "JobStatus": "string",
      "Message": "string",
      "OutputDataConfig": { ... },
      "SubmitTime": number
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ExportJobPropertiesList

The properties of listed FHIR export jobs.

Type: Array of [ExportJobProperties](#) objects

NextToken

The pagination token used to identify the next page of results to return.

Type: String

Length Constraints: Maximum length of 8192.

Pattern: \p{ASCII}{0,8192}

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied. Your account is not authorized to perform this operation.

HTTP Status Code: 400

InternalServerError

An unknown internal error occurred in the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested data store was not found.

HTTP Status Code: 400

ThrottlingException

The user has exceeded their maximum number of allowed calls to the given API.

HTTP Status Code: 400

ValidationException

The user input parameter was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListFHIRImportJobs

List all FHIR import jobs associated with an account and their statuses.

Request Syntax

```
{
  "DatastoreId": "string",
  "JobName": "string",
  "JobStatus": "string",
  "MaxResults": number,
  "NextToken": "string",
  "SubmittedAfter": number,
  "SubmittedBefore": number
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

DatastoreId

Limits the response to the import job with the specified data store ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

Required: Yes

JobName

Limits the response to the import job with the specified job name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

Required: No

JobStatus

Limits the response to the import job with the specified job status.

Type: String

Valid Values: SUBMITTED | QUEUED | IN_PROGRESS | COMPLETED_WITH_ERRORS
| COMPLETED | FAILED | CANCEL_SUBMITTED | CANCEL_IN_PROGRESS |
CANCEL_COMPLETED | CANCEL_FAILED

Required: No

MaxResults

Limits the number of results returned for `ListFHIRImportJobs` to a maximum quantity specified by the user.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 500.

Required: No

NextToken

The pagination token used to identify the next page of results to return.

Type: String

Length Constraints: Maximum length of 8192.

Pattern: `\p{ASCII}{0,8192}`

Required: No

SubmittedAfter

Limits the response to FHIR import jobs submitted after a user-specified date.

Type: Timestamp

Required: No

SubmittedBefore

Limits the response to FHIR import jobs submitted before a user- specified date.

Type: Timestamp

Required: No

Response Syntax

```
{
  "ImportJobPropertiesList": [
    {
      "DataAccessRoleArn": "string",
      "DatastoreId": "string",
      "EndTime": number,
      "InputDataConfig": { ... },
      "JobId": "string",
      "JobName": "string",
      "JobOutputDataConfig": { ... },
      "JobProgressReport": {
        "Throughput": number,
        "TotalNumberOfFilesReadWithCustomerError": number,
        "TotalNumberOfImportedFiles": number,
        "TotalNumberOfResourcesImported": number,
        "TotalNumberOfResourcesScanned": number,
        "TotalNumberOfResourcesWithCustomerError": number,
        "TotalNumberOfScannedFiles": number,
        "TotalSizeOfScannedFilesInMB": number
      },
      "JobStatus": "string",
      "Message": "string",
      "SubmitTime": number
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ImportJobPropertiesList](#)

The properties for listed import jobs.

Type: Array of [ImportJobProperties](#) objects

[NextToken](#)

The pagination token used to identify the next page of results to return.

Type: String

Length Constraints: Maximum length of 8192.

Pattern: \p{ASCII}{0,8192}

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied. Your account is not authorized to perform this operation.

HTTP Status Code: 400

InternalServerErrorException

An unknown internal error occurred in the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested data store was not found.

HTTP Status Code: 400

ThrottlingException

The user has exceeded their maximum number of allowed calls to the given API.

HTTP Status Code: 400

ValidationException

The user input parameter was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Returns a list of all existing tags associated with a data store.

Request Syntax

```
{  
  "ResourceARN": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ResourceARN

The Amazon Resource Name (ARN) of the data store to which tags are being added.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `^arn:aws((-us-gov)|(-iso)|(-iso-b)|(-cn))?:healthlake:[a-z0-9-]+:\d{12}:datastore\/fhir\/.{32}`

Required: Yes

Response Syntax

```
{  
  "Tags": [  
    {  
      "Key": "string",  
      "Value": "string"  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Tags

Returns a list of tags associated with a data store.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

The requested data store was not found.

HTTP Status Code: 400

ValidationException

The user input parameter was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartFHIRExportJob

Start a FHIR export job.

Request Syntax

```
{  
  "ClientToken": "string",  
  "DataAccessRoleArn": "string",  
  "DatastoreId": "string",  
  "JobName": "string",  
  "OutputDataConfig": { ... }  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClientToken

An optional user provided token used for ensuring API idempotency.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9-]+$`

Required: No

DataAccessRoleArn

The Amazon Resource Name (ARN) used during initiation of the export job.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws(-[^\:]+)?:iam:[0-9]{12}:role/.+`

Required: Yes

DatastoreId

The data store identifier from which files are being exported.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

Required: Yes

JobName

The export job name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

Required: No

OutputDataConfig

The output data configuration supplied when the export job was started.

Type: [OutputDataConfig](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

Response Syntax

```
{
  "DatastoreId": "string",
  "JobId": "string",
  "JobStatus": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DatastoreId

The data store identifier from which files are being exported.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

JobId

The export job identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

JobStatus

The export job status.

Type: String

Valid Values: SUBMITTED | QUEUED | IN_PROGRESS | COMPLETED_WITH_ERRORS
| COMPLETED | FAILED | CANCEL_SUBMITTED | CANCEL_IN_PROGRESS |
CANCEL_COMPLETED | CANCEL_FAILED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied. Your account is not authorized to perform this operation.

HTTP Status Code: 400

InternalServerErrorException

An unknown internal error occurred in the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested data store was not found.

HTTP Status Code: 400

ThrottlingException

The user has exceeded their maximum number of allowed calls to the given API.

HTTP Status Code: 400

ValidationException

The user input parameter was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartFHIRImportJob

Start importing bulk FHIR data into an ACTIVE data store. The import job imports FHIR data found in the `InputDataConfig` object and stores processing results in the `JobOutputDataConfig` object.

Request Syntax

```
{  
  "ClientToken": "string",  
  "DataAccessRoleArn": "string",  
  "DatastoreId": "string",  
  "InputDataConfig": { ... },  
  "JobName": "string",  
  "JobOutputDataConfig": { ... }  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClientToken

The optional user-provided token used for ensuring API idempotency.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9-]+$`

Required: No

DataAccessRoleArn

The Amazon Resource Name (ARN) that grants access permission to AWS HealthLake.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws(-[^\:]+)?:iam::[0-9]{12}:role/.+`

Required: Yes

DatastoreId

The data store identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

Required: Yes

InputDataConfig

The input properties for the import job request.

Type: [InputDataConfig](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

JobName

The import job name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

Required: No

JobOutputDataConfig

The output data configuration supplied when the export job was created.

Type: [OutputDataConfig](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

Response Syntax

```
{
  "DatastoreId": "string",
  "JobId": "string",
  "JobStatus": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DatastoreId

The data store identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

JobId

The import job identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

JobStatus

The import job status.

Type: String

Valid Values: SUBMITTED | QUEUED | IN_PROGRESS | COMPLETED_WITH_ERRORS
| COMPLETED | FAILED | CANCEL_SUBMITTED | CANCEL_IN_PROGRESS |
CANCEL_COMPLETED | CANCEL_FAILED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied. Your account is not authorized to perform this operation.

HTTP Status Code: 400

InternalServerErrorException

An unknown internal error occurred in the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested data store was not found.

HTTP Status Code: 400

ThrottlingException

The user has exceeded their maximum number of allowed calls to the given API.

HTTP Status Code: 400

ValidationException

The user input parameter was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Add a user-specified key and value tag to a data store.

Request Syntax

```
{
  "ResourceARN": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ResourceARN](#)

The Amazon Resource Name (ARN) that grants access to the data store tags are being added to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `^arn:aws((-us-gov)|(-iso)|(-iso-b)|(-cn))?:healthlake:[a-z0-9-]+:\d{12}:datastore\/fhir\/.{32}`

Required: Yes

[Tags](#)

The user-specified key and value pair tags being added to a data store.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

The requested data store was not found.

HTTP Status Code: 400

ValidationException

The user input parameter was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Remove a user-specified key and value tag from a data store.

Request Syntax

```
{  
  "ResourceARN": "string",  
  "TagKeys": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ResourceARN](#)

The Amazon Resource Name (ARN) of the data store from which tags are being removed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `^arn:aws((-us-gov)|(-iso)|(-iso-b)|(-cn))?:healthlake:[a-z0-9-]+:\d{12}:datastore\/fhir\/.{32}`

Required: Yes

[TagKeys](#)

The keys for the tags to be removed from the data store.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^([\p{L}\p{Z}\p{N}_.:\/=+~@]*)$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

The requested data store was not found.

HTTP Status Code: 400

ValidationException

The user input parameter was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The Amazon HealthLake API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [DatastoreFilter](#)
- [DatastoreProperties](#)
- [ErrorCause](#)
- [ExportJobProperties](#)
- [IdentityProviderConfiguration](#)
- [ImportJobProperties](#)
- [InputDataConfig](#)
- [JobProgressReport](#)
- [KmsEncryptionConfig](#)
- [OutputDataConfig](#)
- [PreloadDataConfig](#)
- [S3Configuration](#)
- [SseConfiguration](#)
- [Tag](#)

DatastoreFilter

The filters applied to a data store query.

Contents

CreatedAfter

Filter to set cutoff dates for records. All data stores created after the specified date are included in the results.

Type: Timestamp

Required: No

CreatedBefore

Filter to set cutoff dates for records. All data stores created before the specified date are included in the results.

Type: Timestamp

Required: No

DatastoreName

Filter data store results by name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

Required: No

DatastoreStatus

Filter data store results by status.

Type: String

Valid Values: CREATING | ACTIVE | DELETING | DELETED | CREATE_FAILED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DatastoreProperties

The data store properties.

Contents

DatastoreArn

The Amazon Resource Name (ARN) used in the creation of the data store.

Type: String

Pattern: `^arn:aws((-us-gov)|(-iso)|(-iso-b)|(-cn))?:healthlake:[a-zA-Z0-9-]+:[0-9]{12}:datastore/.+?`

Required: Yes

DatastoreEndpoint

The AWS endpoint for the data store.

Type: String

Length Constraints: Maximum length of 10000.

Pattern: `[\P{M}\p{M}]{0,10000}`

Required: Yes

DatastoreId

The data store identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

Required: Yes

DatastoreStatus

The data store status.

Type: String

Valid Values: CREATING | ACTIVE | DELETING | DELETED | CREATE_FAILED

Required: Yes

DatastoreTypeVersion

The FHIR release version supported by the data store. Current support is for version R4.

Type: String

Valid Values: R4

Required: Yes

CreatedAt

The time the data store was created.

Type: Timestamp

Required: No

DatastoreName

The data store name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

Required: No

ErrorCause

The error cause for the current data store operation.

Type: [ErrorCause](#) object

Required: No

IdentityProviderConfiguration

The identity provider selected during data store creation.

Type: [IdentityProviderConfiguration](#) object

Required: No

PreloadDataConfig

The preloaded Synthea data configuration for the data store.

Type: [PreloadDataConfig](#) object

Required: No

SseConfiguration

The server-side encryption key configuration for a customer provided encryption key.

Type: [SseConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ErrorCause

The error information for `CreateFHIRDatastore` and `DeleteFHIRDatastore` actions.

Contents

ErrorCategory

The error category for `ErrorCause`.

Type: String

Valid Values: `RETRYABLE_ERROR` | `NON_RETRYABLE_ERROR`

Required: No

ErrorMessage

The error message text for `ErrorCause`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ExportJobProperties

The properties of a FHIR export job.

Contents

DatastoreId

The data store identifier from which files are being exported.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

Required: Yes

JobId

The export job identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

Required: Yes

JobStatus

The export job status.

Type: String

Valid Values: SUBMITTED | QUEUED | IN_PROGRESS | COMPLETED_WITH_ERRORS
| COMPLETED | FAILED | CANCEL_SUBMITTED | CANCEL_IN_PROGRESS |
CANCEL_COMPLETED | CANCEL_FAILED

Required: Yes

OutputDataConfig

The output data configuration supplied when the export job was created.

Type: [OutputDataConfig](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

SubmitTime

The time the export job was initiated.

Type: Timestamp

Required: Yes

DataAccessRoleArn

The Amazon Resource Name (ARN) used during the initiation of the export job.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws(-[^\:]+)?:iam::[0-9]{12}:role/.+`

Required: No

EndTime

The time the export job completed.

Type: Timestamp

Required: No

JobName

The export job name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

Required: No

Message

An explanation of any errors that might have occurred during the export job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IdentityProviderConfiguration

The identity provider configuration selected when the data store was created.

Contents

AuthorizationStrategy

The authorization strategy selected when the HealthLake data store is created.

Note

HealthLake provides support for both SMART on FHIR V1 and V2 as described below.

- SMART_ON_FHIR_V1 – Support for only SMART on FHIR V1, which includes read (read/search) and write (create/update/delete) permissions.
- SMART_ON_FHIR – Support for both SMART on FHIR V1 and V2, which includes create, read, update, delete, and search permissions.
- AWS_AUTH – The default HealthLake authorization strategy; not affiliated with SMART on FHIR.

Type: String

Valid Values: SMART_ON_FHIR_V1 | SMART_ON_FHIR | AWS_AUTH

Required: Yes

FineGrainedAuthorizationEnabled

The parameter to enable SMART on FHIR fine-grained authorization for the data store.

Type: Boolean

Required: No

IdpLambdaArn

The Amazon Resource Name (ARN) of the Lambda function to use to decode the access token created by the authorization server.

Type: String

Length Constraints: Minimum length of 49. Maximum length of 256.

Pattern: `arn:aws:lambda:[a-z]{2}-[a-z]+\d{1}:\d{12}:function:[a-zA-Z0-9\-\_\.\.]+(:(\d{12}|[a-zA-Z0-9\-\_\.\.]+))?`

Required: No

Metadata

The JSON metadata elements to use in your identity provider configuration. Required elements are listed based on the launch specification of the SMART application. For more information on all possible elements, see [Metadata](#) in SMART's App Launch specification.

`authorization_endpoint`: The URL to the OAuth2 authorization endpoint.

`grant_types_supported`: An array of grant types that are supported at the token endpoint. You must provide at least one grant type option. Valid options are `authorization_code` and `client_credentials`.

`token_endpoint`: The URL to the OAuth2 token endpoint.

`capabilities`: An array of strings of the SMART capabilities that the authorization server supports.

`code_challenge_methods_supported`: An array of strings of supported PKCE code challenge methods. You must include the S256 method in the array of PKCE code challenge methods.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImportJobProperties

The import job properties.

Contents

DatastoreId

The data store identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: $^([\p{L}\p{Z}\p{N}_.: /+=\-%@] *)\$$

Required: Yes

InputDataConfig

The input data configuration supplied when the import job was created.

Type: [InputDataConfig](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

JobId

The import job identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: $^([\p{L}\p{Z}\p{N}_.: /+=\-%@] *)\$$

Required: Yes

JobStatus

The import job status.

Type: String

Valid Values: SUBMITTED | QUEUED | IN_PROGRESS | COMPLETED_WITH_ERRORS
| COMPLETED | FAILED | CANCEL_SUBMITTED | CANCEL_IN_PROGRESS |
CANCEL_COMPLETED | CANCEL_FAILED

Required: Yes

SubmitTime

The time the import job was submitted for processing.

Type: Timestamp

Required: Yes

DataAccessRoleArn

The Amazon Resource Name (ARN) that grants AWS HealthLake access to the input data.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws(-[^:]+)?:iam::[0-9]{12}:role/.+`

Required: No

EndTime

The time the import job was completed.

Type: Timestamp

Required: No

JobName

The import job name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

Required: No

JobOutputDataConfig

The output data configuration supplied when the export job was created.

Type: [OutputDataConfig](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

JobProgressReport

Displays the progress of the import job, including total resources scanned, total resources imported, and total size of data imported.

Type: [JobProgressReport](#) object

Required: No

Message

An explanation of any errors that might have occurred during the FHIR import job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\-%@]*)$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InputDataConfig

The import job input properties.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

S3Uri

The `S3Uri` is the user-specified S3 location of the FHIR data to be imported into AWS HealthLake.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `s3://[a-z0-9][\.\-a-z0-9]{1,61}[a-z0-9](/.*)?`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

JobProgressReport

The progress report for the import job.

Contents

Throughput

The transaction rate the import job is processed at.

Type: Double

Required: No

TotalNumberOfFilesReadWithCustomerError

The number of files that failed to be read from the S3 input bucket due to customer error.

Type: Long

Required: No

TotalNumberOfImportedFiles

The number of files imported.

Type: Long

Required: No

TotalNumberOfResourcesImported

The number of resources imported.

Type: Long

Required: No

TotalNumberOfResourcesScanned

The number of resources scanned from the S3 input bucket.

Type: Long

Required: No

TotalNumberOfResourcesWithCustomerError

The number of resources that failed due to customer error.

Type: Long

Required: No

TotalNumberOfScannedFiles

The number of files scanned from the S3 input bucket.

Type: Long

Required: No

TotalSizeOfScannedFilesInMB

The size (in MB) of files scanned from the S3 input bucket.

Type: Double

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

KmsEncryptionConfig

The customer-managed-key (CMK) used when creating a data store. If a customer-owned key is not specified, an AWS-owned key is used for encryption.

Contents

CmkType

The type of customer-managed-key (CMK) used for encryption.

Type: String

Valid Values: CUSTOMER_MANAGED_KMS_KEY | AWS_OWNED_KMS_KEY

Required: Yes

KmsKeyId

The Key Management Service (KMS) encryption key id/alias used to encrypt the data store contents at rest.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 400.

Pattern: (arn:aws((-us-gov)|(-iso)|(-iso-b)|(-cn))?:kms:)?([a-z]{2}-[a-z]+(-[a-z]+)?-\d:)?(\d{12}:)?(((key/)?[a-zA-Z0-9-_]+)|(alias/[a-zA-Z0-9:/_-]+))

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OutputDataConfig

The output data configuration supplied when the export job was created.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

S3Configuration

The output data configuration supplied when the export job was created.

Type: [S3Configuration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PreloadDataConfig

The input properties for the preloaded (Synthea) data store.

Contents

PreloadDataType

The type of preloaded data. Only Synthea preloaded data is supported.

Type: String

Valid Values: SYNTHEA

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3Configuration

The configuration of the S3 bucket for either an import or export job. This includes assigning access permissions.

Contents

KmsKeyId

The Key Management Service (KMS) key ID used to access the S3 bucket.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 400.

Pattern: (arn:aws((-us-gov)|(-iso)|(-iso-b)|(-cn))?:kms:)?([a-z]{2}-[a-z]+(-[a-z]+)?-\\d:)?(\\d{12}:)?(((key/)?[a-zA-Z0-9-_]+)|(alias/[a-zA-Z0-9:/_]+))

Required: Yes

S3Uri

The S3Uri is the user-specified S3 location of the FHIR data to be imported into AWS HealthLake.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: s3://[a-z0-9][\\.-a-z0-9]{1,61}[a-z0-9](/.*)?

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

SseConfiguration

The server-side encryption key configuration for a customer-provided encryption key.

Contents

KmsEncryptionConfig

The Key Management Service (KMS) encryption configuration used to provide details for data encryption.

Type: [KmsEncryptionConfig](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

A label consisting of a user-defined key and value. The form for tags is {"Key", "Value"}

Contents

Key

The key portion of a tag. Tag keys are case sensitive.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\ -@]*)$`

Required: Yes

Value

The value portion of a tag. Tag values are case-sensitive.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\ -@]*)$`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400