



API Reference

Amazon Inspector Classic



API Version 2016-02-16

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon Inspector Classic: API Reference

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
AddAttributesToFindings	4
Request Syntax	4
Request Parameters	4
Response Syntax	5
Response Elements	5
Errors	5
Examples	6
See Also	7
CreateAssessmentTarget	9
Request Syntax	9
Request Parameters	9
Response Syntax	10
Response Elements	10
Errors	10
Examples	11
See Also	12
CreateAssessmentTemplate	14
Request Syntax	14
Request Parameters	14
Response Syntax	16
Response Elements	16
Errors	16
Examples	17
See Also	18
CreateExclusionsPreview	20
Request Syntax	20
Request Parameters	20
Response Syntax	20
Response Elements	21
Errors	21
See Also	22
CreateResourceGroup	23

Request Syntax	23
Request Parameters	23
Response Syntax	24
Response Elements	24
Errors	24
Examples	25
See Also	26
DeleteAssessmentRun	27
Request Syntax	27
Request Parameters	27
Response Elements	27
Errors	27
Examples	28
See Also	29
DeleteAssessmentTarget	31
Request Syntax	31
Request Parameters	31
Response Elements	31
Errors	31
Examples	32
See Also	33
DeleteAssessmentTemplate	35
Request Syntax	35
Request Parameters	35
Response Elements	35
Errors	35
Examples	36
See Also	37
DescribeAssessmentRuns	39
Request Syntax	39
Request Parameters	39
Response Syntax	39
Response Elements	41
Errors	41
Examples	42
See Also	44

DescribeAssessmentTargets	45
Request Syntax	45
Request Parameters	45
Response Syntax	45
Response Elements	46
Errors	46
Examples	47
See Also	48
DescribeAssessmentTemplates	50
Request Syntax	50
Request Parameters	50
Response Syntax	50
Response Elements	51
Errors	52
Examples	52
See Also	53
DescribeCrossAccountAccessRole	55
Response Syntax	55
Response Elements	55
Errors	56
Examples	56
See Also	57
DescribeExclusions	58
Request Syntax	58
Request Parameters	58
Response Syntax	59
Response Elements	59
Errors	60
See Also	60
DescribeFindings	62
Request Syntax	62
Request Parameters	62
Response Syntax	63
Response Elements	65
Errors	65
Examples	66

See Also	69
DescribeResourceGroups	70
Request Syntax	70
Request Parameters	70
Response Syntax	70
Response Elements	71
Errors	71
Examples	72
See Also	73
DescribeRulesPackages	75
Request Syntax	75
Request Parameters	75
Response Syntax	76
Response Elements	76
Errors	77
Examples	77
See Also	79
GetAssessmentReport	80
Request Syntax	80
Request Parameters	80
Response Syntax	81
Response Elements	81
Errors	82
See Also	83
GetExclusionsPreview	84
Request Syntax	84
Request Parameters	84
Response Syntax	86
Response Elements	86
Errors	87
See Also	88
GetTelemetryMetadata	89
Request Syntax	89
Request Parameters	89
Response Syntax	89
Response Elements	90

Errors	90
Examples	91
See Also	95
ListAssessmentRunAgents	96
Request Syntax	96
Request Parameters	96
Response Syntax	97
Response Elements	98
Errors	98
Examples	99
See Also	103
ListAssessmentRuns	105
Request Syntax	105
Request Parameters	106
Response Syntax	107
Response Elements	107
Errors	107
Examples	108
See Also	109
ListAssessmentTargets	110
Request Syntax	110
Request Parameters	110
Response Syntax	111
Response Elements	111
Errors	112
Examples	112
See Also	113
ListAssessmentTemplates	115
Request Syntax	115
Request Parameters	115
Response Syntax	116
Response Elements	117
Errors	117
Examples	118
See Also	119
ListEventSubscriptions	120

Request Syntax	120
Request Parameters	120
Response Syntax	121
Response Elements	121
Errors	122
Examples	123
See Also	124
ListExclusions	125
Request Syntax	125
Request Parameters	125
Response Syntax	126
Response Elements	126
Errors	127
See Also	127
ListFindings	129
Request Syntax	129
Request Parameters	130
Response Syntax	131
Response Elements	131
Errors	131
Examples	132
See Also	133
ListRulesPackages	134
Request Syntax	134
Request Parameters	134
Response Syntax	135
Response Elements	135
Errors	135
Examples	136
See Also	137
ListTagsForResource	138
Request Syntax	138
Request Parameters	138
Response Syntax	138
Response Elements	139
Errors	139

Examples	140
See Also	141
PreviewAgents	142
Request Syntax	142
Request Parameters	142
Response Syntax	143
Response Elements	143
Errors	144
Examples	145
See Also	146
RegisterCrossAccountAccessRole	147
Request Syntax	147
Request Parameters	147
Response Elements	147
Errors	148
Examples	148
See Also	149
RemoveAttributesFromFindings	151
Request Syntax	151
Request Parameters	151
Response Syntax	152
Response Elements	152
Errors	152
Examples	153
See Also	154
SetTagsForResource	156
Request Syntax	156
Request Parameters	156
Response Elements	157
Errors	157
Examples	158
See Also	159
StartAssessmentRun	160
Request Syntax	160
Request Parameters	160
Response Syntax	161

Response Elements	161
Errors	161
Examples	162
See Also	163
StopAssessmentRun	165
Request Syntax	165
Request Parameters	165
Response Elements	166
Errors	166
Examples	167
See Also	167
SubscribeToEvent	169
Request Syntax	169
Request Parameters	169
Response Elements	170
Errors	170
Examples	171
See Also	172
UnsubscribeFromEvent	173
Request Syntax	173
Request Parameters	173
Response Elements	174
Errors	174
Examples	175
See Also	176
UpdateAssessmentTarget	177
Request Syntax	177
Request Parameters	177
Response Elements	178
Errors	178
Examples	179
See Also	180
Data Types	181
AgentAlreadyRunningAssessment	183
Contents	183
See Also	183

AgentFilter	184
Contents	184
See Also	184
AgentPreview	185
Contents	185
See Also	186
AssessmentRun	188
Contents	188
See Also	191
AssessmentRunAgent	192
Contents	192
See Also	193
AssessmentRunFilter	194
Contents	194
See Also	196
AssessmentRunNotification	197
Contents	197
See Also	198
AssessmentRunStateChange	199
Contents	199
See Also	199
AssessmentTarget	200
Contents	200
See Also	201
AssessmentTargetFilter	202
Contents	202
See Also	202
AssessmentTemplate	203
Contents	203
See Also	205
AssessmentTemplateFilter	206
Contents	206
See Also	207
AssetAttributes	208
Contents	208
See Also	209

Attribute	211
Contents	211
See Also	211
DurationRange	212
Contents	212
See Also	212
EventSubscription	213
Contents	213
See Also	213
Exclusion	214
Contents	214
See Also	215
ExclusionPreview	216
Contents	216
See Also	217
FailedItemDetails	218
Contents	218
See Also	218
Finding	219
Contents	219
See Also	222
FindingFilter	223
Contents	223
See Also	225
InspectorServiceAttributes	226
Contents	226
See Also	226
NetworkInterface	228
Contents	228
See Also	230
PrivateIp	231
Contents	231
See Also	231
ResourceGroup	232
Contents	232
See Also	232

ResourceGroupTag	234
Contents	234
See Also	234
RulesPackage	235
Contents	235
See Also	236
Scope	237
Contents	237
See Also	237
SecurityGroup	238
Contents	238
See Also	238
Subscription	239
Contents	239
See Also	239
Tag	241
Contents	241
See Also	241
TelemetryMetadata	242
Contents	242
See Also	242
TimestampRange	244
Contents	244
See Also	244
Common Parameters	245
Common Errors	248

Welcome

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Amazon Inspector Classic enables you to analyze the behavior of your AWS resources and to identify potential security issues. For more information, see [Amazon Inspector Classic User Guide](#).

This document was last published on August 7, 2025.

Actions

The following actions are supported:

- [AddAttributesToFindings](#)
- [CreateAssessmentTarget](#)
- [CreateAssessmentTemplate](#)
- [CreateExclusionsPreview](#)
- [CreateResourceGroup](#)
- [DeleteAssessmentRun](#)
- [DeleteAssessmentTarget](#)
- [DeleteAssessmentTemplate](#)
- [DescribeAssessmentRuns](#)
- [DescribeAssessmentTargets](#)
- [DescribeAssessmentTemplates](#)
- [DescribeCrossAccountAccessRole](#)
- [DescribeExclusions](#)
- [DescribeFindings](#)
- [DescribeResourceGroups](#)
- [DescribeRulesPackages](#)
- [GetAssessmentReport](#)
- [GetExclusionsPreview](#)
- [GetTelemetryMetadata](#)
- [ListAssessmentRunAgents](#)
- [ListAssessmentRuns](#)
- [ListAssessmentTargets](#)
- [ListAssessmentTemplates](#)
- [ListEventSubscriptions](#)
- [ListExclusions](#)
- [ListFindings](#)
- [ListRulesPackages](#)

- [ListTagsForResource](#)
- [PreviewAgents](#)
- [RegisterCrossAccountAccessRole](#)
- [RemoveAttributesFromFindings](#)
- [SetTagsForResource](#)
- [StartAssessmentRun](#)
- [StopAssessmentRun](#)
- [SubscribeToEvent](#)
- [UnsubscribeFromEvent](#)
- [UpdateAssessmentTarget](#)

AddAttributesToFindings

⚠ Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Assigns attributes (key and value pairs) to the findings that are specified by the ARNs of the findings.

Request Syntax

```
{  
  "attributes": [  
    {  
      "key": "string",  
      "value": "string"  
    }  
,  
    "findingArns": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

attributes

The array of attributes that you want to assign to specified findings.

Type: Array of [Attribute](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: Yes

findingArns

The ARNs that specify the findings that you want to assign attributes to.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
  "failedItems": {  
    "string" : {  
      "failureCode": "string",  
      "retryable": boolean  
    }  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

failedItems

Attribute details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of AddAttributesToFindings.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 189
X-Amz-Target: InspectorService.AddAttributesToFindings
X-Amz-Date: 20160329T233810Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
```

```
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
    "attributes": [
        {
            "key": "Example",
            "value": "example"
        }
    ],
    "findingArns": [
        "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-8l1VIE0D/run/0-Z02cjjug/finding/0-T8yM9mEU"
    ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 4c8b9c50-f607-11e5-9380-d76f0924b6d7
Content-Type: application/x-amz-json-1.1
Content-Length: 18
Date: Tue, 29 Mar 2016 23:38:11 GMT
{
    "failedItems": {}
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateAssessmentTarget

A Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Creates a new assessment target using the ARN of the resource group that is generated by [CreateResourceGroup](#). If `resourceGroupArn` is not specified, all EC2 instances in the current AWS account and region are included in the assessment target. If the [service-linked role](#) isn't already registered, this action also creates and registers a service-linked role to grant Amazon Inspector Classic access to AWS Services needed to perform security assessments. You can create up to 50 assessment targets per AWS account. You can run up to 500 concurrent agents per AWS account. For more information, see [Amazon Inspector Classic Assessment Targets](#).

Request Syntax

```
{  
    "assessmentTargetName": "string",  
    "resourceGroupArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[assessmentTargetName](#)

The user-defined name that identifies the assessment target that you want to create. The name must be unique within the AWS account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: Yes

[resourceGroupArn](#)

The ARN that specifies the resource group that is used to create the assessment target. If `resourceGroupArn` is not specified, all EC2 instances in the current AWS account and region are included in the assessment target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{  
  "assessmentTargetArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[assessmentTargetArn](#)

The ARN that specifies the assessment target that is created.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidCrossAccountRoleException

Amazon Inspector Classic cannot assume the cross-account role that it needs to list your EC2 instances during the assessment run.

HTTP Status Code: 400

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error code describes the limit exceeded.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of CreateAssessmentTarget.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 129
X-Amz-Target: InspectorService.CreateAssessmentTarget
X-Amz-Date: 20160331T174054Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
    "assessmentTargetName": "ExampleAssessmentTarget",
    "resourceGroupArn": "arn:aws:inspector:us-
west-2:123456789012:resourcegroup/0-AB6DMKnv"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: b87f981e-f767-11e5-82d7-bb83264505be
Content-Type: application/x-amz-json-1.1
Content-Length: 84
Date: Thu, 31 Mar 2016 17:40:55 GMT
{
    "assessmentTargetArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-nvgVhaxX"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateAssessmentTemplate

A Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Creates an assessment template for the assessment target that is specified by the ARN of the assessment target. If the [service-linked role](#) isn't already registered, this action also creates and registers a service-linked role to grant Amazon Inspector Classic access to AWS Services needed to perform security assessments.

Request Syntax

```
{
  "assessmentTargetArn": "string",
  "assessmentTemplateName": "string",
  "durationInSeconds": number,
  "rulesPackageArns": [ "string" ],
  "userAttributesForFindings": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[assessmentTargetArn](#)

The ARN that specifies the assessment target for which you want to create the assessment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

[assessmentTemplateName](#)

The user-defined name that identifies the assessment template that you want to create.

You can create several assessment templates for an assessment target. The names of the assessment templates that correspond to a particular assessment target must be unique.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: Yes

[durationInSeconds](#)

The duration of the assessment run in seconds.

Type: Integer

Valid Range: Minimum value of 180. Maximum value of 86400.

Required: Yes

[rulesPackageArns](#)

The ARNs that specify the rules packages that you want to attach to the assessment template.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

[userAttributesForFindings](#)

The user-defined attributes that are assigned to every finding that is generated by the assessment run that uses this assessment template. An attribute is a key and value pair (an [Attribute](#) object). Within an assessment template, each key must be unique.

Type: Array of [Attribute](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

Response Syntax

```
{  
    "assessmentTemplateArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[assessmentTemplateArn](#)

The ARN that specifies the assessment template that is created.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

LimitExceeded**Exception**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error code describes the limit exceeded.

HTTP Status Code: 400

NoSuchEntity**Exception**

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailable**Exception**

The service is temporary unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of CreateAssessmentTemplate.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 335
X-Amz-Target: InspectorService.CreateAssessmentTemplate
X-Amz-Date: 20160331T175559Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
    "assessmentTargetArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-nvgVhaxX",
```

```
"assessmentTemplateName": "ExampleAssessmentTemplate",
"userAttributesForFindings": [
    {
        "key": "Example",
        "value": "example"
    }
],
"durationInSeconds": 180,
"rulesPackageArns": [
    "arn:aws:inspector:us-
west-2:758058086616:rulespackage/0-11B9DBXp"
]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: d3d3d58e-f769-11e5-9da0-9bde5220d15c
Content-Type: application/x-amz-json-1.1
Content-Length: 106
Date: Thu, 31 Mar 2016 17:56:00 GMT
{
    "assessmentTemplateArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-nvgVhaxX/template/0-it5r2S4T"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateExclusionsPreview

⚠ Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Starts the generation of an exclusions preview for the specified assessment template. The exclusions preview lists the potential exclusions (ExclusionPreview) that Inspector Classic can detect before it runs the assessment.

Request Syntax

```
{  
    "assessmentTemplateArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[assessmentTemplateArn](#)

The ARN that specifies the assessment template for which you want to create an exclusions preview.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{
```

```
"previewToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

previewToken

Specifies the unique identifier of the requested exclusions preview. You can use the unique identifier to retrieve the exclusions preview when running the GetExclusionsPreview API.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

PreviewGenerationInProgressException

The request is rejected. The specified assessment template is currently generating an exclusions preview.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateResourceGroup

A Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Creates a resource group using the specified set of tags (key and value pairs) that are used to select the EC2 instances to be included in an Amazon Inspector Classic assessment target. The created resource group is then used to create an Amazon Inspector Classic assessment target. For more information, see [CreateAssessmentTarget](#).

Request Syntax

```
{  
  "resourceGroupTags": [  
    {  
      "key": "string",  
      "value": "string"  
    }  
  ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

resourceGroupTags

A collection of keys and an array of possible values, '[{"key":"key1","values":["Value1","Value2"]}, {"key":"Key2","values":["Value3"]}]'.

For example, '[{"key":"Name","values":["TestEC2Instance"]}]'.

Type: Array of [ResourceGroupTag](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: Yes

Response Syntax

```
{  
    "resourceGroupArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[resourceGroupArn](#)

The ARN that specifies the resource group that is created.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

LimitExceeded**Exception**

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error code describes the limit exceeded.

HTTP Status Code: 400

ServiceTemporarilyUnavailable**Exception**

The service is temporary unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of CreateResourceGroup.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 67
X-Amz-Target: InspectorService.CreateResourceGroup
X-Amz-Date: 20160331T171757Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
    "resourceGroupTags": [
        {
            "key": "Name",
            "value": "example"
        }
    ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 8416dfb4-f764-11e5-872a-fde3682789d5
Content-Type: application/x-amz-json-1.1
Content-Length: 88
Date: Thu, 31 Mar 2016 17:17:58 GMT
{
    "resourceGroupArn": "arn:aws:inspector:us-
west-2:123456789012:resourcegroup/0-AB6DMKnv"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteAssessmentRun

⚠ Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Deletes the assessment run that is specified by the ARN of the assessment run.

Request Syntax

```
{  
    "assessmentRunArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

assessmentRunArn

The ARN that specifies the assessment run that you want to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AssessmentRunInProgressException

You cannot perform a specified action if an assessment run is currently in progress.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DeleteAssessmentRun.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
```

```
Accept-Encoding: identity
Content-Length: 117
X-Amz-Target: InspectorService.DeleteAssessmentRun
X-Amz-Date: 20160331T183810Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
    "assessmentRunArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-nvgVhaxX/template/0-it5r2S4T/run/0-11LMTAVe"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: b8494bff-f76f-11e5-9d49-6dd670a2a95d
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 18:38:11 GMT
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteAssessmentTarget

⚠ Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Deletes the assessment target that is specified by the ARN of the assessment target.

Request Syntax

```
{  
    "assessmentTargetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

assessmentTargetArn

The ARN that specifies the assessment target that you want to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AssessmentRunInProgressException

You cannot perform a specified action if an assessment run is currently in progress.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DeleteAssessmentTarget.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
```

```
Accept-Encoding: identity
Content-Length: 85
X-Amz-Target: InspectorService.DeleteAssessmentTarget
X-Amz-Date: 20160331T184144Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
    "assessmentTargetArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 37dee3da-f770-11e5-b61e-e163adb0c30c
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 18:41:45 GMT
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteAssessmentTemplate

⚠ Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Deletes the assessment template that is specified by the ARN of the assessment template.

Request Syntax

```
{  
    "assessmentTemplateArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

assessmentTemplateArn

The ARN that specifies the assessment template that you want to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AssessmentRunInProgressException

You cannot perform a specified action if an assessment run is currently in progress.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DeleteAssessmentTemplate.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
```

```
Accept-Encoding: identity
Content-Length: 107
X-Amz-Target: InspectorService.DeleteAssessmentTemplate
X-Amz-Date: 20160331T184505Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
    "assessmentTemplateArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-nvgVhaxX/template/0-it5r2S4T"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: afcc2e7e-f770-11e5-8f9c-054cd1296cf6
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 18:45:06 GMT
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAssessmentRuns

⚠ Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Describes the assessment runs that are specified by the ARNs of the assessment runs.

Request Syntax

```
{  
    "assessmentRunArns": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

assessmentRunArns

The ARN that specifies the assessment run that you want to describe.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
    "assessmentRuns": [  
        {
```

```
"arn": "string",
"assessmentTemplateArn": "string",
"completedAt": number,
"createdAt": number,
"dataCollected": boolean,
"durationInSeconds": number,
"findingCounts": {
    "string" : number
},
"name": "string",
"notifications": [
    {
        "date": number,
        "error": boolean,
        "event": "string",
        "message": "string",
        "snsPublishStatusCode": "string",
        "snsTopicArn": "string"
    }
],
"rulesPackageArns": [ "string" ],
"startedAt": number,
"state": "string",
"stateChangedAt": number,
"stateChanges": [
    {
        "state": "string",
        "stateChangedAt": number
    }
],
"userAttributesForFindings": [
    {
        "key": "string",
        "value": "string"
    }
]
},
"failedItems": {
    "string" : {
        "failureCode": "string",
        "retryable": boolean
    }
}
```

{}

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[assessmentRuns](#)

Information about the assessment run.

Type: Array of [AssessmentRun](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

[failedItems](#)

Assessment run details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeAssessmentRuns`.

Sample Request

```
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 120
X-Amz-Target: InspectorService.DescribeAssessmentRuns
X-Amz-Date: 20160323T213431Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
    "assessmentRunArns": [
        "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-4r1V2mAw/run/0-MKkpXXPE"
    ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 0834f495-f13f-11e5-8a9a-395a36305628
Content-Type: application/x-amz-json-1.1
Content-Length: 1156
Date: Wed, 23 Mar 2016 21:34:32 GMT
{
    "assessmentRuns": [
        {
            "arn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-MKkpXXPE",
            "assessmentTemplateArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw",
            "status": "PENDING"
        }
    ]
}
```

```
"completedAt": 1458680301.4,  
"createdAt": 1458680170.035,  
"dataCollected": true,  
"durationInSeconds": 3600,  
"name": "Run 1 for ExampleAssessmentTemplate",  
"notifications": [],  
"rulesPackageArns": [  
    "arn:aws:inspector:us-west-2:758058086616:rulepackage/0-  
X1KXtaWp"  
],  
"startedAt": 1458680170.161,  
"state": "COMPLETED",  
"stateChangedAt": 1458680301.4,  
"stateChanges": [  
    {  
        "state": "CREATED",  
        "stateChangedAt": 1458680170.035  
    },  
    {  
        "state": "START_DATA_COLLECTION_PENDING",  
        "stateChangedAt": 1458680170.065  
    },  
    {  
        "state": "START_DATA_COLLECTION_IN_PROGRESS",  
        "stateChangedAt": 1458680170.096  
    },  
    {  
        "state": "COLLECTING_DATA",  
        "stateChangedAt": 1458680170.161  
    },  
    {  
        "state": "STOP_DATA_COLLECTION_PENDING",  
        "stateChangedAt": 1458680239.883  
    },  
    {  
        "state": "DATA_COLLECTED",  
        "stateChangedAt": 1458680299.847  
    },  
    {  
        "state": "EVALUATING_RULES",  
        "stateChangedAt": 1458680300.099  
    },  
    {  
        "state": "COMPLETED",  
    }  
]
```

```
        "stateChangedAt": 1458680301.4
    }
],
"userAttributesForFindings": []
}
],
"failedItems": {}
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAssessmentTargets

A Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Describes the assessment targets that are specified by the ARNs of the assessment targets.

Request Syntax

```
{  
  "assessmentTargetArns": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

assessmentTargetArns

The ARNs that specifies the assessment targets that you want to describe.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{
```

```
"assessmentTargets": [  
    {  
        "arn        "createdAt": number,  
        "name        "resourceGroupArn        "updatedAt": number  
    }  
,  
    "failedItems": {  
        "string" : {  
            "failureCode": "string",  
            "retryable": boolean  
        }  
    }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentTargets

Information about the assessment targets.

Type: Array of [AssessmentTarget](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

failedItems

Assessment target details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeAssessmentTargets`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 88
X-Amz-Target: InspectorService.DescribeAssessmentTargets
X-Amz-Date: 20160323T214315Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
    "assessmentTargetArns": [
        "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq"
    ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 407ddf01-f140-11e5-823c-bd257ba1495d
Content-Type: application/x-amz-json-1.1
Content-Length: 287
Date: Wed, 23 Mar 2016 21:43:16 GMT
{
    "assessmentTargets": [
        {
            "arn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq",
            "createdAt": 1458074191.459,
            "name": "ExampleAssessmentTarget",
            "resourceGroupArn": "arn:aws:inspector:us-
west-2:123456789012:resourcegroup/0-PyGXopAI",
            "updatedAt": 1458074191.459
        }
    ],
    "failedItems": {}
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAssessmentTemplates

⚠ Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Describes the assessment templates that are specified by the ARNs of the assessment templates.

Request Syntax

```
{  
    "assessmentTemplateArns": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

assessmentTemplateArns

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
    "assessmentTemplates": [  
        {
```

```
"arn": "string",
"assessmentRunCount": number,
"assessmentTargetArn": "string",
"createdAt": number,
"durationInSeconds": number,
"lastAssessmentRunArn": "string",
"name": "string",
"rulesPackageArns": [ "string" ],
"userAttributesForFindings": [
  {
    "key": "string",
    "value": "string"
  }
]
},
"failedItems": {
  "string" : {
    "failureCode": "string",
    "retryable": boolean
  }
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[assessmentTemplates](#)

Information about the assessment templates.

Type: Array of [AssessmentTemplate](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

[failedItems](#)

Assessment template details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeAssessmentTemplates`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 110
X-Amz-Target: InspectorService.DescribeAssessmentTemplates
X-Amz-Date: 20160323T214822Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
    "assessmentTemplateArns": [
        "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-4r1V2mAw"
```

```
        ]  
    }
```

Sample Response

```
HTTP/1.1 200 OK  
x-amzn-RequestId: f73a449b-f140-11e5-b473-ed8493878c40  
Content-Type: application/x-amz-json-1.1  
Content-Length: 422  
Date: Wed, 23 Mar 2016 21:48:23 GMT  
{  
    "assessmentTemplates": [  
        {  
            "arn": "arn:aws:inspector:us-  
west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw",  
            "assessmentTargetArn": "arn:aws:inspector:us-  
west-2:123456789012:target/0-0kFIPusq",  
            "createdAt": 1458074191.844,  
            "durationInSeconds": 3600,  
            "name": "ExampleAssessmentTemplate",  
            "rulesPackageArns": [  
                "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-  
X1KXtawP"  
            ],  
            "userAttributesForFindings": []  
        }  
    ],  
    "failedItems": {}  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeCrossAccountAccessRole

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Describes the IAM role that enables Amazon Inspector Classic to access your AWS account.

Response Syntax

```
{  
  "registeredAt": number,  
  "roleArn": "string",  
  "valid": boolean  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[registeredAt](#)

The date when the cross-account access role was registered.

Type: Timestamp

[roleArn](#)

The ARN that specifies the IAM role that Amazon Inspector Classic uses to access your AWS account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

valid

A Boolean value that specifies whether the IAM role has the necessary policies attached to enable Amazon Inspector Classic to access your AWS account.

Type: Boolean

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of `DescribeCrossAccountAccessRole`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: InspectorService.DescribeCrossAccountAccessRole
X-Amz-Date: 20160323T215330Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: aef491a7-f141-11e5-bf1e-bbcffe8bf2e
Content-Type: application/x-amz-json-1.1
Content-Length: 99
Date: Wed, 23 Mar 2016 21:53:32 GMT
{
    "registeredAt": 1458069182.826,
    "roleArn": "arn:aws:iam::123456789012:role/inspector",
    "valid": true
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeExclusions

⚠ Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Describes the exclusions that are specified by the exclusions' ARNs.

Request Syntax

```
{  
  "exclusionArns": [ "string" ],  
  "locale": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

exclusionArns

The list of ARNs that specify the exclusions that you want to describe.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

locale

The locale into which you want to translate the exclusion's title, description, and recommendation.

Type: String

Valid Values: EN_US

Required: No

Response Syntax

```
{  
    "exclusions": {  
        "string" : {  
            "arn": "string",  
            "attributes": [  
                {  
                    "key": "string",  
                    "value": "string"  
                }  
            ],  
            "description": "string",  
            "recommendation": "string",  
            "scopes": [  
                {  
                    "key": "string",  
                    "value": "string"  
                }  
            ],  
            "title": "string"  
        }  
    },  
    "failedItems": {  
        "string" : {  
            "failureCode": "string",  
            "retryable": boolean  
        }  
    }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

exclusions

Information about the exclusions.

Type: String to [Exclusion](#) object map

Map Entries: Maximum number of 100 items.

Key Length Constraints: Minimum length of 1. Maximum length of 300.

failedItems

Exclusion details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeFindings

⚠ Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Describes the findings that are specified by the ARNs of the findings.

Request Syntax

```
{  
    "findingArns": [ "string" ],  
    "locale": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

findingArns

The ARN that specifies the finding that you want to describe.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

locale

The locale into which you want to translate a finding description, recommendation, and the short description that identifies the finding.

Type: String

Valid Values: EN_US

Required: No

Response Syntax

```
{  
    "failedItems": {  
        "string" : {  
            "failureCode": "string",  
            "retryable": boolean  
        }  
    },  
    "findings": [  
        {  
            "arn": "string",  
            "assetAttributes": {  
                "agentId": "string",  
                "amiId": "string",  
                "autoScalingGroup": "string",  
                "hostname": "string",  
                "ipv4Addresses": [ "string" ],  
                "networkInterfaces": [  
                    {  
                        "ipv6Addresses": [ "string" ],  
                        "networkInterfaceId": "string",  
                        "privateDnsName": "string",  
                        "privateIpAddress": "string",  
                        "privateIpAddresses": [  
                            {  
                                "privateDnsName": "string",  
                                "privateIpAddress": "string"  
                            }  
                        ],  
                        "publicDnsName": "string",  
                        "publicIp": "string",  
                        "securityGroups": [  
                            {  
                                "groupId": "string",  
                                "groupName": "string"  
                            }  
                        ]  
                    }  
                ]  
            }  
        }  
    ]  
}
```

```
        ],
        "subnetId": "string",
        "vpcId": "string"
    }
],
"schemaVersion": number,
"tags": [
    {
        "key": "string",
        "value": "string"
    }
],
},
"assetType": "string",
"attributes": [
    {
        "key": "string",
        "value": "string"
    }
],
"confidence": number,
"createdAt": number,
"description": "string",
"id": "string",
"indicatorOfCompromise": boolean,
"numericSeverity": number,
"recommendation": "string",
"schemaVersion": number,
"service": "string",
"serviceAttributes": {
    "assessmentRunArn": "string",
    "rulesPackageArn": "string",
    "schemaVersion": number
},
"severity": "string",
"title": "string",
"updatedAt": number,
"userAttributes": [
    {
        "key": "string",
        "value": "string"
    }
]
}
```

```
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[failedItems](#)

Finding details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

[findings](#)

Information about the finding.

Type: Array of [Finding](#) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeFindings`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 133
X-Amz-Target: InspectorService.DescribeFindings
X-Amz-Date: 20160323T215809Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
    "findingArns": [
        "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-4r1V2mAw/run/0-MKkpXXPE/finding/0-HwPnsDm4"
    ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 555dbc27-f142-11e5-9dc2-6746fe4b2002
Content-Type: application/x-amz-json-1.1
Content-Length: 892
Date: Wed, 23 Mar 2016 21:58:10 GMT
{
    "failedItems": {},
    "findings": [
        {
            "arn": "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-4r1V2mAw/run/0-MKkpXXPE/finding/0-HwPnsDm4",
            "category": "AWS Lambda Function Configuration Issues",
            "details": {
                "functionArn": "arn:aws:lambda:us-west-2:123456789012:function:my-lambda-function",
                "functionName": "my-lambda-function",
                "region": "us-west-2"
            },
            "id": "0-HwPnsDm4",
            "severity": "INFO",
            "status": "PENDING"
        }
    ]
}
```

```
        "arn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-MKkpXXPE/finding/0-
HwPnsDm4",
        "assetAttributes": {
            "agentId": "i-092e1184e67721f24",
            "amiId": "ami-0ad99772",
            "autoScalingGroup": "auto scaling group",
            "hostname": "ec2-54-202-242-173.us-
west-2.compute.amazonaws.com",
            "ipv4Addresses": [],
            "networkInterfaces": [
                {
                    "ipv6Addresses": [],
                    "networkInterfaceId": "eni-09b5ad02",
                    "privateDnsName": "ip-172-31-36-75.us-
west-2.compute.internal",
                    "privateIpAddress": "172.31.36.75",
                    "privateIpAddresses": [
                        {
                            "privateDnsName": "ip-172-31-36-75.us-
west-2.compute.internal",
                            "privateIpAddress": "172.31.36.75"
                        }
                    ],
                    "publicDnsName": "ec2-54-202-242-173.us-
west-2.compute.amazonaws.com",
                    "publicIp": "54.202.242.173",
                    "securityGroups": [
                        {
                            "groupId": "sg-48578931",
                            "groupName": "default"
                        }
                    ],
                    "subnetId": "subnet-8aeebbfc",
                    "vpcId": "vpc-05515b61"
                }
            ],
            "schemaVersion": 1,
            "tags": [
                {
                    "key": "scaling",
                    "value": "yes"
                },
                {

```

```
        "key": "aws:autoscaling:groupName",
        "value": "auto scaling group"
    },
    {
        "key": "Name",
        "value": "beta_amazon_linux_201803_scaling"
    },
    {
        "key": "beta",
        "value": "true"
    }
]
},
"assetType": "ec2-instance",
"attributes": [],
"confidence": 10,
"createdAt": 1458680301.37,
"description": "Amazon Inspector Classic did not find any potential security issues during this assessment.",
"indicatorOfCompromise": false,
"numericSeverity": 0,
"recommendation": "No remediation needed.",
"schemaVersion": 1,
"service": "Inspector",
"serviceAttributes": {
    "assessmentRunArn": "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-MKkpXXPE",
    "rulesPackageArn": "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-X1KXtawP",
    "schemaVersion": 1
},
"severity": "Informational",
"title": "No potential security issues found",
"updatedAt": 1458680301.37,
"userAttributes": []
}
]
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeResourceGroups

A Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Describes the resource groups that are specified by the ARNs of the resource groups.

Request Syntax

```
{  
    "resourceGroupArns": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

resourceGroupArns

The ARN that specifies the resource group that you want to describe.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
    "failedItems": {
```

```
"string" : {
    "failureCode": "string",
    "retryable": boolean
}
},
"resourceGroups": [
{
    "arn": "string",
    "createdAt": number,
    "tags": [
        {
            "key": "string",
            "value": "string"
        }
    ]
}
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[failedItems](#)

Resource group details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

[resourceGroups](#)

Information about a resource group.

Type: Array of [ResourceGroup](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeResourceGroups`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 92
X-Amz-Target: InspectorService.DescribeResourceGroups
X-Amz-Date: 20160323T220453Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
    "resourceGroupArns": [
        "arn:aws:inspector:us-west-2:123456789012:resourcegroup/0-PyGXopAI"
    ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 4636d6a9-f143-11e5-9f03-eb6e194efa59
Content-Type: application/x-amz-json-1.1
Content-Length: 191
Date: Wed, 23 Mar 2016 22:04:54 GMT
{
    "failedItems": {},
    "resourceGroups": [
        {
            "arn": "arn:aws:inspector:us-west-2:123456789012:resourcegroup/0-
PyGXopAI",
            "createdAt": 1458074191.098,
            "tags": [
                {
                    "key": "Name",
                    "value": "example"
                }
            ]
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

DescribeRulesPackages

⚠ Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Describes the rules packages that are specified by the ARNs of the rules packages.

Request Syntax

```
{  
  "locale": "string",  
  "rulesPackageArns": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

locale

The locale that you want to translate a rules package description into.

Type: String

Valid Values: EN_US

Required: No

rulesPackageArns

The ARN that specifies the rules package that you want to describe.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
    "failedItems": {  
        "string" : {  
            "failureCode": "string",  
            "retryable": boolean  
        }  
    },  
    "rulesPackages": [  
        {  
            "arn": "string",  
            "description": "string",  
            "name": "string",  
            "provider": "string",  
            "version": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

failedItems

Rules package details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

rulesPackages

Information about the rules package.

Type: Array of [RulesPackage](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeRulesPackages`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 90
X-Amz-Target: InspectorService.DescribeRulesPackages
X-Amz-Date: 20160323T220919Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
```

```
        "rulesPackageArns": [
            "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-9hgA516p"
        ]
    }
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: e4a6aee0-f143-11e5-a5ad-73b7f19c946c
Content-Type: application/x-amz-json-1.1
Content-Length: 387
Date: Wed, 23 Mar 2016 22:09:20 GMT
{
    "failedItems": {},
    "rulesPackages": [
        {
            "arn": "arn:aws:inspector:us-
west-2:758058086616:rulespackage/0-9hgA516p",
            "description": "The rules in this package help verify whether the EC2 instances in your application are exposed to Common Vulnerabilities and Exposures (CVEs). Attacks can exploit unpatched vulnerabilities to compromise the confidentiality, integrity, or availability of your service or data. The CVE system provides a reference for publicly known information security vulnerabilities and exposures. For more information, see [https://cve.mitre.org/](https://cve.mitre.org/). If a particular CVE appears in one of the produced Findings at the end of a completed Inspector Classic assessment, you can search [https://cve.mitre.org/](https://cve.mitre.org/) using the CVE's ID (for example, \"CVE-2009-0021\") to find detailed information about this CVE, its severity, and how to mitigate it. ",
            "name": "Common Vulnerabilities and Exposures",
            "provider": "Amazon Web Services, Inc.",
            "version": "1.1"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetAssessmentReport

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Produces an assessment report that includes detailed and comprehensive results of a specified assessment run.

Request Syntax

```
{  
  "assessmentRunArn": "string",  
  "reportFileFormat": "string",  
  "reportType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

assessmentRunArn

The ARN that specifies the assessment run for which you want to generate a report.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

reportFileFormat

Specifies the file format (html or pdf) of the assessment report that you want to generate.

Type: String

Valid Values: HTML | PDF

Required: Yes

reportType

Specifies the type of the assessment report that you want to generate. There are two types of assessment reports: a finding report and a full report. For more information, see [Assessment Reports](#).

Type: String

Valid Values: FINDING | FULL

Required: Yes

Response Syntax

```
{  
  "status": "string",  
  "url": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

status

Specifies the status of the request to generate an assessment report.

Type: String

Valid Values: WORK_IN_PROGRESS | FAILED | COMPLETED

url

Specifies the URL where you can find the generated assessment report. This parameter is only returned if the report is successfully generated.

Type: String

Length Constraints: Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AssessmentRunInProgressException

You cannot perform a specified action if an assessment run is currently in progress.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

HTTP Status Code: 400

UnsupportedFeatureException

Used by the [GetAssessmentReport](#) API. The request was rejected because you tried to generate a report for an assessment run that existed before reporting was supported in Amazon

Inspector. You can only generate reports for assessment runs that took place or will take place after generating reports in Amazon Inspector Classic became available.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetExclusionsPreview

⚠ Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Retrieves the exclusions preview (a list of ExclusionPreview objects) specified by the preview token. You can obtain the preview token by running the CreateExclusionsPreview API.

Request Syntax

```
{  
    "assessmentTemplateArn": "string",  
    "locale": "string",  
    "maxResults": number,  
    "nextToken": "string",  
    "previewToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[assessmentTemplateArn](#)

The ARN that specifies the assessment template for which the exclusions preview was requested.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

locale

The locale into which you want to translate the exclusion's title, description, and recommendation.

Type: String

Valid Values: EN_US

Required: No

maxResults

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 100. The maximum value is 500.

Type: Integer

Required: No

nextToken

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the GetExclusionsPreviewRequest action. Subsequent calls to the action fill nextToken in the request with the value of nextToken from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

previewToken

The unique identifier associated of the exclusions preview.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

Response Syntax

```
{  
    "exclusionPreviews": [  
        {  
            "attributes": [  
                {  
                    "key": "string",  
                    "value": "string"  
                }  
            ],  
            "description": "string",  
            "recommendation": "string",  
            "scopes": [  
                {  
                    "key": "string",  
                    "value": "string"  
                }  
            ],  
            "title": "string"  
        }  
    ],  
    "nextToken": "string",  
    "previewStatus": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[exclusionPreviews](#)

Information about the exclusions included in the preview.

Type: Array of [ExclusionPreview](#) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

nextToken

When a response is generated, if there is more data to be listed, this parameters is present in the response and contains the value to use for the nextToken parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

previewStatus

Specifies the status of the request to generate an exclusions preview.

Type: String

Valid Values: WORK_IN_PROGRESS | COMPLETED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTelemetryMetadata

⚠ Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Information about the data that is collected for the specified assessment run.

Request Syntax

```
{  
  "assessmentRunArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

assessmentRunArn

The ARN that specifies the assessment run that has the telemetry data that you want to obtain.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
  "telemetryMetadata": [  
    {  
      "
```

```
    "count": number,
    "dataSize": number,
    "messageType": "string"
}
]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[telemetryMetadata](#)

Telemetry details.

Type: Array of [TelemetryMetadata](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5000 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetTelemetryMetadata.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 117
X-Amz-Target: InspectorService.GetTelemetryMetadata
X-Amz-Date: 20160329T223852Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
    "assessmentRunArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-MKkpXXPE"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 03ffa82f-f5ff-11e5-9cf9-9fd5e2aef2f6
Content-Type: application/x-amz-json-1.1
Content-Length: 1990
Date: Tue, 29 Mar 2016 22:38:53 GMT
{
    "telemetryMetadata": [
        {
            "count": 2,
            "dataSize": 345,
            "messageType": "InspectorDuplicateProcess"
        },
        {
            "count": 1,
            "dataSize": 123,
            "messageType": "InspectorProcessStart"
        }
    ]
}
```

```
        "count": 3,
        "dataSize": 255,
        "messageType": "InspectorTimeEventMsg"
    },
    {
        "count": 4,
        "dataSize": 1082,
        "messageType": "InspectorNetworkInterface"
    },
    {
        "count": 2,
        "dataSize": 349,
        "messageType": "InspectorDnsEntry"
    },
    {
        "count": 11,
        "dataSize": 2514,
        "messageType": "InspectorDirectoryInfoMsg"
    },
    {
        "count": 1,
        "dataSize": 179,
        "messageType": "InspectorTcpV6ListeningPort"
    },
    {
        "count": 101,
        "dataSize": 10949,
        "messageType": "InspectorTerminal"
    },
    {
        "count": 26,
        "dataSize": 5916,
        "messageType": "InspectorUser"
    },
    {
        "count": 282,
        "dataSize": 32148,
        "messageType": "InspectorDynamicallyLoadedCodeModule"
    },
    {
        "count": 18,
        "dataSize": 10172,
        "messageType": "InspectorCreateProcess"
    },
}
```

```
{  
    "count": 3,  
    "dataSize": 8001,  
    "messageType": "InspectorProcessPerformance"  
},  
{  
    "count": 1,  
    "dataSize": 360,  
    "messageType": "InspectorOperatingSystem"  
},  
{  
    "count": 6,  
    "dataSize": 546,  
    "messageType": "InspectorStopProcess"  
},  
{  
    "count": 1,  
    "dataSize": 1553,  
    "messageType": "InspectorInstanceMetaData"  
},  
{  
    "count": 2,  
    "dataSize": 434,  
    "messageType": "InspectorTcpV4Connection"  
},  
{  
    "count": 474,  
    "dataSize": 2960322,  
    "messageType": "InspectorPackageInfo"  
},  
{  
    "count": 3,  
    "dataSize": 2235,  
    "messageType": "InspectorSystemPerformance"  
},  
{  
    "count": 105,  
    "dataSize": 46048,  
    "messageType": "InspectorCodeModule"  
},  
{  
    "count": 1,  
    "dataSize": 182,  
    "messageType": "InspectorUdpV6ListeningPort"
```

```
},
{
  "count": 2,
  "dataSize": 371,
  "messageType": "InspectorUdpV4ListeningPort"
},
{
  "count": 18,
  "dataSize": 8362,
  "messageType": "InspectorKernelModule"
},
{
  "count": 29,
  "dataSize": 48788,
  "messageType": "InspectorConfigurationInfo"
},
{
  "count": 1,
  "dataSize": 79,
  "messageType": "InspectorMonitoringStart"
},
{
  "count": 5,
  "dataSize": 0,
  "messageType": "InspectorSplitMsgBegin"
},
{
  "count": 51,
  "dataSize": 4593,
  "messageType": "InspectorGroup"
},
{
  "count": 1,
  "dataSize": 184,
  "messageType": "InspectorTcpV4ListeningPort"
},
{
  "count": 1159,
  "dataSize": 3146579,
  "messageType": "Total"
},
{
  "count": 5,
  "dataSize": 0,
```

```
        "messageType": "InspectorSplitMsgEnd"
    },
    [
        {
            "count": 1,
            "dataSize": 612,
            "messageType": "InspectorLoadImageInProcess"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAssessmentRunAgents

⚠ Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Lists the agents of the assessment runs that are specified by the ARNs of the assessment runs.

Request Syntax

```
{  
    "assessmentRunArn": "string",  
    "filter": {  
        "agentHealthCodes": [ "string" ],  
        "agentHealths": [ "string" ]  
    },  
    "maxResults": number,  
    "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

assessmentRunArn

The ARN that specifies the assessment run whose agents you want to list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

filter

You can use this parameter to specify a subset of data to be included in the action's response.

For a record to match a filter, all specified filter attributes must match. When multiple values are specified for a filter attribute, any of the values can match.

Type: [AgentFilter](#) object

Required: No

maxResults

You can use this parameter to indicate the maximum number of items that you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

nextToken

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListAssessmentRunAgents** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{  
  "assessmentRunAgents": [  
    {  
      "agentHealth": "string",  
      "agentHealthCode": "string",  
      "agentHealthDetails": "string",  
      "agentId": "string",  
      "assessmentRunArn": "string",  
      "autoScalingGroup": "string",  
      "status": "string"  
    }  
  ]  
}
```

```
"telemetryMetadata": [  
    {  
        "count": number,  
        "dataSize": number,  
        "messageType": "string"  
    }  
],  
"nextTokenstring"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentRunAgents

A list of ARNs that specifies the agents returned by the action.

Type: Array of [AssessmentRunAgent](#) objects

Array Members: Minimum number of 0 items. Maximum number of 500 items.

nextToken

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListAssessmentRunAgents.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 117
X-Amz-Target: InspectorService.ListAssessmentRunAgents
X-Amz-Date: 20160323T212138Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
    "assessmentRunArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-MKkpXXPE"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 3b752481-f13d-11e5-9f2a-87dc3189b81c
Content-Type: application/x-amz-json-1.1
Content-Length: 2206
Date: Wed, 23 Mar 2016 21:21:39 GMT
{
    "assessmentRunAgents": [
        {
            "agentHealth": "HEALTHY",
            "agentHealthCode": "HEALTHY",
            "agentId": "i-49113b93",
            "assessmentRunArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-MKkpXXPE",
            "telemetryMetadata": [
                {
                    "count": 2,
                    "dataSize": 345,
                    "messageType": "InspectorDuplicateProcess"
                },
                {
                    "count": 3,
                    "dataSize": 255,
                    "messageType": "InspectorTimeEventMsg"
                },
                {
                    "count": 4,
                    "dataSize": 1082,
                    "messageType": "InspectorNetworkInterface"
                },
                {
                    "count": 2,
                    "dataSize": 349,
                    "messageType": "InspectorDnsEntry"
                },
                {
                    "count": 11,
                    "dataSize": 2514,
                    "messageType": "InspectorDirectoryInfoMsg"
                },
                {

```

```
        "count": 1,
        "dataSize": 179,
        "messageType": "InspectorTcpV6ListeningPort"
    },
    {
        "count": 101,
        "dataSize": 10949,
        "messageType": "InspectorTerminal"
    },
    {
        "count": 26,
        "dataSize": 5916,
        "messageType": "InspectorUser"
    },
    {
        "count": 282,
        "dataSize": 32148,
        "messageType": "InspectorDynamicallyLoadedCodeModule"
    },
    {
        "count": 18,
        "dataSize": 10172,
        "messageType": "InspectorCreateProcess"
    },
    {
        "count": 3,
        "dataSize": 8001,
        "messageType": "InspectorProcessPerformance"
    },
    {
        "count": 1,
        "dataSize": 360,
        "messageType": "InspectorOperatingSystem"
    },
    {
        "count": 6,
        "dataSize": 546,
        "messageType": "InspectorStopProcess"
    },
    {
        "count": 1,
        "dataSize": 1553,
        "messageType": "InspectorInstanceMetaData"
    },
}
```

```
{  
    "count": 2,  
    "dataSize": 434,  
    "messageType": "InspectorTcpV4Connection"  
},  
{  
    "count": 474,  
    "dataSize": 2960322,  
    "messageType": "InspectorPackageInfo"  
},  
{  
    "count": 3,  
    "dataSize": 2235,  
    "messageType": "InspectorSystemPerformance"  
},  
{  
    "count": 105,  
    "dataSize": 46048,  
    "messageType": "InspectorCodeModule"  
},  
{  
    "count": 1,  
    "dataSize": 182,  
    "messageType": "InspectorUdpV6ListeningPort"  
},  
{  
    "count": 2,  
    "dataSize": 371,  
    "messageType": "InspectorUdpV4ListeningPort"  
},  
{  
    "count": 18,  
    "dataSize": 8362,  
    "messageType": "InspectorKernelModule"  
},  
{  
    "count": 29,  
    "dataSize": 48788,  
    "messageType": "InspectorConfigurationInfo"  
},  
{  
    "count": 1,  
    "dataSize": 79,  
    "messageType": "InspectorMonitoringStart"
```

```
        },
        {
            "count": 5,
            "dataSize": 0,
            "messageType": "InspectorSplitMsgBegin"
        },
        {
            "count": 51,
            "dataSize": 4593,
            "messageType": "InspectorGroup"
        },
        {
            "count": 1,
            "dataSize": 184,
            "messageType": "InspectorTcpV4ListeningPort"
        },
        {
            "count": 1159,
            "dataSize": 3146579,
            "messageType": "Total"
        },
        {
            "count": 5,
            "dataSize": 0,
            "messageType": "InspectorSplitMsgEnd"
        },
        {
            "count": 1,
            "dataSize": 612,
            "messageType": "InspectorLoadImageInProcess"
        }
    ]
}
]
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAssessmentRuns

⚠ Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Lists the assessment runs that correspond to the assessment templates that are specified by the ARNs of the assessment templates.

Request Syntax

```
{  
    "assessmentTemplateArns": [ "string" ],  
    "filter": {  
        "completionTimeRange": {  
            "beginDate": number,  
            "endDate": number  
        },  
        "durationRange": {  
            "maxSeconds": number,  
            "minSeconds": number  
        },  
        "namePattern": "string",  
        "rulesPackageArns": [ "string" ],  
        "startTimeRange": {  
            "beginDate": number,  
            "endDate": number  
        },  
        "stateChangeTimeRange": {  
            "beginDate": number,  
            "endDate": number  
        },  
        "states": [ "string" ]  
    },  
    "maxResults": number,  
    "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[assessmentTemplateArns](#)

The ARNs that specify the assessment templates whose assessment runs you want to list.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

[filter](#)

You can use this parameter to specify a subset of data to be included in the action's response.

For a record to match a filter, all specified filter attributes must match. When multiple values are specified for a filter attribute, any of the values can match.

Type: [AssessmentRunFilter](#) object

Required: No

[maxResults](#)

You can use this parameter to indicate the maximum number of items that you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

[nextToken](#)

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListAssessmentRuns** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{  
    "assessmentRunArns": [ "string" ],  
    "nextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[assessmentRunArns](#)

A list of ARNs that specifies the assessment runs that are returned by the action.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

[nextToken](#)

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListAssessmentRuns.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: InspectorService.ListAssessmentRuns
X-Amz-Date: 20160323T194135Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 410dabf6-f12f-11e5-8b5a-810259c0c3ae
Content-Type: application/x-amz-json-1.1
Content-Length: 215
Date: Wed, 23 Mar 2016 19:41:36 GMT
{
    "assessmentRunArns":
    [
        "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-4r1V2mAw/run/0-MKkpXXPE",
        "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-4r1V2mAw/run/0-v5D6fI3v"
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAssessmentTargets

⚠ Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Lists the ARNs of the assessment targets within this AWS account. For more information about assessment targets, see [Amazon Inspector Classic Assessment Targets](#).

Request Syntax

```
{  
  "filter": {  
    "assessmentTargetNamePattern": "string"  
  },  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

filter

You can use this parameter to specify a subset of data to be included in the action's response.

For a record to match a filter, all specified filter attributes must match. When multiple values are specified for a filter attribute, any of the values can match.

Type: [AssessmentTargetFilter](#) object

Required: No

maxResults

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

nextToken

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListAssessmentTargets** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{  
    "assessmentTargetArns": [ "string" ],  
    "nextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentTargetArns

A list of ARNs that specifies the assessment targets that are returned by the action.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

nextToken

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListAssessmentTargets.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
```

```
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: InspectorService.ListAssessmentTargets
X-Amz-Date: 20160323T201018Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 445f71f6-f133-11e5-932b-dd9c937d073a
Content-Type: application/x-amz-json-1.1
Content-Length: 87
Date: Wed, 23 Mar 2016 20:10:19 GMT
{
    "assessmentTargetArns": [
        "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq"
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAssessmentTemplates

⚠ Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Lists the assessment templates that correspond to the assessment targets that are specified by the ARNs of the assessment targets.

Request Syntax

```
{  
    "assessmentTargetArns": [ "string" ],  
    "filter": {  
        "durationRange": {  
            "maxSeconds": number,  
            "minSeconds": number  
        },  
        "namePattern": "string",  
        "rulesPackageArns": [ "string" ]  
    },  
    "maxResults": number,  
    "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[assessmentTargetArns](#)

A list of ARNs that specifies the assessment targets whose assessment templates you want to list.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

filter

You can use this parameter to specify a subset of data to be included in the action's response.

For a record to match a filter, all specified filter attributes must match. When multiple values are specified for a filter attribute, any of the values can match.

Type: [AssessmentTemplateFilter](#) object

Required: No

maxResults

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

nextToken

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListAssessmentTemplates** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{  
  "assessmentTemplateArns": [ "string" ],
```

```
    "nextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[assessmentTemplateArns](#)

A list of ARNs that specifies the assessment templates returned by the action.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

[nextToken](#)

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListAssessmentTemplates.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: InspectorService.ListAssessmentTemplates
X-Amz-Date: 20160323T202549Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 6f406528-f135-11e5-aa71-8de73166bfa9
Content-Type: application/x-amz-json-1.1
Content-Length: 190
Date: Wed, 23 Mar 2016 20:25:50 GMT
{
```

```
        "assessmentTemplateArns": [
            "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-4r1V2mAw",
            "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-Uza6ihLh"
        ]
    }
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListEventSubscriptions

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Lists all the event subscriptions for the assessment template that is specified by the ARN of the assessment template. For more information, see [SubscribeToEvent](#) and [UnsubscribeFromEvent](#).

Request Syntax

```
{  
    "maxResults": number,  
    "nextToken": "string",  
    "resourceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

nextToken

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListEventSubscriptions** action. Subsequent calls to the action fill

nextToken in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

resourceArn

The ARN of the assessment template for which you want to list the existing event subscriptions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "subscriptions": [
    {
      "eventSubscriptions": [
        {
          "event": "string",
          "subscribedAt": number
        }
      ],
      "resourceArn": "string",
      "topicArn": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

subscriptions

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Details of the returned event subscriptions.

Type: Array of [Subscription](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListEventSubscriptions.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 97
X-Amz-Target: InspectorService.ListEventSubscriptions
X-Amz-Date: 20160331T202943Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
    "resourceArn": "arn:aws:inspector:us-west-2:123456789012:target/0-
nvgVhaxX/template/0-7sbz2Kz0"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 4e21c005-f77f-11e5-823c-bd257ba1495d
Content-Type: application/x-amz-json-1.1
Content-Length: 272
Date: Thu, 31 Mar 2016 20:29:44 GMT
```

```
{  
    "subscriptions": [  
        {  
            "eventSubscriptions": [  
                {  
                    "event": "ASSESSMENT_RUN_COMPLETED",  
                    "subscribedAt": 1459455440.867  
                }  
            ],  
            "resourceArn": "arn:aws:inspector:us-  
west-2:123456789012:target/0-nvgVhaxX/template/0-7sbz2Kz0",  
            "topicArn": "arn:aws:sns:us-west-2:123456789012:exAMPLetopic"  
        }  
    ]  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListExclusions

A Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

List exclusions that are generated by the assessment run.

Request Syntax

```
{  
  "assessmentRunArn": "string",  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

assessmentRunArn

The ARN of the assessment run that generated the exclusions that you want to list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

maxResults

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 100. The maximum value is 500.

Type: Integer

Required: No

nextToken

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the ListExclusionsRequest action. Subsequent calls to the action fill nextToken in the request with the value of nextToken from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{  
    "exclusionArns": [ "string" ],  
    "nextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

exclusionArns

A list of exclusions' ARNs returned by the action.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

nextToken

When a response is generated, if there is more data to be listed, this parameters is present in the response and contains the value to use for the nextToken parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListFindings

⚠ Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Lists findings that are generated by the assessment runs that are specified by the ARNs of the assessment runs.

Request Syntax

```
{
  "assessmentRunArns": [ "string" ],
  "filter": {
    "agentIds": [ "string" ],
    "attributes": [
      {
        "key": "string",
        "value": "string"
      }
    ],
    "autoScalingGroups": [ "string" ],
    "creationTimeRange": {
      "beginDate": number,
      "endDate": number
    },
    "ruleNames": [ "string" ],
    "rulesPackageArns": [ "string" ],
    "severities": [ "string" ],
    "userAttributes": [
      {
        "key": "string",
        "value": "string"
      }
    ]
  },
  "maxResults": number,
```

```
    "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[assessmentRunArns](#)

The ARNs of the assessment runs that generate the findings that you want to list.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

[filter](#)

You can use this parameter to specify a subset of data to be included in the action's response.

For a record to match a filter, all specified filter attributes must match. When multiple values are specified for a filter attribute, any of the values can match.

Type: [FindingFilter](#) object

Required: No

[maxResults](#)

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

[nextToken](#)

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListFindings** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{  
    "findingArns    "nextToken}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[**findingArns**](#)

A list of ARNs that specifies the findings returned by the action.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

[**nextToken**](#)

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListFindings.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: InspectorService.ListFindings
X-Amz-Date: 20160323T203109Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 2df2e847-f136-11e5-b2c3-cd62ea256ca4
Content-Type: application/x-amz-json-1.1
Content-Length: 247
Date: Wed, 23 Mar 2016 20:31:10 GMT
{
    "findingArns": [
        "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-4r1V2mAw/run/0-MKkpXXPE/finding/0-HwPnsDm4",
        "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-4r1V2mAw/run/0-v5D6fI3v/finding/0-tyvmqBLy"
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListRulesPackages

A Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Lists all available Amazon Inspector Classic rules packages.

Request Syntax

```
{  
    "maxResults": number,  
    "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

nextToken

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListRulesPackages** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{  
    "nextToken": "string",  
    "rulesPackageArns": [ "string" ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

[rulesPackageArns](#)

The list of ARNs that specifies the rules packages returned by the action.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListRulesPackages.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: InspectorService.ListRulesPackages
X-Amz-Date: 20160323T203727Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 0e3779a9-f137-11e5-be28-e130082e2a98
```

```
Content-Type: application/x-amz-json-1.1
Content-Length: 424
Date: Wed, 23 Mar 2016 20:37:26 GMT
{
    "rulesPackageArns": [
        "arn:aws:inspector:us-
west-2:758058086616:rulespackage/0-9hgA516p",
        "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-
H5hpSawc",
        "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-
JJ0tZiqQ",
        "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-
vg5GGHSD"
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

⚠ Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Lists all tags associated with an assessment template.

Request Syntax

```
{  
  "resourceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

resourceArn

The ARN that specifies the assessment template whose tags you want to list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
  "tags": [  
    {
```

```
        "key": "string",
        "value": "string"
    }
]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[tags](#)

A collection of key and value pairs.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListTagsForResource.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 97
X-Amz-Target: InspectorService.ListTagsForResource
X-Amz-Date: 20160323T212838Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
    "resourceArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq/template/0-gcwFliYu"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 3580d562-f13e-11e5-8a9a-395a36305628
Content-Type: application/x-amz-json-1.1
Content-Length: 50
Date: Wed, 23 Mar 2016 21:28:39 GMT
{
    "tags": [
        {
            "key": "Name",
            "value": "Example"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PreviewAgents

⚠ Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Previews the agents installed on the EC2 instances that are part of the specified assessment target.

Request Syntax

```
{  
    "maxResults": number,  
    "nextToken": "string",  
    "previewAgentsArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

nextToken

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **PreviewAgents** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

[previewAgentsArn](#)

The ARN of the assessment target whose agents you want to preview.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
    "agentPreviews": [  
        {  
            "agentHealth": "string",  
            "agentId": "string",  
            "agentVersion": "string",  
            "autoScalingGroup": "string",  
            "hostname": "string",  
            "ipv4Address": "string",  
            "kernelVersion": "string",  
            "operatingSystem": "string"  
        }  
    ],  
    "nextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[agentPreviews](#)

The resulting list of agents.

Type: Array of [AgentPreview](#) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

nextToken

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidCrossAccountRoleException

Amazon Inspector Classic cannot assume the cross-account role that it needs to list your EC2 instances during the assessment run.

HTTP Status Code: 400

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of PreviewAgents.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 82
X-Amz-Target: InspectorService.PreviewAgents
X-Amz-Date: 20160329T224634Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
    "previewAgentsArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 176c8915-f600-11e5-ac8a-bb6015f4022c
Content-Type: application/x-amz-json-1.1
Content-Length: 44
Date: Tue, 29 Mar 2016 22:46:36 GMT
{
    "agentPreviews": [
        {
            "hostname": "example",
            "agentId": "i-49113b93",
            "autoScalingGroup": "example",
            "agentHealth": "HEALTHY",
            "agentVersion": "exampleversion",
```

```
        "operatingSystem": "exampleOS",
        "kernelVersion": "examplekernelversion",
        "ipv4Address": "example"
    }
]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RegisterCrossAccountAccessRole

A Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Registers the IAM role that grants Amazon Inspector Classic access to AWS Services needed to perform security assessments.

Request Syntax

```
{  
    "roleArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

roleArn

The ARN of the IAM role that grants Amazon Inspector Classic access to AWS Services needed to perform security assessments.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidCrossAccountRoleException

Amazon Inspector Classic cannot assume the cross-account role that it needs to list your EC2 instances during the assessment run.

HTTP Status Code: 400

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of RegisterCrossAccountAccessRole.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
```

```
Content-Length: 55
X-Amz-Target: InspectorService.RegisterCrossAccountAccessRole
X-Amz-Date: 20160329T225544Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
    "roleArn": "arn:aws:iam::123456789012:role/inspector"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 5f553cfa-f601-11e5-a47c-b7e2de2d572c
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Tue, 29 Mar 2016 22:55:46 GMT
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

RemoveAttributesFromFindings

⚠ Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Removes entire attributes (key and value pairs) from the findings that are specified by the ARNs of the findings where an attribute with the specified key exists.

Request Syntax

```
{  
  "attributeKeys": [ "string" ],  
  "findingArns": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

attributeKeys

The array of attribute keys that you want to remove from specified findings.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

findingArns

The ARNs that specify the findings that you want to remove attributes from.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
    "failedItems": {  
        "string" : {  
            "failureCode": "string",  
            "retryable": boolean  
        }  
    }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[failedItems](#)

Attributes details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of RemoveAttributesFromFindings.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 181
X-Amz-Target: InspectorService.RemoveAttributesFromFindings
X-Amz-Date: 20160329T234159Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
    "attributeKeys": [
```

```
        "key=Example,value=example"
    ],
    "findingArns": [
        "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-8l1VIE0D/run/0-Z02cjjug/finding/0-T8yM9mEU"
    ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: d4ebb8cf-f607-11e5-94d7-d9eab7a1ae2a
Content-Type: application/x-amz-json-1.1
Content-Length: 18
Date: Tue, 29 Mar 2016 23:42:00 GMT
{
    "failedItems": {}
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

SetTagsForResource

⚠ Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Sets tags (key and value pairs) to the assessment template that is specified by the ARN of the assessment template.

Request Syntax

```
{  
  "resourceArn": "string",  
  "tags": [  
    {  
      "key": "string",  
      "value": "string"  
    }  
  ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

resourceArn

The ARN of the assessment template that you want to set tags to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

[tags](#)

A collection of key and value pairs that you want to set to the assessment template.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of SetTagsForResource.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 144
X-Amz-Target: InspectorService.SetTagsForResource
X-Amz-Date: 20160331T185018Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
    "resourceArn": "arn:aws:inspector:us-west-2:123456789012:target/0-nvgVhaxX/template/0-7sbz2Kz0",
    "tags": [
        {
            "key": "Example",
            "value": "example"
        }
    ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 6a3f5af3-f771-11e5-8599-f1b50afafb5a
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 18:50:18 GMT
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartAssessmentRun

⚠ Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Starts the assessment run specified by the ARN of the assessment template. For this API to function properly, you must not exceed the limit of running up to 500 concurrent agents per AWS account.

Request Syntax

```
{  
  "assessmentRunName": "string",  
  "assessmentTemplateArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

assessmentRunName

You can specify the name for the assessment run. The name must be unique for the assessment template whose ARN is used to start the assessment run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: No

assessmentTemplateArn

The ARN of the assessment template of the assessment run that you want to start.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
    "assessmentRunArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[assessmentRunArn](#)

The ARN of the assessment run that has been started.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AgentsAlreadyRunningAssessmentException

You started an assessment run, but one of the instances is already participating in another assessment run.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidCrossAccountRoleException

Amazon Inspector Classic cannot assume the cross-account role that it needs to list your EC2 instances during the assessment run.

HTTP Status Code: 400

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error code describes the limit exceeded.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of StartAssessmentRun.

Sample Request

POST / HTTP/1.1

```
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 142
X-Amz-Target: InspectorService.StartAssessmentRun
X-Amz-Date: 20160331T182519Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
    "assessmentRunName": "examplerun",
    "assessmentTemplateArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-nvgVhaxX/template/0-it5r2S4T"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: ed349455-f76d-11e5-b473-ed8493878c40
Content-Type: application/x-amz-json-1.1
Content-Length: 116
Date: Thu, 31 Mar 2016 18:25:22 GMT
{
    "assessmentRunArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-nvgVhaxX/template/0-it5r2S4T/run/0-j0oroxY"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StopAssessmentRun

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Stops the assessment run that is specified by the ARN of the assessment run.

Request Syntax

```
{  
    "assessmentRunArn": "string",  
    "stopAction": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

assessmentRunArn

The ARN of the assessment run that you want to stop.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

stopAction

An input option that can be set to either START_EVALUATION or SKIP_EVALUATION.

START_EVALUATION (the default value), stops the AWS agent from collecting data and begins

the results evaluation and the findings generation process. SKIP_EVALUATION cancels the assessment run immediately, after which no findings are generated.

Type: String

Valid Values: START_EVALUATION | SKIP_EVALUATION

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of StopAssessmentRun.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 117
X-Amz-Target: InspectorService.StopAssessmentRun
X-Amz-Date: 20160331T183401Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
    "assessmentRunArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-nvgVhaxX/template/0-it5r2S4T/run/0-11LMTAVe"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 23e1a935-f76f-11e5-92d3-7ba54a65df23
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 18:34:02 GMT
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

SubscribeToEvent

⚠ Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Enables the process of sending Amazon Simple Notification Service (SNS) notifications about a specified event to a specified SNS topic.

Request Syntax

```
{  
  "event": "string",  
  "resourceArn": "string",  
  "topicArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

event

The event for which you want to receive SNS notifications.

Type: String

Valid Values: ASSESSMENT_RUN_STARTED | ASSESSMENT_RUN_COMPLETED | ASSESSMENT_RUN_STATE_CHANGED | FINDING_REPORTED | OTHER

Required: Yes

resourceArn

The ARN of the assessment template that is used during the event for which you want to receive SNS notifications.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

topicArn

The ARN of the SNS topic to which the SNS notifications are sent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error code describes the limit exceeded.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `SubscribeToEvent`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 200
X-Amz-Target: InspectorService.SubscribeToEvent
X-Amz-Date: 20160331T201719Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
    "resourceArn": "arn:aws:inspector:us-west-2:123456789012:target/0-nvgVhaxX/template/0-7sbz2Kz0",
    "event": "ASSESSMENT_RUN_COMPLETED",
    "topicArn": "arn:aws:sns:us-west-2:123456789012:exampletopic"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 929b6c44-f77d-11e5-bcc6-cd3a7bd10be0
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 20:17:20 GMT
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UnsubscribeFromEvent

⚠ Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Disables the process of sending Amazon Simple Notification Service (SNS) notifications about a specified event to a specified SNS topic.

Request Syntax

```
{  
  "event": "string",  
  "resourceArn": "string",  
  "topicArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

event

The event for which you want to stop receiving SNS notifications.

Type: String

Valid Values: ASSESSMENT_RUN_STARTED | ASSESSMENT_RUN_COMPLETED | ASSESSMENT_RUN_STATE_CHANGED | FINDING_REPORTED | OTHER

Required: Yes

resourceArn

The ARN of the assessment template that is used during the event for which you want to stop receiving SNS notifications.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

[topicArn](#)

The ARN of the SNS topic to which SNS notifications are sent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidArgumentException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of UnsubscribeFromEvent.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 200
X-Amz-Target: InspectorService.UnsubscribeFromEvent
X-Amz-Date: 20160331T203404Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
    "resourceArn": "arn:aws:inspector:us-west-2:123456789012:target/0-nvgVhaxX/template/0-7sbz2Kz0",
    "event": "ASSESSMENT_RUN_COMPLETED",
    "topicArn": "arn:aws:sns:us-west-2:123456789012:exampletopic"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: e9c2e864-f77f-11e5-82d7-bb83264505be
Content-Type: application/x-amz-json-1.1
Content-Length: 0
```

Date: Thu, 31 Mar 2016 20:34:06 GMT

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateAssessmentTarget

⚠ Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Updates the assessment target that is specified by the ARN of the assessment target.

If `resourceGroupArn` is not specified, all EC2 instances in the current AWS account and region are included in the assessment target.

Request Syntax

```
{  
    "assessmentTargetArn": "string",  
    "assessmentTargetName": "string",  
    "resourceGroupArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[assessmentTargetArn](#)

The ARN of the assessment target that you want to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

[assessmentTargetName](#)

The name of the assessment target that you want to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: Yes

resourceGroupArn

The ARN of the resource group that is used to specify the new resource group to associate with the assessment target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of UpdateAssessmentTarget.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 206
X-Amz-Target: InspectorService.UpdateAssessmentTarget
X-Amz-Date: 20160331T185748Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
    "assessmentTargetArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-nvgVhaxX",
    "assessmentTargetName": "Example",
    "resourceGroupArn": "arn:aws:inspector:us-
west-2:123456789012:resourcegroup/0-yNbgL5Pt"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 76bc43e7-f772-11e5-a5f3-fb6257e71620
Content-Type: application/x-amz-json-1.1
```

```
Content-Length: 0
Date: Thu, 31 Mar 2016 18:57:49 GMT
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The Amazon Inspector API contains several data types that various actions use. This section describes each data type in detail.

 **Note**

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AgentAlreadyRunningAssessment](#)
- [AgentFilter](#)
- [AgentPreview](#)
- [AssessmentRun](#)
- [AssessmentRunAgent](#)
- [AssessmentRunFilter](#)
- [AssessmentRunNotification](#)
- [AssessmentRunStateChange](#)
- [AssessmentTarget](#)
- [AssessmentTargetFilter](#)
- [AssessmentTemplate](#)
- [AssessmentTemplateFilter](#)
- [AssetAttributes](#)
- [Attribute](#)
- [DurationRange](#)
- [EventSubscription](#)
- [Exclusion](#)
- [ExclusionPreview](#)
- [FailedItemDetails](#)
- [Finding](#)

- [FindingFilter](#)
- [InspectorServiceAttributes](#)
- [NetworkInterface](#)
- [PrivateIp](#)
- [ResourceGroup](#)
- [ResourceGroupTag](#)
- [RulesPackage](#)
- [Scope](#)
- [SecurityGroup](#)
- [Subscription](#)
- [Tag](#)
- [TelemetryMetadata](#)
- [TimestampRange](#)

AgentAlreadyRunningAssessment

Used in the exception error that is thrown if you start an assessment run for an assessment target that includes an EC2 instance that is already participating in another started assessment run.

Contents

agentId

ID of the agent that is running on an EC2 instance that is already participating in another started assessment run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

assessmentRunArn

The ARN of the assessment run that has already been started.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AgentFilter

Contains information about an Amazon Inspector Classic agent. This data type is used as a request parameter in the [ListAssessmentRunAgents](#) action.

Contents

agentHealthCodes

The detailed health state of the agent. Values can be set to **IDLE**, **RUNNING**, **SHUTDOWN**, **UNHEALTHY**, **THROTTLED**, and **UNKNOWN**.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Valid Values: IDLE | RUNNING | SHUTDOWN | UNHEALTHY | THROTTLED | UNKNOWN

Required: Yes

agentHealths

The current health state of the agent. Values can be set to **HEALTHY** or **UNHEALTHY**.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Valid Values: HEALTHY | UNHEALTHY | UNKNOWN

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AgentPreview

Used as a response element in the [PreviewAgents](#) action.

Contents

agentId

The ID of the EC2 instance where the agent is installed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

agentHealth

The health status of the Amazon Inspector Classic Agent.

Type: String

Valid Values: HEALTHY | UNHEALTHY | UNKNOWN

Required: No

agentVersion

The version of the Amazon Inspector Classic Agent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

autoScalingGroup

The Auto Scaling group for the EC2 instance where the agent is installed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

hostname

The hostname of the EC2 instance on which the Amazon Inspector Classic Agent is installed.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

ipv4Address

The IP address of the EC2 instance on which the Amazon Inspector Classic Agent is installed.

Type: String

Length Constraints: Minimum length of 7. Maximum length of 15.

Required: No

kernelVersion

The kernel version of the operating system running on the EC2 instance on which the Amazon Inspector Classic Agent is installed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

operatingSystem

The operating system running on the EC2 instance on which the Amazon Inspector Classic Agent is installed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentRun

A snapshot of an Amazon Inspector Classic assessment run that contains the findings of the assessment run .

Used as the response element in the [DescribeAssessmentRuns](#) action.

Contents

arn

The ARN of the assessment run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

assessmentTemplateArn

The ARN of the assessment template that is associated with the assessment run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

createdAt

The time when [StartAssessmentRun](#) was called.

Type: Timestamp

Required: Yes

dataCollected

A Boolean value (true or false) that specifies whether the process of collecting data from the agents is completed.

Type: Boolean

Required: Yes

durationInSeconds

The duration of the assessment run.

Type: Integer

Valid Range: Minimum value of 180. Maximum value of 86400.

Required: Yes

findingCounts

Provides a total count of generated findings per severity.

Type: String to integer map

Valid Keys: Low | Medium | High | Informational | Undefined

Required: Yes

name

The auto-generated name for the assessment run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: Yes

notifications

A list of notifications for the event subscriptions. A notification about a particular generated finding is added to this list only once.

Type: Array of [AssessmentRunNotification](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: Yes

rulesPackageArns

The rules packages selected for the assessment run.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

state

The state of the assessment run.

Type: String

Valid Values: CREATED | START_DATA_COLLECTION_PENDING |
START_DATA_COLLECTION_IN_PROGRESS | COLLECTING_DATA
| STOP_DATA_COLLECTION_PENDING | DATA_COLLECTED |
START_EVALUATING_RULES_PENDING | EVALUATING_RULES | FAILED | ERROR |
COMPLETED | COMPLETED_WITH_ERRORS | CANCELED

Required: Yes

stateChangedAt

The last time when the assessment run's state changed.

Type: Timestamp

Required: Yes

stateChanges

A list of the assessment run state changes.

Type: Array of [AssessmentRunStateChange](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: Yes

userAttributesForFindings

The user-defined attributes that are assigned to every generated finding.

Type: Array of [Attribute](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: Yes

completedAt

The assessment run completion time that corresponds to the rules packages evaluation completion time or failure.

Type: Timestamp

Required: No

startedAt

The time when [StartAssessmentRun](#) was called.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentRunAgent

Contains information about an Amazon Inspector Classic agent. This data type is used as a response element in the [ListAssessmentRunAgents](#) action.

Contents

agentHealth

The current health state of the agent.

Type: String

Valid Values: HEALTHY | UNHEALTHY | UNKNOWN

Required: Yes

agentHealthCode

The detailed health state of the agent.

Type: String

Valid Values: IDLE | RUNNING | SHUTDOWN | UNHEALTHY | THROTTLED | UNKNOWN

Required: Yes

agentId

The AWS account of the EC2 instance where the agent is installed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

assessmentRunArn

The ARN of the assessment run that is associated with the agent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

telemetryMetadata

The Amazon Inspector Classic application data metrics that are collected by the agent.

Type: Array of [TelemetryMetadata](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5000 items.

Required: Yes

agentHealthDetails

The description for the agent health code.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: No

autoScalingGroup

The Auto Scaling group of the EC2 instance that is specified by the agent ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentRunFilter

Used as the request parameter in the [ListAssessmentRuns](#) action.

Contents

completionTimeRange

For a record to match a filter, the value that is specified for this data type property must inclusively match any value between the specified minimum and maximum values of the **completedAt** property of the [AssessmentRun](#) data type.

Type: [TimestampRange](#) object

Required: No

durationRange

For a record to match a filter, the value that is specified for this data type property must inclusively match any value between the specified minimum and maximum values of the **durationInSeconds** property of the [AssessmentRun](#) data type.

Type: [DurationRange](#) object

Required: No

namePattern

For a record to match a filter, an explicit value or a string containing a wildcard that is specified for this data type property must match the value of the **assessmentRunName** property of the [AssessmentRun](#) data type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: No

rulesPackageArns

For a record to match a filter, the value that is specified for this data type property must be contained in the list of values of the **rulesPackages** property of the [AssessmentRun](#) data type.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

startTimeRange

For a record to match a filter, the value that is specified for this data type property must inclusively match any value between the specified minimum and maximum values of the **startTime** property of the [AssessmentRun](#) data type.

Type: [TimestampRange](#) object

Required: No

stateChangeTimeRange

For a record to match a filter, the value that is specified for this data type property must match the **stateChangedAt** property of the [AssessmentRun](#) data type.

Type: [TimestampRange](#) object

Required: No

states

For a record to match a filter, one of the values specified for this data type property must be the exact match of the value of the **assessmentRunState** property of the [AssessmentRun](#) data type.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Valid Values: CREATED | START_DATA_COLLECTION_PENDING |
START_DATA_COLLECTION_IN_PROGRESS | COLLECTING_DATA
| STOP_DATA_COLLECTION_PENDING | DATA_COLLECTED |
START_EVALUATING_RULES_PENDING | EVALUATING_RULES | FAILED | ERROR |
COMPLETED | COMPLETED_WITH_ERRORS | CANCELED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentRunNotification

Used as one of the elements of the [AssessmentRun](#) data type.

Contents

date

The date of the notification.

Type: Timestamp

Required: Yes

error

The Boolean value that specifies whether the notification represents an error.

Type: Boolean

Required: Yes

event

The event for which a notification is sent.

Type: String

Valid Values: ASSESSMENT_RUN_STARTED | ASSESSMENT_RUN_COMPLETED | ASSESSMENT_RUN_STATE_CHANGED | FINDING_REPORTED | OTHER

Required: Yes

message

The message included in the notification.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: No

snsPublishStatusCode

The status code of the SNS notification.

Type: String

Valid Values: SUCCESS | TOPIC_DOES_NOT_EXIST | ACCESS_DENIED | INTERNAL_ERROR

Required: No

snsTopicArn

The SNS topic to which the SNS notification is sent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentRunStateChange

Used as one of the elements of the [AssessmentRun](#) data type.

Contents

state

The assessment run state.

Type: String

Valid Values: CREATED | START_DATA_COLLECTION_PENDING |
START_DATA_COLLECTION_IN_PROGRESS | COLLECTING_DATA
| STOP_DATA_COLLECTION_PENDING | DATA_COLLECTED |
START_EVALUATING_RULES_PENDING | EVALUATING_RULES | FAILED | ERROR |
COMPLETED | COMPLETED_WITH_ERRORS | CANCELED

Required: Yes

stateChangedAt

The last time the assessment run state changed.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentTarget

Contains information about an Amazon Inspector Classic application. This data type is used as the response element in the [DescribeAssessmentTargets](#) action.

Contents

arn

The ARN that specifies the Amazon Inspector Classic assessment target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

createdAt

The time at which the assessment target is created.

Type: Timestamp

Required: Yes

name

The name of the Amazon Inspector Classic assessment target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: Yes

updatedAt

The time at which [UpdateAssessmentTarget](#) is called.

Type: Timestamp

Required: Yes

resourceGroupArn

The ARN that specifies the resource group that is associated with the assessment target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentTargetFilter

Used as the request parameter in the [ListAssessmentTargets](#) action.

Contents

assessmentTargetNamePattern

For a record to match a filter, an explicit value or a string that contains a wildcard that is specified for this data type property must match the value of the **assessmentTargetName** property of the [AssessmentTarget](#) data type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentTemplate

Contains information about an Amazon Inspector Classic assessment template. This data type is used as the response element in the [DescribeAssessmentTemplates](#) action.

Contents

arn

The ARN of the assessment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

assessmentRunCount

The number of existing assessment runs associated with this assessment template. This value can be zero or a positive integer.

Type: Integer

Required: Yes

assessmentTargetArn

The ARN of the assessment target that corresponds to this assessment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

createdAt

The time at which the assessment template is created.

Type: Timestamp

Required: Yes

durationInSeconds

The duration in seconds specified for this assessment template. The default value is 3600 seconds (one hour). The maximum value is 86400 seconds (one day).

Type: Integer

Valid Range: Minimum value of 180. Maximum value of 86400.

Required: Yes

name

The name of the assessment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: Yes

rulesPackageArns

The rules packages that are specified for this assessment template.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

userAttributesForFindings

The user-defined attributes that are assigned to every generated finding from the assessment run that uses this assessment template.

Type: Array of [Attribute](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: Yes

lastAssessmentRunArn

The Amazon Resource Name (ARN) of the most recent assessment run associated with this assessment template. This value exists only when the value of assessmentRunCount is greater than zero.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentTemplateFilter

Used as the request parameter in the [ListAssessmentTemplates](#) action.

Contents

durationRange

For a record to match a filter, the value specified for this data type property must inclusively match any value between the specified minimum and maximum values of the **durationInSeconds** property of the [AssessmentTemplate](#) data type.

Type: [DurationRange](#) object

Required: No

namePattern

For a record to match a filter, an explicit value or a string that contains a wildcard that is specified for this data type property must match the value of the **assessmentTemplateName** property of the [AssessmentTemplate](#) data type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: No

rulesPackageArns

For a record to match a filter, the values that are specified for this data type property must be contained in the list of values of the **rulesPackageArns** property of the [AssessmentTemplate](#) data type.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssetAttributes

A collection of attributes of the host from which the finding is generated.

Contents

schemaVersion

The schema version of this data type.

Type: Integer

Valid Range: Minimum value of 0.

Required: Yes

agentId

The ID of the agent that is installed on the EC2 instance where the finding is generated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

amIID

The ID of the Amazon Machine Image (AMI) that is installed on the EC2 instance where the finding is generated.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

autoScalingGroup

The Auto Scaling group of the EC2 instance where the finding is generated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

hostname

The hostname of the EC2 instance where the finding is generated.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

ipv4Addresses

The list of IP v4 addresses of the EC2 instance where the finding is generated.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 7. Maximum length of 15.

Required: No

networkInterfaces

An array of the network interfaces interacting with the EC2 instance where the finding is generated.

Type: Array of [NetworkInterface](#) objects

Required: No

tags

The tags related to the EC2 instance where the finding is generated.

Type: Array of [Tag](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Attribute

This data type is used as a request parameter in the [AddAttributesToFindings](#) and [CreateAssessmentTemplate](#) actions.

Contents

key

The attribute key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

value

The value assigned to the attribute key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DurationRange

This data type is used in the [AssessmentTemplateFilter](#) data type.

Contents

maxSeconds

The maximum value of the duration range. Must be less than or equal to 604800 seconds (1 week).

Type: Integer

Valid Range: Minimum value of 180. Maximum value of 86400.

Required: No

minSeconds

The minimum value of the duration range. Must be greater than zero.

Type: Integer

Valid Range: Minimum value of 180. Maximum value of 86400.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EventSubscription

This data type is used in the [Subscription](#) data type.

Contents

event

The event for which Amazon Simple Notification Service (SNS) notifications are sent.

Type: String

Valid Values: ASSESSMENT_RUN_STARTED | ASSESSMENT_RUN_COMPLETED | ASSESSMENT_RUN_STATE_CHANGED | FINDING_REPORTED | OTHER

Required: Yes

subscribedAt

The time at which [SubscribeToEvent](#) is called.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Exclusion

Contains information about what was excluded from an assessment run.

Contents

arn

The ARN that specifies the exclusion.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

description

The description of the exclusion.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: Yes

recommendation

The recommendation for the exclusion.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: Yes

scopes

The AWS resources for which the exclusion pertains.

Type: Array of [Scope](#) objects

Array Members: Minimum number of 1 item.

Required: Yes

title

The name of the exclusion.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: Yes

attributes

The system-defined attributes for the exclusion.

Type: Array of [Attribute](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ExclusionPreview

Contains information about what is excluded from an assessment run given the current state of the assessment template.

Contents

description

The description of the exclusion preview.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: Yes

recommendation

The recommendation for the exclusion preview.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: Yes

scopes

The AWS resources for which the exclusion preview pertains.

Type: Array of [Scope](#) objects

Array Members: Minimum number of 1 item.

Required: Yes

title

The name of the exclusion preview.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: Yes

attributes

The system-defined attributes for the exclusion preview.

Type: Array of [Attribute](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FailedItemDetails

Includes details about the failed items.

Contents

failureCode

The status code of a failed item.

Type: String

Valid Values: INVALID_ARN | DUPLICATE_ARN | ITEM_DOES_NOT_EXIST | ACCESS_DENIED | LIMIT_EXCEEDED | INTERNAL_ERROR

Required: Yes

retryable

Indicates whether you can immediately retry a request for this item for a specified resource.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Finding

Contains information about an Amazon Inspector Classic finding. This data type is used as the response element in the [DescribeFindings](#) action.

Contents

arn

The ARN that specifies the finding.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

attributes

The system-defined attributes for the finding.

Type: Array of [Attribute](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: Yes

createdAt

The time when the finding was generated.

Type: Timestamp

Required: Yes

updatedAt

The time when [AddAttributesToFindings](#) is called.

Type: Timestamp

Required: Yes

userAttributes

The user-defined attributes that are assigned to the finding.

Type: Array of [Attribute](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: Yes

assetAttributes

A collection of attributes of the host from which the finding is generated.

Type: [AssetAttributes](#) object

Required: No

assetType

The type of the host from which the finding is generated.

Type: String

Valid Values: ec2-instance

Required: No

confidence

This data element is currently not used.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 10.

Required: No

description

The description of the finding.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

id

The ID of the finding.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Required: No

indicatorOfCompromise

This data element is currently not used.

Type: Boolean

Required: No

numericSeverity

The numeric value of the finding severity.

Type: Double

Valid Range: Minimum value of 0.0. Maximum value of 10.0.

Required: No

recommendation

The recommendation for the finding.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

schemaVersion

The schema version of this data type.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

service

The data element is set to "Inspector".

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Required: No

serviceAttributes

This data type is used in the [Finding](#) data type.

Type: [InspectorServiceAttributes](#) object

Required: No

severity

The finding severity. Values can be set to High, Medium, Low, and Informational.

Type: String

Valid Values: Low | Medium | High | Informational | Undefined

Required: No

title

The name of the finding.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FindingFilter

This data type is used as a request parameter in the [ListFindings](#) action.

Contents

agentIds

For a record to match a filter, one of the values that is specified for this data type property must be the exact match of the value of the **agentId** property of the [Finding](#) data type.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 99 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

attributes

For a record to match a filter, the list of values that are specified for this data type property must be contained in the list of values of the **attributes** property of the [Finding](#) data type.

Type: Array of [Attribute](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

autoScalingGroups

For a record to match a filter, one of the values that is specified for this data type property must be the exact match of the value of the **autoScalingGroup** property of the [Finding](#) data type.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

creationTimeRange

The time range during which the finding is generated.

Type: [TimestampRange](#) object

Required: No

ruleNames

For a record to match a filter, one of the values that is specified for this data type property must be the exact match of the value of the **ruleName** property of the [Finding](#) data type.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Maximum length of 1000.

Required: No

rulesPackageArns

For a record to match a filter, one of the values that is specified for this data type property must be the exact match of the value of the **rulesPackageArn** property of the [Finding](#) data type.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

severities

For a record to match a filter, one of the values that is specified for this data type property must be the exact match of the value of the **severity** property of the [Finding](#) data type.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Valid Values: Low | Medium | High | Informational | Undefined

Required: No

userAttributes

For a record to match a filter, the value that is specified for this data type property must be contained in the list of values of the **userAttributes** property of the [Finding](#) data type.

Type: Array of [Attribute](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InspectorServiceAttributes

This data type is used in the [Finding](#) data type.

Contents

schemaVersion

The schema version of this data type.

Type: Integer

Valid Range: Minimum value of 0.

Required: Yes

assessmentRunArn

The ARN of the assessment run during which the finding is generated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

rulesPackageArn

The ARN of the rules package that is used to generate the finding.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

NetworkInterface

Contains information about the network interfaces interacting with an EC2 instance. This data type is used as one of the elements of the [AssetAttributes](#) data type.

Contents

ipv6Addresses

The IP addresses associated with the network interface.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

networkInterfaceId

The ID of the network interface.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

privateDnsName

The name of a private DNS associated with the network interface.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

privateIpAddress

The private IP address associated with the network interface.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

privateIpAddresses

A list of the private IP addresses associated with the network interface. Includes the privateDnsName and privateIpAddress.

Type: Array of [PrivateIp](#) objects

Required: No

publicDnsName

The name of a public DNS associated with the network interface.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

publicIp

The public IP address from which the network interface is reachable.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

securityGroups

A list of the security groups associated with the network interface. Includes the groupId and groupName.

Type: Array of [SecurityGroup](#) objects

Required: No

subnetId

The ID of a subnet associated with the network interface.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

vpcId

The ID of a VPC associated with the network interface.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PrivateIp

Contains information about a private IP address associated with a network interface. This data type is used as a response element in the [DescribeFindings](#) action.

Contents

privateDnsName

The DNS name of the private IP address.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

privateIpAddress

The full IP address of the network interface.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceGroup

Contains information about a resource group. The resource group defines a set of tags that, when queried, identify the AWS resources that make up the assessment target. This data type is used as the response element in the [DescribeResourceGroups](#) action.

Contents

arn

The ARN of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

createdAt

The time at which resource group is created.

Type: Timestamp

Required: Yes

tags

The tags (key and value pairs) of the resource group. This data type property is used in the [CreateResourceGroup](#) action.

Type: Array of [ResourceGroupTag](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceGroupTag

This data type is used as one of the elements of the [ResourceGroup](#) data type.

Contents

key

A tag key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

value

The value assigned to a tag key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RulesPackage

Contains information about an Amazon Inspector Classic rules package. This data type is used as the response element in the [DescribeRulesPackages](#) action.

Contents

arn

The ARN of the rules package.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

name

The name of the rules package.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: Yes

provider

The provider of the rules package.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: Yes

version

The version ID of the rules package.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: Yes

description

The description of the rules package.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Scope

This data type contains key-value pairs that identify various Amazon resources.

Contents

key

The type of the scope.

Type: String

Valid Values: INSTANCE_ID | RULES_PACKAGE_ARN

Required: No

value

The resource identifier for the specified scope type.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SecurityGroup

Contains information about a security group associated with a network interface. This data type is used as one of the elements of the [NetworkInterface](#) data type.

Contents

groupId

The ID of the security group.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

groupName

The name of the security group.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Subscription

This data type is used as a response element in the [ListEventSubscriptions](#) action.

Contents

eventSubscriptions

The list of existing event subscriptions.

Type: Array of [EventSubscription](#) objects

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Required: Yes

resourceArn

The ARN of the assessment template that is used during the event for which the SNS notification is sent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

topicArn

The ARN of the Amazon Simple Notification Service (SNS) topic to which the SNS notifications are sent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

A key and value pair. This data type is used as a request parameter in the [SetTagsForResource](#) action and a response element in the [ListTagsForResource](#) action.

Contents

key

A tag key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

value

A value assigned to a tag key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TelemetryMetadata

The metadata about the Amazon Inspector Classic application data metrics collected by the agent. This data type is used as the response element in the [GetTelemetryMetadata](#) action.

Contents

count

The count of messages that the agent sends to the Amazon Inspector Classic service.

Type: Long

Required: Yes

messageType

A specific type of behavioral data that is collected by the agent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

dataSize

The data size of messages that the agent sends to the Amazon Inspector service.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TimestampRange

This data type is used in the [AssessmentRunFilter](#) data type.

Contents

beginDate

The minimum value of the timestamp range.

Type: Timestamp

Required: No

endDate

The maximum value of the timestamp range.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests in the IAM User Guide](#).

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request").

The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400