



API Reference

Amazon Inspector Classic



API Version 2016-02-16

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon Inspector Classic: API Reference

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
AddAttributesToFindings	4
Request Syntax	4
Request Parameters	4
Response Syntax	5
Response Elements	5
Errors	5
Examples	7
See Also	8
CreateAssessmentTarget	9
Request Syntax	9
Request Parameters	9
Response Syntax	10
Response Elements	10
Errors	10
Examples	13
See Also	14
CreateAssessmentTemplate	15
Request Syntax	15
Request Parameters	15
Response Syntax	17
Response Elements	17
Errors	17
Examples	19
See Also	20
CreateExclusionsPreview	22
Request Syntax	22
Request Parameters	22
Response Syntax	22
Response Elements	23
Errors	23
See Also	25
CreateResourceGroup	26

Request Syntax	26
Request Parameters	26
Response Syntax	27
Response Elements	27
Errors	27
Examples	29
See Also	30
DeleteAssessmentRun	31
Request Syntax	31
Request Parameters	31
Response Elements	31
Errors	31
Examples	33
See Also	34
DeleteAssessmentTarget	36
Request Syntax	36
Request Parameters	36
Response Elements	36
Errors	36
Examples	38
See Also	39
DeleteAssessmentTemplate	41
Request Syntax	41
Request Parameters	41
Response Elements	41
Errors	41
Examples	43
See Also	44
DescribeAssessmentRuns	46
Request Syntax	46
Request Parameters	46
Response Syntax	46
Response Elements	48
Errors	48
Examples	49
See Also	51

DescribeAssessmentTargets	53
Request Syntax	53
Request Parameters	53
Response Syntax	53
Response Elements	54
Errors	54
Examples	55
See Also	56
DescribeAssessmentTemplates	58
Request Syntax	58
Request Parameters	58
Response Syntax	58
Response Elements	59
Errors	60
Examples	60
See Also	62
DescribeCrossAccountAccessRole	63
Response Syntax	63
Response Elements	63
Errors	64
Examples	64
See Also	65
DescribeExclusions	67
Request Syntax	67
Request Parameters	67
Response Syntax	68
Response Elements	68
Errors	69
See Also	70
DescribeFindings	71
Request Syntax	71
Request Parameters	71
Response Syntax	72
Response Elements	74
Errors	74
Examples	75

See Also	78
DescribeResourceGroups	79
Request Syntax	79
Request Parameters	79
Response Syntax	79
Response Elements	80
Errors	80
Examples	81
See Also	83
DescribeRulesPackages	84
Request Syntax	84
Request Parameters	84
Response Syntax	85
Response Elements	85
Errors	86
Examples	86
See Also	88
GetAssessmentReport	89
Request Syntax	89
Request Parameters	89
Response Syntax	90
Response Elements	90
Errors	91
See Also	93
GetExclusionsPreview	94
Request Syntax	94
Request Parameters	94
Response Syntax	96
Response Elements	96
Errors	97
See Also	98
GetTelemetryMetadata	100
Request Syntax	100
Request Parameters	100
Response Syntax	100
Response Elements	101

Errors	101
Examples	102
See Also	107
ListAssessmentRunAgents	108
Request Syntax	108
Request Parameters	108
Response Syntax	109
Response Elements	110
Errors	110
Examples	112
See Also	116
ListAssessmentRuns	117
Request Syntax	117
Request Parameters	118
Response Syntax	119
Response Elements	119
Errors	119
Examples	121
See Also	122
ListAssessmentTargets	123
Request Syntax	123
Request Parameters	123
Response Syntax	124
Response Elements	124
Errors	125
Examples	126
See Also	127
ListAssessmentTemplates	128
Request Syntax	128
Request Parameters	128
Response Syntax	129
Response Elements	130
Errors	130
Examples	131
See Also	132
ListEventSubscriptions	134

Request Syntax	134
Request Parameters	134
Response Syntax	135
Response Elements	135
Errors	136
Examples	137
See Also	139
ListExclusions	140
Request Syntax	140
Request Parameters	140
Response Syntax	141
Response Elements	141
Errors	142
See Also	143
ListFindings	144
Request Syntax	144
Request Parameters	145
Response Syntax	146
Response Elements	146
Errors	146
Examples	148
See Also	149
ListRulesPackages	150
Request Syntax	150
Request Parameters	150
Response Syntax	151
Response Elements	151
Errors	151
Examples	152
See Also	153
ListTagsForResource	155
Request Syntax	155
Request Parameters	155
Response Syntax	155
Response Elements	156
Errors	156

Examples	157
See Also	158
PreviewAgents	160
Request Syntax	160
Request Parameters	160
Response Syntax	161
Response Elements	161
Errors	162
Examples	163
See Also	165
RegisterCrossAccountAccessRole	166
Request Syntax	166
Request Parameters	166
Response Elements	166
Errors	167
Examples	168
See Also	169
RemoveAttributesFromFindings	170
Request Syntax	170
Request Parameters	170
Response Syntax	171
Response Elements	171
Errors	171
Examples	173
See Also	174
SetTagsForResource	175
Request Syntax	175
Request Parameters	175
Response Elements	176
Errors	176
Examples	177
See Also	178
StartAssessmentRun	180
Request Syntax	180
Request Parameters	180
Response Syntax	181

Response Elements	181
Errors	181
Examples	184
See Also	185
StopAssessmentRun	186
Request Syntax	186
Request Parameters	186
Response Elements	187
Errors	187
Examples	188
See Also	189
SubscribeToEvent	191
Request Syntax	191
Request Parameters	191
Response Elements	192
Errors	192
Examples	194
See Also	195
UnsubscribeFromEvent	196
Request Syntax	196
Request Parameters	196
Response Elements	197
Errors	197
Examples	198
See Also	199
UpdateAssessmentTarget	201
Request Syntax	201
Request Parameters	201
Response Elements	202
Errors	202
Examples	203
See Also	204
Data Types	206
AgentAlreadyRunningAssessment	208
Contents	208
See Also	208

AgentFilter	209
Contents	209
See Also	209
AgentPreview	210
Contents	210
See Also	211
AssessmentRun	213
Contents	213
See Also	216
AssessmentRunAgent	217
Contents	217
See Also	218
AssessmentRunFilter	219
Contents	219
See Also	221
AssessmentRunNotification	222
Contents	222
See Also	223
AssessmentRunStateChange	224
Contents	224
See Also	224
AssessmentTarget	225
Contents	225
See Also	226
AssessmentTargetFilter	227
Contents	227
See Also	227
AssessmentTemplate	228
Contents	228
See Also	230
AssessmentTemplateFilter	231
Contents	231
See Also	232
AssetAttributes	233
Contents	233
See Also	234

Attribute	236
Contents	236
See Also	236
DurationRange	237
Contents	237
See Also	237
EventSubscription	238
Contents	238
See Also	238
Exclusion	239
Contents	239
See Also	240
ExclusionPreview	241
Contents	241
See Also	242
FailedItemDetails	243
Contents	243
See Also	243
Finding	244
Contents	244
See Also	247
FindingFilter	248
Contents	248
See Also	250
InspectorServiceAttributes	251
Contents	251
See Also	251
NetworkInterface	253
Contents	253
See Also	255
Privatelp	256
Contents	256
See Also	256
ResourceGroup	257
Contents	257
See Also	257

ResourceGroupTag	259
Contents	259
See Also	259
RulesPackage	260
Contents	260
See Also	261
Scope	262
Contents	262
See Also	262
SecurityGroup	263
Contents	263
See Also	263
Subscription	264
Contents	264
See Also	264
Tag	266
Contents	266
See Also	266
TelemetryMetadata	267
Contents	267
See Also	267
TimestampRange	269
Contents	269
See Also	269
Common Parameters	270
Common Error Types	273

Welcome

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Amazon Inspector Classic enables you to analyze the behavior of your AWS resources and to identify potential security issues. For more information, see [Amazon Inspector Classic User Guide](#).

This document was last published on April 30, 2026.

Actions

The following actions are supported:

- [AddAttributesToFindings](#)
- [CreateAssessmentTarget](#)
- [CreateAssessmentTemplate](#)
- [CreateExclusionsPreview](#)
- [CreateResourceGroup](#)
- [DeleteAssessmentRun](#)
- [DeleteAssessmentTarget](#)
- [DeleteAssessmentTemplate](#)
- [DescribeAssessmentRuns](#)
- [DescribeAssessmentTargets](#)
- [DescribeAssessmentTemplates](#)
- [DescribeCrossAccountAccessRole](#)
- [DescribeExclusions](#)
- [DescribeFindings](#)
- [DescribeResourceGroups](#)
- [DescribeRulesPackages](#)
- [GetAssessmentReport](#)
- [GetExclusionsPreview](#)
- [GetTelemetryMetadata](#)
- [ListAssessmentRunAgents](#)
- [ListAssessmentRuns](#)
- [ListAssessmentTargets](#)
- [ListAssessmentTemplates](#)
- [ListEventSubscriptions](#)
- [ListExclusions](#)
- [ListFindings](#)
- [ListRulesPackages](#)

- [ListTagsForResource](#)
- [PreviewAgents](#)
- [RegisterCrossAccountAccessRole](#)
- [RemoveAttributesFromFindings](#)
- [SetTagsForResource](#)
- [StartAssessmentRun](#)
- [StopAssessmentRun](#)
- [SubscribeToEvent](#)
- [UnsubscribeFromEvent](#)
- [UpdateAssessmentTarget](#)

AddAttributesToFindings

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Assigns attributes (key and value pairs) to the findings that are specified by the ARNs of the findings.

Request Syntax

```
{
  "attributes": [
    {
      "key": "string",
      "value": "string"
    }
  ],
  "findingArns": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

attributes

The array of attributes that you want to assign to specified findings.

Type: Array of [Attribute](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: Yes

[findingArns](#)

The ARNs that specify the findings that you want to assign attributes to.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{
  "failedItems": {
    "string" : {
      "failureCode": "string",
      "retryable": boolean
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[failedItems](#)

Attribute details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporarily unavailable.

canRetry

You can wait and then retry your request.

message

Details of the exception error.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `AddAttributesToFindings`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 189
X-Amz-Target: InspectorService.AddAttributesToFindings
X-Amz-Date: 20160329T233810Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "attributes": [
    {
      "key": "Example",
      "value": "example"
    }
  ],
  "findingArns": [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-811VIE0D/run/0-Z02cjjug/finding/0-T8yM9mEU"
```

```
]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 4c8b9c50-f607-11e5-9380-d76f0924b6d7
Content-Type: application/x-amz-json-1.1
Content-Length: 18
Date: Tue, 29 Mar 2016 23:38:11 GMT
{
  "failedItems": {}
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateAssessmentTarget

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Creates a new assessment target using the ARN of the resource group that is generated by [CreateResourceGroup](#). If resourceGroupArn is not specified, all EC2 instances in the current AWS account and region are included in the assessment target. If the [service-linked role](#) isn't already registered, this action also creates and registers a service-linked role to grant Amazon Inspector Classic access to AWS Services needed to perform security assessments. You can create up to 50 assessment targets per AWS account. You can run up to 500 concurrent agents per AWS account. For more information, see [Amazon Inspector Classic Assessment Targets](#).

Request Syntax

```
{
  "assessmentTargetName": "string",
  "resourceGroupArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[assessmentTargetName](#)

The user-defined name that identifies the assessment target that you want to create. The name must be unique within the AWS account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: Yes

resourceGroupArn

The ARN that specifies the resource group that is used to create the assessment target. If resourceGroupArn is not specified, all EC2 instances in the current AWS account and region are included in the assessment target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{  
  "assessmentTargetArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentTargetArn

The ARN that specifies the assessment target that is created.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidCrossAccountRoleException

Amazon Inspector Classic cannot assume the cross-account role that it needs to list your EC2 instances during the assessment run.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error code describes the limit exceeded.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporarily unavailable.

canRetry

You can wait and then retry your request.

message

Details of the exception error.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `CreateAssessmentTarget`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 129
X-Amz-Target: InspectorService.CreateAssessmentTarget
X-Amz-Date: 20160331T174054Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentTargetName": "ExampleAssessmentTarget",
  "resourceGroupArn": "arn:aws:inspector:us-
west-2:123456789012:resourcegroup/0-AB6DMKnv"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: b87f981e-f767-11e5-82d7-bb83264505be
Content-Type: application/x-amz-json-1.1
Content-Length: 84
Date: Thu, 31 Mar 2016 17:40:55 GMT
{
  "assessmentTargetArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-nvgVhaxX"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateAssessmentTemplate

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Creates an assessment template for the assessment target that is specified by the ARN of the assessment target. If the [service-linked role](#) isn't already registered, this action also creates and registers a service-linked role to grant Amazon Inspector Classic access to AWS Services needed to perform security assessments.

Request Syntax

```
{
  "assessmentTargetArn": "string",
  "assessmentTemplateName": "string",
  "durationInSeconds": number,
  "rulesPackageArns": [ "string" ],
  "userAttributesForFindings": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[assessmentTargetArn](#)

The ARN that specifies the assessment target for which you want to create the assessment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

assessmentTemplateName

The user-defined name that identifies the assessment template that you want to create. You can create several assessment templates for an assessment target. The names of the assessment templates that correspond to a particular assessment target must be unique.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: Yes

durationInSeconds

The duration of the assessment run in seconds.

Type: Integer

Valid Range: Minimum value of 180. Maximum value of 86400.

Required: Yes

rulesPackageArns

The ARNs that specify the rules packages that you want to attach to the assessment template.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

userAttributesForFindings

The user-defined attributes that are assigned to every finding that is generated by the assessment run that uses this assessment template. An attribute is a key and value pair (an [Attribute](#) object). Within an assessment template, each key must be unique.

Type: Array of [Attribute](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

Response Syntax

```
{  
  "assessmentTemplateArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[assessmentTemplateArn](#)

The ARN that specifies the assessment template that is created.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error code describes the limit exceeded.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporarily unavailable.

canRetry

You can wait and then retry your request.

message

Details of the exception error.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `CreateAssessmentTemplate`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 335
X-Amz-Target: InspectorService.CreateAssessmentTemplate
X-Amz-Date: 20160331T175559Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 boto-core/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentTargetArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-nvgVhaxX",
  "assessmentTemplateName": "ExampleAssessmentTemplate",
  "userAttributesForFindings": [
    {
```

```
        "key": "Example",
        "value": "example"
    }
],
"durationInSeconds": 180,
"rulesPackageArns": [
    "arn:aws:inspector:us-
west-2:758058086616:rulespackage/0-11B9DBXp"
]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: d3d3d58e-f769-11e5-9da0-9bde5220d15c
Content-Type: application/x-amz-json-1.1
Content-Length: 106
Date: Thu, 31 Mar 2016 17:56:00 GMT
{
    "assessmentTemplateArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-nvgVhaxX/template/0-it5r2S4T"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateExclusionsPreview

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Starts the generation of an exclusions preview for the specified assessment template. The exclusions preview lists the potential exclusions (ExclusionPreview) that Inspector Classic can detect before it runs the assessment.

Request Syntax

```
{  
  "assessmentTemplateArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

assessmentTemplateArn

The ARN that specifies the assessment template for which you want to create an exclusions preview.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{
```

```
"previewToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

previewToken

Specifies the unique identifier of the requested exclusions preview. You can use the unique identifier to retrieve the exclusions preview when running the `GetExclusionsPreview` API.

Type: String

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

PreviewGenerationInProgressException

The request is rejected. The specified assessment template is currently generating an exclusions preview.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporarily unavailable.

canRetry

You can wait and then retry your request.

message

Details of the exception error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateResourceGroup

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Creates a resource group using the specified set of tags (key and value pairs) that are used to select the EC2 instances to be included in an Amazon Inspector Classic assessment target. The created resource group is then used to create an Amazon Inspector Classic assessment target. For more information, see [CreateAssessmentTarget](#).

Request Syntax

```
{
  "resourceGroupTags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[resourceGroupTags](#)

A collection of keys and an array of possible values, `'[{"key":"key1","values":["Value1","Value2"]}, {"key":"Key2","values":["Value3"]}]'`.

For example, `'[{"key":"Name","values":["TestEC2Instance"]}]'`.

Type: Array of [ResourceGroupTag](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: Yes

Response Syntax

```
{  
  "resourceGroupArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[resourceGroupArn](#)

The ARN that specifies the resource group that is created.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error code describes the limit exceeded.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporarily unavailable.

canRetry

You can wait and then retry your request.

message

Details of the exception error.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `CreateResourceGroup`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 67
X-Amz-Target: InspectorService.CreateResourceGroup
X-Amz-Date: 20160331T171757Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "resourceGroupTags": [
    {
      "key": "Name",
      "value": "example"
    }
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 8416dfb4-f764-11e5-872a-fde3682789d5
Content-Type: application/x-amz-json-1.1
Content-Length: 88
Date: Thu, 31 Mar 2016 17:17:58 GMT
{
```

```
        "resourceGroupArn": "arn:aws:inspector:us-  
west-2:123456789012:resourcegroup/0-AB6DMKnv"  
    }
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteAssessmentRun

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Deletes the assessment run that is specified by the ARN of the assessment run.

Request Syntax

```
{
  "assessmentRunArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

assessmentRunArn

The ARN that specifies the assessment run that you want to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AssessmentRunInProgressException

You cannot perform a specified action if an assessment run is currently in progress.

assessmentRunArns

The ARNs of the assessment runs that are currently in progress.

assessmentRunArnsTruncated

Boolean value that indicates whether the ARN list of the assessment runs is truncated.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 400

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

canRetry

You can wait and then retry your request.

message

Details of the exception error.


HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DeleteAssessmentRun.

Sample Request



```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 117
X-Amz-Target: InspectorService.DeleteAssessmentRun
X-Amz-Date: 20160331T183810Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentRunArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-nvgVhaxX/template/0-it5r2S4T/run/0-11LMTAVe"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: b8494bff-f76f-11e5-9d49-6dd670a2a95d
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 18:38:11 GMT
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteAssessmentTarget

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Deletes the assessment target that is specified by the ARN of the assessment target.

Request Syntax

```
{
  "assessmentTargetArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

assessmentTargetArn

The ARN that specifies the assessment target that you want to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AssessmentRunInProgressException

You cannot perform a specified action if an assessment run is currently in progress.

assessmentRunArns

The ARNs of the assessment runs that are currently in progress.

assessmentRunArnsTruncated

Boolean value that indicates whether the ARN list of the assessment runs is truncated.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 400

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporarily unavailable.

canRetry

You can wait and then retry your request.

message

Details of the exception error.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DeleteAssessmentTarget`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 85
X-Amz-Target: InspectorService.DeleteAssessmentTarget
X-Amz-Date: 20160331T184144Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentTargetArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 37dee3da-f770-11e5-b61e-e163adb0c30c
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 18:41:45 GMT
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteAssessmentTemplate

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Deletes the assessment template that is specified by the ARN of the assessment template.

Request Syntax

```
{
  "assessmentTemplateArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[assessmentTemplateArn](#)

The ARN that specifies the assessment template that you want to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AssessmentRunInProgressException

You cannot perform a specified action if an assessment run is currently in progress.

assessmentRunArns

The ARNs of the assessment runs that are currently in progress.

assessmentRunArnsTruncated

Boolean value that indicates whether the ARN list of the assessment runs is truncated.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 400

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

canRetry

You can wait and then retry your request.

message

Details of the exception error.


HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DeleteAssessmentTemplate`.

Sample Request



```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 107
X-Amz-Target: InspectorService.DeleteAssessmentTemplate
X-Amz-Date: 20160331T184505Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentTemplateArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-nvgVhaxX/template/0-it5r2S4T"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: afcc2e7e-f770-11e5-8f9c-054cd1296cf6
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 18:45:06 GMT
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAssessmentRuns

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Describes the assessment runs that are specified by the ARNs of the assessment runs.

Request Syntax

```
{
  "assessmentRunArns": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[assessmentRunArns](#)

The ARN that specifies the assessment run that you want to describe.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{
  "assessmentRuns": [
    {
```

```
"arn": "string",
"assessmentTemplateArn": "string",
"completedAt": number,
"createdAt": number,
"dataCollected": boolean,
"durationInSeconds": number,
"findingCounts": {
  "string" : number
},
"name": "string",
"notifications": [
  {
    "date": number,
    "error": boolean,
    "event": "string",
    "message": "string",
    "snsPublishStatusCode": "string",
    "snsTopicArn": "string"
  }
],
"rulesPackageArns": [ "string" ],
"startedAt": number,
"state": "string",
"stateChangedAt": number,
"stateChanges": [
  {
    "state": "string",
    "stateChangedAt": number
  }
],
"userAttributesForFindings": [
  {
    "key": "string",
    "value": "string"
  }
]
}
],
"failedItems": {
  "string" : {
    "failureCode": "string",
    "retryable": boolean
  }
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentRuns

Information about the assessment run.

Type: Array of [AssessmentRun](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

failedItems

Assessment run details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribeAssessmentRuns.

Sample Request

```
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 120
X-Amz-Target: InspectorService.DescribeAssessmentRuns
X-Amz-Date: 20160323T213431Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentRunArns": [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-4r1V2mAw/run/0-MKkpXXPE"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 0834f495-f13f-11e5-8a9a-395a36305628
Content-Type: application/x-amz-json-1.1
Content-Length: 1156
Date: Wed, 23 Mar 2016 21:34:32 GMT
{
  "assessmentRuns": [
    {
      "arn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-MKkpXXPE",
      "assessmentTemplateArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw",
      "completedAt": 1458680301.4,
      "createdAt": 1458680170.035,
      "dataCollected": true,
      "durationInSeconds": 3600,
      "name": "Run 1 for ExampleAssessmentTemplate",
      "notifications": [],
      "rulesPackageArns": [
        "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-
X1KXtawP"
      ],
      "startedAt": 1458680170.161,
      "state": "COMPLETED",
      "stateChangedAt": 1458680301.4,
      "stateChanges": [
        {
          "state": "CREATED",
          "stateChangedAt": 1458680170.035
        },
        {
          "state": "START_DATA_COLLECTION_PENDING",
          "stateChangedAt": 1458680170.065
        },
        {
          "state": "START_DATA_COLLECTION_IN_PROGRESS",
          "stateChangedAt": 1458680170.096
        },
        {
          "state": "COLLECTING_DATA",
          "stateChangedAt": 1458680170.161
        },
        {
```

```
        "state": "STOP_DATA_COLLECTION_PENDING",
        "stateChangedAt": 1458680239.883
    },
    {
        "state": "DATA_COLLECTED",
        "stateChangedAt": 1458680299.847
    },
    {
        "state": "EVALUATING_RULES",
        "stateChangedAt": 1458680300.099
    },
    {
        "state": "COMPLETED",
        "stateChangedAt": 1458680301.4
    }
],
"userAttributesForFindings": []
}
],
"failedItems": {}
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAssessmentTargets

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Describes the assessment targets that are specified by the ARNs of the assessment targets.

Request Syntax

```
{  
  "assessmentTargetArns": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[assessmentTargetArns](#)

The ARNs that specifies the assessment targets that you want to describe.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{
```

```
"assessmentTargets": [  
  {  
    "arn": "string",  
    "createdAt": number,  
    "name": "string",  
    "resourceGroupArn": "string",  
    "updatedAt": number  
  }  
],  
"failedItems": {  
  "string" : {  
    "failureCode": "string",  
    "retryable": boolean  
  }  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentTargets

Information about the assessment targets.

Type: Array of [AssessmentTarget](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

failedItems

Assessment target details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribeAssessmentTargets.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 88
```

```
X-Amz-Target: InspectorService.DescribeAssessmentTargets
X-Amz-Date: 20160323T214315Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentTargetArns": [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 407ddf01-f140-11e5-823c-bd257ba1495d
Content-Type: application/x-amz-json-1.1
Content-Length: 287
Date: Wed, 23 Mar 2016 21:43:16 GMT
{
  "assessmentTargets": [
    {
      "arn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq",
      "createdAt": 1458074191.459,
      "name": "ExampleAssessmentTarget",
      "resourceGroupArn": "arn:aws:inspector:us-
west-2:123456789012:resourcegroup/0-PyGXopAI",
      "updatedAt": 1458074191.459
    }
  ],
  "failedItems": {}
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAssessmentTemplates

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Describes the assessment templates that are specified by the ARNs of the assessment templates.

Request Syntax

```
{
  "assessmentTemplateArns": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

assessmentTemplateArns

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{
  "assessmentTemplates": [
    {
      "arn": "string",
```

```
    "assessmentRunCount": number,
    "assessmentTargetArn": "string",
    "createdAt": number,
    "durationInSeconds": number,
    "lastAssessmentRunArn": "string",
    "name": "string",
    "rulesPackageArns": [ "string" ],
    "userAttributesForFindings": [
      {
        "key": "string",
        "value": "string"
      }
    ]
  }
],
"failedItems": {
  "string" : {
    "failureCode": "string",
    "retryable": boolean
  }
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentTemplates

Information about the assessment templates.

Type: Array of [AssessmentTemplate](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

failedItems

Assessment template details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribeAssessmentTemplates.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 110
X-Amz-Target: InspectorService.DescribeAssessmentTemplates
X-Amz-Date: 20160323T214822Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentTemplateArns": [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-4r1V2mAw"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: f73a449b-f140-11e5-b473-ed8493878c40
Content-Type: application/x-amz-json-1.1
Content-Length: 422
Date: Wed, 23 Mar 2016 21:48:23 GMT
{
  "assessmentTemplates": [
    {
      "arn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw",
      "assessmentTargetArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq",
      "createdAt": 1458074191.844,
      "durationInSeconds": 3600,
      "name": "ExampleAssessmentTemplate",
      "rulesPackageArns": [
        "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-
X1KXtawP"
      ],
      "userAttributesForFindings": []
    }
  ]
}
```

```
    }  
  ],  
  "failedItems": {}  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeCrossAccountAccessRole

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Describes the IAM role that enables Amazon Inspector Classic to access your AWS account.

Response Syntax

```
{
  "registeredAt": number,
  "roleArn": "string",
  "valid": boolean
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

registeredAt

The date when the cross-account access role was registered.

Type: Timestamp

roleArn

The ARN that specifies the IAM role that Amazon Inspector Classic uses to access your AWS account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

valid

A Boolean value that specifies whether the IAM role has the necessary policies attached to enable Amazon Inspector Classic to access your AWS account.

Type: Boolean

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of DescribeCrossAccountAccessRole.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: InspectorService.DescribeCrossAccountAccessRole
X-Amz-Date: 20160323T215330Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
```

```
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: aef491a7-f141-11e5-bf1e-bbcaff8bf2e
Content-Type: application/x-amz-json-1.1
Content-Length: 99
Date: Wed, 23 Mar 2016 21:53:32 GMT
{
  "registeredAt": 1458069182.826,
  "roleArn": "arn:aws:iam::123456789012:role/inspector",
  "valid": true
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeExclusions

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Describes the exclusions that are specified by the exclusions' ARNs.

Request Syntax

```
{
  "exclusionArns": [ "string" ],
  "locale": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

exclusionArns

The list of ARNs that specify the exclusions that you want to describe.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

locale

The locale into which you want to translate the exclusion's title, description, and recommendation.

Type: String

Valid Values: EN_US

Required: No

Response Syntax

```
{
  "exclusions": {
    "string": {
      "arn": "string",
      "attributes": [
        {
          "key": "string",
          "value": "string"
        }
      ],
      "description": "string",
      "recommendation": "string",
      "scopes": [
        {
          "key": "string",
          "value": "string"
        }
      ],
      "title": "string"
    }
  },
  "failedItems": {
    "string": {
      "failureCode": "string",
      "retryable": boolean
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

exclusions

Information about the exclusions.

Type: String to [Exclusion](#) object map

Map Entries: Maximum number of 100 items.

Key Length Constraints: Minimum length of 1. Maximum length of 300.

failedItems

Exclusion details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeFindings

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Describes the findings that are specified by the ARNs of the findings.

Request Syntax

```
{
  "findingArns": [ "string" ],
  "locale": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

findingArns

The ARN that specifies the finding that you want to describe.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

locale

The locale into which you want to translate a finding description, recommendation, and the short description that identifies the finding.

Type: String

Valid Values: EN_US

Required: No

Response Syntax

```
{
  "failedItems": {
    "string": {
      "failureCode": "string",
      "retryable": boolean
    }
  },
  "findings": [
    {
      "arn": "string",
      "assetAttributes": {
        "agentId": "string",
        "amiId": "string",
        "autoScalingGroup": "string",
        "hostname": "string",
        "ipv4Addresses": [ "string" ],
        "networkInterfaces": [
          {
            "ipv6Addresses": [ "string" ],
            "networkInterfaceId": "string",
            "privateDnsName": "string",
            "privateIpAddress": "string",
            "privateIpAddresses": [
              {
                "privateDnsName": "string",
                "privateIpAddress": "string"
              }
            ],
            "publicDnsName": "string",
            "publicIp": "string",
            "securityGroups": [
              {
                "groupId": "string",
                "groupName": "string"
              }
            ]
          }
        ]
      }
    }
  ]
}
```

```
    ],
    "subnetId": "string",
    "vpcId": "string"
  }
],
"schemaVersion": number,
"tags": [
  {
    "key": "string",
    "value": "string"
  }
]
],
"assetType": "string",
"attributes": [
  {
    "key": "string",
    "value": "string"
  }
],
"confidence": number,
"createdAt": number,
"description": "string",
"id": "string",
"indicatorOfCompromise": boolean,
"numericSeverity": number,
"recommendation": "string",
"schemaVersion": number,
"service": "string",
"serviceAttributes": {
  "assessmentRunArn": "string",
  "rulesPackageArn": "string",
  "schemaVersion": number
},
"severity": "string",
"title": "string",
"updatedAt": number,
"userAttributes": [
  {
    "key": "string",
    "value": "string"
  }
]
]
```

```
]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

failedItems

Finding details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

findings

Information about the finding.

Type: Array of [Finding](#) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribeFindings.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 133
X-Amz-Target: InspectorService.DescribeFindings
X-Amz-Date: 20160323T215809Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "findingArns": [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-4r1V2mAw/run/0-MKkpXXPE/finding/0-HwPnsDm4"
  ]
}
```

Sample Response

```

HTTP/1.1 200 OK
x-amzn-RequestId: 555dbc27-f142-11e5-9dc2-6746fe4b2002
Content-Type: application/x-amz-json-1.1
Content-Length: 892
Date: Wed, 23 Mar 2016 21:58:10 GMT
{
  "failedItems": {},
  "findings": [
    {
      "arn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-MKkpXXPE/finding/0-
HwPnsDm4",
      "assetAttributes": {
        "agentId": "i-092e1184e67721f24",
        "amiId": "ami-0ad99772",
        "autoScalingGroup": "auto scaling group",
        "hostname": "ec2-54-202-242-173.us-
west-2.compute.amazonaws.com",
        "ipv4Addresses": [],
        "networkInterfaces": [
          {
            "ipv6Addresses": [],
            "networkInterfaceId": "eni-09b5ad02",
            "privateDnsName": "ip-172-31-36-75.us-
west-2.compute.internal",
            "privateIpAddress": "172.31.36.75",
            "privateIpAddresses": [
              {
                "privateDnsName": "ip-172-31-36-75.us-
west-2.compute.internal",
                "privateIpAddress": "172.31.36.75"
              }
            ],
            "publicDnsName": "ec2-54-202-242-173.us-
west-2.compute.amazonaws.com",
            "publicIp": "54.202.242.173",

```

```
        "securityGroups": [
            {
                "groupId": "sg-48578931",
                "groupName": "default"
            }
        ],
        "subnetId": "subnet-8aeebbfc",
        "vpcId": "vpc-05515b61"
    }
],
"schemaVersion": 1,
"tags": [
    {
        "key": "scaling",
        "value": "yes"
    },
    {
        "key": "aws:autoscaling:groupName",
        "value": "auto scaling group"
    },
    {
        "key": "Name",
        "value": "beta_amazon_linux_201803_scaling"
    },
    {
        "key": "beta",
        "value": "true"
    }
]
},
"assetType": "ec2-instance",
"attributes": [],
"confidence": 10,
"createdAt": 1458680301.37,
"description": "Amazon Inspector Classic did not find any
potential security issues during this assessment.",
"indicatorOfCompromise": false,
"numericSeverity": 0,
"recommendation": "No remediation needed.",
"schemaVersion": 1,
"service": "Inspector",
"serviceAttributes": {
    "assessmentRunArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-MKkpXXPE",
```

```
        "rulesPackageArn": "arn:aws:inspector:us-  
west-2:758058086616:rulespackage/0-X1KXtawP",  
        "schemaVersion": 1  
    },  
    "severity": "Informational",  
    "title": "No potential security issues found",  
    "updatedAt": 1458680301.37,  
    "userAttributes": []  
  }  
]  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeResourceGroups

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Describes the resource groups that are specified by the ARNs of the resource groups.

Request Syntax

```
{
  "resourceGroupArns": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[resourceGroupArns](#)

The ARN that specifies the resource group that you want to describe.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{
  "failedItems": {
```

```
    "string" : {
      "failureCode": "string",
      "retryable": boolean
    }
  },
  "resourceGroups": [
    {
      "arn": "string",
      "createdAt": number,
      "tags": [
        {
          "key": "string",
          "value": "string"
        }
      ]
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

failedItems

Resource group details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

resourceGroups

Information about a resource group.

Type: Array of [ResourceGroup](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribeResourceGroups.

Sample Request

```
POST / HTTP/1.1
```

```
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 92
X-Amz-Target: InspectorService.DescribeResourceGroups
X-Amz-Date: 20160323T220453Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "resourceGroupArns": [
    "arn:aws:inspector:us-west-2:123456789012:resourcegroup/0-PyGXopAI"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 4636d6a9-f143-11e5-9f03-eb6e194efa59
Content-Type: application/x-amz-json-1.1
Content-Length: 191
Date: Wed, 23 Mar 2016 22:04:54 GMT
{
  "failedItems": {},
  "resourceGroups": [
    {
      "arn": "arn:aws:inspector:us-west-2:123456789012:resourcegroup/0-
PyGXopAI",
      "createdAt": 1458074191.098,
      "tags": [
        {
          "key": "Name",
          "value": "example"
        }
      ]
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeRulesPackages

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Describes the rules packages that are specified by the ARNs of the rules packages.

Request Syntax

```
{
  "locale": "string",
  "rulesPackageArns": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

locale

The locale that you want to translate a rules package description into.

Type: String

Valid Values: EN_US

Required: No

rulesPackageArns

The ARN that specifies the rules package that you want to describe.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{
  "failedItems": {
    "string" : {
      "failureCode": "string",
      "retryable": boolean
    }
  },
  "rulesPackages": [
    {
      "arn": "string",
      "description": "string",
      "name": "string",
      "provider": "string",
      "version": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

failedItems

Rules package details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

rulesPackages

Information about the rules package.

Type: Array of [RulesPackage](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribeRulesPackages.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 90
X-Amz-Target: InspectorService.DescribeRulesPackages
X-Amz-Date: 20160323T220919Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "rulesPackageArns": [
    "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-9hgA516p"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: e4a6aee0-f143-11e5-a5ad-73b7f19c946c
Content-Type: application/x-amz-json-1.1
Content-Length: 387
Date: Wed, 23 Mar 2016 22:09:20 GMT
{
  "failedItems": {},
  "rulesPackages": [
    {
      "arn": "arn:aws:inspector:us-
west-2:758058086616:rulespackage/0-9hgA516p",
      "description": "The rules in this package help verify whether the
EC2 instances in your application are exposed to Common Vulnerabilities and
Exposures (CVEs). Attacks can exploit unpatched vulnerabilities to
compromise the confidentiality, integrity, or availability of your service
or data. The CVE system provides a reference for publicly known
information security vulnerabilities and exposures. For more information, see
```

```
        [https://cve.mitre.org/](https://cve.mitre.org/). If a particular
    CVE appears in one of the produced Findings at the end of a completed
        Inspector Classic assessment, you can search [https://
cve.mitre.org/](https://cve.mitre.org/) using the CVE's ID (for example,
    \"CVE-2009-0021\") to
        find detailed information about this CVE, its severity, and how to
    mitigate it. ",
        "name": "Common Vulnerabilities and Exposures",
        "provider": "Amazon Web Services, Inc.",
        "version": "1.1"
    }
]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetAssessmentReport

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Produces an assessment report that includes detailed and comprehensive results of a specified assessment run.

Request Syntax

```
{
  "assessmentRunArn": "string",
  "reportFileFormat": "string",
  "reportType": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

assessmentRunArn

The ARN that specifies the assessment run for which you want to generate a report.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

reportFileFormat

Specifies the file format (html or pdf) of the assessment report that you want to generate.

Type: String

Valid Values: HTML | PDF

Required: Yes

reportType

Specifies the type of the assessment report that you want to generate. There are two types of assessment reports: a finding report and a full report. For more information, see [Assessment Reports](#).

Type: String

Valid Values: FINDING | FULL

Required: Yes

Response Syntax

```
{
  "status": "string",
  "url": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

status

Specifies the status of the request to generate an assessment report.

Type: String

Valid Values: WORK_IN_PROGRESS | FAILED | COMPLETED

url

Specifies the URL where you can find the generated assessment report. This parameter is only returned if the report is successfully generated.

Type: String

Length Constraints: Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AssessmentRunInProgressException

You cannot perform a specified action if an assessment run is currently in progress.

assessmentRunArns

The ARNs of the assessment runs that are currently in progress.

assessmentRunArnsTruncated

Boolean value that indicates whether the ARN list of the assessment runs is truncated.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 400

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

canRetry

You can wait and then retry your request.

message

Details of the exception error.

HTTP Status Code: 400

UnsupportedFeatureException

Used by the [GetAssessmentReport](#) API. The request was rejected because you tried to generate a report for an assessment run that existed before reporting was supported in Amazon

Inspector. You can only generate reports for assessment runs that took place or will take place after generating reports in Amazon Inspector Classic became available.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetExclusionsPreview

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Retrieves the exclusions preview (a list of ExclusionPreview objects) specified by the preview token. You can obtain the preview token by running the CreateExclusionsPreview API.

Request Syntax

```
{
  "assessmentTemplateArn": "string",
  "locale": "string",
  "maxResults": number,
  "nextToken": "string",
  "previewToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

assessmentTemplateArn

The ARN that specifies the assessment template for which the exclusions preview was requested.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

locale

The locale into which you want to translate the exclusion's title, description, and recommendation.

Type: String

Valid Values: EN_US

Required: No

maxResults

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 100. The maximum value is 500.

Type: Integer

Required: No

nextToken

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the `GetExclusionsPreviewRequest` action. Subsequent calls to the action fill `nextToken` in the request with the value of `nextToken` from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

previewToken

The unique identifier associated of the exclusions preview.

Type: String

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Response Syntax

```
{
  "exclusionPreviews": [
    {
      "attributes": [
        {
          "key": "string",
          "value": "string"
        }
      ],
      "description": "string",
      "recommendation": "string",
      "scopes": [
        {
          "key": "string",
          "value": "string"
        }
      ],
      "title": "string"
    }
  ],
  "nextToken": "string",
  "previewStatus": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

exclusionPreviews

Information about the exclusions included in the preview.

Type: Array of [ExclusionPreview](#) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

nextToken

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the nextToken parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

previewStatus

Specifies the status of the request to generate an exclusions preview.

Type: String

Valid Values: WORK_IN_PROGRESS | COMPLETED

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTelemetryMetadata

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Information about the data that is collected for the specified assessment run.

Request Syntax

```
{  
  "assessmentRunArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[assessmentRunArn](#)

The ARN that specifies the assessment run that has the telemetry data that you want to obtain.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
  "telemetryMetadata": [  
    {
```

```
    "count": number,
    "dataSize": number,
    "messageType": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[telemetryMetadata](#)

Telemetry details.

Type: Array of [TelemetryMetadata](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5000 items.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `GetTelemetryMetadata`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
```

```
Content-Length: 117
X-Amz-Target: InspectorService.GetTelemetryMetadata
X-Amz-Date: 20160329T223852Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentRunArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-MKkpXXPE"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 03ffa82f-f5ff-11e5-9cf9-9fd5e2aef2f6
Content-Type: application/x-amz-json-1.1
Content-Length: 1990
Date: Tue, 29 Mar 2016 22:38:53 GMT
{
  "telemetryMetadata": [
    {
      "count": 2,
      "dataSize": 345,
      "messageType": "InspectorDuplicateProcess"
    },
    {
      "count": 3,
      "dataSize": 255,
      "messageType": "InspectorTimeEventMsg"
    },
    {
      "count": 4,
      "dataSize": 1082,
      "messageType": "InspectorNetworkInterface"
    },
    {
      "count": 2,
      "dataSize": 349,
      "messageType": "InspectorDnsEntry"
    }
  ]
}
```

```
    },
    {
      "count": 11,
      "dataSize": 2514,
      "messageType": "InspectorDirectoryInfoMsg"
    },
    {
      "count": 1,
      "dataSize": 179,
      "messageType": "InspectorTcpV6ListeningPort"
    },
    {
      "count": 101,
      "dataSize": 10949,
      "messageType": "InspectorTerminal"
    },
    {
      "count": 26,
      "dataSize": 5916,
      "messageType": "InspectorUser"
    },
    {
      "count": 282,
      "dataSize": 32148,
      "messageType": "InspectorDynamicallyLoadedCodeModule"
    },
    {
      "count": 18,
      "dataSize": 10172,
      "messageType": "InspectorCreateProcess"
    },
    {
      "count": 3,
      "dataSize": 8001,
      "messageType": "InspectorProcessPerformance"
    },
    {
      "count": 1,
      "dataSize": 360,
      "messageType": "InspectorOperatingSystem"
    },
    {
      "count": 6,
      "dataSize": 546,
```

```
    "messageType": "InspectorStopProcess"
  },
  {
    "count": 1,
    "dataSize": 1553,
    "messageType": "InspectorInstanceMetaData"
  },
  {
    "count": 2,
    "dataSize": 434,
    "messageType": "InspectorTcpV4Connection"
  },
  {
    "count": 474,
    "dataSize": 2960322,
    "messageType": "InspectorPackageInfo"
  },
  {
    "count": 3,
    "dataSize": 2235,
    "messageType": "InspectorSystemPerformance"
  },
  {
    "count": 105,
    "dataSize": 46048,
    "messageType": "InspectorCodeModule"
  },
  {
    "count": 1,
    "dataSize": 182,
    "messageType": "InspectorUdpV6ListeningPort"
  },
  {
    "count": 2,
    "dataSize": 371,
    "messageType": "InspectorUdpV4ListeningPort"
  },
  {
    "count": 18,
    "dataSize": 8362,
    "messageType": "InspectorKernelModule"
  },
  {
    "count": 29,
```

```
        "dataSize": 48788,  
        "messageType": "InspectorConfigurationInfo"  
    },  
    {  
        "count": 1,  
        "dataSize": 79,  
        "messageType": "InspectorMonitoringStart"  
    },  
    {  
        "count": 5,  
        "dataSize": 0,  
        "messageType": "InspectorSplitMsgBegin"  
    },  
    {  
        "count": 51,  
        "dataSize": 4593,  
        "messageType": "InspectorGroup"  
    },  
    {  
        "count": 1,  
        "dataSize": 184,  
        "messageType": "InspectorTcpV4ListeningPort"  
    },  
    {  
        "count": 1159,  
        "dataSize": 3146579,  
        "messageType": "Total"  
    },  
    {  
        "count": 5,  
        "dataSize": 0,  
        "messageType": "InspectorSplitMsgEnd"  
    },  
    {  
        "count": 1,  
        "dataSize": 612,  
        "messageType": "InspectorLoadImageInProgress"  
    }  
  ]  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAssessmentRunAgents

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Lists the agents of the assessment runs that are specified by the ARNs of the assessment runs.

Request Syntax

```
{
  "assessmentRunArn": "string",
  "filter": {
    "agentHealthCodes": [ "string" ],
    "agentHealths": [ "string" ]
  },
  "maxResults": number,
  "nextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[assessmentRunArn](#)

The ARN that specifies the assessment run whose agents you want to list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

filter

You can use this parameter to specify a subset of data to be included in the action's response.

For a record to match a filter, all specified filter attributes must match. When multiple values are specified for a filter attribute, any of the values can match.

Type: [AgentFilter](#) object

Required: No

maxResults

You can use this parameter to indicate the maximum number of items that you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

nextToken

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListAssessmentRunAgents** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{
  "assessmentRunAgents": [
    {
      "agentHealth": "string",
      "agentHealthCode": "string",
      "agentHealthDetails": "string",
      "agentId": "string",
      "assessmentRunArn": "string",
      "autoScalingGroup": "string",
```

```
    "telemetryMetadata": [  
      {  
        "count": number,  
        "dataSize": number,  
        "messageType": "string"  
      }  
    ]  
  },  
  "nextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentRunAgents

A list of ARNs that specifies the agents returned by the action.

Type: Array of [AssessmentRunAgent](#) objects

Array Members: Minimum number of 0 items. Maximum number of 500 items.

nextToken

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListAssessmentRunAgents.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 117
X-Amz-Target: InspectorService.ListAssessmentRunAgents
X-Amz-Date: 20160323T212138Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentRunArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-MKkpXXPE"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 3b752481-f13d-11e5-9f2a-87dc3189b81c
Content-Type: application/x-amz-json-1.1
Content-Length: 2206
Date: Wed, 23 Mar 2016 21:21:39 GMT
{
  "assessmentRunAgents": [
    {
      "agentHealth": "HEALTHY",
      "agentHealthCode": "HEALTHY",
      "agentId": "i-49113b93",
      "assessmentRunArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-MKkpXXPE",
```

```
"telemetryMetadata": [  
  {  
    "count": 2,  
    "dataSize": 345,  
    "messageType": "InspectorDuplicateProcess"  
  },  
  {  
    "count": 3,  
    "dataSize": 255,  
    "messageType": "InspectorTimeEventMsg"  
  },  
  {  
    "count": 4,  
    "dataSize": 1082,  
    "messageType": "InspectorNetworkInterface"  
  },  
  {  
    "count": 2,  
    "dataSize": 349,  
    "messageType": "InspectorDnsEntry"  
  },  
  {  
    "count": 11,  
    "dataSize": 2514,  
    "messageType": "InspectorDirectoryInfoMsg"  
  },  
  {  
    "count": 1,  
    "dataSize": 179,  
    "messageType": "InspectorTcpV6ListeningPort"  
  },  
  {  
    "count": 101,  
    "dataSize": 10949,  
    "messageType": "InspectorTerminal"  
  },  
  {  
    "count": 26,  
    "dataSize": 5916,  
    "messageType": "InspectorUser"  
  },  
  {  
    "count": 282,  
    "dataSize": 32148,  
  }  
]
```

```
    "messageType": "InspectorDynamicallyLoadedCodeModule"
  },
  {
    "count": 18,
    "dataSize": 10172,
    "messageType": "InspectorCreateProcess"
  },
  {
    "count": 3,
    "dataSize": 8001,
    "messageType": "InspectorProcessPerformance"
  },
  {
    "count": 1,
    "dataSize": 360,
    "messageType": "InspectorOperatingSystem"
  },
  {
    "count": 6,
    "dataSize": 546,
    "messageType": "InspectorStopProcess"
  },
  {
    "count": 1,
    "dataSize": 1553,
    "messageType": "InspectorInstanceMetaData"
  },
  {
    "count": 2,
    "dataSize": 434,
    "messageType": "InspectorTcpV4Connection"
  },
  {
    "count": 474,
    "dataSize": 2960322,
    "messageType": "InspectorPackageInfo"
  },
  {
    "count": 3,
    "dataSize": 2235,
    "messageType": "InspectorSystemPerformance"
  },
  {
    "count": 105,
```

```
    "dataSize": 46048,
    "messageType": "InspectorCodeModule"
  },
  {
    "count": 1,
    "dataSize": 182,
    "messageType": "InspectorUdpV6ListeningPort"
  },
  {
    "count": 2,
    "dataSize": 371,
    "messageType": "InspectorUdpV4ListeningPort"
  },
  {
    "count": 18,
    "dataSize": 8362,
    "messageType": "InspectorKernelModule"
  },
  {
    "count": 29,
    "dataSize": 48788,
    "messageType": "InspectorConfigurationInfo"
  },
  {
    "count": 1,
    "dataSize": 79,
    "messageType": "InspectorMonitoringStart"
  },
  {
    "count": 5,
    "dataSize": 0,
    "messageType": "InspectorSplitMsgBegin"
  },
  {
    "count": 51,
    "dataSize": 4593,
    "messageType": "InspectorGroup"
  },
  {
    "count": 1,
    "dataSize": 184,
    "messageType": "InspectorTcpV4ListeningPort"
  },
  {
```

```
        "count": 1159,  
        "dataSize": 3146579,  
        "messageType": "Total"  
    },  
    {  
        "count": 5,  
        "dataSize": 0,  
        "messageType": "InspectorSplitMsgEnd"  
    },  
    {  
        "count": 1,  
        "dataSize": 612,  
        "messageType": "InspectorLoadImageInProgress"  
    }  
  ]  
}  
]  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAssessmentRuns

⚠ Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Lists the assessment runs that correspond to the assessment templates that are specified by the ARNs of the assessment templates.

Request Syntax

```
{
  "assessmentTemplateArns": [ "string" ],
  "filter": {
    "completionTimeRange": {
      "beginDate": number,
      "endDate": number
    },
    "durationRange": {
      "maxSeconds": number,
      "minSeconds": number
    },
    "namePattern": "string",
    "rulesPackageArns": [ "string" ],
    "startTimeRange": {
      "beginDate": number,
      "endDate": number
    },
    "stateChangeTimeRange": {
      "beginDate": number,
      "endDate": number
    },
    "states": [ "string" ]
  },
  "maxResults": number,
  "nextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[assessmentTemplateArns](#)

The ARNs that specify the assessment templates whose assessment runs you want to list.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

[filter](#)

You can use this parameter to specify a subset of data to be included in the action's response.

For a record to match a filter, all specified filter attributes must match. When multiple values are specified for a filter attribute, any of the values can match.

Type: [AssessmentRunFilter](#) object

Required: No

[maxResults](#)

You can use this parameter to indicate the maximum number of items that you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

[nextToken](#)

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListAssessmentRuns** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{
  "assessmentRunArns": [ "string" ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentRunArns

A list of ARNs that specifies the assessment runs that are returned by the action.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

nextToken

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListAssessmentRuns.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: InspectorService.ListAssessmentRuns
X-Amz-Date: 20160323T194135Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 410dabf6-f12f-11e5-8b5a-810259c0c3ae
Content-Type: application/x-amz-json-1.1
Content-Length: 215
Date: Wed, 23 Mar 2016 19:41:36 GMT
{
  "assessmentRunArns":
  [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-4r1V2mAw/run/0-MKkpXXPE",
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-4r1V2mAw/run/0-v5D6fI3v"
  ]
}
```

```
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAssessmentTargets

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Lists the ARNs of the assessment targets within this AWS account. For more information about assessment targets, see [Amazon Inspector Classic Assessment Targets](#).

Request Syntax

```
{
  "filter": {
    "assessmentTargetNamePattern": "string"
  },
  "maxResults": number,
  "nextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

filter

You can use this parameter to specify a subset of data to be included in the action's response.

For a record to match a filter, all specified filter attributes must match. When multiple values are specified for a filter attribute, any of the values can match.

Type: [AssessmentTargetFilter](#) object

Required: No

maxResults

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

nextToken

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListAssessmentTargets** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{
  "assessmentTargetArns": [ "string" ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentTargetArns

A list of ARNs that specifies the assessment targets that are returned by the action.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

nextToken

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListAssessmentTargets.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: InspectorService.ListAssessmentTargets
X-Amz-Date: 20160323T201018Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 445f71f6-f133-11e5-932b-dd9c937d073a
Content-Type: application/x-amz-json-1.1
Content-Length: 87
Date: Wed, 23 Mar 2016 20:10:19 GMT
{
  "assessmentTargetArns": [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq"
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAssessmentTemplates

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Lists the assessment templates that correspond to the assessment targets that are specified by the ARNs of the assessment targets.

Request Syntax

```
{
  "assessmentTargetArns": [ "string" ],
  "filter": {
    "durationRange": {
      "maxSeconds": number,
      "minSeconds": number
    },
    "namePattern": "string",
    "rulesPackageArns": [ "string" ]
  },
  "maxResults": number,
  "nextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

assessmentTargetArns

A list of ARNs that specifies the assessment targets whose assessment templates you want to list.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

filter

You can use this parameter to specify a subset of data to be included in the action's response.

For a record to match a filter, all specified filter attributes must match. When multiple values are specified for a filter attribute, any of the values can match.

Type: [AssessmentTemplateFilter](#) object

Required: No

maxResults

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

nextToken

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListAssessmentTemplates** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{
  "assessmentTemplateArns": [ "string" ],
  "nextToken": "string"
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentTemplateArns

A list of ARNs that specifies the assessment templates returned by the action.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

nextToken

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.


HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `ListAssessmentTemplates`.

Sample Request



```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: InspectorService.ListAssessmentTemplates
X-Amz-Date: 20160323T202549Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 6f406528-f135-11e5-aa71-8de73166bfa9
Content-Type: application/x-amz-json-1.1
Content-Length: 190
Date: Wed, 23 Mar 2016 20:25:50 GMT
{
  "assessmentTemplateArns": [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-4r1V2mAw",
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-Uza6ihLh"
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListEventSubscriptions

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Lists all the event subscriptions for the assessment template that is specified by the ARN of the assessment template. For more information, see [SubscribeToEvent](#) and [UnsubscribeFromEvent](#).

Request Syntax

```
{
  "maxResults": number,
  "nextToken": "string",
  "resourceArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[maxResults](#)

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

[nextToken](#)

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListEventSubscriptions** action. Subsequent calls to the action fill

nextToken in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

resourceArn

The ARN of the assessment template for which you want to list the existing event subscriptions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "subscriptions": [
    {
      "eventSubscriptions": [
        {
          "event": "string",
          "subscribedAt": number
        }
      ],
      "resourceArn": "string",
      "topicArn": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

subscriptions

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Details of the returned event subscriptions.

Type: Array of [Subscription](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListEventSubscriptions.

Sample Request



```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 97
X-Amz-Target: InspectorService.ListEventSubscriptions
X-Amz-Date: 20160331T202943Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "resourceArn": "arn:aws:inspector:us-west-2:123456789012:target/0-
nvgVhaxX/template/0-7sbz2Kz0"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 4e21c005-f77f-11e5-823c-bd257ba1495d
Content-Type: application/x-amz-json-1.1
Content-Length: 272
Date: Thu, 31 Mar 2016 20:29:44 GMT
{
  "subscriptions": [
    {
      "eventSubscriptions": [
        {
          "event": "ASSESSMENT_RUN_COMPLETED",
          "subscribedAt": 1459455440.867
        }
      ],
      "resourceArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-nvgVhaxX/template/0-7sbz2Kz0",
      "topicArn": "arn:aws:sns:us-west-2:123456789012:exampletopic"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListExclusions

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

List exclusions that are generated by the assessment run.

Request Syntax

```
{
  "assessmentRunArn": "string",
  "maxResults": number,
  "nextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[assessmentRunArn](#)

The ARN of the assessment run that generated the exclusions that you want to list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

[maxResults](#)

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 100. The maximum value is 500.

Type: Integer

Required: No

nextToken

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the ListExclusionsRequest action. Subsequent calls to the action fill nextToken in the request with the value of nextToken from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{
  "exclusionArns": [ "string" ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

exclusionArns

A list of exclusions' ARNs returned by the action.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

nextToken

When a response is generated, if there is more data to be listed, this parameters is present in the response and contains the value to use for the nextToken parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListFindings

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Lists findings that are generated by the assessment runs that are specified by the ARNs of the assessment runs.

Request Syntax

```
{
  "assessmentRunArns": [ "string" ],
  "filter": {
    "agentIds": [ "string" ],
    "attributes": [
      {
        "key": "string",
        "value": "string"
      }
    ],
    "autoScalingGroups": [ "string" ],
    "creationTimeRange": {
      "beginDate": number,
      "endDate": number
    },
    "ruleNames": [ "string" ],
    "rulesPackageArns": [ "string" ],
    "severities": [ "string" ],
    "userAttributes": [
      {
        "key": "string",
        "value": "string"
      }
    ]
  },
  "maxResults": number,
```

```
"nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[assessmentRunArns](#)

The ARNs of the assessment runs that generate the findings that you want to list.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

[filter](#)

You can use this parameter to specify a subset of data to be included in the action's response.

For a record to match a filter, all specified filter attributes must match. When multiple values are specified for a filter attribute, any of the values can match.

Type: [FindingFilter](#) object

Required: No

[maxResults](#)

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

[nextToken](#)

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListFindings** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{  
  "findingArns": [ "string" ],  
  "nextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

findingArns

A list of ARNs that specifies the findings returned by the action.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

nextToken

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListFindings.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: InspectorService.ListFindings
X-Amz-Date: 20160323T203109Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 2df2e847-f136-11e5-b2c3-cd62ea256ca4
Content-Type: application/x-amz-json-1.1
Content-Length: 247
Date: Wed, 23 Mar 2016 20:31:10 GMT
{
  "findingArns": [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-4r1V2mAw/run/0-MKkpXXPE/finding/0-HwPnsDm4",
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-4r1V2mAw/run/0-v5D6fI3v/finding/0-tyvmqBLy"
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListRulesPackages

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Lists all available Amazon Inspector Classic rules packages.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

nextToken

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListRulesPackages** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "rulesPackageArns": [ "string" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

rulesPackageArns

The list of ARNs that specifies the rules packages returned by the action.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListRulesPackages.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
```

```
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: InspectorService.ListRulesPackages
X-Amz-Date: 20160323T203727Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 boto-core/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 0e3779a9-f137-11e5-be28-e130082e2a98
Content-Type: application/x-amz-json-1.1
Content-Length: 424
Date: Wed, 23 Mar 2016 20:37:26 GMT
{
  "rulesPackageArns": [
    "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-9hgA516p",
    "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-H5hpSawc",
    "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-JJ0tZiqQ",
    "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-vg5GGHSD"
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Lists all tags associated with an assessment template.

Request Syntax

```
{
  "resourceArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

resourceArn

The ARN that specifies the assessment template whose tags you want to list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{
  "tags": [
    {
      "key": "string",
```

```
    "value": "string"  
  }  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tags

A collection of key and value pairs.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `ListTagsForResource`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 97
X-Amz-Target: InspectorService.ListTagsForResource
X-Amz-Date: 20160323T212838Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
```

```
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "resourceArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq/template/0-gcwFliYu"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 3580d562-f13e-11e5-8a9a-395a36305628
Content-Type: application/x-amz-json-1.1
Content-Length: 50
Date: Wed, 23 Mar 2016 21:28:39 GMT
{
  "tags": [
    {
      "key": "Name",
      "value": "Example"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PreviewAgents

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Previews the agents installed on the EC2 instances that are part of the specified assessment target.

Request Syntax

```
{
  "maxResults": number,
  "nextToken": "string",
  "previewAgentsArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[maxResults](#)

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

[nextToken](#)

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **PreviewAgents** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

previewAgentsArn

The ARN of the assessment target whose agents you want to preview.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{
  "agentPreviews": [
    {
      "agentHealth": "string",
      "agentId": "string",
      "agentVersion": "string",
      "autoScalingGroup": "string",
      "hostname": "string",
      "ipv4Address": "string",
      "kernelVersion": "string",
      "operatingSystem": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

agentPreviews

The resulting list of agents.

Type: Array of [AgentPreview](#) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

nextToken

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidCrossAccountRoleException

Amazon Inspector Classic cannot assume the cross-account role that it needs to list your EC2 instances during the assessment run.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of PreviewAgents.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 82
X-Amz-Target: InspectorService.PreviewAgents
X-Amz-Date: 20160329T224634Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 boto3/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "previewAgentsArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 176c8915-f600-11e5-ac8a-bb6015f4022c
Content-Type: application/x-amz-json-1.1
Content-Length: 44
Date: Tue, 29 Mar 2016 22:46:36 GMT
{
  "agentPreviews": [
    {
      "hostname": "example",
      "agentId": "i-49113b93",
      "autoScalingGroup": "example",
      "agentHealth": HEALTHY,
      "agentVersion": "exampleversion",
      "operatingSystem": "exampleOS",
      "kernelVersion": "examplekernelversion",
      "ipv4Address": "example"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RegisterCrossAccountAccessRole

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Registers the IAM role that grants Amazon Inspector Classic access to AWS Services needed to perform security assessments.

Request Syntax

```
{
  "roleArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

roleArn

The ARN of the IAM role that grants Amazon Inspector Classic access to AWS Services needed to perform security assessments.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidCrossAccountRoleException

Amazon Inspector Classic cannot assume the cross-account role that it needs to list your EC2 instances during the assessment run.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporarily unavailable.

canRetry

You can wait and then retry your request.

message

Details of the exception error.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `RegisterCrossAccountAccessRole`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 55
X-Amz-Target: InspectorService.RegisterCrossAccountAccessRole
X-Amz-Date: 20160329T225544Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "roleArn": "arn:aws:iam::123456789012:role/inspector"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 5f553cfa-f601-11e5-a47c-b7e2de2d572c
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Tue, 29 Mar 2016 22:55:46 GMT
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RemoveAttributesFromFindings

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Removes entire attributes (key and value pairs) from the findings that are specified by the ARNs of the findings where an attribute with the specified key exists.

Request Syntax

```
{
  "attributeKeys": [ "string" ],
  "findingArns": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

attributeKeys

The array of attribute keys that you want to remove from specified findings.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

findingArns

The ARNs that specify the findings that you want to remove attributes from.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{
  "failedItems": {
    "string" : {
      "failureCode": "string",
      "retryable": boolean
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

failedItems

Attributes details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporarily unavailable.

canRetry

You can wait and then retry your request.

message

Details of the exception error.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `RemoveAttributesFromFindings`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 181
X-Amz-Target: InspectorService.RemoveAttributesFromFindings
X-Amz-Date: 20160329T234159Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 boto3/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "attributeKeys": [
    "key=Example,value=example"
  ],
  "findingArns": [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-8l1VIE0D/run/0-Z02cjjug/finding/0-T8yM9mEU"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: d4ebb8cf-f607-11e5-94d7-d9eab7a1ae2a
Content-Type: application/x-amz-json-1.1
Content-Length: 18
Date: Tue, 29 Mar 2016 23:42:00 GMT
{
  "failedItems": {}
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

SetTagsForResource

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Sets tags (key and value pairs) to the assessment template that is specified by the ARN of the assessment template.

Request Syntax

```
{
  "resourceArn": "string",
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[resourceArn](#)

The ARN of the assessment template that you want to set tags to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

tags

A collection of key and value pairs that you want to set to the assessment template.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporarily unavailable.

canRetry

You can wait and then retry your request.

message

Details of the exception error.


HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `SetTagsForResource`.

Sample Request



```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 144
X-Amz-Target: InspectorService.SetTagsForResource
X-Amz-Date: 20160331T185018Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "resourceArn": "arn:aws:inspector:us-west-2:123456789012:target/0-
nvgVhaxX/template/0-7sbz2Kz0",
  "tags": [
    {
      "key": "Example",
      "value": "example"
    }
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 6a3f5af3-f771-11e5-8599-f1b50afafb5a
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 18:50:18 GMT
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartAssessmentRun

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Starts the assessment run specified by the ARN of the assessment template. For this API to function properly, you must not exceed the limit of running up to 500 concurrent agents per AWS account.

Request Syntax

```
{
  "assessmentRunName": "string",
  "assessmentTemplateArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[assessmentRunName](#)

You can specify the name for the assessment run. The name must be unique for the assessment template whose ARN is used to start the assessment run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: No

[assessmentTemplateArn](#)

The ARN of the assessment template of the assessment run that you want to start.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
  "assessmentRunArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[assessmentRunArn](#)

The ARN of the assessment run that has been started.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AgentsAlreadyRunningAssessmentException

You started an assessment run, but one of the instances is already participating in another assessment run.

agents

agentsTruncated

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 400

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidCrossAccountRoleException

Amazon Inspector Classic cannot assume the cross-account role that it needs to list your EC2 instances during the assessment run.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error code describes the limit exceeded.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporarily unavailable.

canRetry

You can wait and then retry your request.

message

Details of the exception error.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `StartAssessmentRun`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 142
X-Amz-Target: InspectorService.StartAssessmentRun
X-Amz-Date: 20160331T182519Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentRunName": "examplerun",
  "assessmentTemplateArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-nvgVhaxX/template/0-it5r2S4T"
}
```

Sample Response

```
HTTP/1.1 200 OK
```

```
x-amzn-RequestId: ed349455-f76d-11e5-b473-ed8493878c40
Content-Type: application/x-amz-json-1.1
Content-Length: 116
Date: Thu, 31 Mar 2016 18:25:22 GMT
{
  "assessmentRunArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-nvgVhaxX/template/0-it5r2S4T/run/0-j0oroxyY"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StopAssessmentRun

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Stops the assessment run that is specified by the ARN of the assessment run.

Request Syntax

```
{
  "assessmentRunArn": "string",
  "stopAction": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

assessmentRunArn

The ARN of the assessment run that you want to stop.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

stopAction

An input option that can be set to either `START_EVALUATION` or `SKIP_EVALUATION`. `START_EVALUATION` (the default value), stops the AWS agent from collecting data and begins the results evaluation and the findings generation process. `SKIP_EVALUATION` cancels the assessment run immediately, after which no findings are generated.

Type: String

Valid Values: START_EVALUATION | SKIP_EVALUATION

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

canRetry

You can wait and then retry your request.

message

Details of the exception error.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of StopAssessmentRun.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
```

```
Content-Length: 117
X-Amz-Target: InspectorService.StopAssessmentRun
X-Amz-Date: 20160331T183401Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentRunArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-nvgVhaxX/template/0-it5r2S4T/run/0-11LMTAVe"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 23e1a935-f76f-11e5-92d3-7ba54a65df23
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 18:34:02 GMT
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

SubscribeToEvent

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Enables the process of sending Amazon Simple Notification Service (SNS) notifications about a specified event to a specified SNS topic.

Request Syntax

```
{
  "event": "string",
  "resourceArn": "string",
  "topicArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

event

The event for which you want to receive SNS notifications.

Type: String

Valid Values: ASSESSMENT_RUN_STARTED | ASSESSMENT_RUN_COMPLETED | ASSESSMENT_RUN_STATE_CHANGED | FINDING_REPORTED | OTHER

Required: Yes

resourceArn

The ARN of the assessment template that is used during the event for which you want to receive SNS notifications.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

topicArn

The ARN of the SNS topic to which the SNS notifications are sent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error code describes the limit exceeded.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporarily unavailable.

canRetry

You can wait and then retry your request.

message

Details of the exception error.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `SubscribeToEvent`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 200
X-Amz-Target: InspectorService.SubscribeToEvent
X-Amz-Date: 20160331T201719Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "resourceArn": "arn:aws:inspector:us-west-2:123456789012:target/0-
nvgVhaxX/template/0-7sbz2Kz0",
  "event": "ASSESSMENT_RUN_COMPLETED",
  "topicArn": "arn:aws:sns:us-west-2:123456789012:exampletopic"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 929b6c44-f77d-11e5-bcc6-cd3a7bd10be0
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 20:17:20 GMT
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UnsubscribeFromEvent

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Disables the process of sending Amazon Simple Notification Service (SNS) notifications about a specified event to a specified SNS topic.

Request Syntax

```
{
  "event": "string",
  "resourceArn": "string",
  "topicArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

event

The event for which you want to stop receiving SNS notifications.

Type: String

Valid Values: ASSESSMENT_RUN_STARTED | ASSESSMENT_RUN_COMPLETED | ASSESSMENT_RUN_STATE_CHANGED | FINDING_REPORTED | OTHER

Required: Yes

resourceArn

The ARN of the assessment template that is used during the event for which you want to stop receiving SNS notifications.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

topicArn

The ARN of the SNS topic to which SNS notifications are sent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporarily unavailable.

canRetry

You can wait and then retry your request.

message

Details of the exception error.

HTTP Status Code: 400

Examples**Example**

This example illustrates one usage of `UnsubscribeFromEvent`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 200
X-Amz-Target: InspectorService.UnsubscribeFromEvent
X-Amz-Date: 20160331T203404Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 boto3/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "resourceArn": "arn:aws:inspector:us-west-2:123456789012:target/0-
nvgVhaxX/template/0-7sbz2Kz0",
  "event": "ASSESSMENT_RUN_COMPLETED",
  "topicArn": "arn:aws:sns:us-west-2:123456789012:exampletopic"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: e9c2e864-f77f-11e5-82d7-bb83264505be
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 20:34:06 GMT
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateAssessmentTarget

Important

End of support notice: On May 20, 2026, AWS will end support for (Amazon Inspector Classic). After May 20, 2026, you will no longer be able to access the Amazon Inspector Classic console or Amazon Inspector Classic resources. For more information, see [Amazon Inspector Classic end of support](#).

Updates the assessment target that is specified by the ARN of the assessment target.

If `resourceGroupArn` is not specified, all EC2 instances in the current AWS account and region are included in the assessment target.

Request Syntax

```
{
  "assessmentTargetArn": "string",
  "assessmentTargetName": "string",
  "resourceGroupArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[assessmentTargetArn](#)

The ARN of the assessment target that you want to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

[assessmentTargetName](#)

The name of the assessment target that you want to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: Yes

resourceGroupArn

The ARN of the resource group that is used to specify the new resource group to associate with the assessment target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InternalException

Internal server error.

canRetry

You can immediately retry your request.

message

Details of the exception error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

canRetry

You can immediately retry your request.

errorCode

Code that indicates the type of error that is generated.

message

Details of the exception error.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporarily unavailable.

canRetry

You can wait and then retry your request.

message

Details of the exception error.

HTTP Status Code: 400

Examples**Example**

This example illustrates one usage of `UpdateAssessmentTarget`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 206
X-Amz-Target: InspectorService.UpdateAssessmentTarget
X-Amz-Date: 20160331T185748Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentTargetArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-nvgVhaxX",
  "assessmentTargetName": "Example",
  "resourceGroupArn": "arn:aws:inspector:us-
west-2:123456789012:resourcegroup/0-yNbgL5Pt"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 76bc43e7-f772-11e5-a5f3-fb6257e71620
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 18:57:49 GMT
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The Amazon Inspector API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AgentAlreadyRunningAssessment](#)
- [AgentFilter](#)
- [AgentPreview](#)
- [AssessmentRun](#)
- [AssessmentRunAgent](#)
- [AssessmentRunFilter](#)
- [AssessmentRunNotification](#)
- [AssessmentRunStateChange](#)
- [AssessmentTarget](#)
- [AssessmentTargetFilter](#)
- [AssessmentTemplate](#)
- [AssessmentTemplateFilter](#)
- [AssetAttributes](#)
- [Attribute](#)
- [DurationRange](#)
- [EventSubscription](#)
- [Exclusion](#)
- [ExclusionPreview](#)
- [FailedItemDetails](#)
- [Finding](#)

- [FindingFilter](#)
- [InspectorServiceAttributes](#)
- [NetworkInterface](#)
- [PrivatelP](#)
- [ResourceGroup](#)
- [ResourceGroupTag](#)
- [RulesPackage](#)
- [Scope](#)
- [SecurityGroup](#)
- [Subscription](#)
- [Tag](#)
- [TelemetryMetadata](#)
- [TimestampRange](#)

AgentAlreadyRunningAssessment

Used in the exception error that is thrown if you start an assessment run for an assessment target that includes an EC2 instance that is already participating in another started assessment run.

Contents

agentId

ID of the agent that is running on an EC2 instance that is already participating in another started assessment run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

assessmentRunArn

The ARN of the assessment run that has already been started.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AgentFilter

Contains information about an Amazon Inspector Classic agent. This data type is used as a request parameter in the [ListAssessmentRunAgents](#) action.

Contents

agentHealthCodes

The detailed health state of the agent. Values can be set to **IDLE**, **RUNNING**, **SHUTDOWN**, **UNHEALTHY**, **THROTTLED**, and **UNKNOWN**.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Valid Values: IDLE | RUNNING | SHUTDOWN | UNHEALTHY | THROTTLED | UNKNOWN

Required: Yes

agentHealths

The current health state of the agent. Values can be set to **HEALTHY** or **UNHEALTHY**.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Valid Values: HEALTHY | UNHEALTHY | UNKNOWN

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AgentPreview

Used as a response element in the [PreviewAgents](#) action.

Contents

agentId

The ID of the EC2 instance where the agent is installed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

agentHealth

The health status of the Amazon Inspector Classic Agent.

Type: String

Valid Values: HEALTHY | UNHEALTHY | UNKNOWN

Required: No

agentVersion

The version of the Amazon Inspector Classic Agent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

autoScalingGroup

The Auto Scaling group for the EC2 instance where the agent is installed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

hostname

The hostname of the EC2 instance on which the Amazon Inspector Classic Agent is installed.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

ipv4Address

The IP address of the EC2 instance on which the Amazon Inspector Classic Agent is installed.

Type: String

Length Constraints: Minimum length of 7. Maximum length of 15.

Required: No

kernelVersion

The kernel version of the operating system running on the EC2 instance on which the Amazon Inspector Classic Agent is installed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

operatingSystem

The operating system running on the EC2 instance on which the Amazon Inspector Classic Agent is installed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentRun

A snapshot of an Amazon Inspector Classic assessment run that contains the findings of the assessment run .

Used as the response element in the [DescribeAssessmentRuns](#) action.

Contents

arn

The ARN of the assessment run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

assessmentTemplateArn

The ARN of the assessment template that is associated with the assessment run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

createdAt

The time when [StartAssessmentRun](#) was called.

Type: Timestamp

Required: Yes

dataCollected

A Boolean value (true or false) that specifies whether the process of collecting data from the agents is completed.

Type: Boolean

Required: Yes

durationInSeconds

The duration of the assessment run.

Type: Integer

Valid Range: Minimum value of 180. Maximum value of 86400.

Required: Yes

findingCounts

Provides a total count of generated findings per severity.

Type: String to integer map

Valid Keys: Low | Medium | High | Informational | Undefined

Required: Yes

name

The auto-generated name for the assessment run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: Yes

notifications

A list of notifications for the event subscriptions. A notification about a particular generated finding is added to this list only once.

Type: Array of [AssessmentRunNotification](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: Yes

rulesPackageArns

The rules packages selected for the assessment run.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

state

The state of the assessment run.

Type: String

Valid Values: CREATED | START_DATA_COLLECTION_PENDING | START_DATA_COLLECTION_IN_PROGRESS | COLLECTING_DATA | STOP_DATA_COLLECTION_PENDING | DATA_COLLECTED | START_EVALUATING_RULES_PENDING | EVALUATING_RULES | FAILED | ERROR | COMPLETED | COMPLETED_WITH_ERRORS | CANCELED

Required: Yes

stateChangedAt

The last time when the assessment run's state changed.

Type: Timestamp

Required: Yes

stateChanges

A list of the assessment run state changes.

Type: Array of [AssessmentRunStateChange](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: Yes

userAttributesForFindings

The user-defined attributes that are assigned to every generated finding.

Type: Array of [Attribute](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: Yes

completedAt

The assessment run completion time that corresponds to the rules packages evaluation completion time or failure.

Type: Timestamp

Required: No

startedAt

The time when [StartAssessmentRun](#) was called.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentRunAgent

Contains information about an Amazon Inspector Classic agent. This data type is used as a response element in the [ListAssessmentRunAgents](#) action.

Contents

agentHealth

The current health state of the agent.

Type: String

Valid Values: HEALTHY | UNHEALTHY | UNKNOWN

Required: Yes

agentHealthCode

The detailed health state of the agent.

Type: String

Valid Values: IDLE | RUNNING | SHUTDOWN | UNHEALTHY | THROTTLED | UNKNOWN

Required: Yes

agentId

The AWS account of the EC2 instance where the agent is installed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

assessmentRunArn

The ARN of the assessment run that is associated with the agent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

telemetryMetadata

The Amazon Inspector Classic application data metrics that are collected by the agent.

Type: Array of [TelemetryMetadata](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5000 items.

Required: Yes

agentHealthDetails

The description for the agent health code.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: No

autoScalingGroup

The Auto Scaling group of the EC2 instance that is specified by the agent ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentRunFilter

Used as the request parameter in the [ListAssessmentRuns](#) action.

Contents

completionTimeRange

For a record to match a filter, the value that is specified for this data type property must inclusively match any value between the specified minimum and maximum values of the **completedAt** property of the [AssessmentRun](#) data type.

Type: [TimestampRange](#) object

Required: No

durationRange

For a record to match a filter, the value that is specified for this data type property must inclusively match any value between the specified minimum and maximum values of the **durationInSeconds** property of the [AssessmentRun](#) data type.

Type: [DurationRange](#) object

Required: No

namePattern

For a record to match a filter, an explicit value or a string containing a wildcard that is specified for this data type property must match the value of the **assessmentRunName** property of the [AssessmentRun](#) data type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: No

rulesPackageArns

For a record to match a filter, the value that is specified for this data type property must be contained in the list of values of the **rulesPackages** property of the [AssessmentRun](#) data type.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

startTimeRange

For a record to match a filter, the value that is specified for this data type property must inclusively match any value between the specified minimum and maximum values of the **startTime** property of the [AssessmentRun](#) data type.

Type: [TimestampRange](#) object

Required: No

stateChangeTimeRange

For a record to match a filter, the value that is specified for this data type property must match the **stateChangedAt** property of the [AssessmentRun](#) data type.

Type: [TimestampRange](#) object

Required: No

states

For a record to match a filter, one of the values specified for this data type property must be the exact match of the value of the **assessmentRunState** property of the [AssessmentRun](#) data type.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Valid Values: CREATED | START_DATA_COLLECTION_PENDING | START_DATA_COLLECTION_IN_PROGRESS | COLLECTING_DATA | STOP_DATA_COLLECTION_PENDING | DATA_COLLECTED | START_EVALUATING_RULES_PENDING | EVALUATING_RULES | FAILED | ERROR | COMPLETED | COMPLETED_WITH_ERRORS | CANCELED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentRunNotification

Used as one of the elements of the [AssessmentRun](#) data type.

Contents

date

The date of the notification.

Type: Timestamp

Required: Yes

error

The Boolean value that specifies whether the notification represents an error.

Type: Boolean

Required: Yes

event

The event for which a notification is sent.

Type: String

Valid Values: ASSESSMENT_RUN_STARTED | ASSESSMENT_RUN_COMPLETED | ASSESSMENT_RUN_STATE_CHANGED | FINDING_REPORTED | OTHER

Required: Yes

message

The message included in the notification.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: No

snsPublishStatusCode

The status code of the SNS notification.

Type: String

Valid Values: SUCCESS | TOPIC_DOES_NOT_EXIST | ACCESS_DENIED | INTERNAL_ERROR

Required: No

snsTopicArn

The SNS topic to which the SNS notification is sent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentRunStateChange

Used as one of the elements of the [AssessmentRun](#) data type.

Contents

state

The assessment run state.

Type: String

Valid Values: CREATED | START_DATA_COLLECTION_PENDING | START_DATA_COLLECTION_IN_PROGRESS | COLLECTING_DATA | STOP_DATA_COLLECTION_PENDING | DATA_COLLECTED | START_EVALUATING_RULES_PENDING | EVALUATING_RULES | FAILED | ERROR | COMPLETED | COMPLETED_WITH_ERRORS | CANCELED

Required: Yes

stateChangedAt

The last time the assessment run state changed.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentTarget

Contains information about an Amazon Inspector Classic application. This data type is used as the response element in the [DescribeAssessmentTargets](#) action.

Contents

arn

The ARN that specifies the Amazon Inspector Classic assessment target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

createdAt

The time at which the assessment target is created.

Type: Timestamp

Required: Yes

name

The name of the Amazon Inspector Classic assessment target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: Yes

updatedAt

The time at which [UpdateAssessmentTarget](#) is called.

Type: Timestamp

Required: Yes

resourceGroupArn

The ARN that specifies the resource group that is associated with the assessment target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentTargetFilter

Used as the request parameter in the [ListAssessmentTargets](#) action.

Contents

assessmentTargetNamePattern

For a record to match a filter, an explicit value or a string that contains a wildcard that is specified for this data type property must match the value of the **assessmentTargetName** property of the [AssessmentTarget](#) data type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentTemplate

Contains information about an Amazon Inspector Classic assessment template. This data type is used as the response element in the [DescribeAssessmentTemplates](#) action.

Contents

arn

The ARN of the assessment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

assessmentRunCount

The number of existing assessment runs associated with this assessment template. This value can be zero or a positive integer.

Type: Integer

Required: Yes

assessmentTargetArn

The ARN of the assessment target that corresponds to this assessment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

createdAt

The time at which the assessment template is created.

Type: Timestamp

Required: Yes

durationInSeconds

The duration in seconds specified for this assessment template. The default value is 3600 seconds (one hour). The maximum value is 86400 seconds (one day).

Type: Integer

Valid Range: Minimum value of 180. Maximum value of 86400.

Required: Yes

name

The name of the assessment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: Yes

rulesPackageArns

The rules packages that are specified for this assessment template.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

userAttributesForFindings

The user-defined attributes that are assigned to every generated finding from the assessment run that uses this assessment template.

Type: Array of [Attribute](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: Yes

lastAssessmentRunArn

The Amazon Resource Name (ARN) of the most recent assessment run associated with this assessment template. This value exists only when the value of `assessmentRunCount` is greaterpa than zero.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentTemplateFilter

Used as the request parameter in the [ListAssessmentTemplates](#) action.

Contents

durationRange

For a record to match a filter, the value specified for this data type property must inclusively match any value between the specified minimum and maximum values of the **durationInSeconds** property of the [AssessmentTemplate](#) data type.

Type: [DurationRange](#) object

Required: No

namePattern

For a record to match a filter, an explicit value or a string that contains a wildcard that is specified for this data type property must match the value of the **assessmentTemplateName** property of the [AssessmentTemplate](#) data type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: No

rulesPackageArns

For a record to match a filter, the values that are specified for this data type property must be contained in the list of values of the **rulesPackageArns** property of the [AssessmentTemplate](#) data type.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssetAttributes

A collection of attributes of the host from which the finding is generated.

Contents

schemaVersion

The schema version of this data type.

Type: Integer

Valid Range: Minimum value of 0.

Required: Yes

agentId

The ID of the agent that is installed on the EC2 instance where the finding is generated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

amiId

The ID of the Amazon Machine Image (AMI) that is installed on the EC2 instance where the finding is generated.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

autoScalingGroup

The Auto Scaling group of the EC2 instance where the finding is generated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

hostname

The hostname of the EC2 instance where the finding is generated.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

ipv4Addresses

The list of IP v4 addresses of the EC2 instance where the finding is generated.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 7. Maximum length of 15.

Required: No

networkInterfaces

An array of the network interfaces interacting with the EC2 instance where the finding is generated.

Type: Array of [NetworkInterface](#) objects

Required: No

tags

The tags related to the EC2 instance where the finding is generated.

Type: Array of [Tag](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Attribute

This data type is used as a request parameter in the [AddAttributesToFindings](#) and [CreateAssessmentTemplate](#) actions.

Contents

key

The attribute key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

value

The value assigned to the attribute key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DurationRange

This data type is used in the [AssessmentTemplateFilter](#) data type.

Contents

maxSeconds

The maximum value of the duration range. Must be less than or equal to 604800 seconds (1 week).

Type: Integer

Valid Range: Minimum value of 180. Maximum value of 86400.

Required: No

minSeconds

The minimum value of the duration range. Must be greater than zero.

Type: Integer

Valid Range: Minimum value of 180. Maximum value of 86400.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EventSubscription

This data type is used in the [Subscription](#) data type.

Contents

event

The event for which Amazon Simple Notification Service (SNS) notifications are sent.

Type: String

Valid Values: ASSESSMENT_RUN_STARTED | ASSESSMENT_RUN_COMPLETED | ASSESSMENT_RUN_STATE_CHANGED | FINDING_REPORTED | OTHER

Required: Yes

subscribedAt

The time at which [SubscribeToEvent](#) is called.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Exclusion

Contains information about what was excluded from an assessment run.

Contents

arn

The ARN that specifies the exclusion.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

description

The description of the exclusion.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: Yes

recommendation

The recommendation for the exclusion.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: Yes

scopes

The AWS resources for which the exclusion pertains.

Type: Array of [Scope](#) objects

Array Members: Minimum number of 1 item.

Required: Yes

title

The name of the exclusion.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: Yes

attributes

The system-defined attributes for the exclusion.

Type: Array of [Attribute](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ExclusionPreview

Contains information about what is excluded from an assessment run given the current state of the assessment template.

Contents

description

The description of the exclusion preview.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: Yes

recommendation

The recommendation for the exclusion preview.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: Yes

scopes

The AWS resources for which the exclusion preview pertains.

Type: Array of [Scope](#) objects

Array Members: Minimum number of 1 item.

Required: Yes

title

The name of the exclusion preview.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: Yes

attributes

The system-defined attributes for the exclusion preview.

Type: Array of [Attribute](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FailedItemDetails

Includes details about the failed items.

Contents

failureCode

The status code of a failed item.

Type: String

Valid Values: INVALID_ARN | DUPLICATE_ARN | ITEM_DOES_NOT_EXIST | ACCESS_DENIED | LIMIT_EXCEEDED | INTERNAL_ERROR

Required: Yes

retryable

Indicates whether you can immediately retry a request for this item for a specified resource.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Finding

Contains information about an Amazon Inspector Classic finding. This data type is used as the response element in the [DescribeFindings](#) action.

Contents

arn

The ARN that specifies the finding.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

attributes

The system-defined attributes for the finding.

Type: Array of [Attribute](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: Yes

createdAt

The time when the finding was generated.

Type: Timestamp

Required: Yes

updatedAt

The time when [AddAttributesToFindings](#) is called.

Type: Timestamp

Required: Yes

userAttributes

The user-defined attributes that are assigned to the finding.

Type: Array of [Attribute](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: Yes

assetAttributes

A collection of attributes of the host from which the finding is generated.

Type: [AssetAttributes](#) object

Required: No

assetType

The type of the host from which the finding is generated.

Type: String

Valid Values: `ec2-instance`

Required: No

confidence

This data element is currently not used.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 10.

Required: No

description

The description of the finding.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

id

The ID of the finding.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Required: No

indicatorOfCompromise

This data element is currently not used.

Type: Boolean

Required: No

numericSeverity

The numeric value of the finding severity.

Type: Double

Valid Range: Minimum value of 0.0. Maximum value of 10.0.

Required: No

recommendation

The recommendation for the finding.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

schemaVersion

The schema version of this data type.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

service

The data element is set to "Inspector".

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Required: No

serviceAttributes

This data type is used in the [Finding](#) data type.

Type: [InspectorServiceAttributes](#) object

Required: No

severity

The finding severity. Values can be set to High, Medium, Low, and Informational.

Type: String

Valid Values: Low | Medium | High | Informational | Undefined

Required: No

title

The name of the finding.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FindingFilter

This data type is used as a request parameter in the [ListFindings](#) action.

Contents

agentIds

For a record to match a filter, one of the values that is specified for this data type property must be the exact match of the value of the **agentId** property of the [Finding](#) data type.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 99 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

attributes

For a record to match a filter, the list of values that are specified for this data type property must be contained in the list of values of the **attributes** property of the [Finding](#) data type.

Type: Array of [Attribute](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

autoScalingGroups

For a record to match a filter, one of the values that is specified for this data type property must be the exact match of the value of the **autoScalingGroup** property of the [Finding](#) data type.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

creationTimeRange

The time range during which the finding is generated.

Type: [TimestampRange](#) object

Required: No

ruleNames

For a record to match a filter, one of the values that is specified for this data type property must be the exact match of the value of the **ruleName** property of the [Finding](#) data type.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Maximum length of 1000.

Required: No

rulesPackageArns

For a record to match a filter, one of the values that is specified for this data type property must be the exact match of the value of the **rulesPackageArn** property of the [Finding](#) data type.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

severities

For a record to match a filter, one of the values that is specified for this data type property must be the exact match of the value of the **severity** property of the [Finding](#) data type.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Valid Values: Low | Medium | High | Informational | Undefined

Required: No

userAttributes

For a record to match a filter, the value that is specified for this data type property must be contained in the list of values of the **userAttributes** property of the [Finding](#) data type.

Type: Array of [Attribute](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InspectorServiceAttributes

This data type is used in the [Finding](#) data type.

Contents

schemaVersion

The schema version of this data type.

Type: Integer

Valid Range: Minimum value of 0.

Required: Yes

assessmentRunArn

The ARN of the assessment run during which the finding is generated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

rulesPackageArn

The ARN of the rules package that is used to generate the finding.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

NetworkInterface

Contains information about the network interfaces interacting with an EC2 instance. This data type is used as one of the elements of the [AssetAttributes](#) data type.

Contents

ipv6Addresses

The IP addresses associated with the network interface.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

networkInterfaceId

The ID of the network interface.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

privateDnsName

The name of a private DNS associated with the network interface.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

privateIpAddress

The private IP address associated with the network interface.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

privateIpAddresses

A list of the private IP addresses associated with the network interface. Includes the `privateDnsName` and `privateIpAddress`.

Type: Array of [PrivateIp](#) objects

Required: No

publicDnsName

The name of a public DNS associated with the network interface.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

publicIp

The public IP address from which the network interface is reachable.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

securityGroups

A list of the security groups associated with the network interface. Includes the `groupId` and `groupName`.

Type: Array of [SecurityGroup](#) objects

Required: No

subnetId

The ID of a subnet associated with the network interface.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

vpId

The ID of a VPC associated with the network interface.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Privatelp

Contains information about a private IP address associated with a network interface. This data type is used as a response element in the [DescribeFindings](#) action.

Contents

privateDnsName

The DNS name of the private IP address.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

privateIpAddress

The full IP address of the network interface.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceGroup

Contains information about a resource group. The resource group defines a set of tags that, when queried, identify the AWS resources that make up the assessment target. This data type is used as the response element in the [DescribeResourceGroups](#) action.

Contents

arn

The ARN of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

createdAt

The time at which resource group is created.

Type: Timestamp

Required: Yes

tags

The tags (key and value pairs) of the resource group. This data type property is used in the [CreateResourceGroup](#) action.

Type: Array of [ResourceGroupTag](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceGroupTag

This data type is used as one of the elements of the [ResourceGroup](#) data type.

Contents

key

A tag key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

value

The value assigned to a tag key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RulesPackage

Contains information about an Amazon Inspector Classic rules package. This data type is used as the response element in the [DescribeRulesPackages](#) action.

Contents

arn

The ARN of the rules package.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

name

The name of the rules package.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: Yes

provider

The provider of the rules package.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: Yes

version

The version ID of the rules package.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: Yes

description

The description of the rules package.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Scope

This data type contains key-value pairs that identify various Amazon resources.

Contents

key

The type of the scope.

Type: String

Valid Values: INSTANCE_ID | RULES_PACKAGE_ARN

Required: No

value

The resource identifier for the specified scope type.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SecurityGroup

Contains information about a security group associated with a network interface. This data type is used as one of the elements of the [NetworkInterface](#) data type.

Contents

groupId

The ID of the security group.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

groupName

The name of the security group.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Subscription

This data type is used as a response element in the [ListEventSubscriptions](#) action.

Contents

eventSubscriptions

The list of existing event subscriptions.

Type: Array of [EventSubscription](#) objects

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Required: Yes

resourceArn

The ARN of the assessment template that is used during the event for which the SNS notification is sent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

topicArn

The ARN of the Amazon Simple Notification Service (SNS) topic to which the SNS notifications are sent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

A key and value pair. This data type is used as a request parameter in the [SetTagsForResource](#) action and a response element in the [ListTagsForResource](#) action.

Contents

key

A tag key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

value

A value assigned to a tag key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TelemetryMetadata

The metadata about the Amazon Inspector Classic application data metrics collected by the agent. This data type is used as the response element in the [GetTelemetryMetadata](#) action.

Contents

count

The count of messages that the agent sends to the Amazon Inspector Classic service.

Type: Long

Required: Yes

messageType

A specific type of behavioral data that is collected by the agent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

dataSize

The data size of messages that the agent sends to the Amazon Inspector service.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TimestampRange

This data type is used in the [AssessmentRunFilter](#) data type.

Contents

beginDate

The minimum value of the timestamp range.

Type: Timestamp

Required: No

endDate

The maximum value of the timestamp range.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Error Types

This section lists common error types that this AWS service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

IncompleteSignature

The request signature doesn't conform to AWS standards. Verify that you're using valid AWS credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 403

InternalFailure

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact AWS Support.

HTTP Status Code: 500

MalformedHttpRequestException

The request body can't be processed. This typically happens when the request body can't be decompressed using the specified content encoding algorithm. Verify that the content encoding header matches the compression format used.

HTTP Status Code: 400

NotAuthorized

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

OptInRequired

Your AWS account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

RequestAbortedException

The request was aborted before a response could be returned. This typically happens when the client closes the connection.

HTTP Status Code: 400

RequestEntityTooLargeException

The request entity is too large. Reduce the size of the request body and try again.

HTTP Status Code: 413

RequestTimeoutException

The request timed out. The server didn't receive the complete request within the expected time frame. Try again.

HTTP Status Code: 408

ServiceUnavailable

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

ThrottlingException

Your request rate is too high. The AWS SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

UnknownOperationException

The action or operation isn't recognized. Verify that the action name is spelled correctly and that it's supported by the API version you're using.

HTTP Status Code: 404

UnrecognizedClientException

The X.509 certificate or AWS access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

ValidationError

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400