

# **API Reference**

# **Amazon Managed Workflows for Apache Airflow Serverless**



**API Version 2024-07-26** 

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

# Amazon Managed Workflows for Apache Airflow Serverless: API Reference

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

# **Table of Contents**

Welcome	1
Actions	2
CreateWorkflow	3
Request Syntax	3
Request Parameters	4
Response Syntax	7
Response Elements	7
Errors	9
See Also	11
DeleteWorkflow	13
Request Syntax	13
Request Parameters	13
Response Syntax	14
Response Elements	14
Errors	15
See Also	16
GetTaskInstance	18
Request Syntax	18
Request Parameters	18
Response Syntax	19
Response Elements	19
Errors	23
See Also	24
GetWorkflow	26
Request Syntax	26
Request Parameters	26
Response Syntax	27
Response Elements	27
Errors	30
See Also	32
GetWorkflowRun	34
Request Syntax	34
Request Parameters	34
Response Syntax	35

Response Elements	35
Errors	36
See Also	38
ListTagsForResource	40
Request Syntax	40
Request Parameters	40
Response Syntax	40
Response Elements	41
Errors	41
See Also	43
ListTaskInstances	44
Request Syntax	44
Request Parameters	44
Response Syntax	45
Response Elements	45
Errors	46
See Also	47
ListWorkflowRuns	49
Request Syntax	49
Request Parameters	49
Response Syntax	50
Response Elements	50
Errors	51
See Also	52
ListWorkflows	54
Request Syntax	54
Request Parameters	54
Response Syntax	55
Response Elements	55
Errors	55
See Also	57
ListWorkflowVersions	58
Request Syntax	58
Request Parameters	58
Response Syntax	59
Response Elements	59

Errors	. 60
See Also	. 61
StartWorkflowRun	. 63
Request Syntax	. 63
Request Parameters	. 63
Response Syntax	. 64
Response Elements	. 65
Errors	65
See Also	. 68
StopWorkflowRun	. 69
Request Syntax	. 69
Request Parameters	. 69
Response Syntax	. 70
Response Elements	. 70
Errors	. 71
See Also	. 73
TagResource	. 74
Request Syntax	. 74
Request Parameters	. 74
Response Elements	. 75
Errors	. 75
See Also	. 77
UntagResource	. 78
Request Syntax	. 78
Request Parameters	. 78
Response Elements	. 79
Errors	. 79
See Also	. 81
UpdateWorkflow	. 82
Request Syntax	. 82
Request Parameters	. 82
Response Syntax	. 84
Response Elements	. 84
Errors	. 85
See Also	. 88
ata Types	89

DefinitionS3Location	90
Contents	90
See Also	90
EncryptionConfiguration	92
Contents	92
See Also	92
LoggingConfiguration	93
Contents	93
See Also	93
NetworkConfiguration	94
Contents	94
See Also	94
RunDetailSummary	96
Contents	96
See Also	97
ScheduleConfiguration	98
Contents	98
See Also	98
TaskInstanceSummary	99
Contents	99
See Also	101
ValidationExceptionField	102
Contents	102
See Also	102
WorkflowRunDetail	103
Contents	103
See Also	106
WorkflowRunSummary	107
Contents	107
See Also	108
WorkflowSummary	109
Contents	109
See Also	111
WorkflowVersionSummary	112
Contents	112
See Also	113

Common Parameters	115
Common Errors	118

# Welcome

Amazon Managed Workflows for Apache Airflow Serverless provides a managed workflow orchestration platform for running Apache Airflow workflows in a serverless environment. You can use Amazon Managed Workflows for Apache Airflow Serverless to create, manage, and run data processing workflows without managing the underlying infrastructure, Airflow clusters, metadata databases, or scheduling overhead. The service provides secure multi-tenant run environments with automatic scaling, comprehensive logging, and integration with multiple AWS services for orchestrating complex analytics workloads.

This document was last published on November 21, 2025.

# **Actions**

# The following actions are supported:

- CreateWorkflow
- DeleteWorkflow
- GetTaskInstance
- GetWorkflow
- GetWorkflowRun
- ListTagsForResource
- ListTaskInstances
- ListWorkflowRuns
- ListWorkflows
- ListWorkflowVersions
- StartWorkflowRun
- StopWorkflowRun
- TagResource
- UntagResource
- UpdateWorkflow

# CreateWorkflow

Creates a new workflow in Amazon Managed Workflows for Apache Airflow Serverless. This operation initializes a workflow with the specified configuration including the workflow definition, execution role, and optional settings for encryption, logging, and networking. You must provide the workflow definition as a YAML file stored in Amazon S3 that defines the DAG structure using supported AWS operators. Amazon Managed Workflows for Apache Airflow Serverless automatically creates the first version of the workflow and sets up the necessary execution environment with multi-tenant isolation and security controls.

# **Request Syntax**

```
{
   "ClientToken": "string",
   "DefinitionS3Location": {
      "Bucket": "string",
      "ObjectKey": "string",
      "VersionId": "string"
   },
   "Description": "string",
   "EncryptionConfiguration": {
      "KmsKeyId": "string",
      "Type": "string"
   },
   "EngineVersion": number,
   "LoggingConfiguration": {
      "LogGroupName": "string"
   },
   "Name": "string",
   "NetworkConfiguration": {
      "SecurityGroupIds": [ "string" ],
      "SubnetIds": [ "string" ]
   },
   "RoleArn": "string",
   "Tags": {
      "string" : "string"
   },
   "TriggerMode": "string"
}
```

CreateWorkflow API Version 2024-07-26 3

# **Request Parameters**

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

## ClientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. This token prevents duplicate workflow creation requests.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern:  $[\x21-\x7E]$ +

Required: No

## **DefinitionS3Location**

The Amazon S3 location where the workflow definition file is stored. This must point to a valid YAML file that defines the workflow structure using supported AWS operators and tasks. Amazon Managed Workflows for Apache Airflow Serverless takes a snapshot of the definition at creation time, so subsequent changes to the Amazon S3 object will not affect the workflow unless you create a new version. In your YAML definition, include task dependencies, scheduling information, and operator configurations that are compatible with the Amazon Managed Workflows for Apache Airflow Serverless execution environment.

Type: DefinitionS3Location object

Required: Yes

# **Description**

An optional description of the workflow that you can use to provide additional context about the workflow's purpose and functionality.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .+

Request Parameters API Version 2024-07-26 4

Required: No

# **EncryptionConfiguration**

The configuration for encrypting workflow data at rest and in transit. Specifies the encryption type and optional KMS key for customer-managed encryption.

Type: EncryptionConfiguration object

Required: No

# **EngineVersion**

The version of the Amazon Managed Workflows for Apache Airflow Serverless engine that you want to use for this workflow. This determines the feature set, supported operators, and execution environment capabilities available to your workflow. Amazon Managed Workflows for Apache Airflow Serverless maintains backward compatibility across versions while introducing new features and improvements. Currently supports version 1 with plans for additional versions as the service evolves.

Type: Integer

Required: No

# LoggingConfiguration

The configuration for workflow logging. Specifies the CloudWatch log group where workflow execution logs are stored. Amazon Managed Workflows for Apache Airflow Serverless automatically exports worker logs and task-level information to the specified log group in your account using remote logging functionality. This provides comprehensive observability for debugging and monitoring workflow execution across the distributed, serverless environment.

Type: LoggingConfiguration object

Required: No

# Name

The name of the workflow. You must use unique workflow names within your AWS account. The service generates a unique identifier that is appended to ensure temporal uniqueness across the account lifecycle.

Type: String

Request Parameters API Version 2024-07-26 5

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern:  $[a-zA-Z0-9]+[a-zA-Z0-9\.\-_]*$ 

Required: Yes

# NetworkConfiguration

Network configuration for the workflow execution environment, including VPC security groups and subnets for secure network access. When specified, Amazon Managed Workflows for Apache Airflow Serverless deploys ECS worker tasks in your customer VPC to provide secure connectivity to your resources. If not specified, tasks run in the service's default worker VPC with network isolation from other customers. This configuration enables secure access to VPC-only resources like RDS databases or private endpoints.

Type: NetworkConfiguration object

Required: No

## RoleArn

The Amazon Resource Name (ARN) of the IAM role that Amazon Managed Workflows for Apache Airflow Serverless assumes when executing the workflow. This role must have the necessary permissions to access the required AWS services and resources that your workflow tasks will interact with. The role is used for task execution in the isolated, multi-tenant environment and should follow the principle of least privilege. Amazon Managed Workflows for Apache Airflow Serverless validates role access during workflow creation but runtime permission checks are performed by the target services.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: arn: aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?:iam::[0-9]  $\{12\}$ :role(/[a-zA-Z0-9+=,.@\_\-]{1,512})\*?/[a-zA-Z0-9+=,.@\_\-]{1,64}

Required: Yes

# **Tags**

A map of tags to assign to the workflow resource. Tags are key-value pairs that are used for resource organization and cost allocation.

Request Parameters API Version 2024-07-26 G

**API Reference** 

```
Type: String to string map
```

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

```
Key Pattern: .*
```

Value Length Constraints: Minimum length of 0. Maximum length of 256.

```
Value Pattern: . *
```

Required: No

# TriggerMode

The trigger mode for the workflow execution.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: .\*

Required: No

# **Response Syntax**

```
{
    "CreatedAt": "string",
    "IsLatestVersion": boolean,
    "RevisionId": "string",
    "Warnings": [ "string" ],
    "WorkflowArn": "string",
    "WorkflowStatus": "string",
    "WorkflowVersion": "string"
}
```

# **Response Elements**

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Response Syntax API Version 2024-07-26 7

#### **CreatedAt**

The timestamp when the workflow was created, in ISO 8601 date-time format.

Type: Timestamp

#### **IsLatestVersion**

A Boolean flag that indicates whether this workflow version is the latest version of the workflow.

Type: Boolean

## RevisionId

A unique identifier for this revision of the workflow configuration. This ID changes when the workflow is updated and you can use it for optimistic concurrency control in update operations. The revision ID helps prevent conflicting updates and ensures that updates are applied to the expected version of the workflow configuration.

Type: String

# **Warnings**

Warning messages generated during workflow creation.

Type: Array of strings

## WorkflowArn

The Amazon Resource Name (ARN) of the newly created workflow. This ARN uniquely identifies the workflow resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

```
Pattern: arn: aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?: airflow-serverless:([a-z]{2}-[a-z]+-[0-9]{1}):([0-9]{12}):workflow/([a-zA-Z0-9][a-zA-Z0-9\.\-_]{0,254}-[a-zA-Z0-9]{10})
```

## WorkflowStatus

The current status of the workflow. Possible values are READY (workflow is ready to run) and DELETING (workflow is being deleted).

Type: String

Valid Values: READY | DELETING

## WorkflowVersion

The version identifier of the workflow. This is a service-generated alphanumeric string that uniquely identifies this version of the workflow. Amazon Managed Workflows for Apache Airflow Serverless uses a version-first approach where each workflow can have multiple immutable versions, which allows you to maintain different configurations and roll back to previous versions as needed. The version identifier is used in ARNs and API operations to reference specific workflow versions.

Type: String

Length Constraints: Fixed length of 32.

Pattern:  $[a-z0-9]{32}$ 

## **Errors**

For information about the errors that are common to all actions, see Common Errors.

# AccessDeniedException

You do not have sufficient permission to perform this action.

HTTP Status Code: 400

# ConflictException

You cannot create a resource that already exists, or the resource is in a state that prevents the requested operation.

#### Resourceld

The unique identifier of the resource.

## ResourceType

The type of the resource.

HTTP Status Code: 400

Errors API Version 2024-07-26 9

#### InternalServerException

An unexpected server-side error occurred during request processing.

## RetryAfterSeconds

The number of seconds to wait before retrying the operation.

HTTP Status Code: 500

## OperationTimeoutException

The operation timed out.

HTTP Status Code: 500

#### ServiceQuotaExceededException

The request exceeds the service quota for Amazon Managed Workflows for Apache Airflow Serverless resources. This can occur when you attempt to create more workflows than allowed, exceed concurrent workflow run limits, or surpass task execution limits. Amazon Managed Workflows for Apache Airflow Serverless implements admission control using DynamoDB-based counters to manage resource utilization across the multi-tenant environment. Contact AWS Support to request quota increases if you need higher limits for your use case.

#### QuotaCode

The code of the quota.

#### Resourceld

The unique identifier of the resource.

#### ResourceType

The type of resource affected.

### ServiceCode

The code for the service.

HTTP Status Code: 400

## **ThrottlingException**

The request was denied because too many requests were made in a short period, exceeding the service rate limits. Amazon Managed Workflows for Apache Airflow Serverless implements

Errors API Version 2024-07-26 10

throttling controls to ensure fair resource allocation across all customers in the multi-tenant environment. This helps maintain service stability and performance. If you encounter throttling, implement exponential backoff and retry logic in your applications, or consider distributing your API calls over a longer time period.

#### QuotaCode

The code of the quota.

## RetryAfterSeconds

The number of seconds to wait before retrying the operation.

#### ServiceCode

The code for the service.

HTTP Status Code: 400

## **ValidationException**

The specified request parameters are invalid, missing, or inconsistent with Amazon Managed Workflows for Apache Airflow Serverless service requirements. This can occur when workflow definitions contain unsupported operators, when required IAM permissions are missing, when S3 locations are inaccessible, or when network configurations are invalid. The service validates workflow definitions, execution roles, and resource configurations to ensure compatibility with the managed Airflow environment and security requirements.

#### **FieldList**

The fields that failed validation.

#### Reason

The reason the request failed validation.

HTTP Status Code: 400

# See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

• AWS Command Line Interface V2

See Also API Version 2024-07-26 11

- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

See Also API Version 2024-07-26 12

# **DeleteWorkflow**

Deletes a workflow and all its versions. This operation permanently removes the workflow and cannot be undone. Amazon Managed Workflows for Apache Airflow Serverless ensures that all associated resources are properly cleaned up, including stopping any running executions, removing scheduled triggers, and cleaning up execution history. The deletion process respects the multitenant isolation boundaries and ensures that no residual data or configurations remain that could affect other customers or workflows.

# **Request Syntax**

```
{
    "WorkflowArn": "string",
    "WorkflowVersion": "string"
}
```

# **Request Parameters**

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

# **WorkflowArn**

The Amazon Resource Name (ARN) of the workflow you want to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

```
Pattern: arn: aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?:airflow-serverless:([a-z]{2}-[a-z]+-[0-9]{1}):([0-9]{12}):workflow/([a-zA-Z0-9][a-zA-Z0-9\.\-_]{0,254}-[a-zA-Z0-9]{10})
```

Required: Yes

#### WorkflowVersion

Optional. The specific version of the workflow to delete. If not specified, all versions of the workflow are deleted.

DeleteWorkflow API Version 2024-07-26 13

Type: String

Length Constraints: Fixed length of 32.

Pattern:  $[a-z0-9]{32}$ 

Required: No

# **Response Syntax**

```
{
    "WorkflowArn": "string",
    "WorkflowVersion": "string"
}
```

# **Response Elements**

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## WorkflowArn

The Amazon Resource Name (ARN) of the deleted workflow.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

```
Pattern: arn: aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?: airflow-serverless:([a-z]{2}-[a-z]+-[0-9]{1}):([0-9]{12}):workflow/([a-zA-Z0-9][a-zA-Z0-9]..-]{0,254}-<math>[a-zA-Z0-9]{10})
```

#### WorkflowVersion

The version of the workflow that was deleted.

Type: String

Length Constraints: Fixed length of 32.

Pattern:  $[a-z0-9]{32}$ 

Response Syntax API Version 2024-07-26 14

#### **Errors**

For information about the errors that are common to all actions, see Common Errors.

# AccessDeniedException

You do not have sufficient permission to perform this action.

HTTP Status Code: 400

## InternalServerException

An unexpected server-side error occurred during request processing.

## RetryAfterSeconds

The number of seconds to wait before retrying the operation.

HTTP Status Code: 500

## OperationTimeoutException

The operation timed out.

HTTP Status Code: 500

# ResourceNotFoundException

The specified resource was not found. You can only access or modify a resource that already exists.

#### Resourceld

The unique identifier of the resource.

## ResourceType

The type of the resource.

HTTP Status Code: 400

#### **ThrottlingException**

The request was denied because too many requests were made in a short period, exceeding the service rate limits. Amazon Managed Workflows for Apache Airflow Serverless implements throttling controls to ensure fair resource allocation across all customers in the multi-tenant environment. This helps maintain service stability and performance. If you encounter throttling,

Errors API Version 2024-07-26 15

implement exponential backoff and retry logic in your applications, or consider distributing your API calls over a longer time period.

## QuotaCode

The code of the quota.

## RetryAfterSeconds

The number of seconds to wait before retrying the operation.

#### ServiceCode

The code for the service.

HTTP Status Code: 400

## ValidationException

The specified request parameters are invalid, missing, or inconsistent with Amazon Managed Workflows for Apache Airflow Serverless service requirements. This can occur when workflow definitions contain unsupported operators, when required IAM permissions are missing, when S3 locations are inaccessible, or when network configurations are invalid. The service validates workflow definitions, execution roles, and resource configurations to ensure compatibility with the managed Airflow environment and security requirements.

#### **FieldList**

The fields that failed validation.

#### Reason

The reason the request failed validation.

HTTP Status Code: 400

# See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET
- AWS SDK for C++

See Also API Version 2024-07-26 16

- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

See Also API Version 2024-07-26 17

# GetTaskInstance

Retrieves detailed information about a specific task instance within a workflow run. Task instances represent individual tasks that are executed as part of a workflow in the Amazon Managed Workflows for Apache Airflow Serverless environment. Each task instance runs in an isolated ECS container with dedicated resources and security boundaries. The service tracks task execution state, retry attempts, and provides detailed timing and error information for troubleshooting and monitoring purposes.

# **Request Syntax**

```
{
    "RunId": "string",
    "TaskInstanceId": "string",
    "WorkflowArn": "string"
}
```

# **Request Parameters**

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

# RunId

The unique identifier of the workflow run that contains the task instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9]+[a-zA-Z0-9\.\-\_]\*

Required: Yes

# **TaskInstanceId**

The unique identifier of the task instance to retrieve.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

GetTaskInstance API Version 2024-07-26 18

```
Pattern: [a-zA-Z0-9]+[a-zA-Z0-9\.\-_]*
```

Required: Yes

## WorkflowArn

The Amazon Resource Name (ARN) of the workflow that contains the task instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

```
Pattern: arn: aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?:airflow-serverless:([a-z]\{2\}-[a-z]+-[0-9]\{1\}):([0-9]\{12\}):workflow/([a-zA-Z0-9][a-zA-Z0-9\.\-_]\{0,254\}-[a-zA-Z0-9]\{10\})
```

Required: Yes

# **Response Syntax**

```
{
   "AttemptNumber": number,
   "DurationInSeconds": number,
   "EndedAt": "string",
   "ErrorMessage": "string",
   "LogStream": "string",
   "ModifiedAt": "string",
   "OperatorName": "string",
   "RunId": "string",
   "StartedAt": "string",
   "Status": "string",
   "TaskId": "string",
   "TaskInstanceId": "string",
   "WorkflowArn": "string",
   "WorkflowVersion": "string",
   "Xcom": {
      "string" : "string"
   }
}
```

# **Response Elements**

If the action is successful, the service sends back an HTTP 200 response.

Response Syntax API Version 2024-07-26 19

The following data is returned in JSON format by the service.

# **AttemptNumber**

The attempt number for this task instance.

Type: Integer

## **DurationInSeconds**

The duration of the task instance execution in seconds. This value is null if the task is not complete.

Type: Integer

# EndedAt

The timestamp when the task instance completed execution, in ISO 8601 date-time format. This value is null if the task is not complete.

Type: Timestamp

# **ErrorMessage**

The error message if the task instance failed. This value is null if the task completed successfully.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: .\*

# LogStream

The CloudWatch log stream name for this task instance execution.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9]+[a-zA-Z0-9\.\-\_]\*

# **ModifiedAt**

The timestamp when the task instance was last modified, in ISO 8601 date-time format.

## Type: Timestamp

# **OperatorName**

The name of the Apache Airflow operator used for this task instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: .\*

## RunId

The unique identifier of the workflow run that contains this task instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9]+[a-zA-Z0-9].

# **StartedAt**

The timestamp when the task instance started execution, in ISO 8601 date-time format. This value is null if the task has not started.

Type: Timestamp

# **Status**

The current status of the task instance.

Type: String

Valid Values: QUEUED | FAILED | SCHEDULED | RUNNING | SUCCESS | UP\_FOR\_RESCHEDULE | UP\_FOR\_RETRY | UPSTREAM\_FAILED | REMOVED | RESTARTING | DEFERRED | NONE | CANCELLED | TIMEOUT

## **TaskId**

The unique identifier of the task definition within the workflow.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9]+[a-zA-Z0-9\.\-\_]\*

## **TaskInstanceId**

The unique identifier of this task instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9]+[a-zA-Z0-9\.\-\_]\*

# WorkflowArn

The Amazon Resource Name (ARN) of the workflow that contains this task instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: arn: aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?: airflow-serverless:( $[a-z]{2}-[a-z]+-[0-9]{1}$ ):( $[0-9]{12}$ ):workflow/([a-zA-Z0-9][a-zA-Z0-9].\-\_] $\{0,254\}-[a-zA-Z0-9]{10}$ )

# WorkflowVersion

The version of the workflow that contains this task instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: .+

# Xcom

Cross-communication data exchanged between tasks in the workflow execution.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 255.

Key Pattern: . \*

Value Length Constraints: Minimum length of 1. Maximum length of 255.

Value Pattern: .\*

## **Errors**

For information about the errors that are common to all actions, see Common Errors.

## AccessDeniedException

You do not have sufficient permission to perform this action.

HTTP Status Code: 400

#### InternalServerException

An unexpected server-side error occurred during request processing.

## RetryAfterSeconds

The number of seconds to wait before retrying the operation.

HTTP Status Code: 500

## OperationTimeoutException

The operation timed out.

HTTP Status Code: 500

#### ResourceNotFoundException

The specified resource was not found. You can only access or modify a resource that already exists.

#### Resourceld

The unique identifier of the resource.

#### ResourceType

The type of the resource.

HTTP Status Code: 400

# ThrottlingException

The request was denied because too many requests were made in a short period, exceeding the service rate limits. Amazon Managed Workflows for Apache Airflow Serverless implements

Errors API Version 2024-07-26 23

throttling controls to ensure fair resource allocation across all customers in the multi-tenant environment. This helps maintain service stability and performance. If you encounter throttling, implement exponential backoff and retry logic in your applications, or consider distributing your API calls over a longer time period.

#### QuotaCode

The code of the quota.

## RetryAfterSeconds

The number of seconds to wait before retrying the operation.

#### ServiceCode

The code for the service.

HTTP Status Code: 400

## ValidationException

The specified request parameters are invalid, missing, or inconsistent with Amazon Managed Workflows for Apache Airflow Serverless service requirements. This can occur when workflow definitions contain unsupported operators, when required IAM permissions are missing, when S3 locations are inaccessible, or when network configurations are invalid. The service validates workflow definitions, execution roles, and resource configurations to ensure compatibility with the managed Airflow environment and security requirements.

#### **FieldList**

The fields that failed validation.

#### Reason

The reason the request failed validation.

HTTP Status Code: 400

# See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

AWS Command Line Interface V2

See Also API Version 2024-07-26 24

- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

See Also API Version 2024-07-26 25

# **GetWorkflow**

Retrieves detailed information about a workflow, including its configuration, status, and metadata.

# **Request Syntax**

```
{
    "WorkflowArn": "string",
    "WorkflowVersion": "string"
}
```

# **Request Parameters**

For information about the parameters that are common to all actions, see **Common Parameters**.

The request accepts the following data in JSON format.

## WorkflowArn

The Amazon Resource Name (ARN) of the workflow you want to retrieve.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

```
Pattern: arn: aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?: airflow-serverless:([a-z]{2}-[a-z]+-[0-9]{1}):([0-9]{12}):workflow/([a-zA-Z0-9][a-zA-Z0-9].\-_]\{0,254\}-[a-zA-Z0-9]{10})
```

Required: Yes

#### WorkflowVersion

Optional. The specific version of the workflow to retrieve. If not specified, the latest version is returned.

Type: String

Length Constraints: Fixed length of 32.

Pattern:  $[a-z0-9]{32}$ 

GetWorkflow API Version 2024-07-26 26

Required: No

# **Response Syntax**

```
{
   "CreatedAt": "string",
   "DefinitionS3Location": {
      "Bucket": "string",
      "ObjectKey": "string",
      "VersionId": "string"
   },
   "Description": "string",
   "EncryptionConfiguration": {
      "KmsKeyId": "string",
      "Type": "string"
   },
   "EngineVersion": number,
   "LoggingConfiguration": {
      "LogGroupName": "string"
   },
   "ModifiedAt": "string",
   "Name": "string",
   "NetworkConfiguration": {
      "SecurityGroupIds": [ "string" ],
      "SubnetIds": [ "string" ]
   },
   "RoleArn": "string",
   "ScheduleConfiguration": {
      "CronExpression": "string"
   },
   "TriggerMode": "string",
   "WorkflowArn": "string",
   "WorkflowDefinition": "string",
   "WorkflowStatus": "string",
   "WorkflowVersion": "string"
}
```

# **Response Elements**

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Response Syntax API Version 2024-07-26 27

#### **CreatedAt**

The timestamp when the workflow was created, in ISO 8601 date-time format.

Type: Timestamp

# **DefinitionS3Location**

The Amazon S3 location of the workflow definition file.

Type: DefinitionS3Location object

# **Description**

The description of the workflow.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .+

# **EncryptionConfiguration**

The encryption configuration for the workflow.

Type: EncryptionConfiguration object

# **EngineVersion**

The version of the Amazon Managed Workflows for Apache Airflow Serverless engine that this workflow uses.

Type: Integer

# LoggingConfiguration

The logging configuration for the workflow.

Type: LoggingConfiguration object

# **ModifiedAt**

The timestamp when the workflow was last modified, in ISO 8601 date-time format.

Type: Timestamp

#### Name

The name of the workflow.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9]+[a-zA-Z0-9\.\-\_]\*

# NetworkConfiguration

The network configuration for the workflow execution environment.

Type: NetworkConfiguration object

# RoleArn

The Amazon Resource Name (ARN) of the IAM role used for workflow execution.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: arn: aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?:iam::[0-9]  $\{12\}$ :role(/[a-zA-Z0-9+=,.@\_\-]{1,512})\*?/[a-zA-Z0-9+=,.@\_\-]{1,64}

# **ScheduleConfiguration**

The schedule configuration for the workflow, including cron expressions for automated execution. Amazon Managed Workflows for Apache Airflow Serverless uses EventBridge Scheduler for cost-effective, timezone-aware scheduling. When a workflow includes schedule information in its YAML definition, the service automatically configures the appropriate triggers for automated execution. Only one version of a workflow can have an active schedule at any given time.

Type: ScheduleConfiguration object

# **TriggerMode**

The trigger mode for the workflow execution.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

#### Pattern: .\*

### WorkflowArn

The Amazon Resource Name (ARN) of the workflow.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

```
Pattern: arn: aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?: airflow-serverless:([a-z]{2}-[a-z]+-[0-9]{1}):([0-9]{12}):workflow/([a-zA-Z0-9]{10})
```

### WorkflowDefinition

The workflow definition content.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: .\*

### WorkflowStatus

The current status of the workflow.

Type: String

Valid Values: READY | DELETING

### WorkflowVersion

The version identifier of the workflow.

Type: String

Length Constraints: Fixed length of 32.

Pattern:  $[a-z0-9]{32}$ 

#### **Errors**

For information about the errors that are common to all actions, see Common Errors.

Errors API Version 2024-07-26 30

### AccessDeniedException

You do not have sufficient permission to perform this action.

HTTP Status Code: 400

### InternalServerException

An unexpected server-side error occurred during request processing.

### RetryAfterSeconds

The number of seconds to wait before retrying the operation.

HTTP Status Code: 500

### OperationTimeoutException

The operation timed out.

HTTP Status Code: 500

### ResourceNotFoundException

The specified resource was not found. You can only access or modify a resource that already exists.

#### Resourceld

The unique identifier of the resource.

#### ResourceType

The type of the resource.

HTTP Status Code: 400

### **ThrottlingException**

The request was denied because too many requests were made in a short period, exceeding the service rate limits. Amazon Managed Workflows for Apache Airflow Serverless implements throttling controls to ensure fair resource allocation across all customers in the multi-tenant environment. This helps maintain service stability and performance. If you encounter throttling, implement exponential backoff and retry logic in your applications, or consider distributing your API calls over a longer time period.

Errors API Version 2024-07-26 31

#### QuotaCode

The code of the quota.

### RetryAfterSeconds

The number of seconds to wait before retrying the operation.

#### ServiceCode

The code for the service.

HTTP Status Code: 400

#### ValidationException

The specified request parameters are invalid, missing, or inconsistent with Amazon Managed Workflows for Apache Airflow Serverless service requirements. This can occur when workflow definitions contain unsupported operators, when required IAM permissions are missing, when S3 locations are inaccessible, or when network configurations are invalid. The service validates workflow definitions, execution roles, and resource configurations to ensure compatibility with the managed Airflow environment and security requirements.

#### **FieldList**

The fields that failed validation.

#### Reason

The reason the request failed validation.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2

- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **GetWorkflowRun**

Retrieves detailed information about a specific workflow run, including its status, execution details, and task instances.

# **Request Syntax**

```
{
    "RunId": "string",
    "WorkflowArn": "string"
}
```

# **Request Parameters**

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

### RunId

The unique identifier of the workflow run to retrieve.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9]+[a-zA-Z0-9\.\-\_]\*

Required: Yes

### WorkflowArn

The Amazon Resource Name (ARN) of the workflow that contains the run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

```
Pattern: arn: aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?: airflow-serverless:([a-z]{2}-[a-z]+-[0-9]{1}):([0-9]{12}): workflow/([a-zA-Z0-9][a-zA-Z0-9\.\-_]{0,254}-[a-zA-Z0-9]{10})
```

Required: Yes

GetWorkflowRun API Version 2024-07-26 34

# **Response Syntax**

```
{
   "OverrideParameters": {
      "string" : JSON value
   },
   "RunDetail": {
      "CompletedOn": "string",
      "CreatedAt": "string",
      "Duration": number,
      "ErrorMessage": "string",
      "ModifiedAt": "string",
      "RunId": "string",
      "RunState": "string",
      "RunType": "string",
      "StartedOn": "string",
      "TaskInstances": [ "string" ],
      "WorkflowArn": "string",
      "WorkflowVersion": "string"
   "RunId": "string",
   "RunType": "string",
   "WorkflowArn": "string",
   "WorkflowVersion": "string"
}
```

# **Response Elements**

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **OverrideParameters**

Parameters that were overridden for this specific workflow run.

Type: String to JSON value map

#### RunDetail

Detailed information about the workflow run execution, including timing, status, and task instances.

Response Syntax API Version 2024-07-26 35

### Type: WorkflowRunDetail object

### RunId

The unique identifier of this workflow run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9]+[a-zA-Z0-9\.\-\_]\*

### RunType

The type of workflow run. Values are ON\_DEMAND (manually triggered) or SCHEDULED (automatically triggered by schedule).

Type: String

Valid Values: ON\_DEMAND | SCHEDULED

### WorkflowArn

The Amazon Resource Name (ARN) of the workflow that contains this run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: arn: aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?: airflow-serverless:( $[a-z]{2}-[a-z]+-[0-9]{1}$ ):( $[0-9]{12}$ ):workflow/( $[a-zA-Z0-9]{10}$ )

## WorkflowVersion

The version of the workflow that is used for this run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: .+

### **Errors**

For information about the errors that are common to all actions, see Common Errors.

Errors API Version 2024-07-26 36

#### AccessDeniedException

You do not have sufficient permission to perform this action.

HTTP Status Code: 400

#### InternalServerException

An unexpected server-side error occurred during request processing.

### RetryAfterSeconds

The number of seconds to wait before retrying the operation.

HTTP Status Code: 500

### OperationTimeoutException

The operation timed out.

HTTP Status Code: 500

### ResourceNotFoundException

The specified resource was not found. You can only access or modify a resource that already exists.

#### Resourceld

The unique identifier of the resource.

#### ResourceType

The type of the resource.

HTTP Status Code: 400

# ThrottlingException

The request was denied because too many requests were made in a short period, exceeding the service rate limits. Amazon Managed Workflows for Apache Airflow Serverless implements throttling controls to ensure fair resource allocation across all customers in the multi-tenant environment. This helps maintain service stability and performance. If you encounter throttling, implement exponential backoff and retry logic in your applications, or consider distributing your API calls over a longer time period.

Errors API Version 2024-07-26 37

#### QuotaCode

The code of the quota.

### RetryAfterSeconds

The number of seconds to wait before retrying the operation.

#### ServiceCode

The code for the service.

HTTP Status Code: 400

### **ValidationException**

The specified request parameters are invalid, missing, or inconsistent with Amazon Managed Workflows for Apache Airflow Serverless service requirements. This can occur when workflow definitions contain unsupported operators, when required IAM permissions are missing, when S3 locations are inaccessible, or when network configurations are invalid. The service validates workflow definitions, execution roles, and resource configurations to ensure compatibility with the managed Airflow environment and security requirements.

#### **FieldList**

The fields that failed validation.

#### Reason

The reason the request failed validation.

HTTP Status Code: 400

# See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2

- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# ListTagsForResource

Lists all tags that are associated with a specified Amazon Managed Workflows for Apache Airflow Serverless resource.

# **Request Syntax**

```
{
    "ResourceArn": "string"
}
```

# **Request Parameters**

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

#### ResourceArn

The Amazon Resource Name (ARN) of the resource for which to list tags.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

```
Pattern: arn: aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?: airflow-serverless:([a-z]{2}-[a-z]+-[0-9]{1}):([0-9]{12}):workflow/([a-zA-Z0-9][a-zA-Z0-9\.\-_]{0,254}-[a-zA-Z0-9]{10})
```

Required: Yes

# **Response Syntax**

```
{
    "<u>Tags</u>": {
        "string" : "string"
    }
}
```

ListTagsForResource API Version 2024-07-26 40

# **Response Elements**

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **Tags**

A map of tags that are associated with the resource, where each tag consists of a key-value pair.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: .\*

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: .\*

### **Errors**

For information about the errors that are common to all actions, see Common Errors.

# AccessDeniedException

You do not have sufficient permission to perform this action.

HTTP Status Code: 400

# InternalServerException

An unexpected server-side error occurred during request processing.

# ${\bf Retry After Seconds}$

The number of seconds to wait before retrying the operation.

HTTP Status Code: 500

## OperationTimeoutException

The operation timed out.

Response Elements API Version 2024-07-26 41

HTTP Status Code: 500

### ResourceNotFoundException

The specified resource was not found. You can only access or modify a resource that already exists.

#### Resourceld

The unique identifier of the resource.

### ResourceType

The type of the resource.

HTTP Status Code: 400

### **ThrottlingException**

The request was denied because too many requests were made in a short period, exceeding the service rate limits. Amazon Managed Workflows for Apache Airflow Serverless implements throttling controls to ensure fair resource allocation across all customers in the multi-tenant environment. This helps maintain service stability and performance. If you encounter throttling, implement exponential backoff and retry logic in your applications, or consider distributing your API calls over a longer time period.

#### QuotaCode

The code of the quota.

### RetryAfterSeconds

The number of seconds to wait before retrying the operation.

### ServiceCode

The code for the service.

HTTP Status Code: 400

### ValidationException

The specified request parameters are invalid, missing, or inconsistent with Amazon Managed Workflows for Apache Airflow Serverless service requirements. This can occur when workflow definitions contain unsupported operators, when required IAM permissions are missing, when S3 locations are inaccessible, or when network configurations are invalid. The service validates

Errors API Version 2024-07-26 42

workflow definitions, execution roles, and resource configurations to ensure compatibility with the managed Airflow environment and security requirements.

### **FieldList**

The fields that failed validation.

#### Reason

The reason the request failed validation.

HTTP Status Code: 400

# **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# ListTaskInstances

Lists all task instances for a specific workflow run, with optional pagination support.

# **Request Syntax**

```
{
   "MaxResults": number,
   "NextToken": "string",
   "RunId": "string",
   "WorkflowArn": "string"
}
```

# **Request Parameters**

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

### **MaxResults**

The maximum number of task instances to return in a single response.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

### NextToken

The pagination token you need to use to retrieve the next set of results. This value is returned from a previous call to ListTaskInstances.

Type: String

Required: No

#### RunId

The unique identifier of the workflow run for which you want a list of task instances.

Type: String

ListTaskInstances API Version 2024-07-26 44

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9]+[a-zA-Z0-9\.\-\_]\*

Required: Yes

#### WorkflowArn

The Amazon Resource Name (ARN) of the workflow that contains the run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

```
Pattern: arn: aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?: airflow-serverless:([a-z]{2}-[a-z]+-[0-9]{1}):([0-9]{12}): workflow/([a-zA-Z0-9][a-zA-Z0-9\.\-_]{0,254}-[a-zA-Z0-9]{10})
```

Required: Yes

# **Response Syntax**

# **Response Elements**

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Response Syntax API Version 2024-07-26 45

#### NextToken

The pagination token you need to use to retrieve the next set of results. This value is null if there are no more results.

Type: String

### **TaskInstances**

A list of task instance summaries for the specified workflow run.

Type: Array of TaskInstanceSummary objects

### **Errors**

For information about the errors that are common to all actions, see Common Errors.

### AccessDeniedException

You do not have sufficient permission to perform this action.

HTTP Status Code: 400

### InternalServerException

An unexpected server-side error occurred during request processing.

#### RetryAfterSeconds

The number of seconds to wait before retrying the operation.

HTTP Status Code: 500

### OperationTimeoutException

The operation timed out.

HTTP Status Code: 500

#### **ThrottlingException**

The request was denied because too many requests were made in a short period, exceeding the service rate limits. Amazon Managed Workflows for Apache Airflow Serverless implements throttling controls to ensure fair resource allocation across all customers in the multi-tenant environment. This helps maintain service stability and performance. If you encounter throttling,

Errors API Version 2024-07-26 46 implement exponential backoff and retry logic in your applications, or consider distributing your API calls over a longer time period.

### QuotaCode

The code of the quota.

### RetryAfterSeconds

The number of seconds to wait before retrying the operation.

#### ServiceCode

The code for the service.

HTTP Status Code: 400

### ValidationException

The specified request parameters are invalid, missing, or inconsistent with Amazon Managed Workflows for Apache Airflow Serverless service requirements. This can occur when workflow definitions contain unsupported operators, when required IAM permissions are missing, when S3 locations are inaccessible, or when network configurations are invalid. The service validates workflow definitions, execution roles, and resource configurations to ensure compatibility with the managed Airflow environment and security requirements.

#### **FieldList**

The fields that failed validation.

#### Reason

The reason the request failed validation.

HTTP Status Code: 400

# See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET
- AWS SDK for C++

- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# ListWorkflowRuns

Lists all runs for a specified workflow, with optional pagination and filtering support.

# **Request Syntax**

```
{
   "MaxResults": number,
   "NextToken": "string",
   "WorkflowArn": "string",
   "WorkflowVersion": "string"
}
```

# **Request Parameters**

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

### **MaxResults**

The maximum number of workflow runs to return in a single response.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

### **NextToken**

The pagination token you need to use to retrieve the next set of results. This value is returned from a previous call to ListWorkflowRuns.

Type: String

Required: No

## **WorkflowArn**

The Amazon Resource Name (ARN) of the workflow for which you want a list of runs.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

ListWorkflowRuns API Version 2024-07-26 49

```
Pattern: arn: aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?:airflow-serverless:([a-z]{2}-[a-z]+-[0-9]{1}):([0-9]{12}):workflow/([a-zA-Z0-9][a-zA-Z0-9\.\-_]{0,254}-[a-zA-Z0-9]{10})
```

Required: Yes

### WorkflowVersion

Optional. The specific version of the workflow for which you want a list of runs. If not specified, runs for all versions are returned.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: .+

Required: No

# **Response Syntax**

```
{
   "NextToken": "string",
   "WorkflowRuns": [
         "RunDetailSummary": {
            ""CreatedOn": "string",
            "EndedAt": "string",
            "StartedAt": "string",
            "Status": "string"
         },
         "RunId": "string",
         "RunType": "string",
         "WorkflowArn": "string",
         "WorkflowVersion": "string"
      }
   ]
}
```

# **Response Elements**

If the action is successful, the service sends back an HTTP 200 response.

Response Syntax API Version 2024-07-26 50

The following data is returned in JSON format by the service.

### NextToken

The pagination token you need to use to retrieve the next set of results. This value is null if there are no more results.

Type: String

## WorkflowRuns

A list of workflow run summaries for the specified workflow.

Type: Array of WorkflowRunSummary objects

### **Errors**

For information about the errors that are common to all actions, see Common Errors.

### AccessDeniedException

You do not have sufficient permission to perform this action.

HTTP Status Code: 400

### InternalServerException

An unexpected server-side error occurred during request processing.

### RetryAfterSeconds

The number of seconds to wait before retrying the operation.

HTTP Status Code: 500

### OperationTimeoutException

The operation timed out.

HTTP Status Code: 500

### **ThrottlingException**

The request was denied because too many requests were made in a short period, exceeding the service rate limits. Amazon Managed Workflows for Apache Airflow Serverless implements

Errors API Version 2024-07-26 51

throttling controls to ensure fair resource allocation across all customers in the multi-tenant environment. This helps maintain service stability and performance. If you encounter throttling, implement exponential backoff and retry logic in your applications, or consider distributing your API calls over a longer time period.

### QuotaCode

The code of the quota.

### RetryAfterSeconds

The number of seconds to wait before retrying the operation.

#### ServiceCode

The code for the service.

HTTP Status Code: 400

### **ValidationException**

The specified request parameters are invalid, missing, or inconsistent with Amazon Managed Workflows for Apache Airflow Serverless service requirements. This can occur when workflow definitions contain unsupported operators, when required IAM permissions are missing, when S3 locations are inaccessible, or when network configurations are invalid. The service validates workflow definitions, execution roles, and resource configurations to ensure compatibility with the managed Airflow environment and security requirements.

#### **FieldList**

The fields that failed validation.

#### Reason

The reason the request failed validation.

HTTP Status Code: 400

# See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

• AWS Command Line Interface V2

- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# ListWorkflows

Lists all workflows in your account, with optional pagination support. This operation returns summary information for workflows, showing only the most recently created version of each workflow. Amazon Managed Workflows for Apache Airflow Serverless maintains workflow metadata in a highly available, distributed storage system that enables efficient querying and filtering. The service implements proper access controls to ensure you can only view workflows that you have permissions to access, supporting both individual and team-based workflow management scenarios.

# **Request Syntax**

```
{
    "MaxResults": number,
    "NextToken": "string"
}
```

# **Request Parameters**

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

#### **MaxResults**

The maximum number of workflows you want to return in a single response.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

### NextToken

The pagination token you need to use to retrieve the next set of results. This value is returned from a previous call to ListWorkflows.

Type: String

Required: No

ListWorkflows API Version 2024-07-26 54

# **Response Syntax**

# **Response Elements**

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **NextToken**

The pagination token you need to use to retrieve the next set of results. This value is null if there are no more results.

Type: String

### **Workflows**

A list of workflow summaries for all workflows in your account.

Type: Array of WorkflowSummary objects

### **Errors**

For information about the errors that are common to all actions, see Common Errors.

Response Syntax API Version 2024-07-26 55

### AccessDeniedException

You do not have sufficient permission to perform this action.

HTTP Status Code: 400

### InternalServerException

An unexpected server-side error occurred during request processing.

### RetryAfterSeconds

The number of seconds to wait before retrying the operation.

HTTP Status Code: 500

### OperationTimeoutException

The operation timed out.

HTTP Status Code: 500

### ThrottlingException

The request was denied because too many requests were made in a short period, exceeding the service rate limits. Amazon Managed Workflows for Apache Airflow Serverless implements throttling controls to ensure fair resource allocation across all customers in the multi-tenant environment. This helps maintain service stability and performance. If you encounter throttling, implement exponential backoff and retry logic in your applications, or consider distributing your API calls over a longer time period.

### QuotaCode

The code of the quota.

### RetryAfterSeconds

The number of seconds to wait before retrying the operation.

### ServiceCode

The code for the service.

HTTP Status Code: 400

# ValidationException

The specified request parameters are invalid, missing, or inconsistent with Amazon Managed Workflows for Apache Airflow Serverless service requirements. This can occur when workflow

Errors API Version 2024-07-26 56

definitions contain unsupported operators, when required IAM permissions are missing, when S3 locations are inaccessible, or when network configurations are invalid. The service validates workflow definitions, execution roles, and resource configurations to ensure compatibility with the managed Airflow environment and security requirements.

#### **FieldList**

The fields that failed validation.

#### Reason

The reason the request failed validation.

HTTP Status Code: 400

### See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# ListWorkflowVersions

Lists all versions of a specified workflow, with optional pagination support.

# **Request Syntax**

```
{
    "MaxResults": number,
    "NextToken": "string",
    "WorkflowArn": "string"
}
```

# **Request Parameters**

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

### **MaxResults**

The maximum number of workflow versions to return in a single response.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

### NextToken

The pagination token you need to use to retrieve the next set of results. This value is returned from a previous call to ListWorkflowVersions.

Type: String

Required: No

# WorkflowArn

The Amazon Resource Name (ARN) of the workflow for which you want to list versions.

Type: String

ListWorkflowVersions API Version 2024-07-26 58

Length Constraints: Minimum length of 1. Maximum length of 2048.

```
Pattern: arn:aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?:airflow-serverless:([a-z]{2}-[a-z]+-[0-9]{1}):([0-9]{12}):workflow/([a-zA-Z0-9][a-zA-Z0-9\.\-_]{0,254}-[a-zA-Z0-9]{10})

Required: Yes
```

# **Response Syntax**

```
{
   "NextToken": "string",
   "WorkflowVersions": [
      {
         "CreatedAt": "string",
         "DefinitionS3Location": {
            "Bucket": "string",
            "ObjectKey": "string",
            "VersionId": "string"
         },
         "IsLatestVersion": boolean,
         "ModifiedAt": "string",
         "ScheduleConfiguration": {
            "CronExpression": "string"
         },
         "TriggerMode": "string",
         "WorkflowArn": "string",
         "WorkflowVersion": "string"
      }
   ]
}
```

# **Response Elements**

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

#### NextToken

The pagination token you need to use to retrieve the next set of results. This value is null if there are no more results.

Response Syntax API Version 2024-07-26 59

Type: String

### WorkflowVersions

A list of workflow version summaries for the specified workflow.

Type: Array of WorkflowVersionSummary objects

#### **Errors**

For information about the errors that are common to all actions, see **Common Errors**.

### AccessDeniedException

You do not have sufficient permission to perform this action.

HTTP Status Code: 400

### InternalServerException

An unexpected server-side error occurred during request processing.

### RetryAfterSeconds

The number of seconds to wait before retrying the operation.

HTTP Status Code: 500

## OperationTimeoutException

The operation timed out.

HTTP Status Code: 500

### **ThrottlingException**

The request was denied because too many requests were made in a short period, exceeding the service rate limits. Amazon Managed Workflows for Apache Airflow Serverless implements throttling controls to ensure fair resource allocation across all customers in the multi-tenant environment. This helps maintain service stability and performance. If you encounter throttling, implement exponential backoff and retry logic in your applications, or consider distributing your API calls over a longer time period.

#### QuotaCode

The code of the quota.

Errors API Version 2024-07-26 60

#### RetryAfterSeconds

The number of seconds to wait before retrying the operation.

#### ServiceCode

The code for the service.

HTTP Status Code: 400

### ValidationException

The specified request parameters are invalid, missing, or inconsistent with Amazon Managed Workflows for Apache Airflow Serverless service requirements. This can occur when workflow definitions contain unsupported operators, when required IAM permissions are missing, when S3 locations are inaccessible, or when network configurations are invalid. The service validates workflow definitions, execution roles, and resource configurations to ensure compatibility with the managed Airflow environment and security requirements.

#### **FieldList**

The fields that failed validation.

#### Reason

The reason the request failed validation.

HTTP Status Code: 400

# See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin

- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# StartWorkflowRun

Starts a new execution of a workflow. This operation creates a workflow run that executes the tasks that are defined in the workflow. Amazon Managed Workflows for Apache Airflow Serverless schedules the workflow execution across its managed Airflow environment, automatically scaling ECS worker tasks based on the workload. The service handles task isolation, dependency resolution, and provides comprehensive monitoring and logging throughout the execution lifecycle.

# **Request Syntax**

```
{
    "ClientToken": "string",
    "OverrideParameters": {
        "string" : JSON value
    },
    "WorkflowArn": "string",
    "WorkflowVersion": "string"
}
```

# **Request Parameters**

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

### ClientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. This token prevents duplicate workflow run requests.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern:  $[\x21-\x7E]+$ 

Required: No

#### **OverrideParameters**

Optional parameters to override default workflow parameters for this specific run. These parameters are passed to the workflow during execution and can be used to customize behavior

StartWorkflowRun API Version 2024-07-26 63

without modifying the workflow definition. Parameters are made available as environment variables to tasks and you can reference them within the YAML workflow definition using standard parameter substitution syntax.

Type: String to JSON value map

Required: No

#### WorkflowArn

The Amazon Resource Name (ARN) of the workflow you want to run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

```
Pattern: arn: aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?: airflow-serverless:([a-z]{2}-[a-z]+-[0-9]{1}):([0-9]{12}):workflow/([a-zA-Z0-9][a-zA-Z0-9].\-_]\{0,254\}-[a-zA-Z0-9]\{10\})
```

Required: Yes

### WorkflowVersion

Optional. The specific version of the workflow to execute. If not specified, the latest version is used.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: .+

Required: No

# **Response Syntax**

```
{
    "RunId": "string",
    "StartedAt": "string",
    "Status": "string"
}
```

Response Syntax API Version 2024-07-26 64

# **Response Elements**

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### RunId

The unique identifier of the newly started workflow run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9]+[a-zA-Z0-9\.\-\_]\*

## **StartedAt**

The timestamp when the workflow run was started, in ISO 8601 date-time format.

Type: Timestamp

### **Status**

The initial status of the workflow run. This is typically STARTING when you first create the run.

Type: String

Valid Values: STARTING | QUEUED | RUNNING | SUCCESS | FAILED | TIMEOUT |

STOPPING | STOPPED

## **Errors**

For information about the errors that are common to all actions, see **Common Errors**.

# AccessDeniedException

You do not have sufficient permission to perform this action.

HTTP Status Code: 400

# ConflictException

You cannot create a resource that already exists, or the resource is in a state that prevents the requested operation.

Response Elements API Version 2024-07-26 65

#### Resourceld

The unique identifier of the resource.

#### ResourceType

The type of the resource.

HTTP Status Code: 400

### InternalServerException

An unexpected server-side error occurred during request processing.

### RetryAfterSeconds

The number of seconds to wait before retrying the operation.

HTTP Status Code: 500

### OperationTimeoutException

The operation timed out.

HTTP Status Code: 500

#### ResourceNotFoundException

The specified resource was not found. You can only access or modify a resource that already exists.

#### Resourceld

The unique identifier of the resource.

#### ResourceType

The type of the resource.

HTTP Status Code: 400

#### ServiceQuotaExceededException

The request exceeds the service quota for Amazon Managed Workflows for Apache Airflow Serverless resources. This can occur when you attempt to create more workflows than allowed, exceed concurrent workflow run limits, or surpass task execution limits. Amazon Managed Workflows for Apache Airflow Serverless implements admission control using DynamoDB-based

counters to manage resource utilization across the multi-tenant environment. Contact AWS Support to request quota increases if you need higher limits for your use case.

#### QuotaCode

The code of the quota.

#### Resourceld

The unique identifier of the resource.

### ResourceType

The type of resource affected.

#### ServiceCode

The code for the service.

HTTP Status Code: 400

#### **ThrottlingException**

The request was denied because too many requests were made in a short period, exceeding the service rate limits. Amazon Managed Workflows for Apache Airflow Serverless implements throttling controls to ensure fair resource allocation across all customers in the multi-tenant environment. This helps maintain service stability and performance. If you encounter throttling, implement exponential backoff and retry logic in your applications, or consider distributing your API calls over a longer time period.

#### QuotaCode

The code of the quota.

### RetryAfterSeconds

The number of seconds to wait before retrying the operation.

### ServiceCode

The code for the service.

HTTP Status Code: 400

#### ValidationException

The specified request parameters are invalid, missing, or inconsistent with Amazon Managed Workflows for Apache Airflow Serverless service requirements. This can occur when workflow

definitions contain unsupported operators, when required IAM permissions are missing, when S3 locations are inaccessible, or when network configurations are invalid. The service validates workflow definitions, execution roles, and resource configurations to ensure compatibility with the managed Airflow environment and security requirements.

#### **FieldList**

The fields that failed validation.

#### Reason

The reason the request failed validation.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# StopWorkflowRun

Stops a running workflow execution. This operation terminates all running tasks and prevents new tasks from starting. Amazon Managed Workflows for Apache Airflow Serverless gracefully shuts down the workflow execution by stopping task scheduling and terminating active ECS worker containers. The operation transitions the workflow run to a STOPPING state and then to STOPPED once all cleanup is complete. In-flight tasks may complete or be terminated depending on their current execution state.

# **Request Syntax**

```
{
    "RunId": "string",
    "WorkflowArn": "string"
}
```

# **Request Parameters**

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

### RunId

The unique identifier of the workflow run to stop.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9]+[a-zA-Z0-9\.\-\_]\*

Required: Yes

### WorkflowArn

The Amazon Resource Name (ARN) of the workflow that contains the run you want to stop.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

StopWorkflowRun API Version 2024-07-26 69

```
Pattern: arn:aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?:airflow-serverless:([a-z]{2}-[a-z]+-[0-9]{1}):([0-9]{12}):workflow/([a-zA-Z0-9][a-zA-Z0-9\.\-_]{0,254}-[a-zA-Z0-9]{10})
```

Required: Yes

# **Response Syntax**

```
{
    "RunId": "string",
    "Status": "string",
    "WorkflowArn": "string",
    "WorkflowVersion": "string"
}
```

# **Response Elements**

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## RunId

The unique identifier of the stopped workflow run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9]+[a-zA-Z0-9\.\-\_]\*

## **Status**

The status of the workflow run after the stop operation. This is typically STOPPING or STOPPED.

Type: String

Valid Values: STARTING | QUEUED | RUNNING | SUCCESS | FAILED | TIMEOUT | STOPPING | STOPPED

### **WorkflowArn**

The Amazon Resource Name (ARN) of the workflow that contains the stopped run.

Response Syntax API Version 2024-07-26 70

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

```
Pattern: arn: aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?:airflow-serverless:([a-z]{2}-[a-z]+-[0-9]{1}):([0-9]{12}):workflow/([a-zA-Z0-9][a-zA-Z0-9].\-]{0,254}-[a-zA-Z0-9]{10})
```

#### WorkflowVersion

The version of the workflow that was stopped.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: .+

### **Errors**

For information about the errors that are common to all actions, see Common Errors.

# AccessDeniedException

You do not have sufficient permission to perform this action.

HTTP Status Code: 400

### InternalServerException

An unexpected server-side error occurred during request processing.

#### RetryAfterSeconds

The number of seconds to wait before retrying the operation.

HTTP Status Code: 500

# OperationTimeoutException

The operation timed out.

HTTP Status Code: 500

#### ResourceNotFoundException

The specified resource was not found. You can only access or modify a resource that already exists.

#### Resourceld

The unique identifier of the resource.

### ResourceType

The type of the resource.

HTTP Status Code: 400

### **ThrottlingException**

The request was denied because too many requests were made in a short period, exceeding the service rate limits. Amazon Managed Workflows for Apache Airflow Serverless implements throttling controls to ensure fair resource allocation across all customers in the multi-tenant environment. This helps maintain service stability and performance. If you encounter throttling, implement exponential backoff and retry logic in your applications, or consider distributing your API calls over a longer time period.

#### QuotaCode

The code of the quota.

### RetryAfterSeconds

The number of seconds to wait before retrying the operation.

#### ServiceCode

The code for the service.

HTTP Status Code: 400

#### ValidationException

The specified request parameters are invalid, missing, or inconsistent with Amazon Managed Workflows for Apache Airflow Serverless service requirements. This can occur when workflow definitions contain unsupported operators, when required IAM permissions are missing, when S3 locations are inaccessible, or when network configurations are invalid. The service validates workflow definitions, execution roles, and resource configurations to ensure compatibility with the managed Airflow environment and security requirements.

#### **FieldList**

The fields that failed validation.

#### Reason

The reason the request failed validation.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- · AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **TagResource**

Adds tags to an Amazon Managed Workflows for Apache Airflow Serverless resource. Tags are key-value pairs that help you organize and categorize your resources.

# **Request Syntax**

```
{
    "ResourceArn": "string",
    "Tags": {
        "string" : "string"
    }
}
```

# **Request Parameters**

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

### ResourceArn

The Amazon Resource Name (ARN) of the resource to which to add tags.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

```
Pattern: arn: aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?:airflow-serverless:([a-z]{2}-[a-z]+-[0-9]{1}):([0-9]{12}):workflow/([a-zA-Z0-9][a-zA-Z0-9\.\-_]{0,254}-[a-zA-Z0-9]{10})
```

Required: Yes

# <u>Tags</u>

A map of tags to add to the resource. Each tag consists of a key-value pair.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

TagResource API Version 2024-07-26 74

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: . \*

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: .\*

Required: Yes

# **Response Elements**

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

#### **Errors**

For information about the errors that are common to all actions, see Common Errors.

### AccessDeniedException

You do not have sufficient permission to perform this action.

HTTP Status Code: 400

#### InternalServerException

An unexpected server-side error occurred during request processing.

### RetryAfterSeconds

The number of seconds to wait before retrying the operation.

HTTP Status Code: 500

### OperationTimeoutException

The operation timed out.

HTTP Status Code: 500

#### ResourceNotFoundException

The specified resource was not found. You can only access or modify a resource that already exists.

Response Elements API Version 2024-07-26 75

#### Resourceld

The unique identifier of the resource.

#### ResourceType

The type of the resource.

HTTP Status Code: 400

#### **ThrottlingException**

The request was denied because too many requests were made in a short period, exceeding the service rate limits. Amazon Managed Workflows for Apache Airflow Serverless implements throttling controls to ensure fair resource allocation across all customers in the multi-tenant environment. This helps maintain service stability and performance. If you encounter throttling, implement exponential backoff and retry logic in your applications, or consider distributing your API calls over a longer time period.

#### QuotaCode

The code of the quota.

### RetryAfterSeconds

The number of seconds to wait before retrying the operation.

#### ServiceCode

The code for the service.

HTTP Status Code: 400

#### ValidationException

The specified request parameters are invalid, missing, or inconsistent with Amazon Managed Workflows for Apache Airflow Serverless service requirements. This can occur when workflow definitions contain unsupported operators, when required IAM permissions are missing, when S3 locations are inaccessible, or when network configurations are invalid. The service validates workflow definitions, execution roles, and resource configurations to ensure compatibility with the managed Airflow environment and security requirements.

#### **FieldList**

The fields that failed validation.

#### Reason

The reason the request failed validation.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **UntagResource**

Removes tags from an Amazon Managed Workflows for Apache Airflow Serverless resource. This operation removes the specified tags from the resource.

# **Request Syntax**

```
{
    "ResourceArn": "string",
    "TagKeys": [ "string" ]
}
```

# **Request Parameters**

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

### ResourceArn

The Amazon Resource Name (ARN) of the resource from which to remove tags.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

```
Pattern: arn: aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?: airflow-serverless:([a-z]{2}-[a-z]+-[0-9]{1}):([0-9]{12}):workflow/([a-zA-Z0-9][a-zA-Z0-9].\-_]\{0,254\}-[a-zA-Z0-9]\{10\})
```

Required: Yes

# **TagKeys**

A list of tag keys to remove from the resource. Only the keys are required; the values are ignored.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

UntagResource API Version 2024-07-26 78

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: .\*

Required: Yes

# **Response Elements**

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

#### **Errors**

For information about the errors that are common to all actions, see Common Errors.

### AccessDeniedException

You do not have sufficient permission to perform this action.

HTTP Status Code: 400

### InternalServerException

An unexpected server-side error occurred during request processing.

## RetryAfterSeconds

The number of seconds to wait before retrying the operation.

HTTP Status Code: 500

### OperationTimeoutException

The operation timed out.

HTTP Status Code: 500

### ResourceNotFoundException

The specified resource was not found. You can only access or modify a resource that already exists.

#### Resourceld

The unique identifier of the resource.

Response Elements API Version 2024-07-26 79

### ResourceType

The type of the resource.

HTTP Status Code: 400

### **ThrottlingException**

The request was denied because too many requests were made in a short period, exceeding the service rate limits. Amazon Managed Workflows for Apache Airflow Serverless implements throttling controls to ensure fair resource allocation across all customers in the multi-tenant environment. This helps maintain service stability and performance. If you encounter throttling, implement exponential backoff and retry logic in your applications, or consider distributing your API calls over a longer time period.

#### QuotaCode

The code of the quota.

### RetryAfterSeconds

The number of seconds to wait before retrying the operation.

### ServiceCode

The code for the service.

HTTP Status Code: 400

### **ValidationException**

The specified request parameters are invalid, missing, or inconsistent with Amazon Managed Workflows for Apache Airflow Serverless service requirements. This can occur when workflow definitions contain unsupported operators, when required IAM permissions are missing, when S3 locations are inaccessible, or when network configurations are invalid. The service validates workflow definitions, execution roles, and resource configurations to ensure compatibility with the managed Airflow environment and security requirements.

#### **FieldList**

The fields that failed validation.

#### Reason

The reason the request failed validation.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **UpdateWorkflow**

Updates an existing workflow with new configuration settings. This operation allows you to modify the workflow definition, role, and other settings. When you update a workflow, Amazon Managed Workflows for Apache Airflow Serverless automatically creates a new version with the updated configuration and disables scheduling on all previous versions to ensure only one version is actively scheduled at a time. The update operation maintains workflow history while providing a clean transition to the new configuration.

# **Request Syntax**

```
{
   "DefinitionS3Location": {
      "Bucket": "string",
      "ObjectKey": "string",
      "VersionId": "string"
   },
   "Description": "string",
   "EngineVersion": number,
   "LoggingConfiguration": {
      "LogGroupName": "string"
   },
   "NetworkConfiguration": {
      "SecurityGroupIds": [ "string" ],
      "SubnetIds": [ "string" ]
   },
   "RoleArn": "string",
   "TriggerMode": "string",
   "WorkflowArn": "string"
}
```

# **Request Parameters**

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

### **DefinitionS3Location**

The Amazon S3 location where the updated workflow definition file is stored.

Type: DefinitionS3Location object

UpdateWorkflow API Version 2024-07-26 82

#### Required: Yes

### **Description**

An updated description for the workflow.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .+

Required: No

## **EngineVersion**

The version of the Amazon Managed Workflows for Apache Airflow Serverless engine that you want to use for the updated workflow.

Type: Integer

Required: No

### **LoggingConfiguration**

Updated logging configuration for the workflow.

Type: <u>LoggingConfiguration</u> object

Required: No

# NetworkConfiguration

Updated network configuration for the workflow execution environment.

Type: NetworkConfiguration object

Required: No

### RoleArn

The Amazon Resource Name (ARN) of the IAM role that Amazon Managed Workflows for Apache Airflow Serverless assumes when it executes the updated workflow.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Request Parameters API Version 2024-07-26 83

```
Pattern: arn: aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?:iam::[0-9] \{12\}:role(/[a-zA-Z0-9+=,.@_\-]\{1,512\})*?/[a-zA-Z0-9+=,.@_\-]\{1,64\}
```

Required: Yes

### **TriggerMode**

The trigger mode for the workflow execution.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: .\*

Required: No

## WorkflowArn

The Amazon Resource Name (ARN) of the workflow you want to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

```
Pattern: arn: aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?:airflow-serverless:([a-z]{2}-[a-z]+-[0-9]{1}):([0-9]{12}):workflow/([a-zA-Z0-9][a-zA-Z0-9].\-_]\{0,254\}-[a-zA-Z0-9]\{10\})
```

Required: Yes

# **Response Syntax**

```
{
    "ModifiedAt": "string",
    "Warnings": [ "string" ],
    "WorkflowArn": "string",
    "WorkflowVersion": "string"
}
```

# **Response Elements**

If the action is successful, the service sends back an HTTP 200 response.

Response Syntax API Version 2024-07-26 84

The following data is returned in JSON format by the service.

### **ModifiedAt**

The timestamp when the workflow was last modified, in ISO 8601 date-time format.

Type: Timestamp

### **Warnings**

Warning messages generated during workflow update.

Type: Array of strings

### WorkflowArn

The Amazon Resource Name (ARN) of the updated workflow.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

```
Pattern: arn: aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?: airflow-serverless:([a-z]{2}-[a-z]+-[0-9]{1}):([0-9]{12}):workflow/([a-zA-Z0-9][a-zA-Z0-9].\-_]\{0,254\}-[a-zA-Z0-9]{10})
```

### WorkflowVersion

The version identifier of the updated workflow.

Type: String

Length Constraints: Fixed length of 32.

Pattern: [a-z0-9]{32}

# **Errors**

For information about the errors that are common to all actions, see Common Errors.

## AccessDeniedException

You do not have sufficient permission to perform this action.

HTTP Status Code: 400

### ConflictException

You cannot create a resource that already exists, or the resource is in a state that prevents the requested operation.

#### Resourceld

The unique identifier of the resource.

### ResourceType

The type of the resource.

HTTP Status Code: 400

### InternalServerException

An unexpected server-side error occurred during request processing.

### RetryAfterSeconds

The number of seconds to wait before retrying the operation.

HTTP Status Code: 500

### OperationTimeoutException

The operation timed out.

HTTP Status Code: 500

#### ResourceNotFoundException

The specified resource was not found. You can only access or modify a resource that already exists.

#### Resourceld

The unique identifier of the resource.

#### ResourceType

The type of the resource.

HTTP Status Code: 400

#### ServiceQuotaExceededException

The request exceeds the service quota for Amazon Managed Workflows for Apache Airflow Serverless resources. This can occur when you attempt to create more workflows than allowed, exceed concurrent workflow run limits, or surpass task execution limits. Amazon Managed Workflows for Apache Airflow Serverless implements admission control using DynamoDB-based counters to manage resource utilization across the multi-tenant environment. Contact AWS Support to request quota increases if you need higher limits for your use case.

#### QuotaCode

The code of the quota.

#### Resourceld

The unique identifier of the resource.

#### ResourceType

The type of resource affected.

#### ServiceCode

The code for the service.

HTTP Status Code: 400

### **ThrottlingException**

The request was denied because too many requests were made in a short period, exceeding the service rate limits. Amazon Managed Workflows for Apache Airflow Serverless implements throttling controls to ensure fair resource allocation across all customers in the multi-tenant environment. This helps maintain service stability and performance. If you encounter throttling, implement exponential backoff and retry logic in your applications, or consider distributing your API calls over a longer time period.

#### QuotaCode

The code of the quota.

#### RetryAfterSeconds

The number of seconds to wait before retrying the operation.

#### ServiceCode

The code for the service.

HTTP Status Code: 400

### ValidationException

The specified request parameters are invalid, missing, or inconsistent with Amazon Managed Workflows for Apache Airflow Serverless service requirements. This can occur when workflow definitions contain unsupported operators, when required IAM permissions are missing, when S3 locations are inaccessible, or when network configurations are invalid. The service validates workflow definitions, execution roles, and resource configurations to ensure compatibility with the managed Airflow environment and security requirements.

#### **FieldList**

The fields that failed validation.

#### Reason

The reason the request failed validation.

HTTP Status Code: 400

### See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface V2
- · AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Data Types**

The AmazonMWAAServerless API contains several data types that various actions use. This section describes each data type in detail.



### Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

#### The following data types are supported:

- DefinitionS3Location
- EncryptionConfiguration
- LoggingConfiguration
- NetworkConfiguration
- RunDetailSummary
- ScheduleConfiguration
- TaskInstanceSummary
- ValidationExceptionField
- WorkflowRunDetail
- WorkflowRunSummary
- WorkflowSummary
- WorkflowVersionSummary

# **DefinitionS3Location**

Specifies the Amazon S3 location of a workflow definition file. This structure contains the bucket name, object key, and optional version ID for the workflow definition. Amazon Managed Workflows for Apache Airflow Serverless takes a snapshot of the definition file at the time of workflow creation or update, ensuring that the workflow behavior remains consistent even if the source file is modified. The definition must be a valid YAML file that uses supported AWS operators and Amazon Managed Workflows for Apache Airflow Serverless syntax.

### **Contents**

#### **Bucket**

The name of the Amazon S3 bucket that contains the workflow definition file.

Type: String

Required: Yes

### **ObjectKey**

The key (name) of the workflow definition file within the S3 bucket.

Type: String

Required: Yes

#### VersionId

Optional. The version ID of the workflow definition file in Amazon S3. If not specified, the latest version is used.

Type: String

Required: No

# See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

• AWS SDK for C++

DefinitionS3Location API Version 2024-07-26 90

- AWS SDK for Java V2
- AWS SDK for Ruby V3

# **EncryptionConfiguration**

Configuration for encrypting workflow data at rest and in transit. Amazon Managed Workflows for Apache Airflow Serverless provides comprehensive encryption capabilities to protect sensitive workflow data, parameters, and execution logs. When using customer-managed keys, the service integrates with AWS AWS KMS to provide fine-grained access control and audit capabilities. Encryption is applied consistently across the distributed execution environment including task containers, metadata storage, and log streams.

### **Contents**

### Type

The type of encryption to use. Values are AWS\_MANAGED\_KEY (AWS manages the encryption key) or CUSTOMER\_MANAGED\_KEY (you provide a KMS key).

Type: String

Valid Values: AWS\_MANAGED\_KEY | CUSTOMER\_MANAGED\_KEY

Required: Yes

### KmsKeyId

The ID or ARN of the AWS KMS key to use for encryption. Required when Type is CUSTOMER\_MANAGED\_KEY.

Type: String

Required: No

# See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

EncryptionConfiguration API Version 2024-07-26 92

# LoggingConfiguration

Configuration for workflow logging that specifies where you should store your workflow execution logs. Amazon Managed Workflows for Apache Airflow Serverless provides comprehensive logging capabilities that capture workflow execution details, task-level information, and system events. Logs are automatically exported to your specified CloudWatch log group using remote logging functionality, providing centralized observability across the distributed, multi-tenant execution environment. This enables effective debugging, monitoring, and compliance auditing of workflow executions.

### **Contents**

### LogGroupName

The name of the CloudWatch log group where workflow execution logs are stored.

Type: String

Required: Yes

### See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

LoggingConfiguration API Version 2024-07-26 93

# NetworkConfiguration

Network configuration for workflow execution. Specifies VPC security groups and subnets for secure network access. When provided, Amazon Managed Workflows for Apache Airflow Serverless deploys ECS worker tasks in your specified VPC configuration, enabling secure access to VPC-only resources. The service uses a proxy API container architecture where one container handles external communication while the worker container connects to your VPC for task execution. This design provides both security isolation and connectivity flexibility.

### **Contents**

### SecurityGroupIds

A list of VPC security group IDs to associate with the workflow execution environment.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: sg-[a-z0-9]\*

Required: No

#### **SubnetIds**

A list of VPC subnet IDs where the workflow execution environment is deployed.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: subnet - [a-z0-9]\*

Required: No

# See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

AWS SDK for C++

NetworkConfiguration API Version 2024-07-26 94

- AWS SDK for Java V2
- AWS SDK for Ruby V3

# RunDetailSummary

Summary information about a workflow run's execution details, including status and timing information.

## **Contents**

#### CreatedOn

The timestamp when the workflow run was created, in ISO 8601 date-time format.

Type: Timestamp

Required: No

#### **EndedAt**

The timestamp when the workflow run completed execution, in ISO 8601 date-time format. This value is null if the run is not complete.

Type: Timestamp

Required: No

#### **StartedAt**

The timestamp when the workflow run started execution, in ISO 8601 date-time format.

Type: Timestamp

Required: No

#### **Status**

The current status of the workflow run.

Type: String

Valid Values: STARTING | QUEUED | RUNNING | SUCCESS | FAILED | TIMEOUT |

STOPPING | STOPPED

Required: No

RunDetailSummary API Version 2024-07-26 96

# See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

# **ScheduleConfiguration**

The configuration to use to schedule automated workflow execution using cron expressions. Amazon Managed Workflows for Apache Airflow Serverless integrates with EventBridge Scheduler to provide cost-effective, timezone-aware scheduling capabilities. The service supports both time-based and event-based scheduling (event-based scheduling available post-GA). When a workflow definition includes scheduling information, Amazon Managed Workflows for Apache Airflow Serverless automatically configures the appropriate triggers and ensures only one version of a workflow has an active schedule at any time.

### **Contents**

### CronExpression

A cron expression that defines when the workflow is automatically executed. Uses standard cron syntax.

Type: String

Required: No

# See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ScheduleConfiguration API Version 2024-07-26 98

# **TaskInstanceSummary**

Summary information about a task instance within a workflow run, including its status and execution details.

### **Contents**

#### **DurationInSeconds**

The duration of the task instance execution in seconds. This value is null if the task is not complete.

Type: Integer

Required: No

### **OperatorName**

The name of the Apache Airflow operator used for this task instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: .\*

Required: No

#### RunId

The unique identifier of the workflow run that contains this task instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9]+[a-zA-Z0-9\.\-\_]\*

Required: No

#### **Status**

The current status of the task instance.

TaskInstanceSummary API Version 2024-07-26 99

Type: String

Valid Values: QUEUED | FAILED | SCHEDULED | RUNNING | SUCCESS | UP\_FOR\_RESCHEDULE | UP\_FOR\_RETRY | UPSTREAM\_FAILED | REMOVED | RESTARTING | DEFERRED | NONE | CANCELLED | TIMEOUT

Required: No

#### **TaskInstanceId**

The unique identifier of this task instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9]+[a-zA-Z0-9\.\-\_]\*

Required: No

#### WorkflowArn

The Amazon Resource Name (ARN) of the workflow that contains this task instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: arn: aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?: airflow-serverless:( $[a-z]{2}-[a-z]+-[0-9]{1}$ ):( $[0-9]{12}$ ):workflow/([a-zA-Z0-9][a-zA-Z0-9].\-\_] $\{0,254\}-[a-zA-Z0-9]\{10\}$ )

Required: No

#### WorkflowVersion

The version of the workflow that contains this task instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: .+

Required: No

Contents API Version 2024-07-26 100

# **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

# ValidationExceptionField

Contains information about a field that failed validation, including the field name and a descriptive error message.

# **Contents**

# Message

A message that describes why the field failed validation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: .\*

Required: Yes

#### Name

The name of the field that failed validation.

Type: String

Required: Yes

# See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ValidationExceptionField API Version 2024-07-26 102

# WorkflowRunDetail

Detailed information about a workflow run execution, including timing, status, error information, and associated task instances. This structure provides comprehensive visibility into the workflow execution lifecycle within the Amazon Managed Workflows for Apache Airflow Serverless serverless environment. The service tracks execution across distributed ECS worker tasks and provides detailed timing information, error diagnostics, and task instance relationships to support effective monitoring and troubleshooting of complex workflow executions.

# **Contents**

# CompletedOn

The timestamp when the workflow run completed execution, in ISO 8601 date-time format. This value is null if the run is not complete.

Type: Timestamp

Required: No

### CreatedAt

The timestamp when the workflow run was created, in ISO 8601 date-time format.

Type: Timestamp

Required: No

#### Duration

The total duration of the workflow run execution in seconds. This value is null if the run is not complete.

Type: Integer

Required: No

## **ErrorMessage**

The error message if the workflow run failed. This value is null if the run completed successfully.

Type: String

WorkflowRunDetail API Version 2024-07-26 103

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: .\*

Required: No

### **ModifiedAt**

The timestamp when the workflow run was last modified, in ISO 8601 date-time format.

Type: Timestamp

Required: No

### RunId

The unique identifier of this workflow run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9]+[a-zA-Z0-9\.\-\_]\*

Required: No

### RunState

The current execution state of the workflow run.

Type: String

Valid Values: STARTING | QUEUED | RUNNING | SUCCESS | FAILED | TIMEOUT |

STOPPING | STOPPED

Required: No

# RunType

The type of workflow run.

Type: String

Valid Values: ON\_DEMAND | SCHEDULED

Required: No

Contents API Version 2024-07-26 104

### StartedOn

The timestamp when the workflow run started execution, in ISO 8601 date-time format.

Type: Timestamp

Required: No

### **TaskInstances**

A list of task instance IDs that are part of this workflow run.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9]+[a-zA-Z0-9\.\-\_]\*

Required: No

### WorkflowArn

The Amazon Resource Name (ARN) of the workflow that contains this run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: arn: aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?: airflow-serverless:( $[a-z]{2}-[a-z]+-[0-9]{1}$ ):( $[0-9]{12}$ ):workflow/([a-zA-Z0-9][a-zA-Z0-9].\-\_] $\{0,254\}-[a-zA-Z0-9]\{10\}$ )

Required: No

### WorkflowVersion

The version of the workflow used for this run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: .+

Required: No

Contents API Version 2024-07-26 105

# **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

# WorkflowRunSummary

Summary information about a workflow run, including basic identification and status information.

# **Contents**

# RunDetailSummary

Summary details about the workflow run execution.

Type: RunDetailSummary object

Required: No

#### RunId

The unique identifier of the workflow run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9]+[a-zA-Z0-9\.\-\_]\*

Required: No

# RunType

The type of workflow run.

Type: String

Valid Values: ON\_DEMAND | SCHEDULED

Required: No

# WorkflowArn

The Amazon Resource Name (ARN) of the workflow that contains this run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

WorkflowRunSummary API Version 2024-07-26 107

```
Pattern: arn: aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?: airflow-serverless:([a-z]{2}-[a-z]+-[0-9]{1}):([0-9]{12}):workflow/([a-zA-Z0-9][a-zA-Z0-9].\-_]\{0,254\}-[a-zA-Z0-9]\{10\})
```

Required: No

### WorkflowVersion

The version of the workflow used for this run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: .+

Required: No

# See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

# WorkflowSummary

Summary information about a workflow, including basic identification and metadata.

## Contents

## WorkflowArn

The Amazon Resource Name (ARN) of the workflow.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

```
Pattern: arn: aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?:airflow-serverless:([a-z]\{2\}-[a-z]+-[0-9]\{1\}):([0-9]\{12\}):workflow/([a-zA-Z0-9][a-zA-Z0-9].\-_]\{0,254\}-[a-zA-Z0-9]\{10\})
```

Required: Yes

### CreatedAt

The timestamp when the workflow was created, in ISO 8601 date-time format.

Type: Timestamp

Required: No

### Description

The description of the workflow.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .+

Required: No

## **ModifiedAt**

The timestamp when the workflow was last modified, in ISO 8601 date-time format.

Type: Timestamp

WorkflowSummary API Version 2024-07-26 109

## Required: No

### Name

The name of the workflow.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9]+[a-zA-Z0-9\.\-\_]\*

Required: No

# TriggerMode

The trigger mode for the workflow execution.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: .\*

Required: No

## WorkflowStatus

The current status of the workflow.

Type: String

Valid Values: READY | DELETING

Required: No

### WorkflowVersion

The version identifier of the workflow.

Type: String

Length Constraints: Fixed length of 32.

Pattern: [a-z0-9]{32}

Required: No

# **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

# WorkflowVersionSummary

Summary information about a workflow version, including identification and configuration details.

## Contents

### WorkflowArn

The Amazon Resource Name (ARN) of the workflow that contains this version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: arn: aws(?:-(?:cn|us-gov|iso|iso-b|iso-e|iso-f))?: airflow-serverless:( $[a-z]{2}-[a-z]+-[0-9]{1}$ ):( $[0-9]{12}$ ):workflow/([a-zA-Z0-9][a-zA-Z0-9].\-\_] $\{0,254\}-[a-zA-Z0-9]{10}$ )

Required: Yes

## **WorkflowVersion**

The version identifier of the workflow version.

Type: String

Length Constraints: Fixed length of 32.

Pattern:  $[a-z0-9]{32}$ 

Required: Yes

#### **CreatedAt**

The timestamp when the workflow version was created, in ISO 8601 date-time format.

Type: Timestamp

Required: No

## **DefinitionS3Location**

The Amazon S3 location of the workflow definition file for this version.

Type: DefinitionS3Location object

WorkflowVersionSummary API Version 2024-07-26 112

Required: No

### **IsLatestVersion**

Boolean flag that indicates whether this is the latest version of the workflow.

Type: Boolean

Required: No

## **ModifiedAt**

The timestamp when the workflow version was last modified, in ISO 8601 date-time format.

Type: Timestamp

Required: No

# ScheduleConfiguration

The schedule configuration for this workflow version.

Type: ScheduleConfiguration object

Required: No

# TriggerMode

The trigger mode for the workflow execution.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: .\*

Required: No

# See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2

# • AWS SDK for Ruby V3

# **Common Parameters**

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see <u>Signing AWS API requests</u> in the *IAM User Guide*.

## **Action**

The action to be performed.

Type: string

Required: Yes

### Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

# X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

### X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4\_request"). The value is expressed in the following format: access\_key/YYYYMMDD/region/service/aws4\_request.

For more information, see Create a signed AWS API request in the IAM User Guide.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

### X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see Elements of an AWS API request signature in the *IAM User Guide*.

Type: string

Required: Conditional

# X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see AWS services that work with IAM in the IAM User Guide.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

## X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

# X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see <u>Create a signed AWS API request</u> in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

# **Common Errors**

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

# AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

# **IncompleteSignature**

The request signature does not conform to AWS standards.

HTTP Status Code: 400

### **InternalFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### **InvalidAction**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

### InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

### **NotAuthorized**

You do not have permission to perform this action.

HTTP Status Code: 400

## OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

## RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

### ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

# **ThrottlingException**

The request was denied due to request throttling.

HTTP Status Code: 400

## ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400