



API Reference

Network Flow Monitor



API Version 2023-04-19

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Network Flow Monitor: API Reference

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
CreateMonitor	3
Request Syntax	3
URI Request Parameters	3
Request Body	3
Response Syntax	5
Response Elements	6
Errors	8
See Also	8
CreateScope	10
Request Syntax	10
URI Request Parameters	10
Request Body	10
Response Syntax	11
Response Elements	12
Errors	13
See Also	13
DeleteMonitor	15
Request Syntax	15
URI Request Parameters	15
Request Body	15
Response Syntax	15
Response Elements	15
Errors	15
See Also	16
DeleteScope	18
Request Syntax	18
URI Request Parameters	18
Request Body	18
Response Syntax	18
Response Elements	18
Errors	18
See Also	19

GetMonitor	21
Request Syntax	21
URI Request Parameters	21
Request Body	21
Response Syntax	21
Response Elements	22
Errors	24
See Also	24
GetQueryResultsMonitorTopContributors	26
Request Syntax	26
URI Request Parameters	26
Request Body	27
Response Syntax	27
Response Elements	28
Errors	29
See Also	30
GetQueryResultsWorkloadInsightsTopContributors	31
Request Syntax	31
URI Request Parameters	31
Request Body	32
Response Syntax	32
Response Elements	32
Errors	33
See Also	34
GetQueryResultsWorkloadInsightsTopContributorsData	35
Request Syntax	35
URI Request Parameters	35
Request Body	36
Response Syntax	36
Response Elements	36
Errors	37
See Also	38
GetQueryStatusMonitorTopContributors	39
Request Syntax	39
URI Request Parameters	39
Request Body	39

Response Syntax	40
Response Elements	40
Errors	40
See Also	41
GetQueryStatusWorkloadInsightsTopContributors	42
Request Syntax	42
URI Request Parameters	42
Request Body	42
Response Syntax	43
Response Elements	43
Errors	43
See Also	44
GetQueryStatusWorkloadInsightsTopContributorsData	45
Request Syntax	45
URI Request Parameters	45
Request Body	46
Response Syntax	46
Response Elements	46
Errors	46
See Also	47
GetScope	49
Request Syntax	49
URI Request Parameters	49
Request Body	49
Response Syntax	49
Response Elements	50
Errors	51
See Also	52
ListMonitors	53
Request Syntax	53
URI Request Parameters	53
Request Body	53
Response Syntax	54
Response Elements	54
Errors	54
See Also	55

ListScopes	56
Request Syntax	56
URI Request Parameters	56
Request Body	56
Response Syntax	56
Response Elements	57
Errors	57
See Also	58
ListTagsForResource	59
Request Syntax	59
URI Request Parameters	59
Request Body	59
Response Syntax	59
Response Elements	59
Errors	60
See Also	61
StartQueryMonitorTopContributors	62
Request Syntax	62
URI Request Parameters	62
Request Body	63
Response Syntax	64
Response Elements	64
Errors	65
See Also	65
StartQueryWorkloadInsightsTopContributors	67
Request Syntax	67
URI Request Parameters	67
Request Body	68
Response Syntax	69
Response Elements	69
Errors	70
See Also	70
StartQueryWorkloadInsightsTopContributorsData	72
Request Syntax	72
URI Request Parameters	72
Request Body	72

Response Syntax	74
Response Elements	74
Errors	74
See Also	75
StopQueryMonitorTopContributors	76
Request Syntax	76
URI Request Parameters	76
Request Body	76
Response Syntax	76
Response Elements	77
Errors	77
See Also	77
StopQueryWorkloadInsightsTopContributors	79
Request Syntax	79
URI Request Parameters	79
Request Body	79
Response Syntax	79
Response Elements	80
Errors	80
See Also	80
StopQueryWorkloadInsightsTopContributorsData	82
Request Syntax	82
URI Request Parameters	82
Request Body	82
Response Syntax	82
Response Elements	83
Errors	83
See Also	83
TagResource	85
Request Syntax	85
URI Request Parameters	85
Request Body	85
Response Syntax	86
Response Elements	86
Errors	86
See Also	87

UntagResource	88
Request Syntax	88
URI Request Parameters	88
Request Body	88
Response Syntax	88
Response Elements	89
Errors	89
See Also	90
UpdateMonitor	91
Request Syntax	91
URI Request Parameters	91
Request Body	92
Response Syntax	93
Response Elements	94
Errors	95
See Also	96
UpdateScope	97
Request Syntax	97
URI Request Parameters	97
Request Body	98
Response Syntax	98
Response Elements	98
Errors	99
See Also	100
Data Types	102
KubernetesMetadata	103
Contents	103
See Also	104
MonitorLocalResource	105
Contents	105
See Also	105
MonitorRemoteResource	106
Contents	106
See Also	106
MonitorSummary	107
Contents	107

See Also	108
MonitorTopContributorsRow	109
Contents	109
See Also	113
ScopeSummary	115
Contents	115
See Also	115
TargetId	117
Contents	117
See Also	117
TargetIdentifier	118
Contents	118
See Also	118
TargetResource	119
Contents	119
See Also	119
TraversedComponent	120
Contents	120
See Also	120
WorkloadInsightsTopContributorsDataPoint	122
Contents	122
See Also	122
WorkloadInsightsTopContributorsRow	123
Contents	123
See Also	124
Common Parameters	126
Common Errors	129

Welcome

Network Flow Monitor is a feature of Amazon CloudWatch Network Monitoring that provides visibility into the performance of network flows for your AWS workloads, between instances in subnets, as well as to and from AWS. Lightweight agents that you install on the instances capture performance metrics for your network flows, such as packet loss and latency, and send them to the Network Flow Monitor backend. Then, you can view and analyze metrics from the top contributors for each metric type, to help troubleshoot issues.

In addition, when you create a monitor, Network Flow Monitor provides a network health indicator (NHI) that informs you whether there were AWS network issues for one or more of the network flows tracked by a monitor, during a time period that you choose. By using this value, you can independently determine if the AWS network is impacting your workload during a specific time frame, to help you focus troubleshooting efforts.

To learn more about Network Flow Monitor, see the [Network Flow Monitor User Guide](#) in the Amazon CloudWatch User Guide.

This document was last published on July 8, 2025.

Actions

The following actions are supported:

- [CreateMonitor](#)
- [CreateScope](#)
- [DeleteMonitor](#)
- [DeleteScope](#)
- [GetMonitor](#)
- [GetQueryResultsMonitorTopContributors](#)
- [GetQueryResultsWorkloadInsightsTopContributors](#)
- [GetQueryResultsWorkloadInsightsTopContributorsData](#)
- [GetQueryStatusMonitorTopContributors](#)
- [GetQueryStatusWorkloadInsightsTopContributors](#)
- [GetQueryStatusWorkloadInsightsTopContributorsData](#)
- [GetScope](#)
- [ListMonitors](#)
- [ListScopes](#)
- [ListTagsForResource](#)
- [StartQueryMonitorTopContributors](#)
- [StartQueryWorkloadInsightsTopContributors](#)
- [StartQueryWorkloadInsightsTopContributorsData](#)
- [StopQueryMonitorTopContributors](#)
- [StopQueryWorkloadInsightsTopContributors](#)
- [StopQueryWorkloadInsightsTopContributorsData](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateMonitor](#)
- [UpdateScope](#)

CreateMonitor

Create a monitor for specific network flows between local and remote resources, so that you can monitor network performance for one or several of your workloads. For each monitor, Network Flow Monitor publishes detailed end-to-end performance metrics and a network health indicators (NHI) that informs you whether there were AWS network issues for one or more of the network flows tracked by a monitor, during a time period that you choose.

Request Syntax

```
POST /monitors HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "localResources": [
    {
      "identifier": "string",
      "type": "string"
    }
  ],
  "monitorName": "string",
  "remoteResources": [
    {
      "identifier": "string",
      "type": "string"
    }
  ],
  "scopeArn": "string",
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[clientToken](#)

A unique, case-sensitive string of up to 64 ASCII characters that you specify to make an idempotent API request. Don't reuse the same client token for other API requests.

Type: String

Length Constraints: Fixed length of 36.

Pattern: [a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}

Required: No

[localResources](#)

The local resources to monitor. A local resource, in a bi-directional flow of a workload, is the host where the agent is installed. For example, if a workload consists of an interaction between a web service and a backend database (for example, Amazon Relational Database Service (RDS)), the EC2 instance hosting the web service, which also runs the agent, is the local resource.

Type: Array of [MonitorLocalResource](#) objects

Array Members: Minimum number of 1 item.

Required: Yes

[monitorName](#)

The name of the monitor.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9_.-]+

Required: Yes

[remoteResources](#)

The remote resources to monitor. A remote resource is the other endpoint in the bi-directional flow of a workload, with a local resource. For example, Amazon Relational Database Service (RDS) can be a remote resource.

Type: Array of [MonitorRemoteResource](#) objects

Required: No

[scopeArn](#)

The Amazon Resource Name (ARN) of the scope for the monitor.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: arn:.*

Required: Yes

[tags](#)

The tags for a monitor. You can add a maximum of 200 tags.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "createdAtnumber,
  "localResourcesidentifierstring",
      "typestring"
    }
  \\\],
  "modifiedAtnumber,
  "monitorArnstring",
```

```
"monitorName": "string",  
"monitorStatus": "string",  
"remoteResources": [  
    {  
        "identifier": "string",  
        "type": "string"  
    }  
,  
    "tags": {  
        "string": "string"  
    }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

createdAt

The date and time when the monitor was created.

Type: Timestamp

localResources

The local resources to monitor. A local resource, in a bi-directional flow of a workload, is the host where the agent is installed.

Type: Array of [MonitorLocalResource](#) objects

modifiedAt

The last date and time that the monitor was modified.

Type: Timestamp

monitorArn

The Amazon Resource Name (ARN) of the monitor.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 512.

Pattern: arn:.*

monitorName

The name of the monitor.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9_.-]+

monitorStatus

The status of a monitor. The status can be one of the following

- PENDING: The monitor is in the process of being created.
- ACTIVE: The monitor is active.
- INACTIVE: The monitor is inactive.
- ERROR: Monitor creation failed due to an error.
- DELETING: The monitor is in the process of being deleted.

Type: String

Valid Values: PENDING | ACTIVE | INACTIVE | ERROR | DELETING

remoteResources

The remote resources to monitor. A remote resource is the other endpoint in the bi-directional flow of a workload, with a local resource. For example, Amazon Relational Database Service (RDS) can be a remote resource. The remote resource is identified by its ARN or an identifier.

Type: Array of [MonitorRemoteResource](#) objects

tags

The tags for a monitor.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 403

ConflictException

The requested resource is in use.

HTTP Status Code: 409

InternalServerException

An internal error occurred.

HTTP Status Code: 500

ServiceQuotaExceededException

The request exceeded a service quota.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

Invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateScope

Create a scope of resources that you want to be available for Network Flow Monitor to generate metrics for, when you have active agents on those resources sending metrics reports to the Network Flow Monitor backend. This call returns a scope ID to identify the scope.

When you create a scope, you enable permissions for Network Flow Monitor. The scope is set to the resources for the AWS that enables the feature.

Request Syntax

```
POST /scopes HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "tags": {
    "string" : "string"
  },
  "targets": [
    {
      "region": "string",
      "targetIdentifier": {
        "targetId": { ... },
        "targetType": "string"
      }
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive string of up to 64 ASCII characters that you specify to make an idempotent API request. Don't reuse the same client token for other API requests.

Type: String

Length Constraints: Fixed length of 36.

Pattern: [a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}

Required: No

tags

The tags for a scope. You can add a maximum of 200 tags.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

targets

The targets to define the scope to be monitored. Currently, a target is an AWS account.

Type: Array of [TargetResource](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "scopeArn": "string",
  "scopeId": "string",
  "status": "string",
  "tags": {
    "string" : "string"
  }
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

scopeArn

The Amazon Resource Name (ARN) of the scope.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: arn:.*

scopeId

The identifier for the scope that includes the resources you want to get metrics for. A scope ID is an internally-generated identifier that includes all the resources for a specific root account.

Type: String

status

The status for a call to create a scope. The status can be one of the following: SUCCEEDED, IN_PROGRESS, or FAILED.

Type: String

Valid Values: SUCCEEDED | IN_PROGRESS | FAILED

tags

The tags for a scope.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 403

ConflictException

The requested resource is in use.

HTTP Status Code: 409

InternalServerException

An internal error occurred.

HTTP Status Code: 500

ServiceQuotaExceededException

The request exceeded a service quota.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

Invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteMonitor

Deletes a monitor in Network Flow Monitor.

Request Syntax

```
DELETE /monitors/monitorName HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

monitorName

The name of the monitor to delete.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9_.-]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 403

InternalServerException

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The request specifies a resource that doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

Invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteScope

Deletes a scope that has been defined.

Request Syntax

```
DELETE /scopes/scopeId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

scopeId

The identifier for the scope that includes the resources you want to get data results for. A scope ID is an internally-generated identifier that includes all the resources for a specific root account.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 403

InternalServerException

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The request specifies a resource that doesn't exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request exceeded a service quota.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

Invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetMonitor

Gets information about a monitor in Network Flow Monitor based on a monitor name. The information returned includes the Amazon Resource Name (ARN), create time, modified time, resources included in the monitor, and status information.

Request Syntax

```
GET /monitors/monitorName HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

monitorName

The name of the monitor.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9_.-]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "createdAtlocalResourcesidentifiertype
```

```
],  
  "modifiedAt": number,  
  "monitorArn": "string",  
  "monitorName": "string",  
  "monitorStatus": "string",  
  "remoteResources": [  
    {  
      "identifier": "string",  
      "type": "string"  
    }  
  ],  
  "tags": {  
    "string": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

createdAt

The date and time when the monitor was created.

Type: Timestamp

localResources

The local resources for this monitor.

Type: Array of [MonitorLocalResource](#) objects

modifiedAt

The date and time when the monitor was last modified.

Type: Timestamp

monitorArn

The Amazon Resource Name (ARN) of the monitor.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 512.

Pattern: arn:.*

monitorName

The name of the monitor.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9_.-]+

monitorStatus

The status of a monitor. The status can be one of the following

- PENDING: The monitor is in the process of being created.
- ACTIVE: The monitor is active.
- INACTIVE: The monitor is inactive.
- ERROR: Monitor creation failed due to an error.
- DELETING: The monitor is in the process of being deleted.

Type: String

Valid Values: PENDING | ACTIVE | INACTIVE | ERROR | DELETING

remoteResources

The remote resources for this monitor.

Type: Array of [MonitorRemoteResource](#) objects

tags

The tags for a monitor.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 403

InternalServerError

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The request specifies a resource that doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

Invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetQueryResultsMonitorTopContributors

Return the data for a query with the Network Flow Monitor query interface. You specify the query that you want to return results for by providing a query ID and a monitor name. This query returns the top contributors for a specific monitor.

Create a query ID for this call by calling the corresponding API call to start the query, `StartQueryMonitorTopContributors`. Use the scope ID that was returned for your account by `CreateScope`.

Top contributors in Network Flow Monitor are network flows with the highest values for a specific metric type. Top contributors can be across all workload insights, for a given scope, or for a specific monitor. Use the applicable call for the top contributors that you want to be returned.

Request Syntax

```
GET /monitors/monitorName/topContributorsQueries/queryId/results?  
maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[maxResults](#)

The number of query results that you want to return with this call.

[monitorName](#)

The name of the monitor.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9_.-]+

Required: Yes

[nextToken](#)

The token for the next set of results. You receive this token from a previous call.

[queryId](#)

The identifier for the query. A query ID is an internally-generated identifier for a specific query returned from an API call to create a query.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextTokentopContributorsdestinationCategorydnatIpkubernetesMetadatalocalPodNamelocalPodNamespacelocalServiceNameremotePodNameremotePodNamespaceremoteServiceNamelocalAzlocalInstanceArnlocalInstanceIdlocalIplocalRegionlocalSubnetArnlocalSubnetIdlocalVpcArnlocalVpcIdremoteAzremoteInstanceArnremoteInstanceId
```

```
"remoteIp": "string",
"remoteRegion": "string",
"remoteSubnetArn": "string",
"remoteSubnetId": "string",
"remoteVpcArn": "string",
"remoteVpcId": "string",
"snatIp": "string",
"targetPort": number,
"traversedConstructs": [
  {
    "componentArn": "string",
    "componentId": "string",
    "componentType": "string",
    "serviceName": "string"
  }
],
"value": number
},
"unit": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

The token for the next set of results. You receive this token from a previous call.

Type: String

[topContributors](#)

The top contributor network flows overall for a specific metric type, for example, the number of retransmissions.

Type: Array of [MonitorTopContributorsRow](#) objects

[unit](#)

The units for a metric returned by the query.

Type: String

Valid Values: Seconds | Microseconds | Milliseconds | Bytes | Kilobytes | Megabytes | Gigabytes | Terabytes | Bits | Kilobits | Megabits | Gigabits | Terabits | Percent | Count | Bytes/Second | Kilobytes/Second | Megabytes/Second | Gigabytes/Second | Terabytes/Second | Bits/Second | Kilobits/Second | Megabits/Second | Gigabits/Second | Terabits/Second | Count/Second | None

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 403

InternalServerException

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The request specifies a resource that doesn't exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request exceeded a service quota.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

Invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetQueryResultsWorkloadInsightsTopContributors

Return the data for a query with the Network Flow Monitor query interface. You specify the query that you want to return results for by providing a query ID and a monitor name.

This query returns the top contributors for a scope for workload insights. Workload insights provide a high level view of network flow performance data collected by agents. To return the data for the top contributors, see [GetQueryResultsWorkloadInsightsTopContributorsData](#).

Create a query ID for this call by calling the corresponding API call to start the query, [StartQueryWorkloadInsightsTopContributors](#). Use the scope ID that was returned for your account by [CreateScope](#).

Top contributors in Network Flow Monitor are network flows with the highest values for a specific metric type. Top contributors can be across all workload insights, for a given scope, or for a specific monitor. Use the applicable call for the top contributors that you want to be returned.

Request Syntax

```
GET /workloadInsights/scopeId/topContributorsQueries/queryId/results?  
maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[maxResults](#)

The number of query results that you want to return with this call.

[nextToken](#)

The token for the next set of results. You receive this token from a previous call.

[queryId](#)

The identifier for the query. A query ID is an internally-generated identifier for a specific query returned from an API call to create a query.

Required: Yes

scopeld

The identifier for the scope that includes the resources you want to get data results for. A scope ID is an internally-generated identifier that includes all the resources for a specific root account.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "topContributors": [
    {
      "accountId": "string",
      "localAz": "string",
      "localRegion": "string",
      "localSubnetArn": "string",
      "localSubnetId": "string",
      "localVpcArn": "string",
      "localVpcId": "string",
      "remoteIdentifier": "string",
      "value": number
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The token for the next set of results. You receive this token from a previous call.

Type: String

topContributors

The top contributor network flows overall for a specific metric type, for example, the number of retransmissions.

Type: Array of [WorkloadInsightsTopContributorsRow](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 403

InternalServerError

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The request specifies a resource that doesn't exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request exceeded a service quota.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

Invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetQueryResultsWorkloadInsightsTopContributorsData

Return the data for a query with the Network Flow Monitor query interface. Specify the query that you want to return results for by providing a query ID and a scope ID.

This query returns the data for top contributors for workload insights for a specific scope. Workload insights provide a high level view of network flow performance data collected by agents for a scope. To return just the top contributors, see [GetQueryResultsWorkloadInsightsTopContributors](#).

Create a query ID for this call by calling the corresponding API call to start the query, [StartQueryWorkloadInsightsTopContributorsData](#). Use the scope ID that was returned for your account by [CreateScope](#).

Top contributors in Network Flow Monitor are network flows with the highest values for a specific metric type. Top contributors can be across all workload insights, for a given scope, or for a specific monitor. Use the applicable call for the top contributors that you want to be returned.

The top contributor network flows overall are for a specific metric type, for example, the number of retransmissions.

Request Syntax

```
GET /workloadInsights/scopeId/topContributorsDataQueries/queryId/results?  
maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[maxResults](#)

The number of query results that you want to return with this call.

[nextToken](#)

The token for the next set of results. You receive this token from a previous call.

[queryId](#)

The identifier for the query. A query ID is an internally-generated identifier for a specific query returned from an API call to create a query.

Required: Yes

scopeld

The identifier for the scope that includes the resources you want to get data results for. A scope ID is an internally-generated identifier that includes all the resources for a specific root account.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "datapoints": [
    {
      "label": "string",
      "timestamps": [ "string" ],
      "values": [ number ]
    }
  ],
  "nextToken": "string",
  "unit": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

datapoints

The datapoints returned by the query.

Type: Array of [WorkloadInsightsTopContributorsDataPoint](#) objects

nextToken

The token for the next set of results. You receive this token from a previous call.

Type: String

unit

The units for a metric returned by the query.

Type: String

Valid Values: Seconds | Microseconds | Milliseconds | Bytes | Kilobytes | Megabytes | Gigabytes | Terabytes | Bits | Kilobits | Megabits | Gigabits | Terabits | Percent | Count | Bytes/Second | Kilobytes/Second | Megabytes/Second | Gigabytes/Second | Terabytes/Second | Bits/Second | Kilobits/Second | Megabits/Second | Gigabits/Second | Terabits/Second | Count/Second | None

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 403

InternalServerError

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The request specifies a resource that doesn't exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request exceeded a service quota.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

Invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetQueryStatusMonitorTopContributors

Returns the current status of a query for the Network Flow Monitor query interface, for a specified query ID and monitor. This call returns the query status for the top contributors for a monitor.

When you create a query, use this call to check the status of the query to make sure that it has SUCCEEDED before you review the results. Use the same query ID that you used for the corresponding API call to start (create) the query, StartQueryMonitorTopContributors.

When you run a query, use this call to check the status of the query to make sure that the query has SUCCEEDED before you review the results.

Request Syntax

```
GET /monitors/monitorName/topContributorsQueries/queryId/status HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

monitorName

The name of the monitor.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9_.-]+

Required: Yes

queryId

The identifier for the query. A query ID is an internally-generated identifier for a specific query returned from an API call to start a query.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
    "status
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

status

When you run a query, use this call to check the status of the query to make sure that the query has SUCCEEDED before you review the results.

- QUEUED: The query is scheduled to run.
- RUNNING: The query is in progress but not complete.
- SUCCEEDED: The query completed successfully.
- FAILED: The query failed due to an error.
- CANCELED: The query was canceled.

Type: String

Valid Values: QUEUED | RUNNING | SUCCEEDED | FAILED | CANCELED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 403

InternalServerException

An internal error occurred.

HTTP Status Code: 500

ServiceQuotaExceededException

The request exceeded a service quota.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

Invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetQueryStatusWorkloadInsightsTopContributors

Return the data for a query with the Network Flow Monitor query interface. Specify the query that you want to return results for by providing a query ID and a monitor name. This query returns the top contributors for workload insights.

When you start a query, use this call to check the status of the query to make sure that it has SUCCEEDED before you review the results. Use the same query ID that you used for the corresponding API call to start the query, `StartQueryWorkloadInsightsTopContributors`.

Top contributors in Network Flow Monitor are network flows with the highest values for a specific metric type. Top contributors can be across all workload insights, for a given scope, or for a specific monitor. Use the applicable call for the top contributors that you want to be returned.

Request Syntax

```
GET /workloadInsights/scopeId/topContributorsQueries/queryId/status HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[queryId](#)

The identifier for the query. A query ID is an internally-generated identifier for a specific query returned from an API call to start a query.

Required: Yes

[scopeId](#)

The identifier for the scope that includes the resources you want to get data results for. A scope ID is an internally-generated identifier that includes all the resources for a specific root account.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "status
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

status

When you run a query, use this call to check the status of the query to make sure that the query has SUCCEEDED before you review the results.

- QUEUED: The query is scheduled to run.
- RUNNING: The query is in progress but not complete.
- SUCCEEDED: The query completed successfully.
- FAILED: The query failed due to an error.
- CANCELED: The query was canceled.

Type: String

Valid Values: QUEUED | RUNNING | SUCCEEDED | FAILED | CANCELED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 403

InternalServerException

An internal error occurred.

HTTP Status Code: 500

ServiceQuotaExceededException

The request exceeded a service quota.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

Invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetQueryStatusWorkloadInsightsTopContributorsData

Returns the current status of a query for the Network Flow Monitor query interface, for a specified query ID and monitor. This call returns the query status for the top contributors data for workload insights.

When you start a query, use this call to check the status of the query to make sure that it has SUCCEEDED before you review the results. Use the same query ID that you used for the corresponding API call to start the query, StartQueryWorkloadInsightsTopContributorsData.

Top contributors in Network Flow Monitor are network flows with the highest values for a specific metric type. Top contributors can be across all workload insights, for a given scope, or for a specific monitor. Use the applicable call for the top contributors that you want to be returned.

The top contributor network flows overall are for a specific metric type, for example, the number of retransmissions.

Request Syntax

```
GET /workloadInsights/scopeId/topContributorsDataQueries/queryId/status HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[queryId](#)

The identifier for the query. A query ID is an internally-generated identifier for a specific query returned from an API call to start a query.

Required: Yes

[scopeId](#)

The identifier for the scope that includes the resources you want to get data results for. A scope ID is an internally-generated identifier that includes all the resources for a specific root account. A scope ID is returned from a CreateScope API call.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "status
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

status

The status of a query for top contributors data.

- QUEUED: The query is scheduled to run.
- RUNNING: The query is in progress but not complete.
- SUCCEEDED: The query completed successfully.
- FAILED: The query failed due to an error.
- CANCELED: The query was canceled.

Type: String

Valid Values: QUEUED | RUNNING | SUCCEEDED | FAILED | CANCELED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 403

InternalServerException

An internal error occurred.

HTTP Status Code: 500

ServiceQuotaExceededException

The request exceeded a service quota.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

Invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetScope

Gets information about a scope, including the name, status, tags, and target details. The scope in Network Flow Monitor is an account.

Request Syntax

```
GET /scopes/scopeId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

scopeId

The identifier for the scope that includes the resources you want to get data results for. A scope ID is an internally-generated identifier that includes all the resources for a specific root account. A scope ID is returned from a CreateScope API call.

Length Constraints: Minimum length of 1.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "scopeArn": "string",
  "scopeId": "string",
  "status": "string",
  "tags": {
    "string" : "string"
  }
},
```

```
"targets": [  
    {  
        "region        "targetIdentifier": {  
            "targetId": { ... },  
            "targetType": "string"  
        }  
    }  
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

scopeArn

The Amazon Resource Name (ARN) of the scope.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: arn:.*

scopeId

The identifier for the scope that includes the resources you want to get data results for. A scope ID is an internally-generated identifier that includes all the resources for a specific root account. A scope ID is returned from a CreateScope API call.

Type: String

status

The status of a scope. The status can be one of the following: SUCCEEDED, IN_PROGRESS, or FAILED.

Type: String

Valid Values: SUCCEEDED | IN_PROGRESS | FAILED

tags

The tags for a scope.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

targets

The targets for a scope

Type: Array of [TargetResource](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 403

InternalServerError

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The request specifies a resource that doesn't exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request exceeded a service quota.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

Invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListMonitors

List all monitors in an account. Optionally, you can list only monitors that have a specific status, by using the STATUS parameter.

Request Syntax

```
GET /monitors?maxResults=maxResults&monitorStatus=monitorStatus&nextToken=nextToken
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The number of query results that you want to return with this call.

Valid Range: Minimum value of 1. Maximum value of 25.

monitorStatus

The status of a monitor. The status can be one of the following

- PENDING: The monitor is in the process of being created.
- ACTIVE: The monitor is active.
- INACTIVE: The monitor is inactive.
- ERROR: Monitor creation failed due to an error.
- DELETING: The monitor is in the process of being deleted.

Valid Values: PENDING | ACTIVE | INACTIVE | ERROR | DELETING

nextToken

The token for the next set of results. You receive this token from a previous call.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "monitorsmonitorArnmonitorNamemonitorStatusnextToken
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

monitors

The monitors that are in an account.

Type: Array of [MonitorSummary](#) objects

nextToken

The token for the next set of results. You receive this token from a previous call.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 403

InternalServerException

An internal error occurred.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

Invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListScopes

List all the scopes for an account.

Request Syntax

```
GET /scopes?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The number of query results that you want to return with this call.

Valid Range: Minimum value of 1. Maximum value of 25.

nextToken

The token for the next set of results. You receive this token from a previous call.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "nextTokenscopesscopeArnscopeIdstatus
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The token for the next set of results. You receive this token from a previous call.

Type: String

scopes

The scopes returned by the call.

Type: Array of [ScopeSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 403

InternalServerError

An internal error occurred.

HTTP Status Code: 500

ServiceQuotaExceededException

The request exceeded a service quota.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

Invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Returns all the tags for a resource.

Request Syntax

```
GET /tags/resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the resource.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: arn:.*

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tags

The tags for a resource.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 403

ConflictException

The requested resource is in use.

HTTP Status Code: 409

InternalServerError

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The request specifies a resource that doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

Invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartQueryMonitorTopContributors

Create a query that you can use with the Network Flow Monitor query interface to return the top contributors for a monitor. Specify the monitor that you want to create the query for.

The call returns a query ID that you can use with [GetQueryResultsMonitorTopContributors](#) to run the query and return the top contributors for a specific monitor.

Top contributors in Network Flow Monitor are network flows with the highest values for a specific metric type. Top contributors can be across all workload insights, for a given scope, or for a specific monitor. Use the applicable APIs for the top contributors that you want to be returned.

Request Syntax

```
POST /monitors/monitorName/topContributorsQueries HTTP/1.1
Content-type: application/json

{
  "destinationCategoryendTimelimitmetricNamestartTime
```

URI Request Parameters

The request uses the following URI parameters.

monitorName

The name of the monitor.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9_.-]+

Required: Yes

Request Body

The request accepts the following data in JSON format.

destinationCategory

The category that you want to query top contributors for, for a specific monitor. Destination categories can be one of the following:

- INTRA_AZ: Top contributor network flows within a single Availability Zone
- INTER_AZ: Top contributor network flows between Availability Zones
- INTER_VPC: Top contributor network flows between VPCs
- AMAZON_S3: Top contributor network flows to or from Amazon S3
- AMAZON_DYNAMODB: Top contributor network flows to or from Amazon Dynamo DB
- UNCLASSIFIED: Top contributor network flows that do not have a bucket classification

Type: String

Valid Values: INTRA_AZ | INTER_AZ | INTER_VPC | UNCLASSIFIED | AMAZON_S3 | AMAZON_DYNAMODB

Required: Yes

endTime

The timestamp that is the date and time end of the period that you want to retrieve results for with your query.

Type: Timestamp

Required: Yes

limit

The maximum number of top contributors to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 500.

Required: No

metricName

The metric that you want to query top contributors for. That is, you can specify a metric with this call and return the top contributor network flows, for that type of metric, for a monitor and (optionally) within a specific category, such as network flows between Availability Zones.

Type: String

Valid Values: ROUND_TRIP_TIME | TIMEOUTS | RETRANSMISSIONS | DATA_TRANSFERRED

Required: Yes

startTime

The timestamp that is the date and time beginning of the period that you want to retrieve results for with your query.

Type: Timestamp

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
    "queryId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

queryId

The identifier for the query. A query ID is an internally-generated identifier for a specific query returned from an API call to start a query.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 403

InternalServerException

An internal error occurred.

HTTP Status Code: 500

ServiceQuotaExceededException

The request exceeded a service quota.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

Invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartQueryWorkloadInsightsTopContributors

Create a query with the Network Flow Monitor query interface that you can run to return workload insights top contributors. Specify the scope that you want to create a query for.

The call returns a query ID that you can use with

[GetQueryResultsWorkloadInsightsTopContributors](#) to run the query and return the top contributors for the workload insights for a scope.

Top contributors in Network Flow Monitor are network flows with the highest values for a specific metric type. Top contributors can be across all workload insights, for a given scope, or for a specific monitor. Use the applicable APIs for the top contributors that you want to be returned.

Request Syntax

```
POST /workloadInsights/scopeId/topContributorsQueries HTTP/1.1
Content-type: application/json

{
  "destinationCategoryendTimelimitmetricNamestartTime
```

URI Request Parameters

The request uses the following URI parameters.

scopeId

The identifier for the scope that includes the resources you want to get data results for. A scope ID is an internally-generated identifier that includes all the resources for a specific root account. A scope ID is returned from a CreateScope API call.

Required: Yes

Request Body

The request accepts the following data in JSON format.

[destinationCategory](#)

The destination category for a top contributors row. Destination categories can be one of the following:

- INTRA_AZ: Top contributor network flows within a single Availability Zone
- INTER_AZ: Top contributor network flows between Availability Zones
- INTER_VPC: Top contributor network flows between VPCs
- AWS_SERVICES: Top contributor network flows to or from AWS services
- UNCLASSIFIED: Top contributor network flows that do not have a bucket classification

Type: String

Valid Values: INTRA_AZ | INTER_AZ | INTER_VPC | UNCLASSIFIED | AMAZON_S3 | AMAZON_DYNAMODB

Required: Yes

[endTime](#)

The timestamp that is the date and time end of the period that you want to retrieve results for with your query.

Type: Timestamp

Required: Yes

[limit](#)

The maximum number of top contributors to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 500.

Required: No

metricName

The metric that you want to query top contributors for. That is, you can specify this metric to return the top contributor network flows, for this type of metric, for a monitor and (optionally) within a specific category, such as network flows between Availability Zones.

Type: String

Valid Values: TIMEOUTS | RETRANSMISSIONS | DATA_TRANSFERRED

Required: Yes

startTime

The timestamp that is the date and time beginning of the period that you want to retrieve results for with your query.

Type: Timestamp

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
    "queryId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

queryId

The identifier for the query. A query ID is an internally-generated identifier for a specific query returned from an API call to start a query.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 403

InternalServerError

An internal error occurred.

HTTP Status Code: 500

ServiceQuotaExceededException

The request exceeded a service quota.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

Invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartQueryWorkloadInsightsTopContributorsData

Create a query with the Network Flow Monitor query interface that you can run to return data for workload insights top contributors. Specify the scope that you want to create a query for.

The call returns a query ID that you can use with

[GetQueryResultsWorkloadInsightsTopContributorsData](#) to run the query and return the data for the top contributors for the workload insights for a scope.

Top contributors in Network Flow Monitor are network flows with the highest values for a specific metric type. Top contributors can be across all workload insights, for a given scope, or for a specific monitor. Use the applicable call for the top contributors that you want to be returned.

Request Syntax

```
POST /workloadInsights/scopeId/topContributorsDataQueries HTTP/1.1
Content-type: application/json

{
  "destinationCategoryendTimemetricNamestartTime
```

URI Request Parameters

The request uses the following URI parameters.

scopeId

The identifier for the scope that includes the resources you want to get data results for. A scope ID is an internally-generated identifier that includes all the resources for a specific root account.

Required: Yes

Request Body

The request accepts the following data in JSON format.

destinationCategory

The destination category for a top contributors. Destination categories can be one of the following:

- INTRA_AZ: Top contributor network flows within a single Availability Zone
- INTER_AZ: Top contributor network flows between Availability Zones
- INTER_VPC: Top contributor network flows between VPCs
- AWS_SERVICES: Top contributor network flows to or from AWS services
- UNCLASSIFIED: Top contributor network flows that do not have a bucket classification

Type: String

Valid Values: INTRA_AZ | INTER_AZ | INTER_VPC | UNCLASSIFIED | AMAZON_S3 | AMAZON_DYNAMODB

Required: Yes

endTime

The timestamp that is the date and time end of the period that you want to retrieve results for with your query.

Type: Timestamp

Required: Yes

metricName

The metric that you want to query top contributors for. That is, you can specify this metric to return the top contributor network flows, for this type of metric, for a monitor and (optionally) within a specific category, such as network flows between Availability Zones.

Type: String

Valid Values: TIMEOUTS | RETRANSMISSIONS | DATA_TRANSFERRED

Required: Yes

startTime

The timestamp that is the date and time beginning of the period that you want to retrieve results for with your query.

Type: Timestamp

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "queryId
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

queryId

The identifier for the query. A query ID is an internally-generated identifier for a specific query returned from an API call to start a query.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 403

InternalServerError

An internal error occurred.

HTTP Status Code: 500

ServiceQuotaExceededException

The request exceeded a service quota.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

Invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StopQueryMonitorTopContributors

Stop a top contributors query for a monitor. Specify the query that you want to stop by providing a query ID and a monitor name.

Top contributors in Network Flow Monitor are network flows with the highest values for a specific metric type. Top contributors can be across all workload insights, for a given scope, or for a specific monitor. Use the applicable call for the top contributors that you want to be returned.

Request Syntax

```
DELETE /monitors/monitorName/topContributorsQueries/queryId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

monitorName

The name of the monitor.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9_.-]+

Required: Yes

queryId

The identifier for the query. A query ID is an internally-generated identifier for a specific query returned from an API call to create a query.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 403

InternalServerException

An internal error occurred.

HTTP Status Code: 500

ServiceQuotaExceededException

The request exceeded a service quota.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

Invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StopQueryWorkloadInsightsTopContributors

Stop a top contributors query for workload insights. Specify the query that you want to stop by providing a query ID and a scope ID.

Top contributors in Network Flow Monitor are network flows with the highest values for a specific metric type. Top contributors can be across all workload insights, for a given scope, or for a specific monitor. Use the applicable call for the top contributors that you want to be returned.

Request Syntax

```
DELETE /workloadInsights/scopeId/topContributorsQueries/queryId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[queryId](#)

The identifier for the query. A query ID is an internally-generated identifier for a specific query returned from an API call to create a query.

Required: Yes

[scopeId](#)

The identifier for the scope that includes the resources you want to get data results for. A scope ID is an internally-generated identifier that includes all the resources for a specific root account.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 403

InternalServerException

An internal error occurred.

HTTP Status Code: 500

ServiceQuotaExceededException

The request exceeded a service quota.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

Invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StopQueryWorkloadInsightsTopContributorsData

Stop a top contributors data query for workload insights. Specify the query that you want to stop by providing a query ID and a scope ID.

Top contributors in Network Flow Monitor are network flows with the highest values for a specific metric type. Top contributors can be across all workload insights, for a given scope, or for a specific monitor. Use the applicable call for the top contributors that you want to be returned.

Request Syntax

```
DELETE /workloadInsights/scopeId/topContributorsDataQueries/queryId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[queryId](#)

The identifier for the query. A query ID is an internally-generated identifier for a specific query returned from an API call to create a query.

Required: Yes

[scopeId](#)

The identifier for the scope that includes the resources you want to get data results for. A scope ID is an internally-generated identifier that includes all the resources for a specific root account.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 403

InternalServerException

An internal error occurred.

HTTP Status Code: 500

ServiceQuotaExceededException

The request exceeded a service quota.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

Invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Adds a tag to a resource.

Request Syntax

```
POST /tags/resourceArn HTTP/1.1
Content-type: application/json

{
  "tags": {
    "string": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the resource.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: arn:.*

Required: Yes

Request Body

The request accepts the following data in JSON format.

tags

The tags for a resource.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

Response Syntax

HTTP/1.1 200

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 403

ConflictException

The requested resource is in use.

HTTP Status Code: 409

InternalServerException

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The request specifies a resource that doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

Invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Removes a tag from a resource.

Request Syntax

```
DELETE /tags/resourceArn?tagKeys=tagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the resource.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: arn: . *

Required: Yes

tagKeys

Keys that you specified when you tagged a resource.

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 403

ConflictException

The requested resource is in use.

HTTP Status Code: 409

InternalServerException

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The request specifies a resource that doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

Invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateMonitor

Update a monitor to add or remove local or remote resources.

Request Syntax

```
PATCH /monitors/monitorName HTTP/1.1
Content-type: application/json

{
  "clientTokenlocalResourcesToAddidentifiertypelocalResourcesToRemoveidentifiertyperemoteResourcesToAddidentifiertyperemoteResourcesToRemoveidentifiertype
```

URI Request Parameters

The request uses the following URI parameters.

monitorName

The name of the monitor.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9_.-]+

Required: Yes

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive string of up to 64 ASCII characters that you specify to make an idempotent API request. Don't reuse the same client token for other API requests.

Type: String

Length Constraints: Fixed length of 36.

Pattern: [a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}

Required: No

localResourcesToAdd

The local resources to add, as an array of resources with identifiers and types.

Type: Array of [MonitorLocalResource](#) objects

Required: No

localResourcesToRemove

The local resources to remove, as an array of resources with identifiers and types.

Type: Array of [MonitorLocalResource](#) objects

Required: No

remoteResourcesToAdd

The remove resources to add, as an array of resources with identifiers and types.

Type: Array of [MonitorRemoteResource](#) objects

Required: No

remoteResourcesToRemove

The remove resources to remove, as an array of resources with identifiers and types.

Type: Array of [MonitorRemoteResource](#) objects

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "createdAt": number,
  "localResources": [
    {
      "identifier": "string",
      "type": "string"
    }
  ],
  "modifiedAt": number,
  "monitorArn": "string",
  "monitorName": "string",
  "monitorStatus": "string",
  "remoteResources": [
    {
      "identifier": "string",
      "type": "string"
    }
  ],
  "tags": {
    "string": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

createdAt

The date and time when the monitor was created.

Type: Timestamp

localResources

The local resources updated for a monitor, as an array of resources with identifiers and types.

Type: Array of [MonitorLocalResource](#) objects

modifiedAt

The last date and time that the monitor was modified.

Type: Timestamp

monitorArn

The Amazon Resource Name (ARN) of the monitor.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 512.

Pattern: arn:.*

monitorName

The name of the monitor.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [a-zA-Z0-9_.-]+

monitorStatus

The status of a monitor. The status can be one of the following

- PENDING: The monitor is in the process of being created.
- ACTIVE: The monitor is active.
- INACTIVE: The monitor is inactive.
- ERROR: Monitor creation failed due to an error.
- DELETING: The monitor is in the process of being deleted.

Type: String

Valid Values: PENDING | ACTIVE | INACTIVE | ERROR | DELETING

remoteResources

The remote resources updated for a monitor, as an array of resources with identifiers and types.

Type: Array of [MonitorRemoteResource](#) objects

tags

The tags for a monitor.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 403

InternalServerException

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The request specifies a resource that doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

Invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateScope

Update a scope to add or remove resources that you want to be available for Network Flow Monitor to generate metrics for, when you have active agents on those resources sending metrics reports to the Network Flow Monitor backend.

Request Syntax

```
PATCH /scopes/scopeId HTTP/1.1
Content-type: application/json

{
  "resourcesToAddregionstring",
      "targetIdentifiertargetIdtargetTypestring"
      }
    }
  ],
  "resourcesToDeleteregionstring",
      "targetIdentifiertargetIdtargetTypestring"
      }
    }
  ]
}
```

URI Request Parameters

The request uses the following URI parameters.

scopeId

The identifier for the scope that includes the resources you want to get data results for. A scope ID is an internally-generated identifier that includes all the resources for a specific root account.

Required: Yes

Request Body

The request accepts the following data in JSON format.

resourcesToAdd

A list of resources to add to a scope.

Type: Array of [TargetResource](#) objects

Array Members: Minimum number of 1 item. Maximum number of 99 items.

Required: No

resourcesToDelete

A list of resources to delete from a scope.

Type: Array of [TargetResource](#) objects

Array Members: Minimum number of 1 item. Maximum number of 99 items.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "scopeArn": "string",
  "scopeId": "string",
  "status": "string",
  "tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

scopeArn

The Amazon Resource Name (ARN) of the scope.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: arn:.*

scopeId

The identifier for the scope that includes the resources you want to get data results for. A scope ID is an internally-generated identifier that includes all the resources for a specific root account.

Type: String

status

The status for a call to update a scope. The status can be one of the following: SUCCEEDED, IN_PROGRESS, or FAILED.

Type: String

Valid Values: SUCCEEDED | IN_PROGRESS | FAILED

tags

The tags for a scope.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 403

InternalServerException

An internal error occurred.

HTTP Status Code: 500

ResourceNotFoundException

The request specifies a resource that doesn't exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request exceeded a service quota.

HTTP Status Code: 402

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

Invalid request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The Network Flow Monitor API contains several data types that various actions use. This section describes each data type in detail.

 **Note**

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [KubernetesMetadata](#)
- [MonitorLocalResource](#)
- [MonitorRemoteResource](#)
- [MonitorSummary](#)
- [MonitorTopContributorsRow](#)
- [ScopeSummary](#)
- [TargetId](#)
- [TargetIdentifier](#)
- [TargetResource](#)
- [TraversedComponent](#)
- [WorkloadInsightsTopContributorsDataPoint](#)
- [WorkloadInsightsTopContributorsRow](#)

KubernetesMetadata

Meta data about Kubernetes resources.

Contents

localPodName

The name of the pod for a local resource.

Type: String

Required: No

localPodNamespace

The namespace of the pod for a local resource.

Type: String

Required: No

localServiceName

The service name for a local resource.

Type: String

Required: No

remotePodName

The name of the pod for a remote resource.

Type: String

Required: No

remotePodNamespace

The namespace of the pod for a remote resource.

Type: String

Required: No

remoteServiceName

The service name for a remote resource.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MonitorLocalResource

A local resource is the host where the agent is installed. Local resources can be a subnet, a VPC, or an Availability Zone.

Contents

identifier

The identifier of the local resource, such as an ARN.

Type: String

Required: Yes

type

The type of the local resource. Valid values are AWS::EC2::VPC AWS::AvailabilityZone or AWS::EC2::Subnet.

Type: String

Valid Values: AWS::EC2::VPC | AWS::AvailabilityZone | AWS::EC2::Subnet

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MonitorRemoteResource

A remote resource is the other endpoint in a network flow. That is, one endpoint is the local resource and the other is the remote resource. Remote resources can be a subnet, a VPC, an Availability Zone, or an AWS service.

Contents

identifier

The identifier of the remote resource, such as an ARN.

Type: String

Required: Yes

type

The type of the remote resource. Valid values are AWS::EC2::VPC AWS::AvailabilityZone, AWS::EC2::Subnet, or AWS::AWSService.

Type: String

Valid Values: AWS::EC2::VPC | AWS::AvailabilityZone | AWS::EC2::Subnet | AWS::AWSService

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MonitorSummary

A summary of information about a monitor, includ the ARN, the name, and the status.

Contents

monitorArn

The Amazon Resource Name (ARN) of the monitor.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 512.

Pattern: `arn: .*`

Required: Yes

monitorName

The name of the monitor.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

monitorStatus

The status of a monitor. The status can be one of the following

- PENDING: The monitor is in the process of being created.
- ACTIVE: The monitor is active.
- INACTIVE: The monitor is inactive.
- ERROR: Monitor creation failed due to an error.
- DELETING: The monitor is in the process of being deleted.

Type: String

Valid Values: PENDING | ACTIVE | INACTIVE | ERROR | DELETING

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MonitorTopContributorsRow

A set of information for a top contributor network flow in a monitor. In a monitor, Network Flow Monitor returns information about the network flows for top contributors for each metric. Top contributors are network flows with the top values for each metric type.

Contents

destinationCategory

The destination category for a top contributors row. Destination categories can be one of the following:

- INTRA_AZ: Top contributor network flows within a single Availability Zone
- INTER_AZ: Top contributor network flows between Availability Zones
- INTER_VPC: Top contributor network flows between VPCs
- AWS_SERVICES: Top contributor network flows to or from AWS services
- UNCLASSIFIED: Top contributor network flows that do not have a bucket classification

Type: String

Valid Values: INTRA_AZ | INTER_AZ | INTER_VPC | UNCLASSIFIED | AMAZON_S3 | AMAZON_DYNAMODB

Required: No

dnatIp

The destination network address translation (DNAT) IP address for a top contributor network flow.

Type: String

Required: No

kubernetesMetadata

Meta data about Kubernetes resources.

Type: [KubernetesMetadata](#) object

Required: No

localAz

The Availability Zone for the local resource for a top contributor network flow.

Type: String

Required: No

localInstanceArn

The Amazon Resource Name (ARN) of a local resource.

Type: String

Required: No

localInstanceId

The instance identifier for the local resource for a top contributor network flow.

Type: String

Pattern: `i-[a-zA-Z0-9]{8,32}`

Required: No

localIp

The IP address of the local resource for a top contributor network flow.

Type: String

Required: No

localRegion

The AWS Region for the local resource for a top contributor network flow.

Type: String

Required: No

localSubnetArn

The Amazon Resource Name (ARN) of a local subnet.

Type: String

Required: No

localSubnetId

The subnet ID for the local resource for a top contributor network flow.

Type: String

Pattern: subnet-[a-zA-Z0-9]{8,32}

Required: No

localVpcArn

The Amazon Resource Name (ARN) of a local VPC.

Type: String

Required: No

localVpcId

The VPC ID for a top contributor network flow for the local resource.

Type: String

Pattern: vpc-[a-zA-Z0-9]{8,32}

Required: No

remoteAz

The Availability Zone for the remote resource for a top contributor network flow.

Type: String

Required: No

remoteInstanceArn

The Amazon Resource Name (ARN) of a remote resource.

Type: String

Required: No

remoteInstanceId

The instance identifier for the remote resource for a top contributor network flow.

Type: String

Pattern: `i-[a-zA-Z0-9]{8,32}`

Required: No

remotelp

The IP address of the remote resource for a top contributor network flow.

Type: String

Required: No

remoteRegion

The AWS Region for the remote resource for a top contributor network flow.

Type: String

Required: No

remoteSubnetArn

The Amazon Resource Name (ARN) of a remote subnet.

Type: String

Required: No

remoteSubnetId

The subnet ID for the remote resource for a top contributor network flow.

Type: String

Pattern: `subnet-[a-zA-Z0-9]{8,32}`

Required: No

remoteVpcArn

The Amazon Resource Name (ARN) of a remote VPC.

Type: String

Required: No

remoteVpcId

The VPC ID for a top contributor network flow for the remote resource.

Type: String

Pattern: vpc-[a-zA-Z0-9]{8,32}

Required: No

snatIp

The secure network address translation (SNAT) IP address for a top contributor network flow.

Type: String

Required: No

targetPort

The target port.

Type: Integer

Required: No

traversedConstructs

The constructs traversed by a network flow.

Type: Array of [TraversedComponent](#) objects

Required: No

value

The value of the metric for a top contributor network flow.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ScopeSummary

A summary of information about a scope, including the ARN, target ID, and AWS Region.

Contents

scopeArn

The Amazon Resource Name (ARN) of the scope.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: arn:.*

Required: Yes

scopeId

The identifier for the scope that includes the resources you want to get data results for. A scope ID is an internally-generated identifier that includes all the resources for a specific root account.

Type: String

Required: Yes

status

The status of a scope. The status can be one of the following, depending on the state of scope creation: SUCCEEDED, IN_PROGRESS, or FAILED.

Type: String

Valid Values: SUCCEEDED | IN_PROGRESS | FAILED

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TargetId

A target ID is an internally-generated identifier for a target. A target allows you to identify all the resources in a Network Flow Monitor scope. Currently, a target is always an AWS account.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

accountId

The identifier for the account for a target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 12.

Pattern: [0-9]{12}

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TargetIdentifier

A target identifier is a pair of identifying information for a resource that is included in a target. A target identifier includes the target ID and the target type.

Contents

targetId

The identifier for a target.

Type: [TargetId](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

targetType

The type of a target. A target type is currently always ACCOUNT because a target is currently a single AWS account.

Type: String

Valid Values: ACCOUNT

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TargetResource

A target resource in a scope. The resource is identified by a Region and a target identifier, which includes a target ID and a target type.

Contents

region

The AWS Region where the target resource is located.

Type: String

Required: Yes

targetIdentifier

A target identifier is a pair of identifying information for a resource that is included in a target. A target identifier includes the target ID and the target type.

Type: [TargetIdentifier](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TraversedComponent

A section of the network that a network flow has traveled through.

Contents

componentArn

The Amazon Resource Name (ARN) of a tranversed component.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: arn:.*

Required: No

componentId

The identifier for the traversed component.

Type: String

Required: No

componentType

The type of component that was traversed.

Type: String

Required: No

serviceName

The service name for the traversed component.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

WorkloadInsightsTopContributorsDataPoint

A data point for a top contributor network flow in a scope. Network Flow Monitor returns information about the network flows with the top values for each metric type, which are called top contributors.

Contents

label

The label identifying the data point.

Type: String

Required: Yes

timestamps

An array of the timestamps for the data point.

Type: Array of timestamps

Required: Yes

values

The values for the data point.

Type: Array of doubles

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

WorkloadInsightsTopContributorsRow

A row for a top contributor for a scope.

Contents

accountId

The account ID for a specific row of data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 12.

Pattern: [0-9]{12}

Required: No

localAz

The identifier for the Availability Zone where the local resource is located.

Type: String

Required: No

localRegion

The AWS Region where the local resource is located.

Type: String

Required: No

localSubnetArn

The Amazon Resource Name (ARN) of a local subnet.

Type: String

Required: No

localSubnetId

The subnet identifier for the local resource.

Type: String

Pattern: subnet-[a-zA-Z0-9]{8,32}

Required: No

localVpcArn

The Amazon Resource Name (ARN) of a local VPC.

Type: String

Required: No

localVpcId

The identifier for the VPC for the local resource.

Type: String

Pattern: vpc-[a-zA-Z0-9]{8,32}

Required: No

remoteIdentifier

The identifier of a remote resource.

Type: String

Required: No

value

The value for a metric.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests in the IAM User Guide](#).

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request").

The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request is expired

HTTP Status Code: 403

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 403

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

MalformedHttpRequestException

Problems with the request at the HTTP level, e.g. we can't decompress the body according to the decompression algorithm specified by the content-encoding.

HTTP Status Code: 400

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 401

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestAbortedException

Convenient exception that can be used when a request is aborted before a reply is sent back (e.g. client closed connection).

HTTP Status Code: 400

RequestEntityTooLargeException

Problems with the request at the HTTP level. The request entity is too large.

HTTP Status Code: 413

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

RequestTimeoutException

Problems with the request at the HTTP level. Reading the Request timed out.

HTTP Status Code: 408

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

UnrecognizedClientException

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

UnknownOperationException

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 404

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400