



API Reference

# AWS PCS



**API Version 2023-02-10**

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

# AWS PCS: API Reference

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

---

# Table of Contents

<b>Welcome</b> .....	<b>1</b>
<b>Actions</b> .....	<b>2</b>
CreateCluster .....	3
Request Syntax .....	3
Request Parameters .....	4
Response Syntax .....	6
Response Elements .....	8
Errors .....	8
See Also .....	10
CreateComputeNodeGroup .....	12
Request Syntax .....	12
Request Parameters .....	13
Response Syntax .....	16
Response Elements .....	17
Errors .....	17
See Also .....	20
CreateQueue .....	22
Request Syntax .....	22
Request Parameters .....	22
Response Syntax .....	24
Response Elements .....	25
Errors .....	25
See Also .....	28
DeleteCluster .....	29
Request Syntax .....	29
Request Parameters .....	29
Response Elements .....	30
Errors .....	30
See Also .....	32
DeleteComputeNodeGroup .....	33
Request Syntax .....	33
Request Parameters .....	33
Response Elements .....	34
Errors .....	34

---

See Also .....	36
DeleteQueue .....	37
Request Syntax .....	37
Request Parameters .....	37
Response Elements .....	38
Errors .....	38
See Also .....	40
GetCluster .....	41
Request Syntax .....	41
Request Parameters .....	41
Response Syntax .....	41
Response Elements .....	43
Errors .....	43
See Also .....	45
GetComputeNodeGroup .....	47
Request Syntax .....	47
Request Parameters .....	47
Response Syntax .....	47
Response Elements .....	49
Errors .....	49
See Also .....	51
GetQueue .....	52
Request Syntax .....	52
Request Parameters .....	52
Response Syntax .....	52
Response Elements .....	53
Errors .....	53
See Also .....	56
ListClusters .....	57
Request Syntax .....	57
Request Parameters .....	57
Response Syntax .....	58
Response Elements .....	58
Errors .....	58
See Also .....	61
ListComputeNodeGroups .....	62

Request Syntax .....	62
Request Parameters .....	62
Response Syntax .....	63
Response Elements .....	63
Errors .....	64
See Also .....	66
ListQueues .....	67
Request Syntax .....	67
Request Parameters .....	67
Response Syntax .....	68
Response Elements .....	68
Errors .....	69
See Also .....	71
ListTagsForResource .....	72
Request Syntax .....	72
Request Parameters .....	72
Response Syntax .....	72
Response Elements .....	72
Errors .....	73
See Also .....	73
RegisterComputeNodeGroupInstance .....	75
Request Syntax .....	75
Request Parameters .....	75
Response Syntax .....	76
Response Elements .....	76
Errors .....	77
See Also .....	77
TagResource .....	79
Request Syntax .....	79
Request Parameters .....	79
Response Elements .....	80
Errors .....	80
See Also .....	81
UntagResource .....	82
Request Syntax .....	82
Request Parameters .....	82

Response Elements .....	83
Errors .....	83
See Also .....	83
UpdateCluster .....	85
Request Syntax .....	85
Request Parameters .....	86
Response Syntax .....	87
Response Elements .....	88
Errors .....	89
See Also .....	91
UpdateComputeNodeGroup .....	92
Request Syntax .....	92
Request Parameters .....	92
Response Syntax .....	95
Response Elements .....	96
Errors .....	97
See Also .....	99
UpdateQueue .....	101
Request Syntax .....	101
Request Parameters .....	101
Response Syntax .....	102
Response Elements .....	103
Errors .....	103
See Also .....	106
<b>Data Types .....</b>	<b>108</b>
Accounting .....	110
Contents .....	110
See Also .....	110
AccountingRequest .....	112
Contents .....	112
See Also .....	112
CgroupCustomSetting .....	114
Contents .....	114
See Also .....	114
Cluster .....	115
Contents .....	115

---

See Also .....	117
ClusterSlurmConfiguration .....	119
Contents .....	119
See Also .....	120
ClusterSlurmConfigurationRequest .....	121
Contents .....	121
See Also .....	122
ClusterSummary .....	123
Contents .....	123
See Also .....	124
ComputeNodeGroup .....	125
Contents .....	125
See Also .....	129
ComputeNodeGroupConfiguration .....	130
Contents .....	130
See Also .....	130
ComputeNodeGroupSlurmConfiguration .....	131
Contents .....	131
See Also .....	131
ComputeNodeGroupSlurmConfigurationRequest .....	132
Contents .....	132
See Also .....	132
ComputeNodeGroupSummary .....	133
Contents .....	133
See Also .....	135
CustomLaunchTemplate .....	136
Contents .....	136
See Also .....	136
Endpoint .....	137
Contents .....	137
See Also .....	138
ErrorInfo .....	139
Contents .....	139
See Also .....	139
InstanceConfig .....	140
Contents .....	140

---

See Also .....	140
JwtAuth .....	141
Contents .....	141
See Also .....	141
JwtKey .....	142
Contents .....	142
See Also .....	142
Networking .....	143
Contents .....	143
See Also .....	144
NetworkingRequest .....	145
Contents .....	145
See Also .....	146
Queue .....	147
Contents .....	147
See Also .....	149
QueueSlurmConfiguration .....	150
Contents .....	150
See Also .....	150
QueueSlurmConfigurationRequest .....	151
Contents .....	151
See Also .....	151
QueueSummary .....	152
Contents .....	152
See Also .....	154
ScalingConfiguration .....	155
Contents .....	155
See Also .....	155
ScalingConfigurationRequest .....	156
Contents .....	156
See Also .....	156
Scheduler .....	157
Contents .....	157
See Also .....	157
SchedulerRequest .....	158
Contents .....	158

---

See Also .....	158
SlurmAuthKey .....	159
Contents .....	159
See Also .....	159
SlurmCustomSetting .....	160
Contents .....	160
See Also .....	160
SlurmdbdCustomSetting .....	161
Contents .....	161
See Also .....	161
SlurmRest .....	162
Contents .....	162
See Also .....	162
SlurmRestRequest .....	163
Contents .....	163
See Also .....	163
SpotOptions .....	164
Contents .....	164
See Also .....	164
UpdateAccountingRequest .....	165
Contents .....	165
See Also .....	165
UpdateClusterSlurmConfigurationRequest .....	167
Contents .....	167
See Also .....	168
UpdateComputeNodeGroupSlurmConfigurationRequest .....	169
Contents .....	169
See Also .....	169
UpdateQueueSlurmConfigurationRequest .....	170
Contents .....	170
See Also .....	170
UpdateSlurmRestRequest .....	171
Contents .....	171
See Also .....	171
ValidationExceptionField .....	172
Contents .....	172

---

See Also .....	172
<b>Common Parameters .....</b>	<b>173</b>
<b>Common Errors .....</b>	<b>176</b>

# Welcome

AWS Parallel Computing Service (AWS PCS) is a managed service that makes it easier for you to run and scale your high performance computing (HPC) workloads, and build scientific and engineering models on AWS using Slurm. For more information, see the [AWS Parallel Computing Service User Guide](#).

This reference describes the actions and data types of the service management API. You can use the AWS SDKs to call the API actions in software, or use the AWS Command Line Interface (AWS CLI) to call the API actions manually. These API actions manage the service through an AWS account.

The API actions operate on AWS PCS resources. A *resource* is an entity in AWS that you can work with. AWS services create resources when you use the features of the service. Examples of AWS PCS resources include clusters, compute node groups, and queues. For more information about resources in AWS, see [Resource](#) in the *AWS Resource Explorer User Guide*.

An AWS PCS *compute node* is an Amazon EC2 instance. You don't launch compute nodes directly. AWS PCS uses configuration information that you provide to launch compute nodes in your AWS account. You receive billing charges for your running compute nodes. AWS PCS automatically terminates your compute nodes when you delete the AWS PCS resources related to those compute nodes.

This document was last published on April 1, 2026.

# Actions

The following actions are supported:

- [CreateCluster](#)
- [CreateComputeNodeGroup](#)
- [CreateQueue](#)
- [DeleteCluster](#)
- [DeleteComputeNodeGroup](#)
- [DeleteQueue](#)
- [GetCluster](#)
- [GetComputeNodeGroup](#)
- [GetQueue](#)
- [ListClusters](#)
- [ListComputeNodeGroups](#)
- [ListQueues](#)
- [ListTagsForResource](#)
- [RegisterComputeNodeGroupInstance](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateCluster](#)
- [UpdateComputeNodeGroup](#)
- [UpdateQueue](#)

# CreateCluster

Creates a cluster in your account. AWS PCS creates the cluster controller in a service-owned account. The cluster controller communicates with the cluster resources in your account. The subnets and security groups for the cluster must already exist before you use this API action.

## Note

It takes time for AWS PCS to create the cluster. The cluster is in a `Creating` state until it is ready to use. There can only be 1 cluster in a `Creating` state per AWS Region per AWS account. `CreateCluster` fails with a `ServiceQuotaExceededException` if there is already a cluster in a `Creating` state.

## Request Syntax

```
{
  "clientToken": "string",
  "clusterName": "string",
  "networking": {
    "networkType": "string",
    "securityGroupIds": [ "string" ],
    "subnetIds": [ "string" ]
  },
  "scheduler": {
    "type": "string",
    "version": "string"
  },
  "size": "string",
  "slurmConfiguration": {
    "accounting": {
      "defaultPurgeTimeInDays": number,
      "mode": "string"
    },
    "cgroupCustomSettings": [
      {
        "parameterName": "string",
        "parameterValue": "string"
      }
    ],
    "scaleDownIdleTimeInSeconds": number,
```

```
  "slurmCustomSettings": [
    {
      "parameterName": "string",
      "parameterValue": "string"
    }
  ],
  "slurmdbdCustomSettings": [
    {
      "parameterName": "string",
      "parameterValue": "string"
    }
  ],
  "slurmRest": {
    "mode": "string"
  }
},
"tags": {
  "string" : "string"
}
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, the subsequent retries with the same client token return the result from the original successful request and they have no additional effect. If you don't specify a client token, the AWS CLI and SDK automatically generate 1 for you.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 100.

Required: No

### clusterName

A name to identify the cluster. Example: MyCluster

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: (?!pcs\_)^[A-Za-z][A-Za-z0-9-]+

Required: Yes

## networking

The networking configuration used to set up the cluster's control plane.

Type: [NetworkingRequest](#) object

Required: Yes

## scheduler

The cluster management and job scheduling software associated with the cluster.

Type: [SchedulerRequest](#) object

Required: Yes

## size

A value that determines the maximum number of compute nodes in the cluster and the maximum number of jobs (active and queued).

- SMALL: 32 compute nodes and 256 jobs
- MEDIUM: 512 compute nodes and 8192 jobs
- LARGE: 2048 compute nodes and 16,384 jobs

Type: String

Valid Values: SMALL | MEDIUM | LARGE

Required: Yes

## slurmConfiguration

Additional options related to the Slurm scheduler.

Type: [ClusterSlurmConfigurationRequest](#) object

Required: No

## tags

1 or more tags added to the resource. Each tag consists of a tag key and tag value. The tag value is optional and can be an empty string.

Type: String to string map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

## Response Syntax

```
{
  "cluster": {
    "arn": "string",
    "createdAt": "string",
    "endpoints": [
      {
        "ipv6Address": "string",
        "port": "string",
        "privateIpAddress": "string",
        "publicIpAddress": "string",
        "type": "string"
      }
    ],
    "errorInfo": [
      {
        "code": "string",
        "message": "string"
      }
    ],
    "id": "string",
    "modifiedAt": "string",
    "name": "string",
    "networking": {
      "networkType": "string",
      "securityGroupIds": [ "string" ],
      "subnetIds": [ "string" ]
    }
  }
}
```

```
  },
  "scheduler": {
    "type": "string",
    "version": "string"
  },
  "size": "string",
  "slurmConfiguration": {
    "accounting": {
      "defaultPurgeTimeInDays": number,
      "mode": "string"
    },
    "authKey": {
      "secretArn": "string",
      "secretVersion": "string"
    },
    "cgroupCustomSettings": [
      {
        "parameterName": "string",
        "parameterValue": "string"
      }
    ],
    "jwtAuth": {
      "jwtKey": {
        "secretArn": "string",
        "secretVersion": "string"
      }
    },
    "scaleDownIdleTimeInSeconds": number,
    "slurmCustomSettings": [
      {
        "parameterName": "string",
        "parameterValue": "string"
      }
    ],
    "slurmdbdCustomSettings": [
      {
        "parameterName": "string",
        "parameterValue": "string"
      }
    ],
    "slurmRest": {
      "mode": "string"
    }
  },
},
```

```
    "status": "string"  
  }  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### cluster

The cluster resource.

Type: [Cluster](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You don't have permission to perform the action.

#### Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

### **ConflictException**

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

#### Examples

- A cluster with the same name already exists.

- A cluster isn't in ACTIVE status.
- A cluster to delete is in an unstable state. For example, because it still has ACTIVE node groups or queues.
- A queue already exists in a cluster.

**resourceId**

The unique identifier of the resource that caused the conflict exception.

**resourceType**

The type or category of the resource that caused the conflict exception."

HTTP Status Code: 400

**InternalServerErrorException**

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

**ServiceQuotaExceededException**

You exceeded your service quota. Service quotas, also referred to as limits, are the maximum number of service resources or operations for your AWS account. To learn how to increase your service quota, see [Requesting a quota increase](#) in the *Service Quotas User Guide*

Examples

- The max number of clusters or queues has been reached for the account.
- The max number of compute node groups has been reached for the associated cluster.
- The total of maxInstances across all compute node groups has been reached for associated cluster.

**quotaCode**

The **quota code** of the service quota that was exceeded.

**resourceId**

The unique identifier of the resource that caused the quota to be exceeded.

**resourceType**

The type or category of the resource that caused the quota to be exceeded.

**serviceCode**

The service code associated with the quota that was exceeded.

HTTP Status Code: 400

**ThrottlingException**

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

**retryAfterSeconds**

The number of seconds to wait before retrying the request.

HTTP Status Code: 400

**ValidationException**

The request isn't valid.

Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

**fieldList**

A list of fields or properties that failed validation.

**reason**

The specific reason or cause of the validation error.

HTTP Status Code: 400

**See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateComputeNodeGroup

Creates a managed set of compute nodes. You associate a compute node group with a cluster through 1 or more AWS PCS queues or as part of the login fleet. A compute node group includes the definition of the compute properties and lifecycle management. AWS PCS uses the information you provide to this API action to launch compute nodes in your account. You can only specify subnets in the same Amazon VPC as your cluster. You receive billing charges for the compute nodes that AWS PCS launches in your account. You must already have a launch template before you call this API. For more information, see [Launch an instance from a launch template](#) in the *Amazon Elastic Compute Cloud User Guide for Linux Instances*.

## Request Syntax

```
{
  "amiId": "string",
  "clientToken": "string",
  "clusterIdentifier": "string",
  "computeNodeGroupName": "string",
  "customLaunchTemplate": {
    "id": "string",
    "version": "string"
  },
  "iamInstanceProfileArn": "string",
  "instanceConfigs": [
    {
      "instanceType": "string"
    }
  ],
  "purchaseOption": "string",
  "scalingConfiguration": {
    "maxInstanceCount": number,
    "minInstanceCount": number
  },
  "slurmConfiguration": {
    "slurmCustomSettings": [
      {
        "parameterName": "string",
        "parameterValue": "string"
      }
    ]
  }
},
```

```
"spotOptions": {
  "allocationStrategy": "string"
},
"subnetIds": [ "string" ],
"tags": {
  "string" : "string"
}
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### amiId

The ID of the Amazon Machine Image (AMI) that AWS PCS uses to launch compute nodes (Amazon EC2 instances). If you don't provide this value, AWS PCS uses the AMI ID specified in the custom launch template.

Type: String

Pattern: ami-[a-z0-9]+

Required: No

### clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, the subsequent retries with the same client token return the result from the original successful request and they have no additional effect. If you don't specify a client token, the AWS CLI and SDK automatically generate 1 for you.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 100.

Required: No

### clusterIdentifier

The name or ID of the cluster to create a compute node group in.

Type: String

Pattern: `(pcs_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{2,40})`

Required: Yes

### computeNodeGroupName

A name to identify the cluster. Example: MyCluster

Type: String

Length Constraints: Minimum length of 3. Maximum length of 25.

Pattern: `(?!pcs_)^[A-Za-z][A-Za-z0-9-]+`

Required: Yes

### customLaunchTemplate

An Amazon EC2 launch template AWS PCS uses to launch compute nodes.

Type: [CustomLaunchTemplate](#) object

Required: Yes

### iamInstanceProfileArn

The Amazon Resource Name (ARN) of the IAM instance profile used to pass an IAM role when launching EC2 instances. The role contained in your instance profile must have the `pcs:RegisterComputeNodeGroupInstance` permission and the role name must start with `AWSPCS` or must have the path `/aws-pcs/`. For more information, see [IAM instance profiles for AWS PCS](#) in the *AWS PCS User Guide*.

Type: String

Pattern: `arn:aws([a-zA-Z-]{0,10})?:iam::[0-9]{12}:instance-profile/([!~]{1,510}/)?([\w+=, .@-]{1,128})`

Required: Yes

### instanceConfigs

A list of EC2 instance configurations that AWS PCS can provision in the compute node group.

Type: Array of [InstanceConfig](#) objects

Required: Yes

### [purchaseOption](#)

Specifies how EC2 instances are purchased on your behalf. AWS PCS supports On-Demand Instances, Spot Instances, and Amazon EC2 Capacity Blocks for ML. For more information, see [Amazon EC2 billing and purchasing options](#) in the *Amazon Elastic Compute Cloud User Guide*. For more information about AWS PCS support for Capacity Blocks, see [Using Amazon EC2 Capacity Blocks for ML with AWS PCS](#) in the *AWS PCS User Guide*. If you don't provide this option, it defaults to On-Demand.

Type: String

Valid Values: ONDEMAND | SPOT | CAPACITY\_BLOCK

Required: No

### [scalingConfiguration](#)

Specifies the boundaries of the compute node group auto scaling.

Type: [ScalingConfigurationRequest](#) object

Required: Yes

### [slurmConfiguration](#)

Additional options related to the Slurm scheduler.

Type: [ComputeNodeGroupSlurmConfigurationRequest](#) object

Required: No

### [spotOptions](#)

Additional configuration when you specify SPOT as the purchaseOption for the CreateComputeNodeGroup API action.

Type: [SpotOptions](#) object

Required: No

### [subnetIds](#)

The list of subnet IDs where the compute node group launches instances. Subnets must be in the same VPC as the cluster.

Type: Array of strings

Required: Yes

### tags

1 or more tags added to the resource. Each tag consists of a tag key and tag value. The tag value is optional and can be an empty string.

Type: String to string map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

## Response Syntax

```
{
  "computeNodeGroup": {
    "amiId": "string",
    "arn": "string",
    "clusterId": "string",
    "createdAt": "string",
    "customLaunchTemplate": {
      "id": "string",
      "version": "string"
    },
    "errorInfo": [
      {
        "code": "string",
        "message": "string"
      }
    ],
    "iamInstanceProfileArn": "string",
    "id": "string",
    "instanceConfigs": [
      {
        "instanceType": "string"
      }
    ]
  }
}
```

```
    ],
    "modifiedAt": "string",
    "name": "string",
    "purchaseOption": "string",
    "scalingConfiguration": {
      "maxInstanceCount": number,
      "minInstanceCount": number
    },
    "slurmConfiguration": {
      "slurmCustomSettings": [
        {
          "parameterName": "string",
          "parameterValue": "string"
        }
      ]
    },
    "spotOptions": {
      "allocationStrategy": "string"
    },
    "status": "string",
    "subnetIds": [ "string" ]
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [computeNodeGroup](#)

A compute node group associated with a cluster.

Type: [ComputeNodeGroup](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You don't have permission to perform the action.

### Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

## **ConflictException**

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

### Examples

- A cluster with the same name already exists.
- A cluster isn't in ACTIVE status.
- A cluster to delete is in an unstable state. For example, because it still has ACTIVE node groups or queues.
- A queue already exists in a cluster.

### **resourceId**

The unique identifier of the resource that caused the conflict exception.

### **resourceType**

The type or category of the resource that caused the conflict exception."

HTTP Status Code: 400

## **InternalServerError**

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

## **ResourceNotFoundException**

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

### Examples

**resourceId**

The unique identifier of the resource that was not found.

**resourceType**

The type or category of the resource that was not found.

HTTP Status Code: 400

**ServiceQuotaExceededException**

You exceeded your service quota. Service quotas, also referred to as limits, are the maximum number of service resources or operations for your AWS account. To learn how to increase your service quota, see [Requesting a quota increase](#) in the *Service Quotas User Guide*

Examples

- The max number of clusters or queues has been reached for the account.
- The max number of compute node groups has been reached for the associated cluster.
- The total of maxInstances across all compute node groups has been reached for associated cluster.

**quotaCode**

The **quota code** of the service quota that was exceeded.

**resourceId**

The unique identifier of the resource that caused the quota to be exceeded.

**resourceType**

The type or category of the resource that caused the quota to be exceeded.

**serviceCode**

The service code associated with the quota that was exceeded.

HTTP Status Code: 400

**ThrottlingException**

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

## **retryAfterSeconds**

The number of seconds to wait before retrying the request.

HTTP Status Code: 400

## **ValidationException**

The request isn't valid.

### Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

### **fieldList**

A list of fields or properties that failed validation.

### **reason**

The specific reason or cause of the validation error.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateQueue

Creates a job queue. You must associate 1 or more compute node groups with the queue. You can associate 1 compute node group with multiple queues.

## Request Syntax

```
{
  "clientToken": "string",
  "clusterIdentifier": "string",
  "computeNodeGroupConfigurations": [
    {
      "computeNodeId": "string"
    }
  ],
  "queueName": "string",
  "slurmConfiguration": {
    "slurmCustomSettings": [
      {
        "parameterName": "string",
        "parameterValue": "string"
      }
    ]
  },
  "tags": {
    "string" : "string"
  }
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, the subsequent retries with the same client token return the result from the original successful request and they have no additional effect. If you don't specify a client token, the AWS CLI and SDK automatically generate 1 for you.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 100.

Required: No

### clusterIdentifier

The name or ID of the cluster for which to create a queue.

Type: String

Pattern: (pcs\_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{2,40})

Required: Yes

### computeNodeGroupConfigurations

The list of compute node group configurations to associate with the queue. Queues assign jobs to associated compute node groups.

Type: Array of [ComputeNodeGroupConfiguration](#) objects

Required: No

### queueName

A name to identify the queue.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 25.

Pattern: (?!pcs\_)^[A-Za-z][A-Za-z0-9-]+

Required: Yes

### slurmConfiguration

Additional options related to the Slurm scheduler.

Type: [QueueSlurmConfigurationRequest](#) object

Required: No

## tags

1 or more tags added to the resource. Each tag consists of a tag key and tag value. The tag value is optional and can be an empty string.

Type: String to string map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

## Response Syntax

```
{
  "queue": {
    "arn": "string",
    "clusterId": "string",
    "computeNodeGroupConfigurations": [
      {
        "computeNodeGroupId": "string"
      }
    ],
    "createdAt": "string",
    "errorInfo": [
      {
        "code": "string",
        "message": "string"
      }
    ],
    "id": "string",
    "modifiedAt": "string",
    "name": "string",
    "slurmConfiguration": {
      "slurmCustomSettings": [
        {
          "parameterName": "string",
          "parameterValue": "string"
        }
      ]
    }
  }
}
```

```
    },  
    "status": "string"  
  }  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### queue

A queue resource.

Type: [Queue](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You don't have permission to perform the action.

#### Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

### **ConflictException**

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

#### Examples

- A cluster with the same name already exists.

- A cluster isn't in ACTIVE status.
- A cluster to delete is in an unstable state. For example, because it still has ACTIVE node groups or queues.
- A queue already exists in a cluster.

**resourceId**

The unique identifier of the resource that caused the conflict exception.

**resourceType**

The type or category of the resource that caused the conflict exception."

HTTP Status Code: 400

**InternalServerError**

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

**ResourceNotFoundException**

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

Examples**resourceId**

The unique identifier of the resource that was not found.

**resourceType**

The type or category of the resource that was not found.

HTTP Status Code: 400

**ServiceQuotaExceededException**

You exceeded your service quota. Service quotas, also referred to as limits, are the maximum number of service resources or operations for your AWS account. To learn how to increase your service quota, see [Requesting a quota increase](#) in the *Service Quotas User Guide*

Examples

- The max number of clusters or queues has been reached for the account.
- The max number of compute node groups has been reached for the associated cluster.
- The total of maxInstances across all compute node groups has been reached for associated cluster.

**quotaCode**

The **quota code** of the service quota that was exceeded.

**resourceId**

The unique identifier of the resource that caused the quota to be exceeded.

**resourceType**

The type or category of the resource that caused the quota to be exceeded.

**serviceCode**

The service code associated with the quota that was exceeded.

HTTP Status Code: 400

**ThrottlingException**

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

**retryAfterSeconds**

The number of seconds to wait before retrying the request.

HTTP Status Code: 400

**ValidationException**

The request isn't valid.

Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

**fieldList**

A list of fields or properties that failed validation.

**reason**

The specific reason or cause of the validation error.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteCluster

Deletes a cluster and all its linked resources. You must delete all queues and compute node groups associated with the cluster before you can delete the cluster.

## Request Syntax

```
{
  "clientToken": "string",
  "clusterIdentifier": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [clientToken](#)

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, the subsequent retries with the same client token return the result from the original successful request and they have no additional effect. If you don't specify a client token, the AWS CLI and SDK automatically generate 1 for you.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 100.

Required: No

### [clusterIdentifier](#)

The name or ID of the cluster to delete.

Type: String

Pattern: (pcs\_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{2,40})

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

You don't have permission to perform the action.

#### Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

### ConflictException

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

#### Examples

- A cluster with the same name already exists.
- A cluster isn't in ACTIVE status.
- A cluster to delete is in an unstable state. For example, because it still has ACTIVE node groups or queues.
- A queue already exists in a cluster.

#### **resourceId**

The unique identifier of the resource that caused the conflict exception.

#### **resourceType**

The type or category of the resource that caused the conflict exception."

HTTP Status Code: 400

## InternalServerErrorException

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

## ResourceNotFoundException

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

### Examples

#### **resourceId**

The unique identifier of the resource that was not found.

#### **resourceType**

The type or category of the resource that was not found.

HTTP Status Code: 400

## ThrottlingException

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

#### **retryAfterSeconds**

The number of seconds to wait before retrying the request.

HTTP Status Code: 400

## ValidationException

The request isn't valid.

### Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

**fieldList**

A list of fields or properties that failed validation.

**reason**

The specific reason or cause of the validation error.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteComputeNodeGroup

Deletes a compute node group. You must delete all queues associated with the compute node group first.

## Request Syntax

```
{
  "clientToken": "string",
  "clusterIdentifier": "string",
  "computeNodeGroupIdentifier": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, the subsequent retries with the same client token return the result from the original successful request and they have no additional effect. If you don't specify a client token, the AWS CLI and SDK automatically generate 1 for you.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 100.

Required: No

### clusterIdentifier

The name or ID of the cluster of the compute node group.

Type: String

Pattern: (pcs\_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{2,40})

Required: Yes

## computeNodeGroupIdentifier

The name or ID of the compute node group to delete.

Type: String

Pattern: (pcs\_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{2,25})

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

You don't have permission to perform the action.

#### Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

### ConflictException

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

#### Examples

- A cluster with the same name already exists.
- A cluster isn't in ACTIVE status.
- A cluster to delete is in an unstable state. For example, because it still has ACTIVE node groups or queues.

- A queue already exists in a cluster.

**resourceId**

The unique identifier of the resource that caused the conflict exception.

**resourceType**

The type or category of the resource that caused the conflict exception."

HTTP Status Code: 400

**InternalServerErrorException**

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

**ResourceNotFoundException**

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

Examples**resourceId**

The unique identifier of the resource that was not found.

**resourceType**

The type or category of the resource that was not found.

HTTP Status Code: 400

**ThrottlingException**

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

**retryAfterSeconds**

The number of seconds to wait before retrying the request.

HTTP Status Code: 400

**ValidationException**

The request isn't valid.

### Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

### **fieldList**

A list of fields or properties that failed validation.

### **reason**

The specific reason or cause of the validation error.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteQueue

Deletes a job queue. If the compute node group associated with this queue isn't associated with any other queues, AWS PCS terminates all the compute nodes for this queue.

## Request Syntax

```
{
  "clientToken": "string",
  "clusterIdentifier": "string",
  "queueIdentifier": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, the subsequent retries with the same client token return the result from the original successful request and they have no additional effect. If you don't specify a client token, the AWS CLI and SDK automatically generate 1 for you.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 100.

Required: No

### clusterIdentifier

The name or ID of the cluster of the queue.

Type: String

Pattern: (pcs\_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{2,40})

Required: Yes

## queueIdentifier

The name or ID of the queue to delete.

Type: String

Pattern: (pcs\_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{2,25})

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

You don't have permission to perform the action.

#### Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

### ConflictException

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

#### Examples

- A cluster with the same name already exists.
- A cluster isn't in ACTIVE status.
- A cluster to delete is in an unstable state. For example, because it still has ACTIVE node groups or queues.

- A queue already exists in a cluster.

**resourceId**

The unique identifier of the resource that caused the conflict exception.

**resourceType**

The type or category of the resource that caused the conflict exception."

HTTP Status Code: 400

**InternalServerError**

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

**ResourceNotFoundException**

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

Examples**resourceId**

The unique identifier of the resource that was not found.

**resourceType**

The type or category of the resource that was not found.

HTTP Status Code: 400

**ThrottlingException**

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

**retryAfterSeconds**

The number of seconds to wait before retrying the request.

HTTP Status Code: 400

**ValidationException**

The request isn't valid.

### Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

### **fieldList**

A list of fields or properties that failed validation.

### **reason**

The specific reason or cause of the validation error.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetCluster

Returns detailed information about a running cluster in your account. This API action provides networking information, endpoint information for communication with the scheduler, and provisioning status.

## Request Syntax

```
{
  "clusterIdentifier": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### clusterIdentifier

The name or ID of the cluster.

Type: String

Pattern: (pcs\_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{2,40})

Required: Yes

## Response Syntax

```
{
  "cluster": {
    "arn": "string",
    "createdAt": "string",
    "endpoints": [
      {
        "ipv6Address": "string",
        "port": "string",
        "privateIpAddress": "string",
        "publicIpAddress": "string",
        "type": "string"
      }
    ]
  }
}
```

```
    }
  ],
  "errorInfo": [
    {
      "code": "string",
      "message": "string"
    }
  ],
  "id": "string",
  "modifiedAt": "string",
  "name": "string",
  "networking": {
    "networkType": "string",
    "securityGroupIds": [ "string" ],
    "subnetIds": [ "string" ]
  },
  "scheduler": {
    "type": "string",
    "version": "string"
  },
  "size": "string",
  "slurmConfiguration": {
    "accounting": {
      "defaultPurgeTimeInDays": number,
      "mode": "string"
    },
    "authKey": {
      "secretArn": "string",
      "secretVersion": "string"
    },
    "cgroupCustomSettings": [
      {
        "parameterName": "string",
        "parameterValue": "string"
      }
    ],
    "jwtAuth": {
      "jwtKey": {
        "secretArn": "string",
        "secretVersion": "string"
      }
    },
    "scaleDownIdleTimeInSeconds": number,
    "slurmCustomSettings": [
```

```
    {
      "parameterName": "string",
      "parameterValue": "string"
    }
  ],
  "slurmdbdCustomSettings": [
    {
      "parameterName": "string",
      "parameterValue": "string"
    }
  ],
  "slurmRest": {
    "mode": "string"
  }
},
"status": "string"
}
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### cluster

The cluster resource.

Type: [Cluster](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

You don't have permission to perform the action.

### Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.

- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

### **ConflictException**

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

#### Examples

- A cluster with the same name already exists.
- A cluster isn't in ACTIVE status.
- A cluster to delete is in an unstable state. For example, because it still has ACTIVE node groups or queues.
- A queue already exists in a cluster.

#### **resourceId**

The unique identifier of the resource that caused the conflict exception.

#### **resourceType**

The type or category of the resource that caused the conflict exception."

HTTP Status Code: 400

### **InternalServerError**

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

### **ResourceNotFoundException**

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

#### Examples

#### **resourceId**

The unique identifier of the resource that was not found.

**resourceType**

The type or category of the resource that was not found.

HTTP Status Code: 400

**ThrottlingException**

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

**retryAfterSeconds**

The number of seconds to wait before retrying the request.

HTTP Status Code: 400

**ValidationException**

The request isn't valid.

Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

**fieldList**

A list of fields or properties that failed validation.

**reason**

The specific reason or cause of the validation error.

HTTP Status Code: 400

**See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetComputeNodeGroup

Returns detailed information about a compute node group. This API action provides networking information, EC2 instance type, compute node group status, and scheduler (such as Slurm) configuration.

## Request Syntax

```
{
  "clusterIdentifier": "string",
  "computeNodeGroupIdentifier": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### clusterIdentifier

The name or ID of the cluster.

Type: String

Pattern: (pcs\_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{2,40})

Required: Yes

### computeNodeGroupIdentifier

The name or ID of the compute node group.

Type: String

Pattern: (pcs\_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{2,25})

Required: Yes

## Response Syntax

```
{
  "computeNodeGroup": {
```

```
"amiId": "string",
"arn": "string",
"clusterId": "string",
"createdAt": "string",
"customLaunchTemplate": {
  "id": "string",
  "version": "string"
},
"errorInfo": [
  {
    "code": "string",
    "message": "string"
  }
],
"iamInstanceProfileArn": "string",
"id": "string",
"instanceConfigs": [
  {
    "instanceType": "string"
  }
],
"modifiedAt": "string",
"name": "string",
"purchaseOption": "string",
"scalingConfiguration": {
  "maxInstanceCount": number,
  "minInstanceCount": number
},
"slurmConfiguration": {
  "slurmCustomSettings": [
    {
      "parameterName": "string",
      "parameterValue": "string"
    }
  ]
},
"spotOptions": {
  "allocationStrategy": "string"
},
"status": "string",
"subnetIds": [ "string" ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### computeNodeGroup

A compute node group associated with a cluster.

Type: [ComputeNodeGroup](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You don't have permission to perform the action.

#### Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

### **ConflictException**

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

#### Examples

- A cluster with the same name already exists.
- A cluster isn't in `ACTIVE` status.
- A cluster to delete is in an unstable state. For example, because it still has `ACTIVE` node groups or queues.
- A queue already exists in a cluster.

**resourceId**

The unique identifier of the resource that caused the conflict exception.

**resourceType**

The type or category of the resource that caused the conflict exception."

HTTP Status Code: 400

**InternalServerErrorException**

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

**ResourceNotFoundException**

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

Examples**resourceId**

The unique identifier of the resource that was not found.

**resourceType**

The type or category of the resource that was not found.

HTTP Status Code: 400

**ThrottlingException**

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

**retryAfterSeconds**

The number of seconds to wait before retrying the request.

HTTP Status Code: 400

**ValidationException**

The request isn't valid.

Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

**fieldList**

A list of fields or properties that failed validation.

**reason**

The specific reason or cause of the validation error.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetQueue

Returns detailed information about a queue. The information includes the compute node groups that the queue uses to schedule jobs.

## Request Syntax

```
{
  "clusterIdentifier": "string",
  "queueIdentifier": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### clusterIdentifier

The name or ID of the cluster of the queue.

Type: String

Pattern: (pcs\_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{2,40})

Required: Yes

### queueIdentifier

The name or ID of the queue.

Type: String

Pattern: (pcs\_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{2,25})

Required: Yes

## Response Syntax

```
{
  "queue": {
    "arn": "string",
```

```
"clusterId": "string",
"computeNodeGroupConfigurations": [
  {
    "computeNodeGroupId": "string"
  }
],
"createdAt": "string",
"errorInfo": [
  {
    "code": "string",
    "message": "string"
  }
],
"id": "string",
"modifiedAt": "string",
"name": "string",
"slurmConfiguration": {
  "slurmCustomSettings": [
    {
      "parameterName": "string",
      "parameterValue": "string"
    }
  ]
},
"status": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### queue

A queue resource.

Type: [Queue](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## AccessDeniedException

You don't have permission to perform the action.

### Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

## ConflictException

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

### Examples

- A cluster with the same name already exists.
- A cluster isn't in `ACTIVE` status.
- A cluster to delete is in an unstable state. For example, because it still has `ACTIVE` node groups or queues.
- A queue already exists in a cluster.

### **resourceId**

The unique identifier of the resource that caused the conflict exception.

### **resourceType**

The type or category of the resource that caused the conflict exception."

HTTP Status Code: 400

## InternalServerError

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

## ResourceNotFoundException

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

## Examples

### **resourceId**

The unique identifier of the resource that was not found.

### **resourceType**

The type or category of the resource that was not found.

HTTP Status Code: 400

## **ThrottlingException**

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

### **retryAfterSeconds**

The number of seconds to wait before retrying the request.

HTTP Status Code: 400

## **ValidationException**

The request isn't valid.

## Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

### **fieldList**

A list of fields or properties that failed validation.

### **reason**

The specific reason or cause of the validation error.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListClusters

Returns a list of running clusters in your account.

## Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### maxResults

The maximum number of results that are returned per call. You can use `nextToken` to obtain further pages of results. The default is 10 results, and the maximum allowed page size is 100 results. A value of 0 uses the default.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

### nextToken

The value of `nextToken` is a unique pagination token for each page of results returned. If `nextToken` is returned, there are more results available. Make the call again using the returned token to retrieve the next page. Keep all other arguments unchanged. Each pagination token expires after 24 hours. Using an expired pagination token returns an HTTP 400 `InvalidToken` error.

Type: String

Required: No

## Response Syntax

```
{
  "clusters": [
    {
      "arn": "string",
      "createdAt": "string",
      "id": "string",
      "modifiedAt": "string",
      "name": "string",
      "status": "string"
    }
  ],
  "nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### clusters

The list of clusters.

Type: Array of [ClusterSummary](#) objects

### nextToken

The value of `nextToken` is a unique pagination token for each page of results returned. If `nextToken` is returned, there are more results available. Make the call again using the returned token to retrieve the next page. Keep all other arguments unchanged. Each pagination token expires after 24 hours. Using an expired pagination token returns an HTTP 400 `InvalidToken` error.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## AccessDeniedException

You don't have permission to perform the action.

### Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

## ConflictException

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

### Examples

- A cluster with the same name already exists.
- A cluster isn't in `ACTIVE` status.
- A cluster to delete is in an unstable state. For example, because it still has `ACTIVE` node groups or queues.
- A queue already exists in a cluster.

### **resourceId**

The unique identifier of the resource that caused the conflict exception.

### **resourceType**

The type or category of the resource that caused the conflict exception."

HTTP Status Code: 400

## InternalServerError

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

## ResourceNotFoundException

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

## Examples

### **resourceId**

The unique identifier of the resource that was not found.

### **resourceType**

The type or category of the resource that was not found.

HTTP Status Code: 400

## **ThrottlingException**

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

### **retryAfterSeconds**

The number of seconds to wait before retrying the request.

HTTP Status Code: 400

## **ValidationException**

The request isn't valid.

## Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

### **fieldList**

A list of fields or properties that failed validation.

### **reason**

The specific reason or cause of the validation error.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListComputeNodeGroups

Returns a list of all compute node groups associated with a cluster.

## Request Syntax

```
{  
  "clusterIdentifier": "string",  
  "maxResults": number,  
  "nextToken": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### clusterIdentifier

The name or ID of the cluster to list compute node groups for.

Type: String

Pattern: (pcs\_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{2,40})

Required: Yes

### maxResults

The maximum number of results that are returned per call. You can use `nextToken` to obtain further pages of results. The default is 10 results, and the maximum allowed page size is 100 results. A value of 0 uses the default.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

### nextToken

The value of `nextToken` is a unique pagination token for each page of results returned. If `nextToken` is returned, there are more results available. Make the call again using the

returned token to retrieve the next page. Keep all other arguments unchanged. Each pagination token expires after 24 hours. Using an expired pagination token returns an HTTP 400 `InvalidToken` error.

Type: String

Required: No

## Response Syntax

```
{
  "computeNodeGroups": [
    {
      "arn": "string",
      "clusterId": "string",
      "createdAt": "string",
      "id": "string",
      "modifiedAt": "string",
      "name": "string",
      "status": "string"
    }
  ],
  "nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### computeNodeGroups

The list of compute node groups for the cluster.

Type: Array of [ComputeNodeGroupSummary](#) objects

### nextToken

The value of `nextToken` is a unique pagination token for each page of results returned.

If `nextToken` is returned, there are more results available. Make the call again using the returned token to retrieve the next page. Keep all other arguments unchanged. Each pagination

token expires after 24 hours. Using an expired pagination token returns an HTTP 400 `InvalidToken` error.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

You don't have permission to perform the action.

#### Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

### ConflictException

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

#### Examples

- A cluster with the same name already exists.
- A cluster isn't in ACTIVE status.
- A cluster to delete is in an unstable state. For example, because it still has ACTIVE node groups or queues.
- A queue already exists in a cluster.

#### **resourceId**

The unique identifier of the resource that caused the conflict exception.

#### **resourceType**

The type or category of the resource that caused the conflict exception."

HTTP Status Code: 400

### **InternalServerErrorException**

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

### **ResourceNotFoundException**

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

#### Examples

##### **resourceId**

The unique identifier of the resource that was not found.

##### **resourceType**

The type or category of the resource that was not found.

HTTP Status Code: 400

### **ThrottlingException**

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

##### **retryAfterSeconds**

The number of seconds to wait before retrying the request.

HTTP Status Code: 400

### **ValidationException**

The request isn't valid.

#### Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

**fieldList**

A list of fields or properties that failed validation.

**reason**

The specific reason or cause of the validation error.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListQueues

Returns a list of all queues associated with a cluster.

## Request Syntax

```
{  
  "clusterIdentifier": "string",  
  "maxResults": number,  
  "nextToken": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### clusterIdentifier

The name or ID of the cluster to list queues for.

Type: String

Pattern: (pcs\_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{2,40})

Required: Yes

### maxResults

The maximum number of results that are returned per call. You can use `nextToken` to obtain further pages of results. The default is 10 results, and the maximum allowed page size is 100 results. A value of 0 uses the default.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

### nextToken

The value of `nextToken` is a unique pagination token for each page of results returned. If `nextToken` is returned, there are more results available. Make the call again using the

returned token to retrieve the next page. Keep all other arguments unchanged. Each pagination token expires after 24 hours. Using an expired pagination token returns an HTTP 400 `InvalidToken` error.

Type: String

Required: No

## Response Syntax

```
{
  "nextToken": "string",
  "queues": [
    {
      "arn": "string",
      "clusterId": "string",
      "createdAt": "string",
      "id": "string",
      "modifiedAt": "string",
      "name": "string",
      "status": "string"
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### nextToken

The value of `nextToken` is a unique pagination token for each page of results returned. If `nextToken` is returned, there are more results available. Make the call again using the returned token to retrieve the next page. Keep all other arguments unchanged. Each pagination token expires after 24 hours. Using an expired pagination token returns an HTTP 400 `InvalidToken` error.

Type: String

## queues

The list of queues associated with the cluster.

Type: Array of [QueueSummary](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You don't have permission to perform the action.

#### Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

### **ConflictException**

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

#### Examples

- A cluster with the same name already exists.
- A cluster isn't in ACTIVE status.
- A cluster to delete is in an unstable state. For example, because it still has ACTIVE node groups or queues.
- A queue already exists in a cluster.

#### **resourceId**

The unique identifier of the resource that caused the conflict exception.

#### **resourceType**

The type or category of the resource that caused the conflict exception."

HTTP Status Code: 400

### **InternalServerErrorException**

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

### **ResourceNotFoundException**

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

#### Examples

##### **resourceId**

The unique identifier of the resource that was not found.

##### **resourceType**

The type or category of the resource that was not found.

HTTP Status Code: 400

### **ThrottlingException**

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

##### **retryAfterSeconds**

The number of seconds to wait before retrying the request.

HTTP Status Code: 400

### **ValidationException**

The request isn't valid.

#### Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

**fieldList**

A list of fields or properties that failed validation.

**reason**

The specific reason or cause of the validation error.

HTTP Status Code: 400

**See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListTagsForResource

Returns a list of all tags on an AWS PCS resource.

## Request Syntax

```
{  
  "resourceArn": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### resourceArn

The Amazon Resource Name (ARN) of the resource for which to list tags.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws.*:pcs:.*:[0-9]{12}:.*/[a-z0-9_\-]+`

Required: Yes

## Response Syntax

```
{  
  "tags": {  
    "string" : "string"  
  }  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### tags

1 or more tags added to the resource. Each tag consists of a tag key and tag value. The tag value is optional and can be an empty string.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ResourceNotFoundException**

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

#### Examples

##### **resourceId**

The unique identifier of the resource that was not found.

##### **resourceType**

The type or category of the resource that was not found.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# RegisterComputeNodeGroupInstance

## Important

This API action isn't intended for you to use.

AWS PCS uses this API action to register the compute nodes it launches in your account.

## Request Syntax

```
{
  "bootstrapId": "string",
  "clusterIdentifier": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### bootstrapId

The client-generated token to allow for retries.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: `[\S]+`

Required: Yes

### clusterIdentifier

The name or ID of the cluster to register the compute node group instance in.

Type: String

Pattern: `(pcs_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{2,40})`

Required: Yes

## Response Syntax

```
{
  "endpoints": [
    {
      "ipv6Address": "string",
      "port": "string",
      "privateIpAddress": "string",
      "publicIpAddress": "string",
      "type": "string"
    }
  ],
  "nodeID": "string",
  "sharedSecret": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### endpoints

The list of endpoints available for interaction with the scheduler.

Type: Array of [Endpoint](#) objects

### nodeID

The scheduler node ID for this instance.

Type: String

### sharedSecret

For the Slurm scheduler, this is the shared Munge key the scheduler uses to authenticate compute node group instances.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

You don't have permission to perform the action.

#### Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

### InternalServerError

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# TagResource

Adds or edits tags on an AWS PCS resource. Each tag consists of a tag key and a tag value. The tag key and tag value are case-sensitive strings. The tag value can be an empty (null) string. To add a tag, specify a new tag key and a tag value. To edit a tag, specify an existing tag key and a new tag value.

## Request Syntax

```
{
  "resourceArn": "string",
  "tags": {
    "string" : "string"
  }
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### resourceArn

The Amazon Resource Name (ARN) of the resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws.*:pcs:.*:[0-9]{12}:.*/[a-z0-9_\-]+`

Required: Yes

### tags

1 or more tags added to the resource. Each tag consists of a tag key and tag value. The tag value is optional and can be an empty string.

Type: String to string map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ResourceNotFoundException

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

#### Examples

##### **resourceId**

The unique identifier of the resource that was not found.

##### **resourceType**

The type or category of the resource that was not found.

HTTP Status Code: 400

### ServiceQuotaExceededException

You exceeded your service quota. Service quotas, also referred to as limits, are the maximum number of service resources or operations for your AWS account. To learn how to increase your service quota, see [Requesting a quota increase](#) in the *Service Quotas User Guide*

#### Examples

- The max number of clusters or queues has been reached for the account.
- The max number of compute node groups has been reached for the associated cluster.
- The total of maxInstances across all compute node groups has been reached for associated cluster.

**quotaCode**

The **quota code** of the service quota that was exceeded.

**resourceId**

The unique identifier of the resource that caused the quota to be exceeded.

**resourceType**

The type or category of the resource that caused the quota to be exceeded.

**serviceCode**

The service code associated with the quota that was exceeded.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UntagResource

Deletes tags from an AWS PCS resource. To delete a tag, specify the tag key and the Amazon Resource Name (ARN) of the AWS PCS resource.

## Request Syntax

```
{
  "resourceArn": "string",
  "tagKeys": [ "string" ]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [resourceArn](#)

The Amazon Resource Name (ARN) of the resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws.*:pcs:.*:[0-9]{12}:.*/[a-z0-9_\-]+`

Required: Yes

### [tagKeys](#)

1 or more tag keys to remove from the resource. Specify only tag keys and not tag values.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 200 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ResourceNotFoundException

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

#### Examples

##### **resourceId**

The unique identifier of the resource that was not found.

##### **resourceType**

The type or category of the resource that was not found.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

# UpdateCluster

Updates a cluster configuration. You can modify Slurm scheduler settings, accounting configuration, and security groups for an existing cluster.

## Note

You can only update clusters that are in ACTIVE, UPDATE\_FAILED, or SUSPENDED state. All associated resources (queues and compute node groups) must be in ACTIVE state before you can update the cluster.

## Request Syntax

```
{
  "clientToken": "string",
  "clusterIdentifier": "string",
  "slurmConfiguration": {
    "accounting": {
      "defaultPurgeTimeInDays": number,
      "mode": "string"
    },
    "cgroupCustomSettings": [
      {
        "parameterName": "string",
        "parameterValue": "string"
      }
    ],
    "scaleDownIdleTimeInSeconds": number,
    "slurmCustomSettings": [
      {
        "parameterName": "string",
        "parameterValue": "string"
      }
    ],
    "slurmdbdCustomSettings": [
      {
        "parameterName": "string",
        "parameterValue": "string"
      }
    ],
  },
}
```

```
    "slurmRest": {
      "mode": "string"
    }
  }
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [clientToken](#)

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, the subsequent retries with the same client token return the result from the original successful request and they have no additional effect. If you don't specify a client token, the AWS CLI and SDK automatically generate 1 for you.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 100.

Required: No

### [clusterIdentifier](#)

The name or ID of the cluster to update.

Type: String

Pattern: (pcs\_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{2,40})

Required: Yes

### [slurmConfiguration](#)

Additional options related to the Slurm scheduler.

Type: [UpdateClusterSlurmConfigurationRequest](#) object

Required: No

## Response Syntax

```
{
  "cluster": {
    "arn": "string",
    "createdAt": "string",
    "endpoints": [
      {
        "ipv6Address": "string",
        "port": "string",
        "privateIpAddress": "string",
        "publicIpAddress": "string",
        "type": "string"
      }
    ],
    "errorInfo": [
      {
        "code": "string",
        "message": "string"
      }
    ],
    "id": "string",
    "modifiedAt": "string",
    "name": "string",
    "networking": {
      "networkType": "string",
      "securityGroupIds": [ "string" ],
      "subnetIds": [ "string" ]
    },
    "scheduler": {
      "type": "string",
      "version": "string"
    },
    "size": "string",
    "slurmConfiguration": {
      "accounting": {
        "defaultPurgeTimeInDays": number,
        "mode": "string"
      },
      "authKey": {
        "secretArn": "string",
        "secretVersion": "string"
      }
    },
  },
}
```

```
    "cgroupCustomSettings": [
      {
        "parameterName": "string",
        "parameterValue": "string"
      }
    ],
    "jwtAuth": {
      "jwtKey": {
        "secretArn": "string",
        "secretVersion": "string"
      }
    },
    "scaleDownIdleTimeInSeconds": number,
    "slurmCustomSettings": [
      {
        "parameterName": "string",
        "parameterValue": "string"
      }
    ],
    "slurmdbdCustomSettings": [
      {
        "parameterName": "string",
        "parameterValue": "string"
      }
    ],
    "slurmRest": {
      "mode": "string"
    }
  },
  "status": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### cluster

The cluster resource and configuration.

Type: [Cluster](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

You don't have permission to perform the action.

#### Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

### ConflictException

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

#### Examples

- A cluster with the same name already exists.
- A cluster isn't in ACTIVE status.
- A cluster to delete is in an unstable state. For example, because it still has ACTIVE node groups or queues.
- A queue already exists in a cluster.

#### **resourceId**

The unique identifier of the resource that caused the conflict exception.

#### **resourceType**

The type or category of the resource that caused the conflict exception."

HTTP Status Code: 400

### InternalServerError

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

### **ResourceNotFoundException**

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

#### Examples

##### **resourceId**

The unique identifier of the resource that was not found.

##### **resourceType**

The type or category of the resource that was not found.

HTTP Status Code: 400

### **ThrottlingException**

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

##### **retryAfterSeconds**

The number of seconds to wait before retrying the request.

HTTP Status Code: 400

### **ValidationException**

The request isn't valid.

#### Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

##### **fieldList**

A list of fields or properties that failed validation.

**reason**

The specific reason or cause of the validation error.

HTTP Status Code: 400

**See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateComputeNodeGroup

Updates a compute node group. You can update many of the fields related to your compute node group including the configurations for networking, compute nodes, and settings specific to your scheduler (such as Slurm).

## Request Syntax

```
{
  "amiId": "string",
  "clientToken": "string",
  "clusterIdentifier": "string",
  "computeNodeGroupIdentifier": "string",
  "customLaunchTemplate": {
    "id": "string",
    "version": "string"
  },
  "iamInstanceProfileArn": "string",
  "purchaseOption": "string",
  "scalingConfiguration": {
    "maxInstanceCount": number,
    "minInstanceCount": number
  },
  "slurmConfiguration": {
    "slurmCustomSettings": [
      {
        "parameterName": "string",
        "parameterValue": "string"
      }
    ]
  },
  "spotOptions": {
    "allocationStrategy": "string"
  },
  "subnetIds": [ "string" ]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

## amiId

The ID of the Amazon Machine Image (AMI) that AWS PCS uses to launch instances. If not provided, AWS PCS uses the AMI ID specified in the custom launch template.

Type: String

Pattern: `ami-[a-z0-9]+`

Required: No

## clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, the subsequent retries with the same client token return the result from the original successful request and they have no additional effect. If you don't specify a client token, the AWS CLI and SDK automatically generate 1 for you.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 100.

Required: No

## clusterIdentifier

The name or ID of the cluster of the compute node group.

Type: String

Pattern: `(pcs_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{2,40})`

Required: Yes

## computeNodeGroupIdentifier

The name or ID of the compute node group.

Type: String

Pattern: `(pcs_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{2,25})`

Required: Yes

## [customLaunchTemplate](#)

An Amazon EC2 launch template AWS PCS uses to launch compute nodes.

Type: [CustomLaunchTemplate](#) object

Required: No

## [iamInstanceProfileArn](#)

The Amazon Resource Name (ARN) of the IAM instance profile used to pass an IAM role when launching EC2 instances. The role contained in your instance profile must have the `pcs:RegisterComputeNodeGroupInstance` permission and the role name must start with `AWSPCS` or must have the path `/aws-pcs/`. For more information, see [IAM instance profiles for AWS PCS](#) in the *AWS PCS User Guide*.

Type: String

Pattern: `arn:aws([a-zA-Z-]{0,10})?:iam::[0-9]{12}:instance-profile/([!-~]{1,510}/)?([\w+=, .@-]{1,128})`

Required: No

## [purchaseOption](#)

Specifies how EC2 instances are purchased on your behalf. AWS PCS supports On-Demand Instances, Spot Instances, and Amazon EC2 Capacity Blocks for ML. For more information, see [Amazon EC2 billing and purchasing options](#) in the *Amazon Elastic Compute Cloud User Guide*. For more information about AWS PCS support for Capacity Blocks, see [Using Amazon EC2 Capacity Blocks for ML with AWS PCS](#) in the *AWS PCS User Guide*. If you don't provide this option, it defaults to On-Demand.

Type: String

Valid Values: ONDEMAND | SPOT | CAPACITY\_BLOCK

Required: No

## [scalingConfiguration](#)

Specifies the boundaries of the compute node group auto scaling.

Type: [ScalingConfigurationRequest](#) object

Required: No

### slurmConfiguration

Additional options related to the Slurm scheduler.

Type: [UpdateComputeNodeGroupSlurmConfigurationRequest](#) object

Required: No

### spotOptions

Additional configuration when you specify SPOT as the purchaseOption for the CreateComputeNodeGroup API action.

Type: [SpotOptions](#) object

Required: No

### subnetIds

The list of subnet IDs where the compute node group provisions instances. The subnets must be in the same VPC as the cluster.

Type: Array of strings

Required: No

## Response Syntax

```
{
  "computeNodeGroup": {
    "amiId": "string",
    "arn": "string",
    "clusterId": "string",
    "createdAt": "string",
    "customLaunchTemplate": {
      "id": "string",
      "version": "string"
    },
    "errorInfo": [
      {
        "code": "string",
        "message": "string"
      }
    ]
  }
}
```

```
    }
  ],
  "iamInstanceProfileArn": "string",
  "id": "string",
  "instanceConfigs": [
    {
      "instanceType": "string"
    }
  ],
  "modifiedAt": "string",
  "name": "string",
  "purchaseOption": "string",
  "scalingConfiguration": {
    "maxInstanceCount": number,
    "minInstanceCount": number
  },
  "slurmConfiguration": {
    "slurmCustomSettings": [
      {
        "parameterName": "string",
        "parameterValue": "string"
      }
    ]
  },
  "spotOptions": {
    "allocationStrategy": "string"
  },
  "status": "string",
  "subnetIds": [ "string" ]
}
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### computeNodeGroup

A compute node group associated with a cluster.

Type: [ComputeNodeGroup](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

You don't have permission to perform the action.

#### Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

### ConflictException

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

#### Examples

- A cluster with the same name already exists.
- A cluster isn't in ACTIVE status.
- A cluster to delete is in an unstable state. For example, because it still has ACTIVE node groups or queues.
- A queue already exists in a cluster.

#### **resourceId**

The unique identifier of the resource that caused the conflict exception.

#### **resourceType**

The type or category of the resource that caused the conflict exception."

HTTP Status Code: 400

### InternalServerError

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

### **ResourceNotFoundException**

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

#### Examples

##### **resourceId**

The unique identifier of the resource that was not found.

##### **resourceType**

The type or category of the resource that was not found.

HTTP Status Code: 400

### **ServiceQuotaExceededException**

You exceeded your service quota. Service quotas, also referred to as limits, are the maximum number of service resources or operations for your AWS account. To learn how to increase your service quota, see [Requesting a quota increase](#) in the *Service Quotas User Guide*

#### Examples

- The max number of clusters or queues has been reached for the account.
- The max number of compute node groups has been reached for the associated cluster.
- The total of maxInstances across all compute node groups has been reached for associated cluster.

##### **quotaCode**

The **quota code** of the service quota that was exceeded.

##### **resourceId**

The unique identifier of the resource that caused the quota to be exceeded.

##### **resourceType**

The type or category of the resource that caused the quota to be exceeded.

##### **serviceCode**

The service code associated with the quota that was exceeded.

HTTP Status Code: 400

### **ThrottlingException**

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

#### **retryAfterSeconds**

The number of seconds to wait before retrying the request.

HTTP Status Code: 400

### **ValidationException**

The request isn't valid.

#### Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

#### **fieldList**

A list of fields or properties that failed validation.

#### **reason**

The specific reason or cause of the validation error.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateQueue

Updates the compute node group configuration of a queue. Use this API to change the compute node groups that the queue can send jobs to.

## Request Syntax

```
{
  "clientToken": "string",
  "clusterIdentifier": "string",
  "computeNodeGroupConfigurations": [
    {
      "computeNodeId": "string"
    }
  ],
  "queueIdentifier": "string",
  "slurmConfiguration": {
    "slurmCustomSettings": [
      {
        "parameterName": "string",
        "parameterValue": "string"
      }
    ]
  }
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, the subsequent retries with the same client token return the result from the original successful request and they have no additional effect. If you don't specify a client token, the AWS CLI and SDK automatically generate 1 for you.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 100.

Required: No

### clusterIdentifier

The name or ID of the cluster of the queue.

Type: String

Pattern: (pcs\_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{2,40})

Required: Yes

### computeNodeGroupConfigurations

The list of compute node group configurations to associate with the queue. Queues assign jobs to associated compute node groups.

Type: Array of [ComputeNodeGroupConfiguration](#) objects

Required: No

### queueIdentifier

The name or ID of the queue.

Type: String

Pattern: (pcs\_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{2,25})

Required: Yes

### slurmConfiguration

Additional options related to the Slurm scheduler.

Type: [UpdateQueueSlurmConfigurationRequest](#) object

Required: No

## Response Syntax

```
{
  "queue": {
    "arn": "string",
```

```
"clusterId": "string",
"computeNodeGroupConfigurations": [
  {
    "computeNodeGroupId": "string"
  }
],
"createdAt": "string",
"errorInfo": [
  {
    "code": "string",
    "message": "string"
  }
],
"id": "string",
"modifiedAt": "string",
"name": "string",
"slurmConfiguration": {
  "slurmCustomSettings": [
    {
      "parameterName": "string",
      "parameterValue": "string"
    }
  ]
},
"status": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### queue

A queue resource.

Type: [Queue](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## AccessDeniedException

You don't have permission to perform the action.

### Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

## ConflictException

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

### Examples

- A cluster with the same name already exists.
- A cluster isn't in ACTIVE status.
- A cluster to delete is in an unstable state. For example, because it still has ACTIVE node groups or queues.
- A queue already exists in a cluster.

### **resourceId**

The unique identifier of the resource that caused the conflict exception.

### **resourceType**

The type or category of the resource that caused the conflict exception."

HTTP Status Code: 400

## InternalServerError

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

## ResourceNotFoundException

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

## Examples

### **resourceId**

The unique identifier of the resource that was not found.

### **resourceType**

The type or category of the resource that was not found.

HTTP Status Code: 400

## **ServiceQuotaExceededException**

You exceeded your service quota. Service quotas, also referred to as limits, are the maximum number of service resources or operations for your AWS account. To learn how to increase your service quota, see [Requesting a quota increase](#) in the *Service Quotas User Guide*

## Examples

- The max number of clusters or queues has been reached for the account.
- The max number of compute node groups has been reached for the associated cluster.
- The total of maxInstances across all compute node groups has been reached for associated cluster.

### **quotaCode**

The **quota code** of the service quota that was exceeded.

### **resourceId**

The unique identifier of the resource that caused the quota to be exceeded.

### **resourceType**

The type or category of the resource that caused the quota to be exceeded.

### **serviceCode**

The service code associated with the quota that was exceeded.

HTTP Status Code: 400

## **ThrottlingException**

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

## **retryAfterSeconds**

The number of seconds to wait before retrying the request.

HTTP Status Code: 400

## **ValidationException**

The request isn't valid.

### Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

### **fieldList**

A list of fields or properties that failed validation.

### **reason**

The specific reason or cause of the validation error.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# Data Types

The AWS Parallel Computing Service API contains several data types that various actions use. This section describes each data type in detail.

## Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [Accounting](#)
- [AccountingRequest](#)
- [CgroupCustomSetting](#)
- [Cluster](#)
- [ClusterSlurmConfiguration](#)
- [ClusterSlurmConfigurationRequest](#)
- [ClusterSummary](#)
- [ComputeNodeGroup](#)
- [ComputeNodeGroupConfiguration](#)
- [ComputeNodeGroupSlurmConfiguration](#)
- [ComputeNodeGroupSlurmConfigurationRequest](#)
- [ComputeNodeGroupSummary](#)
- [CustomLaunchTemplate](#)
- [Endpoint](#)
- [ErrorInfo](#)
- [InstanceConfig](#)
- [JwtAuth](#)
- [JwtKey](#)
- [Networking](#)
- [NetworkingRequest](#)

- [Queue](#)
- [QueueSlurmConfiguration](#)
- [QueueSlurmConfigurationRequest](#)
- [QueueSummary](#)
- [ScalingConfiguration](#)
- [ScalingConfigurationRequest](#)
- [Scheduler](#)
- [SchedulerRequest](#)
- [SlurmAuthKey](#)
- [SlurmCustomSetting](#)
- [SlurmdbdCustomSetting](#)
- [SlurmRest](#)
- [SlurmRestRequest](#)
- [SpotOptions](#)
- [UpdateAccountingRequest](#)
- [UpdateClusterSlurmConfigurationRequest](#)
- [UpdateComputeNodeGroupSlurmConfigurationRequest](#)
- [UpdateQueueSlurmConfigurationRequest](#)
- [UpdateSlurmRestRequest](#)
- [ValidationExceptionField](#)

# Accounting

The accounting configuration includes configurable settings for Slurm accounting. It's a property of the **ClusterSlurmConfiguration** object.

## Contents

### mode

The default value for mode is NONE. A value of STANDARD means Slurm accounting is enabled.

Type: String

Valid Values: STANDARD | NONE

Required: Yes

### defaultPurgeTimeInDays

The default value for all purge settings for `slurmdbd.conf`. For more information, see the [slurmdbd.conf documentation at SchedMD](#).

The default value for `defaultPurgeTimeInDays` is -1.

A value of -1 means there is no purge time and records persist as long as the cluster exists.

#### Important

0 isn't a valid value.

Type: Integer

Valid Range: Minimum value of -1. Maximum value of 10000.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# AccountingRequest

The accounting configuration includes configurable settings for Slurm accounting. It's a property of the **ClusterSlurmConfiguration** object.

## Contents

### mode

The default value for mode is NONE. A value of STANDARD means Slurm accounting is enabled.

Type: String

Valid Values: STANDARD | NONE

Required: Yes

### defaultPurgeTimeInDays

The default value for all purge settings for `slurmdbd.conf`. For more information, see the [slurmdbd.conf documentation at SchedMD](#).

The default value for `defaultPurgeTimeInDays` is -1.

A value of -1 means there is no purge time and records persist as long as the cluster exists.

#### Important

0 isn't a valid value.

Type: Integer

Valid Range: Minimum value of -1. Maximum value of 10000.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# CgroupCustomSetting

Additional settings that directly map to Cgroup settings.

## Important

AWS PCS supports a subset of Cgroup settings. For more information, see [Configuring custom Cgroup settings in AWS PCS](#) in the *AWS PCS User Guide*.

## Contents

### parameterName

AWS PCS supports custom Cgroup settings for clusters. For more information, see [Configuring custom Cgroup settings in AWS PCS](#) in the *AWS PCS User Guide*.

Type: String

Required: Yes

### parameterValue

The values for the configured Cgroup settings.

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Cluster

The cluster resource and configuration.

## Contents

### **arn**

The unique Amazon Resource Name (ARN) of the cluster.

Type: String

Required: Yes

### **createdAt**

The date and time the resource was created.

Type: Timestamp

Required: Yes

### **id**

The generated unique ID of the cluster.

Type: String

Required: Yes

### **modifiedAt**

The date and time the resource was modified.

Type: Timestamp

Required: Yes

### **name**

The name that identifies the cluster.

Type: String

Required: Yes

## networking

The networking configuration for the cluster's control plane.

Type: [Networking](#) object

Required: Yes

## scheduler

The cluster management and job scheduling software associated with the cluster.

Type: [Scheduler](#) object

Required: Yes

## size

The size of the cluster.

- SMALL: 32 compute nodes and 256 jobs
- MEDIUM: 512 compute nodes and 8192 jobs
- LARGE: 2048 compute nodes and 16,384 jobs

Type: String

Valid Values: SMALL | MEDIUM | LARGE

Required: Yes

## status

The provisioning status of the cluster.

### Note

The provisioning status doesn't indicate the overall health of the cluster.

### Important

The resource enters the SUSPENDING and SUSPENDED states when the scheduler is beyond end of life and we have suspended the cluster. When in these states, you can't use the cluster. The cluster controller is down and all compute instances are terminated.

The resources still count toward your service quotas. You can delete a resource if its status is SUSPENDED. For more information, see [Frequently asked questions about Slurm versions in AWS PCS](#) in the *AWS PCS User Guide*.

Type: String

Valid Values: CREATING | ACTIVE | UPDATING | DELETING | CREATE\_FAILED | DELETE\_FAILED | UPDATE\_FAILED | SUSPENDING | SUSPENDED | RESUMING

Required: Yes

### endpoints

The list of endpoints available for interaction with the scheduler.

Type: Array of [Endpoint](#) objects

Required: No

### errorInfo

The list of errors that occurred during cluster provisioning.

Type: Array of [ErrorInfo](#) objects

Required: No

### slurmConfiguration

Additional options related to the Slurm scheduler.

Type: [ClusterSlurmConfiguration](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

# ClusterSlurmConfiguration

Additional options related to the Slurm scheduler.

## Contents

### accounting

The accounting configuration includes configurable settings for Slurm accounting.

Type: [Accounting](#) object

Required: No

### authKey

The shared Slurm key for authentication, also known as the **cluster secret**.

Type: [SlurmAuthKey](#) object

Required: No

### cgroupCustomSettings

Additional Cgroup-specific configuration that directly maps to Cgroup settings.

Type: Array of [CgroupCustomSetting](#) objects

Required: No

### jwtAuth

The JWT authentication configuration for Slurm REST API access.

Type: [JwtAuth](#) object

Required: No

### scaleDownIdleTimeInSeconds

The time (in seconds) before an idle node is scaled down.

Default: 600

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 10000000.

Required: No

### **slurmCustomSettings**

Additional Slurm-specific configuration that directly maps to Slurm settings.

Type: Array of [SlurmCustomSetting](#) objects

Required: No

### **slurmdbdCustomSettings**

Additional SlurmDBD-specific configuration that directly maps to SlurmDBD settings.

Type: Array of [SlurmdbdCustomSetting](#) objects

Required: No

### **slurmRest**

The Slurm REST API configuration for the cluster.

Type: [SlurmRest](#) object

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ClusterSlurmConfigurationRequest

Additional options related to the Slurm scheduler.

## Contents

### accounting

The accounting configuration includes configurable settings for Slurm accounting.

Type: [AccountingRequest](#) object

Required: No

### cgroupCustomSettings

Additional Cgroup-specific configuration that directly maps to Cgroup settings.

Type: Array of [CgroupCustomSetting](#) objects

Required: No

### scaleDownIdleTimeInSeconds

The time (in seconds) before an idle node is scaled down.

Default: 600

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 10000000.

Required: No

### slurmCustomSettings

Additional Slurm-specific configuration that directly maps to Slurm settings.

Type: Array of [SlurmCustomSetting](#) objects

Required: No

### slurmdbdCustomSettings

Additional SlurmDBD-specific configuration that directly maps to SlurmDBD settings.

Type: Array of [SlurmdbdCustomSetting](#) objects

Required: No

### **slurmRest**

The Slurm REST API configuration for the cluster.

Type: [SlurmRestRequest](#) object

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ClusterSummary

The object returned by the `ListClusters` API action.

## Contents

### **arn**

The unique Amazon Resource Name (ARN) of the cluster.

Type: String

Required: Yes

### **createdAt**

The date and time the resource was created.

Type: Timestamp

Required: Yes

### **id**

The generated unique ID of the cluster.

Type: String

Required: Yes

### **modifiedAt**

The date and time the resource was modified.

Type: Timestamp

Required: Yes

### **name**

The name that identifies the cluster.

Type: String

Required: Yes

## status

The provisioning status of the cluster.

### Note

The provisioning status doesn't indicate the overall health of the cluster.

### Important

The resource enters the SUSPENDING and SUSPENDED states when the scheduler is beyond end of life and we have suspended the cluster. When in these states, you can't use the cluster. The cluster controller is down and all compute instances are terminated. The resources still count toward your service quotas. You can delete a resource if its status is SUSPENDED. For more information, see [Frequently asked questions about Slurm versions in AWS PCS](#) in the *AWS PCS User Guide*.

Type: String

Valid Values: CREATING | ACTIVE | UPDATING | DELETING | CREATE\_FAILED | DELETE\_FAILED | UPDATE\_FAILED | SUSPENDING | SUSPENDED | RESUMING

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ComputeNodeGroup

A compute node group associated with a cluster.

## Contents

### arn

The unique Amazon Resource Name (ARN) of the compute node group.

Type: String

Required: Yes

### clusterId

The ID of the cluster of the compute node group.

Type: String

Required: Yes

### createdAt

The date and time the resource was created.

Type: Timestamp

Required: Yes

### customLaunchTemplate

An Amazon EC2 launch template AWS PCS uses to launch compute nodes.

Type: [CustomLaunchTemplate](#) object

Required: Yes

### iamInstanceProfileArn

The Amazon Resource Name (ARN) of the IAM instance profile used to pass an IAM role when launching EC2 instances. The role contained in your instance profile must have the `pcs:RegisterComputeNodeGroupInstance` permission and the role name must start with `AWSPCS` or must have the path `/aws-pcs/`. For more information, see [IAM instance profiles for AWS PCS](#) in the *AWS PCS User Guide*.

Type: String

Pattern: `arn:aws([a-zA-Z-]{0,10})?:iam::[0-9]{12}:instance-profile/([!~]{1,510}/)?([\w+=,.\e-]{1,128})`

Required: Yes

## **id**

The generated unique ID of the compute node group.

Type: String

Required: Yes

## **instanceConfigs**

A list of EC2 instance configurations that AWS PCS can provision in the compute node group.

Type: Array of [InstanceConfig](#) objects

Required: Yes

## **modifiedAt**

The date and time the resource was modified.

Type: Timestamp

Required: Yes

## **name**

The name that identifies the compute node group.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 25.

Pattern: `(?!pcs_)^[A-Za-z][A-Za-z0-9-]+`

Required: Yes

## **scalingConfiguration**

Specifies the boundaries of the compute node group auto scaling.

Type: [ScalingConfiguration](#) object

Required: Yes

### status

The provisioning status of the compute node group.

#### Note

The provisioning status doesn't indicate the overall health of the compute node group.

#### Important

The resource enters the SUSPENDING and SUSPENDED states when the scheduler is beyond end of life and we have suspended the cluster. When in these states, you can't use the cluster. The cluster controller is down and all compute instances are terminated. The resources still count toward your service quotas. You can delete a resource if its status is SUSPENDED. For more information, see [Frequently asked questions about Slurm versions in AWS PCS](#) in the *AWS PCS User Guide*.

Type: String

Valid Values: CREATING | ACTIVE | UPDATING | DELETING | CREATE\_FAILED | DELETE\_FAILED | UPDATE\_FAILED | DELETED | SUSPENDING | SUSPENDED | RESUMING

Required: Yes

### subnetIds

The list of subnet IDs where instances are provisioned by the compute node group. The subnets must be in the same VPC as the cluster.

Type: Array of strings

Array Members: Minimum number of 1 item.

Pattern: subnet-\w{8,17}

Required: Yes

## amiId

The ID of the Amazon Machine Image (AMI) that AWS PCS uses to launch instances. If not provided, AWS PCS uses the AMI ID specified in the custom launch template.

Type: String

Pattern: ami - [a-z0-9]+

Required: No

## errorInfo

The list of errors that occurred during compute node group provisioning.

Type: Array of [ErrorInfo](#) objects

Required: No

## purchaseOption

Specifies how EC2 instances are purchased on your behalf. AWS PCS supports On-Demand Instances, Spot Instances, and Amazon EC2 Capacity Blocks for ML. For more information, see [Amazon EC2 billing and purchasing options](#) in the *Amazon Elastic Compute Cloud User Guide*. For more information about AWS PCS support for Capacity Blocks, see [Using Amazon EC2 Capacity Blocks for ML with AWS PCS](#) in the *AWS PCS User Guide*. If you don't provide this option, it defaults to On-Demand.

Type: String

Valid Values: ONDEMAND | SPOT | CAPACITY\_BLOCK

Required: No

## slurmConfiguration

Additional options related to the Slurm scheduler.

Type: [ComputeNodeGroupSlurmConfiguration](#) object

Required: No

## spotOptions

Additional configuration when you specify SPOT as the purchaseOption for the CreateComputeNodeGroup API action.

Type: [SpotOptions](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ComputeNodeGroupConfiguration

The compute node group configuration for a queue.

## Contents

### `computeNodeGroupId`

The compute node group ID for the compute node group configuration.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ComputeNodeGroupSlurmConfiguration

Additional options related to the Slurm scheduler.

## Contents

### **slurmCustomSettings**

Additional Slurm-specific configuration that directly maps to Slurm settings.

Type: Array of [SlurmCustomSetting](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ComputeNodeGroupSlurmConfigurationRequest

Additional options related to the Slurm scheduler.

## Contents

### **slurmCustomSettings**

Additional Slurm-specific configuration that directly maps to Slurm settings.

Type: Array of [SlurmCustomSetting](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ComputeNodeGroupSummary

The object returned by the `ListComputeNodeGroups` API action.

## Contents

### **arn**

The unique Amazon Resource Name (ARN) of the compute node group.

Type: String

Required: Yes

### **clusterId**

The ID of the cluster of the compute node group.

Type: String

Required: Yes

### **createdAt**

The date and time the resource was created.

Type: Timestamp

Required: Yes

### **id**

The generated unique ID of the compute node group.

Type: String

Required: Yes

### **modifiedAt**

The date and time the resource was modified.

Type: Timestamp

Required: Yes

## name

The name that identifies the compute node group.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 25.

Pattern: (?!pcs\_)^[A-Za-z][A-Za-z0-9-]+

Required: Yes

## status

The provisioning status of the compute node group.

### Note

The provisioning status doesn't indicate the overall health of the compute node group.

### Important

The resource enters the SUSPENDING and SUSPENDED states when the scheduler is beyond end of life and we have suspended the cluster. When in these states, you can't use the cluster. The cluster controller is down and all compute instances are terminated. The resources still count toward your service quotas. You can delete a resource if its status is SUSPENDED. For more information, see [Frequently asked questions about Slurm versions in AWS PCS](#) in the *AWS PCS User Guide*.

Type: String

Valid Values: CREATING | ACTIVE | UPDATING | DELETING | CREATE\_FAILED | DELETE\_FAILED | UPDATE\_FAILED | DELETED | SUSPENDING | SUSPENDED | RESUMING

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# CustomLaunchTemplate

An Amazon EC2 launch template AWS PCS uses to launch compute nodes.

## Contents

### id

The ID of the EC2 launch template to use to provision instances.

Example: 1t-xxxx

Type: String

Required: Yes

### version

The version of the EC2 launch template to use to provision instances.

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Endpoint

An endpoint available for interaction with the scheduler.

## Contents

### port

The endpoint's connection port number.

Example: 1234

Type: String

Required: Yes

### privateIpAddress

For clusters that use IPv4, this is the endpoint's private IP address.

Example: 10.1.2.3

For clusters configured to use IPv6, this is an empty string.

Type: String

Required: Yes

### type

Indicates the type of endpoint running at the specific IP address.

Type: String

Valid Values: SLURMCTLD | SLURMDBD | SLURMRESTD

Required: Yes

### ipv6Address

The endpoint's IPv6 address.

Example: 2001:db8::1

Type: String

Required: No

### **publicIpAddress**

The endpoint's public IP address.

Example: 192.0.2.1

Type: String

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ErrorInfo

An error that occurred during resource creation.

## Contents

### code

The short-form error code.

Type: String

Required: No

### message

The detailed error information.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# InstanceConfig

An EC2 instance configuration AWS PCS uses to launch compute nodes.

## Contents

### instanceType

The EC2 instance type that AWS PCS can provision in the compute node group.

Example: `t2.xlarge`

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# JwtAuth

The JWT authentication configuration for Slurm REST API access.

## Contents

### jwtKey

The JWT key for Slurm REST API authentication.

Type: [JwtKey](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# JwtKey

The JWT key stored in AWS Secrets Manager for Slurm REST API authentication.

## Contents

### **secretArn**

The Amazon Resource Name (ARN) of the AWS Secrets Manager secret containing the JWT key.

Type: String

Required: Yes

### **secretVersion**

The version of the AWS Secrets Manager secret containing the JWT key.

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Networking

The networking configuration for the cluster's control plane.

## Contents

### networkType

The IP address version the cluster uses. The default is IPV4.

Type: String

Valid Values: IPV4 | IPV6

Required: No

### securityGroupIds

The list of security group IDs associated with the Elastic Network Interface (ENI) created in subnets.

The following rules are required:

- Inbound rule 1
  - Protocol: All
  - Ports: All
  - Source: Self
- Outbound rule 1
  - Protocol: All
  - Ports: All
  - Destination: 0.0.0.0/0 (IPv4) or ::/0 (IPv6)
- Outbound rule 2
  - Protocol: All
  - Ports: All
  - Destination: Self

Type: Array of strings

Pattern: sg-\w{8,17}

Required: No

## **subnetIds**

The ID of the subnet where AWS PCS creates an Elastic Network Interface (ENI) to enable communication between managed controllers and AWS PCS resources. The subnet must have an available IP address, cannot reside in AWS Outposts, AWS Wavelength, or an AWS Local Zone.

Example: subnet-abcd1234

Type: Array of strings

Array Members: Minimum number of 1 item.

Pattern: subnet-\w{8,17}

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# NetworkingRequest

The networking configuration for the cluster's control plane.

## Contents

### networkType

The IP address version the cluster uses. The default is IPV4.

Type: String

Valid Values: IPV4 | IPV6

Required: No

### securityGroupIds

A list of security group IDs associated with the Elastic Network Interface (ENI) created in subnets.

Type: Array of strings

Pattern: sg-\w{8,17}

Required: No

### subnetIds

The list of subnet IDs where AWS PCS creates an Elastic Network Interface (ENI) to enable communication between managed controllers and AWS PCS resources. Subnet IDs have the form subnet-0123456789abcdef0.

Subnets can't be in AWS Outposts, AWS Wavelength or an AWS Local Zone.

#### Note

AWS PCS currently supports only 1 subnet in this list.

Type: Array of strings

Array Members: Minimum number of 1 item.

Pattern: subnet-\w{8,17}

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Queue

A queue resource.

## Contents

### **arn**

The unique Amazon Resource Name (ARN) of the queue.

Type: String

Required: Yes

### **clusterId**

The ID of the cluster of the queue.

Type: String

Required: Yes

### **computeNodeGroupConfigurations**

The list of compute node group configurations associated with the queue. Queues assign jobs to associated compute node groups.

Type: Array of [ComputeNodeGroupConfiguration](#) objects

Required: Yes

### **createdAt**

The date and time the resource was created.

Type: Timestamp

Required: Yes

### **id**

The generated unique ID of the queue.

Type: String

Required: Yes

### **modifiedAt**

The date and time the resource was modified.

Type: Timestamp

Required: Yes

### **name**

The name that identifies the queue.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 25.

Pattern: (?!pcs\_)^[A-Za-z][A-Za-z0-9-]+

Required: Yes

### **status**

The provisioning status of the queue.

#### **Note**

The provisioning status doesn't indicate the overall health of the queue.

#### **Important**

The resource enters the SUSPENDING and SUSPENDED states when the scheduler is beyond end of life and we have suspended the cluster. When in these states, you can't use the cluster. The cluster controller is down and all compute instances are terminated. The resources still count toward your service quotas. You can delete a resource if its status is SUSPENDED. For more information, see [Frequently asked questions about Slurm versions in AWS PCS](#) in the *AWS PCS User Guide*.

Type: String

Valid Values: CREATING | ACTIVE | UPDATING | DELETING | CREATE\_FAILED | DELETE\_FAILED | UPDATE\_FAILED | SUSPENDING | SUSPENDED | RESUMING

Required: Yes

### **errorInfo**

The list of errors that occurred during queue provisioning.

Type: Array of [ErrorInfo](#) objects

Required: No

### **slurmConfiguration**

Additional options related to the Slurm scheduler.

Type: [QueueSlurmConfiguration](#) object

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# QueueSlurmConfiguration

Additional options related to the Slurm scheduler.

## Contents

### **slurmCustomSettings**

Additional Slurm-specific configuration that directly maps to Slurm settings.

Type: Array of [SlurmCustomSetting](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# QueueSlurmConfigurationRequest

Additional options related to the Slurm scheduler.

## Contents

### **slurmCustomSettings**

Additional Slurm-specific configuration that directly maps to Slurm settings.

Type: Array of [SlurmCustomSetting](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# QueueSummary

The object returned by the `ListQueues` API action.

## Contents

### **arn**

The unique Amazon Resource Name (ARN) of the queue.

Type: String

Required: Yes

### **clusterId**

The ID of the cluster of the queue.

Type: String

Required: Yes

### **createdAt**

The date and time the resource was created.

Type: Timestamp

Required: Yes

### **id**

The generated unique ID of the queue.

Type: String

Required: Yes

### **modifiedAt**

The date and time the resource was modified.

Type: Timestamp

Required: Yes

## name

The name that identifies the queue.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 25.

Pattern: (?!pcs\_)^[A-Za-z][A-Za-z0-9-]+

Required: Yes

## status

The provisioning status of the queue.

### Note

The provisioning status doesn't indicate the overall health of the queue.

### Important

The resource enters the SUSPENDING and SUSPENDED states when the scheduler is beyond end of life and we have suspended the cluster. When in these states, you can't use the cluster. The cluster controller is down and all compute instances are terminated. The resources still count toward your service quotas. You can delete a resource if its status is SUSPENDED. For more information, see [Frequently asked questions about Slurm versions in AWS PCS](#) in the *AWS PCS User Guide*.

Type: String

Valid Values: CREATING | ACTIVE | UPDATING | DELETING | CREATE\_FAILED | DELETE\_FAILED | UPDATE\_FAILED | SUSPENDING | SUSPENDED | RESUMING

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ScalingConfiguration

Specifies the boundaries of the compute node group auto scaling.

## Contents

### **maxInstanceCount**

The upper bound of the number of instances allowed in the compute fleet.

Type: Integer

Valid Range: Minimum value of 0.

Required: Yes

### **minInstanceCount**

The lower bound of the number of instances allowed in the compute fleet.

Type: Integer

Valid Range: Minimum value of 0.

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ScalingConfigurationRequest

Specifies the boundaries of the compute node group auto scaling.

## Contents

### **maxInstanceCount**

The upper bound of the number of instances allowed in the compute fleet.

Type: Integer

Valid Range: Minimum value of 0.

Required: Yes

### **minInstanceCount**

The lower bound of the number of instances allowed in the compute fleet.

Type: Integer

Valid Range: Minimum value of 0.

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Scheduler

The cluster management and job scheduling software associated with the cluster.

## Contents

### type

The software AWS PCS uses to manage cluster scaling and job scheduling.

Type: String

Valid Values: SLURM

Required: Yes

### version

The version of the specified scheduling software that AWS PCS uses to manage cluster scaling and job scheduling. For more information, see [Slurm versions in AWS PCS](#) in the *AWS PCS User Guide*.

Valid Values: 23.11 | 24.05 | 24.11 | 25.05

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# SchedulerRequest

The cluster management and job scheduling software associated with the cluster.

## Contents

### type

The software AWS PCS uses to manage cluster scaling and job scheduling.

Type: String

Valid Values: SLURM

Required: Yes

### version

The version of the specified scheduling software that AWS PCS uses to manage cluster scaling and job scheduling. For more information, see [Slurm versions in AWS PCS](#) in the *AWS PCS User Guide*.

Valid Values: 24.11 | 25.05

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# SlurmAuthKey

The shared Slurm key for authentication, also known as the **cluster secret**.

## Contents

### **secretArn**

The Amazon Resource Name (ARN) of the shared Slurm key.

Type: String

Required: Yes

### **secretVersion**

The version of the shared Slurm key.

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# SlurmCustomSetting

Additional settings that directly map to Slurm settings.

## Important

AWS PCS supports a subset of Slurm settings. For more information, see [Configuring custom Slurm settings in AWS PCS](#) in the *AWS PCS User Guide*.

## Contents

### parameterName

AWS PCS supports custom Slurm settings for clusters, compute node groups, and queues. For more information, see [Configuring custom Slurm settings in AWS PCS](#) in the *AWS PCS User Guide*.

Type: String

Required: Yes

### parameterValue

The values for the configured Slurm settings.

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# SlurmdbdCustomSetting

Additional settings that directly map to SlurmDBD settings.

## Important

AWS PCS supports a subset of SlurmDBD settings. For more information, see [Configuring custom SlurmDBD settings in AWS PCS](#) in the *AWS PCS User Guide*.

## Contents

### parameterName

AWS PCS supports custom SlurmDBD settings for clusters. For more information, see [Configuring custom SlurmDBD settings in AWS PCS](#) in the *AWS PCS User Guide*.

Type: String

Required: Yes

### parameterValue

The values for the configured SlurmDBD settings.

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# SlurmRest

The Slurm REST API configuration includes settings for enabling and configuring the Slurm REST API. It's a property of the **ClusterSlurmConfiguration** object.

## Contents

### mode

The default value for mode is NONE. A value of STANDARD means the Slurm REST API is enabled.

Type: String

Valid Values: STANDARD | NONE

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# SlurmRestRequest

The Slurm REST API configuration includes settings for enabling and configuring the Slurm REST API. It's a property of the **ClusterSlurmConfiguration** object.

## Contents

### mode

The default value for mode is NONE. A value of STANDARD means the Slurm REST API is enabled.

Type: String

Valid Values: STANDARD | NONE

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# SpotOptions

Additional configuration when you specify SPOT as the purchaseOption for the CreateComputeNodeGroup API action.

## Contents

### allocationStrategy

The Amazon EC2 allocation strategy AWS PCS uses to provision EC2 instances. AWS PCS supports **lowest price**, **capacity optimized**, and **price capacity optimized**. For more information, see [Use allocation strategies to determine how EC2 Fleet or Spot Fleet fulfills Spot and On-Demand capacity](#) in the *Amazon Elastic Compute Cloud User Guide*. If you don't provide this option, it defaults to **price capacity optimized**.

Type: String

Valid Values: lowest-price | capacity-optimized | price-capacity-optimized

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# UpdateAccountingRequest

The accounting configuration includes configurable settings for Slurm accounting.

## Contents

### defaultPurgeTimeInDays

The default value for all purge settings for `slurmdbd.conf`. For more information, see the [slurmdbd.conf documentation at SchedMD](#).

The default value for `defaultPurgeTimeInDays` is `-1`.

A value of `-1` means there is no purge time and records persist as long as the cluster exists.

#### Important

`0` isn't a valid value.

Type: Integer

Valid Range: Minimum value of `-1`. Maximum value of `10000`.

Required: No

### mode

The default value for `mode` is `NONE`. A value of `STANDARD` means Slurm accounting is enabled.

Type: String

Valid Values: `STANDARD` | `NONE`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# UpdateClusterSlurmConfigurationRequest

Additional options related to the Slurm scheduler.

## Contents

### accounting

The accounting configuration includes configurable settings for Slurm accounting.

Type: [UpdateAccountingRequest](#) object

Required: No

### cgroupCustomSettings

Additional Cgroup-specific configuration that directly maps to Cgroup settings.

Type: Array of [CgroupCustomSetting](#) objects

Required: No

### scaleDownIdleTimeInSeconds

The time (in seconds) before an idle node is scaled down.

Default: 600

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 10000000.

Required: No

### slurmCustomSettings

Additional Slurm-specific configuration that directly maps to Slurm settings.

Type: Array of [SlurmCustomSetting](#) objects

Required: No

### slurmdbdCustomSettings

Additional SlurmDBD-specific configuration that directly maps to SlurmDBD settings.

Type: Array of [SlurmdbdCustomSetting](#) objects

Required: No

### **slurmRest**

The Slurm REST API configuration for the cluster.

Type: [UpdateSlurmRestRequest](#) object

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# UpdateComputeNodeGroupSlurmConfigurationRequest

Additional options related to the Slurm scheduler.

## Contents

### **slurmCustomSettings**

Additional Slurm-specific configuration that directly maps to Slurm settings.

Type: Array of [SlurmCustomSetting](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# UpdateQueueSlurmConfigurationRequest

Additional options related to the Slurm scheduler.

## Contents

### **slurmCustomSettings**

Additional Slurm-specific configuration that directly maps to Slurm settings.

Type: Array of [SlurmCustomSetting](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# UpdateSlurmRestRequest

The Slurm REST API configuration includes settings for enabling and configuring the Slurm REST API.

## Contents

### mode

The default value for mode is NONE. A value of STANDARD means the Slurm REST API is enabled.

Type: String

Valid Values: STANDARD | NONE

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ValidationExceptionField

Stores information about a field in a request that caused an exception.

## Contents

### message

The message body of the exception.

Type: String

Required: Yes

### name

The name of the exception.

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

## X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

## X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4\_request"). The value is expressed in the following format: *access\_key/YYYYMMDD/region/service/aws4\_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

## X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

### **X-Amz-Security-Token**

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

### **X-Amz-Signature**

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

### **X-Amz-SignedHeaders**

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

**Required: Conditional**

# Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

## **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

## **IncompleteSignature**

The request signature does not conform to AWS standards.

HTTP Status Code: 400

## **InternalFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## **InvalidAction**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

## **InvalidClientTokenId**

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

## **NotAuthorized**

You do not have permission to perform this action.

HTTP Status Code: 400

## **OptInRequired**

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

**RequestExpired**

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

**ServiceUnavailable**

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

**ThrottlingException**

The request was denied due to request throttling.

HTTP Status Code: 400

**ValidationError**

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400