

# **REST API Reference**

# **Amazon Pinpoint**



# **Amazon Pinpoint: REST API Reference**

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

# **Table of Contents**

	xiv
Welcome	1
Choosing between Amazon Pinpoint and Amazon Simple Email Service (SES)	1
Regional availability	1
Example REST request and response	2
Hypertext Application Language	2
Operations	4
Resources	16
Active Template Version	18
URI	18
HTTP methods	19
Schemas	22
Properties	23
See also	23
ADM Channel	24
URI	24
HTTP methods	24
Schemas	31
Properties	32
See also	35
APNs Channel	36
URI	37
HTTP methods	37
Schemas	43
Properties	44
See also	49
APNs Sandbox Channel	50
URI	50
HTTP methods	51
Schemas	57
Properties	58
See also	63
APNs VoIP Channel	64
URI	64

HTTP methods	65
Schemas	71
Properties	72
See also	77
APNs VoIP Sandbox Channel	78
URI	78
HTTP methods	79
Schemas	85
Properties	86
See also	91
App	92
URI	92
HTTP methods	92
Schemas	97
Properties	98
See also	99
Application Metrics	100
URI	101
HTTP methods	101
Schemas	107
Properties	108
See also	112
Apps	112
URI	113
HTTP methods	113
Schemas	117
Properties	118
See also	
Attributes	122
URI	
HTTP methods	122
Schemas	
Properties	
See also	
Baidu Channel	
IIRI	130

HTTP methods	131
Schemas	137
Properties	138
See also	141
Campaign	143
URI	143
HTTP methods	143
Schemas	150
Properties	172
See also	210
Campaign Activities	211
URI	211
HTTP methods	211
Schemas	215
Properties	216
See also	219
Campaign Metrics	220
URI	220
HTTP methods	221
Schemas	226
Properties	228
See also	231
Campaign Version	232
URI	232
HTTP methods	232
Schemas	235
Properties	247
See also	280
Campaign Versions	280
URI	280
HTTP methods	280
Schemas	284
Properties	295
See also	
Campaigns	330
URI	330

HTTP methods	330
Schemas	335
Properties	368
See also	407
Channels	408
URI	408
HTTP methods	409
Schemas	411
Properties	412
See also	414
Email Channel	415
URI	415
HTTP methods	415
Schemas	422
Properties	423
See also	428
Email Template	429
URI	430
HTTP methods	430
Schemas	446
Properties	448
See also	455
Endpoint	457
URI	457
HTTP methods	457
Schemas	464
Properties	467
See also	
Endpoints	479
URI	
HTTP methods	480
Schemas	
Properties	
See also	
Event Stream	
	193

HTTP methods	493
Schemas	500
Properties	500
See also	503
Events	504
URI	504
HTTP methods	505
Schemas	507
Properties	508
See also	520
Export Job	521
URI	521
HTTP methods	521
Schemas	524
Properties	525
See also	529
Export Jobs	530
URI	530
HTTP methods	530
Schemas	535
Properties	537
See also	543
GCM Channel	544
URI	544
HTTP methods	544
Schemas	551
Properties	552
See also	556
Import Job	557
URI	558
HTTP methods	558
Schemas	560
Properties	561
See also	
Import Jobs	567
URI	

HTTP methods	568
Schemas	573
Properties	575
See also	583
In-App Messages	584
URI	585
HTTP methods	585
Schemas	587
Properties	590
See also	604
In-App Template	604
URI	605
HTTP methods	605
Schemas	621
Properties	627
See also	637
Journey	639
URI	640
HTTP methods	640
Schemas	647
Properties	652
See also	695
Journey Activity Execution Metrics	696
URI	697
HTTP methods	697
Schemas	701
Properties	701
See also	703
Journey Engagement Metrics	704
URI	704
HTTP methods	704
Schemas	710
Properties	711
See also	715
Journey Execution Metrics	715
LIRI	716

HTTP methods	716
Schemas	719
Properties	720
See also	721
Journey Run Execution Activity Metrics	722
URI	722
HTTP methods	723
Schemas	726
Properties	727
See also	729
Journey Run Execution Metrics	730
URI	730
HTTP methods	730
Schemas	734
Properties	735
See also	736
Journey Runs	737
URI	737
HTTP methods	737
Schemas	741
Properties	741
See also	743
Journey State	744
URI	744
HTTP methods	744
Schemas	747
Properties	750
See also	788
Journeys	789
URI	789
HTTP methods	789
Schemas	795
Properties	803
See also	846
Messages	847
URI	848

HTTP methods	848
Schemas	851
Properties	856
See also	894
OTP Message	895
URI	895
HTTP methods	895
Schemas	898
Properties	899
See also	906
Phone Number Validate	907
URI	907
HTTP methods	907
Schemas	909
Properties	910
See also	914
Push Notification Template	914
URI	915
HTTP methods	915
Schemas	931
Properties	936
See also	948
Recommender Model	950
URI	951
HTTP methods	951
Schemas	958
Properties	959
See also	
Recommender Models	967
URI	968
HTTP methods	968
Schemas	
Properties	
See also	
Segment	
	983

HTTP methods	983
Schemas	990
Properties	998
See also	. 1013
Segment Export Jobs	. 1014
URI	. 1014
HTTP methods	. 1014
Schemas	. 1018
Properties	1019
See also	. 1024
Segment Import Jobs	. 1024
URI	. 1024
HTTP methods	. 1024
Schemas	. 1028
Properties	1029
See also	. 1035
Segment Version	1035
URI	. 1035
HTTP methods	. 1036
Schemas	. 1039
Properties	. 1043
See also	. 1056
Segment Versions	. 1057
URI	. 1057
HTTP methods	. 1057
Schemas	. 1061
Properties	1065
See also	
Segments	1079
URI	
HTTP methods	. 1080
Schemas	. 1085
Properties	
See also	
Settings	
LIRI	1114

HTTP methods	. 1114
Schemas	. 1118
Properties	. 1120
See also	. 1127
SMS Channel	1128
URI	. 1128
HTTP methods	. 1129
Schemas	. 1135
Properties	. 1136
See also	. 1140
SMS Template	. 1141
URI	. 1142
HTTP methods	. 1142
Schemas	. 1158
Properties	. 1160
See also	. 1165
Tags	1166
URI	. 1167
HTTP methods	. 1167
Schemas	. 1169
Properties	. 1170
See also	. 1170
Template Versions	. 1172
URI	. 1172
HTTP methods	. 1172
Schemas	. 1176
Properties	. 1177
See also	
Templates	. 1180
URI	
HTTP methods	. 1181
Schemas	. 1184
Properties	
See also	
User	
LIRI	1189

HTTP methods	1189
Schemas	1194
Properties	1196
See also	1204
Users Messages	1205
URI	1205
HTTP methods	1205
Schemas	1208
Properties	1213
See also	1248
Verify OTP	1249
URI	1249
HTTP methods	1249
Schemas	1252
Properties	1252
See also	1254
Voice Channel	1254
URI	1255
HTTP methods	1255
Schemas	1261
Properties	1262
See also	1265
Voice Template	1266
URI	1267
HTTP methods	1267
Schemas	1283
Properties	1285
See also	1290
Schema samples	1293
JourneyResponse object	1293
RawContent object	1296
Overview	1296
Samples	1297
Document history	

**End of support notice:** On October 30, 2026, AWS will end support for Amazon Pinpoint. After October 30, 2026, you will no longer be able to access the Amazon Pinpoint console or Amazon Pinpoint resources (endpoints, segments, campaigns, journeys, and analytics). For more information, see <a href="Manazon Pinpoint end of support">Amazon Pinpoint end of support</a>. **Note:** APIs related to SMS, voice, mobile push, OTP, and phone number validate are not impacted by this change and are supported by AWS End User Messaging.

# Welcome

Welcome to the *Amazon Pinpoint API Reference*. This guide provides information about Amazon Pinpoint API resources, including supported HTTP methods, parameters, and schemas.

Amazon Pinpoint is an AWS service that you can use to engage with your customers across multiple messaging channels. You can use Amazon Pinpoint to send push notifications, email, SMS text messages, and voice messages.

If you're new to Amazon Pinpoint, you might find it helpful to also review the <u>Amazon Pinpoint</u> <u>Developer Guide</u>. The *Amazon Pinpoint Developer Guide* provides tutorials, code samples, and procedures that demonstrate how to use Amazon Pinpoint features programmatically and how to integrate Amazon Pinpoint functionality into mobile apps and other types of applications. The guide also provides information about key topics such as Amazon Pinpoint integration with other AWS services and the quotas that apply to using the service.

# Choosing between Amazon Pinpoint and Amazon Simple Email Service (SES)

If you send a large number of transactional emails, such as purchase confirmations or password reset messages, consider using Amazon SES. Amazon SES has an API and an SMTP interface, both of which are well suited to sending email from your applications or services. It also offers additional email features, including email receiving capabilities, configuration sets, and sending authorization capabilities.

Amazon SES also includes an SMTP interface that you can integrate with your existing third-party applications, including customer relationship management (CRM) services such as Salesforce. For more information about sending email using Amazon SES, see Amazon SES API v2.

# Regional availability

The Amazon Pinpoint API is available in several AWS Regions and it provides an endpoint for each of these Regions. For a list of all the Regions and endpoints where the API is currently available, see <a href="AWS Service Endpoints">AWS Service Endpoints</a> and <a href="Amazon Pinpoint endpoints">Amazon Pinpoint endpoints</a> and <a href="quotes">quotas</a> in the Amazon Web Services

General Reference. To learn more about AWS Regions, see <a href="Managing AWS Regions">Managing AWS Regions</a> in the Amazon

Web Services General Reference.

In each Region, AWS maintains multiple Availability Zones. These Availability Zones are physically isolated from each other, but are united by private, low-latency, high-throughput, and highly redundant network connections. These Availability Zones enable us to provide very high levels of availability and redundancy, while also minimizing latency. To learn more about the number of Availability Zones that are available in each Region, see AWS Global Infrastructure.

# **Example REST request and response**

The following is an example of a REST request that you send to Amazon Pinpoint:

```
GET /v1/apps/a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6/campaigns
Accept: application/json
```

```
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20161127/us-east-1/mobiletargeting/aws4_request, SignedHeaders=accept;host;x-amz-date, Signature=a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6q7r8s9t0u1v2w3x4y5z6a1b2c3d4e5f6 Host: pinpoint.us-east-1.amazonaws.com
X-Amz-Date: 20161127T202324Z
```

Following this request, Amazon Pinpoint returns a response that includes the following header:

```
Access-Control-Allow-Origin: *
Connection: keep-alive
Content-Length: 94237
Content-Type: application/json
Date: Sun, 27 Nov 2016 20:23:28 GMT
X-Amz-Cf-Id: BerfOyKjyRgVGEKS2q3gHdWBZYFrqq0w4KmpamCCbY6o_xsAzxR1Iw==
x-amzn-RequestId: 595c3386-b4df-11e6-855b-61b43929a1e2
X-Amzn-Trace-Id: Root=1-583b40bd-ca765532129bcbb6c5016375
```

# **Hypertext Application Language**

Amazon Pinpoint provides a resource-based API that uses Hypertext Application Language (HAL). HAL provides a standard convention for expressing the resources and relationships of an API as hyperlinks. Using HAL, you use HTTP methods—for example, GET, PUT, POST, DELETE—to submit requests and to receive information about the API in the response. Applications can use the

information that's returned to explore the functionality of the API. For more information about HAL, see the draft JSON Hypertext Application Language specification.

To request a HAL response from Amazon Pinpoint, specify application/hal+json in the Accept request header.

# **Operations**

The Amazon Pinpoint REST API includes the following operations.

CreateApp

Creates an application.

CreateCampaign

Creates a new campaign for an application or updates the settings of an existing campaign for an application.

CreateEmailTemplate

Creates a message template for messages that are sent through the email channel.

CreateExportJob

Creates an export job for an application.

CreateImportJob

Creates an import job for an application.

CreateInAppTemplate

Creates a new in-app message template.

CreateJourney

Creates a journey for an application.

CreatePushTemplate

Creates a message template for messages that are sent through a push notification channel.

• CreateRecommenderConfiguration

Creates an Amazon Pinpoint configuration for a recommender model.

CreateSegment

Creates a new segment.

CreateSmsTemplate

Creates a message template for messages that are sent through the SMS channel.

#### CreateVoiceTemplate

Creates a message template for messages that are sent through the voice channel.

#### DeleteAdmChannel

Disables the ADM channel for an application and deletes any existing settings for the channel.

#### DeleteApnsChannel

Disables the APNs channel for an application and deletes any existing settings for the channel.

#### DeleteApnsSandboxChannel

Disables the APNs sandbox channel for an application and deletes any existing settings for the channel.

#### DeleteApnsVoipChannel

Disables the APNs VoIP channel for an application and deletes any existing settings for the channel.

#### DeleteApnsVoipSandboxChannel

Disables the APNs VoIP sandbox channel for an application and deletes any existing settings for the channel.

# DeleteApp

Deletes an application.

#### DeleteBaiduChannel

Disables the Baidu channel for an application and deletes any existing settings for the channel.

## • DeleteCampaign

Deletes a campaign from an application.

## DeleteEmailChannel

Disables the email channel for an application and deletes any existing settings for the channel.

# DeleteEmailTemplate

Deletes a message template for messages that were sent through the email channel.

DeleteEndpoint

5

Deletes an endpoint from an application.

DeleteEventStream

Deletes the event stream for an application.

DeleteGcmChannel

Disables the GCM channel for an application and deletes any existing settings for the channel.

DeleteInAppTemplate

Deletes an existing in-app message template.

DeleteJourney

Deletes a journey from an application.

DeletePushTemplate

Deletes a message template for messages that were sent through a push notification channel.

DeleteRecommenderConfiguration

Deletes an Amazon Pinpoint configuration for a recommender model.

DeleteSegment

Deletes a segment from an application.

DeleteSmsChannel

Disables the SMS channel for an application and deletes any existing settings for the channel.

DeleteSmsTemplate

Deletes a message template for messages that were sent through the SMS channel.

DeleteUserEndpoints

Deletes all the endpoints that are associated with a specific user ID.

DeleteVoiceChannel

Disables the voice channel for an application and deletes any existing settings for the channel.

DeleteVoiceTemplate

Deletes a message template for messages that were sent through the voice channel.

#### GetAdmChannel

Retrieves information about the status and settings of the ADM channel for an application.

#### GetApnsChannel

Retrieves information about the status and settings of the APNs channel for an application.

#### GetApnsSandboxChannel

Retrieves information about the status and settings of the APNs sandbox channel for an application.

#### GetApnsVoipChannel

Retrieves information about the status and settings of the APNs VoIP channel for an application.

#### GetApnsVoipSandboxChannel

Retrieves information about the status and settings of the APNs VoIP sandbox channel for an application.

#### GetApp

Retrieves information about an application.

## GetApplicationDateRangeKpi

Retrieves (queries) pre-aggregated data for a standard metric that applies to an application.

# • GetApplicationSettings

Retrieves information about the settings for an application.

# GetApps

Retrieves information about all the applications that are associated with your Amazon Pinpoint account.

## GetBaiduChannel

Retrieves information about the status and settings of the Baidu channel for an application.

# GetCampaign

Retrieves information about the status, configuration, and other settings for a campaign.

#### GetCampaignActivities

Retrieves information about all the activities for a campaign.

#### GetCampaignDateRangeKpi

Retrieves (queries) pre-aggregated data for a standard metric that applies to a campaign.

#### GetCampaigns

Retrieves information about the status, configuration, and other settings for all the campaigns that are associated with an application.

#### GetCampaignVersion

Retrieves information about the status, configuration, and other settings for a specific version of a campaign.

#### GetCampaignVersions

Retrieves information about the status, configuration, and other settings for all versions of a campaign.

#### GetChannels

Retrieves information about the history and status of each channel for an application.

#### GetEmailChannel

Retrieves information about the status and settings of the email channel for an application.

#### GetEmailTemplate

Retrieves the content and settings of a message template for messages that are sent through the email channel.

#### GetEndpoint

Retrieves information about the settings and attributes of a specific endpoint for an application.

#### GetEventStream

Retrieves information about the event stream settings for an application.

#### GetExportJob

Retrieves information about the status and settings of a specific export job for an application.

## GetExportJobs

Retrieves information about the status and settings of all the export jobs for an application.

#### GetGcmChannel

Retrieves information about the status and settings of the GCM channel for an application.

#### GetImportJob

Retrieves information about the status and settings of a specific import job for an application.

#### GetImportJobs

Retrieves information about the status and settings of all the import jobs for an application.

#### GetInAppMessages

Retrieves information about the in-app messages that have been sent to the requested endpoint.

## GetInAppTemplate

Retrieves the content and configuration of an in-app message template.

#### GetJourney

Retrieves information about the status, configuration, and other settings for a journey.

## GetJourneyDateRangeKpi

Retrieves (queries) pre-aggregated data for a standard engagement metric that applies to a journey.

# • GetJourneyExecutionActivityMetrics

Retrieves (queries) pre-aggregated data for a standard execution metric that applies to a journey activity.

# • GetJourneyExecutionMetrics

Retrieves (queries) pre-aggregated data for a standard execution metric that applies to a journey.

# GetJourneyRunExecutionActivityMetrics

Retrieves (queries) pre-aggregated data for a standard run execution metric that applies to a journey activity.

# • GetJourneyRunExecutionMetrics

Retrieves (queries) pre-aggregated data for a standard run execution metric that applies to a journey.

#### GetJourneyRuns

Provides information about the runs of a journey.

#### GetPushTemplate

Retrieves the content and settings of a message template for messages that are sent through a push notification channel.

#### GetRecommenderConfiguration

Retrieves information about an Amazon Pinpoint configuration for a recommender model.

#### GetRecommenderConfigurations

Retrieves information about all the recommender model configurations that are associated with your Amazon Pinpoint account.

#### GetSegment

Retrieves information about the configuration, dimension, and other settings for a specific segment that's associated with an application.

# • GetSegmentExportJobs

Retrieves information about the status and settings of the export jobs for a segment.

# • GetSegmentImportJobs

Retrieves information about the status and settings of the import jobs for a segment.

# GetSegments

Retrieves information about the configuration, dimension, and other settings for all the segments that are associated with an application.

# GetSegmentVersion

Retrieves information about the configuration, dimension, and other settings for a specific version of a segment that's associated with an application.

# GetSegmentVersions

Retrieves information about the configuration, dimension, and other settings for all the versions of a specific segment that's associated with an application.

#### GetSmsChannel

Retrieves information about the status and settings of the SMS channel for an application.

#### GetSmsTemplate

Retrieves the content and settings of a message template for messages that are sent through the SMS channel.

#### GetUserEndpoints

Retrieves information about all the endpoints that are associated with a specific user ID.

#### GetVoiceChannel

Retrieves information about the status and settings of the voice channel for an application.

## GetVoiceTemplate

Retrieves the content and settings of a message template for messages that are sent through the voice channel.

#### ListJourneys

Retrieves information about the status, configuration, and other settings for all the journeys that are associated with an application.

#### • ListTagsForResource

Retrieves all the tags (keys and values) that are associated with an application, campaign, message template, or segment.

# ListTemplates

Retrieves information about all the message templates that are associated with your Amazon Pinpoint account.

# ListTemplateVersions

Retrieves information about all the versions of a specific message template.

#### PhoneNumberValidate

Retrieves information about a phone number.

#### PutEvents

Creates a new event to record for endpoints, or creates or updates endpoint data that existing events are associated with.

#### PutEventStream

Creates a new event stream for an application or updates the settings of an existing event stream for an application.

#### RemoveAttributes

Removes one or more custom attributes, of the same attribute type, from the application. Existing endpoints still have the attributes but Amazon Pinpoint will stop capturing new or changed values for these attributes.

#### SendMessages

Creates and sends a direct message.

#### SendOTPMessage

Use this operation to send an OTP code to a user of your application. When you use this API, Amazon Pinpoint generates a random code and sends it to your user.

#### SendUsersMessages

Creates and sends a message to a list of users.

#### TagResource

Adds one or more tags (keys and values) to an application, campaign, message template, or segment.

#### UntagResource

Removes one or more tags (keys and values) from an application, campaign, message template, or segment.

#### • UpdateAdmChannel

Enables the ADM channel for an application or updates the status and settings of the ADM channel for an application.

#### UpdateApnsChannel

Enables the APNs channel for an application or updates the status and settings of the APNs channel for an application.

#### UpdateApnsSandboxChannel

Enables the APNs sandbox channel for an application or updates the status and settings of the APNs sandbox channel for an application.

#### UpdateApnsVoipChannel

Enables the APNs VoIP channel for an application or updates the status and settings of the APNs VoIP channel for an application.

#### UpdateApnsVoipSandboxChannel

Enables the APNs VoIP sandbox channel for an application or updates the status and settings of the APNs VoIP sandbox channel for an application.

#### UpdateApplicationSettings

Updates the settings for an application.

#### UpdateBaiduChannel

Enables the Baidu channel for an application or updates the status and settings of the Baidu channel for an application.

## UpdateCampaign

Updates the configuration and other settings for a campaign.

# UpdateEmailChannel

Enables the email channel for an application or updates the status and settings of the email channel for an application.

# • UpdateEmailTemplate

Updates an existing message template for messages that are sent through the email channel.

# UpdateEndpoint

Creates a new endpoint for an application or updates the settings and attributes of an existing endpoint for an application. You can also use this operation to define custom attributes for an endpoint. If an update includes one or more values for a custom attribute, Amazon Pinpoint replaces (overwrites) any existing values with the new values.

#### UpdateEndpointsBatch

Creates a new batch of endpoints for an application or updates the settings and attributes of a batch of existing endpoints for an application. You can also use this operation to define custom attributes for a batch of endpoints. If an update includes one or more values for a custom attribute, Amazon Pinpoint replaces (overwrites) any existing values with the new values.

#### UpdateGcmChannel

Enables the GCM channel for an application or updates the status and settings of the GCM channel for an application.

#### UpdateInAppTemplate

Updates an existing in-app message template.

#### UpdateJourney

Updates the configuration and other settings for a journey.

#### UpdateJourneyState

Cancels (stops) an active journey.

#### UpdatePushTemplate

Updates an existing message template for messages that are sent through a push notification channel.

# • UpdateRecommenderConfiguration

Updates an Amazon Pinpoint configuration for a recommender model.

# UpdateSegment

Updates the configuration, dimension, and other settings for an existing segment.

# UpdateSmsChannel

Enables the SMS channel for an application or updates the status and settings of the SMS channel for an application.

#### <u>UpdateSmsTemplate</u>

Updates an existing message template for messages that are sent through the SMS channel.

#### UpdateTemplateActiveVersion

Changes the status of a specific version of a message template to active.

• UpdateVoiceChannel

Enables the voice channel for an application or updates the status and settings of the voice channel for an application.

• UpdateVoiceTemplate

Updates an existing message template for messages that are sent through the voice channel.

VerifyOTPMessage

Verifies a One-Time Password that was generated by the OTP Message resource.

# Resources

The Amazon Pinpoint REST API includes the following resources.

#### **Topics**

- Active Template Version
- ADM Channel
- APNs Channel
- APNs Sandbox Channel
- APNs VoIP Channel
- APNs VoIP Sandbox Channel
- App
- Application Metrics
- Apps
- Attributes
- Baidu Channel
- Campaign
- Campaign Activities
- Campaign Metrics
- Campaign Version
- Campaign Versions
- Campaigns
- Channels
- Email Channel
- Email Template
- Endpoint
- Endpoints
- Event Stream
- Events
- Export Job
- Export Jobs

- GCM Channel
- Import Job
- Import Jobs
- In-App Messages
- In-App Template
- Journey
- Journey Activity Execution Metrics
- Journey Engagement Metrics
- Journey Execution Metrics
- Journey Run Execution Activity Metrics
- · Journey Run Execution Metrics
- Journey Runs
- Journey State
- Journeys
- Messages
- OTP Message
- Phone Number Validate
- Push Notification Template
- Recommender Model
- Recommender Models
- <u>Segment</u>
- Segment Export Jobs
- Segment Import Jobs
- Segment Version
- Segment Versions
- Segments
- Settings
- SMS Channel
- SMS Template
- Tags

- Template Versions
- Templates
- User
- Users Messages
- Verify OTP
- Voice Channel
- Voice Template

# **Active Template Version**

A *message template* is a set of content and settings that you can define, save, and reuse in email messages, push notifications, SMS text messages, and voice messages for any of your Amazon Pinpoint applications.

To help you develop and maintain templates, Amazon Pinpoint supports versioning for all types of message templates. Each time you update a template, Amazon Pinpoint automatically saves your changes to (overwrites) the latest existing version of the template, unless you choose to create a new version of the template. Each version of a template is a snapshot of the template that you can use in a message.

Of the template versions, you can designate one version as the *active version*. The *active version* is the version that Amazon Pinpoint uses by default for any new messages that are based on the template. Depending on your organization's workflow for managing message templates, the active version is typically the version that's been most recently reviewed and approved for use in messages. It isn't necessarily the latest version of a template. To determine which version of a template is currently the active version, send a GET request to the appropriate resource for the template's type, and omit the version query parameter from your request. In response to your request, Amazon Pinpoint returns the version identifier and other information about the active version of the template.

You can use the Active Template Version resource to change the status of a specific version of a template to *active*.

#### URI

/v1/templates/template-name/template-type/active-version

Active Template Version 18

# **HTTP** methods

# **PUT**

Operation ID: UpdateTemplateActiveVersion

Changes the status of a specific version of a message template to *active*.

# **Path parameters**

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can contain a maximum of 128 characters. The characters can be alphanumeric characters, underscor es (_), or hyphens (-). Template names are case sensitive.
template-type	String	True	The type of channel that the message template is designed for. Valid values are: EMAIL, PUSH, SMS, and VOICE.

HTTP methods 19

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	MessageBody	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	MessageBody	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	MessageBody	The request failed because the specified resource was not found (NotFoundException).
405	MessageBody	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large

HTTP methods 20

Status code	Response model	Description
		(RequestEntityTooLargeExcep tion).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Active Template Version resource.

# **Path parameters**

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can contain a maximum of 128 characters. The characters can be alphanumeric characters, underscores (_), or hyphens (-).

HTTP methods 21

Name	Туре	Required	Description
			Template names are case sensitive.
template-type	String	True	The type of channel that the message template is designed for. Valid values are: EMAIL, PUSH, SMS, and VOICE.

# Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Request bodies**

#### **PUT schema**

```
{
    "<u>Version</u>": "string"
}
```

# **Response bodies**

# MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

Schemas 22

# **Properties**

### MessageBody

Provides information about an API request or response.

#### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

#### Message

The message that's returned from the API.

**Type**: string **Required**: False

### **TemplateActiveVersionRequest**

Specifies which version of a message template to use as the active version of the template.

#### Version

The version of the message template to use as the active version of the template. Valid values are: latest, for the most recent version of the template; or, the unique identifier for any existing version of the template. If you specify an identifier, the value must match the identifier for an existing template version. To retrieve a list of versions and version identifiers for a template, use the <u>Template Versions</u> resource.

**Type**: string **Required**: False

### See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## **UpdateTemplateActiveVersion**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **ADM Channel**

A *channel* is a type of platform that you can deliver messages to. You can use the ADM channel to send push notifications through the Amazon Device Messaging (ADM) service to apps that are running on Amazon devices, such as Kindle Fire tablets. Before you can use Amazon Pinpoint to send messages to Amazon devices, you must enable the ADM channel for an Amazon Pinpoint application.

The ADM Channel resource represents the status and authentication settings of the ADM channel for a specific application. You can use this resource to enable, retrieve information about, update, or disable (delete) the ADM channel for an application.

#### URI

/v1/apps/application-id/channels/adm

## **HTTP** methods

#### **GET**

Operation ID: GetAdmChannel

ADM Channel 24

Retrieves information about the status and settings of the ADM channel for an application.

# **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# **Header parameters**

	Required	Description
String	False	Indicates which content types, expressed as MIME types, the client understands.
S		<b>False</b> False

### Responses

Status code	Response model	Description
200	<u>ADMChannelResponse</u>	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).

Status code	Response model	Description
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **PUT**

# **Operation ID:** UpdateAdmChannel

Enables the ADM channel for an application or updates the status and settings of the ADM channel for an application.

# **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	<u>ADMChannelResponse</u>	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).

Status code	Response model	Description
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **DELETE**

# Operation ID: DeleteAdmChannel

Disables the ADM channel for an application and deletes any existing settings for the channel.

# **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	<u>ADMChannelResponse</u>	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).

Status code	Response model	Description
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **OPTIONS**

Retrieves information about the communication requirements and options that are available for the ADM Channel resource.

### **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

### Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Request bodies**

#### **PUT schema**

```
{
  "ClientId": "string",
  "ClientSecret": "string",
  "Enabled": boolean
}
```

# **Response bodies**

### **ADMChannelResponse schema**

```
{
  "ApplicationId": "string",
  "IsArchived": boolean,
  "Version": integer,
  "CreationDate": "string",
```

Schemas 31

```
"LastModifiedDate": "string",

"LastModifiedBy": "string",

"Id": "string",

"Enabled": boolean,

"HasCredential": boolean,

"Platform": "string"
}
```

#### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

# **ADMChannelRequest**

Specifies the status and settings of the ADM (Amazon Device Messaging) channel for an application.

#### ClientId

The Client ID that you received from Amazon to send messages by using ADM.

**Type**: string **Required**: True

#### ClientSecret

The Client Secret that you received from Amazon to send messages by using ADM.

**Type**: string **Required**: True

#### **Enabled**

Specifies whether to enable the ADM channel for the application.

**Type**: boolean **Required**: False

# **ADMChannelResponse**

Provides information about the status and settings of the ADM (Amazon Device Messaging) channel for an application.

### **ApplicationId**

The unique identifier for the application that the ADM channel applies to.

**Type**: string **Required**: False

#### **IsArchived**

Specifies whether the ADM channel is archived.

**Type**: boolean **Required**: False

#### Version

The current version of the ADM channel.

**Type**: integer **Required**: False

#### CreationDate

The date and time when the ADM channel was enabled.

**Type**: string **Required**: False

#### LastModifiedDate

The date and time when the ADM channel was last modified.

**Type**: string **Required**: False

### LastModifiedBy

The user who last modified the ADM channel.

**Type**: string **Required**: False

#### Id

(Deprecated) An identifier for the ADM channel. This property is retained only for backward compatibility.

**Type**: string **Required**: False

#### **Enabled**

Specifies whether the ADM channel is enabled for the application.

**Type**: boolean **Required**: False

#### **HasCredential**

(Not used) This property is retained only for backward compatibility.

**Type**: boolean **Required**: False

#### **Platform**

The type of messaging or notification platform for the channel. For the ADM channel, this value is ADM.

Type: string

Required: True

### MessageBody

Provides information about an API request or response.

#### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

### Message

The message that's returned from the API.

**Type**: string **Required**: False

### See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

### **GetAdmChannel**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- · AWS SDK for Python
- AWS SDK for Ruby V3

See also 35

## **UpdateAdmChannel**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

#### **DeleteAdmChannel**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **APNs Channel**

A *channel* is a type of platform that you can deliver messages to. You can use the APNs channel to send push notification messages to the Apple Push Notification service (APNs). Before you can use Amazon Pinpoint to send notification messages to APNs, you must enable the APNs channel for an Amazon Pinpoint application.

APNs Channel 36

The APNs Channel resource represents the status and authentication settings of the APNs channel for a specific application. You can use this resource to enable, retrieve information about, update, or disable (delete) the APNs channel for an application.

### **URI**

/v1/apps/application-id/channels/apns

# **HTTP** methods

#### **GET**

Operation ID: GetApnsChannel

Retrieves information about the status and settings of the APNs channel for an application.

### **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

#### **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

URI 37

### Responses

Status code	Response model	Description
200	<u>APNSChannelResponse</u>	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error,

Status code	Response model	Description
		exception, or failure (Internal
		ServerErrorException).

### **PUT**

### Operation ID: UpdateApnsChannel

Enables the APNs channel for an application or updates the status and settings of the APNs channel for an application.

# **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

### Responses

Status code	Response model	Description
200	<u>APNSChannelResponse</u>	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	MessageBody	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error,

Status code	Response model	Description
		exception, or failure (Internal
		ServerErrorException).

### **DELETE**

# Operation ID: DeleteApnsChannel

Disables the APNs channel for an application and deletes any existing settings for the channel.

# **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifier for the application. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

### **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	APNSChannelResponse	The request succeeded.

Status code	Response model	Description
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

#### **OPTIONS**

Retrieves information about the communication requirements and options that are available for the APNs Channel resource.

### **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

#### Responses

Status code	Response model	Description
200	None	The request succeeded.

### **Schemas**

# **Request bodies**

#### **PUT schema**

```
{
   "Certificate": "string",
   "PrivateKey": "string",
   "Enabled": boolean,
   "TokenKeyId": "string",
   "TeamId": "string",
   "TokenKey": "string",
   "BundleId": "string",
   "DefaultAuthenticationMethod": "string"
}
```

Schemas 43

### **Response bodies**

#### **APNSChannelResponse schema**

```
{
  "ApplicationId": "string",
  "IsArchived": boolean,
  "Version": integer,
  "CreationDate": "string",
  "LastModifiedDate": "string",
  "LastModifiedBy": "string",
  "Id": "string",
  "Enabled": boolean,
  "HasCredential": boolean,
  "Platform": "string",
  "HasTokenKey": boolean,
  "DefaultAuthenticationMethod": "string"
}
```

#### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

## **APNSChannelRequest**

Specifies the status and settings of the APNs (Apple Push Notification service) channel for an application.

#### Certificate

The APNs client certificate that you received from Apple, if you want Amazon Pinpoint to communicate with APNs by using an APNs certificate.

**Type**: string **Required**: False

#### **PrivateKey**

The private key for the APNs client certificate that you want Amazon Pinpoint to use to communicate with APNs.

Type: string

Required: False

#### **Enabled**

Specifies whether to enable the APNs channel for the application.

**Type**: boolean **Required**: False

### TokenKeyId

The key identifier that's assigned to your APNs signing key, if you want Amazon Pinpoint to communicate with APNs by using APNs tokens.

Type: string

Required: False

#### **TeamId**

The identifier that's assigned to your Apple developer account team. This identifier is used for APNs tokens.

Type: string

Required: False

### **TokenKey**

The authentication key to use for APNs tokens.

Type: string

Required: False

#### **BundleId**

The bundle identifier that's assigned to your iOS app. This identifier is used for APNs tokens.

**Type**: string **Required**: False

#### **DefaultAuthenticationMethod**

The default authentication method that you want Amazon Pinpoint to use when authenticating with APNs, KEY or TOKEN.

**Type**: string **Required**: False

### **APNSChannelResponse**

Provides information about the status and settings of the APNs (Apple Push Notification service) channel for an application.

#### **ApplicationId**

The unique identifier for the application that the APNs channel applies to.

**Type**: string **Required**: False

#### **IsArchived**

Specifies whether the APNs channel is archived.

**Type**: boolean **Required**: False

#### Version

The current version of the APNs channel.

**Type**: integer **Required**: False

#### CreationDate

The date and time when the APNs channel was enabled.

**Type**: string **Required**: False

#### LastModifiedDate

The date and time when the APNs channel was last modified.

**Type**: string **Required**: False

### LastModifiedBy

The user who last modified the APNs channel.

**Type**: string **Required**: False

#### Id

(Deprecated) An identifier for the APNs channel. This property is retained only for backward compatibility.

**Type**: string **Required**: False

#### **Enabled**

Specifies whether the APNs channel is enabled for the application.

**Type**: boolean **Required**: False

#### **HasCredential**

(Not used) This property is retained only for backward compatibility.

**Type**: boolean **Required**: False

#### **Platform**

The type of messaging or notification platform for the channel. For the APNs channel, this value is APNS.

**Type**: string **Required**: True

#### HasTokenKey

Specifies whether the APNs channel is configured to communicate with APNs by using APNs tokens. To provide an authentication key for APNs tokens, set the TokenKey property of the channel.

**Type**: boolean **Required**: False

#### **DefaultAuthenticationMethod**

The default authentication method that Amazon Pinpoint uses to authenticate with APNs for this channel, key or certificate.

**Type**: string **Required**: False

# MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

#### Message

The message that's returned from the API.

**Type**: string **Required**: False

### See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

### **GetApnsChannel**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **UpdateApnsChannel**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3

See also 49

- · AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

### **DeleteApnsChannel**

- AWS Command Line Interface
- · AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- · AWS SDK for Python
- AWS SDK for Ruby V3

## **APNs Sandbox Channel**

A *channel* is a type of platform that you can deliver messages to. You can use the APNs sandbox channel to send push notification messages to the sandbox environment of the Apple Push Notification service (APNs). Before you can use Amazon Pinpoint to send notification messages to the APNs sandbox environment, you must enable the APNs sandbox channel for an Amazon Pinpoint application.

The APNs Sandbox Channel resource represents the status and authentication settings of the APNs sandbox channel for a specific application. You can use this resource to enable, retrieve information about, update, or disable (delete) the APNs sandbox channel for an application.

#### URI

/v1/apps/application-id/channels/apns\_sandbox

APNs Sandbox Channel 50

# **HTTP** methods

### **GET**

# **Operation ID:** GetApnsSandboxChannel

Retrieves information about the status and settings of the APNs sandbox channel for an application.

### **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

### Responses

Status code	Response model	Description
200	<u>APNSSandboxChannel</u>	The request succeeded.
	Response	

Status code	Response model	Description
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	MessageBody	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **PUT**

### Operation ID: UpdateApnsSandboxChannel

Enables the APNs sandbox channel for an application or updates the status and settings of the APNs sandbox channel for an application.

### **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

### **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

## Responses

Status code	Response model	Description
200	APNSSandboxChannel Response	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).

Status code	Response model	Description
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **DELETE**

**Operation ID:** DeleteApnsSandboxChannel

Disables the APNs sandbox channel for an application and deletes any existing settings for the channel.

### **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

### Responses

Status code	Response model	Description
200	APNSSandboxChannel Response	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is

Status code	Response model	<b>Description</b> forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **OPTIONS**

Retrieves information about the communication requirements and options that are available for the APNs Sandbox Channel resource.

### Path parameters

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

### Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Request bodies**

#### **PUT schema**

```
{
   "Certificate": "string",
   "PrivateKey": "string",
   "Enabled": boolean,
   "TokenKeyId": "string",
   "TeamId": "string",
   "TokenKey": "string",
   "BundleId": "string",
   "DefaultAuthenticationMethod": "string"
}
```

# **Response bodies**

Schemas 57

#### APNSSandboxChannelResponse schema

```
{
   "ApplicationId": "string",
   "IsArchived": boolean,
   "Version": integer,
   "CreationDate": "string",
   "LastModifiedDate": "string",
   "LastModifiedBy": "string",
   "Id": "string",
   "Enabled": boolean,
   "HasCredential": boolean,
   "Platform": "string",
   "HasTokenKey": boolean,
   "DefaultAuthenticationMethod": "string"
}
```

#### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

# **APNSSandboxChannelRequest**

Specifies the status and settings of the APNs (Apple Push Notification service) sandbox channel for an application.

#### Certificate

The APNs client certificate that you received from Apple, if you want Amazon Pinpoint to communicate with the APNs sandbox environment by using an APNs certificate.

**Type**: string **Required**: False

### **PrivateKey**

The private key for the APNs client certificate that you want Amazon Pinpoint to use to communicate with the APNs sandbox environment.

**Type**: string

Required: False

#### **Enabled**

Specifies whether to enable the APNs sandbox channel for the application.

**Type**: boolean **Required**: False

### **TokenKeyId**

The key identifier that's assigned to your APNs signing key, if you want Amazon Pinpoint to communicate with the APNs sandbox environment by using APNs tokens.

Type: string

Required: False

#### **TeamId**

The identifier that's assigned to your Apple developer account team. This identifier is used for APNs tokens.

Type: string

Required: False

### **TokenKey**

The authentication key to use for APNs tokens.

Type: string

Required: False

#### **BundleId**

The bundle identifier that's assigned to your iOS app. This identifier is used for APNs tokens.

**Type**: string **Required**: False

### DefaultAuthenticationMethod

The default authentication method that you want Amazon Pinpoint to use when authenticating with the APNs sandbox environment, key or certificate.

**Type**: string **Required**: False

## APNSSandboxChannelResponse

Provides information about the status and settings of the APNs (Apple Push Notification service) sandbox channel for an application.

### **ApplicationId**

The unique identifier for the application that the APNs sandbox channel applies to.

**Type**: string **Required**: False

### **IsArchived**

Specifies whether the APNs sandbox channel is archived.

**Type**: boolean **Required**: False

#### Version

The current version of the APNs sandbox channel.

**Type**: integer **Required**: False

#### CreationDate

The date and time when the APNs sandbox channel was enabled.

**Type**: string **Required**: False

#### LastModifiedDate

The date and time when the APNs sandbox channel was last modified.

**Type**: string **Required**: False

### LastModifiedBy

The user who last modified the APNs sandbox channel.

**Type**: string **Required**: False

#### Id

(Deprecated) An identifier for the APNs sandbox channel. This property is retained only for backward compatibility.

**Type**: string **Required**: False

#### **Enabled**

Specifies whether the APNs sandbox channel is enabled for the application.

**Type**: boolean **Required**: False

### **HasCredential**

(Not used) This property is retained only for backward compatibility.

**Type**: boolean **Required**: False

### **Platform**

The type of messaging or notification platform for the channel. For the APNs sandbox channel, this value is APNS\_SANDBOX.

**Type**: string **Required**: True

### HasTokenKey

Specifies whether the APNs sandbox channel is configured to communicate with APNs by using APNs tokens. To provide an authentication key for APNs tokens, set the TokenKey property of the channel.

**Type**: boolean **Required**: False

#### **DefaultAuthenticationMethod**

The default authentication method that Amazon Pinpoint uses to authenticate with the APNs sandbox environment for this channel, key or certificate.

**Type**: string **Required**: False

## MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

#### Message

The message that's returned from the API.

**Type**: string **Required**: False

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## **GetApnsSandboxChannel**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

## **UpdateApnsSandboxChannel**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin

See also 63

- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

### **DeleteApnsSandboxChannel**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

## **APNs VoIP Channel**

A *channel* is a type of platform that you can deliver messages to. You can use the APNs VoIP channel to send VoIP notification messages to the Apple Push Notification service (APNs). Before you can use Amazon Pinpoint to send VoIP notification messages to APNs, you must enable the APNs VoIP channel for an Amazon Pinpoint application.

The APNs VoIP Channel resource represents the status and authentication settings of the APNs VoIP channel for a specific application. You can use this resource to enable, retrieve information about, update, or disable (delete) the APNs VoIP channel for an application.

### **URI**

/v1/apps/application-id/channels/apns\_voip

APNs VoIP Channel 64

# **HTTP** methods

## **GET**

## Operation ID: GetApnsVoipChannel

Retrieves information about the status and settings of the APNs VoIP channel for an application.

## **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

## Responses

Status code	Response model	Description
200	APNSVoipChannelRes ponse	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).

Status code	Response model	Description
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	MessageBody	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **PUT**

# **Operation ID:** UpdateApnsVoipChannel

Enables the APNs VoIP channel for an application or updates the status and settings of the APNs VoIP channel for an application.

## **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

### Responses

Status code	Response model	Description
200	APNSVoipChannelRes ponse	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	MessageBody	The request was denied because access to the specified resource is

Status code	Response model	Description
		forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	MessageBody	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	MessageBody	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	MessageBody	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **DELETE**

## Operation ID: DeleteApnsVoipChannel

Disables the APNs VoIP channel for an application and deletes any existing settings for the channel.

## **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

## Responses

Status code	Response model	Description
200	APNSVoipChannelRes ponse	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).

Status code	Response model	Description
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **OPTIONS**

Retrieves information about the communication requirements and options that are available for the APNs VoIP Channel resource.

### Path parameters

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

### Responses

Status code	Response model	Description
200	None	The request succeeded.

## **Schemas**

## **Request bodies**

### **PUT schema**

```
{
   "Certificate": "string",
   "PrivateKey": "string",
   "Enabled": boolean,
   "TokenKeyId": "string",
   "TeamId": "string",
   "TokenKey": "string",
   "BundleId": "string",
   "DefaultAuthenticationMethod": "string"
}
```

# **Response bodies**

Schemas 71

### APNSVoipChannelResponse schema

```
{
   "ApplicationId": "string",
   "IsArchived": boolean,
   "Version": integer,
   "CreationDate": "string",
   "LastModifiedDate": "string",
   "LastModifiedBy": "string",
   "Id": "string",
   "Enabled": boolean,
   "HasCredential": boolean,
   "Platform": "string",
   "HasTokenKey": boolean,
   "DefaultAuthenticationMethod": "string"
}
```

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

## **Properties**

## **APNSVoipChannelRequest**

Specifies the status and settings of the APNs (Apple Push Notification service) VoIP channel for an application.

#### Certificate

The APNs client certificate that you received from Apple, if you want Amazon Pinpoint to communicate with APNs by using an APNs certificate.

**Type**: string **Required**: False

### **PrivateKey**

The private key for the APNs client certificate that you want Amazon Pinpoint to use to communicate with APNs.

**Type**: string

Required: False

#### **Enabled**

Specifies whether to enable the APNs VoIP channel for the application.

**Type**: boolean **Required**: False

## TokenKeyId

The key identifier that's assigned to your APNs signing key, if you want Amazon Pinpoint to communicate with APNs by using APNs tokens.

Type: string

Required: False

### **TeamId**

The identifier that's assigned to your Apple developer account team. This identifier is used for APNs tokens.

Type: string

**Required**: False

### **TokenKey**

The authentication key to use for APNs tokens.

Type: string

Required: False

### **BundleId**

The bundle identifier that's assigned to your iOS app. This identifier is used for APNs tokens.

**Type**: string **Required**: False

### **DefaultAuthenticationMethod**

The default authentication method that you want Amazon Pinpoint to use when authenticating with APNs, key or certificate.

**Type**: string **Required**: False

## **APNSVoipChannelResponse**

Provides information about the status and settings of the APNs (Apple Push Notification service) VoIP channel for an application.

### **ApplicationId**

The unique identifier for the application that the APNs VoIP channel applies to.

**Type**: string **Required**: False

### **IsArchived**

Specifies whether the APNs VoIP channel is archived.

**Type**: boolean **Required**: False

#### Version

The current version of the APNs VoIP channel.

**Type**: integer **Required**: False

#### CreationDate

The date and time when the APNs VoIP channel was enabled.

**Type**: string **Required**: False

#### LastModifiedDate

The date and time when the APNs VoIP channel was last modified.

**Type**: string **Required**: False

### LastModifiedBy

The user who last modified the APNs VoIP channel.

**Type**: string **Required**: False

#### Id

(Deprecated) An identifier for the APNs VoIP channel. This property is retained only for backward compatibility.

**Type**: string **Required**: False

#### **Enabled**

Specifies whether the APNs VoIP channel is enabled for the application.

**Type**: boolean **Required**: False

### **HasCredential**

(Not used) This property is retained only for backward compatibility.

**Type**: boolean **Required**: False

### **Platform**

The type of messaging or notification platform for the channel. For the APNs VoIP channel, this value is APNS\_VOIP.

**Type**: string **Required**: True

### HasTokenKey

Specifies whether the APNs VoIP channel is configured to communicate with APNs by using APNs tokens. To provide an authentication key for APNs tokens, set the TokenKey property of the channel.

**Type**: boolean **Required**: False

#### **DefaultAuthenticationMethod**

The default authentication method that Amazon Pinpoint uses to authenticate with APNs for this channel, key or certificate.

**Type**: string **Required**: False

## MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

#### Message

The message that's returned from the API.

**Type**: string **Required**: False

### See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## **GetApnsVoipChannel**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

## **UpdateApnsVoipChannel**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3

See also 77

- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

## **DeleteApnsVoipChannel**

- AWS Command Line Interface
- · AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- · AWS SDK for Python
- AWS SDK for Ruby V3

## **APNs VoIP Sandbox Channel**

A *channel* is a type of platform that you can deliver messages to. You can use the APNs VoIP sandbox channel to send VoIP notification messages to the sandbox environment of the Apple Push Notification service (APNs). Before you can use Amazon Pinpoint to send VoIP notification messages to the APNs sandbox environment, you must enable the APNs VoIP sandbox channel for an Amazon Pinpoint application.

The APNs VoIP Sandbox Channel resource represents the status and authentication settings of the APNs VoIP sandbox channel for a specific application. You can use this resource to enable, retrieve information about, update, or disable (delete) the APNs VoIP sandbox channel for an application.

### URI

/v1/apps/application-id/channels/apns\_voip\_sandbox

APNs VoIP Sandbox Channel 78

# **HTTP** methods

### **GET**

## Operation ID: GetApnsVoipSandboxChannel

Retrieves information about the status and settings of the APNs VoIP sandbox channel for an application.

## **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

## Responses

Status code	Response model	Description
200	APNSVoipSandboxCha	The request succeeded.
	<u>nnelResponse</u>	

Status code	Response model	Description
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	MessageBody	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **PUT**

## Operation ID: UpdateApnsVoipSandboxChannel

Enables the APNs VoIP sandbox channel for an application or updates the status and settings of the APNs VoIP sandbox channel for an application.

## **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

## Responses

Status code	Response model	Description
200	APNSVoipSandboxCha nnelResponse	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).

Status code	Response model	Description
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **DELETE**

**Operation ID:** DeleteApnsVoipSandboxChannel

Disables the APNs VoIP sandbox channel for an application and deletes any existing settings for the channel.

## **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

### Responses

Status code	Response model	Description
200	APNSVoipSandboxCha nnelResponse	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is

Status code	Response model	Description
		forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **OPTIONS**

Retrieves information about the communication requirements and options that are available for the APNs VoIP Sandbox Channel resource.

### Path parameters

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

### Responses

Status code	Response model	Description
200	None	The request succeeded.

## **Schemas**

## **Request bodies**

### **PUT schema**

```
{
   "Certificate": "string",
   "PrivateKey": "string",
   "Enabled": boolean,
   "TokenKeyId": "string",
   "TeamId": "string",
   "TokenKey": "string",
   "BundleId": "string",
   "DefaultAuthenticationMethod": "string"
}
```

# **Response bodies**

Schemas 85

### APNSVoipSandboxChannelResponse schema

```
{
   "ApplicationId": "string",
   "IsArchived": boolean,
   "Version": integer,
   "CreationDate": "string",
   "LastModifiedDate": "string",
   "LastModifiedBy": "string",
   "Id": "string",
   "Enabled": boolean,
   "HasCredential": boolean,
   "Platform": "string",
   "HasTokenKey": boolean,
   "DefaultAuthenticationMethod": "string"
}
```

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

## **Properties**

## **APNSVoipSandboxChannelRequest**

Specifies the status and settings of the APNs (Apple Push Notification service) VoIP sandbox channel for an application.

#### Certificate

The APNs client certificate that you received from Apple, if you want Amazon Pinpoint to communicate with the APNs sandbox environment by using an APNs certificate.

**Type**: string **Required**: False

### **PrivateKey**

The private key for the APNs client certificate that you want Amazon Pinpoint to use to communicate with the APNs sandbox environment.

**Type**: string

Required: False

#### **Enabled**

Specifies whether the APNs VoIP sandbox channel is enabled for the application.

**Type**: boolean **Required**: False

## **TokenKeyId**

The key identifier that's assigned to your APNs signing key, if you want Amazon Pinpoint to communicate with the APNs sandbox environment by using APNs tokens.

Type: string

Required: False

#### **TeamId**

The identifier that's assigned to your Apple developer account team. This identifier is used for APNs tokens.

Type: string

Required: False

## **TokenKey**

The authentication key to use for APNs tokens.

Type: string

Required: False

#### **BundleId**

The bundle identifier that's assigned to your iOS app. This identifier is used for APNs tokens.

**Type**: string **Required**: False

#### **DefaultAuthenticationMethod**

The default authentication method that you want Amazon Pinpoint to use when authenticating with the APNs sandbox environment for this channel, key or certificate.

**Type**: string **Required**: False

## **APNSVoipSandboxChannelResponse**

Provides information about the status and settings of the APNs (Apple Push Notification service) VoIP sandbox channel for an application.

### **ApplicationId**

The unique identifier for the application that the APNs VoIP sandbox channel applies to.

**Type**: string **Required**: False

### **IsArchived**

Specifies whether the APNs VoIP sandbox channel is archived.

**Type**: boolean **Required**: False

#### Version

The current version of the APNs VoIP sandbox channel.

**Type**: integer **Required**: False

#### CreationDate

The date and time when the APNs VoIP sandbox channel was enabled.

**Type**: string **Required**: False

#### LastModifiedDate

The date and time when the APNs VoIP sandbox channel was last modified.

**Type**: string **Required**: False

### LastModifiedBy

The user who last modified the APNs VoIP sandbox channel.

**Type**: string **Required**: False

#### Id

(Deprecated) An identifier for the APNs VoIP sandbox channel. This property is retained only for backward compatibility.

**Type**: string **Required**: False

#### **Enabled**

Specifies whether the APNs VoIP sandbox channel is enabled for the application.

**Type**: boolean **Required**: False

### **HasCredential**

(Not used) This property is retained only for backward compatibility.

**Type**: boolean **Required**: False

### **Platform**

The type of messaging or notification platform for the channel. For the APNs VoIP sandbox channel, this value is APNS\_VOIP\_SANDBOX.

**Type**: string **Required**: True

### HasTokenKey

Specifies whether the APNs VoIP sandbox channel is configured to communicate with APNs by using APNs tokens. To provide an authentication key for APNs tokens, set the TokenKey property of the channel.

**Type**: boolean **Required**: False

#### **DefaultAuthenticationMethod**

The default authentication method that Amazon Pinpoint uses to authenticate with the APNs sandbox environment for this channel, KEY or CERTIFICATE.

**Type**: string **Required**: False

## MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

#### Message

The message that's returned from the API.

**Type**: string **Required**: False

### See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

### **GetApnsVoipSandboxChannel**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

## **UpdateApnsVoipSandboxChannel**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin

See also 91

- AWS SDK for PHP V3
- · AWS SDK for Python
- AWS SDK for Ruby V3

## DeleteApnsVoipSandboxChannel

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- · AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **App**

An *app* represents an Amazon Pinpoint application, also referred to as a *project*, in which you define an audience and you engage this audience with tailored messages. For example, you can use an application to send push notifications to users of your iOS or Android app, send email to newsletter subscribers, or send SMS messages to your customers' mobile phones.

You can use the App resource to retrieve information about or delete an existing application. To create a new application, use the Apps resource and send a POST request to the /apps URI.

### URI

/v1/apps/application-id

## **HTTP** methods

#### **GET**

**Operation ID:** GetApp

App 92

Retrieves information about an application.

# Path parameters

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client
			understands.

## Responses

Status code	Response model	Description
200	ApplicationResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).

Status code	Response model	Description
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **DELETE**

Operation ID: DeleteApp

Deletes an application.

## **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	ApplicationResponse	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).

Status code	Response model	Description
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **OPTIONS**

Retrieves information about the communication requirements and options that are available for the App resource.

## **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

### Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Response bodies**

# ApplicationResponse schema

```
{
    "Name": "string",
    "Id": "string",
    "Arn": "string",
    "CreationDate": "string",
    "tags": {
    }
}
```

## MessageBody schema

```
{
    "RequestID": "string",
```

Schemas 97

```
""Message": "string"
}
```

# **Properties**

## **ApplicationResponse**

Provides information about an application.

#### Name

The display name of the application. This name is displayed as the **Project name** on the Amazon Pinpoint console.

**Type**: string **Required**: True

#### Id

The unique identifier for the application. This identifier is displayed as the **Project ID** on the Amazon Pinpoint console.

**Type**: string **Required**: True

#### Arn

The Amazon Resource Name (ARN) of the application.

**Type**: string **Required**: True

#### CreationDate

The creation date for the application.

**Type**: string **Required**: False

#### tags

A string-to-string map of key-value pairs that identifies the tags that are associated with the application. Each tag consists of a required tag key and an associated tag value.

**Type**: object **Required**: False

## MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

### Message

The message that's returned from the API.

**Type**: string **Required**: False

# See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## **GetApp**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2

See also 99

- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

### **DeleteApp**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- · AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Application Metrics**

An application metric is a measurable value, also referred to as a key performance indicator (KPI), that can help you monitor and assess trends related to user engagement, campaign outreach, and more for an application. For example, you can use an application metric to see a breakdown of the number of campaign messages that were opened by recipients for each campaign that's associated with an Amazon Pinpoint application. Amazon Pinpoint automatically collects, aggregates, and stores this data for all of your applications. If you integrated a mobile app with Amazon Pinpoint by using an AWS Mobile SDK, Amazon Pinpoint extends this support to include additional metrics, such as a breakdown of the percentage of push notifications that were opened by recipients of each campaign. For information about integrating a mobile app, see <a href="Integrating Amazon Pinpoint">Integrating Amazon Pinpoint</a> with Your Application in the Amazon Pinpoint Developer Guide.

Application Metrics 100

The Application Metrics resource represents a collection of standard metrics that apply to an Amazon Pinpoint application. As part of the Amazon Pinpoint Analytics APIs, this resource provides you with programmatic access to pre-aggregated data for each of these metrics. For a list of application metrics that are currently supported, see the Amazon Pinpoint Developer Guide.

You can use the Application Metrics resource to retrieve pre-aggregated data for a standard metric that applies to an application.

### **URI**

/v1/apps/application-id/kpis/daterange/kpi-name

## **HTTP** methods

### **GET**

Operation ID: GetApplicationDateRangeKpi

Retrieves (queries) pre-aggregated data for a standard metric that applies to an application.

## Path parameters

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.
kpi-name	String	True	The name of the metric, also referred to as a <i>key performan ce indicator (KPI)</i> , to retrieve data for. This value describes the associated metric and consists of two or

URI 101

Name	Туре	Required	Description
			more terms, which are comprised of lowercase alphanume ric characters, separated by a hyphen. Examples are email-open-rate and successfu l-delivery-rate. For a list of valid values, see the Amazon Pinpoint
			Developer Guide.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# **Query parameters**

Name	Туре	Required	Description
next-token	String	False	The string that specifies which page of results to return in a paginated response. This parameter is not supported for application,

Name	Туре	Required	Description
			campaign, and journey metrics.
end-time	String	False	The last date and time to retrieve data for, as part of an inclusive date range that filters the query results. This value should be in extended ISO 8601 format and use Coordinat ed Universal Time (UTC), for example: 2019-07-2 6T20:00:00Z for 8:00 PM UTC July 26, 2019.

Name	Туре	Required	Description
start-time	String	False	The first date and time to retrieve data for, as part of an inclusive date range that filters the query results. This value should be in extended ISO 8601 format and use Coordinat ed Universal Time (UTC), for example: 2019-07-1 9T20:00:00Z for 8:00 PM UTC July 19, 2019. This value should also be fewer than 90 days from the current day.
page-size	String	False	The maximum number of items to include in each page of a paginated response. This parameter is not supported for application, campaign, and journey metrics.

## Responses

Status code	Response model	Description
200	ApplicationDateRan geKpiResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).

Status code	Response model	Description
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Application Metrics resource.

## **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.
kpi-name	String	True	The name of the metric, also referred to as a key performan ce indicator (KPI), to retrieve data for. This value describes the associated metric and consists of two or more terms, which are comprised of lowercase alphanume ric characters, separated by a hyphen. Examples are

Name	Туре	Required	Description
			email-open-rate
			and successfu
			l-delivery-
			rate. For a list of
			valid values, see the
			<b>Amazon Pinpoint</b>
			Developer Guide.

### Responses

Status code	Response model	Description
200	None	The request succeeded.

## **Schemas**

# **Response bodies**

# ${\bf Application Date Range Kpi Response\ schema}$

Schemas 107

```
}

}

NextToken": "string",

"ApplicationId": "string",

"StartTime": "string",

"EndTime": "string"
}
```

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

## ApplicationDateRangeKpiResponse

Provides the results of a query that retrieved the data for a standard metric that applies to an application, and provides information about that query.

### **KpiName**

The name of the metric, also referred to as a *key performance indicator (KPI)*, that the data was retrieved for. This value describes the associated metric and consists of two or more terms, which are comprised of lowercase alphanumeric characters, separated by a hyphen. For a list of possible values, see the Amazon Pinpoint Developer Guide.

**Type**: string **Required**: True

### **KpiResult**

An array of objects that contains the results of the query. Each object contains the value for the metric and metadata about that value.

Type: BaseKpiResult

Required: True

#### NextToken

The string to use in a subsequent request to get the next page of results in a paginated response. This value is null for the Application Metrics resource because the resource returns all results in a single page.

**Type**: string **Required**: False

### **ApplicationId**

The unique identifier for the application that the metric applies to.

**Type**: string **Required**: True

#### **StartTime**

The first date and time of the date range that was used to filter the query results, in extended ISO 8601 format. The date range is inclusive.

**Type**: string **Required**: True

#### **EndTime**

The last date and time of the date range that was used to filter the query results, in extended ISO 8601 format. The date range is inclusive.

**Type**: string **Required**: True

# BaseKpiResult

Provides the results of a query that retrieved the data for a standard metric that applies to an application, campaign, or journey.

#### **Rows**

An array of objects that provides the results of a query that retrieved the data for a standard metric that applies to an application, campaign, or journey.

**Type**: Array of type ResultRow

Required: True

## MessageBody

Provides information about an API request or response.

### **RequestID**

The unique identifier for the request or response.

Type: string

Required: False

### Message

The message that's returned from the API.

Type: string

Required: False

### ResultRow

Provides the results of a query that retrieved the data for a standard metric that applies to an application, campaign, or journey.

## GroupedBys

An array of objects that defines the field and field values that were used to group data in a result set that contains multiple results. This value is null if the data in a result set isn't grouped.

Type: Array of type ResultRowValue

Required: True

#### **Values**

An array of objects that provides pre-aggregated values for a standard metric that applies to an application, campaign, or journey.

Type: Array of type ResultRowValue

Required: True

#### **ResultRowValue**

Provides a single value and metadata about that value as part of an array of query results for a standard metric that applies to an application, campaign, or journey.

### Key

The friendly name of the metric whose value is specified by the Value property.

Type: string

**Required**: True

#### **Value**

In a Values object, the value for the metric that the query retrieved data for. In a GroupedBys object, the value for the field that was used to group data in a result set that contains multiple results (Values objects).

**Type**: string

Required: True

### Type

The data type of the value specified by the Value property.

Type: string

**Required**: True

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## GetApplicationDateRangeKpi

- AWS Command Line Interface
- · AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Apps**

An *app* represents an Amazon Pinpoint application, also referred to as a *project*, in which you define an audience and you engage this audience with tailored messages. For example, you can use an application to send push notifications to users of your iOS or Android app, send email to newsletter subscribers, or send SMS messages to your customers' mobile phones.

After you create an application, you can define your audience by registering endpoints and defining segments. To engage your audience, define campaigns or write direct messages, and send your messages by using any supported channel, including channels for mobile push notifications, email, SMS, and voice. You can then monitor application analytics by creating an event stream, which streams data for message deliveries and events that your app reports to Amazon Pinpoint. Analytics are also provided on the Amazon Pinpoint console.

You can use the Apps resource to create a new application or retrieve information about all of your existing applications. To delete an application, use the <a href="App">App</a> resource and send a DELETE request to the /apps/application-id URI.

See also 112

## **URI**

/v1/apps

# **HTTP** methods

## **GET**

# **Operation ID:** GetApps

Retrieves information about all the applications that are associated with your Amazon Pinpoint account.

## **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

## **Query parameters**

Name	Туре	Required	Description
token	String	False	The NextToken string that specifies which page of results to return in a paginated response.
page-size	String	False	The maximum number of items to include in each page of a paginated response.

URI 113

Name	Туре	Required	Description
			This parameter
			is not supported
			for application,
			campaign, and
			journey metrics.

# Responses

Status code	Response model	Description
200	ApplicationsResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).

Status code	Response model	Description
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **POST**

**Operation ID:** CreateApp

Creates an application.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

## Responses

Status code	Response model	Description
201	ApplicationResponse	The request succeeded and the specified resource was created.

Status code	Response model	Description
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Apps resource.

## Responses

Status code	Response model	Description
200	None	The request succeeded.

## **Schemas**

## **Request bodies**

#### **POST schema**

```
{
    "Name": "string",
    "tags": {
    }
}
```

# **Response bodies**

## **ApplicationsResponse schema**

Schemas 117

## ApplicationResponse schema

```
{
    "Name": "string",
    "Id": "string",
    "Arn": "string",
    "CreationDate": "string",
    "tags": {
    }
}
```

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

## **ApplicationResponse**

Provides information about an application.

#### Name

The display name of the application. This name is displayed as the **Project name** on the Amazon Pinpoint console.

**Type**: string **Required**: True

#### Id

The unique identifier for the application. This identifier is displayed as the **Project ID** on the Amazon Pinpoint console.

Type: string

### Required: True

#### Arn

The Amazon Resource Name (ARN) of the application.

**Type**: string **Required**: True

#### CreationDate

The creation date for the application.

**Type**: string **Required**: False

#### tags

A string-to-string map of key-value pairs that identifies the tags that are associated with the application. Each tag consists of a required tag key and an associated tag value.

**Type**: object **Required**: False

# ${\bf Applications Response}$

Provides information about all of your applications.

#### NextToken

The string to use in a subsequent request to get the next page of results in a paginated response. This value is null if there are no additional pages.

**Type**: string **Required**: False

#### Item

An array of responses, one for each application that was returned.

Type: Array of type ApplicationResponse

Required: False

## CreateApplicationRequest

Specifies the display name of an application and the tags to associate with the application.

#### Name

The display name of the application. This name is displayed as the **Project name** on the Amazon Pinpoint console.

**Type**: string **Required**: True

#### tags

A string-to-string map of key-value pairs that defines the tags to associate with the application. Each tag consists of a required tag key and an associated tag value.

**Type**: object **Required**: False

## MessageBody

Provides information about an API request or response.

## RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

### Message

The message that's returned from the API.

Type: string

### Required: False

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## **GetApps**

- AWS Command Line Interface
- · AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

## CreateApp

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

See also 121

## **Attributes**

An *attribute* is a characteristic of a user or an endpoint. It can be a standard attribute that Amazon Pinpoint defines or a custom attribute that you define. For example, you might create custom attributes that capture your users' contact information, their preferences, and the dates when they opted in or out of receiving specific types of messages from you.

The Attributes resource represents custom attributes that you've defined for users and endpoints that are associated with a specific application. You can use this resource to remove one or more custom attributes from the Amazon Pinpoint application. Existing endpoints continue to persist these attributes and these existing values continue to appear on the Amazon Pinpoint console and in export jobs. However, Amazon Pinpoint stops capturing new or changed values for a custom attribute. For information about the attributes that you can use to define an endpoint, see the Endpoint resource.

To retrieve a list of custom attributes and attribute values for a specific user, use the <u>User</u> resource. To add or retrieve custom attributes and attribute values for endpoints, use the <u>Endpoints</u> or <u>Endpoint</u> resource.

### **URI**

/v1/apps/application-id/attributes/attribute-type

### **HTTP** methods

#### **PUT**

**Operation ID:** RemoveAttributes

Removes one or more custom attributes, of the same attribute type, from the application. Existing endpoints still have the attributes but Amazon Pinpoint will stop capturing new or changed values for these attributes.

### Path parameters

Name	Type	Required	Description
attribute-type	String	True	The type of attribute or attributes to

Attributes 122

Name Type Required Description

remove. Valid values are:

- endpointcustom-at tributes –
   Custom attribute s that describe endpoints, such as the date when an associated user opted in or out of receiving communications from you through a specific type of channel.
- endpoint metric-at
   tributes Custom metrics
   that your app
   reports to Amazon
   Pinpoint for
   endpoints, such
   as the number of
   app sessions or the
   number of items
   left in a cart.
- endpoint user-attr
   ibutes Custom
   attributes that
   describe users, such

Name	Type	Required	Description
			as first name, last name, and age.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

## Responses

Status code	Response model	Description
200	AttributesResource	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).

Status code	Response model	Description
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Attributes resource.

## **Path parameters**

Name	Туре	Required	Description
attribute-type	String	True	The type of attribute or attributes to remove. Valid values are:
			<ul> <li>endpoint-custom-at tributes — Custom attribute s that describe endpoints, such as the date when an associated user opted in or out of receiving communications from you through a specific type of channel.</li> <li>endpoint-metric-at tributes — Custom metrics that your app reports to Amazon Pinpoint for endpoints, such as the number of app sessions or the number of items left in a cart.</li> <li>endpoint-</li> </ul>
			user-attr

Name	Туре	Required	Description
			ibutes – Custom attributes that describe users, such as first name, last name, and age.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Request bodies**

## **PUT schema**

```
{
    "Blacklist": [
        "string"
    ]
}
```

# **Response bodies**

Schemas 127

### AttributesResource schema

```
{
   "ApplicationId": "string",
   "AttributeType": "string",
   "Attributes": [
     "string"
]
}
```

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

## **AttributesResource**

Provides information about the type and the names of attributes that were removed from all the endpoints that are associated with an application.

### **ApplicationId**

The unique identifier for the application.

**Type**: string **Required**: True

## AttributeType

The type of attribute or attributes that were removed from the endpoints. Valid values are:

- endpoint-custom-attributes Custom attributes that describe endpoints.
- endpoint-metric-attributes Custom metrics that your app reports to Amazon Pinpoint for endpoints.
- endpoint-user-attributes Custom attributes that describe users.

**Type**: string **Required**: True

#### **Attributes**

An array that specifies the names of the remaining attributes after any attributes were removed from the endpoints.

**Type**: Array of type string

Required: False

## MessageBody

Provides information about an API request or response.

#### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

#### Message

The message that's returned from the API.

**Type**: string **Required**: False

## UpdateAttributesRequest

Specifies one or more attributes to remove from all the endpoints that are associated with an application.

#### **Blacklist**

An array of the attributes to remove from all the endpoints that are associated with the application. The array can specify the complete, exact name of each attribute to remove or it can specify a glob pattern that an attribute name must match in order for the attribute to be removed.

**Type**: Array of type string

**Required**: False

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

#### RemoveAttributes

- AWS Command Line Interface
- · AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

## **Baidu Channel**

A *channel* is a type of platform that you can deliver messages to. You can use the Baidu channel to send push notification messages to the Baidu Cloud Push service, which is a Chinese cloud service. Before you can use Amazon Pinpoint to send notification messages to the Baidu Cloud Push service, you must enable the Baidu channel for an Amazon Pinpoint application.

The Baidu Channel resource represents the status and authentication settings of the Baidu channel for a specific application. You can use this resource to enable, retrieve information about, update, or disable (delete) the Baidu channel for an application.

### URI

/v1/apps/application-id/channels/baidu

See also 130

# **HTTP** methods

# **GET**

# Operation ID: GetBaiduChannel

Retrieves information about the status and settings of the Baidu channel for an application.

# **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	BaiduChannelResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).

Status code	Response model	Description
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **PUT**

# Operation ID: UpdateBaiduChannel

Enables the Baidu channel for an application or updates the status and settings of the Baidu channel for an application.

# **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	BaiduChannelResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is

Status code	Response model	Description
		forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **DELETE**

# Operation ID: DeleteBaiduChannel

Disables the Baidu channel for an application and deletes any existing settings for the channel.

# **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	BaiduChannelResponse	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	MessageBody	The request was denied because access to the specified resource is forbidden (ForbiddenException).

Status code	Response model	Description
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Baidu Channel resource.

### **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

### Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Request bodies**

#### **PUT schema**

```
{
  "ApiKey": "string",
  "SecretKey": "string",
  "Enabled": boolean
}
```

# **Response bodies**

### BaiduChannelResponse schema

```
{
  "ApplicationId": "string",
  "IsArchived": boolean,
  "Version": integer,
  "CreationDate": "string",
```

```
"LastModifiedDate": "string",

"LastModifiedBy": "string",

"Id": "string",

"Enabled": boolean,

"HasCredential": boolean,

"Platform": "string",

"Credential": "string"
}
```

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

# BaiduChannelRequest

Specifies the status and settings of the Baidu (Baidu Cloud Push) channel for an application.

### **ApiKey**

The API key that you received from the Baidu Cloud Push service to communicate with the service.

**Type**: string **Required**: True

#### SecretKey

The secret key that you received from the Baidu Cloud Push service to communicate with the service.

**Type**: string **Required**: True

#### **Enabled**

Specifies whether to enable the Baidu channel for the application.

Properties 138

**Type**: boolean **Required**: False

# BaiduChannelResponse

Provides information about the status and settings of the Baidu (Baidu Cloud Push) channel for an application.

### **ApplicationId**

The unique identifier for the application that the Baidu channel applies to.

**Type**: string **Required**: False

#### **IsArchived**

Specifies whether the Baidu channel is archived.

**Type**: boolean **Required**: False

#### Version

The current version of the Baidu channel.

**Type**: integer **Required**: False

#### CreationDate

The date and time when the Baidu channel was enabled.

**Type**: string **Required**: False

#### LastModifiedDate

The date and time when the Baidu channel was last modified.

Properties 139

**Type**: string **Required**: False

### LastModifiedBy

The user who last modified the Baidu channel.

**Type**: string **Required**: False

#### Id

(Deprecated) An identifier for the Baidu channel. This property is retained only for backward compatibility.

**Type**: string **Required**: False

#### **Enabled**

Specifies whether the Baidu channel is enabled for the application.

**Type**: boolean **Required**: False

#### HasCredential

(Not used) This property is retained only for backward compatibility.

**Type**: boolean **Required**: False

#### **Platform**

The type of messaging or notification platform for the channel. For the Baidu channel, this value is BAIDU.

Type: string

Properties 140

Required: True

#### Credential

The API key that you received from the Baidu Cloud Push service to communicate with the service.

**Type**: string **Required**: True

### MessageBody

Provides information about an API request or response.

#### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

### Message

The message that's returned from the API.

**Type**: string **Required**: False

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

#### **GetBaiduChannel**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2

See also 141

- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

### **UpdateBaiduChannel**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

### **DeleteBaiduChannel**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

See also 142

# Campaign

A *campaign* is a messaging initiative that engages a specific segment of users for an Amazon Pinpoint application. The information represented by this resource includes the segment of users that a campaign sends messages to, the message that a campaign delivers, and the schedule on which a campaign runs.

You can use the Campaign resource to retrieve information about, update, or delete a specific campaign. To create a campaign, use the <u>Campaigns</u> resource and send a POST request to the / apps/application-id/campaigns URI.

### **URI**

/v1/apps/application-id/campaigns/campaign-id

### **HTTP** methods

### **GET**

Operation ID: GetCampaign

Retrieves information about the status, configuration, and other settings for a campaign.

### Path parameters

Name	Туре	Required	Description
campaign-id	String	True	The unique identifier for the campaign.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

Campaign 143

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	CampaignResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	MessageBody	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	MessageBody	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	MessageBody	The request failed because the payload for the body of the request is too large

Status code	Response model	Description
		(RequestEntityTooLargeExcep tion).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **PUT**

# Operation ID: UpdateCampaign

Updates the configuration and other settings for a campaign.

# **Path parameters**

Name	Туре	Required	Description
campaign-id	String	True	The unique identifier for the campaign.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	CampaignResponse	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	MessageBody	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	MessageBody	The request failed because the specified resource was not found (NotFoundException).
405	MessageBody	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	MessageBody	The request failed because the payload for the body of the request is too large

Status code	Response model	Description
		(RequestEntityTooLargeExcep tion).
429	MessageBody	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **DELETE**

Operation ID: DeleteCampaign

Deletes a campaign from an application.

# Path parameters

Name	Туре	Required	Description
campaign-id	String	True	The unique identifier for the campaign.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	CampaignResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	MessageBody	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	MessageBody	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large

Status code	Response model	Description
		(RequestEntityTooLargeExcep tion).
429	MessageBody	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Campaign resource.

# **Path parameters**

Name	Туре	Required	Description
campaign-id	String	True	The unique identifier for the campaign.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

#### Responses

Status code	Response model	Description
200	None	The request succeeded.

### **Schemas**

### **Request bodies**

#### **PUT schema**

```
"TreatmentName": "string",
"TreatmentDescription": "string",
"MessageConfiguration": {
  "DefaultMessage": {
    "Body": "string",
    "Title": "string",
    "ImageUrl": "string",
    "ImageIconUrl": "string",
    "ImageSmallIconUrl": "string",
    "MediaUrl": "string",
    "Action": enum,
    "Url": "string",
    "SilentPush": boolean,
    "JsonBody": "string",
    "RawContent": "string",
    "TimeToLive": integer
  },
  "APNSMessage": {
    "Body": "string",
    "Title": "string",
    "ImageUrl": "string",
    "ImageIconUrl": "string",
    "ImageSmallIconUrl": "string",
    "MediaUrl": "string",
    "Action": enum,
    "Url": "string",
    "SilentPush": boolean,
    "JsonBody": "string",
    "RawContent": "string",
```

```
"TimeToLive": integer
},
"GCMMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"ADMMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"BaiduMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUr<u>l</u>": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "<u>JsonBody</u>": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
```

```
"EmailMessage": {
  "Body": "string",
  "Title": "string",
  "HtmlBody": "string",
  "FromAddress": "string",
  "Headers": [
    {
      "Name": "string",
      ""Value": "string"
    }
  ]
},
"SMSMessage": {
  "Body": "string",
  "MessageType": enum,
  "SenderId": "string",
  "OriginationNumber": "string",
  "EntityId": "string",
  "TemplateId": "string"
},
"CustomMessage": {
  "Data": "string"
},
"InAppMessage": {
  "Body": "string",
  "Layout": enum,
  "Content": [
    {
      "HeaderConfig": {
        "Header": "string",
        "TextColor": "string",
        "Alignment": enum
      },
      "BackgroundColor": "string",
      "BodyConfig": {
        "Body": "string",
        "TextColor": "string",
        "Alignment": enum
      },
      "ImageUrl": "string",
      "PrimaryBtn": {
        "DefaultConfig": {
          "Text": "string",
          "ButtonAction": enum,
```

```
"Link": "string",
        "TextColor": "string",
        "BackgroundColor": "string",
        "BorderRadius": integer
      },
      "Web": {
        "ButtonAction": enum,
        "Link": "string"
      },
      "IOS": {
        "ButtonAction": enum,
        "Link": "string"
      },
      "Android": {
        "ButtonAction": enum,
        "Link": "string"
      }
    },
    "SecondaryBtn": {
      "DefaultConfig": {
        "Text": "string",
        "ButtonAction": enum,
        "Link": "string",
        "TextColor": "string",
        "BackgroundColor": "string",
        "BorderRadius": integer
      },
      "Web": {
        "ButtonAction": enum,
        "Link": "string"
      },
      "IOS": {
        "ButtonAction": enum,
        "Link": "string"
      },
      "Android": {
        "ButtonAction": enum,
        "Link": "string"
      }
    }
 }
],
"CustomConfig": {
}
```

```
}
},
"Sche<u>dule</u>": {
  "StartTime": "string",
  "EndTime": "string",
  "Frequency": enum,
  "IsLocalTime": boolean,
  "<u>Timezone</u>": "string",
  "QuietTime": {
    "Start": "string",
    "End": "string"
  },
  "EventFilter": {
    "Dimensions": {
      "EventType": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      },
      "Attributes": {
      },
      "Metrics": {
      }
    },
    "FilterType": enum
  }
},
"TemplateConfiguration": {
  "SMSTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "EmailTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "PushTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "VoiceTemplate": {
    "Name": "string",
    "Version": "string"
```

```
},
  "InAppT<u>emplate</u>": {
    "Name": "string",
    "Version": "string"
  }
},
"CustomDeliveryConfiguration": {
  "EndpointTypes": [
    enum
  ],
  "DeliveryUri": "string"
},
"SegmentId": "string",
"SegmentVersion": integer,
"IsPaused": boolean,
"AdditionalTreatments": [
  {
    "TreatmentName": "string",
    "TreatmentDescription": "string",
    "MessageConfiguration": {
      "DefaultMessage": {
        "Body": "string",
        "Title": "string",
        "ImageUrl": "string",
        "ImageIconUrl": "string",
        "ImageSmallIconUrl": "string",
        "MediaUrl": "string",
        "Action": enum,
        "Url": "string",
        "SilentPush": boolean,
        "JsonBody": "string",
        "RawContent": "string",
        "TimeToLive": integer
      },
      "APNSMessage": {
        "Body": "string",
        "Title": "string",
        "ImageUrl": "string",
        "ImageIconUrl": "string",
        "ImageSmallIconUrl": "string",
        ""MediaUrl": "string",
        "Action": enum,
        "Url": "string",
        "SilentPush": boolean,
```

```
"JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"GCMMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"ADMMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"BaiduMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
```

```
"TimeToLive": integer
},
"EmailMessage": {
  "Body": "string",
  "Title": "string",
  "HtmlBody": "string",
  "FromAddress": "string",
  "Headers": [
    {
      "Name": "string",
      "Value": "string"
   }
 ]
},
"SMSMessage": {
 "Body": "string",
  "MessageType": enum,
  "SenderId": "string",
  "OriginationNumber": "string",
 "EntityId": "string",
 "TemplateId": "string"
},
"CustomMessage": {
 "Data": "string"
},
"InAppMessage": {
 "Body": "string",
  "Layout": enum,
  "Content": [
    }
      "HeaderConfig": {
        "Header": "string",
        "TextColor": "string",
        "Alignment": enum
      "BackgroundColor": "string",
      "BodyConfig": {
        "Body": "string",
        "TextColor": "string",
        "Alignment": enum
      },
      "ImageUrl": "string",
      "PrimaryBtn": {
        "DefaultConfig": {
```

```
"Text": "string",
        "ButtonAction": enum,
        "Link": "string",
        "TextColor": "string",
        "BackgroundColor": "string",
        "BorderRadius": integer
      },
      "Web": {
        "ButtonAction": enum,
        "Link": "string"
      },
      "IOS": {
        "ButtonAction": enum,
        "Link": "string"
      },
      "Android": {
        "ButtonAction": enum,
        "Link": "string"
      }
    },
    "SecondaryBtn": {
      "DefaultConfig": {
        "Text": "string",
        "ButtonAction": enum,
        "Link": "string",
        "TextColor": "string",
        "BackgroundColor": "string",
        "BorderRadius": integer
      },
      "Web": {
        "ButtonAction": enum,
        "Link": "string"
      },
      "IOS": {
        "ButtonAction": enum,
        "Link": "string"
      },
      "Android": {
        "ButtonAction": enum,
        "Link": "string"
      }
    }
 }
],
```

```
"CustomConfig": {
 }
},
"Schedule": {
  "StartTime": "string",
  "EndTime": "string",
  "Frequency": enum,
  "IsLocalTime": boolean,
  "Timezone": "string",
  "QuietTime": {
    "Start": "string",
    "End": "string"
  },
  "EventFilter": {
    "Dimensions": {
      "EventType": {
        "DimensionType": enum,
        "Values": [
          "string"
      },
      "Attributes": {
      },
      "Metrics": {
      }
    },
    "FilterType": enum
  }
},
"TemplateConfiguration": {
  "SMSTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "EmailTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "PushTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "VoiceTemplate": {
```

```
"Name": "string",
          "Version": "string"
        },
        "InAppTemplate": {
          "Name": "string",
          "Version": "string"
        }
      },
      "CustomDeliveryConfiguration": {
        "EndpointTypes": [
          enum
        ],
        "<u>DeliveryUri</u>": "string"
      "SizePercent": integer
    }
  ],
  "HoldoutPercent": integer,
  "Limits": {
    "Daily": integer,
    "Total": integer,
    "Session": integer,
    "MessagesPerSecond": integer,
    "MaximumDuration": integer
  },
  "Name": "string",
  "Hook": {
    "LambdaFunctionName": "string",
    "WebUrl": "string",
    "Mode": enum
  },
  "Description": "string",
  "tags": {
  },
  "Priority": integer
}
```

# **Response bodies**

#### CampaignResponse schema

```
{
    "TreatmentName": "string",
```

```
"TreatmentDescription": "string",
"MessageConfiguration": {
  "DefaultMessage": {
    "Body": "string",
    "Title": "string",
    "ImageUrl": "string",
    "ImageIconUrl": "string",
    "ImageSmallIconUrl": "string",
    "MediaUrl": "string",
    "Action": enum,
    "Url": "string",
    "SilentPush": boolean,
    "JsonBody": "string",
    "RawContent": "string",
    "<u>TimeToLive</u>": integer
  },
  "APNSMessage": {
    "Body": "string",
    "Title": "string",
    "ImageUrl": "string",
    "ImageIconUrl": "string",
    "ImageSmallIconUrl": "string",
    "MediaUrl": "string",
    "Action": enum,
    "Url": "string",
    "SilentPush": boolean,
    "JsonBody": "string",
    "RawContent": "string",
    "TimeToLive": integer
  },
  "GCMMessage": {
    "Body": "string",
    "Title": "string",
    "ImageUr<u>l</u>": "string",
    "ImageIconUrl": "string",
    "ImageSmallIconUrl": "string",
    "MediaUrl": "string",
    "Action": enum,
    "Url": "string",
    "SilentPush": boolean,
    "<u>JsonBody</u>": "string",
    "RawContent": "string",
    "TimeToLive": integer
  },
```

```
"ADMMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"BaiduMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"EmailMessage": {
  "Body": "string",
  "Title": "string",
  "HtmlBody": "string",
  "FromAddress": "string",
  "Headers": [
    {
      "Name": "string",
      "Value": "string"
    }
  ]
},
"SMSMessage": {
  "Body": "string",
  "MessageType": enum,
  "SenderId": "string",
```

```
"OriginationNumber": "string",
  "EntityId": "string",
  "TemplateId": "string"
},
"CustomMessage": {
  "Data": "string"
},
"InAppMessage": {
  "Body": "string",
  "Layout": enum,
  "Content": [
    {
      "HeaderConfig": {
        "Header": "string",
        "TextColor": "string",
        "Alignment": enum
      },
      "BackgroundColor": "string",
      "BodyConfig": {
        "Body": "string",
        "TextColor": "string",
        "Alignment": enum
      },
      "ImageUrl": "string",
      "PrimaryBtn": {
        "DefaultConfig": {
          "Text": "string",
          "ButtonAction": enum,
          "Link": "string",
          "TextColor": "string",
          "BackgroundColor": "string",
          "BorderRadius": integer
        },
        "Web": {
          "ButtonAction": enum,
          "Link": "string"
        },
        "IOS": {
          "ButtonAction": enum,
          "Link": "string"
        },
        "Android": {
          "ButtonAction": enum,
          "Link": "string"
```

```
}
        },
        "SecondaryBtn": {
          "DefaultConfig": {
            "Text": "string",
            "ButtonAction": enum,
            "Link": "string",
            "TextColor": "string",
            "BackgroundColor": "string",
            "BorderRadius": integer
          },
          "Web": {
            "ButtonAction": enum,
            "Link": "string"
          },
          "IOS": {
            "ButtonAction": enum,
            "Link": "string"
          },
          "Android": {
            "ButtonAction": enum,
            "Link": "string"
          }
        }
      }
    ],
    "CustomConfig": {
    }
  }
},
"Schedule": {
  "StartTime": "string",
 "EndTime": "string",
  "Frequency": enum,
  "IsLocalTime": boolean,
  "Timezone": "string",
  "QuietTime": {
    "Start": "string",
    "End": "string"
  },
  "EventFilter": {
    "Dimensions": {
      "EventType": {
        "DimensionType": enum,
```

```
"Values": [
          "string"
        ]
      },
      "Attributes": {
      },
      "Metrics": {
    },
    "FilterType": enum
  }
},
"TemplateConfiguration": {
  "SMSTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "EmailTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "PushTemplate": {
    "Name": "string",
    ""Version": "string"
  },
  "VoiceTemplate": {
    "Name": "string",
    "Version": "string"
 },
  "InAppTemplate": {
    "Name": "string",
    "Version": "string"
  }
},
"CustomDeliveryConfiguration": {
  "EndpointTypes": [
    enum
  ],
  "DeliveryUri": "string"
},
"Id": "string",
"ApplicationId": "string",
""CreationDate": "string",
"LastModifiedDate": "string",
```

```
"SegmentId": "string",
"SegmentVersion": integer,
"AdditionalTreatments": [
  {
    "TreatmentName": "string",
    "TreatmentDescription": "string",
    "MessageConfiguration": {
      "DefaultMessage": {
        "Body": "string",
        "Title": "string",
        "ImageUrl": "string",
        "ImageIconUrl": "string",
        "ImageSmallIconUrl": "string",
        "MediaUrl": "string",
        "Action": enum,
        "Url": "string",
        "SilentPush": boolean,
        "JsonBody": "string",
        "RawContent": "string",
        "TimeToLive": integer
      },
      "APNSM<u>essage</u>": {
        "Body": "string",
        "Title": "string",
        "ImageUrl": "string",
        "ImageIconUrl": "string",
        "ImageSmallIconUrl": "string",
        "MediaUrl": "string",
        "Action": enum,
        "Url": "string",
        "SilentPush": boolean,
        "JsonBody": "string",
        "RawContent": "string",
        "TimeToLive": integer
      },
      "GCMMessage": {
        "Body": "string",
        "Title": "string",
        "ImageUrl": "string",
        "ImageIconUrl": "string",
        "ImageSmallIconUrl": "string",
        "MediaUrl": "string",
        "Action": enum,
        "Url": "string",
```

```
"SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"ADMMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
 "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"BaiduMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
 "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
 "TimeToLive": integer
},
"EmailMessage": {
  "Body": "string",
  "Title": "string",
  "HtmlBody": "string",
  "FromAddress": "string",
  "Headers": [
    {
      "Name": "string",
      "Value": "string"
    }
  ]
```

```
},
"SMSMessage": {
 "Body": "string",
  "MessageType": enum,
  "SenderId": "string",
  "OriginationNumber": "string",
 "EntityId": "string",
 "TemplateId": "string"
},
"CustomMessage": {
 "Data": "string"
},
"InAppMessage": {
  "Body": "string",
  "Layout": enum,
  "Content": [
    {
      "HeaderConfig": {
        "Header": "string",
        "TextColor": "string",
        "Alignment": enum
      },
      "BackgroundColor": "string",
      "BodyConfig": {
        "Body": "string",
        "TextColor": "string",
        "Alignment": enum
      },
      "ImageUrl": "string",
      "PrimaryBtn": {
        "DefaultConfig": {
          "Text": "string",
          "ButtonAction": enum,
          "Link": "string",
          "TextColor": "string",
          "BackgroundColor": "string",
          "BorderRadius": integer
        },
        "Web": {
          "ButtonAction": enum,
          "Link": "string"
        },
        "IOS": {
          "ButtonAction": enum,
```

```
"Link": "string"
          },
          "Android": {
            "ButtonAction": enum,
            "Link": "string"
          }
        },
        "SecondaryBtn": {
          "DefaultConfig": {
            "Text": "string",
            "ButtonAction": enum,
            "Link": "string",
            "TextColor": "string",
            "BackgroundColor": "string",
            "BorderRadius": integer
          },
          "Web": {
            "ButtonAction": enum,
            "Link": "string"
          },
          "IOS": {
            "ButtonAction": enum,
            "Link": "string"
          },
          "Android": {
            "ButtonAction": enum,
            "Link": "string"
          }
        }
      }
    ],
    "CustomConfig": {
  }
},
"Schedule": {
  "StartTime": "string",
  "EndTime": "string",
  "Frequency": enum,
  "IsLocalTime": boolean,
  "<u>Timezone</u>": "string",
  "QuietTime": {
    "Start": "string",
    "End": "string"
```

```
},
  "EventFilter": {
    "Dimensions": {
      "EventType": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      },
      "Attributes": {
      },
      "Metrics": {
      }
    "FilterType": enum
  }
},
"TemplateConfiguration": {
  "SMSTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "EmailTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "PushTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "VoiceTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "InAppTemplate": {
    "Name": "string",
    "Version": "string"
  }
},
"CustomDeliveryConfiguration": {
  "EndpointTypes": [
    enum
  ],
  "DeliveryUri": "string"
```

```
},
      "SizePercent": integer,
      "Id": "string",
      "State": {
        "CampaignStatus": enum
    }
  ],
  "HoldoutPercent": integer,
  "Name": "string",
  "Limits": {
    "Daily": integer,
    "Total": integer,
    "Session": integer,
    "MessagesPerSecond": integer,
    "MaximumDuration": integer
  },
  "Description": "string",
  "Hook": {
    "LambdaFunctionName": "string",
    "WebUrl": "string",
    "Mode": enum
  },
  "State": {
    "CampaignStatus": enum
  },
  "DefaultState": {
    "CampaignStatus": enum
  },
  "Version": integer,
  "IsPaused": boolean,
  "Arn": "string",
  "tags": {
  },
  "Priority": integer
}
```

# MessageBody schema

```
{
    "<u>RequestID</u>": "string",
    "<u>Message</u>": "string"
```

}

# **Properties**

### **AttributeDimension**

Specifies attribute-based criteria for including or excluding endpoints from a segment.

# AttributeType

The type of segment dimension to use. Valid values are:

- INCLUSIVE endpoints that have attributes matching the values are included in the segment.
- EXCLUSIVE endpoints that have attributes matching the values are excluded from the segment.
- CONTAINS endpoints that have attributes' substrings match the values are included in the segment.
- BEFORE endpoints with attributes read as ISO\_INSTANT datetimes before the value are included in the segment.
- AFTER endpoints with attributes read as ISO\_INSTANT datetimes after the value are included in the segment.
- BETWEEN endpoints with attributes read as ISO\_INSTANT datetimes between the values are included in the segment.
- ON endpoints with attributes read as ISO\_INSTANT dates on the value are included in the segment. Time is ignored in this comparison.

**Type**: string **Required**: False

Values: INCLUSIVE | EXCLUSIVE | CONTAINS | BEFORE | AFTER | BETWEEN |

NOT\_BETWEEN | ON

#### **Values**

The criteria values to use for the segment dimension. Depending on the value of the AttributeType property, endpoints are included or excluded from the segment if their attribute values match the criteria values.

**Type**: Array of type string

Required: True

# CampaignCustomMessage

Specifies the contents of a message that's sent through a custom channel to recipients of a campaign.

#### Data

The raw, JSON-formatted string to use as the payload for the message. The maximum size is 5 KB.

**Type**: string **Required**: False

# CampaignEmailMessage

Specifies the content and "From" address for an email message that's sent to recipients of a campaign.

# **Body**

The body of the email for recipients whose email clients don't render HTML content.

**Type**: string **Required**: False

#### Title

The subject line, or title, of the email.

**Type**: string **Required**: False

# HtmlBody

The body of the email, in HTML format, for recipients whose email clients render HTML content.

**Type**: string **Required**: False

#### **FromAddress**

The verified email address to send the email from. The default address is the FromAddress specified for the email channel for the application.

**Type**: string **Required**: False

#### **Headers**

The list of MessageHeaders for the email. You can have up to 15 MessageHeaders for each email.

**Type**: Array of type MessageHeader

Required: False

# CampaignEventFilter

Specifies the settings for events that cause a campaign to be sent.

### **Dimensions**

The dimension settings of the event filter for the campaign.

**Type**: EventDimensions

Required: True

## **FilterType**

The type of event that causes the campaign to be sent. Valid values are: SYSTEM, sends the campaign when a system event occurs; and, ENDPOINT, sends the campaign when an endpoint event (Events resource) occurs.

**Type**: string **Required**: True

Values: SYSTEM | ENDPOINT | USER

# CampaignHook

Specifies settings for invoking an AWS Lambda function that customizes a segment for a campaign.

#### LambdaFunctionName

The name or Amazon Resource Name (ARN) of the AWS Lambda function that Amazon Pinpoint invokes to customize a segment for a campaign.

Type: string

Required: False

### WebUrl

The web URL that Amazon Pinpoint calls to invoke the AWS Lambda function over HTTPS.

**Type**: string

Required: False

#### Mode

The mode that Amazon Pinpoint uses to invoke the AWS Lambda function. Possible values are:

- FILTER Invoke the function to customize the segment that's used by a campaign.
- DELIVERY (Deprecated) Previously, invoked the function to send a campaign through a custom channel. This functionality is not supported anymore. To send a campaign through a custom channel, use the CustomDeliveryConfiguration and CampaignCustomMessage objects of the campaign.

**Type**: string

Required: False

Values: DELIVERY | FILTER

# CampaignInAppMessage

Specifies the appearance of an in-app message, including the message type, the title and body text, text and background colors, and the configurations of buttons that appear in the message.

### **Body**

The body text of the in-app notification.

**Type**: string **Required**: False

## Layout

A string that describes how the in-app message will appear. You can specify one of the following:

- BOTTOM\_BANNER a message that appears as a banner at the bottom of the page.
- TOP BANNER a message that appears as a banner at the top of the page.
- OVERLAYS a message that covers entire screen.
- MOBILE\_FEED a message that appears in a window in front of the page.
- MIDDLE\_BANNER a message that appears as a banner in the middle of the page.
- CAROUSEL a scrollable layout of up to five unique messages.

Type: string

**Required**: False

Values: BOTTOM\_BANNER | TOP\_BANNER | OVERLAYS | MOBILE\_FEED | MIDDLE\_BANNER

| CAROUSEL

### Content

An array that contains configurtion information about the in-app message for the campaign, including title and body text, text colors, background colors, image URLs, and button configurations.

Type: Array of type InAppMessageContent

Required: False

## CustomConfig

An object that contains custom data (in the form of key-value pairs) that is included in the in-app messaging payload.

**Type**: object **Required**: False

# **CampaignLimits**

For a campaign, specifies limits on the messages that the campaign can send. For an application, specifies the default limits for messages that campaigns in the application can send.

# **Daily**

The maximum number of messages that a campaign can send to a single endpoint during a 24-hour period. For an application, this value specifies the default limit for the number of messages that campaigns and journeys can send to a single endpoint during a 24-hour period. The maximum value is 100.

**Type**: integer **Required**: False

### **Total**

The maximum number of messages that a campaign can send to a single endpoint during the course of the campaign. If a campaign recurs, this setting applies to all runs of the campaign. The maximum value is 100.

**Type**: integer **Required**: False

#### Session

The maximum number of messages that the campaign can send per user session.

**Type**: integer **Required**: False

## MessagesPerSecond

The maximum number of messages that a campaign can send each second. For an application, this value specifies the default limit for the number of messages that campaigns can send each second. The minimum value is 1. The maximum value is 20,000.

**Type**: integer **Required**: False

#### **MaximumDuration**

The maximum amount of time, in seconds, that a campaign can attempt to deliver a message after the scheduled start time for the campaign. The minimum value is 60 seconds.

**Type**: integer **Required**: False

# CampaignResponse

Provides information about the status, configuration, and other settings for a campaign.

#### **TreatmentName**

The custom name of the default treatment for the campaign, if the campaign has multiple treatments. A *treatment* is a variation of a campaign that's used for A/B testing.

**Type**: string **Required**: False

## **TreatmentDescription**

The custom description of the default treatment for the campaign.

**Type**: string **Required**: False

# MessageConfiguration

The message configuration settings for the campaign.

**Type:** MessageConfiguration

**Required**: False

#### Schedule

The schedule settings for the campaign.

Type: <u>Schedule</u> Required: False

# **TemplateConfiguration**

The message template that's used for the campaign.

**Type**: TemplateConfiguration

Required: False

# CustomDeliveryConfiguration

The delivery configuration settings for sending the campaign through a custom channel.

Type: CustomDeliveryConfiguration

Required: False

Id

The unique identifier for the campaign.

**Type**: string **Required**: True

# **ApplicationId**

The unique identifier for the application that the campaign applies to.

**Type**: string **Required**: True

## CreationDate

The date, in ISO 8601 format, when the campaign was created.

**Type**: string **Required**: True

### LastModifiedDate

The date, in ISO 8601 format, when the campaign was last modified.

**Type**: string **Required**: True

# SegmentId

The unique identifier for the segment that's associated with the campaign.

**Type**: string **Required**: True

# **SegmentVersion**

The version number of the segment that's associated with the campaign.

**Type**: integer **Required**: True

### **AdditionalTreatments**

An array of responses, one for each treatment that you defined for the campaign, in addition to the default treatment.

**Type**: Array of type TreatmentResource

Required: False

### **HoldoutPercent**

The allocated percentage of users (segment members) who shouldn't receive messages from the campaign.

**Type**: integer **Required**: False

#### Name

The name of the campaign.

Type: string

Required: False

### Limits

The messaging limits for the campaign.

**Type**: CampaignLimits

Required: False

# **Description**

The custom description of the campaign.

Type: string

Required: False

### Hook

The settings for the AWS Lambda function to use as a code hook for the campaign. You can use this hook to customize the segment that's used by the campaign.

Type: CampaignHook

**Required**: False

### State

The current status of the campaign.

**Type:** CampaignState

Required: False

#### **DefaultState**

The current status of the campaign's default treatment. This value exists only for campaigns that have more than one treatment.

**Type**: CampaignState

Required: False

#### Version

The version number of the campaign.

**Type**: integer **Required**: False

#### **IsPaused**

Specifies whether the campaign is paused. A paused campaign doesn't run unless you resume it by changing this value to false. If you restart a campaign, the campaign restarts from the beginning and not at the point you paused it.

**Type**: boolean **Required**: False

#### Arn

The Amazon Resource Name (ARN) of the campaign.

**Type**: string **Required**: True

#### tags

A string-to-string map of key-value pairs that identifies the tags that are associated with the campaign. Each tag consists of a required tag key and an associated tag value.

**Type**: object **Required**: False

# **Priority**

Defines the priority of the campaign. This value used to determine the order in which messages are displayed to the recipient if there are multiple messages scheduled to be displayed at the same time.

**Type**: integer **Required**: False

# CampaignSmsMessage

Specifies the content and settings for an SMS message that's sent to recipients of a campaign.

# **Body**

The body of the SMS message.

**Type**: string **Required**: False

# MessageType

The SMS message type. Valid values are TRANSACTIONAL (for messages that are critical or time-sensitive, such as a one-time passwords) and PROMOTIONAL (for messsages that aren't critical or time-sensitive, such as marketing messages).

**Type**: string **Required**: False

Values: TRANSACTIONAL | PROMOTIONAL

### SenderId

The alphabetic Sender ID to display as the sender of the message on a recipient's device. Support for sender IDs varies by country or region. To specify a phone number as the sender, omit this parameter and use OriginationNumber instead. For more information about support for Sender ID by country, see the Amazon Pinpoint User Guide.

**Type**: string **Required**: False

# OriginationNumber

The number to send the SMS message from. The phone number that you specify must exist in your Amazon Pinpoint account—you can't pass an arbitrary phone number. If you want to use a sender ID to send your message, omit this parameter and use SenderId instead.

Type: string

Required: False

# **EntityId**

A registered Entity ID (currently only used when sending messages to recipients in India).

**Type**: string **Required**: False

# **TemplateId**

A registered Template ID (currently only used when sending messages to recipients in India).

**Type**: string **Required**: False

# CampaignState

Provides information about the status of a campaign.

# **CampaignStatus**

The current status of the campaign, or the current status of a treatment that belongs to an A/B test campaign.

If a campaign uses A/B testing, the campaign has a status of COMPLETED only if all campaign treatments have a status of COMPLETED. If you delete the segment that's associated with a campaign, the campaign fails and has a status of DELETED.

**Type**: string **Required**: False

Values: SCHEDULED | EXECUTING | PENDING\_NEXT\_RUN | COMPLETED | PAUSED |

DELETED | INVALID | PENDING\_APPROVAL | DRAFT

# ${\bf Custom Delivery Configuration}$

Specifies the delivery configuration settings for sending a campaign or campaign treatment through a custom channel. This object is required if you use the CampaignCustomMessage object to define the message to send for the campaign or campaign treatment.

### **EndpointTypes**

The types of endpoints to send the campaign or treatment to. Each valid value maps to a type of channel that you can associate with an endpoint by using the ChannelType property of an endpoint.

**Type**: Array of type string

**Required**: False

Values: PUSH | GCM | APNS | APNS\_SANDBOX | APNS\_VOIP | APNS\_VOIP\_SANDBOX |

ADM | SMS | VOICE | EMAIL | BAIDU | CUSTOM | IN\_APP

# DeliveryUri

The destination to send the campaign or treatment to. This value can be one of the following:

• The name or Amazon Resource Name (ARN) of an AWS Lambda function to invoke to handle delivery of the campaign or treatment.

• The URL for a web application or service that supports HTTPS and can receive the message. The URL has to be a full URL, including the HTTPS protocol.

**Type**: string **Required**: True

# DefaultButtonConfiguration

Information about the default behavior for a button that appears in an in-app message. You can optionally add button configurations that specifically apply to iOS, Android, or web browser users.

#### **Text**

The text that appears on a button in an in-app message.

**Type**: string **Required**: True

#### **ButtonAction**

The action that occurs when a recipient chooses a button in an in-app message. You can specify one of the following:

- LINK A link to a web destination.
- DEEP\_LINK A link to a specific page in an application.

• CLOSE – Dismisses the message.

**Type**: string **Required**: True

Values: LINK | DEEP\_LINK | CLOSE

#### I ink

The destination (such as a URL) for a button.

**Type**: string **Required**: False

### **TextColor**

The color of the body text in a button, expressed as a string consisting of a hex color code (such as "#000000" for black).

**Type**: string **Required**: False

## BackgroundColor

The background color of a button, expressed as a string consisting of a hex color code (such as "#000000" for black).

**Type**: string **Required**: False

### **BorderRadius**

The border radius of a button.

**Type**: integer **Required**: False

# **EventDimensions**

Specifies the dimensions for an event filter that determines when a campaign is sent or a journey activity is performed.

### **EventType**

The name of the event that causes the campaign to be sent or the journey activity to be performed. This can be a standard event that Amazon Pinpoint generates, such as \_email.delivered or \_custom.delivered. For campaigns, this can also be a custom event that's specific to your application. For information about standard events, see <a href="Streaming Amazon Pinpoint Events">Streaming Amazon Pinpoint Events</a> in the Amazon Pinpoint Developer Guide.

Type: <u>SetDimension</u>
Required: False

#### **Attributes**

One or more custom attributes that your application reports to Amazon Pinpoint. You can use these attributes as selection criteria when you create an event filter.

**Type**: object **Required**: False

#### **Metrics**

One or more custom metrics that your application reports to Amazon Pinpoint. You can use these metrics as selection criteria when you create an event filter.

**Type**: object **Required**: False

# InAppMessageBodyConfig

Configuration information related to the main body text of an in-app message.

### **Body**

The main body text of the message.

**Type**: string **Required**: True

### **TextColor**

The color of the body text, expressed as a string consisting of a hex color code (such as "#000000" for black).

**Type**: string **Required**: False

# **Alignment**

The text alignment of the main body text of the message.

**Type**: string **Required**: True

Values: LEFT | CENTER | RIGHT

# InAppMessageButton

Configuration information for a button that appears in an in-app message.

# **DefaultConfig**

An object that defines the default behavior for a button in an in-app message.

Type: DefaultButtonConfiguration

Required: False

#### Web

An object that defines the default behavior for a button in in-app messages for web applications.

**Type**: OverrideButtonConfiguration

Required: False

#### IOS

An object that defines the default behavior for a button in in-app messages sent to iOS devices.

**Type**: OverrideButtonConfiguration

Required: False

### **Android**

An object that defines the default behavior for a button in in-app messages sent to Android.

**Type:** OverrideButtonConfiguration

**Required**: False

# InAppMessageContent

Configuration information related to an in-app message.

# HeaderConfig

An object that contains configuration information about the header or title text of the in-app message.

**Type**: InAppMessageHeaderConfig

**Required**: False

## BackgroundColor

The background color for an in-app message banner, expressed as a string consisting of a hex color code (such as "#000000" for black).

**Type**: string **Required**: False

## **BodyConfig**

An object that contains configuration information about the header or title text of the in-app message.

Type: InAppMessageBodyConfig

Required: False

## **ImageUrl**

The URL of the image that appears on an in-app message banner.

**Type**: string **Required**: False

# **PrimaryBtn**

An object that contains configuration information about the primary button in an in-app message.

Type: InAppMessageButton

Required: False

# SecondaryBtn

An object that contains configuration information about the secondary button in an in-app message.

Type: InAppMessageButton

Required: False

# In App Message Header Config

Configuration information related to the message header for an in-app message.

#### Header

The text that appears in the header or title of the message.

**Type**: string **Required**: True

### **TextColor**

The color of the body text, expressed as a string consisting of a hex color code (such as "#000000" for black).

**Type**: string **Required**: False

# **Alignment**

The text alignment of the title of the message.

**Type**: string **Required**: True

Values: LEFT | CENTER | RIGHT

# Message

Specifies the content and settings for a push notification that's sent to recipients of a campaign.

# **Body**

The body of the notification message. The maximum number of characters is 200.

**Type**: string **Required**: False

#### **Title**

The title to display above the notification message on a recipient's device.

**Type**: string **Required**: False

## **ImageUrl**

The URL of an image to display in the push notification.

**Type**: string **Required**: False

# **ImageIconUrl**

The URL of the image to display as the push notification icon, such as the icon for the app.

**Type**: string **Required**: False

# **ImageSmallIconUrl**

The URL of the image to display as the small, push notification icon, such as a small version of the icon for the app.

**Type**: string **Required**: False

#### MediaUrl

The URL of the image or video to display in the push notification.

**Type**: string **Required**: False

## **Action**

The action to occur if a recipient taps the push notification. Valid values are:

- OPEN\_APP Your app opens or it becomes the foreground app if it was sent to the background. This is the default action.
- DEEP\_LINK Your app opens and displays a designated user interface in the app. This setting uses the deep-linking features of iOS and Android.
- URL The default mobile browser on the recipient's device opens and loads the web page at a URL that you specify.

**Type**: string **Required**: False

Values: OPEN\_APP | DEEP\_LINK | URL

#### Url

The URL to open in a recipient's default mobile browser, if a recipient taps the push notification and the value of the Action property is URL.

**Type**: string **Required**: False

#### **SilentPush**

Specifies whether the notification is a silent push notification, which is a push notification that doesn't display on a recipient's device. Silent push notifications can be used for cases such as updating an app's configuration, displaying messages in an in-app message center, or supporting phone home functionality.

**Type**: boolean **Required**: False

### **JsonBody**

The JSON payload to use for a silent push notification.

**Type**: string **Required**: False

#### RawContent

The raw, JSON-formatted string to use as the payload for the notification message. If specified, this value overrides all other content for the message.

**Type**: string **Required**: False

#### **TimeToLive**

The number of seconds that the push notification service should keep the message, if the service is unable to deliver the notification the first time. This value is converted to an expiration value when it's sent to a push notification service. If this value is 0, the service treats the notification as if it expires immediately and the service doesn't store or try to deliver the notification again.

This value doesn't apply to messages that are sent through the Amazon Device Messaging (ADM) service.

Type: integer

Required: False

# MessageBody

Provides information about an API request or response.

## RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

## Message

The message that's returned from the API.

**Type**: string **Required**: False

# MessageConfiguration

Specifies the message configuration settings for a campaign.

# DefaultMessage

The default message that the campaign sends through all the channels that are configured for the campaign.

Type: Message Required: False

# **APNSMessage**

The message that the campaign sends through the APNs (Apple Push Notification service) channel. If specified, this message overrides the default message.

Type: Message

**REST API Reference** Amazon Pinpoint

**Required**: False

## **GCMMessage**

The message that the campaign sends through the GCM channel, which enables Amazon Pinpoint to send push notifications through the Firebase Cloud Messaging (FCM), formerly Google Cloud Messaging (GCM), service. If specified, this message overrides the default message.

Type: Message Required: False

## **ADMMessage**

The message that the campaign sends through the ADM (Amazon Device Messaging) channel. If specified, this message overrides the default message.

Type: Message Required: False

### **BaiduMessage**

The message that the campaign sends through the Baidu (Baidu Cloud Push) channel. If specified, this message overrides the default message.

Type: Message Required: False

### **EmailMessage**

The message that the campaign sends through the email channel. If specified, this message overrides the default message.



### Note

The maximum email message size is 200 KB. You can use email templates to send larger email messages.

Type: CampaignEmailMessage

Required: False

# **SMSMessage**

The message that the campaign sends through the SMS channel. If specified, this message overrides the default message.

**Type**: CampaignSmsMessage

Required: False

# CustomMessage

The message that the campaign sends through a custom channel, as specified by the delivery configuration (CustomDeliveryConfiguration) settings for the campaign. If specified, this message overrides the default message.

Type: CampaignCustomMessage

Required: False

# InAppMessage

The default message for the in-app messaging channel. This message overrides the default message (DefaultMessage).

Type: CampaignInAppMessage

Required: False

# MessageHeader

Contains the name and value pair of an message header to add to your email. You can have up to 15 MessageHeaders. A header can contain information such as the sender, receiver, route, or timestamp.

#### Name

The name of the message header. The header name can contain up to 126 characters.

**Type**: string **Required**: False

#### Value

The value of the message header. The header value can contain up to 870 characters, including the length of any rendered attributes. For example if you add the {CreationDate} attribute, it renders as YYYY-MM-DDTHH: MM:SS.SSSZ and is 24 characters in length.

**Type**: string

**Required**: False

### MetricDimension

Specifies metric-based criteria for including or excluding endpoints from a segment. These criteria derive from custom metrics that you define for endpoints.

# ComparisonOperator

The operator to use when comparing metric values. Valid values are: GREATER\_THAN, LESS\_THAN, GREATER\_THAN\_OR\_EQUAL, LESS\_THAN\_OR\_EQUAL.

Type: string

Required: True

#### Value

The value to compare.

**Type**: number

Required: True

# OverrideButtonConfiguration

Configuration information related to the configuration of a button with settings that are specific to a certain device type.

#### **ButtonAction**

The action that occurs when a recipient chooses a button in an in-app message. You can specify one of the following:

- LINK A link to a web destination.
- DEEP\_LINK A link to a specific page in an application.
- CLOSE Dismisses the message.

Type: string

Required: False

Values: LINK | DEEP\_LINK | CLOSE

#### Link

The destination (such as a URL) for a button.

Type: string

Required: False

# QuietTime

Specifies the start and end times that define a time range when messages aren't sent to endpoints.

#### Start

The specific time when quiet time begins. This value has to use 24-hour notation and be in HH:MM format, where HH is the hour (with a leading zero, if applicable) and MM is the minutes. For example, use 02:30 to represent 2:30 AM, or 14:30 to represent 2:30 PM.

**Type**: string

Required: False

#### End

The specific time when quiet time ends. This value has to use 24-hour notation and be in HH:MM format, where HH is the hour (with a leading zero, if applicable) and MM is the minutes. For example, use 02:30 to represent 2:30 AM, or 14:30 to represent 2:30 PM.

**Type**: string **Required**: False

## **Schedule**

Specifies the schedule settings for a campaign.

## **StartTime**

The scheduled time when the campaign began or will begin. Valid values are: IMMEDIATE, to start the campaign immediately; or, a specific time in ISO 8601 format.

**Type**: string **Required**: True

#### **EndTime**

The scheduled time, in ISO 8601 format, when the campaign ended or will end.

**Type**: string **Required**: False

## **Frequency**

Specifies how often the campaign is sent or whether the campaign is sent in response to a specific event.

**Type**: string **Required**: False

Values: ONCE | HOURLY | DAILY | WEEKLY | MONTHLY | EVENT | IN\_APP\_EVENT

#### **IsLocalTime**

Specifies whether the start and end times for the campaign schedule use each recipient's local time. To base the schedule on each recipient's local time, set this value to true.

**Type**: boolean **Required**: False

#### Timezone

The starting UTC offset for the campaign schedule, if the value of the IsLocalTime property is true. Valid values are: UTC, UTC+01, UTC+02, UTC+03, UTC+03:30, UTC+04, UTC

```
+04:30, UTC+05; UTC+05:30, UTC+05:45, UTC+06, UTC+06:30, UTC+07, UTC+08, UTC+09, UTC+09:30, UTC+10, UTC+10:30, UTC+11, UTC+12, UTC+13, UTC-02, UTC-03, UTC-04, UTC-05, UTC-06, UTC-07, UTC-08, UTC-09, UTC-10, and UTC-11.
```

**Type**: string **Required**: False

## QuietTime

The default quiet time for the campaign. Quiet time is a specific time range when a campaign doesn't send messages to endpoints, if all the following conditions are met:

- The EndpointDemographic.Timezone property of the endpoint is set to a valid value.
- The current time in the endpoint's time zone is later than or equal to the time specified by the QuietTime. Start property for the campaign.
- The current time in the endpoint's time zone is earlier than or equal to the time specified by the QuietTime. End property for the campaign.

If any of the preceding conditions isn't met, the endpoint will receive messages from the campaign, even if quiet time is enabled.

Type: QuietTime
Required: False

### **EventFilter**

The type of event that causes the campaign to be sent, if the value of the Frequency property is EVENT.

**Type**: CampaignEventFilter

**Required**: False

### **SetDimension**

Specifies the dimension type and values for a segment dimension.

# DimensionType

The type of segment dimension to use. Valid values are: INCLUSIVE, endpoints that match the criteria are included in the segment; and, EXCLUSIVE, endpoints that match the criteria are excluded from the segment.

**Type**: string **Required**: False

Values: INCLUSIVE | EXCLUSIVE

#### **Values**

The criteria values to use for the segment dimension. Depending on the value of the DimensionType property, endpoints are included or excluded from the segment if their values match the criteria values.

**Type**: Array of type string

Required: True

# **Template**

Specifies the name and version of the message template to use for the message.

#### Name

The name of the message template to use for the message. If specified, this value must match the name of an existing message template.

**Type**: string **Required**: False

## Version

The unique identifier for the version of the message template to use for the message. If specified, this value must match the identifier for an existing template version. To retrieve a list of versions and version identifiers for a template, use the Template Versions resource.

If you don't specify a value for this property, Amazon Pinpoint uses the *active version* of the template. The *active version* is typically the version of a template that's been most recently

reviewed and approved for use, depending on your workflow. It isn't necessarily the latest version of a template.

Type: string

Required: False

# **TemplateConfiguration**

Specifies the message template to use for the message, for each type of channel.

# **SMSTemplate**

The SMS template to use for the message.

Type: <u>Template</u> Required: False

# **EmailTemplate**

The email template to use for the message.

Type: <u>Template</u>
Required: False

# **PushTemplate**

The push notification template to use for the message.

Type: <u>Template</u>
Required: False

# VoiceTemplate

The voice template to use for the message. This object isn't supported for campaigns.

Type: <u>Template</u> Required: False

### **InAppTemplate**

The InApp template to use for the message. The InApp template object is not supported for SendMessages.

Type: <u>Template</u> Required: False

### **TreatmentResource**

Specifies the settings for a campaign treatment. A *treatment* is a variation of a campaign that's used for A/B testing of a campaign.

#### **TreatmentName**

The custom name of the treatment.

**Type**: string **Required**: False

### **TreatmentDescription**

The custom description of the treatment.

**Type**: string **Required**: False

### MessageConfiguration

The message configuration settings for the treatment.

**Type:** MessageConfiguration

Required: False

#### Schedule

The schedule settings for the treatment.

Type: Schedule

Required: False

### **TemplateConfiguration**

The message template to use for the treatment.

**Type**: TemplateConfiguration

Required: False

### CustomDeliveryConfiguration

The delivery configuration settings for sending the treatment through a custom channel. This object is required if the MessageConfiguration object for the treatment specifies a CustomMessage object.

Type: CustomDeliveryConfiguration

Required: False

#### **SizePercent**

The allocated percentage of users (segment members) that the treatment is sent to.

**Type**: integer **Required**: True

Id

The unique identifier for the treatment.

**Type**: string **Required**: True

#### **State**

The current status of the treatment.

Type: CampaignState

Required: False

## WriteCampaignRequest

Specifies the configuration and other settings for a campaign.

#### **TreatmentName**

A custom name of the default treatment for the campaign, if the campaign has multiple treatments. A *treatment* is a variation of a campaign that's used for A/B testing.

**Type**: string **Required**: False

### **TreatmentDescription**

A custom description of the default treatment for the campaign.

**Type**: string **Required**: False

### MessageConfiguration

The message configuration settings for the campaign.

**Type**: MessageConfiguration

Required: False

#### Schedule

The schedule settings for the campaign.

Type: <u>Schedule</u> Required: False

## ${\bf Template Configuration}$

The message template to use for the campaign.

**Type**: TemplateConfiguration

Required: False

### CustomDeliveryConfiguration

The delivery configuration settings for sending the campaign through a custom channel. This object is required if the MessageConfiguration object for the campaign specifies a CustomMessage object.

Type: CustomDeliveryConfiguration

Required: False

### SegmentId

The unique identifier for the segment to associate with the campaign.

Type: string

Required: False

### **SegmentVersion**

The version of the segment to associate with the campaign.

**Type**: integer **Required**: False

#### **IsPaused**

Specifies whether to pause the campaign. A paused campaign doesn't run unless you resume it by changing this value to false. If you restart a campaign, the campaign restarts from the beginning and not at the point you paused it. If a campaign is running it will complete and then pause. Pause only pauses or skips the next run for a recurring future scheduled campaign. A campaign scheduled for immediate can't be paused.

**Type**: boolean **Required**: False

### **AdditionalTreatments**

An array of requests that defines additional treatments for the campaign, in addition to the default treatment for the campaign.

Type: Array of type WriteTreatmentResource

Required: False

#### **HoldoutPercent**

The allocated percentage of users (segment members) who shouldn't receive messages from the campaign.

**Type**: integer **Required**: False

#### Limits

The messaging limits for the campaign.

**Type**: CampaignLimits

Required: False

#### Name

A custom name for the campaign.

**Type**: string **Required**: False

#### Hook

The settings for the AWS Lambda function to invoke as a code hook for the campaign. You can use this hook to customize the segment that's used by the campaign.

**Type**: CampaignHook

Required: False

## **Description**

A custom description of the campaign.

Type: string

**REST API Reference** Amazon Pinpoint

**Required**: False

#### tags



### Note

As of **22-05-2023** the PUT UpdateCampaign tags attribute has been deprecated. After this date any value in the tags attribute is not processed and will not generate an error code. Use the Tags resource to add or modify tags.

(Deprecated) A string-to-string map of key-value pairs that defines the tags to associate with the campaign. Each tag consists of a required tag key and an associated tag value.

Type: object Required: False

## **Priority**

An integer between 1 and 5, inclusive, that represents the priority of the in-app message campaign, where 1 is the highest priority and 5 is the lowest. If there are multiple messages scheduled to be displayed at the same time, the priority determines the order in which those messages are displayed.

**Type**: integer Required: False

### WriteTreatmentResource

Specifies the settings for a campaign treatment. A treatment is a variation of a campaign that's used for A/B testing of a campaign.

#### **TreatmentName**

A custom name for the treatment.

**Type**: string **Required**: False

### **TreatmentDescription**

A custom description of the treatment.

**Type**: string

Required: False

### MessageConfiguration

The message configuration settings for the treatment.

**Type**: MessageConfiguration

Required: False

#### Schedule

The schedule settings for the treatment.

Type: <u>Schedule</u> Required: False

### **TemplateConfiguration**

The message template to use for the treatment.

**Type**: TemplateConfiguration

Required: False

## CustomDeliveryConfiguration

The delivery configuration settings for sending the treatment through a custom channel. This object is required if the MessageConfiguration object for the treatment specifies a CustomMessage object.

**Type**: CustomDeliveryConfiguration

Required: False

#### **SizePercent**

The allocated percentage of users (segment members) to send the treatment to.

**Type**: integer **Required**: True

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## GetCampaign

- AWS Command Line Interface
- · AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

## **UpdateCampaign**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin

See also 210

- AWS SDK for PHP V3
- · AWS SDK for Python
- AWS SDK for Ruby V3

## DeleteCampaign

- AWS Command Line Interface
- · AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Campaign Activities**

A *campaign* represents a messaging initiative that engages a specific segment of users for an Amazon Pinpoint application. The Campaign Activities resource provides information about the activities that were performed by a campaign, such as the time during which the campaign ran and the number of endpoints that the campaign delivered messages to.

You can use this resource to retrieve information about the activities that were performed by a specific campaign.

## URI

/v1/apps/application-id/campaigns/campaign-id/activities

# **HTTP** methods

#### **GET**

**Operation ID:** GetCampaignActivities

Campaign Activities 211

Retrieves information about all the activities for a campaign.

## **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.
campaign-id	String	True	The unique identifier for the campaign.

## **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

## **Query parameters**

Name	Type	Required	Description
page-size	String	False	The maximum number of items to include in each page of a paginated response. This parameter is not supported

Name	Туре	Required	Description
			for application, campaign, and journey metrics.
token	String	False	The NextToken string that specifies which page of results to return in a paginated response.

# Responses

Status code	Response model	Description
200	ActivitiesResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	MessageBody	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	MessageBody	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	MessageBody	The request failed because the payload for the body

Status code	Response model	Description
		of the request is too large (RequestEntityTooLargeExcep tion).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Campaign Activities resource.

## **Path parameters**

Name	Туре	Required	Description
campaign-id	String	True	The unique identifier for the campaign.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

#### Responses

Status code	Response model	Description
200	None	The request succeeded.

## **Schemas**

## **Response bodies**

### **ActivitiesResponse schema**

```
"NextToken": "string",
  "Item": [
    {
      "Id": "string",
      "ApplicationId": "string",
      "CampaignId": "string",
      "TreatmentId": "string",
      "State": "string",
      "Result": "string",
      "ScheduledStart": "string",
      "Start": "string",
      "End": "string",
      "SuccessfulEndpointCount": integer,
      "TotalEndpointCount": integer,
      "TimezonesTotalCount": integer,
      "TimezonesCompletedCount": integer,
      "ExecutionMetrics": {
    }
  ]
}
```

## MessageBody schema

```
{
    "<u>RequestID</u>": "string",
    "<u>Message</u>": "string"
```

}

## **Properties**

## **ActivitiesResponse**

Provides information about the activities that were performed by a campaign.

#### NextToken

The string to use in a subsequent request to get the next page of results in a paginated response. This value is null if there are no additional pages.

**Type**: string **Required**: False

#### Item

An array of responses, one for each activity that was performed by the campaign.

**Type**: Array of type ActivityResponse

**Required**: True

## **ActivityResponse**

Provides information about an activity that was performed by a campaign.

Id

The unique identifier for the activity.

**Type**: string **Required**: True

## **ApplicationId**

The unique identifier for the application that the campaign applies to.

Type: string

Required: True

### CampaignId

The unique identifier for the campaign that the activity applies to.

**Type**: string **Required**: True

#### **TreatmentId**

The unique identifier for the campaign treatment that the activity applies to. A treatment is a variation of a campaign that's used for A/B testing of a campaign.

**Type**: string **Required**: False

#### State

The current status of the activity. Possible values are: PENDING, INITIALIZING, RUNNING, PAUSED, CANCELLED, and COMPLETED.

**Type**: string **Required**: False

#### Result

Specifies whether the activity succeeded. Possible values are SUCCESS and FAIL.

**Type**: string **Required**: False

### ScheduledStart

The scheduled start time, in ISO 8601 format, for the activity.

**Type**: string **Required**: False

#### Start

The actual start time, in ISO 8601 format, of the activity.

**Type**: string

Required: False

#### **End**

The actual time, in ISO 8601 format, when the activity was marked CANCELLED or COMPLETED.

Type: string

Required: False

### SuccessfulEndpointCount

The total number of endpoints that the campaign successfully delivered messages to.

**Type**: integer

Required: False

## **TotalEndpointCount**

The total number of endpoints that the campaign attempted to deliver messages to.

**Type**: integer

Required: False

#### **TimezonesTotalCount**

The total number of unique time zones that are in the segment for the campaign.

Type: integer

Required: False

## TimezonesCompletedCount

The total number of time zones that were completed.

**Type**: integer **Required**: False

### **ExecutionMetrics**

A JSON object that contains metrics relating to the campaign execution for this campaign activity. For information about the structure and contents of the results, see <a href="Standard Amazon Pinpoint">Standard Amazon Pinpoint</a> analytics metrics in the Amazon Pinpoint Developer Guide.

**Type**: object **Required**: False

## MessageBody

Provides information about an API request or response.

## RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

### Message

The message that's returned from the API.

**Type**: string **Required**: False

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## **GetCampaignActivities**

• AWS Command Line Interface

See also 219

- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- · AWS SDK for Python
- AWS SDK for Ruby V3

# **Campaign Metrics**

A campaign metric is a measurable value, also referred to as a key performance indicator (KPI), that can help you monitor and assess the performance of a specific campaign. For example, you can use a campaign metric to access data about how many endpoints a campaign message was sent to or how many of those messages were delivered to the intended endpoints. Amazon Pinpoint automatically collects, aggregates, and stores this data for all of your campaigns. If you integrated a mobile app with Amazon Pinpoint by using an AWS Mobile SDK, Amazon Pinpoint extends this support to include additional metrics, such as the percentage of push notifications that were opened by recipients. For information about integrating a mobile app, see <a href="Integrating Amazon Pinpoint With Your Application">Integrating Amazon Pinpoint Developer Guide</a>.

The Campaign Metrics resource represents a collection of standard metrics that apply to individual campaigns. As part of the Amazon Pinpoint Analytics APIs, this resource provides you with programmatic access to pre-aggregated data for each of these metrics. For a list of campaign metrics that are currently supported, see the <u>Amazon Pinpoint Developer Guide</u>.

You can use the Campaign Metrics resource to retrieve pre-aggregated data for a standard metric that applies to an individual campaign. To retrieve data for a standard metric that applies to all the campaigns for an application, use the <u>Application Metrics</u> resource.

### URI

/v1/apps/application-id/campaigns/campaign-id/kpis/daterange/kpi-name

Campaign Metrics 220

# **HTTP** methods

# **GET**

Operation ID: GetCampaignDateRangeKpi

Retrieves (queries) pre-aggregated data for a standard metric that applies to a campaign.

## **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.
kpi-name	String	True	The name of the metric, also referred to as a key performan ce indicator (KPI), to retrieve data for. This value describes the associated metric and consists of two or more terms, which are comprised of lowercase alphanume ric characters, separated by a hyphen. Examples are email-open-rate and successful-delivery-rate. For a list of valid values, see the

Name	Туре	Required	Description
			Amazon Pinpoint  Developer Guide.
campaign-id	String	True	The unique identifier for the campaign.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which
			content types,
			expressed as MIME
			types, the client
			understands.

## **Query parameters**

Name	Туре	Required	Description
next-token	String	False	The string that specifies which page of results to return in a paginated response. This parameter is not supported for application, campaign, and journey metrics.
end-time	String	False	The last date and time to retrieve data for, as part of an inclusive date range that filters the query results.

Name	Туре	Required	Description
			This value should be in extended ISO 8601 format and use Coordinat ed Universal Time (UTC), for example: 2019-07-2 6T20:00:00Z for 8:00 PM UTC July 26, 2019.
start-time	String	False	The first date and time to retrieve data for, as part of an inclusive date range that filters the query results. This value should be in extended ISO 8601 format and use Coordinat ed Universal Time (UTC), for example: 2019-07-1 9T20:00:00Z for 8:00 PM UTC July 19, 2019. This value should also be fewer than 90 days from the current day.

Name	Туре	Required	Description
page-size	String	False	The maximum number of items to include in each page of a paginated response.  This parameter is not supported for application, campaign, and journey metrics.

## Responses

Status code	Response model	Description
200	<pre>CampaignDateRangeK piResponse</pre>	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource

Status code	Response model	Description
		(MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Campaign Metrics resource.

## **Path parameters**

Name	Туре	Required	Description
campaign-id	String	True	The unique identifier for the campaign.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the

Name	Туре	Required	Description
			Amazon Pinpoint console.
kpi-name	String	True	The name of the metric, also referred to as a key performan ce indicator (KPI), to retrieve data for. This value describes the associated metric and consists of two or more terms, which are comprised of lowercase alphanume ric characters, separated by a hyphen. Examples are email-open-rate and successful-delivery-rate. For a list of valid values, see the Amazon Pinpoint Developer Guide.

# Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Response bodies**

### CampaignDateRangeKpiResponse schema

```
{
  "KpiName": "string",
  "KpiResult": {
    "Rows": [
      {
        "GroupedBys": [
          {
             "Key": "string",
             "Value": "string",
             "Type": "string"
          }
        ],
        "Values": [
          {
             "Key": "string",
             "<u>Value</u>": "string",
             "Type": "string"
          }
        ]
      }
    ]
  },
  ""NextToken": "string",
  "ApplicationId": "string",
  "CampaignId": "string",
  "StartTime": "string",
  "EndTime": "string"
}
```

## MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

## **Properties**

## **BaseKpiResult**

Provides the results of a query that retrieved the data for a standard metric that applies to an application, campaign, or journey.

#### **Rows**

An array of objects that provides the results of a query that retrieved the data for a standard metric that applies to an application, campaign, or journey.

Type: Array of type ResultRow

Required: True

## CampaignDateRangeKpiResponse

Provides the results of a query that retrieved the data for a standard metric that applies to a campaign, and provides information about that query.

### **KpiName**

The name of the metric, also referred to as a *key performance indicator (KPI)*, that the data was retrieved for. This value describes the associated metric and consists of two or more terms, which are comprised of lowercase alphanumeric characters, separated by a hyphen. For a list of possible values, see the Amazon Pinpoint Developer Guide.

**Type**: string **Required**: True

## KpiResult

An array of objects that contains the results of the query. Each object contains the value for the metric and metadata about that value.

Type: BaseKpiResult

Required: True

#### NextToken

The string to use in a subsequent request to get the next page of results in a paginated response. This value is null for the Campaign Metrics resource because the resource returns all results in a single page.

**Type**: string **Required**: False

### **ApplicationId**

The unique identifier for the application that the metric applies to.

**Type**: string **Required**: True

### CampaignId

The unique identifier for the campaign that the metric applies to.

**Type**: string **Required**: True

#### StartTime

The first date and time of the date range that was used to filter the query results, in extended ISO 8601 format. The date range is inclusive.

**Type**: string **Required**: True

#### **EndTime**

The last date and time of the date range that was used to filter the query results, in extended ISO 8601 format. The date range is inclusive.

**Type**: string **Required**: True

### MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

Type: string

Required: False

### Message

The message that's returned from the API.

**Type**: string

Required: False

#### ResultRow

Provides the results of a query that retrieved the data for a standard metric that applies to an application, campaign, or journey.

### GroupedBys

An array of objects that defines the field and field values that were used to group data in a result set that contains multiple results. This value is null if the data in a result set isn't grouped.

Type: Array of type ResultRowValue

**Required**: True

#### **Values**

An array of objects that provides pre-aggregated values for a standard metric that applies to an application, campaign, or journey.

Type: Array of type ResultRowValue

Required: True

#### ResultRowValue

Provides a single value and metadata about that value as part of an array of query results for a standard metric that applies to an application, campaign, or journey.

### Key

The friendly name of the metric whose value is specified by the Value property.

**Type**: string **Required**: True

#### **Value**

In a Values object, the value for the metric that the query retrieved data for. In a GroupedBys object, the value for the field that was used to group data in a result set that contains multiple results (Values objects).

**Type**: string **Required**: True

### **Type**

The data type of the value specified by the Value property.

**Type**: string **Required**: True

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## ${\bf Get Campaign Date Range Kpi}$

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++

See also 231

- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Campaign Version**

A *campaign* represents a messaging initiative that engages a specific segment of users for an Amazon Pinpoint application. The Campaign Version resource provides information about a specific version of a campaign, such as the schedule, messaging limits, and message settings for that version of the campaign.

You can use this resource to retrieve information about a specific version of a campaign.

### **URI**

/v1/apps/application-id/campaigns/campaign-id/versions/version

## **HTTP** methods

### **GET**

Operation ID: GetCampaignVersion

Retrieves information about the status, configuration, and other settings for a specific version of a campaign.

### Path parameters

Name	Type	Required	Description
version	String	True	The unique version number (Version property) for the campaign version.

Campaign Version 232

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.
campaign-id	String	True	The unique identifier for the campaign.

## **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

## Responses

Status code	Response model	Description
200	CampaignResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).

Status code	Response model	Description
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Campaign Version resource.

## **Path parameters**

Name	Туре	Required	Description
campaign-id	String	True	The unique identifier for the campaign.
version	String	True	The unique version number (Version property) for the campaign version.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

## **Response bodies**

# CampaignResponse schema

```
{
   "TreatmentName": "string",
   "TreatmentDescription": "string",
   "MessageConfiguration": {
        "DefaultMessage": {
            "Body": "string",
            "Title": "string",
```

```
"ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"APNSMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"GCMMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"ADMMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
```

```
"ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"BaiduMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"EmailMessage": {
  "Body": "string",
  "Title": "string",
  "HtmlBody": "string",
  "FromAddress": "string",
  "Headers": [
    {
      "Name": "string",
      "Value": "string"
    }
  ]
},
"SMSMessage": {
  "Body": "string",
  "MessageType": enum,
  "SenderId": "string",
  "OriginationNumber": "string",
  "EntityId": "string",
  "TemplateId": "string"
},
"CustomMessage": {
```

```
"Data": "string"
},
"InAppMessage": {
  "Body": "string",
  "Layout": enum,
  "Content": [
    {
      "HeaderConfig": {
        "Header": "string",
        "TextColor": "string",
        "Alignment": enum
      },
      "BackgroundColor": "string",
      "BodyConfig": {
        "Body": "string",
        "TextColor": "string",
        "Alignment": enum
      },
      "ImageUrl": "string",
      "PrimaryBtn": {
        "DefaultConfig": {
          "Text": "string",
          "ButtonAction": enum,
          "Link": "string",
          "TextColor": "string",
          "BackgroundColor": "string",
          "BorderRadius": integer
        },
        "Web": {
          "ButtonAction": enum,
          "Link": "string"
        },
        "IOS": {
          "ButtonAction": enum,
          "Link": "string"
        },
        "Android": {
          "ButtonAction": enum,
          "Link": "string"
        }
      },
      "SecondaryBtn": {
        "DefaultConfig": {
          "Text": "string",
```

```
"ButtonAction": enum,
            "Link": "string",
            "TextColor": "string",
            "BackgroundColor": "string",
            "BorderRadius": integer
          },
          "Web": {
            "ButtonAction": enum,
            "Link": "string"
          },
          "IOS": {
            "ButtonAction": enum,
            "Link": "string"
          },
          "Android": {
            "ButtonAction": enum,
            "Link": "string"
          }
        }
      }
    ],
    "CustomConfig": {
    }
  }
},
"Schedule": {
  "StartTime": "string",
  "EndTime": "string",
  "Frequency": enum,
  "IsLocalTime": boolean,
  "Timezone": "string",
  "QuietTime": {
    "Start": "string",
    "End": "string"
  "EventFilter": {
    "Dimensions": {
      "EventType": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      },
      "Attributes": {
```

```
},
      "Metrics": {
      }
    },
    "FilterType": enum
  }
},
"TemplateConfiguration": {
  "SMSTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "EmailTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "PushTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "VoiceTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "InAppTemplate": {
    "Name": "string",
    "Version": "string"
  }
},
"CustomDeliveryConfiguration": {
  "EndpointTypes": [
    enum
  ],
  "<u>DeliveryUri</u>": "string"
"Id": "string",
"ApplicationId": "string",
"CreationDate": "string",
"LastModifiedDate": "string",
"SegmentId": "string",
"SegmentVersion": integer,
"AdditionalTreatments": [
  {
    "TreatmentName": "string",
```

```
"TreatmentDescription": "string",
"MessageConfiguration": {
  "DefaultMessage": {
    "Body": "string",
    "Title": "string",
    "ImageUrl": "string",
    "ImageIconUrl": "string",
    "ImageSmallIconUrl": "string",
    "MediaUrl": "string",
    "Action": enum,
    "Url": "string",
    "SilentPush": boolean,
    "JsonBody": "string",
    "RawContent": "string",
    "TimeToLive": integer
  },
  "APNSMessage": {
    "Body": "string",
    "Title": "string",
    "ImageUrl": "string",
    "ImageIconUrl": "string",
    "ImageSmallIconUrl": "string",
    "MediaUrl": "string",
    "Action": enum,
    "Url": "string",
    "SilentPush": boolean,
    "JsonBody": "string",
    "RawContent": "string",
    "TimeToLive": integer
  },
  "GCMMessage": {
    "Body": "string",
    "Title": "string",
    "ImageUrl": "string",
    "ImageIconUrl": "string",
    "ImageSmallIconUrl": "string",
    "MediaUrl": "string",
    "Action": enum,
    "Url": "string",
    "SilentPush": boolean,
    "JsonBody": "string",
    "RawContent": "string",
    "TimeToLive": integer
 },
```

```
"ADMMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
 "TimeToLive": integer
},
"BaiduMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
 "TimeToLive": integer
},
"EmailMessage": {
 "Body": "string",
  "Title": "string",
  "HtmlBody": "string",
  "FromAddress": "string",
  "Headers": [
    {
      "Name": "string",
      "Value": "string"
   }
 ]
},
"SMSMessage": {
  "Body": "string",
  "MessageType": enum,
  "SenderId": "string",
```

```
"OriginationNumber": "string",
  "EntityId": "string",
 "TemplateId": "string"
},
"CustomMessage": {
 "Data": "string"
},
"InAppMessage": {
  "Body": "string",
  "Layout": enum,
  "Content": [
    {
      "HeaderConfig": {
        "Header": "string",
        "TextColor": "string",
        "Alignment": enum
      },
      "BackgroundColor": "string",
      "BodyConfig": {
        "Body": "string",
        "TextColor": "string",
        "Alignment": enum
      },
      "ImageUrl": "string",
      "PrimaryBtn": {
        "DefaultConfig": {
          "Text": "string",
          "ButtonAction": enum,
          "Link": "string",
          "TextColor": "string",
          "BackgroundColor": "string",
          "BorderRadius": integer
        },
        "Web": {
          "ButtonAction": enum,
          "Link": "string"
        },
        "IOS": {
          "ButtonAction": enum,
          "Link": "string"
        },
        "Android": {
          "ButtonAction": enum,
          "Link": "string"
```

```
}
        },
        "SecondaryBtn": {
          "DefaultConfig": {
            "Text": "string",
            "ButtonAction": enum,
            "Link": "string",
            ""TextColor": "string",
            "BackgroundColor": "string",
            "BorderRadius": integer
          },
          "Web": {
            "ButtonAction": enum,
            "Link": "string"
          },
          "IOS": {
            "ButtonAction": enum,
            "Link": "string"
          },
          "Android": {
            "ButtonAction": enum,
            "Link": "string"
          }
        }
      }
    ],
    "CustomConfig": {
  }
},
"Schedule": {
  "StartTime": "string",
  "EndTime": "string",
  "Frequency": enum,
  "IsLocalTime": boolean,
  "Timezone": "string",
  "QuietTime": {
    "Start": "string",
    "End": "string"
  },
  "EventFilter": {
    "Dimensions": {
      "EventType": {
        "DimensionType": enum,
```

```
"Values": [
          "string"
        ]
      },
      "Attributes": {
      },
      "Metrics": {
    },
    "FilterType": enum
  }
},
"TemplateConfiguration": {
  "SMSTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "EmailTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "PushTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "VoiceTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "InAppT<u>emplate</u>": {
    "Name": "string",
    "Version": "string"
  }
},
"CustomDeliveryConfiguration": {
  "EndpointTypes": [
    enum
  ],
  "DeliveryUri": "string"
},
"<u>SizePercent</u>": integer,
"Id": "string",
"State": {
  "CampaignStatus": enum
```

```
}
    }
  "HoldoutPercent": integer,
  "Name": "string",
  "Limits": {
    "Daily": integer,
    "Total": integer,
    "Session": integer,
    "MessagesPerSecond": integer,
    "MaximumDuration": integer
  },
  "Description": "string",
  "Hook": {
    "LambdaFunctionName": "string",
    "WebUrl": "string",
    "Mode": enum
  },
  "State": {
    "CampaignStatus": enum
  },
  "DefaultState": {
    "CampaignStatus": enum
  "Version": integer,
  "IsPaused": boolean,
  "Arn": "string",
  "tags": {
  },
  "Priority": integer
}
```

## MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

## **AttributeDimension**

Specifies attribute-based criteria for including or excluding endpoints from a segment.

## **AttributeType**

The type of segment dimension to use. Valid values are:

• INCLUSIVE – endpoints that have attributes matching the values are included in the segment.

- EXCLUSIVE endpoints that have attributes matching the values are excluded from the segment.
- CONTAINS endpoints that have attributes' substrings match the values are included in the segment.
- BEFORE endpoints with attributes read as ISO\_INSTANT datetimes before the value are included in the segment.
- AFTER endpoints with attributes read as ISO\_INSTANT datetimes after the value are included in the segment.
- BETWEEN endpoints with attributes read as ISO\_INSTANT datetimes between the values are included in the segment.
- 0N endpoints with attributes read as ISO\_INSTANT dates on the value are included in the segment. Time is ignored in this comparison.

**Type**: string **Required**: False

Values: INCLUSIVE | EXCLUSIVE | CONTAINS | BEFORE | AFTER | BETWEEN |

NOT\_BETWEEN | ON

### **Values**

The criteria values to use for the segment dimension. Depending on the value of the AttributeType property, endpoints are included or excluded from the segment if their attribute values match the criteria values.

**Type**: Array of type string

Required: True

# CampaignCustomMessage

Specifies the contents of a message that's sent through a custom channel to recipients of a campaign.

### **Data**

The raw, JSON-formatted string to use as the payload for the message. The maximum size is 5 KB.

**Type**: string **Required**: False

# CampaignEmailMessage

Specifies the content and "From" address for an email message that's sent to recipients of a campaign.

## **Body**

The body of the email for recipients whose email clients don't render HTML content.

**Type**: string **Required**: False

### **Title**

The subject line, or title, of the email.

**Type**: string **Required**: False

# HtmlBody

The body of the email, in HTML format, for recipients whose email clients render HTML content.

**Type**: string **Required**: False

### **FromAddress**

The verified email address to send the email from. The default address is the FromAddress specified for the email channel for the application.

**Type**: string **Required**: False

### **Headers**

The list of MessageHeaders for the email. You can have up to 15 MessageHeaders for each email.

**Type**: Array of type MessageHeader

Required: False

# CampaignEventFilter

Specifies the settings for events that cause a campaign to be sent.

### **Dimensions**

The dimension settings of the event filter for the campaign.

**Type**: EventDimensions

Required: True

## **FilterType**

The type of event that causes the campaign to be sent. Valid values are: SYSTEM, sends the campaign when a system event occurs; and, ENDPOINT, sends the campaign when an endpoint event (Events resource) occurs.

**Type**: string **Required**: True

Values: SYSTEM | ENDPOINT | USER

# CampaignHook

Specifies settings for invoking an AWS Lambda function that customizes a segment for a campaign.

### LambdaFunctionName

The name or Amazon Resource Name (ARN) of the AWS Lambda function that Amazon Pinpoint invokes to customize a segment for a campaign.

**Type**: string

Required: False

### WebUrl

The web URL that Amazon Pinpoint calls to invoke the AWS Lambda function over HTTPS.

**Type**: string

**Required**: False

### Mode

The mode that Amazon Pinpoint uses to invoke the AWS Lambda function. Possible values are:

- FILTER Invoke the function to customize the segment that's used by a campaign.
- DELIVERY (Deprecated) Previously, invoked the function to send a campaign through a custom channel. This functionality is not supported anymore. To send a campaign through a custom channel, use the CustomDeliveryConfiguration and CampaignCustomMessage objects of the campaign.

**Type**: string

**Required**: False

Values: DELIVERY | FILTER

# CampaignInAppMessage

Specifies the appearance of an in-app message, including the message type, the title and body text, text and background colors, and the configurations of buttons that appear in the message.

### **Body**

The body text of the in-app notification.

**Type**: string **Required**: False

## Layout

A string that describes how the in-app message will appear. You can specify one of the following:

- BOTTOM\_BANNER a message that appears as a banner at the bottom of the page.
- TOP BANNER a message that appears as a banner at the top of the page.
- OVERLAYS a message that covers entire screen.
- MOBILE\_FEED a message that appears in a window in front of the page.
- MIDDLE\_BANNER a message that appears as a banner in the middle of the page.
- CAROUSEL a scrollable layout of up to five unique messages.

Type: string

**Required**: False

Values: BOTTOM\_BANNER | TOP\_BANNER | OVERLAYS | MOBILE\_FEED | MIDDLE\_BANNER

| CAROUSEL

### Content

An array that contains configurtion information about the in-app message for the campaign, including title and body text, text colors, background colors, image URLs, and button configurations.

Type: Array of type InAppMessageContent

Required: False

## CustomConfig

An object that contains custom data (in the form of key-value pairs) that is included in the in-app messaging payload.

**Type**: object

Required: False

# **CampaignLimits**

For a campaign, specifies limits on the messages that the campaign can send. For an application, specifies the default limits for messages that campaigns in the application can send.

## **Daily**

The maximum number of messages that a campaign can send to a single endpoint during a 24-hour period. For an application, this value specifies the default limit for the number of messages that campaigns and journeys can send to a single endpoint during a 24-hour period. The maximum value is 100.

**Type**: integer **Required**: False

#### **Total**

The maximum number of messages that a campaign can send to a single endpoint during the course of the campaign. If a campaign recurs, this setting applies to all runs of the campaign. The maximum value is 100.

**Type**: integer **Required**: False

#### Session

The maximum number of messages that the campaign can send per user session.

**Type**: integer **Required**: False

## MessagesPerSecond

The maximum number of messages that a campaign can send each second. For an application, this value specifies the default limit for the number of messages that campaigns can send each second. The minimum value is 1. The maximum value is 20,000.

**Type**: integer **Required**: False

### **MaximumDuration**

The maximum amount of time, in seconds, that a campaign can attempt to deliver a message after the scheduled start time for the campaign. The minimum value is 60 seconds.

**Type**: integer **Required**: False

# CampaignResponse

Provides information about the status, configuration, and other settings for a campaign.

### **TreatmentName**

The custom name of the default treatment for the campaign, if the campaign has multiple treatments. A *treatment* is a variation of a campaign that's used for A/B testing.

**Type**: string **Required**: False

## **TreatmentDescription**

The custom description of the default treatment for the campaign.

**Type**: string **Required**: False

## MessageConfiguration

The message configuration settings for the campaign.

**Type:** MessageConfiguration

Required: False

#### Schedule

The schedule settings for the campaign.

Type: <u>Schedule</u> Required: False

## **TemplateConfiguration**

The message template that's used for the campaign.

**Type**: TemplateConfiguration

Required: False

## CustomDeliveryConfiguration

The delivery configuration settings for sending the campaign through a custom channel.

Type: CustomDeliveryConfiguration

Required: False

Id

The unique identifier for the campaign.

**Type**: string **Required**: True

# **ApplicationId**

The unique identifier for the application that the campaign applies to.

**Type**: string **Required**: True

### CreationDate

The date, in ISO 8601 format, when the campaign was created.

**Type**: string **Required**: True

### LastModifiedDate

The date, in ISO 8601 format, when the campaign was last modified.

**Type**: string **Required**: True

## SegmentId

The unique identifier for the segment that's associated with the campaign.

**Type**: string **Required**: True

# **SegmentVersion**

The version number of the segment that's associated with the campaign.

**Type**: integer **Required**: True

### **AdditionalTreatments**

An array of responses, one for each treatment that you defined for the campaign, in addition to the default treatment.

**Type**: Array of type TreatmentResource

Required: False

### **HoldoutPercent**

The allocated percentage of users (segment members) who shouldn't receive messages from the campaign.

**Type**: integer **Required**: False

#### Name

The name of the campaign.

Type: string

Required: False

### Limits

The messaging limits for the campaign.

**Type**: CampaignLimits

Required: False

## **Description**

The custom description of the campaign.

Type: string

Required: False

### Hook

The settings for the AWS Lambda function to use as a code hook for the campaign. You can use this hook to customize the segment that's used by the campaign.

Type: CampaignHook

Required: False

### **State**

The current status of the campaign.

**Type**: CampaignState

Required: False

### **DefaultState**

The current status of the campaign's default treatment. This value exists only for campaigns that have more than one treatment.

**Type**: CampaignState

Required: False

### Version

The version number of the campaign.

**Type**: integer **Required**: False

#### **IsPaused**

Specifies whether the campaign is paused. A paused campaign doesn't run unless you resume it by changing this value to false. If you restart a campaign, the campaign restarts from the beginning and not at the point you paused it.

**Type**: boolean **Required**: False

### Arn

The Amazon Resource Name (ARN) of the campaign.

**Type**: string **Required**: True

### tags

A string-to-string map of key-value pairs that identifies the tags that are associated with the campaign. Each tag consists of a required tag key and an associated tag value.

**Type**: object **Required**: False

## **Priority**

Defines the priority of the campaign. This value used to determine the order in which messages are displayed to the recipient if there are multiple messages scheduled to be displayed at the same time.

**Type**: integer **Required**: False

# CampaignSmsMessage

Specifies the content and settings for an SMS message that's sent to recipients of a campaign.

# **Body**

The body of the SMS message.

**Type**: string **Required**: False

## MessageType

The SMS message type. Valid values are TRANSACTIONAL (for messages that are critical or time-sensitive, such as a one-time passwords) and PROMOTIONAL (for messsages that aren't critical or time-sensitive, such as marketing messages).

**Type**: string **Required**: False

Values: TRANSACTIONAL | PROMOTIONAL

### SenderId

The alphabetic Sender ID to display as the sender of the message on a recipient's device. Support for sender IDs varies by country or region. To specify a phone number as the sender, omit this parameter and use OriginationNumber instead. For more information about support for Sender ID by country, see the Amazon Pinpoint User Guide.

**Type**: string **Required**: False

# OriginationNumber

The number to send the SMS message from. The phone number that you specify must exist in your Amazon Pinpoint account—you can't pass an arbitrary phone number. If you want to use a sender ID to send your message, omit this parameter and use SenderId instead.

Type: string

Required: False

## **EntityId**

A registered Entity ID (currently only used when sending messages to recipients in India).

**Type**: string **Required**: False

## **TemplateId**

A registered Template ID (currently only used when sending messages to recipients in India).

**Type**: string **Required**: False

# CampaignState

Provides information about the status of a campaign.

## **CampaignStatus**

The current status of the campaign, or the current status of a treatment that belongs to an A/B test campaign.

If a campaign uses A/B testing, the campaign has a status of COMPLETED only if all campaign treatments have a status of COMPLETED. If you delete the segment that's associated with a campaign, the campaign fails and has a status of DELETED.

**Type**: string **Required**: False

Values: SCHEDULED | EXECUTING | PENDING\_NEXT\_RUN | COMPLETED | PAUSED |

DELETED | INVALID | PENDING\_APPROVAL | DRAFT

# CustomDeliveryConfiguration

Specifies the delivery configuration settings for sending a campaign or campaign treatment through a custom channel. This object is required if you use the CampaignCustomMessage object to define the message to send for the campaign or campaign treatment.

### **EndpointTypes**

The types of endpoints to send the campaign or treatment to. Each valid value maps to a type of channel that you can associate with an endpoint by using the ChannelType property of an endpoint.

**Type**: Array of type string

**Required**: False

Values: PUSH | GCM | APNS | APNS\_SANDBOX | APNS\_VOIP | APNS\_VOIP\_SANDBOX |

ADM | SMS | VOICE | EMAIL | BAIDU | CUSTOM | IN\_APP

## DeliveryUri

The destination to send the campaign or treatment to. This value can be one of the following:

- The name or Amazon Resource Name (ARN) of an AWS Lambda function to invoke to handle delivery of the campaign or treatment.
- The URL for a web application or service that supports HTTPS and can receive the message. The URL has to be a full URL, including the HTTPS protocol.

**Type**: string **Required**: True

# DefaultButtonConfiguration

Information about the default behavior for a button that appears in an in-app message. You can optionally add button configurations that specifically apply to iOS, Android, or web browser users.

#### **Text**

The text that appears on a button in an in-app message.

**Type**: string **Required**: True

### **ButtonAction**

The action that occurs when a recipient chooses a button in an in-app message. You can specify one of the following:

- LINK A link to a web destination.
- DEEP\_LINK A link to a specific page in an application.

• CLOSE – Dismisses the message.

**Type**: string **Required**: True

Values: LINK | DEEP\_LINK | CLOSE

### I ink

The destination (such as a URL) for a button.

**Type**: string **Required**: False

### **TextColor**

The color of the body text in a button, expressed as a string consisting of a hex color code (such as "#000000" for black).

**Type**: string **Required**: False

### BackgroundColor

The background color of a button, expressed as a string consisting of a hex color code (such as "#000000" for black).

**Type**: string **Required**: False

### **BorderRadius**

The border radius of a button.

**Type**: integer **Required**: False

## **EventDimensions**

Specifies the dimensions for an event filter that determines when a campaign is sent or a journey activity is performed.

## **EventType**

The name of the event that causes the campaign to be sent or the journey activity to be performed. This can be a standard event that Amazon Pinpoint generates, such as \_\_email.delivered or \_custom.delivered. For campaigns, this can also be a custom event that's specific to your application. For information about standard events, see <a href="Streaming Amazon Pinpoint Events">Streaming Amazon Pinpoint Events</a> in the Amazon Pinpoint Developer Guide.

Type: <u>SetDimension</u>
Required: False

### **Attributes**

One or more custom attributes that your application reports to Amazon Pinpoint. You can use these attributes as selection criteria when you create an event filter.

**Type**: object **Required**: False

#### **Metrics**

One or more custom metrics that your application reports to Amazon Pinpoint. You can use these metrics as selection criteria when you create an event filter.

**Type**: object **Required**: False

# InAppMessageBodyConfig

Configuration information related to the main body text of an in-app message.

## **Body**

The main body text of the message.

**Type**: string **Required**: True

### **TextColor**

The color of the body text, expressed as a string consisting of a hex color code (such as "#000000" for black).

**Type**: string **Required**: False

# **Alignment**

The text alignment of the main body text of the message.

**Type**: string **Required**: True

Values: LEFT | CENTER | RIGHT

# InAppMessageButton

Configuration information for a button that appears in an in-app message.

# **DefaultConfig**

An object that defines the default behavior for a button in an in-app message.

Type: DefaultButtonConfiguration

Required: False

### Web

An object that defines the default behavior for a button in in-app messages for web applications.

Type: OverrideButtonConfiguration

Required: False

### IOS

An object that defines the default behavior for a button in in-app messages sent to iOS devices.

**Type**: OverrideButtonConfiguration

Required: False

### **Android**

An object that defines the default behavior for a button in in-app messages sent to Android.

**Type:** OverrideButtonConfiguration

**Required**: False

## InAppMessageContent

Configuration information related to an in-app message.

## HeaderConfig

An object that contains configuration information about the header or title text of the in-app message.

**Type**: InAppMessageHeaderConfig

**Required**: False

## BackgroundColor

The background color for an in-app message banner, expressed as a string consisting of a hex color code (such as "#000000" for black).

**Type**: string **Required**: False

### **BodyConfig**

An object that contains configuration information about the header or title text of the in-app message.

Type: InAppMessageBodyConfig

Required: False

## **ImageUrl**

The URL of the image that appears on an in-app message banner.

**Type**: string **Required**: False

## **PrimaryBtn**

An object that contains configuration information about the primary button in an in-app message.

Type: InAppMessageButton

Required: False

## SecondaryBtn

An object that contains configuration information about the secondary button in an in-app message.

Type: InAppMessageButton

Required: False

# In App Message Header Config

Configuration information related to the message header for an in-app message.

### Header

The text that appears in the header or title of the message.

**Type**: string **Required**: True

### **TextColor**

The color of the body text, expressed as a string consisting of a hex color code (such as "#000000" for black).

**Type**: string **Required**: False

## **Alignment**

The text alignment of the title of the message.

**Type**: string **Required**: True

Values: LEFT | CENTER | RIGHT

# Message

Specifies the content and settings for a push notification that's sent to recipients of a campaign.

## **Body**

The body of the notification message. The maximum number of characters is 200.

**Type**: string **Required**: False

### **Title**

The title to display above the notification message on a recipient's device.

**Type**: string **Required**: False

## **ImageUrl**

The URL of an image to display in the push notification.

**Type**: string **Required**: False

# **ImageIconUrl**

The URL of the image to display as the push notification icon, such as the icon for the app.

**Type**: string **Required**: False

## **ImageSmallIconUrl**

The URL of the image to display as the small, push notification icon, such as a small version of the icon for the app.

**Type**: string **Required**: False

### MediaUrl

The URL of the image or video to display in the push notification.

**Type**: string **Required**: False

### **Action**

The action to occur if a recipient taps the push notification. Valid values are:

- OPEN\_APP Your app opens or it becomes the foreground app if it was sent to the background. This is the default action.
- DEEP\_LINK Your app opens and displays a designated user interface in the app. This setting uses the deep-linking features of iOS and Android.
- URL The default mobile browser on the recipient's device opens and loads the web page at a URL that you specify.

**Type**: string **Required**: False

Values: OPEN\_APP | DEEP\_LINK | URL

### Url

The URL to open in a recipient's default mobile browser, if a recipient taps the push notification and the value of the Action property is URL.

**Type**: string **Required**: False

### **SilentPush**

Specifies whether the notification is a silent push notification, which is a push notification that doesn't display on a recipient's device. Silent push notifications can be used for cases such as updating an app's configuration, displaying messages in an in-app message center, or supporting phone home functionality.

**Type**: boolean **Required**: False

### **JsonBody**

The JSON payload to use for a silent push notification.

**Type**: string **Required**: False

#### RawContent

The raw, JSON-formatted string to use as the payload for the notification message. If specified, this value overrides all other content for the message.

**Type**: string **Required**: False

#### **TimeToLive**

The number of seconds that the push notification service should keep the message, if the service is unable to deliver the notification the first time. This value is converted to an expiration value when it's sent to a push notification service. If this value is 0, the service treats the notification as if it expires immediately and the service doesn't store or try to deliver the notification again.

This value doesn't apply to messages that are sent through the Amazon Device Messaging (ADM) service.

Type: integer

Required: False

## MessageBody

Provides information about an API request or response.

## RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

## Message

The message that's returned from the API.

**Type**: string **Required**: False

# MessageConfiguration

Specifies the message configuration settings for a campaign.

# DefaultMessage

The default message that the campaign sends through all the channels that are configured for the campaign.

Type: Message Required: False

## **APNSMessage**

The message that the campaign sends through the APNs (Apple Push Notification service) channel. If specified, this message overrides the default message.

Type: Message

**REST API Reference** Amazon Pinpoint

**Required**: False

### **GCMMessage**

The message that the campaign sends through the GCM channel, which enables Amazon Pinpoint to send push notifications through the Firebase Cloud Messaging (FCM), formerly Google Cloud Messaging (GCM), service. If specified, this message overrides the default message.

Type: Message Required: False

### **ADMMessage**

The message that the campaign sends through the ADM (Amazon Device Messaging) channel. If specified, this message overrides the default message.

Type: Message Required: False

### **BaiduMessage**

The message that the campaign sends through the Baidu (Baidu Cloud Push) channel. If specified, this message overrides the default message.

Type: Message Required: False

### **EmailMessage**

The message that the campaign sends through the email channel. If specified, this message overrides the default message.



### Note

The maximum email message size is 200 KB. You can use email templates to send larger email messages.

Type: CampaignEmailMessage

Required: False

### **SMSMessage**

The message that the campaign sends through the SMS channel. If specified, this message overrides the default message.

**Type**: CampaignSmsMessage

Required: False

## CustomMessage

The message that the campaign sends through a custom channel, as specified by the delivery configuration (CustomDeliveryConfiguration) settings for the campaign. If specified, this message overrides the default message.

Type: CampaignCustomMessage

Required: False

### **InAppMessage**

The default message for the in-app messaging channel. This message overrides the default message (DefaultMessage).

Type: CampaignInAppMessage

Required: False

# MessageHeader

Contains the name and value pair of an message header to add to your email. You can have up to 15 MessageHeaders. A header can contain information such as the sender, receiver, route, or timestamp.

#### Name

The name of the message header. The header name can contain up to 126 characters.

**Type**: string **Required**: False

### Value

The value of the message header. The header value can contain up to 870 characters, including the length of any rendered attributes. For example if you add the {CreationDate} attribute, it renders as YYYY-MM-DDTHH: MM: SS. SSSZ and is 24 characters in length.

**Type**: string

**Required**: False

### MetricDimension

Specifies metric-based criteria for including or excluding endpoints from a segment. These criteria derive from custom metrics that you define for endpoints.

## ComparisonOperator

The operator to use when comparing metric values. Valid values are: GREATER\_THAN, LESS\_THAN, GREATER\_THAN\_OR\_EQUAL, LESS\_THAN\_OR\_EQUAL.

Type: string

Required: True

#### Value

The value to compare.

**Type**: number

Required: True

# OverrideButtonConfiguration

Configuration information related to the configuration of a button with settings that are specific to a certain device type.

### **ButtonAction**

The action that occurs when a recipient chooses a button in an in-app message. You can specify one of the following:

- LINK A link to a web destination.
- DEEP\_LINK A link to a specific page in an application.

• CLOSE – Dismisses the message.

Type: string

Required: False

Values: LINK | DEEP\_LINK | CLOSE

#### Link

The destination (such as a URL) for a button.

Type: string

Required: False

# QuietTime

Specifies the start and end times that define a time range when messages aren't sent to endpoints.

#### Start

The specific time when quiet time begins. This value has to use 24-hour notation and be in HH:MM format, where HH is the hour (with a leading zero, if applicable) and MM is the minutes. For example, use 02:30 to represent 2:30 AM, or 14:30 to represent 2:30 PM.

**Type**: string

Required: False

#### End

The specific time when quiet time ends. This value has to use 24-hour notation and be in HH:MM format, where HH is the hour (with a leading zero, if applicable) and MM is the minutes. For example, use 02:30 to represent 2:30 AM, or 14:30 to represent 2:30 PM.

**Type**: string **Required**: False

## **Schedule**

Specifies the schedule settings for a campaign.

## **StartTime**

The scheduled time when the campaign began or will begin. Valid values are: IMMEDIATE, to start the campaign immediately; or, a specific time in ISO 8601 format.

**Type**: string **Required**: True

### **EndTime**

The scheduled time, in ISO 8601 format, when the campaign ended or will end.

**Type**: string **Required**: False

## **Frequency**

Specifies how often the campaign is sent or whether the campaign is sent in response to a specific event.

**Type**: string **Required**: False

Values: ONCE | HOURLY | DAILY | WEEKLY | MONTHLY | EVENT | IN\_APP\_EVENT

#### **IsLocalTime**

Specifies whether the start and end times for the campaign schedule use each recipient's local time. To base the schedule on each recipient's local time, set this value to true.

**Type**: boolean **Required**: False

#### Timezone

The starting UTC offset for the campaign schedule, if the value of the IsLocalTime property is true. Valid values are: UTC, UTC+01, UTC+02, UTC+03, UTC+03:30, UTC+04, UTC

```
+04:30, UTC+05, UTC+05:30, UTC+05:45, UTC+06, UTC+06:30, UTC+07, UTC+08, UTC+09, UTC+09:30, UTC+10, UTC+10:30, UTC+11, UTC+12, UTC+13, UTC-02, UTC-03, UTC-04, UTC-05, UTC-06, UTC-07, UTC-08, UTC-09, UTC-10, and UTC-11.
```

**Type**: string **Required**: False

### QuietTime

The default quiet time for the campaign. Quiet time is a specific time range when a campaign doesn't send messages to endpoints, if all the following conditions are met:

- The EndpointDemographic.Timezone property of the endpoint is set to a valid value.
- The current time in the endpoint's time zone is later than or equal to the time specified by the QuietTime. Start property for the campaign.
- The current time in the endpoint's time zone is earlier than or equal to the time specified by the QuietTime. End property for the campaign.

If any of the preceding conditions isn't met, the endpoint will receive messages from the campaign, even if guiet time is enabled.

Type: QuietTime
Required: False

#### **EventFilter**

The type of event that causes the campaign to be sent, if the value of the Frequency property is EVENT.

**Type**: CampaignEventFilter

**Required**: False

### **SetDimension**

Specifies the dimension type and values for a segment dimension.

### DimensionType

The type of segment dimension to use. Valid values are: INCLUSIVE, endpoints that match the criteria are included in the segment; and, EXCLUSIVE, endpoints that match the criteria are excluded from the segment.

**Type**: string **Required**: False

Values: INCLUSIVE | EXCLUSIVE

#### **Values**

The criteria values to use for the segment dimension. Depending on the value of the DimensionType property, endpoints are included or excluded from the segment if their values match the criteria values.

**Type**: Array of type string

Required: True

## **Template**

Specifies the name and version of the message template to use for the message.

#### Name

The name of the message template to use for the message. If specified, this value must match the name of an existing message template.

**Type**: string **Required**: False

### Version

The unique identifier for the version of the message template to use for the message. If specified, this value must match the identifier for an existing template version. To retrieve a list of versions and version identifiers for a template, use the <u>Template Versions</u> resource.

If you don't specify a value for this property, Amazon Pinpoint uses the *active version* of the template. The *active version* is typically the version of a template that's been most recently

reviewed and approved for use, depending on your workflow. It isn't necessarily the latest version of a template.

Type: string

Required: False

## **TemplateConfiguration**

Specifies the message template to use for the message, for each type of channel.

## **SMSTemplate**

The SMS template to use for the message.

Type: <u>Template</u> Required: False

## **EmailTemplate**

The email template to use for the message.

Type: <u>Template</u>
Required: False

## **PushTemplate**

The push notification template to use for the message.

Type: <u>Template</u>
Required: False

## VoiceTemplate

The voice template to use for the message. This object isn't supported for campaigns.

Type: <u>Template</u> Required: False

### **InAppTemplate**

The InApp template to use for the message. The InApp template object is not supported for SendMessages.

Type: <u>Template</u> Required: False

### **TreatmentResource**

Specifies the settings for a campaign treatment. A *treatment* is a variation of a campaign that's used for A/B testing of a campaign.

#### **TreatmentName**

The custom name of the treatment.

**Type**: string **Required**: False

## **TreatmentDescription**

The custom description of the treatment.

**Type**: string **Required**: False

### MessageConfiguration

The message configuration settings for the treatment.

**Type:** MessageConfiguration

Required: False

#### Schedule

The schedule settings for the treatment.

Type: Schedule

Required: False

## **TemplateConfiguration**

The message template to use for the treatment.

**Type**: TemplateConfiguration

Required: False

## CustomDeliveryConfiguration

The delivery configuration settings for sending the treatment through a custom channel. This object is required if the MessageConfiguration object for the treatment specifies a CustomMessage object.

Type: CustomDeliveryConfiguration

Required: False

#### **SizePercent**

The allocated percentage of users (segment members) that the treatment is sent to.

**Type**: integer **Required**: True

Id

The unique identifier for the treatment.

**Type**: string **Required**: True

#### **State**

The current status of the treatment.

Type: CampaignState

Required: False

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## **GetCampaignVersion**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Campaign Versions**

A *campaign* represents a messaging initiative that engages a specific segment of users for an Amazon Pinpoint application. The Campaign Versions resource provides information about versions of a specific campaign, such as the schedule, messaging limits, and message settings for each version of the campaign.

You can use this resource to retrieve information about versions of a campaign.

## **URI**

/v1/apps/application-id/campaigns/campaign-id/versions

## **HTTP** methods

#### **GET**

**Operation ID:** GetCampaignVersions

See also 280

Retrieves information about the status, configuration, and other settings for all versions of a campaign.

## **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.
campaign-id	String	True	The unique identifier for the campaign.

## **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

## **Query parameters**

Name	Туре	Required	Description
page-size	String	False	The maximum number of items to include in each page of a paginated response. This parameter

HTTP methods 281

Name	Туре	Required	Description
			is not supported for application, campaign, and journey metrics.
token	String	False	The NextToken string that specifies which page of results to return in a paginated response.

# Responses

Status code	Response model	Description
200	CampaignsResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).

HTTP methods 282

Status code	Response model	Description
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Campaign Versions resource.

## **Path parameters**

Name	Туре	Required	Description
campaign-id	String	True	The unique identifier for the campaign.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

HTTP methods 283

#### Responses

Status code	Response model	Description
200	None	The request succeeded.

## **Schemas**

## **Response bodies**

## CampaignsResponse schema

```
{
  "Item": [
    {
      "TreatmentName": "string",
      "TreatmentDescription": "string",
      "MessageConfiguration": {
        "DefaultMessage": {
          "Body": "string",
          "Title": "string",
          "ImageUrl": "string",
          "ImageIconUrl": "string",
          "ImageSmallIconUrl": "string",
          "MediaUrl": "string",
          "Action": enum,
          "Url": "string",
          "SilentPush": boolean,
          "JsonBody": "string",
          "RawContent": "string",
          "TimeToLive": integer
        },
        "APNSMessage": {
          "Body": "string",
          "Title": "string",
          "ImageUrl": "string",
          "ImageIconUrl": "string",
          "ImageSmallIconUrl": "string",
          "MediaUrl": "string",
          "Action": enum,
          "Url": "string",
          "SilentPush": boolean,
```

```
"JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"GCMMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"ADMMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"BaiduMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
```

```
"TimeToLive": integer
},
"EmailMessage": {
  "Body": "string",
  "Title": "string",
  "HtmlBody": "string",
  "FromAddress": "string",
  "Headers": [
    {
      "Name": "string",
      "Value": "string"
   }
 ]
},
"SMSMessage": {
 "Body": "string",
  "MessageType": enum,
  "SenderId": "string",
  "OriginationNumber": "string",
 "EntityId": "string",
 "TemplateId": "string"
},
"CustomMessage": {
 "Data": "string"
},
"InAppMessage": {
 "Body": "string",
  "Layout": enum,
  "Content": [
    }
      "HeaderConfig": {
        "Header": "string",
        "TextColor": "string",
        "Alignment": enum
      "BackgroundColor": "string",
      "BodyConfig": {
        "Body": "string",
        "TextColor": "string",
        "Alignment": enum
      },
      "ImageUrl": "string",
      "PrimaryBtn": {
        "DefaultConfig": {
```

```
"Text": "string",
        "ButtonAction": enum,
        "Link": "string",
        "TextColor": "string",
        "BackgroundColor": "string",
        "BorderRadius": integer
      },
      "Web": {
        "ButtonAction": enum,
        "Link": "string"
      },
      "IOS": {
        "ButtonAction": enum,
        "Link": "string"
      },
      "Android": {
        "ButtonAction": enum,
        "Link": "string"
      }
    },
    "SecondaryBtn": {
      "DefaultConfig": {
        "Text": "string",
        "ButtonAction": enum,
        "Link": "string",
        "TextColor": "string",
        "BackgroundColor": "string",
        "BorderRadius": integer
      },
      "Web": {
        "ButtonAction": enum,
        "Link": "string"
      },
      "IOS": {
        "ButtonAction": enum,
        "Link": "string"
      },
      "Android": {
        "ButtonAction": enum,
        "Link": "string"
      }
    }
 }
],
```

```
"CustomConfig": {
 }
},
"Schedule": {
  "StartTime": "string",
  "EndTime": "string",
  "Frequency": enum,
  "IsLocalTime": boolean,
  "Timezone": "string",
  "QuietTime": {
    "Start": "string",
    "End": "string"
  },
  "EventFilter": {
    "Dimensions": {
      "EventType": {
        "DimensionType": enum,
        "Values": [
          "string"
      },
      "Attributes": {
      },
      "Metrics": {
      }
    },
    "FilterType": enum
  }
},
"TemplateConfiguration": {
  "SMSTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "EmailTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "PushTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "VoiceTemplate": {
```

```
"Name": "string",
    "Version": "string"
  },
  "InAppTemplate": {
    "Name": "string",
    "Version": "string"
  }
},
"CustomDeliveryConfiguration": {
  "EndpointTypes": [
    enum
 ],
  "DeliveryUri": "string"
},
"Id": "string",
"ApplicationId": "string",
"CreationDate": "string",
"LastModifiedDate": "string",
"SegmentId": "string",
"SegmentVersion": integer,
"AdditionalTreatments": [
  {
    "TreatmentName": "string",
    "TreatmentDescription": "string",
    "MessageConfiguration": {
      "DefaultMessage": {
        "Body": "string",
        "Title": "string",
        "ImageUrl": "string",
        "ImageIconUrl": "string",
        "ImageSmallIconUrl": "string",
        "MediaUrl": "string",
        "Action": enum,
        "Url": "string",
        "SilentPush": boolean,
        "JsonBody": "string",
        "RawContent": "string",
        "TimeToLive": integer
      },
      "APNSMessage": {
        "Body": "string",
        "Title": "string",
        "ImageUrl": "string",
        "ImageIconUrl": "string",
```

```
"ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"GCMMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "<u>TimeToLive</u>": integer
},
"ADMMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"BaiduMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
```

```
"Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"EmailMessage": {
  "Body": "string",
  "Title": "string",
  "HtmlBody": "string",
  "FromAddress": "string",
  "Headers": [
    {
      "Name": "string",
      "Value": "string"
    }
  ]
},
"SMSMessage": {
  "Body": "string",
  "MessageType": enum,
  "SenderId": "string",
  ""OriginationNumber": "string",
  "EntityId": "string",
  "TemplateId": "string"
},
"CustomMessage": {
  "Data": "string"
},
"InAppMessage": {
  "Body": "string",
  "Layout": enum,
  "Content": [
    {
      "HeaderConfig": {
        "Header": "string",
        "TextColor": "string",
        "Alignment": enum
      },
      "BackgroundColor": "string",
      "BodyConfig": {
        "Body": "string",
        "TextColor": "string",
```

```
"Alignment": enum
},
"ImageUrl": "string",
"PrimaryBtn": {
  "DefaultConfig": {
    "Text": "string",
    "ButtonAction": enum,
    "Link": "string",
    "TextColor": "string",
    "BackgroundColor": "string",
    "BorderRadius": integer
  },
  "Web": {
    "ButtonAction": enum,
    "Link": "string"
  },
  "IOS": {
    "ButtonAction": enum,
    "Link": "string"
  },
  "Android": {
    "ButtonAction": enum,
    "Link": "string"
  }
},
"SecondaryBtn": {
  "DefaultConfig": {
    "Text": "string",
    "ButtonAction": enum,
    "Link": "string",
    "TextColor": "string",
    "BackgroundColor": "string",
    "BorderRadius": integer
  },
  "Web": {
    "ButtonAction": enum,
    "Link": "string"
  },
  "IOS": {
    "ButtonAction": enum,
    "Link": "string"
  },
  "Android": {
    "ButtonAction": enum,
```

```
"Link": "string"
          }
        }
      }
   ],
    "CustomConfig": {
 }
},
"Schedule": {
 "StartTime": "string",
 "EndTime": "string",
 "Frequency": enum,
 "IsLocalTime": boolean,
  "Timezone": "string",
  "QuietTime": {
   "Start": "string",
   "End": "string"
 },
  "EventFilter": {
    "Dimensions": {
      "EventType": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      },
      "Attributes": {
      "<u>Metrics</u>": {
      }
   },
    "FilterType": enum
 }
"TemplateConfiguration": {
 "SMSTemplate": {
   "Name": "string",
   "Version": "string"
 },
  "EmailTemplate": {
   "Name": "string",
   "Version": "string"
 },
```

```
"PushTemplate": {
        "Name": "string",
        "Version": "string"
      },
      "VoiceTemplate": {
        "Name": "string",
        "Version": "string"
      },
      "InAppTemplate": {
        "Name": "string",
        "Version": "string"
      }
    },
    "CustomDeliveryConfiguration": {
      "EndpointTypes": [
        enum
      ],
      "DeliveryUri": "string"
    },
    "SizePercent": integer,
    "Id": "string",
    "State": {
      "CampaignStatus": enum
    }
  }
],
"HoldoutPercent": integer,
"Name": "string",
"Limits": {
  "Daily": integer,
  "Total": integer,
  "Session": integer,
  "MessagesPerSecond": integer,
  "MaximumDuration": integer
"Description": "string",
"Hook": {
  "LambdaFunctionName": "string",
  "WebUrl": "string",
  "Mode": enum
},
"State": {
  "CampaignStatus": enum
},
```

```
"DefaultState": {
    "CampaignStatus": enum
},
    "Version": integer,
    "IsPaused": boolean,
    "Arn": "string",
    "tags": {
    },
    "Priority": integer
}
],
    "NextToken": "string"
}
```

## MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

### **AttributeDimension**

Specifies attribute-based criteria for including or excluding endpoints from a segment.

## AttributeType

The type of segment dimension to use. Valid values are:

- INCLUSIVE endpoints that have attributes matching the values are included in the segment.
- EXCLUSIVE endpoints that have attributes matching the values are excluded from the segment.
- CONTAINS endpoints that have attributes' substrings match the values are included in the segment.
- BEFORE endpoints with attributes read as ISO\_INSTANT datetimes before the value are included in the segment.
- AFTER endpoints with attributes read as ISO\_INSTANT datetimes after the value are included in the segment.

• BETWEEN – endpoints with attributes read as ISO\_INSTANT datetimes between the values are included in the segment.

• ON – endpoints with attributes read as ISO\_INSTANT dates on the value are included in the segment. Time is ignored in this comparison.

Type: string

Required: False

Values: INCLUSIVE | EXCLUSIVE | CONTAINS | BEFORE | AFTER | BETWEEN |

NOT\_BETWEEN | ON

#### **Values**

The criteria values to use for the segment dimension. Depending on the value of the AttributeType property, endpoints are included or excluded from the segment if their attribute values match the criteria values.

**Type**: Array of type string

Required: True

## CampaignCustomMessage

Specifies the contents of a message that's sent through a custom channel to recipients of a campaign.

#### **Data**

The raw, JSON-formatted string to use as the payload for the message. The maximum size is 5 KB.

Type: string

Required: False

## CampaignEmailMessage

Specifies the content and "From" address for an email message that's sent to recipients of a campaign.

### **Body**

The body of the email for recipients whose email clients don't render HTML content.

**Type**: string **Required**: False

#### Title

The subject line, or title, of the email.

**Type**: string **Required**: False

## HtmlBody

The body of the email, in HTML format, for recipients whose email clients render HTML content.

**Type**: string **Required**: False

#### **FromAddress**

The verified email address to send the email from. The default address is the FromAddress specified for the email channel for the application.

**Type**: string **Required**: False

#### **Headers**

The list of MessageHeaders for the email. You can have up to 15 MessageHeaders for each email.

**Type**: Array of type MessageHeader

Required: False

## CampaignEventFilter

Specifies the settings for events that cause a campaign to be sent.

#### **Dimensions**

The dimension settings of the event filter for the campaign.

**Type**: EventDimensions

Required: True

## FilterType

The type of event that causes the campaign to be sent. Valid values are: SYSTEM, sends the campaign when a system event occurs; and, ENDPOINT, sends the campaign when an endpoint event (Events resource) occurs.

**Type**: string **Required**: True

Values: SYSTEM | ENDPOINT | USER

## CampaignHook

Specifies settings for invoking an AWS Lambda function that customizes a segment for a campaign.

#### LambdaFunctionName

The name or Amazon Resource Name (ARN) of the AWS Lambda function that Amazon Pinpoint invokes to customize a segment for a campaign.

**Type**: string **Required**: False

#### WebUrl

The web URL that Amazon Pinpoint calls to invoke the AWS Lambda function over HTTPS.

**Type**: string **Required**: False

#### Mode

The mode that Amazon Pinpoint uses to invoke the AWS Lambda function. Possible values are:

FILTER – Invoke the function to customize the segment that's used by a campaign.

 DELIVERY – (Deprecated) Previously, invoked the function to send a campaign through a custom channel. This functionality is not supported anymore. To send a campaign through a custom channel, use the CustomDeliveryConfiguration and CampaignCustomMessage objects of the campaign.

Type: string

Required: False

Values: DELIVERY | FILTER

## CampaignInAppMessage

Specifies the appearance of an in-app message, including the message type, the title and body text, text and background colors, and the configurations of buttons that appear in the message.

## **Body**

The body text of the in-app notification.

**Type**: string

Required: False

### Layout

A string that describes how the in-app message will appear. You can specify one of the following:

• BOTTOM\_BANNER – a message that appears as a banner at the bottom of the page.

• TOP\_BANNER – a message that appears as a banner at the top of the page.

• OVERLAYS – a message that covers entire screen.

MOBILE\_FEED – a message that appears in a window in front of the page.

• MIDDLE\_BANNER – a message that appears as a banner in the middle of the page.

• CAROUSEL – a scrollable layout of up to five unique messages.

**Type**: string **Required**: False

Values: BOTTOM\_BANNER | TOP\_BANNER | OVERLAYS | MOBILE\_FEED | MIDDLE\_BANNER | CAROUSEL

#### Content

An array that contains configurtion information about the in-app message for the campaign, including title and body text, text colors, background colors, image URLs, and button configurations.

**Type**: Array of type InAppMessageContent

Required: False

## CustomConfig

An object that contains custom data (in the form of key-value pairs) that is included in the in-app messaging payload.

Type: object

Required: False

## **CampaignLimits**

For a campaign, specifies limits on the messages that the campaign can send. For an application, specifies the default limits for messages that campaigns in the application can send.

### **Daily**

The maximum number of messages that a campaign can send to a single endpoint during a 24-hour period. For an application, this value specifies the default limit for the number of messages that campaigns and journeys can send to a single endpoint during a 24-hour period. The maximum value is 100.

**Type**: integer **Required**: False

#### **Total**

The maximum number of messages that a campaign can send to a single endpoint during the course of the campaign. If a campaign recurs, this setting applies to all runs of the campaign. The maximum value is 100.

**Type**: integer **Required**: False

#### Session

The maximum number of messages that the campaign can send per user session.

**Type**: integer **Required**: False

## MessagesPerSecond

The maximum number of messages that a campaign can send each second. For an application, this value specifies the default limit for the number of messages that campaigns can send each second. The minimum value is 1. The maximum value is 20,000.

**Type**: integer **Required**: False

### **MaximumDuration**

The maximum amount of time, in seconds, that a campaign can attempt to deliver a message after the scheduled start time for the campaign. The minimum value is 60 seconds.

**Type**: integer **Required**: False

## CampaignResponse

Provides information about the status, configuration, and other settings for a campaign.

#### **TreatmentName**

The custom name of the default treatment for the campaign, if the campaign has multiple treatments. A *treatment* is a variation of a campaign that's used for A/B testing.

**Type**: string **Required**: False

### **TreatmentDescription**

The custom description of the default treatment for the campaign.

**Type**: string **Required**: False

## MessageConfiguration

The message configuration settings for the campaign.

**Type**: MessageConfiguration

Required: False

#### Schedule

The schedule settings for the campaign.

Type: <u>Schedule</u> Required: False

## **TemplateConfiguration**

The message template that's used for the campaign.

**Type**: TemplateConfiguration

Required: False

### CustomDeliveryConfiguration

The delivery configuration settings for sending the campaign through a custom channel.

Type: CustomDeliveryConfiguration

Required: False

#### Id

The unique identifier for the campaign.

**Type**: string **Required**: True

## **ApplicationId**

The unique identifier for the application that the campaign applies to.

**Type**: string **Required**: True

#### CreationDate

The date, in ISO 8601 format, when the campaign was created.

**Type**: string **Required**: True

## LastModifiedDate

The date, in ISO 8601 format, when the campaign was last modified.

**Type**: string **Required**: True

## SegmentId

The unique identifier for the segment that's associated with the campaign.

**Type**: string **Required**: True

### **SegmentVersion**

The version number of the segment that's associated with the campaign.

**Type**: integer **Required**: True

#### **AdditionalTreatments**

An array of responses, one for each treatment that you defined for the campaign, in addition to the default treatment.

**Type**: Array of type TreatmentResource

Required: False

## **HoldoutPercent**

The allocated percentage of users (segment members) who shouldn't receive messages from the campaign.

**Type**: integer **Required**: False

#### Name

The name of the campaign.

**Type**: string **Required**: False

#### Limits

The messaging limits for the campaign.

**Type**: CampaignLimits

Required: False

### Description

The custom description of the campaign.

Type: string

Required: False

#### Hook

The settings for the AWS Lambda function to use as a code hook for the campaign. You can use this hook to customize the segment that's used by the campaign.

Type: CampaignHook

Required: False

#### **State**

The current status of the campaign.

**Type**: CampaignState

Required: False

#### **DefaultState**

The current status of the campaign's default treatment. This value exists only for campaigns that have more than one treatment.

Type: CampaignState

Required: False

### Version

The version number of the campaign.

**Type**: integer **Required**: False

#### **IsPaused**

Specifies whether the campaign is paused. A paused campaign doesn't run unless you resume it by changing this value to false. If you restart a campaign, the campaign restarts from the beginning and not at the point you paused it.

**Type**: boolean **Required**: False

#### Arn

The Amazon Resource Name (ARN) of the campaign.

**Type**: string **Required**: True

### tags

A string-to-string map of key-value pairs that identifies the tags that are associated with the campaign. Each tag consists of a required tag key and an associated tag value.

**Type**: object **Required**: False

## **Priority**

Defines the priority of the campaign. This value used to determine the order in which messages are displayed to the recipient if there are multiple messages scheduled to be displayed at the same time.

**Type**: integer **Required**: False

## CampaignSmsMessage

Specifies the content and settings for an SMS message that's sent to recipients of a campaign.

## **Body**

The body of the SMS message.

**Type**: string **Required**: False

## MessageType

The SMS message type. Valid values are TRANSACTIONAL (for messages that are critical or time-sensitive, such as a one-time passwords) and PROMOTIONAL (for messsages that aren't critical or time-sensitive, such as marketing messages).

**Type**: string **Required**: False

Values: TRANSACTIONAL | PROMOTIONAL

#### SenderId

The alphabetic Sender ID to display as the sender of the message on a recipient's device. Support for sender IDs varies by country or region. To specify a phone number as the sender, omit this parameter and use OriginationNumber instead. For more information about support for Sender ID by country, see the Amazon Pinpoint User Guide.

**Type**: string **Required**: False

## OriginationNumber

The number to send the SMS message from. The phone number that you specify must exist in your Amazon Pinpoint account—you can't pass an arbitrary phone number. If you want to use a sender ID to send your message, omit this parameter and use SenderId instead.

**Type**: string **Required**: False

## **EntityId**

A registered Entity ID (currently only used when sending messages to recipients in India).

**Type**: string **Required**: False

### TemplateId

A registered Template ID (currently only used when sending messages to recipients in India).

**Type**: string

Required: False

## CampaignState

Provides information about the status of a campaign.

## **CampaignStatus**

The current status of the campaign, or the current status of a treatment that belongs to an A/B test campaign.

If a campaign uses A/B testing, the campaign has a status of COMPLETED only if all campaign treatments have a status of COMPLETED. If you delete the segment that's associated with a campaign, the campaign fails and has a status of DELETED.

Type: string

Required: False

Values: SCHEDULED | EXECUTING | PENDING\_NEXT\_RUN | COMPLETED | PAUSED |

DELETED | INVALID | PENDING\_APPROVAL | DRAFT

# CampaignsResponse

Provides information about the configuration and other settings for all the campaigns that are associated with an application.

#### **Item**

An array of responses, one for each campaign that's associated with the application.

**Type**: Array of type CampaignResponse

**Required**: True

#### NextToken

The string to use in a subsequent request to get the next page of results in a paginated response. This value is null if there are no additional pages.

**Type**: string

Required: False

## CustomDeliveryConfiguration

Specifies the delivery configuration settings for sending a campaign or campaign treatment through a custom channel. This object is required if you use the CampaignCustomMessage object to define the message to send for the campaign or campaign treatment.

## **EndpointTypes**

The types of endpoints to send the campaign or treatment to. Each valid value maps to a type of channel that you can associate with an endpoint by using the ChannelType property of an endpoint.

Type: Array of type string

Required: False

Values: PUSH | GCM | APNS | APNS\_SANDBOX | APNS\_VOIP | APNS\_VOIP\_SANDBOX |

ADM | SMS | VOICE | EMAIL | BAIDU | CUSTOM | IN\_APP

## DeliveryUri

The destination to send the campaign or treatment to. This value can be one of the following:

- The name or Amazon Resource Name (ARN) of an AWS Lambda function to invoke to handle delivery of the campaign or treatment.
- The URL for a web application or service that supports HTTPS and can receive the message. The URL has to be a full URL, including the HTTPS protocol.

**Type**: string **Required**: True

## DefaultButtonConfiguration

Information about the default behavior for a button that appears in an in-app message. You can optionally add button configurations that specifically apply to iOS, Android, or web browser users.

#### **Text**

The text that appears on a button in an in-app message.

**Type**: string **Required**: True

#### **ButtonAction**

The action that occurs when a recipient chooses a button in an in-app message. You can specify one of the following:

- LINK A link to a web destination.
- DEEP\_LINK A link to a specific page in an application.
- CLOSE Dismisses the message.

**Type**: string **Required**: True

Values: LINK | DEEP\_LINK | CLOSE

#### Link

The destination (such as a URL) for a button.

**Type**: string **Required**: False

#### **TextColor**

The color of the body text in a button, expressed as a string consisting of a hex color code (such as "#000000" for black).

**Type**: string **Required**: False

### BackgroundColor

The background color of a button, expressed as a string consisting of a hex color code (such as "#000000" for black).

Type: string

Required: False

#### **BorderRadius**

The border radius of a button.

**Type**: integer **Required**: False

### **EventDimensions**

Specifies the dimensions for an event filter that determines when a campaign is sent or a journey activity is performed.

## **EventType**

The name of the event that causes the campaign to be sent or the journey activity to be performed. This can be a standard event that Amazon Pinpoint generates, such as \_email.delivered or \_custom.delivered. For campaigns, this can also be a custom event that's specific to your application. For information about standard events, see <a href="Streaming Amazon Pinpoint Events">Streaming Amazon Pinpoint Events</a> in the Amazon Pinpoint Developer Guide.

**Type**: SetDimension

Required: False

#### **Attributes**

One or more custom attributes that your application reports to Amazon Pinpoint. You can use these attributes as selection criteria when you create an event filter.

**Type**: object **Required**: False

#### **Metrics**

One or more custom metrics that your application reports to Amazon Pinpoint. You can use these metrics as selection criteria when you create an event filter.

**Type**: object **Required**: False

## InAppMessageBodyConfig

Configuration information related to the main body text of an in-app message.

## **Body**

The main body text of the message.

**Type**: string **Required**: True

### **TextColor**

The color of the body text, expressed as a string consisting of a hex color code (such as "#000000" for black).

**Type**: string **Required**: False

## **Alignment**

The text alignment of the main body text of the message.

**Type**: string **Required**: True

Values: LEFT | CENTER | RIGHT

# In App Message Button

Configuration information for a button that appears in an in-app message.

### **DefaultConfig**

An object that defines the default behavior for a button in an in-app message.

Type: DefaultButtonConfiguration

Required: False

#### Web

An object that defines the default behavior for a button in in-app messages for web applications.

Type: OverrideButtonConfiguration

Required: False

#### IOS

An object that defines the default behavior for a button in in-app messages sent to iOS devices.

**Type**: OverrideButtonConfiguration

Required: False

### **Android**

An object that defines the default behavior for a button in in-app messages sent to Android.

Type: OverrideButtonConfiguration

Required: False

## InAppMessageContent

Configuration information related to an in-app message.

### HeaderConfig

An object that contains configuration information about the header or title text of the in-app message.

Type: InAppMessageHeaderConfig

Required: False

### BackgroundColor

The background color for an in-app message banner, expressed as a string consisting of a hex color code (such as "#000000" for black).

**Type**: string **Required**: False

## **BodyConfig**

An object that contains configuration information about the header or title text of the in-app message.

Type: InAppMessageBodyConfig

Required: False

## **ImageUrl**

The URL of the image that appears on an in-app message banner.

**Type**: string **Required**: False

## **PrimaryBtn**

An object that contains configuration information about the primary button in an in-app message.

**Type**: InAppMessageButton

Required: False

# SecondaryBtn

An object that contains configuration information about the secondary button in an in-app message.

**Type**: InAppMessageButton

Required: False

## InAppMessageHeaderConfig

Configuration information related to the message header for an in-app message.

### Header

The text that appears in the header or title of the message.

**Type**: string **Required**: True

### **TextColor**

The color of the body text, expressed as a string consisting of a hex color code (such as "#000000" for black).

**Type**: string **Required**: False

### **Alignment**

The text alignment of the title of the message.

**Type**: string **Required**: True

Values: LEFT | CENTER | RIGHT

# Message

Specifies the content and settings for a push notification that's sent to recipients of a campaign.

## **Body**

The body of the notification message. The maximum number of characters is 200.

**Type**: string **Required**: False

### **Title**

The title to display above the notification message on a recipient's device.

**Type**: string **Required**: False

### **ImageUrl**

The URL of an image to display in the push notification.

**Type**: string **Required**: False

### **ImageIconUrl**

The URL of the image to display as the push notification icon, such as the icon for the app.

**Type**: string **Required**: False

## **ImageSmallIconUrl**

The URL of the image to display as the small, push notification icon, such as a small version of the icon for the app.

**Type**: string **Required**: False

### MediaUrl

The URL of the image or video to display in the push notification.

**Type**: string **Required**: False

### Action

The action to occur if a recipient taps the push notification. Valid values are:

• OPEN\_APP – Your app opens or it becomes the foreground app if it was sent to the background. This is the default action.

• DEEP\_LINK – Your app opens and displays a designated user interface in the app. This setting uses the deep-linking features of iOS and Android.

• URL – The default mobile browser on the recipient's device opens and loads the web page at a URL that you specify.

Type: string

Required: False

Values: OPEN\_APP | DEEP\_LINK | URL

#### Url

The URL to open in a recipient's default mobile browser, if a recipient taps the push notification and the value of the Action property is URL.

Type: string

Required: False

#### **SilentPush**

Specifies whether the notification is a silent push notification, which is a push notification that doesn't display on a recipient's device. Silent push notifications can be used for cases such as updating an app's configuration, displaying messages in an in-app message center, or supporting phone home functionality.

**Type**: boolean

Required: False

## **JsonBody**

The JSON payload to use for a silent push notification.

Type: string

Required: False

#### **RawContent**

The raw, JSON-formatted string to use as the payload for the notification message. If specified, this value overrides all other content for the message.

**Type**: string

Required: False

#### **TimeToLive**

The number of seconds that the push notification service should keep the message, if the service is unable to deliver the notification the first time. This value is converted to an expiration value when it's sent to a push notification service. If this value is 0, the service treats the notification as if it expires immediately and the service doesn't store or try to deliver the notification again.

This value doesn't apply to messages that are sent through the Amazon Device Messaging (ADM) service.

**Type**: integer

Required: False

## MessageBody

Provides information about an API request or response.

## RequestID

The unique identifier for the request or response.

Type: string

Required: False

## Message

The message that's returned from the API.

Type: string

Required: False

## MessageConfiguration

Specifies the message configuration settings for a campaign.

### DefaultMessage

The default message that the campaign sends through all the channels that are configured for the campaign.

Type: Message
Required: False

### **APNSMessage**

The message that the campaign sends through the APNs (Apple Push Notification service) channel. If specified, this message overrides the default message.

Type: Message
Required: False

## **GCMMessage**

The message that the campaign sends through the GCM channel, which enables Amazon Pinpoint to send push notifications through the Firebase Cloud Messaging (FCM), formerly Google Cloud Messaging (GCM), service. If specified, this message overrides the default message.

Type: Message
Required: False

## **ADMMessage**

The message that the campaign sends through the ADM (Amazon Device Messaging) channel. If specified, this message overrides the default message.

Type: Message
Required: False

### **BaiduMessage**

The message that the campaign sends through the Baidu (Baidu Cloud Push) channel. If specified, this message overrides the default message.

Type: Message **Required**: False

### **EmailMessage**

The message that the campaign sends through the email channel. If specified, this message overrides the default message.



## Note

The maximum email message size is 200 KB. You can use email templates to send larger email messages.

Type: CampaignEmailMessage

**Required**: False

### **SMSMessage**

The message that the campaign sends through the SMS channel. If specified, this message overrides the default message.

Type: CampaignSmsMessage

Required: False

## CustomMessage

The message that the campaign sends through a custom channel, as specified by the delivery configuration (CustomDeliveryConfiguration) settings for the campaign. If specified, this message overrides the default message.

Type: CampaignCustomMessage

**Required**: False

### **InAppMessage**

The default message for the in-app messaging channel. This message overrides the default message (DefaultMessage).

**Type**: CampaignInAppMessage

**Required**: False

## MessageHeader

Contains the name and value pair of an message header to add to your email. You can have up to 15 MessageHeaders. A header can contain information such as the sender, receiver, route, or timestamp.

#### Name

The name of the message header. The header name can contain up to 126 characters.

**Type**: string **Required**: False

#### **Value**

The value of the message header. The header value can contain up to 870 characters, including the length of any rendered attributes. For example if you add the {CreationDate} attribute, it renders as YYYY-MM-DDTHH: MM:SS.SSSZ and is 24 characters in length.

**Type**: string **Required**: False

### MetricDimension

Specifies metric-based criteria for including or excluding endpoints from a segment. These criteria derive from custom metrics that you define for endpoints.

### ComparisonOperator

The operator to use when comparing metric values. Valid values are: GREATER\_THAN, LESS\_THAN, GREATER\_THAN\_OR\_EQUAL, LESS\_THAN\_OR\_EQUAL, and EQUAL.

**Type**: string **Required**: True

#### Value

The value to compare.

**Type**: number **Required**: True

## OverrideButtonConfiguration

Configuration information related to the configuration of a button with settings that are specific to a certain device type.

#### **ButtonAction**

The action that occurs when a recipient chooses a button in an in-app message. You can specify one of the following:

- LINK A link to a web destination.
- DEEP\_LINK A link to a specific page in an application.
- CLOSE Dismisses the message.

**Type**: string **Required**: False

Values: LINK | DEEP\_LINK | CLOSE

#### Link

The destination (such as a URL) for a button.

**Type**: string **Required**: False

## QuietTime

Specifies the start and end times that define a time range when messages aren't sent to endpoints.

#### Start

The specific time when quiet time begins. This value has to use 24-hour notation and be in HH:MM format, where HH is the hour (with a leading zero, if applicable) and MM is the minutes. For example, use 02:30 to represent 2:30 AM, or 14:30 to represent 2:30 PM.

Type: string

Required: False

#### End

The specific time when quiet time ends. This value has to use 24-hour notation and be in HH:MM format, where HH is the hour (with a leading zero, if applicable) and MM is the minutes. For example, use 02:30 to represent 2:30 AM, or 14:30 to represent 2:30 PM.

**Type**: string

Required: False

### Schedule

Specifies the schedule settings for a campaign.

### StartTime

The scheduled time when the campaign began or will begin. Valid values are: IMMEDIATE, to start the campaign immediately; or, a specific time in ISO 8601 format.

**Type**: string

Required: True

## **EndTime**

The scheduled time, in ISO 8601 format, when the campaign ended or will end.

Type: string

Required: False

### Frequency

Specifies how often the campaign is sent or whether the campaign is sent in response to a specific event.

**Type**: string **Required**: False

Values: ONCE | HOURLY | DAILY | WEEKLY | MONTHLY | EVENT | IN\_APP\_EVENT

#### **IsLocalTime**

Specifies whether the start and end times for the campaign schedule use each recipient's local time. To base the schedule on each recipient's local time, set this value to true.

**Type**: boolean **Required**: False

#### Timezone

The starting UTC offset for the campaign schedule, if the value of the IsLocalTime property is true. Valid values are: UTC, UTC+01, UTC+02, UTC+03, UTC+03:30, UTC+04, UTC+04:30, UTC+05, UTC+05:30, UTC+05:45, UTC+06, UTC+06:30, UTC+07, UTC+08, UTC+09, UTC+09:30, UTC+10, UTC+10:30, UTC+11, UTC+12, UTC+13, UTC-02, UTC-03, UTC-04, UTC-05, UTC-06, UTC-07, UTC-08, UTC-09, UTC-10, and UTC-11.

**Type**: string **Required**: False

### QuietTime

The default quiet time for the campaign. Quiet time is a specific time range when a campaign doesn't send messages to endpoints, if all the following conditions are met:

- The EndpointDemographic. Timezone property of the endpoint is set to a valid value.
- The current time in the endpoint's time zone is later than or equal to the time specified by the QuietTime. Start property for the campaign.
- The current time in the endpoint's time zone is earlier than or equal to the time specified by the QuietTime. End property for the campaign.

**REST API Reference** Amazon Pinpoint

If any of the preceding conditions isn't met, the endpoint will receive messages from the campaign, even if quiet time is enabled.

Type: QuietTime Required: False

### **EventFilter**

The type of event that causes the campaign to be sent, if the value of the Frequency property is EVENT.

Type: CampaignEventFilter

Required: False

### **SetDimension**

Specifies the dimension type and values for a segment dimension.

## DimensionType

The type of segment dimension to use. Valid values are: INCLUSIVE, endpoints that match the criteria are included in the segment; and, EXCLUSIVE, endpoints that match the criteria are excluded from the segment.

Type: string

Required: False

Values: INCLUSIVE | EXCLUSIVE

#### **Values**

The criteria values to use for the segment dimension. Depending on the value of the DimensionType property, endpoints are included or excluded from the segment if their values match the criteria values.

**Type**: Array of type string

Required: True

## **Template**

Specifies the name and version of the message template to use for the message.

### Name

The name of the message template to use for the message. If specified, this value must match the name of an existing message template.

**Type**: string **Required**: False

#### Version

The unique identifier for the version of the message template to use for the message. If specified, this value must match the identifier for an existing template version. To retrieve a list of versions and version identifiers for a template, use the Template Versions resource.

If you don't specify a value for this property, Amazon Pinpoint uses the *active version* of the template. The *active version* is typically the version of a template that's been most recently reviewed and approved for use, depending on your workflow. It isn't necessarily the latest version of a template.

**Type**: string **Required**: False

# TemplateConfiguration

Specifies the message template to use for the message, for each type of channel.

## **SMSTemplate**

The SMS template to use for the message.

Type: <u>Template</u> Required: False

## **EmailTemplate**

The email template to use for the message.

Type: <u>Template</u>
Required: False

## **PushTemplate**

The push notification template to use for the message.

Type: <u>Template</u> Required: False

## VoiceTemplate

The voice template to use for the message. This object isn't supported for campaigns.

Type: <u>Template</u>
Required: False

### **InAppTemplate**

The InApp template to use for the message. The InApp template object is not supported for SendMessages.

Type: <u>Template</u>
Required: False

### **TreatmentResource**

Specifies the settings for a campaign treatment. A *treatment* is a variation of a campaign that's used for A/B testing of a campaign.

#### **TreatmentName**

The custom name of the treatment.

Type: string

Required: False

### **TreatmentDescription**

The custom description of the treatment.

**Type**: string

Required: False

## MessageConfiguration

The message configuration settings for the treatment.

**Type**: MessageConfiguration

Required: False

#### Schedule

The schedule settings for the treatment.

Type: <u>Schedule</u> Required: False

### **TemplateConfiguration**

The message template to use for the treatment.

**Type**: TemplateConfiguration

Required: False

## CustomDeliveryConfiguration

The delivery configuration settings for sending the treatment through a custom channel. This object is required if the MessageConfiguration object for the treatment specifies a CustomMessage object.

**Type**: CustomDeliveryConfiguration

Required: False

#### **SizePercent**

The allocated percentage of users (segment members) that the treatment is sent to.

**Type**: integer **Required**: True

#### Id

The unique identifier for the treatment.

**Type**: string **Required**: True

#### **State**

The current status of the treatment.

**Type**: CampaignState

Required: False

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## GetCampaignVersions

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3

See also 329

- AWS SDK for Python
- AWS SDK for Ruby V3

# **Campaigns**

A *campaign* represents a messaging initiative that engages a specific segment of users for an Amazon Pinpoint application. The information represented by this resource includes the segment of users that a campaign sends messages to, the message that a campaign delivers, and the schedule on which a campaign runs.

You can use the Campaigns resource to create, update, or delete a campaign, or to retrieve information about all the campaigns that are associated with an application.

## **URI**

/v1/apps/application-id/campaigns

## **HTTP** methods

### **GET**

Operation ID: GetCampaigns

Retrieves information about the status, configuration, and other settings for all the campaigns that are associated with an application.

## Path parameters

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

Campaigns 330

## **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# **Query parameters**

Name	Туре	Required	Description
page-size	String	False	The maximum number of items to include in each page of a paginated response. This parameter is not supported for application, campaign, and journey metrics.
token	String	False	The NextToken string that specifies which page of results to return in a paginated response.

# Responses

Status code	Response model	Description
200	CampaignsResponse	The request succeeded.

Status code	Response model	Description
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **POST**

# Operation ID: CreateCampaign

Creates a new campaign for an application or updates the settings of an existing campaign for an application.

## **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

## Responses

Status code	Response model	Description
201	CampaignResponse	The request succeeded and the specified resource was created.

Status code	Response model	Description
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	MessageBody	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Campaigns resource.

## **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

### Responses

Status code	Response model	Description
200	None	The request succeeded.

## **Schemas**

## **Request bodies**

### **POST schema**

```
{
    "TreatmentName": "string",
    "TreatmentDescription": "string",
    "MessageConfiguration": {
        "DefaultMessage": {
             "Body": "string",
             "Title": "string",
             "ImageUrl": "string",
             "ImageIconUrl": "string",
             "ImageSmallIconUrl": "string",
             "MediaUrl": "string",
             "MediaUrl": "string",
             "MediaUrl": "string",
```

```
"Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"APNSMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"GCMMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "<u>TimeToLive</u>": integer
},
"ADMMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
```

```
"SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"BaiduMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"EmailMessage": {
  "Body": "string",
  "Title": "string",
  "HtmlBody": "string",
  "FromAddress": "string",
  "Headers": [
    {
      "Name": "string",
      "Value": "string"
    }
  ]
},
"SMSMessage": {
  "Body": "string",
  "MessageType": enum,
  "SenderId": "string",
  "OriginationNumber": "string",
  "EntityId": "string",
  "TemplateId": "string"
},
"CustomMessage": {
  "Data": "string"
"InAppMessage": {
  "Body": "string",
```

```
"Layout": enum,
"Content": [
  {
    "HeaderConfig": {
      "Header": "string",
      "TextColor": "string",
      "Alignment": enum
   },
    "BackgroundColor": "string",
    "BodyConfig": {
      "Body": "string",
      "TextColor": "string",
      "Alignment": enum
    },
    ""ImageUrl": "string",
    "PrimaryBtn": {
      "DefaultConfig": {
        "Text": "string",
        "ButtonAction": enum,
        "Link": "string",
        "TextColor": "string",
        "BackgroundColor": "string",
        "BorderRadius": integer
      },
      "Web": {
        "ButtonAction": enum,
        "Link": "string"
      },
      "IOS": {
        "ButtonAction": enum,
        "Link": "string"
      },
      "Android": {
        "ButtonAction": enum,
        "Link": "string"
      }
    },
    "SecondaryBtn": {
      "DefaultConfig": {
        "Text": "string",
        "ButtonAction": enum,
        "Link": "string",
        "TextColor": "string",
        "BackgroundColor": "string",
```

```
"BorderRadius": integer
          },
          "Web": {
            "ButtonAction": enum,
            "Link": "string"
          },
          "IOS": {
            "ButtonAction": enum,
            "Link": "string"
          },
          "Android": {
            "ButtonAction": enum,
            "Link": "string"
          }
        }
      }
    ],
    "CustomConfig": {
    }
  }
},
"Sche<u>dule</u>": {
  "StartTime": "string",
  "EndTime": "string",
  "Frequency": enum,
  "IsLocalTime": boolean,
  "<u>Timezone</u>": "string",
  "QuietTime": {
    "Start": "string",
    "End": "string"
  },
  "EventFilter": {
    "Dimensions": {
      "EventType": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      },
      "Attributes": {
      },
      "Metrics": {
      }
    },
```

```
"FilterType": enum
  }
},
"TemplateConfiguration": {
  "SMSTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "EmailTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "PushTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "VoiceTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "InAppTemplate": {
    "Name": "string",
    "Version": "string"
  }
},
"CustomDeliveryConfiguration": {
  "EndpointTypes": [
    enum
  ],
  "DeliveryUri": "string"
},
"SegmentId": "string",
"SegmentVersion": integer,
"IsPaused": boolean,
"AdditionalTreatments": [
  {
    "TreatmentName": "string",
    "TreatmentDescription": "string",
    "MessageConfiguration": {
      "DefaultMessage": {
        "Body": "string",
        "Title": "string",
        "ImageUrl": "string",
        "ImageIconUrl": "string",
```

```
"ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"APNSMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"GCMMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"ADMMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
```

```
"Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"BaiduMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
 "TimeToLive": integer
},
"EmailMessage": {
  "Body": "string",
  "Title": "string",
  "HtmlBody": "string",
  "FromAddress": "string",
  "Headers": [
    {
      "Name": "string",
      "Value": "string"
   }
 ]
},
"SMSMessage": {
  "Body": "string",
  "MessageType": enum,
  "SenderId": "string",
  "OriginationNumber": "string",
 "EntityId": "string",
 "TemplateId": "string"
},
"CustomMessage": {
 "Data": "string"
},
```

```
"InAppMessage": {
  "Body": "string",
  "Layout": enum,
  "Content": [
    {
      "HeaderConfig": {
        "Header": "string",
        "TextColor": "string",
        "Alignment": enum
      },
      "BackgroundColor": "string",
      "BodyConfig": {
        "Body": "string",
        "TextColor": "string",
        "Alignment": enum
      },
      "ImageUrl": "string",
      "PrimaryBtn": {
        "DefaultConfig": {
          "Text": "string",
          "ButtonAction": enum,
          "Link": "string",
          "TextColor": "string",
          "BackgroundColor": "string",
          "BorderRadius": integer
        },
        "Web": {
          "ButtonAction": enum,
          "Link": "string"
        },
        "IOS": {
          "ButtonAction": enum,
          "Link": "string"
        },
        "Android": {
          "ButtonAction": enum,
          "Link": "string"
        }
      },
      "SecondaryBtn": {
        "DefaultConfig": {
          "Text": "string",
          "ButtonAction": enum,
          "Link": "string",
```

```
"TextColor": "string",
            "BackgroundColor": "string",
            "BorderRadius": integer
          },
          "Web": {
            "ButtonAction": enum,
            "Link": "string"
          },
          "IOS": {
            "ButtonAction": enum,
            "Link": "string"
          },
          "Android": {
            "ButtonAction": enum,
            "Link": "string"
          }
        }
      }
    ],
    "CustomConfig": {
 }
},
"Schedule": {
  "StartTime": "string",
  "EndTime": "string",
  "Frequency": enum,
  "IsLocalTime": boolean,
  "Timezone": "string",
  "QuietTime": {
    "Start": "string",
    "End": "string"
  },
  "EventFilter": {
    "Dimensions": {
      "EventType": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      },
      "Attributes": {
      },
      "Metrics": {
```

```
}
        },
        "FilterType": enum
      }
    },
    "TemplateConfiguration": {
      "SMSTemplate": {
        "Name": "string",
        "Version": "string"
      },
      "EmailTemplate": {
        "Name": "string",
        "Version": "string"
      },
      "PushTemplate": {
        "Name": "string",
        "Version": "string"
      },
      "VoiceTemplate": {
        "Name": "string",
        "Version": "string"
      },
      "InAppTemplate": {
        "Name": "string",
        "Version": "string"
      }
    },
    "CustomDeliveryConfiguration": {
      "EndpointTypes": [
        enum
      ],
      "DeliveryUri": "string"
    },
    "<u>SizePercent</u>": integer
  }
],
"HoldoutPercent": integer,
"Limits": {
  "Daily": integer,
  "Total": integer,
  "Session": integer,
  "MessagesPerSecond": integer,
  "MaximumDuration": integer
},
```

```
"Name": "string",
"Hook": {
    "LambdaFunctionName": "string",
    "WebUrl": "string",
    "Mode": enum
},
"Description": "string",
"tags": {
},
"Priority": integer
}
```

## **Response bodies**

### CampaignsResponse schema

```
{
  "Item": [
    {
      "TreatmentName": "string",
      "TreatmentDescription": "string",
      "MessageConfiguration": {
        "DefaultMessage": {
          "Body": "string",
          "Title": "string",
          "ImageUrl": "string",
          "ImageIconUrl": "string",
          "ImageSmallIconUrl": "string",
          "MediaUrl": "string",
          "Action": enum,
          "Url": "string",
          "SilentPush": boolean,
          "JsonBody": "string",
          "RawContent": "string",
          "TimeToLive": integer
        },
        "APNSMessage": {
          "Body": "string",
          "Title": "string",
          "ImageUrl": "string",
          "ImageIconUrl": "string",
          "ImageSmallIconUrl": "string",
          "MediaUrl": "string",
```

```
"Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"GCMMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"ADMMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"BaiduMessage": {
 "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
```

```
"SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"EmailMessage": {
 "Body": "string",
  "Title": "string",
  "HtmlBody": "string",
  "FromAddress": "string",
  "Headers": [
    {
      "Name": "string",
      "Value": "string"
   }
 ]
},
"SMSMessage": {
 "Body": "string",
 "MessageType": enum,
  "SenderId": "string",
  "OriginationNumber": "string",
  "EntityId": "string",
 "TemplateId": "string"
},
"CustomMessage": {
 "Data": "string"
},
"InAppMessage": {
 "Body": "string",
  "Layout": enum,
  "Content": [
    {
      "HeaderConfig": {
        "Header": "string",
        "TextColor": "string",
        "Alignment": enum
      },
      "BackgroundColor": "string",
      "BodyConfig": {
        "Body": "string",
        "TextColor": "string",
        "Alignment": enum
      },
```

```
"ImageUrl": "string",
"PrimaryBtn": {
  "DefaultConfig": {
    "Text": "string",
    "ButtonAction": enum,
    "Link": "string",
    "TextColor": "string",
    "BackgroundColor": "string",
    "BorderRadius": integer
  },
  "Web": {
    "ButtonAction": enum,
    "Link": "string"
  },
  "IOS": {
    "ButtonAction": enum,
    "Link": "string"
  },
  "Android": {
    "ButtonAction": enum,
    "Link": "string"
  }
},
"SecondaryBtn": {
  "DefaultConfig": {
    "Text": "string",
    "ButtonAction": enum,
    "Link": "string",
    "TextColor": "string",
    "BackgroundColor": "string",
    "BorderRadius": integer
  },
  "Web": {
    "ButtonAction": enum,
    "Link": "string"
  },
  "IOS": {
    "ButtonAction": enum,
    "Link": "string"
  },
  "Android": {
    "ButtonAction": enum,
    "Link": "string"
  }
```

```
}
      }
    ],
    "CustomConfig": {
  }
},
"Sche<u>dule</u>": {
  "StartTime": "string",
  "EndTime": "string",
  "Frequency": enum,
  "IsLocalTime": boolean,
  "Timezone": "string",
  "QuietTime": {
   "Start": "string",
    "End": "string"
  },
  "EventFilter": {
    "Dimensions": {
      "EventType": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      },
      "Attributes": {
      },
      "Metrics": {
      }
    },
    "FilterType": enum
  }
},
"TemplateConfiguration": {
  "SMSTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "EmailTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "PushTemplate": {
    "Name": "string",
```

```
"Version": "string"
  },
  "VoiceTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "InAppTemplate": {
    "Name": "string",
    "Version": "string"
 }
},
"CustomDeliveryConfiguration": {
  "EndpointTypes": [
    enum
 ],
  "DeliveryUri": "string"
},
"Id": "string",
"ApplicationId": "string",
"CreationDate": "string",
"LastModifiedDate": "string",
"SegmentId": "string",
"SegmentVersion": integer,
"AdditionalTreatments": [
  {
    "TreatmentName": "string",
    "TreatmentDescription": "string",
    "MessageConfiguration": {
      "DefaultMessage": {
        "Body": "string",
        "Title": "string",
        "ImageUrl": "string",
        "ImageIconUrl": "string",
        "ImageSmallIconUrl": "string",
        "MediaUrl": "string",
        "Action": enum,
        "Url": "string",
        "SilentPush": boolean,
        "JsonBody": "string",
        "RawContent": "string",
        "TimeToLive": integer
      },
      "APNSMessage": {
        "Body": "string",
```

```
"Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"GCMMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"ADMMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"BaiduMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
```

```
"ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  ""MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"EmailMessage": {
  "Body": "string",
  "Title": "string",
  "HtmlBody": "string",
  "FromAddress": "string",
  "Headers": [
    {
      "Name": "string",
      "Value": "string"
    }
  ]
},
"SMSMessage": {
  "Body": "string",
  "MessageType": enum,
  "SenderId": "string",
  "OriginationNumber": "string",
  "EntityId": "string",
  "TemplateId": "string"
},
"CustomMessage": {
  "Data": "string"
},
"InAppMessage": {
  "Body": "string",
  "Layout": enum,
  "Content": [
    {
      "HeaderConfig": {
        "Header": "string",
        "TextColor": "string",
        "Alignment": enum
      },
      "BackgroundColor": "string",
```

```
"BodyConfig": {
  "Body": "string",
  "TextColor": "string",
  "Alignment": enum
},
"ImageUrl": "string",
"PrimaryBtn": {
  "DefaultConfig": {
    "Text": "string",
    "ButtonAction": enum,
    "Link": "string",
    "TextColor": "string",
    "BackgroundColor": "string",
    "BorderRadius": integer
  },
  "Web": {
    "ButtonAction": enum,
    "Link": "string"
  },
  "IOS": {
    "ButtonAction": enum,
    "Link": "string"
  },
  "Android": {
    "ButtonAction": enum,
    "Link": "string"
  }
},
"SecondaryBtn": {
  "DefaultConfig": {
    "Text": "string",
    "ButtonAction": enum,
    "Link": "string",
    "TextColor": "string",
    "BackgroundColor": "string",
    "BorderRadius": integer
  },
  "Web": {
    "ButtonAction": enum,
    "Link": "string"
 },
  "IOS": {
    "ButtonAction": enum,
    "Link": "string"
```

```
},
          "Android": {
            "ButtonAction": enum,
            "Link": "string"
          }
        }
      }
    ],
    "CustomConfig": {
 }
},
"Schedule": {
  "StartTime": "string",
 "EndTime": "string",
  "Frequency": enum,
  "IsLocalTime": boolean,
  "Timezone": "string",
  "QuietTime": {
    "Start": "string",
    "End": "string"
 },
  "EventFilter": {
    "Dimensions": {
      "EventType": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      },
      "Attributes": {
      },
      "Metrics": {
      }
    "FilterType": enum
 }
},
"TemplateConfiguration": {
  "SMSTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "EmailTemplate": {
```

```
"Name": "string",
        "Version": "string"
      },
      "PushTemplate": {
        "Name": "string",
        "Version": "string"
      },
      "VoiceTemplate": {
        "Name": "string",
        "Version": "string"
      },
      "InAppTemplate": {
        "Name": "string",
        "Version": "string"
      }
    },
    "CustomDeliveryConfiguration": {
      "EndpointTypes": [
        enum
      ],
      "DeliveryUri": "string"
    },
    "SizePercent": integer,
    "Id": "string",
    "State": {
      "CampaignStatus": enum
    }
  }
],
"HoldoutPe<u>rcent</u>": integer,
"Name": "string",
"Limits": {
  "Daily": integer,
  "Total": integer,
  "Session": integer,
  "MessagesPerSecond": integer,
  "MaximumDuration": integer
},
"Description": "string",
"Hook": {
  "LambdaFunctionName": "string",
  "WebUrl": "string",
  "Mode": enum
},
```

```
"State": {
        "CampaignStatus": enum
      },
      "DefaultState": {
        "CampaignStatus": enum
      },
      "Version": integer,
      "IsPaused": boolean,
      "Arn": "string",
      "tags": {
      },
      "Priority": integer
    }
  ],
  "NextToken": "string"
}
```

## CampaignResponse schema

```
{
  "TreatmentName": "string",
  "TreatmentDescription": "string",
  "MessageConfiguration": {
    "DefaultMessage": {
      "Body": "string",
      "Title": "string",
      "ImageUrl": "string",
      "ImageIconUrl": "string",
      "ImageSmallIconUrl": "string",
      "MediaUrl": "string",
      "Action": enum,
      "Url": "string",
      "SilentPush": boolean,
      "JsonBody": "string",
      "RawContent": "string",
      "TimeToLive": integer
    },
    "APNSMessage": {
      "Body": "string",
      "Title": "string",
      "ImageUrl": "string",
      "ImageIconUrl": "string",
      "ImageSmallIconUrl": "string",
```

```
"MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"GCMMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"ADMMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"BaiduMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
```

```
"Url": "string",
  "SilentPush": boolean,
  "<u>JsonBody</u>": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"EmailMessage": {
  "Body": "string",
  "Title": "string",
  "HtmlBody": "string",
  "FromAddress": "string",
  "Headers": [
    {
      "Name": "string",
      "Value": "string"
    }
  ]
},
"SMSMessage": {
  "Body": "string",
  "MessageType": enum,
  "SenderId": "string",
  "OriginationNumber": "string",
  "EntityId": "string",
  "TemplateId": "string"
},
"CustomMessage": {
  "Data": "string"
},
"InAppMessage": {
  "Body": "string",
  "Layout": enum,
  "Content": [
    {
      "HeaderConfig": {
        "Header": "string",
        "TextColor": "string",
        "Alignment": enum
      },
      "BackgroundColor": "string",
      "BodyConfig": {
        "Body": "string",
        "TextColor": "string",
        "Alignment": enum
```

```
},
"ImageUrl": "string",
"PrimaryBtn": {
  "DefaultConfig": {
    "Text": "string",
    "ButtonAction": enum,
    "Link": "string",
    "TextColor": "string",
    "BackgroundColor": "string",
    "BorderRadius": integer
  },
  "Web": {
    "ButtonAction": enum,
    "Link": "string"
 },
  "IOS": {
    "ButtonAction": enum,
    "Link": "string"
 },
  "Android": {
    "ButtonAction": enum,
    "Link": "string"
 }
},
"SecondaryBtn": {
  "DefaultConfig": {
    "Text": "string",
    "ButtonAction": enum,
    "Link": "string",
    "TextColor": "string",
    "BackgroundColor": "string",
    "BorderRadius": integer
  },
  "Web": {
    "ButtonAction": enum,
    "Link": "string"
 },
  "IOS": {
    "ButtonAction": enum,
    "Link": "string"
 },
  "Android": {
    "ButtonAction": enum,
    "Link": "string"
```

```
}
        }
      }
    ],
    "CustomConfig": {
    }
  }
},
"Schedule": {
  "StartTime": "string",
  "EndTime": "string",
  "Frequency": enum,
  "IsLocalTime": boolean,
  "Timezone": "string",
  "QuietTime": {
    "Start": "string",
    "End": "string"
  },
  "EventFilter": {
    "Dimensions": {
      "EventType": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      },
      "Attributes": {
      },
      "Metrics": {
      }
    },
    "FilterType": enum
  }
},
"TemplateConfiguration": {
  "SMSTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "EmailTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "PushTemplate": {
```

```
"Name": "string",
    "Version": "string"
  },
  "VoiceTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "InAppTemplate": {
    "Name": "string",
    "Version": "string"
  }
},
"CustomDeliveryConfiguration": {
  "EndpointTypes": [
    enum
  ],
  "DeliveryUri": "string"
},
"Id": "string",
"ApplicationId": "string",
""CreationDate": "string",
"LastModifiedDate": "string",
"SegmentId": "string",
"SegmentVersion": integer,
"AdditionalTreatments": [
  {
    "TreatmentName": "string",
    "TreatmentDescription": "string",
    "MessageConfiguration": {
      "DefaultMessage": {
        "Body": "string",
        "Title": "string",
        "ImageUrl": "string",
        "ImageIconUrl": "string",
        "ImageSmallIconUrl": "string",
        "MediaUrl": "string",
        "Action": enum,
        "Url": "string",
        "SilentPush": boolean,
        "JsonBody": "string",
        "RawContent": "string",
        "TimeToLive": integer
      },
      "APNSMessage": {
```

```
"Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"GCMMessage": {
 "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
 "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
 "TimeToLive": integer
},
"ADMMessage": {
  "Body": "string",
  "Title": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  ""MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
 "RawContent": "string",
  "TimeToLive": integer
},
"BaiduMessage": {
 "Body": "string",
  "Title": "string",
```

```
"ImageUrl": "string",
  "ImageIconUrl": "string",
  "ImageSmallIconUrl": "string",
  "MediaUrl": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "JsonBody": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"EmailMessage": {
  "Body": "string",
  "Title": "string",
  "HtmlBody": "string",
  "FromAddress": "string",
  "Headers": [
    {
      "Name": "string",
      "Value": "string"
    }
  ]
},
"SMSMessage": {
  "Body": "string",
  "MessageType": enum,
  "SenderId": "string",
  "OriginationNumber": "string",
  "EntityId": "string",
 "TemplateId": "string"
},
"CustomMessage": {
  "Data": "string"
},
"InAppMessage": {
  "Body": "string",
  "Layout": enum,
  "Content": [
    {
      "HeaderConfig": {
        ""Header": "string",
        "TextColor": "string",
        "Alignment": enum
      },
```

```
"BackgroundColor": "string",
"BodyConfig": {
  "Body": "string",
  "TextColor": "string",
  "Alignment": enum
},
"ImageUrl": "string",
"PrimaryBtn": {
  "DefaultConfig": {
    "Text": "string",
    "ButtonAction": enum,
    "Link": "string",
    "TextColor": "string",
    "BackgroundColor": "string",
    "BorderRadius": integer
  },
  "Web": {
    "ButtonAction": enum,
    "Link": "string"
  },
  "IOS": {
    "ButtonAction": enum,
    "Link": "string"
  },
  "Android": {
    "ButtonAction": enum,
    "Link": "string"
  }
},
"SecondaryBtn": {
  "DefaultConfig": {
    "Text": "string",
    "ButtonAction": enum,
    "Link": "string",
    "TextColor": "string",
    "BackgroundColor": "string",
    "BorderRadius": integer
  },
  "Web": {
    "ButtonAction": enum,
    "Link": "string"
  },
  "IOS": {
    "ButtonAction": enum,
```

```
"Link": "string"
          },
          "Android": {
            "ButtonAction": enum,
            "Link": "string"
          }
        }
      }
    ],
    "CustomConfig": {
  }
},
"Schedule": {
  "StartTime": "string",
  "EndTime": "string",
  "Frequency": enum,
  "IsLocalTime": boolean,
  "Timezone": "string",
  "QuietTime": {
   "Start": "string",
   "End": "string"
  },
  "EventFilter": {
    "Dimensions": {
      "EventType": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      },
      "Attributes": {
      },
      ""Metrics": {
      }
    },
    "FilterType": enum
  }
},
"TemplateConfiguration": {
  "SMSTemplate": {
    "Name": "string",
    "Version": "string"
  },
```

```
"EmailTemplate": {
        "Name": "string",
        "Version": "string"
      },
      "PushTemplate": {
        "Name": "string",
        "Version": "string"
      },
      "VoiceTemplate": {
        "Name": "string",
        "Version": "string"
      },
      "InAppT<u>emplate</u>": {
        "Name": "string",
        "Version": "string"
      }
    },
    "CustomDeliveryConfiguration": {
      "EndpointTypes": [
        enum
      ],
      "DeliveryUri": "string"
    },
    "SizePercent": integer,
    "Id": "string",
    "State": {
      "CampaignStatus": enum
  }
],
"HoldoutPercent": integer,
"Name": "string",
"Limits": {
  "Daily": integer,
  "Total": integer,
  "Session": integer,
  "MessagesPe<u>rSecond</u>": integer,
  "MaximumDuration": integer
},
"Description": "string",
"Hook": {
  "LambdaFunctionName": "string",
  "WebUrl": "string",
  "Mode": enum
```

```
},
"State": {
    "CampaignStatus": enum
},
"DefaultState": {
    "CampaignStatus": enum
},
"Version": integer,
"IsPaused": boolean,
"Arn": "string",
"tags": {
},
"Priority": integer
}
```

## MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

### **AttributeDimension**

Specifies attribute-based criteria for including or excluding endpoints from a segment.

# **AttributeType**

The type of segment dimension to use. Valid values are:

- INCLUSIVE endpoints that have attributes matching the values are included in the segment.
- EXCLUSIVE endpoints that have attributes matching the values are excluded from the segment.
- CONTAINS endpoints that have attributes' substrings match the values are included in the segment.
- BEFORE endpoints with attributes read as ISO\_INSTANT datetimes before the value are included in the segment.

• AFTER – endpoints with attributes read as ISO\_INSTANT datetimes after the value are included in the segment.

- BETWEEN endpoints with attributes read as ISO\_INSTANT datetimes between the values are included in the segment.
- ON endpoints with attributes read as ISO\_INSTANT dates on the value are included in the segment. Time is ignored in this comparison.

**Type**: string **Required**: False

Values: INCLUSIVE | EXCLUSIVE | CONTAINS | BEFORE | AFTER | BETWEEN |

NOT\_BETWEEN | ON

### **Values**

The criteria values to use for the segment dimension. Depending on the value of the AttributeType property, endpoints are included or excluded from the segment if their attribute values match the criteria values.

**Type**: Array of type string

Required: True

# ${\bf Campaign Custom Message}$

Specifies the contents of a message that's sent through a custom channel to recipients of a campaign.

#### Data

The raw, JSON-formatted string to use as the payload for the message. The maximum size is 5 KB.

**Type**: string **Required**: False

# CampaignEmailMessage

Specifies the content and "From" address for an email message that's sent to recipients of a campaign.

### **Body**

The body of the email for recipients whose email clients don't render HTML content.

**Type**: string **Required**: False

#### Title

The subject line, or title, of the email.

**Type**: string **Required**: False

## HtmlBody

The body of the email, in HTML format, for recipients whose email clients render HTML content.

**Type**: string **Required**: False

### **FromAddress**

The verified email address to send the email from. The default address is the FromAddress specified for the email channel for the application.

**Type**: string **Required**: False

### **Headers**

The list of MessageHeaders for the email. You can have up to 15 MessageHeaders for each email.

**Type**: Array of type MessageHeader

Required: False

# CampaignEventFilter

Specifies the settings for events that cause a campaign to be sent.

### **Dimensions**

The dimension settings of the event filter for the campaign.

**Type**: EventDimensions

Required: True

# FilterType

The type of event that causes the campaign to be sent. Valid values are: SYSTEM, sends the campaign when a system event occurs; and, ENDPOINT, sends the campaign when an endpoint event (Events resource) occurs.

**Type**: string **Required**: True

Values: SYSTEM | ENDPOINT | USER

# CampaignHook

Specifies settings for invoking an AWS Lambda function that customizes a segment for a campaign.

### LambdaFunctionName

The name or Amazon Resource Name (ARN) of the AWS Lambda function that Amazon Pinpoint invokes to customize a segment for a campaign.

**Type**: string **Required**: False

#### WebUrl

The web URL that Amazon Pinpoint calls to invoke the AWS Lambda function over HTTPS.

**Type**: string **Required**: False

#### Mode

The mode that Amazon Pinpoint uses to invoke the AWS Lambda function. Possible values are:

• FILTER – Invoke the function to customize the segment that's used by a campaign.

 DELIVERY – (Deprecated) Previously, invoked the function to send a campaign through a custom channel. This functionality is not supported anymore. To send a campaign through a custom channel, use the CustomDeliveryConfiguration and CampaignCustomMessage objects of the campaign.

**Type**: string

Required: False

Values: DELIVERY | FILTER

# CampaignInAppMessage

Specifies the appearance of an in-app message, including the message type, the title and body text, text and background colors, and the configurations of buttons that appear in the message.

## **Body**

The body text of the in-app notification.

Type: string

Required: False

## Layout

A string that describes how the in-app message will appear. You can specify one of the following:

- BOTTOM\_BANNER a message that appears as a banner at the bottom of the page.
- TOP\_BANNER a message that appears as a banner at the top of the page.
- OVERLAYS a message that covers entire screen.
- MOBILE\_FEED a message that appears in a window in front of the page.
- MIDDLE\_BANNER a message that appears as a banner in the middle of the page.
- CAROUSEL a scrollable layout of up to five unique messages.

**Type**: string **Required**: False

Values: BOTTOM\_BANNER | TOP\_BANNER | OVERLAYS | MOBILE\_FEED | MIDDLE\_BANNER | CAROUSEL

#### Content

An array that contains configurtion information about the in-app message for the campaign, including title and body text, text colors, background colors, image URLs, and button configurations.

**Type**: Array of type InAppMessageContent

Required: False

# CustomConfig

An object that contains custom data (in the form of key-value pairs) that is included in the in-app messaging payload.

**Type**: object

Required: False

# **CampaignLimits**

For a campaign, specifies limits on the messages that the campaign can send. For an application, specifies the default limits for messages that campaigns in the application can send.

## **Daily**

The maximum number of messages that a campaign can send to a single endpoint during a 24-hour period. For an application, this value specifies the default limit for the number of messages that campaigns and journeys can send to a single endpoint during a 24-hour period. The maximum value is 100.

**Type**: integer

**Required**: False

#### **Total**

The maximum number of messages that a campaign can send to a single endpoint during the course of the campaign. If a campaign recurs, this setting applies to all runs of the campaign. The maximum value is 100.

**Type**: integer **Required**: False

#### Session

The maximum number of messages that the campaign can send per user session.

**Type**: integer **Required**: False

## MessagesPerSecond

The maximum number of messages that a campaign can send each second. For an application, this value specifies the default limit for the number of messages that campaigns can send each second. The minimum value is 1. The maximum value is 20,000.

**Type**: integer **Required**: False

### **MaximumDuration**

The maximum amount of time, in seconds, that a campaign can attempt to deliver a message after the scheduled start time for the campaign. The minimum value is 60 seconds.

**Type**: integer **Required**: False

# CampaignResponse

Provides information about the status, configuration, and other settings for a campaign.

#### **TreatmentName**

The custom name of the default treatment for the campaign, if the campaign has multiple treatments. A *treatment* is a variation of a campaign that's used for A/B testing.

**Type**: string **Required**: False

### **TreatmentDescription**

The custom description of the default treatment for the campaign.

**Type**: string **Required**: False

# MessageConfiguration

The message configuration settings for the campaign.

**Type**: MessageConfiguration

Required: False

### **Schedule**

The schedule settings for the campaign.

Type: <u>Schedule</u> Required: False

## **TemplateConfiguration**

The message template that's used for the campaign.

**Type**: TemplateConfiguration

Required: False

### CustomDeliveryConfiguration

The delivery configuration settings for sending the campaign through a custom channel.

Type: CustomDeliveryConfiguration

Required: False

#### Id

The unique identifier for the campaign.

**Type**: string **Required**: True

# **ApplicationId**

The unique identifier for the application that the campaign applies to.

**Type**: string **Required**: True

#### CreationDate

The date, in ISO 8601 format, when the campaign was created.

**Type**: string **Required**: True

### LastModifiedDate

The date, in ISO 8601 format, when the campaign was last modified.

**Type**: string **Required**: True

# SegmentId

The unique identifier for the segment that's associated with the campaign.

**Type**: string **Required**: True

### **SegmentVersion**

The version number of the segment that's associated with the campaign.

**Type**: integer **Required**: True

### **AdditionalTreatments**

An array of responses, one for each treatment that you defined for the campaign, in addition to the default treatment.

**Type**: Array of type TreatmentResource

Required: False

## **HoldoutPercent**

The allocated percentage of users (segment members) who shouldn't receive messages from the campaign.

**Type**: integer **Required**: False

#### Name

The name of the campaign.

**Type**: string **Required**: False

#### Limits

The messaging limits for the campaign.

**Type**: CampaignLimits

Required: False

### Description

The custom description of the campaign.

Type: string

Required: False

#### Hook

The settings for the AWS Lambda function to use as a code hook for the campaign. You can use this hook to customize the segment that's used by the campaign.

Type: CampaignHook

Required: False

#### **State**

The current status of the campaign.

Type: CampaignState

Required: False

### **DefaultState**

The current status of the campaign's default treatment. This value exists only for campaigns that have more than one treatment.

Type: CampaignState

Required: False

### Version

The version number of the campaign.

**Type**: integer **Required**: False

#### **IsPaused**

Specifies whether the campaign is paused. A paused campaign doesn't run unless you resume it by changing this value to false. If you restart a campaign, the campaign restarts from the beginning and not at the point you paused it.

**Type**: boolean **Required**: False

#### Arn

The Amazon Resource Name (ARN) of the campaign.

**Type**: string **Required**: True

### tags

A string-to-string map of key-value pairs that identifies the tags that are associated with the campaign. Each tag consists of a required tag key and an associated tag value.

**Type**: object **Required**: False

# **Priority**

Defines the priority of the campaign. This value used to determine the order in which messages are displayed to the recipient if there are multiple messages scheduled to be displayed at the same time.

**Type**: integer **Required**: False

# CampaignSmsMessage

Specifies the content and settings for an SMS message that's sent to recipients of a campaign.

# **Body**

The body of the SMS message.

**Type**: string **Required**: False

# MessageType

The SMS message type. Valid values are TRANSACTIONAL (for messages that are critical or time-sensitive, such as a one-time passwords) and PROMOTIONAL (for messsages that aren't critical or time-sensitive, such as marketing messages).

**Type**: string **Required**: False

Values: TRANSACTIONAL | PROMOTIONAL

#### SenderId

The alphabetic Sender ID to display as the sender of the message on a recipient's device. Support for sender IDs varies by country or region. To specify a phone number as the sender, omit this parameter and use OriginationNumber instead. For more information about support for Sender ID by country, see the Amazon Pinpoint User Guide.

**Type**: string **Required**: False

### OriginationNumber

The number to send the SMS message from. The phone number that you specify must exist in your Amazon Pinpoint account—you can't pass an arbitrary phone number. If you want to use a sender ID to send your message, omit this parameter and use SenderId instead.

**Type**: string **Required**: False

## **EntityId**

A registered Entity ID (currently only used when sending messages to recipients in India).

**Type**: string **Required**: False

### TemplateId

A registered Template ID (currently only used when sending messages to recipients in India).

**Type**: string

Required: False

# CampaignState

Provides information about the status of a campaign.

## **CampaignStatus**

The current status of the campaign, or the current status of a treatment that belongs to an A/B test campaign.

If a campaign uses A/B testing, the campaign has a status of COMPLETED only if all campaign treatments have a status of COMPLETED. If you delete the segment that's associated with a campaign, the campaign fails and has a status of DELETED.

Type: string

Required: False

Values: SCHEDULED | EXECUTING | PENDING\_NEXT\_RUN | COMPLETED | PAUSED |

DELETED | INVALID | PENDING\_APPROVAL | DRAFT

# CampaignsResponse

Provides information about the configuration and other settings for all the campaigns that are associated with an application.

#### **Item**

An array of responses, one for each campaign that's associated with the application.

**Type**: Array of type CampaignResponse

**Required**: True

#### NextToken

The string to use in a subsequent request to get the next page of results in a paginated response. This value is null if there are no additional pages.

**Type**: string **Required**: False

# CustomDeliveryConfiguration

Specifies the delivery configuration settings for sending a campaign or campaign treatment through a custom channel. This object is required if you use the CampaignCustomMessage object to define the message to send for the campaign or campaign treatment.

## **EndpointTypes**

The types of endpoints to send the campaign or treatment to. Each valid value maps to a type of channel that you can associate with an endpoint by using the Channel Type property of an endpoint.

Type: Array of type string

Required: False

Values: PUSH | GCM | APNS | APNS\_SANDBOX | APNS\_VOIP | APNS\_VOIP\_SANDBOX |

ADM | SMS | VOICE | EMAIL | BAIDU | CUSTOM | IN\_APP

# DeliveryUri

The destination to send the campaign or treatment to. This value can be one of the following:

- The name or Amazon Resource Name (ARN) of an AWS Lambda function to invoke to handle delivery of the campaign or treatment.
- The URL for a web application or service that supports HTTPS and can receive the message. The URL has to be a full URL, including the HTTPS protocol.

**Type**: string **Required**: True

# DefaultButtonConfiguration

Information about the default behavior for a button that appears in an in-app message. You can optionally add button configurations that specifically apply to iOS, Android, or web browser users.

#### **Text**

The text that appears on a button in an in-app message.

**Type**: string **Required**: True

#### **ButtonAction**

The action that occurs when a recipient chooses a button in an in-app message. You can specify one of the following:

- LINK A link to a web destination.
- DEEP\_LINK A link to a specific page in an application.
- CLOSE Dismisses the message.

**Type**: string **Required**: True

Values: LINK | DEEP\_LINK | CLOSE

#### Link

The destination (such as a URL) for a button.

**Type**: string **Required**: False

#### **TextColor**

The color of the body text in a button, expressed as a string consisting of a hex color code (such as "#000000" for black).

**Type**: string **Required**: False

### BackgroundColor

The background color of a button, expressed as a string consisting of a hex color code (such as "#000000" for black).

Type: string

Required: False

#### **BorderRadius**

The border radius of a button.

**Type**: integer **Required**: False

### **EventDimensions**

Specifies the dimensions for an event filter that determines when a campaign is sent or a journey activity is performed.

### **EventType**

The name of the event that causes the campaign to be sent or the journey activity to be performed. This can be a standard event that Amazon Pinpoint generates, such as \_email.delivered or \_custom.delivered. For campaigns, this can also be a custom event that's specific to your application. For information about standard events, see <a href="Streaming Amazon Pinpoint Events">Streaming Amazon Pinpoint Events</a> in the Amazon Pinpoint Developer Guide.

**Type**: SetDimension

Required: False

#### **Attributes**

One or more custom attributes that your application reports to Amazon Pinpoint. You can use these attributes as selection criteria when you create an event filter.

**Type**: object **Required**: False

#### **Metrics**

One or more custom metrics that your application reports to Amazon Pinpoint. You can use these metrics as selection criteria when you create an event filter.

**Type**: object **Required**: False

# InAppMessageBodyConfig

Configuration information related to the main body text of an in-app message.

### **Body**

The main body text of the message.

**Type**: string **Required**: True

#### **TextColor**

The color of the body text, expressed as a string consisting of a hex color code (such as "#000000" for black).

**Type**: string **Required**: False

### **Alignment**

The text alignment of the main body text of the message.

**Type**: string **Required**: True

Values: LEFT | CENTER | RIGHT

# In App Message Button

Configuration information for a button that appears in an in-app message.

### **DefaultConfig**

An object that defines the default behavior for a button in an in-app message.

Type: DefaultButtonConfiguration

Required: False

#### Web

An object that defines the default behavior for a button in in-app messages for web applications.

Type: OverrideButtonConfiguration

Required: False

#### IOS

An object that defines the default behavior for a button in in-app messages sent to iOS devices.

**Type**: OverrideButtonConfiguration

Required: False

#### **Android**

An object that defines the default behavior for a button in in-app messages sent to Android.

**Type**: OverrideButtonConfiguration

Required: False

# InAppMessageContent

Configuration information related to an in-app message.

### HeaderConfig

An object that contains configuration information about the header or title text of the in-app message.

Type: InAppMessageHeaderConfig

Required: False

### BackgroundColor

The background color for an in-app message banner, expressed as a string consisting of a hex color code (such as "#000000" for black).

**Type**: string **Required**: False

## **BodyConfig**

An object that contains configuration information about the header or title text of the in-app message.

Type: InAppMessageBodyConfig

Required: False

### **ImageUrl**

The URL of the image that appears on an in-app message banner.

**Type**: string **Required**: False

### **PrimaryBtn**

An object that contains configuration information about the primary button in an in-app message.

**Type**: InAppMessageButton

Required: False

# SecondaryBtn

An object that contains configuration information about the secondary button in an in-app message.

**Type**: InAppMessageButton

Required: False

# InAppMessageHeaderConfig

Configuration information related to the message header for an in-app message.

#### Header

The text that appears in the header or title of the message.

**Type**: string **Required**: True

### **TextColor**

The color of the body text, expressed as a string consisting of a hex color code (such as "#000000" for black).

**Type**: string **Required**: False

### **Alignment**

The text alignment of the title of the message.

**Type**: string **Required**: True

Values: LEFT | CENTER | RIGHT

# Message

Specifies the content and settings for a push notification that's sent to recipients of a campaign.

### **Body**

The body of the notification message. The maximum number of characters is 200.

**Type**: string **Required**: False

#### **Title**

The title to display above the notification message on a recipient's device.

**Type**: string **Required**: False

### **ImageUrl**

The URL of an image to display in the push notification.

**Type**: string **Required**: False

### **ImageIconUrl**

The URL of the image to display as the push notification icon, such as the icon for the app.

**Type**: string **Required**: False

### **ImageSmallIconUrl**

The URL of the image to display as the small, push notification icon, such as a small version of the icon for the app.

**Type**: string **Required**: False

#### MediaUrl

The URL of the image or video to display in the push notification.

**Type**: string **Required**: False

#### Action

The action to occur if a recipient taps the push notification. Valid values are:

**REST API Reference** Amazon Pinpoint

• OPEN APP – Your app opens or it becomes the foreground app if it was sent to the background. This is the default action.

 DEEP\_LINK – Your app opens and displays a designated user interface in the app. This setting uses the deep-linking features of iOS and Android.

• URL – The default mobile browser on the recipient's device opens and loads the web page at a URL that you specify.

**Type**: string

Required: False

Values: OPEN\_APP | DEEP\_LINK | URL

Url

The URL to open in a recipient's default mobile browser, if a recipient taps the push notification and the value of the Action property is URL.

**Type**: string

**Required**: False

**SilentPush** 

Specifies whether the notification is a silent push notification, which is a push notification that doesn't display on a recipient's device. Silent push notifications can be used for cases such as updating an app's configuration, displaying messages in an in-app message center, or supporting phone home functionality.

Type: boolean

Required: False

**JsonBody** 

The JSON payload to use for a silent push notification.

Type: string

Required: False

#### **RawContent**

The raw, JSON-formatted string to use as the payload for the notification message. If specified, this value overrides all other content for the message.

**Type**: string

Required: False

#### **TimeToLive**

The number of seconds that the push notification service should keep the message, if the service is unable to deliver the notification the first time. This value is converted to an expiration value when it's sent to a push notification service. If this value is 0, the service treats the notification as if it expires immediately and the service doesn't store or try to deliver the notification again.

This value doesn't apply to messages that are sent through the Amazon Device Messaging (ADM) service.

**Type**: integer

Required: False

# MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

Type: string

Required: False

# Message

The message that's returned from the API.

Type: string

Required: False

# MessageConfiguration

Specifies the message configuration settings for a campaign.

### DefaultMessage

The default message that the campaign sends through all the channels that are configured for the campaign.

Type: Message
Required: False

### **APNSMessage**

The message that the campaign sends through the APNs (Apple Push Notification service) channel. If specified, this message overrides the default message.

Type: Message
Required: False

### **GCMMessage**

The message that the campaign sends through the GCM channel, which enables Amazon Pinpoint to send push notifications through the Firebase Cloud Messaging (FCM), formerly Google Cloud Messaging (GCM), service. If specified, this message overrides the default message.

Type: Message
Required: False

# **ADMMessage**

The message that the campaign sends through the ADM (Amazon Device Messaging) channel. If specified, this message overrides the default message.

Type: Message
Required: False

### BaiduMessage

The message that the campaign sends through the Baidu (Baidu Cloud Push) channel. If specified, this message overrides the default message.

Type: Message **Required**: False

### **EmailMessage**

The message that the campaign sends through the email channel. If specified, this message overrides the default message.



### Note

The maximum email message size is 200 KB. You can use email templates to send larger email messages.

Type: CampaignEmailMessage

**Required**: False

### **SMSMessage**

The message that the campaign sends through the SMS channel. If specified, this message overrides the default message.

Type: CampaignSmsMessage

Required: False

# CustomMessage

The message that the campaign sends through a custom channel, as specified by the delivery configuration (CustomDeliveryConfiguration) settings for the campaign. If specified, this message overrides the default message.

Type: CampaignCustomMessage

Required: False

### **InAppMessage**

The default message for the in-app messaging channel. This message overrides the default message (DefaultMessage).

**Type**: CampaignInAppMessage

**Required**: False

### MessageHeader

Contains the name and value pair of an message header to add to your email. You can have up to 15 MessageHeaders. A header can contain information such as the sender, receiver, route, or timestamp.

#### Name

The name of the message header. The header name can contain up to 126 characters.

**Type**: string **Required**: False

#### **Value**

The value of the message header. The header value can contain up to 870 characters, including the length of any rendered attributes. For example if you add the {CreationDate} attribute, it renders as YYYY-MM-DDTHH: MM:SS.SSSZ and is 24 characters in length.

**Type**: string **Required**: False

### MetricDimension

Specifies metric-based criteria for including or excluding endpoints from a segment. These criteria derive from custom metrics that you define for endpoints.

### ComparisonOperator

The operator to use when comparing metric values. Valid values are: GREATER\_THAN, LESS\_THAN, GREATER\_THAN\_OR\_EQUAL, LESS\_THAN\_OR\_EQUAL, and EQUAL.

**Type**: string **Required**: True

#### Value

The value to compare.

**Type**: number **Required**: True

# OverrideButtonConfiguration

Configuration information related to the configuration of a button with settings that are specific to a certain device type.

#### **ButtonAction**

The action that occurs when a recipient chooses a button in an in-app message. You can specify one of the following:

- LINK A link to a web destination.
- DEEP\_LINK A link to a specific page in an application.
- CLOSE Dismisses the message.

**Type**: string **Required**: False

Values: LINK | DEEP\_LINK | CLOSE

#### Link

The destination (such as a URL) for a button.

**Type**: string **Required**: False

# QuietTime

Specifies the start and end times that define a time range when messages aren't sent to endpoints.

#### Start

The specific time when quiet time begins. This value has to use 24-hour notation and be in HH:MM format, where HH is the hour (with a leading zero, if applicable) and MM is the minutes. For example, use 02:30 to represent 2:30 AM, or 14:30 to represent 2:30 PM.

Type: string

Required: False

#### End

The specific time when quiet time ends. This value has to use 24-hour notation and be in HH:MM format, where HH is the hour (with a leading zero, if applicable) and MM is the minutes. For example, use 02:30 to represent 2:30 AM, or 14:30 to represent 2:30 PM.

**Type**: string

Required: False

### Schedule

Specifies the schedule settings for a campaign.

#### StartTime

The scheduled time when the campaign began or will begin. Valid values are: IMMEDIATE, to start the campaign immediately; or, a specific time in ISO 8601 format.

**Type**: string

Required: True

### **EndTime**

The scheduled time, in ISO 8601 format, when the campaign ended or will end.

Type: string

Required: False

### Frequency

Specifies how often the campaign is sent or whether the campaign is sent in response to a specific event.

**Type**: string **Required**: False

Values: ONCE | HOURLY | DAILY | WEEKLY | MONTHLY | EVENT | IN\_APP\_EVENT

#### **IsLocalTime**

Specifies whether the start and end times for the campaign schedule use each recipient's local time. To base the schedule on each recipient's local time, set this value to true.

**Type**: boolean **Required**: False

#### Timezone

The starting UTC offset for the campaign schedule, if the value of the IsLocalTime property is true. Valid values are: UTC, UTC+01, UTC+02, UTC+03, UTC+03:30, UTC+04, UTC+04:30, UTC+05, UTC+05:30, UTC+05:45, UTC+06, UTC+06:30, UTC+07, UTC+08, UTC+09, UTC+09:30, UTC+10, UTC+10:30, UTC+11, UTC+12, UTC+13, UTC-02, UTC-03, UTC-04, UTC-05, UTC-06, UTC-07, UTC-08, UTC-09, UTC-10, and UTC-11.

**Type**: string **Required**: False

### QuietTime

The default quiet time for the campaign. Quiet time is a specific time range when a campaign doesn't send messages to endpoints, if all the following conditions are met:

- The EndpointDemographic. Timezone property of the endpoint is set to a valid value.
- The current time in the endpoint's time zone is later than or equal to the time specified by the QuietTime. Start property for the campaign.
- The current time in the endpoint's time zone is earlier than or equal to the time specified by the QuietTime. End property for the campaign.

If any of the preceding conditions isn't met, the endpoint will receive messages from the campaign, even if quiet time is enabled.

Type: QuietTime Required: False

#### **EventFilter**

The type of event that causes the campaign to be sent, if the value of the Frequency property is EVENT.

**Type**: CampaignEventFilter

Required: False

### **SetDimension**

Specifies the dimension type and values for a segment dimension.

### DimensionType

The type of segment dimension to use. Valid values are: INCLUSIVE, endpoints that match the criteria are included in the segment; and, EXCLUSIVE, endpoints that match the criteria are excluded from the segment.

Type: string

Required: False

Values: INCLUSIVE | EXCLUSIVE

#### **Values**

The criteria values to use for the segment dimension. Depending on the value of the DimensionType property, endpoints are included or excluded from the segment if their values match the criteria values.

Type: Array of type string

Required: True

### **Template**

Specifies the name and version of the message template to use for the message.

#### Name

The name of the message template to use for the message. If specified, this value must match the name of an existing message template.

**Type**: string **Required**: False

#### Version

The unique identifier for the version of the message template to use for the message. If specified, this value must match the identifier for an existing template version. To retrieve a list of versions and version identifiers for a template, use the <u>Template Versions</u> resource.

If you don't specify a value for this property, Amazon Pinpoint uses the *active version* of the template. The *active version* is typically the version of a template that's been most recently reviewed and approved for use, depending on your workflow. It isn't necessarily the latest version of a template.

**Type**: string **Required**: False

# TemplateConfiguration

Specifies the message template to use for the message, for each type of channel.

# **SMSTemplate**

The SMS template to use for the message.

Type: <u>Template</u> Required: False

### **EmailTemplate**

The email template to use for the message.

Type: <u>Template</u>
Required: False

### **PushTemplate**

The push notification template to use for the message.

Type: <u>Template</u> Required: False

### VoiceTemplate

The voice template to use for the message. This object isn't supported for campaigns.

Type: <u>Template</u>
Required: False

### **InAppTemplate**

The InApp template to use for the message. The InApp template object is not supported for SendMessages.

Type: <u>Template</u>
Required: False

#### **TreatmentResource**

Specifies the settings for a campaign treatment. A *treatment* is a variation of a campaign that's used for A/B testing of a campaign.

#### **TreatmentName**

The custom name of the treatment.

**Type**: string **Required**: False

### **TreatmentDescription**

The custom description of the treatment.

**Type**: string

Required: False

### MessageConfiguration

The message configuration settings for the treatment.

**Type**: MessageConfiguration

Required: False

#### Schedule

The schedule settings for the treatment.

Type: <u>Schedule</u> Required: False

### **TemplateConfiguration**

The message template to use for the treatment.

**Type**: TemplateConfiguration

Required: False

### CustomDeliveryConfiguration

The delivery configuration settings for sending the treatment through a custom channel. This object is required if the MessageConfiguration object for the treatment specifies a CustomMessage object.

**Type**: CustomDeliveryConfiguration

Required: False

#### **SizePercent**

The allocated percentage of users (segment members) that the treatment is sent to.

**Type**: integer **Required**: True

Id

The unique identifier for the treatment.

**Type**: string **Required**: True

#### **State**

The current status of the treatment.

**Type**: CampaignState

Required: False

# WriteCampaignRequest

Specifies the configuration and other settings for a campaign.

#### **TreatmentName**

A custom name of the default treatment for the campaign, if the campaign has multiple treatments. A *treatment* is a variation of a campaign that's used for A/B testing.

Type: string

Required: False

### **TreatmentDescription**

A custom description of the default treatment for the campaign.

Type: string

Required: False

### MessageConfiguration

The message configuration settings for the campaign.

**Type**: MessageConfiguration

Required: False

#### Schedule

The schedule settings for the campaign.

Type: Schedule
Required: False

### **TemplateConfiguration**

The message template to use for the campaign.

**Type**: TemplateConfiguration

Required: False

# CustomDeliveryConfiguration

The delivery configuration settings for sending the campaign through a custom channel. This object is required if the MessageConfiguration object for the campaign specifies a CustomMessage object.

Type: CustomDeliveryConfiguration

Required: False

# SegmentId

The unique identifier for the segment to associate with the campaign.

**Type**: string **Required**: False

### **SegmentVersion**

The version of the segment to associate with the campaign.

**Type**: integer **Required**: False

#### **IsPaused**

Specifies whether to pause the campaign. A paused campaign doesn't run unless you resume it by changing this value to false. If you restart a campaign, the campaign restarts from the beginning and not at the point you paused it. If a campaign is running it will complete and then pause. Pause only pauses or skips the next run for a recurring future scheduled campaign. A campaign scheduled for immediate can't be paused.

**Type**: boolean **Required**: False

#### **AdditionalTreatments**

An array of requests that defines additional treatments for the campaign, in addition to the default treatment for the campaign.

**Type**: Array of type WriteTreatmentResource

**Required**: False

#### **HoldoutPercent**

The allocated percentage of users (segment members) who shouldn't receive messages from the campaign.

**Type**: integer **Required**: False

#### Limits

The messaging limits for the campaign.

**Type:** CampaignLimits

**REST API Reference** Amazon Pinpoint

Required: False

#### Name

A custom name for the campaign.

**Type**: string Required: False

#### Hook

The settings for the AWS Lambda function to invoke as a code hook for the campaign. You can use this hook to customize the segment that's used by the campaign.

Type: CampaignHook

Required: False

### Description

A custom description of the campaign.

Type: string Required: False

#### tags



### Note

As of 22-05-2023 the PUT UpdateCampaign tags attribute has been deprecated. After this date any value in the tags attribute is not processed and will not generate an error code. Use the Tags resource to add or modify tags.

(Deprecated) A string-to-string map of key-value pairs that defines the tags to associate with the campaign. Each tag consists of a required tag key and an associated tag value.

Type: object Required: False

### **Priority**

An integer between 1 and 5, inclusive, that represents the priority of the in-app message campaign, where 1 is the highest priority and 5 is the lowest. If there are multiple messages scheduled to be displayed at the same time, the priority determines the order in which those messages are displayed.

**Type**: integer **Required**: False

#### WriteTreatmentResource

Specifies the settings for a campaign treatment. A *treatment* is a variation of a campaign that's used for A/B testing of a campaign.

#### **TreatmentName**

A custom name for the treatment.

**Type**: string **Required**: False

### **TreatmentDescription**

A custom description of the treatment.

**Type**: string **Required**: False

### MessageConfiguration

The message configuration settings for the treatment.

**Type**: MessageConfiguration

Required: False

#### Schedule

The schedule settings for the treatment.

Type: <u>Schedule</u> Required: False

### **TemplateConfiguration**

The message template to use for the treatment.

**Type**: TemplateConfiguration

Required: False

### CustomDeliveryConfiguration

The delivery configuration settings for sending the treatment through a custom channel. This object is required if the MessageConfiguration object for the treatment specifies a CustomMessage object.

Type: CustomDeliveryConfiguration

Required: False

#### **SizePercent**

The allocated percentage of users (segment members) to send the treatment to.

**Type**: integer **Required**: True

# See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

# **GetCampaigns**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2

See also 407

- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- · AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# CreateCampaign

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Channels**

A *channel* is a type of platform that you can deliver messages to. For example, use the email channel to send email to newsletter subscribers, use the SMS channel to send SMS text messages to your customers, or use a push notification channel to send push notifications to users of your iOS or Android app.

You can use the Channels resource to retrieve information about the history and status of each channel for a specific application. To retrieve more detailed information about a specific type of channel or to perform other channel-specific operations, use the resource for that type of channel.

#### URI

/v1/apps/application-id/channels

Channels 408

# **HTTP** methods

# **GET**

## Operation ID: GetChannels

Retrieves information about the history and status of each channel for an application.

# **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	<u>ChannelsResponse</u>	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).

Status code	Response model	Description
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Channels resource.

### **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

### Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Response bodies**

# ChannelsResponse schema

```
{
    "Channels": {
    }
}
```

# MessageBody schema

```
{
    "RequestID": "string",
```

Schemas 411

```
""Message": "string"
}
```

# **Properties**

# ChannelResponse

Provides information about the general settings and status of a channel for an application.

### **ApplicationId**

The unique identifier for the application.

**Type**: string **Required**: False

#### **IsArchived**

Specifies whether the channel is archived.

**Type**: boolean **Required**: False

#### Version

The current version of the channel.

**Type**: integer **Required**: False

#### CreationDate

The date and time, in ISO 8601 format, when the channel was enabled.

**Type**: string **Required**: False

#### LastModifiedDate

The date and time, in ISO 8601 format, when the channel was last modified.

**Type**: string

Required: False

### LastModifiedBy

The user who last modified the channel.

Type: string

Required: False

### Id

(Deprecated) An identifier for the channel. This property is retained only for backward compatibility.

Type: string

Required: False

#### **Enabled**

Specifies whether the channel is enabled for the application.

Type: boolean

Required: False

#### HasCredential

(Not used) This property is retained only for backward compatibility.

Type: boolean

Required: False

# ChannelsResponse

Provides information about the general settings and status of all channels for an application, including channels that aren't enabled for the application.

#### Channels

A map that contains a multipart response for each channel. For each item in this object, the ChannelType is the key and the Channel is the value.

**Type**: object **Required**: True

### MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

**Type**: string

Required: False

### Message

The message that's returned from the API.

**Type**: string **Required**: False

# See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

### **GetChannels**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2

See also 414

- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Email Channel**

A *channel* is a type of platform that you can deliver messages to. You can use the email channel to send email to users. Before you can use Amazon Pinpoint to send email, you must enable the email channel for an Amazon Pinpoint application.

The Email Channel resource represents the status, identity, and other settings of the email channel for a specific application. You can use this resource to enable, retrieve information about, update, or disable (delete) the email channel for an application.

### **URI**

/v1/apps/application-id/channels/email

# **HTTP** methods

#### **GET**

Operation ID: GetEmailChannel

Retrieves information about the status and settings of the email channel for an application.

# Path parameters

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the

Email Channel 415

Name	Type	Required	Description
			Project ID on the
			Amazon Pinpoint
			console.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	EmailChannelResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	MessageBody	The request failed because the specified resource was not found (NotFoundException).
405	MessageBody	The request failed because the method is not allowed for the specified resource

Status code	Response model	Description
		(MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **PUT**

# Operation ID: UpdateEmailChannel

Enables the email channel for an application or updates the status and settings of the email channel for an application.

## **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the

Name	Туре	Required	Description
			Amazon Pinpoint
			console.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	EmailChannelResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource

Status code	Response model	Description
		(MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **DELETE**

Operation ID: DeleteEmailChannel

Disables the email channel for an application and deletes any existing settings for the channel.

## **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	<u>EmailChannelResponse</u>	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	MessageBody	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	MessageBody	The request failed because the specified resource was not found (NotFoundException).
405	MessageBody	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	MessageBody	The request failed because the payload for the body of the request is too large

Status code	Response model	Description
		(RequestEntityTooLargeExcep tion).
429	MessageBody	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Email Channel resource.

## **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## Responses

Status code	Response model	Description
200	None	The request succeeded.

### **Schemas**

## **Request bodies**

#### **PUT schema**

```
{
   "Enabled": boolean,
   "Identity": "string",
   "FromAddress": "string",
   "RoleArn": "string",
   "OrchestrationSendingRoleArn": "string",
   "ConfigurationSet": "string"
}
```

## **Response bodies**

### EmailChannelResponse schema

```
{
  "ApplicationId": "string",
  "IsArchived": boolean,
  "Version": integer,
  "CreationDate": "string",
  "LastModifiedDate": "string",
  "LastModifiedBy": "string",
  "Id": "string",
  "Enabled": boolean,
  "Identity": "string",
  "FromAddress": "string",
  "RoleArn": "string",
  "OrchestrationSendingRoleArn": "string",
  "ConfigurationSet": "string",
  "Platform": "string",
  "MessagesPerSecond": integer,
  "HasCredential": boolean
}
```

## MessageBody schema

```
{
```

Schemas 422

```
"RequestID": "string",
"Message": "string"
}
```

# **Properties**

## **EmailChannelRequest**

Specifies the status and settings of the email channel for an application.

#### **Enabled**

Specifies whether to enable the email channel for the application.

**Type**: boolean **Required**: False

### Identity

The Amazon Resource Name (ARN) of the identity, verified with Amazon Simple Email Service (Amazon SES), that you want to use when you send email through the channel.

**Type**: string **Required**: True

#### **FromAddress**

The verified email address that you want to send email from when you send email through the channel.

**Type**: string **Required**: True

#### RoleArn

(Depricated) The ARN of the AWS Identity and Access Management (IAM) role that you want Amazon Pinpoint to use when it submits email-related event data for the channel.

Type: string

Required: False

### ${\bf Or chest ration Sending Role Arn}$

The ARN of an IAM role for Amazon Pinpoint to use to send email from your campaigns or journeys through Amazon SES.

**Type**: string **Required**: False

### ConfigurationSet

The <u>Amazon SES configuration set</u> that you want to apply to messages that you send through the channel.

**Type**: string **Required**: False

## **EmailChannelResponse**

Provides information about the status and settings of the email channel for an application.

### **ApplicationId**

The unique identifier for the application that the email channel applies to.

**Type**: string **Required**: False

#### **IsArchived**

Specifies whether the email channel is archived.

**Type**: boolean **Required**: False

#### Version

The current version of the email channel.

Type: integer Required: False

### CreationDate

The date and time, in ISO 8601 format, when the email channel was enabled.

Type: string

Required: False

#### LastModifiedDate

The date and time, in ISO 8601 format, when the email channel was last modified.

Type: string

Required: False

### LastModifiedBy

The user who last modified the email channel.

Type: string

Required: False

#### Id

(Deprecated) An identifier for the email channel. This property is retained only for backward compatibility.

Type: string

Required: False

### **Enabled**

Specifies whether the email channel is enabled for the application.

Type: boolean Required: False

### Identity

The Amazon Resource Name (ARN) of the identity, verified with Amazon Simple Email Service (Amazon SES), that's used when you send email through the channel.

**Type**: string

Required: False

#### **FromAddress**

The verified email address that email is sent from when you send email through the channel.

Type: string

Required: False

#### RoleArn

The ARN of the AWS Identity and Access Management (IAM) role that Amazon Pinpoint uses to submit email-related event data for the channel.

Type: string

Required: False

### OrchestrationSendingRoleArn

The ARN of an IAM role for Amazon Pinpoint to use to send email from your campaigns or journeys through Amazon SES.

Type: string

Required: False

## ConfigurationSet

The Amazon SES configuration set that's applied to messages that are sent through the channel.

Type: string

Required: False

#### **Platform**

The type of messaging or notification platform for the channel. For the email channel, this value is EMAIL.

**Type**: string **Required**: True

### MessagesPerSecond

The maximum number of emails that can be sent through the channel each second.

**Type**: integer **Required**: False

#### HasCredential

(Not used) This property is retained only for backward compatibility.

**Type**: boolean **Required**: False

## MessageBody

Provides information about an API request or response.

## RequestID

The unique identifier for the request or response.

Type: string

**Required**: False

### Message

The message that's returned from the API.

Type: string

### Required: False

### See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

### **GetEmailChannel**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **UpdateEmailChannel**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

See also 428

### **DeleteEmailChannel**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Email Template**

An *email template* is a type of message template that contains content and settings that you can define, save, and reuse in messages that you send through the email channel for any of your Amazon Pinpoint applications. You can use email templates in any type of email message that you create and send by using Amazon Pinpoint.

When you create an email template, you specify the content and settings that you want to reuse in various components of messages that are based on the template. These components, referred to as *template parts*, can be the message title or subject, the message body, or both. This content can be static text or personalized content that you define by using the Handlebars template system and message variables. When you send a message that's based on a template, Amazon Pinpoint populates the message with the content and settings that you defined in the template.

The Email Template resource represents the repository of email templates that are associated with your Amazon Pinpoint account. You can use this resource to create, retrieve, update, or delete a message template for messages that you send through the email channel.

Amazon Pinpoint supports versioning for all types of message templates. When you use the Email Template resource to work with a template, you can use supported parameters to specify whether your request applies to only a specific version of the template or to the overall template. For example, if you update a template, you can specify whether you want to save your updates as a

Email Template 429

new version of the template or save them to the latest existing version of the template. To retrieve information about all the versions of a template, use the Template Versions resource.

# **URI**

/v1/templates/template-name/email

## **HTTP** methods

### **GET**

Operation ID: GetEmailTemplate

Retrieves the content and settings of a message template for messages that are sent through the email channel.

## **Path parameters**

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can contain a maximum of 128 characters. The characters can be alphanumeric characters, underscor es (_), or hyphens (-). Template names are case sensitive.

URI 430

## **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# **Query parameters**

Name	Туре	Required	Description
version	String	False	The unique identifie r for the version of the message template to update, retrieve information about, or delete. To retrieve identifiers and other informati on for all the versions of a template, use the Template Versions resource.
			If specified, this value must match the identifier for an existing template version. If specified for an update operation, this value must match the identifier for the latest existing version of the template.

Name Type Required Description

This restriction helps ensure that race conditions don't occur.

If you don't specify a value for this parameter, Amazon Pinpoint does the following:

- For a get operation , retrieves informati on about the active version of the template.
- For an update operation, saves the updates to (overwrites) the latest existing version of the template, if the create-ne w-version parameter isn't used or is set to false.
- For a delete operation, deletes the template, including all versions of the template.

## Responses

Status code	Response model	Description
200	EmailTemplateRespo nse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).

Status code	Response model	Description
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **POST**

# Operation ID: CreateEmailTemplate

Creates a message template for messages that are sent through the email channel.

# Path parameters

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can contain a maximum of 128 characters. The characters can be alphanumeric characters, underscores (_), or hyphens (-). Template names are case sensitive.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types,

Name	Туре	Required	Description
			expressed as MIME
			types, the client
			understands.

# Responses

Status code	Response model	Description
201	<pre>CreateTemplateMess ageBody</pre>	The request succeeded and the specified resource was created.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
409	<u>MessageBody</u>	The request failed due to a conflict with the current state of the specified resource (ConflictException).
429	MessageBody	The request failed because too many requests were sent during a certain amount of

Status code	Response model	Description
		time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **PUT**

# Operation ID: UpdateEmailTemplate

Updates an existing message template for messages that are sent through the email channel.

# **Path parameters**

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can contain a maximum of 128 characters. The characters can be alphanumeric characters, underscor es (_), or hyphens (-). Template names are case sensitive.

## **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client
			understands.

## **Query parameters**

Name	Туре	Required	Description
create-new- version	String	False	Specifies whether to save the updates as a new version of the message template.  Valid values are: true, save the updates as a new version; and, false, save the updates to (overwrite) the latest existing version of the template.
			If you don't specify a value for this parameter, Amazon Pinpoint saves the updates to (overwrites) the latest existing version of the template. If you specify a value of true for this parameter, don't

Name Type Required Description

specify a value
for the version
parameter. Otherwise
, an error will occur.

Name	Туре	Required	Description
version	String	False	The unique identifier for the version of the message template to update, retrieve information about, or delete. To retrieve identifiers and other information for all the versions of a template, use the Template Versions resource.  If specified, this value must match the identifier for an existing template version. If specified for an update operation, this value must match the identifier for the latest existing version of the template. This restriction helps ensure that race conditions don't
			occur.
			If you don't specify a value for this parameter, Amazon Pinpoint does the following:

Name	Туре	Required	Description
			<ul> <li>For a get operation         <ul> <li>retrieves informati</li> <li>on about the active</li> <li>version of the</li> <li>template.</li> </ul> </li> </ul>
			• For an update operation, saves the updates to (overwrites) the latest existing version of the template, if the create-ne w-version parameter isn't used or is set to false.
			<ul> <li>For a delete         operation, deletes         the template,         including all         versions of the         template.</li> </ul>

## Responses

Status code	Response model	Description
202	<u>MessageBody</u>	The request was accepted for processing. Processing may not be complete.
400	MessageBody	The request contains a syntax error (BadRequestException).

Status code	Response model	Description
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **DELETE**

Operation ID: DeleteEmailTemplate

Deletes a message template for messages that were sent through the email channel.

## **Path parameters**

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can contain a maximum of 128 characters. The characters can be alphanumeric characters, underscor es (_), or hyphens (-). Template names are case sensitive.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

## **Query parameters**

Name	Туре	Required	Description
version	String	False	The unique identifie r for the version of the message

Name Type Required Description

template to update, retrieve information about, or delete. To retrieve identifiers and other informati on for all the versions of a template, use the <u>Template</u>
Versionsresource.

If specified, this value must match the identifier for an existing template version. If specified for an update operation, this value must match the identifier for the latest existing version of the template. This restriction helps ensure that race conditions don't occur.

If you don't specify a value for this parameter, Amazon Pinpoint does the following:

 For a get operation , retrieves informati on about the active

Name	Туре	Required	Description
			version of the template.
			• For an update operation, saves the updates to (overwrites) the latest existing version of the template, if the create-ne w-version parameter isn't used or is set to false.
			<ul> <li>For a delete operation, deletes the template, including all versions of the template.</li> </ul>

## Responses

Status code	Response model	Description
202	MessageBody	The request was accepted for processing. Processing may not be complete.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	MessageBody	The request was denied because access to the specified resource is

Status code	Response model	Description
		forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Email Template resource.

### **Path parameters**

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can contain a maximum of 128 characters. The characters can be alphanumeric characters, underscor es (_), or hyphens (-). Template names are case sensitive.

## Responses

Status code	Response model	Description
200	None	The request succeeded.

## **Schemas**

# **Request bodies**

### **POST schema**

```
{
   "TemplateDescription": "string",
   "DefaultSubstitutions": "string",
   "tags": {
   },
   "Subject": "string",
   "TextPart": "string",
```

Schemas 446

#### **PUT schema**

```
{
  "TemplateDescription": "string",
  "DefaultSubstitutions": "string",
  "tags": {
  },
  "Subject": "string",
  "TextPart": "string",
  "HtmlPart": "string",
  "RecommenderId": "string",
  "Headers": [
    {
      "Name": "string",
      "Value": "string"
    }
  ]
}
```

## **Response bodies**

### EmailTemplateResponse schema

```
"CreationDate": "string",
"LastModifiedDate": "string",
"TemplateType": enum,
"TemplateName": "string",
"TemplateDescription": "string",
"DefaultSubstitutions": "string",
"Version": "string",
"tags": {
```

Schemas 447

```
},
"Arn": "string",
"Subject": "string",
"TextPart": "string",
"HtmlPart": "string",
"RecommenderId": "string"
}
```

### CreateTemplateMessageBody schema

```
{
   "RequestID": "string",
   "Message": "string",
   "Arn": "string"
}
```

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

## CreateTemplateMessageBody

Provides information about a request to create a message template.

### RequestID

The unique identifier for the request to create the message template.

**Type**: string **Required**: False

### Message

The message that's returned from the API for the request to create the message template.

**Type**: string Required: False

#### Arn

The Amazon Resource Name (ARN) of the message template that was created.

**Type**: string **Required**: False

## **EmailTemplateRequest**

Specifies the content and settings for a message template that can be used in messages that are sent through the email channel.

### **TemplateDescription**

A custom description of the message template.

**Type**: string Required: False

#### **DefaultSubstitutions**

A JSON object that specifies the default values to use for message variables in the message template. This object is a set of key-value pairs. Each key defines a message variable in the template. The corresponding value defines the default value for that variable. When you create a message that's based on the template, you can override these defaults with message-specific and address-specific variables and values.

**Type**: string Required: False

#### tags



### Note

As of 22-05-2023 the tags attribute has been deprecated. After this date any value in the PUT UpdateEmailTemplate tags attribute are not processed and an error code is not

returned. The POST CreateEmailTemplate tags attribute is processed. Use the <u>Tags</u> resource to add or modify tags.

(Deprecated) A string-to-string map of key-value pairs that defines the tags to associate with the message template. Each tag consists of a required tag key and an associated tag value.

**Type**: object **Required**: False

### Subject

The subject line, or title, to use in email messages that are based on the message template.

Type: string

**Required**: False

#### **TextPart**

The message body, in plain text format, to use in email messages that are based on the message template. We recommend using plain text format for email clients that don't render HTML content and clients that are connected to high-latency networks, such as mobile devices.

Type: string

Required: False

#### **HtmlPart**

The message body, in HTML format, to use in email messages that are based on the message template. We recommend using HTML format for email clients that render HTML content. You can include links, formatted text, and more in an HTML message.

Type: string

Required: False

#### RecommenderId

The unique identifier for the recommender model to use for the message template. Amazon Pinpoint uses this value to determine how to retrieve and process data from a recommender model when it sends messages that use the template, if the template contains message variables for recommendation data.

**Type**: string **Required**: False

#### **Headers**

The list of MessageHeaders for the email. You can have up to 15 Headers.

**Type**: Array of type MessageHeader

Required: False

## **EmailTemplateResponse**

Provides information about the content and settings for a message template that can be used in messages that are sent through the email channel.

#### CreationDate

The date, in ISO 8601 format, when the message template was created.

**Type**: string **Required**: True

#### LastModifiedDate

The date, in ISO 8601 format, when the message template was last modified.

**Type**: string **Required**: True

### **TemplateType**

The type of channel that the message template is designed for. For an email template, this value is EMAIL.

**Type**: string

**Required**: True

Values: EMAIL | SMS | VOICE | PUSH | INAPP

### **TemplateName**

The name of the message template.

**Type**: string **Required**: True

### **TemplateDescription**

The custom description of the message template.

Type: string

Required: False

#### **DefaultSubstitutions**

The JSON object that specifies the default values that are used for message variables in the message template. This object is a set of key-value pairs. Each key defines a message variable in the template. The corresponding value defines the default value for that variable.

Type: string

Required: False

#### Version

The unique identifier, as an integer, for the active version of the message template, or the version of the template that you specified by using the version parameter in your request.

Type: string

Required: False

#### tags

A string-to-string map of key-value pairs that identifies the tags that are associated with the message template. Each tag consists of a required tag key and an associated tag value.

**Type**: object

Required: False

#### Arn

The Amazon Resource Name (ARN) of the message template.

Type: string

Required: False

### Subject

The subject line, or title, that's used in email messages that are based on the message template.

Type: string

Required: False

#### **TextPart**

The message body, in plain text format, that's used in email messages that are based on the message template.

**Type**: string

Required: False

### **HtmlPart**

The message body, in HTML format, that's used in email messages that are based on the message template.

Type: string

Required: False

#### RecommenderId

The unique identifier for the recommender model that's used by the message template.

Type: string

Required: False

## MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

Type: string

Required: False

### Message

The message that's returned from the API.

Type: string

Required: False

## MessageHeader

Contains the name and value pair of an message header to add to your email. You can have up to 15 MessageHeaders. A header can contain information such as the sender, receiver, route, or timestamp.

#### Name

The name of the message header. The header name can contain up to 126 characters.

Type: string

Required: False

#### Value

The value of the message header. The header value can contain up to 870 characters, including the length of any rendered attributes. For example if you add the {CreationDate} attribute, it renders as YYYY-MM-DDTHH: MM:SS.SSSZ and is 24 characters in length.

**Type**: string **Required**: False

### See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## **GetEmailTemplate**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# CreateEmailTemplate

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2

See also 455

- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

## **UpdateEmailTemplate**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

## DeleteEmailTemplate

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

See also 456

# **Endpoint**

An *endpoint* represents a destination that you can send messages to, such as a mobile device, email address, or phone number.

You can use the Endpoint resource to create, retrieve information about, update, or delete a specific endpoint from an application. This includes updating the settings and attributes of an endpoint. To perform these tasks for multiple endpoints in a single operation, use the <a href="Endpoints">Endpoints</a> resource.

**Note:** Quotas apply to the number of custom attributes that you can define for endpoints. If you send a PUT request that defines additional custom attributes for an endpoint and the addition of these attributes exceeds these quotas, Amazon Pinpoint returns an HTTP 400 response. For information about the quotas that apply to attributes, see <a href="Manazon Pinpoint Quotas"><u>Amazon Pinpoint Quotas</u></a> in the *Amazon Pinpoint Developer Guide*. To remove custom attributes from endpoints, use the Attributes resource.

## **URI**

/v1/apps/application-id/endpoints/endpoint-id

## **HTTP** methods

#### **GET**

Operation ID: GetEndpoint

Retrieves information about the settings and attributes of a specific endpoint for an application.

## Path parameters

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

Endpoint 457

Name	Туре	Required	Description
endpoint-id	String	True	The case insensiti ve unique identifie r for the endpoint. The identifier can't contain \$, { or }.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	<u>EndpointResponse</u>	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).

Status code	Response model	Description
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **PUT**

## Operation ID: UpdateEndpoint

Creates a new endpoint for an application or updates the settings and attributes of an existing endpoint for an application. You can also use this operation to define custom attributes for an endpoint. If an update includes one or more values for a custom attribute, Amazon Pinpoint replaces (overwrites) any existing values with the new values.

## **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.
endpoint-id	String	True	The case insensiti ve unique identifie r for the endpoint. The identifier can't contain \$, { or }.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
202	MessageBody	The request was accepted for processing. Processing may not be complete.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).

Status code	Response model	Description
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **DELETE**

**Operation ID:** DeleteEndpoint

Deletes an endpoint from an application.

# **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.
endpoint-id	String	True	The case insensiti ve unique identifie r for the endpoint. The identifier can't contain \$, { or }.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
202	<u>EndpointResponse</u>	The Endpoint was not found and may have already been deleted.

Status code	Response model	Description
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Endpoint resource.

## **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.
endpoint-id	String	True	The case insensitive unique identifier for the endpoint.

## Responses

Status code	Response model	Description
200	None	The request succeeded.

## **Schemas**

# **Request bodies**

### **PUT schema**

```
{
  "ChannelType": enum,
  "Address": "string",
  "EndpointStatus": "string",
  "OptOut": "string",
  "RequestId": "string",
```

```
"Location": {
    "Latitude": number,
    "Longitude": number,
    "PostalCode": "string",
    "City": "string",
    "Region": "string",
    "Country": "string"
  },
  "Demographic": {
    "Make": "string",
    "Model": "string",
    "ModelVersion": "string",
    "Timezone": "string",
    "Locale": "string",
    "AppVersion": "string",
    "Platform": "string",
    "PlatformVersion": "string"
  },
  "EffectiveDate": "string",
  "Attributes": {
  },
  "Metrics": {
  },
  "User": {
    "UserId": "string",
    "UserAttributes": {
    }
  }
}
```

## **Response bodies**

## **EndpointResponse schema**

```
"ChannelType": enum,
"Address": "string",
"EndpointStatus": "string",
"OptOut": "string",
"RequestId": "string",
"Location": {
    "Latitude": number,
    "Longitude": number,
```

```
"PostalCode": "string",
    "City": "string",
    "Region": "string",
    "Country": "string"
  },
  "Demographic": {
    "Make": "string",
    "Model": "string",
    "ModelVersion": "string",
    "Timezone": "string",
    "Locale": "string",
    "AppVersion": "string",
    "Platform": "string",
    "PlatformVersion": "string"
  },
  "EffectiveDate": "string",
  "Attributes": {
  },
  "Metrics": {
  },
  "User": {
   "UserId": "string",
    "UserAttributes": {
    }
  },
  "ApplicationId": "string",
  "Id": "string",
  "CohortId": "string",
  "CreationDate": "string"
}
```

## MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

# **EndpointDemographic**

Specifies demographic information about an endpoint, such as the applicable time zone and platform.

#### Make

The manufacturer of the endpoint device, such as Apple or Samsung. Can contain a maximum of 50 characters.

Type: string

Required: False

### Model

The model name or number of the endpoint device, such as iPhone or SM-G900F. Can contain a maximum of 100 characters.

Type: string

Required: False

#### **ModelVersion**

The model version of the endpoint device. Can contain a maximum of 50 characters.

Type: string

Required: False

### **Timezone**

The time zone of the endpoint, specified as a tz database name value, such as America/Los\_Angeles.

Type: string

Required: False

#### Locale

An identifier that represents the endpoint's language, in IETF BCP 47 format. This identifier typically consists of an ISO 639-1 alpha-2 code, followed by an underscore (\_), followed by an ISO 3166-1 alpha-2 value. For example, the locale code for United States English is en\_US.

In some cases, an ISO 3166-1 numeric-3 value is used instead of an ISO 3166-1 alpha-2 value. For example, the locale code for Latin American Spanish is es\_419.

In other cases, the ISO 639-1 alpha-2 is replaced with a three-letter code. For example, the locale code for Hawaiian is haw\_US.

**Type**: string **Required**: False

### **AppVersion**

The version of the app that's associated with the endpoint. Can contain a maximum of 50 characters.

**Type**: string **Required**: False

#### **Platform**

The platform of the endpoint device, such as iOS. Can contain a maximum of 50 characters.

**Type**: string **Required**: False

#### **PlatformVersion**

The version of the platform for the endpoint device. Can contain a maximum of 50 characters.

**Type**: string **Required**: False

# **EndpointLocation**

Specifies geographic information about an endpoint.

#### Latitude

The latitude coordinate of the endpoint location, rounded to one decimal place. Must be between -90 and 90. If you specify a latitude, you must also specify a longitude.

**Type**: number **Required**: False

## Longitude

The longitude coordinate of the endpoint location, rounded to one decimal place. Must be between -180 and 180. If you specify a longitude, you must also specify a latitude.

**Type**: number **Required**: False

#### **PostalCode**

The postal or ZIP code for the area where the endpoint is located.

**Type**: string

Required: False

### City

The name of the city where the endpoint is located. Can contain a maximum of 75 characters.

Type: string

Required: False

## Region

The name of the region where the endpoint is located. This value is typically a first-level subdivision a country, such as a state, province, prefecture, administrative region, district, or department. Can contain a maximum of 75 characters.

**Type**: string **Required**: False

### Country

A code that represents the country or region where the endpoint is located. Must be in ISO 3166-1 Alpha-2 or Alpha-3 format. For example, for the United States, you can use US or USA.

**Type**: string Required: False

## **EndpointRequest**

Specifies the channel type and other settings for an endpoint.

## ChannelType

The channel to use when sending messages or push notifications to the endpoint.



#### Note

Do not use PUSH but instead use provider-specific channels, otherwise your endpoints are not targeted.

Type: string Required: False

Values: PUSH | GCM | APNS | APNS\_SANDBOX | APNS\_VOIP | APNS\_VOIP\_SANDBOX |

ADM | SMS | VOICE | EMAIL | BAIDU | CUSTOM | IN\_APP

#### **Address**

The destination address for messages or push notifications that you send to the endpoint. The address varies by channel. For a push notification channel, use the token provided by the push notification service, such as an Apple Push Notification service (APNs) device token or a Firebase Cloud Messaging (FCM) registration token. For the SMS channel, use a phone number in E.164 format, such as +12065550100. For the email channel, use an email address.

If the endpoint is created without an address then *OptOut* is automatically set to ALL. When an address is added OptOut has to be set to NONE for the endpoint to receive messages.

**Type**: string **Required**: False

### **EndpointStatus**

Specifies whether to send messages or push notifications to the endpoint. Valid values are: ACTIVE, messages are sent to the endpoint; and, INACTIVE, messages aren't sent to the endpoint.

Amazon Pinpoint automatically sets this value to ACTIVE when you create an endpoint or update an existing endpoint. Amazon Pinpoint automatically sets this value to INACTIVE if you update another endpoint that has the same address specified by the Address property.

See exception note below.



## Note

If the value of EndpointStatus for an endpoint is INACTIVE, and you send a message to that endpoint through a campaign or journey, Amazon Pinpoint doesn't attempt to send the message. If you send a message using the SendMessages and SendUserMessages API, the value of EndpointStatus is ignored.

**Type**: string Required: False

## **OptOut**

Specifies whether the user who's associated with the endpoint has opted out of receiving messages and push notifications from you. Possible values are: ALL, the user has opted out and doesn't want to receive any messages or push notifications; and, NONE, the user hasn't opted out and wants to receive all messages and push notifications.

See exception note below.



### Note

If the value of OptOut for an endpoint is ALL, and you send a message to that endpoint through a campaign or journey, Amazon Pinpoint doesn't attempt to send the message. If you send a message using the SendMessages API, the value of OptOut is ignored.

Type: string

Required: False

### RequestId

The unique identifier for the most recent request to update the endpoint.

**Type**: string **Required**: False

#### Location

The geographic information for the endpoint.

**Type:** EndpointLocation

Required: False

### Demographic

The demographic information for the endpoint, such as the time zone and platform.

**Type**: EndpointDemographic

Required: False

#### **EffectiveDate**

The date and time, in ISO 8601 format, when the endpoint is updated.

**Type**: string **Required**: False

#### **Attributes**

One or more custom attributes that describe the endpoint by associating a name with an array of values. For example, the value of a custom attribute named Interests might be: ["Science", "Music", "Travel"]. You can use these attributes as filter criteria when you create segments. Attribute names are case sensitive.

An attribute name can contain up to 50 characters. An attribute value can contain up to 100 characters. When you define the name of a custom attribute, avoid using the following characters:

number sign (#), colon (:), question mark (?), backslash (\), and slash (/). The Amazon Pinpoint console can't display attribute names that contain these characters. This restriction doesn't apply to attribute values.

**Type**: object **Required**: False

#### **Metrics**

One or more custom metrics that your app reports to Amazon Pinpoint for the endpoint.

**Type**: object **Required**: False

#### User

One or more custom attributes that describe the user who's associated with the endpoint.

Type: EndpointUser
Required: False

## **EndpointResponse**

Provides information about the channel type and other settings for an endpoint.

## ChannelType

The channel that's used when sending messages or push notifications to the endpoint.

**Type**: string **Required**: False

Values: PUSH | GCM | APNS | APNS\_SANDBOX | APNS\_VOIP | APNS\_VOIP\_SANDBOX |

ADM | SMS | VOICE | EMAIL | BAIDU | CUSTOM | IN\_APP

#### **Address**

The destination address for messages or push notifications that you send to the endpoint. The address varies by channel. For example, the address for a push notification channel is typically the token provided by a push notification service, such as an Apple Push Notification service (APNs)

device token or a Firebase Cloud Messaging (FCM) registration token. The address for the SMS channel is a phone number in E.164 format, such as +12065550100. The address for the email channel is an email address.

**Type**: string **Required**: False

## **EndpointStatus**

Specifies whether messages or push notifications are sent to the endpoint. Possible values are: ACTIVE, messages are sent to the endpoint; and, INACTIVE, messages aren't sent to the endpoint.

Amazon Pinpoint automatically sets this value to ACTIVE when you create an endpoint or update an existing endpoint. Amazon Pinpoint automatically sets this value to INACTIVE if you update another endpoint that has the same address specified by the Address property.

**Type**: string **Required**: False

## **OptOut**

Specifies whether the user who's associated with the endpoint has opted out of receiving messages and push notifications from you. Possible values are: ALL, the user has opted out and doesn't want to receive any messages or push notifications; and, NONE, the user hasn't opted out and wants to receive all messages and push notifications.

**Type**: string **Required**: False

## RequestId

The unique identifier for the most recent request to update the endpoint.

**Type**: string **Required**: False

#### Location

The geographic information for the endpoint.

Type: EndpointLocation

Required: False

## **Demographic**

The demographic information for the endpoint, such as the time zone and platform.

Type: EndpointDemographic

**Required**: False

#### **EffectiveDate**

The date and time, in ISO 8601 format, when the endpoint was last updated.

**Type**: string **Required**: False

#### **Attributes**

One or more custom attributes that describe the endpoint by associating a name with an array of values. For example, the value of a custom attribute named Interests might be: ["Science", "Music", "Travel"]. You can use these attributes as filter criteria when you create segments.

**Type**: object **Required**: False

#### **Metrics**

One or more custom metrics that your app reports to Amazon Pinpoint for the endpoint.

**Type**: object **Required**: False

#### User

One or more custom user attributes that your app reports to Amazon Pinpoint for the user who's associated with the endpoint.

Type: EndpointUser

Required: False

## **ApplicationId**

The unique identifier for the application that's associated with the endpoint.

**Type**: string **Required**: False

#### Id

The unique identifier that you assigned to the endpoint. The identifier should be a globally unique identifier (GUID) to ensure that it doesn't conflict with other endpoint identifiers that are associated with the application.

**Type**: string **Required**: False

#### CohortId

A number from 0–99 that represents the cohort that the endpoint is assigned to. Endpoints are grouped into cohorts randomly, and each cohort contains approximately 1 percent of the endpoints for an application. Amazon Pinpoint assigns cohorts to the holdout or treatment allocations for campaigns.

**Type**: string **Required**: False

#### CreationDate

The date and time, in ISO 8601 format, when the endpoint was created.

**Type**: string **Required**: False

## **EndpointUser**

Specifies data for one or more attributes that describe the user who's associated with an endpoint.

#### UserId

The unique identifier for the user. The identifier can't contain \$, { or }.

**Type**: string **Required**: False

#### **UserAttributes**

One or more custom attributes that describe the user by associating a name with an array of values. For example, the value of an attribute named Interests might be: ["Science", "Music", "Travel"]. You can use these attributes as filter criteria when you create segments. Attribute names are case sensitive.

An attribute name can contain up to 50 characters. An attribute value can contain up to 100 characters. When you define the name of a custom attribute, avoid using the following characters: number sign (#), colon (:), question mark (?), backslash (\), and slash (/). The Amazon Pinpoint console can't display attribute names that contain these characters. This restriction doesn't apply to attribute values.

**Type**: object **Required**: False

## MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

### Message

The message that's returned from the API.

Type: string

### Required: False

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## GetEndpoint

- AWS Command Line Interface
- · AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# UpdateEndpoint

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

See also 478

## DeleteEndpoint

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Endpoints**

An *endpoint* represents a destination that you can send messages to, such as a mobile device, email address, or phone number.

You can use the Endpoints resource to create, retrieve information about, or update a batch of endpoints for a specific application. This includes updating the settings and attributes of a batch of endpoints for an application. A batch can include up to 100 endpoints. To perform these tasks for a single endpoint, use the Endpoint resource.

**Note:** Quotas apply to the number of custom attributes that you can define for endpoints. If you send a PUT request that defines additional custom attributes for a batch of endpoints and the addition of these attributes exceeds these quotas, Amazon Pinpoint returns an HTTP 400 response. For information about the quotas that apply to attributes, see <a href="Amazon Pinpoint Quotas">Amazon Pinpoint Quotas</a> in the <a href="Amazon Pinpoint Developer Guide">Amazon Pinpoint Developer Guide</a>. To remove custom attributes from endpoints, use the <a href="Attributes">Attributes</a> resource.

## URI

/v1/apps/application-id/endpoints

Endpoints 479

# **HTTP** methods

### **PUT**

## Operation ID: UpdateEndpointsBatch

Creates a new batch of endpoints for an application or updates the settings and attributes of a batch of existing endpoints for an application. You can also use this operation to define custom attributes for a batch of endpoints. If an update includes one or more values for a custom attribute, Amazon Pinpoint replaces (overwrites) any existing values with the new values.

## **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

## Responses

Status code	Response model	Description
202	<u>MessageBody</u>	The request was accepted for processing. Processing may not be complete.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).

Status code	Response model	Description
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Endpoints resource.

## **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Request bodies**

### **PUT schema**

ſ

```
"Item": [
    {
      "ChannelType": enum,
      "Address": "string",
      "EndpointStatus": "string",
      "OptOut": "string",
      "RequestId": "string",
      "Location": {
        "Latitu<u>de</u>": number,
        "Longitude": number,
        "PostalCode": "string",
        "City": "string",
        "Region": "string",
        "Country": "string"
      },
      "Demographic": {
        "Make": "string",
        "Model": "string",
        "ModelVersion": "string",
        "Timezone": "string",
        "Locale": "string",
        "AppVersion": "string",
        "Platform": "string",
        "PlatformVersion": "string"
      },
      "EffectiveDate": "string",
      "Attributes": {
      },
      "Metrics": {
      },
      "User": {
        "UserId": "string",
        "UserAttributes": {
        }
      "Id": "string"
    }
  ]
}
```

# **Response bodies**

## MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

## EndpointBatchItem

Specifies an endpoint to create or update and the settings and attributes to set or change for the endpoint.

## ChannelType

The channel to use when sending messages or push notifications to the endpoint.

```
Type: string
Required: False
Values: PUSH | GCM | APNS | APNS_SANDBOX | APNS_VOIP | APNS_VOIP_SANDBOX |
ADM | SMS | VOICE | EMAIL | BAIDU | CUSTOM | IN_APP
```

#### **Address**

The destination address for messages or push notifications that you send to the endpoint. The address varies by channel. For a push notification channel, use the token provided by the push notification service, such as an Apple Push Notification service (APNs) device token or a Firebase Cloud Messaging (FCM) registration token. For the SMS channel, use a phone number in E.164 format, such as +12065550100. For the email channel, use an email address.

If the endpoint is created without an address then *OptOut* is automatically set to ALL. When an address is added *OptOut* has to be set to NONE for the endpoint to receive messages.

**Type**: string **Required**: False

### **EndpointStatus**

Specifies whether to send messages or push notifications to the endpoint. Valid values are: ACTIVE, messages are sent to the endpoint; and, INACTIVE, messages aren't sent to the endpoint.

Amazon Pinpoint automatically sets this value to ACTIVE when you create an endpoint or update an existing endpoint. Amazon Pinpoint automatically sets this value to INACTIVE if you update another endpoint that has the same address specified by the Address property.

If an endpoint is ACTIVE, Amazon Pinpoint will send messages through campaigns and journeys. If an ACTIVE endpoint enters a journey and becomes INACTIVE before completing the journey, Amazon Pinpoint will continue to send messages to the endpoint.



### Note

If the value of EndpointStatus for an endpoint is INACTIVE, and you send a message to that endpoint through a campaign or journey, Amazon Pinpoint doesn't attempt to send the message. If you send a message using the SendMessages and SendUserMessages API, the value of EndpointStatus is ignored.

**Type**: string Required: False

## **OptOut**

Specifies whether the user who's associated with the endpoint has opted out of receiving messages and push notifications from you. Possible values are: ALL, the user has opted out and doesn't want to receive any messages or push notifications; and, NONE, the user hasn't opted out and wants to receive all messages and push notifications.



#### Note

If the value of OptOut for an endpoint is ALL, and you send a message to that endpoint through a campaign or journey, Amazon Pinpoint doesn't attempt to send the message. If you send a message using the SendMessages API, the value of OptOut is ignored.

Type: string

Required: False

### RequestId

The unique identifier for the request to create or update the endpoint.

**Type**: string **Required**: False

#### Location

The geographic information for the endpoint.

**Type**: EndpointLocation

Required: False

## Demographic

The demographic information for the endpoint, such as the time zone and platform.

**Type**: EndpointDemographic

**Required**: False

#### **EffectiveDate**

The date and time, in ISO 8601 format, when the endpoint was created or updated.

**Type**: string **Required**: False

#### **Attributes**

One or more custom attributes that describe the endpoint by associating a name with an array of values. For example, the value of a custom attribute named Interests might be: ["Science", "Music", "Travel"]. You can use these attributes as filter criteria when you create segments. Attribute names are case sensitive.

An attribute name can contain up to 50 characters. An attribute value can contain up to 100 characters. When you define the name of a custom attribute, avoid using the following characters:

number sign (#), colon (:), question mark (?), backslash (\), and slash (/). The Amazon Pinpoint console can't display attribute names that contain these characters. This restriction doesn't apply to attribute values.

**Type**: object **Required**: False

#### **Metrics**

One or more custom metrics that your app reports to Amazon Pinpoint for the endpoint.

**Type**: object **Required**: False

User

One or more custom attributes that describe the user who's associated with the endpoint.

Type: EndpointUser
Required: False

Id

The case insensitive unique identifier for the endpoint in the context of the batch. The identifier can't contain \$, { or }.

**Type**: string **Required**: False

# Endpoint Batch Request

Specifies a batch of endpoints to create or update and the settings and attributes to set or change for each endpoint.

#### Item

An array that defines the endpoints to create or update and, for each endpoint, the property values to set or change. An array can contain a maximum of 100 items.

Type: Array of type EndpointBatchItem

Required: True

## **EndpointDemographic**

Specifies demographic information about an endpoint, such as the applicable time zone and platform.

#### Make

The manufacturer of the endpoint device, such as Apple or Samsung. Can contain a maximum of 50 characters.

Type: string

Required: False

#### Model

The model name or number of the endpoint device, such as iPhone or SM-G900F. Can contain a maximum of 100 characters.

Type: string

Required: False

#### **ModelVersion**

The model version of the endpoint device. Can contain a maximum of 50 characters.

Type: string

Required: False

#### **Timezone**

The time zone of the endpoint, specified as a tz database name value, such as America/Los\_Angeles.

**Type**: string **Required**: False

#### Locale

An identifier that represents the endpoint's language, in IETF BCP 47 format. This identifier typically consists of an ISO 639-1 alpha-2 code, followed by an underscore (\_), followed by an ISO 3166-1 alpha-2 value. For example, the locale code for United States English is en\_US.

In some cases, an ISO 3166-1 numeric-3 value is used instead of an ISO 3166-1 alpha-2 value. For example, the locale code for Latin American Spanish is es\_419.

In other cases, the ISO 639-1 alpha-2 is replaced with a three-letter code. For example, the locale code for Hawaiian is haw\_US.

**Type**: string **Required**: False

### **AppVersion**

The version of the app that's associated with the endpoint. Can contain a maximum of 50 characters.

**Type**: string **Required**: False

#### **Platform**

The platform of the endpoint device, such as iOS. Can contain a maximum of 50 characters.

**Type**: string **Required**: False

#### **PlatformVersion**

The version of the platform for the endpoint device. Can contain a maximum of 50 characters.

**Type**: string **Required**: False

# **EndpointLocation**

Specifies geographic information about an endpoint.

#### Latitude

The latitude coordinate of the endpoint location, rounded to one decimal place. Must be between -90 and 90. If you specify a latitude, you must also specify a longitude.

**Type**: number **Required**: False

### Longitude

The longitude coordinate of the endpoint location, rounded to one decimal place. Must be between -180 and 180. If you specify a longitude, you must also specify a latitude.

**Type**: number **Required**: False

#### **PostalCode**

The postal or ZIP code for the area where the endpoint is located.

**Type**: string

Required: False

### City

The name of the city where the endpoint is located. Can contain a maximum of 75 characters.

Type: string

Required: False

## Region

The name of the region where the endpoint is located. This value is typically a first-level subdivision a country, such as a state, province, prefecture, administrative region, district, or department. Can contain a maximum of 75 characters.

**Type**: string **Required**: False

### **Country**

A code that represents the country or region where the endpoint is located. Must be in ISO 3166-1 Alpha-2 or Alpha-3 format. For example, for the United States, you can use US or USA.

**Type**: string **Required**: False

### **EndpointUser**

Specifies data for one or more attributes that describe the user who's associated with an endpoint.

#### UserId

The unique identifier for the user. The identifier can't contain \$, { or }.

**Type**: string **Required**: False

#### **UserAttributes**

One or more custom attributes that describe the user by associating a name with an array of values. For example, the value of an attribute named Interests might be: ["Science", "Music", "Travel"]. You can use these attributes as filter criteria when you create segments. Attribute names are case sensitive.

An attribute name can contain up to 50 characters. An attribute value can contain up to 100 characters. When you define the name of a custom attribute, avoid using the following characters: number sign (#), colon (:), question mark (?), backslash (\), and slash (/). The Amazon Pinpoint console can't display attribute names that contain these characters. This restriction doesn't apply to attribute values.

**Type**: object **Required**: False

## MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

Type: string

Required: False

### Message

The message that's returned from the API.

Type: string

Required: False

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## UpdateEndpointsBatch

- AWS Command Line Interface
- · AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

See also 492

## **Event Stream**

The Kinesis platform offers services that you can use to load and analyze streaming data on AWS. You can configure Amazon Pinpoint to stream events to Firehose or Kinesis Data Streams. By streaming events, you enable more flexible options for analysis and storage.

You can use the Event Stream resource to create, retrieve information about, update, or delete an event stream for an application. You can configure only one event stream for each Amazon Pinpoint application. To combine data from multiple applications, configure each application to use the same stream.

### **URI**

/v1/apps/application-id/eventstream

# **HTTP** methods

### **GET**

**Operation ID:** GetEventStream

Retrieves information about the event stream settings for an application.

### Path parameters

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

Event Stream 493

## **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	<u>EventStream</u>	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	MessageBody	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	MessageBody	The request failed because the payload for the body of the request is too large

Status code	Response model	Description
		(RequestEntityTooLargeExcep tion).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **POST**

## **Operation ID:** PutEventStream

Creates a new event stream for an application or updates the settings of an existing event stream for an application.

## **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	<u>EventStream</u>	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	MessageBody	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	MessageBody	The request failed because the specified resource was not found (NotFoundException).
405	MessageBody	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large

Status code	Response model	Description
		(RequestEntityTooLargeExcep tion).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **DELETE**

Operation ID: DeleteEventStream

Deletes the event stream for an application.

# **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	<u>EventStream</u>	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	MessageBody	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	MessageBody	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large

Status code	Response model	Description
		(RequestEntityTooLargeExcep tion).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Event Stream resource.

## **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## Responses

Status code	Response model	Description
200	None	The request succeeded.

## **Schemas**

## **Request bodies**

#### **POST schema**

```
{
    "DestinationStreamArn": "string",
    "RoleArn": "string"
}
```

## **Response bodies**

#### **EventStream schema**

```
{
   "ApplicationId": "string",
   "DestinationStreamArn": "string",
   "RoleArn": "string",
   "ExternalId": "string",
   "LastModifiedDate": "string",
   "LastUpdatedBy": "string"
}
```

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

#### **EventStream**

Specifies settings for publishing event data to Amazon Kinesis Data Streams or Amazon Data Firehose delivery streams.

### **ApplicationId**

The unique identifier for the application to publish event data for.

Schemas 500

**Type**: string **Required**: True

#### **DestinationStreamArn**

The Amazon Resource Name (ARN) of the Amazon Kinesis Data Stream or Amazon Data Firehose delivery stream to publish event data to.

For a Kinesis Data Stream, the ARN format is: arn:aws:kinesis:region:account-id:stream/stream\_name

For a Firehose delivery stream, the ARN format is: arn:aws:firehose:region:account-id:deliverystream/stream\_name

**Type**: string **Required**: True

#### RoleArn

The AWS Identity and Access Management (IAM) role that authorizes Amazon Pinpoint to publish event data to the stream in your AWS account.

**Type**: string **Required**: True

#### **ExternalId**

(Deprecated) Your AWS account ID, which you assigned to an external ID key in an IAM trust policy. Amazon Pinpoint previously used this value to assume an IAM role when publishing event data, but we removed this requirement. We don't recommend use of external IDs for IAM roles that are assumed by Amazon Pinpoint.

**Type**: string **Required**: False

#### LastModifiedDate

The date, in ISO 8601 format, when the event stream was last modified.

**Type**: string **Required**: False

### LastUpdatedBy

The user who last modified the event stream.

**Type**: string **Required**: False

## MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

### Message

The message that's returned from the API.

**Type**: string **Required**: False

### WriteEventStream

Specifies the Amazon Resource Name (ARN) of an event stream to publish events to and the AWS Identity and Access Management (IAM) role to use when publishing those events.

### **DestinationStreamArn**

The Amazon Resource Name (ARN) of the Amazon Kinesis Data Stream or Amazon Data Firehose delivery stream that you want to publish event data to.

For a Kinesis Data Stream, the ARN format is: arn:aws:kinesis:region:account-id:stream\_name

For a Firehose delivery stream, the ARN format is: arn:aws:firehose:region:account-id:deliverystream/stream\_name

**Type**: string **Required**: True

#### RoleArn

The AWS Identity and Access Management (IAM) role that authorizes Amazon Pinpoint to publish event data to the stream in your AWS account.

**Type**: string **Required**: True

### See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

#### **GetEventStream**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

#### **PutEventStream**

- AWS Command Line Interface
- AWS SDK for .NET

See also 503

- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

### **DeleteEventStream**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Events**

In Amazon Pinpoint, you can create *events* to record and track how users interact with your app. For example, you can log interactions such as account creations, sign-in attempts, and purchases as events.

You can use the Events resource to record events for endpoints. This includes creating events and creating or updating data for endpoints that are associated with events.

### **URI**

/v1/apps/application-id/events

Events 504

# **HTTP** methods

### **POST**

## **Operation ID:** PutEvents

Creates a new event to record for endpoints, or creates or updates endpoint data that existing events are associated with.

## **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifier for the application. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

## Responses

Status code	Response model	Description
202	<u>EventsResponse</u>	The request was accepted for processing. Processing may not be complete.

Status code	Response model	Description
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	MessageBody	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Events resource.

## **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Request bodies**

### **POST schema**

```
{
   "BatchItem": {
   }
}
```

# **Response bodies**

## **EventsResponse schema**

```
{
```

Schemas 507

```
"<u>Results</u>": {
}
}
```

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

## **EndpointDemographic**

Specifies demographic information about an endpoint, such as the applicable time zone and platform.

### Make

The manufacturer of the endpoint device, such as Apple or Samsung. Can contain a maximum of 50 characters.

**Type**: string **Required**: False

#### Model

The model name or number of the endpoint device, such as iPhone or SM-G900F. Can contain a maximum of 100 characters.

**Type**: string **Required**: False

#### **ModelVersion**

The model version of the endpoint device. Can contain a maximum of 50 characters.

Type: string

Required: False

#### **Timezone**

The time zone of the endpoint, specified as a tz database name value, such as America/Los\_Angeles.

Type: string

**Required**: False

#### Locale

An identifier that represents the endpoint's language, in IETF BCP 47 format. This identifier typically consists of an ISO 639-1 alpha-2 code, followed by an underscore (\_), followed by an ISO 3166-1 alpha-2 value. For example, the locale code for United States English is en\_US.

In some cases, an ISO 3166-1 numeric-3 value is used instead of an ISO 3166-1 alpha-2 value. For example, the locale code for Latin American Spanish is es\_419.

In other cases, the ISO 639-1 alpha-2 is replaced with a three-letter code. For example, the locale code for Hawaiian is haw\_US.

Type: string

Required: False

### **AppVersion**

The version of the app that's associated with the endpoint. Can contain a maximum of 50 characters.

**Type**: string

Required: False

#### **Platform**

The platform of the endpoint device, such as iOS. Can contain a maximum of 50 characters.

**Type**: string

Required: False

#### **PlatformVersion**

The version of the platform for the endpoint device. Can contain a maximum of 50 characters.

Type: string

Required: False

## EndpointItemResponse

Provides the status code and message that result from processing data for an endpoint.

#### **StatusCode**

The status code that's returned in the response as a result of processing the endpoint data.

Type: integer

Required: False

### Message

The custom message that's returned in the response as a result of processing the endpoint data.

Type: string

Required: False

## **EndpointLocation**

Specifies geographic information about an endpoint.

#### Latitude

The latitude coordinate of the endpoint location, rounded to one decimal place. Must be between -90 and 90. If you specify a latitude, you must also specify a longitude.

Type: number

**Required**: False

### Longitude

The longitude coordinate of the endpoint location, rounded to one decimal place. Must be between -180 and 180. If you specify a longitude, you must also specify a latitude.

**Type**: number **Required**: False

#### **PostalCode**

The postal or ZIP code for the area where the endpoint is located.

**Type**: string **Required**: False

### City

The name of the city where the endpoint is located. Can contain a maximum of 75 characters.

**Type**: string **Required**: False

### Region

The name of the region where the endpoint is located. This value is typically a first-level subdivision a country, such as a state, province, prefecture, administrative region, district, or department. Can contain a maximum of 75 characters.

**Type**: string **Required**: False

### **Country**

A code that represents the country or region where the endpoint is located. Must be in ISO 3166-1 Alpha-2 or Alpha-3 format. For example, for the United States, you can use US or USA.

**Type**: string **Required**: False

### **EndpointUser**

Specifies data for one or more attributes that describe the user who's associated with an endpoint.

#### UserId

The unique identifier for the user. The identifier can't contain \$, { or }.

Type: string Required: False

#### **UserAttributes**

One or more custom attributes that describe the user by associating a name with an array of values. For example, the value of an attribute named Interests might be: ["Science", "Music", "Travel"]. You can use these attributes as filter criteria when you create segments. Attribute names are case sensitive.

An attribute name can contain up to 50 characters. An attribute value can contain up to 100 characters. When you define the name of a custom attribute, avoid using the following characters: number sign (#), colon (:), question mark (?), backslash (\), and slash (/). The Amazon Pinpoint console can't display attribute names that contain these characters. This restriction doesn't apply to attribute values.

**Type**: object **Required**: False

### **Event**

Specifies information about an event that reports data to Amazon Pinpoint.

## **EventType**

The name of the event.



### Note

Avoid using the following characters: #:?\/. The Amazon Pinpoint console doesn't correctly display event names that contain these characters.

**Type**: string

Required: True

### **Attributes**

One or more custom attributes that are associated with the event.

Type: object

Required: False

#### **Metrics**

One or more custom metrics that are associated with the event.

Type: object

Required: False

### **Timestamp**

The date and time, in ISO 8601 format, when the event occurred.

Type: string

**Required**: True

### ClientSdkVersion

The version of the SDK that's running on the client device.

Type: string

**Required**: False

## AppPackageName

The package name of the app that's recording the event.

Type: string

Required: False

### **AppTitle**

The title of the app that's recording the event.

**Type**: string **Required**: False

### **AppVersionCode**

The version number of the app that's recording the event.

**Type**: string **Required**: False

#### **SdkName**

The name of the SDK that's being used to record the event.

**Type**: string **Required**: False

#### Session

Information about the session in which the event occurred.

Type: <u>Session</u>
Required: False

## **EventItemResponse**

Provides the status code and message that result from processing an event.

#### StatusCode

The status code that's returned in the response as a result of processing the event. Possible values are: 202, for events that were accepted; and, 400, for events that weren't valid.

**Type**: integer **Required**: False

#### Message

A custom message that's returned in the response as a result of processing the event.

**Type**: string **Required**: False

### **EventsBatch**

Specifies a batch of endpoints and events to process.

### **Endpoint**

A set of properties and attributes that are associated with the endpoint.

Type: PublicEndpoint

Required: True

#### **Events**

A set of properties that are associated with the event.

**Type**: object **Required**: True

# ${\bf Events Request}$

Specifies a batch of events to process.

#### **BatchItem**

The batch of events to process. For each item in a batch, the endpoint ID acts as a key that has an EventsBatch object as its value. The identifier can't contain \$, { or }.

**Type**: object **Required**: True

## **EventsResponse**

Provides information about endpoints and the events that they're associated with.

#### **Results**

A map that contains a multipart response for each endpoint. For each item in this object, the endpoint ID is the key and the item response is the value. If no item response exists, the value can also be one of the following: 202, the request was processed successfully; or 400, the payload wasn't valid or required fields were missing.

**Type**: object **Required**: False

## **ItemResponse**

Provides information about the results of a request to create or update an endpoint that's associated with an event.

### EndpointItemResponse

The response that was received after the endpoint data was accepted.

Type: EndpointItemResponse

**Required**: False

### **EventsItemResponse**

A multipart response object that contains a key and a value for each event in the request. In each object, the event ID is the key and an EventItemResponse object is the value.

**Type**: object **Required**: False

## MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

#### Message

The message that's returned from the API.

**Type**: string **Required**: False

## **PublicEndpoint**

Specifies the properties and attributes of an endpoint that's associated with an event.

### ChannelType

The channel that's used when sending messages or push notifications to the endpoint.

**Type**: string **Required**: False

Values: PUSH | GCM | APNS | APNS\_SANDBOX | APNS\_VOIP | APNS\_VOIP\_SANDBOX |

ADM | SMS | VOICE | EMAIL | BAIDU | CUSTOM | IN\_APP

#### **Address**

The unique identifier for the recipient, such as a device token, email address, or mobile phone number.

**Type**: string **Required**: False

### **EndpointStatus**

Specifies whether to send messages or push notifications to the endpoint. Valid values are: ACTIVE, messages are sent to the endpoint; and, INACTIVE, messages aren't sent to the endpoint.

Amazon Pinpoint automatically sets this value to ACTIVE when you create an endpoint or update an existing endpoint. Amazon Pinpoint automatically sets this value to INACTIVE if you update another endpoint that has the same address specified by the Address property.

Type: string

Required: False

### **OptOut**

Specifies whether the user who's associated with the endpoint has opted out of receiving messages and push notifications from you. Possible values are: ALL, the user has opted out and doesn't want to receive any messages or push notifications; and, NONE, the user hasn't opted out and wants to receive all messages and push notifications.

**Type**: string **Required**: False

### RequestId

A unique identifier that's generated each time the endpoint is updated.

**Type**: string **Required**: False

### Location

The geographic information for the endpoint.

**Type**: EndpointLocation

Required: False

### **Demographic**

The demographic information for the endpoint, such as the time zone and platform.

Type: EndpointDemographic

Required: False

#### **EffectiveDate**

The date and time, in ISO 8601 format, when the endpoint was last updated.

**Type**: string **Required**: False

#### **Attributes**

One or more custom attributes that describe the endpoint by associating a name with an array of values. You can use these attributes as filter criteria when you create segments.

**Type**: object **Required**: False

#### **Metrics**

One or more custom metrics that your app reports to Amazon Pinpoint for the endpoint.

**Type**: object **Required**: False

#### User

One or more custom user attributes that your app reports to Amazon Pinpoint for the user who's associated with the endpoint.

Type: EndpointUser
Required: False

### Session

Provides information about a session.

### Id

The unique identifier for the session.

**Type**: string **Required**: True

#### **Duration**

The duration of the session, in milliseconds. Duration is required if a value is provided for the StopTimestamp.

**Type**: integer **Required**: False

### StartTimestamp

The date and time when the session began.

**Type**: string **Required**: True

### StopTimestamp

The date and time when the session ended.

**Type**: string

Required: False

### See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

#### **PutEvents**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

See also 520

# **Export Job**

The Export Job resource represents a job that exports endpoint definitions to a file. The file can be added directly to an Amazon Simple Storage Service (Amazon S3) bucket by using the Amazon Pinpoint API or downloaded directly to a computer by using the Amazon Pinpoint console.

An *endpoint* uniquely identifies a mobile device, email address, or phone number that can receive a message. By using export jobs, you can export information about all the endpoints that are associated with an application, or you can export information about the subset of endpoints that belong to a segment.

You can use the Export Job resource to retrieve information about the status and settings of a specific export job for an application. To create an export job for an application or to retrieve information about all the export jobs for an application, use the Export Jobs resource.

### URI

/v1/apps/application-id/jobs/export/job-id

### **HTTP** methods

#### **GET**

**Operation ID:** GetExportJob

Retrieves information about the status and settings of a specific export job for an application.

## Path parameters

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

Export Job 521

Name	Type	Required	Description
job-id	String	True	The unique identifier for the job.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.
			• •

# Responses

Status code	Response model	Description
200	ExportJobResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource

Status code	Response model	Description
		(MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Export Job resource.

## **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

Name	Туре	Required	Description
job-id	String	True	The unique identifier
			for the job.

### Responses

Status code	Response model	Description
200	None	The request succeeded.

### **Schemas**

## **Response bodies**

### **ExportJobResponse schema**

```
{
  "ApplicationId": "string",
  "Id": "string",
  "JobStatus": enum,
  "CompletedPieces": integer,
  "FailedPieces": integer,
  "TotalPieces": integer,
  "CreationDate": "string",
  "CompletionDate": "string",
  "Type": "string",
  "TotalFailures": integer,
  "TotalProcessed": integer,
  "Failures": [
    "string"
  ],
  "Definition": {
    "SegmentId": "string",
    "SegmentVersion": integer,
    "S3UrlPrefix": "string",
    "RoleArn": "string"
  }
}
```

Schemas 524

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

## **Properties**

### **ExportJobResource**

Provides information about the resource settings for a job that exports endpoint definitions to a file. The file can be added directly to an Amazon Simple Storage Service (Amazon S3) bucket by using the Amazon Pinpoint API or downloaded directly to a computer by using the Amazon Pinpoint console.

### SegmentId

The identifier for the segment that the endpoint definitions were exported from. If this value isn't present, Amazon Pinpoint exported definitions for all the endpoints that are associated with the application.

**Type**: string **Required**: False

### **SegmentVersion**

The version of the segment that the endpoint definitions were exported from.

**Type**: integer **Required**: False

#### S3UrlPrefix

The URL of the location in an Amazon Simple Storage Service (Amazon S3) bucket where the endpoint definitions were exported to. This location is typically a folder that contains multiple files. The URL should be in the following format: s3://bucket-name/folder-name/.

Type: string

Required: True

#### RoleArn

The Amazon Resource Name (ARN) of the AWS Identity and Access Management (IAM) role that authorized Amazon Pinpoint to access the Amazon S3 location where the endpoint definitions were exported to.

**Type**: string **Required**: True

### **ExportJobResponse**

Provides information about the status and settings of a job that exports endpoint definitions to a file. The file can be added directly to an Amazon Simple Storage Service (Amazon S3) bucket by using the Amazon Pinpoint API or downloaded directly to a computer by using the Amazon Pinpoint console.

### **ApplicationId**

The unique identifier for the application that's associated with the export job.

**Type**: string **Required**: True

### Id

The unique identifier for the export job.

**Type**: string **Required**: True

#### **JobStatus**

The status of the export job. The job status is FAILED if Amazon Pinpoint wasn't able to process one or more pieces in the job.

**Type**: string **Required**: True

Values: CREATED | PREPARING\_FOR\_INITIALIZATION | INITIALIZING | PROCESSING
| PENDING\_JOB | COMPLETING | COMPLETED | CANCELLING | CANCELLED | FAILING
| FAILED

### **CompletedPieces**

The number of pieces that were processed successfully (completed) by the export job, as of the time of the request.

**Type**: integer **Required**: False

#### **FailedPieces**

The number of pieces that weren't processed successfully (failed) by the export job, as of the time of the request.

**Type**: integer **Required**: False

#### **TotalPieces**

The total number of pieces that must be processed to complete the export job. Each piece consists of an approximately equal portion of the endpoint definitions that are part of the export job.

**Type**: integer **Required**: False

#### CreationDate

The date, in ISO 8601 format, when the export job was created.

**Type**: string **Required**: True

### **CompletionDate**

The date, in ISO 8601 format, when the export job was completed.

**Type**: string **Required**: False

## **Type**

The job type. This value is EXPORT for export jobs.

**Type**: string **Required**: True

#### **TotalFailures**

The total number of endpoint definitions that weren't processed successfully (failed) by the export job, typically because an error, such as a syntax error, occurred.

**Type**: integer **Required**: False

#### **TotalProcessed**

The total number of endpoint definitions that were processed by the export job.

**Type**: integer **Required**: False

#### **Failures**

An array of entries, one for each of the first 100 entries that weren't processed successfully (failed) by the export job, if any.

Type: Array of type string

Required: False

#### **Definition**

The resource settings that apply to the export job.

**Type**: ExportJobResource

Required: True

## MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

## Message

The message that's returned from the API.

**Type**: string **Required**: False

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

# GetExportJob

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python

See also 529

### AWS SDK for Ruby V3

# **Export Jobs**

The Export Jobs resource represents jobs that export endpoint definitions to files. A file can be added directly to an Amazon Simple Storage Service (Amazon S3) bucket by using the Amazon Pinpoint API or downloaded directly to a computer by using the Amazon Pinpoint console.

An *endpoint* uniquely identifies a mobile device, email address, or phone number that can receive a message. By using export jobs, you can export information about all the endpoints that are associated with an application, or you can export information about the subset of endpoints that belong to a segment.

You can use the Export Jobs resource to create an export job for an application or to retrieve information about all the export jobs for an application. This includes checking the status of an inprogress export job and accessing the history of your export jobs.

## **URI**

/v1/apps/application-id/jobs/export

## **HTTP** methods

#### **GET**

**Operation ID:** GetExportJobs

Retrieves information about the status and settings of all the export jobs for an application.

## **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

Export Jobs 530

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# **Query parameters**

Name	Туре	Required	Description
page-size	String	False	The maximum number of items to include in each page of a paginated response. This parameter is not supported for application, campaign, and journey metrics.
token	String	False	The NextToken string that specifies which page of results to return in a paginated response.

# Responses

Status code	Response model	Description
200	<pre>ExportJobsResponse</pre>	The request succeeded.

Status code	Response model	Description
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	MessageBody	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **POST**

# **Operation ID:** CreateExportJob

Creates an export job for an application.

# **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

## Responses

Status code	Response model	Description
202	ExportJobResponse	The request was accepted for processing. Processing may not be complete.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).

Status code	Response model	Description
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Export Jobs resource.

## **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Request bodies**

## **POST schema**

```
{
    "SegmentId": "string",
    "SegmentVersion": integer,
    "S3UrlPrefix": "string",
    "RoleArn": "string"
}
```

# **Response bodies**

Schemas 535

### **ExportJobsResponse schema**

```
{
  "Item": [
      "ApplicationId": "string",
      "Id": "string",
      "JobStatus": enum,
      "CompletedPieces": integer,
      "FailedPieces": integer,
      "TotalPieces": integer,
      "CreationDate": "string",
      "CompletionDate": "string",
      "Type": "string",
      "TotalFailures": integer,
      "TotalProcessed": integer,
      "Failures": [
        "string"
      "Definition": {
        "SegmentId": "string",
        "SegmentVersion": integer,
        "S3UrlPrefix": "string",
        "RoleArn": "string"
      }
    }
  ],
  "NextToken": "string"
}
```

### **ExportJobResponse schema**

```
{
  "ApplicationId": "string",
  "Id": "string",
  "JobStatus": enum,
  "CompletedPieces": integer,
  "FailedPieces": integer,
  "TotalPieces": integer,
  "CreationDate": "string",
  "CompletionDate": "string",
  "Type": "string",
```

Schemas 536

```
"TotalFailures": integer,
"TotalProcessed": integer,
"Failures": [
    "string"
],
"Definition": {
    "SegmentId": "string",
    "SegmentVersion": integer,
    "S3UrlPrefix": "string",
    "RoleArn": "string"
}
```

## MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

# **ExportJobRequest**

Specifies the settings for a job that exports endpoint definitions to an Amazon Simple Storage Service (Amazon S3) bucket.

## SegmentId

The identifier for the segment to export endpoint definitions from. If you don't specify this value, Amazon Pinpoint exports definitions for all the endpoints that are associated with the application.

**Type**: string **Required**: False

## **SegmentVersion**

The version of the segment to export endpoint definitions from, if specified.

Type: integer

Required: False

#### S3UrlPrefix

The URL of the location in an Amazon Simple Storage Service (Amazon S3) bucket where you want to export endpoint definitions to. This location is typically a folder that contains multiple files. The URL should be in the following format: s3://bucket-name/folder-name/.

**Type**: string **Required**: True

#### RoleArn

The Amazon Resource Name (ARN) of the AWS Identity and Access Management (IAM) role that authorizes Amazon Pinpoint to access the Amazon S3 location where you want to export endpoint definitions to.

**Type**: string **Required**: True

## **ExportJobResource**

Provides information about the resource settings for a job that exports endpoint definitions to a file. The file can be added directly to an Amazon Simple Storage Service (Amazon S3) bucket by using the Amazon Pinpoint API or downloaded directly to a computer by using the Amazon Pinpoint console.

## SegmentId

The identifier for the segment that the endpoint definitions were exported from. If this value isn't present, Amazon Pinpoint exported definitions for all the endpoints that are associated with the application.

**Type**: string **Required**: False

### **SegmentVersion**

The version of the segment that the endpoint definitions were exported from.

**Type**: integer **Required**: False

#### S3UrlPrefix

The URL of the location in an Amazon Simple Storage Service (Amazon S3) bucket where the endpoint definitions were exported to. This location is typically a folder that contains multiple files. The URL should be in the following format: s3://bucket-name/folder-name/.

**Type**: string **Required**: True

#### RoleArn

The Amazon Resource Name (ARN) of the AWS Identity and Access Management (IAM) role that authorized Amazon Pinpoint to access the Amazon S3 location where the endpoint definitions were exported to.

**Type**: string **Required**: True

# **ExportJobResponse**

Provides information about the status and settings of a job that exports endpoint definitions to a file. The file can be added directly to an Amazon Simple Storage Service (Amazon S3) bucket by using the Amazon Pinpoint API or downloaded directly to a computer by using the Amazon Pinpoint console.

## **ApplicationId**

The unique identifier for the application that's associated with the export job.

**Type**: string **Required**: True

Id

The unique identifier for the export job.

**Type**: string **Required**: True

#### **JobStatus**

The status of the export job. The job status is FAILED if Amazon Pinpoint wasn't able to process one or more pieces in the job.

**Type**: string **Required**: True

Values: CREATED | PREPARING\_FOR\_INITIALIZATION | INITIALIZING | PROCESSING
| PENDING\_JOB | COMPLETING | COMPLETED | CANCELLING | CANCELLED | FAILING

| FAILED

## **CompletedPieces**

The number of pieces that were processed successfully (completed) by the export job, as of the time of the request.

**Type**: integer **Required**: False

#### **FailedPieces**

The number of pieces that weren't processed successfully (failed) by the export job, as of the time of the request.

**Type**: integer **Required**: False

#### **TotalPieces**

The total number of pieces that must be processed to complete the export job. Each piece consists of an approximately equal portion of the endpoint definitions that are part of the export job.

**Type**: integer **Required**: False

#### CreationDate

The date, in ISO 8601 format, when the export job was created.

**Type**: string **Required**: True

## CompletionDate

The date, in ISO 8601 format, when the export job was completed.

Type: string

Required: False

### **Type**

The job type. This value is EXPORT for export jobs.

**Type**: string **Required**: True

TotalFailures

The total number of endpoint definitions that weren't processed successfully (failed) by the export job, typically because an error, such as a syntax error, occurred.

Type: integer

Required: False

#### **TotalProcessed**

The total number of endpoint definitions that were processed by the export job.

**Type**: integer

Required: False

#### **Failures**

An array of entries, one for each of the first 100 entries that weren't processed successfully (failed) by the export job, if any.

Type: Array of type string

Required: False

#### **Definition**

The resource settings that apply to the export job.

Type: ExportJobResource

Required: True

# ExportJobsResponse

Provides information about all the export jobs that are associated with an application or segment. An export job is a job that exports endpoint definitions to a file.

#### Item

An array of responses, one for each export job that's associated with the application (Export Jobs resource) or segment (Segment Export Jobs resource).

**Type**: Array of type ExportJobResponse

Required: True

#### NextToken

The string to use in a subsequent request to get the next page of results in a paginated response. This value is null if there are no additional pages.

**Type**: string **Required**: False

# MessageBody

Provides information about an API request or response.

#### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

## Message

The message that's returned from the API.

**Type**: string **Required**: False

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

# GetExportJobs

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# CreateExportJob

- AWS Command Line Interface
- AWS SDK for .NET

See also 543

- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

## **GCM Channel**

A *channel* is a type of platform that you can deliver messages to. You can use the GCM channel to send push notification messages to the Firebase Cloud Messaging (FCM) service, which replaces the Google Cloud Messaging (GCM) service. Before you can use Amazon Pinpoint to send notification messages to FCM, you must enable the GCM channel for an Amazon Pinpoint application.

The GCM Channel resource represents the status and authentication settings of the GCM channel for a specific application. You can use this resource to enable, retrieve information about, update, or disable (delete) the GCM channel for an application.

#### URI

/v1/apps/application-id/channels/gcm

# **HTTP methods**

#### **GET**

Operation ID: GetGcmChannel

Retrieves information about the status and settings of the GCM channel for an application.

## Path parameters

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati

GCM Channel 544

Name	Туре	Required	Description
			on. This identifier
			is displayed as the
			Project ID on the
			Amazon Pinpoint
			console.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	<u>GCMChannelResponse</u>	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).

Status code	Response model	Description
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **PUT**

# **Operation ID:** UpdateGcmChannel

Enables the GCM channel for an application or updates the status and settings of the GCM channel for an application.

## **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier

Name	Туре	Required	Description
			is displayed as the
			Project ID on the
			Amazon Pinpoint
			console.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	<u>GCMChannelResponse</u>	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed

Status code	Response model	Description
		for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **DELETE**

**Operation ID:** DeleteGcmChannel

Disables the GCM channel for an application and deletes any existing settings for the channel.

# **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the

Name	Туре	Required	Description
			Amazon Pinpoint
			console.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	<u>GCMChannelResponse</u>	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource

Status code	Response model	Description
		(MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **OPTIONS**

Retrieves information about the communication requirements and options that are available for the GCM Channel resource.

# **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

#### Responses

Status code	Response model	Description
200	None	The request succeeded.

## **Schemas**

# **Request bodies**

#### **PUT schema**

```
{
  "ApiKey": "string",
  "Enabled": boolean,
  "ServiceJson": "string",
  "DefaultAuthenticationMethod": "string"
}
```

# **Response bodies**

## **GCMChannelResponse schema**

```
{
   "ApplicationId": "string",
   "IsArchived": boolean,
   "Version": integer,
   "CreationDate": "string",
   "LastModifiedDate": "string",
   "LastModifiedBy": "string",
   "Id": "string",
   "Enabled": boolean,
   "HasCredential": boolean,
   "Platform": "string",
   "Credential": "string",
   "Credential": "string",
   "MasFcmServiceCredentials": boolean,
   "DefaultAuthenticationMethod": "string"
}
```

Schemas 551

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

# **GCMChannelRequest**

Specifies the status and settings of the GCM channel for an application. This channel enables Amazon Pinpoint to send push notifications through the Firebase Cloud Messaging (FCM), formerly Google Cloud Messaging (GCM), service.

## **ApiKey**

The Web API Key, also referred to as an API\_KEY or server key, that you received from Google to communicate with Google services.

**Type**: string **Required**: False

#### **Enabled**

Specifies whether to enable the GCM channel for the application.

**Type**: boolean **Required**: False

#### ServiceJson

The contents of the JSON file provided by Google during registration in order to generate an access token for authentication. For more information see Migrate from legacy FCM APIs to HTTP v1.

**Type**: string **Required**: False

#### **DefaultAuthenticationMethod**

The default authentication method used for GCM. Values are either "TOKEN" or "KEY". Defaults to "KEY".

**Type**: string

Required: False

## **GCMChannelResponse**

Provides information about the status and settings of the GCM channel for an application. The GCM channel enables Amazon Pinpoint to send push notifications through the Firebase Cloud Messaging (FCM), formerly Google Cloud Messaging (GCM), service.

## **ApplicationId**

The unique identifier for the application that the GCM channel applies to.

**Type**: string

Required: False

#### **IsArchived**

Specifies whether the GCM channel is archived.

Type: boolean

Required: False

#### Version

The current version of the GCM channel.

**Type**: integer

Required: False

#### CreationDate

The date and time when the GCM channel was enabled.

**Type**: string **Required**: False

## LastModifiedDate

The date and time when the GCM channel was last modified.

**Type**: string **Required**: False

## LastModifiedBy

The user who last modified the GCM channel.

**Type**: string **Required**: False

#### Id

(Deprecated) An identifier for the GCM channel. This property is retained only for backward compatibility.

**Type**: string **Required**: False

#### **Enabled**

Specifies whether the GCM channel is enabled for the application.

**Type**: boolean **Required**: False

#### **HasCredential**

(Not used) This property is retained only for backward compatibility.

**Type**: boolean **Required**: False

#### **Platform**

The type of messaging or notification platform for the channel. For the GCM channel, this value is GCM.

**Type**: string **Required**: True

#### Credential

The Web API Key, also referred to as an API\_KEY or server key, that you received from Google to communicate with Google services.

**Type**: string **Required**: False

#### **HasFcmServiceCredentials**

Returns true if the JSON file provided by Google during registration process was used in the **ServiceJson** field of the request.

**Type**: boolean **Required**: False

#### **DefaultAuthenticationMethod**

The default authentication method used for GCM. Values are either "TOKEN" or "KEY". Defaults to "KEY".

**Type**: string **Required**: False

# MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

## Message

The message that's returned from the API.

**Type**: string **Required**: False

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## **GetGcmChannel**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **UpdateGcmChannel**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2

See also 556

- AWS SDK for JavaScript V3
- · AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

### **DeleteGcmChannel**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# Import Job

The Import Job resource represents a job that imports endpoint definitions from one or more files. The files can be stored in an Amazon Simple Storage Service (Amazon S3) bucket or uploaded directly from a computer by using the Amazon Pinpoint console.

An *endpoint* uniquely identifies a mobile device, email address, or phone number that can receive a message. Importing endpoint definitions is useful if you've already created user segments outside Amazon Pinpoint but you want to engage your users with Amazon Pinpoint campaigns. By using an import job, you can import the endpoint definitions for those users and create a segment that contains all the imported data.

You can use the Import Job resource to retrieve information about the status and settings of a specific import job for an application. To create or update an import job for an application or to retrieve information about all the import jobs for an application, use the Import Jobs resource.

Import Job 557

# **URI**

/v1/apps/application-id/jobs/import/job-id

# **HTTP** methods

## **GET**

Operation ID: GetImportJob

Retrieves information about the status and settings of a specific import job for an application.

## **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.
job-id	String	True	The unique identifier for the job.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

URI 558

## Responses

Status code	Response model	Description
200	ImportJobResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error,

Status code	Response model	Description
		exception, or failure (Internal
		ServerErrorException).

## **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Import Job resource.

## **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.
job-id	String	True	The unique identifier for the job.

## Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Response bodies**

# ImportJobResponse schema

{

Schemas 560

```
"ApplicationId": "string",
  "Id": "string",
  "JobStatus": enum,
  "CompletedPieces": integer,
  "FailedPieces": integer,
  "TotalPieces": integer,
  "CreationDate": "string",
  "CompletionDate": "string",
  "Type": "string",
  "TotalFailures": integer,
  "TotalProcessed": integer,
  "Failures": [
    "string"
  ],
  "Definition": {
    "S3Url": "string",
    "RoleArn": "string",
    "ExternalId": "string",
    "Format": enum,
    "RegisterEndpoints": boolean,
    "DefineSegment": boolean,
    "SegmentName": "string",
    "SegmentId": "string"
  }
}
```

#### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

# **ImportJobResource**

Provides information about the resource settings for a job that imports endpoint definitions from one or more files. The files can be stored in an Amazon Simple Storage Service (Amazon S3) bucket or uploaded directly from a computer by using the Amazon Pinpoint console.

#### S3Url

The URL of the Amazon Simple Storage Service (Amazon S3) bucket that contains the endpoint definitions to import. This location can be a folder or a single file. If the location is a folder, Amazon Pinpoint imports endpoint definitions from the files in this location, including any subfolders that the folder contains.

The URL should be in the following format: s3://bucket-name/folder-name/file-name.

The location can end with the key for an individual object or a prefix that qualifies multiple objects.

**Type**: string **Required**: True

### RoleArn

The Amazon Resource Name (ARN) of the AWS Identity and Access Management (IAM) role that authorizes Amazon Pinpoint to access the Amazon S3 location to import endpoint definitions from.

**Type**: string **Required**: True

#### **ExternalId**

(Deprecated) Your AWS account ID, which you assigned to an external ID key in an IAM trust policy. Amazon Pinpoint previously used this value to assume an IAM role when importing endpoint definitions, but we removed this requirement. We don't recommend use of external IDs for IAM roles that are assumed by Amazon Pinpoint.

**Type**: string **Required**: False

#### **Format**

The format of the files that contain the endpoint definitions to import. Valid values are: CSV, for comma-separated values format; and, JSON, for newline-delimited JSON format.

If the files are stored in an Amazon S3 location and that location contains multiple files that use different formats, Amazon Pinpoint imports data only from the files that use the specified format.

**Type**: string Required: True

Values: CSV | JSON

## RegisterEndpoints

Specifies whether the import job registers the endpoints with Amazon Pinpoint, when the endpoint definitions are imported.

Type: boolean **Required**: False

## **DefineSegment**

Specifies whether the import job creates a segment that contains the endpoints, when the endpoint definitions are imported.

Type: boolean Required: False

## SegmentName

The custom name for the segment that's created by the import job, if the value of the DefineSegment property is true.



## Note

A segment must have a name otherwise it will not appear in the Amazon Pinpoint console.

**Type**: string

Required: False

## SegmentId

The identifier for the segment that the import job updates or adds endpoint definitions to, if the import job updates an existing segment.

**Type**: string **Required**: False

# **ImportJobResponse**

Provides information about the status and settings of a job that imports endpoint definitions from one or more files. The files can be stored in an Amazon Simple Storage Service (Amazon S3) bucket or uploaded directly from a computer by using the Amazon Pinpoint console.

## **ApplicationId**

The unique identifier for the application that's associated with the import job.

**Type**: string **Required**: True

### Id

The unique identifier for the import job.

**Type**: string **Required**: True

#### **JobStatus**

The status of the import job. The job status is FAILED if Amazon Pinpoint wasn't able to process one or more pieces in the job.

```
Type: string
Required: True
Values: CREATED | PREPARING_FOR_INITIALIZATION | INITIALIZING | PROCESSING
| PENDING_JOB | COMPLETING | COMPLETED | CANCELLING | CANCELLED | FAILING
| FAILED
```

## **CompletedPieces**

The number of pieces that were processed successfully (completed) by the import job, as of the time of the request.

**Type**: integer **Required**: False

### **FailedPieces**

The number of pieces that weren't processed successfully (failed) by the import job, as of the time of the request.

**Type**: integer **Required**: False

### **TotalPieces**

The total number of pieces that must be processed to complete the import job. Each piece consists of an approximately equal portion of the endpoint definitions that are part of the import job.

**Type**: integer **Required**: False

### CreationDate

The date, in ISO 8601 format, when the import job was created.

**Type**: string **Required**: True

## CompletionDate

The date, in ISO 8601 format, when the import job was completed.

**Type**: string **Required**: False

## Type

The job type. This value is IMPORT for import jobs.

**Type**: string **Required**: True

### **TotalFailures**

The total number of endpoint definitions that weren't processed successfully (failed) by the import job, typically because an error, such as a syntax error, occurred.

**Type**: integer **Required**: False

### **TotalProcessed**

The total number of endpoint definitions that were processed by the import job.

**Type**: integer **Required**: False

### **Failures**

An array of entries, one for each of the first 100 entries that weren't processed successfully (failed) by the import job, if any.

Type: Array of type string

Required: False

### **Definition**

The resource settings that apply to the import job.

**Type**: ImportJobResource

Required: True

# MessageBody

Provides information about an API request or response.

## RequestID

The unique identifier for the request or response.

Type: string

Required: False

### Message

The message that's returned from the API.

**Type**: string **Required**: False

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

# GetImportJob

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Import Jobs**

The Import Jobs resource represents jobs that import endpoint definitions from one or more files. The files can be stored in an Amazon Simple Storage Service (Amazon S3) bucket or uploaded directly from a computer by using the Amazon Pinpoint console.

An *endpoint* uniquely identifies a mobile device, email address, or phone number that can receive a message. Importing endpoint definitions is useful if you've already created user segments outside

See also 567

Amazon Pinpoint but you want to engage your users with Amazon Pinpoint campaigns. By using an import job, you can import the endpoint definitions for those users and create a segment that contains all the imported data.

You can use the Import Jobs resource to create or retrieve information about the import jobs for an application. This includes checking the status of an in-progress import job and retrieving information about all the import jobs for an application.

## **URI**

/v1/apps/application-id/jobs/import

## **HTTP** methods

## **GET**

Operation ID: GetImportJobs

Retrieves information about the status and settings of all the import jobs for an application.

## Path parameters

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME

URI 568

Name	Туре	Required	Description
			types, the client understands.

# **Query parameters**

Name	Туре	Required	Description
page-size	String	False	The maximum number of items to include in each page of a paginated response. This parameter is not supported for application, campaign, and journey metrics.
token	String	False	The NextToken string that specifies which page of results to return in a paginated response.

# Responses

Status code	Response model	Description
200	ImportJobsResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is

Status code	Response model	Description
		forbidden (ForbiddenException).
404	MessageBody	The request failed because the specified resource was not found (NotFoundException).
405	MessageBody	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	MessageBody	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	MessageBody	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **POST**

Operation ID: CreateImportJob

Creates an import job for an application.

# **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
201	ImportJobResponse	The request succeeded and the specified resource was created.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).

Status code	Response model	Description
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Import Jobs resource.

## Path parameters

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Request bodies**

### **POST schema**

```
{
  "S3Url": "string",
  "RoleArn": "string",
  "ExternalId": "string",
  "Format": enum,
  "RegisterEndpoints": boolean,
  "DefineSegment": boolean,
  "SegmentName": "string",
  "SegmentId": "string"
}
```

# **Response bodies**

## ImportJobsResponse schema

```
{
  "Item": [
      "ApplicationId": "string",
      "Id": "string",
      "JobStatus": enum,
      "CompletedPieces": integer,
      "FailedPieces": integer,
      "TotalPieces": integer,
      "CreationDate": "string",
      "CompletionDate": "string",
      "Type": "string",
      "TotalFailures": integer,
      "TotalProcessed": integer,
      "Failures": [
        "string"
      "Definition": {
        "S3Url": "string",
        "RoleArn": "string",
        "ExternalId": "string",
        "Format": enum,
        "RegisterEndpoints": boolean,
        "DefineSegment": boolean,
        "SegmentName": "string",
        "SegmentId": "string"
      }
    }
  ],
  "NextToken": "string"
}
```

## ImportJobResponse schema

```
{
  "ApplicationId": "string",
  "Id": "string",
  "JobStatus": enum,
  "CompletedPieces": integer,
  "FailedPieces": integer,
```

```
"TotalPieces": integer,
  "CreationDate": "string",
  "CompletionDate": "string",
  "Type": "string",
  "TotalFailures": integer,
  "TotalProcessed": integer,
  "Failures": [
    "string"
  ],
  "Definition": {
    "S3Url": "string",
    "RoleArn": "string",
    "ExternalId": "string",
    "Format": enum,
    "RegisterEndpoints": boolean,
    "DefineSegment": boolean,
    "SegmentName": "string",
    "SegmentId": "string"
  }
}
```

## MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

# **ImportJobRequest**

Specifies the settings for a job that imports endpoint definitions from an Amazon Simple Storage Service (Amazon S3) bucket.

#### S3Url

The URL of the Amazon Simple Storage Service (Amazon S3) bucket that contains the endpoint definitions to import. This location can be a folder or a single file. If the location is a folder, Amazon Pinpoint imports endpoint definitions from the files in this location, including any subfolders that the folder contains.

The URL should be in the following format: s3://bucket-name/folder-name/file-name.

The location can end with the key for an individual object or a prefix that qualifies multiple objects.

**Type**: string **Required**: True

### RoleArn

The Amazon Resource Name (ARN) of the AWS Identity and Access Management (IAM) role that authorizes Amazon Pinpoint to access the Amazon S3 location to import endpoint definitions from.

**Type**: string **Required**: True

### **ExternalId**

(Deprecated) Your AWS account ID, which you assigned to an external ID key in an IAM trust policy. Amazon Pinpoint previously used this value to assume an IAM role when importing endpoint definitions, but we removed this requirement. We don't recommend use of external IDs for IAM roles that are assumed by Amazon Pinpoint.

**Type**: string **Required**: False

#### **Format**

The format of the files that contain the endpoint definitions to import. Valid values are: CSV, for comma-separated values format; and, JSON, for newline-delimited JSON format. If the Amazon S3 location stores multiple files that use different formats, Amazon Pinpoint imports data only from the files that use the specified format.

**Type**: string **Required**: True

Values: CSV | JSON

## RegisterEndpoints

Specifies whether to register the endpoints with Amazon Pinpoint, when the endpoint definitions are imported.

**Type**: boolean **Required**: False

## **DefineSegment**

Specifies whether to create a segment that contains the endpoints, when the endpoint definitions are imported.

**Type**: boolean **Required**: False

## SegmentName

A custom name for the segment that's created by the import job, if the value of the DefineSegment property is true.

**Type**: string **Required**: False

## SegmentId

The identifier for the segment to update or add the imported endpoint definitions to, if the import job is meant to update an existing segment.

**Type**: string **Required**: False

# **ImportJobResource**

Provides information about the resource settings for a job that imports endpoint definitions from one or more files. The files can be stored in an Amazon Simple Storage Service (Amazon S3) bucket or uploaded directly from a computer by using the Amazon Pinpoint console.

### S3Url

The URL of the Amazon Simple Storage Service (Amazon S3) bucket that contains the endpoint definitions to import. This location can be a folder or a single file. If the location is a folder, Amazon Pinpoint imports endpoint definitions from the files in this location, including any subfolders that the folder contains.

The URL should be in the following format: s3://bucket-name/folder-name/file-name.

The location can end with the key for an individual object or a prefix that qualifies multiple objects.

**Type**: string **Required**: True

## RoleArn

The Amazon Resource Name (ARN) of the AWS Identity and Access Management (IAM) role that authorizes Amazon Pinpoint to access the Amazon S3 location to import endpoint definitions from.

**Type**: string **Required**: True

### **ExternalId**

(Deprecated) Your AWS account ID, which you assigned to an external ID key in an IAM trust policy. Amazon Pinpoint previously used this value to assume an IAM role when importing endpoint definitions, but we removed this requirement. We don't recommend use of external IDs for IAM roles that are assumed by Amazon Pinpoint.

**Type**: string **Required**: False

#### **Format**

The format of the files that contain the endpoint definitions to import. Valid values are: CSV, for comma-separated values format; and, JSON, for newline-delimited JSON format.

If the files are stored in an Amazon S3 location and that location contains multiple files that use different formats, Amazon Pinpoint imports data only from the files that use the specified format.

**Type**: string Required: True

Values: CSV | JSON

## RegisterEndpoints

Specifies whether the import job registers the endpoints with Amazon Pinpoint, when the endpoint definitions are imported.

Type: boolean **Required**: False

## **DefineSegment**

Specifies whether the import job creates a segment that contains the endpoints, when the endpoint definitions are imported.

Type: boolean Required: False

## SegmentName

The custom name for the segment that's created by the import job, if the value of the DefineSegment property is true.



## Note

A segment must have a name otherwise it will not appear in the Amazon Pinpoint console.

**Type**: string

Required: False

# SegmentId

The identifier for the segment that the import job updates or adds endpoint definitions to, if the import job updates an existing segment.

**Type**: string **Required**: False

# **ImportJobResponse**

Provides information about the status and settings of a job that imports endpoint definitions from one or more files. The files can be stored in an Amazon Simple Storage Service (Amazon S3) bucket or uploaded directly from a computer by using the Amazon Pinpoint console.

## **ApplicationId**

The unique identifier for the application that's associated with the import job.

**Type**: string **Required**: True

#### Id

The unique identifier for the import job.

**Type**: string **Required**: True

#### **JobStatus**

The status of the import job. The job status is FAILED if Amazon Pinpoint wasn't able to process one or more pieces in the job.

```
Type: string
Required: True
Values: CREATED | PREPARING_FOR_INITIALIZATION | INITIALIZING | PROCESSING
| PENDING_JOB | COMPLETING | COMPLETED | CANCELLING | CANCELLED | FAILING
| FAILED
```

## **CompletedPieces**

The number of pieces that were processed successfully (completed) by the import job, as of the time of the request.

**Type**: integer **Required**: False

## **FailedPieces**

The number of pieces that weren't processed successfully (failed) by the import job, as of the time of the request.

**Type**: integer **Required**: False

### **TotalPieces**

The total number of pieces that must be processed to complete the import job. Each piece consists of an approximately equal portion of the endpoint definitions that are part of the import job.

**Type**: integer **Required**: False

### CreationDate

The date, in ISO 8601 format, when the import job was created.

**Type**: string **Required**: True

## CompletionDate

The date, in ISO 8601 format, when the import job was completed.

**Type**: string **Required**: False

## **Type**

The job type. This value is IMPORT for import jobs.

**Type**: string

Required: True

### **TotalFailures**

The total number of endpoint definitions that weren't processed successfully (failed) by the import job, typically because an error, such as a syntax error, occurred.

**Type**: integer **Required**: False

#### **TotalProcessed**

The total number of endpoint definitions that were processed by the import job.

**Type**: integer **Required**: False

### **Failures**

An array of entries, one for each of the first 100 entries that weren't processed successfully (failed) by the import job, if any.

**Type**: Array of type string

Required: False

### **Definition**

The resource settings that apply to the import job.

Type: ImportJobResource

Required: True

# ImportJobsResponse

Provides information about the status and settings of all the import jobs that are associated with an application or segment. An import job is a job that imports endpoint definitions from one or more files.

**REST API Reference** Amazon Pinpoint

#### Item

An array of responses, one for each import job that's associated with the application (Import Jobs resource) or segment (Segment Import Jobs resource).

**Type**: Array of type ImportJobResponse

Required: True

### NextToken

The string to use in a subsequent request to get the next page of results in a paginated response. This value is null if there are no additional pages.

Type: string

Required: False

# MessageBody

Provides information about an API request or response.

## RequestID

The unique identifier for the request or response.

Type: string

Required: False

## Message

The message that's returned from the API.

**Type**: string

Required: False

# See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

See also 583

## GetImportJobs

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# CreateImportJob

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **In-App Messages**

Use the InAppMessages resource to retrieve information about the in-app messages that have been sent to specific endpoints.

In-App Messages 584

# **URI**

/v1/apps/application-id/endpoints/endpoint-id/inappmessages

# **HTTP** methods

## **GET**

Operation ID: GetInAppMessages

Retrieves information about the in-app messages that have been sent to the requested endpoint.

## **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.
endpoint-id	String	True	The case insensiti ve unique identifie r for the endpoint. The identifier can't contain \$, { or }.

## **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

URI 585

## Responses

Status code	Response model	Description
200	InAppMessagesRespo nse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).

Status code	Response model	Description
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **OPTIONS**

Retrieves information about the communication requirements and options that are available for the In-App Template resource.

# **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.
endpoint-id	String	True	The case insensitive unique identifier for the endpoint.

# Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Response bodies**

## InAppMessagesResponse schema

```
{
  "InAppMessageCampaigns": [
      "CampaignId": "string",
      "TreatmentId": "string",
      "DailyCap": integer,
      "TotalCap": integer,
      "SessionCap": integer,
      "Priority": integer,
      "Schedule": {
        "QuietTime": {
          "Start": "string",
          "End": "string"
        },
        "EventFilter": {
          "Dimensions": {
            "EventType": {
              "DimensionType": enum,
              "Values": [
                "string"
              ]
            },
            "Attributes": {
            },
            "Metrics": {
            }
          "FilterType": enum
        },
        "EndDate": "string"
      },
      "InAppMessage": {
        "Layout": enum,
        "Content": [
          {
            "HeaderConfig": {
              "Header": "string",
              "TextColor": "string",
              "Alignment": enum
            },
            "BackgroundColor": "string",
            "BodyConfig": {
```

```
"Body": "string",
  "TextColor": "string",
  "Alignment": enum
},
""ImageUrl": "string",
"PrimaryBtn": {
  "DefaultConfig": {
    "Text": "string",
    "ButtonAction": enum,
    "Link": "string",
    "TextColor": "string",
    "BackgroundColor": "string",
    "BorderRadius": integer
 },
  "Web": {
    "ButtonAction": enum,
    "Link": "string"
 },
  "IOS": {
    "ButtonAction": enum,
    "Link": "string"
 },
  "Android": {
    "ButtonAction": enum,
    "Link": "string"
 }
},
"SecondaryBtn": {
  "DefaultConfig": {
    "Text": "string",
    "ButtonAction": enum,
    "Link": "string",
    "TextColor": "string",
    "BackgroundColor": "string",
    "BorderRadius": integer
 },
  "Web": {
    "ButtonAction": enum,
    "Link": "string"
 },
  "IOS": {
    "ButtonAction": enum,
    "Link": "string"
 },
```

## MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

## **AttributeDimension**

Specifies attribute-based criteria for including or excluding endpoints from a segment.

# AttributeType

The type of segment dimension to use. Valid values are:

- INCLUSIVE endpoints that have attributes matching the values are included in the segment.
- EXCLUSIVE endpoints that have attributes matching the values are excluded from the segment.
- CONTAINS endpoints that have attributes' substrings match the values are included in the segment.
- BEFORE endpoints with attributes read as ISO\_INSTANT datetimes before the value are included in the segment.
- AFTER endpoints with attributes read as ISO\_INSTANT datetimes after the value are included in the segment.

 BETWEEN – endpoints with attributes read as ISO\_INSTANT datetimes between the values are included in the segment.

• 0N – endpoints with attributes read as ISO\_INSTANT dates on the value are included in the segment. Time is ignored in this comparison.

**Type**: string **Required**: False

Values: INCLUSIVE | EXCLUSIVE | CONTAINS | BEFORE | AFTER | BETWEEN |

NOT\_BETWEEN | ON

#### **Values**

The criteria values to use for the segment dimension. Depending on the value of the AttributeType property, endpoints are included or excluded from the segment if their attribute values match the criteria values.

**Type**: Array of type string

Required: True

# CampaignEventFilter

Specifies the settings for events that cause a campaign to be sent.

### **Dimensions**

The dimension settings of the event filter for the campaign.

**Type**: EventDimensions

Required: True

### **FilterType**

The type of event that causes the campaign to be sent. Valid values are: SYSTEM, sends the campaign when a system event occurs; and, ENDPOINT, sends the campaign when an endpoint event (Events resource) occurs.

**Type**: string **Required**: True

Values: SYSTEM | ENDPOINT | USER

## **DefaultButtonConfiguration**

Information about the default behavior for a button that appears in an in-app message. You can optionally add button configurations that specifically apply to iOS, Android, or web browser users.

### **Text**

The text that appears on a button in an in-app message.

**Type**: string **Required**: True

#### **ButtonAction**

The action that occurs when a recipient chooses a button in an in-app message. You can specify one of the following:

- LINK A link to a web destination.
- DEEP\_LINK A link to a specific page in an application.
- CLOSE Dismisses the message.

**Type**: string **Required**: True

Values: LINK | DEEP\_LINK | CLOSE

#### Link

The destination (such as a URL) for a button.

**Type**: string **Required**: False

## **TextColor**

The color of the body text in a button, expressed as a string consisting of a hex color code (such as "#000000" for black).

**Type**: string **Required**: False

## BackgroundColor

The background color of a button, expressed as a string consisting of a hex color code (such as "#000000" for black).

**Type**: string **Required**: False

#### **BorderRadius**

The border radius of a button.

**Type**: integer **Required**: False

### **EventDimensions**

Specifies the dimensions for an event filter that determines when a campaign is sent or a journey activity is performed.

## **EventType**

The name of the event that causes the campaign to be sent or the journey activity to be performed. This can be a standard event that Amazon Pinpoint generates, such as \_email.delivered or \_custom.delivered. For campaigns, this can also be a custom event that's specific to your application. For information about standard events, see <a href="Streaming Amazon Pinpoint Events">Streaming Amazon Pinpoint Events</a> in the Amazon Pinpoint Developer Guide.

Type: <u>SetDimension</u>
Required: False

### **Attributes**

One or more custom attributes that your application reports to Amazon Pinpoint. You can use these attributes as selection criteria when you create an event filter.

**Type**: object **Required**: False

### **Metrics**

One or more custom metrics that your application reports to Amazon Pinpoint. You can use these metrics as selection criteria when you create an event filter.

**Type**: object **Required**: False

## InAppCampaignSchedule

## QuietTime

The start and end times that define a time range when messages aren't sent to endpoints.

Type: QuietTime Required: False

### **EventFilter**

The type of event that causes the campaign to be sent, if the value of the Frequency property is EVENT.

Type: CampaignEventFilter

Required: False

### **EndDate**

A timestamp that represents the latest time, in ISO 8601 format, that the campaign can be sent to endpoints.

**Type**: string **Required**: False

# InAppMessage

### Layout

A string that describes how the in-app message will appear. You can specify one of the following:

- BOTTOM\_BANNER a message that appears as a banner at the bottom of the page.
- TOP\_BANNER a message that appears as a banner at the top of the page.
- OVERLAYS a message that covers entire screen.
- MOBILE\_FEED a message that appears in a window in front of the page.
- MIDDLE\_BANNER a message that appears as a banner in the middle of the page.
- CAROUSEL a scrollable layout of up to five unique messages.

**Type**: string **Required**: False

Values: BOTTOM\_BANNER | TOP\_BANNER | OVERLAYS | MOBILE\_FEED | MIDDLE\_BANNER

| CAROUSEL

### Content

Contains information about the configuration of an in-app message template.

**Type**: Array of type InAppMessageContent

Required: False

## CustomConfig

An object that contains custom data (in the form of key-value pairs) that is included in the in-app messaging payload.

**Type**: object **Required**: False

# InAppMessageBodyConfig

Configuration information related to the main body text of an in-app message.

### **Body**

The main body text of the message.

**Type**: string **Required**: True

### **TextColor**

The color of the body text, expressed as a string consisting of a hex color code (such as "#000000" for black).

**Type**: string **Required**: False

## **Alignment**

The text alignment of the main body text of the message.

**Type**: string **Required**: True

Values: LEFT | CENTER | RIGHT

# InAppMessageButton

Configuration information for a button that appears in an in-app message.

# **DefaultConfig**

An object that defines the default behavior for a button in an in-app message.

Type: DefaultButtonConfiguration

Required: False

### Web

An object that defines the default behavior for a button in in-app messages for web applications.

**Type**: OverrideButtonConfiguration

Required: False

### IOS

An object that defines the default behavior for a button in in-app messages sent to iOS devices.

Type: OverrideButtonConfiguration

Required: False

### **Android**

An object that defines the default behavior for a button in in-app messages sent to Android.

Type: OverrideButtonConfiguration

**Required**: False

# InAppMessageCampaign

## CampaignId

The unique identifier for the campaign that the in-app message applies to.

Type: string

Required: False

### **TreatmentId**

The unique identifier for the campaign treatment. A treatment is a variation of a campaign that's used for A/B testing.

Type: string

Required: False

## **DailyCap**

The maximum number of times any in-app message can be shown to the user in a 24-hour period.

**Type**: integer

Required: False

### **TotalCap**

The maximum number of times an in-app message can be shown to the user.

**Type**: integer **Required**: False

## **SessionCap**

The maximum number of times an in-app message can be shown to the user during a single session in the application.

**Type**: integer **Required**: False

## **Priority**

An integer between 1 and 5, inclusive, that represents the priority of the campaign, with 1 being the highest priority and 5 being the lowest. This value is used to determine the order in which messages are displayed to the recipient if there are multiple messages scheduled to be displayed at the same time.

**Type**: integer **Required**: False

### **Schedule**

The schedule settings for the campaign.

Type: InAppCampaignSchedule

Required: False

## InAppMessage

Specifies the settings for a message that's sent to users of an application (an in-app message).

Type: InAppMessage

Required: False

# InAppMessageContent

Configuration information related to an in-app message.

### HeaderConfig

An object that contains configuration information about the header or title text of the in-app message.

Type: InAppMessageHeaderConfig

Required: False

### BackgroundColor

The background color for an in-app message banner, expressed as a string consisting of a hex color code (such as "#000000" for black).

Type: string

Required: False

### **BodyConfig**

An object that contains configuration information about the header or title text of the in-app message.

Type: InAppMessageBodyConfig

Required: False

### ImageUrl

The URL of the image that appears on an in-app message banner.

Type: string

Required: False

# PrimaryBtn

An object that contains configuration information about the primary button in an in-app message.

Type: InAppMessageButton

Required: False

### SecondaryBtn

An object that contains configuration information about the secondary button in an in-app message.

Type: InAppMessageButton

Required: False

# InAppMessageHeaderConfig

Configuration information related to the message header for an in-app message.

#### Header

The text that appears in the header or title of the message.

Type: string

**Required**: True

#### **TextColor**

The color of the body text, expressed as a string consisting of a hex color code (such as "#000000" for black).

Type: string

Required: False

### **Alignment**

The text alignment of the title of the message.

**Type**: string

Required: True

Values: LEFT | CENTER | RIGHT

# InAppMessagesResponse

Object that contains information about in-app messages.

### InAppMessageCampaigns

A list of in-app message campaigns.

Type: Array of type InAppMessageCampaign

Required: False

# MessageBody

Provides information about an API request or response.

#### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

#### Message

The message that's returned from the API.

**Type**: string **Required**: False

#### MetricDimension

Specifies metric-based criteria for including or excluding endpoints from a segment. These criteria derive from custom metrics that you define for endpoints.

### ComparisonOperator

The operator to use when comparing metric values. Valid values are: GREATER\_THAN, LESS\_THAN, GREATER\_THAN\_OR\_EQUAL, LESS\_THAN\_OR\_EQUAL, and EQUAL.

Type: string

Required: True

#### Value

The value to compare.

**Type**: number **Required**: True

### OverrideButtonConfiguration

Configuration information related to the configuration of a button with settings that are specific to a certain device type.

#### **ButtonAction**

The action that occurs when a recipient chooses a button in an in-app message. You can specify one of the following:

- LINK A link to a web destination.
- DEEP\_LINK A link to a specific page in an application.
- CLOSE Dismisses the message.

**Type**: string **Required**: False

Values: LINK | DEEP\_LINK | CLOSE

#### Link

The destination (such as a URL) for a button.

**Type**: string **Required**: False

# QuietTime

Specifies the start and end times that define a time range when messages aren't sent to endpoints.

#### Start

The specific time when quiet time begins. This value has to use 24-hour notation and be in HH:MM format, where HH is the hour (with a leading zero, if applicable) and MM is the minutes. For example, use 02:30 to represent 2:30 AM, or 14:30 to represent 2:30 PM.

**Type**: string **Required**: False

#### End

The specific time when quiet time ends. This value has to use 24-hour notation and be in HH:MM format, where HH is the hour (with a leading zero, if applicable) and MM is the minutes. For example, use 02:30 to represent 2:30 AM, or 14:30 to represent 2:30 PM.

**Type**: string **Required**: False

### **SetDimension**

Specifies the dimension type and values for a segment dimension.

## DimensionType

The type of segment dimension to use. Valid values are: INCLUSIVE, endpoints that match the criteria are included in the segment; and, EXCLUSIVE, endpoints that match the criteria are excluded from the segment.

**Type**: string **Required**: False

Values: INCLUSIVE | EXCLUSIVE

#### **Values**

The criteria values to use for the segment dimension. Depending on the value of the DimensionType property, endpoints are included or excluded from the segment if their values match the criteria values.

Type: Array of type string

Required: True

### See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## **GetInAppMessages**

- AWS Command Line Interface
- · AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- · AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **In-App Template**

An *in-app messaging template* is a type of message template that contains content and settings that you can define, save, and reuse in messages that you send to users of your applications.

When you create an in-app messaging template, you specify the layout of the message and the content contained in the message. You can also change the color and position of the message text, add buttons to the message, and add images to the message.

The In-App Template resource represents the repository of in-app messaging templates that are associated with your Amazon Pinpoint account. You can use this resource to create, retrieve, update, or delete a message template for messages that you send through the in-app messaging channel.

Amazon Pinpoint supports versioning for all types of message templates. When you use the In-App Template resource to work with a template, you can use supported parameters to specify

See also 604

whether your request applies to only a specific version of the template or to the overall template. For example, if you update a template, you can specify whether you want to save your updates as a new version of the template or save them to the latest existing version of the template. To retrieve information about all the versions of a template, use the Template Versions resource.

# **URI**

/v1/templates/template-name/inapp

# **HTTP** methods

### **GET**

Operation ID: GetInAppTemplate

Retrieves the content and configuration of an in-app message template.

### **Path parameters**

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can contain a maximum of 128 characters. The characters can be alphanumeric characters, underscor es (_), or hyphens (-). Template names are case sensitive.

URI 605

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# **Query parameters**

Name	Туре	Required	Description
version	String	False	The unique identifie r for the version of the message template to update, retrieve information about, or delete. To retrieve identifiers and other informati on for all the versions of a template, use the Template Versions resource.
			If specified, this value must match the identifier for an existing template version. If specified for an update operation, this value must match the identifier for the latest existing version of the template.

Name Type Required Description

This restriction helps ensure that race conditions don't occur.

If you don't specify a value for this parameter, Amazon Pinpoint does the following:

- For a get operation , retrieves informati on about the active version of the template.
- For an update operation, saves the updates to (overwrites) the latest existing version of the template, if the create-ne w-version parameter isn't used or is set to false.
- For a delete operation, deletes the template, including all versions of the template.

# Responses

Status code	Response model	Description
200	<pre>InAppTemplateRespo nse</pre>	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).

Status code	Response model	Description
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **POST**

Operation ID: CreateInAppTemplate

Creates a new in-app message template.

# Path parameters

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can contain a maximum of 128 characters. The characters can be alphanumeric characters, underscor es (_), or hyphens (-). Template names are case sensitive.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which
			content types,

Name	Туре	Required	Description
			expressed as MIME
			types, the client
			understands.

# Responses

Status code	Response model	Description
201	TemplateCreateMess ageBody	The request succeeded and the specified resource was created.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
409	<u>MessageBody</u>	The request failed due to a conflict with the current state of the specified resource (ConflictException).
429	MessageBody	The request failed because too many requests were sent during a certain amount of

Status code	Response model	Description
		time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **PUT**

Operation ID: UpdateInAppTemplate

Updates an existing in-app message template.

# Path parameters

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can contain a maximum of 128 characters. The characters can be alphanumeric characters, underscor es (_), or hyphens (-). Template names are case sensitive.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# **Query parameters**

Name	Туре	Required	Description
create-new- version	String	False	Specifies whether to save the updates as a new version of the message template.  Valid values are:  true, save the updates as a new version; and, false, save the updates to (overwrite) the latest existing version of the template.
			If you don't specify a value for this parameter, Amazon Pinpoint saves the updates to (overwrites) the latest existing version of the template. If you specify a value of true for this parameter, don't

Name Type Required Description

specify a value
for the version
parameter. Otherwise
, an error will occur.

Name	Туре	Required	Description
version	String	False	The unique identifie r for the version of the message template to update, retrieve information about, or delete. To retrieve identifiers and other informati on for all the versions of a template, use the Template Versions resource.  If specified, this value must match the identifier for an existing template version. If specified for an update operation, this value must match the identifier for the latest existing version of the template. This restriction helps ensure that race conditions don't occur.
			If you don't specify a value for this parameter, Amazon Pinpoint does the following:

Name	Туре	Required	Description
			<ul> <li>For a get operation , retrieves informati on about the active version of the template.</li> </ul>
			• For an update operation, saves the updates to (overwrites) the latest existing version of the template, if the create-ne w-version parameter isn't used or is set to false.
			<ul> <li>For a delete         operation, deletes         the template,         including all         versions of the         template.</li> </ul>

# Responses

Status code	Response model	Description
202	<u>MessageBody</u>	The request was accepted for processing. Processing may not be complete.
400	MessageBody	The request contains a syntax error (BadRequestException).

Status code	Response model	Description
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **DELETE**

**Operation ID:** DeleteInAppTemplate

Deletes an existing in-app message template.

# **Path parameters**

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can contain a maximum of 128 characters. The characters can be alphanumeric characters, underscor es (_), or hyphens (-). Template names are case sensitive.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# **Query parameters**

Name	Туре	Required	Description
version	String	False	The unique identifie r for the version of the message

Name Type Required Description

template to update, retrieve information about, or delete. To retrieve identifiers and other informati on for all the versions of a template, use the <u>Template</u>
Versionsresource.

If specified, this value must match the identifier for an existing template version. If specified for an update operation, this value must match the identifier for the latest existing version of the template. This restriction helps ensure that race conditions don't occur.

If you don't specify a value for this parameter, Amazon Pinpoint does the following:

 For a get operation , retrieves informati on about the active

Name	Туре	Required	Description
			version of the template.
			• For an update operation, saves the updates to (overwrites) the latest existing version of the template, if the create-ne w-version parameter isn't used or is set to false.
			<ul> <li>For a delete operation, deletes the template, including all versions of the template.</li> </ul>

# Responses

Status code	Response model	Description
202	MessageBody	The request was accepted for processing. Processing may not be complete.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	MessageBody	The request was denied because access to the specified resource is

Status code	Response model	Description
		forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **OPTIONS**

Retrieves information about the communication requirements and options that are available for the In-App Template resource.

# **Path parameters**

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can contain a maximum of 128 characters. The characters can be alphanumeric characters, underscor es (_), or hyphens (-). Template names are case sensitive.

# Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Request bodies**

### **POST schema**

```
{
  "tags": {
  },
  "TemplateDescription": "string",
  "Layout": enum,
  "Content": [
    {
```

```
"HeaderConfig": {
  "Header": "string",
  "TextColor": "string",
  "Alignment": enum
},
"BackgroundColor": "string",
"BodyConfig": {
  "Body": "string",
  "TextColor": "string",
  "Alignment": enum
},
""ImageUrl": "string",
"PrimaryBtn": {
  "DefaultConfig": {
    "Text": "string",
    "ButtonAction": enum,
    "Link": "string",
    "TextColor": "string",
    "BackgroundColor": "string",
    "BorderRadius": integer
  },
  "Web": {
    "ButtonAction": enum,
    "Link": "string"
  },
  "IOS": {
    "ButtonAction": enum,
    "Link": "string"
  },
  "Androi<u>d</u>": {
    "ButtonAction": enum,
    "Link": "string"
  }
},
"SecondaryBtn": {
  "DefaultConfig": {
    "Text": "string",
    "ButtonAction": enum,
    "Link": "string",
    "TextColor": "string",
    "BackgroundColor": "string",
    "BorderRadius": integer
  },
  "Web": {
```

```
"ButtonAction": enum,
          "Link": "string"
        },
        "IOS": {
          "ButtonAction": enum,
          "Link": "string"
        },
        "Android": {
          "ButtonAction": enum,
          "Link": "string"
        }
      }
    }
  ],
  "CustomConfig": {
  }
}
```

#### **PUT schema**

```
"tags": {
},
"TemplateDescription": "string",
"Layout": enum,
"Content": [
  {
    "HeaderConfig": {
      ""Header": "string",
      "TextColor": "string",
      "Alignment": enum
    },
    "BackgroundColor": "string",
    "BodyConfig": {
      "Body": "string",
      "TextColor": "string",
      "Alignment": enum
    },
    ""ImageUrl": "string",
    "PrimaryBtn": {
      "DefaultConfig": {
        "Text": "string",
        "ButtonAction": enum,
```

```
"Link": "string",
        "TextColor": "string",
        "BackgroundColor": "string",
        "BorderRadius": integer
      },
      "Web": {
        "ButtonAction": enum,
        "Link": "string"
      },
      "IOS": {
        "ButtonAction": enum,
        "Link": "string"
      },
      "Android": {
        "ButtonAction": enum,
        "Link": "string"
      }
    },
    "SecondaryBtn": {
      "DefaultConfig": {
        "Text": "string",
        "ButtonAction": enum,
        "Link": "string",
        "TextColor": "string",
        "BackgroundColor": "string",
        "BorderRadius": integer
      },
      "Web": {
        "ButtonAction": enum,
        "Link": "string"
      },
      "IOS": {
        "ButtonAction": enum,
        "Link": "string"
      },
      "Android": {
        "ButtonAction": enum,
        "Link": "string"
      }
    }
  }
],
"CustomConfig": {
}
```

}

# **Response bodies**

### InAppTemplateResponse schema

```
{
  "CreationDate": "string",
  "LastModifiedDate": "string",
  "TemplateType": enum,
  "TemplateName": "string",
  "TemplateDescription": "string",
  "Version": "string",
  "tags": {
  },
  "Arn": "string",
  "Layout": enum,
  "Content": [
    {
      "HeaderConfig": {
        "Header": "string",
        "TextColor": "string",
        "Alignment": enum
      },
      "BackgroundColor": "string",
      "BodyConfig": {
        "Body": "string",
        "TextColor": "string",
        "Alignment": enum
      },
      "ImageUrl": "string",
      "PrimaryBtn": {
        "DefaultConfig": {
          "Text": "string",
          "ButtonAction": enum,
          "Link": "string",
          "TextColor": "string",
          "BackgroundColor": "string",
          "BorderRadius": integer
        },
        "Web": {
          "ButtonAction": enum,
          "Link": "string"
```

```
},
        "IOS": {
          "ButtonAction": enum,
          "Link": "string"
        },
        "Android": {
          "ButtonAction": enum,
          "Link": "string"
        }
      },
      "SecondaryBtn": {
        "DefaultConfig": {
          "Text": "string",
          "ButtonAction": enum,
          "Link": "string",
          "TextColor": "string",
          "BackgroundColor": "string",
          "BorderRadius": integer
        },
        "Web": {
          "ButtonAction": enum,
          "Link": "string"
        },
        "IOS": {
          "ButtonAction": enum,
          "Link": "string"
        },
        "Android": {
          "ButtonAction": enum,
          "Link": "string"
        }
      }
    }
  ],
  "CustomConfig": {
  }
}
```

### TemplateCreateMessageBody schema

```
{
    "RequestID": "string",
    "Message": "string",
```

```
""Arn": "string"
}
```

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

# DefaultButtonConfiguration

Information about the default behavior for a button that appears in an in-app message. You can optionally add button configurations that specifically apply to iOS, Android, or web browser users.

#### **Text**

The text that appears on a button in an in-app message.

**Type**: string **Required**: True

#### **ButtonAction**

The action that occurs when a recipient chooses a button in an in-app message. You can specify one of the following:

- LINK A link to a web destination.
- DEEP\_LINK A link to a specific page in an application.
- CLOSE Dismisses the message.

Type: string

Required: True

Values: LINK | DEEP\_LINK | CLOSE

#### Link

The destination (such as a URL) for a button.

**Type**: string **Required**: False

#### **TextColor**

The color of the body text in a button, expressed as a string consisting of a hex color code (such as "#000000" for black).

**Type**: string **Required**: False

## BackgroundColor

The background color of a button, expressed as a string consisting of a hex color code (such as "#000000" for black).

**Type**: string **Required**: False

#### **BorderRadius**

The border radius of a button.

**Type**: integer **Required**: False

# InAppMessageBodyConfig

Configuration information related to the main body text of an in-app message.

### **Body**

The main body text of the message.

**Type**: string **Required**: True

#### **TextColor**

The color of the body text, expressed as a string consisting of a hex color code (such as "#000000" for black).

**Type**: string **Required**: False

# **Alignment**

The text alignment of the main body text of the message.

**Type**: string **Required**: True

Values: LEFT | CENTER | RIGHT

## InAppMessageButton

Configuration information for a button that appears in an in-app message.

### **DefaultConfig**

An object that defines the default behavior for a button in an in-app message.

Type: <u>DefaultButtonConfiguration</u>

**Required**: False

#### Web

An object that defines the default behavior for a button in in-app messages for web applications.

**Type**: OverrideButtonConfiguration

Required: False

#### IOS

An object that defines the default behavior for a button in in-app messages sent to iOS devices.

Type: OverrideButtonConfiguration

Required: False

#### **Android**

An object that defines the default behavior for a button in in-app messages sent to Android.

**Type**: OverrideButtonConfiguration

Required: False

## InAppMessageContent

Configuration information related to an in-app message.

### HeaderConfig

An object that contains configuration information about the header or title text of the in-app message.

Type: InAppMessageHeaderConfig

Required: False

### BackgroundColor

The background color for an in-app message banner, expressed as a string consisting of a hex color code (such as "#000000" for black).

**Type**: string **Required**: False

### **BodyConfig**

An object that contains configuration information about the header or title text of the in-app message.

Type: InAppMessageBodyConfig

Required: False

### **ImageUrl**

The URL of the image that appears on an in-app message banner.

Type: string

Required: False

### **PrimaryBtn**

An object that contains configuration information about the primary button in an in-app message.

**Type**: InAppMessageButton

Required: False

### SecondaryBtn

An object that contains configuration information about the secondary button in an in-app message.

Type: InAppMessageButton

Required: False

# InAppMessageHeaderConfig

Configuration information related to the message header for an in-app message.

#### Header

The text that appears in the header or title of the message.

**Type**: string **Required**: True

#### **TextColor**

The color of the body text, expressed as a string consisting of a hex color code (such as "#000000" for black).

**Type**: string **Required**: False

## **Alignment**

The text alignment of the title of the message.

**REST API Reference** Amazon Pinpoint

**Type**: string Required: True

Values: LEFT | CENTER | RIGHT

# **InAppTemplateRequest**

Specifies the content and settings for a message template that can be used to send in-app messages.

#### tags



#### Note

As of 22-05-2023 the tags attribute has been deprecated. After this date any value in the PUT UpdateInAppTemplate tags attribute is not processed and an error code is not returned. The POST CreateInAppTemplate tags attribute is processed. Use the Tags resource to add or modify tags.

(Deprecated) A string-to-string map of key-value pairs that defines the tags to associate with the message template. Each tag consists of a required tag key and an associated tag value.

Type: object Required: False

### **TemplateDescription**

An optional description of the in-app template.

**Type**: string Required: False

### Layout

A string that determines the appearance of the in-app message. You can specify one of the following:

• BOTTOM\_BANNER – a message that appears as a banner at the bottom of the page.

- TOP BANNER a message that appears as a banner at the top of the page.
- OVERLAYS a message that covers entire screen.
- MOBILE\_FEED a message that appears in a window in front of the page.
- MIDDLE\_BANNER a message that appears as a banner in the middle of the page.

• CAROUSEL – a scrollable layout of up to five unique messages.

**Type**: string **Required**: False

Values: BOTTOM\_BANNER | TOP\_BANNER | OVERLAYS | MOBILE\_FEED | MIDDLE\_BANNER

| CAROUSEL

#### Content

An object that contains information about the content of an in-app message, including its title and body text, text colors, background colors, images, buttons, and behaviors.

**Type**: Array of type InAppMessageContent

Required: False

### CustomConfig

Information about the custom data that is included in an in-app messaging payload.

**Type**: object **Required**: False

# InAppTemplateResponse

Provides information about the content and settings for an in-app message template.

#### CreationDate

The date, in ISO 8601 format, when the message template was created.

**Type**: string **Required**: True

#### LastModifiedDate

The date, in ISO 8601 format, when the message template was last modified.

**Type**: string **Required**: True

### **TemplateType**

The type of channel that the message template is designed for. For an in-app message template, this value is INAPP.

**Type**: string **Required**: True

Values: EMAIL | SMS | VOICE | PUSH | INAPP

### **TemplateName**

The name of the in-app message template.

**Type**: string **Required**: True

### **TemplateDescription**

A description of the message template.

**Type**: string **Required**: False

#### Version

The unique identifier, shown as an integer, of the active version of the message template, or the version of the template that you specified by using the version parameter in your request.

**Type**: string **Required**: False

#### tags

A string-to-string map of key-value pairs that identifies the tags that are associated with the message template. Each tag consists of a required tag key and an associated tag value.

**Type**: object **Required**: False

#### Arn

The Amazon Resource Name (ARN) of the message template.

**Type**: string **Required**: False

#### Layout

A string that determines the appearance of the in-app message. You can specify one of the following:

- BOTTOM BANNER a message that appears as a banner at the bottom of the page.
- TOP\_BANNER a message that appears as a banner at the top of the page.
- OVERLAYS a message that covers entire screen.
- MOBILE\_FEED a message that appears in a window in front of the page.
- MIDDLE BANNER a message that appears as a banner in the middle of the page.
- CAROUSEL a scrollable layout of up to five unique messages.

**Type**: string **Required**: False

Values: BOTTOM\_BANNER | TOP\_BANNER | OVERLAYS | MOBILE\_FEED | MIDDLE\_BANNER

| CAROUSEL

### Content

An array that contains configurtion information about the message, including title and body text, text colors, background colors, image URLs, and button configurations.

**Type**: Array of type InAppMessageContent

Required: False

### CustomConfig

An object that contains custom data (in the form of key-value pairs) that is included in the in-app messaging payload.

**Type**: object **Required**: False

## MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

#### Message

The message that's returned from the API.

**Type**: string **Required**: False

# OverrideButtonConfiguration

Configuration information related to the configuration of a button with settings that are specific to a certain device type.

#### **ButtonAction**

The action that occurs when a recipient chooses a button in an in-app message. You can specify one of the following:

- LINK A link to a web destination.
- DEEP\_LINK A link to a specific page in an application.

• CLOSE – Dismisses the message.

**Type**: string **Required**: False

Values: LINK | DEEP\_LINK | CLOSE

#### Link

The destination (such as a URL) for a button.

**Type**: string **Required**: False

## **TemplateCreateMessageBody**

### RequestID

**Type**: string **Required**: False

#### Message

**Type**: string **Required**: False

#### Arn

**Type**: string **Required**: False

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

See also 637

## **GetInAppTemplate**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

## CreateInAppTemplate

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

## **UpdateInAppTemplate**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++

See also 638

- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

## **DeleteInAppTemplate**

- AWS Command Line Interface
- · AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Journey**

A *journey* is an automated workflow that performs a series of messaging activities for an Amazon Pinpoint application. Each activity is a customizable component that specifies what causes the activity to occur, when the activity occurs, what the activity does, and which users the activity applies to. The paths and relationships between activities vary based on conditions and criteria that you define, such as specific user attributes and events.

The Journey resource represents an individual journey that's associated with an Amazon Pinpoint application. The information represented by this resource includes settings for the activities that comprise a journey, settings for the segments that define which users participate in journey activities, the messages that a journey sends, and the schedule that defines when a journey runs.

Journey 639

You can use this resource to retrieve information about, update, or delete a journey. To create a journey, use the Journeys resource.

## **URI**

/v1/apps/application-id/journeys/journey-id

## **HTTP** methods

## **GET**

## Operation ID: GetJourney

Retrieves information about the status, configuration, and other settings for a journey.

### **Path parameters**

Name	Туре	Required	Description
journey-id	String	True	The unique identifier for the journey.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

URI 640

## Responses

Status code	Response model	Description
200	JourneyResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error,

Status code	Response model	Description
		exception, or failure (Internal
		ServerErrorException).

## **PUT**

# **Operation ID:** UpdateJourney

Updates the configuration and other settings for a journey.

# **Path parameters**

Name	Туре	Required	Description
journey-id	String	True	The unique identifier for the journey.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

## Responses

Status code	Response model	Description
200	JourneyResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	MessageBody	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
409	<u>MessageBody</u>	The request failed due to a conflict with the current state of the specified resource (ConflictException).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	MessageBody	The request failed because too many requests were sent during a certain amount of

Status code	Response model	Description
		time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **DELETE**

**Operation ID:** DeleteJourney

Deletes a journey from an application.

# **Path parameters**

Name	Туре	Required	Description
journey-id	String	True	The unique identifier for the journey.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME

Name	Туре	Required	Description
			types, the client understands.

# Responses

Status code	Response model	Description
200	JourneyResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of

Status code	Response model	Description
		time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Journey resource.

## **Path parameters**

Name	Туре	Required	Description
journey-id	String	True	The unique identifier for the journey.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## Responses

Status code	Response model	Description
200	None	The request succeeded.

## **Schemas**

## **Request bodies**

#### **PUT schema**

```
"Name": "string",
"Schedule": {
  "StartTime": "string",
  "EndTime": "string",
  "Timezone": "string"
},
"StartCondition": {
  "Description": "string",
  "EventStartCondition": {
    "EventFilter": {
      "Dimensions": {
        "EventType": {
          "DimensionType": enum,
          "Values": [
            "string"
          ]
        },
        "Attributes": {
        },
        "Metrics": {
        }
      },
      "FilterType": enum
    "SegmentId": "string"
  },
  "SegmentStartCondition": {
    "SegmentId": "string"
  }
},
"Limits": {
 "<u>DailyCap</u>": integer,
  "TotalCap": integer,
  "TimeframeCap": {
    "Days": integer,
    "Cap": integer
```

```
},
  "MessagesPerSecond": integer,
  "EndpointReentryCap": integer,
  "EndpointReentryInterval": "string"
},
"StartActivity": "string",
"Activities": {
},
"RefreshFrequency": "string",
"QuietTime": {
 "Start": "string",
 "End": "string"
},
"WaitForQuietTime": boolean,
"SendingSchedule": boolean,
"OpenHours": {
  "EMAIL": {
  },
  "<u>SMS</u>": {
  },
  "PUSH": {
 },
  "VOICE": {
  },
  "CUSTOM": {
  }
},
"ClosedDays": {
  "EMAIL": [
    {
      "Name": "string",
      "StartDateTime": "string",
      "EndDateTime": "string"
    }
  ],
  "SMS": [
    {
      "Name": "string",
      "StartDateTime": "string",
      "EndDateTime": "string"
    }
  ],
  "PUSH": [
```

```
"Name": "string",
        "StartDateTime": "string",
        "EndDateTime": "string"
      }
    ],
    "VOICE": [
        "Name": "string",
        "StartDateTime": "string",
        "EndDateTime": "string"
      }
    ],
    "CUSTOM": [
        "Name": "string",
        "StartDateTime": "string",
        "EndDateTime": "string"
      }
    ]
  },
  "RefreshOnSegmentUpdate": boolean,
  "LocalTime": boolean,
  "CreationDate": "string",
  "LastModifiedDate": "string",
  "State": enum,
  "TimezoneEstimationMethods": [
    enum
  ]
}
```

## **Response bodies**

### JourneyResponse schema

```
"Name": "string",
"Schedule": {
    "StartTime": "string",
    "EndTime": "string",
    "Timezone": "string"
},
"StartCondition": {
    "Description": "string",
```

```
"EventStartCondition": {
    "EventFilter": {
      "Dimensions": {
        "EventType": {
          "DimensionType": enum,
          "Values": [
            "string"
          ]
        },
        "Att<u>ributes</u>": {
        "Metrics": {
        }
      },
      "FilterType": enum
    "Segment<u>Id</u>": "string"
  },
  "SegmentStartCondition": {
    "SegmentId": "string"
  }
},
"Limits": {
  "DailyCap": integer,
  "TotalCap": integer,
  "TimeframeCap": {
    "Days": integer,
    "Cap": integer
  },
  "MessagesPerSecond": integer,
  "EndpointReentryCap": integer,
  "EndpointReentryInterval": "string"
},
"StartActivity": "string",
"Activities": {
},
"RefreshFrequency": "string",
"QuietTime": {
 "Start": "string",
  "End": "string"
},
"WaitForQuietTime": boolean,
"SendingSchedule": boolean,
"OpenHours": {
```

```
"EMAIL": {
  },
  "<u>SMS</u>": {
  },
  "<u>PUSH</u>": {
  },
  "VOICE": {
  },
  "CUSTOM": {
  }
},
"ClosedDays": {
  "EMAIL": [
      "Name": "string",
      "StartDateTime": "string",
      "EndDateTime": "string"
    }
  ],
  "SMS": [
      "Name": "string",
      "StartDateTime": "string",
      "EndDateTime": "string"
    }
  ],
  "PUSH": [
      "Name": "string",
      "StartDateTime": "string",
      "EndDateTime": "string"
    }
  ],
  "<u>VOICE</u>": [
      "Name": "string",
      "StartDateTime": "string",
      "EndDateTime": "string"
    }
  ],
  "CUSTOM": [
      "Name": "string",
      "StartDateTime": "string",
```

```
"EndDateTime": "string"
      }
    ]
  },
  "RefreshOnSegmentUpdate": boolean,
  "LocalTime": boolean,
  "CreationDate": "string",
  "LastModifiedDate": "string",
  "State": enum,
  "tags": {
  },
  "TimezoneEstimationMethods": [
    enum
  ],
  "Id": "string",
  "ApplicationId": "string"
}
```

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

## **Activity**

Specifies the configuration and other settings for an activity in a journey.

## **Description**

The custom description of the activity.

**Type**: string **Required**: False

### ConditionalSplit

The settings for a yes/no split activity. This type of activity sends participants down one of two paths in a journey, based on conditions that you specify.

**Type**: ConditionalSplitActivity

Required: False

#### **Holdout**

The settings for a holdout activity. This type of activity stops a journey for a specified percentage of participants.

Type: HoldoutActivity

**Required**: False

#### MultiCondition

The settings for a multivariate split activity. This type of activity sends participants down one of as many as five paths (including a default *Else* path) in a journey, based on conditions that you specify.

Type: MultiConditionalSplitActivity

Required: False

## RandomSplit

The settings for a random split activity. This type of activity randomly sends specified percentages of participants down one of as many as five paths in a journey, based on conditions that you specify.

**Type**: RandomSplitActivity

Required: False

#### Wait

The settings for a wait activity. This type of activity waits for a certain amount of time or until a specific date and time before moving participants to the next activity in a journey.

**Type**: WaitActivity

Required: False

#### **EMAIL**

The settings for an email activity. This type of activity sends an email message to participants.

Type: EmailMessageActivity

Required: False

#### **SMS**

The settings for an SMS activity. This type of activity sends a text message to participants.

**Type**: SMSMessageActivity

**Required**: False

#### **PUSH**

The settings for a push notification activity. This type of activity sends a push notification to participants.

**Type**: PushMessageActivity

Required: False

#### **CUSTOM**

The settings for a custom message activity. This type of activity calls an AWS Lambda function or web hook that sends messages to participants.

Type: CustomMessageActivity

Required: False

### **AttributeDimension**

Specifies attribute-based criteria for including or excluding endpoints from a segment.

### **AttributeType**

The type of segment dimension to use. Valid values are:

• INCLUSIVE – endpoints that have attributes matching the values are included in the segment.

- EXCLUSIVE endpoints that have attributes matching the values are excluded from the segment.
- CONTAINS endpoints that have attributes' substrings match the values are included in the segment.
- BEFORE endpoints with attributes read as ISO\_INSTANT datetimes before the value are included in the segment.
- AFTER endpoints with attributes read as ISO\_INSTANT datetimes after the value are included in the segment.
- BETWEEN endpoints with attributes read as ISO\_INSTANT datetimes between the values are included in the segment.
- 0N endpoints with attributes read as ISO\_INSTANT dates on the value are included in the segment. Time is ignored in this comparison.

**Type**: string **Required**: False

Values: INCLUSIVE | EXCLUSIVE | CONTAINS | BEFORE | AFTER | BETWEEN |

NOT\_BETWEEN | ON

#### **Values**

The criteria values to use for the segment dimension. Depending on the value of the AttributeType property, endpoints are included or excluded from the segment if their attribute values match the criteria values.

**Type**: Array of type string

**Required**: True

## **ClosedDays**

The time when a journey will not send messages. QuietTime should be configured first and SendingSchedule should be set to true.

#### **EMAIL**

Rules for the Email channel.

Type: Array of type ClosedDaysRule

Required: False

#### **SMS**

Rules for the SMS channel.

Type: Array of type ClosedDaysRule

Required: False

#### **PUSH**

Rules for the Push channel.

**Type**: Array of type ClosedDaysRule

Required: False

#### **VOICE**

Rules for the Voice channel.

**Type**: Array of type ClosedDaysRule

Required: False

#### **CUSTOM**

Rules for the Custom channel.

Type: Array of type ClosedDaysRule

Required: False

# ClosedDaysRule

Specifies the rule settings for when messages can't be sent.

#### Name

The name of the closed rule.

**Type**: string **Required**: True

#### **StartDateTime**

StartDateTime ISO 8601 format

**Type**: string **Required**: True

#### **EndDateTime**

EndDateTime ISO 8601 format

**Type**: string **Required**: True

### **Condition**

Specifies the conditions to evaluate for an activity in a journey, and how to evaluate those conditions.

#### **Conditions**

The conditions to evaluate for the activity.

**Type**: Array of type SimpleCondition

Required: False

### **Operator**

Specifies how to handle multiple conditions for the activity. For example, if you specify two conditions for an activity, whether both or only one of the conditions must be met for the activity to be performed.

**Type**: string **Required**: False

Values: ALL | ANY

## ConditionalSplitActivity

Specifies the settings for a yes/no split activity in a journey. This type of activity sends participants down one of two paths in a journey, based on conditions that you specify.



#### Note

To create yes/no split activities that send participants down different paths based on push notification events (such as Open or Received events), your mobile app has to specify the User ID and Endpoint ID values. For more information, see Integrating Amazon Pinpoint with your application in the Amazon Pinpoint Developer Guide.

#### **Condition**

The conditions that define the paths for the activity, and the relationship between the conditions.

**Type: Condition** Required: False

### **TrueActivity**

The unique identifier for the activity to perform if the conditions are met.

Type: string **Required**: False

### **FalseActivity**

The unique identifier for the activity to perform if the conditions aren't met.

**Type**: string Required: False

#### **EvaluationWaitTime**

The amount of time to wait before determining whether the conditions are met, or the date and time when Amazon Pinpoint determines whether the conditions are met.

Type: WaitTime Required: False

## CustomMessageActivity

The settings for a custom message activity. This type of activity calls an AWS Lambda function or web hook that sends messages to participants.

### MessageConfig

Specifies the message data included in a custom channel message that's sent to participants in a journey.

**Type**: JourneyCustomMessage

Required: False

### **NextActivity**

The unique identifier for the next activity to perform, after Amazon Pinpoint calls the AWS Lambda function or web hook.

Type: string

Required: False

### DeliveryUri

The destination to send the campaign or treatment to. This value can be one of the following:

- The name or Amazon Resource Name (ARN) of an AWS Lambda function to invoke to handle delivery of the campaign or treatment.
- The URL for a web application or service that supports HTTPS and can receive the message. The URL has to be a full URL, including the HTTPS protocol.

**Type**: string

Required: False

#### **EndpointTypes**

The types of endpoints to send the custom message to. Each valid value maps to a type of channel that you can associate with an endpoint by using the ChannelType property of an endpoint.

**Type**: Array of type string

Required: False

Values: PUSH | GCM | APNS | APNS\_SANDBOX | APNS\_VOIP | APNS\_VOIP\_SANDBOX |

ADM | SMS | VOICE | EMAIL | BAIDU | CUSTOM | IN\_APP

### **TemplateName**

The name of the custom message template to use for the message. If specified, this value must match the name of an existing message template.

**Type**: string **Required**: False

### **TemplateVersion**

The unique identifier for the version of the message template to use for the message. If specified, this value must match the identifier for an existing template version. To retrieve a list of versions and version identifiers for a template, use the Template Versions resource.

If you don't specify a value for this property, Amazon Pinpoint uses the *active version* of the template. The *active version* is typically the version of a template that's been most recently reviewed and approved for use, depending on your workflow. It isn't necessarily the latest version of a template.

**Type**: string **Required**: False

## **EmailMessageActivity**

Specifies the settings for an email activity in a journey. This type of activity sends an email message to participants.

### MessageConfig

Specifies the sender address for an email message that's sent to participants in the journey.

Type: JourneyEmailMessage

Required: False

### **NextActivity**

The unique identifier for the next activity to perform, after the message is sent.

**Type**: string **Required**: False

### **TemplateName**

The name of the email message template to use for the message. If specified, this value must match the name of an existing message template.

**Type**: string **Required**: False

### **TemplateVersion**

The unique identifier for the version of the email template to use for the message. If specified, this value must match the identifier for an existing template version. To retrieve a list of versions and version identifiers for a template, use the <u>Template Versions</u> resource.

If you don't specify a value for this property, Amazon Pinpoint uses the *active version* of the template. The *active version* is typically the version of a template that's been most recently reviewed and approved for use, depending on your workflow. It isn't necessarily the latest version of a template.

**Type**: string **Required**: False

#### **EventCondition**

Specifies the conditions to evaluate for an event that applies to an activity in a journey.

#### **Dimensions**

The dimensions for the event filter to use for the activity.

**Type:** EventDimensions

Required: False

### MessageActivity

The message identifier (message\_id) for the message to use when determining whether message events meet the condition.

**Type**: string **Required**: False

#### **EventDimensions**

Specifies the dimensions for an event filter that determines when a campaign is sent or a journey activity is performed.

## **EventType**

The name of the event that causes the campaign to be sent or the journey activity to be performed. This can be a standard event that Amazon Pinpoint generates, such as \_\_email.delivered or \_custom.delivered. For campaigns, this can also be a custom event that's specific to your application. For information about standard events, see <a href="Streaming Amazon Pinpoint Events">Streaming Amazon Pinpoint Events</a> in the Amazon Pinpoint Developer Guide.

Type: <u>SetDimension</u>
Required: False

#### **Attributes**

One or more custom attributes that your application reports to Amazon Pinpoint. You can use these attributes as selection criteria when you create an event filter.

**Type**: object **Required**: False

#### **Metrics**

One or more custom metrics that your application reports to Amazon Pinpoint. You can use these metrics as selection criteria when you create an event filter.

**Type**: object **Required**: False

#### **EventFilter**

Specifies the settings for an event that causes a campaign to be sent or a journey activity to be performed.

#### **Dimensions**

The dimensions for the event filter to use for the campaign or the journey activity.

**Type**: EventDimensions

**Required**: True

### **FilterType**

The type of event that causes the campaign to be sent or the journey activity to be performed. Valid values are: SYSTEM, sends the campaign or performs the activity when a system event occurs; and, ENDPOINT, sends the campaign or performs the activity when an endpoint event (Events resource) occurs.

**Type**: string **Required**: True

Values: SYSTEM | ENDPOINT | USER

### **EventStartCondition**

Specifies the settings for an event that causes a journey activity to start.

#### **EventFilter**

The EventFilter for defined for scheduling Event based Journey

Type: <u>EventFilter</u>
Required: False

### SegmentId

Accept only Endpoints events from this specific dynamic segmentId

**Type**: string **Required**: False

### **GPSCoordinates**

Specifies the GPS coordinates of a location.

#### Latitude

The latitude coordinate of the location.

**Type**: number **Required**: True

### Longitude

The longitude coordinate of the location.

**Type**: number **Required**: True

### **GPSPointDimension**

Specifies GPS-based criteria for including or excluding endpoints from a segment.

#### **Coordinates**

The GPS coordinates to measure distance from.

**Type:** GPSCoordinates

Required: True

## RangeInKilometers

The range, in kilometers, from the GPS coordinates.

Type: number

Required: False

# **HoldoutActivity**

Specifies the settings for a holdout activity in a journey. This type of activity stops a journey for a specified percentage of participants.

### Percentage

The percentage of participants who shouldn't continue the journey.

To determine which participants are held out, Amazon Pinpoint applies a probability-based algorithm to the percentage that you specify. Therefore, the actual percentage of participants who are held out may not be equal to the percentage that you specify.

**Type**: integer **Required**: True

### **NextActivity**

The unique identifier for the next activity to perform, after performing the holdout activity.

**Type**: string **Required**: False

## **JourneyCustomMessage**

Specifies the message content for a custom channel message that's sent to participants in a journey.

#### Data

The message content that's passed to an AWS Lambda function or to a web hook.

**Type**: string **Required**: False

## **JourneyEmailMessage**

Specifies the "From" address for an email message that's sent to participants in a journey.

#### **FromAddress**

The verified email address to send the email message from. The default address is the FromAddress specified for the email channel for the application.

**Type**: string **Required**: False

## **JourneyLimits**

Specifies limits on the messages that a journey can send and the number of times participants can enter a journey.

### **DailyCap**

The maximum number of messages that the journey can send to a single participant during a 24-hour period. The maximum value is 100.

**Type**: integer **Required**: False

## **TotalCap**

The maximum number of messages a journey can sent to a single endpoint. The maximum value is 100. If set to 0, this limit will not apply.

**Type**: integer **Required**: False

### **TimeframeCap**

The number of messages that an endpoint can receive during the specified timeframe.

**Type**: JourneyTimeframeCap

Required: False

### MessagesPerSecond

The maximum number of messages that the journey can send each second.

**Type**: integer **Required**: False

### **EndpointReentryCap**

The maximum number of times that a participant can enter the journey. The maximum value is 100. To allow participants to enter the journey an unlimited number of times, set this value to 0.

**Type**: integer **Required**: False

### EndpointReentryInterval

Minimum time that must pass before an endpoint can re-enter a given journey.

Type: string

Required: False

## JourneyPushMessage

Specifies the message configuration for a push notification that's sent to participants in a journey.

#### **TimeToLive**

The number of seconds that the push notification service should keep the message, if the service is unable to deliver the notification the first time. This value is converted to an expiration value when it's sent to a push notification service. If this value is 0, the service treats the notification as if it expires immediately and the service doesn't store or try to deliver the notification again.

This value doesn't apply to messages that are sent through the Amazon Device Messaging (ADM) service.

**Type**: string

Required: False

# **JourneyResponse**

Provides information about the status, configuration, and other settings for a journey.

#### Name

The name of the journey.

**Type**: string

Required: False

### Schedule

The schedule settings for the journey.

Type: JourneySchedule

Required: False

### **StartCondition**

The segment that defines which users are participants in the journey.

**Type: StartCondition** 

Required: False

### Limits

The messaging and entry limits for the journey.

**Type:** JourneyLimits

Required: False

## **StartActivity**

The unique identifier for the first activity in the journey.

Type: string

**Required**: False

#### **Activities**

A map that contains a set of Activity objects, one object for each activity in the journey. For each Activity object, the key is the unique identifier (string) for an activity and the value is the settings for the activity.

**Type**: object **Required**: False

### RefreshFrequency

The frequency with which Amazon Pinpoint evaluates segment and event data for the journey, as a duration in ISO 8601 format.

**Type**: string

**Required**: False

#### QuietTime

The quiet time settings for the journey. Quiet time is a specific time range when a journey doesn't send messages to participants, if all the following conditions are met:

- The EndpointDemographic. Timezone property of the endpoint for the participant is set to a valid value.
- The current time in the participant's time zone is later than or equal to the time specified by the QuietTime. Start property for the journey.
- The current time in the participant's time zone is earlier than or equal to the time specified by the QuietTime. End property for the journey.

If any of the preceding conditions isn't met, the participant will receive messages from the journey, even if quiet time is enabled.

Type: QuietTime
Required: False

### WaitForQuietTime

Indicates whether endpoints in quiet hours should enter a wait activity until quiet hours have elapsed.

**Type**: boolean **Required**: False

### SendingSchedule

Indicates if journey has Advance Quiet Time enabled. This flag should be set to true in order to allow using OpenHours and ClosedDays.

**Type**: boolean **Required**: False

### **OpenHours**

The time when a journey can send messages. QuietTime should be configured first and SendingSchedule should be set to true.

Type: OpenHours
Required: False

### ClosedDays

The time when a journey will not send messages. QuietTime should be configured first and SendingSchedule should be set to true.

Type: <u>ClosedDays</u> Required: False

## RefreshOn Segment Update

Indicates whether the journey participants should be refreshed when a segment is updated.

**Type**: boolean **Required**: False

#### LocalTime

Specifies whether the journey's scheduled start and end times use each participant's local time. If this value is true, the schedule uses each participant's local time.

**Type**: boolean **Required**: False

#### CreationDate

The date, in ISO 8601 format, when the journey was created.

**Type**: string **Required**: False

#### LastModifiedDate

The date, in ISO 8601 format, when the journey was last modified.

**Type**: string **Required**: False

#### **State**

The current status of the journey. Possible values are:

- DRAFT The journey is being developed and hasn't been published yet.
- ACTIVE The journey has been developed and published. Depending on the journey's schedule, the journey may currently be running or scheduled to start running at a later time. If a journey's status is ACTIVE, you can't add, change, or remove activities from it.
- COMPLETED The journey has been published and has finished running. All participants have entered the journey and no participants are waiting to complete the journey or any activities in the journey.
- CANCELLED The journey has been stopped. If a journey's status is CANCELLED, you can't add, change, or remove activities or segment settings from the journey.
- CLOSED The journey has been published and has started running. It may have also passed
  its scheduled end time, or passed its scheduled start time and a refresh frequency hasn't been

**REST API Reference** Amazon Pinpoint

specified for it. If a journey's status is CLOSED, you can't add participants to it, and no existing participants can enter the journey for the first time. However, any existing participants who are currently waiting to start an activity may continue the journey.



#### Note

A journey in the CLOSED state is still counted against the **Maximum number of active** journeys quota. For more information see Journey quotas.

Type: string Required: False

Values: DRAFT | ACTIVE | PAUSED | COMPLETED | CANCELLED | CLOSED |

PENDING APPROVAL

### tags

This object is not used or supported.

**Type**: object Required: False

#### **TimezoneEstimationMethods**

An array of time zone estimation methods, if any, to use for determining an Endpoints time zone if the Endpoint does not have a value for the Demographic. Timezone attribute.

- PHONE\_NUMBER A time zone is estimated based on the Endpoint.Location.Country and Endpoint.Address.
- POSTAL\_CODE A time zone is estimated based on the Endpoint.Location.Country and Endpoint.Location.PostalCode.



### Note

POSTAL\_CODE estimation is only supported in the United States, United Kingdom, Australia, New Zealand, Canada, France, Italy, Spain, Germany and in regions where Amazon Pinpoint is available.

• Both - A time zone is estimated based on the Endpoint.Location.Country, Endpoint.Address and Endpoint.Location.PostalCode.

Type: Array of type string

Required: False

Values: PHONE\_NUMBER | POSTAL\_CODE

#### Id

The unique identifier for the journey.

**Type**: string **Required**: True

### **ApplicationId**

The unique identifier for the application that the journey applies to.

**Type**: string **Required**: True

## **JourneySMSMessage**

Specifies the sender ID and message type for an SMS message that's sent to participants in a journey.

#### SenderId

The sender ID to display as the sender of the message on a recipient's device. Support for sender IDs varies by country. For more information, see <u>Supported Countries and Regions</u> in the Amazon Pinpoint User Guide.

**Type**: string **Required**: False

### OriginationNumber

The number to send the SMS message from. The phone number that you specify must exist in your Amazon Pinpoint account—you can't pass an arbitrary phone number. If you want to use a sender ID to send your message, omit this parameter and use SenderId instead.

**Type**: string **Required**: False

### MessageType

The SMS message type. Valid values are TRANSACTIONAL (for messages that are critical or time-sensitive, such as a one-time passwords) and PROMOTIONAL (for messsages that aren't critical or time-sensitive, such as marketing messages).

**Type**: string **Required**: False

Values: TRANSACTIONAL | PROMOTIONAL

## **EntityId**

A registered Entity ID (currently only used when sending messages to recipients in India).

**Type**: string **Required**: False

### TemplateId

A registered Template ID (currently only used when sending messages to recipients in India).

**Type**: string **Required**: False

## **JourneySchedule**

Specifies the schedule settings for a journey.

#### StartTime

The scheduled time, in ISO 8601 format, when the journey began or will begin.

**Type**: string **Required**: False

#### **EndTime**

The scheduled time, in ISO 8601 format, when the journey ended or will end.

**Type**: string **Required**: False

#### **Timezone**

The starting UTC offset for the journey schedule, if the value of the journey's LocalTime property is true. Valid values are: UTC, UTC+01, UTC+02, UTC+03, UTC+03:30, UTC+04, UTC+04:30, UTC+05:30, UTC+05:45, UTC+06, UTC+06:30, UTC+07, UTC+08, UTC+08:45, UTC+09, UTC+09:30, UTC+10, UTC+10:30, UTC+11, UTC+12, UTC+12:45, UTC+13, UTC+13:45, UTC-02, UTC-02:30, UTC-03, UTC-03:30, UTC-04, UTC-05, UTC-06, UTC-07, UTC-08, UTC-09, UTC-09:30, UTC-10, and UTC-11.

**Type**: string **Required**: False

# JourneyTimeframeCap

The number of messages that can be sent to an endpoint during the specified timeframe for all journeys.

### **Days**

The length of the timeframe in days. The maximum value is 30. If set to 0, this limit will not apply.

**Type**: integer **Required**: False

#### Cap

The maximum number of messages that all journeys can send to an endpoint during the specified timeframe. The maximum value is 100. If set to 0, this limit will not apply.

**Type**: integer **Required**: False

## MessageBody

Provides information about an API request or response.

## RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

### Message

The message that's returned from the API.

**Type**: string **Required**: False

### MetricDimension

Specifies metric-based criteria for including or excluding endpoints from a segment. These criteria derive from custom metrics that you define for endpoints.

### ComparisonOperator

The operator to use when comparing metric values. Valid values are: GREATER\_THAN, LESS\_THAN, GREATER\_THAN\_OR\_EQUAL, LESS\_THAN\_OR\_EQUAL, and EQUAL.

**Type**: string **Required**: True

#### Value

The value to compare.

**Type**: number **Required**: True

### MultiConditionalBranch

Specifies a condition to evaluate for an activity path in a journey.

#### **Condition**

The condition to evaluate for the activity path.

**Type**: SimpleCondition

Required: False

### NextActivity

The unique identifier for the next activity to perform, after completing the activity for the path.

**Type**: string **Required**: False

## MultiConditionalSplitActivity

Specifies the settings for a multivariate split activity in a journey. This type of activity sends participants down one of as many as five paths (including a default Else path) in a journey, based on conditions that you specify.



## Note

To create multivariate split activities that send participants down different paths based on push notification events (such as Open or Received events), your mobile app has to specify the User ID and Endpoint ID values. For more information, see Integrating Amazon Pinpoint with your application in the Amazon Pinpoint Developer Guide.

#### **Branches**

The paths for the activity, including the conditions for entering each path and the activity to perform for each path.

**Type**: Array of type MultiConditionalBranch

Required: False

### **DefaultActivity**

The unique identifier for the activity to perform for participants who don't meet any of the conditions specified for other paths in the activity.

**Type**: string **Required**: False

#### **EvaluationWaitTime**

The amount of time to wait or the date and time when Amazon Pinpoint determines whether the conditions are met.

Type: WaitTime Required: False

## **OpenHours**

Specifies the times when message are allowed to be sent to endpoints.

### **EMAIL**

Specifies the schedule settings for the email channel.

**Type**: object **Required**: False

#### **SMS**

Specifies the schedule settings for the SMS channel.

**Type**: object **Required**: False

#### **PUSH**

Specifies the schedule settings for the push channel.

Type: object

Required: False

#### **VOICE**

Specifies the schedule settings for the voice channel.

**Type**: object **Required**: False

#### **CUSTOM**

Specifies the schedule settings for the custom channel.

**Type**: object **Required**: False

## **OpenHoursRule**

Specifies the start and end time for OpenHours.

#### **StartTime**

The start of the scheduled time, in ISO 8601 format, when the channel can send messages.

**Type**: string **Required**: True

#### **EndTime**

The end of the scheduled time, in ISO 8601 format, when the channel can't send messages.

**Type**: string **Required**: True

## PushMessageActivity

Specifies the settings for a push notification activity in a journey. This type of activity sends a push notification to participants.

### MessageConfig

Specifies the time to live (TTL) value for push notifications that are sent to participants in a journey.

**Type**: JourneyPushMessage

Required: False

### **NextActivity**

The unique identifier for the next activity to perform, after the message is sent.

Type: string

Required: False

### **TemplateName**

The name of the push notification template to use for the message. If specified, this value must match the name of an existing message template.

Type: string

Required: False

### **TemplateVersion**

The unique identifier for the version of the push notification template to use for the message. If specified, this value must match the identifier for an existing template version. To retrieve a list of versions and version identifiers for a template, use the Template Versionsresource.

If you don't specify a value for this property, Amazon Pinpoint uses the *active version* of the template. The *active version* is typically the version of a template that's been most recently reviewed and approved for use, depending on your workflow. It isn't necessarily the latest version of a template.

Type: string

Required: False

## QuietTime

Specifies the start and end times that define a time range when messages aren't sent to endpoints.

#### Start

The specific time when quiet time begins. This value has to use 24-hour notation and be in HH:MM format, where HH is the hour (with a leading zero, if applicable) and MM is the minutes. For example, use 02:30 to represent 2:30 AM, or 14:30 to represent 2:30 PM.

**Type**: string **Required**: False

#### End

The specific time when quiet time ends. This value has to use 24-hour notation and be in HH:MM format, where HH is the hour (with a leading zero, if applicable) and MM is the minutes. For example, use 02:30 to represent 2:30 AM, or 14:30 to represent 2:30 PM.

**Type**: string **Required**: False

## RandomSplitActivity

Specifies the settings for a random split activity in a journey. This type of activity randomly sends specified percentages of participants down one of as many as five paths in a journey, based on conditions that you specify.

#### **Branches**

The paths for the activity, including the percentage of participants to enter each path and the activity to perform for each path.

Type: Array of type <a href="RandomSplitEntry">RandomSplitEntry</a>

Required: False

## RandomSplitEntry

Specifies the settings for a path in a random split activity in a journey.

### **Percentage**

The percentage of participants to send down the activity path.

To determine which participants are sent down each path, Amazon Pinpoint applies a probability-based algorithm to the percentages that you specify for the paths. Therefore, the actual percentage of participants who are sent down a path may not be equal to the percentage that you specify.

**Type**: integer **Required**: False

## **NextActivity**

The unique identifier for the next activity to perform, after completing the activity for the path.

**Type**: string **Required**: False

## RecencyDimension

Specifies criteria for including or excluding endpoints from a segment based on how recently an endpoint was active.

## RecencyType

The type of recency dimension to use for the segment. Valid values are: ACTIVE, endpoints that were active within the specified duration are included in the segment; and, INACTIVE, endpoints that weren't active within the specified duration are included in the segment.

**Type**: string **Required**: True

Values: ACTIVE | INACTIVE

#### **Duration**

The duration to use when determining whether an endpoint is active or inactive.

Type: string

Required: True

Values: HR\_24 | DAY\_7 | DAY\_14 | DAY\_30

## **SMSMessageActivity**

Specifies the settings for an SMS activity in a journey. This type of activity sends a text message to participants.

### MessageConfig

Specifies the sender ID and message type for an SMS message that's sent to participants in a journey.

**Type**: JourneySMSMessage

Required: False

### **NextActivity**

The unique identifier for the next activity to perform, after the message is sent.

**Type**: string **Required**: False

### **TemplateName**

The name of the SMS message template to use for the message. If specified, this value must match the name of an existing message template.

**Type**: string **Required**: False

## **TemplateVersion**

The unique identifier for the version of the SMS template to use for the message. If specified, this value must match the identifier for an existing template version. To retrieve a list of versions and version identifiers for a template, use the Template Versions resource.

If you don't specify a value for this property, Amazon Pinpoint uses the *active version* of the template. The *active version* is typically the version of a template that's been most recently

reviewed and approved for use, depending on your workflow. It isn't necessarily the latest version of a template.

**Type**: string **Required**: False

## **SegmentBehaviors**

Specifies dimension settings for including or excluding endpoints from a segment based on how recently an endpoint was active.

### Recency

The dimension settings that are based on how recently an endpoint was active.

**Type**: RecencyDimension

Required: False

## **SegmentCondition**

Specifies a segment to associate with an activity in a journey.

## SegmentId

The unique identifier for the segment to associate with the activity.

**Type**: string **Required**: True

## SegmentDemographics

Specifies demographic-based dimension settings for including or excluding endpoints from a segment. These settings derive from characteristics of endpoint devices, such as platform, make, and model.

#### Channel

The channel criteria for the segment.

Type: <u>SetDimension</u>
Required: False

#### **Platform**

The device platform criteria for the segment.

Type: <u>SetDimension</u>
Required: False

# DeviceType

The device type criteria for the segment.

Type: <u>SetDimension</u>
Required: False

## **AppVersion**

The app version criteria for the segment.

Type: <u>SetDimension</u>
Required: False

#### Make

The device make criteria for the segment.

Type: <u>SetDimension</u>
Required: False

#### Model

The device model criteria for the segment.

Type: <u>SetDimension</u>
Required: False

# SegmentDimensions

Specifies the dimension settings for a segment.

### **Demographic**

The demographic-based criteria, such as device platform, for the segment.

**Type:** SegmentDemographics

**Required**: False

#### Location

The location-based criteria, such as region or GPS coordinates, for the segment.

**Type**: SegmentLocation

Required: False

#### **Behavior**

The behavior-based criteria, such as how recently users have used your app, for the segment.

**Type**: SegmentBehaviors

**Required**: False

#### **Attributes**

One or more custom attributes to use as criteria for the segment. For more information see AttributeDimension

**Type**: object **Required**: False

#### **Metrics**

One or more custom metrics to use as criteria for the segment.

**Type**: object **Required**: False

#### **UserAttributes**

One or more custom user attributes to use as criteria for the segment.

Type: object

Required: False

## **SegmentLocation**

Specifies geographical dimension settings for a segment.

## **Country**

The country or region code, in ISO 3166-1 alpha-2 format, for the segment.

**Type:** SetDimension

Required: False

#### **GPSPoint**

The GPS location and range for the segment.

**Type:** GPSPointDimension

Required: False

## **SetDimension**

Specifies the dimension type and values for a segment dimension.

## DimensionType

The type of segment dimension to use. Valid values are: INCLUSIVE, endpoints that match the criteria are included in the segment; and, EXCLUSIVE, endpoints that match the criteria are excluded from the segment.

**Type**: string

Required: False

Values: INCLUSIVE | EXCLUSIVE

#### **Values**

The criteria values to use for the segment dimension. Depending on the value of the DimensionType property, endpoints are included or excluded from the segment if their values match the criteria values.

**Type**: Array of type string

Required: True

## **SimpleCondition**

Specifies a condition to evaluate for an activity in a journey.

### segmentDimensions

The dimension settings for the segment that's associated with the activity.

**Type**: SegmentDimensions

Required: False

## **SegmentCondition**

The segment that's associated with the activity.

**Type**: SegmentCondition

Required: False

#### **EventCondition**

The dimension settings for the event that's associated with the activity.

**Type**: EventCondition

Required: False

### **StartCondition**

Specifies the conditions for the first activity in a journey. This activity and its conditions determine which users are participants in a journey.

### Description

The custom description of the condition.

**Type**: string **Required**: False

#### **EventStartCondition**

The event start condition that can trigger a journey.

Type: EventStartCondition

Required: False

## SegmentStartCondition

The segment that's associated with the first activity in the journey. This segment determines which users are participants in the journey.

**Type**: SegmentCondition

Required: False

## WaitActivity

Specifies the settings for a wait activity in a journey. This type of activity waits for a certain amount of time or until a specific date and time before moving participants to the next activity in a journey.

#### WaitTime

The amount of time to wait or the date and time when the activity moves participants to the next activity in the journey.

Type: WaitTime Required: False

## **NextActivity**

The unique identifier for the next activity to perform, after performing the wait activity.

Type: string

Required: False

#### **WaitTime**

Specifies a duration or a date and time that indicates when Amazon Pinpoint determines whether an activity's conditions have been met or an activity moves participants to the next activity in a journey.

#### WaitFor

The amount of time to wait, as a duration in ISO 8601 format, before determining whether the activity's conditions have been met or moving participants to the next activity in the journey.

**Type**: string **Required**: False

#### WaitUntil

The date and time, in ISO 8601 format, when Amazon Pinpoint determines whether the activity's conditions have been met or the activity moves participants to the next activity in the journey.

**Type**: string **Required**: False

## WriteJourneyRequest

Specifies the configuration and other settings for a journey.

#### Name

The name of the journey. A journey name can contain a maximum of 150 characters. The characters can be alphanumeric characters or symbols, such as underscores (\_) or hyphens (-). A journey name can't contain any spaces.

**Type**: string **Required**: False

#### Schedule

The schedule settings for the journey.

Type: JourneySchedule

Required: False

#### **StartCondition**

The segment that defines which users are participants in the journey.

**Type**: StartCondition

Required: False

#### Limits

The messaging and entry limits for the journey.

**Type**: JourneyLimits

Required: False

## **StartActivity**

The unique identifier for the first activity in the journey. The identifier for this activity can contain a maximum of 128 characters. The characters must be alphanumeric characters.

**Type**: string

Required: False

#### **Activities**

A map that contains a set of Activity objects, one object for each activity in the journey. For each Activity object, the key is the unique identifier (string) for an activity and the value is the settings for the activity. An activity identifier can contain a maximum of 100 characters. The characters must be alphanumeric characters.

Type: object

Required: False

### RefreshFrequency

The frequency with which Amazon Pinpoint evaluates segment and event data for the journey, as a duration in ISO 8601 format.

**Type**: string **Required**: False

### QuietTime

The quiet time settings for the journey. Quiet time is a specific time range when a journey doesn't send messages to participants, if all the following conditions are met:

- The EndpointDemographic.Timezone property of the endpoint for the participant is set to a valid value.
- The current time in the participant's time zone is later than or equal to the time specified by the QuietTime. Start property for the journey.
- The current time in the participant's time zone is earlier than or equal to the time specified by the QuietTime. End property for the journey.

If any of the preceding conditions isn't met, the participant will receive messages from the journey, even if quiet time is enabled.

Type: QuietTime Required: False

#### WaitForQuietTime

Indicates whether endpoints in quiet hours should enter a wait activity until quiet hours have elapsed.

**Type**: boolean **Required**: False

## SendingSchedule

Indicates if journey has Advance Quiet Time enabled. This flag should be set to true in order to allow using OpenHours and ClosedDays.

**Type**: boolean **Required**: False

### **OpenHours**

The time when journey allow to send messages. QuietTime should be configured first and SendingSchedule should be set to true.

Type: OpenHours
Required: False

## ClosedDays

The time when journey will stop sending messages. QuietTime should be configured first and SendingSchedule should be set to true.

Type: ClosedDays
Required: False

## RefreshOnSegmentUpdate

Indicates whether the journey participants should be refreshed when a segment is updated.

**Type**: boolean **Required**: False

#### LocalTime

Specifies whether the journey's scheduled start and end times use each participant's local time. To base the schedule on each participant's local time, set this value to true.

**Type**: boolean **Required**: False

#### CreationDate

The date, in ISO 8601 format, when the journey was created.

Type: string

**Required**: False

#### LastModifiedDate

The date, in ISO 8601 format, when the journey was last modified.

**Type**: string

Required: False

#### **State**

The status of the journey. Valid values are:

DRAFT – Saves the journey and doesn't publish it.

ACTIVE – Saves and publishes the journey. Depending on the journey's schedule, the journey
starts running immediately or at the scheduled start time. If a journey's status is ACTIVE, you
can't add, change, or remove activities from it.

The CANCELLED, COMPLETED, and CLOSED values are not supported in requests to create or update a journey. To cancel a journey, use the Journey State resource.

**Type**: string

Required: False

Values: DRAFT | ACTIVE | PAUSED | COMPLETED | CANCELLED | CLOSED |

PENDING\_APPROVAL

### **TimezoneEstimationMethods**

An array of time zone estimation methods, if any, to use for determining an <a href="Endpoints"><u>Endpoints</u></a> time zone if the Endpoint does not have a value for the Demographic. Timezone attribute.

- PHONE\_NUMBER A time zone is estimated based on the Endpoint.Location.Country and Endpoint.Address.
- POSTAL\_CODE A time zone is estimated based on the Endpoint.Location.Country and Endpoint.Location.PostalCode.

**REST API Reference** Amazon Pinpoint



### Note

POSTAL\_CODE estimation is only supported in the United States, United Kingdom, Australia, New Zealand, Canada, France, Italy, Spain, Germany and in regions where Amazon Pinpoint is available.

Both - A time zone is estimated based on the Endpoint.Location.Country, Endpoint.Address and Endpoint.Location.PostalCode.

**Type**: Array of type string

Required: False

Values: PHONE\_NUMBER | POSTAL\_CODE

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## **GetJourney**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

## **UpdateJourney**

AWS Command Line Interface

See also 695

- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

## **DeleteJourney**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Journey Activity Execution Metrics**

A journey activity execution metric is a measurable value, also referred to as a key performance indicator (KPI), that can help you assess the status of participants in a journey activity. For example, you can use this type of metric to determine how many participants started and completed an activity. Amazon Pinpoint automatically collects, aggregates, and stores this data for all of your journey activities.

The Journey Activity Execution Metrics resource represents a collection of standard execution metrics that apply to an individual journey activity. As part of the Amazon Pinpoint Analytics APIs,

this resource provides you with programmatic access to pre-aggregated data for each of these metrics. For a list of metrics that are currently supported, see the <u>Amazon Pinpoint Developer</u> Guide.

You can use the Journey Activity Execution Metrics resource to retrieve pre-aggregated data for standard execution metrics that apply to a journey activity.

## **URI**

/v1/apps/application-id/journeys/journey-id/activities/journey-activity-id/execution-metrics

## **HTTP** methods

#### **GET**

**Operation ID:** GetJourneyExecutionActivityMetrics

Retrieves (queries) pre-aggregated data for a standard execution metric that applies to a journey activity.

### **Path parameters**

Name	Type	Required	Description
journey-a ctivity-id	String	True	The unique identifie r for the journey activity.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.
journey-id	String	True	The unique identifier for the journey.

URI 697

## **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# **Query parameters**

Name	Туре	Required	Description
page-size	String	False	The maximum number of items to include in each page of a paginated response. This parameter is not supported for application, campaign, and journey metrics.
next-token	String	False	The string that specifies which page of results to return in a paginated response. This parameter is not supported for application, campaign, and journey metrics.

## Responses

Status code	Response model	Description
200	JourneyExecutionAc tivityMetricsRespo nse	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).

Status code	Response model	Description
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Journey Activity Execution Metrics resource.

## **Path parameters**

Name	Type	Required	Description
journey-a ctivity-id	String	True	The unique identifie r for the journey activity.
journey-id	String	True	The unique identifier for the journey.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## Responses

Status code	Response model	Description
200	None	The request succeeded.

## **Schemas**

## **Response bodies**

## JourneyExecutionActivityMetricsResponse schema

```
{
   "ApplicationId": "string",
   "JourneyId": "string",
   "JourneyActivityId": "string",
   "ActivityType": "string",
   "LastEvaluatedTime": "string",
   "Metrics": {
   }
}
```

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

# ${\bf Journey Execution Activity Metrics Response}$

Provides the results of a query that retrieved the data for a standard execution metric that applies to a journey activity, and provides information about that query.

## **ApplicationId**

The unique identifier for the application that the metric applies to.

**Type**: string **Required**: True

## JourneyId

The unique identifier for the journey that the metric applies to.

Schemas 701

**Type**: string **Required**: True

### **JourneyActivityId**

The unique identifier for the activity that the metric applies to.

**Type**: string **Required**: True

## ActivityType

The type of activity that the metric applies to. Possible values are:

- CONDITIONAL\_SPLIT For a yes/no split activity, which is an activity that sends participants down one of two paths in a journey.
- HOLDOUT For a holdout activity, which is an activity that stops a journey for a specified percentage of participants.
- MESSAGE For an email activity, which is an activity that sends an email message to participants.
- MULTI\_CONDITIONAL\_SPLIT For a multivariate split activity, which is an activity that sends participants down one of as many as five paths in a journey.
- RANDOM\_SPLIT For a random split activity, which is an activity that sends specified
  percentages of participants down one of as many as five paths in a journey.
- WAIT For a wait activity, which is an activity that waits for a certain amount of time or until a specific date and time before moving participants to the next activity in a journey.

**Type**: string **Required**: True

#### LastEvaluatedTime

The date and time, in ISO 8601 format, when Amazon Pinpoint last evaluated the execution status of the activity and updated the data for the metric.

**Type**: string **Required**: True

#### **Metrics**

A JSON object that contains the results of the query. The results vary depending on the type of activity (ActivityType). For information about the structure and contents of the results, see the Amazon Pinpoint Developer Guide.

**Type**: object **Required**: True

## MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

Type: string

Required: False

### Message

The message that's returned from the API.

Type: string

Required: False

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## GetJourneyExecutionActivityMetrics

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++

See also 703

- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Journey Engagement Metrics**

A journey engagement metric is a measurable value, also referred to as a key performance indicator (KPI), that can help you monitor and assess the performance of a journey. For example, you can use a journey engagement metric to access data about how many messages were sent by a journey or how many of those messages were delivered to participants. Amazon Pinpoint automatically collects, aggregates, and stores this data for all of your journeys.

The Journey Engagement Metrics resource represents a collection of standard metrics that apply to a journey. As part of the Amazon Pinpoint Analytics APIs, this resource provides you with programmatic access to pre-aggregated data for each of these metrics. For a list of journey engagement metrics that are currently supported, see the Amazon Pinpoint Developer Guide.

You can use the Journey Engagement Metrics resource to retrieve pre-aggregated data for a standard metric that applies to an individual journey.

## **URI**

/v1/apps/application-id/journeys/journey-id/kpis/daterange/kpi-name

## **HTTP** methods

#### **GET**

Operation ID: GetJourneyDateRangeKpi

Retrieves (queries) pre-aggregated data for a standard engagement metric that applies to a journey.

Journey Engagement Metrics 704

## **Path parameters**

Name	Туре	Required	Description
journey-id	String	True	The unique identifier for the journey.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.
kpi-name	String	True	The name of the metric, also referred to as a key performan ce indicator (KPI), to retrieve data for. This value describes the associated metric and consists of two or more terms, which are comprised of lowercase alphanume ric characters, separated by a hyphen. Examples are email-open-rate and successfu l-delivery-rate. For a list of valid values, see the Amazon Pinpoint Developer Guide.

## **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# **Query parameters**

Name	Туре	Required	Description
next-token	String	False	The string that specifies which page of results to return in a paginated response. This parameter is not supported for application, campaign, and journey metrics.
end-time	String	False	The last date and time to retrieve data for, as part of an inclusive date range that filters the query results. This value should be in extended ISO 8601 format and use Coordinat ed Universal Time (UTC), for example: 2019-07-2 6T20:00:00Z for

Name	Туре	Required	Description
			8:00 PM UTC July 26, 2019.
start-time	String	False	The first date and time to retrieve data for, as part of an inclusive date range that filters the query results. This value should be in extended ISO 8601 format and use Coordinat ed Universal Time (UTC), for example: 2019-07-1 9T20:00:00Z for 8:00 PM UTC July 19, 2019. This value should also be fewer than 90 days from the current day.
page-size	String	False	The maximum number of items to include in each page of a paginated response.  This parameter is not supported for application, campaign, and journey metrics.

## Responses

Status code	Response model	Description
200	<u>JourneyDateRangeKp</u> <u>iResponse</u>	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).

Status code	Response model	Description
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Journey Engagement Metrics resource.

## **Path parameters**

Name	Туре	Required	Description
journey-id	String	True	The unique identifier for the journey.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.
kpi-name	String	True	The name of the metric, also referred to as a key performan ce indicator (KPI), to retrieve data for. This value describes the associated metric and consists of two or more terms, which are comprised of lowercase alphanume

Name	Type	Required	Description
			ric characters,
			separated by a
			hyphen. Examples are
			email-open-rate
			and successfu
			l-delivery-
			rate. For a list of
			valid values, see the
			Amazon Pinpoint
			Developer Guide.

### Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Response bodies**

## JourneyDateRangeKpiResponse schema

Schemas 710

```
"Key": "string",
    "Yalue": "string",
    "Type": "string"
}

]

}

[
]

NextToken": "string",
    "ApplicationId": "string",
    "JourneyId": "string",
    "StartTime": "string",
    "EndTime": "string",
}
```

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

## **Properties**

## **BaseKpiResult**

Provides the results of a query that retrieved the data for a standard metric that applies to an application, campaign, or journey.

#### **Rows**

An array of objects that provides the results of a query that retrieved the data for a standard metric that applies to an application, campaign, or journey.

**Type**: Array of type ResultRow

Required: True

## **JourneyDateRangeKpiResponse**

Provides the results of a query that retrieved the data for a standard engagement metric that applies to a journey, and provides information about that query.

#### **KpiName**

The name of the metric, also referred to as a *key performance indicator (KPI)*, that the data was retrieved for. This value describes the associated metric and consists of two or more terms, which are comprised of lowercase alphanumeric characters, separated by a hyphen. For a list of possible values, see the Amazon Pinpoint Developer Guide.

**Type**: string **Required**: True

#### **KpiResult**

An array of objects that contains the results of the query. Each object contains the value for the metric and metadata about that value.

Type: BaseKpiResult
Required: True

#### NextToken

The string to use in a subsequent request to get the next page of results in a paginated response. This value is null for the Journey Engagement Metrics resource because the resource returns all results in a single page.

**Type**: string **Required**: False

### **ApplicationId**

The unique identifier for the application that the metric applies to.

**Type**: string **Required**: True

### Journeyld

The unique identifier for the journey that the metric applies to.

Type: string

Required: True

#### StartTime

The first date and time of the date range that was used to filter the query results, in extended ISO 8601 format. The date range is inclusive.

**Type**: string **Required**: True

#### **EndTime**

The last date and time of the date range that was used to filter the query results, in extended ISO 8601 format. The date range is inclusive.

**Type**: string **Required**: True

## MessageBody

Provides information about an API request or response.

## RequestID

The unique identifier for the request or response.

Type: string

Required: False

## Message

The message that's returned from the API.

Type: string

Required: False

#### ResultRow

Provides the results of a query that retrieved the data for a standard metric that applies to an application, campaign, or journey.

### GroupedBys

An array of objects that defines the field and field values that were used to group data in a result set that contains multiple results. This value is null if the data in a result set isn't grouped.

Type: Array of type ResultRowValue

**Required**: True

#### **Values**

An array of objects that provides pre-aggregated values for a standard metric that applies to an application, campaign, or journey.

**Type**: Array of type ResultRowValue

Required: True

#### **ResultRowValue**

Provides a single value and metadata about that value as part of an array of query results for a standard metric that applies to an application, campaign, or journey.

### Key

The friendly name of the metric whose value is specified by the Value property.

**Type**: string **Required**: True

#### Value

In a Values object, the value for the metric that the query retrieved data for. In a GroupedBys object, the value for the field that was used to group data in a result set that contains multiple results (Values objects).

Type: string

Required: True

#### **Type**

The data type of the value specified by the Value property.

**Type**: string **Required**: True

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## GetJourneyDateRangeKpi

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Journey Execution Metrics**

A journey execution metric is a measurable value, also referred to as a key performance indicator (KPI), that can help you assess the status of participants in a journey. For example, you can use this type of metric to determine how many participants are actively proceeding through the activities in the journey. Amazon Pinpoint automatically collects, aggregates, and stores this data for all of your journeys.

See also 715

The Journey Execution Metrics resource represents a collection of standard execution metrics that apply to a journey. As part of the Amazon Pinpoint Analytics APIs, this resource provides you with programmatic access to pre-aggregated data for each of these metrics. For a list of metrics that are currently supported, see the <u>Amazon Pinpoint Developer Guide</u>.

You can use the Journey Execution Metrics resource to retrieve pre-aggregated data for standard execution metrics that apply to a journey. To retrieve data for a standard metric that applies to an individual activity in a journey, use the Journey Activity Execution Metrics resource.

## **URI**

/v1/apps/application-id/journeys/journey-id/execution-metrics

## **HTTP** methods

#### **GET**

Operation ID: GetJourneyExecutionMetrics

Retrieves (queries) pre-aggregated data for a standard execution metric that applies to a journey.

### **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.
journey-id	String	True	The unique identifier for the journey.

URI 716

## **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# **Query parameters**

Name	Туре	Required	Description
page-size	String	False	The maximum number of items to include in each page of a paginated response.  This parameter is not supported for application, campaign, and journey metrics.
next-token	String	False	The string that specifies which page of results to return in a paginated response. This parameter is not supported for application, campaign, and journey metrics.

## Responses

Status code	Response model	Description
200	JourneyExecutionMe tricsResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).

Status code	Response model	Description
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Journey Execution Metrics resource.

## **Path parameters**

Name	Туре	Required	Description
journey-id	String	True	The unique identifier for the journey.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

### Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Response bodies**

Schemas 719

### JourneyExecutionMetricsResponse schema

```
{
  "ApplicationId": "string",
  "JourneyId": "string",
  "LastEvaluatedTime": "string",
  "Metrics": {
  }
}
```

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

# JourneyExecutionMetricsResponse

Provides the results of a query that retrieved the data for a standard execution metric that applies to a journey, and provides information about that query.

## **ApplicationId**

The unique identifier for the application that the metric applies to.

**Type**: string **Required**: True

#### Journeyld

The unique identifier for the journey that the metric applies to.

**Type**: string **Required**: True

#### LastEvaluatedTime

The date and time, in ISO 8601 format, when Amazon Pinpoint last evaluated the journey and updated the data for the metric.

**Type**: string **Required**: True

#### **Metrics**

A JSON object that contains the results of the query. For information about the structure and contents of the results, see the Amazon Pinpoint Developer Guide.

**Type**: object **Required**: True

## MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

### Message

The message that's returned from the API.

**Type**: string **Required**: False

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

See also 721

## GetJourneyExecutionMetrics

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Journey Run Execution Activity Metrics**

A journey run activity execution metric is a measurable value, also referred to as a key performance indicator (KPI), that can help you assess the status of participants in a journey activity for a particular journey run. For example, you can use this type of metric to determine how many participants started and completed an activity. Amazon Pinpoint automatically collects, aggregates, and stores this data for all of your journey activities.

The Journey Run Execution Activity Metrics resource represents a collection of standard execution metrics that apply to an individual journey activity for a journey run. As part of the Amazon Pinpoint Analytics APIs, this resource provides you with programmatic access to pre-aggregated data for each of these metrics. For a list of metrics that are currently supported, see <a href="Standard">Standard</a> Amazon Pinpoint analytics metrics in the Amazon Pinpoint Developer Guide.

You can use the <u>Journey Activity Execution Metrics</u> resource to retrieve pre-aggregated data for standard execution metrics that apply to a journey activity across all journey runs.

### URI

/v1/apps/application-id/journeys/journey-id/runs/run-id/activities/journey-activity-id/execution-metrics

# **HTTP** methods

### **GET**

Operation ID: GetJourneyRunExecutionActivityMetrics

Retrieves (queries) pre-aggregated data for a standard run execution metric that applies to a journey activity.

### **Path parameters**

Name	Туре	Required	Description
run-id	String	True	The unique identifier for the journey run.
journey-a ctivity-id	String	True	The unique identifie r for the journey activity.
journey-id	String	True	The unique identifier for the journey.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types,
			expressed as MIME

Name	Туре	Required	Description
			types, the client
			understands.

# **Query parameters**

Name	Туре	Required	Description
next-token	String	False	The string that specifies which page of results to return in a paginated response. This parameter is not supported for application, campaign, and journey metrics.
page-size	String	False	The maximum number of items to include in each page of a paginated response. This parameter is not supported for application, campaign, and journey metrics.

# Responses

Status code	Response model	Description
200	JourneyRunExecutio	The request succeeded.
	<pre>nActivityMetricsRe sponse_</pre>	

Status code	Response model	Description
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Journey Run Activity Execution Metrics resource.

### **Path parameters**

Name	Туре	Required	Description
journey-a ctivity-id	String	True	The unique identifie r for the journey activity.
run-id	String	True	The unique identifier for the journey run.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.
journey-id	String	True	The unique identifier for the journey.

# Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Response bodies**

Schemas 726

#### JourneyRunExecutionActivityMetricsResponse schema

```
{
   "ApplicationId": "string",
   "JourneyId": "string",
   "BunId": "string",
   "ActivityType": "string",
   "LastEvaluatedTime": "string",
   "Metrics": {
   }
}
```

## MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

## JourneyRunExecutionActivityMetricsResponse

Provides the results of a query that retrieved the data for a standard execution metric that applies to a journey activity for a particular journey run, and provides information about that query.

## **ApplicationId**

The unique identifier for the application that the metric applies to.

**Type**: string **Required**: True

### Journeyld

The unique identifier for the journey that the metric applies to.

**Type**: string **Required**: True

#### **JourneyActivityId**

The unique identifier for the activity that the metric applies to.

**Type**: string **Required**: True

#### RunId

The unique identifier for the journey run that the metric applies to.

**Type**: string **Required**: True

### ActivityType

The type of activity that the metric applies to. Possible values are:

- CONDITIONAL\_SPLIT For a yes/no split activity, which is an activity that sends participants down one of two paths in a journey.
- HOLDOUT For a holdout activity, which is an activity that stops a journey for a specified percentage of participants.
- MESSAGE For an email activity, which is an activity that sends an email message to participants.
- MULTI\_CONDITIONAL\_SPLIT For a multivariate split activity, which is an activity that sends participants down one of as many as five paths in a journey.
- RANDOM\_SPLIT For a random split activity, which is an activity that sends specified
  percentages of participants down one of as many as five paths in a journey.
- WAIT For a wait activity, which is an activity that waits for a certain amount of time or until a specific date and time before moving participants to the next activity in a journey.

**Type**: string **Required**: True

#### LastEvaluatedTime

The date and time, in ISO 8601 format, when Amazon Pinpoint last evaluated the execution status of the activity for this journey run and updated the data for the metric.

**Type**: string **Required**: True

#### **Metrics**

A JSON object that contains the results of the query. For information about the structure and contents of the results, see <u>Standard Amazon Pinpoint analytics metrics</u> in the *Amazon Pinpoint Developer Guide*.

**Type**: object **Required**: True

## MessageBody

Provides information about an API request or response.

#### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

#### Message

The message that's returned from the API.

**Type**: string **Required**: False

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## ${\bf Get Journey Run Execution Activity Metrics}$

- AWS Command Line Interface
- AWS SDK for .NET

See also 729

- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- · AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Journey Run Execution Metrics**

A *journey run execution metric* is a measurable value, also referred to as a *key performance indicator* (*KPI*), that can help you assess the status of participants in a journey. For example, you can use this type of metric to determine how many participants are actively proceeding through the journey. Amazon Pinpoint automatically collects, aggregates, and stores this data for all of your journeys.

The Journey Run Execution Metrics resource represents a collection of standard execution metrics that apply to a particular run of a journey. As part of the Amazon Pinpoint Analytics APIs, this resource provides you with programmatic access to pre-aggregated data for each of these metrics. For a list of metrics that are currently supported, see <a href="Standard Amazon Pinpoint analytics metrics">Standard Amazon Pinpoint analytics metrics</a> in the Amazon Pinpoint Developer Guide.

You can use the Journey Run Execution Metrics resource to retrieve pre-aggregated data for standard execution metrics that apply to a journey run. To retrieve data for a standard metric that applies to the journey across all runs, use the <u>Journey Execution Metrics</u> resource.

#### URI

/v1/apps/application-id/journeys/journey-id/runs/run-id/execution-metrics

## **HTTP** methods

#### **GET**

Operation ID: GetJourneyRunExecutionMetrics

Retrieves (queries) pre-aggregated data for a standard run execution metric that applies to a journey.

## **Path parameters**

Name	Туре	Required	Description
run-id	String	True	The unique identifier for the journey run.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.
journey-id	String	True	The unique identifier for the journey.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

## **Query parameters**

Name	Туре	Required	Description
page-size	String	False	The maximum number of items to include in each page of a paginated response. This parameter

Name	Туре	Required	Description
			is not supported for application, campaign, and journey metrics.
next-token	String	False	The string that specifies which page of results to return in a paginated response. This parameter is not supported for application, campaign, and journey metrics.

# Responses

Status code	Response model	Description
200	JourneyRunExecutio nMetricsResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).

Status code	Response model	Description
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Journey Run Execution Metrics resource.

## **Path parameters**

Name	Туре	Required	Description
run-id	String	True	The unique identifier for the journey run.

Name	Type	Required	Description
journey-id	String	True	The unique identifier for the journey.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

### Responses

Status code	Response model	Description
200	None	The request succeeded.

## **Schemas**

## **Response bodies**

## JourneyRunExecutionMetricsResponse schema

```
{
  "ApplicationId": "string",
  "JourneyId": "string",
  "RunId": "string",
  "LastEvaluatedTime": "string",
  "Metrics": {
  }
}
```

# MessageBody schema

```
{
```

Schemas 734

```
"RequestID": "string",
"Message": "string"
}
```

# **Properties**

## JourneyRunExecutionMetricsResponse

Provides the results of a query that retrieved the data for a standard execution metric that applies to a journey run, and provides information about that query.

### **ApplicationId**

The unique identifier for the application that the metric applies to.

**Type**: string **Required**: True

#### Journeyld

The unique identifier for the journey that the metric applies to.

**Type**: string **Required**: True

#### RunId

The unique identifier for the journey run that the metric applies to.

**Type**: string **Required**: True

#### LastEvaluatedTime

The date and time, in ISO 8601 format, when Amazon Pinpoint last evaluated the journey run and updated the data for the metric.

**Type**: string **Required**: True

#### **Metrics**

A JSON object that contains the results of the query. For information about the structure and contents of the results, see the <u>Standard Amazon Pinpoint analytics metrics</u> in the *Amazon Pinpoint Developer Guide*.

**Type**: object **Required**: True

## MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

Type: string

Required: False

### Message

The message that's returned from the API.

Type: string

Required: False

# See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

# ${\bf Get Journey Run Execution Metrics}$

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++

See also 736

- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Journey Runs**

A *journey* is an automated workflow that performs a series of messaging activities for an Amazon Pinpoint application. A journey run represents each scheduled entry of endpoints into the journey. The journey run resource provides information about each journey run, including timing information and status.

Each journey run represents a single evaluation of a segment, so can include endpoints in different timezones. These endpoints may actually enter the journey at different times, depending on their timezones, but each are represented by the same journey run.

#### **URI**

/v1/apps/application-id/journeys/journey-id/runs

## **HTTP** methods

#### **GET**

Operation ID: GetJourneyRuns

Provides information about the runs of a journey.

## **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier

Journey Runs 737

Name	Type	Required	Description
			is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.
journey-id	String	True	The unique identifier for the journey.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# **Query parameters**

Name	Туре	Required	Description
page-size	String	False	The maximum number of items to include in each page of a paginated response. This parameter is not supported for application, campaign, and journey metrics.
token	String	False	The NextToken string that specifies which page of

Name	Туре	Required	Description
			results to return in a
			paginated response.

# Responses

Status code	Response model	Description
200	JourneyRunsResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of

Status code	Response model	Description
		time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Journey Run resource.

## **Path parameters**

Name	Type	Required	Description
journey-id	String	True	The unique identifier for the journey.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## Responses

Status code	Response model	Description
200	None	The request succeeded.

## **Schemas**

## **Response bodies**

### JourneyRunsResponse schema

## MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

## JourneyRunResponse

Provides information from a specified run of a journey.

#### RunId

The unique identifier for the run.

**Type**: string **Required**: True

#### CreationTime

The time when the journey run was created or scheduled, in ISO 8601 format.

Schemas 741

**Type**: string **Required**: True

### LastUpdateTime

The last time the journey run was updated, in ISO 8601 format...

**Type**: string **Required**: True

#### **Status**

The current status of the run.

**Type**: string

Required: True

Values: SCHEDULED | RUNNING | COMPLETED | CANCELLED

## JourneyRunsResponse

Provides information from all runs of a journey.

#### NextToken

The string to use in a subsequent request to get the next page of results in a paginated response. This value is null if there are no additional pages.

Type: string

Required: False

#### Item

An array of responses, one for each run of the journey

**Type**: Array of type <u>JourneyRunResponse</u>

Required: True

# MessageBody

Provides information about an API request or response.

# RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

### Message

The message that's returned from the API.

**Type**: string **Required**: False

# See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

# GetJourneyRuns

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

See also 743

# **Journey State**

A *journey* is an automated workflow that performs a series of messaging activities for an Amazon Pinpoint application. The Journey State resource represents the status of a specific journey, including all of a journey's activities.

You can use this resource to cancel (stop) a journey or to retrieve information about the status and settings for a journey.

# **URI**

/v1/apps/application-id/journeys/journey-id/state

# **HTTP** methods

### **PUT**

Operation ID: UpdateJourneyState

Cancels (stops) an active journey.

# **Path parameters**

Name	Туре	Required	Description
journey-id	String	True	The unique identifier for the journey.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

Journey State 744

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	<u>JourneyResponse</u>	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	MessageBody	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large

HTTP methods 745

Status code	Response model	Description
		(RequestEntityTooLargeExcep tion).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Journey State resource.

# **Path parameters**

Name	Туре	Required	Description
journey-id	String	True	The unique identifier for the journey.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

HTTP methods 746

### Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Request bodies**

### **PUT schema**

```
{
    "<u>State</u>": enum
}
```

# **Response bodies**

# JourneyResponse schema

```
{
  "Name": "string",
  "Schedule": {
    "StartTime": "string",
    ""EndTime": "string",
    "Timezone": "string"
  },
  "StartCondition": {
    "Description": "string",
    "EventStartCondition": {
      "EventFilter": {
        "Dimensions": {
          "EventType": {
            "<u>DimensionType</u>": enum,
            "Values": [
              "string"
            ]
          },
          "Attributes": {
          "Metrics": {
```

Schemas 747

```
},
      "FilterType": enum
    "SegmentId": "string"
  },
  "SegmentStartCondition": {
    "SegmentId": "string"
  }
},
"Limits": {
  "DailyCap": integer,
  "TotalCap": integer,
  "TimeframeCap": {
    "Days": integer,
    "Cap": integer
  },
  "MessagesPerSecond": integer,
  "EndpointReentryCap": integer,
  "EndpointReentryInterval": "string"
},
"StartActivity": "string",
"Activities": {
},
"RefreshFrequency": "string",
"QuietTime": {
  "Start": "string",
  "End": "string"
"WaitForQuietTime": boolean,
"SendingSchedule": boolean,
"OpenHours": {
 "EMAIL": {
 },
  "<u>SMS</u>": {
  },
  "<u>PUSH</u>": {
  },
  "VOICE": {
  },
  "CUSTOM": {
  }
"ClosedDays": {
  "EMAIL": [
```

Schemas 748

```
{
      "Name": "string",
      "StartDateTime": "string",
      "EndDateTime": "string"
    }
  ],
  "SMS": [
    {
      "Name": "string",
      "StartDateTime": "string",
      "EndDateTime": "string"
    }
  ],
  "PUSH": [
      "Name": "string",
      "StartDateTime": "string",
      "EndDateTime": "string"
    }
  ],
  "VOICE": [
      "Name": "string",
      "StartDateTime": "string",
      "EndDateTime": "string"
    }
  ],
  "CUSTOM": [
      "Name": "string",
      "StartDateTime": "string",
      "EndDateTime": "string"
    }
  ]
},
"RefreshOnSegmentUpdate": boolean,
"LocalTime": boolean,
"CreationDate": "string",
"LastModifiedDate": "string",
"State": enum,
"<u>tags</u>": {
},
"TimezoneEstimationMethods": [
  enum
```

Schemas 749

```
],
"Id": "string",
"ApplicationId": "string"
}
```

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

# **Activity**

Specifies the configuration and other settings for an activity in a journey.

# **Description**

The custom description of the activity.

**Type**: string **Required**: False

# ConditionalSplit

The settings for a yes/no split activity. This type of activity sends participants down one of two paths in a journey, based on conditions that you specify.

Type: ConditionalSplitActivity

**Required**: False

#### **Holdout**

The settings for a holdout activity. This type of activity stops a journey for a specified percentage of participants.

Type: HoldoutActivity

Required: False

#### MultiCondition

The settings for a multivariate split activity. This type of activity sends participants down one of as many as five paths (including a default *Else* path) in a journey, based on conditions that you specify.

**Type**: MultiConditionalSplitActivity

**Required**: False

# RandomSplit

The settings for a random split activity. This type of activity randomly sends specified percentages of participants down one of as many as five paths in a journey, based on conditions that you specify.

**Type**: RandomSplitActivity

**Required**: False

#### Wait

The settings for a wait activity. This type of activity waits for a certain amount of time or until a specific date and time before moving participants to the next activity in a journey.

Type: WaitActivity
Required: False

### **EMAIL**

The settings for an email activity. This type of activity sends an email message to participants.

Type: EmailMessageActivity

Required: False

#### **SMS**

The settings for an SMS activity. This type of activity sends a text message to participants.

**Type**: SMSMessageActivity

Required: False

#### **PUSH**

The settings for a push notification activity. This type of activity sends a push notification to participants.

**Type:** PushMessageActivity

**Required**: False

### **CUSTOM**

The settings for a custom message activity. This type of activity calls an AWS Lambda function or web hook that sends messages to participants.

**Type**: CustomMessageActivity

Required: False

### **AttributeDimension**

Specifies attribute-based criteria for including or excluding endpoints from a segment.

# AttributeType

The type of segment dimension to use. Valid values are:

- INCLUSIVE endpoints that have attributes matching the values are included in the segment.
- EXCLUSIVE endpoints that have attributes matching the values are excluded from the segment.
- CONTAINS endpoints that have attributes' substrings match the values are included in the segment.
- BEFORE endpoints with attributes read as ISO\_INSTANT datetimes before the value are included in the segment.
- AFTER endpoints with attributes read as ISO\_INSTANT datetimes after the value are included in the segment.
- BETWEEN endpoints with attributes read as ISO\_INSTANT datetimes between the values are included in the segment.
- 0N endpoints with attributes read as ISO\_INSTANT dates on the value are included in the segment. Time is ignored in this comparison.

**Type**: string **Required**: False

Values: INCLUSIVE | EXCLUSIVE | CONTAINS | BEFORE | AFTER | BETWEEN |

NOT\_BETWEEN | ON

#### **Values**

The criteria values to use for the segment dimension. Depending on the value of the AttributeType property, endpoints are included or excluded from the segment if their attribute values match the criteria values.

Type: Array of type string

Required: True

# ClosedDays

The time when a journey will not send messages. QuietTime should be configured first and SendingSchedule should be set to true.

#### **EMAIL**

Rules for the Email channel.

**Type**: Array of type ClosedDaysRule

Required: False

#### **SMS**

Rules for the SMS channel.

**Type**: Array of type ClosedDaysRule

Required: False

#### **PUSH**

Rules for the Push channel.

Type: Array of type ClosedDaysRule

Required: False

### **VOICE**

Rules for the Voice channel.

**Type**: Array of type ClosedDaysRule

Required: False

#### **CUSTOM**

Rules for the Custom channel.

Type: Array of type ClosedDaysRule

Required: False

# ${\bf Closed Days Rule}$

Specifies the rule settings for when messages can't be sent.

### Name

The name of the closed rule.

**Type**: string **Required**: True

### **StartDateTime**

StartDateTime ISO 8601 format

**Type**: string **Required**: True

### **EndDateTime**

EndDateTime ISO 8601 format

**Type**: string **Required**: True

# Condition

Specifies the conditions to evaluate for an activity in a journey, and how to evaluate those conditions.

### **Conditions**

The conditions to evaluate for the activity.

**Type**: Array of type SimpleCondition

Required: False

# Operator

Specifies how to handle multiple conditions for the activity. For example, if you specify two conditions for an activity, whether both or only one of the conditions must be met for the activity to be performed.

**Type**: string Required: False

Values: ALL | ANY

# ConditionalSplitActivity

Specifies the settings for a yes/no split activity in a journey. This type of activity sends participants down one of two paths in a journey, based on conditions that you specify.



# Note

To create yes/no split activities that send participants down different paths based on push notification events (such as Open or Received events), your mobile app has to specify the User ID and Endpoint ID values. For more information, see Integrating Amazon Pinpoint with your application in the Amazon Pinpoint Developer Guide.

### **Condition**

The conditions that define the paths for the activity, and the relationship between the conditions.

Type: Condition
Required: False

# **TrueActivity**

The unique identifier for the activity to perform if the conditions are met.

Type: string

Required: False

# **FalseActivity**

The unique identifier for the activity to perform if the conditions aren't met.

Type: string

Required: False

#### **EvaluationWaitTime**

The amount of time to wait before determining whether the conditions are met, or the date and time when Amazon Pinpoint determines whether the conditions are met.

Type: WaitTime Required: False

# CustomMessageActivity

The settings for a custom message activity. This type of activity calls an AWS Lambda function or web hook that sends messages to participants.

# MessageConfig

Specifies the message data included in a custom channel message that's sent to participants in a journey.

Type: <u>JourneyCustomMessage</u>

**Required**: False

### **NextActivity**

The unique identifier for the next activity to perform, after Amazon Pinpoint calls the AWS Lambda function or web hook.

Type: string

Required: False

# **DeliveryUri**

The destination to send the campaign or treatment to. This value can be one of the following:

- The name or Amazon Resource Name (ARN) of an AWS Lambda function to invoke to handle delivery of the campaign or treatment.
- The URL for a web application or service that supports HTTPS and can receive the message. The URL has to be a full URL, including the HTTPS protocol.

**Type**: string

Required: False

# **EndpointTypes**

The types of endpoints to send the custom message to. Each valid value maps to a type of channel that you can associate with an endpoint by using the Channel Type property of an endpoint.

**Type**: Array of type string

Required: False

Values: PUSH | GCM | APNS | APNS\_SANDBOX | APNS\_VOIP | APNS\_VOIP\_SANDBOX |

ADM | SMS | VOICE | EMAIL | BAIDU | CUSTOM | IN\_APP

### **TemplateName**

The name of the custom message template to use for the message. If specified, this value must match the name of an existing message template.

Type: string

**Required**: False

### **TemplateVersion**

The unique identifier for the version of the message template to use for the message. If specified, this value must match the identifier for an existing template version. To retrieve a list of versions and version identifiers for a template, use the Template Versions resource.

If you don't specify a value for this property, Amazon Pinpoint uses the *active version* of the template. The *active version* is typically the version of a template that's been most recently reviewed and approved for use, depending on your workflow. It isn't necessarily the latest version of a template.

**Type**: string **Required**: False

# **EmailMessageActivity**

Specifies the settings for an email activity in a journey. This type of activity sends an email message to participants.

# MessageConfig

Specifies the sender address for an email message that's sent to participants in the journey.

Type: JourneyEmailMessage

**Required**: False

# **NextActivity**

The unique identifier for the next activity to perform, after the message is sent.

**Type**: string **Required**: False

# **TemplateName**

The name of the email message template to use for the message. If specified, this value must match the name of an existing message template.

Type: string

Required: False

### **TemplateVersion**

The unique identifier for the version of the email template to use for the message. If specified, this value must match the identifier for an existing template version. To retrieve a list of versions and version identifiers for a template, use the Template Versions resource.

If you don't specify a value for this property, Amazon Pinpoint uses the *active version* of the template. The *active version* is typically the version of a template that's been most recently reviewed and approved for use, depending on your workflow. It isn't necessarily the latest version of a template.

**Type**: string **Required**: False

### **EventCondition**

Specifies the conditions to evaluate for an event that applies to an activity in a journey.

### **Dimensions**

The dimensions for the event filter to use for the activity.

**Type:** EventDimensions

Required: False

# MessageActivity

The message identifier (message\_id) for the message to use when determining whether message events meet the condition.

**Type**: string **Required**: False

### **EventDimensions**

Specifies the dimensions for an event filter that determines when a campaign is sent or a journey activity is performed.

# **EventType**

The name of the event that causes the campaign to be sent or the journey activity to be performed. This can be a standard event that Amazon Pinpoint generates, such as \_email.delivered or \_custom.delivered. For campaigns, this can also be a custom event that's specific to your application. For information about standard events, see <a href="Streaming Amazon">Streaming Amazon</a> Pinpoint Events in the Amazon Pinpoint Developer Guide.

**Type**: SetDimension

Required: False

#### **Attributes**

One or more custom attributes that your application reports to Amazon Pinpoint. You can use these attributes as selection criteria when you create an event filter.

**Type**: object

Required: False

#### **Metrics**

One or more custom metrics that your application reports to Amazon Pinpoint. You can use these metrics as selection criteria when you create an event filter.

Type: object

Required: False

### **EventFilter**

Specifies the settings for an event that causes a campaign to be sent or a journey activity to be performed.

#### **Dimensions**

The dimensions for the event filter to use for the campaign or the journey activity.

**Type**: EventDimensions

**Required**: True

# FilterType

The type of event that causes the campaign to be sent or the journey activity to be performed. Valid values are: SYSTEM, sends the campaign or performs the activity when a system event occurs; and, ENDPOINT, sends the campaign or performs the activity when an endpoint event (Events resource) occurs.

**Type**: string **Required**: True

Values: SYSTEM | ENDPOINT | USER

### **EventStartCondition**

Specifies the settings for an event that causes a journey activity to start.

### **EventFilter**

The EventFilter for defined for scheduling Event based Journey

Type: <u>EventFilter</u> Required: False

### SegmentId

Accept only Endpoints events from this specific dynamic segmentId

**Type**: string **Required**: False

### **GPSCoordinates**

Specifies the GPS coordinates of a location.

### Latitude

The latitude coordinate of the location.

**Type**: number **Required**: True

### Longitude

The longitude coordinate of the location.

**Type**: number **Required**: True

### **GPSPointDimension**

Specifies GPS-based criteria for including or excluding endpoints from a segment.

### **Coordinates**

The GPS coordinates to measure distance from.

**Type**: GPSCoordinates

**Required**: True

### RangeInKilometers

The range, in kilometers, from the GPS coordinates.

**Type**: number **Required**: False

# **HoldoutActivity**

Specifies the settings for a holdout activity in a journey. This type of activity stops a journey for a specified percentage of participants.

# Percentage

The percentage of participants who shouldn't continue the journey.

To determine which participants are held out, Amazon Pinpoint applies a probability-based algorithm to the percentage that you specify. Therefore, the actual percentage of participants who are held out may not be equal to the percentage that you specify.

**Type**: integer **Required**: True

### **NextActivity**

The unique identifier for the next activity to perform, after performing the holdout activity.

**Type**: string **Required**: False

# **JourneyCustomMessage**

Specifies the message content for a custom channel message that's sent to participants in a journey.

#### Data

The message content that's passed to an AWS Lambda function or to a web hook.

**Type**: string **Required**: False

# **JourneyEmailMessage**

Specifies the "From" address for an email message that's sent to participants in a journey.

#### **FromAddress**

The verified email address to send the email message from. The default address is the FromAddress specified for the email channel for the application.

**Type**: string **Required**: False

# **JourneyLimits**

Specifies limits on the messages that a journey can send and the number of times participants can enter a journey.

# **DailyCap**

The maximum number of messages that the journey can send to a single participant during a 24-hour period. The maximum value is 100.

**Type**: integer **Required**: False

# **TotalCap**

The maximum number of messages a journey can sent to a single endpoint. The maximum value is 100. If set to 0, this limit will not apply.

**Type**: integer **Required**: False

### TimeframeCap

The number of messages that an endpoint can receive during the specified timeframe.

**Type**: JourneyTimeframeCap

Required: False

# MessagesPerSecond

The maximum number of messages that the journey can send each second.

**Type**: integer **Required**: False

# **EndpointReentryCap**

The maximum number of times that a participant can enter the journey. The maximum value is 100. To allow participants to enter the journey an unlimited number of times, set this value to 0.

**Type**: integer **Required**: False

# EndpointReentryInterval

Minimum time that must pass before an endpoint can re-enter a given journey.

**Type**: string **Required**: False

# **JourneyPushMessage**

Specifies the message configuration for a push notification that's sent to participants in a journey.

### **TimeToLive**

The number of seconds that the push notification service should keep the message, if the service is unable to deliver the notification the first time. This value is converted to an expiration value when it's sent to a push notification service. If this value is 0, the service treats the notification as if it expires immediately and the service doesn't store or try to deliver the notification again.

This value doesn't apply to messages that are sent through the Amazon Device Messaging (ADM) service.

**Type**: string **Required**: False

# **JourneyResponse**

Provides information about the status, configuration, and other settings for a journey.

### Name

The name of the journey.

**Type**: string **Required**: False

#### Schedule

The schedule settings for the journey.

Type: JourneySchedule

Required: False

#### **StartCondition**

The segment that defines which users are participants in the journey.

**Type: StartCondition** 

Required: False

#### Limits

The messaging and entry limits for the journey.

Type: <u>JourneyLimits</u>
Required: False

# **StartActivity**

The unique identifier for the first activity in the journey.

**Type**: string **Required**: False

#### **Activities**

A map that contains a set of Activity objects, one object for each activity in the journey. For each Activity object, the key is the unique identifier (string) for an activity and the value is the settings for the activity.

**Type**: object **Required**: False

# RefreshFrequency

The frequency with which Amazon Pinpoint evaluates segment and event data for the journey, as a duration in ISO 8601 format.

**Type**: string **Required**: False

### QuietTime

The quiet time settings for the journey. Quiet time is a specific time range when a journey doesn't send messages to participants, if all the following conditions are met:

• The EndpointDemographic. Timezone property of the endpoint for the participant is set to a valid value.

• The current time in the participant's time zone is later than or equal to the time specified by the QuietTime. Start property for the journey.

• The current time in the participant's time zone is earlier than or equal to the time specified by the QuietTime. End property for the journey.

If any of the preceding conditions isn't met, the participant will receive messages from the journey, even if quiet time is enabled.

Type: QuietTime Required: False

### WaitForQuietTime

Indicates whether endpoints in quiet hours should enter a wait activity until quiet hours have elapsed.

**Type**: boolean **Required**: False

# SendingSchedule

Indicates if journey has Advance Quiet Time enabled. This flag should be set to true in order to allow using OpenHours and ClosedDays.

**Type**: boolean **Required**: False

# **OpenHours**

The time when a journey can send messages. QuietTime should be configured first and SendingSchedule should be set to true.

Type: OpenHours
Required: False

### ClosedDays

The time when a journey will not send messages. QuietTime should be configured first and SendingSchedule should be set to true.

Type: ClosedDays
Required: False

# RefreshOnSegmentUpdate

Indicates whether the journey participants should be refreshed when a segment is updated.

**Type**: boolean **Required**: False

#### LocalTime

Specifies whether the journey's scheduled start and end times use each participant's local time. If this value is true, the schedule uses each participant's local time.

**Type**: boolean **Required**: False

#### CreationDate

The date, in ISO 8601 format, when the journey was created.

**Type**: string **Required**: False

# LastModifiedDate

The date, in ISO 8601 format, when the journey was last modified.

**Type**: string **Required**: False

#### State

The current status of the journey. Possible values are:

- DRAFT The journey is being developed and hasn't been published yet.
- ACTIVE The journey has been developed and published. Depending on the journey's schedule, the journey may currently be running or scheduled to start running at a later time. If a journey's status is ACTIVE, you can't add, change, or remove activities from it.
- COMPLETED The journey has been published and has finished running. All participants have entered the journey and no participants are waiting to complete the journey or any activities in the journey.
- CANCELLED The journey has been stopped. If a journey's status is CANCELLED, you can't add, change, or remove activities or segment settings from the journey.
- CLOSED The journey has been published and has started running. It may have also passed its scheduled end time, or passed its scheduled start time and a refresh frequency hasn't been specified for it. If a journey's status is CLOSED, you can't add participants to it, and no existing participants can enter the journey for the first time. However, any existing participants who are currently waiting to start an activity may continue the journey.

### Note

A journey in the CLOSED state is still counted against the Maximum number of active journeys quota. For more information see Journey quotas.

**Type**: string

**Required**: False

Values: DRAFT | ACTIVE | PAUSED | COMPLETED | CANCELLED | CLOSED |

PENDING\_APPROVAL

#### tags

This object is not used or supported.

**Type**: object **Required**: False

#### **TimezoneEstimationMethods**

An array of time zone estimation methods, if any, to use for determining an Endpoints time zone if the Endpoint does not have a value for the Demographic. Timezone attribute.

- PHONE\_NUMBER A time zone is estimated based on the Endpoint.Location.Country and Endpoint.Address.
- POSTAL\_CODE A time zone is estimated based on the Endpoint.Location.Country and Endpoint.Location.PostalCode.



# Note

POSTAL\_CODE estimation is only supported in the United States, United Kingdom, Australia, New Zealand, Canada, France, Italy, Spain, Germany and in regions where Amazon Pinpoint is available.

 Both - A time zone is estimated based on the Endpoint.Location.Country, Endpoint.Address and Endpoint.Location.PostalCode.

**Type**: Array of type string

Required: False

Values: PHONE\_NUMBER | POSTAL\_CODE

#### Id

The unique identifier for the journey.

**Type**: string Required: True

# **ApplicationId**

The unique identifier for the application that the journey applies to.

**Type**: string Required: True

# **JourneySMSMessage**

Specifies the sender ID and message type for an SMS message that's sent to participants in a journey.

#### SenderId

The sender ID to display as the sender of the message on a recipient's device. Support for sender IDs varies by country. For more information, see <u>Supported Countries and Regions</u> in the Amazon Pinpoint User Guide.

**Type**: string

Required: False

# OriginationNumber

The number to send the SMS message from. The phone number that you specify must exist in your Amazon Pinpoint account—you can't pass an arbitrary phone number. If you want to use a sender ID to send your message, omit this parameter and use SenderId instead.

**Type**: string

Required: False

### MessageType

The SMS message type. Valid values are TRANSACTIONAL (for messages that are critical or time-sensitive, such as a one-time passwords) and PROMOTIONAL (for messsages that aren't critical or time-sensitive, such as marketing messages).

Type: string

Required: False

Values: TRANSACTIONAL | PROMOTIONAL

### **EntityId**

A registered Entity ID (currently only used when sending messages to recipients in India).

**Type**: string

Required: False

# **TemplateId**

A registered Template ID (currently only used when sending messages to recipients in India).

**Type**: string **Required**: False

# **JourneySchedule**

Specifies the schedule settings for a journey.

### StartTime

The scheduled time, in ISO 8601 format, when the journey began or will begin.

**Type**: string **Required**: False

### **EndTime**

The scheduled time, in ISO 8601 format, when the journey ended or will end.

**Type**: string **Required**: False

#### **Timezone**

The starting UTC offset for the journey schedule, if the value of the journey's LocalTime property is true. Valid values are: UTC, UTC+01, UTC+02, UTC+03, UTC+03:30, UTC+04, UTC+04:30, UTC+05, UTC+05:30, UTC+05:45, UTC+06, UTC+06:30, UTC+07, UTC+08, UTC+08:45, UTC+09, UTC+09:30, UTC+10, UTC+10:30, UTC+11, UTC+12, UTC+12:45, UTC+13, UTC+13:45, UTC-02, UTC-02:30, UTC-03, UTC-03:30, UTC-04, UTC-05, UTC-06, UTC-07, UTC-08, UTC-09, UTC-09:30, UTC-10, and UTC-11.

**Type**: string **Required**: False

# **JourneyStateRequest**

Changes the status of a journey.

#### **State**

The status of the journey. Currently, the supported values are ACTIVE, PAUSED, and CANCELLED.

If you cancel a journey, Amazon Pinpoint continues to perform activities that are currently in progress, until those activities are complete. Amazon Pinpoint also continues to collect and aggregate analytics data for those activities, until they are complete, and any activities that were complete when you cancelled the journey.

After you cancel a journey, you can't add, change, or remove any activities from the journey. In addition, Amazon Pinpoint stops evaluating the journey and doesn't perform any activities that haven't started.

When the journey is paused, Amazon Pinpoint continues to perform activities that are currently in progress, until those activities are complete. Endpoints will stop entering journeys when the journey is paused and will resume entering the journey after the journey is resumed. For wait activities, wait time is paused when the journey is paused. Currently, PAUSED only supports journeys with a segment refresh interval.

**Type**: string **Required**: True

Values: DRAFT | ACTIVE | PAUSED | COMPLETED | CANCELLED | CLOSED |

PENDING\_APPROVAL

# **JourneyTimeframeCap**

The number of messages that can be sent to an endpoint during the specified timeframe for all journeys.

### **Days**

The length of the timeframe in days. The maximum value is 30. If set to 0, this limit will not apply.

**Type**: integer **Required**: False

### Cap

The maximum number of messages that all journeys can send to an endpoint during the specified timeframe. The maximum value is 100. If set to 0, this limit will not apply.

**Type**: integer **Required**: False

# MessageBody

Provides information about an API request or response.

# **RequestID**

The unique identifier for the request or response.

Type: string

Required: False

# Message

The message that's returned from the API.

Type: string

Required: False

# MetricDimension

Specifies metric-based criteria for including or excluding endpoints from a segment. These criteria derive from custom metrics that you define for endpoints.

# ComparisonOperator

The operator to use when comparing metric values. Valid values are: GREATER\_THAN, LESS\_THAN, GREATER\_THAN\_OR\_EQUAL, LESS\_THAN\_OR\_EQUAL, and EQUAL.

**Type**: string **Required**: True

#### Value

The value to compare.

**Type**: number Required: True

### MultiConditionalBranch

Specifies a condition to evaluate for an activity path in a journey.

### **Condition**

The condition to evaluate for the activity path.

**Type:** SimpleCondition

Required: False

# **NextActivity**

The unique identifier for the next activity to perform, after completing the activity for the path.

Type: string **Required**: False

# MultiConditionalSplitActivity

Specifies the settings for a multivariate split activity in a journey. This type of activity sends participants down one of as many as five paths (including a default Else path) in a journey, based on conditions that you specify.



To create multivariate split activities that send participants down different paths based on push notification events (such as Open or Received events), your mobile app has to specify the User ID and Endpoint ID values. For more information, see Integrating Amazon Pinpoint with your application in the Amazon Pinpoint Developer Guide.

#### **Branches**

The paths for the activity, including the conditions for entering each path and the activity to perform for each path.

**Type**: Array of type MultiConditionalBranch

Required: False

# **DefaultActivity**

The unique identifier for the activity to perform for participants who don't meet any of the conditions specified for other paths in the activity.

**Type**: string **Required**: False

#### **EvaluationWaitTime**

The amount of time to wait or the date and time when Amazon Pinpoint determines whether the conditions are met.

Type: WaitTime Required: False

# **OpenHours**

Specifies the times when message are allowed to be sent to endpoints.

### **EMAIL**

Specifies the schedule settings for the email channel.

**Type**: object **Required**: False

#### **SMS**

Specifies the schedule settings for the SMS channel.

Type: object

Required: False

#### **PUSH**

Specifies the schedule settings for the push channel.

**Type**: object **Required**: False

### **VOICE**

Specifies the schedule settings for the voice channel.

**Type**: object **Required**: False

### **CUSTOM**

Specifies the schedule settings for the custom channel.

**Type**: object **Required**: False

# OpenHoursRule

Specifies the start and end time for OpenHours.

#### StartTime

The start of the scheduled time, in ISO 8601 format, when the channel can send messages.

**Type**: string **Required**: True

#### **EndTime**

The end of the scheduled time, in ISO 8601 format, when the channel can't send messages.

Type: string

Required: True

# PushMessageActivity

Specifies the settings for a push notification activity in a journey. This type of activity sends a push notification to participants.

# MessageConfig

Specifies the time to live (TTL) value for push notifications that are sent to participants in a journey.

Type: JourneyPushMessage

Required: False

# **NextActivity**

The unique identifier for the next activity to perform, after the message is sent.

**Type**: string

Required: False

### **TemplateName**

The name of the push notification template to use for the message. If specified, this value must match the name of an existing message template.

Type: string

Required: False

### **TemplateVersion**

The unique identifier for the version of the push notification template to use for the message. If specified, this value must match the identifier for an existing template version. To retrieve a list of versions and version identifiers for a template, use the Template Versionsresource.

If you don't specify a value for this property, Amazon Pinpoint uses the *active version* of the template. The *active version* is typically the version of a template that's been most recently

reviewed and approved for use, depending on your workflow. It isn't necessarily the latest version of a template.

Type: string

Required: False

# QuietTime

Specifies the start and end times that define a time range when messages aren't sent to endpoints.

### Start

The specific time when quiet time begins. This value has to use 24-hour notation and be in HH:MM format, where HH is the hour (with a leading zero, if applicable) and MM is the minutes. For example, use 02:30 to represent 2:30 AM, or 14:30 to represent 2:30 PM.

**Type**: string

Required: False

#### **End**

The specific time when quiet time ends. This value has to use 24-hour notation and be in HH:MM format, where HH is the hour (with a leading zero, if applicable) and MM is the minutes. For example, use 02:30 to represent 2:30 AM, or 14:30 to represent 2:30 PM.

Type: string

Required: False

# RandomSplitActivity

Specifies the settings for a random split activity in a journey. This type of activity randomly sends specified percentages of participants down one of as many as five paths in a journey, based on conditions that you specify.

#### **Branches**

The paths for the activity, including the percentage of participants to enter each path and the activity to perform for each path.

**Type**: Array of type RandomSplitEntry

Required: False

# RandomSplitEntry

Specifies the settings for a path in a random split activity in a journey.

### **Percentage**

The percentage of participants to send down the activity path.

To determine which participants are sent down each path, Amazon Pinpoint applies a probability-based algorithm to the percentages that you specify for the paths. Therefore, the actual percentage of participants who are sent down a path may not be equal to the percentage that you specify.

**Type**: integer **Required**: False

### **NextActivity**

The unique identifier for the next activity to perform, after completing the activity for the path.

**Type**: string **Required**: False

# RecencyDimension

Specifies criteria for including or excluding endpoints from a segment based on how recently an endpoint was active.

# RecencyType

The type of recency dimension to use for the segment. Valid values are: ACTIVE, endpoints that were active within the specified duration are included in the segment; and, INACTIVE, endpoints that weren't active within the specified duration are included in the segment.

Type: string

Required: True

Values: ACTIVE | INACTIVE

### **Duration**

The duration to use when determining whether an endpoint is active or inactive.

**Type**: string **Required**: True

Values: HR\_24 | DAY\_7 | DAY\_14 | DAY\_30

# **SMSMessageActivity**

Specifies the settings for an SMS activity in a journey. This type of activity sends a text message to participants.

### MessageConfig

Specifies the sender ID and message type for an SMS message that's sent to participants in a journey.

Type: JourneySMSMessage

Required: False

## **NextActivity**

The unique identifier for the next activity to perform, after the message is sent.

**Type**: string **Required**: False

## **TemplateName**

The name of the SMS message template to use for the message. If specified, this value must match the name of an existing message template.

**Type**: string **Required**: False

### **TemplateVersion**

The unique identifier for the version of the SMS template to use for the message. If specified, this value must match the identifier for an existing template version. To retrieve a list of versions and version identifiers for a template, use the Template Versions resource.

If you don't specify a value for this property, Amazon Pinpoint uses the *active version* of the template. The *active version* is typically the version of a template that's been most recently reviewed and approved for use, depending on your workflow. It isn't necessarily the latest version of a template.

**Type**: string

Required: False

# **SegmentBehaviors**

Specifies dimension settings for including or excluding endpoints from a segment based on how recently an endpoint was active.

### Recency

The dimension settings that are based on how recently an endpoint was active.

**Type**: RecencyDimension

Required: False

# **SegmentCondition**

Specifies a segment to associate with an activity in a journey.

# SegmentId

The unique identifier for the segment to associate with the activity.

**Type**: string

Required: True

# SegmentDemographics

Specifies demographic-based dimension settings for including or excluding endpoints from a segment. These settings derive from characteristics of endpoint devices, such as platform, make, and model.

### Channel

The channel criteria for the segment.

Type: <u>SetDimension</u>
Required: False

### **Platform**

The device platform criteria for the segment.

Type: <u>SetDimension</u>
Required: False

## DeviceType

The device type criteria for the segment.

Type: <u>SetDimension</u>
Required: False

### **AppVersion**

The app version criteria for the segment.

Type: <u>SetDimension</u>
Required: False

#### Make

The device make criteria for the segment.

**Type:** SetDimension

Required: False

#### Model

The device model criteria for the segment.

Type: <u>SetDimension</u>
Required: False

# **SegmentDimensions**

Specifies the dimension settings for a segment.

# **Demographic**

The demographic-based criteria, such as device platform, for the segment.

**Type:** SegmentDemographics

Required: False

### Location

The location-based criteria, such as region or GPS coordinates, for the segment.

**Type**: SegmentLocation

Required: False

#### **Behavior**

The behavior-based criteria, such as how recently users have used your app, for the segment.

**Type**: SegmentBehaviors

Required: False

### **Attributes**

One or more custom attributes to use as criteria for the segment. For more information see AttributeDimension

**Type**: object **Required**: False

### **Metrics**

One or more custom metrics to use as criteria for the segment.

**Type**: object **Required**: False

### **UserAttributes**

One or more custom user attributes to use as criteria for the segment.

**Type**: object **Required**: False

# **SegmentLocation**

Specifies geographical dimension settings for a segment.

## Country

The country or region code, in ISO 3166-1 alpha-2 format, for the segment.

Type: <u>SetDimension</u>
Required: False

### **GPSPoint**

The GPS location and range for the segment.

**Type**: GPSPointDimension

Required: False

### **SetDimension**

Specifies the dimension type and values for a segment dimension.

### DimensionType

The type of segment dimension to use. Valid values are: INCLUSIVE, endpoints that match the criteria are included in the segment; and, EXCLUSIVE, endpoints that match the criteria are excluded from the segment.

**Type**: string **Required**: False

Values: INCLUSIVE | EXCLUSIVE

#### **Values**

The criteria values to use for the segment dimension. Depending on the value of the DimensionType property, endpoints are included or excluded from the segment if their values match the criteria values.

**Type**: Array of type string

**Required**: True

# **SimpleCondition**

Specifies a condition to evaluate for an activity in a journey.

# segmentDimensions

The dimension settings for the segment that's associated with the activity.

**Type**: <u>SegmentDimensions</u>

Required: False

# SegmentCondition

The segment that's associated with the activity.

**Type**: SegmentCondition

Required: False

#### **EventCondition**

The dimension settings for the event that's associated with the activity.

**Type**: EventCondition

Required: False

### **StartCondition**

Specifies the conditions for the first activity in a journey. This activity and its conditions determine which users are participants in a journey.

### Description

The custom description of the condition.

**Type**: string **Required**: False

#### **EventStartCondition**

The event start condition that can trigger a journey.

**Type**: EventStartCondition

Required: False

### SegmentStartCondition

The segment that's associated with the first activity in the journey. This segment determines which users are participants in the journey.

**Type:** SegmentCondition

Required: False

# WaitActivity

Specifies the settings for a wait activity in a journey. This type of activity waits for a certain amount of time or until a specific date and time before moving participants to the next activity in a journey.

#### WaitTime

The amount of time to wait or the date and time when the activity moves participants to the next activity in the journey.

**REST API Reference** Amazon Pinpoint

Type: WaitTime **Required**: False

### **NextActivity**

The unique identifier for the next activity to perform, after performing the wait activity.

**Type**: string

Required: False

### **WaitTime**

Specifies a duration or a date and time that indicates when Amazon Pinpoint determines whether an activity's conditions have been met or an activity moves participants to the next activity in a journey.

#### WaitFor

The amount of time to wait, as a duration in ISO 8601 format, before determining whether the activity's conditions have been met or moving participants to the next activity in the journey.

**Type**: string

Required: False

#### WaitUntil

The date and time, in ISO 8601 format, when Amazon Pinpoint determines whether the activity's conditions have been met or the activity moves participants to the next activity in the journey.

**Type**: string

Required: False

# See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

See also 788

# **UpdateJourneyState**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Journeys**

A *journey* is an automated workflow that performs a series of messaging activities for an Amazon Pinpoint application. Each activity is a customizable component that specifies what causes the activity to occur, when the activity occurs, what the activity does, and which users the activity applies to. The paths and relationships between activities vary based on conditions and criteria that you define, such as specific user attributes and events.

The Journeys resource represents all the journeys that are associated with an Amazon Pinpoint application. You can use this resource to create a new journey or retrieve information about all the journeys that are associated with an application. To update or delete a journey, use the <u>Journey</u> resource.

### **URI**

/v1/apps/application-id/journeys

# **HTTP** methods

#### **GET**

**Operation ID:** ListJourneys

Journeys 789

Retrieves information about the status, configuration, and other settings for all the journeys that are associated with an application.

# **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# **Query parameters**

Name	Туре	Required	Description
page-size	String	False	The maximum number of items to include in each page of a paginated response. This parameter is not supported for application,

Name	Туре	Required	Description
			campaign, and journey metrics.
token	String	False	The NextToken string that specifies which page of results to return in a paginated response.

# Responses

Status code	Response model	Description
200	<u>JourneysResponse</u>	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	MessageBody	The request failed because the specified resource was not found (NotFoundException).
405	MessageBody	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	MessageBody	The request failed because the payload for the body of the request is too large

Status code	Response model	Description
		(RequestEntityTooLargeExcep tion).
429	MessageBody	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **POST**

**Operation ID:** CreateJourney

Creates a journey for an application.

# Path parameters

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
201	<u>JourneyResponse</u>	The request succeeded and the specified resource was created.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	MessageBody	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	MessageBody	The request failed because the specified resource was not found (NotFoundException).
405	MessageBody	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body

Status code	Response model	Description
		of the request is too large (RequestEntityTooLargeExcep tion).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Journeys resource.

# **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

### Responses

Status code	Response model	Description
200	None	The request succeeded.

## **Schemas**

# **Request bodies**

### **POST schema**

```
"Name": "string",
"Schedule": {
  "StartTime": "string",
 "EndTime": "string",
  "Timezone": "string"
},
"StartCondition": {
  "Description": "string",
  "EventStartCondition": {
    "EventFilter": {
      "Dimensions": {
        "EventType": {
          "DimensionType": enum,
          "Values": [
            "string"
          ]
        },
        "Attributes": {
        },
        "Metrics": {
      },
      "<u>FilterType</u>": enum
    "SegmentId": "string"
  },
  "SegmentStartCondition": {
    "SegmentId": "string"
  }
```

```
},
"Limits": {
  "DailyCap": integer,
  "TotalCap": integer,
  "TimeframeCap": {
    "Days": integer,
    "Cap": integer
  },
  "MessagesPe<u>rSecond</u>": integer,
  "EndpointReentryCap": integer,
  "EndpointReentryInterval": "string"
},
"StartActivity": "string",
"Activities": {
},
"RefreshFrequency": "string",
"QuietTime": {
 "Start": "string",
 "End": "string"
},
"WaitForQuietTime": boolean,
"SendingSchedule": boolean,
"OpenHours": {
  "EMAIL": {
  },
  "SMS": {
  },
  "PUSH": {
  "<u>VOICE</u>": {
  },
  "CUSTOM": {
  }
},
"ClosedDays": {
  "EMAIL": [
    {
      "Name": "string",
      "StartDateTime": "string",
      "EndDateTime": "string"
    }
  ],
  "SMS": [
```

```
"Name": "string",
        "StartDateTime": "string",
        "EndDateTime": "string"
      }
    ],
    "PUSH": [
      {
        "Name": "string",
        "StartDateTime": "string",
        "EndDateTime": "string"
      }
    ],
    "<u>VOICE</u>": [
        "Name": "string",
        "StartDateTime": "string",
        "EndDateTime": "string"
      }
    ],
    "CUSTOM": [
        "Name": "string",
        "StartDateTime": "string",
        "EndDateTime": "string"
      }
    ]
  },
  ""RefreshOnSegmentUpdate": boolean,
  "LocalTime": boolean,
  "CreationDate": "string",
  "LastModifiedDate": "string",
  "State": enum,
  "TimezoneEstimationMethods": [
    enum
  ]
}
```

# **Response bodies**

### JourneysResponse schema

```
{
    "<u>Item</u>": [
```

```
{
  "Name": "string",
  "Schedule": {
    "StartTime": "string",
    "EndTime": "string",
    "Timezone": "string"
  },
  "StartCondition": {
    "Description": "string",
    "EventStartCondition": {
      "EventFilter": {
        "Dimensions": {
          "EventType": {
            "DimensionType": enum,
            "Values": [
              "string"
            ]
          },
          "Attributes": {
          },
          "Metrics": {
          }
        },
        "FilterType": enum
      },
      "SegmentId": "string"
    },
    "SegmentStartCondition": {
      "SegmentId": "string"
    }
  },
  "Limits": {
    "DailyCap": integer,
    "TotalCap": integer,
    "TimeframeCap": {
      "Days": integer,
      "Cap": integer
    },
    "MessagesPerSecond": integer,
    "EndpointReentryCap": integer,
    "EndpointReentryInterval": "string"
  "StartActivity": "string",
  "Activities": {
```

```
},
"RefreshFrequency": "string",
"QuietTime": {
  "Start": "string",
  "End": "string"
},
"WaitForQuietTime": boolean,
"SendingSchedule": boolean,
"OpenHours": {
  "EMAIL": {
  },
  "<u>SMS</u>": {
  },
  "PUSH": {
  },
  "<u>VOICE</u>": {
  },
  "CUSTOM": {
  }
},
"ClosedDays": {
  "EMAIL": [
    {
      "Name": "string",
      "StartDateTime": "string",
      "EndDateTime": "string"
    }
  ],
  "<u>SMS</u>": [
    {
      "Name": "string",
      "StartDateTime": "string",
      "EndDateTime": "string"
    }
  ],
  "PUSH": [
    {
      "Name": "string",
      "StartDateTime": "string",
      "EndDateTime": "string"
    }
  ],
  "VOICE": [
    {
```

```
"Name": "string",
            "StartDateTime": "string",
            "EndDateTime": "string"
          }
        ],
        "CUSTOM": [
            "Name": "string",
            "StartDateTime": "string",
            "EndDateTime": "string"
          }
        ]
      },
      "RefreshOnSegmentUpdate": boolean,
      "LocalTime": boolean,
      "CreationDate": "string",
      "LastModifiedDate": "string",
      "State": enum,
      "tags": {
      },
      "TimezoneEstimationMethods": [
        enum
      ],
      "Id": "string",
      "ApplicationId": "string"
    }
  ],
  "NextToken": "string"
}
```

### JourneyResponse schema

```
"Dimensions": {
        "EventType": {
          "DimensionType": enum,
          "Values": [
            "string"
          ]
        },
        "Attributes": {
        },
        "Metrics": {
      },
      "FilterType": enum
    "SegmentId": "string"
  },
  "SegmentStartCondition": {
    "SegmentId": "string"
  }
},
"Limits": {
  "DailyCap": integer,
  "TotalCap": integer,
  "TimeframeCap": {
    "Days": integer,
    "Cap": integer
  },
  "MessagesPe<u>rSecond</u>": integer,
  "EndpointReentryCap": integer,
  "EndpointReentryInterval": "string"
},
"StartActivity": "string",
"Activities": {
},
"RefreshFrequency": "string",
"QuietTime": {
 "Start": "string",
  "End": "string"
},
"WaitForQuietTime": boolean,
"SendingSchedule": boolean,
"OpenHours": {
  "EMAIL": {
  },
```

```
"SMS": {
  },
  "<u>PUSH</u>": {
  },
  "<u>VOICE</u>": {
  },
  "CUSTOM": {
},
"ClosedDays": {
  "EMAIL": [
    {
      "Name": "string",
      "StartDateTime": "string",
      "EndDateTime": "string"
    }
  ],
  "SMS": [
    {
      "Name": "string",
      "StartDateTime": "string",
      "EndDateTime": "string"
    }
  ],
  "PUSH": [
   {
      "Name": "string",
      "StartDateTime": "string",
      "EndDateTime": "string"
    }
  ],
  "VOICE": [
    {
     "Name": "string",
      "StartDateTime": "string",
      "EndDateTime": "string"
    }
  ],
  "CUSTOM": [
      "Name": "string",
      "StartDateTime": "string",
      "EndDateTime": "string"
    }
```

```
},

"RefreshOnSegmentUpdate": boolean,

"LocalTime": boolean,

"CreationDate": "string",

"LastModifiedDate": "string",

"State": enum,

"tags": {
    },

"TimezoneEstimationMethods": [
    enum
],

"Id": "string",

"ApplicationId": "string"
}
```

### MessageBody schema

```
{
    "RequestID": "string",
    "Message": "string"
}
```

# **Properties**

# **Activity**

Specifies the configuration and other settings for an activity in a journey.

# Description

The custom description of the activity.

**Type**: string **Required**: False

# ConditionalSplit

The settings for a yes/no split activity. This type of activity sends participants down one of two paths in a journey, based on conditions that you specify.

Type: ConditionalSplitActivity

Required: False

#### **Holdout**

The settings for a holdout activity. This type of activity stops a journey for a specified percentage of participants.

Type: HoldoutActivity

Required: False

#### **MultiCondition**

The settings for a multivariate split activity. This type of activity sends participants down one of as many as five paths (including a default *Else* path) in a journey, based on conditions that you specify.

Type: MultiConditionalSplitActivity

**Required**: False

## RandomSplit

The settings for a random split activity. This type of activity randomly sends specified percentages of participants down one of as many as five paths in a journey, based on conditions that you specify.

Type: RandomSplitActivity

Required: False

#### Wait

The settings for a wait activity. This type of activity waits for a certain amount of time or until a specific date and time before moving participants to the next activity in a journey.

Type: WaitActivity
Required: False

#### **EMAIL**

The settings for an email activity. This type of activity sends an email message to participants.

**Type**: EmailMessageActivity

Required: False

#### **SMS**

The settings for an SMS activity. This type of activity sends a text message to participants.

**Type:** SMSMessageActivity

Required: False

#### **PUSH**

The settings for a push notification activity. This type of activity sends a push notification to participants.

**Type**: PushMessageActivity

Required: False

#### **CUSTOM**

The settings for a custom message activity. This type of activity calls an AWS Lambda function or web hook that sends messages to participants.

Type: CustomMessageActivity

Required: False

### **AttributeDimension**

Specifies attribute-based criteria for including or excluding endpoints from a segment.

### AttributeType

The type of segment dimension to use. Valid values are:

• INCLUSIVE – endpoints that have attributes matching the values are included in the segment.

 EXCLUSIVE – endpoints that have attributes matching the values are excluded from the segment.

- CONTAINS endpoints that have attributes' substrings match the values are included in the segment.
- BEFORE endpoints with attributes read as ISO\_INSTANT datetimes before the value are included in the segment.
- AFTER endpoints with attributes read as ISO\_INSTANT datetimes after the value are included in the segment.
- BETWEEN endpoints with attributes read as ISO\_INSTANT datetimes between the values are included in the segment.
- 0N endpoints with attributes read as ISO\_INSTANT dates on the value are included in the segment. Time is ignored in this comparison.

**Type**: string

**Required**: False

Values: INCLUSIVE | EXCLUSIVE | CONTAINS | BEFORE | AFTER | BETWEEN |

NOT\_BETWEEN | ON

#### **Values**

The criteria values to use for the segment dimension. Depending on the value of the AttributeType property, endpoints are included or excluded from the segment if their attribute values match the criteria values.

**Type**: Array of type string

**Required**: True

# ClosedDays

The time when a journey will not send messages. QuietTime should be configured first and SendingSchedule should be set to true.

#### **EMAIL**

Rules for the Email channel.

Type: Array of type ClosedDaysRule

Required: False

### **SMS**

Rules for the SMS channel.

Type: Array of type ClosedDaysRule

Required: False

### **PUSH**

Rules for the Push channel.

Type: Array of type ClosedDaysRule

Required: False

#### **VOICE**

Rules for the Voice channel.

**Type**: Array of type ClosedDaysRule

Required: False

#### **CUSTOM**

Rules for the Custom channel.

Type: Array of type ClosedDaysRule

Required: False

# ClosedDaysRule

Specifies the rule settings for when messages can't be sent.

#### Name

The name of the closed rule.

**Type**: string **Required**: True

### **StartDateTime**

StartDateTime ISO 8601 format

**Type**: string **Required**: True

#### **EndDateTime**

EndDateTime ISO 8601 format

**Type**: string **Required**: True

### **Condition**

Specifies the conditions to evaluate for an activity in a journey, and how to evaluate those conditions.

### **Conditions**

The conditions to evaluate for the activity.

**Type**: Array of type SimpleCondition

Required: False

### **Operator**

Specifies how to handle multiple conditions for the activity. For example, if you specify two conditions for an activity, whether both or only one of the conditions must be met for the activity to be performed.

**Type**: string **Required**: False

Values: ALL | ANY

# ConditionalSplitActivity

Specifies the settings for a yes/no split activity in a journey. This type of activity sends participants down one of two paths in a journey, based on conditions that you specify.



### Note

To create yes/no split activities that send participants down different paths based on push notification events (such as Open or Received events), your mobile app has to specify the User ID and Endpoint ID values. For more information, see Integrating Amazon Pinpoint with your application in the Amazon Pinpoint Developer Guide.

#### **Condition**

The conditions that define the paths for the activity, and the relationship between the conditions.

**Type: Condition** Required: False

## **TrueActivity**

The unique identifier for the activity to perform if the conditions are met.

Type: string **Required**: False

# **FalseActivity**

The unique identifier for the activity to perform if the conditions aren't met.

**Type**: string Required: False

#### **EvaluationWaitTime**

The amount of time to wait before determining whether the conditions are met, or the date and time when Amazon Pinpoint determines whether the conditions are met.

Type: WaitTime Required: False

# CustomMessageActivity

The settings for a custom message activity. This type of activity calls an AWS Lambda function or web hook that sends messages to participants.

### MessageConfig

Specifies the message data included in a custom channel message that's sent to participants in a journey.

**Type**: JourneyCustomMessage

Required: False

### **NextActivity**

The unique identifier for the next activity to perform, after Amazon Pinpoint calls the AWS Lambda function or web hook.

Type: string

Required: False

### DeliveryUri

The destination to send the campaign or treatment to. This value can be one of the following:

- The name or Amazon Resource Name (ARN) of an AWS Lambda function to invoke to handle delivery of the campaign or treatment.
- The URL for a web application or service that supports HTTPS and can receive the message. The URL has to be a full URL, including the HTTPS protocol.

**Type**: string

Required: False

### **EndpointTypes**

The types of endpoints to send the custom message to. Each valid value maps to a type of channel that you can associate with an endpoint by using the ChannelType property of an endpoint.

**Type**: Array of type string

Required: False

Values: PUSH | GCM | APNS | APNS\_SANDBOX | APNS\_VOIP | APNS\_VOIP\_SANDBOX |

ADM | SMS | VOICE | EMAIL | BAIDU | CUSTOM | IN\_APP

### **TemplateName**

The name of the custom message template to use for the message. If specified, this value must match the name of an existing message template.

**Type**: string **Required**: False

### **TemplateVersion**

The unique identifier for the version of the message template to use for the message. If specified, this value must match the identifier for an existing template version. To retrieve a list of versions and version identifiers for a template, use the Template Versions resource.

If you don't specify a value for this property, Amazon Pinpoint uses the *active version* of the template. The *active version* is typically the version of a template that's been most recently reviewed and approved for use, depending on your workflow. It isn't necessarily the latest version of a template.

**Type**: string **Required**: False

# **EmailMessageActivity**

Specifies the settings for an email activity in a journey. This type of activity sends an email message to participants.

## MessageConfig

Specifies the sender address for an email message that's sent to participants in the journey.

Type: JourneyEmailMessage

Required: False

### **NextActivity**

The unique identifier for the next activity to perform, after the message is sent.

**Type**: string **Required**: False

### **TemplateName**

The name of the email message template to use for the message. If specified, this value must match the name of an existing message template.

**Type**: string **Required**: False

### **TemplateVersion**

The unique identifier for the version of the email template to use for the message. If specified, this value must match the identifier for an existing template version. To retrieve a list of versions and version identifiers for a template, use the <u>Template Versions</u> resource.

If you don't specify a value for this property, Amazon Pinpoint uses the *active version* of the template. The *active version* is typically the version of a template that's been most recently reviewed and approved for use, depending on your workflow. It isn't necessarily the latest version of a template.

**Type**: string **Required**: False

### **EventCondition**

Specifies the conditions to evaluate for an event that applies to an activity in a journey.

#### **Dimensions**

The dimensions for the event filter to use for the activity.

**Type**: EventDimensions

Required: False

## MessageActivity

The message identifier (message\_id) for the message to use when determining whether message events meet the condition.

**Type**: string **Required**: False

### **EventDimensions**

Specifies the dimensions for an event filter that determines when a campaign is sent or a journey activity is performed.

### **EventType**

The name of the event that causes the campaign to be sent or the journey activity to be performed. This can be a standard event that Amazon Pinpoint generates, such as \_\_email.delivered or \_custom.delivered. For campaigns, this can also be a custom event that's specific to your application. For information about standard events, see <a href="Streaming Amazon Pinpoint Events">Streaming Amazon Pinpoint Events</a> in the Amazon Pinpoint Developer Guide.

Type: <u>SetDimension</u>
Required: False

#### **Attributes**

One or more custom attributes that your application reports to Amazon Pinpoint. You can use these attributes as selection criteria when you create an event filter.

**Type**: object **Required**: False

#### **Metrics**

One or more custom metrics that your application reports to Amazon Pinpoint. You can use these metrics as selection criteria when you create an event filter.

**Type**: object **Required**: False

### **EventFilter**

Specifies the settings for an event that causes a campaign to be sent or a journey activity to be performed.

### **Dimensions**

The dimensions for the event filter to use for the campaign or the journey activity.

**Type**: EventDimensions

Required: True

## FilterType

The type of event that causes the campaign to be sent or the journey activity to be performed. Valid values are: SYSTEM, sends the campaign or performs the activity when a system event occurs; and, ENDPOINT, sends the campaign or performs the activity when an endpoint event (Events resource) occurs.

**Type**: string **Required**: True

Values: SYSTEM | ENDPOINT | USER

### **EventStartCondition**

Specifies the settings for an event that causes a journey activity to start.

### **EventFilter**

The EventFilter for defined for scheduling Event based Journey

Type: <u>EventFilter</u>
Required: False

### SegmentId

Accept only Endpoints events from this specific dynamic segmentId

**Type**: string **Required**: False

### **GPSCoordinates**

Specifies the GPS coordinates of a location.

### Latitude

The latitude coordinate of the location.

**Type**: number **Required**: True

# Longitude

The longitude coordinate of the location.

**Type**: number **Required**: True

### **GPSPointDimension**

Specifies GPS-based criteria for including or excluding endpoints from a segment.

### **Coordinates**

The GPS coordinates to measure distance from.

**Type:** GPSCoordinates

Required: True

# RangeInKilometers

The range, in kilometers, from the GPS coordinates.

Type: number

Required: False

# **HoldoutActivity**

Specifies the settings for a holdout activity in a journey. This type of activity stops a journey for a specified percentage of participants.

### Percentage

The percentage of participants who shouldn't continue the journey.

To determine which participants are held out, Amazon Pinpoint applies a probability-based algorithm to the percentage that you specify. Therefore, the actual percentage of participants who are held out may not be equal to the percentage that you specify.

**Type**: integer **Required**: True

### **NextActivity**

The unique identifier for the next activity to perform, after performing the holdout activity.

**Type**: string **Required**: False

# **JourneyCustomMessage**

Specifies the message content for a custom channel message that's sent to participants in a journey.

### **Data**

The message content that's passed to an AWS Lambda function or to a web hook.

**Type**: string **Required**: False

# **JourneyEmailMessage**

Specifies the "From" address for an email message that's sent to participants in a journey.

#### **FromAddress**

The verified email address to send the email message from. The default address is the FromAddress specified for the email channel for the application.

**Type**: string **Required**: False

# **JourneyLimits**

Specifies limits on the messages that a journey can send and the number of times participants can enter a journey.

# **DailyCap**

The maximum number of messages that the journey can send to a single participant during a 24-hour period. The maximum value is 100.

**Type**: integer **Required**: False

# **TotalCap**

The maximum number of messages a journey can sent to a single endpoint. The maximum value is 100. If set to 0, this limit will not apply.

**Type**: integer **Required**: False

# **TimeframeCap**

The number of messages that an endpoint can receive during the specified timeframe.

**Type**: JourneyTimeframeCap

Required: False

# MessagesPerSecond

The maximum number of messages that the journey can send each second.

**Type**: integer **Required**: False

### **EndpointReentryCap**

The maximum number of times that a participant can enter the journey. The maximum value is 100. To allow participants to enter the journey an unlimited number of times, set this value to 0.

**Type**: integer **Required**: False

### EndpointReentryInterval

Minimum time that must pass before an endpoint can re-enter a given journey.

**Type**: string

Required: False

# JourneyPushMessage

Specifies the message configuration for a push notification that's sent to participants in a journey.

#### **TimeToLive**

The number of seconds that the push notification service should keep the message, if the service is unable to deliver the notification the first time. This value is converted to an expiration value when it's sent to a push notification service. If this value is 0, the service treats the notification as if it expires immediately and the service doesn't store or try to deliver the notification again.

This value doesn't apply to messages that are sent through the Amazon Device Messaging (ADM) service.

**Type**: string

Required: False

# **JourneyResponse**

Provides information about the status, configuration, and other settings for a journey.

#### Name

The name of the journey.

**Type**: string

Required: False

### Schedule

The schedule settings for the journey.

Type: JourneySchedule

Required: False

### **StartCondition**

The segment that defines which users are participants in the journey.

**Type: StartCondition** 

Required: False

### Limits

The messaging and entry limits for the journey.

**Type:** JourneyLimits

Required: False

# **StartActivity**

The unique identifier for the first activity in the journey.

Type: string

Required: False

#### **Activities**

A map that contains a set of Activity objects, one object for each activity in the journey. For each Activity object, the key is the unique identifier (string) for an activity and the value is the settings for the activity.

**Type**: object **Required**: False

RefreshFrequency

The frequency with which Amazon Pinpoint evaluates segment and event data for the journey, as a duration in ISO 8601 format.

Type: string

**Required**: False

QuietTime

The quiet time settings for the journey. Quiet time is a specific time range when a journey doesn't send messages to participants, if all the following conditions are met:

• The EndpointDemographic.Timezone property of the endpoint for the participant is set to a valid value.

• The current time in the participant's time zone is later than or equal to the time specified by the QuietTime. Start property for the journey.

• The current time in the participant's time zone is earlier than or equal to the time specified by the QuietTime. End property for the journey.

If any of the preceding conditions isn't met, the participant will receive messages from the journey, even if quiet time is enabled.

Type: QuietTime
Required: False

### WaitForQuietTime

Indicates whether endpoints in quiet hours should enter a wait activity until quiet hours have elapsed.

**Type**: boolean **Required**: False

### SendingSchedule

Indicates if journey has Advance Quiet Time enabled. This flag should be set to true in order to allow using OpenHours and ClosedDays.

**Type**: boolean **Required**: False

# **OpenHours**

The time when a journey can send messages. QuietTime should be configured first and SendingSchedule should be set to true.

Type: OpenHours
Required: False

### ClosedDays

The time when a journey will not send messages. QuietTime should be configured first and SendingSchedule should be set to true.

Type: <u>ClosedDays</u> Required: False

# RefreshOnSegmentUpdate

Indicates whether the journey participants should be refreshed when a segment is updated.

**Type**: boolean **Required**: False

#### LocalTime

Specifies whether the journey's scheduled start and end times use each participant's local time. If this value is true, the schedule uses each participant's local time.

**Type**: boolean **Required**: False

#### CreationDate

The date, in ISO 8601 format, when the journey was created.

**Type**: string **Required**: False

#### LastModifiedDate

The date, in ISO 8601 format, when the journey was last modified.

**Type**: string **Required**: False

#### State

The current status of the journey. Possible values are:

- DRAFT The journey is being developed and hasn't been published yet.
- ACTIVE The journey has been developed and published. Depending on the journey's schedule, the journey may currently be running or scheduled to start running at a later time. If a journey's status is ACTIVE, you can't add, change, or remove activities from it.
- COMPLETED The journey has been published and has finished running. All participants have entered the journey and no participants are waiting to complete the journey or any activities in the journey.
- CANCELLED The journey has been stopped. If a journey's status is CANCELLED, you can't add, change, or remove activities or segment settings from the journey.
- CLOSED The journey has been published and has started running. It may have also passed
  its scheduled end time, or passed its scheduled start time and a refresh frequency hasn't been

**REST API Reference** Amazon Pinpoint

specified for it. If a journey's status is CLOSED, you can't add participants to it, and no existing participants can enter the journey for the first time. However, any existing participants who are currently waiting to start an activity may continue the journey.



#### Note

A journey in the CLOSED state is still counted against the **Maximum number of active** journeys quota. For more information see Journey quotas.

Type: string Required: False

Values: DRAFT | ACTIVE | PAUSED | COMPLETED | CANCELLED | CLOSED |

PENDING APPROVAL

### tags

This object is not used or supported.

**Type**: object Required: False

#### **TimezoneEstimationMethods**

An array of time zone estimation methods, if any, to use for determining an Endpoints time zone if the Endpoint does not have a value for the Demographic. Timezone attribute.

- PHONE\_NUMBER A time zone is estimated based on the Endpoint.Location.Country and Endpoint.Address.
- POSTAL\_CODE A time zone is estimated based on the Endpoint.Location.Country and Endpoint.Location.PostalCode.



### Note

POSTAL\_CODE estimation is only supported in the United States, United Kingdom, Australia, New Zealand, Canada, France, Italy, Spain, Germany and in regions where Amazon Pinpoint is available.

• Both - A time zone is estimated based on the Endpoint.Location.Country, Endpoint.Address and Endpoint.Location.PostalCode.

Type: Array of type string

**Required**: False

Values: PHONE\_NUMBER | POSTAL\_CODE

#### Id

The unique identifier for the journey.

**Type**: string **Required**: True

### **ApplicationId**

The unique identifier for the application that the journey applies to.

**Type**: string **Required**: True

# **JourneySMSMessage**

Specifies the sender ID and message type for an SMS message that's sent to participants in a journey.

### SenderId

The sender ID to display as the sender of the message on a recipient's device. Support for sender IDs varies by country. For more information, see <u>Supported Countries and Regions</u> in the Amazon Pinpoint User Guide.

**Type**: string **Required**: False

### OriginationNumber

The number to send the SMS message from. The phone number that you specify must exist in your Amazon Pinpoint account—you can't pass an arbitrary phone number. If you want to use a sender ID to send your message, omit this parameter and use SenderId instead.

**Type**: string **Required**: False

### MessageType

The SMS message type. Valid values are TRANSACTIONAL (for messages that are critical or time-sensitive, such as a one-time passwords) and PROMOTIONAL (for messsages that aren't critical or time-sensitive, such as marketing messages).

**Type**: string **Required**: False

Values: TRANSACTIONAL | PROMOTIONAL

### **EntityId**

A registered Entity ID (currently only used when sending messages to recipients in India).

**Type**: string **Required**: False

### TemplateId

A registered Template ID (currently only used when sending messages to recipients in India).

**Type**: string **Required**: False

# **JourneySchedule**

Specifies the schedule settings for a journey.

#### StartTime

The scheduled time, in ISO 8601 format, when the journey began or will begin.

**Type**: string **Required**: False

### **EndTime**

The scheduled time, in ISO 8601 format, when the journey ended or will end.

**Type**: string **Required**: False

#### **Timezone**

The starting UTC offset for the journey schedule, if the value of the journey's LocalTime property is true. Valid values are: UTC, UTC+01, UTC+02, UTC+03, UTC+03:30, UTC+04, UTC+04:30, UTC+05:30, UTC+05:45, UTC+06, UTC+06:30, UTC+07, UTC+08, UTC+08:45, UTC+09, UTC+09:30, UTC+10, UTC+10:30, UTC+11, UTC+12, UTC+12:45, UTC+13, UTC+13:45, UTC-02, UTC-02:30, UTC-03, UTC-03:30, UTC-04, UTC-05, UTC-06, UTC-07, UTC-08, UTC-09, UTC-09:30, UTC-10, and UTC-11.

**Type**: string **Required**: False

# JourneyTimeframeCap

The number of messages that can be sent to an endpoint during the specified timeframe for all journeys.

### **Days**

The length of the timeframe in days. The maximum value is 30. If set to 0, this limit will not apply.

**Type**: integer **Required**: False

### Cap

The maximum number of messages that all journeys can send to an endpoint during the specified timeframe. The maximum value is 100. If set to 0, this limit will not apply.

**Type**: integer **Required**: False

# **JourneysResponse**

Provides information about the status, configuration, and other settings for all the journeys that are associated with an application.

#### **Item**

An array of responses, one for each journey that's associated with the application.

**Type**: Array of type JourneyResponse

Required: True

#### NextToken

The string to use in a subsequent request to get the next page of results in a paginated response. This value is null if there are no additional pages.

**Type**: string **Required**: False

# MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

### Message

The message that's returned from the API.

**Type**: string

Required: False

### MetricDimension

Specifies metric-based criteria for including or excluding endpoints from a segment. These criteria derive from custom metrics that you define for endpoints.

### ComparisonOperator

The operator to use when comparing metric values. Valid values are: GREATER\_THAN, LESS\_THAN, GREATER\_THAN\_OR\_EQUAL, LESS\_THAN\_OR\_EQUAL, and EQUAL.

**Type**: string **Required**: True

#### **Value**

The value to compare.

**Type**: number **Required**: True

### MultiConditionalBranch

Specifies a condition to evaluate for an activity path in a journey.

#### **Condition**

The condition to evaluate for the activity path.

**Type:** SimpleCondition

Required: False

### **NextActivity**

The unique identifier for the next activity to perform, after completing the activity for the path.

Type: string

**Required**: False

# MultiConditionalSplitActivity

Specifies the settings for a multivariate split activity in a journey. This type of activity sends participants down one of as many as five paths (including a default Else path) in a journey, based on conditions that you specify.



#### Note

To create multivariate split activities that send participants down different paths based on push notification events (such as Open or Received events), your mobile app has to specify the User ID and Endpoint ID values. For more information, see Integrating Amazon Pinpoint with your application in the Amazon Pinpoint Developer Guide.

#### **Branches**

The paths for the activity, including the conditions for entering each path and the activity to perform for each path.

**Type**: Array of type MultiConditionalBranch

**Required**: False

# **DefaultActivity**

The unique identifier for the activity to perform for participants who don't meet any of the conditions specified for other paths in the activity.

**Type**: string Required: False

#### **EvaluationWaitTime**

The amount of time to wait or the date and time when Amazon Pinpoint determines whether the conditions are met.

Type: WaitTime

Required: False

# **OpenHours**

Specifies the times when message are allowed to be sent to endpoints.

### **EMAIL**

Specifies the schedule settings for the email channel.

**Type**: object **Required**: False

### **SMS**

Specifies the schedule settings for the SMS channel.

**Type**: object **Required**: False

### **PUSH**

Specifies the schedule settings for the push channel.

**Type**: object **Required**: False

#### **VOICE**

Specifies the schedule settings for the voice channel.

**Type**: object **Required**: False

#### **CUSTOM**

Specifies the schedule settings for the custom channel.

Type: object

Required: False

# **OpenHoursRule**

Specifies the start and end time for OpenHours.

### **StartTime**

The start of the scheduled time, in ISO 8601 format, when the channel can send messages.

**Type**: string **Required**: True

### **EndTime**

The end of the scheduled time, in ISO 8601 format, when the channel can't send messages.

**Type**: string **Required**: True

# PushMessageActivity

Specifies the settings for a push notification activity in a journey. This type of activity sends a push notification to participants.

# MessageConfig

Specifies the time to live (TTL) value for push notifications that are sent to participants in a journey.

**Type**: JourneyPushMessage

Required: False

# NextActivity

The unique identifier for the next activity to perform, after the message is sent.

**Type**: string **Required**: False

### **TemplateName**

The name of the push notification template to use for the message. If specified, this value must match the name of an existing message template.

**Type**: string **Required**: False

### **TemplateVersion**

The unique identifier for the version of the push notification template to use for the message. If specified, this value must match the identifier for an existing template version. To retrieve a list of versions and version identifiers for a template, use the <u>Template Versions</u> resource.

If you don't specify a value for this property, Amazon Pinpoint uses the *active version* of the template. The *active version* is typically the version of a template that's been most recently reviewed and approved for use, depending on your workflow. It isn't necessarily the latest version of a template.

**Type**: string **Required**: False

### QuietTime

Specifies the start and end times that define a time range when messages aren't sent to endpoints.

#### **Start**

The specific time when quiet time begins. This value has to use 24-hour notation and be in HH:MM format, where HH is the hour (with a leading zero, if applicable) and MM is the minutes. For example, use 02:30 to represent 2:30 AM, or 14:30 to represent 2:30 PM.

**Type**: string **Required**: False

#### End

The specific time when quiet time ends. This value has to use 24-hour notation and be in HH:MM format, where HH is the hour (with a leading zero, if applicable) and MM is the minutes. For example, use 02:30 to represent 2:30 AM, or 14:30 to represent 2:30 PM.

**Type**: string **Required**: False

# RandomSplitActivity

Specifies the settings for a random split activity in a journey. This type of activity randomly sends specified percentages of participants down one of as many as five paths in a journey, based on conditions that you specify.

### **Branches**

The paths for the activity, including the percentage of participants to enter each path and the activity to perform for each path.

**Type**: Array of type RandomSplitEntry

Required: False

# RandomSplitEntry

Specifies the settings for a path in a random split activity in a journey.

### **Percentage**

The percentage of participants to send down the activity path.

To determine which participants are sent down each path, Amazon Pinpoint applies a probability-based algorithm to the percentages that you specify for the paths. Therefore, the actual percentage of participants who are sent down a path may not be equal to the percentage that you specify.

**Type**: integer **Required**: False

# **NextActivity**

The unique identifier for the next activity to perform, after completing the activity for the path.

**Type**: string **Required**: False

# RecencyDimension

Specifies criteria for including or excluding endpoints from a segment based on how recently an endpoint was active.

### RecencyType

The type of recency dimension to use for the segment. Valid values are: ACTIVE, endpoints that were active within the specified duration are included in the segment; and, INACTIVE, endpoints that weren't active within the specified duration are included in the segment.

**Type**: string **Required**: True

Values: ACTIVE | INACTIVE

#### **Duration**

The duration to use when determining whether an endpoint is active or inactive.

**Type**: string **Required**: True

**Values**: HR\_24 | DAY\_7 | DAY\_14 | DAY\_30

# **SMSMessageActivity**

Specifies the settings for an SMS activity in a journey. This type of activity sends a text message to participants.

# MessageConfig

Specifies the sender ID and message type for an SMS message that's sent to participants in a journey.

**Type:** JourneySMSMessage

Required: False

### **NextActivity**

The unique identifier for the next activity to perform, after the message is sent.

**REST API Reference** Amazon Pinpoint

**Type**: string

**Required**: False

### **TemplateName**

The name of the SMS message template to use for the message. If specified, this value must match the name of an existing message template.

Type: string

Required: False

### **TemplateVersion**

The unique identifier for the version of the SMS template to use for the message. If specified, this value must match the identifier for an existing template version. To retrieve a list of versions and version identifiers for a template, use the Template Versions resource.

If you don't specify a value for this property, Amazon Pinpoint uses the active version of the template. The active version is typically the version of a template that's been most recently reviewed and approved for use, depending on your workflow. It isn't necessarily the latest version of a template.

**Type**: string

**Required**: False

# **SegmentBehaviors**

Specifies dimension settings for including or excluding endpoints from a segment based on how recently an endpoint was active.

# Recency

The dimension settings that are based on how recently an endpoint was active.

**Type**: RecencyDimension

Required: False

# **SegmentCondition**

Specifies a segment to associate with an activity in a journey.

# SegmentId

The unique identifier for the segment to associate with the activity.

**Type**: string **Required**: True

# **SegmentDemographics**

Specifies demographic-based dimension settings for including or excluding endpoints from a segment. These settings derive from characteristics of endpoint devices, such as platform, make, and model.

#### Channel

The channel criteria for the segment.

**Type**: SetDimension

Required: False

### **Platform**

The device platform criteria for the segment.

**Type**: SetDimension

Required: False

# DeviceType

The device type criteria for the segment.

**Type**: SetDimension

Required: False

# **AppVersion**

The app version criteria for the segment.

**Type**: <u>SetDimension</u>

Required: False

#### Make

The device make criteria for the segment.

**Type**: SetDimension

**Required**: False

### Model

The device model criteria for the segment.

**Type**: SetDimension

Required: False

# **SegmentDimensions**

Specifies the dimension settings for a segment.

# **Demographic**

The demographic-based criteria, such as device platform, for the segment.

**Type:** SegmentDemographics

Required: False

### Location

The location-based criteria, such as region or GPS coordinates, for the segment.

**Type**: SegmentLocation

Required: False

#### **Behavior**

The behavior-based criteria, such as how recently users have used your app, for the segment.

**Type**: SegmentBehaviors

Required: False

### **Attributes**

One or more custom attributes to use as criteria for the segment. For more information see AttributeDimension

**Type**: object **Required**: False

### **Metrics**

One or more custom metrics to use as criteria for the segment.

**Type**: object **Required**: False

### **UserAttributes**

One or more custom user attributes to use as criteria for the segment.

**Type**: object **Required**: False

# **SegmentLocation**

Specifies geographical dimension settings for a segment.

# Country

The country or region code, in ISO 3166-1 alpha-2 format, for the segment.

Type: <u>SetDimension</u>
Required: False

#### **GPSPoint**

The GPS location and range for the segment.

**Type**: GPSPointDimension

Required: False

### **SetDimension**

Specifies the dimension type and values for a segment dimension.

### DimensionType

The type of segment dimension to use. Valid values are: INCLUSIVE, endpoints that match the criteria are included in the segment; and, EXCLUSIVE, endpoints that match the criteria are excluded from the segment.

**Type**: string **Required**: False

Values: INCLUSIVE | EXCLUSIVE

#### **Values**

The criteria values to use for the segment dimension. Depending on the value of the DimensionType property, endpoints are included or excluded from the segment if their values match the criteria values.

**Type**: Array of type string

Required: True

# **SimpleCondition**

Specifies a condition to evaluate for an activity in a journey.

### segmentDimensions

The dimension settings for the segment that's associated with the activity.

**Type:** SegmentDimensions

**Required**: False

### SegmentCondition

The segment that's associated with the activity.

**Type:** SegmentCondition

Required: False

### **EventCondition**

The dimension settings for the event that's associated with the activity.

**Type:** EventCondition

Required: False

### **StartCondition**

Specifies the conditions for the first activity in a journey. This activity and its conditions determine which users are participants in a journey.

### **Description**

The custom description of the condition.

**Type**: string **Required**: False

#### **EventStartCondition**

The event start condition that can trigger a journey.

**Type**: EventStartCondition

**Required**: False

# SegmentStartCondition

The segment that's associated with the first activity in the journey. This segment determines which users are participants in the journey.

**Type**: SegmentCondition

Required: False

# WaitActivity

Specifies the settings for a wait activity in a journey. This type of activity waits for a certain amount of time or until a specific date and time before moving participants to the next activity in a journey.

### WaitTime

The amount of time to wait or the date and time when the activity moves participants to the next activity in the journey.

Type: WaitTime Required: False

### **NextActivity**

The unique identifier for the next activity to perform, after performing the wait activity.

Type: string

**Required**: False

# WaitTime

Specifies a duration or a date and time that indicates when Amazon Pinpoint determines whether an activity's conditions have been met or an activity moves participants to the next activity in a journey.

#### WaitFor

The amount of time to wait, as a duration in ISO 8601 format, before determining whether the activity's conditions have been met or moving participants to the next activity in the journey.

**Type**: string

Required: False

#### WaitUntil

The date and time, in ISO 8601 format, when Amazon Pinpoint determines whether the activity's conditions have been met or the activity moves participants to the next activity in the journey.

**Type**: string

Required: False

# WriteJourneyRequest

Specifies the configuration and other settings for a journey.

#### Name

The name of the journey. A journey name can contain a maximum of 150 characters. The characters can be alphanumeric characters or symbols, such as underscores (\_) or hyphens (-). A journey name can't contain any spaces.

Type: string

Required: False

#### Schedule

The schedule settings for the journey.

Type: JourneySchedule

Required: False

### **StartCondition**

The segment that defines which users are participants in the journey.

**Type:** StartCondition

Required: False

### Limits

The messaging and entry limits for the journey.

**Type**: <u>JourneyLimits</u>

Required: False

### **StartActivity**

The unique identifier for the first activity in the journey. The identifier for this activity can contain a maximum of 128 characters. The characters must be alphanumeric characters.

**Type**: string

Required: False

#### **Activities**

A map that contains a set of Activity objects, one object for each activity in the journey. For each Activity object, the key is the unique identifier (string) for an activity and the value is the settings for the activity. An activity identifier can contain a maximum of 100 characters. The characters must be alphanumeric characters.

**Type**: object

Required: False

### RefreshFrequency

The frequency with which Amazon Pinpoint evaluates segment and event data for the journey, as a duration in ISO 8601 format.

**Type**: string

**Required**: False

### QuietTime

The quiet time settings for the journey. Quiet time is a specific time range when a journey doesn't send messages to participants, if all the following conditions are met:

- The EndpointDemographic.Timezone property of the endpoint for the participant is set to a valid value.
- The current time in the participant's time zone is later than or equal to the time specified by the QuietTime. Start property for the journey.
- The current time in the participant's time zone is earlier than or equal to the time specified by the QuietTime. End property for the journey.

If any of the preceding conditions isn't met, the participant will receive messages from the journey, even if quiet time is enabled.

Type: QuietTime Required: False

### WaitForQuietTime

Indicates whether endpoints in quiet hours should enter a wait activity until quiet hours have elapsed.

**Type**: boolean **Required**: False

### SendingSchedule

Indicates if journey has Advance Quiet Time enabled. This flag should be set to true in order to allow using OpenHours and ClosedDays.

**Type**: boolean **Required**: False

# **OpenHours**

The time when journey allow to send messages. QuietTime should be configured first and SendingSchedule should be set to true.

Type: OpenHours
Required: False

# ClosedDays

The time when journey will stop sending messages. QuietTime should be configured first and SendingSchedule should be set to true.

Type: ClosedDays
Required: False

### RefreshOnSegmentUpdate

Indicates whether the journey participants should be refreshed when a segment is updated.

**Type**: boolean **Required**: False

#### LocalTime

Specifies whether the journey's scheduled start and end times use each participant's local time. To base the schedule on each participant's local time, set this value to true.

**Type**: boolean **Required**: False

#### CreationDate

The date, in ISO 8601 format, when the journey was created.

Type: string

Required: False

#### LastModifiedDate

The date, in ISO 8601 format, when the journey was last modified.

Type: string

**Required**: False

#### **State**

The status of the journey. Valid values are:

- DRAFT Saves the journey and doesn't publish it.
- ACTIVE Saves and publishes the journey. Depending on the journey's schedule, the journey
  starts running immediately or at the scheduled start time. If a journey's status is ACTIVE, you
  can't add, change, or remove activities from it.

The CANCELLED, COMPLETED, and CLOSED values are not supported in requests to create or update a journey. To cancel a journey, use the Journey State resource.

**Type**: string

Required: False

Values: DRAFT | ACTIVE | PAUSED | COMPLETED | CANCELLED | CLOSED |

PENDING APPROVAL

#### **TimezoneEstimationMethods**

An array of time zone estimation methods, if any, to use for determining an Endpoints time zone if the Endpoint does not have a value for the Demographic. Timezone attribute.

- PHONE\_NUMBER A time zone is estimated based on the Endpoint.Location.Country and Endpoint.Address.
- POSTAL\_CODE A time zone is estimated based on the Endpoint.Location.Country and Endpoint.Location.PostalCode.

#### Note

POSTAL CODE estimation is only supported in the United States, United Kingdom, Australia, New Zealand, Canada, France, Italy, Spain, Germany and in regions where Amazon Pinpoint is available.

 Both - A time zone is estimated based on the Endpoint.Location.Country, Endpoint.Address and Endpoint.Location.PostalCode.

**Type**: Array of type string

**Required**: False

Values: PHONE\_NUMBER | POSTAL\_CODE

### See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

See also 846

# ListJourneys

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# CreateJourney

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- · AWS SDK for Python
- AWS SDK for Ruby V3

# Messages

The Messages resource represents a *direct message*, which is a one-time message that you send directly to a limited audience without creating a campaign. You can send a direct message to as many as 100 recipients. The message can be a push notification for users of your mobile app, an SMS message, an email message, or a voice message.

Messages 847

When you send a direct message, Amazon Pinpoint delivers it immediately. You can't schedule the delivery of direct messages. In addition, you can't send a direct message to a segment. If you want to schedule a message to be sent at a certain time or you want to send a message to a segment, you should create a campaign rather than sending a direct message.

While sending transactional template-based messages using the Amazon Pinpoint API, CLI or SDK, you need to make sure that values are provided for all the template variable either at request time or as default values with the template. Messages failing to render due to missing attribute value will not be received successfully.

You can use the Messages resource to send a direct message.

# **URI**

/v1/apps/application-id/messages

# **HTTP** methods

### **POST**

**Operation ID:** SendMessages

Creates and sends a direct message.

#### Path parameters

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

URI 848

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	MessageResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large

HTTP methods 849

Status code	Response model	Description
		(RequestEntityTooLargeExcep tion).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Messages resource.

# **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# Responses

Status code	Response model	Description
200	None	The request succeeded.

HTTP methods 850

# **Schemas**

# **Request bodies**

## **POST schema**

```
"TraceId": "string",
"Context": {
},
"MessageConfiguration": {
  "DefaultMessage": {
    "Body": "string",
    "Substitutions": {
    }
  },
  "DefaultPushNotificationMessage": {
    "Body": "string",
    "Substitutions": {
    },
    "Title": "string",
    "Action": enum,
    "Url": "string",
    "SilentPush": boolean,
    "Data": {
    }
 },
  "APNSMessage": {
    "Body": "string",
    "Substitutions": {
    "Title": "string",
    "Action": enum,
    "Url": "string",
    "SilentPush": boolean,
    "Data": {
    },
    "MediaUrl": "string",
    "Sound": "string",
    "Badge": integer,
    "Category": "string",
    "ThreadId": "string",
    "RawContent": "string",
```

```
"PreferredAuthenticationMethod": "string",
  "TimeToLive": integer,
  "Priority": "string",
  "CollapseId": "string",
  "APNSPushType": "string"
},
"GCMMessage": {
  "Body": "string",
  "Substitutions": {
 },
  "Title": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "Data": {
 },
  "IconReference": "string",
  "Sound": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "SmallImageIconUrl": "string",
  "RawContent": "string",
  "CollapseKey": "string",
  "RestrictedPackageName": "string",
  "TimeToLive": integer,
  "Priority": "string",
  "PreferredAuthenticationMethod": "string"
},
"BaiduMessage": {
  "Body": "string",
  "Substitutions": {
 },
  "Title": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "Data": {
 },
  "IconReference": "string",
  "Sound": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "SmallImageIconUrl": "string",
  "RawContent": "string",
```

```
"TimeToLive": integer
},
"ADMMessage": {
  "Body": "string",
  "Substitutions": {
  },
  "Title": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "Data": {
  },
  "IconReference": "string",
  "Sound": "string",
  "ImageUr<u>l</u>": "string",
  "ImageIconUrl": "string",
  "SmallImageIconUrl": "string",
  "RawContent": "string",
  "ConsolidationKey": "string",
  "ExpiresAfter": "string",
  "MD5": "string"
},
"EmailMessage": {
  "Body": "string",
  "Substitutions": {
  },
  "FromAddress": "string",
  "FeedbackForwardingAddress": "string",
  "ReplyToAddresses": [
    "string"
  ],
  "SimpleEmail": {
    "Subject": {
      "Data": "string",
      "Charset": "string"
    },
    "TextPart": {
      "Data": "string",
      "Charset": "string"
    },
    "Html<br/>Part": {
      "Data": "string",
      "Charset": "string"
    },
```

```
"Headers": [
        {
          "Name": "string",
          "Value": "string"
      ]
    },
    "RawEmail": {
      "Data": "string"
    }
  },
  "SMSMessage": {
    "Body": "string",
    "Substitutions": {
    },
    "SenderId": "string",
    "MessageType": enum,
    "Keyword": "string",
    "OriginationNumber": "string",
    "EntityId": "string",
    "TemplateId": "string",
    "MediaUrl": "string"
  },
  "VoiceMessage": {
    "Body": "string",
    "Substitutions": {
    },
    "LanguageCode": "string",
    "VoiceId": "string",
    "OriginationNumber": "string"
  }
},
"TemplateConfiguration": {
  "SMSTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "EmailTemplate": {
    "Name": "string",
    "Version": "string"
  },
  "PushTemplate": {
    "Name": "string",
    "Version": "string"
```

```
},
"VoiceTemplate": {
    "Name": "string",
    "Version": "string"
},
"InAppTemplate": {
    "Name": "string",
    "Version": "string"
}
},
"Addresses": {
},
"Endpoints": {
}
```

# **Response bodies**

# MessageResponse schema

```
{
  "ApplicationId": "string",
   "RequestId": "string",
   "Result": {
   },
   "EndpointResult": {
   }
}
```

# MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

# **ADMMessage**

Specifies the settings for a one-time message that's sent directly to an endpoint through the ADM (Amazon Device Messaging) channel.

## **Body**

The body of the notification message.

**Type**: string **Required**: False

#### **Substitutions**

The default message variables to use in the notification message. You can override the default variables with individual address variables.

**Type**: object **Required**: False

### **Title**

The title to display above the notification message on the recipient's device.

**Type**: string **Required**: False

## **Action**

The action to occur if the recipient taps the push notification. Valid values are:

- OPEN\_APP Your app opens or it becomes the foreground app if it was sent to the background.
   This is the default action.
- DEEP\_LINK Your app opens and displays a designated user interface in the app. This action uses the deep-linking features of the Android platform.
- URL The default mobile browser on the recipient's device opens and loads the web page at a URL that you specify.

Type: string

Required: False

Values: OPEN\_APP | DEEP\_LINK | URL

## Url

The URL to open in the recipient's default mobile browser, if a recipient taps the push notification and the value of the Action property is URL.

Type: string

Required: False

## **SilentPush**

Specifies whether the notification is a silent push notification, which is a push notification that doesn't display on a recipient's device. Silent push notifications can be used for cases such as updating an app's configuration or supporting phone home functionality.

Type: boolean

Required: False

### **Data**

The JSON data payload to use for the push notification, if the notification is a silent push notification. This payload is added to the data.pinpoint.jsonBody object of the notification.

Type: object

Required: False

### **IconReference**

The icon image name of the asset saved in your app.

**Type**: string

Required: False

### Sound

The sound to play when the recipient receives the push notification. You can use the default stream or specify the file name of a sound resource that's bundled in your app. On an Android platform, the sound file must reside in /res/raw/.

**Type**: string **Required**: False

## **ImageUrl**

The URL of an image to display in the push notification.

**Type**: string **Required**: False

## **ImageIconUrl**

The URL of the large icon image to display in the content view of the push notification.

Type: string

Required: False

# **SmallimageIconUrl**

The URL of the small icon image to display in the status bar and the content view of the push notification.

Type: string

Required: False

## **RawContent**

The raw, JSON-formatted string to use as the payload for the notification message. If specified, this value overrides all other content for the message.

**Type**: string **Required**: False

## ConsolidationKey

An arbitrary string that indicates that multiple messages are logically the same and that Amazon Device Messaging (ADM) can drop previously enqueued messages in favor of this message.

**Type**: string

Required: False

## **ExpiresAfter**

The amount of time, in seconds, that ADM should store the message if the recipient's device is offline. Amazon Pinpoint specifies this value in the expiresAfter parameter when it sends the notification message to ADM.

**Type**: string

**Required**: False

### MD5

The base64-encoded, MD5 checksum of the value specified by the Data property. ADM uses the MD5 value to verify the integrity of the data.

**Type**: string

Required: False

# **APNSMessage**

Specifies the settings for a one-time message that's sent directly to an endpoint through the APNs (Apple Push Notification service) channel.

## **Body**

The body of the notification message.

Type: string

Required: False

### **Substitutions**

The default message variables to use in the notification message. You can override these default variables with individual address variables.

**Type**: object **Required**: False

### **Title**

The title to display above the notification message on the recipient's device.

**Type**: string **Required**: False

### **Action**

The action to occur if the recipient taps the push notification. Valid values are:

OPEN\_APP – Your app opens or it becomes the foreground app if it was sent to the background.
 This is the default action.

DEEP\_LINK – Your app opens and displays a designated user interface in the app. This setting
uses the deep-linking features of the iOS platform.

• URL – The default mobile browser on the recipient's device opens and loads the web page at a URL that you specify.

**Type**: string **Required**: False

Values: OPEN\_APP | DEEP\_LINK | URL

### Url

The URL to open in the recipient's default mobile browser, if a recipient taps the push notification and the value of the Action property is URL.

**Type**: string **Required**: False

### **SilentPush**

Specifies whether the notification is a silent push notification. A silent (or background) push notification isn't displayed on recipients' devices. You can use silent push notifications to make small updates to your app, or to display messages in an in-app message center.

Amazon Pinpoint uses this property to determine the correct value for the apns-push-type request header when it sends the notification message to APNs. If you specify a value of true for this property, Amazon Pinpoint sets the value for the apns-push-type header field to background.



## Note

If you specify the raw content of an APNs push notification, the message payload has to include the content-available key. For silent (background) notifications, set the value of content-available to 1. Additionally, the message payload for a silent notification can't include the alert, badge, or sound keys. For more information, see Generating a Remote Notification and Pushing Background Updates to Your App on the Apple Developer website.

Apple has indicated that they will throttle "excessive" background notifications based on current traffic volumes. To prevent your notifications being throttled, Apple recommends that you send no more than 3 silent push notifications to each recipient per hour.

Type: boolean **Required**: False

#### **Data**

The JSON payload to use for a silent push notification. This payload is added to the data.pinpoint.jsonBody object of the notification.

**Type**: object Required: False

## MediaUrl

The URL of an image or video to display in the push notification.

Type: string

**Required**: False

### Sound

The key for the sound to play when the recipient receives the push notification. The value for this key is the name of a sound file in your app's main bundle or the Library/Sounds folder in your app's data container. If the sound file can't be found or you specify default for the value, the system plays the default alert sound.

**Type**: string

**Required**: False

## **Badge**

The key that indicates whether and how to modify the badge of your app's icon when the recipient receives the push notification. If this key isn't included in the dictionary, the badge doesn't change. To remove the badge, set this value to 0.

**Type**: integer

**Required**: False

## **Category**

The key that indicates the notification type for the push notification. This key is a value that's defined by the identifier property of one of your app's registered categories.

**Type**: string

Required: False

### **ThreadId**

The key that represents your app-specific identifier for grouping notifications. If you provide a Notification Content app extension, you can use this value to group your notifications together.

**Type**: string

**Required**: False

### RawContent

The raw, JSON-formatted string to use as the payload for the notification message. If specified, this value overrides all other content for the message. For an example of the RawContent property, see Schema sample: RawContent object for a push notification.



## Note

If you specify the raw content of an APNs push notification, the message payload has to include the content-available key. The value of the content-available key has to be an integer, and can only be 0 or 1. If you're sending a standard notification, set the value of content-available to 0. If you're sending a silent (background) notification, set the value of content-available to 1. Additionally, silent notification payloads can't include the alert, badge, or sound keys. For more information, see Generating a Remote Notification and Pushing Background Updates to Your App on the Apple Developer website. If you want to send a push notification to users of the Safari web browser on a macOS laptop or desktop computer, you must specify the raw message payload. Also, the raw message payload must include a url-args array within the aps object. The url-args array is required in order to send push notifications to the Safari web browser. However, it is acceptable for the array to contain a single, empty element. For more information about Safari push notifications, see Configuring Safari Push Notifications on the Apple Developer website.

Type: string

Required: False

### PreferredAuthenticationMethod

The authentication method that you want Amazon Pinpoint to use when authenticating with APNs, CERTIFICATE or TOKEN.

**Type**: string

**Required**: False

### **TimeToLive**

The amount of time, in seconds, that APNs should store and attempt to deliver the push notification, if the service is unable to deliver the notification the first time. If this value is 0, APNs treats the notification as if it expires immediately and the service doesn't store or try to deliver the notification again.

Amazon Pinpoint specifies this value in the apns-expiration request header when it sends the notification message to APNs.

**Type**: integer **Required**: False

## **Priority**

The priority of the push notification. Valid values are:

- 5 Low priority, the notification might be delayed, delivered as part of a group, or throttled.
- 10 High priority, the notification is sent immediately. This is the default value. A high priority notification should trigger an alert, play a sound, or badge your app's icon on the recipient's device.

Amazon Pinpoint specifies this value in the apns-priority request header when it sends the notification message to APNs.

The equivalent values for Firebase Cloud Messaging (FCM), formerly Google Cloud Messaging (GCM), are normal, for 5, and high, for 10. If you specify an FCM value for this property, Amazon Pinpoint accepts and converts the value to the corresponding APNs value.

**Type**: string **Required**: False

## CollapseId

An arbitrary identifier that, if assigned to multiple messages, APNs uses to coalesce the messages into a single push notification instead of delivering each message individually. This value can't exceed 64 bytes.

Amazon Pinpoint specifies this value in the apns-collapse-id request header when it sends the notification message to APNs.

Type: string

Required: False

## **APNSPushType**

The type of push notification to send. Valid values are:

• alert – For a standard notification that's displayed on recipients' devices and prompts a recipient to interact with the notification.

- background For a silent notification that delivers content in the background and isn't displayed on recipients' devices.
- complication For a notification that contains update information for an app's complication timeline.
- fileprovider For a notification that signals changes to a File Provider extension.
- mdm For a notification that tells managed devices to contact the MDM server.
- voip For a notification that provides information about an incoming VoIP call.

Amazon Pinpoint specifies this value in the apns-push-type request header when it sends the notification message to APNs. If you don't specify a value for this property, Amazon Pinpoint sets the value to alert or background automatically, based on the value that you specify for the SilentPush or RawContent property of the message.

For more information about the apns-push-type request header, see <u>Sending Notification</u> Requests to APNs on the Apple Developer website.

Type: string

Required: False

# AddressConfiguration

Specifies address-based configuration settings for a message that's sent directly to an endpoint.

### **Substitutions**

A map of the message variables to merge with the variables specified by properties of the DefaultMessage object. The variables specified in this map take precedence over all other variables.

Type: object

Required: False

### **Context**

An object that maps custom attributes to attributes for the address and is attached to the message. Attribute names are case sensitive.

For a push notification, this payload is added to the data.pinpoint object. For an email or text message, this payload is added to email/SMS delivery receipt event attributes.

Type: object

Required: False

#### RawContent

The raw, JSON-formatted string to use as the payload for the message. If specified, this value overrides all other values for the message.

Type: string

**Required**: False

# **BodyOverride**

The message body to use instead of the default message body. This value overrides the default message body.

Type: string

Required: False

### **TitleOverride**

The message title to use instead of the default message title. This value overrides the default message title.

**Type**: string **Required**: False

## ChannelType

The channel to use when sending the message.

**Type**: string **Required**: False

Values: PUSH | GCM | APNS | APNS\_SANDBOX | APNS\_VOIP | APNS\_VOIP\_SANDBOX |

ADM | SMS | VOICE | EMAIL | BAIDU | CUSTOM | IN\_APP

# BaiduMessage

Specifies the settings for a one-time message that's sent directly to an endpoint through the Baidu (Baidu Cloud Push) channel.

## **Body**

The body of the notification message.

**Type**: string **Required**: False

#### **Substitutions**

The default message variables to use in the notification message. You can override the default variables with individual address variables.

**Type**: object **Required**: False

## Title

The title to display above the notification message on the recipient's device.

**REST API Reference** Amazon Pinpoint

**Type**: string

**Required**: False

### **Action**

The action to occur if the recipient taps the push notification. Valid values are:

• OPEN\_APP – Your app opens or it becomes the foreground app if it was sent to the background.

This is the default action.

• DEEP\_LINK – Your app opens and displays a designated user interface in the app. This action

uses the deep-linking features of the Android platform.

• URL – The default mobile browser on the recipient's device opens and loads the web page at a

URL that you specify.

**Type**: string

Required: False

Values: OPEN\_APP | DEEP\_LINK | URL

Url

The URL to open in the recipient's default mobile browser, if a recipient taps the push notification

and the value of the Action property is URL.

**Type**: string

Required: False

**SilentPush** 

Specifies whether the notification is a silent push notification, which is a push notification that

doesn't display on a recipient's device. Silent push notifications can be used for cases such as

updating an app's configuration or supporting phone home functionality.

Type: boolean

**Required**: False

#### **Data**

The JSON data payload to use for the push notification, if the notification is a silent push notification. This payload is added to the data.pinpoint.jsonBody object of the notification.

**Type**: object **Required**: False

### **IconReference**

The icon image name of the asset saved in your app.

Type: string

Required: False

### Sound

The sound to play when the recipient receives the push notification. You can use the default stream or specify the file name of a sound resource that's bundled in your app. On an Android platform, the sound file must reside in /res/raw/.

Type: string

**Required**: False

# ImageUrl

The URL of an image to display in the push notification.

Type: string

Required: False

# **ImageIconUrl**

The URL of the large icon image to display in the content view of the push notification.

Type: string

Required: False

## **SmallImageIconUrl**

The URL of the small icon image to display in the status bar and the content view of the push notification.

**Type**: string **Required**: False

### **RawContent**

The raw, JSON-formatted string to use as the payload for the notification message. If specified, this value overrides all other content for the message.

**Type**: string **Required**: False

## **TimeToLive**

The amount of time, in seconds, that the Baidu Cloud Push service should store the message if the recipient's device is offline. The default value and maximum supported time is 604,800 seconds (7 days).

**Type**: integer **Required**: False

# DefaultMessage

Specifies the default message for all channels.

# Body

The default body of the message.

**Type**: string **Required**: False

## **Substitutions**

The default message variables to use in the message. You can override these default variables with individual address variables.

**Type**: object **Required**: False

# DefaultPushNotificationMessage

Specifies the default settings and content for a push notification that's sent directly to an endpoint.

## **Body**

The default body of the notification message.

**Type**: string **Required**: False

## **Substitutions**

The default message variables to use in the notification message. You can override the default variables with individual address variables.

**Type**: object **Required**: False

### **Title**

The default title to display above the notification message on a recipient's device.

**Type**: string **Required**: False

### Action

The default action to occur if a recipient taps the push notification. Valid values are:

- OPEN\_APP Your app opens or it becomes the foreground app if it was sent to the background.
   This is the default action.
- DEEP\_LINK Your app opens and displays a designated user interface in the app. This setting uses the deep-linking features of the iOS and Android platforms.
- URL The default mobile browser on the recipient's device opens and loads the web page at a URL that you specify.

Type: string

Required: False

Values: OPEN\_APP | DEEP\_LINK | URL

### Url

The default URL to open in a recipient's default mobile browser, if a recipient taps the push notification and the value of the Action property is URL.

**Type**: string

Required: False

## **SilentPush**

Specifies whether the default notification is a silent push notification, which is a push notification that doesn't display on a recipient's device. Silent push notifications can be used for cases such as updating an app's configuration or delivering messages to an in-app notification center.

Type: boolean

Required: False

### **Data**

The JSON data payload to use for the default push notification, if the notification is a silent push notification. This payload is added to the data.pinpoint.jsonBody object of the notification.

Type: object

Required: False

# DirectMessageConfiguration

Specifies the settings and content for the default message and any default messages that you tailored for specific channels.

## DefaultMessage

The default message for all channels.

Type: DefaultMessage

Required: False

## DefaultPushNotificationMessage

The default push notification message for all push notification channels.

Type: DefaultPushNotificationMessage

Required: False

## **APNSMessage**

The default push notification message for the APNs (Apple Push Notification service) channel. This message overrides the default push notification message (DefaultPushNotificationMessage).

Type: APNSMessage

**Required**: False

## **GCMMessage**

The default push notification message for the GCM channel, which is used to send notifications through the Firebase Cloud Messaging (FCM), formerly Google Cloud Messaging (GCM), service. This message overrides the default push notification message (DefaultPushNotificationMessage).

**Type:** GCMMessage

Required: False

## BaiduMessage

The default push notification message for the Baidu (Baidu Cloud Push) channel. This message overrides the default push notification message (DefaultPushNotificationMessage).

Type: BaiduMessage

Required: False

## **ADMMessage**

The default push notification message for the ADM (Amazon Device Messaging) channel. This message overrides the default push notification message (DefaultPushNotificationMessage).

Type: <u>ADMMessage</u>
Required: False

## **EmailMessage**

The default message for the email channel. This message overrides the default message (DefaultMessage).

Type: EmailMessage
Required: False

## **SMSMessage**

The default message for the SMS channel. This message overrides the default message (DefaultMessage).

Type: <u>SMSMessage</u> Required: False

## VoiceMessage

The default message for the voice channel. This message overrides the default message (DefaultMessage).

Type: VoiceMessage
Required: False

# **EmailMessage**

Specifies the default settings and content for a one-time email message that's sent directly to an endpoint.

# **Body**

The body of the email message.

**Type**: string **Required**: False

### **Substitutions**

The default message variables to use in the email message. You can override the default variables with individual address variables.

**Type**: object **Required**: False

### **FromAddress**

The verified email address to send the email message from. The default value is the FromAddress specified for the email channel.

**Type**: string **Required**: False

## FeedbackForwardingAddress

The email address to forward bounces and complaints to, if feedback forwarding is enabled.

**Type**: string **Required**: False

# ReplyToAddresses

The reply-to email address(es) for the email message. If a recipient replies to the email, each reply-to address receives the reply.

Type: Array of type string

Required: False

# SimpleEmail

The email message, composed of a subject, a text part, and an HTML part.

Type: SimpleEmail

## Required: False

### **RawEmail**

The email message, represented as a raw MIME message.

Type: RawEmail Required: False

# **EndpointMessageResult**

Provides information about the delivery status and results of sending a message directly to an endpoint.

## **DeliveryStatus**

The delivery status of the message. Possible values are:

- DUPLICATE The endpoint address is a duplicate of another endpoint address. Amazon Pinpoint won't attempt to send the message again.
- OPT\_OUT The SendMessages API does not honor the endpoint OPT\_OUT status.
- PERMANENT\_FAILURE An error occurred when delivering the message to the endpoint. Amazon Pinpoint won't attempt to send the message again.
- SUCCESSFUL The message was successfully delivered to the endpoint.
- TEMPORARY\_FAILURE A temporary error occurred. Amazon Pinpoint won't attempt to send the message again.
- THROTTLED Amazon Pinpoint throttled the operation to send the message to the endpoint.
- UNKNOWN FAILURE An unknown error occurred.

**Type**: string **Required**: True

Values: SUCCESSFUL | THROTTLED | TEMPORARY\_FAILURE | PERMANENT\_FAILURE |

UNKNOWN\_FAILURE | OPT\_OUT | DUPLICATE

### **StatusCode**

The downstream service status code for delivering the message.

**Type**: integer **Required**: True

## StatusMessage

The status message for delivering the message.

**Type**: string

Required: False

## **UpdatedToken**

For push notifications that are sent through the GCM channel, specifies whether the endpoint's device registration token was updated as part of delivering the message.

Type: string

Required: False

## Messageld

The unique identifier for the message that was sent.

Type: string

Required: False

## **Address**

The endpoint address that the message was delivered to.

Type: string

Required: False

# EndpointSendConfiguration

Specifies the content, including message variables and attributes, to use in a message that's sent directly to an endpoint.

### **Substitutions**

A map of the message variables to merge with the variables specified for the default message (DefaultMessage.Substitutions). The variables specified in this map take precedence over all other variables.

**Type**: object **Required**: False

### **Context**

A map of custom attributes to attach to the message for the address. Attribute names are case sensitive.

For a push notification, this payload is added to the data.pinpoint object. For an email or text message, this payload is added to email/SMS delivery receipt event attributes.

**Type**: object **Required**: False

### **RawContent**

The raw, JSON-formatted string to use as the payload for the message. If specified, this value overrides all other values for the message.

**Type**: string **Required**: False

# **BodyOverride**

The body of the message. If specified, this value overrides the default message body.

**Type**: string **Required**: False

### **TitleOverride**

The title or subject line of the message. If specified, this value overrides the default message title or subject line.

**Type**: string **Required**: False

# **GCMMessage**

Specifies the settings for a one-time message that's sent directly to an endpoint through the GCM channel. The GCM channel enables Amazon Pinpoint to send messages to the Firebase Cloud Messaging (FCM), formerly Google Cloud Messaging (GCM), service.

## **Body**

The body of the notification message.

**Type**: string **Required**: False

### **Substitutions**

The default message variables to use in the notification message. You can override the default variables with individual address variables.

**Type**: object **Required**: False

### **Title**

The title to display above the notification message on the recipient's device.

**Type**: string **Required**: False

### Action

The action to occur if the recipient taps the push notification. Valid values are:

- OPEN\_APP Your app opens or it becomes the foreground app if it was sent to the background.
   This is the default action.
- DEEP\_LINK Your app opens and displays a designated user interface in the app. This action uses the deep-linking features of the Android platform. This is a legacy FCM key and cannot be

used with FCMV1. You can use RawContent with deep link in the payload. For more information, see Using Google Firebase Cloud Messaging (FCM) v1 payloads.

 URL – The default mobile browser on the recipient's device opens and loads the web page at a URL that you specify.

**Type**: string **Required**: False

Values: OPEN\_APP | DEEP\_LINK | URL

#### Url

The URL to open in the recipient's default mobile browser, if a recipient taps the push notification and the value of the Action property is URL.

**Type**: string **Required**: False

## **SilentPush**

Specifies whether the notification is a silent push notification, which is a push notification that doesn't display on a recipient's device. Silent push notifications can be used for cases such as updating an app's configuration or supporting phone home functionality.

**Type**: boolean **Required**: False

## Data

The JSON data payload to use for the push notification, if the notification is a silent push notification. This payload is added to the data.pinpoint.jsonBody object of the notification.

**Type**: object **Required**: False

### **IconReference**

The icon image name of the asset saved in your app.

Type: string

Required: False

### Sound

The sound to play when the recipient receives the push notification. You can use the default stream or specify the file name of a sound resource that's bundled in your app. On an Android platform, the sound file must reside in /res/raw/.

Type: string

Required: False

## **ImageUrl**

The URL of an image to display in the push notification.

Type: string

Required: False

## **ImageIconUrl**

The URL of the large icon image to display in the content view of the push notification.

Type: string

Required: False

# SmallImageIconUrl

The URL of the small icon image to display in the status bar and the content view of the push notification.

**Type**: string

Required: False

### **RawContent**

The raw, JSON-formatted string to use as the payload for the notification message. If specified, this value overrides all other content for the message. For an example of the RawContent property, see Schema sample: RawContent object for a push notification.

**Type**: string **Required**: False

## **CollapseKey**

An arbitrary string that identifies a group of messages that can be collapsed to ensure that only the last message is sent when delivery can resume. This helps avoid sending too many instances of the same messages when the recipient's device comes online again or becomes active.

Amazon Pinpoint specifies this value in the Firebase Cloud Messaging (FCM) collapse\_key parameter when it sends the notification message to FCM.

**Type**: string **Required**: False

## RestrictedPackageName

The package name of the application where registration tokens must match in order for the recipient to receive the message.

**Type**: string **Required**: False

### **TimeToLive**

The amount of time, in seconds, that FCM should store and attempt to deliver the push notification, if the service is unable to deliver the notification the first time. If you don't specify this value, FCM defaults to the maximum value, which is 2,419,200 seconds (28 days).

Amazon Pinpoint specifies this value in the FCM time\_to\_live parameter when it sends the notification message to FCM.

Type: integer

Required: False

## **Priority**

The priority of the push notification. Valid values are:

• normal – The notification might be delayed. Delivery is optimized for battery usage on the recipient's device. Use this value unless immediate delivery is required.

• high – The notification is sent immediately and might wake a sleeping device.

Amazon Pinpoint specifies this value in the FCM priority parameter when it sends the notification message to FCM.

The equivalent values for Apple Push Notification service (APNs) are 5, for normal, and 10, for high. If you specify an APNs value for this property, Amazon Pinpoint accepts and converts the value to the corresponding FCM value.

**Type**: string **Required**: False

#### PreferredAuthenticationMethod

The preferred authentication method, with valid values "KEY" or "TOKEN". If a value isn't provided then the **DefaultAuthenticationMethod** is used.

**Type**: string **Required**: False

# MessageBody

Provides information about an API request or response.

# **RequestID**

The unique identifier for the request or response.

**Type**: string **Required**: False

### Message

The message that's returned from the API.

**Type**: string **Required**: False

# MessageHeader

Contains the name and value pair of an message header to add to your email. You can have up to 15 MessageHeaders. A header can contain information such as the sender, receiver, route, or timestamp.

#### Name

The name of the message header. The header name can contain up to 126 characters.

**Type**: string **Required**: False

#### Value

The value of the message header. The header value can contain up to 870 characters, including the length of any rendered attributes. For example if you add the {CreationDate} attribute, it renders as YYYY-MM-DDTHH: MM: SS. SSSZ and is 24 characters in length.

**Type**: string **Required**: False

# MessageRequest

Specifies the configuration and other settings for a message.

## Traceld

The unique identifier for tracing the message. This identifier is visible in message events.

**Type**: string **Required**: False

#### Context

A map of custom attributes to attach to the message. For a push notification, this payload is added to the data.pinpoint object. For an email or text message, this payload is added to email/SMS delivery receipt event attributes.

**Type**: object **Required**: False

## MessageConfiguration

The settings and content for the default message and any default messages that you defined for specific channels.

**Type**: DirectMessageConfiguration

Required: False

## **TemplateConfiguration**

The message template to use for the message.

**Type**: TemplateConfiguration

Required: False

#### **Addresses**

A map of key-value pairs, where each key is an address and each value is an <u>AddressConfiguration</u> object. An address can be a push notification token, a phone number, or an email address. You can use an <u>AddressConfiguration</u> object to tailor the message for an address by specifying settings such as content overrides and message variables.

**Type**: object **Required**: False

## **Endpoints**

A map of key-value pairs, where each key is an endpoint ID and each value is an <a href="EndpointSendConfiguration"><u>EndpointSendConfiguration</u></a> object. You can use an <a href="EndpointSendConfiguration"><u>EndpointSendConfiguration</u></a> object to tailor the message for an endpoint by specifying settings such as content overrides and message variables.

Type: object

Required: False

# MessageResponse

Provides information about the results of a request to send a message to an endpoint address.

## **ApplicationId**

The unique identifier for the application that was used to send the message.

Type: string

**Required**: True

## RequestId

The identifier for the original request that the message was delivered for.

**Type**: string

Required: False

### Result

A map that contains a multipart response for each address (email address, phone number, or push notification token) that the message was sent to. In the map, the address is the key and the result is the value.

**Type**: object

Required: False

# **EndpointResult**

A map that contains a multipart response for each address that the message was sent to. In the map, the endpoint ID is the key and the result is the value.

Type: object

Required: False

### MessageResult

Provides information about the results of sending a message directly to an endpoint address.

### **DeliveryStatus**

The delivery status of the message. Possible values are:

• DUPLICATE – The endpoint address is a duplicate of another endpoint address. Amazon Pinpoint won't attempt to send the message again.

- OPT\_OUT The SendMessages API does not honor the OPT\_OUT attribute when sending to endpoints and therefore will not use the OPT\_OUT message status.
- PERMANENT\_FAILURE An error occurred when delivering the message to the endpoint address.
   Amazon Pinpoint won't attempt to send the message again.
- SUCCESSFUL The message was successfully delivered to the endpoint address.
- TEMPORARY\_FAILURE A temporary error occurred. Amazon Pinpoint won't attempt to send the message again.
- THROTTLED Amazon Pinpoint throttled the operation to send the message to the endpoint address.
- UNKNOWN\_FAILURE An unknown error occurred.

**Type**: string **Required**: True

Values: SUCCESSFUL | THROTTLED | TEMPORARY\_FAILURE | PERMANENT\_FAILURE |

UNKNOWN\_FAILURE | OPT\_OUT | DUPLICATE

#### StatusCode

The downstream service status code for delivering the message.

**Type**: integer **Required**: True

#### StatusMessage

The status message for delivering the message.

**Type**: string **Required**: False

### **UpdatedToken**

For push notifications that are sent through the GCM channel, specifies whether the endpoint's device registration token was updated as part of delivering the message.

**Type**: string **Required**: False

#### Messageld

The unique identifier for the message that was sent.

**Type**: string **Required**: False

### **RawEmail**

Specifies the contents of an email message, represented as a raw MIME message.

#### **Data**

The email message, represented as a raw MIME message. The entire message must be base64 encoded.

**Type**: string **Required**: False

## **SMSMessage**

Specifies the default settings for a one-time SMS message that's sent directly to an endpoint.

## Body

The body of the SMS message.

Type: string

Required: False

#### **Substitutions**

The message variables to use in the SMS message. You can override the default variables with individual address variables.

**Type**: object **Required**: False

#### SenderId

The alphabetic Sender ID to display as the sender of the message on a recipient's device. Support for sender IDs varies by country. To specify a phone number as the sender, omit this parameter and use OriginationNumber instead. For more information about support for Sender ID by country, see the Amazon Pinpoint User Guide.

**Type**: string **Required**: False

### MessageType

The SMS message type. Valid values are TRANSACTIONAL (for messages that are critical or time-sensitive, such as a one-time passwords) and PROMOTIONAL (for messsages that aren't critical or time-sensitive, such as marketing messages).

**Type**: string **Required**: False

Values: TRANSACTIONAL | PROMOTIONAL

#### **Keyword**

The SMS program name that you provided to AWS Support when you requested your dedicated number.

**Type**: string **Required**: False

### OriginationNumber

The number to send the SMS message from. The phone number that you specify must exist in your Amazon Pinpoint account—you can't pass an arbitrary phone number. If you want to use a sender ID to send your message, omit this parameter and use SenderId instead.

**Type**: string **Required**: False

# **EntityId**

A registered Entity ID (currently only used when sending messages to recipients in India).

**Type**: string **Required**: False

### **TemplateId**

A registered Template ID (currently only used when sending messages to recipients in India).

**Type**: string **Required**: False

#### MediaUrl

This field is reserved for future use.

**Type**: string **Required**: False

# **SimpleEmail**

Specifies the contents of an email message, composed of a subject, a text part, and an HTML part.

## Subject

The subject line, or title, of the email.

Type: SimpleEmailPart

Required: False

#### **TextPart**

The body of the email message, in plain text format. We recommend using plain text format for email clients that don't render HTML content and clients that are connected to high-latency networks, such as mobile devices.

Type: SimpleEmailPart

Required: False

#### **HtmlPart**

The body of the email message, in HTML format. We recommend using HTML format for email clients that render HTML content. You can include links, formatted text, and more in an HTML message.

**Type**: SimpleEmailPart

Required: False

#### **Headers**

List of Headers for the email.

**Type**: Array of type MessageHeader

Required: False

# SimpleEmailPart

Specifies the subject or body of an email message, represented as textual email data and the applicable character set.

#### **Data**

The textual data of the message content.

**Type**: string **Required**: False

#### Charset

The applicable character set for the message content.

**Type**: string **Required**: False

## **Template**

Specifies the name and version of the message template to use for the message.

#### Name

The name of the message template to use for the message. If specified, this value must match the name of an existing message template.

**Type**: string **Required**: False

#### Version

The unique identifier for the version of the message template to use for the message. If specified, this value must match the identifier for an existing template version. To retrieve a list of versions and version identifiers for a template, use the Template Versions resource.

If you don't specify a value for this property, Amazon Pinpoint uses the *active version* of the template. The *active version* is typically the version of a template that's been most recently reviewed and approved for use, depending on your workflow. It isn't necessarily the latest version of a template.

**Type**: string **Required**: False

# **TemplateConfiguration**

Specifies the message template to use for the message, for each type of channel.

## **SMSTemplate**

The SMS template to use for the message.

Type: <u>Template</u> Required: False

### **EmailTemplate**

The email template to use for the message.

Type: <u>Template</u> Required: False

### **PushTemplate**

The push notification template to use for the message.

Type: <u>Template</u> Required: False

### VoiceTemplate

The voice template to use for the message. This object isn't supported for campaigns.

Type: <u>Template</u>
Required: False

### **InAppTemplate**

The InApp template to use for the message. The InApp template object is not supported for SendMessages.

Type: <u>Template</u> Required: False

## VoiceMessage

Specifies the settings for a one-time voice message that's sent directly to an endpoint through the voice channel.

### **Body**

The text of the script to use for the voice message.

Type: string

Required: False

#### **Substitutions**

The default message variables to use in the voice message. You can override the default variables with individual address variables.

**Type**: object **Required**: False

#### LanguageCode

The code for the language to use when synthesizing the text of the message script. For a list of supported languages and the code for each one, see the Amazon Polly Developer Guide.

**Type**: string **Required**: False

#### VoiceId

The name of the voice to use when delivering the message. For a list of supported voices, see the Amazon Polly Developer Guide.

**Type**: string **Required**: False

### OriginationNumber

The phone number, in E.164 format, to send the voice message from. This value should be one of the dedicated long codes that's assigned to your AWS account.

**Type**: string **Required**: False

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

See also 894

## SendMessages

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **OTP Message**

Use this resource to generate a One-Time Password (OTP) and send it to a user of your application. When the user enters the OTP code in your application, use the the <u>Verify OTP</u> resource to confirm the validity of the OTP.

### **URI**

/v1/apps/application-id/otp

## **HTTP** methods

#### **POST**

### Operation ID: SendOTPMessage

Use this operation to send an OTP code to a user of your application. When you use this API, Amazon Pinpoint generates a random code and sends it to your user.

### Path parameters

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati

OTP Message 895

Name	Type	Required	Description
			on. This identifier
			is displayed as the
			Project ID on the
			Amazon Pinpoint
			console.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	MessageResponse	200 response
400	MessageBody	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	MessageBody	The request failed because the specified resource was not found (NotFoundException).

Status code	Response model	Description
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **OPTIONS**

# **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the

Name Type Required Description

Amazon Pinpoint console.

### Responses

Status code	Response model	Description
200	None	The request succeeded.

## **Schemas**

# **Request bodies**

#### **POST schema**

```
{
    "Channel": "string",
    "OriginationIdentity": "string",
    "DestinationIdentity": "string",
    "BrandName": "string",
    "Language": "string",
    "CodeLength": integer,
    "ValidityPeriod": integer,
    "ReferenceId": "string",
    "AllowedAttempts": integer,
    "EntityId": "string",
    "TemplateId": "string"
}
```

# **Response bodies**

### MessageResponse schema

```
{
  "ApplicationId": "string",
  "RequestId": "string",
  "Result": {
  },
```

Schemas 898

```
"EndpointResult": {
  }
}
```

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

# Endpoint Message Result

Provides information about the delivery status and results of sending a message directly to an endpoint.

### **DeliveryStatus**

The delivery status of the message. Possible values are:

- DUPLICATE The endpoint address is a duplicate of another endpoint address. Amazon Pinpoint won't attempt to send the message again.
- OPT\_OUT The SendMessages API does not honor the endpoint OPT\_OUT status.
- PERMANENT\_FAILURE An error occurred when delivering the message to the endpoint.
   Amazon Pinpoint won't attempt to send the message again.
- SUCCESSFUL The message was successfully delivered to the endpoint.
- TEMPORARY\_FAILURE A temporary error occurred. Amazon Pinpoint won't attempt to send the message again.
- THROTTLED Amazon Pinpoint throttled the operation to send the message to the endpoint.
- UNKNOWN FAILURE An unknown error occurred.

```
Type: string
Required: True
Values: SUCCESSFUL | THROTTLED | TEMPORARY_FAILURE | PERMANENT_FAILURE |
UNKNOWN_FAILURE | OPT_OUT | DUPLICATE
```

#### StatusCode

The downstream service status code for delivering the message.

**Type**: integer **Required**: True

### StatusMessage

The status message for delivering the message.

**Type**: string **Required**: False

### **UpdatedToken**

For push notifications that are sent through the GCM channel, specifies whether the endpoint's device registration token was updated as part of delivering the message.

**Type**: string **Required**: False

### Messageld

The unique identifier for the message that was sent.

**Type**: string **Required**: False

#### **Address**

The endpoint address that the message was delivered to.

**Type**: string **Required**: False

## MessageBody

Provides information about an API request or response.

#### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

#### Message

The message that's returned from the API.

**Type**: string **Required**: False

## MessageResponse

Provides information about the results of a request to send a message to an endpoint address.

### **ApplicationId**

The unique identifier for the application that was used to send the message.

**Type**: string **Required**: True

### RequestId

The identifier for the original request that the message was delivered for.

**Type**: string **Required**: False

#### Result

A map that contains a multipart response for each address (email address, phone number, or push notification token) that the message was sent to. In the map, the address is the key and the result is the value.

Type: object

Required: False

### **EndpointResult**

A map that contains a multipart response for each address that the message was sent to. In the map, the endpoint ID is the key and the result is the value.

**Type**: object **Required**: False

## MessageResult

Provides information about the results of sending a message directly to an endpoint address.

### **DeliveryStatus**

The delivery status of the message. Possible values are:

- DUPLICATE The endpoint address is a duplicate of another endpoint address. Amazon Pinpoint won't attempt to send the message again.
- OPT\_OUT The SendMessages API does not honor the OPT\_OUT attribute when sending to endpoints and therefore will not use the OPT\_OUT message status.
- PERMANENT\_FAILURE An error occurred when delivering the message to the endpoint address.
   Amazon Pinpoint won't attempt to send the message again.
- SUCCESSFUL The message was successfully delivered to the endpoint address.
- TEMPORARY\_FAILURE A temporary error occurred. Amazon Pinpoint won't attempt to send the message again.
- THROTTLED Amazon Pinpoint throttled the operation to send the message to the endpoint address.
- UNKNOWN\_FAILURE An unknown error occurred.

**Type**: string **Required**: True

Values: SUCCESSFUL | THROTTLED | TEMPORARY\_FAILURE | PERMANENT\_FAILURE |

UNKNOWN\_FAILURE | OPT\_OUT | DUPLICATE

#### **StatusCode**

The downstream service status code for delivering the message.

**Type**: integer **Required**: True

#### StatusMessage

The status message for delivering the message.

**Type**: string **Required**: False

### **UpdatedToken**

For push notifications that are sent through the GCM channel, specifies whether the endpoint's device registration token was updated as part of delivering the message.

**Type**: string **Required**: False

### Messageld

The unique identifier for the message that was sent.

**Type**: string **Required**: False

## SendOTPMessageRequestParameters

Specifies the details of and parameters for the OTP that you are generating.

#### Channel

The communication channel that the OTP code is sent through. Currently, only SMS messages are supported, so the only acceptable value is SMS.

Type: string

Required: True

### OriginationIdentity

The originating identity (such as a long code, short code, or sender ID) that is used to send the OTP code. If you use a long code or toll-free number to send the OTP, the phone number must be in E.164 format.

**Type**: string **Required**: True

### DestinationIdentity

The phone number, in E.164 format, that the OTP code was sent to.

**Type**: string **Required**: True

#### **BrandName**

The name of the brand, company, or product that is associated with the OTP code. This name can contain up to 20 characters. Amazon Pinpoint automatically adds the brand name to the OTP message that it sends.

**Type**: string **Required**: False

#### Language

The language, in IETF BCP-47 format, to use when sending the message. Acceptable values are:

- de-DE German
- en-GB English (UK)
- en-US English (US)
- es-419 Spanish (Latin America)
- es-ES Spanish
- fr-CA French (Canada)

- fr-FR French
- ja-JP Japanese
- ko-KR Korean
- pt-BR Portuguese (Brazil)
- zh-CN Chinese (Simplified)
- zh-TW Chinese (Traditional)

Type: string

Required: False

### CodeLength

The number of digits that will be in the OTP code that's sent to the recipient. OTP codes can contain between 5 and 8 digits, inclusive. The default value is 6 digits.

**Type**: integer

Required: False

### **ValidityPeriod**

The amount of time, in minutes, that the OTP code will be valid. The validity period can be between 5 and 60 minutes, inclusive. The default value is 15 minutes.

Type: integer

Required: False

#### ReferenceId

A unique reference ID for the request. The reference ID exactly match the reference ID that you provide when you validate the OTP. The reference ID can contain between 1 and 48 characters, inclusive. For security purposes, you should use a reference ID that is unique to the application that is sending the OTP code.

**Type**: string

Required: True

#### AllowedAttempts

The number of times the recipient can unsuccessfully attempt to validate the OTP. If the number of attempts exceeds this value, the OTP automatically becomes invalid. The maximum number of allowed attempts is 5. The default value is 3 attempts.

**Type**: integer **Required**: False

### **EntityId**

An Entity ID that is registered with a regulatory agency. This is currently only used when sending messages to recipients in India. If you aren't sending to recipients in India, you can omit this parameter.

**Type**: string

Required: False

### **TemplateId**

A Template ID that is registered with a regulatory agency. This is currently only used when sending messages to recipients in India. If you aren't sending to recipients in India, you can omit this parameter.

Type: string

Required: False

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

# SendOTPMessage

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++

See also 906

- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Phone Number Validate**

You can use the Phone Number Validate resource to convert a phone number to E.164 format and to get more information about a phone number.

This resource accepts a POST request that includes a phone number in the request body. It responds with information about the phone number. This information includes whether the phone number is valid and the type of phone line that's associated with the number, such as mobile or landline. It also provides other helpful information about the number, such as the carrier that the number is registered with and the location where the number was originally registered.

#### **URI**

/v1/phone/number/validate

### **HTTP** methods

#### **POST**

Operation ID: PhoneNumberValidate

Retrieves information about a phone number.

### **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME

Phone Number Validate 907

Name	Туре	Required	Description
			types, the client understands.

# Responses

Status code	Response model	Description
200	NumberValidateResp onse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent

Status code	Response model	Description
		during a certain amount of time (TooManyRequestsEx ception).
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Phone Number Validate resource.

## Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Request bodies**

### **POST schema**

```
{
   "PhoneNumber": "string",
   "IsoCountryCode": "string"
}
```

# **Response bodies**

# NumberValidateResponse schema

```
{
```

Schemas 909

```
"CountryCodeIso2": "string",
"Country": "string",
"City": "string",
"ZipCode": "string",
"County": "string",
"Timezone": "string",
"CleansedPhoneNumberNational": "string",
"CleansedPhoneNumberE164": "string",
"Carrier": "string",
"PhoneTypeCode": integer,
"PhoneType": "string",
"OriginalPhoneNumber": "string",
"OriginalCountryCodeIso2": "string"
}
```

#### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

# MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

### Message

The message that's returned from the API.

Type: string

Required: False

## NumberValidateRequest

Specifies a phone number to validate and retrieve information about.

#### **PhoneNumber**

The phone number to retrieve information about. The phone number that you provide should include a valid numeric country code. Otherwise, the operation might result in an error.

**Type**: string **Required**: False

### IsoCountryCode

The two-character code, in ISO 3166-1 alpha-2 format, for the country or region where the phone number was originally registered.

**Type**: string **Required**: False

## NumberValidateResponse

Provides information about a phone number.

## CountryCodelso2

The two-character code, in ISO 3166-1 alpha-2 format, for the country or region where the phone number was originally registered.

**Type**: string **Required**: False

## CountryCodeNumeric

The numeric code for the country or region where the phone number was originally registered.

**Type**: string **Required**: False

#### **Country**

The name of the country or region where the phone number was originally registered.

**Type**: string **Required**: False

### City

The name of the city where the phone number was originally registered.

**Type**: string **Required**: False

### **ZipCode**

The postal or ZIP code for the location where the phone number was originally registered.

**Type**: string **Required**: False

## County

The name of the county where the phone number was originally registered.

**Type**: string **Required**: False

#### **Timezone**

The time zone for the location where the phone number was originally registered.

**Type**: string **Required**: False

#### CleansedPhoneNumberNational

The cleansed phone number, in the format for the location where the phone number was originally registered.

Type: string

Required: False

#### CleansedPhoneNumberE164

The cleansed phone number, in E.164 format, for the location where the phone number was originally registered.

Type: string

Required: False

#### **Carrier**

The carrier or service provider that the phone number is currently registered with. In some countries and regions, this value may be the carrier or service provider that the phone number was originally registered with.

Type: string

Required: False

### **PhoneTypeCode**

The phone type, represented by an integer. Valid values are: 0 (mobile), 1 (landline), 2 (VoIP), 3 (invalid), 4 (other), and 5 (prepaid).

Type: integer

Required: False

### **PhoneType**

The description of the phone type. Valid values are: MOBILE, LANDLINE, VOIP, INVALID, PREPAID, and OTHER.

Type: string

Required: False

### OriginalPhoneNumber

The phone number that was sent in the request body.

**Type**: string **Required**: False

### OriginalCountryCodeIso2

The two-character code, in ISO 3166-1 alpha-2 format, that was sent in the request body.

**Type**: string **Required**: False

### See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

### **PhoneNumberValidate**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Push Notification Template**

A *push notification template* is a type of message template that contains content and settings that you can define, save, and reuse in messages that you send through a push notification channel

See also 914

for any of your Amazon Pinpoint applications. You can use push notification templates in push notifications that you send from campaigns, or to a limited audience as direct or test messages.

When you create a push notification template, you specify the content and settings that you want to reuse in various components of messages that are based on the template. These components, referred to as *template parts*, can be the message title, the message body, or both. This content can be static text or personalized content that you define by using the Handlebars template system and message variables. A template part can also be a channel-specific setting, such as a sound to play or an action to occur when a recipient interacts with a push notification that's based on the template. When you send a message that's based on a template, Amazon Pinpoint populates the message with the content and settings that you defined in the template.

The Push Notification Template resource represents the repository of push notification templates that are associated with your Amazon Pinpoint account. You can use this resource to create, retrieve, update, or delete a message template for messages that you send through a push notification channel.

Amazon Pinpoint supports versioning for all types of message templates. When you use the Push Notification Template resource to work with a template, you can use supported parameters to specify whether your request applies to only a specific version of the template or to the overall template. For example, if you update a template, you can specify whether you want to save your updates as a new version of the template or save them to the latest existing version of the template. To retrieve information about all the versions of a template, use the <u>Template Versions</u> resource.

### **URI**

/v1/templates/template-name/push

# **HTTP** methods

#### **GET**

**Operation ID:** GetPushTemplate

Retrieves the content and settings of a message template for messages that are sent through a push notification channel.

URI 915

## **Path parameters**

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can contain a maximum of 128 characters. The characters can be alphanumeric characters, underscor es (_), or hyphens (-). Template names are case sensitive.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# **Query parameters**

Name	Туре	Required	Description
version	String	False	The unique identifie r for the version of the message template to update,

Name Type Required Description

retrieve information about, or delete. To retrieve identifiers and other informati on for all the versions of a template, use the <u>Template</u>
Versionsresource.

If specified, this value must match the identifier for an existing template version. If specified for an update operation, this value must match the identifier for the latest existing version of the template. This restriction helps ensure that race conditions don't occur.

If you don't specify a value for this parameter, Amazon Pinpoint does the following:

 For a get operation , retrieves informati on about the active version of the template.

Name	Type	Required	Description
			• For an update operation, saves the updates to (overwrites) the latest existing version of the template, if the create-ne w-version parameter isn't used or is set to false.
			<ul> <li>For a delete operation, deletes the template, including all versions of the template.</li> </ul>

# Responses

Status code	Response model	Description
200	PushNotificationTe mplateResponse	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	MessageBody	The request was denied because access to the specified resource is forbidden (ForbiddenException).

Status code	Response model	Description
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **POST**

# Operation ID: CreatePushTemplate

Creates a message template for messages that are sent through a push notification channel.

# **Path parameters**

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can contain a maximum of 128 characters. The characters can be alphanumeric characters, underscor es (_), or hyphens (-). Template names are case sensitive.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
201	<pre>CreateTemplateMess ageBody</pre>	The request succeeded and the specified resource was created.

Status code	Response model	Description
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
409	<u>MessageBody</u>	The request failed due to a conflict with the current state of the specified resource (ConflictException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **PUT**

Operation ID: UpdatePushTemplate

Updates an existing message template for messages that are sent through a push notification channel.

# **Path parameters**

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can contain a maximum of 128 characters. The characters can be alphanumeric characters, underscor es (_), or hyphens (-). Template names are case sensitive.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# **Query parameters**

Name	Туре	Required	Description
create-new- version	String	False	Specifies whether to save the updates as

Name Type Required Description

a new version of the message template. Valid values are: true, save the updates as a new version; and, false, save the updates to (overwrite) the latest existing version of the template.

If you don't specify a value for this parameter, Amazon Pinpoint saves the updates to (overwrites) the latest existing version of the template. If you specify a value of true for this parameter, don't specify a value for the version parameter. Otherwise , an error will occur.

Name	Туре	Required	Description
version	String	False	The unique identifie r for the version of the message template to update, retrieve information about, or delete. To retrieve identifiers and other informati on for all the versions of a template, use the Template Versions resource.  If specified, this value must match the identifier for an existing template version. If specified for an update operation, this value must match the identifier for the latest existing version of the template. This restriction helps ensure that race conditions don't occur.
			If you don't specify a value for this parameter, Amazon Pinpoint does the following:

Name	Туре	Required	Description
			<ul> <li>For a get operation         <ul> <li>retrieves informati</li> <li>on about the active</li> <li>version of the</li> <li>template.</li> </ul> </li> </ul>
			• For an update operation, saves the updates to (overwrites) the latest existing version of the template, if the create-ne w-version parameter isn't used or is set to false.
			<ul> <li>For a delete         operation, deletes         the template,         including all         versions of the         template.</li> </ul>

## Responses

Status code	Response model	Description
202	<u>MessageBody</u>	The request was accepted for processing. Processing may not be complete.
400	MessageBody	The request contains a syntax error (BadRequestException).

Status code	Response model	Description
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **DELETE**

Operation ID: DeletePushTemplate

Deletes a message template for messages that were sent through a push notification channel.

## **Path parameters**

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can contain a maximum of 128 characters. The characters can be alphanumeric characters, underscores (_), or hyphens (-). Template names are case sensitive.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# **Query parameters**

Name	Туре	Required	Description
version	String	False	The unique identifie r for the version of the message

Name Type Required Description

template to update, retrieve information about, or delete. To retrieve identifiers and other informati on for all the versions of a template, use the <u>Template</u>
Versionsresource.

If specified, this value must match the identifier for an existing template version. If specified for an update operation, this value must match the identifier for the latest existing version of the template. This restriction helps ensure that race conditions don't occur.

If you don't specify a value for this parameter, Amazon Pinpoint does the following:

 For a get operation , retrieves informati on about the active

Name	Туре	Required	Description
			version of the template.
			• For an update operation, saves the updates to (overwrites) the latest existing version of the template, if the create-ne w-version parameter isn't used or is set to false.
			<ul> <li>For a delete operation, deletes the template, including all versions of the template.</li> </ul>

## Responses

Status code	Response model	Description
202	MessageBody	The request was accepted for processing. Processing may not be complete.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	MessageBody	The request was denied because access to the specified resource is

Status code	Response model	Description
		forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Push Notification Template resource.

## **Path parameters**

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can contain a maximum of 128 characters. The characters can be alphanumeric characters, underscor es (_), or hyphens (-). Template names are case sensitive.

## Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Request bodies**

## **POST schema**

```
"Body": "string",
  "Action": enum,
  "Sound": "string",
  "Url": "string"
},
"ADM": {
  "Title": "string",
  "Body": "string",
  "Action": enum,
  "Sound": "string",
  "Url": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "SmallImageIconUrl": "string",
  "RawContent": "string"
},
"GCM": {
  "Title": "string",
  "Body": "string",
  "Action": enum,
  "Sound": "string",
  "Url": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "SmallImageIconUrl": "string",
  "RawContent": "string"
},
"Baidu": {
  "Title": "string",
  "Body": "string",
  "Action": enum,
  "Sound": "string",
  "Url": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "SmallImageIconUrl": "string",
  "RawContent": "string"
},
"APNS": {
  "Title": "string",
  "Body": "string",
  "Action": enum,
  "Sound": "string",
  "Url": "string",
```

```
"MediaUrl": "string",
    "RawContent": "string"
},
    "RecommenderId": "string"
}
```

#### **PUT schema**

```
{
  "TemplateDescription": "string",
  "DefaultSubstitutions": "string",
  "tags": {
  },
  "Default": {
    "<u>Title</u>": "string",
    "Body": "string",
    "Action": enum,
    "Sound": "string",
    "Url": "string"
  },
  "ADM": {
    "Title": "string",
    "Body": "string",
    "Action": enum,
    "Sound": "string",
    "Url": "string",
    "ImageUrl": "string",
    "ImageIconUrl": "string",
    "SmallImageIconUrl": "string",
    "RawContent": "string"
  },
  "GCM": {
    "<u>Title</u>": "string",
    "Body": "string",
    "Action": enum,
    "Sound": "string",
    "Url": "string",
    "ImageUrl": "string",
    "ImageIconUrl": "string",
    "SmallImageIconUrl": "string",
    "RawContent": "string"
  },
  "Baidu": {
```

```
"Title": "string",
    "Body": "string",
    "Action": enum,
    "Sound": "string",
    "Url": "string",
    "ImageUrl": "string",
    "ImageIconUrl": "string",
    "SmallImageIconUrl": "string",
    "RawContent": "string"
  },
  "APNS": {
    "Title": "string",
    "Body": "string",
    "Action": enum,
    "Sound": "string",
    "Url": "string",
    "MediaUrl": "string",
    "RawContent": "string"
  },
  "RecommenderId": "string"
}
```

# **Response bodies**

### PushNotificationTemplateResponse schema

```
"CreationDate": "string",
"LastModifiedDate": "string",
"TemplateType": enum,
"TemplateName": "string",
"TemplateDescription": "string",
"DefaultSubstitutions": "string",
"Version": "string",
"tags": {
},
"Arn": "string",
"Default": {
 "Title": "string",
  "Body": "string",
  "Action": enum,
  "Sound": "string",
  "Url": "string"
```

```
},
"ADM": {
  "Title": "string",
  "Body": "string",
  "Action": enum,
  "Sound": "string",
  "Url": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "SmallImageIconUrl": "string",
  "RawContent": "string"
},
"GCM": {
  "Title": "string",
  "Body": "string",
  "Action": enum,
  "Sound": "string",
  "Url": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "SmallImageIconUrl": "string",
  "RawContent": "string"
},
"Baidu": {
  "Title": "string",
  "Body": "string",
  "Action": enum,
  "Sound": "string",
  "Url": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "SmallImageIconUrl": "string",
  "RawContent": "string"
},
"APNS": {
  "Title": "string",
  "Body": "string",
  "Action": enum,
  "Sound": "string",
  "Url": "string",
  "Medi<u>aUrl</u>": "string",
  "RawContent": "string"
},
"RecommenderId": "string"
```

```
}
```

### CreateTemplateMessageBody schema

```
{
   "RequestID": "string",
   "Message": "string",
   "Arn": "string"
}
```

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

## APNSPushNotificationTemplate

Specifies channel-specific content and settings for a message template that can be used in push notifications that are sent through the APNs (Apple Push Notification service) channel.

#### Title

The title to use in push notifications that are based on the message template. This title appears above the notification message on a recipient's device.

**Type**: string **Required**: False

### **Body**

The message body to use in push notifications that are based on the message template.

**Type**: string **Required**: False

#### **Action**

The action to occur if a recipient taps a push notification that's based on the message template. Valid values are:

- OPEN\_APP Your app opens or it becomes the foreground app if it was sent to the background.
   This is the default action.
- DEEP\_LINK Your app opens and displays a designated user interface in the app. This setting uses the deep-linking features of the iOS platform.
- URL The default mobile browser on the recipient's device opens and loads the web page at a URL that you specify.

**Type**: string **Required**: False

Values: OPEN\_APP | DEEP\_LINK | URL

#### Sound

The key for the sound to play when the recipient receives a push notification that's based on the message template. The value for this key is the name of a sound file in your app's main bundle or the Library/Sounds folder in your app's data container. If the sound file can't be found or you specify default for the value, the system plays the default alert sound.

**Type**: string **Required**: False

#### Url

The URL to open in the recipient's default mobile browser, if a recipient taps a push notification that's based on the message template and the value of the Action property is URL.

**Type**: string **Required**: False

#### MediaUrl

The URL of an image or video to display in push notifications that are based on the message template.

**Type**: string **Required**: False

#### **RawContent**

The raw, JSON-formatted string to use as the payload for push notifications that are based on the message template. If specified, this value overrides all other content for the message template.

**Type**: string **Required**: False

## AndroidPushNotificationTemplate

Specifies channel-specific content and settings for a message template that can be used in push notifications that are sent through the ADM (Amazon Device Messaging), Baidu (Baidu Cloud Push), or GCM (Firebase Cloud Messaging, formerly Google Cloud Messaging) channel.

#### **Title**

The title to use in a push notification that's based on the message template. This title appears above the notification message on a recipient's device.

**Type**: string **Required**: False

### **Body**

The message body to use in a push notification that's based on the message template.

**Type**: string **Required**: False

#### Action

The action to occur if a recipient taps a push notification that's based on the message template. Valid values are:

OPEN\_APP – Your app opens or it becomes the foreground app if it was sent to the background.
 This is the default action.

• DEEP\_LINK – Your app opens and displays a designated user interface in the app. This action uses the deep-linking features of the Android platform.

• URL – The default mobile browser on the recipient's device opens and loads the web page at a URL that you specify.

**Type**: string **Required**: False

Values: OPEN\_APP | DEEP\_LINK | URL

#### Sound

The sound to play when a recipient receives a push notification that's based on the message template. You can use the default stream or specify the file name of a sound resource that's bundled in your app. On an Android platform, the sound file must reside in /res/raw/.

**Type**: string **Required**: False

#### Url

The URL to open in a recipient's default mobile browser, if a recipient taps a push notification that's based on the message template and the value of the Action property is URL.

**Type**: string **Required**: False

#### **ImageUrl**

The URL of an image to display in a push notification that's based on the message template.

**Type**: string **Required**: False

#### **ImageIconUrl**

The URL of the large icon image to display in the content view of a push notification that's based on the message template.

**Type**: string

Required: False

### **SmallImageIconUrl**

The URL of the small icon image to display in the status bar and the content view of a push notification that's based on the message template.

Type: string

Required: False

#### **RawContent**

The raw, JSON-formatted string to use as the payload for a push notification that's based on the message template. If specified, this value overrides all other content for the message template.

Type: string

Required: False

# CreateTemplateMessageBody

Provides information about a request to create a message template.

### RequestID

The unique identifier for the request to create the message template.

Type: string

Required: False

### Message

The message that's returned from the API for the request to create the message template.

**Type**: string

Required: False

#### Arn

The Amazon Resource Name (ARN) of the message template that was created.

**Type**: string **Required**: False

## DefaultPushNotificationTemplate

Specifies the default settings and content for a message template that can be used in messages that are sent through a push notification channel.

### **Title**

The title to use in push notifications that are based on the message template. This title appears above the notification message on a recipient's device.

**Type**: string **Required**: False

### Body

The message body to use in push notifications that are based on the message template.

**Type**: string

Required: False

#### **Action**

The action to occur if a recipient taps a push notification that's based on the message template. Valid values are:

- OPEN\_APP Your app opens or it becomes the foreground app if it was sent to the background. This is the default action.
- DEEP\_LINK Your app opens and displays a designated user interface in the app. This setting
  uses the deep-linking features of the iOS and Android platforms.
- URL The default mobile browser on the recipient's device opens and loads the web page at a URL that you specify.

**Type**: string **Required**: False

Values: OPEN\_APP | DEEP\_LINK | URL

#### Sound

The sound to play when a recipient receives a push notification that's based on the message template. You can use the default stream or specify the file name of a sound resource that's bundled in your app. On an Android platform, the sound file must reside in /res/raw/.

For an iOS platform, this value is the key for the name of a sound file in your app's main bundle or the Library/Sounds folder in your app's data container. If the sound file can't be found or you specify default for the value, the system plays the default alert sound.

**Type**: string **Required**: False

#### Url

The URL to open in a recipient's default mobile browser, if a recipient taps a push notification that's based on the message template and the value of the Action property is URL.

**Type**: string **Required**: False

# MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

### Message

The message that's returned from the API.

**Type**: string Required: False

## PushNotificationTemplateRequest

Specifies the content and settings for a message template that can be used in messages that are sent through a push notification channel.

### **TemplateDescription**

A custom description of the message template.

**Type**: string Required: False

#### **DefaultSubstitutions**

A JSON object that specifies the default values to use for message variables in the message template. This object is a set of key-value pairs. Each key defines a message variable in the template. The corresponding value defines the default value for that variable. When you create a message that's based on the template, you can override these defaults with message-specific and address-specific variables and values.

**Type**: string Required: False

#### tags



### Note

As of 22-05-2023 the tags attribute has been deprecated. After this date any value in the PUT UpdatePushTemplate tags attribute is not processed and an error code is not returned. The POST CreatePushTemplate tags attribute is processed. Use the Tags resource to add or modify tags.

(Deprecated) A string-to-string map of key-value pairs that defines the tags to associate with the message template. Each tag consists of a required tag key and an associated tag value.

**Type**: object **Required**: False

#### **Default**

The default message template to use for push notification channels.

**Type**: DefaultPushNotificationTemplate

Required: False

#### **ADM**

The message template to use for the ADM (Amazon Device Messaging) channel. This message template overrides the default template for push notification channels (DefaultPushNotificationTemplate).

**Type**: AndroidPushNotificationTemplate

Required: False

#### **GCM**

The message template to use for the GCM channel, which is used to send notifications through the Firebase Cloud Messaging (FCM), formerly Google Cloud Messaging (GCM), service. This message template overrides the default template for push notification channels (DefaultPushNotificationTemplate).

Type: AndroidPushNotificationTemplate

Required: False

#### Baidu

The message template to use for the Baidu (Baidu Cloud Push) channel. This message template overrides the default template for push notification channels (DefaultPushNotificationTemplate).

**Type**: AndroidPushNotificationTemplate

Required: False

#### **APNS**

The message template to use for the APNs (Apple Push Notification service) channel. This message template overrides the default template for push notification channels (DefaultPushNotificationTemplate).

Type: APNSPushNotificationTemplate

**Required**: False

#### RecommenderId

The unique identifier for the recommender model to use for the message template. Amazon Pinpoint uses this value to determine how to retrieve and process data from a recommender model when it sends messages that use the template, if the template contains message variables for recommendation data.

Type: string

Required: False

## PushNotificationTemplateResponse

Provides information about the content and settings for a message template that can be used in messages that are sent through a push notification channel.

#### CreationDate

The date, in ISO 8601 format, when the message template was created.

**Type**: string

Required: True

#### LastModifiedDate

The date, in ISO 8601 format, when the message template was last modified.

**Type**: string

Required: True

### **TemplateType**

The type of channel that the message template is designed for. For a push notification template, this value is PUSH.

**Type**: string **Required**: True

Values: EMAIL | SMS | VOICE | PUSH | INAPP

### **TemplateName**

The name of the message template.

**Type**: string **Required**: True

### **TemplateDescription**

The custom description of the message template.

**Type**: string **Required**: False

#### **DefaultSubstitutions**

The JSON object that specifies the default values that are used for message variables in the message template. This object is a set of key-value pairs. Each key defines a message variable in the template. The corresponding value defines the default value for that variable.

**Type**: string **Required**: False

### Version

The unique identifier, as an integer, for the active version of the message template, or the version of the template that you specified by using the version parameter in your request.

**Type**: string **Required**: False

#### tags

A string-to-string map of key-value pairs that identifies the tags that are associated with the message template. Each tag consists of a required tag key and an associated tag value.

**Type**: object **Required**: False

#### Arn

The Amazon Resource Name (ARN) of the message template.

**Type**: string **Required**: False

#### **Default**

The default message template that's used for push notification channels.

**Type**: DefaultPushNotificationTemplate

Required: False

#### **ADM**

The message template that's used for the ADM (Amazon Device Messaging) channel. This message template overrides the default template for push notification channels (DefaultPushNotificationTemplate).

**Type**: AndroidPushNotificationTemplate

Required: False

#### **GCM**

The message template that's used for the GCM channel, which is used to send notifications through the Firebase Cloud Messaging (FCM), formerly Google Cloud Messaging (GCM), service. This message template overrides the default template for push notification channels (DefaultPushNotificationTemplate).

Type: AndroidPushNotificationTemplate

Required: False

#### Baidu

The message template that's used for the Baidu (Baidu Cloud Push) channel. This message template overrides the default template for push notification channels (DefaultPushNotificationTemplate).

**Type**: AndroidPushNotificationTemplate

Required: False

#### **APNS**

The message template that's used for the APNs (Apple Push Notification service) channel. This message template overrides the default template for push notification channels (DefaultPushNotificationTemplate).

**Type**: APNSPushNotificationTemplate

Required: False

#### RecommenderId

The unique identifier for the recommender model that's used by the message template.

**Type**: string **Required**: False

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

# **GetPushTemplate**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++

See also 948

- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

## CreatePushTemplate

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **UpdatePushTemplate**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3

See also 949

- · AWS SDK for Python
- AWS SDK for Ruby V3

# **DeletePushTemplate**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Recommender Model**

A recommender model is a type of machine learning (ML) model that generates predictions and recommendations by finding patterns in data. Based on the data that it receives, the model can dynamically predict and deliver a combination of personalized recommendations to add to messages. In Amazon Pinpoint, you can connect to these models, and send personalized recommendations to message recipients based on each recipient's attributes and behavior.

To use a recommender model with Amazon Pinpoint, you start by creating an Amazon Personalize solution and deploying that solution as an Amazon Personalize campaign. Then you create a configuration for the recommender model in Amazon Pinpoint. In the configuration, you specify settings that determine where and how to retrieve and process data from the Amazon Personalize campaign. This includes: how to correlate user or endpoint identifiers in Amazon Pinpoint with user identifiers in the model; the number of recommended items to retrieve for each user or endpoint; and, where to store and how to process recommended items.

After you create a configuration, you can add recommendations from the model to messages that you send from campaigns and journeys. To do this, create an email, push notification, or SMS

Recommender Model 950

message template. In the template, specify the recommender model to use and add message variables that refer to recommended attributes for the model. A *recommended attribute* is a dynamic attribute that stores recommendation data. When you send a message that uses the template, Amazon Pinpoint retrieves the latest data from the recommender model, replaces each message variable with the recommendation data for each recipient, and then sends the message.

The Recommender Model resource represents the configuration settings for an individual recommender model that's associated with your Amazon Pinpoint account. This resource is available in the following AWS Regions: US East (N. Virginia); US West (Oregon); Asia Pacific (Mumbai); Asia Pacific (Sydney); and, Europe (Ireland).

You can use this resource to retrieve information about, update, or delete an Amazon Pinpoint configuration for a recommender model. To create a configuration for a recommender model, use the Recommender Models resource.

### URI

/v1/recommenders/recommender-id

### **HTTP** methods

### **GET**

**Operation ID:** GetRecommenderConfiguration

Retrieves information about an Amazon Pinpoint configuration for a recommender model.

### **Path parameters**

Name	Туре	Required	Description
recommender-id	String	True	The unique identifie r for the recommend er model configura tion. This identifie r is displayed as the <b>Recommender ID</b> on the Amazon Pinpoint console.

URI 951

## **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	RecommenderConfigurationResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	MessageBody	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	MessageBody	The request failed because the specified resource was not found (NotFoundException).
405	MessageBody	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large

Status code	Response model	Description
		(RequestEntityTooLargeExcep tion).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **PUT**

**Operation ID:** UpdateRecommenderConfiguration

Updates an Amazon Pinpoint configuration for a recommender model.

## **Path parameters**

Name	Туре	Required	Description
recommender-id	String	True	The unique identifie r for the recommend er model configura tion. This identifie r is displayed as the <b>Recommender ID</b> on the Amazon Pinpoint console.

## **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	RecommenderConfigurationResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	MessageBody	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	MessageBody	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large

Status code	Response model	Description
		(RequestEntityTooLargeExcep tion).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **DELETE**

Operation ID: DeleteRecommenderConfiguration

Deletes an Amazon Pinpoint configuration for a recommender model.

# **Path parameters**

Name	Туре	Required	Description
recommender-id	String	True	The unique identifie r for the recommend er model configura tion. This identifie r is displayed as the <b>Recommender ID</b> on the Amazon Pinpoint console.

## **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	RecommenderConfigurationResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	MessageBody	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	MessageBody	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large

Status code	Response model	Description
		(RequestEntityTooLargeExcep tion).
429	MessageBody	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Recommender Model resource.

## **Path parameters**

Name	Туре	Required	Description
recommender-id	String	True	The unique identifie r for the recommend er model configura tion. This identifie r is displayed as the <b>Recommender ID</b> on the Amazon Pinpoint console.

#### Responses

Status code	Response model	Description	
200	None	The request succeeded.	

## **Schemas**

## **Request bodies**

### **PUT** schema

```
{
   "Name": "string",
   "Description": "string",
   "RecommendationProviderUri": "string",
   "RecommendationTransformerUri": "string",
   "RecommendationProviderRoleArn": "string",
   "RecommendationsPerMessage": integer,
   "RecommendationProviderIdType": "string",
   "RecommendationsDisplayName": "string",
   "Attributes": {
   }
}
```

# **Response bodies**

### RecommenderConfigurationResponse schema

```
"Id": "string",
   "CreationDate": "string",
   "LastModifiedDate": "string",
   "Name": "string",
   "Description": "string",
   "RecommendationProviderUri": "string",
   "RecommendationTransformerUri": "string",
   "RecommendationProviderRoleArn": "string",
   "RecommendationsPerMessage": integer,
   "RecommendationProviderIdType": "string",
   "RecommendationsDisplayName": "string",
```

```
"Attributes": {
  }
}
```

## MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

## MessageBody

Provides information about an API request or response.

## RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

## Message

The message that's returned from the API.

**Type**: string **Required**: False

# Recommender Configuration Response

Provides information about Amazon Pinpoint configuration settings for retrieving and processing data from a recommender model.

#### Id

The unique identifier for the recommender model configuration.

**Type**: string **Required**: True

### CreationDate

The date, in extended ISO 8601 format, when the configuration was created for the recommender model.

**Type**: string **Required**: True

### LastModifiedDate

The date, in extended ISO 8601 format, when the configuration for the recommender model was last modified.

**Type**: string **Required**: True

#### Name

The custom name of the configuration for the recommender model.

**Type**: string **Required**: False

## **Description**

The custom description of the configuration for the recommender model.

**Type**: string **Required**: False

#### RecommendationProviderUri

The Amazon Resource Name (ARN) of the recommender model that Amazon Pinpoint retrieves the recommendation data from. This value is the ARN of an Amazon Personalize campaign.

**Type**: string **Required**: True

### RecommendationTransformerUri

The name or Amazon Resource Name (ARN) of the AWS Lambda function that Amazon Pinpoint invokes to perform additional processing of recommendation data that it retrieves from the recommender model.

**Type**: string **Required**: False

#### RecommendationProviderRoleArn

The Amazon Resource Name (ARN) of the AWS Identity and Access Management (IAM) role that authorizes Amazon Pinpoint to retrieve recommendation data from the recommender model.

**Type**: string **Required**: True

## RecommendationsPerMessage

The number of recommended items that are retrieved from the model for each endpoint or user, depending on the value for the RecommendationProviderIdType property. This number determines how many recommended items are available for use in message variables.

**Type**: integer **Required**: False

## Recommendation Provider Id Type

The type of Amazon Pinpoint ID that's associated with unique user IDs in the recommender model. This value enables the model to use attribute and event data that's specific to a particular endpoint or user in an Amazon Pinpoint application. Possible values are:

• PINPOINT\_ENDPOINT\_ID – Each user in the model is associated with a particular endpoint in Amazon Pinpoint. The data is correlated based on endpoint IDs in Amazon Pinpoint. This is the default value.

• PINPOINT\_USER\_ID – Each user in the model is associated with a particular user and endpoint in Amazon Pinpoint. The data is correlated based on user IDs in Amazon Pinpoint. If this value is specified, an endpoint definition in Amazon Pinpoint has to specify both a user ID (UserId) and an endpoint ID. Otherwise, messages won't be sent to the user's endpoint.

**Type**: string

Required: False

## RecommendationsDisplayName

The custom display name for the standard endpoint or user attribute (RecommendationItems) that temporarily stores recommended items for each endpoint or user, depending on the value for the RecommendationProviderIdType property. This name appears in the **Attribute finder** of the template editor on the Amazon Pinpoint console.

This value is null if the configuration doesn't invoke an AWS Lambda function (RecommendationTransformerUri) to perform additional processing of recommendation data.

**Type**: string

**Required**: False

#### **Attributes**

A map that defines 1-10 custom endpoint or user attributes, depending on the value for the RecommendationProviderIdType property. Each of these attributes temporarily stores a recommended item that's retrieved from the recommender model and sent to an AWS Lambda function for additional processing. Each attribute can be used as a message variable in a message template.

This value is null if the configuration doesn't invoke an AWS Lambda function (RecommendationTransformerUri) to perform additional processing of recommendation data.

**Type**: object

Required: False

## UpdateRecommenderConfiguration

Specifies Amazon Pinpoint configuration settings for retrieving and processing recommendation data from a recommender model.

#### Name

A custom name of the configuration for the recommender model. The name must start with a letter or number and it can contain up to 128 characters. The characters can be letters, numbers, spaces, underscores (\_), or hyphens (-).

**Type**: string

Required: False

## **Description**

A custom description of the configuration for the recommender model. The description can contain up to 128 characters. The characters can be letters, numbers, spaces, or the following symbols: \_; (), -.

Type: string

Required: False

#### RecommendationProviderUri

The Amazon Resource Name (ARN) of the recommender model to retrieve recommendation data from. This value must match the ARN of an Amazon Personalize campaign.

Type: string

Required: True

#### RecommendationTransformerUri

The name or Amazon Resource Name (ARN) of the AWS Lambda function to invoke for additional processing of recommendation data that's retrieved from the recommender model.

Type: string

Required: False

#### RecommendationProviderRoleArn

The Amazon Resource Name (ARN) of the AWS Identity and Access Management (IAM) role that authorizes Amazon Pinpoint to retrieve recommendation data from the recommender model.

**Type**: string **Required**: True

## RecommendationsPerMessage

The number of recommended items to retrieve from the model for each endpoint or user, depending on the value for the RecommendationProviderIdType property. This number determines how many recommended items are available for use in message variables. The minimum value is 1. The maximum value is 5. The default value is 5.

To use multiple recommended items and custom attributes with message variables, you have to use an AWS Lambda function (RecommendationTransformerUri) to perform additional processing of recommendation data.

**Type**: integer **Required**: False

## Recommendation Provider Id Type

The type of Amazon Pinpoint ID to associate with unique user IDs in the recommender model. This value enables the model to use attribute and event data that's specific to a particular endpoint or user in an Amazon Pinpoint application. Valid values are:

- PINPOINT\_ENDPOINT\_ID Associate each user in the model with a particular endpoint in Amazon Pinpoint. The data is correlated based on endpoint IDs in Amazon Pinpoint. This is the default value.
- PINPOINT\_USER\_ID Associate each user in the model with a particular user and endpoint in Amazon Pinpoint. The data is correlated based on user IDs in Amazon Pinpoint. If you specify this value, an endpoint definition in Amazon Pinpoint has to specify both a user ID (UserId) and an endpoint ID. Otherwise, messages won't be sent to the user's endpoint.

**Type**: string **Required**: False

## RecommendationsDisplayName

A custom display name for the standard endpoint or user attribute (RecommendationItems) that temporarily stores recommended items for each endpoint or user, depending on the value for the RecommendationProviderIdType property. This value is required if the configuration doesn't invoke an AWS Lambda function (RecommendationTransformerUri) to perform additional processing of recommendation data.

This name appears in the **Attribute finder** of the template editor on the Amazon Pinpoint console. The name can contain up to 25 characters. The characters can be letters, numbers, spaces, underscores (\_), or hyphens (-). These restrictions don't apply to attribute values.

**Type**: string **Required**: False

#### **Attributes**

A map of key-value pairs that defines 1-10 custom endpoint or user attributes, depending on the value for the RecommendationProviderIdType property. Each of these attributes temporarily stores a recommended item that's retrieved from the recommender model and sent to an AWS Lambda function for additional processing. Each attribute can be used as a message variable in a message template.

In the map, the key is the name of a custom attribute and the value is a custom display name for that attribute. The display name appears in the **Attribute finder** of the template editor on the Amazon Pinpoint console. The following restrictions apply to these names:

- An attribute name must start with a letter or number and it can contain up to 50 characters. The characters can be letters, numbers, underscores (\_), or hyphens (-). Attribute names are case sensitive and must be unique.
- An attribute display name must start with a letter or number and it can contain up to 25 characters. The characters can be letters, numbers, spaces, underscores (\_), or hyphens (-).

This object is required if the configuration invokes an AWS Lambda function (RecommendationTransformerUri) to process recommendation data. Otherwise, don't include this object in your request.

Type: object

### Required: False

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## GetRecommenderConfiguration

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- · AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# ${\bf Update Recommender Configuration}$

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

See also 966

# DeleteRecommenderConfiguration

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- · AWS SDK for Python
- AWS SDK for Ruby V3

# **Recommender Models**

A recommender model is a type of machine learning (ML) model that generates predictions and recommendations by finding patterns in data. Based on the data that it receives, the model can dynamically predict and deliver a combination of personalized recommendations to add to messages. In Amazon Pinpoint, you can connect to these models, and send personalized recommendations to message recipients based on each recipient's attributes and behavior.

To use a recommender model with Amazon Pinpoint, you start by creating an Amazon Personalize solution and deploying that solution as an Amazon Personalize campaign. Then you create a configuration for the recommender model in Amazon Pinpoint. In the configuration, you specify settings that determine where and how to retrieve and process data from the Amazon Personalize campaign. This includes: how to correlate user or endpoint identifiers in Amazon Pinpoint with user identifiers in the model; the number of recommended items to retrieve for each user or endpoint; and, where to store and how to process recommended items.

After you create a configuration, you can add recommendations from the model to messages that you send from campaigns and journeys. To do this, create an email, push notification, or SMS message template. In the template, specify the recommender model to use and add message variables that refer to recommended attributes for the model. A *recommended attribute* is a dynamic attribute that stores recommendation data. When you send a message that uses the

Recommender Models 967

template, Amazon Pinpoint retrieves the latest data from the recommender model, replaces each message variable with the recommendation data for each recipient, and then sends the message.

The Recommender Models resource represents the repository of recommender model configurations that are associated with your Amazon Pinpoint account. This resource is available in the following AWS Regions: US East (N. Virginia); US West (Oregon); Asia Pacific (Mumbai); Asia Pacific (Sydney); and, Europe (Ireland).

You can use this resource to create a new Amazon Pinpoint configuration for a recommender model or to retrieve information about all the existing configurations for your account. To update or delete a configuration for a recommender model, use the Recommender Model resource.

## **URI**

/v1/recommenders

## **HTTP** methods

#### **GET**

**Operation ID:** GetRecommenderConfigurations

Retrieves information about all the recommender model configurations that are associated with your Amazon Pinpoint account.

### **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

#### **Query parameters**

Name	Туре	Required	Description
token	String	False	The NextToken string that specifies

URI 968

Name	Туре	Required	Description
			which page of results to return in a paginated response.
page-size	String	False	The maximum number of items to include in each page of a paginated response. This parameter is not supported for application, campaign, and journey metrics.

# Responses

Status code	Response model	Description
200	<u>ListRecommenderCon</u> <u>figurationsResponse</u>	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).

Status code	Response model	Description
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **POST**

Operation ID: CreateRecommenderConfiguration

Creates an Amazon Pinpoint configuration for a recommender model.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME

Name	Туре	Required	Description
			types, the client understands.

# Responses

Status code	Response model	Description
201	RecommenderConfigurationResponse	The request succeeded and the specified resource was created.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).

Status code	Response model	Description
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Recommender Models resource.

## Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Request bodies**

### **POST schema**

```
"Name": "string",
"Description": "string",
"RecommendationProviderUri": "string",
"RecommendationTransformerUri": "string",
"RecommendationProviderRoleArn": "string",
"RecommendationSperMessage": integer,
"RecommendationProviderIdType": "string",
```

```
"RecommendationsDisplayName": "string",

"Attributes": {
  }
}
```

# **Response bodies**

## ListRecommenderConfigurationsResponse schema

```
{
  "Item": [
    {
      "Id": "string",
      ""CreationDate": "string",
      "LastModifiedDate": "string",
      "Name": "string",
      "Description": "string",
      "RecommendationProviderUri": "string",
      "RecommendationTransformerUri": "string",
      "RecommendationProviderRoleArn": "string",
      "RecommendationsPerMessage": integer,
      "RecommendationProviderIdType": "string",
      "RecommendationsDisplayName": "string",
      "Attributes": {
      }
    }
  ],
  "NextToken": "string"
}
```

## RecommenderConfigurationResponse schema

```
{
  "Id": "string",
  "CreationDate": "string",
  "LastModifiedDate": "string",
  "Name": "string",
  "Description": "string",
  "RecommendationProviderUri": "string",
  "RecommendationTransformerUri": "string",
  "RecommendationProviderRoleArn": "string",
  "RecommendationSperMessage": integer,
```

```
"RecommendationProviderIdType": "string",
"RecommendationsDisplayName": "string",
"Attributes": {
}
}
```

## MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

# CreateRecommenderConfiguration

Specifies Amazon Pinpoint configuration settings for retrieving and processing recommendation data from a recommender model.

#### Name

A custom name of the configuration for the recommender model. The name must start with a letter or number and it can contain up to 128 characters. The characters can be letters, numbers, spaces, underscores (\_), or hyphens (-).

**Type**: string **Required**: False

## Description

A custom description of the configuration for the recommender model. The description can contain up to 128 characters. The characters can be letters, numbers, spaces, or the following symbols: \_ ; () , -.

**Type**: string **Required**: False

#### RecommendationProviderUri

The Amazon Resource Name (ARN) of the recommender model to retrieve recommendation data from. This value must match the ARN of an Amazon Personalize campaign.

**Type**: string **Required**: True

#### RecommendationTransformerUri

The name or Amazon Resource Name (ARN) of the AWS Lambda function to invoke for additional processing of recommendation data that's retrieved from the recommender model.

**Type**: string **Required**: False

### RecommendationProviderRoleArn

The Amazon Resource Name (ARN) of the AWS Identity and Access Management (IAM) role that authorizes Amazon Pinpoint to retrieve recommendation data from the recommender model.

**Type**: string **Required**: True

## RecommendationsPerMessage

The number of recommended items to retrieve from the model for each endpoint or user, depending on the value for the RecommendationProviderIdType property. This number determines how many recommended items are available for use in message variables. The minimum value is 1. The maximum value is 5. The default value is 5.

To use multiple recommended items and custom attributes with message variables, you have to use an AWS Lambda function (RecommendationTransformerUri) to perform additional processing of recommendation data.

**Type**: integer **Required**: False

## RecommendationProviderIdType

The type of Amazon Pinpoint ID to associate with unique user IDs in the recommender model. This value enables the model to use attribute and event data that's specific to a particular endpoint or user in an Amazon Pinpoint application. Valid values are:

- PINPOINT\_ENDPOINT\_ID Associate each user in the model with a particular endpoint in Amazon Pinpoint. The data is correlated based on endpoint IDs in Amazon Pinpoint. This is the default value.
- PINPOINT\_USER\_ID Associate each user in the model with a particular user and endpoint in Amazon Pinpoint. The data is correlated based on user IDs in Amazon Pinpoint. If you specify this value, an endpoint definition in Amazon Pinpoint has to specify both a user ID (UserId) and an endpoint ID. Otherwise, messages won't be sent to the user's endpoint.

**Type**: string **Required**: False

## RecommendationsDisplayName

A custom display name for the standard endpoint or user attribute (RecommendationItems) that temporarily stores recommended items for each endpoint or user, depending on the value for the RecommendationProviderIdType property. This value is required if the configuration doesn't invoke an AWS Lambda function (RecommendationTransformerUri) to perform additional processing of recommendation data.

This name appears in the **Attribute finder** of the template editor on the Amazon Pinpoint console. The name can contain up to 25 characters. The characters can be letters, numbers, spaces, underscores (\_), or hyphens (-). These restrictions don't apply to attribute values.

**Type**: string **Required**: False

#### **Attributes**

A map of key-value pairs that defines 1-10 custom endpoint or user attributes, depending on the value for the RecommendationProviderIdType property. Each of these attributes temporarily stores a recommended item that's retrieved from the recommender model and sent to an AWS

Lambda function for additional processing. Each attribute can be used as a message variable in a message template.

In the map, the key is the name of a custom attribute and the value is a custom display name for that attribute. The display name appears in the **Attribute finder** of the template editor on the Amazon Pinpoint console. The following restrictions apply to these names:

- An attribute name must start with a letter or number and it can contain up to 50 characters. The characters can be letters, numbers, underscores (\_), or hyphens (-). Attribute names are case sensitive and must be unique.
- An attribute display name must start with a letter or number and it can contain up to 25 characters. The characters can be letters, numbers, spaces, underscores (\_), or hyphens (-).

This object is required if the configuration invokes an AWS Lambda function (RecommendationTransformerUri) to process recommendation data. Otherwise, don't include this object in your request.

**Type**: object **Required**: False

## ListRecommenderConfigurationsResponse

Provides information about all the recommender model configurations that are associated with your Amazon Pinpoint account.

#### Item

An array of responses, one for each recommender model configuration that's associated with your Amazon Pinpoint account.

**Type**: Array of type RecommenderConfigurationResponse

Required: True

#### NextToken

The string to use in a subsequent request to get the next page of results in a paginated response. This value is null if there are no additional pages.

Type: string

Required: False

## MessageBody

Provides information about an API request or response.

## RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

## Message

The message that's returned from the API.

**Type**: string **Required**: False

# Recommender Configuration Response

Provides information about Amazon Pinpoint configuration settings for retrieving and processing data from a recommender model.

#### Id

The unique identifier for the recommender model configuration.

**Type**: string **Required**: True

### CreationDate

The date, in extended ISO 8601 format, when the configuration was created for the recommender model.

**Type**: string **Required**: True

#### LastModifiedDate

The date, in extended ISO 8601 format, when the configuration for the recommender model was last modified.

**Type**: string **Required**: True

#### Name

The custom name of the configuration for the recommender model.

**Type**: string **Required**: False

## **Description**

The custom description of the configuration for the recommender model.

**Type**: string **Required**: False

#### RecommendationProviderUri

The Amazon Resource Name (ARN) of the recommender model that Amazon Pinpoint retrieves the recommendation data from. This value is the ARN of an Amazon Personalize campaign.

**Type**: string **Required**: True

#### RecommendationTransformerUri

The name or Amazon Resource Name (ARN) of the AWS Lambda function that Amazon Pinpoint invokes to perform additional processing of recommendation data that it retrieves from the recommender model.

**Type**: string **Required**: False

#### RecommendationProviderRoleArn

The Amazon Resource Name (ARN) of the AWS Identity and Access Management (IAM) role that authorizes Amazon Pinpoint to retrieve recommendation data from the recommender model.

**Type**: string **Required**: True

### RecommendationsPerMessage

The number of recommended items that are retrieved from the model for each endpoint or user, depending on the value for the RecommendationProviderIdType property. This number determines how many recommended items are available for use in message variables.

**Type**: integer **Required**: False

### RecommendationProviderIdType

The type of Amazon Pinpoint ID that's associated with unique user IDs in the recommender model. This value enables the model to use attribute and event data that's specific to a particular endpoint or user in an Amazon Pinpoint application. Possible values are:

- PINPOINT\_ENDPOINT\_ID Each user in the model is associated with a particular endpoint in Amazon Pinpoint. The data is correlated based on endpoint IDs in Amazon Pinpoint. This is the default value.
- PINPOINT\_USER\_ID Each user in the model is associated with a particular user and endpoint in Amazon Pinpoint. The data is correlated based on user IDs in Amazon Pinpoint. If this value is specified, an endpoint definition in Amazon Pinpoint has to specify both a user ID (UserId) and an endpoint ID. Otherwise, messages won't be sent to the user's endpoint.

**Type**: string **Required**: False

#### RecommendationsDisplayName

The custom display name for the standard endpoint or user attribute (RecommendationItems) that temporarily stores recommended items for each endpoint or user, depending on the value for

the RecommendationProviderIdType property. This name appears in the **Attribute finder** of the template editor on the Amazon Pinpoint console.

This value is null if the configuration doesn't invoke an AWS Lambda function (RecommendationTransformerUri) to perform additional processing of recommendation data.

**Type**: string **Required**: False

#### **Attributes**

A map that defines 1-10 custom endpoint or user attributes, depending on the value for the RecommendationProviderIdType property. Each of these attributes temporarily stores a recommended item that's retrieved from the recommender model and sent to an AWS Lambda function for additional processing. Each attribute can be used as a message variable in a message template.

This value is null if the configuration doesn't invoke an AWS Lambda function (RecommendationTransformerUri) to perform additional processing of recommendation data.

**Type**: object **Required**: False

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

# ${\bf Get Recommender Configurations}$

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- · AWS SDK for Kotlin

See also 981

- AWS SDK for PHP V3
- · AWS SDK for Python
- AWS SDK for Ruby V3

## CreateRecommenderConfiguration

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# Segment

A *segment* designates which users receive messages from a campaign or journey, typically a group of customers that share certain attributes.

You can create a segment by sending a PUT request to the Segment resource. In the body of the request, you specify the dimensions that determine which endpoints belong to the segment. If you use the Segment resource to create a segment, the segment type is DIMENSIONAL, which means that endpoints that belong to the segment vary over time based on user activity. If you want to create a static segment, which includes a fixed set of endpoints, you can send a POST request to the <a href="Import Jobs">Import Jobs</a> resource to import the endpoints that belong to the segment. For more information, see <a href="Import Jobs">Importing Segments</a> in the <a href="Amazon Pinpoint Developer Guide">Amazon Pinpoint Developer Guide</a>.

If you create a new segment that's based on an existing segment (by using a SourceSegments array) and the base segment was imported, the Amazon Pinpoint console displays an inaccurate estimate of the segment size. In this case, the segment size that's displayed on the console equals the size of the imported segment, without any additional filters applied to it.

Segment 982

You can use the Segment resource to create, retrieve information about, update, or delete a segment that's associated with an application.

**Note:** If you delete a segment that's used by an active campaign, the campaign will fail and stop running. Similarly, if you delete a segment that's used by an active journey, the journey might fail and stop running. If the journey does continue to run, any participants who were part of the segment might be removed from the journey prematurely.

## **URI**

/v1/apps/application-id/segments/segment-id

# **HTTP** methods

#### **GET**

## **Operation ID:** GetSegment

Retrieves information about the configuration, dimension, and other settings for a specific segment that's associated with an application.

### Path parameters

Name	Туре	Required	Description
segment-id	String	True	The unique identifier for the segment.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

URI 983

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	SegmentResponse	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	MessageBody	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	MessageBody	The request failed because the specified resource was not found (NotFoundException).
405	MessageBody	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large

Status code	Response model	Description
		(RequestEntityTooLargeExcep tion).
429	MessageBody	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **PUT**

# **Operation ID:** UpdateSegment

Updates the configuration, dimension, and other settings for an existing segment.

# **Path parameters**

Name	Туре	Required	Description
segment-id	String	True	The unique identifier for the segment.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	SegmentResponse	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	MessageBody	The request failed because the specified resource was not found (NotFoundException).
405	MessageBody	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	MessageBody	The request failed because the payload for the body of the request is too large

Status code	Response model	Description
		(RequestEntityTooLargeExcep tion).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **DELETE**

**Operation ID:** DeleteSegment

Deletes a segment from an application.

# Path parameters

Name	Туре	Required	Description
segment-id	String	True	The unique identifier for the segment.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	SegmentResponse	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	MessageBody	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	MessageBody	The request failed because the specified resource was not found (NotFoundException).
405	MessageBody	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	MessageBody	The request failed because the payload for the body of the request is too large

Status code	Response model	Description
		(RequestEntityTooLargeExcep tion).
429	MessageBody	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Segment resource.

# **Path parameters**

Name	Туре	Required	Description
segment-id	String	True	The unique identifier for the segment.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

## **Request bodies**

## **PUT** schema

```
"Name": "string",
"Dimensions": {
  "Demographic": {
    "Channel": {
      "DimensionType": enum,
      "Values": [
        "string"
      ]
    },
    "Platform": {
      "DimensionType": enum,
      "Values": [
        "string"
      ]
    },
    "DeviceType": {
      "DimensionType": enum,
      "Values": [
        "string"
      ]
    },
    "AppVersion": {
      "DimensionType": enum,
      "Values": [
        "string"
      ]
    },
    "<u>Make</u>": {
      "DimensionType": enum,
```

```
"Values": [
        "string"
      ]
    },
    "Model": {
      "DimensionType": enum,
      "Values": [
       "string"
    }
  },
  "Location": {
    "Country": {
      "DimensionType": enum,
      "Values": [
        "string"
      ]
    },
    "GPSPoint": {
      "Coordinates": {
        "Latitude": number,
        "Longitude": number
      },
      "RangeInKilometers": number
    }
  },
  "Behavior": {
    "Recency": {
      ""RecencyType": enum,
      "Duration": enum
    }
  },
  "Attributes": {
  },
  ""Metrics": {
  },
  ""UserAttributes": {
  }
},
"SegmentGroups": {
 "Include": enum,
  "Groups": [
    {
      "Type": enum,
```

```
"Dimensions": [
  {
    "Demographic": {
      "Channel": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      },
      "Platform": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      },
      "DeviceType": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      },
      "AppVersion": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      },
      "Make": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      },
      "<u>Model</u>": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      }
    },
    "Location": {
      "Country": {
        "DimensionType": enum,
        "Values": [
```

```
"string"
                 ]
               },
               "GPSPoint": {
                 "Coordinates": {
                    "<u>Latitude</u>": number,
                    "Longitude": number
                 },
                 "RangeInKilometers": number
               }
             },
             "Behavior": {
               "Recency": {
                 "RecencyType": enum,
                 "Duration": enum
               }
             },
             "Attributes": {
             },
             "Metrics": {
             },
             "<u>UserAttributes</u>": {
             }
           }
        ],
         "SourceType": enum,
         "SourceSegments": [
             "Id": "string",
             "Version": integer
        ]
      }
    ]
  "<u>tags</u>": {
  }
}
```

# **Response bodies**

## SegmentResponse schema

```
{
  "Name": "string",
  "Dimensions": {
    "Demographic": {
      "Channel": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      },
      "Platform": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      },
      "DeviceType": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      },
      "AppVersion": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      },
      "Make": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      },
      "Model": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      }
    },
    "Location": {
```

```
"Country": {
      "DimensionType": enum,
      "Values": [
        "string"
      ]
    },
    "GPSPoint": {
      "Coordinates": {
        "Latitude": number,
        "Longitude": number
      },
      "RangeInKilometers": number
    }
  },
  "Behavior": {
    "Recency": {
      ""RecencyType": enum,
      "Duration": enum
    }
  },
  "Attributes": {
 },
  "Metrics": {
  },
  "UserAttributes": {
  }
},
"SegmentGroups": {
  "Include": enum,
  "Groups": [
    {
      "Type": enum,
      "Dimensions": [
        {
          "Demographic": {
            "Channel": {
              "DimensionType": enum,
              "Values": [
                "string"
              ]
            },
            "Platform": {
              "DimensionType": enum,
              "Values": [
```

```
"string"
   ]
 },
  "DeviceType": {
    "DimensionType": enum,
    "Values": [
      "string"
    ]
 },
  "AppVersion": {
    "DimensionType": enum,
    "Values": [
      "string"
    ]
 },
  "Make": {
    "DimensionType": enum,
    "Values": [
      "string"
    ]
 },
  "Model": {
    "DimensionType": enum,
    "Values": [
      "string"
    ]
 }
},
"Location": {
  "Country": {
    "DimensionType": enum,
    "Values": [
      "string"
    ]
 },
  "GPSPoint": {
    "Coordinates": {
      "Latitude": number,
      "Longitude": number
   },
    "RangeInKilometers": number
 }
},
"Behavior": {
```

```
"Recency": {
                 ""RecencyType": enum,
                 "Duration": enum
              }
            },
            "Attributes": {
            "<u>Metrics</u>": {
            },
            ""UserAttributes": {
          }
        ],
        "SourceType": enum,
        "SourceSegments": [
          {
            "Id": "string",
            "Version": integer
          }
        ]
      }
    ]
  },
  "Id": "string",
  "ApplicationId": "string",
  "CreationDate": "string",
  "LastModifiedDate": "string",
  "Version": integer,
  "SegmentType": enum,
  "ImportDefinition": {
    "Size": integer,
    "S3Url": "string",
    "RoleArn": "string",
    "ExternalId": "string",
    "Format": enum,
    "ChannelCounts": {
    }
  "Arn": "string",
  "tags": {
  }
}
```

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

### **AttributeDimension**

Specifies attribute-based criteria for including or excluding endpoints from a segment.

## AttributeType

The type of segment dimension to use. Valid values are:

- INCLUSIVE endpoints that have attributes matching the values are included in the segment.
- EXCLUSIVE endpoints that have attributes matching the values are excluded from the segment.
- CONTAINS endpoints that have attributes' substrings match the values are included in the segment.
- BEFORE endpoints with attributes read as ISO\_INSTANT datetimes before the value are included in the segment.
- AFTER endpoints with attributes read as ISO\_INSTANT datetimes after the value are included in the segment.
- BETWEEN endpoints with attributes read as ISO\_INSTANT datetimes between the values are included in the segment.
- ON endpoints with attributes read as ISO\_INSTANT dates on the value are included in the segment. Time is ignored in this comparison.

```
Type: string

Required: False

Values: INCLUSIVE | EXCLUSIVE | CONTAINS | BEFORE | AFTER | BETWEEN |

NOT BETWEEN | ON
```

### **Values**

The criteria values to use for the segment dimension. Depending on the value of the AttributeType property, endpoints are included or excluded from the segment if their attribute values match the criteria values.

Type: Array of type string

Required: True

### **GPSCoordinates**

Specifies the GPS coordinates of a location.

### Latitude

The latitude coordinate of the location.

**Type**: number **Required**: True

## Longitude

The longitude coordinate of the location.

**Type**: number **Required**: True

### **GPSPointDimension**

Specifies GPS-based criteria for including or excluding endpoints from a segment.

### **Coordinates**

The GPS coordinates to measure distance from.

**Type**: GPSCoordinates

Required: True

### RangeInKilometers

The range, in kilometers, from the GPS coordinates.

**Type**: number **Required**: False

## MessageBody

Provides information about an API request or response.

## RequestID

The unique identifier for the request or response.

**Type**: string

Required: False

### Message

The message that's returned from the API.

**Type**: string

Required: False

## MetricDimension

Specifies metric-based criteria for including or excluding endpoints from a segment. These criteria derive from custom metrics that you define for endpoints.

# ComparisonOperator

The operator to use when comparing metric values. Valid values are: GREATER\_THAN, LESS\_THAN, GREATER\_THAN\_OR\_EQUAL, LESS\_THAN\_OR\_EQUAL, and EQUAL.

**Type**: string **Required**: True

### Value

The value to compare.

**Type**: number **Required**: True

# RecencyDimension

Specifies criteria for including or excluding endpoints from a segment based on how recently an endpoint was active.

## RecencyType

The type of recency dimension to use for the segment. Valid values are: ACTIVE, endpoints that were active within the specified duration are included in the segment; and, INACTIVE, endpoints that weren't active within the specified duration are included in the segment.

**Type**: string **Required**: True

Values: ACTIVE | INACTIVE

### **Duration**

The duration to use when determining whether an endpoint is active or inactive.

**Type**: string **Required**: True

Values: HR\_24 | DAY\_7 | DAY\_14 | DAY\_30

# **SegmentBehaviors**

Specifies dimension settings for including or excluding endpoints from a segment based on how recently an endpoint was active.

## Recency

The dimension settings that are based on how recently an endpoint was active.

**Type**: RecencyDimension

Required: False

# **SegmentDemographics**

Specifies demographic-based dimension settings for including or excluding endpoints from a segment. These settings derive from characteristics of endpoint devices, such as platform, make, and model.

### Channel

The channel criteria for the segment.

Type: <u>SetDimension</u>
Required: False

### **Platform**

The device platform criteria for the segment.

Type: <u>SetDimension</u>
Required: False

### DeviceType

The device type criteria for the segment.

Type: <u>SetDimension</u>
Required: False

### **AppVersion**

The app version criteria for the segment.

Type: <u>SetDimension</u>
Required: False

### Make

The device make criteria for the segment.

Type: <u>SetDimension</u>
Required: False

### Model

The device model criteria for the segment.

Type: <u>SetDimension</u>
Required: False

# **SegmentDimensions**

Specifies the dimension settings for a segment.

## **Demographic**

The demographic-based criteria, such as device platform, for the segment.

**Type**: SegmentDemographics

Required: False

### Location

The location-based criteria, such as region or GPS coordinates, for the segment.

**Type**: SegmentLocation

Required: False

### **Behavior**

The behavior-based criteria, such as how recently users have used your app, for the segment.

**Type**: SegmentBehaviors

Required: False

### **Attributes**

One or more custom attributes to use as criteria for the segment. For more information see AttributeDimension

**Type**: object **Required**: False

### **Metrics**

One or more custom metrics to use as criteria for the segment.

**Type**: object **Required**: False

### **UserAttributes**

One or more custom user attributes to use as criteria for the segment.

**Type**: object **Required**: False

## SegmentGroup

Specifies the base segments and dimensions for a segment, and the relationships between these base segments and dimensions.

## **Type**

Specifies how to handle multiple dimensions for the segment. For example, if you specify three dimensions for the segment, whether the resulting segment includes endpoints that match all, any, or none of the dimensions.

**Type**: string **Required**: False

Values: ALL | ANY | NONE

### **Dimensions**

An array that defines the dimensions for the segment.

**Type**: Array of type SegmentDimensions

Required: False

## SourceType

Specifies how to handle multiple base segments for the segment. For example, if you specify three base segments for the segment, whether the resulting segment is based on all, any, or none of the base segments.

**Type**: string

Required: False

Values: ALL | ANY | NONE

## SourceSegments

The base segment to build the segment on. A base segment, also referred to as a *source segment*, defines the initial population of endpoints for a segment. When you add dimensions to a segment, Amazon Pinpoint filters the base segment by using the dimensions that you specify.

You can specify more than one dimensional segment or only one imported segment. If you specify an imported segment, the Amazon Pinpoint console displays a segment size estimate that indicates the size of the imported segment without any filters applied to it.

**Type**: Array of type SegmentReference

Required: False

# SegmentGroupList

Specifies the settings that define the relationships between segment groups for a segment.

### Include

Specifies how to handle multiple segment groups for the segment. For example, if the segment includes three segment groups, whether the resulting segment includes endpoints that match all, any, or none of the segment groups.

**Type**: string **Required**: False

Values: ALL | ANY | NONE

### Groups

An array that defines the set of segment criteria to evaluate when handling segment groups for the segment.

**Type**: Array of type SegmentGroup

Required: False

## SegmentImportResource

Provides information about the import job that created a segment. An import job is a job that creates a user segment by importing endpoint definitions.

### Size

The number of endpoint definitions that were imported successfully to create the segment.

**Type**: integer

Required: True

### S3Url

The URL of the Amazon Simple Storage Service (Amazon S3) bucket that the endpoint definitions were imported from to create the segment.

Type: string

Required: True

### RoleArn

The Amazon Resource Name (ARN) of the AWS Identity and Access Management (IAM) role that authorized Amazon Pinpoint to access the Amazon S3 location to import endpoint definitions from.

Type: string

Required: True

### ExternalId

(Deprecated) Your AWS account ID, which you assigned to an external ID key in an IAM trust policy. Amazon Pinpoint previously used this value to assume an IAM role when importing endpoint definitions, but we removed this requirement. We don't recommend use of external IDs for IAM roles that are assumed by Amazon Pinpoint.

**Type**: string **Required**: True

#### **Format**

The format of the files that were imported to create the segment. Valid values are: CSV, for comma-separated values format; and, JSON, for newline-delimited JSON format.

**Type**: string **Required**: True

Values: CSV | JSON

### ChannelCounts

The number of channel types in the endpoint definitions that were imported to create the segment.

**Type**: object **Required**: False

# **SegmentLocation**

Specifies geographical dimension settings for a segment.

## Country

The country or region code, in ISO 3166-1 alpha-2 format, for the segment.

Type: <u>SetDimension</u>

Required: False

### **GPSPoint**

The GPS location and range for the segment.

**Type**: GPSPointDimension

Required: False

# **SegmentReference**

Specifies the segment identifier and version of a segment.

Id

The unique identifier for the segment.

**Type**: string **Required**: True

### Version

The version number of the segment.

**Type**: integer **Required**: False

# SegmentResponse

Provides information about the configuration, dimension, and other settings for a segment.

### Name

The name of the segment.

**Type**: string **Required**: False

### **Dimensions**

The dimension settings for the segment.

**Type:** SegmentDimensions

Required: False

## SegmentGroups

A list of one or more segment groups that apply to the segment. Each segment group consists of zero or more base segments and the dimensions that are applied to those base segments.

Type: SegmentGroupList

Required: False

#### Id

The unique identifier for the segment.

**Type**: string **Required**: True

## **ApplicationId**

The unique identifier for the application that the segment is associated with.

**Type**: string **Required**: True

### CreationDate

The date and time when the segment was created.

**Type**: string **Required**: True

### LastModifiedDate

The date and time when the segment was last modified.

**Type**: string **Required**: False

### Version

The version number of the segment.

**Type**: integer **Required**: False

## SegmentType

The segment type. Valid values are:

- DIMENSIONAL A dynamic segment, which is a segment that uses selection criteria that you specify and is based on endpoint data that's reported by your app. Dynamic segments can change over time.
- IMPORT A static segment, which is a segment that uses selection criteria that you specify and is based on endpoint definitions that you import from a file. Imported segments are static; they don't change over time.

**Type**: string **Required**: True

Values: DIMENSIONAL | IMPORT

### **ImportDefinition**

The settings for the import job that's associated with the segment.

**Type**: SegmentImportResource

Required: False

#### Arn

The Amazon Resource Name (ARN) of the segment.

**Type**: string **Required**: True

### tags

A string-to-string map of key-value pairs that identifies the tags that are associated with the segment. Each tag consists of a required tag key and an associated tag value.

**Type**: object **Required**: False

### **SetDimension**

Specifies the dimension type and values for a segment dimension.

## DimensionType

The type of segment dimension to use. Valid values are: INCLUSIVE, endpoints that match the criteria are included in the segment; and, EXCLUSIVE, endpoints that match the criteria are excluded from the segment.

**Type**: string **Required**: False

Values: INCLUSIVE | EXCLUSIVE

### **Values**

The criteria values to use for the segment dimension. Depending on the value of the DimensionType property, endpoints are included or excluded from the segment if their values match the criteria values.

**Type**: Array of type string

Required: True

# WriteSegmentRequest

Specifies the configuration, dimension, and other settings for a segment. A WriteSegmentRequest object can include a Dimensions object or a SegmentGroups object, but not both.

#### Name

The name of the segment.

**REST API Reference** Amazon Pinpoint



### Note

A segment must have a name otherwise it will not appear in the Amazon Pinpoint console.

Type: string Required: False

### **Dimensions**

The criteria that define the dimensions for the segment. If no values are provided, then all endpoints are included in the segment.

**Type**: SegmentDimensions

Required: False

## SegmentGroups

The segment group to use and the dimensions to apply to the group's base segments in order to build the segment. A segment group can consist of zero or more base segments. Your request can include only one segment group.

**Type**: SegmentGroupList

Required: False

## tags



## Note

As of 22-05-2023 the PUT UpdateSegment tags attribute has been deprecated. After this date any value in the tags attribute is not processed and will not generate an error code. Use the Tags resource to add or modify tags.

(Deprecated) A string-to-string map of key-value pairs that defines the tags to associate with the segment. Each tag consists of a required tag key and an associated tag value.

**Type**: object

### Required: False

# See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

# GetSegment

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- · AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **UpdateSegment**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

See also 1013

## **DeleteSegment**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- · AWS SDK for Python
- AWS SDK for Ruby V3

# **Segment Export Jobs**

The Segment Export Jobs resource represents jobs that export endpoint definitions for a segment. A *segment* designates which users receive messages from a campaign or journey.

You can use this resource to retrieve information about the export jobs for a segment. This includes checking the status of an in-progress export job and accessing the history of your export jobs.

## **URI**

/v1/apps/application-id/segments/segment-id/jobs/export

## **HTTP** methods

### **GET**

**Operation ID:** GetSegmentExportJobs

Retrieves information about the status and settings of the export jobs for a segment.

Segment Export Jobs 1014

# **Path parameters**

Name	Type	Required	Description
segment-id	String	True	The unique identifier for the segment.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.
			unuerstanus.

# **Query parameters**

Name	Туре	Required	Description
page-size	String	False	The maximum number of items to include in each page of a paginated response. This parameter is not supported for application,

Name	Туре	Required	Description
			campaign, and journey metrics.
token	String	False	The NextToken string that specifies which page of results to return in a paginated response.

# Responses

Status code	Response model	Description
200	ExportJobsResponse	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	MessageBody	The request failed because the specified resource was not found (NotFoundException).
405	MessageBody	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	MessageBody	The request failed because the payload for the body of the request is too large

Status code	Response model	Description
		(RequestEntityTooLargeExcep tion).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Segment Export Jobs resource.

# **Path parameters**

Name	Туре	Required	Description
segment-id	String	True	The unique identifier for the segment.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

### Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Response bodies**

### **ExportJobsResponse schema**

```
{
  "Item": [
      "ApplicationId": "string",
      "Id": "string",
      "JobStatus": enum,
      "CompletedPieces": integer,
      "FailedPieces": integer,
      "TotalPieces": integer,
      "CreationDate": "string",
      "CompletionDate": "string",
      "Type": "string",
      "TotalFailures": integer,
      "TotalProcessed": integer,
      "Failures": [
        "string"
      ],
      "Definition": {
        "SegmentId": "string",
        "SegmentVersion": integer,
        "S3UrlPrefix": "string",
        "RoleArn": "string"
      }
    }
  "NextToken": "string"
}
```

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

## **ExportJobResource**

Provides information about the resource settings for a job that exports endpoint definitions to a file. The file can be added directly to an Amazon Simple Storage Service (Amazon S3) bucket by using the Amazon Pinpoint API or downloaded directly to a computer by using the Amazon Pinpoint console.

## SegmentId

The identifier for the segment that the endpoint definitions were exported from. If this value isn't present, Amazon Pinpoint exported definitions for all the endpoints that are associated with the application.

**Type**: string **Required**: False

## **SegmentVersion**

The version of the segment that the endpoint definitions were exported from.

**Type**: integer **Required**: False

### S3UrlPrefix

The URL of the location in an Amazon Simple Storage Service (Amazon S3) bucket where the endpoint definitions were exported to. This location is typically a folder that contains multiple files. The URL should be in the following format: s3://bucket-name/folder-name/.

Type: string

Required: True

### RoleArn

The Amazon Resource Name (ARN) of the AWS Identity and Access Management (IAM) role that authorized Amazon Pinpoint to access the Amazon S3 location where the endpoint definitions were exported to.

**Type**: string **Required**: True

## **ExportJobResponse**

Provides information about the status and settings of a job that exports endpoint definitions to a file. The file can be added directly to an Amazon Simple Storage Service (Amazon S3) bucket by using the Amazon Pinpoint API or downloaded directly to a computer by using the Amazon Pinpoint console.

## **ApplicationId**

The unique identifier for the application that's associated with the export job.

**Type**: string **Required**: True

### Id

The unique identifier for the export job.

**Type**: string **Required**: True

### **JobStatus**

The status of the export job. The job status is FAILED if Amazon Pinpoint wasn't able to process one or more pieces in the job.

**Type**: string **Required**: True

Values: CREATED | PREPARING\_FOR\_INITIALIZATION | INITIALIZING | PROCESSING
| PENDING\_JOB | COMPLETING | COMPLETED | CANCELLING | CANCELLED | FAILING
| FAILED

### **CompletedPieces**

The number of pieces that were processed successfully (completed) by the export job, as of the time of the request.

**Type**: integer **Required**: False

### **FailedPieces**

The number of pieces that weren't processed successfully (failed) by the export job, as of the time of the request.

**Type**: integer **Required**: False

### **TotalPieces**

The total number of pieces that must be processed to complete the export job. Each piece consists of an approximately equal portion of the endpoint definitions that are part of the export job.

**Type**: integer **Required**: False

### CreationDate

The date, in ISO 8601 format, when the export job was created.

**Type**: string **Required**: True

### **CompletionDate**

The date, in ISO 8601 format, when the export job was completed.

**Type**: string **Required**: False

## **Type**

The job type. This value is EXPORT for export jobs.

**Type**: string **Required**: True

### **TotalFailures**

The total number of endpoint definitions that weren't processed successfully (failed) by the export job, typically because an error, such as a syntax error, occurred.

**Type**: integer **Required**: False

### **TotalProcessed**

The total number of endpoint definitions that were processed by the export job.

**Type**: integer **Required**: False

### **Failures**

An array of entries, one for each of the first 100 entries that weren't processed successfully (failed) by the export job, if any.

Type: Array of type string

Required: False

### **Definition**

The resource settings that apply to the export job.

**Type**: ExportJobResource

Required: True

# **ExportJobsResponse**

Provides information about all the export jobs that are associated with an application or segment. An export job is a job that exports endpoint definitions to a file.

#### Item

An array of responses, one for each export job that's associated with the application (Export Jobs resource) or segment (Segment Export Jobs resource).

**Type**: Array of type ExportJobResponse

Required: True

### NextToken

The string to use in a subsequent request to get the next page of results in a paginated response. This value is null if there are no additional pages.

**Type**: string **Required**: False

# MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

### Message

The message that's returned from the API.

**Type**: string **Required**: False

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

# GetSegmentExportJobs

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Segment Import Jobs**

The Segment Import Jobs resource represents jobs that create user segments by importing endpoint definitions. A *segment* designates which users receive messages from a campaign or journey.

You can use this resource to retrieve information about the import jobs for a segment. This includes checking the status of an in-progress import job and accessing the history of your import jobs.

### **URI**

/v1/apps/application-id/segments/segment-id/jobs/import

## **HTTP** methods

### **GET**

Operation ID: GetSegmentImportJobs

See also 1024

Retrieves information about the status and settings of the import jobs for a segment.

# **Path parameters**

Name	Type	Required	Description
segment-id	String	True	The unique identifier for the segment.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# **Query parameters**

Name	Type	Required	Description
page-size	String	False	The maximum number of items to include in each page of a paginated response. This parameter is not supported

Name	Туре	Required	Description
			for application, campaign, and journey metrics.
token	String	False	The NextToken string that specifies which page of results to return in a paginated response.

# Responses

Status code	Response model	Description
200	ImportJobsResponse	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	MessageBody	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	MessageBody	The request failed because the payload for the body

Status code	Response model	Description
		of the request is too large (RequestEntityTooLargeExcep tion).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Segment Import Jobs resource.

# **Path parameters**

Name	Туре	Required	Description
segment-id	String	True	The unique identifier for the segment.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

### Responses

Status code	Response model	Description
200	None	The request succeeded.

## **Schemas**

# **Response bodies**

### ImportJobsResponse schema

```
{
  "!! Item
    {
      "ApplicationId": "string",
      "Id": "string",
      "JobStatus": enum,
      "CompletedPieces": integer,
      "FailedPieces": integer,
      "TotalPieces": integer,
      "CreationDate": "string",
      "CompletionDate": "string",
      "Type": "string",
      "TotalFailures": integer,
      "TotalProcessed": integer,
      "Failures": [
        "string"
      ],
      "Definition": {
        "S3Url": "string",
        "RoleArn": "string",
        "ExternalId": "string",
        "Format": enum,
        "RegisterEndpoints": boolean,
        "DefineSegment": boolean,
        "SegmentName": "string",
        "SegmentId": "string"
      }
    }
  ],
  "NextToken": "string"
```

}

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

## **ImportJobResource**

Provides information about the resource settings for a job that imports endpoint definitions from one or more files. The files can be stored in an Amazon Simple Storage Service (Amazon S3) bucket or uploaded directly from a computer by using the Amazon Pinpoint console.

### S3Url

The URL of the Amazon Simple Storage Service (Amazon S3) bucket that contains the endpoint definitions to import. This location can be a folder or a single file. If the location is a folder, Amazon Pinpoint imports endpoint definitions from the files in this location, including any subfolders that the folder contains.

The URL should be in the following format: s3://bucket-name/folder-name/file-name.

The location can end with the key for an individual object or a prefix that qualifies multiple objects.

**Type**: string **Required**: True

#### RoleArn

The Amazon Resource Name (ARN) of the AWS Identity and Access Management (IAM) role that authorizes Amazon Pinpoint to access the Amazon S3 location to import endpoint definitions from.

**Type**: string **Required**: True

### ExternalId

(Deprecated) Your AWS account ID, which you assigned to an external ID key in an IAM trust policy. Amazon Pinpoint previously used this value to assume an IAM role when importing endpoint definitions, but we removed this requirement. We don't recommend use of external IDs for IAM roles that are assumed by Amazon Pinpoint.

**Type**: string

Required: False

### **Format**

The format of the files that contain the endpoint definitions to import. Valid values are: CSV, for comma-separated values format; and, JSON, for newline-delimited JSON format.

If the files are stored in an Amazon S3 location and that location contains multiple files that use different formats, Amazon Pinpoint imports data only from the files that use the specified format.

**Type**: string **Required**: True

Values: CSV | JSON

### RegisterEndpoints

Specifies whether the import job registers the endpoints with Amazon Pinpoint, when the endpoint definitions are imported.

**Type**: boolean **Required**: False

## **DefineSegment**

Specifies whether the import job creates a segment that contains the endpoints, when the endpoint definitions are imported.

**Type**: boolean **Required**: False

**REST API Reference** Amazon Pinpoint

### SegmentName

The custom name for the segment that's created by the import job, if the value of the DefineSegment property is true.



### Note

A segment must have a name otherwise it will not appear in the Amazon Pinpoint console.

Type: string Required: False

## SegmentId

The identifier for the segment that the import job updates or adds endpoint definitions to, if the import job updates an existing segment.

Type: string Required: False

# **ImportJobResponse**

Provides information about the status and settings of a job that imports endpoint definitions from one or more files. The files can be stored in an Amazon Simple Storage Service (Amazon S3) bucket or uploaded directly from a computer by using the Amazon Pinpoint console.

# **ApplicationId**

The unique identifier for the application that's associated with the import job.

Type: string Required: True

#### Id

The unique identifier for the import job.

**Type**: string **Required**: True

#### **JobStatus**

The status of the import job. The job status is FAILED if Amazon Pinpoint wasn't able to process one or more pieces in the job.

**Type**: string **Required**: True

Values: CREATED | PREPARING\_FOR\_INITIALIZATION | INITIALIZING | PROCESSING | PENDING\_JOB | COMPLETING | COMPLETED | CANCELLING | CANCELLED | FAILING

| FAILED

### CompletedPieces

The number of pieces that were processed successfully (completed) by the import job, as of the time of the request.

**Type**: integer **Required**: False

### **FailedPieces**

The number of pieces that weren't processed successfully (failed) by the import job, as of the time of the request.

**Type**: integer **Required**: False

#### **TotalPieces**

The total number of pieces that must be processed to complete the import job. Each piece consists of an approximately equal portion of the endpoint definitions that are part of the import job.

**Type**: integer **Required**: False

### CreationDate

The date, in ISO 8601 format, when the import job was created.

**Type**: string **Required**: True

### **CompletionDate**

The date, in ISO 8601 format, when the import job was completed.

**Type**: string **Required**: False

### **Type**

The job type. This value is IMPORT for import jobs.

**Type**: string **Required**: True

### **TotalFailures**

The total number of endpoint definitions that weren't processed successfully (failed) by the import job, typically because an error, such as a syntax error, occurred.

**Type**: integer **Required**: False

#### **TotalProcessed**

The total number of endpoint definitions that were processed by the import job.

**Type**: integer **Required**: False

#### **Failures**

An array of entries, one for each of the first 100 entries that weren't processed successfully (failed) by the import job, if any.

Type: Array of type string

Required: False

#### **Definition**

The resource settings that apply to the import job.

Type: ImportJobResource

Required: True

# **ImportJobsResponse**

Provides information about the status and settings of all the import jobs that are associated with an application or segment. An import job is a job that imports endpoint definitions from one or more files.

#### Item

An array of responses, one for each import job that's associated with the application (Import Jobs resource) or segment (Segment Import Jobs resource).

**Type**: Array of type ImportJobResponse

**Required**: True

### NextToken

The string to use in a subsequent request to get the next page of results in a paginated response. This value is null if there are no additional pages.

**Type**: string **Required**: False

# MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

#### Message

The message that's returned from the API.

**Type**: string **Required**: False

# See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

# GetSegmentImportJobs

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- · AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Segment Version**

A *segment* designates which users receive messages from a campaign or journey. The Segment Version resource provides information about a specific version of a segment, such as the dimension settings and criteria values that were used by that version of the segment.

You can use this resource to retrieve information about a specific version of a segment.

### **URI**

/v1/apps/application-id/segments/segment-id/versions/version

See also 1035

# **HTTP** methods

### **GET**

# **Operation ID:** GetSegmentVersion

Retrieves information about the configuration, dimension, and other settings for a specific version of a segment that's associated with an application.

# **Path parameters**

Name	Туре	Required	Description
segment-id	String	True	The unique identifier for the segment.
version	String	True	The unique version number (Version property) for the campaign version.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	SegmentResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error,

Status code	Response model	Description
		exception, or failure (Internal
		ServerErrorException).

# **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Segment Version resource.

# **Path parameters**

Name	Туре	Required	Description
segment-id	String	True	The unique identifier for the segment.
version	String	True	The unique version number (Version property) for the campaign version.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Response bodies**

## SegmentResponse schema

```
{
  "Name": "string",
  "Dimensions": {
    "Demographic": {
      "Channel": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      },
      "Platform": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      },
      "DeviceType": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      },
      "AppVersion": {
        "<u>DimensionType</u>": enum,
        "Values": [
          "string"
        ]
      },
      "Make": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      },
      "Model": {
        "DimensionType": enum,
        "Values": [
```

```
"string"
      ]
    }
  },
  "Location": {
    "Country": {
      "DimensionType": enum,
      ""Values": [
        "string"
      ]
    },
    "GPSPoint": {
      "Coordinates": {
        "Latitu<u>de</u>": number,
        "Longitude": number
      },
      "RangeInKilometers": number
    }
  },
  "Behavior": {
    "Recency": {
      "RecencyType": enum,
      "Duration": enum
    }
  },
  "Attributes": {
  },
  "Me<u>trics</u>": {
  },
  "UserAttributes": {
  }
},
"SegmentGroups": {
  "Include": enum,
  "Groups": [
    {
      "Type": enum,
      "Dimensions": [
        {
          "Demographic": {
             "Channel": {
               "DimensionType": enum,
               "Values": [
                 "string"
```

```
]
  },
  "Platform": {
    "DimensionType": enum,
    "Values": [
      "string"
    ]
  },
  "DeviceType": {
    "DimensionType": enum,
    "Values": [
      "string"
    ]
  },
  "AppVersion": {
    "DimensionType": enum,
    "Values": [
      "string"
    ]
  },
  "Make": {
    "<u>DimensionType</u>": enum,
    "Values": [
      "string"
    ]
  },
  "<u>Model</u>": {
    "DimensionType": enum,
    "Values": [
      "string"
    ]
  }
},
"Location": {
  "Country": {
    "DimensionType": enum,
    "Values": [
      "string"
    ]
  },
  "GPSPoint": {
    "Coordinates": {
      "Latitude": number,
      "Longitude": number
```

```
},
              "RangeInKilometers": number
            }
          },
          "Behavior": {
            "Recency": {
              "RecencyType": enum,
              "Duration": enum
            }
          },
          "Attributes": {
          },
          "Me<u>trics</u>": {
          },
          ""UserAttributes": {
          }
        }
      ],
      "SourceType": enum,
      "SourceSegments": [
          "Id": "string",
          "Version": integer
      ]
    }
  ]
},
"Id": "string",
"ApplicationId": "string",
"CreationDate": "string",
"LastModifiedDate": "string",
"Version": integer,
"SegmentType": enum,
"ImportDefinition": {
  "Size": integer,
  "S3Url": "string",
  "RoleArn": "string",
  "ExternalId": "string",
  "Format": enum,
  "ChannelCounts": {
  }
},
"Arn": "string",
```

```
"<u>tags</u>": {
}
}
```

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

### **AttributeDimension**

Specifies attribute-based criteria for including or excluding endpoints from a segment.

### **AttributeType**

The type of segment dimension to use. Valid values are:

- INCLUSIVE endpoints that have attributes matching the values are included in the segment.
- EXCLUSIVE endpoints that have attributes matching the values are excluded from the segment.
- CONTAINS endpoints that have attributes' substrings match the values are included in the segment.
- BEFORE endpoints with attributes read as ISO\_INSTANT datetimes before the value are included in the segment.
- AFTER endpoints with attributes read as ISO\_INSTANT datetimes after the value are included in the segment.
- BETWEEN endpoints with attributes read as ISO\_INSTANT datetimes between the values are included in the segment.
- 0N endpoints with attributes read as ISO\_INSTANT dates on the value are included in the segment. Time is ignored in this comparison.

**Type**: string **Required**: False

Values: INCLUSIVE | EXCLUSIVE | CONTAINS | BEFORE | AFTER | BETWEEN |

NOT\_BETWEEN | ON

### **Values**

The criteria values to use for the segment dimension. Depending on the value of the AttributeType property, endpoints are included or excluded from the segment if their attribute values match the criteria values.

**Type**: Array of type string

**Required**: True

### **GPSCoordinates**

Specifies the GPS coordinates of a location.

#### Latitude

The latitude coordinate of the location.

**Type**: number **Required**: True

### Longitude

The longitude coordinate of the location.

**Type**: number **Required**: True

### **GPSPointDimension**

Specifies GPS-based criteria for including or excluding endpoints from a segment.

#### **Coordinates**

The GPS coordinates to measure distance from.

**Type:** GPSCoordinates

Required: True

### RangeInKilometers

The range, in kilometers, from the GPS coordinates.

**Type**: number **Required**: False

# MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

### Message

The message that's returned from the API.

**Type**: string **Required**: False

### MetricDimension

Specifies metric-based criteria for including or excluding endpoints from a segment. These criteria derive from custom metrics that you define for endpoints.

## ComparisonOperator

The operator to use when comparing metric values. Valid values are: GREATER\_THAN, LESS\_THAN, GREATER\_THAN\_OR\_EQUAL, LESS\_THAN\_OR\_EQUAL.

**Type**: string **Required**: True

#### Value

The value to compare.

**Type**: number **Required**: True

# RecencyDimension

Specifies criteria for including or excluding endpoints from a segment based on how recently an endpoint was active.

### RecencyType

The type of recency dimension to use for the segment. Valid values are: ACTIVE, endpoints that were active within the specified duration are included in the segment; and, INACTIVE, endpoints that weren't active within the specified duration are included in the segment.

**Type**: string **Required**: True

Values: ACTIVE | INACTIVE

#### **Duration**

The duration to use when determining whether an endpoint is active or inactive.

**Type**: string **Required**: True

Values: HR\_24 | DAY\_7 | DAY\_14 | DAY\_30

# **SegmentBehaviors**

Specifies dimension settings for including or excluding endpoints from a segment based on how recently an endpoint was active.

### Recency

The dimension settings that are based on how recently an endpoint was active.

**Type**: RecencyDimension

Required: False

# **SegmentDemographics**

Specifies demographic-based dimension settings for including or excluding endpoints from a segment. These settings derive from characteristics of endpoint devices, such as platform, make, and model.

### Channel

The channel criteria for the segment.

Type: <u>SetDimension</u>
Required: False

### **Platform**

The device platform criteria for the segment.

Type: <u>SetDimension</u>
Required: False

### DeviceType

The device type criteria for the segment.

Type: <u>SetDimension</u>
Required: False

## **AppVersion**

The app version criteria for the segment.

Type: <u>SetDimension</u>
Required: False

#### Make

The device make criteria for the segment.

Type: <u>SetDimension</u>
Required: False

#### Model

The device model criteria for the segment.

Type: <u>SetDimension</u>
Required: False

# **SegmentDimensions**

Specifies the dimension settings for a segment.

## **Demographic**

The demographic-based criteria, such as device platform, for the segment.

**Type**: SegmentDemographics

Required: False

#### Location

The location-based criteria, such as region or GPS coordinates, for the segment.

**Type**: SegmentLocation

Required: False

### **Behavior**

The behavior-based criteria, such as how recently users have used your app, for the segment.

**Type**: SegmentBehaviors

Required: False

### **Attributes**

One or more custom attributes to use as criteria for the segment. For more information see AttributeDimension

**Type**: object **Required**: False

#### **Metrics**

One or more custom metrics to use as criteria for the segment.

**Type**: object **Required**: False

#### **UserAttributes**

One or more custom user attributes to use as criteria for the segment.

**Type**: object **Required**: False

# SegmentGroup

Specifies the base segments and dimensions for a segment, and the relationships between these base segments and dimensions.

## Type

Specifies how to handle multiple dimensions for the segment. For example, if you specify three dimensions for the segment, whether the resulting segment includes endpoints that match all, any, or none of the dimensions.

**Type**: string **Required**: False

Values: ALL | ANY | NONE

### **Dimensions**

An array that defines the dimensions for the segment.

**Type**: Array of type SegmentDimensions

Required: False

### SourceType

Specifies how to handle multiple base segments for the segment. For example, if you specify three base segments for the segment, whether the resulting segment is based on all, any, or none of the base segments.

**Type**: string

Required: False

Values: ALL | ANY | NONE

## SourceSegments

The base segment to build the segment on. A base segment, also referred to as a *source segment*, defines the initial population of endpoints for a segment. When you add dimensions to a segment, Amazon Pinpoint filters the base segment by using the dimensions that you specify.

You can specify more than one dimensional segment or only one imported segment. If you specify an imported segment, the Amazon Pinpoint console displays a segment size estimate that indicates the size of the imported segment without any filters applied to it.

**Type**: Array of type <u>SegmentReference</u>

Required: False

# SegmentGroupList

Specifies the settings that define the relationships between segment groups for a segment.

#### Include

Specifies how to handle multiple segment groups for the segment. For example, if the segment includes three segment groups, whether the resulting segment includes endpoints that match all, any, or none of the segment groups.

**Type**: string **Required**: False

Values: ALL | ANY | NONE

### Groups

An array that defines the set of segment criteria to evaluate when handling segment groups for the segment.

**Type**: Array of type SegmentGroup

Required: False

# SegmentImportResource

Provides information about the import job that created a segment. An import job is a job that creates a user segment by importing endpoint definitions.

### Size

The number of endpoint definitions that were imported successfully to create the segment.

**Type**: integer

**Required**: True

### S3Url

The URL of the Amazon Simple Storage Service (Amazon S3) bucket that the endpoint definitions were imported from to create the segment.

Type: string

**Required**: True

#### RoleArn

The Amazon Resource Name (ARN) of the AWS Identity and Access Management (IAM) role that authorized Amazon Pinpoint to access the Amazon S3 location to import endpoint definitions from.

Type: string

**Required**: True

#### ExternalId

(Deprecated) Your AWS account ID, which you assigned to an external ID key in an IAM trust policy. Amazon Pinpoint previously used this value to assume an IAM role when importing endpoint definitions, but we removed this requirement. We don't recommend use of external IDs for IAM roles that are assumed by Amazon Pinpoint.

**Type**: string **Required**: True

#### **Format**

The format of the files that were imported to create the segment. Valid values are: CSV, for comma-separated values format; and, JSON, for newline-delimited JSON format.

**Type**: string **Required**: True

Values: CSV | JSON

#### ChannelCounts

The number of channel types in the endpoint definitions that were imported to create the segment.

**Type**: object **Required**: False

# **SegmentLocation**

Specifies geographical dimension settings for a segment.

### Country

The country or region code, in ISO 3166-1 alpha-2 format, for the segment.

Type: <u>SetDimension</u>

Required: False

### **GPSPoint**

The GPS location and range for the segment.

Type: GPSPointDimension

Required: False

# SegmentReference

Specifies the segment identifier and version of a segment.

Id

The unique identifier for the segment.

**Type**: string **Required**: True

### Version

The version number of the segment.

**Type**: integer **Required**: False

# SegmentResponse

Provides information about the configuration, dimension, and other settings for a segment.

#### Name

The name of the segment.

**Type**: string **Required**: False

### **Dimensions**

The dimension settings for the segment.

**Type**: SegmentDimensions

Required: False

## SegmentGroups

A list of one or more segment groups that apply to the segment. Each segment group consists of zero or more base segments and the dimensions that are applied to those base segments.

**Type**: SegmentGroupList

Required: False

#### Id

The unique identifier for the segment.

**Type**: string **Required**: True

## **ApplicationId**

The unique identifier for the application that the segment is associated with.

**Type**: string **Required**: True

### CreationDate

The date and time when the segment was created.

**Type**: string **Required**: True

### LastModifiedDate

The date and time when the segment was last modified.

**Type**: string **Required**: False

#### Version

The version number of the segment.

**Type**: integer **Required**: False

### SegmentType

The segment type. Valid values are:

- DIMENSIONAL A dynamic segment, which is a segment that uses selection criteria that you specify and is based on endpoint data that's reported by your app. Dynamic segments can change over time.
- IMPORT A static segment, which is a segment that uses selection criteria that you specify and is based on endpoint definitions that you import from a file. Imported segments are static; they don't change over time.

**Type**: string **Required**: True

Values: DIMENSIONAL | IMPORT

### **ImportDefinition**

The settings for the import job that's associated with the segment.

**Type**: SegmentImportResource

Required: False

#### Arn

The Amazon Resource Name (ARN) of the segment.

**Type**: string **Required**: True

#### tags

A string-to-string map of key-value pairs that identifies the tags that are associated with the segment. Each tag consists of a required tag key and an associated tag value.

**Type**: object **Required**: False

## **SetDimension**

Specifies the dimension type and values for a segment dimension.

### DimensionType

The type of segment dimension to use. Valid values are: INCLUSIVE, endpoints that match the criteria are included in the segment; and, EXCLUSIVE, endpoints that match the criteria are excluded from the segment.

**Type**: string **Required**: False

Values: INCLUSIVE | EXCLUSIVE

### **Values**

The criteria values to use for the segment dimension. Depending on the value of the DimensionType property, endpoints are included or excluded from the segment if their values match the criteria values.

**Type**: Array of type string

Required: True

# See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

# GetSegmentVersion

• AWS Command Line Interface

See also 1056

- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Segment Versions**

A *segment* designates which users receive messages from a campaign or journey. The Segment Versions resource provides information about versions of a specific segment, such as the dimension settings and criteria values that were used by each version of the segment.

You can use this resource to retrieve information about versions of a segment.

## **URI**

/v1/apps/application-id/segments/segment-id/versions

# **HTTP** methods

#### **GET**

**Operation ID:** GetSegmentVersions

Retrieves information about the configuration, dimension, and other settings for all the versions of a specific segment that's associated with an application.

# **Path parameters**

Name	Туре	Required	Description
segment-id	String	True	The unique identifier for the segment.

Segment Versions 1057

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# **Query parameters**

Name	Туре	Required	Description
page-size	String	False	The maximum number of items to include in each page of a paginated response. This parameter is not supported for application, campaign, and journey metrics.
token	String	False	The NextToken string that specifies

Name	Туре	Required	Description
			which page of results to return in a
			paginated response.

# Responses

Status code	Response model	Description
200	SegmentsResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	MessageBody	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent

Status code	Response model	Description
		during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Segment Versions resource.

# **Path parameters**

Name	Туре	Required	Description
segment-id	String	True	The unique identifier for the segment.
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Response bodies**

## SegmentsResponse schema

```
{
  "<u>Item</u>": [
    {
      "Name": "string",
      "Dimensions": {
        "Demographic": {
          "Channel": {
            "DimensionType": enum,
            "Values": [
              "string"
            ]
          },
          "Platform": {
            "DimensionType": enum,
             "Values": [
              "string"
            ]
          },
          "DeviceType": {
            "DimensionType": enum,
            "Values": [
              "string"
            ]
          },
          "AppVersion": {
            "DimensionType": enum,
            "Values": [
              "string"
            ]
          },
          "Make": {
            "DimensionType": enum,
            "Values": [
              "string"
            ]
          },
          "Model": {
```

```
"DimensionType": enum,
      "Values": [
        "string"
      ]
    }
  },
  "Location": {
    "Country": {
      "DimensionType": enum,
      "Values": [
        "string"
      ]
    },
    "GPSPoint": {
      "Coordinates": {
        "<u>Latitude</u>": number,
        "Longitude": number
      },
      "RangeInKilometers": number
    }
  },
  "Behavior": {
    "Recency": {
      "RecencyType": enum,
      "Duration": enum
    }
  },
  "Attributes": {
  },
  "Metrics": {
  "UserAttributes": {
  }
},
"SegmentGroups": {
  "Include": enum,
  "Groups": [
    {
      "Type": enum,
      "Dimensions": [
          "Demographic": {
            "Channel": {
               "DimensionType": enum,
```

```
"Values": [
      "string"
    ]
 },
  "Platform": {
    "DimensionType": enum,
    "Values": [
     "string"
    ]
 },
  "DeviceType": {
    "DimensionType": enum,
    "Values": [
     "string"
    ]
 },
  "AppVersion": {
    "DimensionType": enum,
    "Values": [
      "string"
    ]
 },
  "Make": {
    "DimensionType": enum,
    "Values": [
      "string"
    ]
  },
  "Model": {
    "DimensionType": enum,
    "Values": [
      "string"
    ]
 }
},
"Location": {
  "Country": {
    "DimensionType": enum,
    "Values": [
     "string"
    ]
  },
  "GPSPoint": {
    "Coordinates": {
```

```
"Latitude": number,
                "Longitude": number
              },
              "RangeInKilometers": number
            }
          },
          "Behavior": {
            "Recency": {
              "RecencyType": enum,
              "Duration": enum
            }
          },
          "Attributes": {
          },
          "Metrics": {
          },
          "UserAttributes": {
        }
      ],
      "SourceType": enum,
      "SourceSegments": [
        {
          "Id": "string",
          "Version": integer
        }
      ]
    }
 ]
},
"Id": "string",
"ApplicationId": "string",
"CreationDate": "string",
"LastModifiedDate": "string",
"Version": integer,
"SegmentType": enum,
"ImportDefinition": {
  "Size": integer,
  "S3Url": "string",
  "RoleArn": "string",
  "ExternalId": "string",
  "Format": enum,
  "ChannelCounts": {
  }
```

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

## **AttributeDimension**

Specifies attribute-based criteria for including or excluding endpoints from a segment.

## **AttributeType**

The type of segment dimension to use. Valid values are:

- INCLUSIVE endpoints that have attributes matching the values are included in the segment.
- EXCLUSIVE endpoints that have attributes matching the values are excluded from the segment.
- CONTAINS endpoints that have attributes' substrings match the values are included in the segment.
- BEFORE endpoints with attributes read as ISO\_INSTANT datetimes before the value are included in the segment.
- AFTER endpoints with attributes read as ISO\_INSTANT datetimes after the value are included in the segment.
- BETWEEN endpoints with attributes read as ISO\_INSTANT datetimes between the values are included in the segment.
- 0N endpoints with attributes read as ISO\_INSTANT dates on the value are included in the segment. Time is ignored in this comparison.

**Type**: string **Required**: False

Values: INCLUSIVE | EXCLUSIVE | CONTAINS | BEFORE | AFTER | BETWEEN |

NOT\_BETWEEN | ON

### **Values**

The criteria values to use for the segment dimension. Depending on the value of the AttributeType property, endpoints are included or excluded from the segment if their attribute values match the criteria values.

**Type**: Array of type string

Required: True

## **GPSCoordinates**

Specifies the GPS coordinates of a location.

### Latitude

The latitude coordinate of the location.

**Type**: number **Required**: True

### Longitude

The longitude coordinate of the location.

**Type**: number **Required**: True

### **GPSPointDimension**

Specifies GPS-based criteria for including or excluding endpoints from a segment.

### **Coordinates**

The GPS coordinates to measure distance from.

**Type**: GPSCoordinates

Required: True

## RangeInKilometers

The range, in kilometers, from the GPS coordinates.

**Type**: number **Required**: False

## MessageBody

Provides information about an API request or response.

## RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

## Message

The message that's returned from the API.

**Type**: string **Required**: False

### MetricDimension

Specifies metric-based criteria for including or excluding endpoints from a segment. These criteria derive from custom metrics that you define for endpoints.

## ComparisonOperator

The operator to use when comparing metric values. Valid values are: GREATER\_THAN, LESS\_THAN, GREATER\_THAN\_OR\_EQUAL, LESS\_THAN\_OR\_EQUAL.

**Type**: string **Required**: True

### Value

The value to compare.

**Type**: number **Required**: True

# RecencyDimension

Specifies criteria for including or excluding endpoints from a segment based on how recently an endpoint was active.

## RecencyType

The type of recency dimension to use for the segment. Valid values are: ACTIVE, endpoints that were active within the specified duration are included in the segment; and, INACTIVE, endpoints that weren't active within the specified duration are included in the segment.

**Type**: string **Required**: True

Values: ACTIVE | INACTIVE

### **Duration**

The duration to use when determining whether an endpoint is active or inactive.

**Type**: string **Required**: True

Values: HR\_24 | DAY\_7 | DAY\_14 | DAY\_30

# **SegmentBehaviors**

Specifies dimension settings for including or excluding endpoints from a segment based on how recently an endpoint was active.

## Recency

The dimension settings that are based on how recently an endpoint was active.

**Type**: RecencyDimension

Required: False

# **SegmentDemographics**

Specifies demographic-based dimension settings for including or excluding endpoints from a segment. These settings derive from characteristics of endpoint devices, such as platform, make, and model.

### Channel

The channel criteria for the segment.

Type: <u>SetDimension</u>
Required: False

### **Platform**

The device platform criteria for the segment.

Type: <u>SetDimension</u>
Required: False

### DeviceType

The device type criteria for the segment.

Type: <u>SetDimension</u>
Required: False

### **AppVersion**

The app version criteria for the segment.

Type: <u>SetDimension</u>
Required: False

### Make

The device make criteria for the segment.

Type: <u>SetDimension</u>
Required: False

### Model

The device model criteria for the segment.

Type: <u>SetDimension</u>
Required: False

# **SegmentDimensions**

Specifies the dimension settings for a segment.

## **Demographic**

The demographic-based criteria, such as device platform, for the segment.

**Type**: SegmentDemographics

Required: False

### Location

The location-based criteria, such as region or GPS coordinates, for the segment.

**Type**: SegmentLocation

Required: False

### **Behavior**

The behavior-based criteria, such as how recently users have used your app, for the segment.

**Type**: SegmentBehaviors

Required: False

### **Attributes**

One or more custom attributes to use as criteria for the segment. For more information see AttributeDimension

**Type**: object **Required**: False

### **Metrics**

One or more custom metrics to use as criteria for the segment.

**Type**: object **Required**: False

### **UserAttributes**

One or more custom user attributes to use as criteria for the segment.

**Type**: object **Required**: False

## SegmentGroup

Specifies the base segments and dimensions for a segment, and the relationships between these base segments and dimensions.

## **Type**

Specifies how to handle multiple dimensions for the segment. For example, if you specify three dimensions for the segment, whether the resulting segment includes endpoints that match all, any, or none of the dimensions.

**Type**: string **Required**: False

Values: ALL | ANY | NONE

### **Dimensions**

An array that defines the dimensions for the segment.

**Type**: Array of type SegmentDimensions

Required: False

## SourceType

Specifies how to handle multiple base segments for the segment. For example, if you specify three base segments for the segment, whether the resulting segment is based on all, any, or none of the base segments.

**Type**: string

Required: False

Values: ALL | ANY | NONE

## SourceSegments

The base segment to build the segment on. A base segment, also referred to as a *source segment*, defines the initial population of endpoints for a segment. When you add dimensions to a segment, Amazon Pinpoint filters the base segment by using the dimensions that you specify.

You can specify more than one dimensional segment or only one imported segment. If you specify an imported segment, the Amazon Pinpoint console displays a segment size estimate that indicates the size of the imported segment without any filters applied to it.

**Type**: Array of type SegmentReference

Required: False

# SegmentGroupList

Specifies the settings that define the relationships between segment groups for a segment.

### Include

Specifies how to handle multiple segment groups for the segment. For example, if the segment includes three segment groups, whether the resulting segment includes endpoints that match all, any, or none of the segment groups.

**Type**: string **Required**: False

Values: ALL | ANY | NONE

### Groups

An array that defines the set of segment criteria to evaluate when handling segment groups for the segment.

**Type**: Array of type SegmentGroup

Required: False

## SegmentImportResource

Provides information about the import job that created a segment. An import job is a job that creates a user segment by importing endpoint definitions.

### Size

The number of endpoint definitions that were imported successfully to create the segment.

**Type**: integer

Required: True

### S3Url

The URL of the Amazon Simple Storage Service (Amazon S3) bucket that the endpoint definitions were imported from to create the segment.

Type: string

**Required**: True

### RoleArn

The Amazon Resource Name (ARN) of the AWS Identity and Access Management (IAM) role that authorized Amazon Pinpoint to access the Amazon S3 location to import endpoint definitions from.

Type: string

**Required**: True

### ExternalId

(Deprecated) Your AWS account ID, which you assigned to an external ID key in an IAM trust policy. Amazon Pinpoint previously used this value to assume an IAM role when importing endpoint definitions, but we removed this requirement. We don't recommend use of external IDs for IAM roles that are assumed by Amazon Pinpoint.

**Type**: string **Required**: True

#### **Format**

The format of the files that were imported to create the segment. Valid values are: CSV, for comma-separated values format; and, JSON, for newline-delimited JSON format.

**Type**: string **Required**: True

Values: CSV | JSON

### ChannelCounts

The number of channel types in the endpoint definitions that were imported to create the segment.

**Type**: object **Required**: False

# **SegmentLocation**

Specifies geographical dimension settings for a segment.

## Country

The country or region code, in ISO 3166-1 alpha-2 format, for the segment.

Type: <u>SetDimension</u>

Required: False

### **GPSPoint**

The GPS location and range for the segment.

Type: GPSPointDimension

Required: False

# SegmentReference

Specifies the segment identifier and version of a segment.

Id

The unique identifier for the segment.

**Type**: string **Required**: True

### Version

The version number of the segment.

**Type**: integer **Required**: False

# SegmentResponse

Provides information about the configuration, dimension, and other settings for a segment.

### Name

The name of the segment.

**Type**: string **Required**: False

### **Dimensions**

The dimension settings for the segment.

**Type**: SegmentDimensions

Required: False

## SegmentGroups

A list of one or more segment groups that apply to the segment. Each segment group consists of zero or more base segments and the dimensions that are applied to those base segments.

Type: SegmentGroupList

Required: False

#### Id

The unique identifier for the segment.

**Type**: string **Required**: True

## **ApplicationId**

The unique identifier for the application that the segment is associated with.

**Type**: string **Required**: True

### CreationDate

The date and time when the segment was created.

**Type**: string **Required**: True

### LastModifiedDate

The date and time when the segment was last modified.

**Type**: string **Required**: False

### Version

The version number of the segment.

**Type**: integer **Required**: False

## SegmentType

The segment type. Valid values are:

- DIMENSIONAL A dynamic segment, which is a segment that uses selection criteria that you specify and is based on endpoint data that's reported by your app. Dynamic segments can change over time.
- IMPORT A static segment, which is a segment that uses selection criteria that you specify and is based on endpoint definitions that you import from a file. Imported segments are static; they don't change over time.

**Type**: string **Required**: True

Values: DIMENSIONAL | IMPORT

### **ImportDefinition**

The settings for the import job that's associated with the segment.

**Type**: SegmentImportResource

Required: False

#### Arn

The Amazon Resource Name (ARN) of the segment.

**Type**: string **Required**: True

### tags

A string-to-string map of key-value pairs that identifies the tags that are associated with the segment. Each tag consists of a required tag key and an associated tag value.

**Type**: object **Required**: False

## SegmentsResponse

Provides information about all the segments that are associated with an application.

#### Item

An array of responses, one for each segment that's associated with the application (Segments resource) or each version of a segment that's associated with the application (Segment Versions resource).

**Type**: Array of type SegmentResponse

**Required**: True

### NextToken

The string to use in a subsequent request to get the next page of results in a paginated response. This value is null if there are no additional pages.

**Type**: string **Required**: False

### **SetDimension**

Specifies the dimension type and values for a segment dimension.

# DimensionType

The type of segment dimension to use. Valid values are: INCLUSIVE, endpoints that match the criteria are included in the segment; and, EXCLUSIVE, endpoints that match the criteria are excluded from the segment.

Type: string

Required: False

Values: INCLUSIVE | EXCLUSIVE

### **Values**

The criteria values to use for the segment dimension. Depending on the value of the DimensionType property, endpoints are included or excluded from the segment if their values match the criteria values.

Type: Array of type string

Required: True

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

# **GetSegmentVersions**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Segments**

A *segment* designates which users receive messages from a campaign or journey, typically a group of customers that share certain attributes.

See also 1079

You can create a segment by sending a POST request to the Segments resource. The body of your request specifies the dimensions that determine which endpoints belong to the segment. If you use the Segments resource to create a segment, the segment type is DIMENSIONAL, which means that endpoints that belong to the segment vary over time based on user activity. If you want to create a static segment, which includes a fixed set of endpoints, you can send a POST request to the <a href="Import Jobs">Import</a> resource to import the endpoints that belong to the segment. For more information, see <a href="Import Jobs">Importing Segments</a> in the Amazon Pinpoint Developer Guide.

You can use the Segments resource to create, retrieve information about, or update the settings for segments that are associated with an application.

## **URI**

/v1/apps/application-id/segments

# **HTTP methods**

### **GET**

## **Operation ID:** GetSegments

Retrieves information about the configuration, dimension, and other settings for all the segments that are associated with an application.

### Path parameters

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

URI 1080

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# **Query parameters**

Name	Туре	Required	Description
page-size	String	False	The maximum number of items to include in each page of a paginated response. This parameter is not supported for application, campaign, and journey metrics.
token	String	False	The NextToken string that specifies which page of results to return in a paginated response.

# Responses

Status code	Response model	Description
200	SegmentsResponse	The request succeeded.

Status code	Response model	Description
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	MessageBody	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **POST**

# **Operation ID:** CreateSegment

Creates a new segment.

# **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

## Responses

Status code	Response model	Description
201	SegmentResponse	The request succeeded and the specified resource was created.
400	MessageBody	The request contains a syntax error (BadRequestException).

Status code	Response model	Description
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Segments resource.

## **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Request bodies**

### **POST schema**

```
"DimensionType": enum,
    "Values": [
      "string"
    ]
  },
  "DeviceType": {
    "DimensionType": enum,
    "<u>Values</u>": [
      "string"
    ]
  },
  "AppVersion": {
    "DimensionType": enum,
    "Values": [
     "string"
    ]
  },
  "Make": {
    "DimensionType": enum,
    "Values": [
      "string"
    ]
  },
  "<u>Model</u>": {
    "DimensionType": enum,
    "Values": [
      "string"
    ]
  }
},
"Location": {
  "Country": {
    "DimensionType": enum,
    "<u>Values</u>": [
      "string"
    ]
  },
  "GPSPoint": {
    "Coordinates": {
      "Latitude": number,
      "Longitude": number
    },
    "RangeInKilometers": number
  }
```

```
},
  "Behavior": {
    "Recency": {
      "RecencyType": enum,
      "Duration": enum
    }
  },
  "Attributes": {
  },
  "Metrics": {
  },
  "<u>UserAttributes</u>": {
  }
},
"SegmentGroups": {
  "Include": enum,
  "Groups": [
    {
      "Type": enum,
      "Dimensions": [
          "Demographic": {
             "Channel": {
               "DimensionType": enum,
               "Values": [
                 "string"
              ]
            },
             "Platform": {
               "DimensionType": enum,
               "Values": [
                 "string"
               ]
            },
            "DeviceType": {
               "DimensionType": enum,
               "Values": [
                 "string"
               ]
            },
            "AppVersion": {
               "DimensionType": enum,
               "Val<u>ues</u>": [
                 "string"
```

```
]
      },
      "Make": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      },
      "Model": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      }
    },
    "Location": {
      "Country": {
        "DimensionType": enum,
        "Values": [
          "string"
        ]
      },
      "GPSPoint": {
        "Coordinates": {
          "Latitude": number,
          "Longitude": number
        },
        "RangeInKilometers": number
      }
    },
    "Behavior": {
      "Recency": {
        "RecencyType": enum,
        "Duration": enum
      }
    },
    "Attributes": {
    },
    "Metrics": {
    },
    "<u>UserAttributes</u>": {
    }
  }
],
```

# **Response bodies**

## SegmentsResponse schema

```
{
  "Item": [
      "Name": "string",
      "Dimensions": {
        "Demographic": {
          "Channel": {
            "DimensionType": enum,
            "Values": [
              "string"
            ]
          },
          "Platform": {
            "DimensionType": enum,
            "Values": [
              "string"
            ]
          },
          "DeviceType": {
            "DimensionType": enum,
            "Values": [
              "string"
            ]
          },
          "AppVersion": {
```

```
"DimensionType": enum,
    "Values": [
      "string"
    ]
  },
  "Make": {
    "DimensionType": enum,
    "Val<u>ues</u>": [
     "string"
    ]
  },
  "Model": {
    "DimensionType": enum,
    "Values": [
     "string"
    ]
  }
},
"Location": {
  "Country": {
    "DimensionType": enum,
    "Values": [
     "string"
    ]
  },
  "GPSPoint": {
    "Coordinates": {
      "<u>Latitude</u>": number,
      "Longitude": number
    },
    "RangeInKilometers": number
  }
},
"Behavior": {
  "Recency": {
    "RecencyType": enum,
    "Duration": enum
  }
},
"Attributes": {
},
"Metrics": {
},
"UserAttributes": {
```

```
}
},
"SegmentGroups": {
  "Include": enum,
  "Groups": [
    {
      "Type": enum,
      "<u>Dimensions</u>": [
        {
          "Demographic": {
             "Channel": {
               "DimensionType": enum,
               "Values": [
                 "string"
               ]
            },
             "Platform": {
               "DimensionType": enum,
               "Values": [
                 "string"
               ]
            },
             "DeviceType": {
               "DimensionType": enum,
               "Values": [
                 "string"
               ]
            },
             "AppVersion": {
               "DimensionType": enum,
               "Values": [
                 "string"
               ]
            },
             "Make": {
               "DimensionType": enum,
               "Values": [
                 "string"
               ]
            },
             "<u>Model</u>": {
               "DimensionType": enum,
               "Values": [
                 "string"
```

```
]
            }
          },
          "Location": {
            "Country": {
              "DimensionType": enum,
              "Values": [
                "string"
              ]
            },
            "GPSPoint": {
              "Coordinates": {
                "Latitude": number,
                "Longitude": number
              },
              "RangeInKilometers": number
            }
          },
          "Behavior": {
            "Recency": {
              ""RecencyType": enum,
              "Duration": enum
            }
          },
          "Attributes": {
          },
          "Metrics": {
          },
          "UserAttributes": {
          }
        }
      ],
      "SourceType": enum,
      "SourceSegments": [
          ""Id": "string",
          "Version": integer
        }
      ]
    }
  ]
"Id": "string",
"ApplicationId": "string",
```

```
"CreationDate": "string",
      "LastModifiedDate": "string",
      "Version": integer,
      "SegmentType": enum,
      "ImportDefinition": {
        "Size": integer,
        "S3Url": "string",
        "RoleArn": "string",
        "ExternalId": "string",
        "Format": enum,
        "ChannelCounts": {
        }
      },
      "Arn": "string",
      "tags": {
      }
    }
  ],
  ""NextToken": "string"
}
```

### SegmentResponse schema

```
"Name": "string",
"Dimensions": {
  "Demographic": {
    "Channel": {
      "DimensionType": enum,
      "Values": [
        "string"
      ]
    },
    "Platform": {
      "DimensionType": enum,
      "Values": [
        "string"
      ]
    },
    "DeviceType": {
      "DimensionType": enum,
      "Values": [
        "string"
```

```
]
  },
  "AppVersion": {
    "DimensionType": enum,
    "Values": [
      "string"
    ]
  },
  "Make": {
    "DimensionType": enum,
    "Values": [
      "string"
    ]
  },
  "Model": {
    "DimensionType": enum,
    "Values": [
      "string"
    ]
  }
},
"Location": {
  "Country": {
    "DimensionType": enum,
    "Values": [
      "string"
    ]
  },
  "GPSPoint": {
    "Coordinates": {
      "Latitu<u>de</u>": number,
      "Longitude": number
    },
    "RangeInKilometers": number
  }
},
"Behavior": {
  "Recency": {
    "RecencyType": enum,
    "Duration": enum
  }
},
"Attributes": {
},
```

```
"Metrics": {
  },
  "UserAt<u>tributes</u>": {
  }
},
"SegmentGroups": {
  "Include": enum,
  "Groups": [
    {
      "Type": enum,
      "Dimensions": [
        {
          "Demographic": {
             "Channel": {
               "DimensionType": enum,
               "Values": [
                 "string"
              ]
            },
            "Platform": {
               "DimensionType": enum,
               "Values": [
                 "string"
              ]
            },
             "DeviceType": {
               "DimensionType": enum,
               "Values": [
                 "string"
              ]
            },
             "AppVersion": {
               "DimensionType": enum,
               ""Values": [
                 "string"
              ]
            },
             "Make": {
               "DimensionType": enum,
               "Values": [
                 "string"
              ]
            },
            "Model": {
```

```
"DimensionType": enum,
            "Values": [
              "string"
            ]
          }
        },
        "Location": {
          "Country": {
            "DimensionType": enum,
            "Values": [
              "string"
            ]
          },
          "GPSPoint": {
            "Coordinates": {
              "<u>Latitude</u>": number,
              "Longitude": number
            },
            "RangeInKilometers": number
          }
        },
        "Behavior": {
          "Recency": {
            "RecencyType": enum,
            "Duration": enum
          }
        },
        "Attributes": {
        "Metrics": {
        },
        ""UserAttributes": {
      }
    "SourceType": enum,
    "SourceSegments": [
      {
        ""Id": "string",
        "Version": integer
      }
    ]
  }
]
```

```
},
  "Id": "string",
  "ApplicationId": "string",
  "CreationDate": "string",
  "LastModifiedDate": "string",
  "Version": integer,
  "SegmentType": enum,
  "ImportDefinition": {
    "Size": integer,
    "S3Url": "string",
    "RoleArn": "string",
    "ExternalId": "string",
    "Format": enum,
    "ChannelCounts": {
  "Arn": "string",
  "<u>tags</u>": {
  }
}
```

## MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

### **AttributeDimension**

Specifies attribute-based criteria for including or excluding endpoints from a segment.

## **AttributeType**

The type of segment dimension to use. Valid values are:

- INCLUSIVE endpoints that have attributes matching the values are included in the segment.
- EXCLUSIVE endpoints that have attributes matching the values are excluded from the segment.

• CONTAINS – endpoints that have attributes' substrings match the values are included in the segment.

- BEFORE endpoints with attributes read as ISO\_INSTANT datetimes before the value are included in the segment.
- AFTER endpoints with attributes read as ISO\_INSTANT datetimes after the value are included in the segment.
- BETWEEN endpoints with attributes read as ISO\_INSTANT datetimes between the values are included in the segment.
- ON endpoints with attributes read as ISO\_INSTANT dates on the value are included in the segment. Time is ignored in this comparison.

**Type**: string

Required: False

Values: INCLUSIVE | EXCLUSIVE | CONTAINS | BEFORE | AFTER | BETWEEN |

NOT\_BETWEEN | ON

### **Values**

The criteria values to use for the segment dimension. Depending on the value of the AttributeType property, endpoints are included or excluded from the segment if their attribute values match the criteria values.

**Type**: Array of type string

Required: True

### **GPSCoordinates**

Specifies the GPS coordinates of a location.

## Latitude

The latitude coordinate of the location.

**Type**: number **Required**: True

### Longitude

The longitude coordinate of the location.

**Type**: number **Required**: True

## **GPSPointDimension**

Specifies GPS-based criteria for including or excluding endpoints from a segment.

### **Coordinates**

The GPS coordinates to measure distance from.

**Type:** GPSCoordinates

Required: True

## RangeInKilometers

The range, in kilometers, from the GPS coordinates.

**Type**: number **Required**: False

# MessageBody

Provides information about an API request or response.

## RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

### Message

The message that's returned from the API.

**Type**: string

Required: False

## MetricDimension

Specifies metric-based criteria for including or excluding endpoints from a segment. These criteria derive from custom metrics that you define for endpoints.

## ComparisonOperator

The operator to use when comparing metric values. Valid values are: GREATER\_THAN, LESS\_THAN, GREATER\_THAN\_OR\_EQUAL, LESS\_THAN\_OR\_EQUAL, and EQUAL.

Type: string

**Required**: True

### **Value**

The value to compare.

Type: number

**Required**: True

# RecencyDimension

Specifies criteria for including or excluding endpoints from a segment based on how recently an endpoint was active.

# RecencyType

The type of recency dimension to use for the segment. Valid values are: ACTIVE, endpoints that were active within the specified duration are included in the segment; and, INACTIVE, endpoints that weren't active within the specified duration are included in the segment.

Type: string

**Required**: True

Values: ACTIVE | INACTIVE

### **Duration**

The duration to use when determining whether an endpoint is active or inactive.

**Type**: string **Required**: True

**Values**: HR\_24 | DAY\_7 | DAY\_14 | DAY\_30

# **SegmentBehaviors**

Specifies dimension settings for including or excluding endpoints from a segment based on how recently an endpoint was active.

## Recency

The dimension settings that are based on how recently an endpoint was active.

**Type**: RecencyDimension

Required: False

# **SegmentDemographics**

Specifies demographic-based dimension settings for including or excluding endpoints from a segment. These settings derive from characteristics of endpoint devices, such as platform, make, and model.

### Channel

The channel criteria for the segment.

Type: <u>SetDimension</u>
Required: False

### **Platform**

The device platform criteria for the segment.

Type: <u>SetDimension</u>
Required: False

## DeviceType

The device type criteria for the segment.

**Type**: SetDimension

Required: False

## **AppVersion**

The app version criteria for the segment.

**Type:** SetDimension

Required: False

### Make

The device make criteria for the segment.

**Type:** SetDimension

Required: False

## Model

The device model criteria for the segment.

**Type:** SetDimension

Required: False

# **SegmentDimensions**

Specifies the dimension settings for a segment.

## **Demographic**

The demographic-based criteria, such as device platform, for the segment.

**Type:** SegmentDemographics

Required: False

#### Location

The location-based criteria, such as region or GPS coordinates, for the segment.

**Type:** SegmentLocation

Required: False

#### **Behavior**

The behavior-based criteria, such as how recently users have used your app, for the segment.

**Type**: SegmentBehaviors

Required: False

#### **Attributes**

One or more custom attributes to use as criteria for the segment. For more information see AttributeDimension

Type: object

Required: False

### **Metrics**

One or more custom metrics to use as criteria for the segment.

Type: object

Required: False

### **UserAttributes**

One or more custom user attributes to use as criteria for the segment.

Type: object

Required: False

### SegmentGroup

Specifies the base segments and dimensions for a segment, and the relationships between these base segments and dimensions.

### **Type**

Specifies how to handle multiple dimensions for the segment. For example, if you specify three dimensions for the segment, whether the resulting segment includes endpoints that match all, any, or none of the dimensions.

**Type**: string **Required**: False

Values: ALL | ANY | NONE

### **Dimensions**

An array that defines the dimensions for the segment.

**Type**: Array of type SegmentDimensions

**Required**: False

### SourceType

Specifies how to handle multiple base segments for the segment. For example, if you specify three base segments for the segment, whether the resulting segment is based on all, any, or none of the base segments.

**Type**: string

Required: False

Values: ALL | ANY | NONE

### **SourceSegments**

The base segment to build the segment on. A base segment, also referred to as a *source segment*, defines the initial population of endpoints for a segment. When you add dimensions to a segment, Amazon Pinpoint filters the base segment by using the dimensions that you specify.

You can specify more than one dimensional segment or only one imported segment. If you specify an imported segment, the Amazon Pinpoint console displays a segment size estimate that indicates the size of the imported segment without any filters applied to it.

**Type**: Array of type <u>SegmentReference</u>

Required: False

### SegmentGroupList

Specifies the settings that define the relationships between segment groups for a segment.

#### Include

Specifies how to handle multiple segment groups for the segment. For example, if the segment includes three segment groups, whether the resulting segment includes endpoints that match all, any, or none of the segment groups.

**Type**: string **Required**: False

Values: ALL | ANY | NONE

### Groups

An array that defines the set of segment criteria to evaluate when handling segment groups for the segment.

**Type**: Array of type <u>SegmentGroup</u>

Required: False

## SegmentImportResource

Provides information about the import job that created a segment. An import job is a job that creates a user segment by importing endpoint definitions.

#### Size

The number of endpoint definitions that were imported successfully to create the segment.

**Type**: integer

Required: True

#### S3Url

The URL of the Amazon Simple Storage Service (Amazon S3) bucket that the endpoint definitions were imported from to create the segment.

**Type**: string **Required**: True

### RoleArn

The Amazon Resource Name (ARN) of the AWS Identity and Access Management (IAM) role that authorized Amazon Pinpoint to access the Amazon S3 location to import endpoint definitions from.

**Type**: string **Required**: True

#### **ExternalId**

(Deprecated) Your AWS account ID, which you assigned to an external ID key in an IAM trust policy. Amazon Pinpoint previously used this value to assume an IAM role when importing endpoint definitions, but we removed this requirement. We don't recommend use of external IDs for IAM roles that are assumed by Amazon Pinpoint.

**Type**: string **Required**: True

#### **Format**

The format of the files that were imported to create the segment. Valid values are: CSV, for comma-separated values format; and, JSON, for newline-delimited JSON format.

**Type**: string **Required**: True

Values: CSV | JSON

#### **ChannelCounts**

The number of channel types in the endpoint definitions that were imported to create the segment.

**Type**: object **Required**: False

## **SegmentLocation**

Specifies geographical dimension settings for a segment.

### **Country**

The country or region code, in ISO 3166-1 alpha-2 format, for the segment.

Type: <u>SetDimension</u>
Required: False

#### **GPSPoint**

The GPS location and range for the segment.

**Type**: GPSPointDimension

Required: False

# SegmentReference

Specifies the segment identifier and version of a segment.

Id

The unique identifier for the segment.

**Type**: string **Required**: True

#### Version

The version number of the segment.

**Type**: integer **Required**: False

## SegmentResponse

Provides information about the configuration, dimension, and other settings for a segment.

#### Name

The name of the segment.

**Type**: string **Required**: False

#### **Dimensions**

The dimension settings for the segment.

**Type**: SegmentDimensions

Required: False

### **SegmentGroups**

A list of one or more segment groups that apply to the segment. Each segment group consists of zero or more base segments and the dimensions that are applied to those base segments.

**Type**: SegmentGroupList

Required: False

### Id

The unique identifier for the segment.

**Type**: string **Required**: True

## **ApplicationId**

The unique identifier for the application that the segment is associated with.

**Type**: string **Required**: True

#### CreationDate

The date and time when the segment was created.

**Type**: string **Required**: True

### LastModifiedDate

The date and time when the segment was last modified.

**Type**: string **Required**: False

### Version

The version number of the segment.

**Type**: integer **Required**: False

### SegmentType

The segment type. Valid values are:

- DIMENSIONAL A dynamic segment, which is a segment that uses selection criteria that you specify and is based on endpoint data that's reported by your app. Dynamic segments can change over time.
- IMPORT A static segment, which is a segment that uses selection criteria that you specify and
  is based on endpoint definitions that you import from a file. Imported segments are static; they
  don't change over time.

**Type**: string **Required**: True

Values: DIMENSIONAL | IMPORT

### **ImportDefinition**

The settings for the import job that's associated with the segment.

**Type**: SegmentImportResource

Required: False

### Arn

The Amazon Resource Name (ARN) of the segment.

**Type**: string **Required**: True

### tags

A string-to-string map of key-value pairs that identifies the tags that are associated with the segment. Each tag consists of a required tag key and an associated tag value.

**Type**: object **Required**: False

## **SegmentsResponse**

Provides information about all the segments that are associated with an application.

#### **Item**

An array of responses, one for each segment that's associated with the application (Segments resource) or each version of a segment that's associated with the application (Segment Versions resource).

**Type**: Array of type <u>SegmentResponse</u>

Required: True

#### NextToken

The string to use in a subsequent request to get the next page of results in a paginated response. This value is null if there are no additional pages.

**Type**: string Required: False

### **SetDimension**

Specifies the dimension type and values for a segment dimension.

### DimensionType

The type of segment dimension to use. Valid values are: INCLUSIVE, endpoints that match the criteria are included in the segment; and, EXCLUSIVE, endpoints that match the criteria are excluded from the segment.

Type: string Required: False

Values: INCLUSIVE | EXCLUSIVE

### **Values**

The criteria values to use for the segment dimension. Depending on the value of the DimensionType property, endpoints are included or excluded from the segment if their values match the criteria values.

Type: Array of type string

**Required**: True

## WriteSegmentRequest

Specifies the configuration, dimension, and other settings for a segment. A WriteSegmentRequest object can include a Dimensions object or a SegmentGroups object, but not both.

#### Name

The name of the segment.



### (i) Note

A segment must have a name otherwise it will not appear in the Amazon Pinpoint console.

**REST API Reference** Amazon Pinpoint

**Type**: string

Required: False

### **Dimensions**

The criteria that define the dimensions for the segment. If no values are provided, then all endpoints are included in the segment.

**Type**: SegmentDimensions

Required: False

### SegmentGroups

The segment group to use and the dimensions to apply to the group's base segments in order to build the segment. A segment group can consist of zero or more base segments. Your request can include only one segment group.

**Type:** SegmentGroupList

Required: False

### tags



### Note

As of 22-05-2023 the PUT UpdateSegment tags attribute has been deprecated. After this date any value in the tags attribute is not processed and will not generate an error code. Use the Tags resource to add or modify tags.

(Deprecated) A string-to-string map of key-value pairs that defines the tags to associate with the segment. Each tag consists of a required tag key and an associated tag value.

Type: object Required: False

### See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

### **GetSegments**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

## CreateSegment

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

See also 1113

# **Settings**

The Settings resource represents the default settings for an Amazon Pinpoint application. You can use this resource to retrieve information about or update the default settings for an application.

### **URI**

/v1/apps/application-id/settings

### **HTTP** methods

### **GET**

**Operation ID:** GetApplicationSettings

Retrieves information about the settings for an application.

### **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

### **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

Settings 1114

### Responses

Status code	Response model	Description
200	ApplicationSetting sResource	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).

Status code	Response model	Description
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **PUT**

Operation ID: UpdateApplicationSettings

Updates the settings for an application.

## **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

### Responses

Status code	Response model	Description
200	ApplicationSetting sResource	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).

Status code	Response model	Description
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Settings resource.

### **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## Responses

Status code	Response model	Description
200	None	The request succeeded.

## **Schemas**

## **Request bodies**

### **PUT schema**

{

Schemas 1118

```
"QuietTime": {
    "Start": "string",
    "End": "string"
  "Limits": {
    "Daily": integer,
    "Total": integer,
    "Session": integer,
    ""MessagesPerSecond": integer,
    "MaximumDuration": integer
  },
  "CampaignHook": {
    "LambdaFunctionName": "string",
    "WebUrl": "string",
    "Mode": enum
  }
}
```

## **Response bodies**

### ApplicationSettingsResource schema

```
{
  "ApplicationId": "string",
  "LastModifiedDate": "string",
  "QuietTime": {
    "Start": "string",
    "End": "string"
  },
  "Limits": {
    "Daily": integer,
    "Total": integer,
    "Session": integer,
    "MessagesPerSecond": integer,
    "MaximumDuration": integer
  },
  "JourneyLimits": {
    "DailyCap": integer,
    "TotalCap": integer,
    "TimeframeCap": {
      "Days": integer,
      "Cap": integer
    }
```

Schemas 1119

```
},
"CampaignHook": {
    "LambdaFunctionName": "string",
    "WebUrl": "string",
    "Mode": enum
}
```

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

## **Properties**

## **ApplicationSettingsJourneyLimits**

The default sending limits for journeys in the application. To override these limits and define custom limits for a specific journey, use the Journey resource.

### **DailyCap**

The daily number of messages that an endpoint can receive from all journeys. The maximum value is 100. If set to 0, this limit will not apply.

**Type**: integer **Required**: False

## **TotalCap**

The default maximum number of messages that a single journey can sent to a single endpoint. The maximum value is 100. If set to 0, this limit will not apply.

**Type**: integer **Required**: False

### **TimeframeCap**

The default maximum number of messages that can be sent to an endpoint during the specified timeframe for all journeys.

**Type**: JourneyTimeframeCap

Required: False

## **ApplicationSettingsResource**

Provides information about an application, including the default settings for an application.

### **ApplicationId**

The unique identifier for the application. This identifier is displayed as the **Project ID** on the Amazon Pinpoint console.

**Type**: string **Required**: True

#### LastModifiedDate

The date and time, in ISO 8601 format, when the application's settings were last modified.

**Type**: string **Required**: False

### QuietTime

The default quiet time for campaigns in the application. Quiet time is a specific time range when messages aren't sent to endpoints, if all the following conditions are met:

- The EndpointDemographic.Timezone property of the endpoint is set to a valid value.
- The current time in the endpoint's time zone is later than or equal to the time specified by the QuietTime.Start property for the application (or a campaign or journey that has custom quiet time settings).
- The current time in the endpoint's time zone is earlier than or equal to the time specified by the QuietTime. End property for the application (or a campaign or journey that has custom quiet time settings).

If any of the preceding conditions isn't met, the endpoint will receive messages from a campaign or journey, even if quiet time is enabled.

Type: QuietTime Required: False

#### Limits

The default sending limits for campaigns in the application.

**Type**: CampaignLimits

Required: False

### **JourneyLimits**

The default sending limits for journeys in the application. These limits apply to each journey for the application but can be overridden, on a per journey basis, with the JourneyLimits resource.

**Type**: ApplicationSettingsJourneyLimits

**Required**: False

### CampaignHook

The settings for the AWS Lambda function to invoke by default as a code hook for campaigns in the application. You can use this hook to customize segments that are used by campaigns in the application.

Type: CampaignHook

Required: False

## CampaignHook

Specifies settings for invoking an AWS Lambda function that customizes a segment for a campaign.

#### LambdaFunctionName

The name or Amazon Resource Name (ARN) of the AWS Lambda function that Amazon Pinpoint invokes to customize a segment for a campaign.

**Type**: string **Required**: False

#### WebUrl

The web URL that Amazon Pinpoint calls to invoke the AWS Lambda function over HTTPS.

**Type**: string **Required**: False

#### Mode

The mode that Amazon Pinpoint uses to invoke the AWS Lambda function. Possible values are:

- FILTER Invoke the function to customize the segment that's used by a campaign.
- DELIVERY (Deprecated) Previously, invoked the function to send a campaign through a custom channel. This functionality is not supported anymore. To send a campaign through a custom channel, use the CustomDeliveryConfiguration and CampaignCustomMessage objects of the campaign.

**Type**: string **Required**: False

Values: DELIVERY | FILTER

## **CampaignLimits**

For a campaign, specifies limits on the messages that the campaign can send. For an application, specifies the default limits for messages that campaigns in the application can send.

### Daily

The maximum number of messages that a campaign can send to a single endpoint during a 24-hour period. For an application, this value specifies the default limit for the number of messages that campaigns and journeys can send to a single endpoint during a 24-hour period. The maximum value is 100.

**Type**: integer **Required**: False

#### **Total**

The maximum number of messages that a campaign can send to a single endpoint during the course of the campaign. If a campaign recurs, this setting applies to all runs of the campaign. The maximum value is 100.

**Type**: integer **Required**: False

#### Session

The maximum number of messages that the campaign can send per user session.

**Type**: integer **Required**: False

### MessagesPerSecond

The maximum number of messages that a campaign can send each second. For an application, this value specifies the default limit for the number of messages that campaigns can send each second. The minimum value is 1. The maximum value is 20,000.

**Type**: integer **Required**: False

### **MaximumDuration**

The maximum amount of time, in seconds, that a campaign can attempt to deliver a message after the scheduled start time for the campaign. The minimum value is 60 seconds.

**Type**: integer **Required**: False

## JourneyTimeframeCap

The number of messages that can be sent to an endpoint during the specified timeframe for all journeys.

### **Days**

The length of the timeframe in days. The maximum value is 30. If set to 0, this limit will not apply.

**Type**: integer **Required**: False

### Cap

The maximum number of messages that all journeys can send to an endpoint during the specified timeframe. The maximum value is 100. If set to 0, this limit will not apply.

**Type**: integer **Required**: False

## MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

### Message

The message that's returned from the API.

Type: string

Required: False

## QuietTime

Specifies the start and end times that define a time range when messages aren't sent to endpoints.

#### Start

The specific time when quiet time begins. This value has to use 24-hour notation and be in HH:MM format, where HH is the hour (with a leading zero, if applicable) and MM is the minutes. For example, use 02:30 to represent 2:30 AM, or 14:30 to represent 2:30 PM.

**Type**: string

Required: False

### **End**

The specific time when quiet time ends. This value has to use 24-hour notation and be in HH:MM format, where HH is the hour (with a leading zero, if applicable) and MM is the minutes. For example, use 02:30 to represent 2:30 AM, or 14:30 to represent 2:30 PM.

**Type**: string **Required**: False

## WriteApplicationSettingsRequest

Specifies the default settings for an application.

### QuietTime

The default quiet time for campaigns in the application. Quiet time is a specific time range when messages aren't sent to endpoints, if all the following conditions are met:

- The EndpointDemographic.Timezone property of the endpoint is set to a valid value.
- The current time in the endpoint's time zone is later than or equal to the time specified by the QuietTime.Start property for the application (or a campaign or journey that has custom quiet time settings).
- The current time in the endpoint's time zone is earlier than or equal to the time specified by the QuietTime. End property for the application (or a campaign or journey that has custom quiet time settings).

If any of the preceding conditions isn't met, the endpoint will receive messages from a campaign or journey, even if quiet time is enabled.

To override the default quiet time settings for a specific campaign or journey, use the <u>Campaign</u> resource or the <u>Journey</u> resource to define a custom quiet time for the campaign or journey.

Type: QuietTime Required: False

#### Limits

The default sending limits for campaigns in the application. To override these limits and define custom limits for a specific campaign or journey, use the <u>Campaign</u> resource or the <u>Journey</u> resource, respectively.

**Type**: CampaignLimits

Required: False

### CampaignHook

The settings for the AWS Lambda function to invoke by default as a code hook for campaigns in the application. You can use this hook to customize segments that are used by campaigns in the application.

To override these settings and define custom settings for a specific campaign, use the CampaignHook object of the Campaign resource.

Type: CampaignHook

Required: False

### See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## **GetApplicationSettings**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2

See also 1127

- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

## **UpdateApplicationSettings**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **SMS Channel**

A *channel* is a type of platform that you can deliver messages to. To send an SMS text message, you send the message through the SMS channel. Before you can use Amazon Pinpoint to send text messages, you must enable the SMS channel for an Amazon Pinpoint application.

The SMS Channel resource represents the status, sender ID, and other settings of the SMS channel for a specific application. You can use this resource to enable, retrieve information about, update, or disable (delete) the SMS channel for an application.

### **URI**

/v1/apps/application-id/channels/sms

SMS Channel 1128

# **HTTP** methods

## **GET**

## **Operation ID:** GetSmsChannel

Retrieves information about the status and settings of the SMS channel for an application.

## **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

## Responses

Status code	Response model	Description
200	SMSChannelResponse	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).

Status code	Response model	Description
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **PUT**

# **Operation ID:** UpdateSmsChannel

Enables the SMS channel for an application or updates the status and settings of the SMS channel for an application.

## **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

## Responses

Status code	Response model	Description
200	<u>SMSChannelResponse</u>	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is

Status code	Response model	<b>Description</b> forbidden (ForbiddenExceptio
404	<u>MessageBody</u>	n).  The request failed because the specified resource was not found (NotFoundException).
405	MessageBody	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **DELETE**

## Operation ID: DeleteSmsChannel

Disables the SMS channel for an application and deletes any existing settings for the channel.

## **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	<u>SMSChannelResponse</u>	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).

Status code	Response model	Description
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **OPTIONS**

Retrieves information about the communication requirements and options that are available for the SMS Channel resource.

### **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

### Responses

Status code	Response model	Description
200	None	The request succeeded.

## **Schemas**

## **Request bodies**

### **PUT schema**

```
{
  "Enabled": boolean,
  "ShortCode": "string",
  "SenderId": "string"
}
```

# **Response bodies**

## SMSChannelResponse schema

```
{
    "ApplicationId": "string",
    "IsArchived": boolean,
    "Version": integer,
```

Schemas 1135

```
"CreationDate": "string",
"LastModifiedDate": "string",
"Id": "string",
"Enabled": boolean,
"ShortCode": "string",
"SenderId": "string",
"Platform": "string",
"PromotionalMessagesPerSecond": integer,
"TransactionalMessagesPerSecond": integer,
"HasCredential": boolean
}
```

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

## MessageBody

Provides information about an API request or response.

### **RequestID**

The unique identifier for the request or response.

**Type**: string **Required**: False

### Message

The message that's returned from the API.

**Type**: string **Required**: False

## **SMSChannelRequest**

Specifies the status and settings of the SMS channel for an application.

#### **Enabled**

Specifies whether to enable the SMS channel for the application.

**Type**: boolean **Required**: False

### **ShortCode**

The registered short code that you want to use when you send messages through the SMS channel.

**Type**: string **Required**: False

#### SenderId

The alphabetic Sender ID to display as the sender of the message on a recipient's device. Support for sender IDs varies by country or region. To specify a phone number as the sender, omit this parameter and use OriginationNumber instead. For more information about support for Sender ID by country, see the Amazon Pinpoint User Guide.

**Type**: string **Required**: False

## **SMSChannelResponse**

Provides information about the status and settings of the SMS channel for an application.

## **ApplicationId**

The unique identifier for the application that the SMS channel applies to.

Type: string

Required: False

#### **IsArchived**

Specifies whether the SMS channel is archived.

**Type**: boolean **Required**: False

#### Version

The current version of the SMS channel.

**Type**: integer **Required**: False

### CreationDate

The date and time, in ISO 8601 format, when the SMS channel was enabled.

**Type**: string **Required**: False

#### LastModifiedDate

The date and time, in ISO 8601 format, when the SMS channel was last modified.

**Type**: string **Required**: False

### LastModifiedBy

The user who last modified the SMS channel.

**Type**: string **Required**: False

#### Id

(Deprecated) An identifier for the SMS channel. This property is retained only for backward compatibility.

**Type**: string **Required**: False

#### **Enabled**

Specifies whether the SMS channel is enabled for the application.

**Type**: boolean **Required**: False

#### ShortCode

The registered short code to use when you send messages through the SMS channel.

**Type**: string **Required**: False

#### SenderId

The SMS Sender ID that was used to send the message.

**Type**: string **Required**: False

#### **Platform**

The type of messaging or notification platform for the channel. For the SMS channel, this value is SMS.

**Type**: string **Required**: True

## ${\bf Promotional Messages Per Second}$

The maximum number of promotional messages that you can send through the SMS channel each second.

Type: integer

Required: False

#### TransactionalMessagesPerSecond

The maximum number of transactional messages that you can send through the SMS channel each second.

**Type**: integer **Required**: False

#### HasCredential

(Not used) This property is retained only for backward compatibility.

**Type**: boolean **Required**: False

### See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

#### **GetSmsChannel**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

See also 1140

## **UpdateSmsChannel**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

#### **DeleteSmsChannel**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- · AWS SDK for Python
- AWS SDK for Ruby V3

# **SMS Template**

An *SMS template* is a type of message template that contains content and settings that you can define, save, and reuse in messages that you send through the SMS channel for any of your Amazon Pinpoint applications. You can use SMS templates in text messages that you send from campaigns, or to a limited audience as direct or test messages.

SMS Template 1141

When you create an SMS template, you specify the settings and content that you want to reuse in the body of messages that are based on the template. This content can be static text or personalized content that you define by using the Handlebars template system and message variables. When you send a message that's based on a template, Amazon Pinpoint populates the message with the settings and content that you defined in the template.

The SMS Template resource represents the repository of SMS templates that are associated with your Amazon Pinpoint account. You can use this resource to create, retrieve, update, or delete a message template for messages that you send through the SMS channel.

Amazon Pinpoint supports versioning for all types of message templates. When you use the SMS Template resource to work with a template, you can use supported parameters to specify whether your request applies to only a specific version of the template or to the overall template. For example, if you update a template, you can specify whether you want to save your updates as a new version of the template or save them to the latest existing version of the template. To retrieve information about all the versions of a template, use the Template Versions resource.

### **URI**

/v1/templates/template-name/sms

### **HTTP** methods

#### **GET**

Operation ID: GetSmsTemplate

Retrieves the content and settings of a message template for messages that are sent through the SMS channel.

### Path parameters

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can

URI 1142

Name	Туре	Required	Description
			contain a maximum
			of 128 characters.
			The characters can
			be alphanumeric
			characters, underscor
			es (_), or hyphens (-).
			Template names are
			case sensitive.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# **Query parameters**

Name	Туре	Required	Description
version	String	False	The unique identifie r for the version of the message template to update, retrieve information about, or delete. To retrieve identifiers and other informati on for all the versions of a template, use the Template  Versions resource.

Name Type

Required

Description

If specified, this value must match the identifier for an existing template version. If specified for an update operation, this value must match the identifier for the latest existing version of the template. This restriction helps ensure that race conditions don't occur.

If you don't specify a value for this parameter, Amazon Pinpoint does the following:

- For a get operation , retrieves informati on about the active version of the template.
- For an update operation, saves the updates to (overwrites) the latest existing version of the template, if the create-ne

Name	Туре	Required	Description
			w-version
			parameter isn't
			used or is set to
			false.
			<ul> <li>For a delete operation, deletes the template, including all versions of the</li> </ul>
			template.

# Responses

Status code	Response model	Description
200	SMSTemplateResponse	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	MessageBody	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	MessageBody	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).

Status code	Response model	Description
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **POST**

# Operation ID: CreateSmsTemplate

Creates a message template for messages that are sent through the SMS channel.

## **Path parameters**

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can contain a maximum of 128 characters. The characters can

Name	Туре	Required	Description
			be alphanumeric characters, underscor es (_), or hyphens (-). Template names are case sensitive.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
201	<pre>CreateTemplateMess ageBody</pre>	The request succeeded and the specified resource was created.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
405	MessageBody	The request failed because the method is not allowed for the specified resource

Status code	Response model	Description
		(MethodNotAllowedE xception).
409	<u>MessageBody</u>	The request failed due to a conflict with the current state of the specified resource (ConflictException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **PUT**

# Operation ID: UpdateSmsTemplate

Updates an existing message template for messages that are sent through the SMS channel.

# Path parameters

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can contain a maximum of 128 characters.

Name	Туре	Required	Description
			The characters can be alphanumeric characters, underscor es (_), or hyphens (-). Template names are
			case sensitive.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# **Query parameters**

Name	Туре	Required	Description
create-new- version	String	False	Specifies whether to save the updates as a new version of the message template.  Valid values are: true, save the updates as a new version; and, false, save the updates to (overwrite) the latest existing version of the template.

Name Type Required Description

If you don't specify a value for this parameter, Amazon Pinpoint saves the updates to (overwrites) the latest existing version of the template. If you specify a value of true for this parameter, don't specify a value for the version parameter. Otherwise , an error will occur.

Name	Туре	Required	Description
version	String	False	The unique identifie r for the version of the message template to update, retrieve information about, or delete. To retrieve identifiers and other informati on for all the versions of a template, use the Template Versionsresource.  If specified, this value must match the identifier for an existing template version. If specified for an update operation, this value must match the identifier for the latest existing version of the template. This restriction helps ensure that race conditions don't occur.
			If you don't specify a value for this parameter, Amazon Pinpoint does the following:

Name	Туре	Required	Description
			<ul> <li>For a get operation , retrieves informati on about the active version of the template.</li> </ul>
			<ul> <li>For an update operation, saves the updates to (overwrites) the latest existing version of the template, if the create-ne w-version parameter isn't used or is set to false.</li> <li>For a delete operation, deletes the template,</li> </ul>
			including all versions of the template.

## Responses

Status code	Response model	Description
202	<u>MessageBody</u>	The request was accepted for processing. Processing may not be complete.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).

Status code	Response model	Description
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **DELETE**

Operation ID: DeleteSmsTemplate

Deletes a message template for messages that were sent through the SMS channel.

### **Path parameters**

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can contain a maximum of 128 characters. The characters can be alphanumeric characters, underscores (_), or hyphens (-). Template names are case sensitive.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

## **Query parameters**

Name	Туре	Required	Description
version	String	False	The unique identifie r for the version of the message

Name Type Required Description

template to update, retrieve information about, or delete. To retrieve identifiers and other informati on for all the versions of a template, use the <u>Template</u>
Versionsresource.

If specified, this value must match the identifier for an existing template version. If specified for an update operation, this value must match the identifier for the latest existing version of the template. This restriction helps ensure that race conditions don't occur.

If you don't specify a value for this parameter, Amazon Pinpoint does the following:

 For a get operation , retrieves informati on about the active

Name	Туре	Required	Description
			version of the template.
			• For an update operation, saves the updates to (overwrites) the latest existing version of the template, if the create-ne w-version parameter isn't used or is set to false.
			<ul> <li>For a delete operation, deletes the template, including all versions of the template.</li> </ul>

## Responses

Status code	Response model	Description
202	MessageBody	The request was accepted for processing. Processing may not be complete.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	MessageBody	The request was denied because access to the specified resource is

Status code	Response model	Description
		forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **OPTIONS**

Retrieves information about the communication requirements and options that are available for the SMS Template resource.

### **Path parameters**

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can contain a maximum of 128 characters. The characters can be alphanumeric characters, underscor es (_), or hyphens (-). Template names are case sensitive.

### Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Request bodies**

### **POST schema**

```
{
   "TemplateDescription": "string",
   "DefaultSubstitutions": "string",
   "tags": {
   },
   "Body": "string",
   "RecommenderId": "string"
```

Schemas 1158

}

#### **PUT schema**

```
{
  "TemplateDescription": "string",
  "DefaultSubstitutions": "string",
  "tags": {
  },
  "Body": "string",
  "RecommenderId": "string"
}
```

### **Response bodies**

### SMSTemplateResponse schema

```
{
    "CreationDate": "string",
    "LastModifiedDate": "string",
    "TemplateType": enum,
    "TemplateName": "string",
    "DefaultSubstitutions": "string",
    "Version": "string",
    "tags": {
    },
    "Arn": "string",
    "Body": "string",
    "RecommenderId": "string"
}
```

## CreateTemplateMessageBody schema

```
{
   "RequestID": "string",
   "Message": "string",
   "Arn": "string"
}
```

Schemas 1159

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

### CreateTemplateMessageBody

Provides information about a request to create a message template.

### **RequestID**

The unique identifier for the request to create the message template.

**Type**: string **Required**: False

#### Message

The message that's returned from the API for the request to create the message template.

**Type**: string **Required**: False

#### Arn

The Amazon Resource Name (ARN) of the message template that was created.

**Type**: string **Required**: False

# MessageBody

Provides information about an API request or response.

#### RequestID

The unique identifier for the request or response.

**Type**: string Required: False

#### Message

The message that's returned from the API.

**Type**: string **Required**: False

### **SMSTemplateRequest**

Specifies the content and settings for a message template that can be used in text messages that are sent through the SMS channel.

### **TemplateDescription**

A custom description of the message template.

**Type**: string Required: False

#### **DefaultSubstitutions**

A JSON object that specifies the default values to use for message variables in the message template. This object is a set of key-value pairs. Each key defines a message variable in the template. The corresponding value defines the default value for that variable. When you create a message that's based on the template, you can override these defaults with message-specific and address-specific variables and values.

**Type**: string Required: False

#### tags



#### Note

As of 22-05-2023 the tags attribute has been deprecated. After this date any value in the PUT UpdateSmsTemplate tags attribute is not processed and an error code is not returned.

The POST CreateSmsTemplate tags attribute is processed. Use the <u>Tags</u> resource to add or modify tags.

(Deprecated) A string-to-string map of key-value pairs that defines the tags to associate with the message template. Each tag consists of a required tag key and an associated tag value.

**Type**: object **Required**: False

#### **Body**

The message body to use in text messages that are based on the message template.

**Type**: string **Required**: False

#### RecommenderId

The unique identifier for the recommender model to use for the message template. Amazon Pinpoint uses this value to determine how to retrieve and process data from a recommender model when it sends messages that use the template, if the template contains message variables for recommendation data.

**Type**: string **Required**: False

## **SMSTemplateResponse**

Provides information about the content and settings for a message template that can be used in text messages that are sent through the SMS channel.

#### CreationDate

The date, in ISO 8601 format, when the message template was created.

**Type**: string **Required**: True

#### LastModifiedDate

The date, in ISO 8601 format, when the message template was last modified.

**Type**: string **Required**: True

### **TemplateType**

The type of channel that the message template is designed for. For an SMS template, this value is SMS.

**Type**: string **Required**: True

Values: EMAIL | SMS | VOICE | PUSH | INAPP

### **TemplateName**

The name of the message template.

**Type**: string **Required**: True

### TemplateDescription

The custom description of the message template.

**Type**: string **Required**: False

#### **DefaultSubstitutions**

The JSON object that specifies the default values that are used for message variables in the message template. This object is a set of key-value pairs. Each key defines a message variable in the template. The corresponding value defines the default value for that variable.

**Type**: string **Required**: False

#### Version

The unique identifier, as an integer, for the active version of the message template, or the version of the template that you specified by using the version parameter in your request.

Type: string

Required: False

#### tags

A string-to-string map of key-value pairs that identifies the tags that are associated with the message template. Each tag consists of a required tag key and an associated tag value.

**Type**: object

Required: False

#### Arn

The Amazon Resource Name (ARN) of the message template.

Type: string

Required: False

#### **Body**

The message body that's used in text messages that are based on the message template.

Type: string

Required: False

#### RecommenderId

The unique identifier for the recommender model that's used by the message template.

**Type**: string

Required: False

### See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## GetSmsTemplate

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

## CreateSmsTemplate

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

See also 1165

## **UpdateSmsTemplate**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

## DeleteSmsTemplate

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Tags**

A *tag* is a label that you optionally define and associate with an application, campaign, message template, or segment in Amazon Pinpoint. Tags can help you categorize and manage these types of resources in different ways, such as by purpose, owner, environment, or other criteria. A resource can have as many as 50 tags.

Tags 1166

Each tag consists of a required *tag key* and an associated *tag value*, both of which you define. A tag key is a general label that acts as a category for more specific tag values. A tag value acts as a descriptor within a tag key. For example, if you have two versions of an Amazon Pinpoint application, one for internal testing and another for external use, you might assign a Stack tag key to both applications. The value of the key might be Test for one version of the application and Production for the other version. For more information about tags, see <u>Tagging Amazon Pinpoint</u> Resources in the *Amazon Pinpoint Developer Guide*.

You can use the Tags resource to add, retrieve, or remove tags from an application, campaign, message template, or segment.

### **URI**

/v1/tags/resource-arn

### **HTTP** methods

### **GET**

Operation ID: ListTagsForResource

Retrieves all the tags (keys and values) that are associated with an application, campaign, message template, or segment.

### Path parameters

Name	Type	Required	Description
resource-arn	String	True	The Amazon Resource Name (ARN) of the resource.

#### Responses

Status code	Response model	Description
200	tagsModel	The request succeeded.

URI 1167

### **POST**

## **Operation ID:** TagResource

Adds one or more tags (keys and values) to an application, campaign, message template, or segment.

### **Path parameters**

Name	Туре	Required	Description
resource-arn	String	True	The Amazon Resource Name (ARN) of the resource.

## Responses

Status code	Response model	Description
204	None	The request succeeded and there's no additional content to send in the body of the response (No Content).

### **DELETE**

### **Operation ID:** UntagResource

Removes one or more tags (keys and values) from an application, campaign, message template, or segment.

## **Path parameters**

Name	Туре	Required	Description
resource-arn	String	True	The Amazon Resource Name (ARN) of the resource.

### **Query parameters**

Name	Туре	Required	Description
tagKeys	String	True	The key of the tag to remove from the resource. To remove multiple tags, append the tagKeys parameter and argument for each additional tag to remove, separated by an ampersand (&).

### Responses

Status code	Response model	Description
204	None	The request succeeded and
		there's no additional content
		to send in the body of the
		response (No Content).

# **Schemas**

# **Request bodies**

### **POST schema**

```
{
    "<u>tags</u>": {
    }
}
```

# **Response bodies**

Schemas 1169

#### tagsModel schema

```
{
    "<u>tags</u>": {
    }
}
```

## **Properties**

## tagsModel

Specifies the tags (keys and values) for an application, campaign, message template, or segment.

### tags

A string-to-string map of key-value pairs that defines the tags for an application, campaign, message template, or segment. Each of these resources can have a maximum of 50 tags.

Each tag consists of a required tag key and an associated tag value. The maximum length of a tag key is 128 characters. The maximum length of a tag value is 256 characters.

**Type**: object **Required**: True

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

## ListTagsForResource

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3

- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

### **TagResource**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

## **UntagResource**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

See also 1171

# **Template Versions**

A *message template* is a set of content and settings that you can define, save, and reuse in email messages, push notifications, SMS text messages, and voice messages for any of your Amazon Pinpoint applications. To help you develop and maintain templates, Amazon Pinpoint supports versioning for all types of message templates.

Each time you update a template, Amazon Pinpoint automatically saves your changes to (overwrites) the latest existing version of the template, unless you choose to create a new version of the template. Each version of a template is a snapshot of the template that you can use in a message.

The Template Versions resource provides information about all the versions of a specific message template. This information includes the unique identifier, creation and modification dates, and settings for each version of the template.

You can use the Template Versions resource to retrieve information about all the versions of a specific message template.

### URI

/v1/templates/template-name/template-type/versions

## **HTTP** methods

#### **GET**

Operation ID: ListTemplateVersions

Retrieves information about all the versions of a specific message template.

## **Path parameters**

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric

Template Versions 1172

Name	Type	Required	Description
			character and can contain a maximum of 128 characters. The characters can be alphanumeric characters, underscor es (_), or hyphens (-). Template names are case sensitive.
template-type	String	True	The type of channel that the message template is designed for. Valid values are: EMAIL, PUSH, SMS, and VOICE.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# **Query parameters**

Name	Туре	Required	Description
page-size	String	False	The maximum number of items to include in each page of a

Name	Туре	Required	Description
			paginated response. This parameter is not supported for application, campaign, and journey metrics.
next-token	String	False	The string that specifies which page of results to return in a paginated response. This parameter is not supported for application, campaign, and journey metrics.

# Responses

Status code	Response model	Description
200	TemplateVersionsRe sponse	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	MessageBody	The request failed because the specified resource was not found (NotFoundException).

Status code	Response model	Description
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Template Versions resource.

# **Path parameters**

Name	Type	Required	Description
template-name	String	True	The name of the message template. A template name must start with

Name	Туре	Required	Description
			an alphanumeric character and can contain a maximum of 128 characters. The characters can be alphanumeric characters, underscor es (_), or hyphens (-). Template names are case sensitive.
template-type	String	True	The type of channel that the message template is designed for. Valid values are: EMAIL, PUSH, SMS, and VOICE.

# Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Response bodies**

# TemplateVersionsResponse schema

```
{
  "RequestID": "string",
  "Message": "string",
  "Item": [
    {
        "TemplateName}": "string",
```

```
"TemplateType": "string",
    "CreationDate": "string",
    "LastModifiedDate": "string",
    "TemplateDescription": "string",
    "DefaultSubstitutions": "string",
    "Version": "string"
}
],
    "NextToken": "string"
}
```

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

## MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

### Message

The message that's returned from the API.

**Type**: string **Required**: False

# Template Version Response

Provides information about a specific version of a message template.

### **TemplateName**

The name of the message template.

**Type**: string **Required**: True

### **TemplateType**

The type of channel that the message template is designed for. Possible values are: EMAIL, PUSH, SMS, INAPP, and VOICE.

**Type**: string **Required**: True

### CreationDate

The date, in ISO 8601 format, when the version of the message template was created.

**Type**: string **Required**: True

### LastModifiedDate

The date, in ISO 8601 format, when the version of the message template was last modified.

**Type**: string **Required**: True

### **TemplateDescription**

The custom description of the version of the message template.

**Type**: string **Required**: False

#### **DefaultSubstitutions**

A JSON object that specifies the default values that are used for message variables in the version of the message template. This object is a set of key-value pairs. Each key defines a message variable in the template. The corresponding value defines the default value for that variable.

**Type**: string **Required**: False

#### Version

The unique identifier for the version of the message template. This value is an integer that Amazon Pinpoint automatically increments and assigns to each new version of a template.

**Type**: string **Required**: False

## **TemplateVersionsResponse**

Provides information about all the versions of a specific message template.

### RequestID

The unique identifier for the request to retrieve information about all the versions of the message template.

**Type**: string **Required**: False

### Message

The message that's returned from the API for the request to retrieve information about all the versions of the message template.

**Type**: string **Required**: False

### Item

An array of responses, one for each version of the message template.

**Type**: Array of type TemplateVersionResponse

Required: True

#### NextToken

The string to use in a subsequent request to get the next page of results in a paginated response. This value is null if there are no additional pages.

**Type**: string **Required**: False

### See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

# ListTemplateVersions

- AWS Command Line Interface
- · AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Templates**

A *message template* is a set of content and settings that you can define, save, and reuse in email messages, push notifications, SMS text messages, and voice messages for any of your Amazon Pinpoint applications.

See also 1180

When you create a message template, you specify the content and settings that you want to reuse in various components of messages that are based on the template. These components, referred to as *template parts*, can be the message title or subject, the message body, or both, depending on the message type. A template part can also be a channel-specific setting, such as an image to display or a sound to play when a recipient receives a message that's based on the template. When you send a message that's based on a template, Amazon Pinpoint populates the message with the content and settings that you defined in the template.

The Templates resource represents the repository of message templates that are associated with your Amazon Pinpoint account. You can use this resource to retrieve information about all the message templates that are associated with your account. To retrieve information about versions of a specific message template, use the Template Versions resource.

### **URI**

/v1/templates

### **HTTP** methods

#### **GET**

**Operation ID:** ListTemplates

Retrieves information about all the message templates that are associated with your Amazon Pinpoint account.

### **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

URI 1181

# **Query parameters**

Name	Туре	Required	Description
page-size	String	False	The maximum number of items to include in each page of a paginated response. This parameter is not supported for application, campaign, and journey metrics.
next-token	String	False	The string that specifies which page of results to return in a paginated response. This parameter is not supported for application, campaign, and journey metrics.
prefix	String	False	The substring to match in the names of the message templates to include in the results. If you specify this value, Amazon Pinpoint returns only those templates whose names begin with the value that you specify.

Name	Туре	Required	Description
template-type	String	False	The type of message template to include in the results. Valid values are: EMAIL, PUSH, SMS, and VOICE. To include all types of templates in the results, don't include this parameter in your request.

# Responses

Status code	Response model	Description
200	<u>TemplatesResponse</u>	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
409	<u>MessageBody</u>	The request failed due to a conflict with the current

Status code	Response model	Description
		state of the specified resource (ConflictException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	MessageBody	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Templates resource.

### Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Response bodies**

# **TemplatesResponse schema**

```
"TemplateName": "string",
    "TemplateDescription": "string",
    "DefaultSubstitutions": "string",
    "Version": "string",
    "tags": {
      },
      "Arn": "string"
    }
],
    "NextToken": "string"
}
```

## MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

# MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

### Message

The message that's returned from the API.

**Type**: string **Required**: False

### **TemplateResponse**

Provides information about a message template that's associated with your Amazon Pinpoint account.

#### CreationDate

The date, in ISO 8601 format, when the message template was created.

**Type**: string **Required**: True

#### LastModifiedDate

The date, in ISO 8601 format, when the message template was last modified.

**Type**: string **Required**: True

### **TemplateType**

The type of channel that the message template is designed for. Possible values are: EMAIL, PUSH, SMS, INAPP, and VOICE.

**Type**: string **Required**: True

Values: EMAIL | SMS | VOICE | PUSH | INAPP

### **TemplateName**

The name of the message template.

**Type**: string **Required**: True

### **TemplateDescription**

The custom description of the message template. This value isn't included in a TemplateResponse object. To retrieve the description of a template, use the

GetEmailTemplate, GetPushTemplate, GetSmsTemplate, or GetVoiceTemplate operation, depending on the type of template that you want to retrieve the description for.

**Type**: string **Required**: False

#### **DefaultSubstitutions**

The JSON object that specifies the default values that are used for message variables in the message template. This object isn't included in a TemplateResponse object. To retrieve this object for a template, use the GetEmailTemplate, GetPushTemplate, GetSmsTemplate, or GetVoiceTemplate operation, depending on the type of template that you want to retrieve the object for.

**Type**: string **Required**: False

#### Version

The unique identifier, as an integer, for the active version of the message template.

**Type**: string **Required**: False

#### tags

A map of key-value pairs that identifies the tags that are associated with the message template. This object isn't included in a TemplateResponse object. To retrieve this object for a template, use the GetEmailTemplate, GetPushTemplate, GetSmsTemplate, or GetVoiceTemplate operation, depending on the type of template that you want to retrieve the object for.

**Type**: object **Required**: False

#### Arn

The Amazon Resource Name (ARN) of the message template. This value isn't included in a TemplateResponse object. To retrieve the ARN of a template, use the GetEmailTemplate,

GetPushTemplate, GetSmsTemplate, or GetVoiceTemplate operation, depending on the type of template that you want to retrieve the ARN for.

Type: string

Required: False

# **TemplatesResponse**

Provides information about all the message templates that are associated with your Amazon Pinpoint account.

#### Item

An array of responses, one for each message template that's associated with your Amazon Pinpoint account and meets any filter criteria that you specified in the request.

**Type**: Array of type TemplateResponse

Required: True

#### NextToken

The string to use in a subsequent request to get the next page of results in a paginated response. This value is null if there are no additional pages.

Type: string

Required: False

# See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

# ListTemplates

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++

See also 1188

- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# User

A *user* is an individual who has a unique user ID. This ID can be associated with zero or more endpoints. For example, if a person uses your app on more than one device, you can associate that person's user ID with the endpoint for each of those devices.

You can use the User resource to retrieve information about all the endpoints that are associated with a user ID, or to delete all the endpoints that are associated with a user ID.

### **URI**

/v1/apps/application-id/users/user-id

# **HTTP methods**

#### **GET**

Operation ID: GetUserEndpoints

Retrieves information about all the endpoints that are associated with a specific user ID.

# **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the

User 1189

Name	Type	Required	Description
			Amazon Pinpoint console.
user-id	String	True	The unique identifie r for the user. The identifier can't contain \$, { or }.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	<u>EndpointsResponse</u>	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).

Status code	Response model	Description
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **DELETE**

# Operation ID: DeleteUserEndpoints

Deletes all the endpoints that are associated with a specific user ID.

# **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the

Name	Туре	Required	Description
			<b>Project ID</b> on the Amazon Pinpoint console.
user-id	String	True	The unique identifie r for the user. The identifier can't contain \$, { or }.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client
			understands.

# Responses

Status code	Response model	Description
202	EndpointsResponse	The request was accepted for processing. Processing may not be complete.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).

Status code	Response model	Description
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **OPTIONS**

Retrieves information about the communication requirements and options that are available for the User resource.

### **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.
user-id	String	True	The unique identifie r for the user. The identifier can't contain \$, { or }.

## Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Response bodies**

# **EndpointsResponse schema**

```
"Longitude": number,
        "PostalCode": "string",
        "City": "string",
        "Region": "string",
        "Country": "string"
      },
      "Demographic": {
        "Make": "string",
        "Model": "string",
        "ModelVersion": "string",
        "Timezone": "string",
        "Locale": "string",
        "AppVersion": "string",
        "Platform": "string",
        "PlatformVersion": "string"
      },
      "EffectiveDate": "string",
      "Att<u>ributes</u>": {
      },
      "Metrics": {
      },
      "User": {
        "UserId": "string",
        "UserAttributes": {
        }
      },
      "ApplicationId": "string",
      "Id": "string",
      "CohortId": "string",
      "CreationDate": "string"
    }
  ]
}
```

### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

# **EndpointDemographic**

Specifies demographic information about an endpoint, such as the applicable time zone and platform.

### Make

The manufacturer of the endpoint device, such as Apple or Samsung. Can contain a maximum of 50 characters.

Type: string

Required: False

### Model

The model name or number of the endpoint device, such as iPhone or SM-G900F. Can contain a maximum of 100 characters.

Type: string

Required: False

#### **ModelVersion**

The model version of the endpoint device. Can contain a maximum of 50 characters.

Type: string

Required: False

### **Timezone**

The time zone of the endpoint, specified as a tz database name value, such as America/Los\_Angeles.

Type: string

Required: False

#### Locale

An identifier that represents the endpoint's language, in IETF BCP 47 format. This identifier typically consists of an ISO 639-1 alpha-2 code, followed by an underscore (\_), followed by an ISO 3166-1 alpha-2 value. For example, the locale code for United States English is en\_US.

In some cases, an ISO 3166-1 numeric-3 value is used instead of an ISO 3166-1 alpha-2 value. For example, the locale code for Latin American Spanish is es\_419.

In other cases, the ISO 639-1 alpha-2 is replaced with a three-letter code. For example, the locale code for Hawaiian is haw\_US.

**Type**: string **Required**: False

### **AppVersion**

The version of the app that's associated with the endpoint. Can contain a maximum of 50 characters.

**Type**: string **Required**: False

#### **Platform**

The platform of the endpoint device, such as iOS. Can contain a maximum of 50 characters.

**Type**: string **Required**: False

#### **PlatformVersion**

The version of the platform for the endpoint device. Can contain a maximum of 50 characters.

**Type**: string **Required**: False

# **EndpointLocation**

Specifies geographic information about an endpoint.

#### Latitude

The latitude coordinate of the endpoint location, rounded to one decimal place. Must be between -90 and 90. If you specify a latitude, you must also specify a longitude.

**Type**: number **Required**: False

### Longitude

The longitude coordinate of the endpoint location, rounded to one decimal place. Must be between -180 and 180. If you specify a longitude, you must also specify a latitude.

**Type**: number **Required**: False

#### **PostalCode**

The postal or ZIP code for the area where the endpoint is located.

Type: string

Required: False

### City

The name of the city where the endpoint is located. Can contain a maximum of 75 characters.

Type: string

Required: False

### Region

The name of the region where the endpoint is located. This value is typically a first-level subdivision a country, such as a state, province, prefecture, administrative region, district, or department. Can contain a maximum of 75 characters.

Type: string

**Required**: False

### Country

A code that represents the country or region where the endpoint is located. Must be in ISO 3166-1 Alpha-2 or Alpha-3 format. For example, for the United States, you can use US or USA.

**Type**: string **Required**: False

# **EndpointResponse**

Provides information about the channel type and other settings for an endpoint.

### ChannelType

The channel that's used when sending messages or push notifications to the endpoint.

Type: string

Required: False

Values: PUSH | GCM | APNS | APNS\_SANDBOX | APNS\_VOIP | APNS\_VOIP\_SANDBOX |

ADM | SMS | VOICE | EMAIL | BAIDU | CUSTOM | IN\_APP

### **Address**

The destination address for messages or push notifications that you send to the endpoint. The address varies by channel. For example, the address for a push notification channel is typically the token provided by a push notification service, such as an Apple Push Notification service (APNs) device token or a Firebase Cloud Messaging (FCM) registration token. The address for the SMS channel is a phone number in E.164 format, such as +12065550100. The address for the email channel is an email address.

Type: string

Required: False

### **EndpointStatus**

Specifies whether messages or push notifications are sent to the endpoint. Possible values are: ACTIVE, messages are sent to the endpoint; and, INACTIVE, messages aren't sent to the endpoint.

Amazon Pinpoint automatically sets this value to ACTIVE when you create an endpoint or update an existing endpoint. Amazon Pinpoint automatically sets this value to INACTIVE if you update another endpoint that has the same address specified by the Address property.

**Type**: string

**Required**: False

### **OptOut**

Specifies whether the user who's associated with the endpoint has opted out of receiving messages and push notifications from you. Possible values are: ALL, the user has opted out and doesn't want to receive any messages or push notifications; and, NONE, the user hasn't opted out and wants to receive all messages and push notifications.

**Type**: string

**Required**: False

### RequestId

The unique identifier for the most recent request to update the endpoint.

**Type**: string

Required: False

### Location

The geographic information for the endpoint.

**Type**: EndpointLocation

**Required**: False

### **Demographic**

The demographic information for the endpoint, such as the time zone and platform.

**Type**: EndpointDemographic

**Required**: False

#### **EffectiveDate**

The date and time, in ISO 8601 format, when the endpoint was last updated.

Type: string

Required: False

#### **Attributes**

One or more custom attributes that describe the endpoint by associating a name with an array of values. For example, the value of a custom attribute named Interests might be: ["Science", "Music", "Travel"]. You can use these attributes as filter criteria when you create segments.

Type: object

Required: False

#### **Metrics**

One or more custom metrics that your app reports to Amazon Pinpoint for the endpoint.

Type: object

Required: False

#### User

One or more custom user attributes that your app reports to Amazon Pinpoint for the user who's associated with the endpoint.

**Type**: EndpointUser

Required: False

### **ApplicationId**

The unique identifier for the application that's associated with the endpoint.

Type: string

Required: False

#### Id

The unique identifier that you assigned to the endpoint. The identifier should be a globally unique identifier (GUID) to ensure that it doesn't conflict with other endpoint identifiers that are associated with the application.

**Type**: string

Required: False

#### CohortId

A number from 0–99 that represents the cohort that the endpoint is assigned to. Endpoints are grouped into cohorts randomly, and each cohort contains approximately 1 percent of the endpoints for an application. Amazon Pinpoint assigns cohorts to the holdout or treatment allocations for campaigns.

**Type**: string

Required: False

#### CreationDate

The date and time, in ISO 8601 format, when the endpoint was created.

**Type**: string

Required: False

# **EndpointUser**

Specifies data for one or more attributes that describe the user who's associated with an endpoint.

### **UserId**

The unique identifier for the user. The identifier can't contain \$, { or }.

**Type**: string

**Required**: False

#### **UserAttributes**

One or more custom attributes that describe the user by associating a name with an array of values. For example, the value of an attribute named Interests might be: ["Science", "Music", "Travel"]. You can use these attributes as filter criteria when you create segments. Attribute names are case sensitive.

An attribute name can contain up to 50 characters. An attribute value can contain up to 100 characters. When you define the name of a custom attribute, avoid using the following characters: number sign (#), colon (:), question mark (?), backslash (\), and slash (/). The Amazon Pinpoint console can't display attribute names that contain these characters. This restriction doesn't apply to attribute values.

**Type**: object **Required**: False

## **EndpointsResponse**

Provides information about all the endpoints that are associated with a user ID.

#### Item

An array of responses, one for each endpoint that's associated with the user ID.

**Type**: Array of type EndpointResponse

Required: True

# MessageBody

Provides information about an API request or response.

### RequestID

The unique identifier for the request or response.

Type: string

Required: False

#### Message

The message that's returned from the API.

**Type**: string **Required**: False

### See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

# **GetUserEndpoints**

- AWS Command Line Interface
- · AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# DeleteUserEndpoints

- AWS Command Line Interface
- · AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin

See also 1204

- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Users Messages**

A *user* is an individual who has a unique user ID. This ID can be associated with zero or more endpoints. For example, if an individual uses your app on multiple devices, you can associate that person's user ID with the endpoint for each of those devices.

You can use the Users Messages resource to send a message to a list of users. If you use this resource to send a message, you specify the message recipients as a list of user IDs. For each user ID in the list, Amazon Pinpoint sends the message to all the endpoints that are associated with the user ID. You can send the message to as many as 100 users per request. For the message content, you can specify a default message and you can tailor your message for different channels, including push notification channels.

When you use this resource to send a message, the message is sent as a *direct message*, which is a one-time message that you send directly to a limited audience without creating a campaign. This means that you can't send the message to a segment. This also means that you can't schedule the delivery of the message. Amazon Pinpoint delivers the message immediately. If you want to send a message to a segment or you want to schedule a message to be sent at a certain time, you should create a campaign instead of using the Users Messages resource to send the message.

You can use the Users Messages resource to send a direct message to a list of users.

### **URI**

/v1/apps/application-id/users-messages

# **HTTP** methods

### **POST**

**Operation ID:** SendUsersMessages

Creates and sends a message to a list of users.

Users Messages 1205

# **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	SendUsersMessageRe sponse	The request succeeded.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).

Status code	Response model	Description
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Users Messages resource.

### **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Request bodies**

### **POST schema**

```
{
  "TraceId": "string",
  "Context": {
  },
  "MessageConfiguration": {
    "DefaultMessage": {
      "Body": "string",
      "Substitutions": {
      }
    },
    "DefaultPushNotificationMessage": {
      "Body": "string",
      "Substitutions": {
      },
      "Title": "string",
      "Action": enum,
```

```
"Url": "string",
  "SilentPush": boolean,
  "Data": {
  }
},
"APNSMessage": {
  "Body": "string",
  "Substitutions": {
  },
  "Title": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "Data": {
  },
  ""MediaUrl": "string",
  "Sound": "string",
  "Badge": integer,
  "Category": "string",
  "ThreadId": "string",
  "RawContent": "string",
  "PreferredAuthenticationMethod": "string",
  "TimeToLive": integer,
  "Priority": "string",
  "CollapseId": "string",
  "APNSPushType": "string"
},
"GCMMessage": {
  "Body": "string",
  "Substitutions": {
  },
  "Title": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "Data": {
  },
  "IconReference": "string",
  "Sound": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "SmallImageIconUrl": "string",
  "RawContent": "string",
  "CollapseKey": "string",
```

```
"RestrictedPackageName": "string",
  "TimeToLive": integer,
  "Priority": "string",
  "PreferredAuthenticationMethod": "string"
},
"BaiduMessage": {
  "Body": "string",
  "Substitutions": {
 },
  "Title": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "Data": {
 },
  "IconReference": "string",
  "Sound": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "SmallImageIconUrl": "string",
  "RawContent": "string",
  "TimeToLive": integer
},
"ADMMessage": {
  "Body": "string",
  "Substitutions": {
 },
  "Title": "string",
  "Action": enum,
  "Url": "string",
  "SilentPush": boolean,
  "Data": {
 },
  "IconReference": "string",
  "Sound": "string",
  "ImageUrl": "string",
  "ImageIconUrl": "string",
  "SmallImageIconUrl": "string",
  "RawContent": "string",
  "ConsolidationKey": "string",
  "ExpiresAfter": "string",
  "MD5": "string"
},
"EmailMessage": {
```

```
"Body": "string",
  "Substitutions": {
  },
  "FromAddress": "string",
  "FeedbackForwardingAddress": "string",
  "ReplyToAddresses": [
    "string"
  ],
  "SimpleEmail": {
    "Subject": {
      "Data": "string",
      "Charset": "string"
    },
    "TextPart": {
     "Data": "string",
      "Charset": "string"
    },
    "HtmlPart": {
      "Data": "string",
      "Charset": "string"
    },
    "Headers": [
      {
        "Name": "string",
        "Value": "string"
      }
    ]
  },
  "RawEmail": {
    "Data": "string"
  }
},
"SMSMessage": {
  "Body": "string",
  "Substitutions": {
  },
  "SenderId": "string",
  "MessageType": enum,
  "Keyword": "string",
  "OriginationNumber": "string",
  "EntityId": "string",
  "TemplateId": "string",
  "MediaUrl": "string"
},
```

Schemas 1211

```
"VoiceMessage": {
      "Body": "string",
      "Substitutions": {
      },
      "LanguageCode": "string",
      "VoiceId": "string",
      "OriginationNumber": "string"
    }
  },
  "TemplateConfiguration": {
    "SMSTemplate": {
      "Name": "string",
      "Version": "string"
    "EmailTemplate": {
      "Name": "string",
      "Version": "string"
    },
    "PushTemplate": {
      "Name": "string",
      "Version": "string"
    },
    "VoiceTemplate": {
      "Name": "string",
      "Version": "string"
    },
    "InAppTemplate": {
      "Name": "string",
      "Version": "string"
    }
  },
  "Users": {
  }
}
```

# **Response bodies**

# SendUsersMessageResponse schema

```
{
  "ApplicationId": "string",
  "RequestId": "string",
  "Result": {
```

Schemas 1212

```
}
}
```

# MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

# **ADMMessage**

Specifies the settings for a one-time message that's sent directly to an endpoint through the ADM (Amazon Device Messaging) channel.

## **Body**

The body of the notification message.

**Type**: string **Required**: False

### **Substitutions**

The default message variables to use in the notification message. You can override the default variables with individual address variables.

**Type**: object **Required**: False

## Title

The title to display above the notification message on the recipient's device.

**Type**: string **Required**: False

### **Action**

The action to occur if the recipient taps the push notification. Valid values are:

OPEN\_APP – Your app opens or it becomes the foreground app if it was sent to the background.
 This is the default action.

- DEEP\_LINK Your app opens and displays a designated user interface in the app. This action uses the deep-linking features of the Android platform.
- URL The default mobile browser on the recipient's device opens and loads the web page at a URL that you specify.

**Type**: string **Required**: False

Values: OPEN\_APP | DEEP\_LINK | URL

#### Url

The URL to open in the recipient's default mobile browser, if a recipient taps the push notification and the value of the Action property is URL.

**Type**: string **Required**: False

### **SilentPush**

Specifies whether the notification is a silent push notification, which is a push notification that doesn't display on a recipient's device. Silent push notifications can be used for cases such as updating an app's configuration or supporting phone home functionality.

**Type**: boolean **Required**: False

#### Data

The JSON data payload to use for the push notification, if the notification is a silent push notification. This payload is added to the data.pinpoint.jsonBody object of the notification.

Type: object

Required: False

### **IconReference**

The icon image name of the asset saved in your app.

**Type**: string **Required**: False

## Sound

The sound to play when the recipient receives the push notification. You can use the default stream or specify the file name of a sound resource that's bundled in your app. On an Android platform, the sound file must reside in /res/raw/.

**Type**: string **Required**: False

## ImageUrl

The URL of an image to display in the push notification.

**Type**: string **Required**: False

## **ImageIconUrl**

The URL of the large icon image to display in the content view of the push notification.

**Type**: string **Required**: False

# SmallimageIconUrl

The URL of the small icon image to display in the status bar and the content view of the push notification.

**Type**: string **Required**: False

#### RawContent

The raw, JSON-formatted string to use as the payload for the notification message. If specified, this value overrides all other content for the message.

Type: string

Required: False

## ConsolidationKey

An arbitrary string that indicates that multiple messages are logically the same and that Amazon Device Messaging (ADM) can drop previously enqueued messages in favor of this message.

**Type**: string

Required: False

## **ExpiresAfter**

The amount of time, in seconds, that ADM should store the message if the recipient's device is offline. Amazon Pinpoint specifies this value in the expiresAfter parameter when it sends the notification message to ADM.

**Type**: string

Required: False

### MD5

The base64-encoded, MD5 checksum of the value specified by the Data property. ADM uses the MD5 value to verify the integrity of the data.

**Type**: string

Required: False

# **APNSMessage**

Specifies the settings for a one-time message that's sent directly to an endpoint through the APNs (Apple Push Notification service) channel.

## **Body**

The body of the notification message.

Type: string

Required: False

#### **Substitutions**

The default message variables to use in the notification message. You can override these default variables with individual address variables.

Type: object

Required: False

### **Title**

The title to display above the notification message on the recipient's device.

Type: string

Required: False

## Action

The action to occur if the recipient taps the push notification. Valid values are:

OPEN\_APP – Your app opens or it becomes the foreground app if it was sent to the background.
 This is the default action.

• DEEP\_LINK – Your app opens and displays a designated user interface in the app. This setting uses the deep-linking features of the iOS platform.

• URL – The default mobile browser on the recipient's device opens and loads the web page at a URL that you specify.

**Type**: string

Required: False

Values: OPEN\_APP | DEEP\_LINK | URL

### Url

The URL to open in the recipient's default mobile browser, if a recipient taps the push notification and the value of the Action property is URL.

**Type**: string **Required**: False

### **SilentPush**

Specifies whether the notification is a silent push notification. A silent (or background) push notification isn't displayed on recipients' devices. You can use silent push notifications to make small updates to your app, or to display messages in an in-app message center.

Amazon Pinpoint uses this property to determine the correct value for the apns-push-type request header when it sends the notification message to APNs. If you specify a value of true for this property, Amazon Pinpoint sets the value for the apns-push-type header field to background.

# Note

If you specify the raw content of an APNs push notification, the message payload has to include the content-available key. For silent (background) notifications, set the value of content-available to 1. Additionally, the message payload for a silent notification can't include the alert, badge, or sound keys. For more information, see <a href="Memote Notification">Generating a</a> <a href="Remote Notification">Remote Notification</a> and <a href="Pushing Background Updates to Your App">Pushing Background Updates to Your App</a> on the Apple Developer website.

Apple has indicated that they will throttle "excessive" background notifications based on current traffic volumes. To prevent your notifications being throttled, Apple recommends that you send no more than 3 silent push notifications to each recipient per hour.

**Type**: boolean **Required**: False

#### **Data**

The JSON payload to use for a silent push notification. This payload is added to the data.pinpoint.jsonBody object of the notification.

**Type**: object **Required**: False

#### MediaUrl

The URL of an image or video to display in the push notification.

**Type**: string **Required**: False

#### Sound

The key for the sound to play when the recipient receives the push notification. The value for this key is the name of a sound file in your app's main bundle or the Library/Sounds folder in your app's data container. If the sound file can't be found or you specify default for the value, the system plays the default alert sound.

**Type**: string **Required**: False

## **Badge**

The key that indicates whether and how to modify the badge of your app's icon when the recipient receives the push notification. If this key isn't included in the dictionary, the badge doesn't change. To remove the badge, set this value to 0.

**Type**: integer **Required**: False

## **Category**

The key that indicates the notification type for the push notification. This key is a value that's defined by the identifier property of one of your app's registered categories.

**Type**: string **Required**: False

#### **ThreadId**

The key that represents your app-specific identifier for grouping notifications. If you provide a Notification Content app extension, you can use this value to group your notifications together.

**Type**: string **Required**: False

### **RawContent**

The raw, JSON-formatted string to use as the payload for the notification message. If specified, this value overrides all other content for the message. For an example of the RawContent property, see Schema sample: RawContent object for a push notification.

# Note

If you specify the raw content of an APNs push notification, the message payload has to include the content-available key. The value of the content-available key has to be an integer, and can only be 0 or 1. If you're sending a standard notification, set the value of content-available to 0. If you're sending a silent (background) notification, set the value of content-available to 1. Additionally, silent notification payloads can't include the alert, badge, or sound keys. For more information, see <a href="Menerating a Remote">Generating a Remote</a> <a href="Motification">Notification</a> and <a href="Pushing Background Updates to Your App">Pushing Background Updates to Your App</a> on the Apple Developer website. If you want to send a push notification to users of the Safari web browser on a macOS laptop or desktop computer, you must specify the raw message payload. Also, the raw message payload must include a url-args array within the aps object. The url-args array is required in order to send push notifications to the Safari web browser. However, it is acceptable for the array to contain a single, empty element. For more information about Safari push notifications, see <a href="Configuring Safari Push Notifications">Configuring Safari Push Notifications</a> on the Apple Developer website.

**Type**: string **Required**: False

### PreferredAuthenticationMethod

The authentication method that you want Amazon Pinpoint to use when authenticating with APNs, CERTIFICATE or TOKEN.

Type: string

Required: False

#### **TimeToLive**

The amount of time, in seconds, that APNs should store and attempt to deliver the push notification, if the service is unable to deliver the notification the first time. If this value is 0, APNs treats the notification as if it expires immediately and the service doesn't store or try to deliver the notification again.

Amazon Pinpoint specifies this value in the apns-expiration request header when it sends the notification message to APNs.

**Type**: integer

**Required**: False

## **Priority**

The priority of the push notification. Valid values are:

- 5 Low priority, the notification might be delayed, delivered as part of a group, or throttled.
- 10 High priority, the notification is sent immediately. This is the default value. A high priority notification should trigger an alert, play a sound, or badge your app's icon on the recipient's device.

Amazon Pinpoint specifies this value in the apns-priority request header when it sends the notification message to APNs.

The equivalent values for Firebase Cloud Messaging (FCM), formerly Google Cloud Messaging (GCM), are normal, for 5, and high, for 10. If you specify an FCM value for this property, Amazon Pinpoint accepts and converts the value to the corresponding APNs value.

Type: string

Required: False

## CollapseId

An arbitrary identifier that, if assigned to multiple messages, APNs uses to coalesce the messages into a single push notification instead of delivering each message individually. This value can't exceed 64 bytes.

Amazon Pinpoint specifies this value in the apns-collapse-id request header when it sends the notification message to APNs.

**Type**: string **Required**: False

## **APNSPushType**

The type of push notification to send. Valid values are:

- alert For a standard notification that's displayed on recipients' devices and prompts a recipient to interact with the notification.
- background For a silent notification that delivers content in the background and isn't displayed on recipients' devices.
- complication For a notification that contains update information for an app's complication timeline.
- fileprovider For a notification that signals changes to a File Provider extension.
- mdm For a notification that tells managed devices to contact the MDM server.
- voip For a notification that provides information about an incoming VoIP call.

Amazon Pinpoint specifies this value in the apns-push-type request header when it sends the notification message to APNs. If you don't specify a value for this property, Amazon Pinpoint sets the value to alert or background automatically, based on the value that you specify for the SilentPush or RawContent property of the message.

For more information about the apns-push-type request header, see <u>Sending Notification</u> Requests to <u>APNs</u> on the Apple Developer website.

Type: string

Required: False

# BaiduMessage

Specifies the settings for a one-time message that's sent directly to an endpoint through the Baidu (Baidu Cloud Push) channel.

## **Body**

The body of the notification message.

**Type**: string **Required**: False

## **Substitutions**

The default message variables to use in the notification message. You can override the default variables with individual address variables.

**Type**: object **Required**: False

### **Title**

The title to display above the notification message on the recipient's device.

**Type**: string **Required**: False

### Action

The action to occur if the recipient taps the push notification. Valid values are:

- OPEN\_APP Your app opens or it becomes the foreground app if it was sent to the background.
   This is the default action.
- DEEP\_LINK Your app opens and displays a designated user interface in the app. This action uses the deep-linking features of the Android platform.
- URL The default mobile browser on the recipient's device opens and loads the web page at a URL that you specify.

**REST API Reference** Amazon Pinpoint

**Type**: string

Required: False

Values: OPEN\_APP | DEEP\_LINK | URL

## Url

The URL to open in the recipient's default mobile browser, if a recipient taps the push notification and the value of the Action property is URL.

**Type**: string

Required: False

## **SilentPush**

Specifies whether the notification is a silent push notification, which is a push notification that doesn't display on a recipient's device. Silent push notifications can be used for cases such as updating an app's configuration or supporting phone home functionality.

Type: boolean

Required: False

### **Data**

The JSON data payload to use for the push notification, if the notification is a silent push notification. This payload is added to the data.pinpoint.jsonBody object of the notification.

Type: object

Required: False

### **IconReference**

The icon image name of the asset saved in your app.

**Type**: string

Required: False

### Sound

The sound to play when the recipient receives the push notification. You can use the default stream or specify the file name of a sound resource that's bundled in your app. On an Android platform, the sound file must reside in /res/raw/.

**Type**: string **Required**: False

## **ImageUrl**

The URL of an image to display in the push notification.

**Type**: string **Required**: False

## **ImageIconUrl**

The URL of the large icon image to display in the content view of the push notification.

Type: string

Required: False

# **SmallimageIconUrl**

The URL of the small icon image to display in the status bar and the content view of the push notification.

Type: string

Required: False

## **RawContent**

The raw, JSON-formatted string to use as the payload for the notification message. If specified, this value overrides all other content for the message.

**Type**: string **Required**: False

### **TimeToLive**

The amount of time, in seconds, that the Baidu Cloud Push service should store the message if the recipient's device is offline. The default value and maximum supported time is 604,800 seconds (7 days).

**Type**: integer **Required**: False

# DefaultMessage

Specifies the default message for all channels.

# **Body**

The default body of the message.

Type: string

Required: False

## **Substitutions**

The default message variables to use in the message. You can override these default variables with individual address variables.

**Type**: object **Required**: False

# Default Push Notification Message

Specifies the default settings and content for a push notification that's sent directly to an endpoint.

# **Body**

The default body of the notification message.

Type: string

Required: False

### **Substitutions**

The default message variables to use in the notification message. You can override the default variables with individual address variables.

**Type**: object **Required**: False

### **Title**

The default title to display above the notification message on a recipient's device.

**Type**: string **Required**: False

### **Action**

The default action to occur if a recipient taps the push notification. Valid values are:

- OPEN\_APP Your app opens or it becomes the foreground app if it was sent to the background.
   This is the default action.
- DEEP\_LINK Your app opens and displays a designated user interface in the app. This setting
  uses the deep-linking features of the iOS and Android platforms.
- URL The default mobile browser on the recipient's device opens and loads the web page at a URL that you specify.

**Type**: string **Required**: False

Values: OPEN\_APP | DEEP\_LINK | URL

### Url

The default URL to open in a recipient's default mobile browser, if a recipient taps the push notification and the value of the Action property is URL.

**Type**: string **Required**: False

### **SilentPush**

Specifies whether the default notification is a silent push notification, which is a push notification that doesn't display on a recipient's device. Silent push notifications can be used for cases such as updating an app's configuration or delivering messages to an in-app notification center.

**Type**: boolean **Required**: False

#### **Data**

The JSON data payload to use for the default push notification, if the notification is a silent push notification. This payload is added to the data.pinpoint.jsonBody object of the notification.

**Type**: object **Required**: False

# DirectMessageConfiguration

Specifies the settings and content for the default message and any default messages that you tailored for specific channels.

## DefaultMessage

The default message for all channels.

Type: DefaultMessage

**Required**: False

# DefaultPushNotificationMessage

The default push notification message for all push notification channels.

Type: DefaultPushNotificationMessage

Required: False

# **APNSMessage**

The default push notification message for the APNs (Apple Push Notification service) channel. This message overrides the default push notification message (DefaultPushNotificationMessage).

Type: APNSMessage

**Required**: False

## **GCMMessage**

The default push notification message for the GCM channel, which is used to send notifications through the Firebase Cloud Messaging (FCM), formerly Google Cloud Messaging (GCM), service. This message overrides the default push notification message (DefaultPushNotificationMessage).

Type: GCMMessage

**Required**: False

## BaiduMessage

The default push notification message for the Baidu (Baidu Cloud Push) channel. This message overrides the default push notification message (DefaultPushNotificationMessage).

Type: BaiduMessage

Required: False

## **ADMMessage**

The default push notification message for the ADM (Amazon Device Messaging) channel. This message overrides the default push notification message (DefaultPushNotificationMessage).

Type: ADMMessage

**Required**: False

## **EmailMessage**

The default message for the email channel. This message overrides the default message (DefaultMessage).

Type: EmailMessage

**Required**: False

## **SMSMessage**

The default message for the SMS channel. This message overrides the default message (DefaultMessage).

Type: <u>SMSMessage</u> Required: False

## VoiceMessage

The default message for the voice channel. This message overrides the default message (DefaultMessage).

Type: VoiceMessage
Required: False

# **EmailMessage**

Specifies the default settings and content for a one-time email message that's sent directly to an endpoint.

## **Body**

The body of the email message.

**Type**: string **Required**: False

#### **Substitutions**

The default message variables to use in the email message. You can override the default variables with individual address variables.

**Type**: object **Required**: False

## **FromAddress**

The verified email address to send the email message from. The default value is the FromAddress specified for the email channel.

Type: string

Required: False

# Feedback Forwarding Address

The email address to forward bounces and complaints to, if feedback forwarding is enabled.

Type: string

Required: False

# ReplyToAddresses

The reply-to email address(es) for the email message. If a recipient replies to the email, each reply-to address receives the reply.

**Type**: Array of type string

Required: False

## **SimpleEmail**

The email message, composed of a subject, a text part, and an HTML part.

Type: SimpleEmail

Required: False

### **RawEmail**

The email message, represented as a raw MIME message.

Type: RawEmail
Required: False

# Endpoint Message Result

Provides information about the delivery status and results of sending a message directly to an endpoint.

## **DeliveryStatus**

The delivery status of the message. Possible values are:

 DUPLICATE – The endpoint address is a duplicate of another endpoint address. Amazon Pinpoint won't attempt to send the message again.

- OPT\_OUT The SendMessages API does not honor the endpoint OPT\_OUT status.
- PERMANENT\_FAILURE An error occurred when delivering the message to the endpoint. Amazon Pinpoint won't attempt to send the message again.
- SUCCESSFUL The message was successfully delivered to the endpoint.
- TEMPORARY\_FAILURE A temporary error occurred. Amazon Pinpoint won't attempt to send the message again.
- THROTTLED Amazon Pinpoint throttled the operation to send the message to the endpoint.
- UNKNOWN\_FAILURE An unknown error occurred.

**Type**: string

**Required**: True

Values: SUCCESSFUL | THROTTLED | TEMPORARY\_FAILURE | PERMANENT\_FAILURE |

UNKNOWN\_FAILURE | OPT\_OUT | DUPLICATE

#### StatusCode

The downstream service status code for delivering the message.

Type: integer

Required: True

## StatusMessage

The status message for delivering the message.

Type: string

**Required**: False

## **UpdatedToken**

For push notifications that are sent through the GCM channel, specifies whether the endpoint's device registration token was updated as part of delivering the message.

**Type**: string **Required**: False

## Messageld

The unique identifier for the message that was sent.

**Type**: string **Required**: False

## **Address**

The endpoint address that the message was delivered to.

**Type**: string **Required**: False

# **EndpointSendConfiguration**

Specifies the content, including message variables and attributes, to use in a message that's sent directly to an endpoint.

#### **Substitutions**

A map of the message variables to merge with the variables specified for the default message (DefaultMessage.Substitutions). The variables specified in this map take precedence over all other variables.

**Type**: object **Required**: False

#### Context

A map of custom attributes to attach to the message for the address. Attribute names are case sensitive.

For a push notification, this payload is added to the data.pinpoint object. For an email or text message, this payload is added to email/SMS delivery receipt event attributes.

**Type**: object **Required**: False

### **RawContent**

The raw, JSON-formatted string to use as the payload for the message. If specified, this value overrides all other values for the message.

**Type**: string **Required**: False

## **BodyOverride**

The body of the message. If specified, this value overrides the default message body.

**Type**: string **Required**: False

### **TitleOverride**

The title or subject line of the message. If specified, this value overrides the default message title or subject line.

**Type**: string **Required**: False

# **GCMMessage**

Specifies the settings for a one-time message that's sent directly to an endpoint through the GCM channel. The GCM channel enables Amazon Pinpoint to send messages to the Firebase Cloud Messaging (FCM), formerly Google Cloud Messaging (GCM), service.

## **Body**

The body of the notification message.

Type: string

Required: False

### **Substitutions**

The default message variables to use in the notification message. You can override the default variables with individual address variables.

**Type**: object

Required: False

## **Title**

The title to display above the notification message on the recipient's device.

Type: string

Required: False

### **Action**

The action to occur if the recipient taps the push notification. Valid values are:

• OPEN\_APP – Your app opens or it becomes the foreground app if it was sent to the background. This is the default action.

DEEP\_LINK – Your app opens and displays a designated user interface in the app. This action
uses the deep-linking features of the Android platform. This is a legacy FCM key and cannot be
used with FCMV1. You can use RawContent with deep link in the payload. For more information,
see Using Google Firebase Cloud Messaging (FCM) v1 payloads.

 URL – The default mobile browser on the recipient's device opens and loads the web page at a URL that you specify.

**Type**: string

Required: False

Values: OPEN\_APP | DEEP\_LINK | URL

### Url

The URL to open in the recipient's default mobile browser, if a recipient taps the push notification and the value of the Action property is URL.

**Type**: string **Required**: False

### **SilentPush**

Specifies whether the notification is a silent push notification, which is a push notification that doesn't display on a recipient's device. Silent push notifications can be used for cases such as updating an app's configuration or supporting phone home functionality.

**Type**: boolean **Required**: False

#### **Data**

The JSON data payload to use for the push notification, if the notification is a silent push notification. This payload is added to the data.pinpoint.jsonBody object of the notification.

**Type**: object **Required**: False

#### **IconReference**

The icon image name of the asset saved in your app.

**Type**: string **Required**: False

## Sound

The sound to play when the recipient receives the push notification. You can use the default stream or specify the file name of a sound resource that's bundled in your app. On an Android platform, the sound file must reside in /res/raw/.

Type: string

Required: False

## **ImageUrl**

The URL of an image to display in the push notification.

**Type**: string **Required**: False

## **ImageIconUrl**

The URL of the large icon image to display in the content view of the push notification.

**Type**: string **Required**: False

## SmallimageIconUrl

The URL of the small icon image to display in the status bar and the content view of the push notification.

**Type**: string **Required**: False

#### **RawContent**

The raw, JSON-formatted string to use as the payload for the notification message. If specified, this value overrides all other content for the message. For an example of the RawContent property, see Schema sample: RawContent object for a push notification.

**Type**: string **Required**: False

# CollapseKey

An arbitrary string that identifies a group of messages that can be collapsed to ensure that only the last message is sent when delivery can resume. This helps avoid sending too many instances of the same messages when the recipient's device comes online again or becomes active.

Amazon Pinpoint specifies this value in the Firebase Cloud Messaging (FCM) collapse\_key parameter when it sends the notification message to FCM.

Type: string

Required: False

## RestrictedPackageName

The package name of the application where registration tokens must match in order for the recipient to receive the message.

Type: string

Required: False

## **TimeToLive**

The amount of time, in seconds, that FCM should store and attempt to deliver the push notification, if the service is unable to deliver the notification the first time. If you don't specify this value, FCM defaults to the maximum value, which is 2,419,200 seconds (28 days).

Amazon Pinpoint specifies this value in the FCM time\_to\_live parameter when it sends the notification message to FCM.

**Type**: integer

Required: False

## **Priority**

The priority of the push notification. Valid values are:

- normal The notification might be delayed. Delivery is optimized for battery usage on the recipient's device. Use this value unless immediate delivery is required.
- high The notification is sent immediately and might wake a sleeping device.

Amazon Pinpoint specifies this value in the FCM priority parameter when it sends the notification message to FCM.

The equivalent values for Apple Push Notification service (APNs) are 5, for normal, and 10, for high. If you specify an APNs value for this property, Amazon Pinpoint accepts and converts the value to the corresponding FCM value.

**Type**: string **Required**: False

## PreferredAuthenticationMethod

The preferred authentication method, with valid values "KEY" or "TOKEN". If a value isn't provided then the **DefaultAuthenticationMethod** is used.

**Type**: string **Required**: False

# MessageBody

Provides information about an API request or response.

## RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

### Message

The message that's returned from the API.

**Type**: string **Required**: False

# MessageHeader

Contains the name and value pair of an message header to add to your email. You can have up to 15 MessageHeaders. A header can contain information such as the sender, receiver, route, or timestamp.

#### Name

The name of the message header. The header name can contain up to 126 characters.

**Type**: string

Required: False

### **Value**

The value of the message header. The header value can contain up to 870 characters, including the length of any rendered attributes. For example if you add the {CreationDate} attribute, it renders as YYYY-MM-DDTHH: MM:SS.SSSZ and is 24 characters in length.

Type: string

Required: False

## **RawEmail**

Specifies the contents of an email message, represented as a raw MIME message.

#### **Data**

The email message, represented as a raw MIME message. The entire message must be base64 encoded.

Type: string

**Required**: False

# **SMSMessage**

Specifies the default settings for a one-time SMS message that's sent directly to an endpoint.

## **Body**

The body of the SMS message.

Type: string

**Required**: False

### **Substitutions**

The message variables to use in the SMS message. You can override the default variables with individual address variables.

**Type**: object **Required**: False

### SenderId

The alphabetic Sender ID to display as the sender of the message on a recipient's device. Support for sender IDs varies by country. To specify a phone number as the sender, omit this parameter and use OriginationNumber instead. For more information about support for Sender ID by country, see the Amazon Pinpoint User Guide.

**Type**: string

**Required**: False

## MessageType

The SMS message type. Valid values are TRANSACTIONAL (for messages that are critical or time-sensitive, such as a one-time passwords) and PROMOTIONAL (for messsages that aren't critical or time-sensitive, such as marketing messages).

Type: string

Required: False

Values: TRANSACTIONAL | PROMOTIONAL

# Keyword

The SMS program name that you provided to AWS Support when you requested your dedicated number.

**Type**: string

Required: False

## OriginationNumber

The number to send the SMS message from. The phone number that you specify must exist in your Amazon Pinpoint account—you can't pass an arbitrary phone number. If you want to use a sender ID to send your message, omit this parameter and use SenderId instead.

**Type**: string **Required**: False

## **EntityId**

A registered Entity ID (currently only used when sending messages to recipients in India).

**Type**: string **Required**: False

## **TemplateId**

A registered Template ID (currently only used when sending messages to recipients in India).

**Type**: string **Required**: False

### MediaUrl

This field is reserved for future use.

**Type**: string **Required**: False

# Send Users Message Request

Specifies the configuration and other settings for a message to send to all the endpoints that are associated with a list of users.

### **Traceld**

The unique identifier for tracing the message. This identifier is visible only in events.

**Type**: string

Required: False

#### **Context**

A map of custom attribute-value pairs. For a push notification, Amazon Pinpoint adds these attributes to the data.pinpoint object in the body of the notification payload. Amazon Pinpoint also provides these attributes in the events that it generates for users-messages deliveries.

**Type**: object **Required**: False

## MessageConfiguration

The settings and content for the default message and any default messages that you defined for specific channels.

Type: DirectMessageConfiguration

Required: False

## **TemplateConfiguration**

The message template to use for the message.

**Type**: <u>TemplateConfiguration</u>

Required: False

### **Users**

A map that associates user IDs with <u>EndpointSendConfiguration</u> objects. You can use an <u>EndpointSendConfiguration</u> object to tailor the message for a user by specifying settings such as content overrides and message variables.

**Type**: object **Required**: True

# SendUsersMessageResponse

Provides information about which users and endpoints a message was sent to.

## **ApplicationId**

The unique identifier for the application that was used to send the message.

**Type**: string **Required**: True

## RequestId

The unique identifier that was assigned to the message request.

**Type**: string **Required**: False

#### Result

An object that indicates which endpoints the message was sent to, for each user. The object lists user IDs and, for each user ID, provides the endpoint IDs that the message was sent to. For each endpoint ID, it provides an EndpointMessageResult object.

**Type**: object **Required**: False

# SimpleEmail

Specifies the contents of an email message, composed of a subject, a text part, and an HTML part.

## Subject

The subject line, or title, of the email.

Type: SimpleEmailPart

Required: False

#### **TextPart**

The body of the email message, in plain text format. We recommend using plain text format for email clients that don't render HTML content and clients that are connected to high-latency networks, such as mobile devices.

Type: SimpleEmailPart

Required: False

#### **HtmlPart**

The body of the email message, in HTML format. We recommend using HTML format for email clients that render HTML content. You can include links, formatted text, and more in an HTML message.

**Type**: SimpleEmailPart

Required: False

### **Headers**

List of Headers for the email.

Type: Array of type MessageHeader

**Required**: False

# SimpleEmailPart

Specifies the subject or body of an email message, represented as textual email data and the applicable character set.

#### **Data**

The textual data of the message content.

**Type**: string

**Required**: False

## **Charset**

The applicable character set for the message content.

Type: string

Required: False

## **Template**

Specifies the name and version of the message template to use for the message.

## Name

The name of the message template to use for the message. If specified, this value must match the name of an existing message template.

**Type**: string **Required**: False

### Version

The unique identifier for the version of the message template to use for the message. If specified, this value must match the identifier for an existing template version. To retrieve a list of versions and version identifiers for a template, use the Template Versions resource.

If you don't specify a value for this property, Amazon Pinpoint uses the *active version* of the template. The *active version* is typically the version of a template that's been most recently reviewed and approved for use, depending on your workflow. It isn't necessarily the latest version of a template.

**Type**: string **Required**: False

# TemplateConfiguration

Specifies the message template to use for the message, for each type of channel.

# **SMSTemplate**

The SMS template to use for the message.

Type: <u>Template</u> Required: False

# **EmailTemplate**

The email template to use for the message.

Type: <u>Template</u>
Required: False

### **PushTemplate**

The push notification template to use for the message.

Type: <u>Template</u> Required: False

#### VoiceTemplate

The voice template to use for the message. This object isn't supported for campaigns.

Type: <u>Template</u>
Required: False

#### **InAppTemplate**

The InApp template to use for the message. The InApp template object is not supported for SendMessages.

Type: <u>Template</u>
Required: False

### VoiceMessage

Specifies the settings for a one-time voice message that's sent directly to an endpoint through the voice channel.

## **Body**

The text of the script to use for the voice message.

**Type**: string

Required: False

#### **Substitutions**

The default message variables to use in the voice message. You can override the default variables with individual address variables.

**Type**: object **Required**: False

#### LanguageCode

The code for the language to use when synthesizing the text of the message script. For a list of supported languages and the code for each one, see the Amazon Polly Developer Guide.

**Type**: string **Required**: False

#### VoiceId

The name of the voice to use when delivering the message. For a list of supported voices, see the Amazon Polly Developer Guide.

**Type**: string **Required**: False

### OriginationNumber

The phone number, in E.164 format, to send the voice message from. This value should be one of the dedicated long codes that's assigned to your AWS account.

**Type**: string **Required**: False

### See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

See also 1248

### SendUsersMessages

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Verify OTP**

Use this resource to check the validity of One-Time Passwords (OTPs) that were generated using the OTP Message resource.

### **URI**

/v1/apps/application-id/verify-otp

### **HTTP** methods

#### **POST**

Operation ID: VerifyOTPMessage

Verifies a One-Time Password that was generated by the OTP Message resource.

#### **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier

Verify OTP 1249

Name	Туре	Required	Description
			is displayed as the
			Project ID on the
			Amazon Pinpoint
			console.

# **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# Responses

Status code	Response model	Description
200	VerificationResponse	200 response
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed

Status code	Response model	Description
		for the specified resource (MethodNotAllowedE xception).
413	MessageBody	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	MessageBody	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

## **OPTIONS**

# **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

#### Responses

Status code	Response model	Description
200	None	The request succeeded.

### **Schemas**

# **Request bodies**

#### **POST schema**

```
{
    "DestinationIdentity": "string",
    "Otp": "string",
    "ReferenceId": "string"
}
```

# **Response bodies**

### VerificationResponse schema

```
{
    "<u>Valid</u>": boolean
}
```

# MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

# MessageBody

Provides information about an API request or response.

Schemas 1252

#### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

#### Message

The message that's returned from the API.

**Type**: string **Required**: False

## VerificationResponse

Provides information about the validity of the OTP code provided in the request.

#### **Valid**

Specifies whether the OTP is valid or not.

**Type**: boolean **Required**: False

# VerifyOTPMessageRequestParameters

Specifies the details of the OTP that you are validating.

# DestinationIdentity

The phone number, in E.164 format, that the OTP code was sent to.

**Type**: string **Required**: True

#### **Otp**

The OTP code that you are validating.

**Type**: string **Required**: True

#### ReferenceId

The reference ID that you used when you sent the OTP code to the recipient. The reference ID must be an exact match.

**Type**: string **Required**: True

#### See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

# VerifyOTPMessage

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

### **Voice Channel**

A *channel* is a type of platform that you can deliver messages to. To send a voice message, you send the message through the voice channel. Before you can use Amazon Pinpoint to send voice messages, you must enable the voice channel for an Amazon Pinpoint application.

See also 1254

The Voice Channel resource represents the status and other information about the voice channel for a specific application. You can use this resource to enable, retrieve information about, update, or disable (delete) the voice channel for an application.

### URI

/v1/apps/application-id/channels/voice

# **HTTP methods**

#### **GET**

Operation ID: GetVoiceChannel

Retrieves information about the status and settings of the voice channel for an application.

### **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

#### **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

URI 1255

### Responses

Status code	Response model	Description
200	VoiceChannelResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error,

Status code	Response model	Description
		exception, or failure (Internal
		ServerErrorException).

### **PUT**

### Operation ID: UpdateVoiceChannel

Enables the voice channel for an application or updates the status and settings of the voice channel for an application.

## **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

## **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

### Responses

Status code	Response model	Description
200	VoiceChannelResponse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error,

Status code	Response model	Description
		exception, or failure (Internal
		ServerErrorException).

### **DELETE**

## Operation ID: DeleteVoiceChannel

Disables the voice channel for an application and deletes any existing settings for the channel.

## **Path parameters**

Name	Туре	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

### **Header parameters**

Name	Туре	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

## Responses

Status code	Response model	Description
200	VoiceChannelResponse	The request succeeded.

Status code	Response model	Description
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

#### **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Voice Channel resource.

### **Path parameters**

Name	Type	Required	Description
application-id	String	True	The unique identifie r for the applicati on. This identifier is displayed as the <b>Project ID</b> on the Amazon Pinpoint console.

### Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Request bodies**

#### **PUT schema**

```
{
    "<u>Enabled</u>": boolean
}
```

# **Response bodies**

### VoiceChannelResponse schema

```
{
"ApplicationId": "string",
```

Schemas 1261

```
"IsArchived": boolean,

"Version": integer,

"CreationDate": "string",

"LastModifiedDate": "string",

"LastModifiedBy": "string",

"Id": "string",

"Enabled": boolean,

"Platform": "string",

"HasCredential": boolean
}
```

#### MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

# MessageBody

Provides information about an API request or response.

#### RequestID

The unique identifier for the request or response.

**Type**: string **Required**: False

#### Message

The message that's returned from the API.

**Type**: string **Required**: False

# $\label{lem:lemma$

Specifies the status and settings of the voice channel for an application.

#### **Enabled**

Specifies whether to enable the voice channel for the application.

**Type**: boolean **Required**: False

# VoiceChannelResponse

Provides information about the status and settings of the voice channel for an application.

### **ApplicationId**

The unique identifier for the application that the voice channel applies to.

**Type**: string **Required**: False

#### **IsArchived**

Specifies whether the voice channel is archived.

**Type**: boolean **Required**: False

#### Version

The current version of the voice channel.

**Type**: integer **Required**: False

#### CreationDate

The date and time, in ISO 8601 format, when the voice channel was enabled.

Type: string

Required: False

#### LastModifiedDate

The date and time, in ISO 8601 format, when the voice channel was last modified.

Type: string

Required: False

#### LastModifiedBy

The user who last modified the voice channel.

Type: string

Required: False

#### Id

(Deprecated) An identifier for the voice channel. This property is retained only for backward compatibility.

Type: string

Required: False

#### **Enabled**

Specifies whether the voice channel is enabled for the application.

Type: boolean

Required: False

#### **Platform**

The type of messaging or notification platform for the channel. For the voice channel, this value is VOICE.

Type: string

Required: True

#### HasCredential

(Not used) This property is retained only for backward compatibility.

**Type**: boolean **Required**: False

### See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

#### **GetVoiceChannel**

- AWS Command Line Interface
- · AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **UpdateVoiceChannel**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin

See also 1265

- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

#### **DeleteVoiceChannel**

- AWS Command Line Interface
- · AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

# **Voice Template**

A *voice template* is a type of message template that contains content and settings that you can define, save, and reuse in messages that you send through the voice channel for any of your Amazon Pinpoint applications. You can use voice templates in voice messages that you send as direct or test messages.

When you create a voice template, you specify the content and settings that you want to reuse in various components of messages that are based on the template. These components, referred to as *template parts*, can be the text of the message script and any settings that you want to apply, such as the voice to use when delivering the message. The message script can include static text and, optionally, personalized content that you define by using the Handlebars template system and message variables. When you send a message that's based on a template, Amazon Pinpoint populates the message with the content and settings that you defined in the template.

The Voice Template resource represents the repository of voice templates that are associated with your Amazon Pinpoint account. You can use this resource to create, retrieve, update, or delete a message template for messages that you send through the voice channel.

Voice Template 1266

Amazon Pinpoint supports versioning for all types of message templates. When you use the Voice Template resource to work with a template, you can use supported parameters to specify whether your request applies to only a specific version of the template or to the overall template. For example, if you update a template, you can specify whether you want to save your updates as a new version of the template or save them to the latest existing version of the template. To retrieve information about all the versions of a template, use the Template Versions resource.

### **URI**

/v1/templates/template-name/voice

### **HTTP** methods

#### **GET**

Operation ID: GetVoiceTemplate

Retrieves the content and settings of a message template for messages that are sent through the voice channel.

#### Path parameters

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can contain a maximum of 128 characters. The characters can be alphanumeric characters, underscores (_), or hyphens (-). Template names are
			case sensitive.

URI 1267

## **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# **Query parameters**

Name	Туре	Required	Description
version	String	False	The unique identifie r for the version of the message template to update, retrieve information about, or delete. To retrieve identifiers and other informati on for all the versions of a template, use the Template Versions resource.
			If specified, this value must match the identifier for an existing template version. If specified for an update operation, this value must match the identifier for the latest existing version of the template.

Name Type Required Description

This restriction helps ensure that race conditions don't occur.

If you don't specify a value for this parameter, Amazon Pinpoint does the following:

- For a get operation , retrieves informati on about the active version of the template.
- For an update operation, saves the updates to (overwrites) the latest existing version of the template, if the create-ne w-version parameter isn't used or is set to false.
- For a delete operation, deletes the template, including all versions of the template.

### Responses

Status code	Response model	Description
200	VoiceTemplateRespo nse	The request succeeded.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).

Status code	Response model	Description
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **POST**

# Operation ID: CreateVoiceTemplate

Creates a message template for messages that are sent through the voice channel.

# Path parameters

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can contain a maximum of 128 characters. The characters can be alphanumeric characters, underscores (_), or hyphens (-). Template names are case sensitive.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types,

Name	Туре	Required	Description
			expressed as MIME
			types, the client
			understands.

# Responses

Status code	Response model	Description
201	<pre>CreateTemplateMess ageBody</pre>	The request succeeded and the specified resource was created.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
409	<u>MessageBody</u>	The request failed due to a conflict with the current state of the specified resource (ConflictException).
429	MessageBody	The request failed because too many requests were sent during a certain amount of

Status code	Response model	Description
		time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **PUT**

# Operation ID: UpdateVoiceTemplate

Updates an existing message template for messages that are sent through the voice channel.

# **Path parameters**

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can contain a maximum of 128 characters. The characters can be alphanumeric characters, underscor es (_), or hyphens (-). Template names are case sensitive.

## **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

## **Query parameters**

Name	Туре	Required	Description
create-new- version	String	False	Specifies whether to save the updates as a new version of the message template.  Valid values are:  true, save the updates as a new version; and, false, save the updates to (overwrite) the latest existing version of the template.
			If you don't specify a value for this parameter, Amazon Pinpoint saves the updates to (overwrites) the latest existing version of the template. If you specify a value of true for this parameter, don't

Name Type Required Description

specify a value
for the version
parameter. Otherwise
, an error will occur.

Name	Туре	Required	Description
version	String	False	The unique identifie r for the version of the message template to update, retrieve information about, or delete. To retrieve identifiers and other informati on for all the versions of a template, use the Template Versions resource.  If specified, this value must match the identifier for an existing template version. If specified for an update operation, this value must match the identifier for the latest existing version of the template. This restriction helps ensure that race conditions don't occur.
			If you don't specify a value for this parameter, Amazon Pinpoint does the following:

Name	Туре	Required	Description
			<ul> <li>For a get operation , retrieves informati on about the active version of the template.</li> </ul>
			<ul> <li>For an update operation, saves the updates to (overwrites) the latest existing version of the template, if the create-ne w-version parameter isn't used or is set to false.</li> <li>For a delete</li> </ul>
			operation, deletes the template, including all versions of the template.

## Responses

Status code	Response model	Description
202	<u>MessageBody</u>	The request was accepted for processing. Processing may not be complete.
400	<u>MessageBody</u>	The request contains a syntax error (BadRequestException).

Status code	Response model	Description
403	<u>MessageBody</u>	The request was denied because access to the specified resource is forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

# **DELETE**

**Operation ID:** DeleteVoiceTemplate

Deletes a message template for messages that were sent through the voice channel.

### **Path parameters**

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can contain a maximum of 128 characters. The characters can be alphanumeric characters, underscores (_), or hyphens (-). Template names are case sensitive.

# **Header parameters**

Name	Type	Required	Description
accept	String	False	Indicates which content types, expressed as MIME types, the client understands.

# **Query parameters**

Name	Туре	Required	Description
version	String	False	The unique identifie r for the version of the message

Name Type Required Description

template to update, retrieve information about, or delete. To retrieve identifiers and other informati on for all the versions of a template, use the <u>Template</u>
Versionsresource.

If specified, this value must match the identifier for an existing template version. If specified for an update operation, this value must match the identifier for the latest existing version of the template. This restriction helps ensure that race conditions don't occur.

If you don't specify a value for this parameter, Amazon Pinpoint does the following:

 For a get operation , retrieves informati on about the active

Name	Туре	Required	Description
			version of the template.
			• For an update operation, saves the updates to (overwrites) the latest existing version of the template, if the create-ne w-version parameter isn't used or is set to false.
			<ul> <li>For a delete operation, deletes the template, including all versions of the template.</li> </ul>

## Responses

Status code	Response model	Description
202	MessageBody	The request was accepted for processing. Processing may not be complete.
400	MessageBody	The request contains a syntax error (BadRequestException).
403	MessageBody	The request was denied because access to the specified resource is

Status code	Response model	Description
		forbidden (ForbiddenException).
404	<u>MessageBody</u>	The request failed because the specified resource was not found (NotFoundException).
405	<u>MessageBody</u>	The request failed because the method is not allowed for the specified resource (MethodNotAllowedE xception).
413	<u>MessageBody</u>	The request failed because the payload for the body of the request is too large (RequestEntityTooLargeException).
429	<u>MessageBody</u>	The request failed because too many requests were sent during a certain amount of time (TooManyRequestsEx ception).
500	<u>MessageBody</u>	The request failed due to an unknown internal server error, exception, or failure (Internal ServerErrorException).

### **OPTIONS**

Retrieves information about the communication requirements and options that are available for the Voice Template resource.

## **Path parameters**

Name	Туре	Required	Description
template-name	String	True	The name of the message template. A template name must start with an alphanumeric character and can contain a maximum of 128 characters. The characters can be alphanumeric characters, underscor es (_), or hyphens (-). Template names are case sensitive.

## Responses

Status code	Response model	Description
200	None	The request succeeded.

# **Schemas**

# **Request bodies**

## **POST schema**

```
{
   "TemplateDescription": "string",
   "DefaultSubstitutions": "string",
   "tags": {
   },
   "Body": "string",
   "LanguageCode": "string",
```

Schemas 1283

```
"VoiceId": "string"
}
```

#### **PUT schema**

```
{
   "TemplateDescription": "string",
   "DefaultSubstitutions": "string",
   "tags": {
   },
   "Body": "string",
   "LanguageCode": "string",
   "VoiceId": "string"
}
```

## **Response bodies**

## VoiceTemplateResponse schema

```
{
    "CreationDate": "string",
    "LastModifiedDate": "string",
    "TemplateType": enum,
    "TemplateName": "string",
    "DefnultSubstitutions": "string",
    "Version": "string",
    "tags": {
    },
    "Arn": "string",
    "Body": "string",
    "LanguageCode": "string",
    "VoiceId": "string",
}
```

## CreateTemplateMessageBody schema

```
{
   "RequestID": "string",
   "Message": "string",
   "Arn": "string"
```

Schemas 1284

}

## MessageBody schema

```
{
   "RequestID": "string",
   "Message": "string"
}
```

# **Properties**

## CreateTemplateMessageBody

Provides information about a request to create a message template.

## RequestID

The unique identifier for the request to create the message template.

**Type**: string **Required**: False

## Message

The message that's returned from the API for the request to create the message template.

**Type**: string **Required**: False

#### Arn

The Amazon Resource Name (ARN) of the message template that was created.

**Type**: string **Required**: False

## MessageBody

Provides information about an API request or response.

#### RequestID

The unique identifier for the request or response.

**Type**: string

Required: False

## Message

The message that's returned from the API.

Type: string

Required: False

## VoiceTemplateRequest

Specifies the content and settings for a message template that can be used in messages that are sent through the voice channel.

## **TemplateDescription**

A custom description of the message template.

Type: string

Required: False

#### **DefaultSubstitutions**

A JSON object that specifies the default values to use for message variables in the message template. This object is a set of key-value pairs. Each key defines a message variable in the template. The corresponding value defines the default value for that variable. When you create a message that's based on the template, you can override these defaults with message-specific and address-specific variables and values.

Type: string

Required: False

**REST API Reference Amazon Pinpoint** 

#### tags



## Note

As of 22-05-2023 the tags attribute has been deprecated. After this date any value in the PUT UpdateVoiceTemplate tags attribute is not processed and an error code is not returned. The POST CreateVoiceTemplate tags attribute is processed. Use the Tags resource to add or modify tags.

(Deprecated) A string-to-string map of key-value pairs that defines the tags to associate with the message template. Each tag consists of a required tag key and an associated tag value.

Type: object Required: False

## **Body**

The text of the script to use in messages that are based on the message template, in plain text format.

**Type**: string Required: False

#### LanguageCode

The code for the language to use when synthesizing the text of the script in messages that are based on the message template. For a list of supported languages and the code for each one, see the Amazon Polly Developer Guide.

**Type**: string Required: False

#### Voiceld

The name of the voice to use when delivering messages that are based on the message template. For a list of supported voices, see the Amazon Polly Developer Guide.

Type: string

Required: False

## VoiceTemplateResponse

Provides information about the content and settings for a message template that can be used in messages that are sent through the voice channel.

#### CreationDate

The date, in ISO 8601 format, when the message template was created.

**Type**: string **Required**: True

#### LastModifiedDate

The date, in ISO 8601 format, when the message template was last modified.

**Type**: string **Required**: True

## **TemplateType**

The type of channel that the message template is designed for. For a voice template, this value is VOICE.

**Type**: string **Required**: True

Values: EMAIL | SMS | VOICE | PUSH | INAPP

## **TemplateName**

The name of the message template.

**Type**: string **Required**: True

## **TemplateDescription**

The custom description of the message template.

**Type**: string

Required: False

#### **DefaultSubstitutions**

The JSON object that specifies the default values that are used for message variables in the message template. This object is a set of key-value pairs. Each key defines a message variable in the template. The corresponding value defines the default value for that variable.

**Type**: string

Required: False

#### Version

The unique identifier, as an integer, for the active version of the message template, or the version of the template that you specified by using the version parameter in your request.

Type: string

Required: False

#### tags

A string-to-string map of key-value pairs that identifies the tags that are associated with the message template. Each tag consists of a required tag key and an associated tag value.

Type: object

Required: False

#### Arn

The Amazon Resource Name (ARN) of the message template.

Type: string

Required: False

#### **Body**

The text of the script that's used in messages that are based on the message template, in plain text format.

**Type**: string **Required**: False

## LanguageCode

The code for the language that's used when synthesizing the text of the script in messages that are based on the message template. For a list of supported languages and the code for each one, see the Amazon Polly Developer Guide.

**Type**: string **Required**: False

#### VoiceId

The name of the voice that's used when delivering messages that are based on the message template. For a list of supported voices, see the Amazon Polly Developer Guide.

**Type**: string **Required**: False

## See also

For more information about using this API in one of the language-specific AWS SDKs and references, see the following:

# GetVoiceTemplate

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2

See also 1290

- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

## CreateVoiceTemplate

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

## **UpdateVoiceTemplate**

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

See also 1291

# DeleteVoiceTemplate

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

See also 1292

# Schema samples

The following topics provide samples that use example data to show the structure of various objects of the Amazon Pinpoint API.

## **Topics**

- Schema sample: JourneyResponse object
- Schema sample: RawContent object for a push notification

# Schema sample: JourneyResponse object

When you retrieve information about a journey by sending a GET request to the <u>Journey</u> or <u>Journeys</u> resource, Amazon Pinpoint returns a JourneyResponse object. This object provides information about the status, configuration, and other settings for a journey. It also provides information about all the activities in a journey and the relationships between those activities. This information is stored in an Activities object.

An Activities object is a map that contains a set of Activity objects. It contains one Activity object for each activity in a journey. For each Activity object in the map, the key is the unique identifier for an activity and the value is one or more settings for the activity. By using an activity's unique identifier in combination with the NextActivity property, you can trace the relationships between activities in a journey.

The following sample of a JourneyResponse object includes example data that shows the structure of an Activities object. It also shows the structure of individual Activity objects that the Activities object contains. In this sample, the journey has eight activities in addition to the start activity. It has: four email (EMAIL) activities; one wait (Wait) activity; one yes/no split (ConditionalSplit) activity; one multivariate split (MultiCondition) activity; and, one random split (RandomSplit) activity.

The Activity object for each of these activities specifies the settings for the activity. For example, the first activity in the Activities object has the following characteristics and settings:

- The unique identifier is Viv6yKziaa.
- The activity is an email (EMAIL) activity.
- The activity sends an email message from the welcome@example.com address.

JourneyResponse object 1293

• The activity sends an email message that uses a template named Welcome New Subscribers.

• When participants complete the activity, they move to the multivariate split (MultiCondition) activity whose unique identifier is 1tvNWcuvXK, as specified by the NextActivity property of the email activity.

Other types of activities specify settings that apply to that type of activity. For example, the multivariate split (MultiCondition) activity in this sample specifies two paths—participants in the activity are sent down one of the two paths based on a segment condition. Similarly, the random split (RandomSplit) activity in this sample specifies two paths—50% of randomly selected participants are sent down one path and 50% of randomly selected participants are sent down the other path.

## Sample JourneyResponse object

```
{
  "Name" : "Example Corp New Subscriber Journey",
  "Schedule" : {
    "Timezone" : "UTC-08"
  },
  "StartCondition" : {
    "SegmentStartCondition" : {
      "SegmentId": "50a12f64634ca8e71e92005b9example"
    }
  },
  "StartActivity" : "OroHkysnX3",
  "Activities" : {
    "Viv6yKziaa" : {
      "EMAIL" : {
        "MessageConfig" : {
          "FromAddress" : "welcome@example.com"
        },
        "NextActivity" : "1tvNWcuvXK",
        "TemplateName" : "Welcome_New_Subscribers"
      }
    },
    "0roHkysnX3" : {
      "EMAIL" : {
        "MessageConfig" : {
          "FromAddress" : "welcome@example.com"
        },
        "NextActivity" : "p1g0HvW0hc"
```

JourneyResponse object 1294

```
}
},
"12LUtDeRst" : {
  "Wait" : {
    "NextActivity" : "Viv6yKziaa"
  }
},
"p1g0HvW0hc" : {
  "ConditionalSplit" : {
    "Condition" : {
      "Conditions" : [ { } ],
      "Operator" : "ANY"
    },
    "TrueActivity" : "12LUtDeRst",
    "FalseActivity" : "3l1znWgu9N"
  }
},
"1tvNWcuvXK" : {
  "MultiCondition" : {
    "Branches" : [ {
      "Condition" : {
        "SegmentCondition" : {
          "SegmentId" : "42d8c7eb0990a57ba1d5476a3example"
        }
      },
      "NextActivity" : "nMvVg72WFd"
    }, {
      "NextActivity" : "HSGfxJ6itl"
    }, { } ]
  }
},
"nMvVg72WFd" : {
  "EMAIL" : { }
},
"HSGfxJ6itl" : {
  "EMAIL" : { }
},
"311znWgu9N" : {
  "RandomSplit" : {
    "Branches" : [ {
     "Percentage" : 50
    }, {
      "Percentage" : 50
    } ]
```

JourneyResponse object 1295

```
}
}
}

Index of the state of the state
```

# Schema sample: RawContent object for a push notification

When you send a push notification through a push notification channel, you have the option of using a RawContent object to specify the settings and contents of the notification. Using a RawContent object can be helpful when you want to send custom data to an app for processing, as part of sending a notification. If you use a RawContent object to define the settings and contents of a push notification, the settings and content that you specify in the object override all other settings and content for the notification.

## **Overview**

A RawContent object is a raw, JSON-formatted string that contains the payload for a push notification. The data in the payload is formatted as a set of key-value pairs, with the quotation marks escaped.

The contents of a RawContent object vary, depending primarily on the target platform and push notification service. For each platform and service, the contents of this object maps to a specific message object of the Amazon Pinpoint API:

- Amazon Device Messaging For push notifications that you want to send through the ADM
  channel to the Amazon Device Messaging (ADM) service, use the fields and options defined by
  the ADMMessage object. Enclose the RawContent object in that object.
- Apple Push Notification service For push notifications that you want to send through an APNs channel to the Apple Push Notification (APNs) service, use the fields and options defined by the APNSMessage object. Enclose the RawContent object in that object.
- Baidu Cloud Push For push notifications that you want to send through the Baidu channel to the Baidu Cloud Push service, use the fields and options defined by the <u>BaiduMessage</u> object. Enclose the RawContent object in that object.

RawContent object 1296

• Firebase Cloud Messaging – For push notifications that you want to send through the GCM channel to the Firebase Cloud Messaging (FCM) service, use the fields and options defined by the GCMMessage object. Enclose the RawContent object in that object.

The preceding links go to the object definitions for the SendMessages operation, which corresponds to sending a POST request to the Messages resource. However, you can use these objects with other Amazon Pinpoint API operations that send push notifications.

The structure and design of these objects aligns with the requirements and options that are provided by the corresponding platform and push notification service. For detailed information about the options for a particular platform or service, see the documentation for the platform or service.

#### Important

Avoid putting sensitive data, such as credit card numbers, in RawContent objects. If you have to include sensitive data in an object, make sure that you encrypt the data before you send it and use the decryption features provided by the target platform.

## **Samples**

The samples in this topic use comparable example data to show the structure of two RawContent objects. The objects specify the settings and contents of a standard push notification. The notification congratulates an existing user of a fitness app because the user reported a new personal record for a running time.

The first sample is designed to be sent to APNs for delivery to the app on an iOS device:

```
{
   "APNSMessage":{
      "RawContent":"{\n\"aps\":{\n\"title\":\"Hello\",\n\"subtitle
\":\"Hello from Pinpoint!\",\n\"body\":\"Have a good day!\"\n},\n\"category\":
\T^{n}, \n\
   }
}
```

For a list of keys, see Payload key reference in the Apple developer guide.

Samples 1297

The second sample is designed to be sent to FCM for delivery to the app on an Android device:

```
{
    "GCMMessage":{
          "RawContent":"{\n \"collapse_key\":\"string\",\n\"priority\":\"string\",\n
\"time_to_live\":1234,\n\"notification\": {\n\"title\":\"Hello\",\n\"body\":\"Hello
from Pinpoint!\",\n \"android_channel_id\":\"string\",\n\"body_loc_args\":[\n\"string
\"\n],\n\"body_loc_key\":\"string\",\n\"click_action\":\"string\",\n\"color\": \"string
\",\n\"icon\":\"string\",\n\"string\",\n\"title_loc_args
\":[\n\"string\"\n],\n\"title_loc_key\":\"string\"\n},\n\"data\":{\n\"customKey\":\"customValue\"\n}\n}"
    }
}
```

Amazon Pinpoint also supports FCM v1 payloads in the raw content, see <u>Using Google Firebase</u> Cloud Messaging (FCM) v1 payloads.

Samples 1298

# **Document history**

The following table describes the important changes to the documentation since the last release of Amazon Pinpoint.

• API version: 2016-12-01 (latest)

• Latest documentation update: April 4, 2024

Change	API Version	Description	Date Changed
End of support notice	2016-12-01	End of support notice: On October 30, 2026, AWS will end support for Amazon Pinpoint. After October 30, 2026, you will no longer be able to access the Amazon Pinpoint console or Amazon Pinpoint resources (endpoints, segments, campaigns , journeys, and analytics). For more information, see Amazon Pinpoint end of support. Note: APIs related to SMS, voice, mobile push, OTP, and phone number validate are not impacted by this change and are	May 20, 2025

Change	API Version	Description	Date Changed
		supported by AWS End User Messaging.	
Changed feature	2016-12-01	Added support for email headers.	May 7, 2024
Changed feature	2016-12-01	Updated the RawContent samples for push notifications.	April 4, 2024
Changed feature	2016-12-01	Added support for Token Credentials when authenticating with GCM.	July 28, 2023
Changed feature	2016-12-01	Added support for journey maximum number of messages that can be sent to an endpoint in a given timeframe.	June 26, 2023
New feature	2016-12-01	Added support for journey run metrics.	April 25, 2023

Change	API Version	Description	Date Changed
Changed feature	2016-12-01	Updated support for Tags in UpdateCam paign , UpdateSeg ment , UpdateEma ilTemplat e , UpdateInA ppTemplat e , UpdatePus hTemplate , UpdateSms Template and UpdateVoi ceTemplate .	April 18, 2023
New feature	2016-12-01	Added support for sending and validatin g OTP messages.	November 26, 2021
New feature	2016-12-01	Added support for sending in-app messages.	November 1, 2021

Change	API Version	Description	Date Changed
Changed feature	2016-12-01	Enhanced support for sending campaigns through custom channels: added CustomDel iveryConf iguration and CampaignC ustomMess age objects; and, deprecated the Delivery value for the CampaignHook object, which was part of a public beta release.	April 23, 2020
New sample	2016-12-01	Added examples of RawContent objects that contain sample data.	April 2, 2020
New feature	2016-12-01	Added support for integrating recommender models with email, push notification, and SMS message templates.	March 4, 2020
New sample	2016-12-01	Added an example of a JourneyRe sponse object that contains sample data.	January 20, 2020

Change	API Version	Description	Date Changed
New feature	2016-12-01	Added versioning support for all types of message templates .	December 20, 2019
New feature	2016-12-01	Added support for using and managing message templates for messages that are sent through the voice channel. Also added support for specifying default values for message variables in all types of message templates .	November 18, 2019
New feature	2016-12-01	Added support for using and managing journeys, and querying analytics data for journeys.	October 31, 2019
New feature	2016-12-01	Added support for using and managing message templates for messages that are sent through the email or SMS channel, or a push notification channel.	October 7, 2019

Change	API Version	Description	Date Changed
New feature	2016-12-01	Added support for querying analytics data for a subset of metrics that apply to applications (projects ) and campaigns.	July 24, 2019
New feature	2016-12-01	Added support for deleting custom attributes from applications (projects ).	May 15, 2019
New feature	2016-12-01	Added support for tagging applications (projects), campaigns, and segments.	February 27, 2019
New feature	2016-12-01	Added support for recording events and associating them with endpoints.	August 7, 2018
Deprecated feature	2016-12-01	Removed the external ID key (ExternalId property) requireme nt for streaming events and importing endpoint definitions.	October 26, 2017
New feature	2016-12-01	Added channels for the Amazon Device Messaging (ADM) and Baidu Cloud Push services.	September 27, 2017

Change	API Version	Description	Date Changed
New feature	2016-12-01	Added support for streaming events to Amazon Data Firehose and Amazon Kinesis Data Streams.	March 24, 2017
General availability	2016-12-01	This release introduce s Amazon Pinpoint and the Amazon Pinpoint API.	December 1, 2016