

Application portfolio assessment strategy for AWS Cloud migration

AWS Prescriptive Guidance



Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS Prescriptive Guidance: Application portfolio assessment strategy for AWS Cloud migration

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Introduction	1
Overview	. 1
Targeted business outcomes	4
Methodology and approach	5
Portfolio-level assessment	
Application-level assessment	5
Discovery acceleration and initial planning	6
High-level objectives and actions	. 7
Outcomes	8
Best practices	8
Prioritized applications assessment	9
High-level objectives and actions	9
Outcomes	10
Best practices	11
Portfolio analysis and migration planning	11
High-level objectives and actions	11
Outcomes	13
Best practices	13
Continuous assessment and improvement	14
High-level objectives and actions	14
Outcomes	15
Best practices	15
Next steps	17
Resources	18
Document history	19
Glossary	20
#	20
Α	21
В	24
С 2	26
D	29
ΕΞ	33
F	35
G	37

Η	
Ι	
L	41
М	
O	
Р	
Q	
R	
S	
т	
U	
V	
W	
Ζ	

Application portfolio assessment strategy for AWS Cloud migration

German Goncalves and Mark Berner, Amazon Web Services (AWS)

May 2024 (document history)

Migrating applications and associated infrastructure to the cloud, requires a strategic and methodical approach to progressively discover and analyze IT assets. These analyses are then used to create high-confidence migration wave plans for implementing migration programs and business transformation. This Amazon Web Services (AWS) Prescriptive Guidance strategy will help you understand the key stages to successfully assess your application portfolio, including the following:

- Identifying key stakeholders and existing sources of data
- Implementing automated discovery tooling
- Progressively enriching the application portfolio dataset
- Prioritizing applications
- Establishing a migration wave plan
- Continuously assessing the portfolio

This strategy is complemented by an <u>Application portfolio assessment guide for AWS Cloud</u> <u>migration</u> that contains detailed how-to guidance.

Overview

When planning to migrate and modernize a portfolio of applications, organizations of any size must progressively rediscover and analyze their current IT estate. The proactive and progressive approach of this strategy recognizes that not all data about applications and infrastructure (compute, storage, networks) are required upfront in order to move forward. What at first seems to be a complex endeavor can be separated into smaller steps, with specific outcomes, by applying a defined approach.


At a high-level, *application portfolio assessment* is the process of gathering application, infrastructure, and business context data to discover, analyze, and plan for moving the portfolio

to the cloud. Assessment activities are critical for any business embarking on long-running cloud programs because the nature of that journey involves risk and cost. It is not only applications that are moving to the cloud, it is the business itself being transformed. Therefore, from deciding to move ahead, to enabling actual migrations, a data-backed analysis is key. The analysis informs the process, reduces risk and cost, aligns business and IT priorities, and accelerates business outcomes.

Application portfolio assessment is typically associated with early stages of migration. This is when there is a strong need for data and analysis to inform the business case and produce initial plans. However, after the early stages, application and infrastructure assessment becomes a continuous and interactive set of activities across the entire lifecycle of long-running programs. The progressive and continuous assessment approach, with varying levels of data quantity and fidelity, enhances the understanding of the portfolio until it is migrated. Then the approach focuses on assessment for further optimization and modernization.

Other migration program activities, such as governance, people and skills, landing zone, security, and operations, have dependencies on the data and analysis resulting from application portfolio assessment. For example, mobilizing a migration program, estimating cost, and producing a business case requires a clear understanding of the application portfolio. Also, platform teams shaping the AWS foundations or extending the current AWS environment require portfolio data to create and implement designs. Migration teams use that same data to develop patterns, establish cutover runbooks, and define migration tooling.

The following diagram shows how the stages of portfolio assessment correspond to the AWS phases of migration. The discovery acceleration and initial planning stage begins in the assess phase, typically during the first five weeks. Prioritized applications assessment, in the sixth and seventh weeks, spans the assess and mobilize phases. The portfolio analysis and migration planning stage happens in weeks 8–14, in the mobilize phase. The continuous assessment and improvement stage happens in the migrate and modernize phase, from week 15 until the end of the migration program. This timeline is indicative. The actual duration of the stages will depend on the overall program organization.



Long-term portfolio assessment outcomes, such as maintaining an up-to-date inventory of IT assets and dependencies, remain constant throughout the journey. However, data requirements, specific objectives, and key stakeholders vary at each stage. In this strategy, the portfolio journey is represented as four main stages aligned to data requirements for the portfolio job at hand:

- Discovery acceleration and initial planning Updating the current understanding of the portfolio, creating a directional business case, establishing base rationalization models for migration, and identifying initial migration candidates
- 2. **Prioritized applications assessment** Performing a detailed assessment, initial design, and migration strategy of prioritized applications that can be moved in the short-term to reduce time-to-value by providing migration experience and establishing cloud foundations
- 3. **Portfolio analysis and migration planning** Building a complete and up-to-date view of the application portfolio by iteratively enriching the dataset, closing data gaps, evolving the business case, and creating high-confidence migration wave plans
- 4. **Continuous assessment and improvement** Enabling migrations at scale by producing detailed application and technology assessments for each migration wave, iterating the migration wave plan, and further assessing migrated workloads for optimization and modernization

Targeted business outcomes

- Obtainment of a complete inventory of applications, infrastructure, and dependencies.
- Early identification of pilot applications, or initial migration candidates, for detailed assessment. The detailed assessment includes initial target architecture design and migration strategy.
- Portfolio rationalization for migration based on defined application prioritization criteria and 6 Rs strategy decision tree.
- Creation of a high-confidence application migration wave plan for the entire portfolio.
- A detailed per-wave and sequential application and technology assessment for migration.
- A detailed assessment of opportunities for further optimizing and modernizing migrated workloads.

Methodology and approach

The strategic approach to application portfolio assessment is to establish a series of stages that will run in parallel to other program workstreams. These stages will progressively collect and analyze application and infrastructure data while pivoting between two main levels: portfolio level and application level.

Portfolio-level assessment

The *portfolio-level assessment* focuses on collecting and analyzing general data from applications and infrastructure to obtain a high-level view of the entire portfolio. This view includes high-level technical and business attributes such as application names, environment, product versions, business and technical criticality, and performance and utilization metrics. This is key to understanding priorities and the scope of the program, creating high-confidence plans, managing the portfolio, and informing the business case.


Application-level assessment

The *application-level assessment* focuses on the architecture and technology of each application. It includes creating AWS designs and defining migration strategies and patterns that support the move to the cloud and further optimization. This type of assessment is typically time consuming, and it's approached in a sequence of smaller chunks, aligned to migration waves, throughout the project lifecycle.

As the migration date approaches, detailed application information, down to the technology level, is required for informing security, operations, infrastructure deployment, and migration activities. Therefore, detailed application-level discovery is targeted at those applications that are candidates to be migrated in the near-term. Detailed discovery is then performed for the next group of applications, in a slightly overlapped sequence, throughout the program lifecycle and in parallel to ongoing migrations.

The following diagram shows the key activities for each stage of assessment and how they pivot between *portfolio-level* assessment (identification of sources of data, high-level discovery, initial inventory, prioritization, and directional business case) and *application-level* assessment (detailed discovery, AWS design, and migration strategy). Portfolio-level and application-level assessments represent the breadth and depth of information required.

Portfolio Level and Application Level Assessments INDICATIVE TIMELINE



Discovery acceleration and initial planning

This stage of portfolio assessment occurs early in the cloud journey. It's typically performed close to an executive decision to move an existent portfolio of applications to the cloud or during exploratory phases. The discovery acceleration and initial planning stage focuses on the following:

- Understanding business drivers
- Identifying existent sources of data
- Evaluating the need for automated discovery tooling
- Establishing base models for application prioritization and migration strategy selection

These activities lead to the following:

- A preliminary analysis of the portfolio
- · Identification of initial migration candidates
- The creation of a directional business case for migration
- An outline of initial plans.

The key is to understand who the stakeholders of this stage are and what data requirements they have for moving forward. Stakeholders range from board members and CxOs, to business unit leads, senior managers, and application owners.

🚺 Tip

For details and guidance, see the relevant section in the <u>Application portfolio assessment</u> guide for AWS Cloud migration.

High-level objectives and actions

- Determine stakeholders Who is impacted by the migration? Who are the decision-makers? Who benefits from this migration? Who is responsible for performing the migration?
- Identify business drivers What business outcomes and goals are being pursued as a result of migration (for example, business transformation, cost reduction, agility)? This information will be a key determinant of migration strategy and prioritization.
- Identify existing sources of data Identify and document existing sources of data, such as people, tooling, documentation. Assign a level of trust to each source. For example, programmatic or automated sources are more trusted than institutional knowledge or documents. Over time, lower-trust data sources will be replaced with higher-trust data sources.
- Build an initial inventory of applications and infrastructure Identify application names, primary function, criticality, IT environments, high-level compliance and regulatory requirements, and known dependencies. Which IT assets are associated to the applications? Identify product names and versions, historic performance data, known issues, and risks.
- Identify data gaps and discovery needs Analyze data gaps and evaluate the need to procure automated discovery tooling. Discovery tool investment decisions should be backed by a need to increase overall confidence in data for accurate analysis. To maintain an up-to-date view of the application portfolio, we recommend specialized tooling for workload discovery.
- Deploy discovery tooling Procure, install, and configure discovery tooling, if applicable, and create a roll-out plan to targeted systems. Two weeks of programmatic data collection to all targeted systems provide enough data to achieve the outcomes of this stage. However, to refine the outputs, ongoing data collection is required in later stages.
- Collect Total Cost of Ownership (TCO) data Use collected data to produce and update TCO reports and to create a directional business case. For more information, see the <u>Best practices</u> section.

- Use application-rationalization models Establish or adopt base application rationalization models for migration. Include the selection of key application attributes, weighting for prioritization, and initial R type (rehost, replatform, refactor (re-architect), repurchase, retain, retire) based on the 6 Rs decision tree.
- Identify initial migration candidates What applications could be moved now to establish or extend AWS foundations and gain experience? At this stage, the model should prioritize simple workloads with low levels of dependencies (for example, zero-three).
- Plan ongoing assessments Plan for the next portfolio assessment activities, such as performing a detailed assessment of prioritized workloads.
- Plan communications Establish a communication plan or cadence for your stakeholders and a scope-control mechanism. It is normal for the scope to change as the migration program progresses. Ensure that there is a single source of truth for portfolio data and that changes to the scope are tracked, assessed, and communicated.

Outcomes

- Documented business drivers, outcomes, goals, and technical guiding principles.
- An initial inventory of applications and infrastructure, and identified data gaps. This is an initial view of the portfolio that will be iterated and refined in further stages.
- A directional business case and estimated cost to migrate.
- A list of three-five applications that are initial migration candidates.
- A communication plan for portfolio-related activities, milestones, and scope changes.

Best practices

- Focus on the stage objectives and keep analysis at a high level. Adopt a progressive approach to data collection, and do not wait for a complete dataset before moving forward.
- Avoid analysis paralysis. Focus on identifying the data gaps and driving actions to close those gaps.
- Procure specialized discovery tooling. Programmatic data, typically obtained through automated tooling, has the higher level of trust and should be preferred before written documentation, static data, and institutional knowledge.
- Work with the identified stakeholders to remove blockers.

- Assign a single-threaded leader to the application portfolio assessment workstream.
- Consider using <u>Migration Evaluator</u> for your directional business case, or explore the AWS Partner Network tools and offerings for <u>TCO and AWS pricing</u>.
- Consider <u>AWS Professional Services</u> and <u>AWS Partners</u> that could help you accelerate business outcomes.

Prioritized applications assessment

After initial application migration candidates are identified, a detailed assessment of those applications accelerates migration outcomes by enabling cloud foundations to be designed and implemented. If those foundations already exist, the application assessment assists with further developing the target environment to meet migration requirements. This stage provides enough data to produce target architecture designs and to define a migration strategy for prioritized applications that can be migrated now to gain confidence and experience. The output of this stage will feed directly into other program workstreams, such as security, migration, and landing zone for implementation. For more information, see <u>Mobilize your organization to accelerate large-scale migrations</u>.

Similarly to the previous stage, identifying key stakeholders is instrumental to understanding data requirements. Business unit leads and senior managers, application owners, application and enterprise architects, and migration and platform leads are typically involved.

🚺 Tip

For details and guidance, see the relevant section in the <u>Application portfolio assessment</u> guide for :AWS Cloud migration.

High-level objectives and actions

- Confirm prioritized applications Establish a baseline for the list of applications that will be analyzed in detail. To accelerate time-to-value. We recommend keeping this list in the range of three-five applications.
- Identify stakeholders Who is impacted by and who benefits from the migration of these applications? Ensure that these stakeholders are part of the detailed analysis of the prioritized applications.

- Create detailed application assessments Thoroughly investigate the current state architecture and technology, strategic roadmap, application lifecycle, operations, security, dependencies, risks, and issues for the prioritized applications. What is the level of confidence on the current understanding of this application?
- Map out an initial AWS design Include target architecture and technology choices, architectural decisions and patterns, licensing, security, operational, functional and nonfunctional requirements:
 - What is the architecture for this application in the cloud, and how will it operate there?
 - Can this design be implemented and operated?
 - Do you need to deploy cloud foundations or extend them?

Depending on your current level of cloud adoption, a complete design might not be achievable if these applications represent your first cloud deployments and the broader platform decisions have not yet been made or a wider migration program has not been established. However, the process of designing the target architecture will surface foundational requirements and current gaps or blockers, and it will clarify actions that must be taken.

- Migration strategy and patterns Evaluate preferred approaches and available automations, migration tooling and techniques, and cutover considerations. What is the preferred migration approach? Can it be documented as a reusable pattern? What migration tools are available? What are the high-level cutover activities?
- Estimate the run rate for these applications Use historical performance data and available tooling to project costs when running these applications on AWS. Is this a predictable workload? Are there any identified usage patterns? What is the effort required to migrate?

Outcomes

- Validated list of prioritized applications
- List of identified application-migration stakeholders
- Documented current state architecture
- Documented initial target architecture and migration strategy for migration candidates
- Identified migration patterns and tooling
- Documented platform requirements, such as security, AWS infrastructure, and operations
- Documented cutover considerations as input for migration planning

• Estimated run rate

Best practices

- Reuse architectural patterns defined by your organization.
- Document architectural decisions for these applications as patterns that can be reused in subsequent detailed assessments.
- Identify key dependencies and address them. What is preventing this application from moving to the cloud now?
- Consult <u>AWS Well-Architected</u> and <u>security best practices</u>.
- Consult the <u>AWS Pricing Calculator</u> to estimate the cost for your architecture solution.
- The sooner migrations are started the sooner data gaps will become clearer. Plan to migrate the prioritized applications while performing the next stage of portfolio assessment.

Portfolio analysis and migration planning

This stage focuses on iterating the portfolio-level view, closing data gaps, and obtaining more data to produce high-confidence migration wave plans for the entire portfolio.

The stakeholders of this stage are typically a mix of the previous two stages. They include CxOs and senior leaders, migration and platform teams, and IT and Enterprise architects. The key is to augment the portfolio-level data fidelity through iteration and refinement.

🚺 Tip

For details and guidance, see the relevant section in the <u>Application portfolio assessment</u> guide for AWS Cloud migrations.

High-level objectives and actions

• Establish a baseline for the application portfolio and associated infrastructure – Iterate portfoliolevel data, building up from the <u>discovery acceleration and initial planning</u> stage, to close gaps and produce a high-level view of the entire application portfolio. At this stage, it is key to refine application-to-infrastructure mapping, usage data, and application metadata attributes. These attributes include ownership, criticality, and the primary function of each application.

- Obtain and analyze dependency data (typically by using specialized discovery tooling) To
 validate applications and aid the creation of migration wave plans, high-confidence applicationdependency data is key at this stage. Dependency data includes communication data, such as
 volume and frequency of communication between systems, and nontechnical dependencies,
 such as operational considerations. These dependencies dictate which applications must move at
 the same time and which applications can operate from different locations.
- Identify and validate compliance and regulatory requirements Identify and validate frameworks, rules, evidence, and documentation requirements.
- Convert assumptions into facts How much has been assumed in previous stages? It is key in this stage to reduce the number of assumptions to a minimum.
- Establish a baseline for the migration portfolio-rationalization models Iterate models from previous stages (for example, application prioritization criteria and the 6 Rs decision tree).
 Validate the models by applying them to the entire application portfolio.
- Document measurable business outcomes To align migration waves to business objectives, identify business outcomes and associated key primary indicators (KPI) for each migration wave.
- Evolve the directional business case Replace benchmarks with actual utilization and cost data, and refine migration costs in line with the updated wave plan. Broaden the coverage to include the full expected value from each expected business outcome, such as cost reduction, IT productivity improvement, increased resilience, and greater agility.
- Document and communicate key dates Document and communicate compelling events (such as data center exit dates, contracts and licensing agreement renewals), application release cycles, migration dates to avoid, technology refresh cycles, and people availability.
- Analyze cost and risk for wave planning How much parallel change can be supported or tolerated? Analyze people requirements, risks identification and mitigation, criticality, and impact.
- Identify skills requirements What is the projected level of readiness to support the different workload types in the cloud? Does the migration wave plan align to the projected readiness? Can the support teams meet the wave plan requirements?
- Document internal processes Document information about current processes impacting cloud migration, such as change management, service management, architectural review boards, risk assessments, and approval workflows.
- Create a migration wave plan To create a wave plan, combine all the elements previously
 discussed in this list. Apply prioritization criteria to the portfolio, and analyze dependencies to
 create waves of applications. Incorporate platform and migration readiness into the migration

wave plan. How long does it take to implement AWS infrastructure and services? What is required for security and operational readiness? What is the impact to the wave duration? How long does it take to implement migration tooling? How long does it take to replicate data, considering network and systems usage? What is the cutover window? How long does it take to roll back?

 Update workstreams – Establish a process to feed portfolio and detailed application assessment data into Migration and Landing Zone workstreams. Ensure these workstreams clearly outline their data requirements.

Outcomes

- High-fidelity application and infrastructure inventory
- High-level migration strategy for each application
- Detailed business case
- High-confidence migration wave plan

Best practices

- Ensure that applications are evenly distributed in the migration wave plan. Consider criticality and complexity to avoid pockets of complexity that could create blockers or delay migrations.
- Prioritize noncritical, simple applications in the first two waves.
- Focus on combining prioritization, dependencies, and business drivers to iterate the wave plan.
- Consider cloud infrastructure, security, and operational readiness (including skills) when creating the wave plan.
- Construct wave plans so that the length of a migration wave, typically ranging 4-8 weeks, outlines the application journey. Each wave should cover the following:
 - Detailed assessment
 - Migration readiness
 - Infrastructure build and test
 - Data transfer
 - Cutover of the applications in the wave
 - Wave closure (for example, lessons learned, post-migration issues resolution)

Define and use a default wave structure to apply a migration <u>factory model</u> that includes detailed assessment, design, implementation, test, cutover, and validation.

Continuous assessment and improvement

After a migration program has been established to implement a migration wave plan, the application portfolio assessment focuses on continuous iteration of the portfolio data and detailed assessments for each wave. In addition, as workloads are migrated, these can be further assessed for optimization and modernization. This stage focuses on gathering application and infrastructure details to validate target architecture and technology choices. It also focuses on outlining specific platform requirements, such as security, operations, and cloud infrastructure, that can be converted into implementation designs and migration cutover plans for each migration wave.

🚺 Tip

For more details and guidance, see the relevant section in the <u>Application portfolio</u> assessment guide for AWS Cloud migration.

High-level objectives and actions

- Application assessments Group detailed application assessments equivalent to migration waves. For each wave of applications, follow the same objectives and actions that are defined in the <u>Prioritized applications assessment</u> section.
- Application optimization and modernization assessment Address technical debt, new business
 requirements, usage and cost analysis, best practices, transformation patterns, industry trends,
 pain points, and operational efficiency. What have you learned about this application running in
 the cloud? What <u>new AWS services</u> have been released? What are the available architectures for
 this application? What benefits do those architectures provide?
- Evolving and tracking the business case Track the benefits achieved against the baseline detailed business case to maintain stakeholder support and keep momentum. Also, expand the case to include further modernization to drive value from improved resilience and agility. Provide information about deeper cost optimization using newly acquired post-migration usage data, giving leadership the basis to prioritize ongoing investment in the program.
- Optimization and evolution Iterate and expand portfolio rationalization models for optimization and portfolio evolution.

Outcomes

Migration outcomes include the following:

- Validated migration scope for each wave
- Documented target architecture and migration strategy for applications in a given migration wave
- Identified and validated migration patterns and tooling
- Documented platform requirements, such as security, AWS infrastructure, and operations, and migration cutover considerations for each wave

Optimization outcomes include the following:

- Portfolio rationalization models and business outcomes
- Refined business case articulating the additional value that further optimization and modernization provides, including which applications to prioritize.
- Proposed architecture and technology changes and expected benefits
- Platform requirements, such as security, AWS infrastructure, and operations
- Implementation plan

Best practices

- Reuse architectural patterns defined by your organization. Consider using <u>AWS Service Catalog</u> to create and manage catalogs of IT services that are approved by your organization for use on AWS.
- Document architectural and technology decisions that can be converted into reusable patterns.
- Identify key dependencies. What is preventing this application from moving to the cloud now? What is preventing this application from being optimized or modernized after it is in AWS?
- Consult AWS Well-Architected and security best practices.
- Maintain alignment of migration and optimization or modernization activities to business outcomes.
- Maintain the evolving business case. Track benefits realization as the basis for steering the program.

• Consider long-term strategic views of the application portfolio in the context of evolving business drivers.

Next steps

- Identify the application portfolio assessment stage that aligns with where your organization is in the cloud journey.
- Get started with the application portfolio assessment guide.

Resources

Guides and strategies

- Application portfolio assessment guide for AWS Cloud migration
- AWS Migration Acceleration Program
- Mobilize your organization to accelerate large-scale migrations

Assistance

- AWS Professional Services
- AWS Migration and Modernization Software Partners

Tools

- Migration Evaluator
- Discovery, Planning, and Recommendation migration tools
- Business Case Analysis migration tools
- AWS Pricing/TCO tools
- AWS Migration Hub

Glossary

• Definitions for migration and modernization terms

Document history

The following table describes significant changes to this strategy. If you want to be notified about future updates, you can subscribe to an <u>RSS feed</u>.

Change	Description	Date
=	Changed name of the first stage to <i>Discovery accelerat</i> <i>ion and initial planning</i> , updated diagrams, and updated the <u>list of resources</u> .	May 30, 2024
=	Initial publication	November 12, 2021

AWS Prescriptive Guidance glossary

The following are commonly used terms in strategies, guides, and patterns provided by AWS Prescriptive Guidance. To suggest entries, please use the **Provide feedback** link at the end of the glossary.

Numbers

7 Rs

Seven common migration strategies for moving applications to the cloud. These strategies build upon the 5 Rs that Gartner identified in 2011 and consist of the following:

- Refactor/re-architect Move an application and modify its architecture by taking full advantage of cloud-native features to improve agility, performance, and scalability. This typically involves porting the operating system and database. Example: Migrate your onpremises Oracle database to the Amazon Aurora PostgreSQL-Compatible Edition.
- Replatform (lift and reshape) Move an application to the cloud, and introduce some level
 of optimization to take advantage of cloud capabilities. Example: Migrate your on-premises
 Oracle database to Amazon Relational Database Service (Amazon RDS) for Oracle in the AWS
 Cloud.
- Repurchase (drop and shop) Switch to a different product, typically by moving from a traditional license to a SaaS model. Example: Migrate your customer relationship management (CRM) system to Salesforce.com.
- Rehost (lift and shift) Move an application to the cloud without making any changes to take advantage of cloud capabilities. Example: Migrate your on-premises Oracle database to Oracle on an EC2 instance in the AWS Cloud.
- Relocate (hypervisor-level lift and shift) Move infrastructure to the cloud without purchasing new hardware, rewriting applications, or modifying your existing operations. You migrate servers from an on-premises platform to a cloud service for the same platform. Example: Migrate a Microsoft Hyper-V application to AWS.
- Retain (revisit) Keep applications in your source environment. These might include applications that require major refactoring, and you want to postpone that work until a later time, and legacy applications that you want to retain, because there's no business justification for migrating them.

• Retire – Decommission or remove applications that are no longer needed in your source environment.

Α

ABAC

See <u>attribute-based access control</u>. abstracted services

See managed services.

ACID

See atomicity, consistency, isolation, durability.

active-active migration

A database migration method in which the source and target databases are kept in sync (by using a bidirectional replication tool or dual write operations), and both databases handle transactions from connecting applications during migration. This method supports migration in small, controlled batches instead of requiring a one-time cutover. It's more flexible but requires more work than <u>active-passive migration</u>.

active-passive migration

A database migration method in which in which the source and target databases are kept in sync, but only the source database handles transactions from connecting applications while data is replicated to the target database. The target database doesn't accept any transactions during migration.

aggregate function

A SQL function that operates on a group of rows and calculates a single return value for the group. Examples of aggregate functions include SUM and MAX.

AI

See artificial intelligence.

AlOps

See artificial intelligence operations.

anonymization

The process of permanently deleting personal information in a dataset. Anonymization can help protect personal privacy. Anonymized data is no longer considered to be personal data. anti-pattern

A frequently used solution for a recurring issue where the solution is counter-productive, ineffective, or less effective than an alternative.

application control

A security approach that allows the use of only approved applications in order to help protect a system from malware.

application portfolio

A collection of detailed information about each application used by an organization, including the cost to build and maintain the application, and its business value. This information is key to <u>the portfolio discovery and analysis process</u> and helps identify and prioritize the applications to be migrated, modernized, and optimized.

artificial intelligence (AI)

The field of computer science that is dedicated to using computing technologies to perform cognitive functions that are typically associated with humans, such as learning, solving problems, and recognizing patterns. For more information, see <u>What is Artificial Intelligence</u>? artificial intelligence operations (AIOps)

The process of using machine learning techniques to solve operational problems, reduce operational incidents and human intervention, and increase service quality. For more information about how AIOps is used in the AWS migration strategy, see the <u>operations</u> integration guide.

asymmetric encryption

An encryption algorithm that uses a pair of keys, a public key for encryption and a private key for decryption. You can share the public key because it isn't used for decryption, but access to the private key should be highly restricted.

atomicity, consistency, isolation, durability (ACID)

A set of software properties that guarantee the data validity and operational reliability of a database, even in the case of errors, power failures, or other problems.

attribute-based access control (ABAC)

The practice of creating fine-grained permissions based on user attributes, such as department, job role, and team name. For more information, see <u>ABAC for AWS</u> in the AWS Identity and Access Management (IAM) documentation.

authoritative data source

A location where you store the primary version of data, which is considered to be the most reliable source of information. You can copy data from the authoritative data source to other locations for the purposes of processing or modifying the data, such as anonymizing, redacting, or pseudonymizing it.

Availability Zone

A distinct location within an AWS Region that is insulated from failures in other Availability Zones and provides inexpensive, low-latency network connectivity to other Availability Zones in the same Region.

AWS Cloud Adoption Framework (AWS CAF)

A framework of guidelines and best practices from AWS to help organizations develop an efficient and effective plan to move successfully to the cloud. AWS CAF organizes guidance into six focus areas called perspectives: business, people, governance, platform, security, and operations. The business, people, and governance perspectives focus on business skills and processes; the platform, security, and operations perspectives focus on technical skills and processes. For example, the people perspective targets stakeholders who handle human resources (HR), staffing functions, and people management. For this perspective, AWS CAF provides guidance for people development, training, and communications to help ready the organization for successful cloud adoption. For more information, see the <u>AWS CAF website</u> and the <u>AWS CAF whitepaper</u>.

AWS Workload Qualification Framework (AWS WQF)

A tool that evaluates database migration workloads, recommends migration strategies, and provides work estimates. AWS WQF is included with AWS Schema Conversion Tool (AWS SCT). It analyzes database schemas and code objects, application code, dependencies, and performance characteristics, and provides assessment reports.

В

bad bot

A bot that is intended to disrupt or cause harm to individuals or organizations.

BCP

See business continuity planning.

behavior graph

A unified, interactive view of resource behavior and interactions over time. You can use a behavior graph with Amazon Detective to examine failed logon attempts, suspicious API calls, and similar actions. For more information, see <u>Data in a behavior graph</u> in the Detective documentation.

big-endian system

A system that stores the most significant byte first. See also endianness.

binary classification

A process that predicts a binary outcome (one of two possible classes). For example, your ML model might need to predict problems such as "Is this email spam or not spam?" or "Is this product a book or a car?"

bloom filter

A probabilistic, memory-efficient data structure that is used to test whether an element is a member of a set.

blue/green deployment

A deployment strategy where you create two separate but identical environments. You run the current application version in one environment (blue) and the new application version in the other environment (green). This strategy helps you quickly roll back with minimal impact.

bot

A software application that runs automated tasks over the internet and simulates human activity or interaction. Some bots are useful or beneficial, such as web crawlers that index information on the internet. Some other bots, known as *bad bots*, are intended to disrupt or cause harm to individuals or organizations.

botnet

Networks of <u>bots</u> that are infected by <u>malware</u> and are under the control of a single party, known as a *bot herder* or *bot operator*. Botnets are the best-known mechanism to scale bots and their impact.

branch

A contained area of a code repository. The first branch created in a repository is the *main branch*. You can create a new branch from an existing branch, and you can then develop features or fix bugs in the new branch. A branch you create to build a feature is commonly referred to as a *feature branch*. When the feature is ready for release, you merge the feature branch back into the main branch. For more information, see <u>About branches</u> (GitHub documentation).

break-glass access

In exceptional circumstances and through an approved process, a quick means for a user to gain access to an AWS account that they don't typically have permissions to access. For more information, see the <u>Implement break-glass procedures</u> indicator in the AWS Well-Architected guidance.

brownfield strategy

The existing infrastructure in your environment. When adopting a brownfield strategy for a system architecture, you design the architecture around the constraints of the current systems and infrastructure. If you are expanding the existing infrastructure, you might blend brownfield and <u>greenfield</u> strategies.

buffer cache

The memory area where the most frequently accessed data is stored.

business capability

What a business does to generate value (for example, sales, customer service, or marketing). Microservices architectures and development decisions can be driven by business capabilities. For more information, see the <u>Organized around business capabilities</u> section of the <u>Running</u> <u>containerized microservices on AWS</u> whitepaper.

business continuity planning (BCP)

A plan that addresses the potential impact of a disruptive event, such as a large-scale migration, on operations and enables a business to resume operations quickly.

С

CAF

See AWS Cloud Adoption Framework.

canary deployment

The slow and incremental release of a version to end users. When you are confident, you deploy the new version and replace the current version in its entirety.

CCoE

See <u>Cloud Center of Excellence</u>.

CDC

See change data capture.

change data capture (CDC)

The process of tracking changes to a data source, such as a database table, and recording metadata about the change. You can use CDC for various purposes, such as auditing or replicating changes in a target system to maintain synchronization.

chaos engineering

Intentionally introducing failures or disruptive events to test a system's resilience. You can use <u>AWS Fault Injection Service (AWS FIS)</u> to perform experiments that stress your AWS workloads and evaluate their response.

CI/CD

See continuous integration and continuous delivery.

classification

A categorization process that helps generate predictions. ML models for classification problems predict a discrete value. Discrete values are always distinct from one another. For example, a model might need to evaluate whether or not there is a car in an image.

client-side encryption

Encryption of data locally, before the target AWS service receives it.

Cloud Center of Excellence (CCoE)

A multi-disciplinary team that drives cloud adoption efforts across an organization, including developing cloud best practices, mobilizing resources, establishing migration timelines, and leading the organization through large-scale transformations. For more information, see the CCOE posts on the AWS Cloud Enterprise Strategy Blog.

cloud computing

The cloud technology that is typically used for remote data storage and IoT device management. Cloud computing is commonly connected to <u>edge computing</u> technology.

cloud operating model

In an IT organization, the operating model that is used to build, mature, and optimize one or more cloud environments. For more information, see Building your Cloud Operating Model.

cloud stages of adoption

The four phases that organizations typically go through when they migrate to the AWS Cloud:

- Project Running a few cloud-related projects for proof of concept and learning purposes
- Foundation Making foundational investments to scale your cloud adoption (e.g., creating a landing zone, defining a CCoE, establishing an operations model)
- Migration Migrating individual applications
- Re-invention Optimizing products and services, and innovating in the cloud

These stages were defined by Stephen Orban in the blog post <u>The Journey Toward Cloud-First</u> <u>& the Stages of Adoption</u> on the AWS Cloud Enterprise Strategy blog. For information about how they relate to the AWS migration strategy, see the <u>migration readiness guide</u>.

CMDB

See configuration management database.

code repository

A location where source code and other assets, such as documentation, samples, and scripts, are stored and updated through version control processes. Common cloud repositories include GitHub or Bitbucket Cloud. Each version of the code is called a *branch*. In a microservice structure, each repository is devoted to a single piece of functionality. A single CI/CD pipeline can use multiple repositories.

cold cache

A buffer cache that is empty, not well populated, or contains stale or irrelevant data. This affects performance because the database instance must read from the main memory or disk, which is slower than reading from the buffer cache.

cold data

Data that is rarely accessed and is typically historical. When querying this kind of data, slow queries are typically acceptable. Moving this data to lower-performing and less expensive storage tiers or classes can reduce costs.

computer vision (CV)

A field of <u>AI</u> that uses machine learning to analyze and extract information from visual formats such as digital images and videos. For example, Amazon SageMaker AI provides image processing algorithms for CV.

configuration drift

For a workload, a configuration change from the expected state. It might cause the workload to become noncompliant, and it's typically gradual and unintentional.

configuration management database (CMDB)

A repository that stores and manages information about a database and its IT environment, including both hardware and software components and their configurations. You typically use data from a CMDB in the portfolio discovery and analysis stage of migration.

conformance pack

A collection of AWS Config rules and remediation actions that you can assemble to customize your compliance and security checks. You can deploy a conformance pack as a single entity in an AWS account and Region, or across an organization, by using a YAML template. For more information, see <u>Conformance packs</u> in the AWS Config documentation.

continuous integration and continuous delivery (CI/CD)

The process of automating the source, build, test, staging, and production stages of the software release process. CI/CD is commonly described as a pipeline. CI/CD can help you automate processes, improve productivity, improve code quality, and deliver faster. For more information, see <u>Benefits of continuous delivery</u>. CD can also stand for *continuous deployment*. For more information, see Continuous Delivery vs. Continuous Deployment.

CV

See computer vision.

D

data at rest

Data that is stationary in your network, such as data that is in storage.

data classification

A process for identifying and categorizing the data in your network based on its criticality and sensitivity. It is a critical component of any cybersecurity risk management strategy because it helps you determine the appropriate protection and retention controls for the data. Data classification is a component of the security pillar in the AWS Well-Architected Framework. For more information, see <u>Data classification</u>.

data drift

A meaningful variation between the production data and the data that was used to train an ML model, or a meaningful change in the input data over time. Data drift can reduce the overall quality, accuracy, and fairness in ML model predictions.

data in transit

Data that is actively moving through your network, such as between network resources.

data mesh

An architectural framework that provides distributed, decentralized data ownership with centralized management and governance.

data minimization

The principle of collecting and processing only the data that is strictly necessary. Practicing data minimization in the AWS Cloud can reduce privacy risks, costs, and your analytics carbon footprint.

data perimeter

A set of preventive guardrails in your AWS environment that help make sure that only trusted identities are accessing trusted resources from expected networks. For more information, see Building a data perimeter on AWS.

data preprocessing

To transform raw data into a format that is easily parsed by your ML model. Preprocessing data can mean removing certain columns or rows and addressing missing, inconsistent, or duplicate values.

data provenance

The process of tracking the origin and history of data throughout its lifecycle, such as how the data was generated, transmitted, and stored.

data subject

An individual whose data is being collected and processed.

data warehouse

A data management system that supports business intelligence, such as analytics. Data warehouses commonly contain large amounts of historical data, and they are typically used for queries and analysis.

```
database definition language (DDL)
```

Statements or commands for creating or modifying the structure of tables and objects in a database.

database manipulation language (DML)

Statements or commands for modifying (inserting, updating, and deleting) information in a database.

DDL

See database definition language.

deep ensemble

To combine multiple deep learning models for prediction. You can use deep ensembles to obtain a more accurate prediction or for estimating uncertainty in predictions.

deep learning

An ML subfield that uses multiple layers of artificial neural networks to identify mapping between input data and target variables of interest.

defense-in-depth

An information security approach in which a series of security mechanisms and controls are thoughtfully layered throughout a computer network to protect the confidentiality, integrity, and availability of the network and the data within. When you adopt this strategy on AWS, you add multiple controls at different layers of the AWS Organizations structure to help secure resources. For example, a defense-in-depth approach might combine multi-factor authentication, network segmentation, and encryption.

delegated administrator

In AWS Organizations, a compatible service can register an AWS member account to administer the organization's accounts and manage permissions for that service. This account is called the *delegated administrator* for that service. For more information and a list of compatible services, see <u>Services that work with AWS Organizations</u> in the AWS Organizations documentation.

deployment

The process of making an application, new features, or code fixes available in the target environment. Deployment involves implementing changes in a code base and then building and running that code base in the application's environments.

development environment

See <u>environment</u>.

detective control

A security control that is designed to detect, log, and alert after an event has occurred. These controls are a second line of defense, alerting you to security events that bypassed the preventative controls in place. For more information, see <u>Detective controls</u> in *Implementing security controls on AWS*.

development value stream mapping (DVSM)

A process used to identify and prioritize constraints that adversely affect speed and quality in a software development lifecycle. DVSM extends the value stream mapping process originally designed for lean manufacturing practices. It focuses on the steps and teams required to create and move value through the software development process.

digital twin

A virtual representation of a real-world system, such as a building, factory, industrial equipment, or production line. Digital twins support predictive maintenance, remote monitoring, and production optimization.

dimension table

In a <u>star schema</u>, a smaller table that contains data attributes about quantitative data in a fact table. Dimension table attributes are typically text fields or discrete numbers that behave like text. These attributes are commonly used for query constraining, filtering, and result set labeling.

disaster

An event that prevents a workload or system from fulfilling its business objectives in its primary deployed location. These events can be natural disasters, technical failures, or the result of human actions, such as unintentional misconfiguration or a malware attack.

disaster recovery (DR)

The strategy and process you use to minimize downtime and data loss caused by a <u>disaster</u>. For more information, see <u>Disaster Recovery of Workloads on AWS: Recovery in the Cloud</u> in the AWS Well-Architected Framework.

DML

See database manipulation language.

domain-driven design

An approach to developing a complex software system by connecting its components to evolving domains, or core business goals, that each component serves. This concept was introduced by Eric Evans in his book, *Domain-Driven Design: Tackling Complexity in the Heart of Software* (Boston: Addison-Wesley Professional, 2003). For information about how you can use domain-driven design with the strangler fig pattern, see <u>Modernizing legacy Microsoft ASP.NET</u> (ASMX) web services incrementally by using containers and Amazon API Gateway.

DR

See disaster recovery.

drift detection

Tracking deviations from a baselined configuration. For example, you can use AWS CloudFormation to <u>detect drift in system resources</u>, or you can use AWS Control Tower to <u>detect</u> <u>changes in your landing zone</u> that might affect compliance with governance requirements.

DVSM

See development value stream mapping.

Ε

EDA

See exploratory data analysis.

EDI

See electronic data interchange.

edge computing

The technology that increases the computing power for smart devices at the edges of an IoT network. When compared with <u>cloud computing</u>, edge computing can reduce communication latency and improve response time.

electronic data interchange (EDI)

The automated exchange of business documents between organizations. For more information, see <u>What is Electronic Data Interchange</u>.

encryption

A computing process that transforms plaintext data, which is human-readable, into ciphertext. encryption key

A cryptographic string of randomized bits that is generated by an encryption algorithm. Keys can vary in length, and each key is designed to be unpredictable and unique.

endianness

The order in which bytes are stored in computer memory. Big-endian systems store the most significant byte first. Little-endian systems store the least significant byte first.

endpoint

See service endpoint.

endpoint service

A service that you can host in a virtual private cloud (VPC) to share with other users. You can create an endpoint service with AWS PrivateLink and grant permissions to other AWS accounts or to AWS Identity and Access Management (IAM) principals. These accounts or principals can connect to your endpoint service privately by creating interface VPC endpoints. For more

information, see <u>Create an endpoint service</u> in the Amazon Virtual Private Cloud (Amazon VPC) documentation.

enterprise resource planning (ERP)

A system that automates and manages key business processes (such as accounting, <u>MES</u>, and project management) for an enterprise.

envelope encryption

The process of encrypting an encryption key with another encryption key. For more information, see <u>Envelope encryption</u> in the AWS Key Management Service (AWS KMS) documentation.

environment

An instance of a running application. The following are common types of environments in cloud computing:

- development environment An instance of a running application that is available only to the core team responsible for maintaining the application. Development environments are used to test changes before promoting them to upper environments. This type of environment is sometimes referred to as a *test environment*.
- lower environments All development environments for an application, such as those used for initial builds and tests.
- production environment An instance of a running application that end users can access. In a CI/CD pipeline, the production environment is the last deployment environment.
- upper environments All environments that can be accessed by users other than the core development team. This can include a production environment, preproduction environments, and environments for user acceptance testing.

epic

In agile methodologies, functional categories that help organize and prioritize your work. Epics provide a high-level description of requirements and implementation tasks. For example, AWS CAF security epics include identity and access management, detective controls, infrastructure security, data protection, and incident response. For more information about epics in the AWS migration strategy, see the program implementation guide.

ERP

See enterprise resource planning.

exploratory data analysis (EDA)

The process of analyzing a dataset to understand its main characteristics. You collect or aggregate data and then perform initial investigations to find patterns, detect anomalies, and check assumptions. EDA is performed by calculating summary statistics and creating data visualizations.

F

fact table

The central table in a <u>star schema</u>. It stores quantitative data about business operations. Typically, a fact table contains two types of columns: those that contain measures and those that contain a foreign key to a dimension table.

fail fast

A philosophy that uses frequent and incremental testing to reduce the development lifecycle. It is a critical part of an agile approach.

fault isolation boundary

In the AWS Cloud, a boundary such as an Availability Zone, AWS Region, control plane, or data plane that limits the effect of a failure and helps improve the resilience of workloads. For more information, see AWS Fault Isolation Boundaries.

feature branch

See branch.

features

The input data that you use to make a prediction. For example, in a manufacturing context, features could be images that are periodically captured from the manufacturing line.

feature importance

How significant a feature is for a model's predictions. This is usually expressed as a numerical score that can be calculated through various techniques, such as Shapley Additive Explanations (SHAP) and integrated gradients. For more information, see <u>Machine learning model</u> <u>interpretability with AWS</u>.

feature transformation

To optimize data for the ML process, including enriching data with additional sources, scaling values, or extracting multiple sets of information from a single data field. This enables the ML model to benefit from the data. For example, if you break down the "2021-05-27 00:15:37" date into "2021", "May", "Thu", and "15", you can help the learning algorithm learn nuanced patterns associated with different data components.

few-shot prompting

Providing an <u>LLM</u> with a small number of examples that demonstrate the task and desired output before asking it to perform a similar task. This technique is an application of in-context learning, where models learn from examples (*shots*) that are embedded in prompts. Few-shot prompting can be effective for tasks that require specific formatting, reasoning, or domain knowledge. See also <u>zero-shot prompting</u>.

FGAC

See fine-grained access control.

```
fine-grained access control (FGAC)
```

The use of multiple conditions to allow or deny an access request.

flash-cut migration

A database migration method that uses continuous data replication through <u>change data</u> <u>capture</u> to migrate data in the shortest time possible, instead of using a phased approach. The objective is to keep downtime to a minimum.

FM

See foundation model.

foundation model (FM)

A large deep-learning neural network that has been training on massive datasets of generalized and unlabeled data. FMs are capable of performing a wide variety of general tasks, such as understanding language, generating text and images, and conversing in natural language. For more information, see <u>What are Foundation Models</u>.

G

generative Al

A subset of <u>AI</u> models that have been trained on large amounts of data and that can use a simple text prompt to create new content and artifacts, such as images, videos, text, and audio. For more information, see <u>What is Generative AI</u>.

geo blocking

See geographic restrictions.

geographic restrictions (geo blocking)

In Amazon CloudFront, an option to prevent users in specific countries from accessing content distributions. You can use an allow list or block list to specify approved and banned countries. For more information, see <u>Restricting the geographic distribution of your content</u> in the CloudFront documentation.

Gitflow workflow

An approach in which lower and upper environments use different branches in a source code repository. The Gitflow workflow is considered legacy, and the <u>trunk-based workflow</u> is the modern, preferred approach.

golden image

A snapshot of a system or software that is used as a template to deploy new instances of that system or software. For example, in manufacturing, a golden image can be used to provision software on multiple devices and helps improve speed, scalability, and productivity in device manufacturing operations.

greenfield strategy

The absence of existing infrastructure in a new environment. When adopting a greenfield strategy for a system architecture, you can select all new technologies without the restriction of compatibility with existing infrastructure, also known as <u>brownfield</u>. If you are expanding the existing infrastructure, you might blend brownfield and greenfield strategies. guardrail

A high-level rule that helps govern resources, policies, and compliance across organizational units (OUs). *Preventive guardrails* enforce policies to ensure alignment to compliance standards. They are implemented by using service control policies and IAM permissions boundaries.

Detective guardrails detect policy violations and compliance issues, and generate alerts for remediation. They are implemented by using AWS Config, AWS Security Hub, Amazon GuardDuty, AWS Trusted Advisor, Amazon Inspector, and custom AWS Lambda checks.

Η

HA

See high availability.

heterogeneous database migration

Migrating your source database to a target database that uses a different database engine (for example, Oracle to Amazon Aurora). Heterogeneous migration is typically part of a rearchitecting effort, and converting the schema can be a complex task. <u>AWS provides AWS SCT</u> that helps with schema conversions.

high availability (HA)

The ability of a workload to operate continuously, without intervention, in the event of challenges or disasters. HA systems are designed to automatically fail over, consistently deliver high-quality performance, and handle different loads and failures with minimal performance impact.

historian modernization

An approach used to modernize and upgrade operational technology (OT) systems to better serve the needs of the manufacturing industry. A *historian* is a type of database that is used to collect and store data from various sources in a factory.

holdout data

A portion of historical, labeled data that is withheld from a dataset that is used to train a <u>machine learning</u> model. You can use holdout data to evaluate the model performance by comparing the model predictions against the holdout data.

homogeneous database migration

Migrating your source database to a target database that shares the same database engine (for example, Microsoft SQL Server to Amazon RDS for SQL Server). Homogeneous migration is typically part of a rehosting or replatforming effort. You can use native database utilities to migrate the schema.

hot data

Data that is frequently accessed, such as real-time data or recent translational data. This data typically requires a high-performance storage tier or class to provide fast query responses. hotfix

An urgent fix for a critical issue in a production environment. Due to its urgency, a hotfix is usually made outside of the typical DevOps release workflow.

hypercare period

Immediately following cutover, the period of time when a migration team manages and monitors the migrated applications in the cloud in order to address any issues. Typically, this period is 1–4 days in length. At the end of the hypercare period, the migration team typically transfers responsibility for the applications to the cloud operations team.

I

laC

See infrastructure as code.

identity-based policy

A policy attached to one or more IAM principals that defines their permissions within the AWS Cloud environment.

idle application

An application that has an average CPU and memory usage between 5 and 20 percent over a period of 90 days. In a migration project, it is common to retire these applications or retain them on premises.

lloT

T

See industrial Internet of Things.

immutable infrastructure

A model that deploys new infrastructure for production workloads instead of updating, patching, or modifying the existing infrastructure. Immutable infrastructures are inherently more consistent, reliable, and predictable than <u>mutable infrastructure</u>. For more information, see the <u>Deploy using immutable infrastructure</u> best practice in the AWS Well-Architected Framework.

inbound (ingress) VPC

In an AWS multi-account architecture, a VPC that accepts, inspects, and routes network connections from outside an application. The <u>AWS Security Reference Architecture</u> recommends setting up your Network account with inbound, outbound, and inspection VPCs to protect the two-way interface between your application and the broader internet.

incremental migration

A cutover strategy in which you migrate your application in small parts instead of performing a single, full cutover. For example, you might move only a few microservices or users to the new system initially. After you verify that everything is working properly, you can incrementally move additional microservices or users until you can decommission your legacy system. This strategy reduces the risks associated with large migrations.

Industry 4.0

A term that was introduced by <u>Klaus Schwab</u> in 2016 to refer to the modernization of manufacturing processes through advances in connectivity, real-time data, automation, analytics, and AI/ML.

infrastructure

ī

All of the resources and assets contained within an application's environment.

infrastructure as code (IaC)

The process of provisioning and managing an application's infrastructure through a set of configuration files. IaC is designed to help you centralize infrastructure management, standardize resources, and scale quickly so that new environments are repeatable, reliable, and consistent.

industrial Internet of Things (IIoT)

The use of internet-connected sensors and devices in the industrial sectors, such as manufacturing, energy, automotive, healthcare, life sciences, and agriculture. For more information, see <u>Building an industrial Internet of Things (IIoT) digital transformation strategy</u>. inspection VPC

In an AWS multi-account architecture, a centralized VPC that manages inspections of network traffic between VPCs (in the same or different AWS Regions), the internet, and on-premises networks. The <u>AWS Security Reference Architecture</u> recommends setting up your Network account with inbound, outbound, and inspection VPCs to protect the two-way interface between your application and the broader internet.

Internet of Things (IoT)

The network of connected physical objects with embedded sensors or processors that communicate with other devices and systems through the internet or over a local communication network. For more information, see <u>What is IoT?</u>

interpretability

A characteristic of a machine learning model that describes the degree to which a human can understand how the model's predictions depend on its inputs. For more information, see Machine learning model interpretability with AWS.

IoT

See Internet of Things.

```
IT information library (ITIL)
```

A set of best practices for delivering IT services and aligning these services with business requirements. ITIL provides the foundation for ITSM.

IT service management (ITSM)

Activities associated with designing, implementing, managing, and supporting IT services for an organization. For information about integrating cloud operations with ITSM tools, see the <u>operations integration guide</u>.

ITIL

See IT information library.

ITSM

See IT service management.

L

label-based access control (LBAC)

An implementation of mandatory access control (MAC) where the users and the data itself are each explicitly assigned a security label value. The intersection between the user security label and data security label determines which rows and columns can be seen by the user.

landing zone

A landing zone is a well-architected, multi-account AWS environment that is scalable and secure. This is a starting point from which your organizations can quickly launch and deploy workloads and applications with confidence in their security and infrastructure environment. For more information about landing zones, see <u>Setting up a secure and scalable multi-account</u> <u>AWS environment</u>.

large language model (LLM)

A deep learning <u>AI</u> model that is pretrained on a vast amount of data. An LLM can perform multiple tasks, such as answering questions, summarizing documents, translating text into other languages, and completing sentences. For more information, see <u>What are LLMs</u>.

large migration

A migration of 300 or more servers.

LBAC

See label-based access control.

least privilege

The security best practice of granting the minimum permissions required to perform a task. For more information, see <u>Apply least-privilege permissions</u> in the IAM documentation.

lift and shift

See 7 Rs.

little-endian system

A system that stores the least significant byte first. See also endianness.

LLM

See large language model.

lower environments

See environment.

Μ

machine learning (ML)

A type of artificial intelligence that uses algorithms and techniques for pattern recognition and learning. ML analyzes and learns from recorded data, such as Internet of Things (IoT) data, to generate a statistical model based on patterns. For more information, see <u>Machine Learning</u>. main branch

See branch.

malware

Software that is designed to compromise computer security or privacy. Malware might disrupt computer systems, leak sensitive information, or gain unauthorized access. Examples of malware include viruses, worms, ransomware, Trojan horses, spyware, and keyloggers.

managed services

AWS services for which AWS operates the infrastructure layer, the operating system, and platforms, and you access the endpoints to store and retrieve data. Amazon Simple Storage Service (Amazon S3) and Amazon DynamoDB are examples of managed services. These are also known as *abstracted services*.

manufacturing execution system (MES)

A software system for tracking, monitoring, documenting, and controlling production processes that convert raw materials to finished products on the shop floor.

MAP

See Migration Acceleration Program.

mechanism

A complete process in which you create a tool, drive adoption of the tool, and then inspect the results in order to make adjustments. A mechanism is a cycle that reinforces and improves itself as it operates. For more information, see <u>Building mechanisms</u> in the AWS Well-Architected Framework.

member account

All AWS accounts other than the management account that are part of an organization in AWS Organizations. An account can be a member of only one organization at a time.

MES

See manufacturing execution system.

Message Queuing Telemetry Transport (MQTT)

A lightweight, machine-to-machine (M2M) communication protocol, based on the <u>publish/</u> <u>subscribe</u> pattern, for resource-constrained <u>IoT</u> devices.

microservice

A small, independent service that communicates over well-defined APIs and is typically owned by small, self-contained teams. For example, an insurance system might include microservices that map to business capabilities, such as sales or marketing, or subdomains, such as purchasing, claims, or analytics. The benefits of microservices include agility, flexible scaling, easy deployment, reusable code, and resilience. For more information, see <u>Integrating</u> microservices by using AWS serverless services.

microservices architecture

An approach to building an application with independent components that run each application process as a microservice. These microservices communicate through a well-defined interface by using lightweight APIs. Each microservice in this architecture can be updated, deployed, and scaled to meet demand for specific functions of an application. For more information, see <u>Implementing microservices on AWS</u>.

Migration Acceleration Program (MAP)

An AWS program that provides consulting support, training, and services to help organizations build a strong operational foundation for moving to the cloud, and to help offset the initial cost of migrations. MAP includes a migration methodology for executing legacy migrations in a methodical way and a set of tools to automate and accelerate common migration scenarios.

migration at scale

The process of moving the majority of the application portfolio to the cloud in waves, with more applications moved at a faster rate in each wave. This phase uses the best practices and lessons learned from the earlier phases to implement a *migration factory* of teams, tools, and processes to streamline the migration of workloads through automation and agile delivery. This is the third phase of the AWS migration strategy.

migration factory

Cross-functional teams that streamline the migration of workloads through automated, agile approaches. Migration factory teams typically include operations, business analysts and owners,

migration engineers, developers, and DevOps professionals working in sprints. Between 20 and 50 percent of an enterprise application portfolio consists of repeated patterns that can be optimized by a factory approach. For more information, see the <u>discussion of migration</u> factories and the Cloud Migration Factory guide in this content set.

migration metadata

The information about the application and server that is needed to complete the migration. Each migration pattern requires a different set of migration metadata. Examples of migration metadata include the target subnet, security group, and AWS account.

migration pattern

A repeatable migration task that details the migration strategy, the migration destination, and the migration application or service used. Example: Rehost migration to Amazon EC2 with AWS Application Migration Service.

Migration Portfolio Assessment (MPA)

An online tool that provides information for validating the business case for migrating to the AWS Cloud. MPA provides detailed portfolio assessment (server right-sizing, pricing, TCO comparisons, migration cost analysis) as well as migration planning (application data analysis and data collection, application grouping, migration prioritization, and wave planning). The <u>MPA tool</u> (requires login) is available free of charge to all AWS consultants and APN Partner consultants.

Migration Readiness Assessment (MRA)

The process of gaining insights about an organization's cloud readiness status, identifying strengths and weaknesses, and building an action plan to close identified gaps, using the AWS CAF. For more information, see the <u>migration readiness guide</u>. MRA is the first phase of the <u>AWS</u> <u>migration strategy</u>.

migration strategy

The approach used to migrate a workload to the AWS Cloud. For more information, see the <u>7 Rs</u> entry in this glossary and see <u>Mobilize your organization to accelerate large-scale migrations</u>. ML

See machine learning.

modernization

Transforming an outdated (legacy or monolithic) application and its infrastructure into an agile, elastic, and highly available system in the cloud to reduce costs, gain efficiencies, and take advantage of innovations. For more information, see <u>Strategy for modernizing applications in the AWS Cloud</u>.

modernization readiness assessment

An evaluation that helps determine the modernization readiness of an organization's applications; identifies benefits, risks, and dependencies; and determines how well the organization can support the future state of those applications. The outcome of the assessment is a blueprint of the target architecture, a roadmap that details development phases and milestones for the modernization process, and an action plan for addressing identified gaps. For more information, see <u>Evaluating modernization readiness for applications in the AWS Cloud</u>.

monolithic applications (monoliths)

Applications that run as a single service with tightly coupled processes. Monolithic applications have several drawbacks. If one application feature experiences a spike in demand, the entire architecture must be scaled. Adding or improving a monolithic application's features also becomes more complex when the code base grows. To address these issues, you can use a microservices architecture. For more information, see <u>Decomposing monoliths into</u> <u>microservices</u>.

MPA

See Migration Portfolio Assessment.

MQTT

See Message Queuing Telemetry Transport.

multiclass classification

A process that helps generate predictions for multiple classes (predicting one of more than two outcomes). For example, an ML model might ask "Is this product a book, car, or phone?" or "Which product category is most interesting to this customer?"

mutable infrastructure

A model that updates and modifies the existing infrastructure for production workloads. For improved consistency, reliability, and predictability, the AWS Well-Architected Framework recommends the use of <u>immutable infrastructure</u> as a best practice.

0

OAC

See origin access control.

OAI

See origin access identity.

ОСМ

See organizational change management.

offline migration

A migration method in which the source workload is taken down during the migration process. This method involves extended downtime and is typically used for small, non-critical workloads.

OI

See operations integration.

OLA

See operational-level agreement.

online migration

A migration method in which the source workload is copied to the target system without being taken offline. Applications that are connected to the workload can continue to function during the migration. This method involves zero to minimal downtime and is typically used for critical production workloads.

OPC-UA

See Open Process Communications - Unified Architecture.

Open Process Communications - Unified Architecture (OPC-UA)

A machine-to-machine (M2M) communication protocol for industrial automation. OPC-UA provides an interoperability standard with data encryption, authentication, and authorization schemes.

operational-level agreement (OLA)

An agreement that clarifies what functional IT groups promise to deliver to each other, to support a service-level agreement (SLA).

operational readiness review (ORR)

A checklist of questions and associated best practices that help you understand, evaluate, prevent, or reduce the scope of incidents and possible failures. For more information, see <u>Operational Readiness Reviews (ORR)</u> in the AWS Well-Architected Framework.

operational technology (OT)

Hardware and software systems that work with the physical environment to control industrial operations, equipment, and infrastructure. In manufacturing, the integration of OT and information technology (IT) systems is a key focus for <u>Industry 4.0</u> transformations. operations integration (OI)

The process of modernizing operations in the cloud, which involves readiness planning, automation, and integration. For more information, see the <u>operations integration guide</u>. organization trail

A trail that's created by AWS CloudTrail that logs all events for all AWS accounts in an organization in AWS Organizations. This trail is created in each AWS account that's part of the organization and tracks the activity in each account. For more information, see <u>Creating a trail</u> for an organization in the CloudTrail documentation.

organizational change management (OCM)

A framework for managing major, disruptive business transformations from a people, culture, and leadership perspective. OCM helps organizations prepare for, and transition to, new systems and strategies by accelerating change adoption, addressing transitional issues, and driving cultural and organizational changes. In the AWS migration strategy, this framework is called *people acceleration*, because of the speed of change required in cloud adoption projects. For more information, see the <u>OCM guide</u>.

origin access control (OAC)

In CloudFront, an enhanced option for restricting access to secure your Amazon Simple Storage Service (Amazon S3) content. OAC supports all S3 buckets in all AWS Regions, server-side encryption with AWS KMS (SSE-KMS), and dynamic PUT and DELETE requests to the S3 bucket. origin access identity (OAI)

In CloudFront, an option for restricting access to secure your Amazon S3 content. When you use OAI, CloudFront creates a principal that Amazon S3 can authenticate with. Authenticated principals can access content in an S3 bucket only through a specific CloudFront distribution. See also <u>OAC</u>, which provides more granular and enhanced access control.

ORR

See operational readiness review.

OT

See operational technology.

outbound (egress) VPC

In an AWS multi-account architecture, a VPC that handles network connections that are initiated from within an application. The <u>AWS Security Reference Architecture</u> recommends setting up your Network account with inbound, outbound, and inspection VPCs to protect the two-way interface between your application and the broader internet.

Ρ

permissions boundary

An IAM management policy that is attached to IAM principals to set the maximum permissions that the user or role can have. For more information, see <u>Permissions boundaries</u> in the IAM documentation.

personally identifiable information (PII)

Information that, when viewed directly or paired with other related data, can be used to reasonably infer the identity of an individual. Examples of PII include names, addresses, and contact information.

ΡII

See personally identifiable information.

playbook

A set of predefined steps that capture the work associated with migrations, such as delivering core operations functions in the cloud. A playbook can take the form of scripts, automated runbooks, or a summary of processes or steps required to operate your modernized environment.

PLC

See programmable logic controller.

PLM

See product lifecycle management.

policy

An object that can define permissions (see <u>identity-based policy</u>), specify access conditions (see <u>resource-based policy</u>), or define the maximum permissions for all accounts in an organization in AWS Organizations (see <u>service control policy</u>).

polyglot persistence

Independently choosing a microservice's data storage technology based on data access patterns and other requirements. If your microservices have the same data storage technology, they can encounter implementation challenges or experience poor performance. Microservices are more easily implemented and achieve better performance and scalability if they use the data store best adapted to their requirements. For more information, see <u>Enabling data persistence in</u> <u>microservices</u>.

portfolio assessment

A process of discovering, analyzing, and prioritizing the application portfolio in order to plan the migration. For more information, see <u>Evaluating migration readiness</u>.

predicate

A query condition that returns true or false, commonly located in a WHERE clause. predicate pushdown

A database query optimization technique that filters the data in the query before transfer. This reduces the amount of data that must be retrieved and processed from the relational database, and it improves query performance.

preventative control

A security control that is designed to prevent an event from occurring. These controls are a first line of defense to help prevent unauthorized access or unwanted changes to your network. For more information, see <u>Preventative controls</u> in *Implementing security controls on AWS*. principal

An entity in AWS that can perform actions and access resources. This entity is typically a root user for an AWS account, an IAM role, or a user. For more information, see *Principal* in <u>Roles</u> terms and concepts in the IAM documentation.

privacy by design

A system engineering approach that takes privacy into account through the whole development process.

private hosted zones

A container that holds information about how you want Amazon Route 53 to respond to DNS queries for a domain and its subdomains within one or more VPCs. For more information, see Working with private hosted zones in the Route 53 documentation.

proactive control

A <u>security control</u> designed to prevent the deployment of noncompliant resources. These controls scan resources before they are provisioned. If the resource is not compliant with the control, then it isn't provisioned. For more information, see the <u>Controls reference guide</u> in the AWS Control Tower documentation and see <u>Proactive controls</u> in *Implementing security controls on AWS*.

product lifecycle management (PLM)

The management of data and processes for a product throughout its entire lifecycle, from design, development, and launch, through growth and maturity, to decline and removal. production environment

See environment.

programmable logic controller (PLC)

In manufacturing, a highly reliable, adaptable computer that monitors machines and automates manufacturing processes.

prompt chaining

Using the output of one <u>LLM</u> prompt as the input for the next prompt to generate better responses. This technique is used to break down a complex task into subtasks, or to iteratively refine or expand a preliminary response. It helps improve the accuracy and relevance of a model's responses and allows for more granular, personalized results.

pseudonymization

The process of replacing personal identifiers in a dataset with placeholder values. Pseudonymization can help protect personal privacy. Pseudonymized data is still considered to be personal data.

publish/subscribe (pub/sub)

A pattern that enables asynchronous communications among microservices to improve scalability and responsiveness. For example, in a microservices-based <u>MES</u>, a microservice can publish event messages to a channel that other microservices can subscribe to. The system can add new microservices without changing the publishing service.

Q

query plan

A series of steps, like instructions, that are used to access the data in a SQL relational database system.

query plan regression

When a database service optimizer chooses a less optimal plan than it did before a given change to the database environment. This can be caused by changes to statistics, constraints, environment settings, query parameter bindings, and updates to the database engine.

R

RACI matrix

See responsible, accountable, consulted, informed (RACI).

RAG

See Retrieval Augmented Generation.

ransomware

A malicious software that is designed to block access to a computer system or data until a payment is made.

RASCI matrix

See responsible, accountable, consulted, informed (RACI).

RCAC

See row and column access control.

read replica

A copy of a database that's used for read-only purposes. You can route queries to the read replica to reduce the load on your primary database.

re-architect

See <u>7 Rs</u>.

recovery point objective (RPO)

The maximum acceptable amount of time since the last data recovery point. This determines what is considered an acceptable loss of data between the last recovery point and the interruption of service.

recovery time objective (RTO)

The maximum acceptable delay between the interruption of service and restoration of service. refactor

See 7 Rs.

Region

A collection of AWS resources in a geographic area. Each AWS Region is isolated and independent of the others to provide fault tolerance, stability, and resilience. For more information, see <u>Specify which AWS Regions your account can use</u>.

regression

An ML technique that predicts a numeric value. For example, to solve the problem of "What price will this house sell for?" an ML model could use a linear regression model to predict a house's sale price based on known facts about the house (for example, the square footage). rehost

See 7 Rs.

release

In a deployment process, the act of promoting changes to a production environment. relocate

See <u>7 Rs</u>.

replatform

See <u>7 Rs</u>.

repurchase

See <u>7 Rs</u>.

resiliency

An application's ability to resist or recover from disruptions. <u>High availability</u> and <u>disaster</u> <u>recovery</u> are common considerations when planning for resiliency in the AWS Cloud. For more information, see <u>AWS Cloud Resilience</u>.

resource-based policy

A policy attached to a resource, such as an Amazon S3 bucket, an endpoint, or an encryption key. This type of policy specifies which principals are allowed access, supported actions, and any other conditions that must be met.

responsible, accountable, consulted, informed (RACI) matrix

A matrix that defines the roles and responsibilities for all parties involved in migration activities and cloud operations. The matrix name is derived from the responsibility types defined in the matrix: responsible (R), accountable (A), consulted (C), and informed (I). The support (S) type is optional. If you include support, the matrix is called a *RASCI matrix*, and if you exclude it, it's called a *RACI matrix*.

responsive control

A security control that is designed to drive remediation of adverse events or deviations from your security baseline. For more information, see <u>Responsive controls</u> in *Implementing security controls on AWS*.

retain

See 7 Rs.

retire

See <u>7 Rs</u>.

Retrieval Augmented Generation (RAG)

A <u>generative AI</u> technology in which an <u>LLM</u> references an authoritative data source that is outside of its training data sources before generating a response. For example, a RAG model might perform a semantic search of an organization's knowledge base or custom data. For more information, see <u>What is RAG</u>.

rotation

The process of periodically updating a <u>secret</u> to make it more difficult for an attacker to access the credentials.

row and column access control (RCAC)

The use of basic, flexible SQL expressions that have defined access rules. RCAC consists of row permissions and column masks.

RPO

See recovery point objective.

RTO

See recovery time objective.

runbook

A set of manual or automated procedures required to perform a specific task. These are typically built to streamline repetitive operations or procedures with high error rates.

S

SAML 2.0

An open standard that many identity providers (IdPs) use. This feature enables federated single sign-on (SSO), so users can log into the AWS Management Console or call the AWS API operations without you having to create user in IAM for everyone in your organization. For more information about SAML 2.0-based federation, see <u>About SAML 2.0-based federation</u> in the IAM documentation.

SCADA

See supervisory control and data acquisition.

SCP

See service control policy.

secret

In AWS Secrets Manager, confidential or restricted information, such as a password or user credentials, that you store in encrypted form. It consists of the secret value and its metadata.

The secret value can be binary, a single string, or multiple strings. For more information, see What's in a Secrets Manager secret? in the Secrets Manager documentation.

security by design

A system engineering approach that takes security into account through the whole development process.

security control

A technical or administrative guardrail that prevents, detects, or reduces the ability of a threat actor to exploit a security vulnerability. There are four primary types of security controls: <u>preventative</u>, <u>detective</u>, <u>responsive</u>, and <u>proactive</u>.

security hardening

The process of reducing the attack surface to make it more resistant to attacks. This can include actions such as removing resources that are no longer needed, implementing the security best practice of granting least privilege, or deactivating unnecessary features in configuration files. security information and event management (SIEM) system

Tools and services that combine security information management (SIM) and security event management (SEM) systems. A SIEM system collects, monitors, and analyzes data from servers, networks, devices, and other sources to detect threats and security breaches, and to generate alerts.

security response automation

A predefined and programmed action that is designed to automatically respond to or remediate a security event. These automations serve as <u>detective</u> or <u>responsive</u> security controls that help you implement AWS security best practices. Examples of automated response actions include modifying a VPC security group, patching an Amazon EC2 instance, or rotating credentials. server-side encryption

Encryption of data at its destination, by the AWS service that receives it. service control policy (SCP)

A policy that provides centralized control over permissions for all accounts in an organization in AWS Organizations. SCPs define guardrails or set limits on actions that an administrator can delegate to users or roles. You can use SCPs as allow lists or deny lists, to specify which services or actions are permitted or prohibited. For more information, see <u>Service control policies</u> in the AWS Organizations documentation.

service endpoint

The URL of the entry point for an AWS service. You can use the endpoint to connect programmatically to the target service. For more information, see <u>AWS service endpoints</u> in *AWS General Reference*.

service-level agreement (SLA)

An agreement that clarifies what an IT team promises to deliver to their customers, such as service uptime and performance.

service-level indicator (SLI)

A measurement of a performance aspect of a service, such as its error rate, availability, or throughput.

service-level objective (SLO)

A target metric that represents the health of a service, as measured by a <u>service-level indicator</u>. shared responsibility model

A model describing the responsibility you share with AWS for cloud security and compliance. AWS is responsible for security *of* the cloud, whereas you are responsible for security *in* the cloud. For more information, see Shared responsibility model.

SIEM

See <u>security information and event management system</u>. single point of failure (SPOF)

A failure in a single, critical component of an application that can disrupt the system.

SLA

See service-level agreement.

SLI

See service-level indicator.

SLO

See service-level objective.

split-and-seed model

A pattern for scaling and accelerating modernization projects. As new features and product releases are defined, the core team splits up to create new product teams. This helps scale your

organization's capabilities and services, improves developer productivity, and supports rapid innovation. For more information, see <u>Phased approach to modernizing applications in the AWS</u> Cloud.

SPOF

See single point of failure.

star schema

A database organizational structure that uses one large fact table to store transactional or measured data and uses one or more smaller dimensional tables to store data attributes. This structure is designed for use in a <u>data warehouse</u> or for business intelligence purposes.

strangler fig pattern

An approach to modernizing monolithic systems by incrementally rewriting and replacing system functionality until the legacy system can be decommissioned. This pattern uses the analogy of a fig vine that grows into an established tree and eventually overcomes and replaces its host. The pattern was <u>introduced by Martin Fowler</u> as a way to manage risk when rewriting monolithic systems. For an example of how to apply this pattern, see <u>Modernizing legacy</u> <u>Microsoft ASP.NET (ASMX) web services incrementally by using containers and Amazon API Gateway</u>.

subnet

A range of IP addresses in your VPC. A subnet must reside in a single Availability Zone. supervisory control and data acquisition (SCADA)

In manufacturing, a system that uses hardware and software to monitor physical assets and production operations.

symmetric encryption

An encryption algorithm that uses the same key to encrypt and decrypt the data. synthetic testing

Testing a system in a way that simulates user interactions to detect potential issues or to monitor performance. You can use <u>Amazon CloudWatch Synthetics</u> to create these tests. system prompt

A technique for providing context, instructions, or guidelines to an <u>LLM</u> to direct its behavior. System prompts help set context and establish rules for interactions with users.

Т

tags

Key-value pairs that act as metadata for organizing your AWS resources. Tags can help you manage, identify, organize, search for, and filter resources. For more information, see <u>Tagging</u> your AWS resources.

target variable

The value that you are trying to predict in supervised ML. This is also referred to as an *outcome variable*. For example, in a manufacturing setting the target variable could be a product defect.

task list

A tool that is used to track progress through a runbook. A task list contains an overview of the runbook and a list of general tasks to be completed. For each general task, it includes the estimated amount of time required, the owner, and the progress.

test environment

See environment.

training

To provide data for your ML model to learn from. The training data must contain the correct answer. The learning algorithm finds patterns in the training data that map the input data attributes to the target (the answer that you want to predict). It outputs an ML model that captures these patterns. You can then use the ML model to make predictions on new data for which you don't know the target.

transit gateway

A network transit hub that you can use to interconnect your VPCs and on-premises networks. For more information, see <u>What is a transit gateway</u> in the AWS Transit Gateway documentation.

trunk-based workflow

An approach in which developers build and test features locally in a feature branch and then merge those changes into the main branch. The main branch is then built to the development, preproduction, and production environments, sequentially.

trusted access

Granting permissions to a service that you specify to perform tasks in your organization in AWS Organizations and in its accounts on your behalf. The trusted service creates a service-linked role in each account, when that role is needed, to perform management tasks for you. For more information, see <u>Using AWS Organizations with other AWS services</u> in the AWS Organizations documentation.

tuning

To change aspects of your training process to improve the ML model's accuracy. For example, you can train the ML model by generating a labeling set, adding labels, and then repeating these steps several times under different settings to optimize the model.

two-pizza team

A small DevOps team that you can feed with two pizzas. A two-pizza team size ensures the best possible opportunity for collaboration in software development.

U

uncertainty

A concept that refers to imprecise, incomplete, or unknown information that can undermine the reliability of predictive ML models. There are two types of uncertainty: *Epistemic uncertainty* is caused by limited, incomplete data, whereas *aleatoric uncertainty* is caused by the noise and randomness inherent in the data. For more information, see the <u>Quantifying uncertainty in</u> <u>deep learning systems</u> guide.

undifferentiated tasks

Also known as *heavy lifting*, work that is necessary to create and operate an application but that doesn't provide direct value to the end user or provide competitive advantage. Examples of undifferentiated tasks include procurement, maintenance, and capacity planning.

upper environments

See environment.

V

vacuuming

A database maintenance operation that involves cleaning up after incremental updates to reclaim storage and improve performance.

version control

Processes and tools that track changes, such as changes to source code in a repository.

VPC peering

A connection between two VPCs that allows you to route traffic by using private IP addresses. For more information, see <u>What is VPC peering</u> in the Amazon VPC documentation. vulnerability

A software or hardware flaw that compromises the security of the system.

W

warm cache

A buffer cache that contains current, relevant data that is frequently accessed. The database instance can read from the buffer cache, which is faster than reading from the main memory or disk.

warm data

Data that is infrequently accessed. When querying this kind of data, moderately slow queries are typically acceptable.

window function

A SQL function that performs a calculation on a group of rows that relate in some way to the current record. Window functions are useful for processing tasks, such as calculating a moving average or accessing the value of rows based on the relative position of the current row. workload

A collection of resources and code that delivers business value, such as a customer-facing application or backend process.

workstream

Functional groups in a migration project that are responsible for a specific set of tasks. Each workstream is independent but supports the other workstreams in the project. For example, the portfolio workstream is responsible for prioritizing applications, wave planning, and collecting migration metadata. The portfolio workstream delivers these assets to the migration workstream, which then migrates the servers and applications.

WORM

See write once, read many.

WQF

See <u>AWS Workload Qualification Framework</u>. write once, read many (WORM)

A storage model that writes data a single time and prevents the data from being deleted or modified. Authorized users can read the data as many times as needed, but they cannot change it. This data storage infrastructure is considered <u>immutable</u>.

Ζ

zero-day exploit

An attack, typically malware, that takes advantage of a zero-day vulnerability.

zero-day vulnerability

An unmitigated flaw or vulnerability in a production system. Threat actors can use this type of vulnerability to attack the system. Developers frequently become aware of the vulnerability as a result of the attack.

zero-shot prompting

Providing an <u>LLM</u> with instructions for performing a task but no examples (*shots*) that can help guide it. The LLM must use its pre-trained knowledge to handle the task. The effectiveness of zero-shot prompting depends on the complexity of the task and the quality of the prompt. See also <u>few-shot prompting</u>.

zombie application

An application that has an average CPU and memory usage below 5 percent. In a migration project, it is common to retire these applications.