



API Reference

AWS Proton



API Version 2020-07-20

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS Proton: API Reference

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	5
AcceptEnvironmentAccountConnection	9
Request Syntax	9
Request Parameters	9
Response Syntax	9
Response Elements	10
Errors	10
See Also	11
CancelComponentDeployment	12
Request Syntax	12
Request Parameters	12
Response Syntax	12
Response Elements	13
Errors	13
See Also	14
CancelEnvironmentDeployment	15
Request Syntax	15
Request Parameters	15
Response Syntax	15
Response Elements	16
Errors	17
See Also	17
CancelServiceInstanceDeployment	19
Request Syntax	19
Request Parameters	19
Response Syntax	20
Response Elements	20
Errors	21
See Also	21
CancelServicePipelineDeployment	23
Request Syntax	23
Request Parameters	23
Response Syntax	23

Response Elements	24
Errors	24
See Also	25
CreateComponent	26
Request Syntax	26
Request Parameters	26
Response Syntax	29
Response Elements	30
Errors	30
See Also	31
CreateEnvironment	32
Request Syntax	32
Request Parameters	33
Response Syntax	36
Response Elements	37
Errors	37
See Also	38
CreateEnvironmentAccountConnection	40
Request Syntax	40
Request Parameters	40
Response Syntax	43
Response Elements	43
Errors	43
See Also	44
CreateEnvironmentTemplate	46
Request Syntax	46
Request Parameters	46
Response Syntax	48
Response Elements	48
Errors	49
See Also	50
CreateEnvironmentTemplateVersion	51
Request Syntax	51
Request Parameters	51
Response Syntax	53
Response Elements	53

Errors	54
See Also	55
CreateRepository	56
Request Syntax	56
Request Parameters	56
Response Syntax	58
Response Elements	58
Errors	58
See Also	59
CreateService	61
Request Syntax	61
Request Parameters	61
Response Syntax	64
Response Elements	65
Errors	65
See Also	66
CreateServiceInstance	67
Request Syntax	67
Request Parameters	67
Response Syntax	69
Response Elements	70
Errors	70
See Also	71
CreateServiceSyncConfig	72
Request Syntax	72
Request Parameters	72
Response Syntax	73
Response Elements	73
Errors	74
See Also	75
CreateServiceTemplate	76
Request Syntax	76
Request Parameters	76
Response Syntax	78
Response Elements	78
Errors	79

See Also	79
CreateServiceTemplateVersion	81
Request Syntax	81
Request Parameters	81
Response Syntax	83
Response Elements	84
Errors	84
See Also	85
CreateTemplateSyncConfig	87
Request Syntax	87
Request Parameters	87
Response Syntax	89
Response Elements	89
Errors	89
See Also	90
DeleteComponent	92
Request Syntax	92
Request Parameters	92
Response Syntax	92
Response Elements	93
Errors	93
See Also	94
DeleteDeployment	95
Request Syntax	95
Request Parameters	95
Response Syntax	95
Response Elements	96
Errors	96
See Also	97
DeleteEnvironment	98
Request Syntax	98
Request Parameters	98
Response Syntax	98
Response Elements	99
Errors	99
See Also	100

DeleteEnvironmentAccountConnection	102
Request Syntax	102
Request Parameters	102
Response Syntax	102
Response Elements	103
Errors	103
See Also	104
DeleteEnvironmentTemplate	105
Request Syntax	105
Request Parameters	105
Response Syntax	105
Response Elements	106
Errors	106
See Also	107
DeleteEnvironmentTemplateVersion	108
Request Syntax	108
Request Parameters	108
Response Syntax	109
Response Elements	109
Errors	110
See Also	111
DeleteRepository	112
Request Syntax	112
Request Parameters	112
Response Syntax	112
Response Elements	113
Errors	113
See Also	114
DeleteService	115
Request Syntax	115
Request Parameters	115
Response Syntax	115
Response Elements	116
Errors	117
See Also	117
DeleteServiceSyncConfig	119

Request Syntax	119
Request Parameters	119
Response Syntax	119
Response Elements	120
Errors	120
See Also	121
DeleteServiceTemplate	122
Request Syntax	122
Request Parameters	122
Response Syntax	122
Response Elements	123
Errors	123
See Also	124
DeleteServiceTemplateVersion	125
Request Syntax	125
Request Parameters	125
Response Syntax	126
Response Elements	127
Errors	127
See Also	128
DeleteTemplateSyncConfig	129
Request Syntax	129
Request Parameters	129
Response Syntax	129
Response Elements	130
Errors	130
See Also	131
GetAccountSettings	132
Response Syntax	132
Response Elements	132
Errors	132
See Also	133
GetComponent	134
Request Syntax	134
Request Parameters	134
Response Syntax	134

Response Elements	135
Errors	135
See Also	136
GetDeployment	137
Request Syntax	137
Request Parameters	137
Response Syntax	138
Response Elements	139
Errors	139
See Also	140
GetEnvironment	141
Request Syntax	141
Request Parameters	141
Response Syntax	141
Response Elements	142
Errors	142
See Also	143
GetEnvironmentAccountConnection	144
Request Syntax	144
Request Parameters	144
Response Syntax	144
Response Elements	145
Errors	145
See Also	146
GetEnvironmentTemplate	147
Request Syntax	147
Request Parameters	147
Response Syntax	147
Response Elements	148
Errors	148
See Also	149
GetEnvironmentTemplateVersion	150
Request Syntax	150
Request Parameters	150
Response Syntax	151
Response Elements	151

Errors	152
See Also	152
GetRepository	154
Request Syntax	154
Request Parameters	154
Response Syntax	154
Response Elements	155
Errors	155
See Also	156
GetRepositorySyncStatus	157
Request Syntax	157
Request Parameters	157
Response Syntax	158
Response Elements	159
Errors	159
See Also	160
GetResourcesSummary	161
Response Syntax	161
Response Elements	162
Errors	163
See Also	163
GetService	165
Request Syntax	165
Request Parameters	165
Response Syntax	165
Response Elements	166
Errors	166
See Also	167
GetServiceInstance	168
Request Syntax	168
Request Parameters	168
Response Syntax	169
Response Elements	169
Errors	169
See Also	170
GetServiceInstanceStateSyncStatus	172

Request Syntax	172
Request Parameters	172
Response Syntax	173
Response Elements	174
Errors	175
See Also	175
GetServiceSyncBlockerSummary	177
Request Syntax	177
Request Parameters	177
Response Syntax	178
Response Elements	178
Errors	178
See Also	179
GetServiceSyncConfig	181
Request Syntax	181
Request Parameters	181
Response Syntax	181
Response Elements	182
Errors	182
See Also	183
GetServiceTemplate	184
Request Syntax	184
Request Parameters	184
Response Syntax	184
Response Elements	185
Errors	185
See Also	186
GetServiceTemplateVersion	187
Request Syntax	187
Request Parameters	187
Response Syntax	188
Response Elements	188
Errors	189
See Also	189
GetTemplateSyncConfig	191
Request Syntax	191

Request Parameters	191
Response Syntax	191
Response Elements	192
Errors	192
See Also	193
GetTemplateSyncStatus	194
Request Syntax	194
Request Parameters	194
Response Syntax	195
Response Elements	196
Errors	197
See Also	197
ListComponentOutputs	199
Request Syntax	199
Request Parameters	199
Response Syntax	200
Response Elements	200
Errors	201
See Also	201
ListComponentProvisionedResources	203
Request Syntax	203
Request Parameters	203
Response Syntax	204
Response Elements	204
Errors	204
See Also	205
ListComponents	207
Request Syntax	207
Request Parameters	207
Response Syntax	208
Response Elements	209
Errors	209
See Also	210
ListDeployments	211
Request Syntax	211
Request Parameters	211

Response Syntax	213
Response Elements	213
Errors	214
See Also	214
ListEnvironmentAccountConnections	216
Request Syntax	216
Request Parameters	216
Response Syntax	217
Response Elements	218
Errors	218
See Also	219
ListEnvironmentOutputs	220
Request Syntax	220
Request Parameters	220
Response Syntax	221
Response Elements	221
Errors	221
See Also	222
ListEnvironmentProvisionedResources	224
Request Syntax	224
Request Parameters	224
Response Syntax	225
Response Elements	225
Errors	225
See Also	226
ListEnvironments	228
Request Syntax	228
Request Parameters	228
Response Syntax	229
Response Elements	229
Errors	230
See Also	231
ListEnvironmentTemplates	232
Request Syntax	232
Request Parameters	232
Response Syntax	232

Response Elements	233
Errors	233
See Also	234
ListEnvironmentTemplateVersions	235
Request Syntax	235
Request Parameters	235
Response Syntax	236
Response Elements	237
Errors	237
See Also	238
ListRepositories	239
Request Syntax	239
Request Parameters	239
Response Syntax	239
Response Elements	240
Errors	240
See Also	241
ListRepositorySyncDefinitions	242
Request Syntax	242
Request Parameters	242
Response Syntax	243
Response Elements	243
Errors	244
See Also	244
ListServiceInstanceStateOutputs	246
Request Syntax	246
Request Parameters	246
Response Syntax	247
Response Elements	247
Errors	248
See Also	248
ListServiceInstanceProvisionedResources	250
Request Syntax	250
Request Parameters	250
Response Syntax	251
Response Elements	251

Errors	252
See Also	252
ListServiceInstances	254
Request Syntax	254
Request Parameters	254
Response Syntax	256
Response Elements	256
Errors	257
See Also	257
ListServicePipelineOutputs	259
Request Syntax	259
Request Parameters	259
Response Syntax	260
Response Elements	260
Errors	260
See Also	261
ListServicePipelineProvisionedResources	263
Request Syntax	263
Request Parameters	263
Response Syntax	263
Response Elements	264
Errors	264
See Also	265
ListServices	266
Request Syntax	266
Request Parameters	266
Response Syntax	266
Response Elements	267
Errors	267
See Also	268
ListServiceTemplates	269
Request Syntax	269
Request Parameters	269
Response Syntax	269
Response Elements	270
Errors	270

See Also	271
ListServiceTemplateVersions	272
Request Syntax	272
Request Parameters	272
Response Syntax	273
Response Elements	274
Errors	274
See Also	275
ListTagsForResource	276
Request Syntax	276
Request Parameters	276
Response Syntax	277
Response Elements	277
Errors	278
See Also	278
NotifyResourceDeploymentStatusChange	280
Request Syntax	280
Request Parameters	280
Response Elements	281
Errors	281
See Also	282
RejectEnvironmentAccountConnection	284
Request Syntax	284
Request Parameters	284
Response Syntax	284
Response Elements	285
Errors	285
See Also	286
TagResource	287
Request Syntax	287
Request Parameters	287
Response Elements	288
Errors	288
See Also	289
UntagResource	290
Request Syntax	290

Request Parameters	290
Response Elements	291
Errors	291
See Also	292
UpdateAccountSettings	293
Request Syntax	293
Request Parameters	293
Response Syntax	294
Response Elements	295
Errors	295
See Also	296
UpdateComponent	297
Request Syntax	297
Request Parameters	297
Response Syntax	300
Response Elements	300
Errors	301
See Also	302
UpdateEnvironment	303
Request Syntax	304
Request Parameters	304
Response Syntax	308
Response Elements	309
Errors	309
See Also	310
UpdateEnvironmentAccountConnection	312
Request Syntax	312
Request Parameters	312
Response Syntax	313
Response Elements	314
Errors	314
See Also	315
UpdateEnvironmentTemplate	316
Request Syntax	316
Request Parameters	316
Response Syntax	317

Response Elements	317
Errors	317
See Also	318
UpdateEnvironmentTemplateVersion	320
Request Syntax	320
Request Parameters	320
Response Syntax	321
Response Elements	322
Errors	322
See Also	323
UpdateService	324
Request Syntax	324
Request Parameters	324
Response Syntax	325
Response Elements	326
Errors	326
See Also	327
UpdateServiceInstance	329
Request Syntax	329
Request Parameters	329
Response Syntax	332
Response Elements	332
Errors	333
See Also	333
UpdateServicePipeline	335
Request Syntax	335
Request Parameters	336
Response Syntax	338
Response Elements	338
Errors	338
See Also	339
UpdateServiceSyncBlocker	341
Request Syntax	341
Request Parameters	341
Response Syntax	341
Response Elements	342

Errors	343
See Also	343
UpdateServiceSyncConfig	345
Request Syntax	345
Request Parameters	345
Response Syntax	346
Response Elements	346
Errors	347
See Also	348
UpdateServiceTemplate	349
Request Syntax	349
Request Parameters	349
Response Syntax	350
Response Elements	350
Errors	350
See Also	351
UpdateServiceTemplateVersion	353
Request Syntax	353
Request Parameters	353
Response Syntax	355
Response Elements	356
Errors	356
See Also	357
UpdateTemplateSyncConfig	358
Request Syntax	358
Request Parameters	358
Response Syntax	360
Response Elements	360
Errors	360
See Also	361
Data Types	362
AccountSettings	365
Contents	365
See Also	366
CompatibleEnvironmentTemplate	367
Contents	367

See Also	367
CompatibleEnvironmentTemplateInput	368
Contents	368
See Also	368
Component	369
Contents	369
See Also	372
ComponentState	373
Contents	373
See Also	374
ComponentSummary	375
Contents	375
See Also	378
CountsSummary	379
Contents	379
See Also	380
Deployment	381
Contents	381
See Also	385
DeploymentState	386
Contents	386
See Also	387
DeploymentSummary	388
Contents	388
See Also	391
Environment	392
Contents	392
See Also	397
EnvironmentAccountConnection	398
Contents	398
See Also	400
EnvironmentAccountConnectionSummary	402
Contents	402
See Also	404
EnvironmentState	405
Contents	405

See Also	406
EnvironmentSummary	407
Contents	407
See Also	411
EnvironmentTemplate	412
Contents	412
See Also	414
EnvironmentTemplateFilter	415
Contents	415
See Also	415
EnvironmentTemplateSummary	416
Contents	416
See Also	417
EnvironmentTemplateVersion	419
Contents	419
See Also	421
EnvironmentTemplateVersionSummary	422
Contents	422
See Also	424
ListServiceInstancesFilter	425
Contents	425
See Also	425
Output	426
Contents	426
See Also	426
ProvisionedResource	427
Contents	427
See Also	427
Repository	429
Contents	429
See Also	430
RepositoryBranch	431
Contents	431
See Also	432
RepositoryBranchInput	433
Contents	433

See Also	433
RepositorySummary	435
Contents	435
See Also	436
RepositorySyncAttempt	437
Contents	437
See Also	437
RepositorySyncDefinition	438
Contents	438
See Also	438
RepositorySyncEvent	440
Contents	440
See Also	440
ResourceCountsSummary	442
Contents	442
See Also	443
ResourceSyncAttempt	444
Contents	444
See Also	445
ResourceSyncEvent	446
Contents	446
See Also	446
Revision	448
Contents	448
See Also	449
S3ObjectSource	450
Contents	450
See Also	450
Service	451
Contents	451
See Also	454
ServiceInstance	455
Contents	455
See Also	458
ServiceInstanceState	459
Contents	459

See Also	460
ServiceInstanceSummary	462
Contents	462
See Also	465
ServicePipeline	466
Contents	466
See Also	468
ServicePipelineState	469
Contents	469
See Also	470
ServiceSummary	471
Contents	471
See Also	472
ServiceSyncBlockerSummary	474
Contents	474
See Also	475
ServiceSyncConfig	476
Contents	476
See Also	477
ServiceTemplate	478
Contents	478
See Also	480
ServiceTemplateSummary	481
Contents	481
See Also	482
ServiceTemplateVersion	484
Contents	484
See Also	487
ServiceTemplateVersionSummary	488
Contents	488
See Also	490
SyncBlocker	491
Contents	491
See Also	492
SyncBlockerContext	493
Contents	493

See Also	493
Tag	494
Contents	494
See Also	494
TemplateSyncConfig	495
Contents	495
See Also	496
TemplateVersionSourceInput	497
Contents	497
See Also	497
Common Parameters	498
Common Errors	501

Welcome

This is the AWS Proton Service API Reference. It provides descriptions, syntax and usage examples for each of the [actions](#) and [data types](#) for the AWS Proton service.

The documentation for each action shows the Query API request parameters and the XML response.

Alternatively, you can use the AWS CLI to access an API. For more information, see the [AWS Command Line Interface User Guide](#).

The AWS Proton service is a two-pronged automation framework. Administrators create service templates to provide standardized infrastructure and deployment tooling for serverless and container based applications. Developers, in turn, select from the available service templates to automate their application or service deployments.

Because administrators define the infrastructure and tooling that AWS Proton deploys and manages, they need permissions to use all of the listed API operations.

When developers select a specific infrastructure and tooling set, AWS Proton deploys their applications. To monitor their applications that are running on AWS Proton, developers need permissions to the service *create*, *list*, *update* and *delete* API operations and the service instance *list* and *update* API operations.

To learn more about AWS Proton, see the [AWS Proton User Guide](#).

Ensuring Idempotency

When you make a mutating API request, the request typically returns a result before the asynchronous workflows of the operation are complete. Operations might also time out or encounter other server issues before they're complete, even if the request already returned a result. This might make it difficult to determine whether the request succeeded. Moreover, you might need to retry the request multiple times to ensure that the operation completes successfully. However, if the original request and the subsequent retries are successful, the operation occurs multiple times. This means that you might create more resources than you intended.

Idempotency ensures that an API request action completes no more than one time. With an idempotent request, if the original request action completes successfully, any subsequent retries complete successfully without performing any further actions. However, the result might contain updated information, such as the current creation status.

The following lists of APIs are grouped according to methods that ensure idempotency.

Idempotent create APIs with a client token

The API actions in this list support idempotency with the use of a *client token*. The corresponding AWS CLI commands also support idempotency using a client token. A client token is a unique, case-sensitive string of up to 64 ASCII characters. To make an idempotent API request using one of these actions, specify a client token in the request. We recommend that you *don't* reuse the same client token for other API requests. If you don't provide a client token for these APIs, a default client token is automatically provided by SDKs.

Given a request action that has succeeded:

If you retry the request using the same client token and the same parameters, the retry succeeds without performing any further actions other than returning the original resource detail data in the response.

If you retry the request using the same client token, but one or more of the parameters are different, the retry throws a `ValidationException` with an `IdempotentParameterMismatch` error.

Client tokens expire eight hours after a request is made. If you retry the request with the expired token, a new resource is created.

If the original resource is deleted and you retry the request, a new resource is created.

Idempotent create APIs with a client token:

- `CreateEnvironmentTemplateVersion`
- `CreateServiceTemplateVersion`
- `CreateEnvironmentAccountConnection`

Idempotent create APIs

Given a request action that has succeeded:

If you retry the request with an API from this group, and the original resource *hasn't* been modified, the retry succeeds without performing any further actions other than returning the original resource detail data in the response.

If the original resource has been modified, the retry throws a `ConflictException`.

If you retry with different input parameters, the retry throws a `ValidationException` with an `IdempotentParameterMismatch` error.

Idempotent create APIs:

- `CreateEnvironmentTemplate`
- `CreateServiceTemplate`
- `CreateEnvironment`
- `CreateService`

Idempotent delete APIs

Given a request action that has succeeded:

When you retry the request with an API from this group and the resource was deleted, its metadata is returned in the response.

If you retry and the resource doesn't exist, the response is empty.

In both cases, the retry succeeds.

Idempotent delete APIs:

- `DeleteEnvironmentTemplate`
- `DeleteEnvironmentTemplateVersion`
- `DeleteServiceTemplate`
- `DeleteServiceTemplateVersion`
- `DeleteEnvironmentAccountConnection`

Asynchronous idempotent delete APIs

Given a request action that has succeeded:

If you retry the request with an API from this group, if the original request delete operation status is `DELETE_IN_PROGRESS`, the retry returns the resource detail data in the response without performing any further actions.

If the original request delete operation is complete, a retry returns an empty response.

Asynchronous idempotent delete APIs:

- **DeleteEnvironment**
- **DeleteService**

This document was last published on July 18, 2025.

Actions

The following actions are supported:

- [AcceptEnvironmentAccountConnection](#)
- [CancelComponentDeployment](#)
- [CancelEnvironmentDeployment](#)
- [CancelServiceInstanceDeployment](#)
- [CancelServicePipelineDeployment](#)
- [CreateComponent](#)
- [CreateEnvironment](#)
- [CreateEnvironmentAccountConnection](#)
- [CreateEnvironmentTemplate](#)
- [CreateEnvironmentTemplateVersion](#)
- [CreateRepository](#)
- [CreateService](#)
- [CreateServiceInstance](#)
- [CreateServiceSyncConfig](#)
- [CreateServiceTemplate](#)
- [CreateServiceTemplateVersion](#)
- [CreateTemplateSyncConfig](#)
- [DeleteComponent](#)
- [DeleteDeployment](#)
- [DeleteEnvironment](#)
- [DeleteEnvironmentAccountConnection](#)
- [DeleteEnvironmentTemplate](#)
- [DeleteEnvironmentTemplateVersion](#)
- [DeleteRepository](#)
- [DeleteService](#)
- [DeleteServiceSyncConfig](#)
- [DeleteServiceTemplate](#)

- [DeleteServiceTemplateVersion](#)
- [DeleteTemplateSyncConfig](#)
- [GetAccountSettings](#)
- [GetComponent](#)
- [GetDeployment](#)
- [GetEnvironment](#)
- [GetEnvironmentAccountConnection](#)
- [GetEnvironmentTemplate](#)
- [GetEnvironmentTemplateVersion](#)
- [GetRepository](#)
- [GetRepositorySyncStatus](#)
- [GetResourcesSummary](#)
- [GetService](#)
- [GetServiceInstance](#)
- [GetServiceInstanceStateSyncStatus](#)
- [GetServiceSyncBlockerSummary](#)
- [GetServiceSyncConfig](#)
- [GetServiceTemplate](#)
- [GetServiceTemplateVersion](#)
- [GetTemplateSyncConfig](#)
- [GetTemplateSyncStatus](#)
- [ListComponentOutputs](#)
- [ListComponentProvisionedResources](#)
- [ListComponents](#)
- [ListDeployments](#)
- [ListEnvironmentAccountConnections](#)
- [ListEnvironmentOutputs](#)
- [ListEnvironmentProvisionedResources](#)
- [ListEnvironments](#)
- [ListEnvironmentTemplates](#)

- [ListEnvironmentTemplateVersions](#)
- [ListRepositories](#)
- [ListRepositorySyncDefinitions](#)
- [ListServiceInstanceOutputs](#)
- [ListServiceInstanceProvisionedResources](#)
- [ListServiceInstances](#)
- [ListServicePipelineOutputs](#)
- [ListServicePipelineProvisionedResources](#)
- [ListServices](#)
- [ListServiceTemplates](#)
- [ListServiceTemplateVersions](#)
- [ListTagsForResource](#)
- [NotifyResourceDeploymentStatusChange](#)
- [RejectEnvironmentAccountConnection](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateAccountSettings](#)
- [UpdateComponent](#)
- [UpdateEnvironment](#)
- [UpdateEnvironmentAccountConnection](#)
- [UpdateEnvironmentTemplate](#)
- [UpdateEnvironmentTemplateVersion](#)
- [UpdateService](#)
- [UpdateServiceInstance](#)
- [UpdateServicePipeline](#)
- [UpdateServiceSyncBlocker](#)
- [UpdateServiceSyncConfig](#)
- [UpdateServiceTemplate](#)
- [UpdateServiceTemplateVersion](#)
- [UpdateTemplateSyncConfig](#)

AcceptEnvironmentAccountConnection

In a management account, an environment account connection request is accepted. When the environment account connection request is accepted, AWS Proton can use the associated IAM role to provision environment infrastructure resources in the associated environment account.

For more information, see [Environment account connections](#) in the *AWS Proton User guide*.

Request Syntax

```
{  
  "id": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

id

The ID of the environment account connection.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

Response Syntax

```
{  
  "environmentAccountConnection": {  
    "arn": "string",  
    "codebuildRoleArn": "string",  
    "componentRoleArn": "string",  
    "environmentAccountId": "string",  
    "environmentName": "string",  
    "id": "string",  
    "lastModifiedAt": number,  
  },  
}
```

```
"managementAccountId": "string",
"requestedAt": number,
"roleArn": "string",
"status": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[environmentAccountConnection](#)

The environment account connection data that's returned by AWS Proton.

Type: [EnvironmentAccountConnection](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CancelComponentDeployment

Attempts to cancel a component deployment (for a component that is in the IN_PROGRESS deployment status).

For more information about components, see [AWS Proton components](#) in the *AWS Proton User Guide*.

Request Syntax

```
{  
  "componentName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

componentName

The name of the component with the deployment to cancel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{  
  "component": {  
    "arn": "string",  
    "createdAt": number,  
    "deploymentStatus": "string",  
    "deploymentStatusMessage": "string",  
  },  
  "status": "string",  
  "statusMessage": "string",  
  "version": "string",  
  "versionMessage": "string",  
  "versionArn": "string",  
  "versionCreatedAt": number  
}
```

```
"description": "string",  
"environmentName": "string",  
"lastAttemptedDeploymentId": "string",  
"lastClientRequestToken": "string",  
"lastDeploymentAttemptedAt": number,  
"lastDeploymentSucceededAt": number,  
"lastModifiedAt": number,  
"lastSucceededDeploymentId": "string",  
"name": "string",  
"serviceInstanceName": "string",  
"serviceName": "string",  
"serviceSpec": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

component

The detailed data of the component with the deployment that is being canceled.

Type: [Component](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CancelEnvironmentDeployment

Attempts to cancel an environment deployment on an [UpdateEnvironment](#) action, if the deployment is IN_PROGRESS. For more information, see [Update an environment](#) in the *AWS Proton User guide*.

The following list includes potential cancellation scenarios.

- If the cancellation attempt succeeds, the resulting deployment state is CANCELLED.
- If the cancellation attempt fails, the resulting deployment state is FAILED.
- If the current [UpdateEnvironment](#) action succeeds before the cancellation attempt starts, the resulting deployment state is SUCCEEDED and the cancellation attempt has no effect.

Request Syntax

```
{  
  "environmentName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[environmentName](#)

The name of the environment with the deployment to cancel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{
```

```
"environment    "arn    "codebuildRoleArn    "componentRoleArn    "createdAt    "deploymentStatus    "deploymentStatusMessage    "description    "environmentAccountConnectionId    "environmentAccountId    "lastAttemptedDeploymentId    "lastDeploymentAttemptedAt    "lastDeploymentSucceededAt    "lastSucceededDeploymentId    "name    "protonServiceRoleArn    "provisioning    "provisioningRepository        "arn        "branch        "name        "provider    },  
    "spec    "templateMajorVersion    "templateMinorVersion    "templateName}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

environment

The environment summary data that's returned by AWS Proton.

Type: [Environment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CancelServiceInstanceDeployment

Attempts to cancel a service instance deployment on an [UpdateServiceInstance](#) action, if the deployment is IN_PROGRESS. For more information, see [Update a service instance](#) in the *AWS Proton User guide*.

The following list includes potential cancellation scenarios.

- If the cancellation attempt succeeds, the resulting deployment state is CANCELLED.
- If the cancellation attempt fails, the resulting deployment state is FAILED.
- If the current [UpdateServiceInstance](#) action succeeds before the cancellation attempt starts, the resulting deployment state is SUCCEEDED and the cancellation attempt has no effect.

Request Syntax

```
{  
    "serviceInstanceId": "string",  
    "serviceName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

serviceInstanceId

The name of the service instance with the deployment to cancel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

serviceName

The name of the service with the service instance deployment to cancel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{  
    "serviceInstance": {  
        "arn": "string",  
        "createdAt": number,  
        "deploymentStatus": "string",  
        "deploymentStatusMessage": "string",  
        "environmentName": "string",  
        "lastAttemptedDeploymentId": "string",  
        "lastClientRequestToken": "string",  
        "lastDeploymentAttemptedAt": number,  
        "lastDeploymentSucceededAt": number,  
        "lastSucceededDeploymentId": "string",  
        "name": "string",  
        "serviceName": "string",  
        "spec": "string",  
        "templateMajorVersion": "string",  
        "templateMinorVersion": "string",  
        "templateName": "string"  
    }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

serviceInstance

The service instance summary data that's returned by AWS Proton.

Type: [ServiceInstance](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CancelServicePipelineDeployment

Attempts to cancel a service pipeline deployment on an [UpdateServicePipeline](#) action, if the deployment is IN_PROGRESS. For more information, see [Update a service pipeline](#) in the *AWS Proton User guide*.

The following list includes potential cancellation scenarios.

- If the cancellation attempt succeeds, the resulting deployment state is CANCELLED.
- If the cancellation attempt fails, the resulting deployment state is FAILED.
- If the current [UpdateServicePipeline](#) action succeeds before the cancellation attempt starts, the resulting deployment state is SUCCEEDED and the cancellation attempt has no effect.

Request Syntax

```
{  
  "serviceName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[serviceName](#)

The name of the service with the service pipeline deployment to cancel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{
```

```
"pipeline": {  
    "arn    "createdAt": number,  
    "deploymentStatus": "string",  
    "deploymentStatusMessage": "string",  
    "lastAttemptedDeploymentId": "string",  
    "lastDeploymentAttemptedAt": number,  
    "lastDeploymentSucceededAt": number,  
    "lastSucceededDeploymentId": "string",  
    "spec": "string",  
    "templateMajorVersion": "string",  
    "templateMinorVersion": "string",  
    "templateName": "string"  
}  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

pipeline

The service pipeline detail data that's returned by AWS Proton.

Type: [ServicePipeline](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateComponent

Create an AWS Proton component. A component is an infrastructure extension for a service instance.

For more information about components, see [AWS Proton components](#) in the *AWS Proton User Guide*.

Request Syntax

```
{
  "clientToken": "string",
  "description": "string",
  "environmentName": "string",
  "manifest": "string",
  "name": "string",
  "serviceInstanceName": "string",
  "serviceName": "string",
  "serviceSpec": "string",
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ],
  "templateFile": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[clientToken](#)

The client token for the created component.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 64.

Pattern: [! -~]*

Required: No

[description](#)

An optional customer-provided description of the component.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

[environmentName](#)

The name of the AWS Proton environment that you want to associate this component with. You must specify this when you don't specify `serviceInstanceName` and `serviceName`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: No

[manifest](#)

A path to a manifest file that lists the Infrastructure as Code (IaC) file, template language, and rendering engine for infrastructure that a custom component provisions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

[name](#)

The customer-provided name of the component.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

serviceInstanceName

The name of the service instance that you want to attach this component to. If you don't specify this, the component isn't attached to any service instance. Specify both `serviceInstanceName` and `serviceName` or neither of them.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[0-9A-Za-z]+[0-9A-Za-z_-\\-]*`

Required: No

serviceName

The name of the service that `serviceInstanceName` is associated with. If you don't specify this, the component isn't attached to any service instance. Specify both `serviceInstanceName` and `serviceName` or neither of them.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[0-9A-Za-z]+[0-9A-Za-z_-\\-]*`

Required: No

serviceSpec

The service spec that you want the component to use to access service inputs. Set this only when you attach the component to a service instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 51200.

Required: No

tags

An optional list of metadata items that you can associate with the AWS Proton component. A tag is a key-value pair.

For more information, see [AWS Proton resources and tagging](#) in the *AWS Proton User Guide*.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

[templateFile](#)

A path to the Infrastructure as Code (IaC) file describing infrastructure that a custom component provisions.

 **Note**

Components support a single IaC file, even if you use Terraform as your template language.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 51200.

Required: Yes

Response Syntax

```
{  
  "component": {  
    "arn": "string",  
    "createdAt": number,  
    "deploymentStatus": "string",  
    "deploymentStatusMessage": "string",  
    "description": "string",  
    "environmentName": "string",  
    "lastAttemptedDeploymentId": "string",  
    "lastClientRequestToken": "string",  
    "lastDeploymentAttemptedAt": number,  
    "lastDeploymentSucceededAt": number,  
    "lastModifiedAt": number,  
    "lastSucceededDeploymentId": "string",  
    "name": "string",  
  },  
}
```

```
    "serviceInstanceName": "string",
    "serviceName": "string",
    "serviceSpec": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[component](#)

The detailed data of the created component.

Type: [Component](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ServiceQuotaExceededException

A quota was exceeded. For more information, see [AWS Proton Quotas](#) in the *AWS Proton User Guide*.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateEnvironment

Deploy a new environment. An AWS Proton environment is created from an environment template that defines infrastructure and resources that can be shared across services.

You can provision environments using the following methods:

- AWS-managed provisioning: AWS Proton makes direct calls to provision your resources.
- Self-managed provisioning: AWS Proton makes pull requests on your repository to provide compiled infrastructure as code (IaC) files that your IaC engine uses to provision resources.

For more information, see [Environments](#) and [Provisioning methods](#) in the *AWS Proton User Guide*.

Request Syntax

```
{  
  "codebuildRoleArn": "string",  
  "componentRoleArn": "string",  
  "description": "string",  
  "environmentAccountConnectionId": "string",  
  "name": "string",  
  "protonServiceRoleArn": "string",  
  "provisioningRepository": {  
    "branch": "string",  
    "name": "string",  
    "provider": "string"  
  },  
  "spec": "string",  
  "tags": [  
    {  
      "key": "string",  
      "value": "string"  
    }  
  ],  
  "templateMajorVersion": "string",  
  "templateMinorVersion": "string",  
  "templateName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[codebuildRoleArn](#)

The Amazon Resource Name (ARN) of the IAM service role that allows AWS Proton to provision infrastructure using CodeBuild-based provisioning on your behalf.

To use CodeBuild-based provisioning for the environment or for any service instance running in the environment, specify either the `environmentAccountConnectionId` or `codebuildRoleArn` parameter.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:(aws|aws-cn|aws-us-gov):iam::\d{12}:role/([\w+=,.@-]{1,512}[/:]*)([\w+=,.@-]{1,64})`

Required: No

[componentRoleArn](#)

The Amazon Resource Name (ARN) of the IAM service role that AWS Proton uses when provisioning directly defined components in this environment. It determines the scope of infrastructure that a component can provision.

You must specify `componentRoleArn` to allow directly defined components to be associated with this environment.

For more information about components, see [AWS Proton components](#) in the *AWS Proton User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:(aws|aws-cn|aws-us-gov):iam::\d{12}:role/([\w+=,.@-]{1,512}[/:]*)([\w+=,.@-]{1,64})`

Required: No

description

A description of the environment that's being created and deployed.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

environmentAccountConnectionId

The ID of the environment account connection that you provide if you're provisioning your environment infrastructure resources to an environment account. For more information, see [Environment account connections](#) in the *AWS Proton User guide*.

To use AWS-managed provisioning for the environment, specify either the `environmentAccountConnectionId` or `protonServiceRoleArn` parameter and omit the `provisioningRepository` parameter.

Type: String

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: No

name

The name of the environment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[0-9A-Za-z]+[0-9A-Za-z_-]*`

Required: Yes

protonServiceRoleArn

The Amazon Resource Name (ARN) of the AWS Proton service role that allows AWS Proton to make calls to other services on your behalf.

To use AWS-managed provisioning for the environment, specify either the `environmentAccountConnectionId` or `protonServiceRoleArn` parameter and omit the `provisioningRepository` parameter.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: arn:(aws|aws-cn|aws-us-gov):[a-zA-Z0-9-]+:[a-zA-Z0-9-]*:\d{12}:([\w+=,.@-]+[/:])*[\w+=,.@-]+

Required: No

[provisioningRepository](#)

The linked repository that you use to host your rendered infrastructure templates for self-managed provisioning. A linked repository is a repository that has been registered with AWS Proton. For more information, see [CreateRepository](#).

To use self-managed provisioning for the environment, specify this parameter and omit the `environmentAccountConnectionId` and `protonServiceRoleArn` parameters.

Type: [RepositoryBranchInput](#) object

Required: No

[spec](#)

A YAML formatted string that provides inputs as defined in the environment template bundle schema file. For more information, see [Environments](#) in the *AWS Proton User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 51200.

Required: Yes

[tags](#)

An optional list of metadata items that you can associate with the AWS Proton environment. A tag is a key-value pair.

For more information, see [AWS Proton resources and tagging](#) in the *AWS Proton User Guide*.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

[templateMajorVersion](#)

The major version of the environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (0|([1-9]{1}\d*))

Required: Yes

[templateMinorVersion](#)

The minor version of the environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (0|([1-9]{1}\d*))

Required: No

[templateName](#)

The name of the environment template. For more information, see [Environment Templates](#) in the *AWS Proton User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{  
  "environment": {  
    "arn": "string",  
    "codebuildRoleArn": "string",  
  },  
}
```

```
"componentRoleArn": "string",
"createdAt": "number",
"deploymentStatus": "string",
"deploymentStatusMessage": "string",
"description": "string",
"environmentAccountConnectionId": "string",
"environmentAccountId": "string",
"lastAttemptedDeploymentId": "string",
"lastDeploymentAttemptedAt": "number",
"lastDeploymentSucceededAt": "number",
"lastSucceededDeploymentId": "string",
"name": "string",
"protonServiceRoleArn": "string",
"provisioning": "string",
"provisioningRepository": {
    "arn": "string",
    "branch": "string",
    "name": "string",
    "provider": "string"
},
"spec": "string",
"templateMajorVersion": "string",
"templateMinorVersion": "string",
"templateName": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

environment

The environment detail data that's returned by AWS Proton.

Type: [Environment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ServiceQuotaExceededException

A quota was exceeded. For more information, see [AWS Proton Quotas](#) in the *AWS Proton User Guide*.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateEnvironmentAccountConnection

Create an environment account connection in an environment account so that environment infrastructure resources can be provisioned in the environment account from a management account.

An environment account connection is a secure bi-directional connection between a *management account* and an *environment account* that maintains authorization and permissions. For more information, see [Environment account connections](#) in the *AWS Proton User guide*.

Request Syntax

```
{  
    "clientToken": "string",  
    "codebuildRoleArn": "string",  
    "componentRoleArn": "string",  
    "environmentName": "string",  
    "managementAccountId": "string",  
    "roleArn": "string",  
    "tags": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[clientToken](#)

When included, if two identical requests are made with the same client token, AWS Proton returns the environment account connection that the first request created.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 64.

Pattern: [! -~]*

Required: No

[codebuildRoleArn](#)

The Amazon Resource Name (ARN) of an IAM service role in the environment account. AWS Proton uses this role to provision infrastructure resources using CodeBuild-based provisioning in the associated environment account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: arn:(aws|aws-cn|aws-us-gov):iam::\d{12}:role/([\w+=,.@-]{1,512}[/])*([\w+=,.@-]{1,64})

Required: No

[componentRoleArn](#)

The Amazon Resource Name (ARN) of the IAM service role that AWS Proton uses when provisioning directly defined components in the associated environment account. It determines the scope of infrastructure that a component can provision in the account.

You must specify `componentRoleArn` to allow directly defined components to be associated with any environments running in this account.

For more information about components, see [AWS Proton components](#) in the *AWS Proton User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: arn:(aws|aws-cn|aws-us-gov):iam::\d{12}:role/([\w+=,.@-]{1,512}[/])*([\w+=,.@-]{1,64})

Required: No

[environmentName](#)

The name of the AWS Proton environment that's created in the associated management account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

managementAccountId

The ID of the management account that accepts or rejects the environment account connection. You create and manage the AWS Proton environment in this account. If the management account accepts the environment account connection, AWS Proton can use the associated IAM role to provision environment infrastructure resources in the associated environment account.

Type: String

Pattern: \d{12}

Required: Yes

roleArn

The Amazon Resource Name (ARN) of the IAM service role that's created in the environment account. AWS Proton uses this role to provision infrastructure resources in the associated environment account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: arn:(aws|aws-cn|aws-us-gov):iam::\d{12}:role/([\w+=,.@-]{1,512}[/:]*)([\w+=,.@-]{1,64})

Required: No

tags

An optional list of metadata items that you can associate with the AWS Proton environment account connection. A tag is a key-value pair.

For more information, see [AWS Proton resources and tagging](#) in the *AWS Proton User Guide*.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

Response Syntax

```
{  
  "environmentAccountConnection": [  
    {"arn": "string",  
     "codebuildRoleArn": "string",  
     "componentRoleArn": "string",  
     "environmentAccountId": "string",  
     "environmentName": "string",  
     "id": "string",  
     "lastModifiedAt": number,  
     "managementAccountId": "string",  
     "requestedAt": number,  
     "roleArn": "string",  
     "status": "string"  
   ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[environmentAccountConnection](#)

The environment account connection detail data that's returned by AWS Proton.

Type: [EnvironmentAccountConnection](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ServiceQuotaExceededException

A quota was exceeded. For more information, see [AWS Proton Quotas](#) in the *AWS Proton User Guide*.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateEnvironmentTemplate

Create an environment template for AWS Proton. For more information, see [Environment Templates](#) in the *AWS Proton User Guide*.

You can create an environment template in one of the two following ways:

- Register and publish a *standard* environment template that instructs AWS Proton to deploy and manage environment infrastructure.
- Register and publish a *customer managed* environment template that connects AWS Proton to your existing provisioned infrastructure that you manage. AWS Proton *doesn't* manage your existing provisioned infrastructure. To create an environment template for customer provisioned and managed infrastructure, include the provisioning parameter and set the value to CUSTOMER_MANAGED. For more information, see [Register and publish an environment template](#) in the *AWS Proton User Guide*.

Request Syntax

```
{  
  "description": "string",  
  "displayName": "string",  
  "encryptionKey": "string",  
  "name": "string",  
  "provisioning": "string",  
  "tags": [  
    {  
      "key": "string",  
      "value": "string"  
    }  
  ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[description](#)

A description of the environment template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

[displayName](#)

The environment template name as displayed in the developer interface.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

[encryptionKey](#)

A customer provided encryption key that AWS Proton uses to encrypt data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: arn:(aws|aws-cn|aws-us-gov):[a-zA-Z0-9-]+:[a-zA-Z0-9-]*:\d{12}:([\w+=,.@-]+[/:])*([\w+=,.@-]+)

Required: No

[name](#)

The name of the environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_\-]*

Required: Yes

provisioning

When included, indicates that the environment template is for customer provisioned and managed infrastructure.

Type: String

Valid Values: CUSTOMER_MANAGED

Required: No

tags

An optional list of metadata items that you can associate with the AWS Proton environment template. A tag is a key-value pair.

For more information, see [AWS Proton resources and tagging](#) in the *AWS Proton User Guide*.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

Response Syntax

```
{  
  "environmentTemplate": {  
    "arn": "string",  
    "createdAt": number,  
    "description": "string",  
    "displayName": "string",  
    "encryptionKey": "string",  
    "lastModifiedAt": number,  
    "name": "string",  
    "provisioning": "string",  
    "recommendedVersion": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[environmentTemplate](#)

The environment template detail data that's returned by AWS Proton.

Type: [EnvironmentTemplate](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ServiceQuotaExceededException

A quota was exceeded. For more information, see [AWS Proton Quotas](#) in the *AWS Proton User Guide*.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateEnvironmentTemplateVersion

Create a new major or minor version of an environment template. A major version of an environment template is a version that *isn't* backwards compatible. A minor version of an environment template is a version that's backwards compatible within its major version.

Request Syntax

```
{  
  "clientToken": "string",  
  "description": "string",  
  "majorVersion": "string",  
  "source": { ... },  
  "tags": [  
    {  
      "key": "string",  
      "value": "string"  
    }  
  ],  
  "templateName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[clientToken](#)

When included, if two identical requests are made with the same client token, AWS Proton returns the environment template version that the first request created.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 64.

Pattern: [! -~]*

Required: No

[description](#)

A description of the new version of an environment template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

[majorVersion](#)

To create a new minor version of the environment template, include major Version.

To create a new major and minor version of the environment template, exclude major Version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (0|([1-9]{1}\d*))

Required: No

[source](#)

An object that includes the template bundle S3 bucket path and name for the new version of an template.

Type: [TemplateVersionSourceInput](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

[tags](#)

An optional list of metadata items that you can associate with the AWS Proton environment template version. A tag is a key-value pair.

For more information, see [AWS Proton resources and tagging](#) in the *AWS Proton User Guide*.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

templateName

The name of the environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_\-]*

Required: Yes

Response Syntax

```
{  
  "environmentTemplateVersion": {  
    "arn": "string",  
    "createdAt": number,  
    "description": "string",  
    "lastModifiedAt": number,  
    "majorVersion": "string",  
    "minorVersion": "string",  
    "recommendedMinorVersion": "string",  
    "schema": "string",  
    "status": "string",  
    "statusMessage": "string",  
    "templateName": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

environmentTemplateVersion

The environment template detail data that's returned by AWS Proton.

Type: [EnvironmentTemplateVersion](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ServiceQuotaExceededException

A quota was exceeded. For more information, see [AWS Proton Quotas](#) in the *AWS Proton User Guide*.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateRepository

Create and register a link to a repository. AWS Proton uses the link to repeatedly access the repository, to either push to it (self-managed provisioning) or pull from it (template sync). You can share a linked repository across multiple resources (like environments using self-managed provisioning, or synced templates). When you create a repository link, AWS Proton creates a [service-linked role](#) for you.

For more information, see [Self-managed provisioning](#), [Template bundles](#), and [Template sync configurations](#) in the *AWS Proton User Guide*.

Request Syntax

```
{  
  "connectionArn": "string",  
  "encryptionKey": "string",  
  "name": "string",  
  "provider": "string",  
  "tags": [  
    {  
      "key": "string",  
      "value": "string"  
    }  
  ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[connectionArn](#)

The Amazon Resource Name (ARN) of your AWS CodeStar connection that connects AWS Proton to your repository provider account. For more information, see [Setting up for AWS Proton](#) in the *AWS Proton User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `arn:(aws|aws-cn|aws-us-gov):[a-zA-Z0-9-]+:[a-zA-Z0-9-]*:\d{12}:([\w+=,.@-]+[/:])*[\w+=,.@-]+`

Required: Yes

[encryptionKey](#)

The ARN of your customer AWS Key Management Service (AWS KMS) key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `arn:(aws|aws-cn|aws-us-gov):[a-zA-Z0-9-]+:[a-zA-Z0-9-]*:\d{12}:([\w+=,.@-]+[/:])*[\w+=,.@-]+`

Required: No

[name](#)

The repository name (for example, `myrepos/myrepo`).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `.*[A-Za-z0-9_.-].*/[A-Za-z0-9_.-].*`

Required: Yes

[provider](#)

The repository provider.

Type: String

Valid Values: GITHUB | GITHUB_ENTERPRISE | BITBUCKET

Required: Yes

[tags](#)

An optional list of metadata items that you can associate with the AWS Proton repository. A tag is a key-value pair.

For more information, see [AWS Proton resources and tagging](#) in the *AWS Proton User Guide*.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

Response Syntax

```
{  
  "repository": {  
    "arn": "string",  
    "connectionArn": "string",  
    "encryptionKey": "string",  
    "name": "string",  
    "provider": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[repository](#)

The repository link's detail data that's returned by AWS Proton.

Type: [Repository](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ServiceQuotaExceededException

A quota was exceeded. For more information, see [AWS Proton Quotas](#) in the *AWS Proton User Guide*.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateService

Create an AWS Proton service. An AWS Proton service is an instantiation of a service template and often includes several service instances and pipeline. For more information, see [Services](#) in the *AWS Proton User Guide*.

Request Syntax

```
{  
  "branchName": "string",  
  "description": "string",  
  "name": "string",  
  "repositoryConnectionArn": "string",  
  "repositoryId": "string",  
  "spec": "string",  
  "tags": [  
    {  
      "key": "string",  
      "value": "string"  
    }  
  ],  
  "templateMajorVersion": "string",  
  "templateMinorVersion": "string",  
  "templateName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

branchName

The name of the code repository branch that holds the code that's deployed in AWS Proton.
Don't include this parameter if your service template doesn't include a service pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: No

[description](#)

A description of the AWS Proton service.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

[name](#)

The service name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

[repositoryConnectionArn](#)

The Amazon Resource Name (ARN) of the repository connection. For more information, see [Setting up an AWS CodeStar connection](#) in the *AWS Proton User Guide*. Don't include this parameter if your service template *doesn't* include a service pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: arn:(aws|aws-cn|aws-us-gov):[a-zA-Z0-9-]+:[a-zA-Z0-9-]*:\d{12}:([\w+=,.@-]+[/:])*[\w+=,.@-]+

Required: No

[repositoryId](#)

The ID of the code repository. Don't include this parameter if your service template *doesn't* include a service pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: No

spec

A link to a spec file that provides inputs as defined in the service template bundle schema file. The spec file is in YAML format. *Don't include pipeline inputs in the spec if your service template doesn't include a service pipeline.* For more information, see [Create a service](#) in the *AWS Proton User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 51200.

Required: Yes

tags

An optional list of metadata items that you can associate with the AWS Proton service. A tag is a key-value pair.

For more information, see [AWS Proton resources and tagging](#) in the *AWS Proton User Guide*.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

templateMajorVersion

The major version of the service template that was used to create the service.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: $(0|([1-9]\{1\}\d*))$

Required: Yes

templateMinorVersion

The minor version of the service template that was used to create the service.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: $(0|([1-9]\{1\}\d*))$

Required: No

templateName

The name of the service template that's used to create the service.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: $[0-9A-Za-z]+[0-9A-Za-z_\-]^*$

Required: Yes

Response Syntax

```
{
  "service": {
    "arn": "string",
    "branchName": "string",
    "createdAt": number,
    "description": "string",
    "lastModifiedAt": number,
    "name": "string",
    "pipeline": {
      "arn": "string",
      "createdAt": number,
      "deploymentStatus": "string",
      "deploymentStatusMessage": "string",
      "lastAttemptedDeploymentId": "string",
      "lastDeploymentAttemptedAt": number,
      "lastDeploymentSucceededAt": number,
      "lastSucceededDeploymentId": "string",
      "spec": "string",
      "templateMajorVersion": "string",
      "templateMinorVersion": "string",
      "templateName": "string"
    },
    "repositoryConnectionArn": "string",
    "repositoryId": "string",
    "spec": "string",
  }
}
```

```
    "status": "string",
    "statusMessage": "string",
    "templateName": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

service

The service detail data that's returned by AWS Proton.

Type: [Service object](#)

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ServiceQuotaExceededException

A quota was exceeded. For more information, see [AWS Proton Quotas](#) in the *AWS Proton User Guide*.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateServiceInstance

Create a service instance.

Request Syntax

```
{  
    "clientToken": "string",  
    "name": "string",  
    "serviceName": "string",  
    "spec": "string",  
    "tags": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ],  
    "templateMajorVersion": "string",  
    "templateMinorVersion": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

clientToken

The client token of the service instance to create.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 64.

Pattern: [! -~]*

Required: No

name

The name of the service instance to create.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

serviceName

The name of the service the service instance is added to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

spec

The spec for the service instance you want to create.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 51200.

Required: Yes

tags

An optional list of metadata items that you can associate with the AWS Proton service instance.

A tag is a key-value pair.

For more information, see [AWS Proton resources and tagging](#) in the *AWS Proton User Guide*.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

templateMajorVersion

To create a new major and minor version of the service template, *exclude major Version*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (0|([1-9]{1}\d*))

Required: No

[templateMinorVersion](#)

To create a new minor version of the service template, include a major Version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (0|([1-9]{1}\d*))

Required: No

Response Syntax

```
{
  "serviceInstance": {
    "arn": "string",
    "createdAt": number,
    "deploymentStatus": "string",
    "deploymentStatusMessage": "string",
    "environmentName": "string",
    "lastAttemptedDeploymentId": "string",
    "lastClientRequestToken": "string",
    "lastDeploymentAttemptedAt": number,
    "lastDeploymentSucceededAt": number,
    "lastSucceededDeploymentId": "string",
    "name": "string",
    "serviceName": "string",
    "spec": "string",
    "templateMajorVersion": "string",
    "templateMinorVersion": "string",
    "templateName": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[servicInstance](#)

The detailed data of the service instance being created.

Type: [ServiceInstance](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateServiceSyncConfig

Create the AWS Proton Ops configuration file.

Request Syntax

```
{  
  "branch": "string",  
  "filePath": "string",  
  "repositoryName": "string",  
  "repositoryProvider": "string",  
  "serviceName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

branch

The repository branch for your AWS Proton Ops file.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: Yes

filePath

The path to the AWS Proton Ops file.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: Yes

repositoryName

The repository name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `.*[A-Za-z0-9_.-].*/[A-Za-z0-9_.-].*`

Required: Yes

[repositoryProvider](#)

The provider type for your repository.

Type: String

Valid Values: GITHUB | GITHUB_ENTERPRISE | BITBUCKET

Required: Yes

[serviceName](#)

The name of the service the AWS Proton Ops file is for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[0-9A-Za-z]+[0-9A-Za-z_\-]*`

Required: Yes

Response Syntax

```
{  
  "serviceSyncConfig": {  
    "branch": "string",  
    "filePath": "string",  
    "repositoryName": "string",  
    "repositoryProvider": "string",  
    "serviceName": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[serviceSyncConfig](#)

The detailed data of the AWS Proton Ops file.

Type: [ServiceSyncConfig](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ServiceQuotaExceededException

A quota was exceeded. For more information, see [AWS Proton Quotas](#) in the *AWS Proton User Guide*.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateServiceTemplate

Create a service template. The administrator creates a service template to define standardized infrastructure and an optional CI/CD service pipeline. Developers, in turn, select the service template from AWS Proton. If the selected service template includes a service pipeline definition, they provide a link to their source code repository. AWS Proton then deploys and manages the infrastructure defined by the selected service template. For more information, see [AWS Proton templates](#) in the *AWS Proton User Guide*.

Request Syntax

```
{  
    "description": "string",  
    "displayName": "string",  
    "encryptionKey": "string",  
    "name": "string",  
    "pipelineProvisioning": "string",  
    "tags": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

description

A description of the service template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

displayName

The name of the service template as displayed in the developer interface.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

encryptionKey

A customer provided encryption key that's used to encrypt data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `arn:(aws|aws-cn|aws-us-gov):[a-zA-Z0-9-]+:[a-zA-Z0-9-]*:\d{12}:([\w+=,.@-]+[/:])*[\w+=,.@-]+`

Required: No

name

The name of the service template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[0-9A-Za-z]+[0-9A-Za-z_-]*`

Required: Yes

pipelineProvisioning

By default, AWS Proton provides a service pipeline for your service. When this parameter is included, it indicates that an AWS Proton service pipeline *isn't* provided for your service. After it's included, it *can't* be changed. For more information, see [Template bundles](#) in the [AWS Proton User Guide](#).

Type: String

Valid Values: CUSTOMER_MANAGED

Required: No

tags

An optional list of metadata items that you can associate with the AWS Proton service template. A tag is a key-value pair.

For more information, see [AWS Proton resources and tagging](#) in the *AWS Proton User Guide*.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

Response Syntax

```
{
  "serviceTemplate": {
    "arn": "string",
    "createdAt": number,
    "description": "string",
    "displayName": "string",
    "encryptionKey": "string",
    "lastModifiedAt": number,
    "name": "string",
    "pipelineProvisioning": "string",
    "recommendedVersion": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

serviceTemplate

The service template detail data that's returned by AWS Proton.

Type: [ServiceTemplate](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ServiceQuotaExceededException

A quota was exceeded. For more information, see [AWS Proton Quotas](#) in the *AWS Proton User Guide*.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateServiceTemplateVersion

Create a new major or minor version of a service template. A major version of a service template is a version that *isn't* backward compatible. A minor version of a service template is a version that's backward compatible within its major version.

Request Syntax

```
{
  "clientToken": "string",
  "compatibleEnvironmentTemplates": [
    {
      "majorVersion": "string",
      "templateName": "string"
    }
  ],
  "description": "string",
  "majorVersion": "string",
  "source": { ... },
  "supportedComponentSources": [ "string" ],
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ],
  "templateName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[clientToken](#)

When included, if two identical requests are made with the same client token, AWS Proton returns the service template version that the first request created.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 64.

Pattern: [! -~]*

Required: No

[compatibleEnvironmentTemplates](#)

An array of environment template objects that are compatible with the new service template version. A service instance based on this service template version can run in environments based on compatible templates.

Type: Array of [CompatibleEnvironmentTemplateInput](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: Yes

[description](#)

A description of the new version of a service template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

[majorVersion](#)

To create a new minor version of the service template, include a major Version.

To create a new major and minor version of the service template, *exclude* major Version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (0|([1-9]{1}\d*))

Required: No

[source](#)

An object that includes the template bundle S3 bucket path and name for the new version of a service template.

Type: [TemplateVersionSourceInput](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

[supportedComponentSources](#)

An array of supported component sources. Components with supported sources can be attached to service instances based on this service template version.

For more information about components, see [AWS Proton components](#) in the *AWS Proton User Guide*.

Type: Array of strings

Valid Values: DIRECTLY_DEFINED

Required: No

[tags](#)

An optional list of metadata items that you can associate with the AWS Proton service template version. A tag is a key-value pair.

For more information, see [AWS Proton resources and tagging](#) in the *AWS Proton User Guide*.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

[templateName](#)

The name of the service template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{
```

```
"serviceTemplateVersion": {  
    "arn    "compatibleEnvironmentTemplates": [  
        {  
            "majorVersion": "string",  
            "templateName": "string"  
        }  
    ],  
    "createdAt": number,  
    "description": "string",  
    "lastModifiedAt": number,  
    "majorVersion": "string",  
    "minorVersion": "string",  
    "recommendedMinorVersion": "string",  
    "schema": "string",  
    "status": "string",  
    "statusMessage": "string",  
    "supportedComponentSources": [ "string" ],  
    "templateName": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

serviceTemplateVersion

The service template version summary of detail data that's returned by AWS Proton.

Type: [ServiceTemplateVersion](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ServiceQuotaExceededException

A quota was exceeded. For more information, see [AWS Proton Quotas](#) in the *AWS Proton User Guide*.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateTemplateSyncConfig

Set up a template to create new template versions automatically by tracking a linked repository. A linked repository is a repository that has been registered with AWS Proton. For more information, see [CreateRepository](#).

When a commit is pushed to your linked repository, AWS Proton checks for changes to your repository template bundles. If it detects a template bundle change, a new major or minor version of its template is created, if the version doesn't already exist. For more information, see [Template sync configurations](#) in the *AWS Proton User Guide*.

Request Syntax

```
{  
  "branch": "string",  
  "repositoryName": "string",  
  "repositoryProvider": "string",  
  "subdirectory": "string",  
  "templateName": "string",  
  "templateType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

branch

The repository branch for your template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: Yes

repositoryName

The repository name (for example, myrepos/myrepo).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `.*[A-Za-z0-9_.-].*/[A-Za-z0-9_.-].*`

Required: Yes

[repositoryProvider](#)

The provider type for your repository.

Type: String

Valid Values: GITHUB | GITHUB_ENTERPRISE | BITBUCKET

Required: Yes

[subdirectory](#)

A repository subdirectory path to your template bundle directory. When included, AWS Proton limits the template bundle search to this repository directory.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

[templateName](#)

The name of your registered template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[0-9A-Za-z]+[0-9A-Za-z_-]*`

Required: Yes

[templateType](#)

The type of the registered template.

Type: String

Valid Values: ENVIRONMENT | SERVICE

Required: Yes

Response Syntax

```
{  
  "templateSyncConfig": {  
    "branch": "string",  
    "repositoryName": "string",  
    "repositoryProvider": "string",  
    "subdirectory": "string",  
    "templateName": "string",  
    "templateType": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[templateSyncConfig](#)

The template sync configuration detail data that's returned by AWS Proton.

Type: [TemplateSyncConfig](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ServiceQuotaExceededException

A quota was exceeded. For more information, see [AWS Proton Quotas](#) in the *AWS Proton User Guide*.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

DeleteComponent

Delete an AWS Proton component resource.

For more information about components, see [AWS Proton components](#) in the *AWS Proton User Guide*.

Request Syntax

```
{  
  "name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

name

The name of the component to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{  
  "component": {  
    "arn": "string",  
    "createdAt": number,  
    "deploymentStatus": "string",  
    "deploymentStatusMessage": "string",  
    "description": "string",  
    "environmentName": "string",  
  }  
}
```

```
"lastAttemptedDeploymentId": "string",
"lastClientRequestToken": "string",
"lastDeploymentAttemptedAt": number,
"lastDeploymentSucceededAt": number,
"lastModifiedAt": number,
"lastSucceededDeploymentId": "string",
"name": "string",
"serviceInstanceName": "string",
"serviceName": "string",
"serviceSpec": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

component

The detailed data of the component being deleted.

Type: [Component](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteDeployment

Delete the deployment.

Request Syntax

```
{  
  "id": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

id

The ID of the deployment to delete.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

Response Syntax

```
{  
  "deployment": {  
    "arn": "string",  
    "completedAt": number,  
    "componentName": "string",  
    "createdAt": number,  
    "deploymentStatus": "string",  
    "deploymentStatusMessage": "string",  
    "environmentName": "string",  
    "id": "string",  
    "initialState": { ... },  
    "lastAttemptedDeploymentId": "string",  
    "lastModifiedAt": number,  
  }  
}
```

```
"lastSucceededDeploymentId": "string",
"serviceInstanceName": "string",
"serviceName": "string",
"targetArn": "string",
"targetResourceCreatedAt": number,
"targetResourceType": "string",
"targetState": { ... }
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

deployment

The detailed data of the deployment being deleted.

Type: [Deployment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteEnvironment

Delete an environment.

Request Syntax

```
{  
  "name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

name

The name of the environment to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{  
  "environment": {  
    "arn": "string",  
    "codebuildRoleArn": "string",  
    "componentRoleArn": "string",  
    "createdAt": number,  
    "deploymentStatus": "string",  
    "deploymentStatusMessage": "string",  
    "description": "string",  
    "environmentAccountConnectionId": "string",  
  }  
}
```

```
"environmentAccountId": "string",
"lastAttemptedDeploymentId": "string",
"lastDeploymentAttemptedAt": number,
"lastDeploymentSucceededAt": number,
"lastSucceededDeploymentId": "string",
"name": "string",
"protonServiceRoleArn": "string",
"provisioning": "string",
"provisioningRepository": {
    "arn": "string",
    "branch": "string",
    "name": "string",
    "provider": "string"
},
"spec": "string",
"templateMajorVersion": "string",
"templateMinorVersion": "string",
"templateName": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[environment](#)

The detailed data of the environment being deleted.

Type: [Environment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteEnvironmentAccountConnection

In an environment account, delete an environment account connection.

After you delete an environment account connection that's in use by an AWS Proton environment, AWS Proton *can't* manage the environment infrastructure resources until a new environment account connection is accepted for the environment account and associated environment. You're responsible for cleaning up provisioned resources that remain without an environment connection.

For more information, see [Environment account connections](#) in the *AWS Proton User guide*.

Request Syntax

```
{  
  "id}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

id

The ID of the environment account connection to delete.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

Response Syntax

```
{  
  "environmentAccountConnection    "arn    "codebuildRoleArn    "componentRoleArn  },  
}
```

```
"environmentAccountId": "string",
"environmentName": "string",
"id": "string",
"lastModifiedAt": number,
"managementAccountId": "string",
"requestedAt": number,
"roleArn": "string",
"status": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[environmentAccountConnection](#)

The detailed data of the environment account connection being deleted.

Type: [EnvironmentAccountConnection](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteEnvironmentTemplate

If no other major or minor versions of an environment template exist, delete the environment template.

Request Syntax

```
{  
  "name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

name

The name of the environment template to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{  
  "environmentTemplate": {  
    "arn": "string",  
    "createdAt": number,  
    "description": "string",  
    "displayName": "string",  
    "encryptionKey": "string",  
    "lastModifiedAt": number,  
    "name": "string",  
  }  
}
```

```
    "provisioning": "string",
    "recommendedVersion": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[environmentTemplate](#)

The detailed data of the environment template being deleted.

Type: [EnvironmentTemplate](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerError

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteEnvironmentTemplateVersion

If no other minor versions of an environment template exist, delete a major version of the environment template if it's not the Recommended version. Delete the Recommended version of the environment template if no other major versions or minor versions of the environment template exist. A major version of an environment template is a version that's not backward compatible.

Delete a minor version of an environment template if it *isn't* the Recommended version. Delete a Recommended minor version of the environment template if no other minor versions of the environment template exist. A minor version of an environment template is a version that's backward compatible.

Request Syntax

```
{  
  "majorVersion": "string",  
  "minorVersion": "string",  
  "templateName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

majorVersion

The environment template major version to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (0|([1-9]{1}\d*))

Required: Yes

minorVersion

The environment template minor version to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (0|([1-9]{1}\d*))

Required: Yes

templateName

The name of the environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{  
  "environmentTemplateVersion": {  
    "arn": "string",  
    "createdAt": number,  
    "description": "string",  
    "lastModifiedAt": number,  
    "majorVersion": "string",  
    "minorVersion": "string",  
    "recommendedMinorVersion": "string",  
    "schema": "string",  
    "status": "string",  
    "statusMessage": "string",  
    "templateName": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[environmentTemplateVersion](#)

The detailed data of the environment template version being deleted.

Type: [EnvironmentTemplateVersion](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteRepository

De-register and unlink your repository.

Request Syntax

```
{  
  "name": "string",  
  "provider": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[name](#)

The repository name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: .*[A-Za-z0-9_.-]*/[A-Za-z0-9_.-]*.*

Required: Yes

[provider](#)

The repository provider.

Type: String

Valid Values: GITHUB | GITHUB_ENTERPRISE | BITBUCKET

Required: Yes

Response Syntax

```
{
```

```
"repository": {  
    "arn": "string",  
    "connectionArn": "string",  
    "encryptionKey": "string",  
    "name": "string",  
    "provider": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

repository

The deleted repository link's detail data that's returned by AWS Proton.

Type: [Repository](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteService

Delete a service, with its instances and pipeline.

Note

You can't delete a service if it has any service instances that have components attached to them.

For more information about components, see [AWS Proton components](#) in the *AWS Proton User Guide*.

Request Syntax

```
{  
  "name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

name

The name of the service to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{
```

```
"service": {  
    "arn    "branchName    "createdAt    "description    "lastModifiedAt    "name    "pipeline": {  
        "arn        "createdAt        "deploymentStatus        "deploymentStatusMessage        "lastAttemptedDeploymentId        "lastDeploymentAttemptedAt        "lastDeploymentSucceededAt        "lastSucceededDeploymentId        "spec        "templateMajorVersion        "templateMinorVersion        "templateName    },  
    "repositoryConnectionArn    "repositoryId    "spec    "status    "statusMessage    "templateName},  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

service

The detailed data of the service being deleted.

Type: [Service object](#)

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteServiceSyncConfig

Delete the AWS Proton Ops file.

Request Syntax

```
{  
    "serviceName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

serviceName

The name of the service that you want to delete the service sync configuration for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{  
    "serviceSyncConfig": {  
        "branch": "string",  
        "filePath": "string",  
        "repositoryName": "string",  
        "repositoryProvider": "string",  
        "serviceName": "string"  
    }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[serviceSyncConfig](#)

The detailed data for the service sync config.

Type: [ServiceSyncConfig](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteServiceTemplate

If no other major or minor versions of the service template exist, delete the service template.

Request Syntax

```
{  
  "name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

name

The name of the service template to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{  
  "serviceTemplate": {  
    "arn": "string",  
    "createdAt": number,  
    "description": "string",  
    "displayName": "string",  
    "encryptionKey": "string",  
    "lastModifiedAt": number,  
    "name": "string",  
    "pipelineProvisioning": "string",  
  }  
}
```

```
    "recommendedVersion": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[serviceTemplate](#)

The detailed data of the service template being deleted.

Type: [ServiceTemplate](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteServiceTemplateVersion

If no other minor versions of a service template exist, delete a major version of the service template if it's not the Recommended version. Delete the Recommended version of the service template if no other major versions or minor versions of the service template exist. A major version of a service template is a version that *isn't* backwards compatible.

Delete a minor version of a service template if it's not the Recommended version. Delete a Recommended minor version of the service template if no other minor versions of the service template exist. A minor version of a service template is a version that's backwards compatible.

Request Syntax

```
{  
  "majorVersion": "string",  
  "minorVersion": "string",  
  "templateName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[majorVersion](#)

The service template major version to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: ($0 | ([1-9]\{1\}\text{d}^*)$)

Required: Yes

[minorVersion](#)

The service template minor version to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: $(0|([1-9]\{1\}\d*))$

Required: Yes

templateName

The name of the service template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: $[0-9A-Za-z]+[0-9A-Za-z_\\-]^*$

Required: Yes

Response Syntax

```
{
  "serviceTemplateVersion": {
    "arn": "string",
    "compatibleEnvironmentTemplates": [
      {
        "majorVersion": "string",
        "templateName": "string"
      }
    ],
    "createdAt": number,
    "description": "string",
    "lastModifiedAt": number,
    "majorVersion": "string",
    "minorVersion": "string",
    "recommendedMinorVersion": "string",
    "schema": "string",
    "status": "string",
    "statusMessage": "string",
    "supportedComponentSources": [ "string" ],
    "templateName": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

serviceTemplateVersion

The detailed data of the service template version being deleted.

Type: [ServiceTemplateVersion](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteTemplateSyncConfig

Delete a template sync configuration.

Request Syntax

```
{  
  "templateName": "string",  
  "templateType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

templateName

The template name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

templateType

The template type.

Type: String

Valid Values: ENVIRONMENT | SERVICE

Required: Yes

Response Syntax

```
{
```

```
"templateSyncConfig": {  
    "branch    "repositoryName    "repositoryProvider    "subdirectory    "templateName    "templateType}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

templateSyncConfig

The template sync configuration detail data that's returned by AWS Proton.

Type: [TemplateSyncConfig](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetAccountSettings

Get detail data for AWS Proton account-wide settings.

Response Syntax

```
{  
  "accountSettings": {  
    "pipelineCodebuildRoleArn": "string",  
    "pipelineProvisioningRepository": {  
      "arn": "string",  
      "branch": "string",  
      "name": "string",  
      "provider": "string"  
    },  
    "pipelineServiceRoleArn": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

accountSettings

The AWS Proton pipeline service role detail data that's returned by AWS Proton.

Type: [AccountSettings](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetComponent

Get detailed data for a component.

For more information about components, see [AWS Proton components](#) in the *AWS Proton User Guide*.

Request Syntax

```
{  
    "name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

name

The name of the component that you want to get the detailed data for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: 「0-9A-Za-z」+「0-9A-Za-z \-」*

Required: Yes

Response Syntax

```
{  
  "component": {  
    "arn": "string",  
    "createdAt": number,  
    "deploymentStatus": "string",  
    "deploymentStatusMessage": "string",  
    "description": "string",  
    "environmentName": "string",  
    "lastDeploymentStatus": "string",  
    "lastDeploymentStatusMessage": "string",  
    "lastModifiedAt": number,  
    "name": "string",  
    "status": "string",  
    "version": "string",  
    "versionLabel": "string",  
    "versionNumber": number  
  }  
}
```

```
"lastAttemptedDeploymentId": "string",
"lastClientRequestToken": "string",
"lastDeploymentAttemptedAt": number,
"lastDeploymentSucceededAt": number,
"lastModifiedAt": number,
"lastSucceededDeploymentId": "string",
"name": "string",
"serviceInstanceName": "string",
"serviceName": "string",
"serviceSpec": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

component

The detailed data of the requested component.

Type: [Component](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerError

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetDeployment

Get detailed data for a deployment.

Request Syntax

```
{  
  "componentName": "string",  
  "environmentName": "string",  
  "id": "string",  
  "serviceInstanceName": "string",  
  "serviceName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

componentName

The name of a component that you want to get the detailed data for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: No

environmentName

The name of a environment that you want to get the detailed data for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: No

id

The ID of the deployment that you want to get the detailed data for.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

serviceInstanceName

The name of the service instance associated with the given deployment ID. `serviceName` must be specified to identify the service instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: No

serviceName

The name of the service associated with the given deployment ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: No

Response Syntax

```
{
  "deployment": {
    "arn": "string",
    "completedAt": number,
    "componentName": "string",
    "createdAt": number,
    "deploymentStatus": "string",
    "status": "string"
  }
}
```

```
"deploymentStatusMessage": "string",  
"environmentName": "string",  
"id": "string",  
"initialState": { ... },  
"lastAttemptedDeploymentId": "string",  
"lastModifiedAt": number,  
"lastSucceededDeploymentId": "string",  
"serviceInstanceName": "string",  
"serviceName": "string",  
"targetArn": "string",  
"targetResourceCreatedAt": number,  
"targetResourceType": "string",  
"targetState": { ... }  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

deployment

The detailed data of the requested deployment.

Type: [Deployment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetEnvironment

Get detailed data for an environment.

Request Syntax

```
{  
  "name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

name

The name of the environment that you want to get the detailed data for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{  
  "environment": {  
    "arn": "string",  
    "codebuildRoleArn": "string",  
    "componentRoleArn": "string",  
    "createdAt": number,  
    "deploymentStatus": "string",  
    "deploymentStatusMessage": "string",  
    "description": "string",  
    "environmentAccountConnectionId": "string",  
  }  
}
```

```
"environmentAccountId": "string",
"lastAttemptedDeploymentId": "string",
"lastDeploymentAttemptedAt": number,
"lastDeploymentSucceededAt": number,
"lastSucceededDeploymentId": "string",
"name": "string",
"protonServiceRoleArn": "string",
"provisioning": "string",
"provisioningRepository": {
    "arn": "string",
    "branch": "string",
    "name": "string",
    "provider": "string"
},
"spec": "string",
"templateMajorVersion": "string",
"templateMinorVersion": "string",
"templateName": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[environment](#)

The detailed data of the requested environment.

Type: [Environment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetEnvironmentAccountConnection

In an environment account, get the detailed data for an environment account connection.

For more information, see [Environment account connections](#) in the *AWS Proton User guide*.

Request Syntax

```
{  
  "id": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

id

The ID of the environment account connection that you want to get the detailed data for.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

Response Syntax

```
{  
  "environmentAccountConnection": {  
    "arn": "string",  
    "codebuildRoleArn": "string",  
    "componentRoleArn": "string",  
    "environmentAccountId": "string",  
    "environmentName": "string",  
    "id": "string",  
    "lastModifiedAt": number,  
    "managementAccountId": "string",  
    "requestedAt": number,  
  }  
}
```

```
    "roleArn": "string",
    "status": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[environmentAccountConnection](#)

The detailed data of the requested environment account connection.

Type: [EnvironmentAccountConnection](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerError

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetEnvironmentTemplate

Get detailed data for an environment template.

Request Syntax

```
{  
  "name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

name

The name of the environment template that you want to get the detailed data for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{  
  "environmentTemplate": {  
    "arn": "string",  
    "createdAt": number,  
    "description": "string",  
    "displayName": "string",  
    "encryptionKey": "string",  
    "lastModifiedAt": number,  
    "name": "string",  
    "provisioning": "string",  
  }  
}
```

```
    "recommendedVersion": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[environmentTemplate](#)

The detailed data of the requested environment template.

Type: [EnvironmentTemplate](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetEnvironmentTemplateVersion

Get detailed data for a major or minor version of an environment template.

Request Syntax

```
{  
  "majorVersion": "string",  
  "minorVersion": "string",  
  "templateName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[majorVersion](#)

To get environment template major version detail data, include `majorVersion`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `(0|([1-9]{1}\d*))`

Required: Yes

[minorVersion](#)

To get environment template minor version detail data, include `minorVersion`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `(0|([1-9]{1}\d*))`

Required: Yes

templateName

The name of the environment template a version of which you want to get detailed data for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{
  "environmentTemplateVersion": {
    "arn": "string",
    "createdAt": number,
    "description": "string",
    "lastModifiedAt": number,
    "majorVersion": "string",
    "minorVersion": "string",
    "recommendedMinorVersion": "string",
    "schema": "string",
    "status": "string",
    "statusMessage": "string",
    "templateName": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

environmentTemplateVersion

The detailed data of the requested environment template version.

Type: [EnvironmentTemplateVersion](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetRepository

Get detail data for a linked repository.

Request Syntax

```
{  
  "name": "string",  
  "provider": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[name](#)

The repository name, for example myrepos/myrepo.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: .*[A-Za-z0-9_.-]*/[A-Za-z0-9_.-]*.*

Required: Yes

[provider](#)

The repository provider.

Type: String

Valid Values: GITHUB | GITHUB_ENTERPRISE | BITBUCKET

Required: Yes

Response Syntax

```
{
```

```
"repository": {  
    "arn": "string",  
    "connectionArn": "string",  
    "encryptionKey": "string",  
    "name": "string",  
    "provider": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

repository

The repository link's detail data that's returned by AWS Proton.

Type: [Repository object](#)

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetRepositorySyncStatus

Get the sync status of a repository used for AWS Proton template sync. For more information about template sync, see .

Note

A repository sync status isn't tied to the AWS Proton Repository resource (or any other AWS Proton resource). Therefore, tags on an AWS Proton Repository resource have no effect on this action. Specifically, you can't use these tags to control access to this action using Attribute-based access control (ABAC).

For more information about ABAC, see [ABAC](#) in the *AWS Proton User Guide*.

Request Syntax

```
{  
  "branch": "string",  
  "repositoryName": "string",  
  "repositoryProvider": "string",  
  "syncType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

branch

The repository branch.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: Yes

repositoryName

The repository name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `.*[A-Za-z0-9_.-]*/[A-Za-z0-9_.-]*.*`

Required: Yes

[repositoryProvider](#)

The repository provider.

Type: String

Valid Values: GITHUB | GITHUB_ENTERPRISE | BITBUCKET

Required: Yes

[syncType](#)

The repository sync type.

Type: String

Valid Values: TEMPLATE_SYNC | SERVICE_SYNC

Required: Yes

Response Syntax

```
{  
  "latestSync": {  
    "events": [  
      {  
        "event": "string",  
        "externalId": "string",  
        "time": number,  
        "type": "string"  
      }  
    ],  
    "startedAt": number,  
    "status": "string"  
  }  
}
```

{}

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

latestSync

The repository sync status detail data that's returned by AWS Proton.

Type: [RepositorySyncAttempt](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetResourcesSummary

Get counts of AWS Proton resources.

For infrastructure-provisioning resources (environments, services, service instances, pipelines), the action returns staleness counts. A resource is stale when it's behind the recommended version of the AWS Proton template that it uses and it needs an update to become current.

The action returns staleness counts (counts of resources that are up-to-date, behind a template major version, or behind a template minor version), the total number of resources, and the number of resources that are in a failed state, grouped by resource type. Components, environments, and service templates return less information - see the components, environments, and serviceTemplates field descriptions.

For context, the action also returns the total number of each type of AWS Proton template in the AWS account.

For more information, see [AWS Proton dashboard](#) in the *AWS Proton User Guide*.

Response Syntax

```
{  
  "counts": {  
    "components": {  
      "behindMajor": number,  
      "behindMinor": number,  
      "failed": number,  
      "total": number,  
      "upToDate": number  
    },  
    "environments": {  
      "behindMajor": number,  
      "behindMinor": number,  
      "failed": number,  
      "total": number,  
      "upToDate": number  
    },  
    "environmentTemplates": {  
      "behindMajor": number,  
      "behindMinor": number,  
      "failed": number,  
      "total": number  
    }  
  }  
}
```

```
        "total": number,
        "upToDate": number
    },
    "pipelines": {
        "behindMajor": number,
        "behindMinor": number,
        "failed": number,
        "total": number,
        "upToDate": number
    },
    "serviceInstances": {
        "behindMajor": number,
        "behindMinor": number,
        "failed": number,
        "total": number,
        "upToDate": number
    },
    "services": {
        "behindMajor": number,
        "behindMinor": number,
        "failed": number,
        "total": number,
        "upToDate": number
    },
    "serviceTemplates": {
        "behindMajor": number,
        "behindMinor": number,
        "failed": number,
        "total": number,
        "upToDate": number
    }
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

counts

Summary counts of each AWS Proton resource type.

Type: [CountsSummary](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetService

Get detailed data for a service.

Request Syntax

```
{  
  "name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

name

The name of the service that you want to get the detailed data for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{  
  "service": {  
    "arn": "string",  
    "branchName": "string",  
    "createdAt": number,  
    "description": "string",  
    "lastModifiedAt": number,  
    "name": "string",  
    "pipeline": {  
      "arn": "string",  
    }  
  }  
}
```

```
"createdAt": number,  
"deploymentStatusstring",  
"deploymentStatusMessage": "string",  
"lastAttemptedDeploymentId": "string",  
"lastDeploymentAttemptedAt": number,  
"lastDeploymentSucceededAt": number,  
"lastSucceededDeploymentId": "string",  
"spec": "string",  
"templateMajorVersion": "string",  
"templateMinorVersion": "string",  
"templateName": "string"  
},  
"repositoryConnectionArn": "string",  
"repositoryId": "string",  
"spec": "string",  
"status": "string",  
"statusMessage": "string",  
"templateName": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

service

The detailed data of the requested service.

Type: [Service object](#)

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetServiceInstance

Get detailed data for a service instance. A service instance is an instantiation of service template and it runs in a specific environment.

Request Syntax

```
{  
  "name": "string",  
  "serviceName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[name](#)

The name of a service instance that you want to get the detailed data for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

[serviceName](#)

The name of the service that you want the service instance input for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{  
  "serviceInstance": {  
    "arn": "string",  
    "createdAt": number,  
    "deploymentStatus": "string",  
    "deploymentStatusMessage": "string",  
    "environmentName": "string",  
    "lastAttemptedDeploymentId": "string",  
    "lastClientRequestToken": "string",  
    "lastDeploymentAttemptedAt": number,  
    "lastDeploymentSucceededAt": number,  
    "lastSucceededDeploymentId": "string",  
    "name": "string",  
    "serviceName": "string",  
    "spec": "string",  
    "templateMajorVersion": "string",  
    "templateMinorVersion": "string",  
    "templateName": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[serviceInstance](#)

The detailed data of the requested service instance.

Type: [ServiceInstance](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetServiceInstanceSyncStatus

Get the status of the synced service instance.

Request Syntax

```
{  
  "serviceInstanceName": "string",  
  "serviceName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

serviceInstanceName

The name of the service instance that you want the sync status input for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

serviceName

The name of the service that the service instance belongs to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{  
  "desiredState": {  
    "branch": "string",  
    "directory": "string",  
    "repositoryName": "string",  
    "repositoryProvider": "string",  
    "sha": "string"  
  },  
  "latestSuccessfulSync": {  
    "events": [  
      {  
        "event": "string",  

```

```
        "type": "string"
    }
],
"initialRevision": {
    "branch": "string",
    "directory": "string",
    "repositoryName": "string",
    "repositoryProvider": "string",
    "sha": "string"
},
"startedAt": number,
"status": "string",
"target": "string",
"targetRevision": {
    "branch": "string",
    "directory": "string",
    "repositoryName": "string",
    "repositoryProvider": "string",
    "sha": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[desiredState](#)

The service instance sync desired state that's returned by AWS Proton

Type: [Revision](#) object

[latestSuccessfulSync](#)

The detailed data of the latest successful sync with the service instance.

Type: [ResourceSyncAttempt](#) object

[latestSync](#)

The detailed data of the latest sync with the service instance.

Type: [ResourceSyncAttempt](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetServiceSyncBlockerSummary

Get detailed data for the service sync blocker summary.

Request Syntax

```
{  
    "serviceInstanceName": "string",  
    "serviceName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

serviceInstanceName

The name of the service instance that you want to get the service sync blocker summary for. If given both the instance name and the service name, only the instance is blocked.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: No

serviceName

The name of the service that you want to get the service sync blocker summary for. If given only the service name, all instances are blocked.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{  
    "serviceSyncBlockerSummary": {  
        "latestBlockers": [  
            {  
                "contexts": [  
                    {  
                        "key": "string",  
                        "value": "string"  
                    }  
                ],  
                "createdAt": number,  
                "createdReason": "string",  
                "id": "string",  
                "resolvedAt": number,  
                "resolvedReason": "string",  
                "status": "string",  
                "type": "string"  
            }  
        ],  
        "serviceInstanceName": "string",  
        "serviceName": "string"  
    }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[serviceSyncBlockerSummary](#)

The detailed data of the requested service sync blocker summary.

Type: [ServiceSyncBlockerSummary](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetServiceSyncConfig

Get detailed information for the service sync configuration.

Request Syntax

```
{  
    "serviceName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

serviceName

The name of the service that you want to get the service sync configuration for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{  
    "serviceSyncConfig": {  
        "branch": "string",  
        "filePath": "string",  
        "repositoryName": "string",  
        "repositoryProvider": "string",  
        "serviceName": "string"  
    }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[serviceSyncConfig](#)

The detailed data of the requested service sync configuration.

Type: [ServiceSyncConfig](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetServiceTemplate

Get detailed data for a service template.

Request Syntax

```
{  
  "name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

name

The name of the service template that you want to get detailed data for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{  
  "serviceTemplate": {  
    "arn": "string",  
    "createdAt": number,  
    "description": "string",  
    "displayName": "string",  
    "encryptionKey": "string",  
    "lastModifiedAt": number,  
    "name": "string",  
    "pipelineProvisioning": "string",  
  }  
}
```

```
    "recommendedVersion": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[serviceTemplate](#)

The detailed data of the requested service template.

Type: [ServiceTemplate](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetServiceTemplateVersion

Get detailed data for a major or minor version of a service template.

Request Syntax

```
{  
  "majorVersion": "string",  
  "minorVersion": "string",  
  "templateName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

majorVersion

To get service template major version detail data, include majorVersion.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (0|([1-9]{1}\d*))

Required: Yes

minorVersion

To get service template minor version detail data, include minorVersion.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (0|([1-9]{1}\d*))

Required: Yes

templateName

The name of the service template a version of which you want to get detailed data for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_\-]*

Required: Yes

Response Syntax

```
{
  "serviceTemplateVersion": {
    "arn": "string",
    "compatibleEnvironmentTemplates": [
      {
        "majorVersion": "string",
        "templateName": "string"
      }
    ],
    "createdAt": number,
    "description": "string",
    "lastModifiedAt": number,
    "majorVersion": "string",
    "minorVersion": "string",
    "recommendedMinorVersion": "string",
    "schema": "string",
    "status": "string",
    "statusMessage": "string",
    "supportedComponentSources": [ "string" ],
    "templateName": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[serviceTemplateVersion](#)

The detailed data of the requested service template version.

Type: [ServiceTemplateVersion](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTemplateSyncConfig

Get detail data for a template sync configuration.

Request Syntax

```
{  
  "templateName": "string",  
  "templateType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

templateName

The template name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

templateType

The template type.

Type: String

Valid Values: ENVIRONMENT | SERVICE

Required: Yes

Response Syntax

```
{
```

```
"templateSyncConfig": {  
    "branch    "repositoryName    "repositoryProvider    "subdirectory    "templateName    "templateType}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

templateSyncConfig

The template sync configuration detail data that's returned by AWS Proton.

Type: [TemplateSyncConfig](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTemplateSyncStatus

Get the status of a template sync.

Request Syntax

```
{  
  "templateName": "string",  
  "templateType": "string",  
  "templateVersion": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[templateName](#)

The template name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

[templateType](#)

The template type.

Type: String

Valid Values: ENVIRONMENT | SERVICE

Required: Yes

[templateVersion](#)

The template major version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: ($0 | ([1-9]\{1\}\d^*)$)

Required: Yes

Response Syntax

```
{
  "desiredState": {
    "branch": "string",
    "directory": "string",
    "repositoryName": "string",
    "repositoryProvider": "string",
    "sha": "string"
  },
  "latestSuccessfulSync": {
    "events": [
      {
        "event": "string",
        "externalId": "string",
        "time": number,
        "type": "string"
      }
    ],
    "initialRevision": {
      "branch": "string",
      "directory": "string",
      "repositoryName": "string",
      "repositoryProvider": "string",
      "sha": "string"
    },
    "startedAt": number,
    "status": "string",
    "target": "string",
    "targetRevision": {
      "branch": "string",
      "directory": "string",
      "repositoryName": "string",
      "repositoryProvider": "string",
      "sha": "string"
    }
  }
},
```

```
"latestSync    "events        {  
            "event            "externalId            "time            "type        }  
    ],  
    "initialRevision        "branch        "directory        "repositoryName        "repositoryProvider        "sha    },  
    "startedAt    "status    "target    "targetRevision        "branch        "directory        "repositoryName        "repositoryProvider        "sha    }  
},  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[desiredState](#)

The template sync desired state that's returned by AWS Proton.

Type: [Revision](#) object

[latestSuccessfulSync](#)

The details of the last successful sync that's returned by AWS Proton.

Type: [ResourceSyncAttempt](#) object

[latestSync](#)

The details of the last sync that's returned by AWS Proton.

Type: [ResourceSyncAttempt](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListComponentOutputs

Get a list of component Infrastructure as Code (IaC) outputs.

For more information about components, see [AWS Proton components](#) in the *AWS Proton User Guide*.

Request Syntax

```
{  
  "componentName": "string",  
  "deploymentId": "string",  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

componentName

The name of the component whose outputs you want.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

deploymentId

The ID of the deployment whose outputs you want.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

nextToken

A token that indicates the location of the next output in the array of outputs, after the list of outputs that was previously requested.

Type: String

Length Constraints: Fixed length of 0.

Required: No

Response Syntax

```
{  
    "nextToken": "string",  
    "outputs": [  
        {  
            "key": "string",  
            "valueString": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

A token that indicates the location of the next output in the array of outputs, after the list of outputs that was previously requested.

Type: String

Length Constraints: Fixed length of 0.

outputs

An array of component Infrastructure as Code (IaC) outputs.

Type: Array of [Output](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListComponentProvisionedResources

List provisioned resources for a component with details.

For more information about components, see [AWS Proton components](#) in the *AWS Proton User Guide*.

Request Syntax

```
{  
  "componentName": "string",  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[componentName](#)

The name of the component whose provisioned resources you want.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

[nextToken](#)

A token that indicates the location of the next provisioned resource in the array of provisioned resources, after the list of provisioned resources that was previously requested.

Type: String

Length Constraints: Fixed length of 0.

Required: No

Response Syntax

```
{  
    "nextToken": "string",  
    "provisionedResources": [  
        {  
            "identifier": "string",  
            "name": "string",  
            "provisioningEngine": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

A token that indicates the location of the next provisioned resource in the array of provisioned resources, after the current requested list of provisioned resources.

Type: String

Length Constraints: Fixed length of 0.

provisionedResources

An array of provisioned resources for a component.

Type: Array of [ProvisionedResource](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListComponents

List components with summary data. You can filter the result list by environment, service, or a single service instance.

For more information about components, see [AWS Proton components](#) in the *AWS Proton User Guide*.

Request Syntax

```
{  
    "environmentName": "string",  
    "maxResults": number,  
    "nextToken": "string",  
    "serviceInstanceName": "string",  
    "serviceName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[environmentName](#)

The name of an environment for result list filtering. AWS Proton returns components associated with the environment or attached to service instances running in it.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: No

[maxResults](#)

The maximum number of components to list.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

A token that indicates the location of the next component in the array of components, after the list of components that was previously requested.

Type: String

Pattern: [A-Za-z0-9+=/] +

Required: No

serviceInstanceName

The name of a service instance for result list filtering. AWS Proton returns the component attached to the service instance, if any.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: No

serviceName

The name of a service for result list filtering. AWS Proton returns components attached to service instances of the service.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: No

Response Syntax

```
{  
  "components": [  
    ...  
  ]  
}
```

```
{  
    "arn": "string",  
    "createdAt": number,  
    "deploymentStatus": "string",  
    "deploymentStatusMessage": "string",  
    "environmentName": "string",  
    "lastAttemptedDeploymentId": "string",  
    "lastDeploymentAttemptedAt": number,  
    "lastDeploymentSucceededAt": number,  
    "lastModifiedAt": number,  
    "lastSucceededDeploymentId": "string",  
    "name": "string",  
    "serviceInstanceName": "string",  
    "serviceName": "string"  
}  
,  
    "nextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[components](#)

An array of components with summary data.

Type: Array of [ComponentSummary](#) objects

[nextToken](#)

A token that indicates the location of the next component in the array of components, after the current requested list of components.

Type: String

Pattern: [A-Za-z0-9+=/] +

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListDeployments

List deployments. You can filter the result list by environment, service, or a single service instance.

Request Syntax

```
{  
    "componentName": "string",  
    "environmentName": "string",  
    "maxResults": number,  
    "nextToken": "string",  
    "serviceInstanceId": "string",  
    "serviceName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[componentName](#)

The name of a component for result list filtering. AWS Proton returns deployments associated with that component.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: No

[environmentName](#)

The name of an environment for result list filtering. AWS Proton returns deployments associated with the environment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[0-9A-Za-z]+[0-9A-Za-z_-\\-]*`

Required: No

maxResults

The maximum number of deployments to list.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

A token that indicates the location of the next deployment in the array of deployment, after the list of deployment that was previously requested.

Type: String

Pattern: `[A-Za-z0-9+=/]+`

Required: No

serviceInstanceName

The name of a service instance for result list filtering. AWS Proton returns the deployments associated with the service instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[0-9A-Za-z]+[0-9A-Za-z_-\\-]*`

Required: No

serviceName

The name of a service for result list filtering. AWS Proton returns deployments associated with service instances of the service.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[0-9A-Za-z]+[0-9A-Za-z_-\\-]*`

Required: No

Response Syntax

```
{  
  "deployments": [  
    {  
      "arn": "string",  
      "completedAt": number,  
      "componentName": "string",  
      "createdAt": number,  
      "deploymentStatus": "string",  
      "environmentName": "string",  
      "id": "string",  
      "lastAttemptedDeploymentId": "string",  
      "lastModifiedAt": number,  
      "lastSucceededDeploymentId": "string",  
      "serviceInstanceName": "string",  
      "serviceName": "string",  
      "targetArn": "string",  
      "targetResourceCreatedAt": number,  
      "targetResourceType": "string"  
    }  
  ],  
  "nextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[deployments](#)

An array of deployment with summary data.

Type: Array of [DeploymentSummary](#) objects

[nextToken](#)

A token that indicates the location of the next deployment in the array of deployment, after the current requested list of deployment.

Type: String

Pattern: [A-Za-z0-9+=/] +

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListEnvironmentAccountConnections

View a list of environment account connections.

For more information, see [Environment account connections](#) in the *AWS Proton User guide*.

Request Syntax

```
{  
  "environmentName": "string",  
  "maxResults": number,  
  "nextToken": "string",  
  "requestedBy": "string",  
  "statuses": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[environmentName](#)

The environment name that's associated with each listed environment account connection.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: No

[maxResults](#)

The maximum number of environment account connections to list.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

A token that indicates the location of the next environment account connection in the array of environment account connections, after the list of environment account connections that was previously requested.

Type: String

Pattern: [A-Za-z0-9+=/] +

Required: No

requestedBy

The type of account making the `ListEnvironmentAccountConnections` request.

Type: String

Valid Values: MANAGEMENT_ACCOUNT | ENVIRONMENT_ACCOUNT

Required: Yes

statuses

The status details for each listed environment account connection.

Type: Array of strings

Valid Values: PENDING | CONNECTED | REJECTED

Required: No

Response Syntax

```
{  
  "environmentAccountConnections": [  
    {  
      "arn": "string",  
      "componentRoleArn": "string",  
      "environmentAccountId": "string",  
      "environmentName": "string",  
      "id": "string",  
      "lastModifiedAt": number,  
      "managementAccountId": "string",  
      "status": "PENDING" | "CONNECTED" | "REJECTED"  
    }  
  ]  
}
```

```
        "requestedAt": number,
        "roleArn": "string",
        "status": "string"
    }
],
"nextTokenstring"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[environmentAccountConnections](#)

An array of environment account connections with details that's returned by AWS Proton.

Type: Array of [EnvironmentAccountConnectionSummary](#) objects

[nextToken](#)

A token that indicates the location of the next environment account connection in the array of environment account connections, after the current requested list of environment account connections.

Type: String

Pattern: [A-Za-z0-9+=/]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListEnvironmentOutputs

List the infrastructure as code outputs for your environment.

Request Syntax

```
{  
  "deploymentId": "string",  
  "environmentName": "string",  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

deploymentId

The ID of the deployment whose outputs you want.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

environmentName

The environment name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

nextToken

A token that indicates the location of the next environment output in the array of environment outputs, after the list of environment outputs that was previously requested.

Type: String

Length Constraints: Fixed length of 0.

Required: No

Response Syntax

```
{  
    "nextToken": "string",  
    "outputs": [  
        {  
            "key": "string",  
            "valueString": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

A token that indicates the location of the next environment output in the array of environment outputs, after the current requested list of environment outputs.

Type: String

Length Constraints: Fixed length of 0.

outputs

An array of environment outputs with detail data.

Type: Array of [Output](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListEnvironmentProvisionedResources

List the provisioned resources for your environment.

Request Syntax

```
{  
  "environmentName": "string",  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

environmentName

The environment name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

nextToken

A token that indicates the location of the next environment provisioned resource in the array of environment provisioned resources, after the list of environment provisioned resources that was previously requested.

Type: String

Length Constraints: Fixed length of 0.

Required: No

Response Syntax

```
{  
    "nextToken": "string",  
    "provisionedResources": [  
        {  
            "identifier": "string",  
            "name": "string",  
            "provisioningEngine": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

A token that indicates the location of the next environment provisioned resource in the array of provisioned resources, after the current requested list of environment provisioned resources.

Type: String

Length Constraints: Fixed length of 0.

provisionedResources

An array of environment provisioned resources.

Type: Array of [ProvisionedResource](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListEnvironments

List environments with detail data summaries.

Request Syntax

```
{  
  "environmentTemplates": [  
    {  
      "majorVersion": "string",  
      "templateName": "string"  
    }  
  ],  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

environmentTemplates

An array of the versions of the environment template.

Type: Array of [EnvironmentTemplateFilter](#) objects

Required: No

maxResults

The maximum number of environments to list.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

A token that indicates the location of the next environment in the array of environments, after the list of environments that was previously requested.

Type: String

Pattern: [A-Za-z0-9+=/] +

Required: No

Response Syntax

```
{  
  "environments": [  
    {  
      "arn": "string",  
      "componentRoleArn": "string",  
      "createdAt": number,  
      "deploymentStatus": "string",  
      "deploymentStatusMessage": "string",  
      "description": "string",  
      "environmentAccountConnectionId": "string",  
      "environmentAccountId": "string",  
      "lastAttemptedDeploymentId": "string",  
      "lastDeploymentAttemptedAt": number,  
      "lastDeploymentSucceededAt": number,  
      "lastSucceededDeploymentId": "string",  
      "name": "string",  
      "protonServiceRoleArn": "string",  
      "provisioning": "string",  
      "templateMajorVersion": "string",  
      "templateMinorVersion": "string",  
      "templateName": "string"  
    }  
  ],  
  "nextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

environments

An array of environment detail data summaries.

Type: Array of [EnvironmentSummary](#) objects

nextToken

A token that indicates the location of the next environment in the array of environments, after the current requested list of environments.

Type: String

Pattern: [A-Za-z0-9+=/] +

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListEnvironmentTemplates

List environment templates.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

The maximum number of environment templates to list.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

A token that indicates the location of the next environment template in the array of environment templates, after the list of environment templates that was previously requested.

Type: String

Pattern: [A-Za-z0-9+=/] +

Required: No

Response Syntax

```
{
```

```
"nextToken": "string",  
"templates": [  
    {  
        "arnstring",  
        "createdAt": number,  
        "description": "string",  
        "displayName": "string",  
        "lastModifiedAt": number,  
        "name": "string",  
        "provisioning": "string",  
        "recommendedVersion": "string"  
    }  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

A token that indicates the location of the next environment template in the array of environment templates, after the current requested list of environment templates.

Type: String

Pattern: [A-Za-z0-9+=/] +

templates

An array of environment templates with detail data.

Type: Array of [EnvironmentTemplateSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListEnvironmentTemplateVersions

List major or minor versions of an environment template with detail data.

Request Syntax

```
{  
  "majorVersion": "string",  
  "maxResults": number,  
  "nextToken": "string",  
  "templateName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

majorVersion

To view a list of minor of versions under a major version of an environment template, include `major Version`.

To view a list of major versions of an environment template, *exclude* `major Version`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `(0|([1-9]{1}\d*))`

Required: No

maxResults

The maximum number of major or minor versions of an environment template to list.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

[nextToken](#)

A token that indicates the location of the next major or minor version in the array of major or minor versions of an environment template, after the list of major or minor versions that was previously requested.

Type: String

Pattern: [A-Za-z0-9+=/]+

Required: No

[templateName](#)

The name of the environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_\-]*

Required: Yes

Response Syntax

```
{
  "nextToken": "string",
  "templateVersions": [
    {
      "arn": "string",
      "createdAt": number,
      "description": "string",
      "lastModifiedAt": number,
      "majorVersion": "string",
      "minorVersion": "string",
      "recommendedMinorVersion": "string",
      "status": "string",
      "statusMessage": "string",
      "templateName": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

A token that indicates the location of the next major or minor version in the array of major or minor versions of an environment template, after the list of major or minor versions that was previously requested.

Type: String

Pattern: [A-Za-z0-9+=/] +

[templateVersions](#)

An array of major or minor versions of an environment template detail data.

Type: Array of [EnvironmentTemplateVersionSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListRepositories

List linked repositories with detail data.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

The maximum number of repositories to list.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

A token that indicates the location of the next repository in the array of repositories, after the list of repositories previously requested.

Type: String

Pattern: [A-Za-z0-9+=/]+

Required: No

Response Syntax

```
{  
  "nextToken": "string",
```

```
"repositories": [  
    {  
        "arn        "connectionArn        "name        "provider    }  
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

A token that indicates the location of the next repository in the array of repositories, after the current requested list of repositories.

Type: String

Pattern: [A-Za-z0-9+=/] +

repositories

An array of repository links.

Type: Array of [RepositorySummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListRepositorySyncDefinitions

List repository sync definitions with detail data.

Request Syntax

```
{  
    "nextToken": "string",  
    "repositoryName": "string",  
    "repositoryProvider": "string",  
    "syncType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

nextToken

A token that indicates the location of the next repository sync definition in the array of repository sync definitions, after the list of repository sync definitions previously requested.

Type: String

Length Constraints: Fixed length of 0.

Required: No

repositoryName

The repository name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: .*[A-Za-z0-9_.-]*.[A-Za-z0-9_.-].*

Required: Yes

repositoryProvider

The repository provider.

Type: String

Valid Values: GITHUB | GITHUB_ENTERPRISE | BITBUCKET

Required: Yes

syncType

The sync type. The only supported value is TEMPLATE_SYNC.

Type: String

Valid Values: TEMPLATE_SYNC | SERVICE_SYNC

Required: Yes

Response Syntax

```
{  
  "nextToken": "string",  
  "syncDefinitions": [  
    {  
      "branch": "string",  
      "directory": "string",  
      "parent": "string",  
      "target": "string"  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

A token that indicates the location of the next repository sync definition in the array of repository sync definitions, after the current requested list of repository sync definitions.

Type: String

Length Constraints: Fixed length of 0.

syncDefinitions

An array of repository sync definitions.

Type: Array of [RepositorySyncDefinition](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListServiceInstanceOutputs

Get a list service of instance Infrastructure as Code (IaC) outputs.

Request Syntax

```
{  
  "deploymentId": "string",  
  "nextToken": "string",  
  "serviceInstanceName": "string",  
  "serviceName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

deploymentId

The ID of the deployment whose outputs you want.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

nextToken

A token that indicates the location of the next output in the array of outputs, after the list of outputs that was previously requested.

Type: String

Length Constraints: Fixed length of 0.

Required: No

serviceInstanceName

The name of the service instance whose outputs you want.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

serviceName

The name of the service that `serviceInstanceName` is associated to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{
  "nextToken": "string",
  "outputs": [
    {
      "key": "string",
      "valueString": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

A token that indicates the location of the next output in the array of outputs, after the current requested list of outputs.

Type: String

Length Constraints: Fixed length of 0.

outputs

An array of service instance Infrastructure as Code (IaC) outputs.

Type: Array of [Output](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListServiceInstanceProvisionedResources

List provisioned resources for a service instance with details.

Request Syntax

```
{  
    "nextToken": "string",  
    "serviceInstanceId": "string",  
    "serviceName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

nextToken

A token that indicates the location of the next provisioned resource in the array of provisioned resources, after the list of provisioned resources that was previously requested.

Type: String

Length Constraints: Fixed length of 0.

Required: No

serviceInstanceId

The name of the service instance whose provisioned resources you want.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

serviceName

The name of the service that `serviceInstanceId` is associated to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{
  "nextToken": "string",
  "provisionedResources": [
    {
      "identifier": "string",
      "name": "string",
      "provisioningEngine": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

A token that indicates the location of the next provisioned resource in the array of provisioned resources, after the current requested list of provisioned resources.

Type: String

Length Constraints: Fixed length of 0.

provisionedResources

An array of provisioned resources for a service instance.

Type: Array of [ProvisionedResource](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListServiceInstances

List service instances with summary data. This action lists service instances of all services in the AWS account.

Request Syntax

```
{
  "filters": [
    {
      "key": "string",
      "value": "string"
    }
  ],
  "maxResults": number,
  "nextToken": "string",
  "serviceName": "string",
  "sortBy": "string",
  "sortOrder": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

filters

An array of filtering criteria that scope down the result list. By default, all service instances in the AWS account are returned.

Type: Array of [ListServiceInstancesFilter](#) objects

Required: No

maxResults

The maximum number of service instances to list.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

A token that indicates the location of the next service in the array of service instances, after the list of service instances that was previously requested.

Type: String

Pattern: [A-Za-z0-9+=/] +

Required: No

serviceName

The name of the service that the service instance belongs to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_\-]*

Required: No

sortBy

The field that the result list is sorted by.

When you choose to sort by `serviceName`, service instances within each service are sorted by service instance name.

Default: `serviceName`

Type: String

Valid Values: `name` | `deploymentStatus` | `templateName` | `serviceName` | `environmentName` | `lastDeploymentAttemptedAt` | `createdAt`

Required: No

sortOrder

Result list sort order.

Default: `ASCENDING`

Type: String

Valid Values: ASCENDING | DESCENDING

Required: No

Response Syntax

```
{  
    "nextToken": "string",  
    "serviceInstances": [  
        {  
            "arn": "string",  
            "createdAt": number,  
            "deploymentStatus": "string",  
            "deploymentStatusMessage": "string",  
            "environmentName": "string",  
            "lastAttemptedDeploymentId": "string",  
            "lastDeploymentAttemptedAt": number,  
            "lastDeploymentSucceededAt": number,  
            "lastSucceededDeploymentId": "string",  
            "name": "string",  
            "serviceName": "string",  
            "templateMajorVersion": "string",  
            "templateMinorVersion": "string",  
            "templateName": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

A token that indicates the location of the next service instance in the array of service instances, after the current requested list of service instances.

Type: String

Pattern: [A-Za-z0-9+=/] +

serviceInstances

An array of service instances with summary data.

Type: Array of [ServiceInstanceSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListServicePipelineOutputs

Get a list of service pipeline Infrastructure as Code (IaC) outputs.

Request Syntax

```
{  
  "deploymentId": "string",  
  "nextToken": "string",  
  "serviceName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

deploymentId

The ID of the deployment you want the outputs for.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

nextToken

A token that indicates the location of the next output in the array of outputs, after the list of outputs that was previously requested.

Type: String

Length Constraints: Fixed length of 0.

Required: No

serviceName

The name of the service whose pipeline's outputs you want.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{  
    "nextToken": "string",  
    "outputs": [  
        {  
            "key": "string",  
            "valueString": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

A token that indicates the location of the next output in the array of outputs, after the current requested list of outputs.

Type: String

Length Constraints: Fixed length of 0.

outputs

An array of service pipeline Infrastructure as Code (IaC) outputs.

Type: Array of [Output](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListServicePipelineProvisionedResources

List provisioned resources for a service and pipeline with details.

Request Syntax

```
{  
  "nextToken": "string",  
  "serviceName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

nextToken

A token that indicates the location of the next provisioned resource in the array of provisioned resources, after the list of provisioned resources that was previously requested.

Type: String

Length Constraints: Fixed length of 0.

Required: No

serviceName

The name of the service whose pipeline's provisioned resources you want.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{
```

```
"nextTokenstring",  
"provisionedResources    {  
        "identifierstring",  
        "namestring",  
        "provisioningEnginestring"  
    }  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

A token that indicates the location of the next provisioned resource in the array of provisioned resources, after the current requested list of provisioned resources.

Type: String

Length Constraints: Fixed length of 0.

provisionedResources

An array of provisioned resources for a service and pipeline.

Type: Array of [ProvisionedResource](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListServices

List services with summaries of detail data.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

The maximum number of services to list.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

A token that indicates the location of the next service in the array of services, after the list of services that was previously requested.

Type: String

Pattern: [A-Za-z0-9+=/] +

Required: No

Response Syntax

```
{
```

```
"nextToken": "string",  
"services": [  
    {  
        "arnstring",  
        "createdAt": number,  
        "description": "string",  
        "lastModifiedAt": number,  
        "name": "string",  
        "status": "string",  
        "statusMessage": "string",  
        "templateName": "string"  
    }  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

A token that indicates the location of the next service in the array of services, after the current requested list of services.

Type: String

Pattern: [A-Za-z0-9+=/]+

services

An array of services with summaries of detail data.

Type: Array of [ServiceSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListServiceTemplates

List service templates with detail data.

Request Syntax

```
{  
    "maxResults": number,  
    "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

The maximum number of service templates to list.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

A token that indicates the location of the next service template in the array of service templates, after the list of service templates previously requested.

Type: String

Pattern: [A-Za-z0-9+=/] +

Required: No

Response Syntax

```
{
```

```
"nextToken": "string",  
"templates": [  
    {  
        "arnstring",  
        "createdAt": number,  
        "description": "string",  
        "displayName": "string",  
        "lastModifiedAt": number,  
        "name": "string",  
        "pipelineProvisioning": "string",  
        "recommendedVersion": "string"  
    }  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

A token that indicates the location of the next service template in the array of service templates, after the current requested list of service templates.

Type: String

Pattern: [A-Za-z0-9+=/]+

templates

An array of service templates with detail data.

Type: Array of [ServiceTemplateSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListServiceTemplateVersions

List major or minor versions of a service template with detail data.

Request Syntax

```
{  
  "majorVersion": "string",  
  "maxResults": number,  
  "nextToken": "string",  
  "templateName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

majorVersion

To view a list of minor of versions under a major version of a service template, include major Version.

To view a list of major versions of a service template, *exclude* major Version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (0|([1-9]{1}\d*))

Required: No

maxResults

The maximum number of major or minor versions of a service template to list.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

[nextToken](#)

A token that indicates the location of the next major or minor version in the array of major or minor versions of a service template, after the list of major or minor versions that was previously requested.

Type: String

Pattern: [A-Za-z0-9+=/] +

Required: No

[templateName](#)

The name of the service template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_\-]*

Required: Yes

Response Syntax

```
{
  "nextToken": "string",
  "templateVersions": [
    {
      "arn": "string",
      "createdAt": number,
      "description": "string",
      "lastModifiedAt": number,
      "majorVersion": "string",
      "minorVersion": "string",
      "recommendedMinorVersion": "string",
      "status": "string",
      "statusMessage": "string",
      "templateName": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

A token that indicates the location of the next major or minor version in the array of major or minor versions of a service template, after the current requested list of service major or minor versions.

Type: String

Pattern: [A-Za-z0-9+=/] +

[templateVersions](#)

An array of major or minor versions of a service template with detail data.

Type: Array of [ServiceTemplateVersionSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

List tags for a resource. For more information, see [AWS Proton resources and tagging](#) in the *AWS Proton User Guide*.

Request Syntax

```
{  
    "maxResults": number,  
    "nextToken": "string",  
    "resourceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

The maximum number of tags to list.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

A token that indicates the location of the next resource tag in the array of resource tags, after the list of resource tags that was previously requested.

Type: String

Required: No

resourceArn

The Amazon Resource Name (ARN) of the resource for the listed tags.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: arn:(aws|aws-cn|aws-us-gov):[a-zA-Z0-9-]+:[a-zA-Z0-9-]*:\d{12}:([\w+=,.@-]+[/:])*[\w+=,.@-]+

Required: Yes

Response Syntax

```
{  
  "nextToken": "string",  
  "tags": [  
    {  
      "key": "string",  
      "value": "string"  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

A token that indicates the location of the next resource tag in the array of resource tags, after the current requested list of resource tags.

Type: String

tags

A list of resource tags with detail data.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The *isn't* sufficient access for performing this action.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

NotifyResourceDeploymentStatusChange

Notify AWS Proton of status changes to a provisioned resource when you use self-managed provisioning.

For more information, see [Self-managed provisioning](#) in the *AWS Proton User Guide*.

Request Syntax

```
{  
  "deploymentId": "string",  
  "outputs": [  
    {  
      "key": "string",  
      "valueString": "string"  
    }  
  ],  
  "resourceArn": "string",  
  "status": "string",  
  "statusMessage": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

deploymentId

The deployment ID for your provisioned resource.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

outputs

The provisioned resource state change detail data that's returned by AWS Proton.

Type: Array of [Output](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

resourceArn

The provisioned resource Amazon Resource Name (ARN).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `arn:(aws|aws-cn|aws-us-gov):[a-zA-Z0-9-]+:[a-zA-Z0-9-]*:\d{12}:([\w+=,.@-]+[/:])*([\w+=,.@-]+)`

Required: Yes

status

The status of your provisioned resource.

Type: String

Valid Values: IN_PROGRESS | FAILED | SUCCEEDED

Required: No

statusMessage

The deployment status message for your provisioned resource.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 5000.

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ServiceQuotaExceededException

A quota was exceeded. For more information, see [AWS Proton Quotas](#) in the *AWS Proton User Guide*.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RejectEnvironmentAccountConnection

In a management account, reject an environment account connection from another environment account.

After you reject an environment account connection request, you *can't* accept or use the rejected environment account connection.

You *can't* reject an environment account connection that's connected to an environment.

For more information, see [Environment account connections](#) in the *AWS Proton User guide*.

Request Syntax

```
{  
  "id": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

id

The ID of the environment account connection to reject.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

Response Syntax

```
{  
  "environmentAccountConnection": {  
    "arn": "string",  
    "codebuildRoleArn": "string",  
  }
```

```
"componentRoleArn": "string",
"environmentAccountId": "string",
"environmentName": "string",
"id": "string",
"lastModifiedAt": number,
"managementAccountId": "string",
"requestedAt": number,
"roleArn": "string",
"status": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[environmentAccountConnection](#)

The environment connection account detail data that's returned by AWS Proton.

Type: [EnvironmentAccountConnection](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Tag a resource. A tag is a key-value pair of metadata that you associate with an AWS Proton resource.

For more information, see [AWS Proton resources and tagging](#) in the *AWS Proton User Guide*.

Request Syntax

```
{  
    "resourceArn": "string",  
    "tags": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

resourceArn

The Amazon Resource Name (ARN) of the AWS Proton resource to apply customer tags to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `arn:(aws|aws-cn|aws-us-gov):[a-zA-Z0-9-]+:[a-zA-Z0-9-]*:\d{12}:([\w+=,.@-]+[/:])*([\w+=,.@-]+)`

Required: Yes

tags

A list of customer tags to apply to the AWS Proton resource.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Remove a customer tag from a resource. A tag is a key-value pair of metadata associated with an AWS Proton resource.

For more information, see [AWS Proton resources and tagging](#) in the *AWS Proton User Guide*.

Request Syntax

```
{  
    "resourceArn": "string",  
    "tagKeys": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

resourceArn

The Amazon Resource Name (ARN) of the resource to remove customer tags from.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: arn:(aws|aws-cn|aws-us-gov):[a-zA-Z0-9-]+:[a-zA-Z0-9-]*:\d{12}:([\w+=,.@-]+[/:])*([\w+=,.@-]+)

Required: Yes

tagKeys

A list of customer tag keys that indicate the customer tags to be removed from the resource.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The request *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateAccountSettings

Update AWS Proton settings that are used for multiple services in the AWS account.

Request Syntax

```
{  
  "deletePipelineProvisioningRepository": boolean,  
  "pipelineCodebuildRoleArn": "string",  
  "pipelineProvisioningRepository": {  
    "branch": "string",  
    "name": "string",  
    "provider": "string"  
  },  
  "pipelineServiceRoleArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[deletePipelineProvisioningRepository](#)

Set to true to remove a configured pipeline repository from the account settings. Don't set this field if you are updating the configured pipeline repository.

Type: Boolean

Required: No

[pipelineCodebuildRoleArn](#)

The Amazon Resource Name (ARN) of the service role you want to use for provisioning pipelines. AWS Proton assumes this role for CodeBuild-based provisioning.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: .*(^\$)|(^\arn:(aws|aws-cn|aws-us-gov):iam::\d{12}:role/([\w+=,.@-]{1,512}[/:]*)*([\w+=,.@-]{1,64})\$).*

Required: No

[pipelineProvisioningRepository](#)

A linked repository for pipeline provisioning. Specify it if you have environments configured for self-managed provisioning with services that include pipelines. A linked repository is a repository that has been registered with AWS Proton. For more information, see [CreateRepository](#).

To remove a previously configured repository, set `deletePipelineProvisioningRepository` to `true`, and don't set `pipelineProvisioningRepository`.

Type: [RepositoryBranchInput](#) object

Required: No

[pipelineServiceRoleArn](#)

The Amazon Resource Name (ARN) of the service role you want to use for provisioning pipelines. Assumed by AWS Proton for AWS-managed provisioning, and by customer-owned automation for self-managed provisioning.

To remove a previously configured ARN, specify an empty string.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `.*(^$)|(^\arn:(aws|aws-cn|aws-us-gov):iam::\d{12}:role/([\w+=,.@-]{1,512}[/:])*([\w+=,.@-]{1,64})$).*`

Required: No

Response Syntax

```
{  
  "accountSettings": {  
    "pipelineCodebuildRoleArn": "string",  
    "pipelineProvisioningRepository": {  
      "arn": "string",  
      "branch": "string",  
    }  
  }  
}
```

```
        "name": "string",
        "provider": "string"
    },
    "pipelineServiceRoleArn": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[accountSettings](#)

The AWS Proton pipeline service role and repository data shared across the AWS account.

Type: [AccountSettings](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateComponent

Update a component.

There are a few modes for updating a component. The `deploymentType` field defines the mode.

Note

You can't update a component while its deployment status, or the deployment status of a service instance attached to it, is `IN_PROGRESS`.

For more information about components, see [AWS Proton components](#) in the *AWS Proton User Guide*.

Request Syntax

```
{  
  "clientToken": "string",  
  "deploymentType": "string",  
  "description": "string",  
  "name": "string",  
  "serviceInstanceName": "string",  
  "serviceName": "string",  
  "serviceSpec": "string",  
  "templateFile": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[clientToken](#)

The client token for the updated component.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 64.

Pattern: [! -~]*

Required: No

deploymentType

The deployment type. It defines the mode for updating a component, as follows:

NONE

In this mode, a deployment *doesn't* occur. Only the requested metadata parameters are updated. You can only specify `description` in this mode.

CURRENT_VERSION

In this mode, the component is deployed and updated with the new `serviceSpec`, `templateSource`, and/or `type` that you provide. Only requested parameters are updated.

Type: String

Valid Values: NONE | CURRENT_VERSION

Required: Yes

description

An optional customer-provided description of the component.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

name

The name of the component to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_\-]*

Required: Yes

serviceInstanceName

The name of the service instance that you want to attach this component to. Don't specify to keep the component's current service instance attachment. Specify an empty string to detach the component from the service instance it's attached to. Specify non-empty values for both `serviceInstanceName` and `serviceName` or for neither of them.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `.*(^$)|^[0-9A-Za-z]+[0-9A-Za-z_\-]*`

Required: No

serviceName

The name of the service that `serviceInstanceName` is associated with. Don't specify to keep the component's current service instance attachment. Specify an empty string to detach the component from the service instance it's attached to. Specify non-empty values for both `serviceInstanceName` and `serviceName` or for neither of them.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `.*(^$)|^[0-9A-Za-z]+[0-9A-Za-z_\-]*`

Required: No

serviceSpec

The service spec that you want the component to use to access service inputs. Set this only when the component is attached to a service instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 51200.

Required: No

templateFile

A path to the Infrastructure as Code (IaC) file describing infrastructure that a custom component provisions.

Note

Components support a single IaC file, even if you use Terraform as your template language.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 51200.

Required: No

Response Syntax

```
{  
  "component": {  
    "arn": "string",  
    "createdAt": number,  
    "deploymentStatus": "string",  
    "deploymentStatusMessage": "string",  
    "description": "string",  
    "environmentName": "string",  
    "lastAttemptedDeploymentId": "string",  
    "lastClientRequestToken": "string",  
    "lastDeploymentAttemptedAt": number,  
    "lastDeploymentSucceededAt": number,  
    "lastModifiedAt": number,  
    "lastSucceededDeploymentId": "string",  
    "name": "string",  
    "serviceInstanceName": "string",  
    "serviceName": "string",  
    "serviceSpec": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[component](#)

The detailed data of the updated component.

Type: [Component](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ServiceQuotaExceededException

A quota was exceeded. For more information, see [AWS Proton Quotas](#) in the *AWS Proton User Guide*.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateEnvironment

Update an environment.

If the environment is associated with an environment account connection, *don't* update or include the `protonServiceRoleArn` and `provisioningRepository` parameter to update or connect to an environment account connection.

You can only update to a new environment account connection if that connection was created in the same environment account that the current environment account connection was created in. The account connection must also be associated with the current environment.

If the environment *isn't* associated with an environment account connection, *don't* update or include the `environmentAccountId` parameter. You *can't* update or connect the environment to an environment account connection if it *isn't* already associated with an environment connection.

You can update either the `environmentAccountId` or `protonServiceRoleArn` parameter and value. You *can't* update both.

If the environment was configured for AWS-managed provisioning, omit the `provisioningRepository` parameter.

If the environment was configured for self-managed provisioning, specify the `provisioningRepository` parameter and omit the `protonServiceRoleArn` and `environmentAccountId` parameters.

For more information, see [Environments](#) and [Provisioning methods](#) in the *AWS Proton User Guide*.

There are four modes for updating an environment. The `deploymentType` field defines the mode.

NONE

In this mode, a deployment *doesn't* occur. Only the requested metadata parameters are updated.

CURRENT_VERSION

In this mode, the environment is deployed and updated with the new spec that you provide. Only requested parameters are updated. *Don't* include minor or major version parameters when you use this deployment-type.

MINOR_VERSION

In this mode, the environment is deployed and updated with the published, recommended (latest) minor version of the current major version in use, by default. You can also specify a different minor version of the current major version in use.

MAJOR_VERSION

In this mode, the environment is deployed and updated with the published, recommended (latest) major and minor version of the current template, by default. You can also specify a different major version that's higher than the major version in use and a minor version.

Request Syntax

```
{  
    "codebuildRoleArn": "string",  
    "componentRoleArn": "string",  
    "deploymentType": "string",  
    "description": "string",  
    "environmentAccountConnectionId": "string",  
    "name": "string",  
    "protonServiceRoleArn": "string",  
    "provisioningRepository": {  
        "branch": "string",  
        "name": "string",  
        "provider": "string"  
    },  
    "spec": "string",  
    "templateMajorVersion": "string",  
    "templateMinorVersion": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[codebuildRoleArn](#)

The Amazon Resource Name (ARN) of the IAM service role that allows AWS Proton to provision infrastructure using CodeBuild-based provisioning on your behalf.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:(aws|aws-cn|aws-us-gov):iam::\d{12}:role/([\w+=,.@-]{1,512}[:])*([\w+=,.@-]{1,64})`

Required: No

[componentRoleArn](#)

The Amazon Resource Name (ARN) of the IAM service role that AWS Proton uses when provisioning directly defined components in this environment. It determines the scope of infrastructure that a component can provision.

The environment must have a `componentRoleArn` to allow directly defined components to be associated with the environment.

For more information about components, see [AWS Proton components](#) in the *AWS Proton User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:(aws|aws-cn|aws-us-gov):iam::\d{12}:role/([\w+=,.@-]{1,512}[:])*([\w+=,.@-]{1,64})`

Required: No

[deploymentType](#)

There are four modes for updating an environment. The `deploymentType` field defines the mode.

NONE

In this mode, a deployment *doesn't* occur. Only the requested metadata parameters are updated.

CURRENT_VERSION

In this mode, the environment is deployed and updated with the new spec that you provide. Only requested parameters are updated. *Don't* include major or minor version parameters when you use this deployment-type.

MINOR_VERSION

In this mode, the environment is deployed and updated with the published, recommended (latest) minor version of the current major version in use, by default. You can also specify a different minor version of the current major version in use.

MAJOR_VERSION

In this mode, the environment is deployed and updated with the published, recommended (latest) major and minor version of the current template, by default. You can also specify a different major version that is higher than the major version in use and a minor version (optional).

Type: String

Valid Values: NONE | CURRENT_VERSION | MINOR_VERSION | MAJOR_VERSION

Required: Yes

description

A description of the environment update.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

environmentAccountId

The ID of the environment account connection.

You can only update to a new environment account connection if it was created in the same environment account that the current environment account connection was created in and is associated with the current environment.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

[name](#)

The name of the environment to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

[protonServiceRoleArn](#)

The Amazon Resource Name (ARN) of the AWS Proton service role that allows AWS Proton to make API calls to other services your behalf.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: arn:(aws|aws-cn|aws-us-gov):[a-zA-Z0-9-]+:[a-zA-Z0-9-]*:\d{12}:([\w+=,.@-]+[/:])*[\w+=,.@-]+

Required: No

[provisioningRepository](#)

The linked repository that you use to host your rendered infrastructure templates for self-managed provisioning. A linked repository is a repository that has been registered with AWS Proton. For more information, see [CreateRepository](#).

Type: [RepositoryBranchInput](#) object

Required: No

[spec](#)

The formatted specification that defines the update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 51200.

Required: No

templateMajorVersion

The major version of the environment to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (0|([1-9]{1}\d*))

Required: No

templateMinorVersion

The minor version of the environment to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (0|([1-9]{1}\d*))

Required: No

Response Syntax

```
{  
  "environment": {  
    "arn": "string",  
    "codebuildRoleArn": "string",  
    "componentRoleArn": "string",  
    "createdAt": number,  
    "deploymentStatus": "string",  
    "deploymentStatusMessage": "string",  
    "description": "string",  
    "environmentAccountConnectionId": "string",  
    "environmentAccountId": "string",  
    "lastAttemptedDeploymentId": "string",  
    "lastDeploymentAttemptedAt": number,  
  }  
}
```

```
"lastDeploymentSucceededAt": number,
"lastSucceededDeploymentId": "string",
"name": "string",
"protonServiceRoleArn": "string",
"provisioning": "string",
"provisioningRepository": {
    "arn": "string",
    "branch": "string",
    "name": "string",
    "provider": "string"
},
"spec": "string",
"templateMajorVersion": "string",
"templateMinorVersion": "string",
"templateName": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[environment](#)

The environment detail data that's returned by AWS Proton.

Type: [Environment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateEnvironmentAccountConnection

In an environment account, update an environment account connection to use a new IAM role.

For more information, see [Environment account connections](#) in the *AWS Proton User guide*.

Request Syntax

```
{  
  "codebuildRoleArn": "string",  
  "componentRoleArn": "string",  
  "id": "string",  
  "roleArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[codebuildRoleArn](#)

The Amazon Resource Name (ARN) of an IAM service role in the environment account. AWS Proton uses this role to provision infrastructure resources using CodeBuild-based provisioning in the associated environment account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:(aws|aws-cn|aws-us-gov):iam::\d{12}:role/([\w+=,.@-]{1,512}[/:]*)*([\w+=,.@-]{1,64})`

Required: No

[componentRoleArn](#)

The Amazon Resource Name (ARN) of the IAM service role that AWS Proton uses when provisioning directly defined components in the associated environment account. It determines the scope of infrastructure that a component can provision in the account.

The environment account connection must have a `componentRoleArn` to allow directly defined components to be associated with any environments running in the account.

For more information about components, see [AWS Proton components](#) in the *AWS Proton User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:(aws|aws-cn|aws-us-gov):iam::\d{12}:role/([\w+=,.@-]{1,512}[/])*([\w+=,.@-]{1,64})`

Required: No

id

The ID of the environment account connection to update.

Type: String

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

roleArn

The Amazon Resource Name (ARN) of the IAM service role that's associated with the environment account connection to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:(aws|aws-cn|aws-us-gov):iam::\d{12}:role/([\w+=,.@-]{1,512}[/])*([\w+=,.@-]{1,64})`

Required: No

Response Syntax

```
{
```

```
"environmentAccountConnection": {  
    "arn    "codebuildRoleArn": "string",  
    "componentRoleArn": "string",  
    "environmentAccountId": "string",  
    "environmentName": "string",  
    "id": "string",  
    "lastModifiedAt": number,  
    "managementAccountId": "string",  
    "requestedAt": number,  
    "roleArn": "string",  
    "status": "string"  
}  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

environmentAccountConnection

The environment account connection detail data that's returned by AWS Proton.

Type: [EnvironmentAccountConnection](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateEnvironmentTemplate

Update an environment template.

Request Syntax

```
{  
  "description": "string",  
  "displayName": "string",  
  "name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[description](#)

A description of the environment template update.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

[displayName](#)

The name of the environment template to update as displayed in the developer interface.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

[name](#)

The name of the environment template to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{  
  "environmentTemplate": {  
    "arn": "string",  
    "createdAt": number,  
    "description": "string",  
    "displayName": "string",  
    "encryptionKey": "string",  
    "lastModifiedAt": number,  
    "name": "string",  
    "provisioning": "string",  
    "recommendedVersion": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[environmentTemplate](#)

The environment template detail data that's returned by AWS Proton.

Type: [EnvironmentTemplate](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateEnvironmentTemplateVersion

Update a major or minor version of an environment template.

Request Syntax

```
{  
  "description": "string",  
  "majorVersion": "string",  
  "minorVersion": "string",  
  "status": "string",  
  "templateName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

description

A description of environment template version to update.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

majorVersion

To update a major version of an environment template, include `major Version`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `(0|([1-9]{1}\d*))`

Required: Yes

minorVersion

To update a minor version of an environment template, include `minorVersion`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `(0|([1-9]{1}\d*))`

Required: Yes

status

The status of the environment template minor version to update.

Type: String

Valid Values: `REGISTRATION_IN_PROGRESS` | `REGISTRATION_FAILED` | `DRAFT` | `PUBLISHED`

Required: No

templateName

The name of the environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[0-9A-Za-z]+[0-9A-Za-z_-]*`

Required: Yes

Response Syntax

```
{  
  "environmentTemplateVersion": {  
    "arn": "string",  
    "createdAt": number,  
    "description": "string",  
    "lastModifiedAt": number,  
    "status": "string"  
  }  
}
```

```
"majorVersion": "string",
"minorVersion": "string",
"recommendedMinorVersion": "string",
"schema": "string",
"status": "string",
"statusMessage": "string",
"templateName": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[environmentTemplateVersion](#)

The environment template version detail data that's returned by AWS Proton.

Type: [EnvironmentTemplateVersion](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateService

Edit a service description or use a spec to add and delete service instances.

Note

Existing service instances and the service pipeline *can't* be edited using this API. They can only be deleted.

Use the `description` parameter to modify the description.

Edit the `spec` parameter to add or delete instances.

Note

You can't delete a service instance (remove it from the spec) if it has an attached component.

For more information about components, see [AWS Proton components](#) in the *AWS Proton User Guide*.

Request Syntax

```
{  
  "description": "string",  
  "name": "string",  
  "spec": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[description](#)

The edited service description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

name

The name of the service to edit.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

spec

Lists the service instances to add and the existing service instances to remain. Omit the existing service instances to delete from the list. *Don't* include edits to the existing service instances or pipeline. For more information, see [Edit a service](#) in the *AWS Proton User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 51200.

Required: No

Response Syntax

```
{  
  "service": {  
    "arn": "string",  
    "branchName": "string",  
    "createdAt": number,  
    "description": "string",  
    "lastModifiedAt": number,  
    "name": "string",  
    "pipeline": {  
      "arn": "string",  
      "id": "string",  
      "name": "string",  
      "order": number  
    }  
  }  
}
```

```
"createdAt": number,  
"deploymentStatusstring",  
"deploymentStatusMessage": "string",  
"lastAttemptedDeploymentId": "string",  
"lastDeploymentAttemptedAt": number,  
"lastDeploymentSucceededAt": number,  
"lastSucceededDeploymentId": "string",  
"spec": "string",  
"templateMajorVersion": "string",  
"templateMinorVersion": "string",  
"templateName": "string"  
},  
"repositoryConnectionArn": "string",  
"repositoryId": "string",  
"spec": "string",  
"status": "string",  
"statusMessage": "string",  
"templateName": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

service

The service detail data that's returned by AWS Proton.

Type: [Service object](#)

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ServiceQuotaExceededException

A quota was exceeded. For more information, see [AWS Proton Quotas](#) in the *AWS Proton User Guide*.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateServiceInstance

Update a service instance.

There are a few modes for updating a service instance. The `deploymentType` field defines the mode.

Note

You can't update a service instance while its deployment status, or the deployment status of a component attached to it, is `IN_PROGRESS`.

For more information about components, see [AWS Proton components](#) in the *AWS Proton User Guide*.

Request Syntax

```
{  
  "clientToken": "string",  
  "deploymentType": "string",  
  "name": "string",  
  "serviceName": "string",  
  "spec": "string",  
  "templateMajorVersion": "string",  
  "templateMinorVersion": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

clientToken

The client token of the service instance to update.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 64.

Pattern: [! -~]*

Required: No

deploymentType

The deployment type. It defines the mode for updating a service instance, as follows:

NONE

In this mode, a deployment *doesn't* occur. Only the requested metadata parameters are updated.

CURRENT_VERSION

In this mode, the service instance is deployed and updated with the new spec that you provide. Only requested parameters are updated. *Don't* include major or minor version parameters when you use this deployment type.

MINOR_VERSION

In this mode, the service instance is deployed and updated with the published, recommended (latest) minor version of the current major version in use, by default. You can also specify a different minor version of the current major version in use.

MAJOR_VERSION

In this mode, the service instance is deployed and updated with the published, recommended (latest) major and minor version of the current template, by default. You can specify a different major version that's higher than the major version in use and a minor version.

Type: String

Valid Values: NONE | CURRENT_VERSION | MINOR_VERSION | MAJOR_VERSION

Required: Yes

name

The name of the service instance to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[0-9A-Za-z]+[0-9A-Za-z_-]*`

Required: Yes

[serviceName](#)

The name of the service that the service instance belongs to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[0-9A-Za-z]+[0-9A-Za-z_-]*`

Required: Yes

[spec](#)

The formatted specification that defines the service instance update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 51200.

Required: No

[templateMajorVersion](#)

The major version of the service template to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `(0|([1-9]{1}\d*))`

Required: No

[templateMinorVersion](#)

The minor version of the service template to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: ($0 | ([1-9]\{1\}\d^*)$)

Required: No

Response Syntax

```
{  
    "serviceInstance": {  
        "arn": "string",  
        "createdAt": number,  
        "deploymentStatus": "string",  
        "deploymentStatusMessage": "string",  
        "environmentName": "string",  
        "lastAttemptedDeploymentId": "string",  
        "lastClientRequestToken": "string",  
        "lastDeploymentAttemptedAt": number,  
        "lastDeploymentSucceededAt": number,  
        "lastSucceededDeploymentId": "string",  
        "name": "string",  
        "serviceName": "string",  
        "spec": "string",  
        "templateMajorVersion": "string",  
        "templateMinorVersion": "string",  
        "templateName": "string"  
    }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

serviceInstance

The service instance summary data that's returned by AWS Proton.

Type: [ServiceInstance](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateServicePipeline

Update the service pipeline.

There are four modes for updating a service pipeline. The `deploymentType` field defines the mode.

NONE

In this mode, a deployment *doesn't* occur. Only the requested metadata parameters are updated.

CURRENT_VERSION

In this mode, the service pipeline is deployed and updated with the new spec that you provide. Only requested parameters are updated. *Don't* include major or minor version parameters when you use this deployment-type.

MINOR_VERSION

In this mode, the service pipeline is deployed and updated with the published, recommended (latest) minor version of the current major version in use, by default. You can specify a different minor version of the current major version in use.

MAJOR_VERSION

In this mode, the service pipeline is deployed and updated with the published, recommended (latest) major and minor version of the current template by default. You can specify a different major version that's higher than the major version in use and a minor version.

Request Syntax

```
{  
  "deploymentType": "string",  
  "serviceName": "string",  
  "spec": "string",  
  "templateMajorVersion": "string",  
  "templateMinorVersion": "string"
```

}

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[deploymentType](#)

The deployment type.

There are four modes for updating a service pipeline. The `deploymentType` field defines the mode.

NONE

In this mode, a deployment *doesn't* occur. Only the requested metadata parameters are updated.

CURRENT_VERSION

In this mode, the service pipeline is deployed and updated with the new spec that you provide. Only requested parameters are updated. *Don't* include major or minor version parameters when you use this deployment-type.

MINOR_VERSION

In this mode, the service pipeline is deployed and updated with the published, recommended (latest) minor version of the current major version in use, by default. You can specify a different minor version of the current major version in use.

MAJOR_VERSION

In this mode, the service pipeline is deployed and updated with the published, recommended (latest) major and minor version of the current template, by default. You can specify a different major version that's higher than the major version in use and a minor version.

Type: String

Valid Values: NONE | CURRENT_VERSION | MINOR_VERSION | MAJOR_VERSION

Required: Yes

serviceName

The name of the service to that the pipeline is associated with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_\-]*

Required: Yes

spec

The spec for the service pipeline to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 51200.

Required: Yes

templateMajorVersion

The major version of the service template that was used to create the service that the pipeline is associated with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (0|([1-9]{1}\d*))

Required: No

templateMinorVersion

The minor version of the service template that was used to create the service that the pipeline is associated with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: ($0 | ([1-9]\{1\}\text{d}^*)$)

Required: No

Response Syntax

```
{  
  "pipeline": {  
    "arn": "string",  
    "createdAt": number,  
    "deploymentStatus": "string",  
    "deploymentStatusMessage": "string",  
    "lastAttemptedDeploymentId": "string",  
    "lastDeploymentAttemptedAt": number,  
    "lastDeploymentSucceededAt": number,  
    "lastSucceededDeploymentId": "string",  
    "spec": "string",  
    "templateMajorVersion": "string",  
    "templateMinorVersion": "string",  
    "templateName": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[pipeline](#)

The pipeline details that are returned by AWS Proton.

Type: [ServicePipeline](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateServiceSyncBlocker

Update the service sync blocker by resolving it.

Request Syntax

```
{  
  "id": "string",  
  "resolvedReason": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

id

The ID of the service sync blocker.

Type: String

Required: Yes

resolvedReason

The reason the service sync blocker was resolved.

Type: String

Required: Yes

Response Syntax

```
{  
  "serviceInstanceName": "string",  
  "serviceName": "string",  
  "serviceSyncBlocker": {  
    "contexts": [  
      {  
        "context": "string",  
        "status": "string"  
      }  
    ]  
  }  
}
```

```
        "key": "string",
        "value": "string"
    },
],
"createdAt": number,
"createdReason": "string",
"id": "string",
"resolvedAt": number,
"resolvedReason": "string",
"status": "string",
"type": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[serviceInstanceName](#)

The name of the service instance that you want to update the service sync blocker for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

[serviceName](#)

The name of the service that you want to update the service sync blocker for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

[serviceSyncBlocker](#)

The detailed data on the service sync blocker that was updated.

Type: [SyncBlocker](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateServiceSyncConfig

Update the AWS Proton Ops config file.

Request Syntax

```
{  
  "branch": "string",  
  "filePath": "string",  
  "repositoryName": "string",  
  "repositoryProvider": "string",  
  "serviceName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

branch

The name of the code repository branch where the AWS Proton Ops file is found.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: Yes

filePath

The path to the AWS Proton Ops file.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: Yes

repositoryName

The name of the repository where the AWS Proton Ops file is found.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `.*[A-Za-z0-9_.-].*/[A-Za-z0-9_.-].*`

Required: Yes

[repositoryProvider](#)

The name of the repository provider where the AWS Proton Ops file is found.

Type: String

Valid Values: GITHUB | GITHUB_ENTERPRISE | BITBUCKET

Required: Yes

[serviceName](#)

The name of the service the AWS Proton Ops file is for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[0-9A-Za-z]+[0-9A-Za-z_\-]*`

Required: Yes

Response Syntax

```
{  
  "serviceSyncConfig": {  
    "branch": "string",  
    "filePath": "string",  
    "repositoryName": "string",  
    "repositoryProvider": "string",  
    "serviceName": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[serviceSyncConfig](#)

The detailed data of the AWS Proton Ops file.

Type: [ServiceSyncConfig](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateServiceTemplate

Update a service template.

Request Syntax

```
{  
  "description": "string",  
  "displayName": "string",  
  "name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[description](#)

A description of the service template update.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

[displayName](#)

The name of the service template to update that's displayed in the developer interface.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

[name](#)

The name of the service template to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

Response Syntax

```
{  
  "serviceTemplate": {  
    "arn": "string",  
    "createdAt": number,  
    "description": "string",  
    "displayName": "string",  
    "encryptionKey": "string",  
    "lastModifiedAt": number,  
    "name": "string",  
    "pipelineProvisioning": "string",  
    "recommendedVersion": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[serviceTemplate](#)

The service template detail data that's returned by AWS Proton.

Type: [ServiceTemplate](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateServiceTemplateVersion

Update a major or minor version of a service template.

Request Syntax

```
{  
    "compatibleEnvironmentTemplates": [  
        {  
            "majorVersion": "string",  
            "templateName": "string"  
        }  
    ],  
    "description": "string",  
    "majorVersion": "string",  
    "minorVersion": "string",  
    "status": "string",  
    "supportedComponentSources": [ "string" ],  
    "templateName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

compatibleEnvironmentTemplates

An array of environment template objects that are compatible with this service template version. A service instance based on this service template version can run in environments based on compatible templates.

Type: Array of [CompatibleEnvironmentTemplateInput](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

description

A description of a service template version to update.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

[majorVersion](#)

To update a major version of a service template, include `major Version`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: $(0|([1-9]\{1\}\d*))$

Required: Yes

[minorVersion](#)

To update a minor version of a service template, include `minorVersion`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: $(0|([1-9]\{1\}\d*))$

Required: Yes

[status](#)

The status of the service template minor version to update.

Type: String

Valid Values: `REGISTRATION_IN_PROGRESS` | `REGISTRATION_FAILED` | `DRAFT` | `PUBLISHED`

Required: No

[supportedComponentSources](#)

An array of supported component sources. Components with supported sources can be attached to service instances based on this service template version.

Note

A change to supportedComponentSources doesn't impact existing component attachments to instances based on this template version. A change only affects later associations.

For more information about components, see [AWS Proton components](#) in the *AWS Proton User Guide*.

Type: Array of strings

Valid Values: DIRECTLY_DEFINED

Required: No

templateName

The name of the service template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_\-]*

Required: Yes

Response Syntax

```
{  
  "serviceTemplateVersion": {  
    "arn": "string",  
    "compatibleEnvironmentTemplates": [  
      {  
        "majorVersion": "string",  
        "templateName": "string"  
      }  
    ],  
    "createdAt": number,  
    "description": "string",  
    "lastModifiedAt": number,  
    "status": "PENDING'|'READY'|'DELETING'|'FAILED'|'UPDATING'|  
    "tags": {  
      "string": "string"  
    },  
    "version": "string"  
  }  
}
```

```
"majorVersion": "string",  
"minorVersion": "string",  
"recommendedMinorVersion": "string",  
"schema": "string",  
"status": "string",  
"statusMessage": "string",  
"supportedComponentSources": [ "string" ],  
"templateName": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[serviceTemplateVersion](#)

The service template version detail data that's returned by AWS Proton.

Type: [ServiceTemplateVersion](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateTemplateSyncConfig

Update template sync configuration parameters, except for the `templateName` and `templateType`. Repository details (branch, name, and provider) should be of a linked repository. A linked repository is a repository that has been registered with AWS Proton. For more information, see [CreateRepository](#).

Request Syntax

```
{  
  "branch": "string",  
  "repositoryName": "string",  
  "repositoryProvider": "string",  
  "subdirectory": "string",  
  "templateName": "string",  
  "templateType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

branch

The repository branch for your template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: Yes

repositoryName

The repository name (for example, `myrepos/myrepo`).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `.*[A-Za-z0-9_.-].*/[A-Za-z0-9_.-].*`

Required: Yes

[repositoryProvider](#)

The repository provider.

Type: String

Valid Values: GITHUB | GITHUB_ENTERPRISE | BITBUCKET

Required: Yes

[subdirectory](#)

A subdirectory path to your template bundle version. When included, limits the template bundle search to this repository directory.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

[templateName](#)

The synced template name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[0-9A-Za-z]+[0-9A-Za-z_\-]*`

Required: Yes

[templateType](#)

The synced template type.

Type: String

Valid Values: ENVIRONMENT | SERVICE

Required: Yes

Response Syntax

```
{  
  "templateSyncConfig": {  
    "branch": "string",  
    "repositoryName": "string",  
    "repositoryProvider": "string",  
    "subdirectory": "string",  
    "templateName": "string",  
    "templateType": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[templateSyncConfig](#)

The template sync configuration detail data that's returned by AWS Proton.

Type: [TemplateSyncConfig](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

There *isn't* sufficient access for performing this action.

HTTP Status Code: 400

ConflictException

The request *couldn't* be made due to a conflicting operation or resource.

HTTP Status Code: 400

InternalServerException

The request failed to register with the service.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource *wasn't* found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input is invalid or an out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS Proton API contains several data types that various actions use. This section describes each data type in detail.

 **Note**

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AccountSettings](#)
- [CompatibleEnvironmentTemplate](#)
- [CompatibleEnvironmentTemplateInput](#)
- [Component](#)
- [ComponentState](#)
- [ComponentSummary](#)
- [CountsSummary](#)
- [Deployment](#)
- [DeploymentState](#)
- [DeploymentSummary](#)
- [Environment](#)
- [EnvironmentAccountConnection](#)
- [EnvironmentAccountConnectionSummary](#)
- [EnvironmentState](#)
- [EnvironmentSummary](#)
- [EnvironmentTemplate](#)
- [EnvironmentTemplateFilter](#)
- [EnvironmentTemplateSummary](#)
- [EnvironmentTemplateVersion](#)
- [EnvironmentTemplateVersionSummary](#)

- [ListServiceInstancesFilter](#)
- [Output](#)
- [ProvisionedResource](#)
- [Repository](#)
- [RepositoryBranch](#)
- [RepositoryBranchInput](#)
- [RepositorySummary](#)
- [RepositorySyncAttempt](#)
- [RepositorySyncDefinition](#)
- [RepositorySyncEvent](#)
- [ResourceCountsSummary](#)
- [ResourceSyncAttempt](#)
- [ResourceSyncEvent](#)
- [Revision](#)
- [S3ObjectSource](#)
- [Service](#)
- [ServiceInstance](#)
- [ServiceInstanceState](#)
- [ServiceInstanceStateSummary](#)
- [ServicePipeline](#)
- [ServicePipelineState](#)
- [ServiceSummary](#)
- [ServiceSyncBlockerSummary](#)
- [ServiceSyncConfig](#)
- [ServiceTemplate](#)
- [ServiceTemplateSummary](#)
- [ServiceTemplateVersion](#)
- [ServiceTemplateVersionSummary](#)
- [SyncBlocker](#)
- [SyncBlockerContext](#)

- [Tag](#)
- [TemplateSyncConfig](#)
- [TemplateVersionSourceInput](#)

AccountSettings

AWS Proton settings that are used for multiple services in the AWS account.

Contents

pipelineCodebuildRoleArn

The Amazon Resource Name (ARN) of the service role that AWS Proton uses for provisioning pipelines. AWS Proton assumes this role for CodeBuild-based provisioning.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `.*(^$)|(^\arn:(aws|aws-cn|aws-us-gov):iam::\d{12}:role/([\w+=,.@-]{1,512}[/:])*([\w+=,.@-]{1,64})$).*`

Required: No

pipelineProvisioningRepository

The linked repository for pipeline provisioning. Required if you have environments configured for self-managed provisioning with services that include pipelines. A linked repository is a repository that has been registered with AWS Proton. For more information, see [CreateRepository](#).

Type: [RepositoryBranch](#) object

Required: No

pipelineServiceRoleArn

The Amazon Resource Name (ARN) of the service role you want to use for provisioning pipelines. Assumed by AWS Proton for AWS-managed provisioning, and by customer-owned automation for self-managed provisioning.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `.*(^$)|(^\arn:(aws|aws-cn|aws-us-gov):iam::\d{12}:role/([\w+=,.@-]{1,512}[/:])*([\w+=,.@-]{1,64})$).*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CompatibleEnvironmentTemplate

Compatible environment template data.

Contents

majorVersion

The major version of the compatible environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: $(0|([1-9]\{1\}\d*))$

Required: Yes

templateName

The compatible environment template name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: $[0-9A-Za-z]+[0-9A-Za-z_-]*$

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CompatibleEnvironmentTemplateInput

Compatible environment template data.

Contents

majorVersion

The major version of the compatible environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: $(0|([1-9]\{1\}\d*))$

Required: Yes

templateName

The compatible environment template name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: $[0-9A-Za-z]+[0-9A-Za-z_\-]^{*}$

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Component

Detailed data of an AWS Proton component resource.

For more information about components, see [AWS Proton components](#) in the *AWS Proton User Guide*.

Contents

arn

The Amazon Resource Name (ARN) of the component.

Type: String

Required: Yes

createdAt

The time when the component was created.

Type: Timestamp

Required: Yes

deploymentStatus

The component deployment status.

Type: String

Valid Values: IN_PROGRESS | FAILED | SUCCEEDED | DELETE_IN_PROGRESS |
DELETE_FAILED | DELETE_COMPLETE | CANCELLING | CANCELLED

Required: Yes

environmentName

The name of the AWS Proton environment that this component is associated with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

lastModifiedAt

The time when the component was last modified.

Type: Timestamp

Required: Yes

name

The name of the component.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_\-]*

Required: Yes

deploymentStatusMessage

The message associated with the component deployment status.

Type: String

Required: No

description

A description of the component.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

lastAttemptedDeploymentId

The ID of the last attempted deployment of this component.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

lastClientRequestToken

The last token the client requested.

Type: String

Required: No

lastDeploymentAttemptedAt

The time when a deployment of the component was last attempted.

Type: Timestamp

Required: No

lastDeploymentSucceededAt

The time when the component was last deployed successfully.

Type: Timestamp

Required: No

lastSucceededDeploymentId

The ID of the last successful deployment of this component.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

serviceInstanceName

The name of the service instance that this component is attached to. Provided when a component is attached to a service instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: No

serviceName

The name of the service that `serviceInstanceName` is associated with. Provided when a component is attached to a service instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: No

serviceSpec

The service spec that the component uses to access service inputs. Provided when a component is attached to a service instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 51200.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ComponentState

The detailed data about the current state of the component.

Contents

serviceInstanceName

The name of the service instance that this component is attached to. Provided when a component is attached to a service instance.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `.*(^$)|^[0-9A-Za-z]+[0-9A-Za-z_-]*`

Required: No

serviceName

The name of the service that `serviceInstanceName` is associated with. Provided when a component is attached to a service instance.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `.*(^$)|^[0-9A-Za-z]+[0-9A-Za-z_-]*`

Required: No

serviceSpec

The service spec that the component uses to access service inputs. Provided when a component is attached to a service instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 51200.

Required: No

templateFile

The template file used.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 51200.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ComponentSummary

Summary data of an AWS Proton component resource.

For more information about components, see [AWS Proton components](#) in the *AWS Proton User Guide*.

Contents

arn

The Amazon Resource Name (ARN) of the component.

Type: String

Required: Yes

createdAt

The time when the component was created.

Type: Timestamp

Required: Yes

deploymentStatus

The component deployment status.

Type: String

Valid Values: IN_PROGRESS | FAILED | SUCCEEDED | DELETE_IN_PROGRESS | DELETE_FAILED | DELETE_COMPLETE | CANCELLING | CANCELLED

Required: Yes

environmentName

The name of the AWS Proton environment that this component is associated with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[0-9A-Za-z]+[0-9A-Za-z_-\\-]*`

Required: Yes

lastModifiedAt

The time when the component was last modified.

Type: Timestamp

Required: Yes

name

The name of the component.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[0-9A-Za-z]+[0-9A-Za-z_-\\-]*`

Required: Yes

deploymentStatusMessage

The message associated with the component deployment status.

Type: String

Required: No

lastAttemptedDeploymentId

The ID of the last attempted deployment of this component.

Type: String

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: No

lastDeploymentAttemptedAt

The time when a deployment of the component was last attempted.

Type: Timestamp

Required: No

lastDeploymentSucceededAt

The time when the component was last deployed successfully.

Type: Timestamp

Required: No

lastSucceededDeploymentId

The ID of the last successful deployment of this component.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

serviceInstanceName

The name of the service instance that this component is attached to. Provided when a component is attached to a service instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: No

serviceName

The name of the service that `serviceInstanceName` is associated with. Provided when a component is attached to a service instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CountsSummary

Summary counts of each AWS Proton resource type.

Contents

components

The total number of components in the AWS account.

The semantics of the components field are different from the semantics of results for other infrastructure-provisioning resources. That's because at this time components don't have associated templates, therefore they don't have the concept of staleness. The components object will only contain total and failed members.

Type: [ResourceCountsSummary](#) object

Required: No

environments

The staleness counts for AWS Proton environments in the AWS account. The environments object will only contain total members.

Type: [ResourceCountsSummary](#) object

Required: No

environmentTemplates

The total number of environment templates in the AWS account. The environmentTemplates object will only contain total members.

Type: [ResourceCountsSummary](#) object

Required: No

pipelines

The staleness counts for AWS Proton pipelines in the AWS account.

Type: [ResourceCountsSummary](#) object

Required: No

serviceInstances

The staleness counts for AWS Proton service instances in the AWS account.

Type: [ResourceCountsSummary](#) object

Required: No

services

The staleness counts for AWS Proton services in the AWS account.

Type: [ResourceCountsSummary](#) object

Required: No

serviceTemplates

The total number of service templates in the AWS account. The `serviceTemplates` object will only contain `total` members.

Type: [ResourceCountsSummary](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Deployment

The detailed information about a deployment.

Contents

arn

The Amazon Resource Name (ARN) of the deployment.

Type: String

Required: Yes

createdAt

The date and time the deployment was created.

Type: Timestamp

Required: Yes

deploymentStatus

The status of the deployment.

Type: String

Valid Values: IN_PROGRESS | FAILED | SUCCEEDED | DELETE_IN_PROGRESS |
DELETE_FAILED | DELETE_COMPLETE | CANCELLING | CANCELLED

Required: Yes

environmentName

The name of the environment associated with this deployment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

id

The ID of the deployment.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

lastModifiedAt

The date and time the deployment was last modified.

Type: Timestamp

Required: Yes

targetArn

The Amazon Resource Name (ARN) of the target of the deployment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: arn:(aws|aws-cn|aws-us-gov):[a-zA-Z0-9-]+:[a-zA-Z0-9-]*:\d{12}:([\w+=,.@-]+[/:])*([\w+=,.@-]+)

Required: Yes

targetResourceCreatedAt

The date and time the deployment target was created.

Type: Timestamp

Required: Yes

targetResourceType

The resource type of the deployment target. It can be an environment, service, service instance, or component.

Type: String

Valid Values: ENVIRONMENT | SERVICE_PIPELINE | SERVICE_INSTANCE | COMPONENT

Required: Yes

completedAt

The date and time the deployment was completed.

Type: Timestamp

Required: No

componentName

The name of the component associated with this deployment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: No

deploymentStatusMessage

The deployment status message.

Type: String

Required: No

initialState

The initial state of the target resource at the time of the deployment.

Type: [DeploymentState](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

lastAttemptedDeploymentId

The ID of the last attempted deployment.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

lastSucceededDeploymentId

The ID of the last successful deployment.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

serviceInstanceName

The name of the deployment's service instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: No

serviceName

The name of the service in this deployment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: No

targetState

The target state of the target resource at the time of the deployment.

Type: [DeploymentState](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeploymentState

The detailed data about the current state of the deployment.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

component

The state of the component associated with the deployment.

Type: [ComponentState](#) object

Required: No

environment

The state of the environment associated with the deployment.

Type: [EnvironmentState](#) object

Required: No

serviceInstance

The state of the service instance associated with the deployment.

Type: [ServiceInstanceState](#) object

Required: No

servicePipeline

The state of the service pipeline associated with the deployment.

Type: [ServicePipelineState](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeploymentSummary

Summary data of the deployment.

Contents

arn

The Amazon Resource Name (ARN) of the deployment.

Type: String

Required: Yes

createdAt

The date and time the deployment was created.

Type: Timestamp

Required: Yes

deploymentStatus

The current status of the deployment.

Type: String

Valid Values: IN_PROGRESS | FAILED | SUCCEEDED | DELETE_IN_PROGRESS |
DELETE_FAILED | DELETE_COMPLETE | CANCELLING | CANCELLED

Required: Yes

environmentName

The name of the environment associated with the deployment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

id

The ID of the deployment.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

lastModifiedAt

The date and time the deployment was last modified.

Type: Timestamp

Required: Yes

targetArn

The Amazon Resource Name (ARN) of the target of the deployment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: arn:(aws|aws-cn|aws-us-gov):[a-zA-Z0-9-]+:[a-zA-Z0-9-]*:\d{12}:([\w+=,.@-]+[/:])*([\w+=,.@-]+)

Required: Yes

targetResourceCreatedAt

The date and time the target resource was created.

Type: Timestamp

Required: Yes

targetResourceType

The resource type of the deployment target. It can be an environment, service, service instance, or component.

Type: String

Valid Values: ENVIRONMENT | SERVICE_PIPELINE | SERVICE_INSTANCE | COMPONENT

Required: Yes

completedAt

The date and time the deployment was completed.

Type: Timestamp

Required: No

componentName

The name of the component associated with the deployment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: No

lastAttemptedDeploymentId

The ID of the last attempted deployment.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

lastSucceededDeploymentId

The ID of the last successful deployment.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

serviceInstanceName

The name of the service instance associated with the deployment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[0-9A-Za-z]+[0-9A-Za-z_-]*`

Required: No

serviceName

The name of the service associated with the deployment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[0-9A-Za-z]+[0-9A-Za-z_-]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Environment

Detailed data of an AWS Proton environment resource. An AWS Proton environment is a set of resources shared across AWS Proton services.

Contents

arn

The Amazon Resource Name (ARN) of the environment.

Type: String

Required: Yes

createdAt

The time when the environment was created.

Type: Timestamp

Required: Yes

deploymentStatus

The environment deployment status.

Type: String

Valid Values: IN_PROGRESS | FAILED | SUCCEEDED | DELETE_IN_PROGRESS |
DELETE_FAILED | DELETE_COMPLETE | CANCELLING | CANCELLED

Required: Yes

lastDeploymentAttemptedAt

The time when a deployment of the environment was last attempted.

Type: Timestamp

Required: Yes

lastDeploymentSucceededAt

The time when the environment was last deployed successfully.

Type: Timestamp

Required: Yes

name

The name of the environment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_\-]*

Required: Yes

templateMajorVersion

The major version of the environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (0|([1-9]{1}\d*))

Required: Yes

templateMinorVersion

The minor version of the environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (0|([1-9]{1}\d*))

Required: Yes

templateName

The Amazon Resource Name (ARN) of the environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_\-]*

Required: Yes

codebuildRoleArn

The Amazon Resource Name (ARN) of the IAM service role that allows AWS Proton to provision infrastructure using CodeBuild-based provisioning on your behalf.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: arn:(aws|aws-cn|aws-us-gov):iam::\d{12}:role/([\w+=,.@-]{1,512}[/:]*)*([\w+=,.@-]{1,64})

Required: No

componentRoleArn

The Amazon Resource Name (ARN) of the IAM service role that AWS Proton uses when provisioning directly defined components in this environment. It determines the scope of infrastructure that a component can provision.

The environment must have a `componentRoleArn` to allow directly defined components to be associated with the environment.

For more information about components, see [AWS Proton components](#) in the *AWS Proton User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: arn:(aws|aws-cn|aws-us-gov):iam::\d{12}:role/([\w+=,.@-]{1,512}[/:]*)*([\w+=,.@-]{1,64})

Required: No

deploymentStatusMessage

An environment deployment status message.

Type: String

Required: No

description

The description of the environment.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

environmentAccountConnectionId

The ID of the environment account connection that's used to provision infrastructure resources in an environment account.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

environmentAccountId

The ID of the environment account that the environment infrastructure resources are provisioned in.

Type: String

Pattern: \d{12}

Required: No

lastAttemptedDeploymentId

The ID of the last attempted deployment of this environment.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

lastSucceededDeploymentId

The ID of the last successful deployment of this environment.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

protonServiceRoleArn

The Amazon Resource Name (ARN) of the AWS Proton service role that allows AWS Proton to make calls to other services on your behalf.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: arn:(aws|aws-cn|aws-us-gov):[a-zA-Z0-9-]+:[a-zA-Z0-9-]*:\d{12}:([\w+=,.@-]+[/:])*([\w+=,.@-]+)

Required: No

provisioning

When included, indicates that the environment template is for customer provisioned and managed infrastructure.

Type: String

Valid Values: CUSTOMER_MANAGED

Required: No

provisioningRepository

The linked repository that you use to host your rendered infrastructure templates for self-managed provisioning. A linked repository is a repository that has been registered with AWS Proton. For more information, see [CreateRepository](#).

Type: [RepositoryBranch](#) object

Required: No

spec

The environment spec.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 51200.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EnvironmentAccountConnection

Detailed data of an AWS Proton environment account connection resource.

Contents

arn

The Amazon Resource Name (ARN) of the environment account connection.

Type: String

Required: Yes

environmentAccountId

The environment account that's connected to the environment account connection.

Type: String

Pattern: \d{12}

Required: Yes

environmentName

The name of the environment that's associated with the environment account connection.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

id

The ID of the environment account connection.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

lastModifiedAt

The time when the environment account connection was last modified.

Type: Timestamp

Required: Yes

managementAccountId

The ID of the management account that's connected to the environment account connection.

Type: String

Pattern: \d{12}

Required: Yes

requestedAt

The time when the environment account connection request was made.

Type: Timestamp

Required: Yes

roleArn

The IAM service role that's associated with the environment account connection.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: arn:(aws|aws-cn|aws-us-gov):[a-zA-Z0-9-]+:[a-zA-Z0-9-]*:\d{12}:([\w+=,.@-]+[/:]*)*[\w+=,.@-]+

Required: Yes

status

The status of the environment account connection.

Type: String

Valid Values: PENDING | CONNECTED | REJECTED

Required: Yes

codebuildRoleArn

The Amazon Resource Name (ARN) of an IAM service role in the environment account. AWS Proton uses this role to provision infrastructure resources using CodeBuild-based provisioning in the associated environment account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:(aws|aws-cn|aws-us-gov):iam::\d{12}:role/([\w+=,.@-]{1,512}[/])*([\w+=,.@-]{1,64})`

Required: No

componentRoleArn

The Amazon Resource Name (ARN) of the IAM service role that AWS Proton uses when provisioning directly defined components in the associated environment account. It determines the scope of infrastructure that a component can provision in the account.

The environment account connection must have a `componentRoleArn` to allow directly defined components to be associated with any environments running in the account.

For more information about components, see [AWS Proton components](#) in the *AWS Proton User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:(aws|aws-cn|aws-us-gov):iam::\d{12}:role/([\w+=,.@-]{1,512}[/])*([\w+=,.@-]{1,64})`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EnvironmentAccountConnectionSummary

Summary data of an AWS Proton environment account connection resource.

Contents

arn

The Amazon Resource Name (ARN) of the environment account connection.

Type: String

Required: Yes

environmentAccountId

The ID of the environment account that's connected to the environment account connection.

Type: String

Pattern: \d{12}

Required: Yes

environmentName

The name of the environment that's associated with the environment account connection.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

id

The ID of the environment account connection.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

lastModifiedAt

The time when the environment account connection was last modified.

Type: Timestamp

Required: Yes

managementAccountId

The ID of the management account that's connected to the environment account connection.

Type: String

Pattern: \d{12}

Required: Yes

requestedAt

The time when the environment account connection request was made.

Type: Timestamp

Required: Yes

roleArn

The IAM service role that's associated with the environment account connection.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: arn:(aws|aws-cn|aws-us-gov):[a-zA-Z0-9-]+:[a-zA-Z0-9-]*:\d{12}:([\w+=,.@-]+[/:])*[\w+=,.@-]+

Required: Yes

status

The status of the environment account connection.

Type: String

Valid Values: PENDING | CONNECTED | REJECTED

Required: Yes

componentRoleArn

The Amazon Resource Name (ARN) of the IAM service role that AWS Proton uses when provisioning directly defined components in the associated environment account. It determines the scope of infrastructure that a component can provision in the account.

The environment account connection must have a `componentRoleArn` to allow directly defined components to be associated with any environments running in the account.

For more information about components, see [AWS Proton components](#) in the *AWS Proton User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `arn:(aws|aws-cn|aws-us-gov):[a-zA-Z0-9-]+:[a-zA-Z0-9-]*:\d{12}:([\w+=,.@-]+[/:])*[\w+=,.@-]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EnvironmentState

The detailed data about the current state of the environment.

Contents

templateMajorVersion

The major version of the environment template that was used to create the environment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: $(0|([1-9]\{1\}\d*))$

Required: Yes

templateMinorVersion

The minor version of the environment template that was used to create the environment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: $(0|([1-9]\{1\}\d*))$

Required: Yes

templateName

The name of the environment template that was used to create the environment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: $[0-9A-Za-z]+[0-9A-Za-z_]*$

Required: Yes

spec

The environment spec that was used to create the environment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 51200.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EnvironmentSummary

Summary data of an AWS Proton environment resource. An AWS Proton environment is a set of resources shared across AWS Proton services.

Contents

arn

The Amazon Resource Name (ARN) of the environment.

Type: String

Required: Yes

createdAt

The time when the environment was created.

Type: Timestamp

Required: Yes

deploymentStatus

The environment deployment status.

Type: String

Valid Values: IN_PROGRESS | FAILED | SUCCEEDED | DELETE_IN_PROGRESS |
DELETE_FAILED | DELETE_COMPLETE | CANCELLING | CANCELLED

Required: Yes

lastDeploymentAttemptedAt

The time when a deployment of the environment was last attempted.

Type: Timestamp

Required: Yes

lastDeploymentSucceededAt

The time when the environment was last deployed successfully.

Type: Timestamp

Required: Yes

name

The name of the environment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

templateMajorVersion

The major version of the environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (0|([1-9]{1}\d*))

Required: Yes

templateMinorVersion

The minor version of the environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (0|([1-9]{1}\d*))

Required: Yes

templateName

The name of the environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_\-]*

Required: Yes

componentRoleArn

The Amazon Resource Name (ARN) of the IAM service role that AWS Proton uses when provisioning directly defined components in this environment. It determines the scope of infrastructure that a component can provision.

The environment must have a `componentRoleArn` to allow directly defined components to be associated with the environment.

For more information about components, see [AWS Proton components](#) in the *AWS Proton User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: arn:(aws|aws-cn|aws-us-gov):[a-zA-Z0-9-]+:[a-zA-Z0-9-]*:\d{12}:([\w+=,.@-]+[/:])*([\w+=,.@-]+)

Required: No

deploymentStatusMessage

An environment deployment status message.

Type: String

Required: No

description

The description of the environment.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

environmentAccountConnectionId

The ID of the environment account connection that the environment is associated with.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

environmentAccountId

The ID of the environment account that the environment infrastructure resources are provisioned in.

Type: String

Pattern: \d{12}

Required: No

lastAttemptedDeploymentId

The ID of the last attempted deployment of this environment.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

lastSucceededDeploymentId

The ID of the last successful deployment of this environment.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

protonServiceRoleArn

The Amazon Resource Name (ARN) of the AWS Proton service role that allows AWS Proton to make calls to other services on your behalf.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `arn:(aws|aws-cn|aws-us-gov):[a-zA-Z0-9-]+:[a-zA-Z0-9-]*:\d{12}:([\w+=,.@-]+[/:])*([\w+=,.@-]+)`

Required: No

provisioning

When included, indicates that the environment template is for customer provisioned and managed infrastructure.

Type: String

Valid Values: CUSTOMER_MANAGED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EnvironmentTemplate

The environment template data.

Contents

arn

The Amazon Resource Name (ARN) of the environment template.

Type: String

Required: Yes

createdAt

The time when the environment template was created.

Type: Timestamp

Required: Yes

lastModifiedAt

The time when the environment template was last modified.

Type: Timestamp

Required: Yes

name

The name of the environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

description

A description of the environment template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

displayName

The name of the environment template as displayed in the developer interface.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

encryptionKey

The customer provided encryption key for the environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: arn:(aws|aws-cn|aws-us-gov):[a-zA-Z0-9-]+:[a-zA-Z0-9-]*:\d{12}:([\w+=,.@-]+[/:])*([\w+=,.@-]+)

Required: No

provisioning

When included, indicates that the environment template is for customer provisioned and managed infrastructure.

Type: String

Valid Values: CUSTOMER_MANAGED

Required: No

recommendedVersion

The ID of the recommended version of the environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: `(0|([1-9]{1}\d*)).(0|([1-9]{1}\d*))`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EnvironmentTemplateFilter

A search filter for environment templates.

Contents

majorVersion

Include majorVersion to filter search for a major version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `(0|([1-9]{1}\d*))`

Required: Yes

templateName

Include templateName to filter search for a template name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[0-9A-Za-z]+[0-9A-Za-z_-]*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EnvironmentTemplateSummary

The environment template data.

Contents

arn

The Amazon Resource Name (ARN) of the environment template.

Type: String

Required: Yes

createdAt

The time when the environment template was created.

Type: Timestamp

Required: Yes

lastModifiedAt

The time when the environment template was last modified.

Type: Timestamp

Required: Yes

name

The name of the environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

description

A description of the environment template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

displayName

The name of the environment template as displayed in the developer interface.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

provisioning

When included, indicates that the environment template is for customer provisioned and managed infrastructure.

Type: String

Valid Values: CUSTOMER_MANAGED

Required: No

recommendedVersion

The recommended version of the environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: (0|([1-9]{1}\d*)).(0|([1-9]{1}\d*))

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EnvironmentTemplateVersion

The environment template version data.

Contents

arn

The Amazon Resource Name (ARN) of the version of an environment template.

Type: String

Required: Yes

createdAt

The time when the version of an environment template was created.

Type: Timestamp

Required: Yes

lastModifiedAt

The time when the version of an environment template was last modified.

Type: Timestamp

Required: Yes

majorVersion

The latest major version that's associated with the version of an environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (0|([1-9]{1}\d*))

Required: Yes

minorVersion

The minor version of an environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (0|([1-9]{1}\d*))

Required: Yes

status

The status of the version of an environment template.

Type: String

Valid Values: REGISTRATION_IN_PROGRESS | REGISTRATION_FAILED | DRAFT | PUBLISHED

Required: Yes

templateName

The name of the version of an environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

description

A description of the minor version of an environment template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

recommendedMinorVersion

The recommended minor version of the environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (\emptyset | ([1-9]{1}\d*))

Required: No

schema

The schema of the version of an environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 51200.

Required: No

statusMessage

The status message of the version of an environment template.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EnvironmentTemplateVersionSummary

A summary of the version of an environment template detail data.

Contents

arn

The Amazon Resource Name (ARN) of the version of an environment template.

Type: String

Required: Yes

createdAt

The time when the version of an environment template was created.

Type: Timestamp

Required: Yes

lastModifiedAt

The time when the version of an environment template was last modified.

Type: Timestamp

Required: Yes

majorVersion

The latest major version that's associated with the version of an environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (0|([1-9]{1}\d*))

Required: Yes

minorVersion

The version of an environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (0|([1-9]{1}\d*))

Required: Yes

status

The status of the version of an environment template.

Type: String

Valid Values: REGISTRATION_IN_PROGRESS | REGISTRATION_FAILED | DRAFT | PUBLISHED

Required: Yes

templateName

The name of the environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

description

A description of the version of an environment template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

recommendedMinorVersion

The recommended minor version of the environment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (\emptyset | ([1-9]{1}\d*))

Required: No

statusMessage

The status message of the version of an environment template.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListServiceInstancesFilter

A filtering criterion to scope down the result list of the [ListServiceInstances](#) action.

Contents

key

The name of a filtering criterion.

Type: String

Valid Values: name | deploymentStatus | templateName | serviceName
| deployedTemplateVersionStatus | environmentName |
lastDeploymentAttemptedAtBefore | lastDeploymentAttemptedAtAfter |
createdAtBefore | createdAtAfter

Required: No

value

A value to filter by.

With the date/time keys (*At{Before, After}), the value is a valid [RFC 3339](#) string with no UTC offset and with an optional fractional precision (for example, 1985-04-12T23:20:50.52Z).

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Output

An infrastructure as code defined resource output.

Contents

key

The output key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

valueString

The output value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ProvisionedResource

Detail data for a provisioned resource.

Contents

identifier

The provisioned resource identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: No

name

The provisioned resource name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: No

provisioningEngine

The resource provisioning engine. At this time, CLOUDFORMATION can be used for AWS-managed provisioning, and TERRAFORM can be used for self-managed provisioning.

For more information, see [Self-managed provisioning](#) in the *AWS Proton User Guide*.

Type: String

Valid Values: CLOUDFORMATION | TERRAFORM

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Repository

Detailed data of a linked repository—a repository that has been registered with AWS Proton.

Contents

arn

The Amazon Resource Name (ARN) of the linked repository.

Type: String

Required: Yes

connectionArn

The Amazon Resource Name (ARN) of your AWS CodeStar connection that connects AWS Proton to your repository provider account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: arn:(aws|aws-cn|aws-us-gov):[a-zA-Z0-9-]+:[a-zA-Z0-9-]*:\d{12}:([\w+=,.@-]+[/:])*([\w+=,.@-]+)

Required: Yes

name

The repository name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: .* [A-Za-z0-9_.-] .*/[A-Za-z0-9_.-] .*

Required: Yes

provider

The repository provider.

Type: String

Valid Values: GITHUB | GITHUB_ENTERPRISE | BITBUCKET

Required: Yes

encryptionKey

Your customer AWS KMS encryption key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: arn:(aws|aws-cn|aws-us-gov):[a-zA-Z0-9-]+:[a-zA-Z0-9-]*:\d{12}:([\w+=,.@-]+[/:])*([\w+=,.@-]+)

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RepositoryBranch

Detail data for a linked repository branch.

Contents

arn

The Amazon Resource Name (ARN) of the linked repository.

Type: String

Required: Yes

branch

The repository branch.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: Yes

name

The repository name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: .*[A-Za-z0-9_.-]*/[A-Za-z0-9_.-]*.*

Required: Yes

provider

The repository provider.

Type: String

Valid Values: GITHUB | GITHUB_ENTERPRISE | BITBUCKET

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RepositoryBranchInput

Detail input data for a linked repository branch.

Contents

branch

The repository branch.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: Yes

name

The repository name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: .*[A-Za-z0-9_.-]*/[A-Za-z0-9_.-].*

Required: Yes

provider

The repository provider.

Type: String

Valid Values: GITHUB | GITHUB_ENTERPRISE | BITBUCKET

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RepositorySummary

Summary data of a linked repository—a repository that has been registered with AWS Proton.

Contents

arn

The Amazon Resource Name (ARN) of the linked repository.

Type: String

Required: Yes

connectionArn

The Amazon Resource Name (ARN) of the connection that connects AWS Proton to your repository.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: arn:(aws|aws-cn|aws-us-gov):[a-zA-Z0-9-]+:[a-zA-Z0-9-]*:\d{12}:([\w+=,.@-]+[/:])*([\w+=,.@-]+)

Required: Yes

name

The repository name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: .* [A-Za-z0-9_.-] .*/[A-Za-z0-9_.-].*

Required: Yes

provider

The repository provider.

Type: String

Valid Values: GITHUB | GITHUB_ENTERPRISE | BITBUCKET

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RepositorySyncAttempt

Detail data for a repository sync attempt activated by a push to a repository.

Contents

events

Detail data for sync attempt events.

Type: Array of [RepositorySyncEvent](#) objects

Required: Yes

startedAt

The time when the sync attempt started.

Type: Timestamp

Required: Yes

status

The sync attempt status.

Type: String

Valid Values: INITIATED | IN_PROGRESS | SUCCEEDED | FAILED | QUEUED

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RepositorySyncDefinition

A repository sync definition.

Contents

branch

The repository branch.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: Yes

directory

The directory in the repository.

Type: String

Required: Yes

parent

The resource that is synced from.

Type: String

Required: Yes

target

The resource that is synced to.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RepositorySyncEvent

Repository sync event detail data for a sync attempt.

Contents

event

Event detail for a repository sync attempt.

Type: String

Required: Yes

time

The time that the sync event occurred.

Type: Timestamp

Required: Yes

type

The type of event.

Type: String

Required: Yes

externalId

The external ID of the sync event.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceCountsSummary

Summary counts of each AWS Proton resource types.

Contents

total

The total number of resources of this type in the AWS account.

Type: Integer

Required: Yes

behindMajor

The number of resources of this type in the AWS account that need a major template version update.

Type: Integer

Required: No

behindMinor

The number of resources of this type in the AWS account that need a minor template version update.

Type: Integer

Required: No

failed

The number of resources of this type in the AWS account that failed to deploy.

Type: Integer

Required: No

upToDate

The number of resources of this type in the AWS account that are up-to-date with their template.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceSyncAttempt

Detail data for a resource sync attempt activated by a push to a repository.

Contents

events

An array of events with detail data.

Type: Array of [ResourceSyncEvent](#) objects

Required: Yes

initialRevision

Detail data for the initial repository commit, path and push.

Type: [Revision](#) object

Required: Yes

startedAt

The time when the sync attempt started.

Type: Timestamp

Required: Yes

status

The status of the sync attempt.

Type: String

Valid Values: INITIATED | IN_PROGRESS | SUCCEEDED | FAILED

Required: Yes

target

The resource that is synced to.

Type: String

Required: Yes

targetRevision

Detail data for the target revision.

Type: [Revision](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceSyncEvent

Detail data for a resource sync event.

Contents

event

A resource sync event.

Type: String

Required: Yes

time

The time when the event occurred.

Type: Timestamp

Required: Yes

type

The type of event.

Type: String

Required: Yes

externalId

The external ID for the event.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Revision

Revision detail data for a commit and push that activates a sync attempt

Contents

branch

The repository branch.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: Yes

directory

The repository directory changed by a commit and push that activated the sync attempt.

Type: String

Required: Yes

repositoryName

The repository name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: .*[A-Za-z0-9_.-]*.[A-Za-z0-9_.-].*

Required: Yes

repositoryProvider

The repository provider.

Type: String

Valid Values: GITHUB | GITHUB_ENTERPRISE | BITBUCKET

Required: Yes

sha

The secure hash algorithm (SHA) hash for the revision.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3ObjectSource

Template bundle S3 bucket data.

Contents

bucket

The name of the S3 bucket that contains a template bundle.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: [a-zA-Z0-9]+[a-zA-Z0-9-\.]+[a-zA-Z0-9]+

Required: Yes

key

The path to the S3 bucket that contains a template bundle.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Service

Detailed data of an AWS Proton service resource.

Contents

arn

The Amazon Resource Name (ARN) of the service.

Type: String

Required: Yes

createdAt

The time when the service was created.

Type: Timestamp

Required: Yes

lastModifiedAt

The time when the service was last modified.

Type: Timestamp

Required: Yes

name

The name of the service.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

spec

The formatted specification that defines the service.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 51200.

Required: Yes

status

The status of the service.

Type: String

Valid Values: CREATE_IN_PROGRESS | CREATE_FAILED_CLEANUP_IN_PROGRESS
| CREATE_FAILED_CLEANUP_COMPLETE | CREATE_FAILED_CLEANUP_FAILED
| CREATE_FAILED | ACTIVE | DELETE_IN_PROGRESS | DELETE_FAILED
| UPDATE_IN_PROGRESS | UPDATE_FAILED_CLEANUP_IN_PROGRESS |
UPDATE_FAILED_CLEANUP_COMPLETE | UPDATE_FAILED_CLEANUP_FAILED |
UPDATE_FAILED | UPDATE_COMPLETE_CLEANUP_FAILED

Required: Yes

templateName

The name of the service template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_\-]*

Required: Yes

branchName

The name of the code repository branch that holds the code that's deployed in AWS Proton.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: No

description

A description of the service.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

pipeline

The service pipeline detail data.

Type: [ServicePipeline](#) object

Required: No

repositoryConnectionArn

The Amazon Resource Name (ARN) of the repository connection. For more information, see [Setting up an AWS CodeStar connection](#) in the *AWS Proton User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: arn:(aws|aws-cn|aws-us-gov):[a-zA-Z0-9-]+:[a-zA-Z0-9-]*:\d{12}:([\w+=,.@-]+[/:])*[\w+=,.@-]+

Required: No

repositoryId

The ID of the source code repository.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: No

statusMessage

A service status message.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceInstance

Detailed data of an AWS Proton service instance resource.

Contents

arn

The Amazon Resource Name (ARN) of the service instance.

Type: String

Required: Yes

createdAt

The time when the service instance was created.

Type: Timestamp

Required: Yes

deploymentStatus

The service instance deployment status.

Type: String

Valid Values: IN_PROGRESS | FAILED | SUCCEEDED | DELETE_IN_PROGRESS |
DELETE_FAILED | DELETE_COMPLETE | CANCELLING | CANCELLED

Required: Yes

environmentName

The name of the environment that the service instance was deployed into.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

lastDeploymentAttemptedAt

The time when a deployment of the service instance was last attempted.

Type: Timestamp

Required: Yes

lastDeploymentSucceededAt

The time when the service instance was last deployed successfully.

Type: Timestamp

Required: Yes

name

The name of the service instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

serviceName

The name of the service that the service instance belongs to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

templateMajorVersion

The major version of the service template that was used to create the service instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: $(0|([1-9]\{1\}\d*))$

Required: Yes

templateMinorVersion

The minor version of the service template that was used to create the service instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: $(0|([1-9]\{1\}\d*))$

Required: Yes

templateName

The name of the service template that was used to create the service instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: $[0-9A-Za-z]+[0-9A-Za-z_-]*$

Required: Yes

deploymentStatusMessage

The message associated with the service instance deployment status.

Type: String

Required: No

lastAttemptedDeploymentId

The ID of the last attempted deployment of this service instance.

Type: String

Pattern: $[0-9a-f]\{8\}-[0-9a-f]\{4\}-[0-9a-f]\{4\}-[0-9a-f]\{4\}-[0-9a-f]\{12\}$

Required: No

lastClientRequestToken

The last client request token received.

Type: String

Required: No

lastSucceededDeploymentId

The ID of the last successful deployment of this service instance.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

spec

The service spec that was used to create the service instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 51200.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceInstanceState

The detailed data about the current state of this service instance.

Contents

spec

The service spec that was used to create the service instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 51200.

Required: Yes

templateMajorVersion

The major version of the service template that was used to create the service pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: ($0 | ([1-9]\{1\}\d*)$)

Required: Yes

templateMinorVersion

The minor version of the service template that was used to create the service pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: ($0 | ([1-9]\{1\}\d*)$)

Required: Yes

templateName

The name of the service template that was used to create the service instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[0-9A-Za-z]+[0-9A-Za-z_-]*`

Required: Yes

lastSuccessfulComponentDeploymentIds

The IDs for the last successful components deployed for this service instance.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 1 item.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: No

lastSuccessfulEnvironmentDeploymentId

The ID for the last successful environment deployed for this service instance.

Type: String

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: No

lastSuccessfulServicePipelineDeploymentId

The ID for the last successful service pipeline deployed for this service instance.

Type: String

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceInstanceSummary

Summary data of an AWS Proton service instance resource.

Contents

arn

The Amazon Resource Name (ARN) of the service instance.

Type: String

Required: Yes

createdAt

The time when the service instance was created.

Type: Timestamp

Required: Yes

deploymentStatus

The service instance deployment status.

Type: String

Valid Values: IN_PROGRESS | FAILED | SUCCEEDED | DELETE_IN_PROGRESS |
DELETE_FAILED | DELETE_COMPLETE | CANCELLING | CANCELLED

Required: Yes

environmentName

The name of the environment that the service instance was deployed into.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

lastDeploymentAttemptedAt

The time when a deployment of the service was last attempted.

Type: Timestamp

Required: Yes

lastDeploymentSucceededAt

The time when the service was last deployed successfully.

Type: Timestamp

Required: Yes

name

The name of the service instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

serviceName

The name of the service that the service instance belongs to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

templateMajorVersion

The service instance template major version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: $(0|([1-9]\{1\}\d*))$

Required: Yes

templateMinorVersion

The service instance template minor version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: $(0|([1-9]\{1\}\d*))$

Required: Yes

templateName

The name of the service template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: $[0-9A-Za-z]+[0-9A-Za-z_-]*$

Required: Yes

deploymentStatusMessage

A service instance deployment status message.

Type: String

Required: No

lastAttemptedDeploymentId

The ID of the last attempted deployment of this service instance.

Type: String

Pattern: $[0-9a-f]\{8\}-[0-9a-f]\{4\}-[0-9a-f]\{4\}-[0-9a-f]\{4\}-[0-9a-f]\{12\}$

Required: No

lastSucceededDeploymentId

The ID of the last successful deployment of this service instance.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServicePipeline

Detailed data of an AWS Proton service instance pipeline resource.

Contents

arn

The Amazon Resource Name (ARN) of the service pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: arn:(aws|aws-cn|aws-us-gov):[a-zA-Z0-9-]+:[a-zA-Z0-9-]*:\d{12}:([\w+=,.@-]+[/:])*[\w+=,.@-]+

Required: Yes

createdAt

The time when the service pipeline was created.

Type: Timestamp

Required: Yes

deploymentStatus

The deployment status of the service pipeline.

Type: String

Valid Values: IN_PROGRESS | FAILED | SUCCEEDED | DELETE_IN_PROGRESS | DELETE_FAILED | DELETE_COMPLETE | CANCELLING | CANCELLED

Required: Yes

lastDeploymentAttemptedAt

The time when a deployment of the service pipeline was last attempted.

Type: Timestamp

Required: Yes

lastDeploymentSucceededAt

The time when the service pipeline was last deployed successfully.

Type: Timestamp

Required: Yes

templateMajorVersion

The major version of the service template that was used to create the service pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: $(0|([1-9]\{1\}\d*))$

Required: Yes

templateMinorVersion

The minor version of the service template that was used to create the service pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: $(0|([1-9]\{1\}\d*))$

Required: Yes

templateName

The name of the service template that was used to create the service pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: $[0-9A-Za-z]+[0-9A-Za-z_\-]^{*}$

Required: Yes

deploymentStatusMessage

A service pipeline deployment status message.

Type: String

Required: No

lastAttemptedDeploymentId

The ID of the last attempted deployment of this service pipeline.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

lastSucceededDeploymentId

The ID of the last successful deployment of this service pipeline.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

spec

The service spec that was used to create the service pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 51200.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServicePipelineState

The detailed data about the current state of the service pipeline.

Contents

templateMajorVersion

The major version of the service template that was used to create the service pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: $(0|([1-9]\{1\}\d*))$

Required: Yes

templateMinorVersion

The minor version of the service template that was used to create the service pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: $(0|([1-9]\{1\}\d*))$

Required: Yes

templateName

The name of the service template that was used to create the service pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: $[0-9A-Za-z]+[0-9A-Za-z_]*$

Required: Yes

spec

The service spec that was used to create the service pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 51200.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceSummary

Summary data of an AWS Proton service resource.

Contents

arn

The Amazon Resource Name (ARN) of the service.

Type: String

Required: Yes

createdAt

The time when the service was created.

Type: Timestamp

Required: Yes

lastModifiedAt

The time when the service was last modified.

Type: Timestamp

Required: Yes

name

The name of the service.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

status

The status of the service.

Type: String

Valid Values: CREATE_IN_PROGRESS | CREATE_FAILED_CLEANUP_IN_PROGRESS
| CREATE_FAILED_CLEANUP_COMPLETE | CREATE_FAILED_CLEANUP_FAILED
| CREATE_FAILED | ACTIVE | DELETE_IN_PROGRESS | DELETE_FAILED
| UPDATE_IN_PROGRESS | UPDATE_FAILED_CLEANUP_IN_PROGRESS |
UPDATE_FAILED_CLEANUP_COMPLETE | UPDATE_FAILED_CLEANUP_FAILED |
UPDATE_FAILED | UPDATE_COMPLETE_CLEANUP_FAILED

Required: Yes

templateName

The name of the service template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

description

A description of the service.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

statusMessage

A service status message.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceSyncBlockerSummary

If a service instance is manually updated, Proton wants to prevent accidentally overriding a manual change.

A blocker is created because of the manual update or deletion of a service instance. The summary describes the blocker as being active or resolved.

Contents

serviceName

The name of the service that you want to get the sync blocker summary for. If given a service instance name and a service name, it will return the blockers only applying to the instance that is blocked.

If given only a service name, it will return the blockers that apply to all of the instances. In order to get the blockers for a single instance, you will need to make two distinct calls, one to get the sync blocker summary for the service and the other to get the sync blocker for the service instance.

Type: String

Required: Yes

latestBlockers

The latest active blockers for the synced service.

Type: Array of [SyncBlocker](#) objects

Required: No

serviceInstanceName

The name of the service instance that you want sync your service configuration with.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceSyncConfig

Detailed data of the service sync configuration.

Contents

branch

The name of the code repository branch that holds the service code AWS Proton will sync with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: Yes

filePath

The file path to the service sync configuration file.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: Yes

repositoryName

The name of the code repository that holds the service code AWS Proton will sync with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: .*[A-Za-z0-9_.-]*.[A-Za-z0-9_.-].*

Required: Yes

repositoryProvider

The name of the repository provider that holds the repository AWS Proton will sync with.

Type: String

Valid Values: GITHUB | GITHUB_ENTERPRISE | BITBUCKET

Required: Yes

serviceName

The name of the service that the service instance is added to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceTemplate

Detailed data of an AWS Proton service template resource.

Contents

arn

The Amazon Resource Name (ARN) of the service template.

Type: String

Required: Yes

createdAt

The time when the service template was created.

Type: Timestamp

Required: Yes

lastModifiedAt

The time when the service template was last modified.

Type: Timestamp

Required: Yes

name

The name of the service template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

description

A description of the service template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

displayName

The service template name as displayed in the developer interface.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

encryptionKey

The customer provided service template encryption key that's used to encrypt data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `arn:(aws|aws-cn|aws-us-gov):[a-zA-Z0-9-]+:[a-zA-Z0-9-]*:\d{12}:([\w+=,.@-]+[/:])*([\w+=,.@-]+)`

Required: No

pipelineProvisioning

If `pipelineProvisioning` is `true`, a service pipeline is included in the service template. Otherwise, a service pipeline *isn't* included in the service template.

Type: String

Valid Values: CUSTOMER_MANAGED

Required: No

recommendedVersion

The recommended version of the service template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: `(0|([1-9]{1}\d*)).(0|([1-9]{1}\d*))`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceTemplateSummary

Summary data of an AWS Proton service template resource.

Contents

arn

The Amazon Resource Name (ARN) of the service template.

Type: String

Required: Yes

createdAt

The time when the service template was created.

Type: Timestamp

Required: Yes

lastModifiedAt

The time when the service template was last modified.

Type: Timestamp

Required: Yes

name

The name of the service template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

description

A description of the service template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

displayName

The service template name as displayed in the developer interface.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

pipelineProvisioning

If `pipelineProvisioning` is `true`, a service pipeline is included in the service template, otherwise a service pipeline *isn't* included in the service template.

Type: String

Valid Values: CUSTOMER_MANAGED

Required: No

recommendedVersion

The recommended version of the service template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: `(0|([1-9]{1}\d*)).(0|([1-9]{1}\d*))`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceTemplateVersion

Detailed data of an AWS Proton service template version resource.

Contents

arn

The Amazon Resource Name (ARN) of the version of a service template.

Type: String

Required: Yes

compatibleEnvironmentTemplates

An array of compatible environment template names for the major version of a service template.

Type: Array of [CompatibleEnvironmentTemplate](#) objects

Required: Yes

createdAt

The time when the version of a service template was created.

Type: Timestamp

Required: Yes

lastModifiedAt

The time when the version of a service template was last modified.

Type: Timestamp

Required: Yes

majorVersion

The latest major version that's associated with the version of a service template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: $(0|([1-9]\{1\}\d*))$

Required: Yes

minorVersion

The minor version of a service template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: $(0|([1-9]\{1\}\d*))$

Required: Yes

status

The service template version status.

Type: String

Valid Values: REGISTRATION_IN_PROGRESS | REGISTRATION_FAILED | DRAFT | PUBLISHED

Required: Yes

templateName

The name of the version of a service template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: $[0-9A-Za-z]+[0-9A-Za-z_\\-]*$

Required: Yes

description

A description of the version of a service template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

recommendedMinorVersion

The recommended minor version of the service template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (0|([1-9]{1}\d*))

Required: No

schema

The schema of the version of a service template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 51200.

Required: No

statusMessage

A service template version status message.

Type: String

Required: No

supportedComponentSources

An array of supported component sources. Components with supported sources can be attached to service instances based on this service template version.

For more information about components, see [AWS Proton components](#) in the *AWS Proton User Guide*.

Type: Array of strings

Valid Values: DIRECTLY_DEFINED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceTemplateVersionSummary

Summary data of an AWS Proton service template version resource.

Contents

arn

The Amazon Resource Name (ARN) of the version of a service template.

Type: String

Required: Yes

createdAt

The time when the version of a service template was created.

Type: Timestamp

Required: Yes

lastModifiedAt

The time when the version of a service template was last modified.

Type: Timestamp

Required: Yes

majorVersion

The latest major version that's associated with the version of a service template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (0|([1-9]{1}\d*))

Required: Yes

minorVersion

The minor version of a service template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (0|([1-9]{1}\d*))

Required: Yes

status

The service template minor version status.

Type: String

Valid Values: REGISTRATION_IN_PROGRESS | REGISTRATION_FAILED | DRAFT | PUBLISHED

Required: Yes

templateName

The name of the service template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [0-9A-Za-z]+[0-9A-Za-z_-]*

Required: Yes

description

A description of the version of a service template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

recommendedMinorVersion

The recommended minor version of the service template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: (\emptyset | ([1-9]{1}\d*))

Required: No

statusMessage

A service template minor version status message.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SyncBlocker

Detailed data of the sync blocker.

Contents

createdAt

The time when the sync blocker was created.

Type: Timestamp

Required: Yes

createdReason

The reason why the sync blocker was created.

Type: String

Required: Yes

id

The ID of the sync blocker.

Type: String

Required: Yes

status

The status of the sync blocker.

Type: String

Valid Values: ACTIVE | RESOLVED

Required: Yes

type

The type of the sync blocker.

Type: String

Valid Values: AUTOMATED

Required: Yes

contexts

The contexts for the sync blocker.

Type: Array of [SyncBlockerContext](#) objects

Required: No

resolvedAt

The time the sync blocker was resolved.

Type: Timestamp

Required: No

resolvedReason

The reason the sync blocker was resolved.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SyncBlockerContext

Detailed data of the context of the sync blocker.

Contents

key

The key for the sync blocker context.

Type: String

Required: Yes

value

The value of the sync blocker context.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

A description of a resource tag.

Contents

key

The key of the resource tag.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

value

The value of the resource tag.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TemplateSyncConfig

The detail data for a template sync configuration.

Contents

branch

The repository branch.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: Yes

repositoryName

The repository name (for example, myrepos/myrepo).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: .*[A-Za-z0-9_.-].*/[A-Za-z0-9_.-].*

Required: Yes

repositoryProvider

The repository provider.

Type: String

Valid Values: GITHUB | GITHUB_ENTERPRISE | BITBUCKET

Required: Yes

templateName

The template name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[0-9A-Za-z]+[0-9A-Za-z_-\\-]*`

Required: Yes

templateType

The template type.

Type: String

Valid Values: ENVIRONMENT | SERVICE

Required: Yes

subdirectory

A subdirectory path to your template bundle version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TemplateVersionSourceInput

Template version source data.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

s3

An S3 source object that includes the template bundle S3 path and name for a template minor version.

Type: [S3ObjectSource](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request").

The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400