



Welcome

Amazon Redshift Serverless



API Version 2021-04-21

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon Redshift Serverless: Welcome

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
ConvertRecoveryPointToSnapshot	5
Request Syntax	5
Request Parameters	5
Response Syntax	6
Response Elements	7
Errors	7
See Also	8
CreateCustomDomainAssociation	9
Request Syntax	9
Request Parameters	9
Response Syntax	10
Response Elements	10
Errors	11
See Also	12
CreateEndpointAccess	13
Request Syntax	13
Request Parameters	13
Response Syntax	14
Response Elements	15
Errors	15
See Also	16
CreateNamespace	18
Request Syntax	18
Request Parameters	18
Response Syntax	21
Response Elements	21
Errors	22
See Also	22
CreateReservation	24
Request Syntax	24
Request Parameters	24
Response Syntax	25

Response Elements	25
Errors	26
See Also	27
CreateScheduledAction	28
Request Syntax	28
Request Parameters	28
Response Syntax	30
Response Elements	31
Errors	31
See Also	32
CreateSnapshot	33
Request Syntax	33
Request Parameters	33
Response Syntax	34
Response Elements	35
Errors	35
See Also	36
CreateSnapshotCopyConfiguration	37
Request Syntax	37
Request Parameters	37
Response Syntax	38
Response Elements	38
Errors	38
See Also	39
CreateUsageLimit	41
Request Syntax	41
Request Parameters	41
Response Syntax	42
Response Elements	43
Errors	43
See Also	44
CreateWorkgroup	45
Request Syntax	45
Request Parameters	46
Response Syntax	49
Response Elements	51

Errors	51
Examples	52
See Also	53
DeleteCustomDomainAssociation	55
Request Syntax	55
Request Parameters	55
Response Elements	56
Errors	56
See Also	57
DeleteEndpointAccess	58
Request Syntax	58
Request Parameters	58
Response Syntax	58
Response Elements	59
Errors	59
See Also	60
DeleteNamespace	61
Request Syntax	61
Request Parameters	61
Response Syntax	62
Response Elements	62
Errors	62
See Also	63
DeleteResourcePolicy	65
Request Syntax	65
Request Parameters	65
Response Elements	65
Errors	65
See Also	66
DeleteScheduledAction	67
Request Syntax	67
Request Parameters	67
Response Syntax	67
Response Elements	68
Errors	68
See Also	69

DeleteSnapshot	70
Request Syntax	70
Request Parameters	70
Response Syntax	70
Response Elements	71
Errors	71
See Also	72
DeleteSnapshotCopyConfiguration	73
Request Syntax	73
Request Parameters	73
Response Syntax	73
Response Elements	73
Errors	74
See Also	75
DeleteUsageLimit	76
Request Syntax	76
Request Parameters	76
Response Syntax	76
Response Elements	76
Errors	77
See Also	77
DeleteWorkgroup	79
Request Syntax	79
Request Parameters	79
Response Syntax	79
Response Elements	81
Errors	81
See Also	82
GetCredentials	83
Request Syntax	83
Request Parameters	83
Response Syntax	84
Response Elements	85
Errors	85
See Also	86
GetCustomDomainAssociation	87

Request Syntax	87
Request Parameters	87
Response Syntax	88
Response Elements	88
Errors	89
See Also	90
GetEndpointAccess	91
Request Syntax	91
Request Parameters	91
Response Syntax	91
Response Elements	92
Errors	92
See Also	93
GetIdentityCenterAuthToken	94
Request Syntax	94
Request Parameters	94
Response Syntax	95
Response Elements	95
Errors	95
See Also	96
GetNamespace	98
Request Syntax	98
Request Parameters	98
Response Syntax	98
Response Elements	99
Errors	99
See Also	100
GetRecoveryPoint	101
Request Syntax	101
Request Parameters	101
Response Syntax	101
Response Elements	101
Errors	102
See Also	102
GetReservation	104
Request Syntax	104

Request Parameters	104
Response Syntax	104
Response Elements	105
Errors	105
See Also	106
GetReservationOffering	107
Request Syntax	107
Request Parameters	107
Response Syntax	107
Response Elements	108
Errors	108
See Also	109
GetResourcePolicy	110
Request Syntax	110
Request Parameters	110
Response Syntax	110
Response Elements	110
Errors	111
See Also	111
GetScheduledAction	113
Request Syntax	113
Request Parameters	113
Response Syntax	113
Response Elements	114
Errors	114
See Also	115
GetSnapshot	116
Request Syntax	116
Request Parameters	116
Response Syntax	117
Response Elements	117
Errors	118
See Also	118
GetTableRestoreStatus	120
Request Syntax	120
Request Parameters	120

Response Syntax	120
Response Elements	121
Errors	121
See Also	121
GetTrack	123
Request Syntax	123
Request Parameters	123
Response Syntax	123
Response Elements	124
Errors	124
Examples	125
See Also	126
GetUsageLimit	127
Request Syntax	127
Request Parameters	127
Response Syntax	127
Response Elements	127
Errors	128
See Also	128
GetWorkgroup	130
Request Syntax	130
Request Parameters	130
Response Syntax	130
Response Elements	132
Errors	132
Examples	133
See Also	133
ListCustomDomainAssociations	135
Request Syntax	135
Request Parameters	135
Response Syntax	136
Response Elements	136
Errors	137
See Also	138
ListEndpointAccess	139
Request Syntax	139

Request Parameters	139
Response Syntax	140
Response Elements	141
Errors	141
See Also	142
ListManagedWorkgroups	143
Request Syntax	143
Request Parameters	143
Response Syntax	144
Response Elements	144
Errors	145
See Also	145
ListNamespaces	146
Request Syntax	146
Request Parameters	146
Response Syntax	146
Response Elements	147
Errors	147
See Also	148
ListRecoveryPoints	149
Request Syntax	149
Request Parameters	149
Response Syntax	150
Response Elements	151
Errors	151
See Also	152
ListReservationOfferings	153
Request Syntax	153
Request Parameters	153
Response Syntax	153
Response Elements	154
Errors	154
See Also	155
ListReservations	156
Request Syntax	156
Request Parameters	156

Response Syntax	156
Response Elements	157
Errors	157
See Also	158
ListScheduledActions	159
Request Syntax	159
Request Parameters	159
Response Syntax	160
Response Elements	160
Errors	161
See Also	161
ListSnapshotCopyConfigurations	163
Request Syntax	163
Request Parameters	163
Response Syntax	164
Response Elements	164
Errors	165
See Also	166
ListSnapshots	167
Request Syntax	167
Request Parameters	167
Response Syntax	168
Response Elements	169
Errors	170
See Also	170
ListTableRestoreStatus	172
Request Syntax	172
Request Parameters	172
Response Syntax	173
Response Elements	174
Errors	174
See Also	175
ListTagsForResource	176
Request Syntax	176
Request Parameters	176
Response Syntax	176

Response Elements	176
Errors	177
See Also	177
ListTracks	179
Request Syntax	179
Request Parameters	179
Response Syntax	180
Response Elements	180
Errors	180
Examples	181
See Also	182
ListUsageLimits	184
Request Syntax	184
Request Parameters	184
Response Syntax	185
Response Elements	185
Errors	186
See Also	187
ListWorkgroups	188
Request Syntax	188
Request Parameters	188
Response Syntax	189
Response Elements	190
Errors	191
Examples	191
See Also	192
PutResourcePolicy	193
Request Syntax	193
Request Parameters	193
Response Syntax	194
Response Elements	194
Errors	194
See Also	195
RestoreFromRecoveryPoint	196
Request Syntax	196
Request Parameters	196

Response Syntax	197
Response Elements	197
Errors	198
See Also	198
RestoreFromSnapshot	200
Request Syntax	200
Request Parameters	200
Response Syntax	202
Response Elements	202
Errors	203
See Also	204
RestoreTableFromRecoveryPoint	205
Request Syntax	205
Request Parameters	205
Response Syntax	207
Response Elements	207
Errors	208
See Also	208
RestoreTableFromSnapshot	210
Request Syntax	210
Request Parameters	210
Response Syntax	212
Response Elements	212
Errors	213
See Also	213
TagResource	215
Request Syntax	215
Request Parameters	215
Response Elements	216
Errors	216
See Also	217
UntagResource	218
Request Syntax	218
Request Parameters	218
Response Elements	218
Errors	219

See Also	219
UpdateCustomDomainAssociation	221
Request Syntax	221
Request Parameters	221
Response Syntax	222
Response Elements	222
Errors	223
See Also	224
UpdateEndpointAccess	225
Request Syntax	225
Request Parameters	225
Response Syntax	225
Response Elements	226
Errors	226
See Also	227
UpdateLakehouseConfiguration	229
Request Syntax	229
Request Parameters	229
Response Syntax	231
Response Elements	231
Errors	232
See Also	232
UpdateNamespace	234
Request Syntax	234
Request Parameters	234
Response Syntax	236
Response Elements	237
Errors	237
See Also	238
UpdateScheduledAction	239
Request Syntax	239
Request Parameters	239
Response Syntax	241
Response Elements	241
Errors	242
See Also	242

UpdateSnapshot	244
Request Syntax	244
Request Parameters	244
Response Syntax	244
Response Elements	245
Errors	245
See Also	246
UpdateSnapshotCopyConfiguration	247
Request Syntax	247
Request Parameters	247
Response Syntax	247
Response Elements	248
Errors	248
See Also	249
UpdateUsageLimit	250
Request Syntax	250
Request Parameters	250
Response Syntax	251
Response Elements	251
Errors	251
See Also	252
UpdateWorkgroup	253
Request Syntax	253
Request Parameters	254
Response Syntax	257
Response Elements	258
Errors	258
Examples	259
See Also	260
Data Types	261
Association	263
Contents	263
See Also	264
ConfigParameter	265
Contents	265
See Also	265

CreateSnapshotScheduleActionParameters	267
Contents	267
See Also	268
Endpoint	269
Contents	269
See Also	269
EndpointAccess	270
Contents	270
See Also	271
ManagedWorkgroupListItem	273
Contents	273
See Also	274
Namespace	275
Contents	275
See Also	278
NetworkInterface	279
Contents	279
See Also	280
PerformanceTarget	281
Contents	281
See Also	281
RecoveryPoint	282
Contents	282
See Also	283
Reservation	284
Contents	284
See Also	285
ReservationOffering	286
Contents	286
See Also	287
ResourcePolicy	288
Contents	288
See Also	288
Schedule	289
Contents	289
See Also	289

ScheduledActionAssociation	291
Contents	291
See Also	291
ScheduledActionResponse	292
Contents	292
See Also	294
ServerlessTrack	296
Contents	296
See Also	296
Snapshot	298
Contents	298
See Also	301
SnapshotCopyConfiguration	303
Contents	303
See Also	304
TableRestoreStatus	305
Contents	305
See Also	307
Tag	309
Contents	309
See Also	309
TargetAction	310
Contents	310
See Also	310
UpdateTarget	311
Contents	311
See Also	311
UsageLimit	312
Contents	312
See Also	313
VpcEndpoint	314
Contents	314
See Also	314
VpcSecurityGroupMembership	315
Contents	315
See Also	315

Workgroup	316
Contents	316
See Also	321
Common Parameters	322
Common Errors	325

Welcome

This is an interface reference for Amazon Redshift Serverless. It contains documentation for one of the programming or command line interfaces you can use to manage Amazon Redshift Serverless.

Amazon Redshift Serverless automatically provisions data warehouse capacity and intelligently scales the underlying resources based on workload demands. Amazon Redshift Serverless adjusts capacity in seconds to deliver consistently high performance and simplified operations for even the most demanding and volatile workloads. Amazon Redshift Serverless lets you focus on using your data to acquire new insights for your business and customers.

To learn more about Amazon Redshift Serverless, see [What is Amazon Redshift Serverless?](#).

This document was last published on March 23, 2026.

Actions

The following actions are supported:

- [ConvertRecoveryPointToSnapshot](#)
- [CreateCustomDomainAssociation](#)
- [CreateEndpointAccess](#)
- [CreateNamespace](#)
- [CreateReservation](#)
- [CreateScheduledAction](#)
- [CreateSnapshot](#)
- [CreateSnapshotCopyConfiguration](#)
- [CreateUsageLimit](#)
- [CreateWorkgroup](#)
- [DeleteCustomDomainAssociation](#)
- [DeleteEndpointAccess](#)
- [DeleteNamespace](#)
- [DeleteResourcePolicy](#)
- [DeleteScheduledAction](#)
- [DeleteSnapshot](#)
- [DeleteSnapshotCopyConfiguration](#)
- [DeleteUsageLimit](#)
- [DeleteWorkgroup](#)
- [GetCredentials](#)
- [GetCustomDomainAssociation](#)
- [GetEndpointAccess](#)
- [GetIdentityCenterAuthToken](#)
- [GetNamespace](#)
- [GetRecoveryPoint](#)
- [GetReservation](#)
- [GetReservationOffering](#)

- [GetResourcePolicy](#)
- [GetScheduledAction](#)
- [GetSnapshot](#)
- [GetTableRestoreStatus](#)
- [GetTrack](#)
- [GetUsageLimit](#)
- [GetWorkgroup](#)
- [ListCustomDomainAssociations](#)
- [ListEndpointAccess](#)
- [ListManagedWorkgroups](#)
- [ListNamespaces](#)
- [ListRecoveryPoints](#)
- [ListReservationOfferings](#)
- [ListReservations](#)
- [ListScheduledActions](#)
- [ListSnapshotCopyConfigurations](#)
- [ListSnapshots](#)
- [ListTableRestoreStatus](#)
- [ListTagsForResource](#)
- [ListTracks](#)
- [ListUsageLimits](#)
- [ListWorkgroups](#)
- [PutResourcePolicy](#)
- [RestoreFromRecoveryPoint](#)
- [RestoreFromSnapshot](#)
- [RestoreTableFromRecoveryPoint](#)
- [RestoreTableFromSnapshot](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateCustomDomainAssociation](#)

- [UpdateEndpointAccess](#)
- [UpdateLakehouseConfiguration](#)
- [UpdateNamespace](#)
- [UpdateScheduledAction](#)
- [UpdateSnapshot](#)
- [UpdateSnapshotCopyConfiguration](#)
- [UpdateUsageLimit](#)
- [UpdateWorkgroup](#)

ConvertRecoveryPointToSnapshot

Converts a recovery point to a snapshot. For more information about recovery points and snapshots, see [Working with snapshots and recovery points](#).

Request Syntax

```
{
  "recoveryPointId": "string",
  "retentionPeriod": number,
  "snapshotName": "string",
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[recoveryPointId](#)

The unique identifier of the recovery point.

Type: String

Required: Yes

[retentionPeriod](#)

How long to retain the snapshot.

Type: Integer

Required: No

[snapshotName](#)

The name of the snapshot.

Type: String

Required: Yes

tags

An array of [Tag objects](#) to associate with the created snapshot.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

Response Syntax

```
{
  "snapshot": {
    "accountsWithProvisionedRestoreAccess": [ "string" ],
    "accountsWithRestoreAccess": [ "string" ],
    "actualIncrementalBackupSizeInMegaBytes": number,
    "adminPasswordSecretArn": "string",
    "adminPasswordSecretKmsKeyId": "string",
    "adminUsername": "string",
    "backupProgressInMegaBytes": number,
    "currentBackupRateInMegaBytesPerSecond": number,
    "elapsedTimeInSeconds": number,
    "estimatedSecondsToCompletion": number,
    "kmsKeyId": "string",
    "namespaceArn": "string",
    "namespaceName": "string",
    "ownerAccount": "string",
    "snapshotArn": "string",
    "snapshotCreateTime": "string",
    "snapshotName": "string",
    "snapshotRemainingDays": number,
    "snapshotRetentionPeriod": number,
    "snapshotRetentionStartTime": "string",
    "status": "string",
    "totalBackupSizeInMegaBytes": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

snapshot

The snapshot converted from the recovery point.

Type: [Snapshot](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ServiceQuotaExceededException

The service limit was exceeded.

HTTP Status Code: 400

TooManyTagsException

The request exceeded the number of tags allowed for a resource.

resourceName

The name of the resource that exceeded the number of tags allowed for a resource.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateCustomDomainAssociation

Creates a custom domain association for Amazon Redshift Serverless.

Request Syntax

```
{
  "customDomainCertificateArn": "string",
  "customDomainName": "string",
  "workgroupName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

customDomainCertificateArn

The custom domain name's certificate Amazon resource name (ARN).

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `.*arn:[\w+=/, .@-]+:acm:[\w+=/, .@-]*:[0-9]+:[\w+=, .@-]+(\/[\w+=, .@-]+)*.*`

Required: Yes

customDomainName

The custom domain name to associate with the workgroup.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 253.

Pattern: `((?!-)[A-Za-z0-9-]{0,62}[A-Za-z0-9])\.+((?!-)[A-Za-z0-9-]{1,62}[A-Za-z0-9])`

Required: Yes

workgroupName

The name of the workgroup associated with the database.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: Yes

Response Syntax

```
{
  "customDomainCertificateArn": "string",
  "customDomainCertificateExpiryTime": "string",
  "customDomainName": "string",
  "workgroupName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

customDomainCertificateArn

The custom domain name's certificate Amazon resource name (ARN).

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: .*arn:[\w+=/, .@-]+:acm:[\w+=/, .@-]*:[0-9]+:[\w+=, .@-]+(/[\w+=, .@-]+)*.*

customDomainCertificateExpiryTime

The expiration time for the certificate.

Type: Timestamp

customDomainName

The custom domain name to associate with the workgroup.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 253.

Pattern: (((?!-)[A-Za-z0-9-]{0,62}[A-Za-z0-9])\.)+((?!-)[A-Za-z0-9-]{1,62}[A-Za-z0-9])

workgroupName

The name of the workgroup associated with the database.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateEndpointAccess

Creates an Amazon Redshift Serverless managed VPC endpoint.

Request Syntax

```
{
  "endpointName": "string",
  "ownerAccount": "string",
  "subnetIds": [ "string" ],
  "vpcSecurityGroupIds": [ "string" ],
  "workgroupName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

endpointName

The name of the VPC endpoint. An endpoint name must contain 1-30 characters. Valid characters are A-Z, a-z, 0-9, and hyphen(-). The first character must be a letter. The name can't contain two consecutive hyphens or end with a hyphen.

Type: String

Required: Yes

ownerAccount

The owner AWS account for the Amazon Redshift Serverless workgroup.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 12.

Pattern: `.*(\d{12}).*`

Required: No

subnetIds

The unique identifiers of subnets from which Amazon Redshift Serverless chooses one to deploy a VPC endpoint.

Type: Array of strings

Required: Yes

vpcSecurityGroupIds

The unique identifiers of the security group that defines the ports, protocols, and sources for inbound traffic that you are authorizing into your endpoint.

Type: Array of strings

Required: No

workgroupName

The name of the workgroup to associate with the VPC endpoint.

Type: String

Required: Yes

Response Syntax

```
{
  "endpoint": {
    "address": "string",
    "endpointArn": "string",
    "endpointCreateTime": "string",
    "endpointName": "string",
    "endpointStatus": "string",
    "port": number,
    "subnetIds": [ "string" ],
    "vpcEndpoint": {
      "networkInterfaces": [
        {
          "availabilityZone": "string",
          "ipv6Address": "string",
          "networkInterfaceId": "string",
          "privateIpAddress": "string",
```

```
        "subnetId": "string"
      }
    ],
    "vpcEndpointId": "string",
    "vpcId": "string"
  },
  "vpcSecurityGroups": [
    {
      "status": "string",
      "vpcSecurityGroupId": "string"
    }
  ],
  "workgroupName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

endpoint

The created VPC endpoint.

Type: [EndpointAccess](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ServiceQuotaExceededException

The service limit was exceeded.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateNamespace

Creates a namespace in Amazon Redshift Serverless.

Request Syntax

```
{
  "adminPasswordSecretKmsKeyId": "string",
  "adminUsername": "string",
  "adminUserPassword": "string",
  "dbName": "string",
  "defaultIamRoleArn": "string",
  "iamRoles": [ "string" ],
  "kmsKeyId": "string",
  "logExports": [ "string" ],
  "manageAdminPassword": boolean,
  "namespaceName": "string",
  "redshiftIdcApplicationArn": "string",
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[adminPasswordSecretKmsKeyId](#)

The ID of the AWS Key Management Service (KMS) key used to encrypt and store the namespace's admin credentials secret. You can only use this parameter if `manageAdminPassword` is true.

Type: String

Required: No

adminUsername

The username of the administrator for the first database created in the namespace.

Type: String

Required: No

adminUserPassword

The password of the administrator for the first database created in the namespace.

You can't use `adminUserPassword` if `manageAdminPassword` is true.

Type: String

Required: No

dbName

The name of the first database created in the namespace.

Type: String

Required: No

defaultIamRoleArn

The Amazon Resource Name (ARN) of the IAM role to set as a default in the namespace.

Type: String

Required: No

iamRoles

A list of IAM roles to associate with the namespace.

Type: Array of strings

Required: No

kmsKeyId

The ID of the AWS Key Management Service key used to encrypt your data.

Type: String

Required: No

logExports

The types of logs the namespace can export. Available export types are `userlog`, `connectionlog`, and `useractivitylog`.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 16 items.

Valid Values: `useractivitylog` | `userlog` | `connectionlog`

Required: No

manageAdminPassword

If `true`, Amazon Redshift uses AWS Secrets Manager to manage the namespace's admin credentials. You can't use `adminUserPassword` if `manageAdminPassword` is `true`. If `manageAdminPassword` is `false` or not set, Amazon Redshift uses `adminUserPassword` for the admin user account's password.

Type: Boolean

Required: No

namespaceName

The name of the namespace.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: `[a-z0-9-]+`

Required: Yes

redshiftIamApplicationArn

The ARN for the Redshift application that integrates with IAM Identity Center.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

[tags](#)

A list of tag instances.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

Response Syntax

```
{
  "namespace": {
    "adminPasswordSecretArn": "string",
    "adminPasswordSecretKmsKeyId": "string",
    "adminUsername": "string",
    "catalogArn": "string",
    "creationDate": "string",
    "dbName": "string",
    "defaultIamRoleArn": "string",
    "iamRoles": [ "string" ],
    "kmsKeyId": "string",
    "lakehouseRegistrationStatus": "string",
    "logExports": [ "string" ],
    "namespaceArn": "string",
    "namespaceId": "string",
    "namespaceName": "string",
    "status": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[namespace](#)

The created namespace object.

Type: [Namespace](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

TooManyTagsException

The request exceeded the number of tags allowed for a resource.

resourceName

The name of the resource that exceeded the number of tags allowed for a resource.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateReservation

Creates an Amazon Redshift Serverless reservation, which gives you the option to commit to a specified number of Redshift Processing Units (RPUs) for a year at a discount from Serverless on-demand (OD) rates.

Request Syntax

```
{  
  "capacity": number,  
  "clientToken": "string",  
  "offeringId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

capacity

The number of Redshift Processing Units (RPUs) to reserve.

Type: Integer

Required: Yes

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. If not provided, the Amazon Web Services SDK populates this field. This token must be a valid UUIDv4 value. For more information about idempotency, see [Making retries safe with idempotent APIs](#).

Type: String

Required: No

offeringId

The ID of the offering associated with the reservation. The offering determines the payment schedule for the reservation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

Response Syntax

```
{
  "reservation": {
    "capacity": number,
    "endDate": "string",
    "offering": {
      "currencyCode": "string",
      "duration": number,
      "hourlyCharge": number,
      "offeringId": "string",
      "offeringType": "string",
      "upfrontCharge": number
    },
    "reservationArn": "string",
    "reservationId": "string",
    "startDate": "string",
    "status": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

reservation

The reservation object that the `CreateReservation` action created.

Type: [Reservation](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ServiceQuotaExceededException

The service limit was exceeded.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

TooManyTagsException

The request exceeded the number of tags allowed for a resource.

resourceName

The name of the resource that exceeded the number of tags allowed for a resource.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateScheduledAction

Creates a scheduled action. A scheduled action contains a schedule and an Amazon Redshift API action. For example, you can create a schedule of when to run the CreateSnapshot API operation.

Request Syntax

```
{
  "enabled": boolean,
  "endTime": number,
  "namespaceName": "string",
  "roleArn": "string",
  "schedule": { ... },
  "scheduledActionDescription": "string",
  "scheduledActionName": "string",
  "startTime": number,
  "targetAction": { ... }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[enabled](#)

Indicates whether the schedule is enabled. If false, the scheduled action does not trigger. For more information about state of the scheduled action, see [ScheduledAction](#).

Type: Boolean

Required: No

[endTime](#)

The end time in UTC when the schedule is no longer active. After this time, the scheduled action does not trigger.

Type: Timestamp

Required: No

namespaceName

The name of the namespace for which to create a scheduled action.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: Yes

roleArn

The ARN of the IAM role to assume to run the scheduled action. This IAM role must have permission to run the Amazon Redshift Serverless API operation in the scheduled action. This IAM role must allow the Amazon Redshift scheduler to schedule creating snapshots. (Principal scheduler.redshift.amazonaws.com) to assume permissions on your behalf. For more information about the IAM role to use with the Amazon Redshift scheduler, see [Using Identity-Based Policies for Amazon Redshift](#) in the Amazon Redshift Management Guide

Type: String

Required: Yes

schedule

The schedule for a one-time (at timestamp format) or recurring (cron format) scheduled action. Schedule invocations must be separated by at least one hour. Times are in UTC.

- Format of at timestamp is yyyy-mm-ddThh:mm:ss. For example, 2016-03-04T17:27:00.
- Format of cron expression is (Minutes Hours Day-of-month Month Day-of-week Year). For example, "(0 10 ? * MON *)". For more information, see [Cron Expressions](#) in the *Amazon CloudWatch Events User Guide*.

Type: [Schedule](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

scheduledActionDescription

The description of the scheduled action.

Type: String

Required: No

scheduledActionName

The name of the scheduled action.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 60.

Pattern: [a-z0-9-]+

Required: Yes

startTime

The start time in UTC when the schedule is active. Before this time, the scheduled action does not trigger.

Type: Timestamp

Required: No

targetAction

A JSON format string of the Amazon Redshift Serverless API operation with input parameters. The following is an example of a target action.

```
"{"CreateSnapshot": {"NamespaceName": "sampleNamespace", "SnapshotName": "sampleSnapshot", "retentionPeriod": "1"}}"
```

Type: [TargetAction](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

Response Syntax

```
{  
  "scheduledAction": {  
    "endTime": number,
```

```
"namespaceName": "string",
"nextInvocations": [ number ],
"roleArn": "string",
"schedule": { ... },
"scheduledActionDescription": "string",
"scheduledActionName": "string",
"scheduledActionUuid": "string",
"startTime": number,
"state": "string",
"targetAction": { ... }
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

scheduledAction

The returned `ScheduledAction` object that describes the properties of a scheduled action.

Type: [ScheduledActionResponse](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateSnapshot

Creates a snapshot of all databases in a namespace. For more information about snapshots, see [Working with snapshots and recovery points](#).

Request Syntax

```
{
  "namespaceName": "string",
  "retentionPeriod": number,
  "snapshotName": "string",
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[namespaceName](#)

The namespace to create a snapshot for.

Type: String

Required: Yes

[retentionPeriod](#)

How long to retain the created snapshot.

Type: Integer

Required: No

[snapshotName](#)

The name of the snapshot.

Type: String

Required: Yes

tags

An array of [Tag objects](#) to associate with the snapshot.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

Response Syntax

```
{
  "snapshot": {
    "accountsWithProvisionedRestoreAccess": [ "string" ],
    "accountsWithRestoreAccess": [ "string" ],
    "actualIncrementalBackupSizeInMegaBytes": number,
    "adminPasswordSecretArn": "string",
    "adminPasswordSecretKmsKeyId": "string",
    "adminUsername": "string",
    "backupProgressInMegaBytes": number,
    "currentBackupRateInMegaBytesPerSecond": number,
    "elapsedTimeInSeconds": number,
    "estimatedSecondsToCompletion": number,
    "kmsKeyId": "string",
    "namespaceArn": "string",
    "namespaceName": "string",
    "ownerAccount": "string",
    "snapshotArn": "string",
    "snapshotCreateTime": "string",
    "snapshotName": "string",
    "snapshotRemainingDays": number,
    "snapshotRetentionPeriod": number,
    "snapshotRetentionStartTime": "string",
    "status": "string",
    "totalBackupSizeInMegaBytes": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

snapshot

The created snapshot object.

Type: [Snapshot](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ServiceQuotaExceededException

The service limit was exceeded.

HTTP Status Code: 400

TooManyTagsException

The request exceeded the number of tags allowed for a resource.

resourceName

The name of the resource that exceeded the number of tags allowed for a resource.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateSnapshotCopyConfiguration

Creates a snapshot copy configuration that lets you copy snapshots to another AWS Region.

Request Syntax

```
{  
  "destinationKmsKeyId": "string",  
  "destinationRegion": "string",  
  "namespaceName": "string",  
  "snapshotRetentionPeriod": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[destinationKmsKeyId](#)

The KMS key to use to encrypt your snapshots in the destination AWS Region.

Type: String

Required: No

[destinationRegion](#)

The destination AWS Region that you want to copy snapshots to.

Type: String

Required: Yes

[namespaceName](#)

The name of the namespace to copy snapshots from.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: Yes

snapshotRetentionPeriod

The retention period of the snapshots that you copy to the destination AWS Region.

Type: Integer

Required: No

Response Syntax

```
{
  "snapshotCopyConfiguration": {
    "destinationKmsKeyId": "string",
    "destinationRegion": "string",
    "namespaceName": "string",
    "snapshotCopyConfigurationArn": "string",
    "snapshotCopyConfigurationId": "string",
    "snapshotRetentionPeriod": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

snapshotCopyConfiguration

The snapshot copy configuration object that is returned.

Type: [SnapshotCopyConfiguration](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ServiceQuotaExceededException

The service limit was exceeded.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateUsageLimit

Creates a usage limit for a specified Amazon Redshift Serverless usage type. The usage limit is identified by the returned usage limit identifier.

Request Syntax

```
{  
  "amount": number,  
  "breachAction": "string",  
  "period": "string",  
  "resourceArn": "string",  
  "usageType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

amount

The limit amount. If time-based, this amount is in Redshift Processing Units (RPU) consumed per hour. If data-based, this amount is in terabytes (TB) of data transferred between Regions in cross-account sharing. The value must be a positive number.

Type: Long

Required: Yes

breachAction

The action that Amazon Redshift Serverless takes when the limit is reached. The default is log.

Type: String

Valid Values: log | emit-metric | deactivate

Required: No

period

The time period that the amount applies to. A weekly period begins on Sunday. The default is monthly.

Type: String

Valid Values: `daily` | `weekly` | `monthly`

Required: No

resourceArn

The Amazon Resource Name (ARN) of the Amazon Redshift Serverless resource to create the usage limit for.

Type: String

Required: Yes

usageType

The type of Amazon Redshift Serverless usage to create a usage limit for.

Type: String

Valid Values: `serverless-compute` | `cross-region-datasharing`

Required: Yes

Response Syntax

```
{
  "usageLimit": {
    "amount": number,
    "breachAction": "string",
    "period": "string",
    "resourceArn": "string",
    "usageLimitArn": "string",
    "usageLimitId": "string",
    "usageType": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

usageLimit

The returned usage limit object.

Type: [UsageLimit](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ServiceQuotaExceededException

The service limit was exceeded.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateWorkgroup

Creates an workgroup in Amazon Redshift Serverless.

VPC Block Public Access (BPA) enables you to block resources in VPCs and subnets that you own in a Region from reaching or being reached from the internet through internet gateways and egress-only internet gateways. If a workgroup is in an account with VPC BPA turned on, the following capabilities are blocked:

- Creating a public access workgroup
- Modifying a private workgroup to public
- Adding a subnet with VPC BPA turned on to the workgroup when the workgroup is public

For more information about VPC BPA, see [Block public access to VPCs and subnets](#) in the *Amazon VPC User Guide*.

Request Syntax

```
{
  "baseCapacity": number,
  "configParameters": [
    {
      "parameterKey": "string",
      "parameterValue": "string"
    }
  ],
  "enhancedVpcRouting": boolean,
  "extraComputeForAutomaticOptimization": boolean,
  "ipAddressType": "string",
  "maxCapacity": number,
  "namespaceName": "string",
  "port": number,
  "pricePerformanceTarget": {
    "level": number,
    "status": "string"
  },
  "publiclyAccessible": boolean,
  "securityGroupIds": [ "string" ],
  "subnetIds": [ "string" ],
  "tags": [
```

```
{
  {
    "key": "string",
    "value": "string"
  }
],
"trackName": "string",
"workgroupName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[baseCapacity](#)

The base data warehouse capacity of the workgroup in Redshift Processing Units (RPU).

Type: Integer

Required: No

[configParameters](#)

An array of parameters to set for advanced control over a database. The options are `auto_mv`, `datestyle`, `enable_case_sensitive_identifier`, `enable_user_activity_logging`, `query_group`, `search_path`, `require_ssl`, `use_fips_ssl`, and either `wlm_json_configuration` or query monitoring metrics that let you define performance boundaries. You can either specify individual query monitoring metrics (such as `max_scan_row_count`, `max_query_execution_time`) or use `wlm_json_configuration` to define query queues with rules, but not both. If you're using `wlm_json_configuration`, the maximum size of `parameterValue` is 8000 characters. For more information about query monitoring rules and available metrics, see [Query monitoring metrics for Amazon Redshift Serverless](#).

Type: Array of [ConfigParameter](#) objects

Required: No

enhancedVpcRouting

The value that specifies whether to turn on enhanced virtual private cloud (VPC) routing, which forces Amazon Redshift Serverless to route traffic through your VPC instead of over the internet.

Type: Boolean

Required: No

extraComputeForAutomaticOptimization

If `true`, allocates additional compute resources for running automatic optimization operations.

Default: `false`

Type: Boolean

Required: No

ipAddressType

The IP address type that the workgroup supports. Possible values are `ipv4` and `dualstack`.

Type: String

Pattern: `(ipv4|dualstack)`

Required: No

maxCapacity

The maximum data-warehouse capacity Amazon Redshift Serverless uses to serve queries. The max capacity is specified in RPUs.

Type: Integer

Required: No

namespaceName

The name of the namespace to associate with the workgroup.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: `[a-z0-9-]+`

Required: Yes

port

The custom port to use when connecting to a workgroup. Valid port ranges are 5431-5455 and 8191-8215. The default is 5439.

Type: Integer

Required: No

pricePerformanceTarget

An object that represents the price performance target settings for the workgroup.

Type: [PerformanceTarget](#) object

Required: No

publiclyAccessible

A value that specifies whether the workgroup can be accessed from a public network.

Type: Boolean

Required: No

securityGroupIds

An array of security group IDs to associate with the workgroup.

Type: Array of strings

Required: No

subnetIds

An array of VPC subnet IDs to associate with the workgroup.

Type: Array of strings

Required: No

tags

A array of tag instances.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

trackName

An optional parameter for the name of the track for the workgroup. If you don't provide a track name, the workgroup is assigned to the current track.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_]+

Required: No

workgroupName

The name of the created workgroup.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: Yes

Response Syntax

```
{
  "workgroup": {
    "baseCapacity": number,
    "configParameters": [
      {
        "parameterKey": "string",
        "parameterValue": "string"
      }
    ],
    "creationDate": "string",
    "crossAccountVpcs": [ "string" ],
    "customDomainCertificateArn": "string",
    "customDomainCertificateExpiryTime": "string",
    "customDomainName": "string",
    "endpoint": {
      "address": "string",
```

```
"port": number,
"vpcEndpoints": [
  {
    "networkInterfaces": [
      {
        "availabilityZone": "string",
        "ipv6Address": "string",
        "networkInterfaceId": "string",
        "privateIpAddress": "string",
        "subnetId": "string"
      }
    ],
    "vpcEndpointId": "string",
    "vpcId": "string"
  }
],
"enhancedVpcRouting": boolean,
"extraComputeForAutomaticOptimization": boolean,
"ipAddressType": "string",
"maxCapacity": number,
"namespaceName": "string",
"patchVersion": "string",
"pendingTrackName": "string",
"port": number,
"pricePerformanceTarget": {
  "level": number,
  "status": "string"
},
"publiclyAccessible": boolean,
"securityGroupIds": [ "string" ],
"status": "string",
"subnetIds": [ "string" ],
"trackName": "string",
"workgroupArn": "string",
"workgroupId": "string",
"workgroupName": "string",
"workgroupVersion": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

workgroup

The created workgroup object.

Type: [Workgroup](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InsufficientCapacityException

There is an insufficient capacity to perform the action.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

Ipv6CidrBlockNotFoundException

There are no subnets in your VPC with associated IPv6 CIDR blocks. To use dual-stack mode, associate an IPv6 CIDR block with each subnet in your VPC.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

TooManyTagsException

The request exceeded the number of tags allowed for a resource.

resourceName

The name of the resource that exceeded the number of tags allowed for a resource.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `CreateWorkgroup`.

Sample Request

```
aws redshift-serverless create-workgroup
--workgroup-name test-workgroup
--namespace-name test-namespace
--track-name current
--region us-east-1
```

Sample Response

```
{
  "workgroup": {
    "workgroupId": "875083e4-50b5-4ad7-bd8b-b01beb74d912",
    "workgroupArn": "arn:aws:redshift-serverless:us-
east-1:012345678901:workgroup/875083e4-50b5-4ad7-bd8b-b01beb74d912",
    "workgroupName": "test-workgroup",
```

```
    "namespaceName": "test-namespace",
    "baseCapacity": 32,
    "enhancedVpcRouting": false,
    ...
    "securityGroupIds": [
      "sg-0f0e3edaf8473b3d2"
    ],
    "subnetIds": [
      "subnet-05a4615a242adf950",
      "subnet-0d364615acc244f2a",
      "subnet-037672f31c13d78a0",
      "subnet-062539bdf89dfa749",
      "subnet-01534423c994e5e30",
      "subnet-042b4ad9afe0826c6"
    ],
    "status": "CREATING",
    "endpoint": {
      "address": "test-workgroup-1.012345678901.us-east-1-dsk.redshift-
serverless-dev.amazonaws.com",
      "port": 5439
    },
    "publiclyAccessible": false,
    "creationDate": "2024-12-13T14:19:50.636000+00:00",
    "pricePerformanceTarget": {
      "status": "DISABLED"
    },
    "ipAddressType": "ipv4",
    "trackName": "current"
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteCustomDomainAssociation

Deletes a custom domain association for Amazon Redshift Serverless.

Request Syntax

```
{  
  "customDomainName": "string",  
  "workgroupName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

customDomainName

The custom domain name associated with the workgroup.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 253.

Pattern: (((?!-)[A-Za-z0-9-]{0,62}[A-Za-z0-9])\.)+((?!-)[A-Za-z0-9-]{1,62}[A-Za-z0-9])

Required: Yes

workgroupName

The name of the workgroup associated with the database.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteEndpointAccess

Deletes an Amazon Redshift Serverless managed VPC endpoint.

Request Syntax

```
{  
  "endpointName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

endpointName

The name of the VPC endpoint to delete.

Type: String

Required: Yes

Response Syntax

```
{  
  "endpoint": {  
    "address": "string",  
    "endpointArn": "string",  
    "endpointCreateTime": "string",  
    "endpointName": "string",  
    "endpointStatus": "string",  
    "port": number,  
    "subnetIds": [ "string" ],  
    "vpcEndpoint": {  
      "networkInterfaces": [  
        {  
          "availabilityZone": "string",  
          "ipv6Address": "string",
```

```
        "networkInterfaceId": "string",
        "privateIpAddress": "string",
        "subnetId": "string"
    }
],
"vpcEndpointId": "string",
"vpcId": "string"
},
"vpcSecurityGroups": [
    {
        "status": "string",
        "vpcSecurityGroupId": "string"
    }
],
"workgroupName": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

endpoint

The deleted VPC endpoint.

Type: [EndpointAccess](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteNamespace

Deletes a namespace from Amazon Redshift Serverless. Before you delete the namespace, you can create a final snapshot that has all of the data within the namespace.

Request Syntax

```
{
  "finalSnapshotName": "string",
  "finalSnapshotRetentionPeriod": number,
  "namespaceName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

finalSnapshotName

The name of the snapshot to be created before the namespace is deleted.

Type: String

Required: No

finalSnapshotRetentionPeriod

How long to retain the final snapshot.

Type: Integer

Required: No

namespaceName

The name of the namespace to delete.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: Yes

Response Syntax

```
{
  "namespace": {
    "adminPasswordSecretArn": "string",
    "adminPasswordSecretKmsKeyId": "string",
    "adminUsername": "string",
    "catalogArn": "string",
    "creationDate": "string",
    "dbName": "string",
    "defaultIamRoleArn": "string",
    "iamRoles": [ "string" ],
    "kmsKeyId": "string",
    "lakehouseRegistrationStatus": "string",
    "logExports": [ "string" ],
    "namespaceArn": "string",
    "namespaceId": "string",
    "namespaceName": "string",
    "status": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[namespace](#)

The deleted namespace object.

Type: [Namespace](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteResourcePolicy

Deletes the specified resource policy.

Request Syntax

```
{  
  "resourceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

resourceArn

The Amazon Resource Name (ARN) of the policy to delete.

Type: String

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteScheduledAction

Deletes a scheduled action.

Request Syntax

```
{  
  "scheduledActionName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

scheduledActionName

The name of the scheduled action to delete.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 60.

Pattern: [a-z0-9-]+

Required: Yes

Response Syntax

```
{  
  "scheduledAction": {  
    "endTime": number,  
    "namespaceName": "string",  
    "nextInvocations": [ number ],  
    "roleArn": "string",  
    "schedule": { ... },  
    "scheduledActionDescription": "string",  
    "scheduledActionName": "string",  
    "scheduledActionUuid": "string",
```

```
    "startTime": number,  
    "state": "string",  
    "targetAction": { ... }  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

scheduledAction

The deleted scheduled action object.

Type: [ScheduledActionResponse](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteSnapshot

Deletes a snapshot from Amazon Redshift Serverless.

Request Syntax

```
{
  "snapshotName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

snapshotName

The name of the snapshot to be deleted.

Type: String

Required: Yes

Response Syntax

```
{
  "snapshot": {
    "accountsWithProvisionedRestoreAccess": [ "string" ],
    "accountsWithRestoreAccess": [ "string" ],
    "actualIncrementalBackupSizeInMegaBytes": number,
    "adminPasswordSecretArn": "string",
    "adminPasswordSecretKmsKeyId": "string",
    "adminUsername": "string",
    "backupProgressInMegaBytes": number,
    "currentBackupRateInMegaBytesPerSecond": number,
    "elapsedTimeInSeconds": number,
    "estimatedSecondsToCompletion": number,
    "kmsKeyId": "string",
    "namespaceArn": "string",
    "namespaceName": "string",
  }
}
```

```
"ownerAccount": "string",
"snapshotArn": "string",
"snapshotCreateTime": "string",
"snapshotName": "string",
"snapshotRemainingDays": number,
"snapshotRetentionPeriod": number,
"snapshotRetentionStartTime": "string",
"status": "string",
"totalBackupSizeInMegaBytes": number
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

snapshot

The deleted snapshot object.

Type: [Snapshot](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteSnapshotCopyConfiguration

Deletes a snapshot copy configuration

Request Syntax

```
{  
  "snapshotCopyConfigurationId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[snapshotCopyConfigurationId](#)

The ID of the snapshot copy configuration to delete.

Type: String

Required: Yes

Response Syntax

```
{  
  "snapshotCopyConfiguration": {  
    "destinationKmsKeyId": "string",  
    "destinationRegion": "string",  
    "namespaceName": "string",  
    "snapshotCopyConfigurationArn": "string",  
    "snapshotCopyConfigurationId": "string",  
    "snapshotRetentionPeriod": number  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[snapshotCopyConfiguration](#)

The deleted snapshot copy configuration object.

Type: [SnapshotCopyConfiguration](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteUsageLimit

Deletes a usage limit from Amazon Redshift Serverless.

Request Syntax

```
{  
  "usageLimitId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

usageLimitId

The unique identifier of the usage limit to delete.

Type: String

Required: Yes

Response Syntax

```
{  
  "usageLimit": {  
    "amount": number,  
    "breachAction": "string",  
    "period": "string",  
    "resourceArn": "string",  
    "usageLimitArn": "string",  
    "usageLimitId": "string",  
    "usageType": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

usageLimit

The deleted usage limit object.

Type: [UsageLimit](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteWorkgroup

Deletes a workgroup.

Request Syntax

```
{  
  "workgroupName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

workgroupName

The name of the workgroup to be deleted.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: Yes

Response Syntax

```
{  
  "workgroup": {  
    "baseCapacity": number,  
    "configParameters": [  
      {  
        "parameterKey": "string",  
        "parameterValue": "string"  
      }  
    ],  
    "creationDate": "string",  
    "crossAccountVpcs": [ "string" ],  
    "customDomainCertificateArn": "string",
```

```

"customDomainCertificateExpiryTime": "string",
"customDomainName": "string",
"endpoint": {
  "address": "string",
  "port": number,
  "vpcEndpoints": [
    {
      "networkInterfaces": [
        {
          "availabilityZone": "string",
          "ipv6Address": "string",
          "networkInterfaceId": "string",
          "privateIpAddress": "string",
          "subnetId": "string"
        }
      ],
      "vpcEndpointId": "string",
      "vpcId": "string"
    }
  ]
},
"enhancedVpcRouting": boolean,
"extraComputeForAutomaticOptimization": boolean,
"ipAddressType": "string",
"maxCapacity": number,
"namespaceName": "string",
"patchVersion": "string",
"pendingTrackName": "string",
"port": number,
"pricePerformanceTarget": {
  "level": number,
  "status": "string"
},
"publiclyAccessible": boolean,
"securityGroupIds": [ "string" ],
"status": "string",
"subnetIds": [ "string" ],
"trackName": "string",
"workgroupArn": "string",
"workgroupId": "string",
"workgroupName": "string",
"workgroupVersion": "string"
}

```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

workgroup

The deleted workgroup object.

Type: [Workgroup](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetCredentials

Returns a database user name and temporary password with temporary authorization to log in to Amazon Redshift Serverless.

By default, the temporary credentials expire in 900 seconds. You can optionally specify a duration between 900 seconds (15 minutes) and 3600 seconds (60 minutes).

The AWS Identity and Access Management (IAM) user or role that runs `GetCredentials` must have an IAM policy attached that allows access to all necessary actions and resources.

If the `DbName` parameter is specified, the IAM policy must allow access to the resource `dbname` for the specified database name.

Request Syntax

```
{
  "customDomainName": "string",
  "dbName": "string",
  "durationSeconds": number,
  "workgroupName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

customDomainName

The custom domain name associated with the workgroup. The custom domain name or the workgroup name must be included in the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 253.

Pattern: `((?!-)[A-Za-z0-9-]{0,62}[A-Za-z0-9])\. +((?!-)[A-Za-z0-9-]{1,62}[A-Za-z0-9])`

Required: No

dbName

The name of the database to get temporary authorization to log on to.

Constraints:

- Must be 1 to 64 alphanumeric characters or hyphens.
- Must contain only uppercase or lowercase letters, numbers, underscore, plus sign, period (dot), at symbol (@), or hyphen.
- The first character must be a letter.
- Must not contain a colon (:) or slash (/).
- Cannot be a reserved word. A list of reserved words can be found in [Reserved Words](#) in the Amazon Redshift Database Developer Guide

Type: String

Required: No

durationSeconds

The number of seconds until the returned temporary password expires. The minimum is 900 seconds, and the maximum is 3600 seconds.

Type: Integer

Required: No

workgroupName

The name of the workgroup associated with the database.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: No

Response Syntax

```
{
```

```
"dbPassword": "string",  
"dbUser": "string",  
"expiration": number,  
"nextRefreshTime": number  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

dbPassword

A temporary password that authorizes the user name returned by `DbUser` to log on to the database `DbName`.

Type: String

dbUser

A database user name that is authorized to log on to the database `DbName` using the password `DbPassword`. If the specified `DbUser` exists in the database, the new user name has the same database privileges as the the user named in `DbUser`. By default, the user is added to PUBLIC.

Type: String

expiration

The date and time the password in `DbPassword` expires.

Type: Timestamp

nextRefreshTime

The date and time of when the `DbUser` and `DbPassword` authorization refreshes.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetCustomDomainAssociation

Gets information about a specific custom domain association.

Request Syntax

```
{  
  "customDomainName": "string",  
  "workgroupName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

customDomainName

The custom domain name associated with the workgroup.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 253.

Pattern: (((?!-)[A-Za-z0-9-]{0,62}[A-Za-z0-9])\.)+((?!-)[A-Za-z0-9-]{1,62}[A-Za-z0-9])

Required: Yes

workgroupName

The name of the workgroup associated with the database.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: Yes

Response Syntax

```
{
  "customDomainCertificateArn": "string",
  "customDomainCertificateExpiryTime": "string",
  "customDomainName": "string",
  "workgroupName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

customDomainCertificateArn

The custom domain name's certificate Amazon resource name (ARN).

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `.*arn:[\w+=/, .@-]+:acm:[\w+=/, .@-]*:[0-9]+:[\w+=, .@-]+(\/[\w+=, .@-]+)*.*`

customDomainCertificateExpiryTime

The expiration time for the certificate.

Type: Timestamp

customDomainName

The custom domain name associated with the workgroup.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 253.

Pattern: `((?!-)[A-Za-z0-9-]{0,62}[A-Za-z0-9])\.((?!-)[A-Za-z0-9-]{1,62}[A-Za-z0-9])`

workgroupName

The name of the workgroup associated with the database.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetEndpointAccess

Returns information, such as the name, about a VPC endpoint.

Request Syntax

```
{  
  "endpointName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

endpointName

The name of the VPC endpoint to return information for.

Type: String

Required: Yes

Response Syntax

```
{  
  "endpoint": {  
    "address": "string",  
    "endpointArn": "string",  
    "endpointCreateTime": "string",  
    "endpointName": "string",  
    "endpointStatus": "string",  
    "port": number,  
    "subnetIds": [ "string" ],  
    "vpcEndpoint": {  
      "networkInterfaces": [  
        {  
          "availabilityZone": "string",  
          "ipv6Address": "string",
```

```
        "networkInterfaceId": "string",
        "privateIpAddress": "string",
        "subnetId": "string"
    }
],
"vpcEndpointId": "string",
"vpcId": "string"
},
"vpcSecurityGroups": [
    {
        "status": "string",
        "vpcSecurityGroupId": "string"
    }
],
"workgroupName": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

endpoint

The returned VPC endpoint.

Type: [EndpointAccess](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetIdentityCenterAuthToken

Returns an Identity Center authentication token for accessing Amazon Redshift Serverless workgroups.

The token provides secure access to data within the specified workgroups using Identity Center identity propagation. The token expires after a specified duration and must be refreshed for continued access.

The AWS Identity and Access Management (IAM) user or role that runs `GetIdentityCenterAuthToken` must have appropriate permissions to access the specified workgroups and Identity Center integration must be configured for the workgroups.

Request Syntax

```
{
  "workgroupNames": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

workgroupNames

A list of workgroup names for which to generate the Identity Center authentication token.

Constraints:

- Must contain between 1 and 20 workgroup names.
- Each workgroup name must be a valid Amazon Redshift Serverless workgroup identifier.
- All specified workgroups must have Identity Center integration enabled.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: `[a-z0-9-]+`

Required: Yes

Response Syntax

```
{  
  "expirationTime": "string",  
  "token": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

expirationTime

The date and time when the Identity Center authentication token expires.

After this time, a new token must be requested for continued access.

Type: Timestamp

token

The Identity Center authentication token that can be used to access data in the specified workgroups.

This token contains the Identity Center identity information and is encrypted for secure transmission.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

DryRunException

This exception is thrown when the request was successful, but dry run was enabled so no action was taken.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetNamespace

Returns information about a namespace in Amazon Redshift Serverless.

Request Syntax

```
{  
  "namespaceName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

namespaceName

The name of the namespace to retrieve information for.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: Yes

Response Syntax

```
{  
  "namespace": {  
    "adminPasswordSecretArn": "string",  
    "adminPasswordSecretKmsKeyId": "string",  
    "adminUsername": "string",  
    "catalogArn": "string",  
    "creationDate": "string",  
    "dbName": "string",  
    "defaultIamRoleArn": "string",  
    "iamRoles": [ "string" ],  
    "kmsKeyId": "string",  
  }  
}
```

```
"lakehouseRegistrationStatus": "string",
"logExports": [ "string " ],
"namespaceArn": "string",
"namespaceId": "string",
"namespaceName": "string",
"status": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[namespace](#)

The returned namespace object.

Type: [Namespace](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetRecoveryPoint

Returns information about a recovery point.

Request Syntax

```
{  
  "recoveryPointId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[recoveryPointId](#)

The unique identifier of the recovery point to return information for.

Type: String

Required: Yes

Response Syntax

```
{  
  "recoveryPoint": {  
    "namespaceArn": "string",  
    "namespaceName": "string",  
    "recoveryPointCreateTime": "string",  
    "recoveryPointId": "string",  
    "totalSizeInMegaBytes": number,  
    "workgroupName": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

recoveryPoint

The returned recovery point object.

Type: [RecoveryPoint](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetReservation

Gets an Amazon Redshift Serverless reservation. A reservation gives you the option to commit to a specified number of Redshift Processing Units (RPUs) for a year at a discount from Serverless on-demand (OD) rates.

Request Syntax

```
{  
  "reservationId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

reservationId

The ID of the reservation to retrieve.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

Response Syntax

```
{  
  "reservation": {  
    "capacity": number,  
    "endDate": "string",  
    "offering": {  
      "currencyCode": "string",  
      "duration": number,  
      "hourlyCharge": number,  
      "offeringId": "string",  
      "offeringType": "string",
```

```
    "upfrontCharge": number
  },
  "reservationArn": "string",
  "reservationId": "string",
  "startDate": "string",
  "status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

reservation

The returned reservation object.

Type: [Reservation](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetReservationOffering

Returns the reservation offering. The offering determines the payment schedule for the reservation.

Request Syntax

```
{  
  "offeringId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

offeringId

The identifier for the offering..

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

Response Syntax

```
{  
  "reservationOffering": {  
    "currencyCode": "string",  
    "duration": number,  
    "hourlyCharge": number,  
    "offeringId": "string",  
    "offeringType": "string",  
    "upfrontCharge": number  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

reservationOffering

The returned reservation offering. The offering determines the payment schedule for the reservation.

Type: [ReservationOffering](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetResourcePolicy

Returns a resource policy.

Request Syntax

```
{  
  "resourceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

resourceArn

The Amazon Resource Name (ARN) of the resource to return.

Type: String

Required: Yes

Response Syntax

```
{  
  "resourcePolicy": {  
    "policy": "string",  
    "resourceArn": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[resourcePolicy](#)

The returned resource policy.

Type: [ResourcePolicy](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetScheduledAction

Returns information about a scheduled action.

Request Syntax

```
{  
  "scheduledActionName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

scheduledActionName

The name of the scheduled action.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 60.

Pattern: [a-z0-9-]+

Required: Yes

Response Syntax

```
{  
  "scheduledAction": {  
    "endTime": number,  
    "namespaceName": "string",  
    "nextInvocations": [ number ],  
    "roleArn": "string",  
    "schedule": { ... },  
    "scheduledActionDescription": "string",  
    "scheduledActionName": "string",  
    "scheduledActionUuid": "string",
```

```
    "startTime": number,  
    "state": "string",  
    "targetAction": { ... }  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

scheduledAction

The returned scheduled action object.

Type: [ScheduledActionResponse](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetSnapshot

Returns information about a specific snapshot.

Request Syntax

```
{  
  "ownerAccount": "string",  
  "snapshotArn": "string",  
  "snapshotName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ownerAccount](#)

The owner AWS account of a snapshot shared with another user.

Type: String

Required: No

[snapshotArn](#)

The Amazon Resource Name (ARN) of the snapshot to return.

Type: String

Required: No

[snapshotName](#)

The name of the snapshot to return.

Type: String

Required: No

Response Syntax

```
{
  "snapshot": {
    "accountsWithProvisionedRestoreAccess": [ "string" ],
    "accountsWithRestoreAccess": [ "string" ],
    "actualIncrementalBackupSizeInMegaBytes": number,
    "adminPasswordSecretArn": "string",
    "adminPasswordSecretKmsKeyId": "string",
    "adminUsername": "string",
    "backupProgressInMegaBytes": number,
    "currentBackupRateInMegaBytesPerSecond": number,
    "elapsedTimeInSeconds": number,
    "estimatedSecondsToCompletion": number,
    "kmsKeyId": "string",
    "namespaceArn": "string",
    "namespaceName": "string",
    "ownerAccount": "string",
    "snapshotArn": "string",
    "snapshotCreateTime": "string",
    "snapshotName": "string",
    "snapshotRemainingDays": number,
    "snapshotRetentionPeriod": number,
    "snapshotRetentionStartTime": "string",
    "status": "string",
    "totalBackupSizeInMegaBytes": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

snapshot

The returned snapshot object.

Type: [Snapshot](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

GetTableRestoreStatus

Returns information about a TableRestoreStatus object.

Request Syntax

```
{
  "tableRestoreRequestId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[tableRestoreRequestId](#)

The ID of the RestoreTableFromSnapshot request to return status for.

Type: String

Required: Yes

Response Syntax

```
{
  "tableRestoreStatus": {
    "message": "string",
    "namespaceName": "string",
    "newTableName": "string",
    "progressInMegaBytes": number,
    "recoveryPointId": "string",
    "requestTime": number,
    "snapshotName": "string",
    "sourceDatabaseName": "string",
    "sourceSchemaName": "string",
    "sourceTableName": "string",
    "status": "string",
    "tableRestoreRequestId": "string",
    "targetDatabaseName": "string",
  }
}
```

```
"targetSchemaName": "string",  
"totalDataInMegaBytes": number,  
"workgroupName": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tableRestoreStatus

The returned `TableRestoreStatus` object that contains information about the status of your `RestoreTableFromSnapshot` request.

Type: [TableRestoreStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTrack

Get the Redshift Serverless version for a specified track.

Request Syntax

```
{
  "trackName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

trackName

The name of the track of which its version is fetched.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_]+

Required: Yes

Response Syntax

```
{
  "track": {
    "trackName": "string",
    "updateTargets": [
      {
        "trackName": "string",
        "workgroupVersion": "string"
      }
    ],
    "workgroupVersion": "string"
  }
}
```

```
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

track

The version of the specified track.

Type: [ServerlessTrack](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

DryRunException

This exception is thrown when the request was successful, but dry run was enabled so no action was taken.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetTrack.

Sample Request

```
aws redshift-serverless get-track
--track-name current
--region us-east-1
```

Sample Response

```
{
  "track": {
    "trackName": "current",
    "workgroupVersion": "1.0.107360",
    "updateTargets": [
      {
        "trackName": "trailing",
```

```
    "workgroupVersion": "1.0.106452"  
  }  
]  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetUsageLimit

Returns information about a usage limit.

Request Syntax

```
{  
  "usageLimitId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

usageLimitId

The unique identifier of the usage limit to return information for.

Type: String

Required: Yes

Response Syntax

```
{  
  "usageLimit": {  
    "amount": number,  
    "breachAction": "string",  
    "period": "string",  
    "resourceArn": "string",  
    "usageLimitArn": "string",  
    "usageLimitId": "string",  
    "usageType": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

usageLimit

The returned usage limit object.

Type: [UsageLimit](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetWorkgroup

Returns information about a specific workgroup.

Request Syntax

```
{  
  "workgroupName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

workgroupName

The name of the workgroup to return information for.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: Yes

Response Syntax

```
{  
  "workgroup": {  
    "baseCapacity": number,  
    "configParameters": [  
      {  
        "parameterKey": "string",  
        "parameterValue": "string"  
      }  
    ],  
    "creationDate": "string",  
    "crossAccountVpcs": [ "string" ],  
    "customDomainCertificateArn": "string",
```

```
"customDomainCertificateExpiryTime": "string",
"customDomainName": "string",
"endpoint": {
  "address": "string",
  "port": number,
  "vpcEndpoints": [
    {
      "networkInterfaces": [
        {
          "availabilityZone": "string",
          "ipv6Address": "string",
          "networkInterfaceId": "string",
          "privateIpAddress": "string",
          "subnetId": "string"
        }
      ],
      "vpcEndpointId": "string",
      "vpcId": "string"
    }
  ]
},
"enhancedVpcRouting": boolean,
"extraComputeForAutomaticOptimization": boolean,
"ipAddressType": "string",
"maxCapacity": number,
"namespaceName": "string",
"patchVersion": "string",
"pendingTrackName": "string",
"port": number,
"pricePerformanceTarget": {
  "level": number,
  "status": "string"
},
"publiclyAccessible": boolean,
"securityGroupIds": [ "string" ],
"status": "string",
"subnetIds": [ "string" ],
"trackName": "string",
"workgroupArn": "string",
"workgroupId": "string",
"workgroupName": "string",
"workgroupVersion": "string"
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

workgroup

The returned workgroup object.

Type: [Workgroup](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `GetWorkgroup`.

Sample Request

```
aws redshift-serverless get-workgroup
--workgroup-name test-wg
--region us-east-1
```

Sample Response

```
{
  "workgroup": {
    "workgroupId": "875083e4-50b5-4ad7-bd8b-b01beb74d912",
    "workgroupArn": "arn:aws:redshift-serverless:us-
east-1:012345678901:workgroup/875083e4-50b5-4ad7-bd8b-b01beb74d912",
    "workgroupName": "test-wg",
    "namespaceName": "test-ns",
    "baseCapacity": 32,
    "enhancedVpcRouting": false,
    ...
    "ipAddressType": "ipv4",
    "trackName": "current",
    "pendingTrackName": "trailing"
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListCustomDomainAssociations

Lists custom domain associations for Amazon Redshift Serverless.

Request Syntax

```
{  
  "customDomainCertificateArn": "string",  
  "customDomainName": "string",  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

customDomainCertificateArn

The custom domain name's certificate Amazon resource name (ARN).

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `.*arn:[\w+=/, .@-]+:acm:[\w+=/, .@-]*:[0-9]+:[\w+=, .@-]+(\/[\w+=, .@-]+)*.*`

Required: No

customDomainName

The custom domain name associated with the workgroup.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 253.

Pattern: `((?!-)[A-Za-z0-9-]{0,62}[A-Za-z0-9])\.((?!-)[A-Za-z0-9-]{1,62}[A-Za-z0-9])`

Required: No

maxResults

An optional parameter that specifies the maximum number of results to return. You can use `nextToken` to display the next page of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

When `nextToken` is returned, there are more results available. The value of `nextToken` is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

Required: No

Response Syntax

```
{
  "associations": [
    {
      "customDomainCertificateArn": "string",
      "customDomainCertificateExpiryTime": "string",
      "customDomainName": "string",
      "workgroupName": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

associations

A list of Association objects.

Type: Array of [Association](#) objects

nextToken

When nextToken is returned, there are more results available. The value of nextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidPaginationException

The provided pagination token is invalid.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListEndpointAccess

Returns an array of EndpointAccess objects and relevant information.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string",  
  "ownerAccount": "string",  
  "vpcId": "string",  
  "workgroupName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[maxResults](#)

An optional parameter that specifies the maximum number of results to return. You can use nextToken to display the next page of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

[nextToken](#)

If your initial ListEndpointAccess operation returns a nextToken, you can include the returned nextToken in following ListEndpointAccess operations, which returns results in the next page.

Type: String

Required: No

[ownerAccount](#)

The owner AWS account for the Amazon Redshift Serverless workgroup.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 12.

Pattern: `.*(\d{12}).*`

Required: No

vpclId

The unique identifier of the virtual private cloud with access to Amazon Redshift Serverless.

Type: String

Required: No

workgroupName

The name of the workgroup associated with the VPC endpoint to return.

Type: String

Required: No

Response Syntax

```
{
  "endpoints": [
    {
      "address": "string",
      "endpointArn": "string",
      "endpointCreateTime": "string",
      "endpointName": "string",
      "endpointStatus": "string",
      "port": number,
      "subnetIds": [ "string" ],
      "vpcEndpoint": {
        "networkInterfaces": [
          {
            "availabilityZone": "string",
            "ipv6Address": "string",
            "networkInterfaceId": "string",
            "privateIpAddress": "string",
            "subnetId": "string"
          }
        ]
      }
    }
  ]
}
```

```
    ],
    "vpcEndpointId": "string",
    "vpcId": "string"
  },
  "vpcSecurityGroups": [
    {
      "status": "string",
      "vpcSecurityGroupId": "string"
    }
  ],
  "workgroupName": "string"
}
],
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

endpoints

The returned VPC endpoints.

Type: Array of [EndpointAccess](#) objects

nextToken

When nextToken is returned, there are more results available. The value of nextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListManagedWorkgroups

Returns information about a list of specified managed workgroups in your account.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string",  
  "sourceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[maxResults](#)

An optional parameter that specifies the maximum number of results to return. You can use `nextToken` to display the next page of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

[nextToken](#)

If your initial `ListManagedWorkgroups` operation returns a `nextToken`, you can include the returned `nextToken` in following `ListManagedWorkgroups` operations, which returns results in the next page.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

Required: No

[sourceArn](#)

The Amazon Resource Name (ARN) for the managed workgroup in the AWS Glue Data Catalog.

Type: String

Pattern: `arn:aws[a-z-]*:glue:[a-z0-9-]+\d+:(database|catalog)[a-z0-9-:]*(?:/[A-Za-z0-9-_{1,255}]*)*`

Required: No

Response Syntax

```
{
  "managedWorkgroups": [
    {
      "creationDate": "string",
      "managedWorkgroupId": "string",
      "managedWorkgroupName": "string",
      "sourceArn": "string",
      "status": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

managedWorkgroups

The returned array of managed workgroups.

Type: Array of [ManagedWorkgroupListItem](#) objects

nextToken

If nextToken is returned, there are more results available. The value of nextToken is a unique pagination token for each page. To retrieve the next page, make the call again using the returned token.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListNamespaces

Returns information about a list of specified namespaces.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

An optional parameter that specifies the maximum number of results to return. You can use `nextToken` to display the next page of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

If your initial `ListNamespaces` operation returns a `nextToken`, you can include the returned `nextToken` in following `ListNamespaces` operations, which returns results in the next page.

Type: String

Required: No

Response Syntax

```
{  
  "namespaces": [  
    {
```

```
    "adminPasswordSecretArn": "string",
    "adminPasswordSecretKmsKeyId": "string",
    "adminUsername": "string",
    "catalogArn": "string",
    "creationDate": "string",
    "dbName": "string",
    "defaultIamRoleArn": "string",
    "iamRoles": [ "string" ],
    "kmsKeyId": "string",
    "lakehouseRegistrationStatus": "string",
    "logExports": [ "string" ],
    "namespaceArn": "string",
    "namespaceId": "string",
    "namespaceName": "string",
    "status": "string"
  }
],
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

namespaces

The list of returned namespaces.

Type: Array of [Namespace](#) objects

nextToken

When nextToken is returned, there are more results available. The value of nextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListRecoveryPoints

Returns an array of recovery points.

Request Syntax

```
{
  "endTime": number,
  "maxResults": number,
  "namespaceArn": "string",
  "namespaceName": "string",
  "nextToken": "string",
  "startTime": number
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

endTime

The time when creation of the recovery point finished.

Type: Timestamp

Required: No

maxResults

An optional parameter that specifies the maximum number of results to return. You can use `nextToken` to display the next page of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

namespaceArn

The Amazon Resource Name (ARN) of the namespace from which to list recovery points.

Type: String

Required: No

namespaceName

The name of the namespace to list recovery points for.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: No

nextToken

If your initial `ListRecoveryPoints` operation returns a `nextToken`, you can include the returned `nextToken` in following `ListRecoveryPoints` operations, which returns results in the next page.

Type: String

Required: No

startTime

The time when the recovery point's creation was initiated.

Type: Timestamp

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "recoveryPoints": [
    {
      "namespaceArn": "string",
      "namespaceName": "string",
      "recoveryPointCreateTime": "string",
```

```
    "recoveryPointId": "string",
    "totalSizeInMegabytes": number,
    "workgroupName": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

If nextToken is returned, there are more results available. The value of nextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

recoveryPoints

The returned recovery point objects.

Type: Array of [RecoveryPoint](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListReservationOfferings

Returns the current reservation offerings in your account.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

Required: No

Response Syntax

```
{
```

```
"nextToken": "string",
"reservationOfferingsList": [
  {
    "currencyCode": "string",
    "duration": number,
    "hourlyCharge": number,
    "offeringId": "string",
    "offeringType": "string",
    "upfrontCharge": number
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The token to use when requesting the next set of items.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

reservationOfferingsList

The returned list of reservation offerings.

Type: Array of [ReservationOffering](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListReservations

Returns a list of Reservation objects.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

Required: No

Response Syntax

```
{  
  "nextToken": "string",  
}
```

```
"reservationsList": [  
  {  
    "capacity": number,  
    "endDate": "string",  
    "offering": {  
      "currencyCode": "string",  
      "duration": number,  
      "hourlyCharge": number,  
      "offeringId": "string",  
      "offeringType": "string",  
      "upfrontCharge": number  
    },  
    "reservationArn": "string",  
    "reservationId": "string",  
    "startDate": "string",  
    "status": "string"  
  }  
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The token to use when requesting the next set of items.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

reservationsList

The serverless reservations returned by the request.

Type: Array of [Reservation](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListScheduledActions

Returns a list of scheduled actions. You can use the flags to filter the list of returned scheduled actions.

Request Syntax

```
{  
  "maxResults": number,  
  "namespaceName": "string",  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

An optional parameter that specifies the maximum number of results to return. Use nextToken to display the next page of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

namespaceName

The name of namespace associated with the scheduled action to retrieve.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: No

nextToken

If `nextToken` is returned, there are more results available. The value of `nextToken` is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "scheduledActions": [
    {
      "namespaceName": "string",
      "scheduledActionName": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

If `nextToken` is returned, there are more results available. The value of `nextToken` is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

scheduledActions

All of the returned scheduled action association objects.

Type: Array of [ScheduledActionAssociation](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidPaginationException

The provided pagination token is invalid.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListSnapshotCopyConfigurations

Returns a list of snapshot copy configurations.

Request Syntax

```
{  
  "maxResults": number,  
  "namespaceName": "string",  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

An optional parameter that specifies the maximum number of results to return. You can use `nextToken` to display the next page of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

namespaceName

The namespace from which to list all snapshot copy configurations.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: `[a-z0-9-]+`

Required: No

nextToken

If `nextToken` is returned, there are more results available. The value of `nextToken` is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "snapshotCopyConfigurations": [
    {
      "destinationKmsKeyId": "string",
      "destinationRegion": "string",
      "namespaceName": "string",
      "snapshotCopyConfigurationArn": "string",
      "snapshotCopyConfigurationId": "string",
      "snapshotRetentionPeriod": number
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

If `nextToken` is returned, there are more results available. The value of `nextToken` is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

snapshotCopyConfigurations

All of the returned snapshot copy configurations.

Type: Array of [SnapshotCopyConfiguration](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidPaginationException

The provided pagination token is invalid.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListSnapshots

Returns a list of snapshots.

Request Syntax

```
{  
  "endTime": number,  
  "maxResults": number,  
  "namespaceArn": "string",  
  "namespaceName": "string",  
  "nextToken": "string",  
  "ownerAccount": "string",  
  "startTime": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

endTime

The timestamp showing when the snapshot creation finished.

Type: Timestamp

Required: No

maxResults

An optional parameter that specifies the maximum number of results to return. You can use `nextToken` to display the next page of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

namespaceArn

The Amazon Resource Name (ARN) of the namespace from which to list all snapshots.

Type: String

Required: No

namespaceName

The namespace from which to list all snapshots.

Type: String

Required: No

nextToken

If `nextToken` is returned, there are more results available. The value of `nextToken` is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Required: No

ownerAccount

The owner AWS account of the snapshot.

Type: String

Required: No

startTime

The time when the creation of the snapshot was initiated.

Type: Timestamp

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "snapshots": [
    {
      "accountsWithProvisionedRestoreAccess": [ "string" ],
```

```
"accountsWithRestoreAccess": [ "string" ],
"actualIncrementalBackupSizeInMegaBytes": number,
"adminPasswordSecretArn": "string",
"adminPasswordSecretKmsKeyId": "string",
"adminUsername": "string",
"backupProgressInMegaBytes": number,
"currentBackupRateInMegaBytesPerSecond": number,
"elapsedTimeInSeconds": number,
"estimatedSecondsToCompletion": number,
"kmsKeyId": "string",
"namespaceArn": "string",
"namespaceName": "string",
"ownerAccount": "string",
"snapshotArn": "string",
"snapshotCreateTime": "string",
"snapshotName": "string",
"snapshotRemainingDays": number,
"snapshotRetentionPeriod": number,
"snapshotRetentionStartTime": "string",
"status": "string",
"totalBackupSizeInMegaBytes": number
}
]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

If `nextToken` is returned, there are more results available. The value of `nextToken` is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

snapshots

All of the returned snapshot objects.

Type: Array of [Snapshot](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

ListTableRestoreStatus

Returns information about an array of TableRestoreStatus objects.

Request Syntax

```
{  
  "maxResults": number,  
  "namespaceName": "string",  
  "nextToken": "string",  
  "workgroupName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

An optional parameter that specifies the maximum number of results to return. You can use `nextToken` to display the next page of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

namespaceName

The namespace from which to list all of the statuses of RestoreTableFromSnapshot operations .

Type: String

Required: No

nextToken

If your initial ListTableRestoreStatus operation returns a `nextToken`, you can include the returned `nextToken` in following ListTableRestoreStatus operations. This will return results on the next page.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

Required: No

workgroupName

The workgroup from which to list all of the statuses of RestoreTableFromSnapshot operations.

Type: String

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "tableRestoreStatuses": [
    {
      "message": "string",
      "namespaceName": "string",
      "newTableName": "string",
      "progressInMegaBytes": number,
      "recoveryPointId": "string",
      "requestTime": number,
      "snapshotName": "string",
      "sourceDatabaseName": "string",
      "sourceSchemaName": "string",
      "sourceTableName": "string",
      "status": "string",
      "tableRestoreRequestId": "string",
      "targetDatabaseName": "string",
      "targetSchemaName": "string",
      "totalDataInMegaBytes": number,
      "workgroupName": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

If your initial `ListTableRestoreStatus` operation returns a `nextToken`, you can include the returned `nextToken` in following `ListTableRestoreStatus` operations. This will return results on the next page.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

tableRestoreStatuses

The array of returned `TableRestoreStatus` objects.

Type: Array of [TableRestoreStatus](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidPaginationException

The provided pagination token is invalid.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Lists the tags assigned to a resource.

Request Syntax

```
{  
  "resourceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

resourceArn

The Amazon Resource Name (ARN) of the resource to list tags for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: Yes

Response Syntax

```
{  
  "tags": [  
    {  
      "key": "string",  
      "value": "string"  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tags

A map of the key-value pairs assigned to the resource.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTracks

List the Amazon Redshift Serverless versions.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[maxResults](#)

The maximum number of response records to return in each call. If the number of remaining response records exceeds the specified MaxRecords value, a value is returned in a marker field of the response. You can retrieve the next set of records by retrying the command with the returned marker value.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

[nextToken](#)

If your initial ListTracksRequest operation returns a nextToken, you can include the returned nextToken in following ListTracksRequest operations, which returns results in the next page.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "tracks": [
    {
      "trackName": "string",
      "updateTargets": [
        {
          "trackName": "string",
          "workgroupVersion": "string"
        }
      ],
      "workgroupVersion": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

When nextToken is returned, there are more results available. The value of nextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

tracks

The returned tracks.

Type: Array of [ServerlessTrack](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidPaginationException

The provided pagination token is invalid.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListTracks.

Sample Request

```
aws redshift-serverless list-tracks
--region us-east-1
```

Sample Response

```
{
```

```
"tracks": [
  {
    "trackName": "current",
    "workgroupVersion": "1.0.106980",
    "updateTargets": [
      {
        "trackName": "trailing",
        "workgroupVersion": "1.0.106452"
      }
    ]
  },
  {
    "trackName": "trailing",
    "workgroupVersion": "1.0.106452",
    "updateTargets": [
      {
        "trackName": "current",
        "workgroupVersion": "1.0.106980"
      }
    ]
  }
]
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListUsageLimits

Lists all usage limits within Amazon Redshift Serverless.

Request Syntax

```
{
  "maxResults": number,
  "nextToken": "string",
  "resourceArn": "string",
  "usageType": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[maxResults](#)

An optional parameter that specifies the maximum number of results to return. You can use `nextToken` to get the next page of results. The default is 100.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

[nextToken](#)

If your initial `ListUsageLimits` operation returns a `nextToken`, you can include the returned `nextToken` in following `ListUsageLimits` operations, which returns results in the next page.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

Required: No

resourceArn

The Amazon Resource Name (ARN) associated with the resource whose usage limits you want to list.

Type: String

Required: No

usageType

The Amazon Redshift Serverless feature whose limits you want to see.

Type: String

Valid Values: `serverless-compute` | `cross-region-datasharing`

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "usageLimits": [
    {
      "amount": number,
      "breachAction": "string",
      "period": "string",
      "resourceArn": "string",
      "usageLimitArn": "string",
      "usageLimitId": "string",
      "usageType": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

When `nextToken` is returned, there are more results available. The value of `nextToken` is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

usageLimits

An array of returned usage limit objects.

Type: Array of [UsageLimit](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidPaginationException

The provided pagination token is invalid.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListWorkgroups

Returns information about a list of specified workgroups.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string",  
  "ownerAccount": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[maxResults](#)

An optional parameter that specifies the maximum number of results to return. You can use `nextToken` to display the next page of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

[nextToken](#)

If your initial `ListWorkgroups` operation returns a `nextToken`, you can include the returned `nextToken` in following `ListNamespaces` operations, which returns results in the next page.

Type: String

Required: No

[ownerAccount](#)

The owner AWS account for the Amazon Redshift Serverless workgroup.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 12.

Pattern: `.*(\d{12}).*`

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "workgroups": [
    {
      "baseCapacity": number,
      "configParameters": [
        {
          "parameterKey": "string",
          "parameterValue": "string"
        }
      ],
      "creationDate": "string",
      "crossAccountVpcs": [ "string" ],
      "customDomainCertificateArn": "string",
      "customDomainCertificateExpiryTime": "string",
      "customDomainName": "string",
      "endpoint": {
        "address": "string",
        "port": number,
        "vpcEndpoints": [
          {
            "networkInterfaces": [
              {
                "availabilityZone": "string",
                "ipv6Address": "string",
                "networkInterfaceId": "string",
                "privateIpAddress": "string",
                "subnetId": "string"
              }
            ],
            "vpcEndpointId": "string",
            "vpcId": "string"
          }
        ]
      }
    }
  ],
}
```

```
"enhancedVpcRouting": boolean,
"extraComputeForAutomaticOptimization": boolean,
"ipAddressType": "string",
"maxCapacity": number,
"namespaceName": "string",
"patchVersion": "string",
"pendingTrackName": "string",
"port": number,
"pricePerformanceTarget": {
  "level": number,
  "status": "string"
},
"publiclyAccessible": boolean,
"securityGroupIds": [ "string " ],
"status": "string",
"subnetIds": [ "string " ],
"trackName": "string",
"workgroupArn": "string",
"workgroupId": "string",
"workgroupName": "string",
"workgroupVersion": "string"
}
]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

If nextToken is returned, there are more results available. The value of nextToken is a unique pagination token for each page. To retrieve the next page, make the call again using the returned token.

Type: String

workgroups

The returned array of workgroups.

Type: Array of [Workgroup](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListWorkgroups.

Sample Request

```
aws redshift-serverless list-workgroups
--region us-east-1
```

Sample Response

```
{
  "workgroups": [
    {
      "workgroupId": "aff51189-e570-474d-9feb-ae83286e057c",
      "workgroupArn": "arn:aws:redshift-serverless:us-east-1:012345678901:workgroup/aff51189-e570-474d-9feb-ae83286e057c",
      "workgroupName": "test-track-1",
      "namespaceName": "test-track-ns",
      "baseCapacity": 32,
      "enhancedVpcRouting": false,
      "trackName": "current",
      "pendingTrackName": "trailing"
    }
  ]
}
```

```
},  
...  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutResourcePolicy

Creates or updates a resource policy. Currently, you can use policies to share snapshots across AWS accounts.

Request Syntax

```
{  
  "policy": "string",  
  "resourceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

policy

The policy to create or update. For example, the following policy grants a user authorization to restore a snapshot.

```
"{\\"Version\\": \\"2012-10-17\\", \\"Statement\\" : [{ \\"Sid  
\\": \\"AllowUserRestoreFromSnapshot\\", \\"Principal\\":  
{\\"AWS\\": [\\"739247239426\\"]}, \\"Action\\": [\\"redshift-  
serverless:RestoreFromSnapshot\\"], \\"Effect\\": \\"Allow\\" }]}"
```

Type: String

Required: Yes

resourceArn

The Amazon Resource Name (ARN) of the account to create or update a resource policy for.

Type: String

Required: Yes

Response Syntax

```
{
  "resourcePolicy": {
    "policy": "string",
    "resourceArn": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

resourcePolicy

The policy that was created or updated.

Type: [ResourcePolicy](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ServiceQuotaExceededException

The service limit was exceeded.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RestoreFromRecoveryPoint

Restore the data from a recovery point.

Request Syntax

```
{  
  "namespaceName": "string",  
  "recoveryPointId": "string",  
  "workgroupName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

namespaceName

The name of the namespace to restore data into.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: Yes

recoveryPointId

The unique identifier of the recovery point to restore from.

Type: String

Required: Yes

workgroupName

The name of the workgroup used to restore data.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: Yes

Response Syntax

```
{
  "namespace": {
    "adminPasswordSecretArn": "string",
    "adminPasswordSecretKmsKeyId": "string",
    "adminUsername": "string",
    "catalogArn": "string",
    "creationDate": "string",
    "dbName": "string",
    "defaultIamRoleArn": "string",
    "iamRoles": [ "string" ],
    "kmsKeyId": "string",
    "lakehouseRegistrationStatus": "string",
    "logExports": [ "string" ],
    "namespaceArn": "string",
    "namespaceId": "string",
    "namespaceName": "string",
    "status": "string"
  },
  "recoveryPointId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

namespace

The namespace that data was restored into.

Type: [Namespace](#) object

recoveryPointId

The unique identifier of the recovery point used for the restore.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RestoreFromSnapshot

Restores a namespace from a snapshot.

Request Syntax

```
{
  "adminPasswordSecretKmsKeyId": "string",
  "manageAdminPassword": boolean,
  "namespaceName": "string",
  "ownerAccount": "string",
  "snapshotArn": "string",
  "snapshotName": "string",
  "workgroupName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[adminPasswordSecretKmsKeyId](#)

The ID of the AWS Key Management Service (KMS) key used to encrypt and store the namespace's admin credentials secret.

Type: String

Required: No

[manageAdminPassword](#)

If `true`, Amazon Redshift uses AWS Secrets Manager to manage the restored snapshot's admin credentials. If `manageAdminPassword` is `false` or not set, Amazon Redshift uses the admin credentials that the namespace or cluster had at the time the snapshot was taken.

Type: Boolean

Required: No

[namespaceName](#)

The name of the namespace to restore the snapshot to.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: Yes

ownerAccount

The AWS account that owns the snapshot.

Type: String

Required: No

snapshotArn

The Amazon Resource Name (ARN) of the snapshot to restore from. Required if restoring from a provisioned cluster to Amazon Redshift Serverless. Must not be specified at the same time as snapshotName.

The format of the ARN is arn:aws:redshift:<region>:<account_id>:snapshot:<cluster_identifier>/<snapshot_identifier>.

Type: String

Required: No

snapshotName

The name of the snapshot to restore from. Must not be specified at the same time as snapshotArn.

Type: String

Required: No

workgroupName

The name of the workgroup used to restore the snapshot.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: Yes

Response Syntax

```
{
  "namespace": {
    "adminPasswordSecretArn": "string",
    "adminPasswordSecretKmsKeyId": "string",
    "adminUsername": "string",
    "catalogArn": "string",
    "creationDate": "string",
    "dbName": "string",
    "defaultIamRoleArn": "string",
    "iamRoles": [ "string" ],
    "kmsKeyId": "string",
    "lakehouseRegistrationStatus": "string",
    "logExports": [ "string" ],
    "namespaceArn": "string",
    "namespaceId": "string",
    "namespaceName": "string",
    "status": "string"
  },
  "ownerAccount": "string",
  "snapshotName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

namespace

A collection of database objects and users.

Type: [Namespace](#) object

ownerAccount

The owner AWS; account of the snapshot that was restored.

Type: String

snapshotName

The name of the snapshot used to restore the namespace.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ServiceQuotaExceededException

The service limit was exceeded.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RestoreTableFromRecoveryPoint

Restores a table from a recovery point to your Amazon Redshift Serverless instance. You can't use this operation to restore tables with interleaved sort keys.

Request Syntax

```
{
  "activateCaseSensitiveIdentifier": boolean,
  "namespaceName": "string",
  "newTableName": "string",
  "recoveryPointId": "string",
  "sourceDatabaseName": "string",
  "sourceSchemaName": "string",
  "sourceTableName": "string",
  "targetDatabaseName": "string",
  "targetSchemaName": "string",
  "workgroupName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[activateCaseSensitiveIdentifier](#)

Indicates whether name identifiers for database, schema, and table are case sensitive. If true, the names are case sensitive. If false, the names are not case sensitive. The default is false.

Type: Boolean

Required: No

[namespaceName](#)

Namespace of the recovery point to restore from.

Type: String

Required: Yes

newTableName

The name of the table to create from the restore operation.

Type: String

Required: Yes

recoveryPointId

The ID of the recovery point to restore the table from.

Type: String

Required: Yes

sourceDatabaseName

The name of the source database that contains the table being restored.

Type: String

Required: Yes

sourceSchemaName

The name of the source schema that contains the table being restored.

Type: String

Required: No

sourceTableName

The name of the source table being restored.

Type: String

Required: Yes

targetDatabaseName

The name of the database to restore the table to.

Type: String

Required: No

targetSchemaName

The name of the schema to restore the table to.

Type: String

Required: No

workgroupName

The workgroup to restore the table to.

Type: String

Required: Yes

Response Syntax

```
{
  "tableRestoreStatus": {
    "message": "string",
    "namespaceName": "string",
    "newTableName": "string",
    "progressInMegaBytes": number,
    "recoveryPointId": "string",
    "requestTime": number,
    "snapshotName": "string",
    "sourceDatabaseName": "string",
    "sourceSchemaName": "string",
    "sourceTableName": "string",
    "status": "string",
    "tableRestoreRequestId": "string",
    "targetDatabaseName": "string",
    "targetSchemaName": "string",
    "totalDataInMegaBytes": number,
    "workgroupName": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tableRestoreStatus

Contains information about a table restore request.

Type: [TableRestoreStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RestoreTableFromSnapshot

Restores a table from a snapshot to your Amazon Redshift Serverless instance. You can't use this operation to restore tables with [interleaved sort keys](#).

Request Syntax

```
{
  "activateCaseSensitiveIdentifier": boolean,
  "namespaceName": "string",
  "newTableName": "string",
  "snapshotName": "string",
  "sourceDatabaseName": "string",
  "sourceSchemaName": "string",
  "sourceTableName": "string",
  "targetDatabaseName": "string",
  "targetSchemaName": "string",
  "workgroupName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[activateCaseSensitiveIdentifier](#)

Indicates whether name identifiers for database, schema, and table are case sensitive. If true, the names are case sensitive. If false, the names are not case sensitive. The default is false.

Type: Boolean

Required: No

[namespaceName](#)

The namespace of the snapshot to restore from.

Type: String

Required: Yes

newTableName

The name of the table to create from the restore operation.

Type: String

Required: Yes

snapshotName

The name of the snapshot to restore the table from.

Type: String

Required: Yes

sourceDatabaseName

The name of the source database that contains the table being restored.

Type: String

Required: Yes

sourceSchemaName

The name of the source schema that contains the table being restored.

Type: String

Required: No

sourceTableName

The name of the source table being restored.

Type: String

Required: Yes

targetDatabaseName

The name of the database to restore the table to.

Type: String

Required: No

targetSchemaName

The name of the schema to restore the table to.

Type: String

Required: No

workgroupName

The workgroup to restore the table to.

Type: String

Required: Yes

Response Syntax

```
{
  "tableRestoreStatus": {
    "message": "string",
    "namespaceName": "string",
    "newTableName": "string",
    "progressInMegaBytes": number,
    "recoveryPointId": "string",
    "requestTime": number,
    "snapshotName": "string",
    "sourceDatabaseName": "string",
    "sourceSchemaName": "string",
    "sourceTableName": "string",
    "status": "string",
    "tableRestoreRequestId": "string",
    "targetDatabaseName": "string",
    "targetSchemaName": "string",
    "totalDataInMegaBytes": number,
    "workgroupName": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tableRestoreStatus

The TableRestoreStatus object that contains the status of the restore operation.

Type: [TableRestoreStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Assigns one or more tags to a resource.

Request Syntax

```
{
  "resourceArn": "string",
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

resourceArn

The Amazon Resource Name (ARN) of the resource to tag.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: Yes

tags

The map of the key-value pairs used to tag the resource.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

TooManyTagsException

The request exceeded the number of tags allowed for a resource.

resourceName

The name of the resource that exceeded the number of tags allowed for a resource.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Removes a tag or set of tags from a resource.

Request Syntax

```
{  
  "resourceArn": "string",  
  "tagKeys": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

resourceArn

The Amazon Resource Name (ARN) of the resource to remove tags from.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: Yes

tagKeys

The tag or set of tags to remove from the resource.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateCustomDomainAssociation

Updates an Amazon Redshift Serverless certificate associated with a custom domain.

Request Syntax

```
{
  "customDomainCertificateArn": "string",
  "customDomainName": "string",
  "workgroupName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

customDomainCertificateArn

The custom domain name's certificate Amazon resource name (ARN). This is optional.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `.*arn:[\w+=/, .@-]+:acm:[\w+=/, .@-]*:[0-9]+:[\w+=, .@-]+(/[\w+=, .@-]+)*.*`

Required: Yes

customDomainName

The custom domain name associated with the workgroup.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 253.

Pattern: `((?!-)[A-Za-z0-9-]{0,62}[A-Za-z0-9])\.((?!-)[A-Za-z0-9-]{1,62}[A-Za-z0-9])`

Required: Yes

workgroupName

The name of the workgroup associated with the database.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: Yes

Response Syntax

```
{
  "customDomainCertificateArn": "string",
  "customDomainCertificateExpiryTime": "string",
  "customDomainName": "string",
  "workgroupName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

customDomainCertificateArn

The custom domain name's certificate Amazon resource name (ARN).

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: .*arn:[\w+=/, .@-]+:acm:[\w+=/, .@-]*:[0-9]+:[\w+=, .@-]+(/[\w+=, .@-]+)*.*

customDomainCertificateExpiryTime

The expiration time for the certificate.

Type: Timestamp

customDomainName

The custom domain name associated with the workgroup.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 253.

Pattern: (((?!-)[A-Za-z0-9-]{0,62}[A-Za-z0-9])\.)+((?!-)[A-Za-z0-9-]{1,62}[A-Za-z0-9])

workgroupName

The name of the workgroup associated with the database.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateEndpointAccess

Updates an Amazon Redshift Serverless managed endpoint.

Request Syntax

```
{
  "endpointName": "string",
  "vpcSecurityGroupIds": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

endpointName

The name of the VPC endpoint to update.

Type: String

Required: Yes

vpcSecurityGroupIds

The list of VPC security groups associated with the endpoint after the endpoint is modified.

Type: Array of strings

Required: No

Response Syntax

```
{
  "endpoint": {
    "address": "string",
    "endpointArn": "string",
    "endpointCreateTime": "string",
  }
}
```

```
"endpointName": "string",
"endpointStatus": "string",
"port": number,
"subnetIds": [ "string" ],
"vpcEndpoint": {
  "networkInterfaces": [
    {
      "availabilityZone": "string",
      "ipv6Address": "string",
      "networkInterfaceId": "string",
      "privateIpAddress": "string",
      "subnetId": "string"
    }
  ],
  "vpcEndpointId": "string",
  "vpcId": "string"
},
"vpcSecurityGroups": [
  {
    "status": "string",
    "vpcSecurityGroupId": "string"
  }
],
"workgroupName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

endpoint

The updated VPC endpoint.

Type: [EndpointAccess](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateLakehouseConfiguration

Modifies the lakehouse configuration for a namespace. This operation allows you to manage Amazon Redshift federated permissions and AWS IAM Identity Center trusted identity propagation.

Request Syntax

```
{
  "catalogName": "string",
  "dryRun": boolean,
  "lakehouseIdcApplicationArn": "string",
  "lakehouseIdcRegistration": "string",
  "lakehouseRegistration": "string",
  "namespaceName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

catalogName

The name of the AWS Glue Data Catalog that will be associated with the namespace enabled with Amazon Redshift federated permissions.

Pattern: `^[a-z0-9_-]*[a-z]+[a-z0-9_-]*$`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-z0-9_-]*[a-z]+[a-z0-9_-]*`

Required: No

dryRun

A boolean value that, if `true`, validates the request without actually updating the lakehouse configuration. Use this to check for errors before making changes.

Type: Boolean

Required: No

lakehouseIdcApplicationArn

The Amazon Resource Name (ARN) of the IAM Identity Center application used for enabling AWS IAM Identity Center trusted identity propagation on a namespace enabled with Amazon Redshift federated permissions.

Type: String

Required: No

lakehouseIdcRegistration

Modifies the AWS IAM Identity Center trusted identity propagation on a namespace enabled with Amazon Redshift federated permissions. Valid values are Associate or Disassociate.

Type: String

Valid Values: Associate | Disassociate

Required: No

lakehouseRegistration

Specifies whether to register or deregister the namespace with Amazon Redshift federated permissions. Valid values are Register or Deregister.

Type: String

Valid Values: Register | Deregister

Required: No

namespaceName

The name of the namespace whose lakehouse configuration you want to modify.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: Yes

Response Syntax

```
{
  "catalogArn": "string",
  "lakehouseIdcApplicationArn": "string",
  "lakehouseRegistrationStatus": "string",
  "namespaceName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

catalogArn

The Amazon Resource Name (ARN) of the AWS Glue Data Catalog associated with the lakehouse configuration.

Type: String

lakehouseIdcApplicationArn

The Amazon Resource Name (ARN) of the IAM Identity Center application used for enabling AWS IAM Identity Center trusted identity propagation.

Type: String

lakehouseRegistrationStatus

The current status of the lakehouse registration. Indicates whether the namespace is successfully registered with Amazon Redshift federated permissions.

Type: String

namespaceName

The name of the namespace.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

DryRunException

This exception is thrown when the request was successful, but dry run was enabled so no action was taken.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateNamespace

Updates a namespace with the specified settings. Unless required, you can't update multiple parameters in one request. For example, you must specify both `adminUsername` and `adminUserPassword` to update either field, but you can't update both `kmsKeyId` and `logExports` in a single request.

Request Syntax

```
{
  "adminPasswordSecretKmsKeyId": "string",
  "adminUsername": "string",
  "adminUserPassword": "string",
  "defaultIamRoleArn": "string",
  "iamRoles": [ "string" ],
  "kmsKeyId": "string",
  "logExports": [ "string" ],
  "manageAdminPassword": boolean,
  "namespaceName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[adminPasswordSecretKmsKeyId](#)

The ID of the AWS Key Management Service (KMS) key used to encrypt and store the namespace's admin credentials secret. You can only use this parameter if `manageAdminPassword` is true.

Type: String

Required: No

[adminUsername](#)

The username of the administrator for the first database created in the namespace. This parameter must be updated together with `adminUserPassword`.

Type: String

Required: No

adminUserPassword

The password of the administrator for the first database created in the namespace. This parameter must be updated together with `adminUsername`.

You can't use `adminUserPassword` if `manageAdminPassword` is true.

Type: String

Required: No

defaultIamRoleArn

The Amazon Resource Name (ARN) of the IAM role to set as a default in the namespace. This parameter must be updated together with `iamRoles`.

Type: String

Required: No

iamRoles

A list of IAM roles to associate with the namespace. This parameter must be updated together with `defaultIamRoleArn`.

Type: Array of strings

Required: No

kmsKeyId

The ID of the AWS Key Management Service key used to encrypt your data.

Type: String

Required: No

logExports

The types of logs the namespace can export. The export types are `userlog`, `connectionlog`, and `useractivitylog`.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 16 items.

Valid Values: useractivitylog | userlog | connectionlog

Required: No

manageAdminPassword

If `true`, Amazon Redshift uses AWS Secrets Manager to manage the namespace's admin credentials. You can't use `adminUserPassword` if `manageAdminPassword` is `true`. If `manageAdminPassword` is `false` or not set, Amazon Redshift uses `adminUserPassword` for the admin user account's password.

Type: Boolean

Required: No

namespaceName

The name of the namespace to update. You can't update the name of a namespace once it is created.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: `[a-z0-9-]+`

Required: Yes

Response Syntax

```
{
  "namespace": {
    "adminPasswordSecretArn": "string",
    "adminPasswordSecretKmsKeyId": "string",
    "adminUsername": "string",
    "catalogArn": "string",
    "creationDate": "string",
    "dbName": "string",
    "defaultIamRoleArn": "string",
    "iamRoles": [ "string" ],
    "kmsKeyId": "string",
```

```
"lakehouseRegistrationStatus": "string",  
"logExports": [ "string" ],  
"namespaceArn": "string",  
"namespaceId": "string",  
"namespaceName": "string",  
"status": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[namespace](#)

A list of tag instances.

Type: [Namespace](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateScheduledAction

Updates a scheduled action.

Request Syntax

```
{
  "enabled": boolean,
  "endTime": number,
  "roleArn": "string",
  "schedule": { ... },
  "scheduledActionDescription": "string",
  "scheduledActionName": "string",
  "startTime": number,
  "targetAction": { ... }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

enabled

Specifies whether to enable the scheduled action.

Type: Boolean

Required: No

endTime

The end time in UTC of the scheduled action to update.

Type: Timestamp

Required: No

roleArn

The ARN of the IAM role to assume to run the scheduled action. This IAM role must have permission to run the Amazon Redshift Serverless API operation in the scheduled action.

This IAM role must allow the Amazon Redshift scheduler to schedule creating snapshots (Principal scheduler.redshift.amazonaws.com) to assume permissions on your behalf. For more information about the IAM role to use with the Amazon Redshift scheduler, see [Using Identity-Based Policies for Amazon Redshift](#) in the Amazon Redshift Management Guide

Type: String

Required: No

[schedule](#)

The schedule for a one-time (at timestamp format) or recurring (cron format) scheduled action. Schedule invocations must be separated by at least one hour. Times are in UTC.

- Format of at timestamp is yyyy-mm-ddThh:mm:ss. For example, 2016-03-04T17:27:00.
- Format of cron expression is (Minutes Hours Day-of-month Month Day-of-week Year). For example, "(0 10 ? * MON *)". For more information, see [Cron Expressions](#) in the *Amazon CloudWatch Events User Guide*.

Type: [Schedule](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

[scheduledActionDescription](#)

The description of the scheduled action to update to.

Type: String

Required: No

[scheduledActionName](#)

The name of the scheduled action to update to.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 60.

Pattern: [a-z0-9-]+

Required: Yes

startTime

The start time in UTC of the scheduled action to update to.

Type: Timestamp

Required: No

targetAction

A JSON format string of the Amazon Redshift Serverless API operation with input parameters. The following is an example of a target action.

```
"{"CreateSnapshot": {"NamespaceName": "sampleNamespace", "SnapshotName": "sampleSnapshot", "retentionPeriod": "1"}}"
```

Type: [TargetAction](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

Response Syntax

```
{
  "scheduledAction": {
    "endTime": number,
    "namespaceName": "string",
    "nextInvocations": [ number ],
    "roleArn": "string",
    "schedule": { ... },
    "scheduledActionDescription": "string",
    "scheduledActionName": "string",
    "scheduledActionUuid": "string",
    "startTime": number,
    "state": "string",
    "targetAction": { ... }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[scheduledAction](#)

The ScheduledAction object that was updated.

Type: [ScheduledActionResponse](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateSnapshot

Updates a snapshot.

Request Syntax

```
{  
  "retentionPeriod": number,  
  "snapshotName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

retentionPeriod

The new retention period of the snapshot.

Type: Integer

Required: No

snapshotName

The name of the snapshot.

Type: String

Required: Yes

Response Syntax

```
{  
  "snapshot": {  
    "accountsWithProvisionedRestoreAccess": [ "string" ],  
    "accountsWithRestoreAccess": [ "string" ],  
    "actualIncrementalBackupSizeInMegaBytes": number,  
    "adminPasswordSecretArn": "string",
```

```
"adminPasswordSecretKmsKeyId": "string",
"adminUsername": "string",
"backupProgressInMegaBytes": number,
"currentBackupRateInMegaBytesPerSecond": number,
"elapsedTimeInSeconds": number,
"estimatedSecondsToCompletion": number,
"kmsKeyId": "string",
"namespaceArn": "string",
"namespaceName": "string",
"ownerAccount": "string",
"snapshotArn": "string",
"snapshotCreateTime": "string",
"snapshotName": "string",
"snapshotRemainingDays": number,
"snapshotRetentionPeriod": number,
"snapshotRetentionStartTime": "string",
"status": "string",
"totalBackupSizeInMegaBytes": number
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

snapshot

The updated snapshot object.

Type: [Snapshot](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateSnapshotCopyConfiguration

Updates a snapshot copy configuration.

Request Syntax

```
{
  "snapshotCopyConfigurationId": "string",
  "snapshotRetentionPeriod": number
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

snapshotCopyConfigurationId

The ID of the snapshot copy configuration to update.

Type: String

Required: Yes

snapshotRetentionPeriod

The new retention period of how long to keep a snapshot in the destination AWS Region.

Type: Integer

Required: No

Response Syntax

```
{
  "snapshotCopyConfiguration": {
    "destinationKmsKeyId": "string",
    "destinationRegion": "string",
    "namespaceName": "string",
    "snapshotCopyConfigurationArn": "string",
    "snapshotCopyConfigurationId": "string",
  }
}
```

```
    "snapshotRetentionPeriod": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

snapshotCopyConfiguration

The updated snapshot copy configuration object.

Type: [SnapshotCopyConfiguration](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateUsageLimit

Update a usage limit in Amazon Redshift Serverless. You can't update the usage type or period of a usage limit.

Request Syntax

```
{  
  "amount": number,  
  "breachAction": "string",  
  "usageLimitId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

amount

The new limit amount. If time-based, this amount is in Redshift Processing Units (RPU) consumed per hour. If data-based, this amount is in terabytes (TB) of data transferred between Regions in cross-account sharing. The value must be a positive number.

Type: Long

Required: No

breachAction

The new action that Amazon Redshift Serverless takes when the limit is reached.

Type: String

Valid Values: log | emit-metric | deactivate

Required: No

usageLimitId

The identifier of the usage limit to update.

Type: String

Required: Yes

Response Syntax

```
{
  "usageLimit": {
    "amount": number,
    "breachAction": "string",
    "period": "string",
    "resourceArn": "string",
    "usageLimitArn": "string",
    "usageLimitId": "string",
    "usageType": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

usageLimit

The updated usage limit object.

Type: [UsageLimit](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateWorkgroup

Updates a workgroup with the specified configuration settings. You can't update multiple parameters in one request. For example, you can update `baseCapacity` or `port` in a single request, but you can't update both in the same request.

VPC Block Public Access (BPA) enables you to block resources in VPCs and subnets that you own in a Region from reaching or being reached from the internet through internet gateways and egress-only internet gateways. If a workgroup is in an account with VPC BPA turned on, the following capabilities are blocked:

- Creating a public access workgroup
- Modifying a private workgroup to public
- Adding a subnet with VPC BPA turned on to the workgroup when the workgroup is public

For more information about VPC BPA, see [Block public access to VPCs and subnets](#) in the *Amazon VPC User Guide*.

Request Syntax

```
{
  "baseCapacity": number,
  "configParameters": [
    {
      "parameterKey": "string",
      "parameterValue": "string"
    }
  ],
  "enhancedVpcRouting": boolean,
  "extraComputeForAutomaticOptimization": boolean,
  "ipAddressType": "string",
  "maxCapacity": number,
  "port": number,
  "pricePerformanceTarget": {
    "level": number,
    "status": "string"
  },
  "publiclyAccessible": boolean,
  "securityGroupIds": [ "string" ],
  "subnetIds": [ "string" ],
```

```
"trackName": "string",  
"workgroupName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

baseCapacity

The new base data warehouse capacity in Redshift Processing Units (RPUs).

Type: Integer

Required: No

configParameters

An array of parameters to set for advanced control over a database. The options are `auto_mv`, `datestyle`, `enable_case_sensitive_identifier`, `enable_user_activity_logging`, `query_group`, `search_path`, `require_ssl`, `use_fips_ssl`, and either `wlm_json_configuration` or query monitoring metrics that let you define performance boundaries. You can either specify individual query monitoring metrics (such as `max_scan_row_count`, `max_query_execution_time`) or use `wlm_json_configuration` to define query queues with rules, but not both. If you're using `wlm_json_configuration`, the maximum size of `parameterValue` is 8000 characters. For more information about query monitoring rules and available metrics, see [Query monitoring metrics for Amazon Redshift Serverless](#).

Type: Array of [ConfigParameter](#) objects

Required: No

enhancedVpcRouting

The value that specifies whether to turn on enhanced virtual private cloud (VPC) routing, which forces Amazon Redshift Serverless to route traffic through your VPC.

Type: Boolean

Required: No

[extraComputeForAutomaticOptimization](#)

If `true`, allocates additional compute resources for running automatic optimization operations.

Default: `false`

Type: Boolean

Required: No

[ipAddressType](#)

The IP address type that the workgroup supports. Possible values are `ipv4` and `dualstack`.

Type: String

Pattern: `(ipv4|dualstack)`

Required: No

[maxCapacity](#)

The maximum data-warehouse capacity Amazon Redshift Serverless uses to serve queries. The max capacity is specified in RPUs.

Type: Integer

Required: No

[port](#)

The custom port to use when connecting to a workgroup. Valid port ranges are 5431-5455 and 8191-8215. The default is 5439.

Type: Integer

Required: No

[pricePerformanceTarget](#)

An object that represents the price performance target settings for the workgroup.

Type: [PerformanceTarget](#) object

Required: No

publiclyAccessible

A value that specifies whether the workgroup can be accessible from a public network.

Type: Boolean

Required: No

securityGroupIds

An array of security group IDs to associate with the workgroup.

Type: Array of strings

Required: No

subnetIds

An array of VPC subnet IDs to associate with the workgroup.

Type: Array of strings

Required: No

trackName

An optional parameter for the name of the track for the workgroup. If you don't provide a track name, the workgroup is assigned to the `current` track.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9_]+`

Required: No

workgroupName

The name of the workgroup to update. You can't update the name of a workgroup once it is created.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: Yes

Response Syntax

```
{
  "workgroup": {
    "baseCapacity": number,
    "configParameters": [
      {
        "parameterKey": "string",
        "parameterValue": "string"
      }
    ],
    "creationDate": "string",
    "crossAccountVpcs": [ "string " ],
    "customDomainCertificateArn": "string",
    "customDomainCertificateExpiryTime": "string",
    "customDomainName": "string",
    "endpoint": {
      "address": "string",
      "port": number,
      "vpcEndpoints": [
        {
          "networkInterfaces": [
            {
              "availabilityZone": "string",
              "ipv6Address": "string",
              "networkInterfaceId": "string",
              "privateIpAddress": "string",
              "subnetId": "string"
            }
          ],
          "vpcEndpointId": "string",
          "vpcId": "string"
        }
      ]
    },
    "enhancedVpcRouting": boolean,
    "extraComputeForAutomaticOptimization": boolean,
```

```
"ipAddressType": "string",
"maxCapacity": number,
"namespaceName": "string",
"patchVersion": "string",
"pendingTrackName": "string",
"port": number,
"pricePerformanceTarget": {
  "level": number,
  "status": "string"
},
"publiclyAccessible": boolean,
"securityGroupIds": [ "string" ],
"status": "string",
"subnetIds": [ "string" ],
"trackName": "string",
"workgroupArn": "string",
"workgroupId": "string",
"workgroupName": "string",
"workgroupVersion": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

workgroup

The updated workgroup object.

Type: [Workgroup](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The submitted action has conflicts.

HTTP Status Code: 400

InsufficientCapacityException

There is an insufficient capacity to perform the action.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

Ipv6CidrBlockNotFoundException

There are no subnets in your VPC with associated IPv6 CIDR blocks. To use dual-stack mode, associate an IPv6 CIDR block with each subnet in your VPC.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

resourceName

The name of the resource that could not be found.

HTTP Status Code: 400

ValidationException

The input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of UpdateWorkgroup.

Sample Request

```
aws redshift-serverless update-workgroup
--workgroup-name test-wg
```

```
--track-name trailing
```

Sample Response

```
{
  "workgroup": {
    "workgroupId": "875083e4-50b5-4ad7-bd8b-b01beb74d912",
    "workgroupArn": "arn:aws:redshift-serverless:us-east-1:012345678901:workgroup/875083e4-50b5-4ad7-bd8b-b01beb74d912",
    "workgroupName": "test-wg",
    "namespaceName": "test-namespace",
    "baseCapacity": 32,
    "enhancedVpcRouting": false,
    ...
    "ipAddressType": "ipv4",
    "trackName": "current"
    "pendingTrackName": "trailing"
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The Amazon Redshift Serverless API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [Association](#)
- [ConfigParameter](#)
- [CreateSnapshotScheduleActionParameters](#)
- [Endpoint](#)
- [EndpointAccess](#)
- [ManagedWorkgroupListItem](#)
- [Namespace](#)
- [NetworkInterface](#)
- [PerformanceTarget](#)
- [RecoveryPoint](#)
- [Reservation](#)
- [ReservationOffering](#)
- [ResourcePolicy](#)
- [Schedule](#)
- [ScheduledActionAssociation](#)
- [ScheduledActionResponse](#)
- [ServerlessTrack](#)
- [Snapshot](#)
- [SnapshotCopyConfiguration](#)
- [TableRestoreStatus](#)

- [Tag](#)
- [TargetAction](#)
- [UpdateTarget](#)
- [UsageLimit](#)
- [VpcEndpoint](#)
- [VpcSecurityGroupMembership](#)
- [Workgroup](#)

Association

An object that represents the custom domain name association.

Contents

customDomainCertificateArn

The custom domain name's certificate Amazon resource name (ARN).

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `.*arn:[\w+=/, .@-]+:acm:[\w+=/, .@-]*:[0-9]+:[\w+=, .@-]+(/[\w+=, .@-]+)*.*`

Required: No

customDomainCertificateExpiryTime

The expiration time for the certificate.

Type: Timestamp

Required: No

customDomainName

The custom domain name associated with the workgroup.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 253.

Pattern: `((?!-)[A-Za-z0-9-]{0,62}[A-Za-z0-9])\.((?!-)[A-Za-z0-9-]{1,62}[A-Za-z0-9])`

Required: No

workgroupName

The name of the workgroup associated with the database.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ConfigParameter

An array of key-value pairs to set for advanced control over Amazon Redshift Serverless.

Contents

parameterKey

The key of the parameter. The options are `auto_mv`, `datestyle`, `enable_case_sensitive_identifier`, `enable_user_activity_logging`, `query_group`, `search_path`, `require_ssl`, `use_fips_ssl`, and either `wlm_json_configuration` or query monitoring metrics that let you define performance boundaries. You can either specify individual query monitoring metrics (such as `max_scan_row_count`, `max_query_execution_time`) or use `wlm_json_configuration` to define query queues with rules, but not both. If you're using `wlm_json_configuration`, the maximum size of `parameterValue` is 8000 characters. For more information about query monitoring rules and available metrics, see [Query monitoring metrics for Amazon Redshift Serverless](#).

Type: String

Required: No

parameterValue

The value of the parameter to set.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CreateSnapshotScheduleActionParameters

The parameters that you can use to configure a [scheduled action](#) to create a snapshot. For more information about creating a scheduled action, see [CreateScheduledAction](#).

Contents

namespaceName

The name of the namespace for which you want to configure a scheduled action to create a snapshot.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: Yes

snapshotNamePrefix

A string prefix that is attached to the name of the snapshot created by the scheduled action. The final name of the snapshot is the string prefix appended by the date and time of when the snapshot was created.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 235.

Required: Yes

retentionPeriod

The retention period of the snapshot created by the scheduled action.

Type: Integer

Required: No

tags

An array of [Tag objects](#) to associate with the snapshot.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Endpoint

The VPC endpoint object.

Contents

address

The DNS address of the VPC endpoint.

Type: String

Required: No

port

The port that Amazon Redshift Serverless listens on.

Type: Integer

Required: No

vpcEndpoints

An array of VpcEndpoint objects.

Type: Array of [VpcEndpoint](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EndpointAccess

Information about an Amazon Redshift Serverless VPC endpoint.

Contents

address

The DNS address of the endpoint.

Type: String

Required: No

endpointArn

The Amazon Resource Name (ARN) of the VPC endpoint.

Type: String

Required: No

endpointCreateTime

The time that the endpoint was created.

Type: Timestamp

Required: No

endpointName

The name of the VPC endpoint.

Type: String

Required: No

endpointStatus

The status of the VPC endpoint.

Type: String

Required: No

port

The port number on which Amazon Redshift Serverless accepts incoming connections.

Type: Integer

Required: No

subnetIds

The unique identifier of subnets where Amazon Redshift Serverless choose to deploy the VPC endpoint.

Type: Array of strings

Required: No

vpcEndpoint

The connection endpoint for connecting to Amazon Redshift Serverless.

Type: [VpcEndpoint](#) object

Required: No

vpcSecurityGroups

The security groups associated with the endpoint.

Type: Array of [VpcSecurityGroupMembership](#) objects

Required: No

workgroupName

The name of the workgroup associated with the endpoint.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ManagedWorkgroupListItem

A collection of Amazon Redshift compute resources managed by AWS Glue.

Contents

creationDate

The creation date of the managed workgroup.

Type: Timestamp

Required: No

managedWorkgroupId

The unique identifier of the managed workgroup.

Type: String

Required: No

managedWorkgroupName

The name of the managed workgroup.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

Pattern: `[a-zA-Z0-9_:\-]+`

Required: No

sourceArn

The Amazon Resource Name (ARN) for the managed workgroup in the AWS Glue Data Catalog.

Type: String

Pattern: `arn:aws[a-z-]*:glue:[a-z0-9-]+\d+:(database|catalog)[a-z0-9-:]*(?:/[A-Za-z0-9-_{1,255}]*)`

Required: No

status

The status of the managed workgroup.

Type: String

Valid Values: CREATING | DELETING | MODIFYING | AVAILABLE | NOT_AVAILABLE

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Namespace

A collection of database objects and users.

Contents

adminPasswordSecretArn

The Amazon Resource Name (ARN) for the namespace's admin user credentials secret.

Type: String

Required: No

adminPasswordSecretKmsKeyId

The ID of the AWS Key Management Service (KMS) key used to encrypt and store the namespace's admin credentials secret.

Type: String

Required: No

adminUsername

The username of the administrator for the first database created in the namespace.

Type: String

Required: No

catalogArn

The Amazon Resource Name (ARN) of the AWS Glue Data Catalog associated with the namespace enabled with Amazon Redshift federated permissions.

Type: String

Required: No

creationDate

The date of when the namespace was created.

Type: Timestamp

Required: No

dbName

The name of the first database created in the namespace.

Type: String

Required: No

defaultIamRoleArn

The Amazon Resource Name (ARN) of the IAM role to set as a default in the namespace.

Type: String

Required: No

iamRoles

A list of IAM roles to associate with the namespace.

Type: Array of strings

Required: No

kmsKeyId

The ID of the AWS Key Management Service key used to encrypt your data.

Type: String

Required: No

lakehouseRegistrationStatus

The status of the lakehouse registration for the namespace. Indicates whether the namespace is successfully registered with Amazon Redshift federated permissions.

Type: String

Required: No

logExports

The types of logs the namespace can export. Available export types are User log, Connection log, and User activity log.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 16 items.

Valid Values: useractivitylog | userlog | connectionlog

Required: No

namespaceArn

The Amazon Resource Name (ARN) associated with a namespace.

Type: String

Required: No

namespaceId

The unique identifier of a namespace.

Type: String

Required: No

namespaceName

The name of the namespace. Must be between 3-64 alphanumeric characters in lowercase, and it cannot be a reserved word. A list of reserved words can be found in [Reserved Words](#) in the Amazon Redshift Database Developer Guide.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: No

status

The status of the namespace.

Type: String

Valid Values: AVAILABLE | MODIFYING | DELETING

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NetworkInterface

Contains information about a network interface in an Amazon Redshift Serverless managed VPC endpoint.

Contents

availabilityZone

The availability Zone.

Type: String

Required: No

ipv6Address

The IPv6 address of the network interface within the subnet.

Type: String

Required: No

networkInterfaceId

The unique identifier of the network interface.

Type: String

Required: No

privateIpAddress

The IPv4 address of the network interface within the subnet.

Type: String

Required: No

subnetId

The unique identifier of the subnet.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PerformanceTarget

An object that represents the price performance target settings for the workgroup.

Contents

level

The target price performance level for the workgroup. Valid values include 1, 25, 50, 75, and 100. These correspond to the price performance levels `LOW_COST`, `ECONOMICAL`, `BALANCED`, `RESOURCEFUL`, and `HIGH_PERFORMANCE`.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

status

Whether the price performance target is enabled for the workgroup.

Type: String

Valid Values: `ENABLED` | `DISABLED`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RecoveryPoint

The automatically created recovery point of a namespace. Recovery points are created every 30 minutes and kept for 24 hours.

Contents

namespaceArn

The Amazon Resource Name (ARN) of the namespace the recovery point is associated with.

Type: String

Required: No

namespaceName

The name of the namespace the recovery point is associated with.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: No

recoveryPointCreateTime

The time the recovery point is created.

Type: Timestamp

Required: No

recoveryPointId

The unique identifier of the recovery point.

Type: String

Required: No

totalSizeInMegaBytes

The total size of the data in the recovery point in megabytes.

Type: Double

Required: No

workgroupName

The name of the workgroup the recovery point is associated with.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Reservation

Represents an Amazon Redshift Serverless reservation, which gives you the option to commit to a specified number of Redshift Processing Units (RPUs) for a year at a discount from Serverless on-demand (OD) rates.

Contents

capacity

The number of Redshift Processing Units (RPUs) to reserve.

Type: Integer

Required: No

endDate

The end date for the serverless reservation. This date is one year after the start date that you specify.

Type: Timestamp

Required: No

offering

The type of offering for the reservation. The offering class determines the payment schedule for the reservation.

Type: [ReservationOffering](#) object

Required: No

reservationArn

The Amazon Resource Name (ARN) that uniquely identifies the serverless reservation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

reservationId

The identifier that uniquely identifies the serverless reservation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

startDate

The start date for the serverless reservation. This is the date you created the reservation.

Type: Timestamp

Required: No

status

The status of the reservation. Possible values include the following:

- `payment-pending`
- `active`
- `payment-failed`
- `retired`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 16.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ReservationOffering

The class of offering for the reservation. The offering class determines the payment schedule for the reservation.

Contents

currencyCode

The currency code for the offering.

Type: String

Required: No

duration

The duration, in seconds, for which the reservation reserves the RPU.

Type: Integer

Required: No

hourlyCharge

The rate you are charged for each hour the reservation is active.

Type: Double

Required: No

offeringId

The offering identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

offeringType

Determines the payment schedule for the reservation.

Type: String

Valid Values: ALL_UPFRONT | NO_UPFRONT

Required: No

upfrontCharge

The up-front price you are charged for the reservation.

Type: Double

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourcePolicy

The resource policy object. Currently, you can use policies to share snapshots across AWS accounts.

Contents

policy

The resource policy.

Type: String

Required: No

resourceArn

The Amazon Resource Name (ARN) of the policy.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Schedule

The schedule of when Amazon Redshift Serverless should run the scheduled action.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

at

The timestamp of when Amazon Redshift Serverless should run the scheduled action. Timestamp is in UTC. Format of at expression is yyyy-mm-ddThh:mm:ss. For example, 2016-03-04T17:27:00.

Type: Timestamp

Required: No

cron

The cron expression to use to schedule a recurring scheduled action. Schedule invocations must be separated by at least one hour. Times are in UTC.

Format of cron expressions is (Minutes Hours Day-of-month Month Day-of-week Year). For example, "(0 10 ? * MON *)". For more information, see [Cron Expressions](#) in the *Amazon CloudWatch Events User Guide*.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ScheduledActionAssociation

Contains names of objects associated with a scheduled action.

Contents

namespaceName

Name of associated Amazon Redshift Serverless namespace.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: No

scheduledActionName

Name of associated scheduled action.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 60.

Pattern: [a-z0-9-]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ScheduledActionResponse

The returned scheduled action object.

Contents

endTime

The end time of

Type: Timestamp

Required: No

namespaceName

The end time in UTC when the schedule is no longer active. After this time, the scheduled action does not trigger.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: No

nextInvocations

An array of timestamps of when the next scheduled actions will trigger.

Type: Array of timestamps

Required: No

roleArn

The ARN of the IAM role to assume to run the scheduled action. This IAM role must have permission to run the Amazon Redshift Serverless API operation in the scheduled action. This IAM role must allow the Amazon Redshift scheduler to schedule creating snapshots. (Principal scheduler.redshift.amazonaws.com) to assume permissions on your behalf. For more information about the IAM role to use with the Amazon Redshift scheduler, see [Using Identity-Based Policies for Amazon Redshift](#) in the Amazon Redshift Management Guide

Type: String

Required: No

schedule

The schedule for a one-time (at timestamp format) or recurring (cron format) scheduled action. Schedule invocations must be separated by at least one hour. Times are in UTC.

- Format of at timestamp is `yyyy-mm-ddThh:mm:ss`. For example, `2016-03-04T17:27:00`.
- Format of cron expression is (Minutes Hours Day-of-month Month Day-of-week Year). For example, `"(0 10 ? * MON *)"`. For more information, see [Cron Expressions](#) in the *Amazon CloudWatch Events User Guide*.

Type: [Schedule](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

scheduledActionDescription

The description of the scheduled action.

Type: String

Required: No

scheduledActionName

The name of the scheduled action.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 60.

Pattern: `[a-z0-9-]+`

Required: No

scheduledActionUuid

The uuid of the scheduled action.

Type: String

Required: No

startTime

The start time in UTC when the schedule is active. Before this time, the scheduled action does not trigger.

Type: Timestamp

Required: No

state

The state of the scheduled action.

Type: String

Valid Values: ACTIVE | DISABLED

Required: No

targetAction

A JSON format string of the Amazon Redshift Serverless API operation with input parameters. The following is an example of a target action.

```
"{"CreateSnapshot": {"NamespaceName": "sampleNamespace", "SnapshotName": "sampleSnapshot", "retentionPeriod": "1"}}"
```

Type: [TargetAction](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServerlessTrack

Defines a track that determines which Amazon Redshift version to apply after a new version is released. If the value for `ServerlessTrack` is `current`, the workgroup is updated to the most recently certified release. If the value is `trailing`, the workgroup is updated to the previously certified release.

Contents

`trackName`

The name of the track. Valid values are `current` and `trailing`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9_]+`

Required: No

`updateTargets`

An array of `UpdateTarget` objects to update with the track.

Type: Array of [UpdateTarget](#) objects

Required: No

`workgroupVersion`

The workgroup version number for the workgroup release.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Snapshot

A snapshot object that contains databases.

Contents

accountsWithProvisionedRestoreAccess

All of the AWS accounts that have access to restore a snapshot to a provisioned cluster.

Type: Array of strings

Required: No

accountsWithRestoreAccess

All of the AWS accounts that have access to restore a snapshot to a namespace.

Type: Array of strings

Required: No

actualIncrementalBackupSizeInMegaBytes

The size of the incremental backup in megabytes.

Type: Double

Required: No

adminPasswordSecretArn

The Amazon Resource Name (ARN) for the namespace's admin user credentials secret.

Type: String

Required: No

adminPasswordSecretKmsKeyId

The ID of the AWS Key Management Service (KMS) key used to encrypt and store the namespace's admin credentials secret.

Type: String

Required: No

adminUsername

The username of the database within a snapshot.

Type: String

Required: No

backupProgressInMegaBytes

The size in megabytes of the data that has been backed up to a snapshot.

Type: Double

Required: No

currentBackupRateInMegaBytesPerSecond

The rate at which data is backed up into a snapshot in megabytes per second.

Type: Double

Required: No

elapsedTimeInSeconds

The amount of time it took to back up data into a snapshot.

Type: Long

Required: No

estimatedSecondsToCompletion

The estimated amount of seconds until the snapshot completes backup.

Type: Long

Required: No

kmsKeyId

The unique identifier of the KMS key used to encrypt the snapshot.

Type: String

Required: No

namespaceArn

The Amazon Resource Name (ARN) of the namespace the snapshot was created from.

Type: String

Required: No

namespaceName

The name of the namespace.

Type: String

Required: No

ownerAccount

The owner AWS; account of the snapshot.

Type: String

Required: No

snapshotArn

The Amazon Resource Name (ARN) of the snapshot.

Type: String

Required: No

snapshotCreateTime

The timestamp of when the snapshot was created.

Type: Timestamp

Required: No

snapshotName

The name of the snapshot.

Type: String

Required: No

snapshotRemainingDays

The amount of days until the snapshot is deleted.

Type: Integer

Required: No

snapshotRetentionPeriod

The period of time, in days, of how long the snapshot is retained.

Type: Integer

Required: No

snapshotRetentionStartTime

The timestamp of when data within the snapshot started getting retained.

Type: Timestamp

Required: No

status

The status of the snapshot.

Type: String

Valid Values: AVAILABLE | CREATING | DELETED | CANCELLED | FAILED | COPYING

Required: No

totalBackupSizeInMegaBytes

The total size, in megabytes, of how big the snapshot is.

Type: Double

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SnapshotCopyConfiguration

The object that you configure to copy snapshots from one namespace to a namespace in another AWS Region.

Contents

destinationKmsKeyId

The ID of the KMS key to use to encrypt your snapshots in the destination AWS Region.

Type: String

Required: No

destinationRegion

The destination AWS Region to copy snapshots to.

Type: String

Required: No

namespaceName

The name of the namespace to copy snapshots from in the source AWS Region.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: No

snapshotCopyConfigurationArn

The ARN of the snapshot copy configuration object.

Type: String

Required: No

snapshotCopyConfigurationId

The ID of the snapshot copy configuration object.

Type: String

Required: No

snapshotRetentionPeriod

The retention period of snapshots that are copied to the destination AWS Region.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TableRestoreStatus

Contains information about a table restore request.

Contents

message

A message that explains the returned status. For example, if the status of the operation is FAILED, the message explains why the operation failed.

Type: String

Required: No

namespaceName

The namespace of the table being restored from.

Type: String

Required: No

newTableName

The name of the table to create from the restore operation.

Type: String

Required: No

progressInMegaBytes

The amount of data restored to the new table so far, in megabytes (MB).

Type: Long

Required: No

recoveryPointId

The ID of the recovery point being restored from.

Type: String

Required: No

requestTime

The time that the table restore request was made, in Universal Coordinated Time (UTC).

Type: Timestamp

Required: No

snapshotName

The name of the snapshot being restored from.

Type: String

Required: No

sourceDatabaseName

The name of the source database being restored from.

Type: String

Required: No

sourceSchemaName

The name of the source schema being restored from.

Type: String

Required: No

sourceTableName

The name of the source table being restored from.

Type: String

Required: No

status

A value that describes the current state of the table restore request. Possible values are SUCCEEDED, FAILED, CANCELED, PENDING, and IN_PROGRESS.

Type: String

Required: No

tableRestoreRequestId

The ID of the RestoreTableFromSnapshot request.

Type: String

Required: No

targetDatabaseName

The name of the database to restore to.

Type: String

Required: No

targetSchemaName

The name of the schema to restore to.

Type: String

Required: No

totalDataInMegaBytes

The total amount of data to restore to the new table, in megabytes (MB).

Type: Long

Required: No

workgroupName

The name of the workgroup being restored from.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

A map of key-value pairs.

Contents

key

The key to use in the tag.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

value

The value of the tag.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TargetAction

A JSON format string of the Amazon Redshift Serverless API operation with input parameters. The following is an example of a target action.

```
"{"CreateSnapshot": {"NamespaceName": "sampleNamespace", "SnapshotName": "sampleSnapshot", "retentionPeriod": "1"}}"
```

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

createSnapshot

The parameters that you can use to configure a [scheduled action](#) to create a snapshot. For more information about creating a scheduled action, see [CreateScheduledAction](#).

Type: [CreateSnapshotScheduleActionParameters](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdateTarget

A track that you can switch the current track to.

Contents

trackName

The name of the new track.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_]+

Required: No

workgroupVersion

The workgroup version for the new track.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UsageLimit

The usage limit object.

Contents

amount

The limit amount. If time-based, this amount is in RPUs consumed per hour. If data-based, this amount is in terabytes (TB). The value must be a positive number.

Type: Long

Required: No

breachAction

The action that Amazon Redshift Serverless takes when the limit is reached.

Type: String

Valid Values: `log` | `emit-metric` | `deactivate`

Required: No

period

The time period that the amount applies to. A weekly period begins on Sunday. The default is monthly.

Type: String

Valid Values: `daily` | `weekly` | `monthly`

Required: No

resourceArn

The Amazon Resource Name (ARN) that identifies the Amazon Redshift Serverless resource.

Type: String

Required: No

usageLimitArn

The Amazon Resource Name (ARN) of the resource associated with the usage limit.

Type: String

Required: No

usageLimitId

The identifier of the usage limit.

Type: String

Required: No

usageType

The Amazon Redshift Serverless feature to limit.

Type: String

Valid Values: `serverless-compute` | `cross-region-datasharing`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VpcEndpoint

The connection endpoint for connecting to Amazon Redshift Serverless through the proxy.

Contents

networkInterfaces

One or more network interfaces of the endpoint. Also known as an interface endpoint.

Type: Array of [NetworkInterface](#) objects

Required: No

vpcEndpointId

The connection endpoint ID for connecting to Amazon Redshift Serverless.

Type: String

Required: No

vpcId

The VPC identifier that the endpoint is associated with.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VpcSecurityGroupMembership

Describes the members of a VPC security group.

Contents

status

The status of the VPC security group.

Type: String

Required: No

vpcSecurityGroupId

The unique identifier of the VPC security group.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Workgroup

The collection of computing resources from which an endpoint is created.

Contents

baseCapacity

The base data warehouse capacity of the workgroup in Redshift Processing Units (RPUs).

Type: Integer

Required: No

configParameters

An array of parameters to set for advanced control over a database. The options are `auto_mv`, `datestyle`, `enable_case_sensitive_identifier`, `enable_user_activity_logging`, `query_group`, `search_path`, `require_ssl`, `use_fips_ssl`, and either `wlm_json_configuration` or query monitoring metrics that let you define performance boundaries. You can either specify individual query monitoring metrics (such as `max_scan_row_count`, `max_query_execution_time`) or use `wlm_json_configuration` to define query queues with rules, but not both. If you're using `wlm_json_configuration`, the maximum size of `parameterValue` is 8000 characters. For more information about query monitoring rules and available metrics, see [Query monitoring metrics for Amazon Redshift Serverless](#).

Type: Array of [ConfigParameter](#) objects

Required: No

creationDate

The creation date of the workgroup.

Type: Timestamp

Required: No

crossAccountVpcs

A list of VPCs. Each entry is the unique identifier of a virtual private cloud with access to Amazon Redshift Serverless. If all of the VPCs for the grantee are allowed, it shows an asterisk.

Type: Array of strings

Required: No

customDomainCertificateArn

The custom domain name's certificate Amazon resource name (ARN).

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `.*arn:[\w+=/, .@-]+:acm:[\w+=/, .@-]*:[0-9]+:[\w+=, .@-]+(\/[\w+=, .@-]+)*.*`

Required: No

customDomainCertificateExpiryTime

The expiration time for the certificate.

Type: Timestamp

Required: No

customDomainName

The custom domain name associated with the workgroup.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 253.

Pattern: `((?!-)[A-Za-z0-9-]{0,62}[A-Za-z0-9])\.(?!-)[A-Za-z0-9-]{1,62}[A-Za-z0-9]`

Required: No

endpoint

The endpoint that is created from the workgroup.

Type: [Endpoint](#) object

Required: No

enhancedVpcRouting

The value that specifies whether to enable enhanced virtual private cloud (VPC) routing, which forces Amazon Redshift Serverless to route traffic through your VPC.

Type: Boolean

Required: No

extraComputeForAutomaticOptimization

A boolean value that, if `true`, indicates that the workgroup allocates additional compute resources to run automatic optimization operations.

Default: `false`

Type: Boolean

Required: No

ipAddressType

The IP address type that the workgroup supports. Possible values are `ipv4` and `dualstack`.

Type: String

Pattern: `(ipv4|dualstack)`

Required: No

maxCapacity

The maximum data-warehouse capacity Amazon Redshift Serverless uses to serve queries. The max capacity is specified in RPUs.

Type: Integer

Required: No

namespaceName

The namespace the workgroup is associated with.

Type: String

Required: No

patchVersion

The patch version of your Amazon Redshift Serverless workgroup. For more information about patch versions, see [Cluster versions for Amazon Redshift](#).

Type: String

Required: No

pendingTrackName

The name for the track that you want to assign to the workgroup. When the track changes, the workgroup is switched to the latest workgroup release available for the track. At this point, the track name is applied.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_]+

Required: No

port

The custom port to use when connecting to a workgroup. Valid port ranges are 5431-5455 and 8191-8215. The default is 5439.

Type: Integer

Required: No

pricePerformanceTarget

An object that represents the price performance target settings for the workgroup.

Type: [PerformanceTarget](#) object

Required: No

publiclyAccessible

A value that specifies whether the workgroup can be accessible from a public network.

Type: Boolean

Required: No

securityGroupIds

An array of security group IDs to associate with the workgroup.

Type: Array of strings

Required: No

status

The status of the workgroup.

Type: String

Valid Values: CREATING | AVAILABLE | MODIFYING | DELETING

Required: No

subnetIds

An array of subnet IDs the workgroup is associated with.

Type: Array of strings

Required: No

trackName

The name of the track for the workgroup.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_]+

Required: No

workgroupArn

The Amazon Resource Name (ARN) that links to the workgroup.

Type: String

Required: No

workgroupId

The unique identifier of the workgroup.

Type: String

Required: No

workgroupName

The name of the workgroup.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 64.

Pattern: [a-z0-9-]+

Required: No

workgroupVersion

The Amazon Redshift Serverless version of your workgroup. For more information about Amazon Redshift Serverless versions, see [Cluster versions for Amazon Redshift](#).

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400