



Welcome

AWS re:Post Private



API Version 2022-05-13

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS re:Post Private: Welcome

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
BatchAddChannelRoleToAccessors	3
Request Syntax	3
URI Request Parameters	3
Request Body	3
Response Syntax	4
Response Elements	4
Errors	5
See Also	5
BatchAddRole	7
Request Syntax	7
URI Request Parameters	7
Request Body	7
Response Syntax	8
Response Elements	8
Errors	9
See Also	9
BatchRemoveChannelRoleFromAccessors	11
Request Syntax	11
URI Request Parameters	11
Request Body	11
Response Syntax	12
Response Elements	12
Errors	13
See Also	13
BatchRemoveRole	15
Request Syntax	15
URI Request Parameters	15
Request Body	15
Response Syntax	16
Response Elements	16
Errors	17
See Also	17

CreateChannel	19
Request Syntax	19
URI Request Parameters	19
Request Body	19
Response Syntax	20
Response Elements	20
Errors	20
See Also	21
CreateSpace	23
Request Syntax	23
URI Request Parameters	23
Request Body	23
Response Syntax	25
Response Elements	25
Errors	26
See Also	27
DeleteSpace	28
Request Syntax	28
URI Request Parameters	28
Request Body	28
Response Syntax	28
Response Elements	28
Errors	28
See Also	29
DeregisterAdmin	30
Request Syntax	30
URI Request Parameters	30
Request Body	30
Response Syntax	30
Response Elements	30
Errors	30
See Also	31
GetChannel	33
Request Syntax	33
URI Request Parameters	33
Request Body	33

Response Syntax	33
Response Elements	34
Errors	35
See Also	36
GetSpace	37
Request Syntax	37
URI Request Parameters	37
Request Body	37
Response Syntax	37
Response Elements	38
Errors	42
See Also	42
ListChannels	44
Request Syntax	44
URI Request Parameters	44
Request Body	44
Response Syntax	44
Response Elements	45
Errors	45
See Also	46
ListSpaces	47
Request Syntax	47
URI Request Parameters	47
Request Body	47
Response Syntax	47
Response Elements	48
Errors	48
See Also	49
ListTagsForResource	50
Request Syntax	50
URI Request Parameters	50
Request Body	50
Response Syntax	50
Response Elements	50
Errors	51
See Also	52

RegisterAdmin	53
Request Syntax	53
URI Request Parameters	53
Request Body	53
Response Syntax	53
Response Elements	53
Errors	53
See Also	54
SendInvites	56
Request Syntax	56
URI Request Parameters	56
Request Body	56
Response Syntax	57
Response Elements	57
Errors	57
See Also	58
TagResource	59
Request Syntax	59
URI Request Parameters	59
Request Body	59
Response Syntax	60
Response Elements	60
Errors	60
See Also	61
UntagResource	62
Request Syntax	62
URI Request Parameters	62
Request Body	62
Response Syntax	62
Response Elements	63
Errors	63
See Also	63
UpdateChannel	65
Request Syntax	65
URI Request Parameters	65
Request Body	65

Response Syntax	66
Response Elements	66
Errors	66
See Also	67
UpdateSpace	68
Request Syntax	68
URI Request Parameters	68
Request Body	68
Response Syntax	69
Response Elements	69
Errors	69
See Also	70
Data Types	72
BatchError	73
Contents	73
See Also	73
ChannelData	74
Contents	74
See Also	75
SpaceData	77
Contents	77
See Also	80
SupportedEmailDomainsParameters	81
Contents	81
See Also	81
SupportedEmailDomainsStatus	82
Contents	82
See Also	82
ValidationExceptionField	83
Contents	83
See Also	83
Common Parameters	84
Common Errors	87

Welcome

AWS re:Post Private is a private version of AWS re:Post for enterprises with Enterprise Support or Enterprise On-Ramp Support plans. It provides access to knowledge and experts to accelerate cloud adoption and increase developer productivity. With your organization-specific private re:Post, you can build an organization-specific developer community that drives efficiencies at scale and provides access to valuable knowledge resources. Additionally, re:Post Private centralizes trusted AWS technical content and offers private discussion forums to improve how your teams collaborate internally and with AWS to remove technical obstacles, accelerate innovation, and scale more efficiently in the cloud.

This document was last published on August 1, 2025.

Actions

The following actions are supported:

- [BatchAddChannelRoleToAccessors](#)
- [BatchAddRole](#)
- [BatchRemoveChannelRoleFromAccessors](#)
- [BatchRemoveRole](#)
- [CreateChannel](#)
- [CreateSpace](#)
- [DeleteSpace](#)
- [DeregisterAdmin](#)
- [GetChannel](#)
- [GetSpace](#)
- [ListChannels](#)
- [ListSpaces](#)
- [ListTagsForResource](#)
- [RegisterAdmin](#)
- [SendInvites](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateChannel](#)
- [UpdateSpace](#)

BatchAddChannelRoleToAccessors

Add role to multiple users or groups in a private re:Post channel.

Request Syntax

```
POST /spaces/spaceId/channels/channelId/roles HTTP/1.1
Content-type: application/json

{
  "accessorIdsstring" ],
  "channelRolestring"
}
```

URI Request Parameters

The request uses the following URI parameters.

channelId

The unique ID of the private re:Post channel.

Length Constraints: Fixed length of 24.

Required: Yes

spaceId

The unique ID of the private re:Post.

Required: Yes

Request Body

The request accepts the following data in JSON format.

accessorIds

The user or group identifiers to add the role to.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 1000 items.

Required: Yes

channelRole

The channel role to add to the users or groups.

Type: String

Valid Values: ASKER | EXPERT | MODERATOR | SUPPORTREQUESTOR

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "addedAccessorsIdserrorsaccessorIderrormessage
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

addedAccessorsIds

An array of successfully updated identifiers.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 1000 items.

errors

An array of errors that occurred when roles were added.

Type: Array of [BatchError](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

BatchAddRole

Add a role to multiple users or groups in a private re:Post.

Request Syntax

```
POST /spaces/spaceId/roles HTTP/1.1
Content-type: application/json

{
  "accessorIdsrole
```

URI Request Parameters

The request uses the following URI parameters.

spaceId

The unique ID of the private re:Post.

Required: Yes

Request Body

The request accepts the following data in JSON format.

accessorIds

The user or group accessor identifiers to add the role to.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 1000 items.

Required: Yes

role

The role to add to the users or groups.

Type: String

Valid Values: EXPERT | MODERATOR | ADMINISTRATOR | SUPPORTREQUESTOR

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "addedAccessorIdsstring" ],
  "errorsaccessorIdstring",
      "errornumber,
      "messagestring"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

addedAccessors

An array of successfully updated accessor identifiers.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 1000 items.

errors

An array of errors that occurred when roles were added.

Type: Array of [BatchError](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

BatchRemoveChannelRoleFromAccessors

Remove a role from multiple users or groups in a private re:Post channel.

Request Syntax

```
PATCH /spaces/spaceId/channels/channelId/roles HTTP/1.1
Content-type: application/json

{
  "accessorIdsstring" ],
  "channelRolestring"
}
```

URI Request Parameters

The request uses the following URI parameters.

channelId

The unique ID of the private re:Post channel.

Length Constraints: Fixed length of 24.

Required: Yes

spaceId

The unique ID of the private re:Post.

Required: Yes

Request Body

The request accepts the following data in JSON format.

accessorIds

The users or groups identifiers to remove the role from.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 1000 items.

Required: Yes

channelRole

The channel role to remove from the users or groups.

Type: String

Valid Values: ASKER | EXPERT | MODERATOR | SUPPORTREQUESTOR

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "errorsaccessorIderrormessageremovedAccessorsIds
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

errors

An array of errors that occurred when roles were removed.

Type: Array of [BatchError](#) objects

removedAccessorsIds

An array of successfully updated identifiers.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 1000 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

BatchRemoveRole

Remove a role from multiple users or groups in a private re:Post.

Request Syntax

```
PATCH /spaces/spaceId/roles HTTP/1.1
Content-type: application/json

{
  "accessorIdsrole
```

URI Request Parameters

The request uses the following URI parameters.

spaceId

The unique ID of the private re:Post.

Required: Yes

Request Body

The request accepts the following data in JSON format.

accessorIds

The user or group accessor identifiers to remove the role from.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 1000 items.

Required: Yes

role

The role to remove from the users or groups.

Type: String

Valid Values: EXPERT | MODERATOR | ADMINISTRATOR | SUPPORTREQUESTOR

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "errorsaccessorIdstring",
      "errornumber,
      "messagestring"
    }
  ],
  "removedAccessorsIdsstring" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

errors

An array of errors that occurred when roles were removed.

Type: Array of [BatchError](#) objects

removedAccessorsIds

An array of successfully updated accessor identifiers.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 1000 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateChannel

Creates a channel in an AWS re:Post Private re:Post.

Request Syntax

```
POST /spaces/spaceId/channels HTTP/1.1
Content-type: application/json

{
  "channelDescriptionchannelName
```

URI Request Parameters

The request uses the following URI parameters.

spaceId

The unique ID of the private re:Post.

Required: Yes

Request Body

The request accepts the following data in JSON format.

channelDescription

A description for the channel. This is used only to help you identify this channel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

channelName

The name for the channel. This must be unique per private re:Post.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
    "channelId
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

channelId

The unique ID of the private re:Post channel.

Type: String

Length Constraints: Fixed length of 24.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

Request would cause a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateSpace

Creates an AWS re:Post Private re:Post.

Request Syntax

```
POST /spaces HTTP/1.1
Content-type: application/json

{
  "description": "string",
  "name": "string",
  "roleArn": "string",
  "subdomain": "string",
  "supportedEmailDomains": {
    "allowedDomains": [ "string" ],
    "enabled": "string"
  },
  "tags": {
    "string" : "string"
  },
  "tier": "string",
  "userKMSKey": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

description

A description for the private re:Post. This is used only to help you identify this private re:Post.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

[name](#)

The name for the private re:Post. This must be unique in your account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 30.

Required: Yes

[roleArn](#)

The IAM role that grants permissions to the private re:Post to convert unanswered questions into AWS support tickets.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: No

[subdomain](#)

The subdomain that you use to access your AWS re:Post Private private re:Post. All custom subdomains must be approved by AWS before use. In addition to your custom subdomain, all private re:Posts are issued an AWS generated subdomain for immediate use.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Required: Yes

[supportedEmailDomains](#)

Type: [SupportedEmailDomainsParameters](#) object

Required: No

[tags](#)

The list of tags associated with the private re:Post.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: (? !aws :)[a-zA-Z+-=._:/]+

Value Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

tier

The pricing tier for the private re:Post.

Type: String

Valid Values: BASIC | STANDARD

Required: Yes

userKMSKey

The AWS KMS key ARN that's used for the AWS KMS encryption. If you don't provide a key, your data is encrypted by default with a key that AWS owns and manages for you.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "spaceId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

spaceId

The unique ID of the private re:Post.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

Request would cause a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteSpace

Deletes an AWS re:Post Private re:Post.

Request Syntax

```
DELETE /spaces/spaceId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

spaceId

The unique ID of the private re:Post.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeregisterAdmin

Removes the user or group from the list of administrators of the private re:Post.

Request Syntax

```
DELETE /spaces/spaceId/admins/adminId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

adminId

The ID of the admin to remove.

Required: Yes

spaceId

The ID of the private re:Post to remove the admin from.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetChannel

Displays information about a channel in a private re:Post.

Request Syntax

```
GET /spaces/spaceId/channels/channelId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

channelId

The unique ID of the private re:Post channel.

Length Constraints: Fixed length of 24.

Required: Yes

spaceId

The unique ID of the private re:Post.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "channelDescription": "string",
  "channelId": "string",
  "channelName": "string",
  "channelRoles": {
```

```
    "string" : [ "string" ]
},
"channelStatus": "string",
"createDateTime": "string",
"deleteDateTime": "string",
"spaceId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[channelDescription](#)

A description for the channel. This is used only to help you identify this channel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

[channelId](#)

The unique ID of the private re:Post channel.

Type: String

Length Constraints: Fixed length of 24.

[channelName](#)

The name for the channel. This must be unique per private re:Post.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

[channelRoles](#)

The channel roles associated to the users and groups of the channel.

Type: String to array of strings map

Valid Values: ASKER | EXPERT | MODERATOR | SUPPORTREQUESTOR

channelStatus

The status pf the channel.

Type: String

Valid Values: CREATED | CREATING | CREATE_FAILED | DELETED | DELETING | DELETE_FAILED

createDateTime

The date when the channel was created.

Type: Timestamp

deleteDateTime

The date when the channel was deleted.

Type: Timestamp

spaceId

The unique ID of the private re:Post.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetSpace

Displays information about the AWS re:Post Private re:Post.

Request Syntax

```
GET /spaces/spaceId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

spaceId

The ID of the private re:Post.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
    "applicationArnarnclientIdconfigurationStatuscontentSizecreateDateTimecustomerRoleArndeleteDateTimedescriptiongroupAdminsidentityStoreIdname
```

```
"randomDomain": "string",
"roles": {
    "string" : [ "string" ]
},
"spaceId": "string",
"status": "string",
"storageLimit": number,
"supportedEmailDomains": {
    "allowedDomains": [ "string" ],
    "enabled": "string"
},
"tier": "string",
"userAdmins": [ "string" ],
"userCount": number,
"userKMSKey": "string",
"vanityDomain": "string",
"vanityDomainStatus": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[applicationArn](#)

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

[arn](#)

The ARN of the private re:Post.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

[clientId](#)

The Identity Center identifier for the Application Instance.

Type: String

configurationStatus

The configuration status of the private re:Post.

Type: String

Valid Values: CONFIGURED | UNCONFIGURED

contentSize

The content size of the private re:Post.

Type: Long

createDateTime

The date when the private re:Post was created.

Type: Timestamp

customerRoleArn

The IAM role that grants permissions to the private re:Post to convert unanswered questions into AWS support tickets.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

deleteDateTime

The date when the private re:Post was deleted.

Type: Timestamp

description

The description of the private re:Post.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

groupAdmins

This parameter has been deprecated.

The list of groups that are administrators of the private re:Post.

Type: Array of strings

identityStoreId

Type: String

name

The name of the private re:Post.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 30.

randomDomain

The AWS generated subdomain of the private re:Post

Type: String

roles

A map of accessor identifiers and their roles.

Type: String to array of strings map

Valid Values: EXPERT | MODERATOR | ADMINISTRATOR | SUPPORTREQUESTOR

spaceId

The unique ID of the private re:Post.

Type: String

status

The creation or deletion status of the private re:Post.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 30.

storageLimit

The storage limit of the private re:Post.

Type: Long

[supportedEmailDomains](#)

Type: [SupportedEmailDomainsStatus](#) object

[tier](#)

The pricing tier of the private re:Post.

Type: String

Valid Values: BASIC | STANDARD

[userAdmins](#)

This parameter has been deprecated.

The list of users that are administrators of the private re:Post.

Type: Array of strings

[userCount](#)

The number of users that have onboarded to the private re:Post.

Type: Integer

[userKMSKey](#)

The custom AWS KMS key ARN that's used for the AWS KMS encryption.

Type: String

[vanityDomain](#)

The custom subdomain that you use to access your private re:Post. All custom subdomains must be approved by AWS before use.

Type: String

[vanityDomainStatus](#)

The approval status of the custom subdomain.

Type: String

Valid Values: PENDING | APPROVED | UNAPPROVED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListChannels

Returns the list of channel within a private re:Post with some information about each channel.

Request Syntax

```
GET /spaces/spaceId/channels?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of channels to include in the results.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

The token for the next set of channel to return. You receive this token from a previous ListChannels operation.

spaceId

The unique ID of the private re:Post.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "channels": [
    {
      "channelDescription": "string",
```

```
    "channelId": "string",
    "channelName": "string",
    "channelStatus": "string",
    "createDateTime": "string",
    "deleteDateTime": "string",
    "groupCount": number,
    "spaceId": "string",
    "userCount": number
  },
],
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[channels](#)

An array of structures that contain some information about the channels in the private re:Post.

Type: Array of [ChannelData](#) objects

[nextToken](#)

The token that you use when you request the next set of channels.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListSpaces

Returns a list of AWS re:Post Private private re:Posts in the account with some information about each private re:Post.

Request Syntax

```
GET /spaces?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[maxResults](#)

The maximum number of private re:Posts to include in the results.

Valid Range: Minimum value of 1. Maximum value of 100.

[nextToken](#)

The token for the next set of private re:Posts to return. You receive this token from a previous ListSpaces operation.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextTokenstring",
  "spacesarnstring",
      "configurationStatusstring",
      "contentSizenumber,
      ...
    }
  ]
}
```

```
"createDateTime": "string",
"deleteDateTime": "string",
"description": "string",
"name": "string",
"randomDomain": "string",
"spaceId": "string",
"status": "string",
"storageLimit": number,
"supportedEmailDomains": {
    "allowedDomains": [ "string" ],
    "enabled": "string"
},
"tier": "string",
"userCount": number,
"userKMSKey": "string",
"vanityDomain": "string",
"vanityDomainStatus": "string"
}
]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The token that you use when you request the next set of private re:Posts.

Type: String

spaces

An array of structures that contain some information about the private re:Posts in the account.

Type: Array of [SpaceData](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Returns the tags that are associated with the AWS re:Post Private resource specified by the resourceArn. The only resource that can be tagged is a private re:Post.

Request Syntax

```
GET /tags/resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The ARN of the resource that the tags are associated with.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "tags": [
    {
      "string": "string"
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tags

The list of tags that are associated with the resource.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: (? !aws :)[a-zA-Z+-_=._:/]+

Value Length Constraints: Minimum length of 1. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RegisterAdmin

Adds a user or group to the list of administrators of the private re:Post.

Request Syntax

```
POST /spaces/spaceId/admins/adminId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

adminId

The ID of the administrator.

Required: Yes

spaceId

The ID of the private re:Post.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

SendInvites

Sends an invitation email to selected users and groups.

Request Syntax

```
POST /spaces/spaceId/invite HTTP/1.1
Content-type: application/json

{
  "accessorIdsbodytitle
```

URI Request Parameters

The request uses the following URI parameters.

spaceId

The ID of the private re:Post.

Required: Yes

Request Body

The request accepts the following data in JSON format.

accessorIds

The array of identifiers for the users and groups.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 1000 items.

Required: Yes

body

The body of the invite.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 600.

Required: Yes

[title](#)

The title of the invite.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: Yes

Response Syntax

HTTP/1.1 200

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Associates tags with an AWS re:Post Private resource. Currently, the only resource that can be tagged is the private re:Post. If you specify a new tag key for the resource, the tag is appended to the list of tags that are associated with the resource. If you specify a tag key that's already associated with the resource, the new tag value that you specify replaces the previous value for that tag.

Request Syntax

```
POST /tags/resourceArn HTTP/1.1
Content-type: application/json

{
  "tags": {
    "string": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The ARN of the resource that the tag is associated with.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

Request Body

The request accepts the following data in JSON format.

tags

The list of tag keys and values that must be associated with the resource. You can associate tag keys only, tags (key and values) only, or a combination of tag keys and tags.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: (? !aws :)[a-zA-Z+-=._:/]+

Value Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

Response Syntax

HTTP/1.1 200

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Removes the association of the tag with the AWS re:Post Private resource.

Request Syntax

```
DELETE /tags/resourceArn?tagKeys=tagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The ARN of the resource.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

tagKeys

The key values of the tag.

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (? !aws :) [a-zA-Z+-.=:_:/]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateChannel

Modifies an existing channel.

Request Syntax

```
PUT /spaces/spaceId/channels/channelId HTTP/1.1
Content-type: application/json

{
  "channelDescriptionchannelName
```

URI Request Parameters

The request uses the following URI parameters.

channelId

The unique ID of the private re:Post channel.

Length Constraints: Fixed length of 24.

Required: Yes

spaceId

The unique ID of the private re:Post.

Required: Yes

Request Body

The request accepts the following data in JSON format.

channelDescription

A description for the channel. This is used only to help you identify this channel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

channelName

The name for the channel. This must be unique per private re:Post.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

Response Syntax

HTTP/1.1 200

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateSpace

Modifies an existing AWS re:Post Private private re:Post.

Request Syntax

```
PUT /spaces/spaceId HTTP/1.1
Content-type: application/json

{
  "descriptionroleArnsupportedEmailDomainsallowedDomainsenabledtier
```

URI Request Parameters

The request uses the following URI parameters.

spaceId

The unique ID of this private re:Post.

Required: Yes

Request Body

The request accepts the following data in JSON format.

description

A description for the private re:Post. This is used only to help you identify this private re:Post.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

roleArn

The IAM role that grants permissions to the private re:Post to convert unanswered questions into AWS support tickets.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: No

supportedEmailDomains

Type: [SupportedEmailDomainsParameters](#) object

Required: No

tier

The pricing tier of this private re:Post.

Type: String

Valid Values: BASIC | STANDARD

Required: No

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS re:Post Private API contains several data types that various actions use. This section describes each data type in detail.

 **Note**

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [BatchError](#)
- [ChannelData](#)
- [SpaceData](#)
- [SupportedEmailDomainsParameters](#)
- [SupportedEmailDomainsStatus](#)
- [ValidationExceptionField](#)

BatchError

An error that occurred during a batch operation.

Contents

accessorId

The accessor identifier that's related to the error.

Type: String

Required: Yes

error

The error code.

Type: Integer

Required: Yes

message

Description of the error.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ChannelData

A structure that contains some information about a channel in a private re:Post.

Contents

channelId

The unique ID of the private re:Post channel.

Type: String

Length Constraints: Fixed length of 24.

Required: Yes

channelName

The name for the channel. This must be unique per private re:Post.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

channelStatus

The status pf the channel.

Type: String

Valid Values: CREATED | CREATING | CREATE_FAILED | DELETED | DELETING | DELETE_FAILED

Required: Yes

createDateTime

The date when the channel was created.

Type: Timestamp

Required: Yes

groupCount

The number of groups that are part of the channel.

Type: Integer

Required: Yes

spaceId

The unique ID of the private re:Post.

Type: String

Required: Yes

userCount

The number of users that are part of the channel.

Type: Integer

Required: Yes

channelDescription

A description for the channel. This is used only to help you identify this channel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

deleteDateTime

The date when the channel was deleted.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SpaceData

A structure that contains some information about a private re:Post in the account.

Contents

arn

The ARN of the private re:Post.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

configurationStatus

The configuration status of the private re:Post.

Type: String

Valid Values: CONFIGURED | UNCONFIGURED

Required: Yes

createDateTime

The date when the private re:Post was created.

Type: Timestamp

Required: Yes

name

The name for the private re:Post.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 30.

Required: Yes

randomDomain

The AWS generated subdomain of the private re:Post.

Type: String

Required: Yes

spaceId

The unique ID of the private re:Post.

Type: String

Required: Yes

status

The creation/deletion status of the private re:Post.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 30.

Required: Yes

storageLimit

The storage limit of the private re:Post.

Type: Long

Required: Yes

tier

The pricing tier of the private re:Post.

Type: String

Valid Values: BASIC | STANDARD

Required: Yes

vanityDomain

This custom subdomain that you use to access your private re:Post. All custom subdomains must be approved by AWS before use.

Type: String

Required: Yes

vanityDomainStatus

This approval status of the custom subdomain.

Type: String

Valid Values: PENDING | APPROVED | UNAPPROVED

Required: Yes

contentSize

The content size of the private re:Post.

Type: Long

Required: No

deleteDateTime

The date when the private re:Post was deleted.

Type: Timestamp

Required: No

description

The description for the private re:Post. This is used only to help you identify this private re:Post.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

supportedEmailDomains

Type: [SupportedEmailDomainsStatus](#) object

Required: No

userCount

The number of onboarded users to the private re:Post.

Type: Integer

Required: No

userKMSKey

The custom AWS KMS key ARN that's used for the AWS KMS encryption.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SupportedEmailDomainsParameters

Contents

allowedDomains

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

enabled

Type: String

Valid Values: ENABLED | DISABLED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SupportedEmailDomainsStatus

Contents

allowedDomains

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

enabled

Type: String

Valid Values: ENABLED | DISABLED | NOT_ALLOWED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ValidationExceptionField

Stores information about a field that's passed inside a request that resulted in an exception.

Contents

message

The name of the field.

Type: String

Required: Yes

name

Message describing why the field failed validation.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests in the IAM User Guide](#).

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request").

The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request is expired

HTTP Status Code: 403

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 403

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

MalformedHttpRequestException

Problems with the request at the HTTP level, e.g. we can't decompress the body according to the decompression algorithm specified by the content-encoding.

HTTP Status Code: 400

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 401

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestAbortedException

Convenient exception that can be used when a request is aborted before a reply is sent back (e.g. client closed connection).

HTTP Status Code: 400

RequestEntityTooLargeException

Problems with the request at the HTTP level. The request entity is too large.

HTTP Status Code: 413

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

RequestTimeoutException

Problems with the request at the HTTP level. Reading the Request timed out.

HTTP Status Code: 408

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

UnrecognizedClientException

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

UnknownOperationException

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 404

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400