



API Reference

Next generation Resilience Hub



API Version 2026-02-17

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Next generation Resilience Hub: API Reference

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
CreateAssertion	5
Request Syntax	5
URI Request Parameters	5
Request Body	5
Response Syntax	6
Response Elements	6
Errors	7
See Also	8
CreateInputSource	9
Request Syntax	9
URI Request Parameters	9
Request Body	9
Response Syntax	10
Response Elements	10
Errors	11
See Also	12
CreatePolicy	13
Request Syntax	13
URI Request Parameters	13
Request Body	13
Response Syntax	16
Response Elements	16
Errors	17
See Also	18
CreateReport	19
Request Syntax	19
URI Request Parameters	19
Request Body	19
Response Syntax	20
Response Elements	20
Errors	21
See Also	22

CreateService	23
Request Syntax	23
URI Request Parameters	24
Request Body	24
Response Syntax	26
Response Elements	29
Errors	29
See Also	30
CreateServiceFunction	32
Request Syntax	32
URI Request Parameters	32
Request Body	32
Response Syntax	33
Response Elements	34
Errors	34
See Also	35
CreateServiceFunctionResources	37
Request Syntax	37
URI Request Parameters	37
Request Body	37
Response Syntax	38
Response Elements	38
Errors	39
See Also	40
CreateSystem	42
Request Syntax	42
URI Request Parameters	42
Request Body	42
Response Syntax	44
Response Elements	44
Errors	45
See Also	46
CreateTest	47
Request Syntax	47
URI Request Parameters	47
Request Body	47

Response Syntax	49
Response Elements	50
Errors	50
See Also	51
CreateUserJourney	53
Request Syntax	53
URI Request Parameters	53
Request Body	53
Response Syntax	55
Response Elements	55
Errors	55
See Also	56
DeleteAssertion	58
Request Syntax	58
URI Request Parameters	58
Request Body	58
Response Syntax	59
Response Elements	59
Errors	59
See Also	60
DeleteInputSource	62
Request Syntax	62
URI Request Parameters	62
Request Body	62
Response Syntax	63
Response Elements	63
Errors	64
See Also	64
DeletePolicy	66
Request Syntax	66
URI Request Parameters	66
Request Body	66
Response Syntax	66
Response Elements	67
Errors	67
See Also	68

DeleteService	70
Request Syntax	70
URI Request Parameters	70
Request Body	70
Response Syntax	70
Response Elements	71
Errors	71
See Also	72
DeleteServiceFunction	74
Request Syntax	74
URI Request Parameters	74
Request Body	74
Response Syntax	75
Response Elements	75
Errors	75
See Also	76
DeleteServiceFunctionResources	78
Request Syntax	78
URI Request Parameters	78
Request Body	78
Response Syntax	79
Response Elements	79
Errors	80
See Also	81
DeleteSystem	83
Request Syntax	83
URI Request Parameters	83
Request Body	83
Response Syntax	83
Response Elements	84
Errors	84
See Also	85
DeleteTest	87
Request Syntax	87
URI Request Parameters	87
Request Body	87

Response Syntax	88
Response Elements	88
Errors	88
See Also	89
DeleteTestSources	91
Request Syntax	91
URI Request Parameters	91
Request Body	91
Response Syntax	92
Response Elements	92
Errors	92
See Also	93
DeleteUserJourney	95
Request Syntax	95
URI Request Parameters	95
Request Body	95
Response Syntax	96
Response Elements	96
Errors	96
See Also	97
GetFailureModeFinding	99
Request Syntax	99
URI Request Parameters	99
Request Body	99
Response Syntax	99
Response Elements	100
Errors	101
See Also	101
GetPolicy	103
Request Syntax	103
URI Request Parameters	103
Request Body	103
Response Syntax	103
Response Elements	104
Errors	104
See Also	105

GetService	107
Request Syntax	107
URI Request Parameters	107
Request Body	107
Response Syntax	107
Response Elements	110
Errors	110
See Also	111
GetSystem	112
Request Syntax	112
URI Request Parameters	112
Request Body	112
Response Syntax	112
Response Elements	113
Errors	113
See Also	114
GetTest	115
Request Syntax	115
URI Request Parameters	115
Request Body	115
Response Syntax	115
Response Elements	116
Errors	117
See Also	118
GetTestRun	119
Request Syntax	119
URI Request Parameters	119
Request Body	119
Response Syntax	119
Response Elements	121
Errors	122
See Also	123
GetTestTemplate	124
Request Syntax	124
URI Request Parameters	124
Request Body	124

Response Syntax	124
Response Elements	125
Errors	125
See Also	126
GetUserJourney	128
Request Syntax	128
URI Request Parameters	128
Request Body	128
Response Syntax	128
Response Elements	129
Errors	129
See Also	130
ImportApp	131
Request Syntax	131
URI Request Parameters	131
Request Body	131
Response Syntax	133
Response Elements	136
Errors	136
See Also	137
ImportPolicy	139
Request Syntax	139
URI Request Parameters	139
Request Body	139
Response Syntax	141
Response Elements	142
Errors	142
See Also	143
ListAssertions	145
Request Syntax	145
URI Request Parameters	145
Request Body	146
Response Syntax	146
Response Elements	146
Errors	147
See Also	148

ListDependencies	149
Request Syntax	149
URI Request Parameters	149
Request Body	150
Response Syntax	150
Response Elements	151
Errors	151
See Also	152
ListFailureModeAssessments	153
Request Syntax	153
URI Request Parameters	153
Request Body	154
Response Syntax	154
Response Elements	155
Errors	155
See Also	156
ListFailureModeFindings	158
Request Syntax	158
URI Request Parameters	158
Request Body	159
Response Syntax	159
Response Elements	159
Errors	160
See Also	161
ListInputSources	162
Request Syntax	162
URI Request Parameters	162
Request Body	163
Response Syntax	163
Response Elements	164
Errors	164
See Also	165
ListPolicies	166
Request Syntax	166
URI Request Parameters	166
Request Body	166

Response Syntax	166
Response Elements	167
Errors	168
See Also	168
ListReports	170
Request Syntax	170
URI Request Parameters	170
Request Body	171
Response Syntax	171
Response Elements	171
Errors	172
See Also	173
ListResolvedTestRunTargetResources	174
Request Syntax	174
URI Request Parameters	174
Request Body	175
Response Syntax	175
Response Elements	175
Errors	176
See Also	177
ListResources	178
Request Syntax	178
URI Request Parameters	178
Request Body	179
Response Syntax	179
Response Elements	180
Errors	180
See Also	181
ListServiceEvents	183
Request Syntax	183
URI Request Parameters	183
Request Body	184
Response Syntax	184
Response Elements	185
Errors	185
See Also	186

ListServiceFunctions	188
Request Syntax	188
URI Request Parameters	188
Request Body	188
Response Syntax	189
Response Elements	189
Errors	190
See Also	190
ListServices	192
Request Syntax	192
URI Request Parameters	192
Request Body	193
Response Syntax	193
Response Elements	194
Errors	195
See Also	196
ListServiceTopologyEdges	197
Request Syntax	197
URI Request Parameters	197
Request Body	197
Response Syntax	198
Response Elements	198
Errors	199
See Also	199
ListSystemEvents	201
Request Syntax	201
URI Request Parameters	201
Request Body	202
Response Syntax	202
Response Elements	203
Errors	203
See Also	204
ListSystems	205
Request Syntax	205
URI Request Parameters	205
Request Body	205

Response Syntax	205
Response Elements	206
Errors	206
See Also	207
ListTagsForResource	209
Request Syntax	209
URI Request Parameters	209
Request Body	209
Response Syntax	209
Response Elements	210
Errors	210
See Also	211
ListTestRunDependencies	213
Request Syntax	213
URI Request Parameters	213
Request Body	214
Response Syntax	214
Response Elements	214
Errors	215
See Also	216
ListTestRunEvents	217
Request Syntax	217
URI Request Parameters	217
Request Body	218
Response Syntax	218
Response Elements	218
Errors	219
See Also	220
ListTestRuns	221
Request Syntax	221
URI Request Parameters	221
Request Body	222
Response Syntax	222
Response Elements	222
Errors	223
See Also	224

ListTestRunSourceEvents	225
Request Syntax	225
URI Request Parameters	225
Request Body	226
Response Syntax	226
Response Elements	226
Errors	227
See Also	228
ListTestRunSources	229
Request Syntax	229
URI Request Parameters	229
Request Body	230
Response Syntax	230
Response Elements	230
Errors	231
See Also	232
ListTests	233
Request Syntax	233
URI Request Parameters	233
Request Body	233
Response Syntax	234
Response Elements	234
Errors	235
See Also	235
ListTestSources	237
Request Syntax	237
URI Request Parameters	237
Request Body	238
Response Syntax	238
Response Elements	238
Errors	239
See Also	240
ListTestTemplates	241
Request Syntax	241
URI Request Parameters	241
Request Body	241

Response Syntax	241
Response Elements	241
Errors	242
See Also	242
ListUserJourneys	244
Request Syntax	244
URI Request Parameters	244
Request Body	244
Response Syntax	245
Response Elements	245
Errors	245
See Also	246
PutTestSources	248
Request Syntax	248
URI Request Parameters	248
Request Body	248
Response Syntax	249
Response Elements	249
Errors	249
See Also	250
StartFailureModeAssessment	252
Request Syntax	252
URI Request Parameters	252
Request Body	252
Response Syntax	253
Response Elements	253
Errors	254
See Also	255
StartTestRun	257
Request Syntax	257
URI Request Parameters	257
Request Body	257
Response Syntax	258
Response Elements	258
Errors	259
See Also	260

StopTestRun	261
Request Syntax	261
URI Request Parameters	261
Request Body	261
Response Syntax	262
Response Elements	262
Errors	262
See Also	263
TagResource	265
Request Syntax	265
URI Request Parameters	265
Request Body	265
Response Syntax	266
Response Elements	266
Errors	266
See Also	267
UntagResource	269
Request Syntax	269
URI Request Parameters	269
Request Body	269
Response Syntax	270
Response Elements	270
Errors	270
See Also	271
UpdateAssertion	272
Request Syntax	272
URI Request Parameters	272
Request Body	272
Response Syntax	273
Response Elements	273
Errors	274
See Also	275
UpdateDependency	276
Request Syntax	276
URI Request Parameters	276
Request Body	276

Response Syntax	277
Response Elements	278
Errors	279
See Also	280
UpdateFailureModeFinding	281
Request Syntax	281
URI Request Parameters	281
Request Body	281
Response Syntax	282
Response Elements	283
Errors	283
See Also	284
UpdatePolicy	286
Request Syntax	286
URI Request Parameters	286
Request Body	286
Response Syntax	288
Response Elements	288
Errors	289
See Also	290
UpdateService	291
Request Syntax	291
URI Request Parameters	291
Request Body	292
Response Syntax	294
Response Elements	296
Errors	296
See Also	298
UpdateServiceFunction	299
Request Syntax	299
URI Request Parameters	299
Request Body	299
Response Syntax	300
Response Elements	301
Errors	301
See Also	302

UpdateSystem	304
Request Syntax	304
URI Request Parameters	304
Request Body	304
Response Syntax	305
Response Elements	305
Errors	306
See Also	307
UpdateTest	308
Request Syntax	308
URI Request Parameters	308
Request Body	308
Response Syntax	310
Response Elements	311
Errors	311
See Also	312
UpdateUserJourney	314
Request Syntax	314
URI Request Parameters	314
Request Body	314
Response Syntax	316
Response Elements	316
Errors	316
See Also	317
Data Types	319
Achievability	324
Contents	324
See Also	325
AlarmStateChangeDetail	326
Contents	326
See Also	326
Assertion	328
Contents	328
See Also	329
AssertionCreatedMetadata	330
Contents	330

See Also	330
AssertionDeletedMetadata	331
Contents	331
See Also	331
AssertionUpdatedMetadata	332
Contents	332
See Also	332
AssessmentCost	333
Contents	333
See Also	333
AssessmentSummary	334
Contents	334
See Also	336
AssociatedSystem	337
Contents	337
See Also	338
AvailabilitySlo	339
Contents	339
See Also	339
CrossAccountRole	340
Contents	340
See Also	340
DataRecoveryTargets	341
Contents	341
See Also	341
DependencyDiscoveryConfig	342
Contents	342
See Also	343
DependencySummary	344
Contents	344
See Also	346
DisasterRecoverySource	347
Contents	347
See Also	347
EdgePropertySummary	349
Contents	349

See Also	349
EffectivePolicyValues	350
Contents	350
See Also	351
EksLabelSelector	352
Contents	352
See Also	353
EksLabelSelectorRequirement	354
Contents	354
See Also	355
EksSource	356
Contents	356
See Also	357
EventActor	358
Contents	358
See Also	358
ExperimentDetails	360
Contents	360
See Also	360
FailedReportOutput	361
Contents	361
See Also	361
Finding	362
Contents	362
See Also	365
FindingSummary	366
Contents	366
See Also	368
InfrastructureAndCodeRecommendation	369
Contents	369
See Also	369
InputSource	370
Contents	370
See Also	370
InputSourceSummary	371
Contents	371

See Also	373
LoggingConfiguration	374
Contents	374
See Also	374
MultiAzTargets	376
Contents	376
See Also	376
MultiRegionTargets	378
Contents	378
See Also	378
ObservabilityAlarmInput	380
Contents	380
See Also	380
ObservabilityAlarmSummary	381
Contents	381
See Also	382
ObservabilityRecommendation	383
Contents	383
See Also	383
PermissionModel	384
Contents	384
See Also	384
Policy	385
Contents	385
See Also	387
PolicySummary	388
Contents	388
See Also	389
QueryDataPoint	391
Contents	391
See Also	391
QueryRange	392
Contents	392
See Also	392
ReportGenerationResult	394
Contents	394

See Also	396
ReportOutput	397
Contents	397
See Also	397
ReportOutputConfiguration	398
Contents	398
See Also	398
ResolvedTargetResource	399
Contents	399
See Also	400
Resource	401
Contents	401
See Also	402
ResourceConfiguration	403
Contents	403
See Also	404
ResourceDiscoveryStatus	405
Contents	405
See Also	406
ResourceTag	407
Contents	407
See Also	407
S3ReportOutput	408
Contents	408
See Also	408
S3ReportOutputConfiguration	409
Contents	409
See Also	409
Service	410
Contents	410
See Also	415
ServiceAchievabilityUpdatedMetadata	416
Contents	416
See Also	416
ServiceCreatedMetadata	418
Contents	418

See Also	418
ServiceDeletedMetadata	419
Contents	419
See Also	419
ServiceEvent	420
Contents	420
See Also	421
ServiceEventDetails	422
Contents	422
See Also	422
ServiceEventMetadata	423
Contents	423
See Also	426
ServiceFunction	427
Contents	427
See Also	429
ServiceFunctionCreatedMetadata	430
Contents	430
See Also	430
ServiceFunctionDeletedMetadata	431
Contents	431
See Also	431
ServiceFunctionResourcesAddedMetadata	432
Contents	432
See Also	432
ServiceFunctionResourcesRemovedMetadata	434
Contents	434
See Also	434
ServiceFunctionUpdatedMetadata	436
Contents	436
See Also	437
ServiceInputSourcesUpdatedMetadata	438
Contents	438
See Also	438
ServicePolicyAssociatedMetadata	439
Contents	439

See Also	439
ServicePolicyDisassociatedMetadata	440
Contents	440
See Also	440
ServiceReference	441
Contents	441
See Also	441
ServiceReferenceChanges	442
Contents	442
See Also	442
ServiceReportConfiguration	443
Contents	443
See Also	443
ServiceResource	444
Contents	444
See Also	444
ServiceResourcesAssociatedMetadata	445
Contents	445
See Also	445
ServiceResourcesDisassociatedMetadata	446
Contents	446
See Also	446
ServiceSummary	447
Contents	447
See Also	450
ServiceSystemAssociatedMetadata	451
Contents	451
See Also	451
ServiceSystemDisassociatedMetadata	452
Contents	452
See Also	452
ServiceTopologyEdgeSummary	454
Contents	454
See Also	455
ServiceWorkflowUpdatedMetadata	456
Contents	456

See Also	456
SloSource	457
Contents	457
See Also	457
StopCondition	459
Contents	459
See Also	459
StringChange	460
Contents	460
See Also	460
SuccessCriteriaAlarmInput	461
Contents	461
See Also	461
SuccessCriteriaAlarmSummary	462
Contents	462
See Also	463
System	464
Contents	464
See Also	466
SystemCreatedMetadata	468
Contents	468
See Also	468
SystemDeletedMetadata	469
Contents	469
See Also	469
SystemEvent	470
Contents	470
See Also	471
SystemEventDetails	472
Contents	472
See Also	472
SystemEventMetadata	473
Contents	473
See Also	474
SystemPolicyAssociatedMetadata	476
Contents	476

See Also	476
SystemPolicyDisassociatedMetadata	477
Contents	477
See Also	477
SystemServiceAssociatedMetadata	478
Contents	478
See Also	478
SystemServiceDisassociatedMetadata	480
Contents	480
See Also	481
SystemSummary	482
Contents	482
See Also	484
SystemUserJourneyCreatedMetadata	485
Contents	485
See Also	485
SystemUserJourneyDeletedMetadata	486
Contents	486
See Also	486
SystemUserJourneyUpdatedMetadata	487
Contents	487
See Also	487
TargetSource	488
Contents	488
See Also	488
Test	490
Contents	490
See Also	492
TestAction	494
Contents	494
See Also	494
TestingRecommendation	495
Contents	495
See Also	495
TestRun	496
Contents	496

See Also	501
TestRunDependencySummary	502
Contents	502
See Also	504
TestRunEvent	505
Contents	505
See Also	506
TestRunObservabilityAlarmSummary	507
Contents	507
See Also	508
TestRunPolicySnapshot	509
Contents	509
See Also	510
TestRunReportConfiguration	511
Contents	511
See Also	511
TestRunSourceEvent	512
Contents	512
See Also	513
TestRunSourceEventDetail	514
Contents	514
See Also	514
TestRunSourceEventError	515
Contents	515
See Also	515
TestRunSourceSummary	516
Contents	516
See Also	516
TestRunSuccessCriteriaAlarmSummary	517
Contents	517
See Also	518
TestRunSummary	519
Contents	519
See Also	521
TestSourceInput	522
Contents	522

See Also	522
TestSourceSummary	523
Contents	523
See Also	523
TestSummary	524
Contents	524
See Also	525
TestTemplate	526
Contents	526
See Also	527
TestTemplateParameter	528
Contents	528
See Also	529
TestTemplateSummary	530
Contents	530
See Also	530
UserJourney	532
Contents	532
See Also	533
UserJourneyChanges	534
Contents	534
See Also	534
UserJourneySummary	535
Contents	535
See Also	536
ValidationExceptionField	537
Contents	537
See Also	537
Common Parameters	538
Common Error Types	541

Welcome

The next generation of AWS Resilience Hub is the single location in AWS where you assess and improve the resilience of your critical applications. It helps Site Reliability Engineers (SREs) and development teams proactively reason about resilience at scale — identifying failure modes, discovering hidden dependencies, and report on progress across the enterprise.

This document was last published on September 15, 2026.

Actions

The following actions are supported:

- [CreateAssertion](#)
- [CreateInputSource](#)
- [CreatePolicy](#)
- [CreateReport](#)
- [CreateService](#)
- [CreateServiceFunction](#)
- [CreateServiceFunctionResources](#)
- [CreateSystem](#)
- [CreateTest](#)
- [CreateUserJourney](#)
- [DeleteAssertion](#)
- [DeleteInputSource](#)
- [DeletePolicy](#)
- [DeleteService](#)
- [DeleteServiceFunction](#)
- [DeleteServiceFunctionResources](#)
- [DeleteSystem](#)
- [DeleteTest](#)
- [DeleteTestSources](#)
- [DeleteUserJourney](#)
- [GetFailureModeFinding](#)
- [GetPolicy](#)
- [GetService](#)
- [GetSystem](#)
- [GetTest](#)
- [GetTestRun](#)
- [GetTestTemplate](#)

- [GetUserJourney](#)
- [ImportApp](#)
- [ImportPolicy](#)
- [ListAssertions](#)
- [ListDependencies](#)
- [ListFailureModeAssessments](#)
- [ListFailureModeFindings](#)
- [ListInputSources](#)
- [ListPolicies](#)
- [ListReports](#)
- [ListResolvedTestRunTargetResources](#)
- [ListResources](#)
- [ListServiceEvents](#)
- [ListServiceFunctions](#)
- [ListServices](#)
- [ListServiceTopologyEdges](#)
- [ListSystemEvents](#)
- [ListSystems](#)
- [ListTagsForResource](#)
- [ListTestRunDependencies](#)
- [ListTestRunEvents](#)
- [ListTestRuns](#)
- [ListTestRunSourceEvents](#)
- [ListTestRunSources](#)
- [ListTests](#)
- [ListTestSources](#)
- [ListTestTemplates](#)
- [ListUserJourneys](#)
- [PutTestSources](#)
- [StartFailureModeAssessment](#)

- [StartTestRun](#)
- [StopTestRun](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateAssertion](#)
- [UpdateDependency](#)
- [UpdateFailureModeFinding](#)
- [UpdatePolicy](#)
- [UpdateService](#)
- [UpdateServiceFunction](#)
- [UpdateSystem](#)
- [UpdateTest](#)
- [UpdateUserJourney](#)

CreateAssertion

Creates a resilience assertion for a service.

Request Syntax

```
POST /v2/create-assertion HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "serviceArn": "string",
  "text": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

Idempotency token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: [A-Za-z0-9_.-]{0,63}

Required: No

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

text

The text content of the assertion.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "assertion": {
    "assertionId": "string",
    "createdAt": number,
    "serviceArn": "string",
    "source": "string",
    "text": "string",
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assertion

The created assertion.

Type: [Assertion](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ServiceQuotaExceededException

Service quota exceeded.

HTTP Status Code: 402

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateInputSource

Creates an input source for a service.

Request Syntax

```
POST /v2/create-input-source HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "resourceConfiguration": { ... },
  "serviceArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

Idempotency token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: [A-Za-z0-9_.-]{0,63}

Required: No

resourceConfiguration

Resource configuration for an input source. Provide exactly one field.

Type: [ResourceConfiguration](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "inputSourceId": "string",
  "serviceArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

inputSourceId

The unique identifier assigned to the created input source.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `\S{1,255}`

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerErrorException

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ServiceQuotaExceededException

Service quota exceeded.

HTTP Status Code: 402

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreatePolicy

Creates a resilience policy that defines availability and disaster recovery requirements.

Request Syntax

```
POST /v2/create-policy HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "availabilitySlo": {
    "target": number
  },
  "clientToken": "string",
  "dataRecovery": {
    "timeBetweenBackupsInMinutes": number
  },
  "description": "string",
  "kmsKeyId": "string",
  "multiAz": {
    "disasterRecoveryApproach": "string",
    "rpoInMinutes": number,
    "rtoInMinutes": number
  },
  "multiRegion": {
    "disasterRecoveryApproach": "string",
    "rpoInMinutes": number,
    "rtoInMinutes": number
  },
  "name": "string",
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

availabilitySlo

The availability SLO for the resilience policy.

Type: [AvailabilitySlo](#) object

Required: No

clientToken

Idempotency token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: [A-Za-z0-9_.-]{0,63}

Required: No

dataRecovery

The data recovery targets for the resilience policy.

Type: [DataRecoveryTargets](#) object

Required: No

description

Resource description for services and policies.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 615.

Required: No

kmsKeyId

KMS key identifier — accepts key ID, key ARN, alias name, or alias ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

multiAz

The multi-AZ disaster recovery targets for the resilience policy.

Type: [MultiAzTargets](#) object

Required: No

multiRegion

The multi-Region disaster recovery targets for the resilience policy.

Type: [MultiRegionTargets](#) object

Required: No

name

Resource name (used in ARN — no spaces allowed).

Type: String

Length Constraints: Minimum length of 2. Maximum length of 60.

Pattern: `[A-Za-z0-9][A-Za-z0-9_\-]{1,59}`

Required: Yes

tags

Resource tags.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `[\x00-\x1f\x22]+`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `[\x00-\x1f\x22]*`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "policy": {
    "associatedServiceCount": number,
    "availabilitySlo": {
      "target": number
    },
    "createdAt": number,
    "dataRecovery": {
      "timeBetweenBackupsInMinutes": number
    },
    "description": "string",
    "kmsKeyId": "string",
    "multiAz": {
      "disasterRecoveryApproach": "string",
      "rpoInMinutes": number,
      "rtoInMinutes": number
    },
    "multiRegion": {
      "disasterRecoveryApproach": "string",
      "rpoInMinutes": number,
      "rtoInMinutes": number
    },
    "name": "string",
    "policyArn": "string",
    "tags": {
      "string" : "string"
    },
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[policy](#)

The created resilience policy.

Type: [Policy](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ServiceQuotaExceededException

Service quota exceeded.

HTTP Status Code: 402

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateReport

On-demand report creation. Idempotent — duplicate requests with same clientToken return existing result.

Request Syntax

```
POST /v2/create-report HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "reportType": "string",
  "serviceArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

Idempotency token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: [A-Za-z0-9_.--]{0,63}

Required: No

reportType

The type of report to generate.

Type: String

Valid Values: FAILURE_MODE | TESTING

Required: Yes

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "reportGenerationResult": {
    "assessmentId": "string",
    "createdAt": number,
    "reportOutput": { ... },
    "reportType": "string",
    "serviceArn": "string",
    "status": "string",
    "testRunId": "string",
    "testTemplateArn": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

reportGenerationResult

The result of the report generation request.

Type: [ReportGenerationResult](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ThrottlingException

Too many requests — rate limit exceeded.

retryAfterSeconds

The number of seconds to wait before retrying the request.

HTTP Status Code: 429

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateService

Creates a service.

Request Syntax

POST /v2/create-service HTTP/1.1

Content-type: application/json

```
{
  "associatedSystems": [
    {
      "systemArn": "string",
      "systemName": "string",
      "userJourneyIds": [ "string" ]
    }
  ],
  "clientToken": "string",
  "dependencyDiscovery": "string",
  "description": "string",
  "kmsKeyId": "string",
  "name": "string",
  "permissionModel": {
    "crossAccountRoles": [
      {
        "crossAccountRoleArn": "string",
        "externalId": "string"
      }
    ],
    "invokerRoleName": "string"
  },
  "policyArn": "string",
  "regions": [ "string" ],
  "reportConfiguration": {
    "reportOutputs": [
      { ... }
    ]
  },
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

associatedSystems

The systems to associate with the service.

Type: Array of [AssociatedSystem](#) objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: No

clientToken

Idempotency token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: [A-Za-z0-9_.-]{0,63}

Required: No

dependencyDiscovery

Caller-settable values for dependency discovery. INITIALIZING is system-managed.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

description

Resource description for services and policies.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 615.

Required: No

kmsKeyId

KMS key identifier — accepts key ID, key ARN, alias name, or alias ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

name

Resource name (used in ARN — no spaces allowed).

Type: String

Length Constraints: Minimum length of 2. Maximum length of 60.

Pattern: `[A-Za-z0-9][A-Za-z0-9_\-]{1,59}`

Required: Yes

permissionModel

The permission model for the service.

Type: [PermissionModel](#) object

Required: Yes

policyArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: No

regions

The Regions where the service operates.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 6.

Pattern: `[a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]`

Required: Yes

reportConfiguration

Configuration for automatic report generation on a Service.

Type: [ServiceReportConfiguration](#) object

Required: No

tags

Resource tags.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `[^\x00-\x1f\x22]+`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `[^\x00-\x1f\x22]*`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "service": {
    "accountId": "string",
    "achievability": {
      "availabilitySlo": "string",
```

```
    "dataRecoveryTimeBetweenBackups": "string",
    "multiAzRtoRpo": "string",
    "multiRegionRtoRpo": "string"
  },
  "assessmentStatus": "string",
  "associatedSystems": [
    {
      "systemArn": "string",
      "systemName": "string",
      "userJourneyIds": [ "string" ]
    }
  ],
  "createdAt": number,
  "dependencyDiscovery": {
    "eligibleResourceCount": number,
    "message": "string",
    "status": "string",
    "updatedAt": number
  },
  "description": "string",
  "effectivePolicyValues": {
    "availabilitySlo": {
      "policyName": "string",
      "source": "string",
      "value": number
    },
    "dataRecoveryTimeBetweenBackups": {
      "policyName": "string",
      "source": "string",
      "value": number
    },
    "multiAzDrApproach": {
      "policyName": "string",
      "source": "string",
      "value": "string"
    },
    "multiAzRpo": {
      "policyName": "string",
      "source": "string",
      "value": number
    },
    "multiAzRto": {
      "policyName": "string",
      "source": "string",
```

```
    "value": number
  },
  "multiRegionDrApproach": {
    "policyName": "string",
    "source": "string",
    "value": "string"
  },
  "multiRegionRpo": {
    "policyName": "string",
    "source": "string",
    "value": number
  },
  "multiRegionRto": {
    "policyName": "string",
    "source": "string",
    "value": number
  }
},
"estimatedAssessmentCost": {
  "amount": number,
  "currency": "string"
},
"kmsKeyId": "string",
"name": "string",
"openFindingsCount": number,
"organizationId": "string",
"ouId": "string",
"permissionModel": {
  "crossAccountRoles": [
    {
      "crossAccountRoleArn": "string",
      "externalId": "string"
    }
  ],
  "invokerRoleName": "string"
},
"policyArn": "string",
"regions": [ "string" ],
"reportConfiguration": {
  "reportOutputs": [
    { ... }
  ]
},
"rerunAssessment": boolean,
```

```
"resolvedFindingsCount": number,
"resourceDiscovery": {
  "errorCode": "string",
  "errorMessage": "string",
  "lastRunAt": number,
  "status": "string"
},
"serviceArn": "string",
"tags": {
  "string" : "string"
},
"updatedAt": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

service

The created service.

Type: [Service](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerErrorException

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ServiceQuotaExceededException

Service quota exceeded.

HTTP Status Code: 402

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateServiceFunction

Creates a service function within a service.

Request Syntax

```
POST /v2/create-service-function HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "criticality": "string",
  "description": "string",
  "name": "string",
  "serviceArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

Idempotency token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: [A-Za-z0-9_.-]{0,63}

Required: No

criticality

The criticality level of the service function.

Type: String

Valid Values: PRIMARY | SUPPLEMENTAL

Required: Yes

description

Resource description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

name

Entity label (not part of ARN — spaces allowed).

Type: String

Length Constraints: Minimum length of 2. Maximum length of 60.

Pattern: `[A-Za-z0-9][A-Za-z0-9 _\-]{1,59}`

Required: Yes

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1})-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "serviceFunction": {
    "createdAt": number,
    "criticality": "string",
    "description": "string",
    "name": "string",
    "resourceCount": number,
    "serviceArn": "string",
    "serviceFunctionId": "string",
    "source": "string",
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

serviceFunction

The created service function.

Type: [ServiceFunction](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerErrorException

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ServiceQuotaExceededException

Service quota exceeded.

HTTP Status Code: 402

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateServiceFunctionResources

Associates resources with a service function.

Request Syntax

```
POST /v2/create-service-function-resources HTTP/1.1
Content-type: application/json
```

```
{
  "resources": [ "string" ],
  "serviceArn": "string",
  "serviceFunctionId": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

resources

The list of resources to associate with the service function.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: Yes

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

serviceFunctionId

The identifier of the service function to associate resources with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `\S{1,255}`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "resources": [ "string" ],
  "serviceArn": "string",
  "serviceFunctionId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

resources

The list of resources that were associated.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

serviceFunctionId

The identifier of the service function.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `\S{1,255}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerErrorException

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)

- [AWS SDK for Ruby V3](#)

CreateSystem

Creates a system that represents a logical grouping of services.

Request Syntax

```
POST /v2/create-system HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "description": "string",
  "kmsKeyId": "string",
  "name": "string",
  "sharingEnabled": boolean,
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

Idempotency token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: [A-Za-z0-9_.-]{0,63}

Required: No

description

Resource description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

kmsKeyId

KMS key identifier — accepts key ID, key ARN, alias name, or alias ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

name

Resource name (used in ARN — no spaces allowed).

Type: String

Length Constraints: Minimum length of 2. Maximum length of 60.

Pattern: `[A-Za-z0-9][A-Za-z0-9_\-]{1,59}`

Required: Yes

sharingEnabled

Indicates whether cross-account sharing is enabled for the system.

Type: Boolean

Required: No

tags

Resource tags.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `[^\x00-\x1f\x22]+`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `[^\x00-\x1f\x22]*`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "system": {
    "createdAt": number,
    "description": "string",
    "kmsKeyId": "string",
    "name": "string",
    "organizationId": "string",
    "ouId": "string",
    "sharingEnabled": boolean,
    "systemArn": "string",
    "systemId": "string",
    "tags": {
      "string" : "string"
    },
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

system

The created system.

Type: [System](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ServiceQuotaExceededException

Service quota exceeded.

HTTP Status Code: 402

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateTest

Creates a test for a service by configuring a test template. Each service has one test per template.

Request Syntax

```
POST /v2/create-test HTTP/1.1
Content-type: application/json

{
  "loggingConfiguration": {
    "cloudWatchLogGroupArn": "string",
    "logSchemaVersion": "string",
    "s3BucketName": "string"
  },
  "parameters": {
    "string" : [ "string" ]
  },
  "roleName": "string",
  "serviceArn": "string",
  "stopConditions": [
    {
      "source": "string",
      "value": "string"
    }
  ],
  "testTemplateArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

loggingConfiguration

The logging configuration for the test.

Type: [LoggingConfiguration](#) object

Required: No

parameters

The parameter values for the test.

Type: String to array of strings map

Map Entries: Minimum number of 0 items. Maximum number of 20 items.

Key Length Constraints: Minimum length of 1. Maximum length of 256.

Key Pattern: `[\w.-]+`

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

roleName

The name of the IAM execution role to use when running the test.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 576.

Pattern: `([A-Za-z0-9_+=,.\@-]+/)*[A-Za-z0-9_+=,.\@-]+`

Required: No

serviceArn

The ARN of the service to create the test for.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

stopConditions

The stop conditions for the test.

Type: Array of [StopCondition](#) objects

Required: No

testTemplateArn

The ARN of the test template to configure.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):([0-9]{12}|aws):[A-Za-z0-9/] [A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "test": {
    "actions": [
      {
        "actionId": "string",
        "description": "string",
        "resourceType": "string"
      }
    ],
    "creationTime": number,
    "loggingConfiguration": {
      "cloudWatchLogGroupArn": "string",
      "logSchemaVersion": "string",
      "s3BucketName": "string"
    },
    "name": "string",
```

```
"parameters": {
  "string": [ "string" ]
},
"roleName": "string",
"serviceArn": "string",
"stopConditions": [
  {
    "source": "string",
    "value": "string"
  }
],
"successfulTestRuns": number,
"testId": "string",
"testTemplateArn": "string",
"totalTestRuns": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

test

The created test.

Type: [Test](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerErrorException

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateUserJourney

Creates a user journey within a system.

Request Syntax

```
POST /v2/create-user-journey HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "description": "string",
  "name": "string",
  "policyArn": "string",
  "systemArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[clientToken](#)

Idempotency token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: [A-Za-z0-9_.-]{0,63}

Required: No

[description](#)

Resource description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

name

Entity label (not part of ARN — spaces allowed).

Type: String

Length Constraints: Minimum length of 2. Maximum length of 60.

Pattern: `[A-Za-z0-9][A-Za-z0-9 _\-]{1,59}`

Required: Yes

policyArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: No

systemArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "userJourney": {
    "createdAt": number,
    "description": "string",
    "name": "string",
    "policyArn": "string",
    "updatedAt": number,
    "userJourneyId": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

userJourney

The created user journey.

Type: [UserJourney](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerErrorException

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ServiceQuotaExceededException

Service quota exceeded.

HTTP Status Code: 402

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteAssertion

Deletes a resilience assertion from a service.

Request Syntax

```
POST /v2/delete-assertion HTTP/1.1
Content-type: application/json
```

```
{
  "assertionId": "string",
  "serviceArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[assertionId](#)

The unique identifier of the assertion to delete.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-5][0-9a-f]{3}-[089ab][0-9a-f]{3}-[0-9a-f]{12}`

Required: Yes

[serviceArn](#)

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "assertionId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[assertionId](#)

The unique identifier of the deleted assertion.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-5][0-9a-f]{3}-[089ab][0-9a-f]{3}-[0-9a-f]{12}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerErrorException

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteInputSource

Deletes an input source.

Request Syntax

```
POST /v2/delete-input-source HTTP/1.1
Content-type: application/json
```

```
{
  "inputSourceId": "string",
  "serviceArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[inputSourceId](#)

The identifier of the input source to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `\S{1,255}`

Required: Yes

[serviceArn](#)

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "inputSourceId": "string",
  "serviceArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[inputSourceId](#)

The identifier of the deleted input source.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `\S{1,255}`

[serviceArn](#)

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerErrorException

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeletePolicy

Deletes a resilience policy.

Request Syntax

```
POST /v2/delete-policy HTTP/1.1
Content-type: application/json
```

```
{
  "policyArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

policyArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{  
  "policyArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[policyArn](#)

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)

- [AWS SDK for Ruby V3](#)

DeleteService

Deletes a service.

Request Syntax

```
POST /v2/delete-service HTTP/1.1
Content-type: application/json
```

```
{
  "serviceArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{  
  "serviceArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)

- [AWS SDK for Ruby V3](#)

DeleteServiceFunction

Deletes a service function.

Request Syntax

```
POST /v2/delete-function HTTP/1.1
Content-type: application/json

{
  "serviceArn": "string",
  "serviceFunctionId": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[serviceArn](#)

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_.-]{0,1023}`

Required: Yes

[serviceFunctionId](#)

The identifier of the service function to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: \S{1,255}

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "serviceFunctionId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[serviceFunctionId](#)

The identifier of the deleted service function.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: \S{1,255}

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteServiceFunctionResources

Removes resources from a service function.

Request Syntax

```
POST /v2/delete-service-function-resources HTTP/1.1
Content-type: application/json
```

```
{
  "resources": [ "string" ],
  "serviceArn": "string",
  "serviceFunctionId": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

resources

The list of resources to remove from the service function.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: Yes

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

serviceFunctionId

The identifier of the service function to remove resources from.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `\S{1,255}`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "resources": [ "string" ],
  "serviceArn": "string",
  "serviceFunctionId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

resources

The list of resources that were removed.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

serviceFunctionId

The identifier of the service function.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `\S{1,255}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerErrorException

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)

- [AWS SDK for Ruby V3](#)

DeleteSystem

Deletes a system.

Request Syntax

```
POST /v2/delete-system HTTP/1.1
Content-type: application/json
```

```
{
  "systemArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

systemArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{  
  "systemArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

systemArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)

- [AWS SDK for Ruby V3](#)

DeleteTest

Deletes a test.

Request Syntax

```
POST /v2/delete-test HTTP/1.1
Content-type: application/json

{
  "serviceArn": "string",
  "testId": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

serviceArn

The ARN of the service the test belongs to.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_.-]{0,1023}`

Required: Yes

testId

The identifier of the test to delete.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "testId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

testId

The identifier of the deleted test.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerErrorException

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteTestSources

Removes monitoring sources from a test. The operation is transactional and idempotent — removing a source that is not attached is a no-op.

Request Syntax

```
POST /v2/delete-test-sources HTTP/1.1
Content-type: application/json
```

```
{
  "serviceArn": "string",
  "testId": "string",
  "testSources": [
    { ... }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

serviceArn

The ARN of the service the test belongs to.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

testId

The identifier of the test to remove sources from.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

[testSources](#)

The monitoring sources to remove.

Type: Array of [TestSourceInput](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteUserJourney

Deletes a user journey.

Request Syntax

```
POST /v2/delete-user-journey HTTP/1.1
Content-type: application/json
```

```
{
  "systemArn": "string",
  "userJourneyId": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

systemArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

userJourneyId

The identifier of the user journey to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: \S{1,255}

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "userJourneyId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[userJourneyId](#)

The identifier of the deleted user journey.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: \S{1,255}

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetFailureModeFinding

Retrieves a finding by findingId.

Request Syntax

```
GET /v2/get-failure-mode-finding?findingId=findingId&serviceArn=serviceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

findingId

The unique identifier of the finding to retrieve.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-5][0-9a-f]{3}-[089ab][0-9a-f]{3}-[0-9a-f]{12}`

Required: Yes

serviceArn

ARN identifier.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/.-]{0,1023}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Content-type: application/json

```
{
  "finding": {
    "comment": "string",
    "description": "string",
    "failureCategory": "string",
    "findingId": "string",
    "infrastructureAndCodeRecommendations": [
      {
        "suggestedChanges": [ "string" ]
      }
    ],
    "name": "string",
    "observabilityRecommendations": [
      {
        "suggestedChanges": [ "string" ]
      }
    ],
    "policyComponent": "string",
    "reasoning": "string",
    "serviceFunctions": [ "string" ],
    "severity": "string",
    "status": "string",
    "testingRecommendations": [
      {
        "suggestedChanges": [ "string" ]
      }
    ],
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[finding](#)

The requested finding.

Type: [Finding](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerErrorException

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetPolicy

Retrieves a resilience policy by ARN.

Request Syntax

```
GET /v2/get-policy?policyArn=policyArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

policyArn

ARN identifier.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "policy": {
    "associatedServiceCount": number,
    "availabilitySlo": {
      "target": number
    },
    "createdAt": number,
    "dataRecovery": {
```

```
    "timeBetweenBackupsInMinutes": number
  },
  "description": "string",
  "kmsKeyId": "string",
  "multiAz": {
    "disasterRecoveryApproach": "string",
    "rpoInMinutes": number,
    "rtoInMinutes": number
  },
  "multiRegion": {
    "disasterRecoveryApproach": "string",
    "rpoInMinutes": number,
    "rtoInMinutes": number
  },
  "name": "string",
  "policyArn": "string",
  "tags": {
    "string" : "string"
  },
  "updatedAt": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[policy](#)

The requested resilience policy.

Type: [Policy](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerErrorException

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetService

Retrieves a service by ARN.

Request Syntax

```
GET /v2/get-service?serviceArn=serviceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

serviceArn

ARN identifier.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "service": {
    "accountId": "string",
    "achievability": {
      "availabilitySlo": "string",
      "dataRecoveryTimeBetweenBackups": "string",
      "multiAzRtoRpo": "string",
      "multiRegionRtoRpo": "string"
    }
  }
}
```

```
},
  "assessmentStatus": "string",
  "associatedSystems": [
    {
      "systemArn": "string",
      "systemName": "string",
      "userJourneyIds": [ "string" ]
    }
  ],
  "createdAt": number,
  "dependencyDiscovery": {
    "eligibleResourceCount": number,
    "message": "string",
    "status": "string",
    "updatedAt": number
  },
  "description": "string",
  "effectivePolicyValues": {
    "availabilitySlo": {
      "policyName": "string",
      "source": "string",
      "value": number
    },
    "dataRecoveryTimeBetweenBackups": {
      "policyName": "string",
      "source": "string",
      "value": number
    },
    "multiAzDrApproach": {
      "policyName": "string",
      "source": "string",
      "value": "string"
    },
    "multiAzRpo": {
      "policyName": "string",
      "source": "string",
      "value": number
    },
    "multiAzRto": {
      "policyName": "string",
      "source": "string",
      "value": number
    },
    "multiRegionDrApproach": {
```

```
    "policyName": "string",
    "source": "string",
    "value": "string"
  },
  "multiRegionRpo": {
    "policyName": "string",
    "source": "string",
    "value": number
  },
  "multiRegionRto": {
    "policyName": "string",
    "source": "string",
    "value": number
  }
},
"estimatedAssessmentCost": {
  "amount": number,
  "currency": "string"
},
"kmsKeyId": "string",
"name": "string",
"openFindingsCount": number,
"organizationId": "string",
"ouId": "string",
"permissionModel": {
  "crossAccountRoles": [
    {
      "crossAccountRoleArn": "string",
      "externalId": "string"
    }
  ],
  "invokerRoleName": "string"
},
"policyArn": "string",
"regions": [ "string" ],
"reportConfiguration": {
  "reportOutputs": [
    { ... }
  ]
},
"rerunAssessment": boolean,
"resolvedFindingsCount": number,
"resourceDiscovery": {
  "errorCode": "string",
```

```
    "errorMessage": "string",
    "lastRunAt": number,
    "status": "string"
  },
  "serviceArn": "string",
  "tags": {
    "string" : "string"
  },
  "updatedAt": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

service

The requested service.

Type: [Service](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetSystem

Retrieves a system by ARN.

Request Syntax

```
GET /v2/get-system?systemArn=systemArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

systemArn

ARN identifier.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/.-]{0,1023}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "system": {
    "createdAt": number,
    "description": "string",
    "kmsKeyId": "string",
    "name": "string",
```

```
"organizationId": "string",
"ouId": "string",
"sharingEnabled": boolean,
"systemArn": "string",
"systemId": "string",
"tags": {
  "string" : "string"
},
"updatedAt": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

system

The requested system.

Type: [System](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetTest

Retrieves a test by ID.

Request Syntax

```
GET /v2/get-test?serviceArn=serviceArn&testId=testId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

serviceArn

The ARN of the service the test belongs to.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

testId

The identifier of the test to retrieve.

Length Constraints: Minimum length of 1.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "test": {
    "actions": [
      {
        "actionId": "string",
        "description": "string",
        "resourceType": "string"
      }
    ],
    "creationTime": number,
    "loggingConfiguration": {
      "cloudWatchLogGroupArn": "string",
      "logSchemaVersion": "string",
      "s3BucketName": "string"
    },
    "name": "string",
    "parameters": {
      "string" : [ "string" ]
    },
    "roleName": "string",
    "serviceArn": "string",
    "stopConditions": [
      {
        "source": "string",
        "value": "string"
      }
    ],
    "successfulTestRuns": number,
    "testId": "string",
    "testTemplateArn": "string",
    "totalTestRuns": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

test

The requested test.

Type: [Test](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetTestRun

Retrieves a test run by ID, including its status, results, and the configuration snapshotted when the run started.

Request Syntax

```
GET /v2/get-test-run?serviceArn=serviceArn&testRunId=testRunId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

serviceArn

The ARN of the service the test run belongs to.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

testRunId

The identifier of the test run to retrieve.

Length Constraints: Minimum length of 1.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "testRun": {
    "accountTargeting": "string",
    "endedAt": number,
    "errorMessage": "string",
    "eventCount": number,
    "experiments": [
      {
        "details": "string",
        "experimentArn": "string"
      }
    ],
    "loggingConfiguration": {
      "cloudWatchLogGroupArn": "string",
      "logSchemaVersion": "string",
      "s3BucketName": "string"
    },
    "parameters": {
      "string" : [ "string" ]
    },
    "permissionModel": {
      "crossAccountRoles": [
        {
          "crossAccountRoleArn": "string",
          "externalId": "string"
        }
      ],
      "invokerRoleName": "string"
    },
    "policy": {
      "availabilitySlo": {
        "target": number
      },
      "dataRecovery": {
        "timeBetweenBackupsInMinutes": number
      },
      "multiAz": {
        "disasterRecoveryApproach": "string",
        "rpoInMinutes": number,
        "rtoInMinutes": number
      },
      "multiRegion": {
        "disasterRecoveryApproach": "string",
        "rpoInMinutes": number,
```

```

        "rtoInMinutes": number
      },
      "name": "string",
      "policyArn": "string"
    },
    "regions": [ "string" ],
    "regionSwitchExecutionId": "string",
    "regionSwitchPlanArn": "string",
    "reportConfiguration": {
      "reportOutput": [
        { ... }
      ]
    },
    "reportOutput": {
      "assessmentId": "string",
      "createdAt": number,
      "reportOutput": { ... },
      "reportType": "string",
      "serviceArn": "string",
      "status": "string",
      "testRunId": "string",
      "testTemplateArn": "string"
    },
    "roleName": "string",
    "serviceArn": "string",
    "startedAt": number,
    "status": "string",
    "stopConditions": [
      {
        "source": "string",
        "value": "string"
      }
    ],
    "testId": "string",
    "testRunId": "string",
    "testTemplateArn": "string"
  }
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

testRun

The requested test run.

Type: [TestRun](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetTestTemplate

Retrieves a resilience test template by ARN, including the parameters it accepts and the fault actions it runs.

Request Syntax

```
GET /v2/get-test-template?testTemplateArn=testTemplateArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

testTemplateArn

The ARN of the test template to retrieve.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):([0-9]{12}|aws):[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "testTemplate": {
    "actions": [
      {
        "actionId": "string",
        "description": "string",
        "resourceType": "string"
      }
    ]
  }
}
```

```
    }
  ],
  "description": "string",
  "name": "string",
  "parameters": [
    {
      "defaultValue": "string",
      "description": "string",
      "maxValues": number,
      "name": "string",
      "required": boolean,
      "type": "string"
    }
  ],
  "testTemplateArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

testTemplate

The requested test template.

Type: [TestTemplate](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetUserJourney

Retrieves a user journey.

Request Syntax

```
GET /v2/get-user-journey?systemArn=systemArn&userJourneyId=userJourneyId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

systemArn

ARN identifier.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

userJourneyId

The identifier of the user journey to retrieve.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `\S{1,255}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "userJourney": {
    "createdAt": number,
    "description": "string",
    "name": "string",
    "policyArn": "string",
    "updatedAt": number,
    "userJourneyId": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

userJourney

The requested user journey.

Type: [UserJourney](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ImportApp

Imports a V1 app into the V2 resource model, creating a service with the same name.

Request Syntax

```
POST /v2/import-app HTTP/1.1
Content-type: application/json

{
  "associatedSystems": [
    {
      "systemArn": "string",
      "systemName": "string",
      "userJourneyIds": [ "string" ]
    }
  ],
  "clientToken": "string",
  "kmsKeyId": "string",
  "policyArn": "string",
  "skipManuallyAddedResources": boolean,
  "tags": {
    "string" : "string"
  },
  "v1AppArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

associatedSystems

The systems to associate with the imported service.

Type: Array of [AssociatedSystem](#) objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: No

clientToken

Idempotency token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `[A-Za-z0-9_.-]{0,63}`

Required: No

kmsKeyId

KMS key identifier — accepts key ID, key ARN, alias name, or alias ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

policyArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: No

skipManuallyAddedResources

Whether to skip manually added resources during import.

Type: Boolean

Required: No

tags

Resource tags.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `[^\x00-\x1f\x22]+`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `[^\x00-\x1f\x22]*`

Required: No

[v1AppArn](#)

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "service": {
    "accountId": "string",
    "achievability": {
      "availabilitySlo": "string",
      "dataRecoveryTimeBetweenBackups": "string",
      "multiAzRtoRpo": "string",
      "multiRegionRtoRpo": "string"
    },
    "assessmentStatus": "string",
    "associatedSystems": [
```

```
{
  "systemArn": "string",
  "systemName": "string",
  "userJourneyIds": [ "string" ]
},
"createdAt": number,
"dependencyDiscovery": {
  "eligibleResourceCount": number,
  "message": "string",
  "status": "string",
  "updatedAt": number
},
"description": "string",
"effectivePolicyValues": {
  "availabilitySlo": {
    "policyName": "string",
    "source": "string",
    "value": number
  },
  "dataRecoveryTimeBetweenBackups": {
    "policyName": "string",
    "source": "string",
    "value": number
  },
  "multiAzDrApproach": {
    "policyName": "string",
    "source": "string",
    "value": "string"
  },
  "multiAzRpo": {
    "policyName": "string",
    "source": "string",
    "value": number
  },
  "multiAzRto": {
    "policyName": "string",
    "source": "string",
    "value": number
  },
  "multiRegionDrApproach": {
    "policyName": "string",
    "source": "string",
    "value": "string"
  }
}
```

```

    },
    "multiRegionRpo": {
      "policyName": "string",
      "source": "string",
      "value": number
    },
    "multiRegionRto": {
      "policyName": "string",
      "source": "string",
      "value": number
    }
  },
  "estimatedAssessmentCost": {
    "amount": number,
    "currency": "string"
  },
  "kmsKeyId": "string",
  "name": "string",
  "openFindingsCount": number,
  "organizationId": "string",
  "ouId": "string",
  "permissionModel": {
    "crossAccountRoles": [
      {
        "crossAccountRoleArn": "string",
        "externalId": "string"
      }
    ],
    "invokerRoleName": "string"
  },
  "policyArn": "string",
  "regions": [ "string" ],
  "reportConfiguration": {
    "reportOutputs": [
      { ... }
    ]
  },
  "rerunAssessment": boolean,
  "resolvedFindingsCount": number,
  "resourceDiscovery": {
    "errorCode": "string",
    "errorMessage": "string",
    "lastRunAt": number,
    "status": "string"
  }
}

```

```
    },  
    "serviceArn": "string",  
    "tags": {  
        "string" : "string"  
    },  
    "updatedAt": number  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

service

The imported service.

Type: [Service](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)

- [AWS SDK for Ruby V3](#)

ImportPolicy

Imports a V1 policy into V2, mapping RTO/RPO values from V1 scenarios.

Request Syntax

```
POST /v2/import-policy HTTP/1.1
Content-type: application/json

{
  "availabilitySlo": {
    "target": number
  },
  "clientToken": "string",
  "kmsKeyId": "string",
  "multiAzDisasterRecoveryApproach": "string",
  "multiRegionDisasterRecoveryApproach": "string",
  "tags": {
    "string" : "string"
  },
  "v1PolicyArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

availabilitySlo

The availability SLO to set on the imported policy.

Type: [AvailabilitySlo](#) object

Required: No

clientToken

Idempotency token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `[A-Za-z0-9_.-]{0,63}`

Required: No

[kmsKeyId](#)

KMS key identifier — accepts key ID, key ARN, alias name, or alias ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

[multiAzDisasterRecoveryApproach](#)

The multi-AZ disaster recovery approach for the imported policy.

Type: String

Valid Values: ACTIVE_ACTIVE | HOT_STANDBY | WARM_STANDBY | PILOT_LIGHT |
BACKUP_AND_RESTORE

Required: No

[multiRegionDisasterRecoveryApproach](#)

The multi-Region disaster recovery approach for the imported policy.

Type: String

Valid Values: ACTIVE_ACTIVE | HOT_STANDBY | WARM_STANDBY | PILOT_LIGHT |
BACKUP_AND_RESTORE

Required: No

[tags](#)

Resource tags.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `[^\x00-\x1f\x22]+`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `[^\x00-\x1f\x22]*`

Required: No

[v1PolicyArn](#)

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "policy": {
    "associatedServiceCount": number,
    "availabilitySlo": {
      "target": number
    },
    "createdAt": number,
    "dataRecovery": {
      "timeBetweenBackupsInMinutes": number
    },
    "description": "string",
    "kmsKeyId": "string",
    "multiAz": {
```

```
    "disasterRecoveryApproach": "string",
    "rpoInMinutes": number,
    "rtoInMinutes": number
  },
  "multiRegion": {
    "disasterRecoveryApproach": "string",
    "rpoInMinutes": number,
    "rtoInMinutes": number
  },
  "name": "string",
  "policyArn": "string",
  "tags": {
    "string" : "string"
  },
  "updatedAt": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[policy](#)

The imported policy.

Type: [Policy](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerErrorException

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListAssertions

Lists resilience assertions for a service.

Request Syntax

```
GET /v2/list-assertions?
maxResults=maxResults&nextToken=nextToken&serviceArn=serviceArn&source=source HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

Pagination page size.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

Pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

serviceArn

ARN identifier.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1})-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

source

Filter assertions by source type.

Valid Values: AI_GENERATED | USER

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "assertions": [
    {
      "assertionId": "string",
      "createdAt": number,
      "serviceArn": "string",
      "source": "string",
      "text": "string",
      "updatedAt": number
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assertions

The list of assertions.

Type: Array of [Assertion](#) objects

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListDependencies

Lists dependencies discovered for services.

Request Syntax

```
GET /v2/list-dependencies?  
maxResults=maxResults&nextToken=nextToken&queryRangeEndTime=queryRangeEndTime&queryRangeGranula  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[maxResults](#)

Pagination page size.

Valid Range: Minimum value of 1. Maximum value of 100.

[nextToken](#)

Pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: $\backslash S\{1,2000\}$

[queryRangeEndTime](#)

The end time for the dependency query range.

[queryRangeGranularity](#)

The granularity for the dependency query range.

Valid Values: HOURLY | DAILY

[queryRangeStartTime](#)

The start time for the dependency query range.

[serviceArn](#)

ARN identifier.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "dependencySummaries": [
    {
      "comment": "string",
      "criticality": "string",
      "dependencyId": "string",
      "dependencyName": "string",
      "dnsName": "string",
      "lastDetectedTime": number,
      "location": "string",
      "provider": "string",
      "queryRange": {
        "dataPoints": [
          {
            "queryCount": number,
            "timestamp": number
          }
        ],
        "endTime": number,
        "granularity": "string",
        "startTime": number
      },
      "serviceArn": "string",
      "sourceRegions": [ "string" ]
    }
  ],
  "nextToken": "string"
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[dependencySummaries](#)

The list of dependency summaries.

Type: Array of [DependencySummary](#) objects

[nextToken](#)

Pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListFailureModeAssessments

Lists failure mode assessments.

Request Syntax

```
GET /v2/list-failure-mode-assessments?  
assessmentStatuses=assessmentStatuses&endedBefore=endedBefore&maxResults=maxResults&nextToken=nextToken  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

assessmentStatuses

Specifies the assessment statuses to include in the results.

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Valid Values: NOT_STARTED | PENDING | IN_PROGRESS | FAILED | SUCCESS

endedBefore

Specifies that only assessments that ended at or before this timestamp appear in the results.

maxResults

Pagination page size.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

Pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: $\backslash S\{1,2000\}$

serviceArn

ARN identifier.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

[sortBy](#)

The field to use for sorting failure mode assessments.

Valid Values: STARTED_AT

[sortOrder](#)

The sort order for results.

Valid Values: ASC | DESC

[startedAfter](#)

Specifies that only assessments that started at or after this timestamp appear in the results.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "assessmentSummaries": [
    {
      "achievability": {
        "availabilitySlo": "string",
        "dataRecoveryTimeBetweenBackups": "string",
        "multiAzRtoRpo": "string",
        "multiRegionRtoRpo": "string"
      },
      "assessmentCost": {
```

```
    "amount": number,
    "currency": "string"
  },
  "assessmentId": "string",
  "assessmentStatus": "string",
  "assessmentStep": "string",
  "billableAssessmentUnitCount": number,
  "endedAt": number,
  "errorCode": "string",
  "errorMessage": "string",
  "serviceArn": "string",
  "startedAt": number,
  "totalFindings": number
}
],
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentSummaries

The list of assessment summaries.

Type: Array of [AssessmentSummary](#) objects

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListFailureModeFindings

List findings.

Request Syntax

```
GET /v2/list-failure-mode-findings?  
failureCategory=failureCategory&maxResults=maxResults&nextToken=nextToken&serviceArn=serviceArn  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

failureCategory

Filter findings by failure category.

Valid Values: SHARED_FATE | EXCESSIVE_LOAD | EXCESSIVE_LATENCY |
MISCONFIGURATION_AND_BUGS | SINGLE_POINT_OF_FAILURE

maxResults

Pagination page size.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

Pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: \S{1,2000}

serviceArn

ARN identifier.

Length Constraints: Minimum length of 31.

Pattern: arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9]
[A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1})-)|(gov-)){0,1}[a-z]+-
[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/.-]{0,1023}

Required: Yes

severity

Filter findings by severity.

Valid Values: LOW | MEDIUM | HIGH

status

Filter findings by status.

Valid Values: OPEN | RESOLVED | IRRELEVANT

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "findingsSummary": [
    {
      "description": "string",
      "failureCategory": "string",
      "findingId": "string",
      "name": "string",
      "policyComponent": "string",
      "serviceArn": "string",
      "severity": "string",
      "status": "string",
      "updatedAt": number
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

findingsSummary

The list of finding summaries.

Type: Array of [FindingSummary](#) objects

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListInputSources

Lists input sources for a service.

Request Syntax

```
GET /v2/list-input-sources?  
maxResults=maxResults&nextToken=nextToken&serviceArn=serviceArn&type=type HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

Pagination page size.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

Pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

serviceArn

ARN identifier.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

type

Filter input sources by type.

Valid Values: CFN_STACK | TAGS | EKS | TERRAFORM | DESIGN_FILE | MONITORING

Request Body

The request does not have a request body.

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "inputSourceSummaries": [
    {
      "cfnStackArn": "string",
      "createdAt": number,
      "designFileS3Url": "string",
      "eks": {
        "clusterArn": "string",
        "labelSelector": {
          "matchExpressions": [
            {
              "key": "string",
              "operator": "string",
              "values": [ "string" ]
            }
          ],
          "matchLabels": {
            "string": "string"
          }
        },
        "namespaces": [ "string" ]
      },
      "inputSourceId": "string",
      "resourceTags": [
        {
          "key": "string",
          "values": [ "string" ]
        }
      ],
      "tfStateFileUrl": "string",
      "type": "string"
    }
  ],
  "nextToken": "string"
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[inputSourceSummaries](#)

The list of input source summaries.

Type: Array of [InputSourceSummary](#) objects

[nextToken](#)

Pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListPolicies

Lists resilience policies.

Request Syntax

```
GET /v2/list-policies?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

Pagination page size.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

Pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "nextToken": "string",
  "policySummaries": [
    {
      "associatedServiceCount": number,
      "availabilitySlo": {
```

```
    "target": number
  },
  "createdAt": number,
  "dataRecovery": {
    "timeBetweenBackupsInMinutes": number
  },
  "multiAz": {
    "disasterRecoveryApproach": "string",
    "rpoInMinutes": number,
    "rtoInMinutes": number
  },
  "multiRegion": {
    "disasterRecoveryApproach": "string",
    "rpoInMinutes": number,
    "rtoInMinutes": number
  },
  "name": "string",
  "policyArn": "string",
  "updatedAt": number
}
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

Pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

[policySummaries](#)

The list of policy summaries.

Type: Array of [PolicySummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerErrorException

Internal service error.

HTTP Status Code: 500

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListReports

List reports for a service, or all reports owned by the account if serviceArn is not provided.

Request Syntax

```
GET /v2/list-reports?
maxResults=maxResults&nextToken=nextToken&reportType=reportType&serviceArn=serviceArn&testRunId=testRunId
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

Pagination page size.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

Pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

reportType

Filter reports by type.

Valid Values: FAILURE_MODE | TESTING

serviceArn

Optional. If not provided, lists all reports owned by the account.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1})-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

testRunId

The unique identifier of a test run.

Length Constraints: Minimum length of 1.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "reportGenerationResults": [
    {
      "assessmentId": "string",
      "createdAt": number,
      "reportOutput": { ... },
      "reportType": "string",
      "serviceArn": "string",
      "status": "string",
      "testRunId": "string",
      "testTemplateArn": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

[reportGenerationResults](#)

The list of report generation results.

Type: Array of [ReportGenerationResult](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ThrottlingException

Too many requests — rate limit exceeded.

retryAfterSeconds

The number of seconds to wait before retrying the request.

HTTP Status Code: 429

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListResolvedTestRunTargetResources

Lists the AWS resources that AWS Fault Injection Service (AWS FIS) resolved as targets for a test run.

Request Syntax

```
GET /v2/test-runs/testRunId/resolved-target-resources?  
maxResults=maxResults&nextToken=nextToken&serviceArn=serviceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

Pagination page size.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

Pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

serviceArn

The ARN of the service the test run belongs to.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

testRunId

The identifier of the test run to list resolved target resources for.

Length Constraints: Minimum length of 1.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "resolvedTargetResources": [
    {
      "resourceType": "string",
      "targetInformation": {
        "string" : "string"
      },
      "targetName": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: \S{1,2000}

resolvedTargetResources

The list of resolved target resources.

Type: Array of [ResolvedTargetResource](#) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListResources

List resources.

Request Syntax

```
GET /v2/list-resources?  
awsRegion=awsRegion&billable=billable&maxResults=maxResults&nextToken=nextToken&resourceTypes=r  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

awsRegion

Filter resources by AWS Region.

Length Constraints: Minimum length of 6.

Pattern: `[a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]`

billable

Specifies whether to filter non-billable resources. When true (the default), the operation returns only billable resources.

maxResults

Pagination page size.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

Pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

resourceTypes

The CloudFormation resource types to include in the response.

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

serviceArn

ARN identifier.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

serviceFunctionId

Filter resources by service function identifier.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `\S{1,255}`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "serviceFunctionId": "string",
  "serviceResources": [
    {
      "inputSource": {
        "identifier": "string",
        "type": "string"
      },
      "resource": {
        "awsAccountId": "string",
```

```
        "awsRegion": "string",
        "identifier": "string",
        "resourceType": "string"
    },
    "resourceIdentifier": "string"
}
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

serviceFunctionId

The service function identifier for the returned resources.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `\S{1,255}`

serviceResources

The list of service resources.

Type: Array of [ServiceResource](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListServiceEvents

Lists events for a service.

Request Syntax

```
GET /v2/list-service-events?  
endTime=endTime&eventTypes=eventTypes&maxResults=maxResults&nextToken=nextToken&serviceArn=serv  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

endTime

The end time for filtering events.

eventTypes

Filter events by type.

Valid Values: SERVICE_CREATED | SERVICE_DELETED | SERVICE_SYSTEM_ASSOCIATED
| SERVICE_SYSTEM_DISASSOCIATED | SERVICE_RESOURCES_ASSOCIATED
| SERVICE_RESOURCES_DISASSOCIATED | SERVICE_WORKFLOW_UPDATED
| SERVICE_INPUT_SOURCES_UPDATED | SERVICE_POLICY_ASSOCIATED
| SERVICE_POLICY_DISASSOCIATED | SERVICE_FUNCTION_CREATED
| SERVICE_FUNCTION_UPDATED | SERVICE_FUNCTION_DELETED |
SERVICE_FUNCTION_RESOURCES_ADDED | SERVICE_FUNCTION_RESOURCES_REMOVED |
SERVICE_ACHIEVABILITY_UPDATED | ASSERTION_CREATED | ASSERTION_UPDATED |
ASSERTION_DELETED

maxResults

Pagination page size.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

Pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

[serviceArn](#)

ARN identifier.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

[startTime](#)

The start time for filtering events.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "events": [
    {
      "actor": {
        "accountId": "string",
        "principalId": "string",
        "type": "string",
        "userName": "string"
      },
      "eventDetails": {
        "description": "string",
        "eventMetadata": { ... },
        "title": "string"
      }
    }
  ]
}
```

```
    "eventId": "string",
    "eventType": "string",
    "serviceArn": "string",
    "timestamp": number
  }
],
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

events

The list of service events.

Type: Array of [ServiceEvent](#) objects

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListServiceFunctions

Lists service functions for a service.

Request Syntax

```
GET /v2/list-functions?maxResults=maxResults&nextToken=nextToken&serviceArn=serviceArn
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

Pagination page size.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

Pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

serviceArn

ARN identifier.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "serviceFunctions": [
    {
      "createdAt": number,
      "criticality": "string",
      "description": "string",
      "name": "string",
      "resourceCount": number,
      "serviceArn": "string",
      "serviceFunctionId": "string",
      "source": "string",
      "updatedAt": number
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

serviceFunctions

The list of service functions.

Type: Array of [ServiceFunction](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListServices

Lists services.

Request Syntax

```
GET /v2/list-services?  
accountId=accountId&assessmentStatus=assessmentStatus&maxResults=maxResults&nextToken=nextToken  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

accountId

Filter services by AWS account ID.

Length Constraints: Fixed length of 12.

Pattern: [0-9]{12}

assessmentStatus

Filter services by assessment status.

Valid Values: NOT_STARTED | PENDING | IN_PROGRESS | FAILED | SUCCESS

maxResults

Pagination page size.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

Pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: \S{1,2000}

ouId

Filter services by organizational unit (OU) identifier.

Length Constraints: Minimum length of 16. Maximum length of 68.

Pattern: `ou-[a-z0-9]{4,32}-[a-z0-9]{8,32}`

[policyArn](#)

ARN identifier.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

[systemArn](#)

ARN identifier.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

[userJourneyId](#)

Filter services by user journey identifier.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `\S{1,255}`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```

"nextToken": "string",
"serviceSummaries": [
  {
    "accountId": "string",
    "achievability": {
      "availabilitySlo": "string",
      "dataRecoveryTimeBetweenBackups": "string",
      "multiAzRtoRpo": "string",
      "multiRegionRtoRpo": "string"
    },
    "assessmentStatus": "string",
    "associatedSystems": [
      {
        "systemArn": "string",
        "systemName": "string",
        "userJourneyIds": [ "string" ]
      }
    ],
    "createdAt": number,
    "dependencyDiscovery": {
      "eligibleResourceCount": number,
      "message": "string",
      "status": "string",
      "updatedAt": number
    },
    "name": "string",
    "openFindingsCount": number,
    "organizationId": "string",
    "ouId": "string",
    "policyArn": "string",
    "regions": [ "string" ],
    "resolvedFindingsCount": number,
    "serviceArn": "string",
    "updatedAt": number
  }
]
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: \S{1,2000}

serviceSummaries

The list of service summaries.

Type: Array of [ServiceSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerErrorException

Internal service error.

HTTP Status Code: 500

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListServiceTopologyEdges

Lists topology edges for a service.

Request Syntax

```
GET /v2/list-service-topology-edges?  
maxResults=maxResults&nextToken=nextToken&serviceArn=serviceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

Pagination page size.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

Pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

serviceArn

ARN identifier.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "serviceTopologyEdgeSummaries": [
    {
      "destinationAccount": "string",
      "destinationRegion": "string",
      "destinationResourceIdentifier": "string",
      "properties": [
        {
          "label": "string",
          "topologyType": "string"
        }
      ],
      "sourceAccount": "string",
      "sourceRegion": "string",
      "sourceResourceIdentifier": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

serviceTopologyEdgeSummaries

The list of service topology edge summaries.

Type: Array of [ServiceTopologyEdgeSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerErrorException

Internal service error.

HTTP Status Code: 500

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListSystemEvents

Lists events for a system.

Request Syntax

```
GET /v2/list-system-events?  
endTime=endTime&eventTypes=eventTypes&maxResults=maxResults&nextToken=nextToken&startTime=start  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

endTime

The end time for filtering events.

eventTypes

Filter events by type.

Valid Values: SYSTEM_CREATED | SYSTEM_DELETED | SYSTEM_USER_JOURNEY_CREATED
| SYSTEM_USER_JOURNEY_UPDATED | SYSTEM_USER_JOURNEY_DELETED
| SYSTEM_SERVICE_ASSOCIATED | SYSTEM_SERVICE_DISASSOCIATED |
SYSTEM_POLICY_ASSOCIATED | SYSTEM_POLICY_DISASSOCIATED

maxResults

Pagination page size.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

Pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: \S{1,2000}

startTime

The start time for filtering events.

systemArn

ARN identifier.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/] [A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "events": [
    {
      "actor": {
        "accountId": "string",
        "principalId": "string",
        "type": "string",
        "userName": "string"
      },
      "eventDetails": {
        "description": "string",
        "eventMetadata": { ... },
        "title": "string"
      },
      "eventId": "string",
      "eventType": "string",
      "systemArn": "string",
      "timestamp": number
    }
  ],
  "nextToken": "string"
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

events

The list of system events.

Type: Array of [SystemEvent](#) objects

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListSystems

Lists systems.

Request Syntax

```
GET /v2/list-systems?maxResults=maxResults&nextToken=nextToken&ouId=ouId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

Pagination page size.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

Pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: \S{1,2000}

ouId

Filter systems by organizational unit (OU) identifier.

Length Constraints: Minimum length of 16. Maximum length of 68.

Pattern: ou-[a-z0-9]{4,32}-[a-z0-9]{8,32}

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{
  "nextToken": "string",
  "systemSummaries": [
    {
      "createdAt": number,
      "name": "string",
      "organizationId": "string",
      "ouId": "string",
      "servicesCount": number,
      "systemArn": "string",
      "systemId": "string",
      "updatedAt": number,
      "userJourneysCount": number
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

systemSummaries

The list of system summaries.

Type: Array of [SystemSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Lists the tags for a resource.

Request Syntax

```
GET /v2/tags/resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[resourceArn](#)

ARN identifier.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tags

Resource tags.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `[^\x00-\x1f\x22]+`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `[^\x00-\x1f\x22]*`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ThrottlingException

Too many requests — rate limit exceeded.

retryAfterSeconds

The number of seconds to wait before retrying the request.

HTTP Status Code: 429

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListTestRunDependencies

Lists the dependencies that a test run blocked. Each dependency reflects the discovered classification captured when the run started, so results do not change if a dependency is reclassified after the run.

Request Syntax

```
GET /v2/test-runs/testRunId/dependencies?  
maxResults=maxResults&nextToken=nextToken&serviceArn=serviceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

Pagination page size.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

Pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

serviceArn

The ARN of the service the test run belongs to.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

testRunId

The identifier of the test run to list dependencies for.

Length Constraints: Minimum length of 1.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "dependencies": [
    {
      "criticality": "string",
      "dependencyId": "string",
      "dependencyName": "string",
      "dnsName": "string",
      "location": "string",
      "provider": "string",
      "source": "string",
      "sourceRegions": [ "string" ]
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[dependencies](#)

The list of dependencies the test run blocked.

Type: Array of [TestRunDependencySummary](#) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListTestRunEvents

Lists the events in a test run's timeline.

Request Syntax

```
GET /v2/test-runs/testRunId/events?  
endedAt=endedAt&maxResults=maxResults&nextToken=nextToken&serviceArn=serviceArn&startedAt=startedAt  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

endedAt

Return events at or before this timestamp.

maxResults

Pagination page size.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

Pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

serviceArn

The ARN of the service the test run belongs to.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1})-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

startedAt

Return events at or after this timestamp.

testRunId

The identifier of the test run to list events for.

Length Constraints: Minimum length of 1.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "events": [
    {
      "attributes": {
        "string" : "string"
      },
      "eventId": "string",
      "eventType": "string",
      "message": "string",
      "timestamp": number
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

events

The list of test run events.

Type: Array of [TestRunEvent](#) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListTestRuns

Lists the runs of a test, or all test runs for a service.

Request Syntax

```
GET /v2/list-test-runs?  
maxResults=maxResults&nextToken=nextToken&serviceArn=serviceArn&testId=testId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

Pagination page size.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

Pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

serviceArn

The ARN of the service to list test runs for.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/] [A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

testId

Filter test runs by test identifier.

Length Constraints: Minimum length of 1.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "testRuns": [
    {
      "accountTargeting": "string",
      "endedAt": number,
      "errorMessage": "string",
      "serviceArn": "string",
      "startedAt": number,
      "status": "string",
      "testRunId": "string",
      "testTemplateArn": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

[testRuns](#)

The list of test run summaries.

Type: Array of [TestRunSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListTestRunSourceEvents

Lists the state-change events observed for a test run monitoring source. Events are returned for one source per call, in chronological order.

Request Syntax

```
GET /v2/test-runs/testRunId/source-events?
maxResults=maxResults&nextToken=nextToken&serviceArn=serviceArn&sourceArn=sourceArn
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

Pagination page size.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

Pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

serviceArn

The ARN of the service the test run belongs to.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

sourceArn

The ARN of the monitoring source to list events for, such as the ARN of a CloudWatch alarm. If the source was not monitored during the test run, the response is an empty list.

Length Constraints: Minimum length of 31. Maximum length of 1024.

Pattern: `arn:aws[a-zA-Z-]*:[a-z][a-z0-9-]*:[a-z]{2}(-[a-z]+)+-\d{1}:\d{12}:.+`

Required: Yes

[testRunId](#)

The identifier of the test run to list source events for.

Length Constraints: Minimum length of 1.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "testRunSourceEvents": [
    {
      "detail": { ... },
      "eventType": "string",
      "sourceArn": "string",
      "timestamp": number
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

testRunSourceEvents

The list of source events, in chronological order.

Type: Array of [TestRunSourceEvent](#) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListTestRunSources

Lists the monitoring source snapshots captured for a test run, optionally filtered by type.

Request Syntax

```
GET /v2/test-runs/testRunId/sources?  
maxResults=maxResults&nextToken=nextToken&serviceArn=serviceArn&type=type HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

Pagination page size.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

Pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

serviceArn

The ARN of the service the test run belongs to.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

testRunId

The identifier of the test run to list sources for.

Length Constraints: Minimum length of 1.

Required: Yes

[type](#)

Filter sources by type.

Valid Values: SUCCESS_CRITERIA | OBSERVABILITY

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "testRunSources": [
    { ... }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

Pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: \S{1,2000}

[testRunSources](#)

The list of monitoring source snapshots.

Type: Array of [TestRunSourceSummary](#) objects

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListTests

Lists the tests configured for a service.

Request Syntax

```
GET /v2/list-tests?maxResults=maxResults&nextToken=nextToken&serviceArn=serviceArn
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[maxResults](#)

Pagination page size.

Valid Range: Minimum value of 1. Maximum value of 100.

[nextToken](#)

Pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

[serviceArn](#)

The ARN of the service to list tests for.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "tests": [
    {
      "creationTime": number,
      "serviceArn": "string",
      "successfulTestRuns": number,
      "testId": "string",
      "testTemplateArn": "string",
      "totalTestRuns": number
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

tests

The list of test summaries.

Type: Array of [TestSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerErrorException

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListTestSources

Lists the monitoring sources attached to a test, optionally filtered by type.

Request Syntax

```
GET /v2/tests/testId/sources?  
maxResults=maxResults&nextToken=nextToken&serviceArn=serviceArn&type=type HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

Pagination page size.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

Pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

serviceArn

The ARN of the service the test belongs to.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

testId

The identifier of the test to list sources for.

Length Constraints: Minimum length of 1.

Required: Yes

type

Filter sources by type.

Valid Values: SUCCESS_CRITERIA | OBSERVABILITY

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "testSources": [
    { ... }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: \S{1,2000}

testSources

The list of configured monitoring sources.

Type: Array of [TestSourceSummary](#) objects

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListTestTemplates

Lists the available resilience test templates. A test template is a pre-configured, AWS recommended test that defines which resilience capability to validate.

Request Syntax

```
GET /v2/list-test-templates HTTP/1.1
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "testTemplates": [
    {
      "description": "string",
      "name": "string",
      "testTemplateArn": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

testTemplates

The list of test template summaries.

Type: Array of [TestTemplateSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerErrorException

Internal service error.

HTTP Status Code: 500

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListUserJourneys

Lists user journeys for a system.

Request Syntax

```
GET /v2/list-user-journeys?  
maxResults=maxResults&nextToken=nextToken&systemArn=systemArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

Pagination page size.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

Pagination token.

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

systemArn

ARN identifier.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "userJourneySummaries": [
    {
      "createdAt": number,
      "name": "string",
      "updatedAt": number,
      "userJourneyId": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `\S{1,2000}`

userJourneySummaries

The list of user journey summaries.

Type: Array of [UserJourneySummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

PutTestSources

Adds or updates the monitoring sources on a test. The operation is transactional — either every source is written or the call fails and nothing is written.

Request Syntax

```
POST /v2/put-test-sources HTTP/1.1
Content-type: application/json
```

```
{
  "serviceArn": "string",
  "testId": "string",
  "testSources": [
    { ... }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

serviceArn

The ARN of the service the test belongs to.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/] [A-Za-z0-9: _/+.-]{0,1023}`

Required: Yes

testId

The identifier of the test to add sources to.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

[testSources](#)

The monitoring sources to add or update.

Type: Array of [TestSourceInput](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ServiceQuotaExceededException

Service quota exceeded.

HTTP Status Code: 402

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

StartFailureModeAssessment

Starts a failure mode assessment.

Request Syntax

```
POST /v2/start-failure-mode-assessment HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "serviceArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

Idempotency token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: [A-Za-z0-9_.-]{0,63}

Required: No

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "assessmentId": "string",
  "assessmentStatus": "string",
  "serviceArn": "string",
  "startedAt": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentId

The unique identifier of the started assessment.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-5][0-9a-f]{3}-[089ab][0-9a-f]{3}-[0-9a-f]{12}`

assessmentStatus

The status of the started assessment.

Type: String

Valid Values: NOT_STARTED | PENDING | IN_PROGRESS | FAILED | SUCCESS

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

startedAt

The timestamp when the assessment started.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ThrottlingException

Too many requests — rate limit exceeded.

retryAfterSeconds

The number of seconds to wait before retrying the request.

HTTP Status Code: 429

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

StartTestRun

Starts a run of a test. Each run scopes to the current resources in the service and produces a pass or fail outcome.

Request Syntax

```
POST /v2/start-test-run HTTP/1.1
Content-type: application/json
```

```
{
  "serviceArn": "string",
  "testId": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

serviceArn

The ARN of the service the test belongs to.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

testId

The identifier of the test to run.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "experimentArns": [ "string" ],
  "status": "string",
  "testRunId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[experimentArns](#)

The ARNs of the AWS Fault Injection Service (AWS FIS) experiments started for the run.

Type: Array of strings

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

[status](#)

The status of the started test run.

Type: String

Valid Values: `INITIALIZING | RUNNING | STOPPING | PASSED | FAILED | STOPPED | ERROR`

testRunId

The identifier of the started test run.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

StopTestRun

Stops an in-progress test run.

Request Syntax

```
POST /v2/stop-test-run HTTP/1.1
Content-type: application/json
```

```
{
  "serviceArn": "string",
  "testRunId": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[serviceArn](#)

The ARN of the service the test run belongs to.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}: [A-Za-z0-9/][A-Za-z0-9:_.-]{0,1023}`

Required: Yes

[testRunId](#)

The identifier of the test run to stop.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "status": "string",
  "testRunId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

status

The status of the test run.

Type: String

Valid Values: INITIALIZING | RUNNING | STOPPING | PASSED | FAILED | STOPPED
| ERROR

testRunId

The identifier of the stopped test run.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerErrorException

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

TagResource

Adds tags to a resource.

Request Syntax

```
POST /v2/tags/resourceArn HTTP/1.1
Content-type: application/json

{
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

ARN identifier.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/_.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

tags

Resource tags.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `[^\x00-\x1f\x22]+`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `[^\x00-\x1f\x22]*`

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ThrottlingException

Too many requests — rate limit exceeded.

retryAfterSeconds

The number of seconds to wait before retrying the request.

HTTP Status Code: 429

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Removes tags from a resource.

Request Syntax

```
DELETE /v2/tags/resourceArn?tagKeys=tagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[resourceArn](#)

ARN identifier.

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/_.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

[tagKeys](#)

The tag keys to remove from the resource.

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[^\x00-\x1f\x22]+`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ThrottlingException

Too many requests — rate limit exceeded.

retryAfterSeconds

The number of seconds to wait before retrying the request.

HTTP Status Code: 429

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateAssertion

Updates a resilience assertion.

Request Syntax

```
POST /v2/update-assertion HTTP/1.1
Content-type: application/json
```

```
{
  "assertionId": "string",
  "serviceArn": "string",
  "text": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

assertionId

The unique identifier of the assertion to update.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-5][0-9a-f]{3}-[089ab][0-9a-f]{3}-[0-9a-f]{12}`

Required: Yes

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

[text](#)

The updated text content of the assertion.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "assertion": {
    "assertionId": "string",
    "createdAt": number,
    "serviceArn": "string",
    "source": "string",
    "text": "string",
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[assertion](#)

The updated assertion.

Type: [Assertion](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateDependency

Updates a dependency classification.

Request Syntax

```
POST /v2/update-dependency HTTP/1.1
Content-type: application/json
```

```
{
  "comment": "string",
  "criticality": "string",
  "dependencyId": "string",
  "serviceArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

comment

A comment about the dependency.

Type: String

Required: No

criticality

The updated criticality level of the dependency.

Type: String

Valid Values: HARD | SOFT | UNKNOWN

Required: No

dependencyId

The identifier of the dependency to update.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-5][0-9a-f]{3}-[089ab][0-9a-f]{3}-[0-9a-f]{12}`

Required: Yes

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "comment": "string",
  "criticality": "string",
  "dependencyId": "string",
  "dependencyName": "string",
  "location": "string",
  "provider": "string",
  "updatedAt": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

comment

The comment about the dependency.

Type: String

criticality

The criticality level of the dependency.

Type: String

Valid Values: HARD | SOFT | UNKNOWN

dependencyId

The identifier of the updated dependency.

Type: String

Length Constraints: Fixed length of 36.

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-5][0-9a-f]{3}-[089ab][0-9a-f]{3}-[0-9a-f]{12}

dependencyName

The name of the updated dependency.

Type: String

location

The location of the dependency.

Type: String

provider

The provider of the dependency.

Type: String

updatedAt

The timestamp when the dependency was updated.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateFailureModeFinding

Updates an existing finding.

Request Syntax

```
POST /v2/update-failure-mode-finding HTTP/1.1
Content-type: application/json
```

```
{
  "comment": "string",
  "findingId": "string",
  "serviceArn": "string",
  "status": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

comment

A comment about the finding update.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

findingId

The identifier of the finding to update.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-5][0-9a-f]{3}-[089ab][0-9a-f]{3}-[0-9a-f]{12}`

Required: Yes

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

status

The new status for the finding.

Type: String

Valid Values: OPEN | RESOLVED | IRRELEVANT

Required: Yes

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "finding": {
    "comment": "string",
    "description": "string",
    "failureCategory": "string",
    "findingId": "string",
    "infrastructureAndCodeRecommendations": [
      {
        "suggestedChanges": [ "string" ]
      }
    ]
  }
}
```

```
    ],  
    "name": "string",  
    "observabilityRecommendations": [  
      {  
        "suggestedChanges": [ "string" ]  
      }  
    ],  
    "policyComponent": "string",  
    "reasoning": "string",  
    "serviceFunctions": [ "string" ],  
    "severity": "string",  
    "status": "string",  
    "testingRecommendations": [  
      {  
        "suggestedChanges": [ "string" ]  
      }  
    ],  
    "updatedAt": number  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[finding](#)

The updated finding.

Type: [Finding](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdatePolicy

Updates an existing resilience policy.

Request Syntax

POST /v2/update-policy HTTP/1.1

Content-type: application/json

```
{
  "availabilitySlo": {
    "target": number
  },
  "dataRecovery": {
    "timeBetweenBackupsInMinutes": number
  },
  "description": "string",
  "multiAz": {
    "disasterRecoveryApproach": "string",
    "rpoInMinutes": number,
    "rtoInMinutes": number
  },
  "multiRegion": {
    "disasterRecoveryApproach": "string",
    "rpoInMinutes": number,
    "rtoInMinutes": number
  },
  "policyArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

availabilitySlo

The updated availability SLO for the policy.

Type: [AvailabilitySlo](#) object

Required: No

[dataRecovery](#)

The updated data recovery targets for the policy.

Type: [DataRecoveryTargets](#) object

Required: No

[description](#)

Resource description for services and policies.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 615.

Required: No

[multiAz](#)

The updated multi-AZ disaster recovery targets for the policy.

Type: [MultiAzTargets](#) object

Required: No

[multiRegion](#)

The updated multi-Region disaster recovery targets for the policy.

Type: [MultiRegionTargets](#) object

Required: No

[policyArn](#)

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1})-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}: [A-Za-z0-9/] [A-Za-z0-9: _/+. -]{0,1023}`

Required: Yes

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "policy": {
    "associatedServiceCount": number,
    "availabilitySlo": {
      "target": number
    },
    "createdAt": number,
    "dataRecovery": {
      "timeBetweenBackupsInMinutes": number
    },
    "description": "string",
    "kmsKeyId": "string",
    "multiAz": {
      "disasterRecoveryApproach": "string",
      "rpoInMinutes": number,
      "rtoInMinutes": number
    },
    "multiRegion": {
      "disasterRecoveryApproach": "string",
      "rpoInMinutes": number,
      "rtoInMinutes": number
    },
    "name": "string",
    "policyArn": "string",
    "tags": {
      "string" : "string"
    },
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

policy

The updated policy.

Type: [Policy](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateService

Updates an existing service.

Request Syntax

POST /v2/update-service HTTP/1.1

Content-type: application/json

```
{
  "associatedSystems": [
    {
      "systemArn": "string",
      "systemName": "string",
      "userJourneyIds": [ "string" ]
    }
  ],
  "dependencyDiscovery": "string",
  "description": "string",
  "permissionModel": {
    "crossAccountRoles": [
      {
        "crossAccountRoleArn": "string",
        "externalId": "string"
      }
    ],
    "invokerRoleName": "string"
  },
  "policyArn": "string",
  "regions": [ "string" ],
  "reportConfiguration": {
    "reportOutputs": [
      { ... }
    ]
  },
  "serviceArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

associatedSystems

The updated systems to associate with the service.

Type: Array of [AssociatedSystem](#) objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: No

dependencyDiscovery

Caller-settable values for dependency discovery. INITIALIZING is system-managed.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

description

Resource description for services and policies.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 615.

Required: No

permissionModel

The updated permission model for the service.

Type: [PermissionModel](#) object

Required: No

policyArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}: [A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: No

regions

The updated AWS Regions where the service operates.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 6.

Pattern: `[a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]`

Required: No

reportConfiguration

Configuration for automatic report generation on a Service.

Type: [ServiceReportConfiguration](#) object

Required: No

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}: [A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "service": {
    "accountId": "string",
    "achievability": {
      "availabilitySlo": "string",
      "dataRecoveryTimeBetweenBackups": "string",
      "multiAzRtoRpo": "string",
      "multiRegionRtoRpo": "string"
    },
    "assessmentStatus": "string",
    "associatedSystems": [
      {
        "systemArn": "string",
        "systemName": "string",
        "userJourneyIds": [ "string" ]
      }
    ],
    "createdAt": number,
    "dependencyDiscovery": {
      "eligibleResourceCount": number,
      "message": "string",
      "status": "string",
      "updatedAt": number
    },
    "description": "string",
    "effectivePolicyValues": {
      "availabilitySlo": {
        "policyName": "string",
        "source": "string",
        "value": number
      },
      "dataRecoveryTimeBetweenBackups": {
        "policyName": "string",
        "source": "string",
        "value": number
      },
      "multiAzDrApproach": {
        "policyName": "string",
```

```
    "source": "string",
    "value": "string"
  },
  "multiAzRpo": {
    "policyName": "string",
    "source": "string",
    "value": number
  },
  "multiAzRto": {
    "policyName": "string",
    "source": "string",
    "value": number
  },
  "multiRegionDrApproach": {
    "policyName": "string",
    "source": "string",
    "value": "string"
  },
  "multiRegionRpo": {
    "policyName": "string",
    "source": "string",
    "value": number
  },
  "multiRegionRto": {
    "policyName": "string",
    "source": "string",
    "value": number
  }
},
"estimatedAssessmentCost": {
  "amount": number,
  "currency": "string"
},
"kmsKeyId": "string",
"name": "string",
"openFindingsCount": number,
"organizationId": "string",
"ouId": "string",
"permissionModel": {
  "crossAccountRoles": [
    {
      "crossAccountRoleArn": "string",
      "externalId": "string"
    }
  ]
}
```

```
    ],
    "invokerRoleName": "string"
  },
  "policyArn": "string",
  "regions": [ "string" ],
  "reportConfiguration": {
    "reportOutputs": [
      { ... }
    ]
  },
  "rerunAssessment": boolean,
  "resolvedFindingsCount": number,
  "resourceDiscovery": {
    "errorCode": "string",
    "errorMessage": "string",
    "lastRunAt": number,
    "status": "string"
  },
  "serviceArn": "string",
  "tags": {
    "string" : "string"
  },
  "updatedAt": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

service

The updated service.

Type: [Service](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ServiceQuotaExceededException

Service quota exceeded.

HTTP Status Code: 402

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateServiceFunction

Updates a service function.

Request Syntax

```
POST /v2/update-function HTTP/1.1
Content-type: application/json
```

```
{
  "criticality": "string",
  "description": "string",
  "name": "string",
  "serviceArn": "string",
  "serviceFunctionId": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[criticality](#)

The updated criticality level of the service function.

Type: String

Valid Values: PRIMARY | SUPPLEMENTAL

Required: No

[description](#)

Resource description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

name

Entity label (not part of ARN — spaces allowed).

Type: String

Length Constraints: Minimum length of 2. Maximum length of 60.

Pattern: `[A-Za-z0-9][A-Za-z0-9 _\-]{1,59}`

Required: No

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

serviceFunctionId

The identifier of the service function to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `\S{1,255}`

Required: Yes

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "serviceFunction": {
    "createdAt": number,
    "criticality": "string",
    "description": "string",
    "name": "string",
    "resourceCount": number,
    "serviceArn": "string",
    "serviceFunctionId": "string",
    "source": "string",
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

serviceFunction

The updated service function.

Type: [ServiceFunction](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerErrorException

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateSystem

Updates an existing system.

Request Syntax

```
POST /v2/update-system HTTP/1.1
Content-type: application/json
```

```
{
  "description": "string",
  "sharingEnabled": boolean,
  "systemArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[description](#)

Resource description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

[sharingEnabled](#)

Whether cross-account sharing is enabled for the system.

Type: Boolean

Required: No

[systemArn](#)

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "system": {
    "createdAt": number,
    "description": "string",
    "kmsKeyId": "string",
    "name": "string",
    "organizationId": "string",
    "ouId": "string",
    "sharingEnabled": boolean,
    "systemArn": "string",
    "systemId": "string",
    "tags": {
      "string" : "string"
    },
    "updatedAt": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

system

The updated system.

Type: [System](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateTest

Updates the configuration of an existing test.

Request Syntax

```
POST /v2/update-test HTTP/1.1
Content-type: application/json

{
  "loggingConfiguration": {
    "cloudWatchLogGroupArn": "string",
    "logSchemaVersion": "string",
    "s3BucketName": "string"
  },
  "parameters": {
    "string" : [ "string" ]
  },
  "roleName": "string",
  "serviceArn": "string",
  "stopConditions": [
    {
      "source": "string",
      "value": "string"
    }
  ],
  "testId": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

loggingConfiguration

The updated logging configuration for the test.

Type: [LoggingConfiguration](#) object

Required: No

parameters

The updated parameter values for the test.

Type: String to array of strings map

Map Entries: Minimum number of 0 items. Maximum number of 20 items.

Key Length Constraints: Minimum length of 1. Maximum length of 256.

Key Pattern: `[\w . - ]+`

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

roleName

The updated IAM execution role name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 576.

Pattern: `([A-Za-z0-9_+=, .@ \- ]+ /) * [A-Za-z0-9_+=, .@ \- ]+`

Required: No

serviceArn

The ARN of the service the test belongs to.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/. - ]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/] [A-Za-z0-9:_/+ . - ]{0,1023}`

Required: Yes

stopConditions

The updated stop conditions for the test.

Type: Array of [StopCondition](#) objects

Required: No

testId

The identifier of the test to update.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "test": {
    "actions": [
      {
        "actionId": "string",
        "description": "string",
        "resourceType": "string"
      }
    ],
    "creationTime": number,
    "loggingConfiguration": {
      "cloudWatchLogGroupArn": "string",
      "logSchemaVersion": "string",
      "s3BucketName": "string"
    },
    "name": "string",
    "parameters": {
      "string" : [ "string" ]
    },
    "roleName": "string",
    "serviceArn": "string",
```

```
  "stopConditions": [  
    {  
      "source": "string",  
      "value": "string"  
    }  
  ],  
  "successfulTestRuns": number,  
  "testId": "string",  
  "testTemplateArn": "string",  
  "totalTestRuns": number  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

test

The updated test.

Type: [Test](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerError

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateUserJourney

Updates an existing user journey.

Request Syntax

```
POST /v2/update-user-journey HTTP/1.1
Content-type: application/json
```

```
{
  "description": "string",
  "name": "string",
  "policyArn": "string",
  "systemArn": "string",
  "userJourneyId": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

description

Resource description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

name

Entity label (not part of ARN — spaces allowed).

Type: String

Length Constraints: Minimum length of 2. Maximum length of 60.

Pattern: `[A-Za-z0-9][A-Za-z0-9 _\-]{1,59}`

Required: No

policyArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: No

systemArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

userJourneyId

The identifier of the user journey to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `\S{1,255}`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "userJourney": {
    "createdAt": number,
    "description": "string",
    "name": "string",
    "policyArn": "string",
    "updatedAt": number,
    "userJourneyId": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

userJourney

The updated user journey.

Type: [UserJourney](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

Access denied — caller lacks required permissions.

HTTP Status Code: 403

ConflictException

Conflict — resource already exists.

HTTP Status Code: 409

InternalServerErrorException

Internal service error.

HTTP Status Code: 500

ResourceNotFoundException

Resource not found.

resourceId

The identifier of the resource that was not found.

resourceType

The type of the resource that was not found.

HTTP Status Code: 404

ValidationException

Validation error — invalid input parameters.

fieldList

The list of fields that failed validation.

reason

The reason for the validation failure.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS Resilience Hub V2 API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [Achievability](#)
- [AlarmStateChangeDetail](#)
- [Assertion](#)
- [AssertionCreatedMetadata](#)
- [AssertionDeletedMetadata](#)
- [AssertionUpdatedMetadata](#)
- [AssessmentCost](#)
- [AssessmentSummary](#)
- [AssociatedSystem](#)
- [AvailabilitySlo](#)
- [CrossAccountRole](#)
- [DataRecoveryTargets](#)
- [DependencyDiscoveryConfig](#)
- [DependencySummary](#)
- [DisasterRecoverySource](#)
- [EdgePropertySummary](#)
- [EffectivePolicyValues](#)
- [EksLabelSelector](#)
- [EksLabelSelectorRequirement](#)
- [EksSource](#)

- [EventActor](#)
- [ExperimentDetails](#)
- [FailedReportOutput](#)
- [Finding](#)
- [FindingSummary](#)
- [InfrastructureAndCodeRecommendation](#)
- [InputSource](#)
- [InputSourceSummary](#)
- [LoggingConfiguration](#)
- [MultiAzTargets](#)
- [MultiRegionTargets](#)
- [ObservabilityAlarmInput](#)
- [ObservabilityAlarmSummary](#)
- [ObservabilityRecommendation](#)
- [PermissionModel](#)
- [Policy](#)
- [PolicySummary](#)
- [QueryDataPoint](#)
- [QueryRange](#)
- [ReportGenerationResult](#)
- [ReportOutput](#)
- [ReportOutputConfiguration](#)
- [ResolvedTargetResource](#)
- [Resource](#)
- [ResourceConfiguration](#)
- [ResourceDiscoveryStatus](#)
- [ResourceTag](#)
- [S3ReportOutput](#)
- [S3ReportOutputConfiguration](#)
- [Service](#)

- [ServiceAchievabilityUpdatedMetadata](#)
- [ServiceCreatedMetadata](#)
- [ServiceDeletedMetadata](#)
- [ServiceEvent](#)
- [ServiceEventDetails](#)
- [ServiceEventMetadata](#)
- [ServiceFunction](#)
- [ServiceFunctionCreatedMetadata](#)
- [ServiceFunctionDeletedMetadata](#)
- [ServiceFunctionResourcesAddedMetadata](#)
- [ServiceFunctionResourcesRemovedMetadata](#)
- [ServiceFunctionUpdatedMetadata](#)
- [ServiceInputSourcesUpdatedMetadata](#)
- [ServicePolicyAssociatedMetadata](#)
- [ServicePolicyDisassociatedMetadata](#)
- [ServiceReference](#)
- [ServiceReferenceChanges](#)
- [ServiceReportConfiguration](#)
- [ServiceResource](#)
- [ServiceResourcesAssociatedMetadata](#)
- [ServiceResourcesDisassociatedMetadata](#)
- [ServiceSummary](#)
- [ServiceSystemAssociatedMetadata](#)
- [ServiceSystemDisassociatedMetadata](#)
- [ServiceTopologyEdgeSummary](#)
- [ServiceWorkflowUpdatedMetadata](#)
- [SloSource](#)
- [StopCondition](#)
- [StringChange](#)
- [SuccessCriteriaAlarmInput](#)

- [SuccessCriteriaAlarmSummary](#)
- [System](#)
- [SystemCreatedMetadata](#)
- [SystemDeletedMetadata](#)
- [SystemEvent](#)
- [SystemEventDetails](#)
- [SystemEventMetadata](#)
- [SystemPolicyAssociatedMetadata](#)
- [SystemPolicyDisassociatedMetadata](#)
- [SystemServiceAssociatedMetadata](#)
- [SystemServiceDisassociatedMetadata](#)
- [SystemSummary](#)
- [SystemUserJourneyCreatedMetadata](#)
- [SystemUserJourneyDeletedMetadata](#)
- [SystemUserJourneyUpdatedMetadata](#)
- [TargetSource](#)
- [Test](#)
- [TestAction](#)
- [TestingRecommendation](#)
- [TestRun](#)
- [TestRunDependencySummary](#)
- [TestRunEvent](#)
- [TestRunObservabilityAlarmSummary](#)
- [TestRunPolicySnapshot](#)
- [TestRunReportConfiguration](#)
- [TestRunSourceEvent](#)
- [TestRunSourceEventDetail](#)
- [TestRunSourceEventError](#)
- [TestRunSourceSummary](#)
- [TestRunSuccessCriteriaAlarmSummary](#)

- [TestRunSummary](#)
- [TestSourceInput](#)
- [TestSourceSummary](#)
- [TestSummary](#)
- [TestTemplate](#)
- [TestTemplateParameter](#)
- [TestTemplateSummary](#)
- [UserJourney](#)
- [UserJourneyChanges](#)
- [UserJourneySummary](#)
- [ValidationExceptionField](#)

Achievability

Describes the achievability status of a service's resilience targets based on the most recent assessment.

Contents

availabilitySlo

The achievability status of the availability SLO target for the service.

Type: String

Valid Values: ACHIEVABLE | NOT_ACHIEVABLE

Required: No

dataRecoveryTimeBetweenBackups

The achievability status of the data recovery time between backups for the service.

Type: String

Valid Values: ACHIEVABLE | NOT_ACHIEVABLE

Required: No

multiAzRtoRpo

The achievability status of the multi-AZ RTO and RPO targets for the service.

Type: String

Valid Values: ACHIEVABLE | NOT_ACHIEVABLE

Required: No

multiRegionRtoRpo

The achievability status of the multi-Region RTO and RPO targets for the service.

Type: String

Valid Values: ACHIEVABLE | NOT_ACHIEVABLE

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AlarmStateChangeDetail

Details about a CloudWatch alarm state change observed during a test run.

Contents

state

The state the alarm transitioned to.

Type: String

Valid Values: OK | ALARM | INSUFFICIENT_DATA

Required: Yes

previousState

The state the alarm transitioned from. Absent on the initial event, which records the alarm's state when collection began.

Type: String

Valid Values: OK | ALARM | INSUFFICIENT_DATA

Required: No

reason

A human-readable explanation of the state change, as reported by CloudWatch.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1023.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Assertion

Represents a resilience assertion for a service.

Contents

assertionId

The unique identifier of the assertion.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-5][0-9a-f]{3}-[089ab][0-9a-f]{3}-[0-9a-f]{12}`

Required: Yes

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1})|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

source

The source of the assertion, indicating whether it was AI-generated or created by a user.

Type: String

Valid Values: `AI_GENERATED` | `USER`

Required: Yes

text

The text content of the assertion.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Required: Yes

createdAt

The timestamp when the assertion was created.

Type: Timestamp

Required: No

updatedAt

The timestamp when the assertion was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssertionCreatedMetadata

Metadata for an assertion created event.

Contents

assertionId

The unique identifier of the created assertion.

Type: String

Required: No

assertionName

The name of the created assertion.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssertionDeletedMetadata

Metadata for an assertion deleted event.

Contents

assertionId

The unique identifier of the deleted assertion.

Type: String

Required: No

assertionName

The name of the deleted assertion.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssertionUpdatedMetadata

Metadata for an assertion updated event.

Contents

assertionId

The unique identifier of the updated assertion.

Type: String

Required: No

assertionName

The name of the updated assertion.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentCost

Represents the cost of running a failure mode assessment.

Contents

amount

The cost amount for the assessment.

Type: Double

Required: No

currency

The currency of the assessment cost.

Type: String

Valid Values: USD

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentSummary

Contains summary information about a failure mode assessment.

Contents

assessmentId

The unique identifier of the assessment.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-5][0-9a-f]{3}-[089ab][0-9a-f]{3}-[0-9a-f]{12}`

Required: Yes

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/.-]{0,1023}`

Required: Yes

achievability

The achievability results from the assessment.

Type: [Achievability](#) object

Required: No

assessmentCost

The cost of the assessment.

Type: [AssessmentCost](#) object

Required: No

assessmentStatus

The current status of the assessment.

Type: String

Valid Values: NOT_STARTED | PENDING | IN_PROGRESS | FAILED | SUCCESS

Required: No

assessmentStep

The current step of the assessment process.

Type: String

Valid Values: TOPOLOGY_GENERATION | INPUT_VALIDATION | DESIGN_ANALYSIS |
TOPOLOGY_ENHANCEMENT | SERVICE_FUNCTION_GENERATION | POLICY_VALIDATION
| RESILIENCE_ASSESSMENT | FAILURE_MODE_FINDINGS_CONSOLIDATION |
FAILURE_MODE_FINDINGS_ENRICHMENT

Required: No

billableAssessmentUnitCount

The number of billable assessment units consumed by the assessment.

Type: Integer

Required: No

endedAt

The timestamp when the assessment ended.

Type: Timestamp

Required: No

errorCode

The error code if the assessment failed.

Type: String

Valid Values: INVALID_PERMISSIONS | CMK_ACCESS_DENIED | AGENT_ERROR | INTERNAL_ERROR | DESIGN_FILE_ACCESS_DENIED

Required: No

errorMessage

A message describing the error if the assessment failed.

Type: String

Required: No

startedAt

The timestamp when the assessment started.

Type: Timestamp

Required: No

totalFindings

The total number of findings generated by the assessment.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssociatedSystem

Represents a system associated with a service.

Contents

systemArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1})-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

systemName

Resource name (used in ARN — no spaces allowed).

Type: String

Length Constraints: Minimum length of 2. Maximum length of 60.

Pattern: `[A-Za-z0-9][A-Za-z0-9_\-]{1,59}`

Required: No

userJourneyIds

The list of user journey identifiers that associate this system with the service.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `\S{1,255}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AvailabilitySlo

Defines the availability service level objective (SLO) for a resilience policy.

Contents

target

The target availability percentage, expressed as a value between 0 and 100.

Type: Double

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CrossAccountRole

Specifies a cross-account IAM role ARN and optional external ID.

Contents

crossAccountRoleArn

ARN of the IAM Role for the profile. Null if the permission profile is the 'Admin' profile.

Type: String

Length Constraints: Minimum length of 32.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):iam:[0-9]{12}:role/(([/][!~]+/){1,511})?[A-Za-z0-9_+=, .@-]{1,64}`

Required: Yes

externalId

The external ID used for assuming the cross-account role.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 1224.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DataRecoveryTargets

Defines data recovery targets for a resilience policy.

Contents

timeBetweenBackupsInMinutes

The target time between backups, in minutes.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DependencyDiscoveryConfig

Configuration for dependency discovery on a service.

Contents

status

The current status of dependency discovery.

Type: String

Valid Values: ENABLED | INITIALIZING | DISABLED

Required: Yes

eligibleResourceCount

The count of resources eligible for dependency attribution.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

message

A status message for dependency discovery, displayed during the initialization state.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

updatedAt

The timestamp when dependency discovery was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DependencySummary

Contains summary information about a discovered dependency.

Contents

criticality

The criticality level of the dependency.

Type: String

Valid Values: HARD | SOFT | UNKNOWN

Required: Yes

dependencyId

The unique identifier of the dependency.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-5][0-9a-f]{3}-[089ab][0-9a-f]{3}-[0-9a-f]{12}`

Required: Yes

dependencyName

The name of the dependency.

Type: String

Required: Yes

dnsName

The DNS name associated with the dependency.

Type: String

Required: Yes

lastDetectedTime

The timestamp when the dependency was last detected.

Type: Timestamp

Required: Yes

location

The location of the dependency.

Type: String

Required: Yes

queryRange

The query range data for the dependency.

Type: [QueryRange](#) object

Required: Yes

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/.-]{0,1023}`

Required: Yes

sourceRegions

The source Regions from which the dependency was detected.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 6.

Pattern: `[a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]`

Required: Yes

comment

A user-provided comment about the dependency.

Type: String

Required: No

provider

The provider of the dependency.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DisasterRecoverySource

Contains the effective disaster recovery approach value for a service.

Contents

policyName

Resource name (used in ARN — no spaces allowed).

Type: String

Length Constraints: Minimum length of 2. Maximum length of 60.

Pattern: `[A-Za-z0-9][A-Za-z0-9_\-]{1,59}`

Required: No

source

Indicates whether the value comes from the service's own account or a cross-account policy.

Type: String

Valid Values: SELF | CROSS_ACCOUNT

Required: No

value

The disaster recovery approach value.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

EdgePropertySummary

Contains property information for a service topology edge.

Contents

label

Human-readable relationship description. Only present for LLM-inferred edges.

Type: String

Required: No

topologyType

The topology type of the edge.

Type: String

Valid Values: CONTAINMENT | DATA_FLOW | OBSERVABILITY | PERMISSIONS

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EffectivePolicyValues

Contains the effective resilience policy values for a service.

Contents

availabilitySlo

The effective availability SLO value for the service.

Type: [SloSource](#) object

Required: No

dataRecoveryTimeBetweenBackups

The effective data recovery time between backups value for the service.

Type: [TargetSource](#) object

Required: No

multiAzDrApproach

The effective multi-AZ disaster recovery approach for the service.

Type: [DisasterRecoverySource](#) object

Required: No

multiAzRpo

The effective multi-AZ RPO value for the service, in minutes.

Type: [TargetSource](#) object

Required: No

multiAzRto

The effective multi-AZ RTO value for the service, in minutes.

Type: [TargetSource](#) object

Required: No

multiRegionDrApproach

The effective multi-Region disaster recovery approach for the service.

Type: [DisasterRecoverySource](#) object

Required: No

multiRegionRpo

The effective multi-Region RPO value for the service, in minutes.

Type: [TargetSource](#) object

Required: No

multiRegionRto

The effective multi-Region RTO value for the service, in minutes.

Type: [TargetSource](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EksLabelSelector

A label selector that filters the Kubernetes objects discovered from an Amazon EKS input source. An object must satisfy both `matchLabels` and `matchExpressions` to match the selector. A selector with neither matches every object. The selector must render to 2,048 characters or fewer in Kubernetes label selector syntax.

Contents

`matchExpressions`

The label requirements that an object must satisfy. All requirements in the list must match for the object to be selected.

Type: Array of [EksLabelSelectorRequirement](#) objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: No

`matchLabels`

The label key-value pairs that an object must have. All pairs must match for the object to be selected.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 20 items.

Key Length Constraints: Minimum length of 1. Maximum length of 317.

Key Pattern: `([a-z0-9]([-a-z0-9.]*[a-z0-9])?/?)[A-Za-z0-9]([-A-Za-z0-9_.]*[A-Za-z0-9])?`

Value Length Constraints: Minimum length of 0. Maximum length of 63.

Value Pattern: `([A-Za-z0-9]([-A-Za-z0-9_.]*[A-Za-z0-9])?)?`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EksLabelSelectorRequirement

A single label requirement in a label selector, expressed as a key, an operator, and an optional list of values.

Contents

key

The label key that the requirement applies to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 317.

Pattern: (`[a-z0-9]([-a-z0-9]*[a-z0-9])?/`)?`[A-Za-z0-9]([-A-Za-z0-9_]*[A-Za-z0-9])?`

Required: Yes

operator

The operator that relates the label key to the values.

Type: String

Valid Values: `IN` | `NOT_IN` | `EXISTS` | `DOES_NOT_EXIST`

Required: Yes

values

The label values to compare against. Specify values when the operator is `IN` or `NOT_IN`. Leave this empty when the operator is `EXISTS` or `DOES_NOT_EXIST`.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Length Constraints: Minimum length of 0. Maximum length of 63.

Pattern: (`[A-Za-z0-9]([-A-Za-z0-9_]*[A-Za-z0-9])?`)?

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EksSource

Defines an Amazon EKS cluster and its namespaces as an input source for resource discovery.

Contents

clusterArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1})-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

namespaces

The list of Kubernetes namespaces within the EKS cluster.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 63.

Pattern: `[a-z0-9]([-a-z0-9]*[a-z0-9])?`

Required: Yes

labelSelector

Filters discovery to the Kubernetes objects whose labels match the selector. When omitted, all supported objects in the specified namespaces are discovered.

Type: [EksLabelSelector](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EventActor

Identifies the actor that triggered an event.

Contents

principalId

The principal ID of the actor.

Type: String

Required: Yes

type

The type of actor, either USER or SYSTEM.

Type: String

Valid Values: USER | SYSTEM

Required: Yes

accountId

The AWS account ID of the actor.

Type: String

Required: No

userName

The user name of the actor.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ExperimentDetails

Details about an AWS Fault Injection Service (AWS FIS) experiment run as part of a test run.

Contents

experimentArn

The ARN of the AWS FIS experiment.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/.-]{0,1023}`

Required: Yes

details

Additional details about the experiment.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FailedReportOutput

Details when report generation failed.

Contents

errorCode

The error code describing why the report generation failed.

Type: String

Valid Values: INSUFFICIENT_PERMISSIONS | CONFIGURATION_ERROR | INTERNAL_ERROR

Required: Yes

errorMessage

The error message describing why the report generation failed.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Finding

Represents a resilience finding from a failure mode assessment.

Contents

comment

A user-provided comment about the finding.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

description

Resource description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

failureCategory

The failure category of the finding.

Type: String

Valid Values: SHARED_FATE | EXCESSIVE_LOAD | EXCESSIVE_LATENCY | MISCONFIGURATION_AND_BUGS | SINGLE_POINT_OF_FAILURE

Required: No

findingId

The unique identifier of the finding.

Type: String

Length Constraints: Fixed length of 36.

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-5][0-9a-f]{3}-[089ab][0-9a-f]{3}-[0-9a-f]{12}

Required: No

infrastructureAndCodeRecommendations

Infrastructure and code recommendations to address the finding.

Type: Array of [InfrastructureAndCodeRecommendation](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

name

The name of the finding.

Type: String

Required: No

observabilityRecommendations

Observability recommendations to address the finding.

Type: Array of [ObservabilityRecommendation](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

policyComponent

The policy component associated with the finding.

Type: String

Valid Values: AVAILABILITY_SLO | MULTI_AZ_DISASTER_RECOVERY |
MULTI_REGION_DISASTER_RECOVERY | DATA_RECOVERY

Required: No

reasoning

The reasoning behind the finding.

Type: String

Required: No

serviceFunctions

The service functions associated with the finding.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `\S{1,255}`

Required: No

severity

The severity of the finding.

Type: String

Valid Values: LOW | MEDIUM | HIGH

Required: No

status

The current status of the finding.

Type: String

Valid Values: OPEN | RESOLVED | IRRELEVANT

Required: No

testingRecommendations

Testing recommendations to address the finding.

Type: Array of [TestingRecommendation](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

updatedAt

The timestamp when the finding was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FindingSummary

Contains summary information about a finding.

Contents

description

Resource description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

failureCategory

The failure category of the finding.

Type: String

Valid Values: SHARED_FATE | EXCESSIVE_LOAD | EXCESSIVE_LATENCY | MISCONFIGURATION_AND_BUGS | SINGLE_POINT_OF_FAILURE

Required: No

findingId

The unique identifier of the finding.

Type: String

Length Constraints: Fixed length of 36.

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-5][0-9a-f]{3}-[089ab][0-9a-f]{3}-[0-9a-f]{12}

Required: No

name

The name of the finding.

Type: String

Required: No

policyComponent

The policy component associated with the finding.

Type: String

Valid Values: AVAILABILITY_SLO | MULTI_AZ_DISASTER_RECOVERY |
MULTI_REGION_DISASTER_RECOVERY | DATA_RECOVERY

Required: No

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9]
[A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-
[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/.-]{0,1023}`

Required: No

severity

The severity of the finding.

Type: String

Valid Values: LOW | MEDIUM | HIGH

Required: No

status

The current status of the finding.

Type: String

Valid Values: OPEN | RESOLVED | IRRELEVANT

Required: No

updatedAt

The timestamp when the finding was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InfrastructureAndCodeRecommendation

An infrastructure and code recommendation to address a finding.

Contents

suggestedChanges

The list of suggested changes.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InputSource

Identifies an input source by its identifier and type.

Contents

identifier

The identifier of the input source.

Type: String

Required: Yes

type

The type of the input source.

Type: String

Valid Values: CFN_STACK | TAGS | EKS | TERRAFORM | DESIGN_FILE | MONITORING

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InputSourceSummary

Contains summary information about an input source for a service.

Contents

inputSourceId

The unique identifier of the input source.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `\S{1,255}`

Required: Yes

cfnStackArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_.-]{0,1023}`

Required: No

createdAt

The timestamp when the input source was created.

Type: Timestamp

Required: No

designFileS3Url

S3 URL — virtual hosted-style or s3:// URL.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `((https://([^\s]+)\.s3[^\s]*\.[^\s]+)|(s3://([^\s]+)))/\S{1,2000}`

Required: No

eks

The Amazon EKS configuration, if this input source uses EKS.

Type: [EksSource](#) object

Required: No

resourceTags

The resource tags used for discovery, if this input source uses tags.

Type: Array of [ResourceTag](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

tfStateFileUrl

S3 URL — virtual hosted-style or s3:// URI.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `((https://([^\s]+)\.s3[^\s]*\.[^\s]+)|(s3://([^\s]+)))/\S{1,2000}`

Required: No

type

The type of the input source.

Type: String

Valid Values: CFN_STACK | TAGS | EKS | TERRAFORM | DESIGN_FILE | MONITORING

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LoggingConfiguration

Configuration for test execution logging destinations.

Contents

cloudWatchLogGroupArn

The ARN of the CloudWatch Logs log group for log delivery.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: No

logSchemaVersion

The version of the log schema.

Type: String

Required: No

s3BucketName

The name of the S3 bucket for log delivery.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MultiAzTargets

Defines the multi-AZ disaster recovery targets for a resilience policy.

Contents

disasterRecoveryApproach

The disaster recovery approach for multi-AZ.

Type: String

Valid Values: ACTIVE_ACTIVE | HOT_STANDBY | WARM_STANDBY | PILOT_LIGHT | BACKUP_AND_RESTORE

Required: No

rpoInMinutes

The recovery point objective (RPO) target for multi-AZ, in minutes.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

rtoInMinutes

The recovery time objective (RTO) target for multi-AZ, in minutes.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MultiRegionTargets

Defines the multi-Region disaster recovery targets for a resilience policy.

Contents

disasterRecoveryApproach

The disaster recovery approach for multi-Region.

Type: String

Valid Values: ACTIVE_ACTIVE | HOT_STANDBY | WARM_STANDBY | PILOT_LIGHT | BACKUP_AND_RESTORE

Required: No

rpoInMinutes

The recovery point objective (RPO) target for multi-Region, in minutes.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

rtoInMinutes

The recovery time objective (RTO) target for multi-Region, in minutes.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ObservabilityAlarmInput

Identifies an observability alarm by its ARN.

Contents

alarmArn

The ARN of the CloudWatch alarm.

Type: String

Length Constraints: Minimum length of 31. Maximum length of 1024.

Pattern: `arn:aws[a-zA-Z-]*:cloudwatch:[a-z]{2}(-[a-z]+)+-\d{1}:\d{12}:alarm:.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ObservabilityAlarmSummary

Summary information about a configured observability alarm.

Contents

accountId

The account ID that owns the CloudWatch alarm.

Type: String

Required: Yes

alarmArn

The ARN of the CloudWatch alarm.

Type: String

Length Constraints: Minimum length of 31. Maximum length of 1024.

Pattern: `arn:aws[a-zA-Z-]*:cloudwatch:[a-z]{2}(-[a-z]+)+-\d{1}:\d{12}:alarm:.`

Required: Yes

alarmName

The name of the CloudWatch alarm.

Type: String

Required: Yes

region

The Region of the CloudWatch alarm.

Type: String

Required: Yes

createdAt

The timestamp when the source was configured.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ObservabilityRecommendation

An observability recommendation to address a finding.

Contents

suggestedChanges

The list of suggested observability changes.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PermissionModel

Defines the permission model for a service.

Contents

invokerRoleName

IAM role name (supports up to 64 characters per IAM limits).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 576.

Pattern: ([A-Za-z0-9_+=, .@\-]+/)*[A-Za-z0-9_+=, .@\-]+

Required: Yes

crossAccountRoles

The list of cross-account IAM role ARNs.

Type: Array of [CrossAccountRole](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Policy

Represents a resilience policy that defines availability and disaster recovery requirements.

Contents

name

Resource name (used in ARN — no spaces allowed).

Type: String

Length Constraints: Minimum length of 2. Maximum length of 60.

Pattern: `[A-Za-z0-9][A-Za-z0-9_\-]{1,59}`

Required: Yes

policyArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

associatedServiceCount

The number of services associated with this policy.

Type: Integer

Required: No

availabilitySlo

The availability SLO defined in the policy.

Type: [AvailabilitySlo](#) object

Required: No

createdAt

The timestamp when the policy was created.

Type: Timestamp

Required: No

dataRecovery

The data recovery targets defined in the policy.

Type: [DataRecoveryTargets](#) object

Required: No

description

Resource description for services and policies.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 615.

Required: No

kmsKeyId

KMS key identifier — accepts key ID, key ARN, alias name, or alias ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

multiAz

The multi-AZ disaster recovery targets defined in the policy.

Type: [MultiAzTargets](#) object

Required: No

multiRegion

The multi-Region disaster recovery targets defined in the policy.

Type: [MultiRegionTargets](#) object

Required: No

tags

Resource tags.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `[^\x00-\x1f\x22]+`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `[^\x00-\x1f\x22]*`

Required: No

updatedAt

The timestamp when the policy was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PolicySummary

Contains summary information about a resilience policy.

Contents

name

Resource name (used in ARN — no spaces allowed).

Type: String

Length Constraints: Minimum length of 2. Maximum length of 60.

Pattern: `[A-Za-z0-9][A-Za-z0-9_\-]{1,59}`

Required: Yes

policyArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

associatedServiceCount

The number of services associated with this policy.

Type: Integer

Required: No

availabilitySlo

The availability SLO defined in the policy.

Type: [AvailabilitySlo](#) object

Required: No

createdAt

The timestamp when the policy was created.

Type: Timestamp

Required: No

dataRecovery

The data recovery targets defined in the policy.

Type: [DataRecoveryTargets](#) object

Required: No

multiAz

The multi-AZ disaster recovery targets defined in the policy.

Type: [MultiAzTargets](#) object

Required: No

multiRegion

The multi-Region disaster recovery targets defined in the policy.

Type: [MultiRegionTargets](#) object

Required: No

updatedAt

The timestamp when the policy was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

QueryDataPoint

A data point in a dependency query range.

Contents

queryCount

The number of queries at this data point.

Type: Long

Required: Yes

timestamp

The timestamp of the data point.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

QueryRange

Defines a time range for dependency query data.

Contents

dataPoints

The data points within the query range.

Type: Array of [QueryDataPoint](#) objects

Array Members: Minimum number of 7 items. Maximum number of 24 items.

Required: Yes

endTime

The end time of the query range.

Type: Timestamp

Required: Yes

granularity

The granularity of the query range data points.

Type: String

Valid Values: HOURLY | DAILY

Required: Yes

startTime

The start time of the query range.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ReportGenerationResult

Result of a report generation attempt.

Contents

reportType

The type of the generated report.

Type: String

Valid Values: FAILURE_MODE | TESTING

Required: Yes

status

The status of the report generation.

Type: String

Valid Values: PENDING | SUCCEEDED | FAILED

Required: Yes

assessmentId

Present for FAILURE_MODE reports.

Type: String

Length Constraints: Fixed length of 36.

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-5][0-9a-f]{3}-[089ab][0-9a-f]{3}-[0-9a-f]{12}

Required: No

createdAt

The timestamp when the report was created.

Type: Timestamp

Required: No

reportOutput

Present when status is SUCCEEDED or FAILED.

Type: [ReportOutput](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

serviceArn

The service this report was generated for.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: No

testRunId

The unique identifier of a test run.

Type: String

Length Constraints: Minimum length of 1.

Required: No

testTemplateArn

An ARN owned by the service. Accepts either a standard 12-digit account ID or the literal "aws" for AWS-managed resources, such as AWS-managed test templates.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):([0-9]{12}|aws):[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ReportOutput

Union of possible report outputs.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

failedReportOutput

Details when report generation failed.

Type: [FailedReportOutput](#) object

Required: No

s3ReportOutput

The S3 location where the report was written.

Type: [S3ReportOutput](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ReportOutputConfiguration

Configuration for a report output destination.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

s3

S3 configuration for report output.

Type: [S3ReportOutputConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResolvedTargetResource

A single AWS resource that AWS Fault Injection Service (AWS FIS) resolved as a target during a test run.

Contents

resourceType

The AWS FIS resource type the target belongs to, such as `aws:ec2:instance`, `aws:ecs:task`, or `aws:eks:pod`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

targetInformation

The raw target information map as returned by AWS FIS.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: Yes

targetName

The name of the target in the AWS FIS experiment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Resource

Represents an AWS resource discovered by Resilience Hub.

Contents

identifier

The identifier of the resource.

Type: String

Required: Yes

awsAccountId

The AWS account ID that owns the resource.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d{12}`

Required: No

awsRegion

The AWS Region where the resource is located.

Type: String

Length Constraints: Minimum length of 6.

Pattern: `[a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]`

Required: No

resourceType

The type of the resource.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceConfiguration

Resource configuration for an input source. Provide exactly one field.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

cfnStackArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: No

designFileS3Url

S3 URL — virtual hosted-style or s3:// URL.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: `((https://([^\./]+)\.s3[^\./]*\.[^\./]+)|(s3://([^\./]+)))/\S{1,2000}`

Required: No

eks

The Amazon EKS configuration for resource discovery.

Type: [EksSource](#) object

Required: No

resourceTags

The resource tags for tag-based resource discovery.

Type: Array of [ResourceTag](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

tfStateFileUrl

S3 URL — virtual hosted-style or s3:// URI.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2000.

Pattern: ((https://([^\./]+)\.s3[^\./]*\.[^\./]+)|(s3://([^\./]+)))/\S{1,2000}

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceDiscoveryStatus

Contains the status of resource discovery for a service.

Contents

errorCode

The error code if resource discovery failed.

Type: String

Valid Values: INVALID_PERMISSIONS | STACK_NOT_FOUND | CLUSTER_NOT_FOUND
| STATE_FILE_NOT_FOUND | ACCESS_DENIED | UNSUPPORTED_CLUSTER |
INTERNAL_ERROR

Required: No

errorMessage

A message describing the error if resource discovery failed.

Type: String

Required: No

lastRunAt

The timestamp of the last resource discovery run.

Type: Timestamp

Required: No

status

The current status of resource discovery.

Type: String

Valid Values: RUNNING | SUCCEEDED | FAILED | COMPLETED_WITH_FAILURES |
NOT_STARTED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceTag

A tag key-value pair used for resource discovery.

Contents

key

Tag key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[^\x00-\x1f\x22]+`

Required: Yes

values

The list of tag values.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[^\x00-\x1f\x22]*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3ReportOutput

S3 location where report was written.

Contents

s3ObjectKey

The S3 object key for the generated report.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3ReportOutputConfiguration

S3 configuration for report output.

Contents

bucketOwner

Account ID of the bucket owner for cross-account access verification.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d{12}`

Required: Yes

bucketPath

S3 bucket path where reports will be written (e.g., my-bucket/ngrh-reports/).

Type: String

Length Constraints: Minimum length of 3. Maximum length of 512.

Pattern: `(s3://)?[a-z0-9][a-z0-9.-]{1,61}[a-z0-9](/.*)?`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Service

Represents a service in Resilience Hub. A service is the primary unit of resilience assessment.

Contents

name

Resource name (used in ARN — no spaces allowed).

Type: String

Length Constraints: Minimum length of 2. Maximum length of 60.

Pattern: `[A-Za-z0-9][A-Za-z0-9_\-]{1,59}`

Required: Yes

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

accountId

The AWS account ID that owns the service.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `[0-9]{12}`

Required: No

achievability

The achievability status of the service's resilience targets.

Type: [Achievability](#) object

Required: No

assessmentStatus

The current assessment status of the service.

Type: String

Valid Values: NOT_STARTED | PENDING | IN_PROGRESS | FAILED | SUCCESS

Required: No

associatedSystems

The systems associated with the service.

Type: Array of [AssociatedSystem](#) objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: No

createdAt

The timestamp when the service was created.

Type: Timestamp

Required: No

dependencyDiscovery

The dependency discovery configuration for the service.

Type: [DependencyDiscoveryConfig](#) object

Required: No

description

Resource description for services and policies.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 615.

Required: No

effectivePolicyValues

The effective policy values for the service.

Type: [EffectivePolicyValues](#) object

Required: No

estimatedAssessmentCost

The estimated cost of running an assessment on the service.

Type: [AssessmentCost](#) object

Required: No

kmsKeyId

KMS key identifier — accepts key ID, key ARN, alias name, or alias ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

openFindingsCount

The number of open findings for the service.

Type: Integer

Required: No

organizationId

The AWS Organizations identifier for the service.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 34.

Pattern: o-[a-z0-9]{10,32}

Required: No

ould

The organizational unit (OU) identifier for the service.

Type: String

Length Constraints: Minimum length of 16. Maximum length of 68.

Pattern: ou-[a-z0-9]{4,32}-[a-z0-9]{8,32}

Required: No

permissionModel

The permission model for the service.

Type: [PermissionModel](#) object

Required: No

policyArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1})-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}: [A-Za-z0-9/][A-Za-z0-9:_/.-]{0,1023}

Required: No

regions

The Regions where the service operates.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 6.

Pattern: `[a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]`

Required: No

reportConfiguration

Configuration for automatic report generation on a Service.

Type: [ServiceReportConfiguration](#) object

Required: No

rerunAssessment

Indicates whether the assessment should be rerun.

Type: Boolean

Required: No

resolvedFindingsCount

The number of resolved findings for the service.

Type: Integer

Required: No

resourceDiscovery

The resource discovery status for the service.

Type: [ResourceDiscoveryStatus](#) object

Required: No

tags

Resource tags.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `[^\x00-\x1f\x22]+`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `[^\x00-\x1f\x22]*`

Required: No

updatedAt

The timestamp when the service was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceAchievabilityUpdatedMetadata

Metadata for a service achievability updated event.

Contents

assessmentId

The assessment identifier that triggered the update.

Type: String

Required: No

availabilitySlo

The updated achievability status of the availability SLO.

Type: String

Required: No

multiAzRtoRpo

The updated achievability status of the multi-AZ RTO and RPO targets.

Type: String

Required: No

multiRegionRtoRpo

The updated achievability status of the multi-Region RTO and RPO targets.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceCreatedMetadata

Metadata for a service created event.

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceDeletedMetadata

Metadata for a service deleted event.

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceEvent

Represents an event in the service event log.

Contents

actor

The actor that triggered the event.

Type: [EventActor](#) object

Required: Yes

eventDetails

The details of the event.

Type: [ServiceEventDetails](#) object

Required: Yes

eventId

The unique identifier of the event.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-5][0-9a-f]{3}-[089ab][0-9a-f]{3}-[0-9a-f]{12}`

Required: Yes

eventType

The type of the event.

Type: String

Valid Values: `SERVICE_CREATED` | `SERVICE_DELETED` | `SERVICE_SYSTEM_ASSOCIATED` | `SERVICE_SYSTEM_DISASSOCIATED` | `SERVICE_RESOURCES_ASSOCIATED` | `SERVICE_RESOURCES_DISASSOCIATED` | `SERVICE_WORKFLOW_UPDATED`

| SERVICE_INPUT_SOURCES_UPDATED | SERVICE_POLICY_ASSOCIATED
| SERVICE_POLICY_DISASSOCIATED | SERVICE_FUNCTION_CREATED
| SERVICE_FUNCTION_UPDATED | SERVICE_FUNCTION_DELETED |
SERVICE_FUNCTION_RESOURCES_ADDED | SERVICE_FUNCTION_RESOURCES_REMOVED |
SERVICE_ACHIEVABILITY_UPDATED | ASSERTION_CREATED | ASSERTION_UPDATED |
ASSERTION_DELETED

Required: Yes

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

timestamp

The timestamp of the event.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceEventDetails

Contains the details of a service event.

Contents

description

The description of the event.

Type: String

Required: Yes

title

The title of the event.

Type: String

Required: Yes

eventMetadata

Type-specific metadata for each service event type.

Type: [ServiceEventMetadata](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceEventMetadata

Type-specific metadata for each service event type.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

assertionCreated

Metadata for an assertion created event.

Type: [AssertionCreatedMetadata](#) object

Required: No

assertionDeleted

Metadata for an assertion deleted event.

Type: [AssertionDeletedMetadata](#) object

Required: No

assertionUpdated

Metadata for an assertion updated event.

Type: [AssertionUpdatedMetadata](#) object

Required: No

serviceAchievabilityUpdated

Metadata for a service achievability updated event.

Type: [ServiceAchievabilityUpdatedMetadata](#) object

Required: No

serviceCreated

Metadata for a service created event.

Type: [ServiceCreatedMetadata](#) object

Required: No

serviceDeleted

Metadata for a service deleted event.

Type: [ServiceDeletedMetadata](#) object

Required: No

serviceFunctionCreated

Metadata for a service function created event.

Type: [ServiceFunctionCreatedMetadata](#) object

Required: No

serviceFunctionDeleted

Metadata for a service function deleted event.

Type: [ServiceFunctionDeletedMetadata](#) object

Required: No

serviceFunctionResourcesAdded

Metadata for a service function resources added event.

Type: [ServiceFunctionResourcesAddedMetadata](#) object

Required: No

serviceFunctionResourcesRemoved

Metadata for a service function resources removed event.

Type: [ServiceFunctionResourcesRemovedMetadata](#) object

Required: No

serviceFunctionUpdated

Metadata for a service function updated event.

Type: [ServiceFunctionUpdatedMetadata](#) object

Required: No

serviceInputSourcesUpdated

Metadata for a service input sources updated event.

Type: [ServiceInputSourcesUpdatedMetadata](#) object

Required: No

servicePolicyAssociated

Metadata for a service policy associated event.

Type: [ServicePolicyAssociatedMetadata](#) object

Required: No

servicePolicyDisassociated

Metadata for a service policy disassociated event.

Type: [ServicePolicyDisassociatedMetadata](#) object

Required: No

serviceResourcesAssociated

Metadata for a service resources associated event.

Type: [ServiceResourcesAssociatedMetadata](#) object

Required: No

serviceResourcesDisassociated

Metadata for a service resources disassociated event.

Type: [ServiceResourcesDisassociatedMetadata](#) object

Required: No

serviceSystemAssociated

Metadata for a service system associated event.

Type: [ServiceSystemAssociatedMetadata](#) object

Required: No

serviceSystemDisassociated

Metadata for a service system disassociated event.

Type: [ServiceSystemDisassociatedMetadata](#) object

Required: No

serviceWorkflowUpdated

Metadata for a service workflow updated event.

Type: [ServiceWorkflowUpdatedMetadata](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceFunction

Represents a logical component of a service.

Contents

criticality

The criticality level of the service function.

Type: String

Valid Values: PRIMARY | SUPPLEMENTAL

Required: Yes

name

Entity label (not part of ARN — spaces allowed).

Type: String

Length Constraints: Minimum length of 2. Maximum length of 60.

Pattern: `[A-Za-z0-9][A-Za-z0-9 _\-]{1,59}`

Required: Yes

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

serviceFunctionId

The unique identifier of the service function.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: \S{1,255}

Required: Yes

createdAt

The timestamp when the service function was created.

Type: Timestamp

Required: No

description

Resource description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

resourceCount

The number of resources associated with the service function.

Type: Integer

Required: No

source

The source of the service function.

Type: String

Valid Values: AI_GENERATED | USER

Required: No

updatedAt

The timestamp when the service function was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceFunctionCreatedMetadata

Metadata for a service function created event.

Contents

serviceFunctionId

The identifier of the created service function.

Type: String

Required: No

serviceFunctionName

The name of the created service function.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceFunctionDeletedMetadata

Metadata for a service function deleted event.

Contents

serviceFunctionId

The identifier of the deleted service function.

Type: String

Required: No

serviceFunctionName

The name of the deleted service function.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceFunctionResourcesAddedMetadata

Metadata for a service function resources added event.

Contents

resourcesAdded

The list of resource ARNs that were added.

Type: Array of strings

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1})-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: No

serviceFunctionId

The identifier of the service function.

Type: String

Required: No

serviceFunctionName

The name of the service function.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceFunctionResourcesRemovedMetadata

Metadata for a service function resources removed event.

Contents

resourcesRemoved

The list of resource ARNs that were removed.

Type: Array of strings

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: No

serviceFunctionId

The identifier of the service function.

Type: String

Required: No

serviceFunctionName

The name of the service function.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceFunctionUpdatedMetadata

Metadata for a service function updated event.

Contents

resourcesAdded

The list of resource ARNs that were added.

Type: Array of strings

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: No

resourcesRemoved

The list of resource ARNs that were removed.

Type: Array of strings

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: No

serviceFunctionId

The identifier of the service function.

Type: String

Required: No

serviceFunctionName

The name of the service function.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceInputSourcesUpdatedMetadata

Metadata for a service input sources updated event.

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServicePolicyAssociatedMetadata

Metadata for a service policy associated event.

Contents

policyArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: No

policyName

The name of the associated policy.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServicePolicyDisassociatedMetadata

Metadata for a service policy disassociated event.

Contents

policyArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: No

policyName

The name of the disassociated policy.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceReference

A reference to a service by ID and name.

Contents

serviceId

The identifier of the referenced service.

Type: String

Required: No

serviceName

The name of the referenced service.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceReferenceChanges

Describes changes to service references.

Contents

added

The list of service references that were added.

Type: Array of [ServiceReference](#) objects

Required: No

removed

The list of service references that were removed.

Type: Array of [ServiceReference](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceReportConfiguration

Configuration for automatic report generation on a Service.

Contents

reportOutputs

Output destinations for generated reports.

Type: Array of [ReportOutputConfiguration](#) objects

Array Members: Fixed number of 1 item.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceResource

Represents a resource associated with a service.

Contents

resource

The resource details.

Type: [Resource](#) object

Required: Yes

resourceIdentifier

The identifier of the resource.

Type: String

Required: Yes

inputSource

The input source that discovered the resource.

Type: [InputSource](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceResourcesAssociatedMetadata

Metadata for a service resources associated event.

Contents

resourceCount

The number of resources associated.

Type: Integer

Required: No

resourceTypes

The types of resources associated.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceResourcesDisassociatedMetadata

Metadata for a service resources disassociated event.

Contents

resourceCount

The number of resources disassociated.

Type: Integer

Required: No

resourceTypes

The types of resources disassociated.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceSummary

Contains summary information about a service.

Contents

name

Resource name (used in ARN — no spaces allowed).

Type: String

Length Constraints: Minimum length of 2. Maximum length of 60.

Pattern: `[A-Za-z0-9][A-Za-z0-9_\-]{1,59}`

Required: Yes

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

accountId

Displayed only if caller has access.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `[0-9]{12}`

Required: No

achievability

The achievability status of the service's resilience targets.

Type: [Achievability](#) object

Required: No

assessmentStatus

The current assessment status of the service.

Type: String

Valid Values: NOT_STARTED | PENDING | IN_PROGRESS | FAILED | SUCCESS

Required: No

associatedSystems

The systems associated with the service.

Type: Array of [AssociatedSystem](#) objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: No

createdAt

The timestamp when the service was created.

Type: Timestamp

Required: No

dependencyDiscovery

The dependency discovery configuration.

Type: [DependencyDiscoveryConfig](#) object

Required: No

openFindingsCount

The number of open findings.

Type: Integer

Required: No

organizationId

Displayed only if caller has access.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 34.

Pattern: o-[a-z0-9]{10,32}

Required: No

ould

Displayed only if caller has access.

Type: String

Length Constraints: Minimum length of 16. Maximum length of 68.

Pattern: ou-[a-z0-9]{4,32}-[a-z0-9]{8,32}

Required: No

policyArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1})-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}: [A-Za-z0-9/] [A-Za-z0-9:_/+.-]{0,1023}

Required: No

regions

The Regions where the service operates.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 6.

Pattern: `[a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]`

Required: No

resolvedFindingsCount

The number of resolved findings.

Type: Integer

Required: No

updatedAt

The timestamp when the service was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceSystemAssociatedMetadata

Metadata for a service system associated event.

Contents

systemArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: No

systemName

The name of the associated system.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceSystemDisassociatedMetadata

Metadata for a service system disassociated event.

Contents

systemArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: No

systemId

The identifier of the disassociated system.

Type: String

Required: No

systemName

The name of the disassociated system.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceTopologyEdgeSummary

Contains summary information about a service topology edge.

Contents

destinationResourceIdentifier

The identifier of the destination resource.

Type: String

Required: Yes

sourceResourceIdentifier

The identifier of the source resource.

Type: String

Required: Yes

destinationAccount

The AWS account ID of the destination resource.

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d{12}

Required: No

destinationRegion

The AWS Region of the destination resource.

Type: String

Length Constraints: Minimum length of 6.

Pattern: [a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]

Required: No

properties

The properties of the topology edge.

Type: Array of [EdgePropertySummary](#) objects

Array Members: Minimum number of 0 items. Maximum number of 3 items.

Required: No

sourceAccount

The AWS account ID of the source resource.

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d{12}

Required: No

sourceRegion

The AWS Region of the source resource.

Type: String

Length Constraints: Minimum length of 6.

Pattern: [a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceWorkflowUpdatedMetadata

Metadata for a service workflow updated event.

Contents

serviceFunctionId

The identifier of the service function.

Type: String

Required: No

serviceFunctionName

The name of the service function.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SloSource

Contains the effective availability SLO value and its source.

Contents

policyName

Resource name (used in ARN — no spaces allowed).

Type: String

Length Constraints: Minimum length of 2. Maximum length of 60.

Pattern: `[A-Za-z0-9][A-Za-z0-9_\-]{1,59}`

Required: No

source

Indicates whether the value comes from the service's own account or a cross-account policy.

Type: String

Valid Values: SELF | CROSS_ACCOUNT

Required: No

value

The availability SLO percentage value.

Type: Double

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

StopCondition

A CloudWatch alarm that automatically stops a test run if it breaches its threshold.

Contents

source

The source of the stop condition.

Type: String

Valid Values: `aws:cloudwatch:alarm` | `none`

Required: Yes

value

The value of the stop condition, such as the ARN of the CloudWatch alarm.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

StringChange

Describes a change from one string value to another.

Contents

newValue

The new value.

Type: String

Required: No

oldValue

The old value.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SuccessCriteriaAlarmInput

Identifies a success criteria alarm by its ARN.

Contents

alarmArn

The ARN of the CloudWatch alarm.

Type: String

Length Constraints: Minimum length of 31. Maximum length of 1024.

Pattern: `arn:aws[a-zA-Z-]*:cloudwatch:[a-z]{2}(-[a-z]+)+-\d{1}:\d{12}:alarm:.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SuccessCriteriaAlarmSummary

Summary information about a configured success criteria alarm.

Contents

accountId

The account ID that owns the CloudWatch alarm.

Type: String

Required: Yes

alarmArn

The ARN of the CloudWatch alarm.

Type: String

Length Constraints: Minimum length of 31. Maximum length of 1024.

Pattern: `arn:aws[a-zA-Z-]*:cloudwatch:[a-z]{2}(-[a-z]+)+-\d{1}:\d{12}:alarm:.`

Required: Yes

alarmName

The name of the CloudWatch alarm.

Type: String

Required: Yes

region

The Region of the CloudWatch alarm.

Type: String

Required: Yes

createdAt

The timestamp when the source was configured.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

System

Represents a system in Resilience Hub. A system is a logical grouping of services.

Contents

name

Resource name (used in ARN — no spaces allowed).

Type: String

Length Constraints: Minimum length of 2. Maximum length of 60.

Pattern: `[A-Za-z0-9][A-Za-z0-9_\-]{1,59}`

Required: Yes

systemArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}: [A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

systemId

System ID for cross-account use without exposing account structure.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `\S{1,255}`

Required: Yes

createdAt

The timestamp when the system was created.

Type: Timestamp

Required: No

description

Resource description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

kmsKeyId

KMS key identifier — accepts key ID, key ARN, alias name, or alias ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

organizationId

The AWS Organizations identifier for the system.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 34.

Pattern: o-[a-z0-9]{10,32}

Required: No

ouId

The organizational unit (OU) identifier for the system.

Type: String

Length Constraints: Minimum length of 16. Maximum length of 68.

Pattern: ou-[a-z0-9]{4,32}-[a-z0-9]{8,32}

Required: No

sharingEnabled

Indicates whether cross-account sharing is enabled.

Type: Boolean

Required: No

tags

Resource tags.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: [[^]\x00-\x1f\x22]+

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: [[^]\x00-\x1f\x22]*

Required: No

updatedAt

The timestamp when the system was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SystemCreatedMetadata

Metadata for a system created event.

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SystemDeletedMetadata

Metadata for a system deleted event.

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SystemEvent

Represents an event in the system event log.

Contents

actor

The actor that triggered the event.

Type: [EventActor](#) object

Required: Yes

eventDetails

The details of the event.

Type: [SystemEventDetails](#) object

Required: Yes

eventId

The unique identifier of the event.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-5][0-9a-f]{3}-[089ab][0-9a-f]{3}-[0-9a-f]{12}`

Required: Yes

eventType

The type of the event.

Type: String

Valid Values: `SYSTEM_CREATED | SYSTEM_DELETED | SYSTEM_USER_JOURNEY_CREATED | SYSTEM_USER_JOURNEY_UPDATED | SYSTEM_USER_JOURNEY_DELETED | SYSTEM_SERVICE_ASSOCIATED | SYSTEM_SERVICE_DISASSOCIATED | SYSTEM_POLICY_ASSOCIATED | SYSTEM_POLICY_DISASSOCIATED`

Required: Yes

systemArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

timestamp

The timestamp of the event.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SystemEventDetails

Contains the details of a system event.

Contents

description

The description of the event.

Type: String

Required: Yes

title

The title of the event.

Type: String

Required: Yes

eventMetadata

Type-specific metadata for each system event type.

Type: [SystemEventMetadata](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SystemEventMetadata

Type-specific metadata for each system event type.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

systemCreated

Metadata for a system created event.

Type: [SystemCreatedMetadata](#) object

Required: No

systemDeleted

Metadata for a system deleted event.

Type: [SystemDeletedMetadata](#) object

Required: No

systemPolicyAssociated

Metadata for a system policy associated event.

Type: [SystemPolicyAssociatedMetadata](#) object

Required: No

systemPolicyDisassociated

Metadata for a system policy disassociated event.

Type: [SystemPolicyDisassociatedMetadata](#) object

Required: No

systemServiceAssociated

Metadata for a system service associated event.

Type: [SystemServiceAssociatedMetadata](#) object

Required: No

systemServiceDisassociated

Metadata for a system service disassociated event.

Type: [SystemServiceDisassociatedMetadata](#) object

Required: No

systemUserJourneyCreated

Metadata for a system user journey created event.

Type: [SystemUserJourneyCreatedMetadata](#) object

Required: No

systemUserJourneyDeleted

Metadata for a system user journey deleted event.

Type: [SystemUserJourneyDeletedMetadata](#) object

Required: No

systemUserJourneyUpdated

Metadata for a system user journey updated event.

Type: [SystemUserJourneyUpdatedMetadata](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SystemPolicyAssociatedMetadata

Metadata for a system policy associated event.

Contents

policyArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: No

policyName

The name of the associated policy.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SystemPolicyDisassociatedMetadata

Metadata for a system policy disassociated event.

Contents

policyArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: No

policyName

The name of the disassociated policy.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SystemServiceAssociatedMetadata

Metadata for a system service associated event.

Contents

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1})-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: No

serviceName

The name of the associated service.

Type: String

Required: No

userJourneys

The user journeys linking the service to the system.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SystemServiceDisassociatedMetadata

Metadata for a system service disassociated event.

Contents

comment

A comment about the disassociation.

Type: String

Required: No

serviceArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: No

serviceName

The name of the disassociated service.

Type: String

Required: No

userJourneysAffected

The user journeys affected by the disassociation.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SystemSummary

Contains summary information about a system.

Contents

name

Resource name (used in ARN — no spaces allowed).

Type: String

Length Constraints: Minimum length of 2. Maximum length of 60.

Pattern: `[A-Za-z0-9][A-Za-z0-9_\-]{1,59}`

Required: Yes

systemId

System ID for cross-account use without exposing account structure.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `\S{1,255}`

Required: Yes

createdAt

The timestamp when the system was created.

Type: Timestamp

Required: No

organizationId

Displayed only if caller has access.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 34.

Pattern: o-[a-z0-9]{10,32}

Required: No

ould

Displayed only if caller has access.

Type: String

Length Constraints: Minimum length of 16. Maximum length of 68.

Pattern: ou-[a-z0-9]{4,32}-[a-z0-9]{8,32}

Required: No

servicesCount

The number of services in the system.

Type: Integer

Required: No

systemArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1})-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/.-]{0,1023}

Required: No

updatedAt

The timestamp when the system was last updated.

Type: Timestamp

Required: No

userJourneysCount

The number of user journeys in the system.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SystemUserJourneyCreatedMetadata

Metadata for a system user journey created event.

Contents

associatedServices

The services associated with the created user journey.

Type: Array of [ServiceReference](#) objects

Required: No

userJourneyName

The name of the created user journey.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SystemUserJourneyDeletedMetadata

Metadata for a system user journey deleted event.

Contents

associatedServicesAtDeletion

The services that were associated at the time of deletion.

Type: Array of [ServiceReference](#) objects

Required: No

userJourneyName

The name of the deleted user journey.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SystemUserJourneyUpdatedMetadata

Metadata for a system user journey updated event.

Contents

changes

The changes made to the user journey.

Type: [UserJourneyChanges](#) object

Required: No

userJourneyName

The name of the updated user journey.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TargetSource

Contains an effective RTO or RPO value and its source.

Contents

policyName

Resource name (used in ARN — no spaces allowed).

Type: String

Length Constraints: Minimum length of 2. Maximum length of 60.

Pattern: `[A-Za-z0-9][A-Za-z0-9_\-]{1,59}`

Required: No

source

Indicates whether the value comes from the service's own account or a cross-account policy.

Type: String

Valid Values: SELF | CROSS_ACCOUNT

Required: No

value

The RTO or RPO value in minutes.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

Test

Represents a test created for a service by configuring a test template.

Contents

creationTime

The timestamp when the test was created.

Type: Timestamp

Required: Yes

name

The name of the test.

Type: String

Required: Yes

serviceArn

The ARN of the service the test belongs to.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1})-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

successfulTestRuns

The number of successful runs of the test.

Type: Integer

Required: Yes

testId

The unique identifier of the test.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

testTemplateArn

The ARN of the test template the test was created from.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):([0-9]{12}|aws):[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

totalTestRuns

The total number of runs of the test.

Type: Integer

Required: Yes

actions

The fault actions the test runs.

Type: Array of [TestAction](#) objects

Required: No

loggingConfiguration

The logging configuration for the test.

Type: [LoggingConfiguration](#) object

Required: No

parameters

The parameter values configured for the test.

Type: String to array of strings map

Map Entries: Minimum number of 0 items. Maximum number of 20 items.

Key Length Constraints: Minimum length of 1. Maximum length of 256.

Key Pattern: `[\w.-]+`

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

roleName

The name of the IAM execution role used to run the test.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 576.

Pattern: `([A-Za-z0-9_+=,.\@-]+/)*[A-Za-z0-9_+=,.\@-]+`

Required: No

stopConditions

The stop conditions for the test.

Type: Array of [StopCondition](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestAction

Represents a fault action that a test runs, along with the resource type it targets.

Contents

actionId

The identifier of the fault action.

Type: String

Required: Yes

resourceType

The resource type that the action targets.

Type: String

Required: Yes

description

A description of the fault action.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestingRecommendation

A testing recommendation to address a finding.

Contents

suggestedChanges

The list of suggested testing changes.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestRun

Represents a single run of a test. Configuration is snapshotted from the test and service at the time the run is started.

Contents

startedAt

The timestamp when the test run started.

Type: Timestamp

Required: Yes

status

The current status of the test run.

Type: String

Valid Values: INITIALIZING | RUNNING | STOPPING | PASSED | FAILED | STOPPED
| ERROR

Required: Yes

testId

The identifier of the test that was run.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

testRunId

The unique identifier of the test run.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

testTemplateArn

The ARN of the test template snapshotted from the test when the run was started.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):([0-9]{12}|aws):[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

accountTargeting

Indicates whether the test run targets resources in a single AWS account or across multiple accounts.

Type: String

Valid Values: SINGLE_ACCOUNT | MULTI_ACCOUNT

Required: No

endedAt

The timestamp when the test run ended.

Type: Timestamp

Required: No

errorMessage

A human-readable reason for test run failure. Only present when the status is FAILED or ERROR.

Type: String

Required: No

eventCount

The number of events recorded for the test run. Use ListTestRunEvents to retrieve the details.

Type: Integer

Required: No

experiments

The AWS Fault Injection Service (AWS FIS) experiments run as part of the test run.

Type: Array of [ExperimentDetails](#) objects

Required: No

loggingConfiguration

The logging configuration snapshotted from the test when the run was started.

Type: [LoggingConfiguration](#) object

Required: No

parameters

The parameter values used for the test run.

Type: String to array of strings map

Map Entries: Minimum number of 0 items. Maximum number of 20 items.

Key Length Constraints: Minimum length of 1. Maximum length of 256.

Key Pattern: `[\w . - ]+`

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

permissionModel

The permission model snapshotted from the service when the run was started.

Type: [PermissionModel](#) object

Required: No

policy

The resilience policy snapshotted from the service when the run was started.

Type: [TestRunPolicySnapshot](#) object

Required: No

regions

The Regions snapshot from the service when the run was started.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 6.

Pattern: `[a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]`

Required: No

regionSwitchExecutionId

The identifier of the ARC Region switch execution detected during the test run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-z]{2}(-[a-z]+)-[0-9]+/[0-9a-fA-F]{16}`

Required: No

regionSwitchPlanArn

The ARN of the ARC Region switch plan associated with the test run.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9]/[A-Za-z0-9:_/.-]{0,1023}`

Required: No

reportConfiguration

The report configuration snapshot from the service when the run was started.

Type: [TestRunReportConfiguration](#) object

Required: No

reportOutput

The report generation result for the test run. Present after report generation completes or fails.

Type: [ReportGenerationResult](#) object

Required: No

roleName

The IAM execution role name snapshotted from the test when the run was started.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 576.

Pattern: ([A-Za-z0-9_+=,.\@\-]+/)*[A-Za-z0-9_+=,.\@\-]+

Required: No

serviceArn

The ARN of the service the test run belongs to.

Type: String

Length Constraints: Minimum length of 31.

Pattern: arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}: [A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}

Required: No

stopConditions

The stop conditions snapshotted from the test when the run was started.

Type: Array of [StopCondition](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestRunDependencySummary

Contains summary information about a dependency that a test run blocked, as captured when the run started.

Contents

criticality

The criticality classification of the dependency when the run started. A dependency that was not discovered has the UNKNOWN criticality.

Type: String

Valid Values: HARD | SOFT | UNKNOWN

Required: Yes

dependencyName

The name of the dependency.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

dnsName

The DNS name of the dependency that the test run blocked.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 253.

Required: Yes

source

The origin of the dependency. A discovered dependency was found by dependency discovery; a manual dependency was entered when the run started.

Type: String

Valid Values: DISCOVERED | MANUAL

Required: Yes

dependencyId

The unique identifier of the dependency. Absent when the dependency was entered manually and was not part of dependency discovery.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-5][0-9a-f]{3}-[089ab][0-9a-f]{3}-[0-9a-f]{12}`

Required: No

location

The location of the dependency.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

provider

The provider of the dependency.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

sourceRegions

The source Regions from which the dependency was detected.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 6.

Pattern: `[a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestRunEvent

A single event in a test run's timeline.

Contents

eventId

The unique identifier of the event.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

eventType

The type of the event, such as `action_started`, `action_completed`, or `rto_recovery_detected`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

message

A human-readable description of what happened.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

timestamp

The timestamp when the event occurred.

Type: Timestamp

Required: Yes

attributes

Machine-parseable key-value attributes for the event.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestRunObservabilityAlarmSummary

Summary information about an observability alarm snapshot captured for a test run.

Contents

accountId

The account ID that owns the CloudWatch alarm.

Type: String

Required: Yes

alarmArn

The ARN of the CloudWatch alarm.

Type: String

Length Constraints: Minimum length of 31. Maximum length of 1024.

Pattern: `arn:aws[a-zA-Z-]*:cloudwatch:[a-z]{2}(-[a-z]+)+-\d{1}:\d{12}:alarm:.+`

Required: Yes

alarmName

The name of the CloudWatch alarm.

Type: String

Required: Yes

region

The Region of the CloudWatch alarm.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestRunPolicySnapshot

A snapshot of the resilience policy captured onto a test run from the service when the run was started.

Contents

availabilitySlo

The availability SLO targets.

Type: [AvailabilitySlo](#) object

Required: No

dataRecovery

The data recovery targets.

Type: [DataRecoveryTargets](#) object

Required: No

multiAz

The multi-AZ resilience targets.

Type: [MultiAzTargets](#) object

Required: No

multiRegion

The multi-Region resilience targets.

Type: [MultiRegionTargets](#) object

Required: No

name

The name of the policy.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 60.

Pattern: `[A-Za-z0-9][A-Za-z0-9_\-]{1,59}`

Required: No

policyArn

The ARN of the policy.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestRunReportConfiguration

A snapshot of the report configuration captured onto a test run from the service when the run was started.

Contents

reportOutput

The output destinations for generated reports.

Type: Array of [ReportOutputConfiguration](#) objects

Array Members: Fixed number of 1 item.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestRunSourceEvent

A state-change event observed for a test run monitoring source.

Contents

detail

The event payload.

Type: [TestRunSourceEventDetail](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

eventType

The type of the event. ALARM indicates an event from a CloudWatch alarm source; the detail member carries either the alarm state change or a collection error.

Type: String

Valid Values: ALARM

Required: Yes

sourceArn

The ARN of the monitoring source the event belongs to.

Type: String

Length Constraints: Minimum length of 31. Maximum length of 1024.

Pattern: `arn:aws[a-zA-Z-]*:[a-z][a-z0-9-]*:[a-z]{2}(-[a-z]+)+-\d{1}:\d{12}:.+`

Required: Yes

timestamp

The timestamp when the event occurred.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestRunSourceEventDetail

The payload of a test run source event. Exactly one member is set.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

alarmStateChange

A CloudWatch alarm state change.

Type: [AlarmStateChangeDetail](#) object

Required: No

error

An error that prevented event collection from the source.

Type: [TestRunSourceEventError](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestRunSourceEventError

Describes an error that prevented event collection from a test run monitoring source.

Contents

errorCode

The error code.

Type: String

Valid Values: ACCESS_DENIED | INTERNAL_ERROR

Required: Yes

errorMessage

A human-readable description of the error.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestRunSourceSummary

A monitoring-source snapshot captured for a test run. Exactly one member is set.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

observabilityAlarm

An observability alarm snapshot captured for the test run.

Type: [TestRunObservabilityAlarmSummary](#) object

Required: No

successCriteriaAlarm

A success criteria alarm snapshot captured for the test run.

Type: [TestRunSuccessCriteriaAlarmSummary](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestRunSuccessCriteriaAlarmSummary

Summary information about a success criteria alarm snapshot captured for a test run.

Contents

accountId

The account ID that owns the CloudWatch alarm.

Type: String

Required: Yes

alarmArn

The ARN of the CloudWatch alarm.

Type: String

Length Constraints: Minimum length of 31. Maximum length of 1024.

Pattern: `arn:aws[a-zA-Z-]*:cloudwatch:[a-z]{2}(-[a-z]+)+-\d{1}:\d{12}:alarm:.`

Required: Yes

alarmName

The name of the CloudWatch alarm.

Type: String

Required: Yes

region

The Region of the CloudWatch alarm.

Type: String

Required: Yes

outcome

The evaluation outcome of the source. Absent while the source has not yet been evaluated; set to the terminal outcome afterwards.

Type: String

Valid Values: PASSED | FAILED | ERROR

Required: No

outcomeReason

A human-readable reason for the outcome.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestRunSummary

Contains summary information about a test run.

Contents

startedAt

The timestamp when the test run started.

Type: Timestamp

Required: Yes

status

The current status of the test run.

Type: String

Valid Values: INITIALIZING | RUNNING | STOPPING | PASSED | FAILED | STOPPED
| ERROR

Required: Yes

testRunId

The unique identifier of the test run.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

testTemplateArn

The ARN of the test template the test run was based on.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):([0-9]{12}|aws):[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

accountTargeting

Indicates whether the test run targets resources in a single AWS account or across multiple accounts.

Type: String

Valid Values: `SINGLE_ACCOUNT` | `MULTI_ACCOUNT`

Required: No

endedAt

The timestamp when the test run ended.

Type: Timestamp

Required: No

errorMessage

A human-readable reason for test run failure. Only present when the status is `FAILED` or `ERROR`.

Type: String

Required: No

serviceArn

The ARN of the service the test run belongs to.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestSourceInput

Identifies a monitoring source to add to or remove from a test. Exactly one member is set.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

observabilityAlarm

An observability alarm included for visibility only.

Type: [ObservabilityAlarmInput](#) object

Required: No

successCriteriaAlarm

A success criteria alarm that determines whether the test passes or fails.

Type: [SuccessCriteriaAlarmInput](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestSourceSummary

A configured monitoring source returned by ListTestSources. Exactly one member is set.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

observabilityAlarm

A configured observability alarm.

Type: [ObservabilityAlarmSummary](#) object

Required: No

successCriteriaAlarm

A configured success criteria alarm.

Type: [SuccessCriteriaAlarmSummary](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestSummary

Contains summary information about a test.

Contents

creationTime

The timestamp when the test was created.

Type: Timestamp

Required: Yes

serviceArn

The ARN of the service the test belongs to.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

successfulTestRuns

The number of successful runs of the test.

Type: Integer

Required: Yes

testId

The unique identifier of the test.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

testTemplateArn

The ARN of the test template the test was created from.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):([0-9]{12}|aws):[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

totalTestRuns

The total number of runs of the test.

Type: Integer

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestTemplate

A pre-configured, AWS recommended test that defines which resilience capability to validate, the fault actions it runs, and the parameters it accepts.

Contents

name

The name of the test template.

Type: String

Required: Yes

testTemplateArn

The ARN of the test template.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):([0-9]{12}|aws):[A-Za-z0-9/] [A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

actions

The fault actions the test template runs.

Type: Array of [TestAction](#) objects

Required: No

description

A description of the test template.

Type: String

Required: No

parameters

The parameters the test template accepts.

Type: Array of [TestTemplateParameter](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestTemplateParameter

Describes a parameter accepted by a test template.

Contents

name

The name of the parameter.

Type: String

Required: Yes

required

Indicates whether the parameter is required.

Type: Boolean

Required: Yes

type

The data type of the parameter.

Type: String

Valid Values: STRING | STRING_LIST | INTEGER

Required: Yes

defaultValue

The default value of the parameter.

Type: String

Required: No

description

A description of the parameter.

Type: String

Required: No

maxValues

The maximum number of values the parameter accepts.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestTemplateSummary

Contains summary information about a test template.

Contents

description

A description of the test template.

Type: String

Required: Yes

name

The name of the test template.

Type: String

Required: Yes

testTemplateArn

The ARN of the test template.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):([0-9]{12}|aws):[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UserJourney

Represents a user journey that defines a critical path through a system.

Contents

name

Entity label (not part of ARN — spaces allowed).

Type: String

Length Constraints: Minimum length of 2. Maximum length of 60.

Pattern: `[A-Za-z0-9][A-Za-z0-9 _\-]{1,59}`

Required: Yes

userJourneyId

The unique identifier of the user journey.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `\S{1,255}`

Required: Yes

createdAt

The timestamp when the user journey was created.

Type: Timestamp

Required: No

description

Resource description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

policyArn

ARN identifier.

Type: String

Length Constraints: Minimum length of 31.

Pattern: `arn:(aws|aws-cn|aws-iso|aws-iso-[a-z]{1}|aws-us-gov):[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:([a-z]{2}-((iso[a-z]{0,1}-)|(gov-)){0,1}[a-z]+-[0-9]):[0-9]{12}:[A-Za-z0-9/][A-Za-z0-9:_/+.-]{0,1023}`

Required: No

updatedAt

The timestamp when the user journey was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UserJourneyChanges

Describes changes made to a user journey.

Contents

associatedServices

Changes to the services associated with the user journey.

Type: [ServiceReferenceChanges](#) object

Required: No

journeyDescription

Changes to the user journey description.

Type: [StringChange](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UserJourneySummary

Contains summary information about a user journey.

Contents

name

Entity label (not part of ARN — spaces allowed).

Type: String

Length Constraints: Minimum length of 2. Maximum length of 60.

Pattern: `[A-Za-z0-9][A-Za-z0-9 _\-]{1,59}`

Required: Yes

userJourneyId

The unique identifier of the user journey.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `\S{1,255}`

Required: Yes

createdAt

The timestamp when the user journey was created.

Type: Timestamp

Required: No

updatedAt

The timestamp when the user journey was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ValidationExceptionField

Describes a field that failed validation.

Contents

message

The validation error message for the field.

Type: String

Required: Yes

name

The name of the field that failed validation.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Error Types

This section lists common error types that this AWS service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

IncompleteSignature

The request signature doesn't conform to AWS standards. Verify that you're using valid AWS credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 403

InternalFailure

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact AWS Support.

HTTP Status Code: 500

MalformedHttpRequestException

The request body can't be processed. This typically happens when the request body can't be decompressed using the specified content encoding algorithm. Verify that the content encoding header matches the compression format used.

HTTP Status Code: 400

NotAuthorized

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

OptInRequired

Your AWS account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

RequestAbortedException

The request was aborted before a response could be returned. This typically happens when the client closes the connection.

HTTP Status Code: 400

RequestEntityTooLargeException

The request entity is too large. Reduce the size of the request body and try again.

HTTP Status Code: 413

RequestTimeoutException

The request timed out. The server didn't receive the complete request within the expected time frame. Try again.

HTTP Status Code: 408

ServiceUnavailable

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

ThrottlingException

Your request rate is too high. The AWS SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

UnknownOperationException

The action or operation isn't recognized. Verify that the action name is spelled correctly and that it's supported by the API version you're using.

HTTP Status Code: 404

UnrecognizedClientException

The X.509 certificate or AWS access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

ValidationError

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400