Developer Guide

AWS SDK for C++

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS SDK for C++: Developer Guide

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

What is the AWS SDK for C++ Developer Guide? 1
Additional documentation and resources 1
Maintenance and support for SDK major versions 2
Getting started 3
Authenticating with AWS 3
Using console credentials 3
Using IAM Identity Center 4
More authentication information 6
Getting the SDK from source 6
Building on Windows 7
Building on Linux/macOS 11
Creating a simple application 15
Getting the SDK from a package manager 21
Prerequisites 7
Get the SDK using vcpkg 22
Troubleshooting build issues 23
CMake Error: Could not find a package configuration file provided by "AWSSDK" 23
CMake Error: Could not find load file (and you're on SDK version 1.8) 24
CMake Error: Could not find load file 25
Runtime Error: cannot proceed because `aws-*.dll` was not found 25
Configuring service clients 27
SDK configuration 28
Client configuration externally 29
Client configuration in code 31
Declarations 31
Descriptions 34
AWS Region 40
Credential providers 40
The credential provider chain 40
Explicit credential provider 44
Identity caching 44
CMake parameters 44
General CMake Variables and Options 44
Android CMake Variables and Options 59

Logging ... 62
HTTP ... 66
Controlling iostreams used by the `HttpClient` and the `AWSClient` ... 66
Using a custom libcrypto ... 68
How to build a custom libcrypto into the SDK for C++ ... 68
Bringing it all together in a docker image ... 70
Using the SDK ... 72
Initializing and shutting down the SDK ... 72
Making AWS service requests ... 73
Asynchronous programming ... 74
Asynchronous SDK methods ... 74
Calling SDK asynchronous methods ... 74
Notification of the Completion of an Asynchronous Operation ... 76
Utility modules ... 79
HTTP Stack ... 79
String Utils ... 79
Hashing Utils ... 79
JSON Parser ... 79
XML Parser ... 80
Memory management ... 80
Allocating and Deallocating Memory ... 80
STL and AWS Strings and Vectors ... 81
Remaining Issues ... 83
Native SDK Developers and Memory Controls ... 83
Handling errors ... 84
Calling AWS services ... 86
Getting started on code examples ... 86
Structure of the code examples ... 86
Building and Debugging Code Examples in Visual Studio ... 87
Getting started troubleshooting runtime errors ... 89
Guided examples ... 92
Amazon CloudWatch examples ... 94
Amazon DynamoDB examples ... 110
Amazon EC2 examples ... 126
Amazon S3 examples ... 151
Amazon SQS examples ... 184

Code examples 201
ACM 202
Actions 202
API Gateway 232
Scenarios 232
Aurora 233
Get started 233
Basics 236
Actions 202
Scenarios 232
Auto Scaling 277
Get started 233
Basics 236
Actions 202
CloudTrail 307
Actions 202
CloudWatch 312
Actions 202
CloudWatch Logs 322
Actions 202
CodeBuild 326
Actions 202
Amazon Cognito Identity Provider 331
Get started 233
Actions 202
Scenarios 232
DynamoDB 354
Get started 233
Basics 236
Actions 202
Scenarios 232
Amazon EC2 433
Get started 233
Actions 202
EventBridge 467
Actions 202

AWS Glue ... 471
Get started ... 233
Basics ... 236
Actions ... 202
HealthImaging ... 510
Get started ... 233
Actions ... 202
Scenarios ... 232
IAM ... 544
Get started ... 233
Basics ... 236
Actions ... 202
AWS IoT ... 586
Get started ... 233
Basics ... 236
Actions ... 202
AWS IoT data ... 628
Actions ... 202
Lambda ... 630
Get started ... 233
Basics ... 236
Actions ... 202
Scenarios ... 232
MediaConvert ... 655
Actions ... 202
Amazon RDS ... 663
Get started ... 233
Basics ... 236
Actions ... 202
Scenarios ... 232
Amazon RDS Data Service ... 700
Scenarios ... 232
Amazon Rekognition ... 701
Get started ... 233
Actions ... 202
Scenarios ... 232

Amazon S3 707
Get started 233
Basics 236
Actions 202
Scenarios 232
Secrets Manager 789
Actions 202
Amazon SES 791
Actions 202
Scenarios 232
Amazon SNS 813
Get started 233
Actions 202
Scenarios 232
Amazon SQS 855
Get started 233
Actions 202
Scenarios 232
AWS STS 891
Actions 202
Amazon Transcribe Streaming 893
Actions 202
Scenarios 232
Security 901
Data Protection 901
Identity and Access Management 902
Audience 903
Authenticating with identities 903
Managing access using policies 905
How AWS services work with IAM 906
Troubleshooting AWS identity and access 907
Compliance Validation 908
Resilience 909
Infrastructure Security 909
Enforcing a minimum TLS version 910
Enforce specific TLS version with libcurl on all platforms 911

Enforce specific TLS version on Windows 912
Amazon S3 Encryption Client Migration (V1 to V2) 915
Migration Overview 915
Update Existing Clients to Read New Formats 915
Migrate Encryption and Decryption Clients to V2 917
Additional Examples 919
Amazon S3 Encryption Client Migration (V2 to V3) 921
Migration Overview 922
Understanding V3 Concepts 922
Update Existing Clients to Read New Formats 925
Migrate Encryption and Decryption Clients to V3 926
Additional Examples 929
Document history 933

What is the AWS SDK for C++ Developer Guide?

Welcome to the AWS SDK for C++ Developer Guide.

The AWS SDK for C++ provides a modern C++ (version C++ 11 or later) interface for Amazon Web Services (AWS). It provides both high-level and low-level APIs for nearly all AWS features, minimizing dependencies and providing platform portability on Windows, macOS, Linux, and mobile.

Getting started with the AWS SDK for C++

> **Note**
>
> The AWS IoT SDKs and the `aws-iot-device-sdk-cpp` are separate from this SDK. The AWS IoT Device SDK for C++ v2 is available at `aws-iot-device-sdk-cpp-v2` on GitHub. For more information about AWS IoT, see What is AWS IoT in the AWS IoT Developer Guide.

Additional documentation and resources

In addition to this guide, the following are valuable online resources for AWS SDK for C++ developers:

- AWS SDKs and Tools Reference Guide: Contains settings, features, and other foundational concepts common amongst AWS SDKs.
- GitHub:
  - SDK source
  - SDK issues
- AWS SDK for C++ API Reference
- AWS C++ Developer Blog
- The AWS Code Sample Catalog
- SDK License
- *Video:* Introducing the AWS SDK for C++ from AWS re:invent 2015

Maintenance and support for SDK major versions

For information about maintenance and support for SDK major versions and their underlying dependencies, see the following in the AWS SDKs and Tools Reference Guide:

- AWS SDKs and tools maintenance policy
- AWS SDKs and tools version support matrix

Getting started with the AWS SDK for C++

AWS SDK for C++ is a modularized, cross-platform, open-source library you can use to connect to Amazon Web Services.

The AWS SDK for C++ uses CMake to support multiple platforms over multiple domains, including video games, systems, mobile, and embedded devices. CMake is a build tool that you can use to manage your application's dependencies and to create makefiles suitable for the platform you're building on. CMake removes the parts of the build that are not used for your platform or application.

Before you run code to access AWS resources, you must establish how your code authenticates with AWS.

- Authenticating with AWS using AWS SDK for C++

To use the AWS SDK for C++ in your code, obtain the SDK executables by building the SDK source directly or by using a package manager.

- Getting the AWS SDK for C++ from source code
- Getting the AWS SDK for C++ from a package manager

If you run into build issues regarding CMake, see Troubleshooting AWS SDK for C++ build issues.

Authenticating with AWS using AWS SDK for C++

You must establish how your code authenticates with AWS when developing with AWS services. You can configure programmatic access to AWS resources in different ways depending on the environment and the AWS access available to you. For choices on all primary methods of authentication, and guidance on configuring it for the SDK, see Authentication and access in the *AWS SDKs and Tools Reference Guide*.

Using console credentials

For local development, we recommend that new users use their existing AWS Management Console sign-in credentials for programmatic access to AWS services. After a browser-based authentication

flow, AWSgenerates temporary credentials that work across local development tools like the AWS CLI, AWS Tools for PowerShell and AWS SDKs. This feature simplifies the process of configuring and managing AWS CLI credentials, especially if you prefer interactive authentication over managing long-term access keys.

If you choose this method, follow the instructions to login with console credentials using the AWS CLI. See Login for AWS local development using console credentials for more details.

Once set up with AWS CLI, the default credential provider chain will automatically start using the login token cached by AWS CLI to make requests.

Using IAM Identity Center

This method includes installing the AWS CLI for ease of configuration and for regularly signing in to the AWS access portal.

If you choose this method, complete the procedure for IAM Identity Center authentication in the *AWS SDKs and Tools Reference Guide*. Afterwards, your environment should contain the following elements:

- The AWS CLI, which you use to start an AWS access portal session before you run your application.
- A shared `AWSconfig` file having a `[default]` profile with a set of configuration values that can be referenced from the SDK. To find the location of this file, see Location of the shared files in the *AWS SDKs and Tools Reference Guide*.
- The shared `config` file sets the `region` setting. This sets the default AWS Region that the SDK uses for AWS requests. This Region is used for SDK service requests that aren't specified with a Region to use.
- The SDK uses the profile's SSO token provider configuration to acquire credentials before sending requests to AWS. The `sso_role_name` value, which is an IAM role connected to an IAM Identity Center permission set, should allow access to the AWS services used in your application.

  The following sample `config` file shows a default profile set up with SSO token provider configuration. The profile's `sso_session` setting refers to the named `sso-session` section. The `sso-session` section contains settings to initiate an AWS access portal session.

```
[default]
sso_session = my-sso
```

```
sso_account_id = 111122223333
sso_role_name = SampleRole
region = us-east-1
output = json

[sso-session my-sso]
sso_region = us-east-1
sso_start_url = https://provided-domain.awsapps.com/start
sso_registration_scopes = sso:account:access
```

The AWS SDK for C++ does not need additional packages (such as SSO and SSOOIDC) to be added to your application to use IAM Identity Center authentication.

Start an AWS access portal session

Before running an application that accesses AWS services, you need an active AWS access portal session for the SDK to use IAM Identity Center authentication to resolve credentials. Depending on your configured session lengths, your access will eventually expire and the SDK will encounter an authentication error. To sign in to the AWS access portal, run the following command in the AWS CLI.

```
aws sso login
```

Since you have a default profile setup, you do not need to call the command with a `--profile` option. If your SSO token provider configuration is using a named profile, the command is `aws sso login --profile named-profile`.

To test if you already have an active session, run the following AWS CLI command.

```
aws sts get-caller-identity
```

The response to this command should report the IAM Identity Center account and permission set configured in the shared `config` file.

> **Note**
>
> If you already have an active AWS access portal session and run `aws sso login`, you will not be required to provide credentials.

The sign-in process might prompt you to allow the AWS CLI access to your data. Because the AWS CLI is built on top of the SDK for Python, permission messages may contain variations of the `botocore` name.

More authentication information

Human users, also known as *human identities*, are the people, administrators, developers, operators, and consumers of your applications. They must have an identity to access your AWS environments and applications. Human users that are members of your organization are also known as *workforce identities*, that means you, the developer. Use temporary credentials when accessing AWS. You can use an identity provider for your human users to provide federated access to AWS accounts by assuming roles, which provide temporary credentials. For centralized access management, we recommend that you use AWS IAM Identity Center (IAM Identity Center) to manage access to your accounts and permissions within those accounts. For more alternatives, see the following:

- To learn more about best practices, see Security best practices in IAM in the *IAM User Guide*.
- To create short-term AWS credentials, see Temporary Security Credentials in the *IAM User Guide*.
- To learn about other AWS SDK for C++ credential providers, see Standardized credential providers in the *AWS SDKs and Tools Reference Guide*.

Getting the AWS SDK for C++ from source code

You can use the AWS SDK for C++ from your code by first building the SDK from source and then installing it locally.

Process overview

General process	Detailed process
Build and install the SDK source 1. Use CMake to generate build files for the SDK. 2. Build the SDK. 3. Install the SDK.	First build the SDK from source and install it. • Building on Windows • Building on Linux/macOS

General process	Detailed process
Build your application using the SDK 1. Write your own code to use the SDK or use a sample application, and add the AWSSDK package to your cmake file. 2. Use CMake to generate build files for your application. 3. Build your application. 4. Run your application.	Then develop your own application using the SDK. • Creating a simple application

Building the AWS SDK for C++ on Windows

To set up the AWS SDK for C++, you can either build the SDK yourself directly from the source or download the libraries using a package manager.

The SDK source is separated into individual packages by service. Installing the entire SDK can take up to an hour. Installing only the specific subset of services that your program uses decreases installation time and also reduces size on disk. To choose which services to install, you need to know the package name of each service your program uses. You can see the list of package directories at aws/aws-sdk-cpp on GitHub. The package name is the suffix of the directory name for the service.

```
aws-sdk-cpp\aws-cpp-sdk-<packageName>   # Repo directory name and packageName
aws-sdk-cpp\aws-cpp-sdk-s3              # Example: Package name is s3
```

Prerequisites

You need a minimum of 4 GB of RAM to build some of the larger AWS clients. The SDK might fail to build on Amazon EC2 instance types *t2.micro*, *t2.small*, and other small instance types due to insufficient memory.

To use the AWS SDK for C++, you need one of the following:

- Microsoft Visual Studio 2015 or later,
- GNU Compiler Collection (GCC) 4.9 or later, or

- Clang 3.3 or later.

Building the SDK for Windows with curl

On Windows, the SDK is built with WinHTTP as the default HTTP client. However, WinHTTP 1.0 does not support HTTP/2 bidirectional streaming, which is required for some AWS services such as Amazon Transcribe and Amazon Lex. Thus, it is sometimes necessary to build curl support with the SDK. To view all available curl download options, see curl Releases and Downloads. One method for building the SDK with curl support is the following:

To build the SDK with curl library support included

1. Navigate to curl for Windows and download the curl binary package for Microsoft Windows.
2. Unpack the package to a folder on your computer, for example, `C:\curl`.
3. Navigate to CA certificates extracted from Mozilla and download the `cacert.pem` file. This Privacy Enhanced Mail (PEM) file contains a bundle of valid digital certificates that are used to verify the authenticity of secure websites. The certificates are distributed by certificate authority (CA) companies such as GlobalSign and Verisign.
4. Move the `cacert.pem` file to the `bin` subfolder that you unpacked in a previous step, for example, `C:\curl\bin`. Rename the file as `curl-ca-bundle.crt`.

Also, the Microsoft Build Engine (MSBuild) must be able to locate the curl `dll` in the procedure that follows. Therefore, you should add the curl `bin` folder path to your Windows `PATH` environment variable, for example, `set PATH=%PATH%;C:\curl\bin`. You must add this each time you open a new command prompt to build the SDK. Alternatively, you can set the environment variable globally in your Windows system settings so that the setting is remembered.

When *Building the SDK from source* in the procedure that follows, see Step 5 (Generate build files) for required command syntax to build curl into your SDK.

When writing your code, you must set `caFile` in the Configuring AWS SDK for C++ service clients in code to the location of your certificate file. For an example using Amazon Transcribe, see `transcribe-streaming` in the *AWS Code Examples Repository* on GitHub.

Building the SDK from source

You can build the SDK from source using command-line tools. Using this method, you can customize your SDK build. For information about available options, see CMake Parameters. There

are three main steps. First, you build the files using CMake. Second, you use MSBuild to build the SDK binaries that work with your operating system and build toolchain. Third, you install or copy the binaries into the correct location on the development machine.

To build the SDK from source

1. Install CMake (minimum version 3.13) and the relevant build tools for your platform. It is recommended to add `cmake` to your PATH. To check your version of CMake, open a command prompt and run command **`cmake --version`**
2. In a command prompt, navigate to a folder where you want to store the SDK.
3. Get the latest source code.

   Version 1.11 uses git submodules to wrap external dependencies. This includes the CRT libraries described in the *AWS SDKs and Tools Reference Guide*.

   Download or clone the SDK source from `aws/aws-sdk-cpp` on GitHub:

   - Clone with Git: HTTPS

     ```
     git clone --recurse-submodules https://github.com/aws/aws-sdk-cpp
     ```

   - Clone with Git: SSH

     ```
     git clone --recurse-submodules git@github.com:aws/aws-sdk-cpp.git
     ```

4. We recommend you store the generated build files outside of the SDK source directory. Create a new directory to store the build files in and navigate to that folder.

   ```
   mkdir sdk_build
   cd sdk_build
   ```

5. Generate the build files by running `cmake`. Specify on the `cmake` command line whether to build a *Debug* or *Release* version. Choose `Debug` throughout this procedure to run a debug configuration of your application code. Choose `Release` throughout this procedure to run a release configuration of your application code. For Windows, the SDK install location is typically `\Program Files (x86)\aws-cpp-sdk-all\`. Command syntax:

   ```
   {path to cmake if not in PATH} {path to source location of aws-sdk-cpp} -DCMAKE_BUILD_TYPE=[Debug | Release] -DCMAKE_PREFIX_PATH={path to install destination}
   ```

For more ways to modify the build output, see CMake Parameters.

To generate the build files, do one of the following:

- **Generate build files (all AWS services)**: To build the entire SDK, run cmake, specifying whether to build a *Debug* or *Release* version. For example:

```
cmake "..\aws-sdk-cpp" -DCMAKE_BUILD_TYPE=Debug -DCMAKE_PREFIX_PATH="C:\Program
 Files (x86)\aws-cpp-sdk-all"
```

- **Generate build files (subset AWS services)**: To build only a particular service or services package(s) for the SDK, add the CMake BUILD_ONLY parameter, with the service names separated by semicolons. The following example builds only the Amazon S3 service package:

```
cmake ..\aws-sdk-cpp -DCMAKE_BUILD_TYPE=Debug -DBUILD_ONLY="s3" -
DCMAKE_PREFIX_PATH="C:\Program Files (x86)\aws-cpp-sdk-all"
```

- **Generate build files (with curl)**: After completing the curl prerequisites, three additional cmake command line options are required to include curl support in the SDK: FORCE_CURL, CURL_INCLUDE_DIR, and CURL_LIBRARY. For example:

```
cmake ..\aws-sdk-cpp -DCMAKE_BUILD_TYPE=Debug -DFORCE_CURL=ON -
DCURL_INCLUDE_DIR='C:/curl/include'
      -DCURL_LIBRARY='C:/curl/lib/libcurl.dll.a' -DCMAKE_PREFIX_PATH="C:\Program
 Files (x86)\aws-cpp-sdk-all"
```

> **Note**
>
> If you get an error Failed to build third-party libraries, check your version of CMake by running **`cmake --version`**. You must use CMake minimum version 3.13.

6. Build the SDK binaries. If you're building the entire SDK, this step can take one hour or longer. Command syntax:

   `{path to cmake if not in PATH} --build . --config=[Debug | Release]`

```
cmake --build . --config=Debug
```

> **Note**
>
> If you encounter the error The code execution cannot proceed ... dll not found. Reinstalling the program may fix this problem.", retry the `cmake` command again.

7. Open a command prompt with **administrator** privileges to install the SDK in the location specified earlier using the `CMAKE_PREFIX_PATH` parameter. Command syntax:

   ```
   {path to cmake if not in PATH} --install . --config=[Debug | Release]
   ```

   ```
   cmake --install . --config=Debug
   ```

Building for Android on Windows

To build for Android, add `-DTARGET_ARCH=ANDROID` to your `cmake` command line. The AWS SDK for C++ includes a CMake toolchain file that includes what you need by referencing the appropriate environment variables (`ANDROID_NDK`).

To build the SDK for Android on Windows, you need to run `cmake` from a Visual Studio (2015 or later) developer command prompt. You'll also need NMAKE NMAKEinstalled and the commands **`git`** and **`patch`** in your path. If you have git installed on a Windows system, you'll most likely find **`patch`** in a sibling directory (`.../Git/usr/bin/`). Once you've verified these requirements, your `cmake` command line will change slightly to use NMAKE.

```
cmake -G "NMake Makefiles" `-DTARGET_ARCH=ANDROID` <other options> ..
```

NMAKE builds serially. To build more quickly, we recommend you install JOM as an alternative to NMAKE, and then change the `cmake` invocation as follows:

```
cmake -G "NMake Makefiles JOM" `-DTARGET_ARCH=ANDROID` <other options> ..
```

For an example application, see Setting up an Android application with AWS SDK for C++

Building the AWS SDK for C++ on Linux/macOS

To set up the AWS SDK for C++, you can either build the SDK yourself directly from the source or download the libraries using a package manager.

The SDK source is separated into individual packages by service. Installing the entire SDK can take up to an hour. Installing only the specific subset of services that your program uses decreases installation time and also reduces size on disk. To choose which services to install, you need to know the package name of each service your program uses. You can see the list of package directories at aws/aws-sdk-cpp on GitHub. The package name is the suffix of the directory name for the service.

```
aws-sdk-cpp\aws-cpp-sdk-<packageName>   # Repo directory name and packageName
aws-sdk-cpp\aws-cpp-sdk-s3              # Example: Package name is s3
```

Prerequisites

You need a minimum of 4 GB of RAM to build some of the larger AWS clients. The SDK might fail to build on Amazon EC2 instance types *t2.micro*, *t2.small*, and other small instance types due to insufficient memory.

To use the AWS SDK for C++, you need one of the following:

- GNU Compiler Collection (GCC) 4.9 or later, or
- Clang 3.3 or later.

Additional Requirements for Linux Systems

You must have the header files (`-dev` packages) for `libcurl`, `libopenssl`, `libuuid`, `zlib`, and, optionally, `libpulse` for Amazon Polly support. You can find the packages by using your system's package manager.

To install the packages on *Debian/Ubuntu-based systems*

- ```
  sudo apt-get install libcurl4-openssl-dev libssl-dev uuid-dev zlib1g-dev libpulse-dev
  ```

To install the packages on *Amazon Linux/Redhat/Fedora/CentOS-based systems*

- ```
  sudo yum install libcurl-devel openssl-devel libuuid-devel pulseaudio-libs-devel
  ```

Building the SDK from Source

You can build the SDK from source using command-line tools as an alternative to using vcpkg. Using this method, you can customize your SDK build. For information about available options, see CMake Parameters.

To build the SDK from source

1. Install CMake (minimum version 3.13) and the relevant build tools for your platform. It is recommended to add `cmake` to your PATH. To check your version of CMake, open a command prompt and run command **`cmake --version`**
2. In a command prompt, navigate to a folder where you want to store the SDK.
3. Get the latest source code.

   Version 1.11 uses git submodules to wrap external dependencies. This includes the CRT libraries described in the *AWS SDKs and Tools Reference Guide*.

   Download or clone the SDK source from `aws/aws-sdk-cpp` on GitHub:

   - Clone with Git: HTTPS

     ```
     git clone --recurse-submodules https://github.com/aws/aws-sdk-cpp
     ```

   - Clone with Git: SSH

     ```
     git clone --recurse-submodules git@github.com:aws/aws-sdk-cpp.git
     ```

4. We recommend you store the generated build files outside of the SDK source directory. Create a new directory to store the build files in and navigate to that folder.

   ```
   mkdir sdk_build
   cd sdk_build
   ```

5. Generate the build files by running `cmake`. Specify on the `cmake` command line whether to build a *Debug* or *Release* version. Choose `Debug` throughout this procedure to run a debug configuration of your application code. Choose `Release` throughout this procedure to run a release configuration of your application code. Command syntax:

```
{path to cmake if not in PATH} {path to source location of aws-sdk-
cpp} -DCMAKE_BUILD_TYPE=[Debug | Release] -DCMAKE_PREFIX_PATH={path to
install} -DCMAKE_INSTALL_PREFIX={path to install}
```

For more ways to modify the build output, see CMake Parameters.

> **Note**
>
> When building on a Mac with a case-insensitive filesystem, check the output of the pwd command in the directory where you run the build. Make sure that the pwd output uses mixed case for directory names such as /Users and Documents.

To generate the build files, do one of the following:

- **Generate build files (all AWS services)**: To build the entire SDK, run cmake, specifying whether to build a *Debug* or *Release* version. For example:

```
cmake ../aws-sdk-cpp -DCMAKE_BUILD_TYPE=Debug -DCMAKE_PREFIX_PATH=/usr/local/ -
DCMAKE_INSTALL_PREFIX=/usr/local/
```

- **Generate build files (subset AWS services)**: To build only a particular service or services package(s) for the SDK, add the CMake BUILD_ONLY parameter, with the service names separated by semicolons. The following example builds only the Amazon S3 service package:

```
cmake ../aws-sdk-cpp -DCMAKE_BUILD_TYPE=Debug -DCMAKE_PREFIX_PATH=/usr/local/ -
DCMAKE_INSTALL_PREFIX=/usr/local/ -DBUILD_ONLY="s3"
```

> **Note**
>
> If you get an error Failed to build third-party libraries, check your version of CMake by running **`cmake --version`**. You must use CMake minimum version 3.13.

6. Build the SDK binaries. If you're building the entire SDK, the operation can take one hour or longer.

```
cmake --build . --config=Debug
```

7. Install the SDK. You may need to escalate privileges depending on the location you chose to install to.

```
cmake --install . --config=Debug
```

Building for Android on Linux

To build for Android, add `-DTARGET_ARCH=ANDROID` to your `cmake` command line. The AWS SDK for C++ includes a CMake toolchain file that includes what you need by referencing the appropriate environment variables (`ANDROID_NDK`). For an example application, see Setting up an Android application with AWS SDK for C++

Creating a simple application using the AWS SDK for C++

CMake is a build tool that you use to manage your application's dependencies and to create makefiles suitable for the platform you're building on. You can use CMake to create and build projects using the AWS SDK for C++.

This example reports the Amazon S3 buckets you own. Having an Amazon S3 bucket in your AWS account is not required for this example, but it will be far more interesting if you have at least one. See Create a Bucket in the *Amazon Simple Storage Service User Guide* if you don't already have one.

Step 1: Write the code

This example consists of one folder containing one source file (`hello_s3.cpp`) and one `CMakeLists.txt` file. The program uses Amazon S3 to report storage bucket information. This code is also available in the AWS Code Examples Repository on GitHub.

You can set many options in a `CMakeLists.txt` build configuration file. For more information, see the CMake tutorial on the CMake website.

> **Note**
>
> Deep Dive: Setting `CMAKE_PREFIX_PATH`

By default, the AWS SDK for C++ on macOS, Linux, Android and other non-Windows platforms is installed into `/usr/local` and on Windows is installed into `\Program Files (x86)\aws-cpp-sdk-all`.
When you install the AWS SDK to these standard locations, CMake automatically finds the necessary resources. However, if you install the AWS SDK to a custom location, you must tell CMake where to find the following resources that result from building the SDK:

- `AWSSDKConfig.cmake`: A configuration file that tells CMake how to find and use the AWS SDK libraries in your project. Without this file, CMake cannot locate AWS SDK header files, link to AWS SDK libraries, or set up the proper compiler flags.
- (for version 1.8 and earlier) The location of dependencies: `aws-c-event-stream`, `aws-c-common`, `aws-checksums`

To set a custom installation path:

```
cmake -DCMAKE_PREFIX_PATH=/path/to/your/aws-sdk-installation /path/to/project/you/are/building
```

If you don't set `CMAKE_PREFIX_PATH` for a custom installation, your build will fail with errors like "Could not find AWSSDK" when CMake tries to process `find_package(AWSSDK)` in your `CMakeLists.txt`.

Note

Deep Dive: Windows Runtime Libraries
To run your program, several DLLs are required in your program's executable location: `aws-c-common.dll`, `aws-c-event-stream.dll`, `aws-checksums.dll`, `aws-cpp-sdk-core.dll`, as well as any specific DLLs based on the components of your program (this example also requires `aws-cpp-sdk-s3` because it uses Amazon S3). The second `if` statement in the `CMakeLists.txt` file copies these libraries from the installation location to the executable location to satisfy this requirement. `AWSSDK_CPY_DYN_LIBS` is a macro defined by AWS SDK for C++ that copies the SDK's DLLs from the installation location to the executable location of your program. If these DLLs are not in the executable location then runtime exceptions of 'file not found' occur. Review this portion of the

`CMakeLists.txt` file for necessary changes for your unique environment if you encounter these errors.

To create the folder and source files

1. Create a `hello_s3` directory and/or project to hold your source files.

   Note

   To complete this example in Visual Studio: choose **Create New Project** and then choose **CMake Project**. Name the project `hello_s3`. This project name is used in the `CMakeLists.txt` file.

2. Within that folder, add a `hello_s3.cpp` file that includes the following code, which reports the Amazon S3 buckets you own.

```
#include <aws/core/Aws.h>
#include <aws/s3/S3Client.h>
#include <iostream>
#include <aws/core/auth/AWSCredentialsProviderChain.h>
using namespace Aws;
using namespace Aws::Auth;

/*
 *  A "Hello S3" starter application which initializes an Amazon Simple Storage
 Service (Amazon S3) client
 *  and lists the Amazon S3 buckets in the selected region.
 *
 *  main function
 *
 *  Usage: 'hello_s3'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
```

```
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        // You don't normally have to test that you are authenticated. But the S3
 service permits anonymous requests, thus the s3Client will return "success" and 0
 buckets even if you are unauthenticated, which can be confusing to a new user.
        auto provider = Aws::MakeShared<DefaultAWSCredentialsProviderChain>("alloc-
tag");
        auto creds = provider->GetAWSCredentials();
        if (creds.IsEmpty()) {
            std::cerr << "Failed authentication" << std::endl;
        }

        Aws::S3::S3Client s3Client(clientConfig);
        auto outcome = s3Client.ListBuckets();

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed with error: " << outcome.GetError() << std::endl;
            result = 1;
        } else {
            std::cout << "Found " << outcome.GetResult().GetBuckets().size()
                      << " buckets\n";
            for (auto &bucket: outcome.GetResult().GetBuckets()) {
                std::cout << bucket.GetName() << std::endl;
            }
        }
    }

    Aws::ShutdownAPI(options); // Should only be called once.
    return result;
}
```

3. Add a `CMakeLists.txt` file that specifies your project's name, executables, source files, and linked libraries.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS s3)
```

```
# Set this project's name.
project("hello_s3")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD AND AWSSDK_INSTALL_AS_SHARED_LIBS)
    # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

    # set(BIN_SUB_DIR "/Debug") # if you are building from the command line you may
 need to uncomment this
    # and set the proper subdirectory to the executables' location.

    AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_s3.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Step 2: Build with CMake

CMake uses the information in `CMakeLists.txt` to build an executable program.

We recommend building the application following standard practices for your IDE.

To build the application from the command line

1. Create a directory where **cmake** will build your application.

```
mkdir my_project_build
```

2. Change to the build directory and run **cmake** using the path to your project's source directory.

```
cd my_project_build
cmake ../
```

3. After **cmake** generates your build directory, you can use **make** (or **nmake** on Windows), or MSBUILD (`msbuild ALL_BUILD.vcxproj` or `cmake --build . --config=Debug`) to build your application.

Step 3: Run

When you run this application, it displays console output that lists the total number of Amazon S3 buckets and the name of each bucket.

We recommend running the application following standard practices for your IDE.

> **Note**
>
> Remember to sign in! If you are using IAM Identity Center to authenticate, remember to sign in using the AWS CLI `aws sso login` command.

To run the program via command line

1. Change to the Debug directory where the result of the build was generated.
2. Run the program using the name of the executable.

```
hello_s3
```

For additional examples using the AWS SDK for C++, see Guided examples for calling AWS services using the AWS SDK for C++.

Getting the AWS SDK for C++ from a package manager

> **Important**
>
> If you are using a package manager like homebrew or vcpkg:
> After updating the SDK for C++ to a new version, you must recompile any library or executable that depends on the SDK.

To set up the AWS SDK for C++, you can either build the SDK yourself directly from the source or download the libraries using a package manager.

The SDK source is separated into individual packages by service. Installing the entire SDK can take up to an hour. Installing only the specific subset of services that your program uses decreases installation time and also reduces size on disk. To choose which services to install, you need to know the package name of each service your program uses. You can see the list of package directories at aws/aws-sdk-cpp on GitHub. The package name is the suffix of the directory name for the service.

```
aws-sdk-cpp\aws-cpp-sdk-<packageName>   # Repo directory name and packageName
aws-sdk-cpp\aws-cpp-sdk-s3              # Example: Package name is s3
```

Prerequisites

You need a minimum of 4 GB of RAM to build some of the larger AWS clients. The SDK might fail to build on Amazon EC2 instance types *t2.micro*, *t2.small*, and other small instance types due to insufficient memory.

Linux/macOS

To use the AWS SDK for C++ on Linux/macOS, you need one of the following:

- GNU Compiler Collection (GCC) 4.9 or later, or
- Clang 3.3 or later.

Windows

To use the AWS SDK for C++ on Windows, you need one of the following:

- Microsoft Visual Studio 2015 or later,
- GNU Compiler Collection (GCC) 4.9 or later, or
- Clang 3.3 or later.

Get the SDK using vcpkg

> **Important**
>
> The available vcpkg distribution is supported by external contributors and is not provided through AWS. The most recent version is always available through installing from source.

vcpkg is a package manager updated and maintained by external contributors. Note that this package manager is not provided through AWS and may not reflect the latest available version for the AWS SDK for C++. There is a delay between when a version is released by AWS and when it is available through an external package manager. The most recent version is always available through installing from source.

You must install vcpkg on your system.

- Download and bootstrap vcpkg by following the instructions on the vcpkg GitHub Readme, substituting the following options when prompted:
  - As part of those instructions, you are guided to enter:

    ```
    .\vcpkg\vcpkg install [packages to install]
    ```

    To install the entire SDK, enter `.\vcpkg\vcpkg install "aws-sdk-cpp[*]" --recurse` or indicate only specific services of the SDK to install by appending a package name in brackets, for example, `.\vcpkg\vcpkg install "aws-sdk-cpp[s3, ec2]" --recurse`

  The output displays a messages including the following:

  ```
  CMake projects should use: "-DCMAKE_TOOLCHAIN_FILE=C:/dev/vcpkg/vcpkg/scripts/
  buildsystems/vcpkg.cmake"
  ```
- Copy the complete `-DCMAKE_TOOLCHAIN_FILE` command to use for CMake later. The vcpkg GitHub Readme also instructs on where to use this for your toolset.

- You may also need to note the build configuration type that you installed via vcpkg. The console output shows the build configuration and the version of the SDK. The following example output indicates the build configuration is "x86-windows" and the AWS SDK for C++ version installed is 1.8.

```
The following packages will be built and installed:
    aws-sdk-cpp[core,dynamodb,kinesis,s3]:x86-windows -> 1.8.126#6
```

After you install the AWS SDK for C++, you can develop your own application using the SDK. The example shown in Creating a simple application reports the Amazon S3 buckets you own.

Troubleshooting AWS SDK for C++ build issues

When building the AWS SDK for C++ from source, some of the following common build issues might arise.

Topics

- CMake Error: Could not find a package configuration file provided by "AWSSDK"
- CMake Error: Could not find load file (and you're on SDK version 1.8)
- CMake Error: Could not find load file
- Runtime Error: cannot proceed because aws-*.dll was not found

CMake Error: Could not find a package configuration file provided by "AWSSDK"

CMake raises the following error if it cannot find the installed SDK.

```
1> [CMake] CMake Error at C:\CodeRepos\CMakeProject1\CMakeLists.txt:4 (find_package):
1> [CMake]   Could not find a package configuration file provided by "AWSSDK" with any
1> [CMake]   of the following names:
1> [CMake]
1> [CMake]     AWSSDKConfig.cmake
1> [CMake]     awssdk-config.cmake
1> [CMake]
1> [CMake]   Add the installation prefix of "AWSSDK" to CMAKE_PREFIX_PATH or set
1> [CMake]   "AWSSDK_DIR" to a directory containing one of the above files.  If
 "AWSSDK"
```

```
1> [CMake]   provides a separate development package or SDK, be sure it has been
1> [CMake]   installed.
```

To resolve this error, tell CMake where to find the installed SDK (e.g. the folder that was generated as a result of the SDK install (Windows, Linux/macOS). Insert the following command before your first call to `find_package()` in your `CMakeLists.txt` file. See ??? for an example.

```
list(APPEND CMAKE_PREFIX_PATH "C:\\Program Files (x86)\\aws-cpp-sdk-all\\lib\\cmake")
```

CMake Error: Could not find load file (and you're on SDK version 1.8)

CMake raises the following error if it cannot find the installed libraries.

```
1> [CMake]   include could not find load file:
1> [CMake]
1> [CMake]     C:/Program Files (x86)/aws-cpp-sdk-all/lib/aws-c-common/cmake/static/
aws-c-common-targets.cmake

1> [CMake]   include could not find load file:
1> [CMake]
1> [CMake]     C:/Program Files (x86)/aws-cpp-sdk-all/lib/aws-checksums/cmake/static/
aws-checksums-targets.cmake
1> [CMake]   include could not find load file:
1> [CMake]
1> [CMake]     C:/Program Files (x86)/aws-cpp-sdk-all/lib/aws-checksums/cmake/static/
aws-checksums-targets.cmake
```

To resolve this error, tell CMake where to find the installed SDK (e.g. the folder that was generated as a result of the SDK install (Windows, Linux/macOS). Insert the following commands before your first call to `find_package()` in your `CMakeLists.txt` file. See ??? for an example.

```
#Set the location of where Windows can find the installed libraries of the SDK.
if(MSVC)
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif()
```

This solution is only for v1.8 of the SDK because these dependencies are handled differently in later versions. Version 1.9 addresses these issues by introducing an intermediate layer between

the `aws-sdk-cpp` and `aws-c-*` libraries. This new layer is called `aws-crt-cpp` , and is a git submodule of the SDK for C++. `aws-crt-cpp` also has the `aws-c-*` libraries (including `aws-c-common`, `aws-checksums`, `aws-c-event-stream`, etc.) as its own git submodules. This allows the SDK for C++ to get all CRT libraries recursively and improves the build process.

CMake Error: Could not find load file

CMake raises the following error if it cannot find the installed libraries.

```
CMake Error at C:/Program Files (x86)/aws-cpp-sdk-all/lib/aws-c-auth/cmake/aws-c-auth-
config.cmake:11
         (include):  include could not find load file:
         C:/Program Files (x86)/aws-cpp-sdk-all/lib/aws-c-auth/cmake/static/aws-c-auth-
targets.cmake
```

To resolve this error, tell CMake to build shared libraries. Insert the following command before your first call to `find_package()` in your `CMakeLists.txt` file. See ??? for an example.

```
set(BUILD_SHARED_LIBS ON CACHE STRING "Link to shared libraries by default.")
```

Runtime Error: cannot proceed because `aws-*.dll` was not found

CMake raises an error similar to the following if it cannot find a required DLL.

```
The code execution cannot proceed because aws-cpp-sdk-[dynamodb].dll was not found.
 Reinstalling the program may fix this problem.
```

This error occurs because the required libraries or executables for the SDK for C++ are not available in the same folder as your application executables. To resolve this error, copy the SDK build output in your executable location. The specific DLL filename of the error will vary depending on which AWS services you are using. Do *one* of the following:

- Copy the contents of the `/bin` folder of the AWS SDK for C++ install to your application's build folder.
- In your `CMakeLists.txt` file, use macro AWSSDK_CPY_DYN_LIBS to copy these for you.

  Add a call to either `AWSSDK_CPY_DYN_LIBS(SERVICE_LIST "" ${CMAKE_CURRENT_BINARY_DIR})` or `AWSSDK_CPY_DYN_LIBS(SERVICE_LIST ""`

`${CMAKE_CURRENT_BINARY_DIR}/${CMAKE_BUILD_TYPE}`) to your `CMakeLists.txt` file to use this macro to do the copying for you. See ??? for an example.

Choose the correct copy path for your build environment. Building via command line frequently puts the build output into a subfolder (`/Debug`), but Visual Studio and other IDEs often do not. Verify where your output executables are, and ensure the macro is copying to that location. When making these types of changes, it is good practice to delete the contents of your build output directory so that you get a clean starting point for the next build.

Configuring service clients in the AWS SDK for C++

To programmatically access AWS services, the AWS SDK for C++ uses a client class for each AWS service. For example, if your application needs to access Amazon EC2, your application creates an Amazon EC2 client object to interface with that service. You then use the service client to make requests to that AWS service.

To make a request to an AWS service, you must first create a service client. For each AWS service your code uses, it has its own library and its own dedicated type for interacting with it. The client exposes one method for each API operation exposed by the service.

There are many alternative ways to configure SDK behavior, but ultimately everything has to do with the behavior of service clients. Any configuration has no effect until a service client that is created from them is used.

You must establish how your code authenticates with AWS when you develop with AWS services. You must also set the AWS Region you want to use.

The AWS SDKs and Tools Reference Guide also contains settings, features, and other foundational concepts common among many of the AWS SDKs.

Topics

- General configuration using Aws::SDKOptions in the AWS SDK for C++
- Configuring AWS SDK for C++ service clients externally
- Configuring AWS SDK for C++ service clients in code
- Setting the AWS Region for the AWS SDK for C++
- Using AWS SDK for C++ credential providers
- CMake parameters for building the AWS SDK for C++
- Configuring and using logging in the AWS SDK for C++
- Overriding your HTTP client in the AWS SDK for C++
- Controlling iostreams used by the HttpClient and the AWSClient in the AWS SDK for C++
- Using a custom libcrypto library in the AWS SDK for C++

General configuration using `Aws::SDKOptions` in the AWS SDK for C++

The `Aws::SDKOptions` struct contains SDK configuration options. `Aws::SDKOptions` focuses on general SDK configuration, whereas the `ClientConfiguration` struct focuses on configuration of communicating with AWS services.

An instance of `Aws::SDKOptions` is passed to the `Aws::InitAPI` and `Aws::ShutdownAPI` methods. The same instance should be sent to both methods.

The following samples demonstrate some of the available options.

- Turn logging on using the default logger

```
Aws::SDKOptions options;
options.loggingOptions.logLevel = Aws::Utils::Logging::LogLevel::Info;
Aws::InitAPI(options);
{
    // make your SDK calls here.
}
Aws::ShutdownAPI(options);
```

- Override the default HTTP client factory

```
Aws::SDKOptions options;
options.httpOptions.httpClientFactory_create_fn = [](){
        return Aws::MakeShared<MyCustomHttpClientFactory>(
            "ALLOC_TAG", arg1);
    };
Aws::InitAPI(options);
{
    // make your SDK calls here.
}
Aws::ShutdownAPI(options);
```

> **Note**
>
> `httpOptions` takes a closure (also called an anonymous function or lambda expression) rather than a `std::shared_ptr`. Each of the SDK factory functions operates in this manner because at the time at which the factory memory allocation occurs, the memory

manager has not yet been installed. By passing a closure to the method, the memory manager will be called to perform the memory allocation when it is safe to do so. A simple technique to accomplish this procedure is by using a Lambda expression.

- Use a global `SIGPIPE` handler

  If you build the SDK for C++ with curl and OpenSSL, you must specify a signal handler. If you don't use your own custom signal handler, set `installSigPipeHandler` to `true`.

```
Aws::SDKOptions options;
options.httpOptions.installSigPipeHandler = true;
Aws::InitAPI(options);
{
    // make your SDK calls here.
}
Aws::ShutdownAPI(options);
```

  When `installSigPipeHandler` is `true`, the SDK for C++ uses a handler that ignores `SIGPIPE` signals. For more information on `SIGPIPE`, see Operation Error Signals on the GNU Operating System website. For more information on the curl handler, see CURLOPT_NOSIGNAL explained on the curl website.

  The underlying libraries of curl and OpenSSL can send a `SIGPIPE` signal to notify when the remote side closes a connection. These signals must be handled by the application. For more information this curl functionality, see libcurl thread safety on the curl website. This behavior is not automatically built-in to the SDK because signal handlers are global for each application and the library is a dependency for the SDK.

Configuring AWS SDK for C++ service clients externally

Many configuration settings can be handled outside of your code. When configuration is handled externally, the configuration is applied across all of your applications. Most configuration settings can be set as either environment variables or in a separate shared AWS `config` file. The shared `config` file can maintain separate sets of settings, called profiles, to provide different configurations for different environments or tests.

Environment variables and shared `config` file settings are standardized and shared across AWS SDKs and tools to support consistent functionality across different programming languages and applications.

See the *AWS SDKs and Tools Reference Guide* to learn about configuring your application through these methods, plus details on each cross-sdk setting. To see all the all settings that the SDK can resolve from the environment variables or configuration files, see the Settings reference in the *AWS SDKs and Tools Reference Guide*.

To make a request to an AWS service, you first instantiate a client for that service. You can configure common settings for service clients such as timeouts, the HTTP client, and retry configuration.

Each service client requires an AWS Region and a credential provider. The SDK uses these values to send requests to the correct Region for your resources and to sign requests with the correct credentials. You can specify these values programmatically in code or have them automatically loaded from the environment.

The SDK has a series of places (or sources) that it checks in order to find a value for configuration settings.

1. Any explicit setting set in the code or on a service client itself takes precedence over anything else.
2. Environment variables
   - For details on setting environment variables, see environment variables in the *AWS SDKs and Tools Reference Guide*.
   - Note that you can configure environment variables for a shell at different levels of scope: system-wide, user-wide, and for a specific terminal session.
3. Shared `config` and `credentials` files
   - For details on setting up these files, see the Shared `config` and `credentials` files in the *AWS SDKs and Tools Reference Guide*.
4. Any default value provided by the SDK source code itself is used last.
   - Some properties, such as Region, don't have a default. You must specify them either explicitly in code, in an environment setting, or in the shared `config` file. If the SDK can't resolve required configuration, API requests can fail at runtime.

> **Note**
>
> To see all the all settings that the SDK can resolve from the environment variables or configuration files, see the Settings reference in the *AWS SDKs and Tools Reference Guide*.

Configuring AWS SDK for C++ service clients in code

When configuration is handled directly in code, the configuration scope is limited to the application that uses that code. Within that application, there are options for the global configuration of all service clients, the configuration to all clients of a certain AWS service type, or the configuration to a specific service client instance.

The AWS SDK for C++ includes AWS service client classes that provide functionality for interacting with the AWS services that you use in your application. In the SDK for C++, you can change the default client configuration, which is helpful when you want to do things like:

- Connect to the Internet through proxy
- Change HTTP transport settings, such as connection timeout and request retries
- Specify TCP socket buffer size hints

`ClientConfiguration` is a structure in the SDK for C++ that you can instantiate and utilize in your code. The following snippet illustrates using this class to access Amazon S3 through a proxy.

```
Aws::Client::ClientConfiguration clientConfig;
clientConfig.proxyHost = "localhost";
clientConfig.proxyPort = 1234;
clientConfig.proxyScheme = Aws::Http::Scheme::HTTPS;
Aws::S3::S3Client(clientConfig);
```

Configuration variable declarations

The `ClientConfiguration` struct declares the following member variables:

```
Aws::String accountId;
Aws::String accountIdEndpointMode = "preferred";
bool allowSystemProxy = false;
Aws::String appId;
Aws::String caPath;
```

```
Aws::String caFile;

struct {
  RequestChecksumCalculation requestChecksumCalculation =
 RequestChecksumCalculation::WHEN_SUPPORTED;
  ResponseChecksumValidation responseChecksumValidation =
 ResponseChecksumValidation::WHEN_SUPPORTED;
} checksumConfig;

ProviderFactories configFactories = ProviderFactories::defaultFactories;
long connectTimeoutMs = 1000;

struct CredentialProviderConfiguration {
    Aws::String profile;
    Aws::String region;
    struct {
        long metadataServiceNumAttempts = 1;
        long metadataServiceTimeout = 1;
        std::shared_ptr<RetryStrategy> imdsRetryStrategy;
        bool disableImdsV1;
        bool disableImds;
    } imdsConfig;
    struct STSCredentialsCredentialProviderConfiguration {
        Aws::String roleArn;
        Aws::String sessionName;
        Aws::String tokenFilePath;
        std::chrono::milliseconds retrieveCredentialsFutureTimeout =
 std::chrono::seconds(10);
    } stsCredentialsProviderConfig;
} credentialProviderConfig;

bool disableExpectHeader = false;
bool disableIMDS = false;
bool disableImdsV1 = false;
bool enableClockSkewAdjustment = true;
Aws::Crt::Optional<bool> enableEndpointDiscovery;
bool enableHostPrefixInjection = true;
bool enableHttpClientTrace = false;
bool enableTcpKeepAlive = true;
Aws::String endpointOverride;
std::shared_ptr<Aws::Utils::Threading::Executor> executor = nullptr;
FollowRedirectsPolicy followRedirects;
Aws::Http::TransferLibType httpLibOverride;
```

```
Aws::Http::TransferLibPerformanceMode httpLibPerfMode =
 Http::TransferLibPerformanceMode::LOW_LATENCY;
long httpRequestTimeoutMs = 0;
unsigned long lowSpeedLimit = 1;
unsigned maxConnections = 25;
Aws::Utils::Array<Aws::String> nonProxyHosts;
Aws::String profileName;
Aws::String proxyCaFile;
Aws::String proxyCaPath;
Aws::Http::Scheme proxyScheme;
Aws::String proxyHost;
unsigned proxyPort = 0;
Aws::String proxyUserName;
Aws::String proxyPassword;
Aws::String proxySSLCertPath;
Aws::String proxySSLCertType;
Aws::String proxySSLKeyPath;
Aws::String proxySSLKeyType;
Aws::String proxySSLKeyPassword;
std::shared_ptr<Aws::Utils::RateLimits::RateLimiterInterface> readRateLimiter =
 nullptr;
Aws::String region;
Aws::Client::RequestCompressionConfig requestCompressionConfig;
long requestTimeoutMs = 0;
std::shared_ptr<RetryStrategy> retryStrategy = nullptr;
Aws::Http::Scheme scheme;
unsigned long tcpKeepAliveIntervalMs = 30000;
std::shared_ptr<smithy::components::tracing::TelemetryProvider> telemetryProvider;
Aws::String userAgent;
bool useDualStack = false;
bool useFIPS = false;
bool verifySSL = true;
Aws::Http::Version version = Http::Version::HTTP_VERSION_2TLS;

struct WinHTTPOptions {
  bool useAnonymousAuth = false;
} winHTTPOptions;

std::shared_ptr<Aws::Utils::RateLimits::RateLimiterInterface> writeRateLimiter =
 nullptr;

static Aws::String LoadConfigFromEnvOrProfile(const Aws::String& envKey, const
 Aws::String& profile,
```

```
                                                    const Aws::String& profileProperty, const
Aws::Vector<Aws::String>& allowedValues,
                                                    const Aws::String& defaultValue);
```

Configuration variable descriptions

The following list describes the `ClientConfiguration` member variables that you can use to customize client behavior.

accountId

Specifies the AWS account ID for account-based endpoint routing. Use the format 111122223333. Account-based endpoint routing improves request performance for some services.

accountIdEndpointMode

Controls account-based endpoint routing behavior. Valid values are "required", "disabled", or "preferred". The default value is "preferred". Set to "disabled" to turn off account-based endpoint routing when necessary.

allowSystemProxy

Controls whether the HTTP client discovers system proxy settings. The default setting is false. Set to true to enable automatic proxy discovery.

appId

Specifies an optional application-specific identifier. When set, this value is appended to the `User-Agent` header in the format `App/{appId}`. You can set this value using the `AWS_SDK_UA_APP_ID` environment variable or the `sdk_ua_app_id` shared config profile attribute.

caPath, caFile

Instructs the HTTP client where to find your SSL certificate trust store. An example trust store might be a directory prepared with the OpenSSL `c_rehash` utility. These variables should not need to be set unless your environment uses symlinks. These variables have no effect on Windows and macOS systems.

checksumConfig

Contains checksum calculation and validation settings. Includes `requestChecksumCalculation` and `responseChecksumValidation` with default value WHEN_SUPPORTED.

configFactories

Specifies factory methods for initializing client utility classes such as `Executor` and `RetryStrategy`. Uses default factories unless overridden.

requestTimeoutMs and connectTimeoutMs

Specifies the amount of time in milliseconds to wait before timing out an HTTP request. For example, consider increasing these times when transferring large files.

credentialProviderConfig

Contains configuration settings for credential providers. Use this structure to customize how the SDK obtains AWS credentials.

disableExpectHeader

Applicable only for CURL HTTP clients. By default, CURL adds an "Expect: 100-Continue" header in an HTTP request to avoid sending the HTTP payload in situations where the server responds with an error immediately after receiving the header. This behavior can save a round-trip and is useful in situations where the payload is small and network latency is relevant. The variable's default setting is false. If set to true, CURL is instructed to send both the HTTP request header and body payload together.

disableIMDS

Controls whether Instance Metadata Service (IMDS) calls are disabled. The default setting is false. Set to true to disable IMDS calls when running outside of EC2 instances.

disableImdsV1

Controls whether IMDSv1 calls are disabled while allowing IMDSv2. The default setting is false. Set to true to disable only IMDSv1 calls for enhanced security.

enableClockSkewAdjustment

Controls whether clock skew is adjusted after each HTTP attempt. The default setting is false.

enableEndpointDiscovery

Controls whether endpoint discovery is used. By default, regional or overridden endpoints are used. To enable endpoint discovery, set the variable to true.

enableHostPrefixInjection

Controls whether the HTTP host adds a "data-" prefix to DiscoverInstances requests. By default, this behavior is enabled. To disable it, set the variable to false.

enableHttpClientTrace

Controls whether HTTP client tracing is enabled for debugging purposes. The default setting is false. Set to true to enable detailed HTTP request and response logging.

enableTcpKeepAlive

Controls whether to send TCP keep-alive packets. The default setting is true. Use in conjunction with the `tcpKeepAliveIntervalMs` variable. This variable is not applicable for WinINet and the IXMLHTTPRequest2 client.

endpointOverride

Specifies an overriding HTTP endpoint with which to communicate with a service.

executor

References the implementation of the asynchronous Executor handler. The default behavior is to create and detach a thread for each async call. To change this behavior, implement a subclass of the `Executor` class and assign an instance to this variable.

followRedirects

Controls the behavior when handling HTTP 300 redirect codes.

httpLibOverride

Specifies the HTTP implementation returned by the default HTTP factory. The default HTTP client for Windows is WinHTTP. The default HTTP client for all other platforms is CURL.

httpLibPerfMode

Specifies the HTTP library performance mode. The default setting is LOW_LATENCY. You can adjust this setting to optimize for different performance characteristics.

httpRequestTimeoutMs

Specifies the HTTP request timeout in milliseconds. The default value is 0 (no timeout). Consider increasing this value when transferring large files.

lowSpeedLimit

Specifies the minimum allowed transfer speed in bytes per second. If the transfer speed falls below the specified speed, the transfer operation is aborted. The default setting is 1 byte/second. This variable is applicable only for CURL clients.

maxConnections

Specifies the maximum number of HTTP connections to a single server. The default value is 25. No maximum allowed value exists other than what your bandwidth can reasonably support.

nonProxyHosts

Specifies an array of hostnames that should bypass proxy settings. Use this setting to exclude specific hosts from proxy configuration.

profileName

Specifies the AWS profile name to use for configuration. The SDK loads settings from the specified profile in the AWS configuration file.

proxyCaFile

Specifies the path to the certificate authority file for proxy connections when it differs from the default.

proxyCaPath

Specifies the path to the certificate authority trust store for proxy connections when it differs from the default.

proxyScheme, proxyHost, proxyPort, proxyUserName, and proxyPassword

Used to set up and configure a proxy for all communications with AWS. Examples of when this functionality might be useful include debugging in conjunction with the Burp suite, or using a proxy to connect to the Internet.

proxySSLCertPath

Specifies the path to the SSL certificate file for proxy connections that require client certificates.

proxySSLCertType

Specifies the SSL certificate type for proxy connections. Common types include PEM and DER.

proxySSLKeyPassword

Specifies the password for the SSL private key used in proxy connections when the key is password-protected.

proxySSLKeyPath

Specifies the path to the SSL private key file for proxy connections that require client certificates.

proxySSLKeyType

Specifies the SSL private key type for proxy connections. Common types include PEM and DER.

writeRateLimiter and readRateLimiter

References to the implementations of read and write rate limiters which are used to throttle the bandwidth used by the transport layer. By default, the read and write rates are not throttled. To introduce throttling, implement a subclass of the `RateLimiterInterface` and assign an instance to these variables.

region

Specifies the AWS Region to use, such as *us-east-1*. By default, the Region used is the default Region configured in the applicable AWS credentials.

requestCompressionConfig

Contains configuration settings for request compression. Use this structure to control when and how requests are compressed before transmission.

retryStrategy

References the implementation of the retry strategy. The default strategy implements an exponential backoff policy. To perform a different strategy, implement a subclass of the `RetryStrategy` class and assign an instance to this variable.

scheme

Specifies the URI addressing scheme, either HTTP or HTTPS. The default scheme is HTTPS.

tcpKeepAliveIntervalMs

Specifies the time interval in milliseconds at which to send a keep-alive packet over a TCP connection. The default interval is 30 seconds. The minimum setting is 15 seconds. This variable is not applicable for WinINet and the IXMLHTTPRequest2 client.

telemetryProvider

References the telemetry provider implementation for collecting metrics and tracing data. Configure this setting to enable observability features.

userAgent

For internal use only. Do not change the setting of this variable.

useDualStack

Controls whether to use dual stack IPv4 and IPv6 endpoints. Note that not all AWS services support IPv6 in all Regions.

useFIPS

Controls whether to use Federal Information Processing Standards (FIPS) 140-2 validated cryptographic modules. The default setting is false. Set to true when FIPS compliance is required.

verifySSL

Controls whether to verify SSL certificates. By default SSL certificates are verified. To disable verification, set the variable to false.

version

Specifies the HTTP version to use for requests. The default setting is HTTP_VERSION_2TLS (HTTP/2 over TLS).

winHTTPOptions

Contains Windows-specific HTTP configuration options. Includes useAnonymousAuth with default setting false.

Setting the AWS Region for the AWS SDK for C++

You can access AWS services that operate in a specific geographic area by using AWS Regions. This can be useful both for redundancy and to keep your data and applications running close to where you and your users access them.

> **Important**
>
> Most resources reside in a specific AWS Region and you must supply the correct Region for the resource when using the SDK.

For examples on how to set the default region through the shared AWS `config` file or environment variables, see AWS Region in the *AWS SDKs and Tools Reference Guide*.

You must set a default AWS Region for the AWS SDK for C++ to use for AWS requests. This default is used for any SDK service method calls that aren't specified with a Region. In the SDK for C++, you can also set the default region using the Client configuration in code.

Using AWS SDK for C++ credential providers

All requests to AWS must be cryptographically signed by using credentials issued by AWS. At runtime, the SDK retrieves configuration values for credentials by checking several locations.

Authentication with AWS can be handled outside of your codebase. Many authentication methods can be automatically detected, used, and refreshed by the SDK using the credential provider chain.

For guided options for getting started on AWS authentication for your project, see Authentication and access in the *AWS SDKs and Tools Reference Guide*.

The credential provider chain

If you don't explicitly specify a credential provider when constructing a client, the SDK for C++ uses a credential provider chain that checks a series of places where you can supply credentials. Once the SDK finds credentials in one of these locations, the search stops.

Credential retrieval order

All SDKs have a series of places (or sources) that they check in order to get valid credentials to use to make a request to an AWS service. After valid credentials are found, the search is stopped. This systematic search is called the credential provider chain.

For each step in the chain, there are different ways to set the values. Setting values directly in code always takes precedence, followed by setting as environment variables, and then in the shared AWS `config` file. For more information, see Precedence of settings in the *AWS SDKs and Tools Reference Guide*.

The SDK attempts to load credentials from the `[default]` profile in the shared AWS `config` and `credentials` files. You can use the `AWS_PROFILE` environment variable to choose a named profile you want the SDK to load instead of using `[default]`. The `config` and `credentials` files are shared by AWS SDKs and tools. The *AWS SDKs and Tools Reference Guide* has information on SDK configuration settings used by all AWS SDKs and the AWS CLI. To learn more about how to configure the SDK through the shared AWS `config` file, see Shared config and credentials files. To learn more about how to configure the SDK through setting environment variables, see Environment variables support.

To authenticate with AWS, the SDK for C++ checks the credential providers in the following order.

1. **AWS access keys (temporary and long-term credentials)**

   The SDK attempts to load credentials from the `AWS_ACCESS_KEY_ID` and `AWS_SECRET_ACCESS_KEY`, and `AWS_SESSION_TOKEN` environment variables, or from the shared AWS `credentials` file.

   - For guidance on configuring this provider, see AWS access keys in the *AWS SDKs and Tools Reference Guide*.
   - For details on SDK configuration properties for this provider, see AWS access keys in the *AWS SDKs and Tools Reference Guide*.

2. **AWS STS web identity**

   When creating mobile applications or client-based web applications that require access to AWS, AWS Security Token Service (AWS STS) returns a set of temporary security credentials for federated users who are authenticated through a public identity provider (IdP).

- When you specify this in a profile, the SDK or tool attempts to retrieve temporary credentials using AWS STS `AssumeRoleWithWebIdentity` API method. For details on this method, see AssumeRoleWithWebIdentity in the *AWS Security Token Service API Reference*.
- For guidance on configuring this provider, see Federate with web identity or OpenID Connect in the *AWS SDKs and Tools Reference Guide*.
- For details on SDK configuration properties for this provider, see Assume role credential provider in the *AWS SDKs and Tools Reference Guide*.

3. **IAM Identity Center**

   If you use IAM Identity Center to authenticate, this is when the SDK for C++ uses the single sign-on token that was set up by running AWS CLI command `aws sso login`. The SDK uses the temporary credentials that the IAM Identity Center exchanged for a valid token. The SDK then uses the temporary credentials when it calls AWS services. For detailed information about this process, see Understand SDK credential resolution for AWS services in the *AWS SDKs and Tools Reference Guide*.

   - For guidance on configuring this provider, see IAM Identity Center authentication in the *AWS SDKs and Tools Reference Guide*.
   - For details on SDK configuration properties for this provider, see IAM Identity Center credential provider in the *AWS SDKs and Tools Reference Guide*.

4. **Login credential identity resolver with AWS Signin**

   If you use AWS sign in and console credentials to authenticate, this is when the SDK for C++ uses the console credentials set up by running `aws login` or `aws login --profile` in the CLI. The SDK uses these credentials when it calls AWS services.

   - For detailed information about this process, see Login for AWS local development using console credentials in the *AWS SDKs and Tools Reference Guide*.

5. **External process provider**

   This provider can be used to provide custom implementations, such as retrieving credentials from an on-premises credentials store or integrating with your on-premises identify provider.

   - For guidance on one way to configure this provider, see IAM Roles Anywhere in the *AWS SDKs and Tools Reference Guide*.
   - For details on SDK configuration properties for this provider, see Process credential provider in the *AWS SDKs and Tools Reference Guide*.

6. **Amazon ECS and Amazon EKS container credentials**

Your Amazon Elastic Container Service tasks and Kubernetes service accounts can have an IAM role associated with them. The permissions granted in the IAM role are assumed by the containers running in the task or containers of the pod. This role allows your SDK for C++ application code (on the container) to use other AWS services.

The SDK attempts to retrieve credentials from the `AWS_CONTAINER_CREDENTIALS_RELATIVE_URI` or `AWS_CONTAINER_CREDENTIALS_FULL_URI` environment variables, which can be set automatically by Amazon ECS and Amazon EKS.

- For details on setting up this role for Amazon ECS, see Amazon ECS task IAM role in the *Amazon Elastic Container Service Developer Guide*.
- For Amazon EKS setup information, see Setting up the Amazon EKS Pod Identity Agent in the Amazon EKS User Guide.
- For details on SDK configuration properties for this provider, see Container credential provider in the *AWS SDKs and Tools Reference Guide*.

7. **Amazon EC2 Instance Metadata Service**

   Create an IAM role and attach it to your instance. The SDK for C++ application on the instance attempts to retrieve the credentials provided by the role from the instance metadata.

   - For details on setting up this role and using metadata, IAM roles for Amazon EC2 and Work with instance metadata in the *Amazon EC2 User Guide*.
   - For details on SDK configuration properties for this provider, see IMDS credential provider in the *AWS SDKs and Tools Reference Guide*.

The credential provider chain can be reviewed at `AWSCredentialsProviderChain` in the AWS SDK for C++ source code on GitHub.

If you followed the recommended approach for new users to get started, you set up AWS Login Credentials authentication during Authenticating with AWS using AWS SDK for C++ of the Getting started topic. Other authentication methods are useful for different situations. To avoid security risks, we recommend always using short-term credentials. For other authentication method procedures, see Authentication and access in the *AWS SDKs and Tools Reference Guide*.

Explicit credential provider

Instead of relying on the credential provider chain to detect your authentication method, you can specify a specific credential provider that the SDK should use. You can do this by providing credentials in your service client's constructor.

The following example creates an Amazon Simple Storage Service client by directly providing temporary access credentials instead of using the chain.

```
    SDKOptions options;
    Aws::InitAPI(options);
    {
        const auto cred_provider =
Aws::MakeShared<Auth::SimpleAWSCredentialsProvider>("TestAllocationTag",
            "awsAccessKeyId",
            "awsSecretKey",
            "sessionToken");
        S3Client client{cred_provider};
    }
    Aws::ShutdownAPI(options);
```

Identity caching

The SDK will cache credentials and other identity types such as SSO tokens. By default, the SDK uses a lazy cache implementation that loads credentials upon first request, caches them, and then attempts to refresh them during another request when they are close to expiring. Clients created from the same `Aws::Client::ClientConfiguration` share a cache.

CMake parameters for building the AWS SDK for C++

Use the CMake parameters listed in this section to customize how your SDK builds.

You can set these options with CMake GUI tools or the command line by using *-D*. For example:

```
cmake -DENABLE_UNITY_BUILD=ON -DREGENERATE_CLIENTS=1
```

General CMake Variables and Options

The following are general **`cmake`** variables and options that affect the build process of the SDK source code.

> **Note**
>
> Use these parameters when building the SDK source code for the SDK for C++ itself.

Topics

- ADD_CUSTOM_CLIENTS
- AUTORUN_UNIT_TESTS
- AWS_AUTORUN_LD_LIBRARY_PATH
- AWS_SDK_WARNINGS_ARE_ERRORS
- AWS_USE_CRYPTO_SHARED_LIBS
- AWS_TEST_REGION
- BUILD_BENCHMARKS
- BUILD_DEPS
- BUILD_ONLY
- BUILD_OPTEL
- BUILD_SHARED_LIBS
- BYPASS_DEFAULT_PROXY
- CPP_STANDARD
- CURL_INCLUDE_DIR
- CURL_LIBRARY
- CUSTOM_MEMORY_MANAGEMENT
- DISABLE_INTERNAL_IMDSV1_CALLS
- ENABLE_ADDRESS_SANITIZER
- ENABLE_CURL_LOGGING
- ENABLE_HTTP_CLIENT_TESTING
- ENABLE_RTTI
- ENABLE_TESTING
- ENABLE_UNITY_BUILD
- ENABLE_VIRTUAL_OPERATIONS

- ENABLE_ZLIB_REQUEST_COMPRESSION
- FORCE_CURL
- FORCE_SHARED_CRT
- G
- MINIMIZE_SIZE
- NO_ENCRYPTION
- NO_HTTP_CLIENT
- REGENERATE_CLIENTS
- REGENERATE_DEFAULTS
- SIMPLE_INSTALL
- TARGET_ARCH
- USE_CRT_HTTP_CLIENT
- USE_IXML_HTTP_REQUEST_2
- USE_OPENSSL
- USE_TLS_V1_2
- USE_TLS_V1_3

ADD_CUSTOM_CLIENTS

Builds any arbitrary clients based on the API definition. Place your definition in the `code-generation/api-definitions` folder, and then pass this argument to **`cmake`** . The **`cmake`** configure step generates your client and includes it as a subdirectory in your build. This is particularly useful to generate a C++ client for using one of your API Gateway services. For example:

```
-
DADD_CUSTOM_CLIENTS="serviceName=myCustomService,version=2015-12-21;serviceName=someOtherServic
```

> **Note**
>
> To use the `ADD_CUSTOM_CLIENTS` parameter, you must have Python 2.7, Java (JDK 1.8+), and Maven installed and in your `PATH`.

AUTORUN_UNIT_TESTS

If ON, run unit tests automatically after building.

Values

ON | *OFF*

Default

ON

AWS_AUTORUN_LD_LIBRARY_PATH

The path to append into LD_LIBRARY_PATH for unit tests autorun by CMake. Set this path if custom runtime libraries are required for overridden dependencies.

Values

String.

Default

N/A

AWS_SDK_WARNINGS_ARE_ERRORS

If ON, treat compiler warnings as errors. Try turning this OFF if observing errors on a new or uncommon compiler.

Values

ON | *OFF*

Default

ON

AWS_USE_CRYPTO_SHARED_LIBS

Forces FindCrypto to use a shared crypto library if found. Turn this OFF to use BUILD_SHARED_LIBS's setting instead.

Values

ON | *OFF*

Default

OFF

AWS_TEST_REGION

The AWS Region to use for integration tests.

Values

String.

Default

N/A

BUILD_BENCHMARKS

If ON, build the benchmark executable.

Values

ON | *OFF*

Default

OFF

BUILD_DEPS

If ON, build third-party dependencies.

Values

ON | *OFF*

Default

ON

BUILD_ONLY

Builds only the clients you want to use. If set to a high-level SDK such as `aws-cpp-sdk-transfer`, *BUILD_ONLY* resolves any low-level client dependencies. It also builds integration and unit tests related to the projects you select, if they exist. This is a list argument, with values separated by semicolon (`;`) characters. For example:

```
-DBUILD_ONLY="s3;cognito-identity"
```

> **Note**
>
> The core SDK module, `aws-sdk-cpp-core`, is *always* built, regardless of the value of the *BUILD_ONLY* parameter.

BUILD_OPTEL

If `ON`, builds the open telemetry implementation of tracing.

Values

ON | *OFF*

Default

OFF

BUILD_SHARED_LIBS

A built-in CMake option, re-exposed here for visibility. If `ON`, it builds shared libraries; otherwise, it builds only static libraries.

> **Note**
>
> To dynamically link to the SDK, you must define the `USE_IMPORT_EXPORT` symbol for all build targets using the SDK.

Values

ON | *OFF*

Default

ON

BYPASS_DEFAULT_PROXY

If `ON`, bypass the machine's default proxy settings when using IXmlHttpRequest2.

Values

ON | *OFF*

Default

ON

CPP_STANDARD

Specifies a custom C++ standard for use with C++ 14 and 17 code bases.

Values

11 | *14* | *17*

Default

11

CURL_INCLUDE_DIR

Path to curl include directory containing `libcurl` headers.

Values

String path to selected `include` directory. For example, `D:/path/to/dir/with/curl/include`.

Default

N/A

CURL_LIBRARY

Path to curl library file to link against. This library can be a static library or an import library, depending on the needs of your application.

Values

String path to the curl library file. For example, `D:/path/to/static/libcur/file/ie/libcurl.lib.a`.

Default

N/A

CUSTOM_MEMORY_MANAGEMENT

To use a custom memory manager, set the value to `1`. You can install a custom allocator so that all STL types use the custom allocation interface. If you set the value `0`, you still might want to use the STL template types to help with DLL safety on Windows.

If static linking is `ON`, custom memory management defaults to *off* (`0`). If dynamic linking is `ON`, custom memory management defaults to *on* (`1`) and avoids cross-DLL allocation and deallocation.

> **Note**
>
> To prevent linker mismatch errors, you must use the same value (`0` or `1`) throughout your build system.

To install your own memory manager to handle allocations made by the SDK, you must set `-DCUSTOM_MEMORY_MANAGEMENT` and define `USE_AWS_MEMORY_MANAGEMENT` for all build targets that depend on the SDK.

DISABLE_INTERNAL_IMDSV1_CALLS

If `ON`, no internal calls are made to the V1 API of the Instance Metadata Service. If `OFF`, IMDSv2 calls will fallback to using IMDSv1 if the IMDSv2 call fails. For more information on IMDSv1 and IMDSv2, see Use the Instance Metadata Service to access instance metadata in the *Amazon EC2 User Guide*.

Values

ON | *OFF*

Default

OFF

ENABLE_ADDRESS_SANITIZER

If ON, turns on Address Sanitizer for gcc or clang.

Values

ON | *OFF*

Default

OFF

ENABLE_CURL_LOGGING

If ON, pipe the internal log for curl to the SDK logger.

Values

ON | *OFF*

Default

OFF

ENABLE_HTTP_CLIENT_TESTING

If ON, build and run corresponding HTTP client test suites.

Values

ON | *OFF*

Default

OFF

ENABLE_RTTI

Controls whether the SDK is built to enable run-time type information (RTTI).

Values

ON | *OFF*

Default

ON

ENABLE_TESTING

Controls whether unit and integration test projects are built during the SDK build.

Values

ON | *OFF*

Default

ON

ENABLE_UNITY_BUILD

If `ON`, most SDK libraries are built as a single, generated `.cpp` file. This can significantly reduce static library size and speed up compilation time.

Values

ON | *OFF*

Default

OFF

ENABLE_VIRTUAL_OPERATIONS

This parameter usually works together with `REGENERATE_CLIENTS` for code generation.

If `ENABLE_VIRTUAL_OPERATIONS` is `ON` and `REGENERATE_CLIENTS` is `ON`, operation-related functions in service clients will be marked as `virtual`.

If `ENABLE_VIRTUAL_OPERATIONS` is `OFF` and `REGENERATE_CLIENTS` is `ON`, `virtual` won't be added to operation functions and service client classes will be marked as `final`.

If `ENABLE_VIRTUAL_OPERATIONS` is `OFF`, the SDK will also add `-ffunction-sections` and `-fdata-sections` compiler flags for gcc and clang when compiling.

For more information, see CMake Parameters on GitHub.

Values

ON | *OFF*

Default

ON

ENABLE_ZLIB_REQUEST_COMPRESSION

For services that support it, request content will be compressed. On by default if dependency is available.

Values

ON | *OFF*

Default

ON

FORCE_CURL

Windows only. If `ON`, forces usage of the curl client instead of the default WinHTTP data transfer provider.

Values

ON | *OFF*

Default

OFF

FORCE_SHARED_CRT

If ON, the SDK links to the C runtime *dynamically*; otherwise, it uses the *BUILD_SHARED_LIBS* setting (sometimes necessary for backward compatibility with earlier versions of the SDK).

Values

ON | *OFF*

Default

ON

G

Generates build artifacts, such as Visual Studio solutions and Xcode projects.

For example, on Windows:

```
-G "Visual Studio 12 Win64"
```

For more information, see the CMake documentation for your platform.

MINIMIZE_SIZE

A superset of ENABLE_UNITY_BUILD. If ON, this option turns on *ENABLE_UNITY_BUILD* and additional binary size reduction settings.

Values

ON | *OFF*

Default

OFF

NO_ENCRYPTION

If ON, prevents the default platform-specific cryptography implementation from being built into the library. Turn this *ON* to inject your own cryptography implementation.

Values

ON | *OFF*

Default

OFF

NO_HTTP_CLIENT

If ON, prevents the default platform-specific HTTP client from being built into the library. If *ON*, you will need to provide your own platform-specific HTTP client implementation.

Values

ON | *OFF*

Default

OFF

REGENERATE_CLIENTS

If ON, this parameter deletes all generated code and generates the client directories from the `code-generation/api-definitions` folder. For example:

```
-DREGENERATE_CLIENTS=1
```

> **Note**
>
> To use the REGENERATE_CLIENTS parameter, you must have Python 2.7, Java (JDK 1.8+), and Maven installed and in your PATH.

REGENERATE_DEFAULTS

If ON, this parameter deletes all generated defaults code and generates it again from the `code-generation/defaults` folder. For example:

```
-DREGENERATE_DEFAULTS=1
```

> **Note**
>
> To use the REGENERATE_DEFAULTS parameter, you must have Python 2.7, Java (JDK 1.8+), and Maven installed and in your PATH.

SIMPLE_INSTALL

If ON, the install process does not insert platform-specific intermediate directories underneath `bin/` and `lib/`. Turn OFF if you need to make multiplatform releases under a single install directory.

Values

ON | *OFF*

Default

ON

TARGET_ARCH

To cross-compile or build for a mobile platform, you must specify the target platform. By default, the build detects the host operating system and builds for the detected operating system.

> **Note**
>
> When *TARGET_ARCH* is *ANDROID*, additional options are available. See Android CMake Variables and Options.

Values

WINDOWS | *LINUX* | *APPLE* | *ANDROID*

USE_CRT_HTTP_CLIENT

If ON, use the common runtime HTTP client, and the legacy systems such as WinHttp and libcurl are not built or included.

Values

ON | *OFF*

Default

OFF

USE_IXML_HTTP_REQUEST_2

Windows only. If `ON`, use the com object IXmlHttpRequest2 for the HTTP stack.

Values

ON | *OFF*

Default

OFF

USE_OPENSSL

If `ON`, the SDK builds using OpenSSL; otherwise, it uses [awslabs/aws-lc](). `AWS-LC` is a general-purpose cryptographic library maintained by the AWS Cryptography team for AWS and their customers. Turning `OFF` the parameter installs `AWS-LC` as replacement of OpenSSL in the system default directory. Don't use if you already have an OpenSSL installation in your system.

Values

ON | *OFF*

Default

ON

USE_TLS_V1_2

If `ON`, the HTTP client enforces TLS 1.2.

Values

ON | *OFF*

Default

ON

USE_TLS_V1_3

If ON, the HTTP client enforces TLS 1.3.

Values

ON | *OFF*

Default

OFF

Android CMake Variables and Options

Use the following variables when you are creating an Android build of the SDK (when TARGET_ARCH is set to *ANDROID*).

Topics

- ANDROID_ABI
- ANDROID_BUILD_CURL
- ANDROID_BUILD_OPENSSL
- ANDROID_BUILD_ZLIB
- ANDROID_NATIVE_API_LEVEL
- ANDROID_STL
- ANDROID_TOOLCHAIN_NAME
- DISABLE_ANDROID_STANDALONE_BUILD
- NDK_DIR

ANDROID_ABI

Android only. Controls which Application Binary Interface (ABI) to output code for.

> **Note**
>
> Not all valid Android ABI values are currently supported.

Values

arm64 | *armeabi-v7a* | *x86_64* | *x86* | *mips64* | *mips*

Default

armeabi-v7a

ANDROID_BUILD_CURL

Android only. If ON, build curl also.

Values

ON | *OFF*

Default

ON

ANDROID_BUILD_OPENSSL

Android only. If ON, build Openssl also.

Values

ON | *OFF*

Default

ON

ANDROID_BUILD_ZLIB

Android only. If ON, build Zlib also.

Values

ON | *OFF*

Default

ON

ANDROID_NATIVE_API_LEVEL

Android only. Controls what API level the SDK builds against. If you set ANDROID_STL to *gnustl*, you can choose any API level. If you use *libc++*, you must use an API level of at least *21*.

Default

Varies by STL choice.

ANDROID_STL

Android only. Controls what flavor of the C++ standard library the SDK uses.

> **Important**
>
> Performance problems can occur within the SDK if the `gnustl` options are used; we strongly recommend using *libc++_shared* or *libc++_static*.

Values

libc++_shared | *libc++_static* | *gnustl_shared* | *gnustl_static*

Default

libc++_shared

ANDROID_TOOLCHAIN_NAME

Android only. Controls which compiler is used to build the SDK.

> **Note**
>
> With GCC being deprecated by the Android NDK, we recommend using the default value.

Default

standalone-clang

DISABLE_ANDROID_STANDALONE_BUILD

Android only. By default, Android builds use a standalone clang-based toolchain constructed via NDK scripts. To use your own toolchain, turn this option *ON*.

Values

ON | *OFF*

Default

OFF

NDK_DIR

Android only. Specifies an override path where the build system should find the Android NDK. By default, the build system checks environment variables (`ANDROID_NDK`) if this variable is not set.

Configuring and using logging in the AWS SDK for C++

The AWS SDK for C++ includes configurable logging that generates a record of actions performed by the SDK during execution. To enable logging, set the `LogLevel` of `SDKOptions` to the appropriate verbosity for your application.

```
Aws::SDKOptions options;
options.loggingOptions.logLevel = Aws::Utils::Logging::LogLevel::Info;
```

There are seven levels of verbosity to choose from. The default value is `Off` and no logs will be generated. `Trace` will generate the most level of detail, and `Fatal` will generate the least messages reporting only fatal error conditions.

Once logging is enabled in your application, the SDK will generate log files in your executable directory following the default naming pattern of `aws_sdk_<date>.log`. The log file generated by the prefix-naming option rolls over once per hour to allow for archiving or deleting log files.

The later versions of the SDK increasingly depend on the underlying AWS Common Runtime (CRT) libraries. These libraries provide common functionality and basic operations among SDKs. All log messages from the CRT libraries will be redirected to the SDK for C++ by default. The log level and logging system you specify for the SDK for C++ also applies to the CRT.

In the previous example, the CRT will inherit `LogLevel::Info` and also log messages at the `Info` level to the same file.

You can independently control the logging for the CRT libraries, either by redirecting its output to a separate log file, or by setting a different log level for messages from the CRT. Often it can be beneficial to reduce the verbosity of the CRT libraries so that they don't overwhelm the logs. For example, the log level for *only* the CRT output can be set to `Warn` as follows:

```
options.loggingOptions.crt_logger_create_fn =
    [](){ return
 Aws::MakeShared<Aws::Utils::Logging::DefaultCRTLogSystem>("CRTLogSystem",
 Aws::Utils::Logging::LogLevel::Warn); };
```

By optionally using the method `InitializeAWSLogging`, you can control the verbosity level and the log output of the `DefaultLogSystem`. You can configure the log filename prefix, or redirect the output to a stream instead of a file.

```
Aws::Utils::Logging::InitializeAWSLogging(
    Aws::MakeShared<Aws::Utils::Logging::DefaultLogSystem>(
        "RunUnitTests", Aws::Utils::Logging::LogLevel::Trace, "aws_sdk_"));
```

Alternatively, instead of using the `DefaultLogSystem`, you can also use this method to provide your own logging implementation.

```
InitializeAWSLogging(Aws::MakeShared<CustomLoggingSystem>());
```

If you call method `InitializeAWSLogging`, free resources at the end of your program by calling `ShutdownAWSLogging`.

```
Aws::Utils::Logging::ShutdownAWSLogging();
```

Example integration test with logging

```
#include <aws/external/gtest.h>

#include <aws/core/utils/memory/stl/AWSString.h>
#include <aws/core/utils/logging/DefaultLogSystem.h>
#include <aws/core/utils/logging/AWSLogging.h>

#include <iostream>

int main(int argc, char** argv)
{
    Aws::Utils::Logging::InitializeAWSLogging(
        Aws::MakeShared<Aws::Utils::Logging::DefaultLogSystem>(
            "RunUnitTests", Aws::Utils::Logging::LogLevel::Trace, "aws_sdk_"));
    ::testing::InitGoogleTest(&argc, argv);
    int exitCode = RUN_ALL_TESTS();
    Aws::Utils::Logging::ShutdownAWSLogging();
    return exitCode;
}
```

Example subclass of `Aws::Utils::Logging::DefaultLogSystem` for custom logging

The following code demonstrates how to subclass the `Aws::Utils::Logging::DefaultLogSystem` class, which is part of the AWS SDK for C++. This example overrides the `ProcessFormattedStatement` virtual function to customize logging.

`Aws::Utils::Logging::DefaultLogSystem` is one of several classes in the AWS SDK for C++ that subclass `Aws::Utils::Logging::LogSystemInterface` for custom logging.

```
class LogSystemOverride : public Aws::Utils::Logging::DefaultLogSystem {
public:
    explicit LogSystemOverride(Aws::Utils::Logging::LogLevel logLevel,
                               const Aws::String &logPrefix)
            : DefaultLogSystem(logLevel, logPrefix), mLogToStreamBuf(false) {}

    const Aws::Utils::Stream::SimpleStreamBuf &GetStreamBuf() const {
        return mStreamBuf;
    }

    void setLogToStreamBuf(bool logToStreamBuf) {
        mLogToStreamBuf = logToStreamBuf;
    }
```

```
protected:

    void ProcessFormattedStatement(Aws::String &&statement) override {
        if (mLogToStreamBuf) {
            std::lock_guard<std::mutex> lock(mStreamMutex);
            mStreamBuf.sputn(statement.c_str(), statement.length());
        }

        DefaultLogSystem::ProcessFormattedStatement(std::move(statement));
    }

private:
    Aws::Utils::Stream::SimpleStreamBuf mStreamBuf;
    // Use a mutex when writing to the buffer because
    // ProcessFormattedStatement can be called from multiple threads.
    std::mutex mStreamMutex;
    std::atomic<bool> mLogToStreamBuf;
};
```

```
int main(int argc, char **argv) {
    Aws::SDKOptions options;
    options.loggingOptions.logLevel = Aws::Utils::Logging::LogLevel::Trace;
    auto logSystemOverride = Aws::MakeShared<LogSystemOverride>("AllocationTag",

 options.loggingOptions.logLevel,

 options.loggingOptions.defaultLogPrefix);
    options.loggingOptions.logger_create_fn = [logSystemOverride]() {
        return logSystemOverride;
    };

    Aws::InitAPI(options);  // Call Aws::InitAPI only once in an application.
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::S3::S3Client s3Client(clientConfig);

        logSystemOverride->setLogToStreamBuf(true);
        auto outcome = s3Client.ListBuckets();
        if (!outcome.IsSuccess()) {
```

```
            std::cerr << "ListBuckets error: " <<
                      outcome.GetError().GetExceptionName() << " " <<
                      outcome.GetError().GetMessage() << std::endl;
        }

        logSystemOverride->setLogToStreamBuf(false);

        std::cout << "Log for ListBuckets" << std::endl;
        std::cout << logSystemOverride->GetStreamBuf().str() << std::endl;
    }

    Aws::ShutdownAPI(options);

    return 0;
}
```

See the complete example on GitHub.

Overriding your HTTP client in the AWS SDK for C++

The default HTTP client for Windows is WinHTTP. The default HTTP client for all other platforms is curl.

Optionally, you can override the HTTP client default by creating a custom `HttpClientFactory` to pass to any service client's constructor. To override the HTTP client, the SDK must be built with curl support. Curl support is built by default in Linux and macOS, but additional steps are required to build on Windows. For more information about building the SDK on Windows with curl support, see Building the AWS SDK for C++ on Windows.

Controlling iostreams used by the `HttpClient` and the `AWSClient` in the AWS SDK for C++

By default, all responses use an input stream backed by a `stringbuf`. If needed, you can override the default behavior. For example, if you are using an Amazon S3 `GetObject` and don't want to load the entire file into memory, you can use `IOStreamFactory` in `AmazonWebServiceRequest` to pass a lambda to create a file stream.

Example file stream request

```
//! Use a custom response stream when downloading an object from an Amazon Simple
```

```
//! Storage Service (Amazon S3) bucket.
/*!
  \param bucketName: The Amazon S3 bucket name.
  \param objectKey: The object key.
  \param filePath: File path for custom response stream.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */

bool AwsDoc::SdkCustomization::customResponseStream(const Aws::String &bucketName,
                                                    const Aws::String &objectKey,
                                                    const Aws::String &filePath,
                                                    const
 Aws::Client::ClientConfiguration &clientConfiguration) {

    Aws::S3::S3Client s3_client(clientConfiguration);

    Aws::S3::Model::GetObjectRequest getObjectRequest;
    getObjectRequest.WithBucket(bucketName).WithKey(objectKey);

    getObjectRequest.SetResponseStreamFactory([filePath]() {
            return Aws::New<Aws::FStream>(
                    "FStreamAllocationTag", filePath, std::ios_base::out);
    });

    Aws::S3::Model::GetObjectOutcome getObjectOutcome = s3_client.GetObject(
            getObjectRequest);

    if (getObjectOutcome.IsSuccess()) {
        std::cout << "Successfully retrieved object to file " << filePath << std::endl;
    }
    else {
        std::cerr << "Error getting object. "
                  << getObjectOutcome.GetError().GetMessage() << std::endl;
    }

    return getObjectOutcome.IsSuccess();
}
```

Note

There's more on GitHub. Find the complete example in the AWS Code Examples Repository.

Using a custom libcrypto library in the AWS SDK for C++

By default, the AWS SDK for C++ uses the default system cryptographic library for transport layer security. However, the SDK for C++ can optionally be configured to use a different libcrypto library when building the SDK from source. This functionally means that all cryptographic operations will be diverted to a custom implementation of OpenSSL. For example, you might want to use the AWS-LC library in FIPS mode to achieve a FIPS standard in your application.

How to build a custom libcrypto into the SDK for C++

Step 1: Build or obtain your libcrypto library

The AWS-LC is one example of an alternative libcrypto library, but any distribution of OpenSSL or OpenSSL-equivalent would work.

The SDK for C++, and its dependency the CRT, both use libcrypto for their cryptographic functions and both need to handle dependencies the same. The SDK for C++ depends on two different HTTP clients depending on if the request uses the SDK's CRT S3 functionality. The CRT specifically is dependent on s2n, a TLS implementation that is initialized at start up time. Both the SDK and the s2n team have a cmake parameter to force the use of a shared libcrypto library regardless of the value of BUILD_SHARED_LIBS. Typically, you want the CRT HTTP client and the regular HTTP client to use the same libcrypto. In this case, that would mean both referencing OpenSSL in the dependency tree. The SDK provides this via AWS_USE_CRYPTO_SHARED_LIBS and s2n (for CRT-based calls) provides this through S2N_USE_CRYPTO_SHARED_LIBS. Dependency resolution is the same between these two libraries, and typically these are set to match, though you can explicitly set them to be different.

For example, to use AWS-LC as the libcrypto library, you would build it as follows:

```
git clone --depth 1 -b fips-2022-11-02 https://github.com/aws/aws-lc && \
    cd aws-lc && \
    mkdir build && \
    cd build && \
    cmake -G Ninja \
        -DCMAKE_INSTALL_LIBDIR=lib \
        -DCMAKE_INSTALL_PREFIX=/lc-install .. && \
    cmake --build . && \
    cmake --install . && \
    rm -rf ./* && \
    cmake -G Ninja \
```

```
        -DBUILD_SHARED_LIBS=ON \
        -DCMAKE_INSTALL_LIBDIR=lib \
        -DCMAKE_INSTALL_PREFIX=/lc-install .. && \
    cmake --build . && \
    cmake --install .
```

Step 2: Build curl from source or use a curl distribution with your libcrypto library

The SDK for C++ requires that an HTTP client is installed on the system that will be used to make HTTP requests. The HTTP client must be built with the libcrypto that you intend to use. The HTTP client is responsible for TLS operations and, thus, uses your libcrypto library.

In the following example, the curl library is rebuilt using an installed version of AWS-LC.

```
git clone --depth 1 -b curl-8_5_0 https://github.com/curl/curl && \
    cd curl && \
    autoreconf -fi && \
    mkdir build && \
    cd build && \
    ../configure \
        --enable-warnings \
        --enable-werror \
        --with-openssl=/lc-install \
        --prefix=/curl-install && \
    make && \
    make install
```

Step 3: Build the SDK using libcrypto and curl libraries

The SDK for C++ can now be built using the previously created libcrypto and curl artifacts. This build of the SDK will use the custom libcrypto library for all cryptographic functionality.

```
git clone --depth 1 --recurse-submodules https://github.com/aws/aws-sdk-cpp \
    cd aws-sdk-cpp && \
    mkdir build && \
    cd build && \
    cmake -G Ninja \
        -DCMAKE_PREFIX_PATH="/curl-install;/lc-install;" \
        -DBUILD_ONLY="s3" \
        -DCMAKE_INSTALL_PREFIX=/sdk-install \
        -DAUTORUN_UNIT_TESTS=OFF .. && \
    cmake --build . && \
```

```
    cmake --install .
```

Bringing it all together in a docker image

The following sample Docker file shows how to implement these steps in Amazon Linux 2023 environment.

```
# User AL2023 Base image
FROM public.ecr.aws/amazonlinux/amazonlinux:2023

# Install Dev Tools
RUN yum groupinstall -y "Development Tools"
RUN yum install -y cmake3 ninja-build

# Build and install AWS-LC on the fips branch both statically and dynamically.
RUN git clone --depth 1 -b fips-2022-11-02 https://github.com/aws/aws-lc && \\
    cd aws-lc && \\
    mkdir build && \\
    cd build && \\
    cmake -G Ninja \\
        -DCMAKE_INSTALL_LIBDIR=lib \\
        -DCMAKE_INSTALL_PREFIX=/lc-install .. && \\
    cmake --build . && \\
    cmake --install . && \\
    rm -rf ./* && \\
    cmake -G Ninja \\
        -DBUILD_SHARED_LIBS=ON \\
        -DCMAKE_INSTALL_LIBDIR=lib \\
        -DCMAKE_INSTALL_PREFIX=/lc-install .. && \\
    cmake --build . && \\
    cmake --install .

# Build and install curl targeting AWS-LC as openssl
RUN git clone --depth 1 -b curl-8_5_0 https://github.com/curl/curl && \\
    cd curl && \\
    autoreconf -fi && \\
    mkdir build && \\
    cd build && \\
    ../configure \\
        --enable-warnings \\
        --enable-werror \\
        --with-openssl=/lc-install \\
```

```
        --prefix=/curl-install && \\
    make && \\
    make install

# Build and install SDK using the Curl and AWS-LC targets previously built
RUN git clone --depth 1 --recurse-submodules https://github.com/aws/aws-sdk-cpp \\
    cd aws-sdk-cpp && \\
    mkdir build && \\
    cd build && \\
    cmake -G Ninja \\
        -DCMAKE_PREFIX_PATH="/curl-install;/lc-install;" \\
        -DBUILD_ONLY="s3" \\
        -DCMAKE_INSTALL_PREFIX=/sdk-install \\
        -DAUTORUN_UNIT_TESTS=OFF .. && \\
    cmake --build . && \\
    cmake --install .
```

Using the AWS SDK for C++

This section provides information about general use of the AWS SDK for C++, beyond what is covered in Getting Started Using the AWS SDK for C++.

For service-specific programming examples, see AWS SDK for C++ Code Examples.

Topics

- Initializing and shutting down the AWS SDK for C++
- Making AWS service requests using the AWS SDK for C++
- Asynchronous programming using the AWS SDK for C++
- Utility modules available in the AWS SDK for C++
- Memory management in the the AWS SDK for C++
- Handling errors in the AWS SDK for C++

Initializing and shutting down the AWS SDK for C++

Applications that use the AWS SDK for C++ must initialize it. Similarly, before the application terminates, the SDK must be shut down. Both operations accept configuration options that affect the initialization and shutdown processes and subsequent calls to the SDK.

All applications that use the AWS SDK for C++ must include the file `aws/core/Aws.h`.

The AWS SDK for C++ must be initialized by calling `Aws::InitAPI`. Before the application terminates, the SDK must be shut down by calling `Aws::ShutdownAPI`. Each method accepts an argument of `Aws::SDKOptions`. All other calls to the SDK can be performed between these two method calls.

All AWS SDK for C++ calls performed between `Aws::InitAPI` and `Aws::ShutdownAPI` should either to be contained within a pair of curly braces or should be invoked by functions called between the two methods.

A basic skeleton application is shown below.

```
#include <aws/core/Aws.h>
```

```
int main(int argc, char** argv)
{
   Aws::SDKOptions options;
   Aws::InitAPI(options);
   {
      // make your SDK calls here.
   }
   Aws::ShutdownAPI(options);
   return 0;
}
```

The SDK for C++ and its dependencies use C++ static objects, and the order of static object destruction is not determined by the C++ standard. To avoid memory issues caused by the nondeterministic order of static variable destruction, do not wrap the calls to `Aws::InitAPI` and `Aws::ShutdownAPI` into another static object.

Making AWS service requests using the AWS SDK for C++

To programmatically access AWS services, SDKs use a client class for each AWS service. For example, if your application needs to access Amazon EC2, your application creates an Amazon EC2 client object to interface with that service. You then use the service client to make requests to that AWS service.

To make a request to an AWS service, you must first create and configure a service client. For each AWS service your code uses, it has its own library and its own dedicated type for interacting with it. The client exposes one method for each API operation exposed by the service.

The namespace for a client class follows the convention `Aws::`*`Service`*`::`*`Service`*`Client`. For example, the client class for AWS Identity and Access Management (IAM) is `Aws::IAM::IAMClient` and the Amazon S3 client class is `Aws::S3::S3Client`.

All client classes for all AWS services are thread-safe.

When instantiating a client class, AWS credentials must be supplied. Credentials can be supplied from your code, the environment, or the shared AWS `config` file and shared `credentials` file. For more information about credentials, see instructions for setting up the recommended IAM Identity Center authentication or use another credential provider that is available.

Asynchronous programming using the AWS SDK for C++

Asynchronous SDK methods

For many methods, the SDK for C++ provides both synchronous and asynchronous versions. A method is asynchronous if it includes the `Async` suffix in its name. For example, the Amazon S3 method `PutObject` is synchronous, while `PutObjectAsync` is asynchronous.

Like all asynchronous operations, an asynchronous SDK method returns before its main task is finished. For example, the `PutObjectAsync` method returns before it finishes uploading the file to the Amazon S3 bucket. While the upload operation continues, the application can perform other operations, including calling other asynchronous methods. The application is notified that an asynchronous operation has finished when an associated callback function is invoked.

The following sections describe a code example that demonstrates calling the `PutObjectAsync` asynchronous method. Each section focuses on individual portions from the example's entire source file.

Calling SDK asynchronous methods

In general, the asynchronous version of an SDK method accepts the following arguments.

- A reference to the same Request-type object as its synchronous counterpart.
- A reference to a response handler callback function. This callback function is invoked when the asynchronous operation finishes. One of the arguments contains the operation's outcome.
- An optional `shared_ptr` to an `AsyncCallerContext` object. The object is passed to the response handler callback. It includes a UUID property that can be used to pass text information to the callback.

The `uploadFileAsync` method shown below sets up and calls the SDK's Amazon S3 `PutObjectAsync` method to asynchronously upload a file to an Amazon S3 bucket.

The function receives references to an `S3Client` object and a `PutObjectRequest` object. It receives them from the main function because we need to ensure that these objects exist throughout the duration of the asynchronous calls.

A `shared_ptr` to an `AsyncCallerContext` object is allocated. Its `UUID` property is set to the Amazon S3 object name. For demonstration purposes, the response handler callback accesses the property and outputs its value.

The call to `PutObjectAsync` includes a reference argument to the response handler callback function `uploadFileAsyncFinished`. This callback function is examined in more detail in the next section.

```
bool AwsDoc::S3::uploadFileAsync(const Aws::S3::S3Client &s3Client,
                                 Aws::S3::Model::PutObjectRequest &request,
                                 const Aws::String &bucketName,
                                 const Aws::String &fileName) {
    request.SetBucket(bucketName);
    request.SetKey(fileName);

    const std::shared_ptr<Aws::IOStream> input_data =
            Aws::MakeShared<Aws::FStream>("SampleAllocationTag",
                                          fileName.c_str(),
                                          std::ios_base::in | std::ios_base::binary);

    if (!*input_data) {
        std::cerr << "Error: unable to open file " << fileName << std::endl;
        return false;
    }

    request.SetBody(input_data);

    // Create and configure the context for the asynchronous put object request.
    std::shared_ptr<Aws::Client::AsyncCallerContext> context =
            Aws::MakeShared<Aws::Client::AsyncCallerContext>("PutObjectAllocationTag");
    context->SetUUID(fileName);

    // Make the asynchronous put object call. Queue the request into a
    // thread executor and call the uploadFileAsyncFinished function when the
    // operation has finished.
    s3Client.PutObjectAsync(request, uploadFileAsyncFinished, context);

    return true;
}
```

The resources for an asynchronous operation must exist until the operation finishes. For example, the client and request objects must exist until the application receives notification that the operation completed. The application itself cannot terminate until the asynchronous operation completes.

For this reason, the `uploadFileAsync` method accepts a references to `S3Client` and `PutObjectRequest` objects instead of creating them in the `uploadFileAsync` method and storing them in a local variable.

In the example, the `PutObjectAsync` method returns to the caller immediately after beginning the asynchronous operation, enabling the calling chain to perform additional tasks while the upload operation is in progress.

If the client were stored in a local variable in the `uploadFileAsync` method, it would go out of scope when the method returned. However, the client object must continue to exist until the asynchronous operation finishes.

Notification of the Completion of an Asynchronous Operation

When an asynchronous operation finishes, an application response handler callback function is invoked. This notification includes the outcome of the operation. The outcome is contained in the same Outcome-type class returned by the method's synchronous counterpart. In the code example, the outcome is in a `PutObjectOutcome` object.

The example's response handler callback function `uploadFileAsyncFinished` is shown below. It checks whether the asynchronous operation succeeded or failed. It uses a `std::condition_variable` to notify the application thread that the async operation has finished.

```
// A mutex is a synchronization primitive that can be used to protect shared
// data from being simultaneously accessed by multiple threads.
std::mutex AwsDoc::S3::upload_mutex;

// A condition_variable is a synchronization primitive that can be used to
// block a thread, or to block multiple threads at the same time.
// The thread is blocked until another thread both modifies a shared
// variable (the condition) and notifies the condition_variable.
std::condition_variable AwsDoc::S3::upload_variable;
```

```
void uploadFileAsyncFinished(const Aws::S3::S3Client *s3Client,
                             const Aws::S3::Model::PutObjectRequest &request,
                             const Aws::S3::Model::PutObjectOutcome &outcome,
                             const std::shared_ptr<const
 Aws::Client::AsyncCallerContext> &context) {
    if (outcome.IsSuccess()) {
        std::cout << "Success: uploadFileAsyncFinished: Finished uploading '"
```

```
                  << context->GetUUID() << "'." << std::endl;
    } else {
        std::cerr << "Error: uploadFileAsyncFinished: " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    // Unblock the thread that is waiting for this function to complete.
    AwsDoc::S3::upload_variable.notify_one();
}
```

With the asynchronous operation finished, the resources associated with it can be released. The application can also terminate if it wishes.

The following code demonstrates how the `uploadFileAsync` and `uploadFileAsyncFinished` methods are used by an application.

The application allocates the `S3Client` and `PutObjectRequest` objects so that they continue to exist until the asynchronous operation finishes. After calling `uploadFileAsync`, the application can perform whatever operations it wishes. For simplicity, the example uses a `std::mutex` and `std::condition_variable` to wait until the response handler callback notifies it that the upload operation has finished.

```
int main(int argc, char* argv[])
{
    if (argc != 3)
    {
        std::cout << R"(
Usage:
    run_put_object_async <file_name> <bucket_name>
Where:
    file_name - The name of the file to upload.
    bucket_name - The name of the bucket to upload the object to.
)" << std::endl;
        return 1;
    }

    const Aws::SDKOptions options;
    Aws::InitAPI(options);
    {
        const Aws::String fileName = argv[1];
        const Aws::String bucketName = argv[2];
```

```
        // A unique_lock is a general-purpose mutex ownership wrapper allowing
        // deferred locking, time-constrained attempts at locking, recursive
        // locking, transfer of lock ownership, and use with
        // condition variables.
        std::unique_lock<std::mutex> lock(AwsDoc::S3::upload_mutex);

        // Create and configure the Amazon S3 client.
        // This client must be declared here, as this client must exist
        // until the put object operation finishes.
        const Aws::S3::S3ClientConfiguration config;
        // Optional: Set to the AWS Region in which the bucket was created (overrides
 config file).
        // config.region = "us-east-1";

        const Aws::S3::S3Client s3Client(config);

        // Create the request object.
        // This request object must be declared here, because the object must exist
        // until the put object operation finishes.
        Aws::S3::Model::PutObjectRequest request;

        AwsDoc::S3::uploadFileAsync(s3Client, request, bucketName, fileName);

        std::cout << "main: Waiting for file upload attempt..." <<
                  std::endl << std::endl;

        // While the put object operation attempt is in progress,
        // you can perform other tasks.
        // This example simply blocks until the put object operation
        // attempt finishes.
        AwsDoc::S3::upload_variable.wait(lock);

        std::cout << std::endl << "main: File upload attempt completed."
                  << std::endl;
    }
    Aws::ShutdownAPI(options);

    return 0;
}
```

See the complete example on Github.

Utility modules available in the AWS SDK for C++

The AWS SDK for C++ includes many utility modules to reduce the complexity of developing AWS applications in C++.

HTTP Stack

An HTTP stack that provides connection pooling, is thread-safe, and can be reused as you need. For more information, see AWS Client Configuration.

Headers	`/aws/core/http/`
API Documentation	`Aws::Http`

String Utils

Core string functions, such as `trim`, `lowercase`, and numeric conversions.

Header	`aws/core/utils/StringUtils.h`
API Documentation	`Aws::Utils::StringUtils`

Hashing Utils

Hashing functions such as SHA256, MD5, Base64, and SHA256_HMAC.

Header	`/aws/core/utils/HashingUtils.h`
API Documentation	`Aws::Utils::HashingUtils`

JSON Parser

A fully functioning yet lightweight JSON parser (a thin wrapper around *cJSON*).

Header	/aws/core/utils/json/JsonSerializer.h
API Documentation	Aws::Utils::Json::JsonValue

XML Parser

A lightweight XML parser (a thin wrapper around *tinyxml2*). The RAII pattern has been added to the interface.

Header	/aws/core/utils/xml/XmlSerializer.h
API Documentation	Aws::Utils::Xml

Memory management in the the AWS SDK for C++

The AWS SDK for C++ provides a way to control memory allocation and deallocation in a library.

> **Note**
>
> Custom memory management is available only if you use a version of the library built using the defined compile-time constant `USE_AWS_MEMORY_MANAGEMENT`.
> If you use a version of the library that is built without the compile-time constant, global memory system functions such as `InitializeAWSMemorySystem` won't work; the global `new` and `delete` functions are used instead.

For more information about the compile-time constant, see STL and AWS Strings and Vectors.

Allocating and Deallocating Memory

To allocate or deallocate memory

1. Subclass `MemorySystemInterface`: `aws/core/utils/memory/MemorySystemInterface.h`.

```
class MyMemoryManager : public Aws::Utils::Memory::MemorySystemInterface
{
public:
    // ...
    virtual void* AllocateMemory(
        std::size_t blockSize, std::size_t alignment,
        const char *allocationTag = nullptr) override;
    virtual void FreeMemory(void* memoryPtr) override;
};
```

> **Note**
>
> You can change the type signature for `AllocateMemory` as needed.

2. Use the `Aws::SDKOptions` struct to configure the use of the custom memory manager. Pass the instance of the struct into `Aws::InitAPI`. Before the application terminates, the SDK must be shut down by calling `Aws::ShutdownAPI` with the same instance.

```
int main(void)
{
  MyMemoryManager sdkMemoryManager;
  SDKOptions options;
  options.memoryManagementOptions.memoryManager = &sdkMemoryManager;
  Aws::InitAPI(options);

  // ... do stuff

  Aws::ShutdownAPI(options);

  return 0;
}
```

STL and AWS Strings and Vectors

When initialized with a memory manager, the AWS SDK for C++ defers all allocation and deallocation to the memory manager. If a memory manager doesn't exist, the SDK uses global new and delete.

If you use custom STL allocators, you must alter the type signatures for all STL objects to match the allocation policy. Because STL is used prominently in the SDK implementation and interface, a single approach in the SDK would inhibit direct passing of default STL objects into the SDK or control of STL allocation. Alternately, a hybrid approach—using custom allocators internally and allowing standard and custom STL objects on the interface—could potentially make it more difficult to investigate memory issues.

The solution is to use the memory system's compile-time constant `USE_AWS_MEMORY_MANAGEMENT` to control which STL types the SDK uses.

If the compile-time constant is enabled (on), the types resolve to STL types with a custom allocator connected to the AWS memory system.

If the compile-time constant is disabled (off), all `Aws::*` types resolve to the corresponding default `std::*` type.

Example code from the `AWSAllocator.h` file in the SDK

```
#ifdef USE_AWS_MEMORY_MANAGEMENT

template< typename T >
class AwsAllocator : public std::allocator< T >
{
   ... definition of allocator that uses AWS memory system
};

#else

template< typename T > using Allocator = std::allocator<T>;

#endif
```

In the example code, the `AwsAllocator` can be a custom allocator or a default allocator, depending on the compile-time constant.

Example code from the `AWSVector.h` file in the SDK

```
template<typename T> using Vector = std::vector<T, Aws::Allocator<T>>;
```

In the example code, we define the `Aws::*` types.

If the compile-time constant is enabled (on), the type maps to a vector using custom memory allocation and the AWS memory system.

If the compile-time constant is disabled (off), the type maps to a regular `std::vector` with default type parameters.

Type aliasing is used for all `std::` types in the SDK that perform memory allocation, such as containers, string streams, and string buffers. The AWS SDK for C++ uses these types.

Remaining Issues

You can control memory allocation in the SDK; however, STL types still dominate the public interface through string parameters to the model object `initialize` and `set` methods. If you don't use STL and use strings and containers instead, you have to create a lot of temporaries whenever you want to make a service call.

To remove most of the temporaries and allocation when you make service calls using non-STL, we have implemented the following:

- Every Init/Set function that takes a string has an overload that takes a `const char*`.
- Every Init/Set function that takes a container (map/vector) has an add variant that takes a single entry.
- Every Init/Set function that takes binary data has an overload that takes a pointer to the data and a `length` value.
- (Optional) Every Init/Set function that takes a string has an overload that takes a non-zero terminated `const char*` and a `length` value.

Native SDK Developers and Memory Controls

Follow these rules in the SDK code:

- Don't use `new` and `delete`; use `Aws::New<>` and `Aws::Delete<>` instead.
- Don't use `new[]` and `delete[]`; use `Aws::NewArray<>` and `Aws::DeleteArray<>`.
- Don't use `std::make_shared`; use `Aws::MakeShared`.
- Use `Aws::UniquePtr` for unique pointers to a single object. Use the `Aws::MakeUnique` function to create the unique pointer.

- Use `Aws::UniqueArray` for unique pointers to an array of objects. Use the `Aws::MakeUniqueArray` function to create the unique pointer.
- Don't directly use STL containers; use one of the `Aws::` typedefs or add a typedef for the container you want. For example:

```
Aws::Map<Aws::String, Aws::String> m_kvPairs;
```

- Use `shared_ptr` for any external pointer passed into and managed by the SDK. You must initialize the shared pointer with a destruction policy that matches how the object was allocated. You can use a raw pointer if the SDK is not expected to clean up the pointer.

Handling errors in the AWS SDK for C++

The AWS SDK for C++ does not use exceptions; however, you can use exceptions in your code. Every service client returns an outcome object that includes the result and an error code.

Example of handling error conditions

```
bool CreateTableAndWaitForItToBeActive()
{
  CreateTableRequest createTableRequest;
  AttributeDefinition hashKey;
  hashKey.SetAttributeName(HASH_KEY_NAME);
  hashKey.SetAttributeType(ScalarAttributeType::S);
  createTableRequest.AddAttributeDefinitions(hashKey);
  KeySchemaElement hashKeySchemaElement;
  hashKeySchemaElement.WithAttributeName(HASH_KEY_NAME).WithKeyType(KeyType::HASH);
  createTableRequest.AddKeySchema(hashKeySchemaElement);
  ProvisionedThroughput provisionedThroughput;
  provisionedThroughput.SetReadCapacityUnits(readCap);
  provisionedThroughput.SetWriteCapacityUnits(writeCap);
  createTableRequest.WithProvisionedThroughput(provisionedThroughput);
  createTableRequest.WithTableName(tableName);

  CreateTableOutcome createTableOutcome = dynamoDbClient-
>CreateTable(createTableRequest);
  if (createTableOutcome.IsSuccess())
  {
     DescribeTableRequest describeTableRequest;
     describeTableRequest.SetTableName(tableName);
     bool shouldContinue = true;
```

```
     DescribeTableOutcome outcome = dynamoDbClient-
>DescribeTable(describeTableRequest);

     while (shouldContinue)
     {
         if (outcome.GetResult().GetTable().GetTableStatus() == TableStatus::ACTIVE)
         {
            break;
         }
         else
         {
            std::this_thread::sleep_for(std::chrono::seconds(1));
         }
     }
     return true;
  }
  else if(createTableOutcome.GetError().GetErrorType() ==
 DynamoDBErrors::RESOURCE_IN_USE)
  {
     return true;
  }

  return false;
}
```

Calling AWS services from the AWS SDK for C++

The following sections contain examples, tutorials, tasks, and guides that show you how to use the AWS SDK for C++ to work with AWS services.

If you're new to the AWS SDK for C++, you might want to read through the Getting started topic first.

You can find more code examples in the C++ example folder on GitHub.

You can find more code examples in the Code examples chapter of this guide or in the AWS Code Examples Repository on GitHub.

Topics

- Getting started with the AWS SDK for C++ code examples
- Getting started troubleshooting runtime errors in the AWS SDK for C++
- Guided examples for calling AWS services using the AWS SDK for C++

Getting started with the AWS SDK for C++ code examples

Structure of the code examples

The C++ example folder on Github contains project folders for each AWS service. Typically, individual .cpp source files in the folders demonstrate a specific functionality or action for that service. For example, for Amazon DynamoDB, *getting* an item from the database and *uploading* an item to the database are two different types of action, so there is a separate file for each in the DynamoDB folder: `get_item.cpp` and `put_item.cpp`. Each .cpp file contains a `main()` function as an entrypoint to a standalone executable. The project executables are generated in a folder designated by your build system, and there is one executable file corresponding to each example source file. The file name of the executable follows the conventions of the platform such as `{name}.exe` or just `{name}` and any custom prefix `CMakeLists.txt` applies such as `run_`.

To run an example functionality

1. Download the desired code example from the AWS Code Examples Repository on GitHub.
2. Open a .cpp file to explore its `main()` function and any called methods.

3. Build the project, as demonstrated with the starter example in Getting started using the AWS SDK for C++. Note that building the project generates each executable for every source file in the project.
4. Run the executable for the selected functionality.
   - In a command prompt, run that program using the executable based on the name of the `*.cpp` file.
   - If you are working within an IDE, choose the `.cpp` file of the functionality you want to demonstrate and select it as the startup option (or startup object).

Unit tests

Tests for examples are written using the GoogleTest framework. To learn more, see GoogleTest Primer on the GoogleTest website.

The unit tests for each example are in a `tests` subfolder containing its own `CMakeLists.txt` file. For each example source file there is a corresponding test file named `gtest_`*`<source file>`*. The test executable for the subfolder is named *`<AWS service>`*`_gtests`.

CMakeLists.txt file

The folder for each service contains a file named `CMakeLists.txt` file. Many of these files contain a construct similar to the following:

```
foreach(EXAMPLE IN LISTS EXAMPLES)
        add_executable(${EXAMPLE} ${EXAMPLE}.cpp)
        target_link_libraries(${EXAMPLE} aws-cpp-sdk-email aws-cpp-sdk-core)
endforeach()
```

For each .cpp file in the folder, the `CMakeLists.txt` file builds an executable (cmake: `add_executable`) with a name based on the name of the source code file without the file extension.

Building and Debugging Code Examples in Visual Studio

Building and running the Amazon S3 code example

1. Obtain the Amazon S3 example source code. This procedure uses the Amazon S3 code examples using the AWS SDK for C++ code example to get up and running using Visual Studio.

2. In Windows Explorer, navigate to the `s3` folder (e.g. `\aws-doc-sdk-examples\cpp\example_code\s3`).
3. Right click on the `s3` example folder and choose **Open with Visual Studio**. Visual Studio for CMake projects don't have a 'project' file, rather, it is the whole folder.
4. In the **Configuration Selector** dropdown in the top menu of Visual Studio, ensure that the selected configuration matches the build type that you selected when building the SDK from source. E.g. a **Debug** configuration should be selected if you built from source using debug (`-DCMAKE_BUILD_TYPE=Debug` in the CMake command line from the SDK installation instructions).
5. Open file `CMakeLists.txt`.
6. Click **Save**. Every time you click **Save** on the `CMakeLists.txt` file, Visual Studio refreshes the CMake-generated files. If you have your **Output** tab displayed, you can see the resulting log messages from this generation.

   - There is a drop-down box within the **Output** tab that says: "**Show output from:**" and **CMake** should be the option selected by default.
   - Last message output should say "**CMake generation finished.**"
   - If last message is not this, then the CMake file has issues. Do not proceed to further steps until this is resolved. See Troubleshooting AWS SDK for C++ build issues.
   - Note that the CMake cache is used by CMake for speed. If you are working through CMake issues, you want to ensure a 'clean slate' so that the error messages you are given is actually reflective of your most recent changes. In the Solution Explorer, right-click on `CMakeLists.txt` and choose **CMake Cache**, then choose **Delete Cache**. Do this frequently when working progressively through CMake issues.
7. To build and run examples from within Visual Studio, Visual Studio places executables in a different folder structure than the command line. To run the code, the SDK executables must be copied to the right place. Find the "`TODO`" line of the CMakeLists file (~line 40) and choose the one commented for use in Visual Studio. Visual Studio does not use a subfolder dedicated to the build type so this is not included. Switch the commented-out line in the `CMakeLists.txt` file for Visual Studio use.
8. Delete the CMake cache (as described above), click in the `CMakeLists.txt` file to select/activate the tab, and choose **Save** on the `CMakeLists.txt` file again to initiate the CMake build files generation.
9. Open the source file of the 'program' you wish to run.

- For example, open `list_buckets.cpp`.
- The Amazon S3 example folder is coded so that each showcased 'feature' of Amazon S3 is demonstrated in a dedicated executable for just that feature. E.g. `list_buckets.cpp` will become an executable that only demonstrates the listing of buckets.

10. In the top menu, choose **Build**, then choose **Build All**.

    - The **Output** tab's **Show output from** should reflect the selection of **Build**, and show all the building and linking messages.
    - The last output should be: "**Build All succeeded.**"
    - Now executables for each of the individual source files are generated. You can confirm this by looking in the build output directory (e.g. `\aws-doc-sdk-examples\cpp\example_code\s3\out\build\x64-Debug`).
    - Note that the executables are prefixed with "run_" because the `CMakeLists.txt` file dictates this.

11. In the top menu, there is a **green arrow** and a **drop-down selector** for **Debug Target**. Choose `run_list_buckets.exe`.
12. Click the **green arrow run button** to **Select Startup Item**.
13. A Visual Studio Debug Console window will open and display the output of the code.
14. Press a key to close the window, or manually close the window, to terminate the program. You can also set breakpoints in the code and when you click run again the breakpoints will be hit.

Getting started troubleshooting runtime errors in the AWS SDK for C++

As you learn to develop applications with the AWS SDK for C++, it's also valuable to get comfortable in using both the AWS Management Console and the AWS CLI. These tools can be used interchangeably for various troubleshooting and diagnostics when runtime errors are encountered.

The following tutorial shows you an example of these troubleshooting and diagnostics tasks. It focuses on the `Access denied` error, which can be encountered for several different reasons. The tutorial shows an example of how you might determine the actual cause of the error. It focuses on two of the possible causes: incorrect permissions for the current user and a resource that isn't available to the current user.

To get the project source and executables

1. Download the Amazon S3 code example folder from AWS Code Examples Repository on GitHub.
2. Open `delete_bucket.cpp` and notice that there are two methods: `main()` and `DeleteBucket()`. `DeleteBucket()` uses the SDK to delete the bucket.
3. Build the Amazon S3 example, using the same build steps explained in Getting started using the AWS SDK for C++. The build process generates an executable for each source file.
4. Open a command prompt to the folder where your build system generated your build executables. Run the executable `run_create_bucket` (your actual executable filename will differ based on your operating system). This creates a bucket in your account (so that you have one to delete).
5. In the command prompt, run the executable `run_delete_bucket`. This example expects a parameter of the name of the bucket that you want to delete. Provide an incorrect bucket name; intentionally create a typo in this bucket name for now, so that we can explore troubleshooting.
6. Confirm that you get an `Access Denied` error message. *Getting an `Access Denied` error message leads you to question whether you created a user with full permissions for Amazon S3, which you'll verify next.*

To install the AWS CLI and find the username that is making calls to AWS

1. To install the latest AWS CLI to your development machine, see Installing the AWS CLI in the *AWS Command Line Interface User Guide*.
2. To verify the AWS CLI is working, open a command prompt and run command `aws -\-version`

```
$ aws -\-
version
aws-cli/2.1.29 Python/3.8.8 Windows/10 exe/AMD64 prompt/off
```

3. To obtain the username that is actually making the calls to AWS, run the AWS CLI command `aws sts get-caller-identity`. In the following example output, that username is *userX*

```
$ aws sts get-caller-
identity
{
```

```
    "UserId": "A12BCD34E5FGHI6JKLM",
    "Account": "1234567890987",
    "Arn": "arn:aws:iam::1234567890987:user/userX"
}
```

There are many ways to specify credentials, but if you followed the approach in Authenticating with AWS using AWS SDK for C++ then this username comes from your AWS shared credentials file. During that procedure you granted your user **AmazonS3FullAccess** permissions.

> **Note**
>
> Generally, most AWS CLI commands follow the syntax structure of:
>
> ```
> $ aws <command> <subcommand> [options and parameters]
> ```
>
> where *command* is the service, and *subcommand* is the method being called on that service. For more details, see Command structure in the AWS CLI in the *AWS Command Line Interface User Guide*.

To verify whether a user has permission to delete a bucket

1. Open the AWS Management Console and log in. For more details, see Getting Started with the AWS Management Console.
2. In the main navigation bar, for **Search for services...**, enter **IAM** and select the IAM service from the results.
3. From the **Dashboard** sidebar, or under **IAM Resources**, select **Users**.
4. From the table of users available for your account, select the username obtained in the preceding procedure.
5. Choose the **Permissions** tab of the **Summary** page, under the **Policy name** table, select **AmazonS3FullAccess**.
6. Look at the **Policy summary** and the JSON data. Verify that this user has full rights for the Amazon S3 service.

```
            "Effect": "Allow",
            "Action": "s3:*",
            "Resource": "*"
```

This process of elimination is common in ruling *out* where the problem might be. In this case, you've verified that the user does have the correct permissions, so the problem must be something else. That is, since you have the correct permissions to access your buckets, the `Access Denied` error may mean that you are trying to access a bucket that isn't yours. When troubleshooting, you'd next review the bucket name that was provided to the program, and notice that a bucket with that name doesn't exist in your account, and thus, you cannot 'access' it.

To update the code example so it runs successfully

1. Back in `delete_bucket.cpp`'s `main()` function, change the Region, using the enum, to the Region of your account. To find your Region of your account, log into the AWS Management Console, and locate the Region in the upper right-hand corner. Also in `main()`, change the bucket name to a bucket that **does** exist in your account. There are several ways to find your current bucket names:
   - You can use the `run_list_buckets` executable that also exists in this code example's folder to programatically get the names of your buckets.
   - Alternatively, you can also use the following AWS CLI command to list your Amazon S3 buckets.

     ```
     $ aws s3
      ls
     2022-01-05 14:27:48 amzn-s3-demo-bucket
     ```

   - Alternatively, you can also use the AWS Management Console. In the main navigation bar, in **Search for services...**, enter **S3**. The Buckets page lists your account's buckets.
2. Rebuild the code and run the updated executable `run_delete_bucket`.
3. Using either the AWS Management Console or the AWS CLI, verify that the Amazon S3 bucket that you created earlier has been deleted.

Guided examples for calling AWS services using the AWS SDK for C++

If you are new to AWS or the AWS code examples, we recommend you start with Getting started on code examples.

Source code that shows how to work with AWS services using the AWS SDK for C++ is available in the Code examples chapter of this guide or directly in the AWS Code Examples Repository on GitHub.

This section selects several AWS services and guides you through the examples using them. The following guided examples are a subset of what is available on Github.

Service examples with additional explanation (see AWS Code Examples Repository for full list)

Service	Summary of what the service provides to your program
Amazon CloudWatch	Collects and monitors metrics for AWS resources you are using
Amazon DynamoDB	A NoSQL database service
Amazon Elastic Compute Cloud (Amazon EC2)	Secure, resizable compute capacity
Amazon Simple Storage Service (Amazon S3)	Data storage and retrieval (objects into buckets)
Amazon Simple Queue Service (Amazon SQS)	Message queuing service to send, store, and receive messages between software components

There are also examples that show how to use Asynchronous methods.

To propose a new code example to the AWS documentation team, see Contributing guidelines on GitHub to create a new request. The team prefers to create code examples that show broad scenarios rather than individual API calls.

Using the Code Examples on Windows

If you are building the examples on Windows with SDK version 1.9, see Troubleshooting AWS SDK for C++ build issues.

Amazon CloudWatch examples using the AWS SDK for C++

Amazon CloudWatch (CloudWatch) is a monitoring service for AWS cloud resources and the applications you run on AWS. You can use the following examples to program CloudWatch using the AWS SDK for C++.

Amazon CloudWatch monitors your AWS resources and the applications you run on AWS in real time. You can use CloudWatch to collect and track metrics, which are variables you can measure for your resources and applications. CloudWatch alarms send notifications or automatically make changes to the resources you are monitoring based on rules that you define.

For more information about CloudWatch, see the Amazon CloudWatch User Guide.

> **Note**
>
> Only the code that is necessary to demonstrate certain techniques is supplied in this Guide, but the complete example code is available on GitHub. On GitHub you can download a single source file or you can clone the repository locally to get, build, and run all examples.

Topics

- Getting Metrics from CloudWatch
- Publishing Custom Metric Data
- Working with CloudWatch Alarms
- Using Alarm Actions in CloudWatch
- Sending Events to CloudWatch

Getting Metrics from CloudWatch

Prerequisites

Before you begin, we recommend you read Getting started using the AWS SDK for C++.

Download the example code and build the solution as described in Getting started on code examples.

To run the examples, the user profile your code uses to make the requests must have proper permissions in AWS (for the service and the action). For more information, see Providing AWS credentials.

Listing Metrics

To list CloudWatch metrics, create a ListMetricsRequest and call the CloudWatchClient's `ListMetrics` function. You can use the `ListMetricsRequest` to filter the returned metrics by namespace, metric name, or dimensions.

> **Note**
>
> A list of metrics and dimensions that are posted by AWS services can be found within the Amazon CloudWatch Metrics and Dimensions Reference in the Amazon CloudWatch User Guide.

Includes

```
#include <aws/core/Aws.h>
#include <aws/monitoring/CloudWatchClient.h>
#include <aws/monitoring/model/ListMetricsRequest.h>
#include <aws/monitoring/model/ListMetricsResult.h>
#include <iomanip>
#include <iostream>
```

Code

```
        Aws::CloudWatch::CloudWatchClient cw;
        Aws::CloudWatch::Model::ListMetricsRequest request;

        if (argc > 1)
        {
            request.SetMetricName(argv[1]);
        }

        if (argc > 2)
        {
            request.SetNamespace(argv[2]);
        }

        bool done = false;
        bool header = false;
        while (!done)
        {
```

```
            auto outcome = cw.ListMetrics(request);
            if (!outcome.IsSuccess())
            {
                std::cout << "Failed to list CloudWatch metrics:" <<
                    outcome.GetError().GetMessage() << std::endl;
                break;
            }

            if (!header)
            {
                std::cout << std::left << std::setw(48) << "MetricName" <<
                    std::setw(32) << "Namespace" << "DimensionNameValuePairs" <<
                    std::endl;
                header = true;
            }

            const auto &metrics = outcome.GetResult().GetMetrics();
            for (const auto &metric : metrics)
            {
                std::cout << std::left << std::setw(48) <<
                    metric.GetMetricName() << std::setw(32) <<
                    metric.GetNamespace();
                const auto &dimensions = metric.GetDimensions();
                for (auto iter = dimensions.cbegin();
                    iter != dimensions.cend(); ++iter)
                {
                    const auto &dimkv = *iter;
                    std::cout << dimkv.GetName() << " = " << dimkv.GetValue();
                    if (iter + 1 != dimensions.cend())
                    {
                        std::cout << ", ";
                    }
                }
                std::cout << std::endl;
            }

            const auto &next_token = outcome.GetResult().GetNextToken();
            request.SetNextToken(next_token);
            done = next_token.empty();
        }
```

The metrics are returned in a ListMetricsResult by calling its `GetMetrics` function. The results may be *paged*. To retrieve the next batch of results, call `SetNextToken` on the original request object

with the return value of the `ListMetricsResult` object's `GetNextToken` function, and pass the modified request object back to another call to `ListMetrics`.

See the complete example.

More Information

- ListMetrics in the Amazon CloudWatch API Reference.

Publishing Custom Metric Data

A number of AWS services publish their own metrics in namespaces beginning with `AWS/` You can also publish custom metric data using your own namespace (as long as it doesn't begin with `AWS/`).

Prerequisites

Before you begin, we recommend you read Getting started using the AWS SDK for C++.

Download the example code and build the solution as described in Getting started on code examples.

To run the examples, the user profile your code uses to make the requests must have proper permissions in AWS (for the service and the action). For more information, see Providing AWS credentials.

Publish Custom Metric Data

To publish your own metric data, call the CloudWatchClient's `PutMetricData` function with a PutMetricDataRequest. The `PutMetricDataRequest` must include the custom namespace to use for the data, and information about the data point itself in a MetricDatum object.

> **Note**
>
> You cannot specify a namespace that begins with `AWS/`. Namespaces that begin with `AWS/` are reserved for use by Amazon Web Services products.

Includes

```
#include <aws/core/Aws.h>
```

```
#include <aws/monitoring/CloudWatchClient.h>
#include <aws/monitoring/model/PutMetricDataRequest.h>
#include <iostream>
```

Code

```
        Aws::CloudWatch::CloudWatchClient cw;

        Aws::CloudWatch::Model::Dimension dimension;
        dimension.SetName("UNIQUE_PAGES");
        dimension.SetValue("URLS");

        Aws::CloudWatch::Model::MetricDatum datum;
        datum.SetMetricName("PAGES_VISITED");
        datum.SetUnit(Aws::CloudWatch::Model::StandardUnit::None);
        datum.SetValue(data_point);
        datum.AddDimensions(dimension);

        Aws::CloudWatch::Model::PutMetricDataRequest request;
        request.SetNamespace("SITE/TRAFFIC");
        request.AddMetricData(datum);

        auto outcome = cw.PutMetricData(request);
        if (!outcome.IsSuccess())
        {
            std::cout << "Failed to put sample metric data:" <<
                outcome.GetError().GetMessage() << std::endl;
        }
        else
        {
            std::cout << "Successfully put sample metric data" << std::endl;
        }
```

See the complete example.

More Information

- Using Amazon CloudWatch Metrics in the Amazon CloudWatch User Guide.
- AWS Namespaces in the Amazon CloudWatch User Guide.
- PutMetricData in the Amazon CloudWatch API Reference.

Working with CloudWatch Alarms

Prerequisites

Before you begin, we recommend you read Getting started using the AWS SDK for C++.

Download the example code and build the solution as described in Getting started on code examples.

To run the examples, the user profile your code uses to make the requests must have proper permissions in AWS (for the service and the action). For more information, see Providing AWS credentials.

Create an Alarm

To create an alarm based on a CloudWatch metric, call the CloudWatchClient's `PutMetricAlarm` function with a PutMetricAlarmRequest filled with the alarm conditions.

Includes

```
#include <aws/core/Aws.h>
#include <aws/monitoring/CloudWatchClient.h>
#include <aws/monitoring/model/PutMetricAlarmRequest.h>
#include <iostream>
```

Code

```
        Aws::CloudWatch::CloudWatchClient cw;
        Aws::CloudWatch::Model::PutMetricAlarmRequest request;
        request.SetAlarmName(alarm_name);
        request.SetComparisonOperator(
            Aws::CloudWatch::Model::ComparisonOperator::GreaterThanThreshold);
        request.SetEvaluationPeriods(1);
        request.SetMetricName("CPUUtilization");
        request.SetNamespace("AWS/EC2");
        request.SetPeriod(60);
        request.SetStatistic(Aws::CloudWatch::Model::Statistic::Average);
        request.SetThreshold(70.0);
        request.SetActionsEnabled(false);
        request.SetAlarmDescription("Alarm when server CPU exceeds 70%");
        request.SetUnit(Aws::CloudWatch::Model::StandardUnit::Seconds);
```

```
        Aws::CloudWatch::Model::Dimension dimension;
        dimension.SetName("InstanceId");
        dimension.SetValue(instanceId);

        request.AddDimensions(dimension);

        auto outcome = cw.PutMetricAlarm(request);
        if (!outcome.IsSuccess())
        {
            std::cout << "Failed to create CloudWatch alarm:" <<
                outcome.GetError().GetMessage() << std::endl;
        }
        else
        {
            std::cout << "Successfully created CloudWatch alarm " << alarm_name
                << std::endl;
        }
```

See the complete example.

List Alarms

To list the CloudWatch alarms that you have created, call the CloudWatchClient's `DescribeAlarms` function with a DescribeAlarmsRequest that you can use to set options for the result.

Includes

```
#include <aws/core/Aws.h>
#include <aws/monitoring/CloudWatchClient.h>
#include <aws/monitoring/model/DescribeAlarmsRequest.h>
#include <aws/monitoring/model/DescribeAlarmsResult.h>
#include <iomanip>
#include <iostream>
```

Code

```
        Aws::CloudWatch::CloudWatchClient cw;
        Aws::CloudWatch::Model::DescribeAlarmsRequest request;
        request.SetMaxRecords(1);
```

```
        bool done = false;
        bool header = false;
        while (!done)
        {
            auto outcome = cw.DescribeAlarms(request);
            if (!outcome.IsSuccess())
            {
                std::cout << "Failed to describe CloudWatch alarms:" <<
                    outcome.GetError().GetMessage() << std::endl;
                break;
            }

            if (!header)
            {
                std::cout << std::left <<
                    std::setw(32) << "Name" <<
                    std::setw(64) << "Arn" <<
                    std::setw(64) << "Description" <<
                    std::setw(20) << "LastUpdated" <<
                    std::endl;
                header = true;
            }

            const auto &alarms = outcome.GetResult().GetMetricAlarms();
            for (const auto &alarm : alarms)
            {
                std::cout << std::left <<
                    std::setw(32) << alarm.GetAlarmName() <<
                    std::setw(64) << alarm.GetAlarmArn() <<
                    std::setw(64) << alarm.GetAlarmDescription() <<
                    std::setw(20) <<
                    alarm.GetAlarmConfigurationUpdatedTimestamp().ToGmtString(
                        SIMPLE_DATE_FORMAT_STR) <<
                    std::endl;
            }

            const auto &next_token = outcome.GetResult().GetNextToken();
            request.SetNextToken(next_token);
            done = next_token.empty();
        }
```

The list of alarms can be obtained by calling `getMetricAlarms` on the DescribeAlarmsResult that is returned by `DescribeAlarms`.

The results may be *paged*. To retrieve the next batch of results, call `SetNextToken` on the original request object with the return value of the `DescribeAlarmsResult` object's `GetNextToken` function, and pass the modified request object back to another call to `DescribeAlarms`.

> **Note**
>
> You can also retrieve alarms for a specific metric by using the CloudWatchClient's `DescribeAlarmsForMetric` function. Its use is similar to `DescribeAlarms`.

See the complete example.

Delete Alarms

To delete CloudWatch alarms, call the CloudWatchClient's `DeleteAlarms` function with a DeleteAlarmsRequest containing one or more names of alarms that you want to delete.

Includes

```
#include <aws/core/Aws.h>
#include <aws/monitoring/CloudWatchClient.h>
#include <aws/monitoring/model/DeleteAlarmsRequest.h>
#include <iostream>
```

Code

```
        Aws::CloudWatch::CloudWatchClient cw;
        Aws::CloudWatch::Model::DeleteAlarmsRequest request;
        request.AddAlarmNames(alarm_name);

        auto outcome = cw.DeleteAlarms(request);
        if (!outcome.IsSuccess())
        {
            std::cout << "Failed to delete CloudWatch alarm:" <<
                outcome.GetError().GetMessage() << std::endl;
        }
        else
        {
            std::cout << "Successfully deleted CloudWatch alarm " << alarm_name
                << std::endl;
        }
```

See the complete example.

More Information

- Creating Amazon CloudWatch Alarms in the Amazon CloudWatch User Guide
- PutMetricAlarm in the Amazon CloudWatch API Reference
- DescribeAlarms in the Amazon CloudWatch API Reference
- DeleteAlarms in the Amazon CloudWatch API Reference

Using Alarm Actions in CloudWatch

Using CloudWatch alarm actions, you can create alarms that perform actions such as automatically stopping, terminating, rebooting, or recovering Amazon EC2 instances.

Alarm actions can be added to an alarm by using the PutMetricAlarmRequest's `SetAlarmActions` function when creating an alarm.

Prerequisites

Before you begin, we recommend you read Getting started using the AWS SDK for C++.

Download the example code and build the solution as described in Getting started on code examples.

To run the examples, the user profile your code uses to make the requests must have proper permissions in AWS (for the service and the action). For more information, see Providing AWS credentials.

Enable Alarm Actions

To enable alarm actions for a CloudWatch alarm, call the CloudWatchClient's `EnableAlarmActions` with a EnableAlarmActionsRequest containing one or more names of alarms whose actions you want to enable.

Includes

```
#include <aws/core/Aws.h>
#include <aws/monitoring/CloudWatchClient.h>
#include <aws/monitoring/model/EnableAlarmActionsRequest.h>
#include <aws/monitoring/model/PutMetricAlarmRequest.h>
```

```
#include <iostream>
```

Code

```
    Aws::CloudWatch::CloudWatchClient cw;
    Aws::CloudWatch::Model::PutMetricAlarmRequest request;
    request.SetAlarmName(alarm_name);
    request.SetComparisonOperator(
        Aws::CloudWatch::Model::ComparisonOperator::GreaterThanThreshold);
    request.SetEvaluationPeriods(1);
    request.SetMetricName("CPUUtilization");
    request.SetNamespace("AWS/EC2");
    request.SetPeriod(60);
    request.SetStatistic(Aws::CloudWatch::Model::Statistic::Average);
    request.SetThreshold(70.0);
    request.SetActionsEnabled(false);
    request.SetAlarmDescription("Alarm when server CPU exceeds 70%");
    request.SetUnit(Aws::CloudWatch::Model::StandardUnit::Seconds);
    request.AddAlarmActions(actionArn);

    Aws::CloudWatch::Model::Dimension dimension;
    dimension.SetName("InstanceId");
    dimension.SetValue(instanceId);
    request.AddDimensions(dimension);

    auto outcome = cw.PutMetricAlarm(request);
    if (!outcome.IsSuccess())
    {
        std::cout << "Failed to create CloudWatch alarm:" <<
            outcome.GetError().GetMessage() << std::endl;
        return;
    }

    Aws::CloudWatch::Model::EnableAlarmActionsRequest enable_request;
    enable_request.AddAlarmNames(alarm_name);

    auto enable_outcome = cw.EnableAlarmActions(enable_request);
    if (!enable_outcome.IsSuccess())
    {
        std::cout << "Failed to enable alarm actions:" <<
            enable_outcome.GetError().GetMessage() << std::endl;
        return;
    }
```

```
    std::cout << "Successfully created alarm " << alarm_name <<
        " and enabled actions on it." << std::endl;
```

See the complete example.

Disable Alarm Actions

To disable alarm actions for a CloudWatch alarm, call the CloudWatchClient's `DisableAlarmActions` with a DisableAlarmActionsRequest containing one or more names of alarms whose actions you want to disable.

Includes

```
#include <aws/core/Aws.h>
#include <aws/monitoring/CloudWatchClient.h>
#include <aws/monitoring/model/DisableAlarmActionsRequest.h>
#include <iostream>
```

Code

```
        Aws::CloudWatch::CloudWatchClient cw;

        Aws::CloudWatch::Model::DisableAlarmActionsRequest disableAlarmActionsRequest;
        disableAlarmActionsRequest.AddAlarmNames(alarm_name);

        auto disableAlarmActionsOutcome =
cw.DisableAlarmActions(disableAlarmActionsRequest);
        if (!disableAlarmActionsOutcome.IsSuccess())
        {
            std::cout << "Failed to disable actions for alarm " << alarm_name <<
                ": " << disableAlarmActionsOutcome.GetError().GetMessage() <<
                std::endl;
        }
        else
        {
            std::cout << "Successfully disabled actions for alarm " <<
                alarm_name << std::endl;
        }
```

See the complete example.

More Information

- Create Alarms to Stop, Terminate, Reboot, or Recover an Instance in the Amazon CloudWatch User Guide
- PutMetricAlarm in the Amazon CloudWatch API Reference
- EnableAlarmActions in the Amazon CloudWatch API Reference
- DisableAlarmActions in the Amazon CloudWatch API Reference

Sending Events to CloudWatch

CloudWatch Events delivers a near real-time stream of system events that describe changes in AWS resources to Amazon EC2 instances, Lambda functions, Kinesis streams, Amazon ECS tasks, Step Functions state machines, Amazon SNS topics, Amazon SQS queues, or built-in targets. You can match events and route them to one or more target functions or streams by using simple rules.

> **Note**
>
> These code snippets assume that you understand the material in Getting Started Using the AWS SDK for C++ and have configured default AWS credentials using the information in Providing AWS Credentials.

Add Events

To add custom CloudWatch events, call the CloudWatchEventsClient's `PutEvents` function with a PutEventsRequest object that contains one or more PutEventsRequestEntry objects that provide details about each event. You can specify several parameters for the entry such as the source and type of the event, resources associated with the event, and so on.

> **Note**
>
> You can specify a maximum of 10 events per call to `putEvents`.

Includes

```
#include <aws/core/Aws.h>
```

```
#include <aws/events/EventBridgeClient.h>
#include <aws/events/model/PutEventsRequest.h>
#include <aws/events/model/PutEventsResult.h>
#include <aws/core/utils/Outcome.h>
#include <iostream>
```

Code

```
        Aws::CloudWatchEvents::EventBridgeClient cwe;

        Aws::CloudWatchEvents::Model::PutEventsRequestEntry event_entry;
        event_entry.SetDetail(MakeDetails(event_key, event_value));
        event_entry.SetDetailType("sampleSubmitted");
        event_entry.AddResources(resource_arn);
        event_entry.SetSource("aws-sdk-cpp-cloudwatch-example");

        Aws::CloudWatchEvents::Model::PutEventsRequest request;
        request.AddEntries(event_entry);

        auto outcome = cwe.PutEvents(request);
        if (!outcome.IsSuccess())
        {
            std::cout << "Failed to post CloudWatch event: " <<
                outcome.GetError().GetMessage() << std::endl;
        }
        else
        {
            std::cout << "Successfully posted CloudWatch event" << std::endl;
        }
```

Add Rules

To create or update a rule, call the CloudWatchEventsClient's `PutRule` function with a PutRuleRequest with the name of the rule and optional parameters such as the event pattern, IAM role to associate with the rule, and a scheduling expression that describes how often the rule is run.

Includes

```
#include <aws/core/Aws.h>
#include <aws/events/EventBridgeClient.h>
#include <aws/events/model/PutRuleRequest.h>
#include <aws/events/model/PutRuleResult.h>
```

```
#include <aws/core/utils/Outcome.h>
#include <iostream>
```

Code

```
        Aws::CloudWatchEvents::EventBridgeClient cwe;
        Aws::CloudWatchEvents::Model::PutRuleRequest request;
        request.SetName(rule_name);
        request.SetRoleArn(role_arn);
        request.SetScheduleExpression("rate(5 minutes)");
        request.SetState(Aws::CloudWatchEvents::Model::RuleState::ENABLED);

        auto outcome = cwe.PutRule(request);
        if (!outcome.IsSuccess())
        {
            std::cout << "Failed to create CloudWatch events rule " <<
                rule_name << ": " << outcome.GetError().GetMessage() <<
                std::endl;
        }
        else
        {
            std::cout << "Successfully created CloudWatch events rule " <<
                rule_name << " with resulting Arn " <<
                outcome.GetResult().GetRuleArn() << std::endl;
        }
```

Add Targets

Targets are the resources that are invoked when a rule is triggered. Example targets include Amazon EC2 instances, Lambda functions, Kinesis streams, Amazon ECS tasks, Step Functions state machines, and built-in targets.

To add a target to a rule, call the CloudWatchEventsClient's `PutTargets` function with a PutTargetsRequest containing the rule to update and a list of targets to add to the rule.

Includes

```
#include <aws/core/Aws.h>
#include <aws/events/EventBridgeClient.h>
#include <aws/events/model/PutTargetsRequest.h>
#include <aws/events/model/PutTargetsResult.h>
#include <aws/core/utils/Outcome.h>
```

```
#include <iostream>
```

Code

```
        Aws::CloudWatchEvents::EventBridgeClient cwe;

        Aws::CloudWatchEvents::Model::Target target;
        target.SetArn(lambda_arn);
        target.SetId(target_id);

        Aws::CloudWatchEvents::Model::PutTargetsRequest request;
        request.SetRule(rule_name);
        request.AddTargets(target);

        auto putTargetsOutcome = cwe.PutTargets(request);
        if (!putTargetsOutcome.IsSuccess())
        {
            std::cout << "Failed to create CloudWatch events target for rule "
                << rule_name << ": " <<
                putTargetsOutcome.GetError().GetMessage() << std::endl;
        }
        else
        {
            std::cout <<
                "Successfully created CloudWatch events target for rule "
                << rule_name << std::endl;
        }
```

See the complete example.

More Information

- Adding Events with PutEvents in the Amazon CloudWatch Events User Guide
- Schedule Expressions for Rules in the Amazon CloudWatch Events User Guide
- Event Types for CloudWatch Events in the Amazon CloudWatch Events User Guide
- Events and Event Patterns in the Amazon CloudWatch Events User Guide
- PutEvents in the Amazon CloudWatch Events API Reference
- PutTargets in the Amazon CloudWatch Events API Reference
- PutRule in the Amazon CloudWatch Events API Reference

Amazon DynamoDB examples using the AWS SDK for C++

Amazon DynamoDB is a fully managed NoSQL database service that provides fast and predictable performance with seamless scalability. The following examples show how you can program Amazon DynamoDB using the AWS SDK for C++.

> **Note**
>
> Only the code that is necessary to demonstrate certain techniques is supplied in this Guide, but the complete example code is available on GitHub. On GitHub you can download a single source file or you can clone the repository locally to get, build, and run all examples.

Topics

- Working with Tables in DynamoDB
- Working with Items in DynamoDB

Working with Tables in DynamoDB

Tables are the containers for all items in a DynamoDB database. Before you can add or remove data from DynamoDB, you must create a table.

For each table, you must define:

- A table *name* that is unique for your AWS account and AWS Region.
- A *primary key* for which every value must be unique. No two items in your table can have the same primary key value.

  A primary key can be *simple*, consisting of a single partition (HASH) key, or *composite*, consisting of a partition and a sort (RANGE) key.

  Each key value has an associated *data type*, enumerated by the ScalarAttributeType class. The key value can be binary (B), numeric (N), or a string (S). For more information, see Naming Rules and Data Types in the Amazon DynamoDB Developer Guide.
- *Provisioned throughput* values that define the number of reserved read/write capacity units for the table.

> **Note**
>
> Amazon DynamoDB pricing is based on the provisioned throughput values that you set on your tables, so reserve only as much capacity as you think you'll need for your table. Provisioned throughput for a table can be modified at any time, so you can adjust capacity if your needs change.

Create a Table

Use the DynamoDB client `CreateTable` method to create a new DynamoDB table. You need to construct table attributes and a table schema, both of which are used to identify the primary key of your table. You must also supply initial provisioned throughput values and a table name. `CreateTable` is an asynchronous operation. `GetTableStatus` will return CREATING until the table is ACTIVE and ready for use.

Create a Table with a Simple Primary Key

This code creates a table with a simple primary key ("Name").

Includes

```
#include <aws/core/Aws.h>
#include <aws/dynamodb/DynamoDBClient.h>
#include <aws/dynamodb/model/AttributeDefinition.h>
#include <aws/dynamodb/model/CreateTableRequest.h>
#include <aws/dynamodb/model/KeySchemaElement.h>
#include <aws/dynamodb/model/ProvisionedThroughput.h>
#include <aws/dynamodb/model/ScalarAttributeType.h>
#include <iostream>
```

Code

```
//! Create an Amazon DynamoDB table.
/*!
  \sa createTable()
  \param tableName: Name for the DynamoDB table.
  \param primaryKey: Primary key for the DynamoDB table.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
```

```
bool AwsDoc::DynamoDB::createTable(const Aws::String &tableName,
                                   const Aws::String &primaryKey,
                                   const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    std::cout << "Creating table " << tableName <<
              " with a simple primary key: \"" << primaryKey << "\"." << std::endl;

    Aws::DynamoDB::Model::CreateTableRequest request;

    Aws::DynamoDB::Model::AttributeDefinition hashKey;
    hashKey.SetAttributeName(primaryKey);
    hashKey.SetAttributeType(Aws::DynamoDB::Model::ScalarAttributeType::S);
    request.AddAttributeDefinitions(hashKey);

    Aws::DynamoDB::Model::KeySchemaElement keySchemaElement;
    keySchemaElement.WithAttributeName(primaryKey).WithKeyType(
            Aws::DynamoDB::Model::KeyType::HASH);
    request.AddKeySchema(keySchemaElement);

    Aws::DynamoDB::Model::ProvisionedThroughput throughput;
    throughput.WithReadCapacityUnits(5).WithWriteCapacityUnits(5);
    request.SetProvisionedThroughput(throughput);
    request.SetTableName(tableName);

    const Aws::DynamoDB::Model::CreateTableOutcome &outcome = dynamoClient.CreateTable(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Table \""
                  << outcome.GetResult().GetTableDescription().GetTableName() <<
                  " created!" << std::endl;
    }
    else {
        std::cerr << "Failed to create table: " << outcome.GetError().GetMessage()
                  << std::endl;
        return false;
    }

    return waitTableActive(tableName, dynamoClient);
}
```

See the complete example.

Create a Table with a Composite Primary Key

Add another AttributeDefinition and KeySchemaElement to CreateTableRequest.

Includes

```
#include <aws/core/Aws.h>
#include <aws/dynamodb/DynamoDBClient.h>
#include <aws/dynamodb/model/AttributeDefinition.h>
#include <aws/dynamodb/model/CreateTableRequest.h>
#include <aws/dynamodb/model/KeySchemaElement.h>
#include <aws/dynamodb/model/ProvisionedThroughput.h>
#include <aws/dynamodb/model/ScalarAttributeType.h>
#include <iostream>
```

Code

```
//! Create an Amazon DynamoDB table with a composite key.
/*!
  \sa createTableWithCompositeKey()
  \param tableName: Name for the DynamoDB table.
  \param partitionKey: Name for the partition (hash) key.
  \param sortKey: Name for the sort (range) key.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::DynamoDB::createTableWithCompositeKey(const Aws::String &tableName,
                                                   const Aws::String &partitionKey,
                                                   const Aws::String &sortKey,
                                                   const
 Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    std::cout << "Creating table " << tableName <<
              " with a composite primary key:\n" \
            "* " << partitionKey << " - partition key\n" \
            "* " << sortKey << " - sort key\n";

    Aws::DynamoDB::Model::CreateTableRequest request;

    Aws::DynamoDB::Model::AttributeDefinition hashKey1, hashKey2;
    hashKey1.WithAttributeName(partitionKey).WithAttributeType(
            Aws::DynamoDB::Model::ScalarAttributeType::S);
```

```
    request.AddAttributeDefinitions(hashKey1);
    hashKey2.WithAttributeName(sortKey).WithAttributeType(
            Aws::DynamoDB::Model::ScalarAttributeType::S);
    request.AddAttributeDefinitions(hashKey2);

    Aws::DynamoDB::Model::KeySchemaElement keySchemaElement1, keySchemaElement2;
    keySchemaElement1.WithAttributeName(partitionKey).WithKeyType(
            Aws::DynamoDB::Model::KeyType::HASH);
    request.AddKeySchema(keySchemaElement1);
    keySchemaElement2.WithAttributeName(sortKey).WithKeyType(
            Aws::DynamoDB::Model::KeyType::RANGE);
    request.AddKeySchema(keySchemaElement2);

    Aws::DynamoDB::Model::ProvisionedThroughput throughput;
    throughput.WithReadCapacityUnits(5).WithWriteCapacityUnits(5);
    request.SetProvisionedThroughput(throughput);

    request.SetTableName(tableName);

    const Aws::DynamoDB::Model::CreateTableOutcome &outcome = dynamoClient.CreateTable(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Table \""
                  << outcome.GetResult().GetTableDescription().GetTableName() <<
                  "\" was created!" << std::endl;
    }
    else {
        std::cerr << "Failed to create table:" << outcome.GetError().GetMessage()
                  << std::endl;
        return false;
    }

    return waitTableActive(tableName, dynamoClient);
}
```

See the complete example on GitHub.

List Tables

You can list the tables in a particular region by calling the DynamoDB client `ListTables` method.

Includes

```
#include <aws/core/Aws.h>
```

```
#include <aws/core/utils/Outcome.h>
#include <aws/dynamodb/DynamoDBClient.h>
#include <aws/dynamodb/model/ListTablesRequest.h>
#include <aws/dynamodb/model/ListTablesResult.h>
#include <iostream>
```

Code

```
//! List the Amazon DynamoDB tables for the current AWS account.
/*!
  \sa listTables()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */

bool AwsDoc::DynamoDB::listTables(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::ListTablesRequest listTablesRequest;
    listTablesRequest.SetLimit(50);
    do {
        const Aws::DynamoDB::Model::ListTablesOutcome &outcome =
 dynamoClient.ListTables(
                listTablesRequest);
        if (!outcome.IsSuccess()) {
            std::cout << "Error: " << outcome.GetError().GetMessage() << std::endl;
            return false;
        }

        for (const auto &tableName: outcome.GetResult().GetTableNames())
            std::cout << tableName << std::endl;
        listTablesRequest.SetExclusiveStartTableName(
                outcome.GetResult().GetLastEvaluatedTableName());

    } while (!listTablesRequest.GetExclusiveStartTableName().empty());

    return true;
}
```

By default, up to 100 tables are returned per call. Use `GetExclusiveStartTableName` on the returned ListTablesOutcome object to get the last table that was evaluated. You can use this value to start the listing after the last returned value of the previous listing.

See the complete example.

Retrieve Information about a Table

You can find out more about a table by calling the DynamoDB client `DescribeTable` method.

Includes

```
#include <aws/core/Aws.h>
#include <aws/dynamodb/DynamoDBClient.h>
#include <aws/dynamodb/model/DescribeTableRequest.h>
#include <iostream>
```

Code

```
//! Describe an Amazon DynamoDB table.
/*!
  \sa describeTable()
  \param tableName: The DynamoDB table name.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::describeTable(const Aws::String &tableName,
                                     const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::DescribeTableRequest request;
    request.SetTableName(tableName);

    const Aws::DynamoDB::Model::DescribeTableOutcome &outcome =
 dynamoClient.DescribeTable(
            request);

    if (outcome.IsSuccess()) {
        const Aws::DynamoDB::Model::TableDescription &td =
 outcome.GetResult().GetTable();
        std::cout << "Table name  : " << td.GetTableName() << std::endl;
        std::cout << "Table ARN   : " << td.GetTableArn() << std::endl;
        std::cout << "Status      : "
                  << Aws::DynamoDB::Model::TableStatusMapper::GetNameForTableStatus(
                         td.GetTableStatus()) << std::endl;
        std::cout << "Item count  : " << td.GetItemCount() << std::endl;
        std::cout << "Size (bytes): " << td.GetTableSizeBytes() << std::endl;
```

```
        const Aws::DynamoDB::Model::ProvisionedThroughputDescription &ptd =
 td.GetProvisionedThroughput();
        std::cout << "Throughput" << std::endl;
        std::cout << "  Read Capacity : " << ptd.GetReadCapacityUnits() << std::endl;
        std::cout << "  Write Capacity: " << ptd.GetWriteCapacityUnits() << std::endl;

        const Aws::Vector<Aws::DynamoDB::Model::AttributeDefinition> &ad =
 td.GetAttributeDefinitions();
        std::cout << "Attributes" << std::endl;
        for (const auto &a: ad)
            std::cout << "  " << a.GetAttributeName() << " (" <<

 Aws::DynamoDB::Model::ScalarAttributeTypeMapper::GetNameForScalarAttributeType(
                             a.GetAttributeType()) <<
                     ")" << std::endl;
    }
    else {
        std::cerr << "Failed to describe table: " << outcome.GetError().GetMessage();
    }

    return outcome.IsSuccess();
}
```

See the complete example on GitHub.

Modify a Table

You can modify your table's provisioned throughput values at any time by calling the DynamoDB client `UpdateTable` method.

Includes

```
#include <aws/core/Aws.h>
#include <aws/core/utils/Outcome.h>
#include <aws/dynamodb/DynamoDBClient.h>
#include <aws/dynamodb/model/ProvisionedThroughput.h>
#include <aws/dynamodb/model/UpdateTableRequest.h>
#include <iostream>
```

Code

```
//! Update a DynamoDB table.
```

```
/*!
  \sa updateTable()
  \param tableName: Name for the DynamoDB table.
  \param readCapacity: Provisioned read capacity.
  \param writeCapacity: Provisioned write capacity.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::DynamoDB::updateTable(const Aws::String &tableName,
                                   long long readCapacity, long long writeCapacity,
                                   const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    std::cout << "Updating " << tableName << " with new provisioned throughput values"
              << std::endl;
    std::cout << "Read capacity : " << readCapacity << std::endl;
    std::cout << "Write capacity: " << writeCapacity << std::endl;

    Aws::DynamoDB::Model::UpdateTableRequest request;
    Aws::DynamoDB::Model::ProvisionedThroughput provisionedThroughput;
    provisionedThroughput.WithReadCapacityUnits(readCapacity).WithWriteCapacityUnits(
            writeCapacity);
    request.WithProvisionedThroughput(provisionedThroughput).WithTableName(tableName);

    const Aws::DynamoDB::Model::UpdateTableOutcome &outcome = dynamoClient.UpdateTable(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully updated the table." << std::endl;
    } else {
        const Aws::DynamoDB::DynamoDBError &error = outcome.GetError();
        if (error.GetErrorType() == Aws::DynamoDB::DynamoDBErrors::VALIDATION &&
            error.GetMessage().find("The provisioned throughput for the table will not
 change") != std::string::npos) {
            std::cout << "The provisioned throughput for the table will not change." <<
 std::endl;
        } else {
            std::cerr << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }

    return waitTableActive(tableName, dynamoClient);
```

```
}
```

See the complete example.

Delete a Table

Call the DynamoDB client `DeleteTable` method and pass it the table's name.

Includes

```
#include <aws/core/Aws.h>
#include <aws/dynamodb/DynamoDBClient.h>
#include <aws/dynamodb/model/DeleteTableRequest.h>
#include <iostream>
```

Code

```
//! Delete an Amazon DynamoDB table.
/*!
  \sa deleteTable()
  \param tableName: The DynamoDB table name.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::deleteTable(const Aws::String &tableName,
                                   const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::DeleteTableRequest request;
    request.SetTableName(tableName);

    const Aws::DynamoDB::Model::DeleteTableOutcome &result = dynamoClient.DeleteTable(
            request);
    if (result.IsSuccess()) {
        std::cout << "Your table \""
                  << result.GetResult().GetTableDescription().GetTableName()
                  << " was deleted.\n";
    }
    else {
        std::cerr << "Failed to delete table: " << result.GetError().GetMessage()
                  << std::endl;
    }
```

```
    return result.IsSuccess();
}
```

See the complete example on GitHub.

More Info

- Guidelines for Working with Tables in the Amazon DynamoDB Developer Guide
- Working with Tables in DynamoDB in the Amazon DynamoDB Developer Guide

Working with Items in DynamoDB

In DynamoDB, an item is a collection of *attributes*, each of which has a *name* and a *value*. An attribute value can be a scalar, set, or document type. For more information, see Naming Rules and Data Types in the Amazon DynamoDB Developer Guide.

Retrieve an Item from a Table

Call the DynamoDB client `GetItem` method. Pass it a GetItemRequest object with the table name and primary key value of the item you want. It returns a GetItemResult object.

You can use the returned `GetItemResult` object's `GetItem()` method to retrieve an `Aws::Map` of key `Aws::String` and value AttributeValue pairs associated with the item.

Includes

```
#include <aws/core/Aws.h>
#include <aws/dynamodb/DynamoDBClient.h>
#include <aws/dynamodb/model/AttributeDefinition.h>
#include <aws/dynamodb/model/GetItemRequest.h>
#include <iostream>
```

Code

```
//! Get an item from an Amazon DynamoDB table.
/*!
  \sa getItem()
  \param tableName: The table name.
  \param partitionKey: The partition key.
```

```
  \param partitionValue: The value for the partition key.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */

bool AwsDoc::DynamoDB::getItem(const Aws::String &tableName,
                               const Aws::String &partitionKey,
                               const Aws::String &partitionValue,
                               const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);
    Aws::DynamoDB::Model::GetItemRequest request;

    // Set up the request.
    request.SetTableName(tableName);
    request.AddKey(partitionKey,
                   Aws::DynamoDB::Model::AttributeValue().SetS(partitionValue));

    // Retrieve the item's fields and values.
    const Aws::DynamoDB::Model::GetItemOutcome &outcome =
 dynamoClient.GetItem(request);
    if (outcome.IsSuccess()) {
        // Reference the retrieved fields/values.
        const Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue> &item =
 outcome.GetResult().GetItem();
        if (!item.empty()) {
            // Output each retrieved field and its value.
            for (const auto &i: item)
                std::cout << "Values: " << i.first << ": " << i.second.GetS()
                          << std::endl;
        }
        else {
            std::cout << "No item found with the key " << partitionKey << std::endl;
        }
    }
    else {
        std::cerr << "Failed to get item: " << outcome.GetError().GetMessage();
    }

    return outcome.IsSuccess();
}
```

See the complete example on GitHub.

Add an Item to a Table

Create key `Aws::String` and value AttributeValue pairs that represent each item. These must include values for the table's primary key fields. If the item identified by the primary key already exists, its fields are *updated* by the request. Add them to the PutItemRequest using the `AddItem` method.

Includes

```
#include <aws/core/Aws.h>
#include <aws/dynamodb/DynamoDBClient.h>
#include <aws/dynamodb/model/AttributeDefinition.h>
#include <aws/dynamodb/model/PutItemRequest.h>
#include <aws/dynamodb/model/PutItemResult.h>
#include <iostream>
```

Code

```
//! Put an item in an Amazon DynamoDB table.
/*!
  \sa putItem()
  \param tableName: The table name.
  \param artistKey: The artist key. This is the partition key for the table.
  \param artistValue: The artist value.
  \param albumTitleKey: The album title key.
  \param albumTitleValue: The album title value.
  \param awardsKey: The awards key.
  \param awardsValue: The awards value.
  \param songTitleKey: The song title key.
  \param songTitleValue: The song title value.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::DynamoDB::putItem(const Aws::String &tableName,
                               const Aws::String &artistKey,
                               const Aws::String &artistValue,
                               const Aws::String &albumTitleKey,
                               const Aws::String &albumTitleValue,
                               const Aws::String &awardsKey,
                               const Aws::String &awardsValue,
                               const Aws::String &songTitleKey,
                               const Aws::String &songTitleValue,
```

```
                                const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::PutItemRequest putItemRequest;
    putItemRequest.SetTableName(tableName);

    putItemRequest.AddItem(artistKey, Aws::DynamoDB::Model::AttributeValue().SetS(
            artistValue)); // This is the hash key.
    putItemRequest.AddItem(albumTitleKey, Aws::DynamoDB::Model::AttributeValue().SetS(
            albumTitleValue));
    putItemRequest.AddItem(awardsKey,
                           Aws::DynamoDB::Model::AttributeValue().SetS(awardsValue));
    putItemRequest.AddItem(songTitleKey,

 Aws::DynamoDB::Model::AttributeValue().SetS(songTitleValue));

    const Aws::DynamoDB::Model::PutItemOutcome outcome = dynamoClient.PutItem(
            putItemRequest);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully added Item!" << std::endl;
    }
    else {
        std::cerr << outcome.GetError().GetMessage() << std::endl;
        return false;
    }

    return waitTableActive(tableName, dynamoClient);
}
```

See the complete example on GitHub.

Update an Existing Item in a Table

You can update an attribute for an item that already exists in a table by using the DynamoDBClient's `UpdateItem` method, providing a table name, primary key value, and fields to update and their corresponding value.

Imports

```
#include <aws/core/Aws.h>
#include <aws/dynamodb/DynamoDBClient.h>
```

```
#include <aws/dynamodb/model/UpdateItemRequest.h>
#include <aws/dynamodb/model/UpdateItemResult.h>
#include <iostream>
```

Code

```
//! Update an Amazon DynamoDB table item.
/*!
  \sa updateItem()
  \param tableName: The table name.
  \param partitionKey: The partition key.
  \param partitionValue: The value for the partition key.
  \param attributeKey: The key for the attribute to be updated.
  \param attributeValue: The value for the attribute to be updated.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
  */

/*
 *  The example code only sets/updates an attribute value. It processes
 *  the attribute value as a string, even if the value could be interpreted
 *  as a number. Also, the example code does not remove an existing attribute
 *  from the key value.
 */

bool AwsDoc::DynamoDB::updateItem(const Aws::String &tableName,
                                  const Aws::String &partitionKey,
                                  const Aws::String &partitionValue,
                                  const Aws::String &attributeKey,
                                  const Aws::String &attributeValue,
                                  const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    // *** Define UpdateItem request arguments.
    // Define TableName argument.
    Aws::DynamoDB::Model::UpdateItemRequest request;
    request.SetTableName(tableName);

    // Define KeyName argument.
    Aws::DynamoDB::Model::AttributeValue attribValue;
    attribValue.SetS(partitionValue);
    request.AddKey(partitionKey, attribValue);
```

```
    // Construct the SET update expression argument.
    Aws::String update_expression("SET #a = :valueA");
    request.SetUpdateExpression(update_expression);

    // Construct attribute name argument.
    Aws::Map<Aws::String, Aws::String> expressionAttributeNames;
    expressionAttributeNames["#a"] = attributeKey;
    request.SetExpressionAttributeNames(expressionAttributeNames);

    // Construct attribute value argument.
    Aws::DynamoDB::Model::AttributeValue attributeUpdatedValue;
    attributeUpdatedValue.SetS(attributeValue);
    Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
 expressionAttributeValues;
    expressionAttributeValues[":valueA"] = attributeUpdatedValue;
    request.SetExpressionAttributeValues(expressionAttributeValues);

    // Update the item.
    const Aws::DynamoDB::Model::UpdateItemOutcome &outcome = dynamoClient.UpdateItem(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Item was updated" << std::endl;
    } else {
        std::cerr << outcome.GetError().GetMessage() << std::endl;
        return false;
    }

    return waitTableActive(tableName, dynamoClient);
}
```

See the complete example.

More Info

- Guidelines for Working with Items in the Amazon DynamoDB Developer Guide
- Working with Items in DynamoDB in the Amazon DynamoDB Developer Guide

Amazon EC2 examples using the AWS SDK for C++

Amazon Elastic Compute Cloud (Amazon EC2) is a web service that provides resizable computing capacity—literally servers in Amazon's data centers—that you use to build and host your software systems. You can use the following examples to program Amazon EC2 using the AWS SDK for C++.

> **Note**
>
> Only the code that is necessary to demonstrate certain techniques is supplied in this Guide, but the complete example code is available on GitHub. On GitHub you can download a single source file or you can clone the repository locally to get, build, and run all examples.

Topics

- Managing Amazon EC2 Instances
- Using Elastic IP Addresses in Amazon EC2
- Using Regions and Availability Zones for Amazon EC2
- Working with Amazon EC2 Key Pairs
- Working with Security Groups in Amazon EC2

Managing Amazon EC2 Instances

Prerequisites

Before you begin, we recommend you read Getting started using the AWS SDK for C++.

Download the example code and build the solution as described in Getting started on code examples.

To run the examples, the user profile your code uses to make the requests must have proper permissions in AWS (for the service and the action). For more information, see Providing AWS credentials.

Create an Instance

Create a new Amazon EC2 instance by calling the EC2Client's `RunInstances` function, providing it with a RunInstancesRequest containing the Amazon Machine Image (AMI) to use and an instance type.

Includes

```
#include <aws/core/Aws.h>
#include <aws/ec2/EC2Client.h>
#include <aws/ec2/model/RunInstancesRequest.h>
#include <iostream>
```

Code

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::RunInstancesRequest runRequest;
    runRequest.SetImageId(amiId);
    runRequest.SetInstanceType(Aws::EC2::Model::InstanceType::t1_micro);
    runRequest.SetMinCount(1);
    runRequest.SetMaxCount(1);

    Aws::EC2::Model::RunInstancesOutcome runOutcome = ec2Client.RunInstances(
            runRequest);
    if (!runOutcome.IsSuccess()) {
        std::cerr << "Failed to launch EC2 instance " << instanceName <<
                  " based on ami " << amiId << ":" <<
                  runOutcome.GetError().GetMessage() << std::endl;
        return false;
    }

    const Aws::Vector<Aws::EC2::Model::Instance> &instances =
runOutcome.GetResult().GetInstances();
    if (instances.empty()) {
        std::cerr << "Failed to launch EC2 instance " << instanceName <<
                  " based on ami " << amiId << ":" <<
                  runOutcome.GetError().GetMessage() << std::endl;
        return false;
    }
```

See the complete example.

Start an Instance

To start an Amazon EC2 instance, call the EC2Client's `StartInstances` function, providing it with a StartInstancesRequest containing the ID of the instance to start.

Includes

```
#include <aws/ec2/EC2Client.h>
#include <aws/ec2/model/StartInstancesRequest.h>
```

Code

```
   Aws::EC2::EC2Client ec2Client(clientConfiguration);

   Aws::EC2::Model::StartInstancesRequest startRequest;
   startRequest.AddInstanceIds(instanceId);
   startRequest.SetDryRun(true);

   Aws::EC2::Model::StartInstancesOutcome dryRunOutcome =
ec2Client.StartInstances(startRequest);
   if (dryRunOutcome.IsSuccess()) {
       std::cerr
               << "Failed dry run to start instance. A dry run should trigger an
error."
               << std::endl;
       return false;
   } else if (dryRunOutcome.GetError().GetErrorType() !=
              Aws::EC2::EC2Errors::DRY_RUN_OPERATION) {
       std::cout << "Failed dry run to start instance " << instanceId << ": "
                 << dryRunOutcome.GetError().GetMessage() << std::endl;
       return false;
   }

   startRequest.SetDryRun(false);
   Aws::EC2::Model::StartInstancesOutcome startInstancesOutcome =
ec2Client.StartInstances(startRequest);

   if (!startInstancesOutcome.IsSuccess()) {
       std::cout << "Failed to start instance " << instanceId << ": " <<
                 startInstancesOutcome.GetError().GetMessage() << std::endl;
   } else {
       std::cout << "Successfully started instance " << instanceId <<
                 std::endl;
   }
```

See the complete example.

Stop an Instance

To stop an Amazon EC2 instance, call the EC2Client's `StopInstances` function, providing it with a StopInstancesRequest containing the ID of the instance to stop.

Includes

```
#include <aws/ec2/model/StopInstancesRequest.h>
```

Code

```
   Aws::EC2::EC2Client ec2Client(clientConfiguration);
   Aws::EC2::Model::StopInstancesRequest request;
   request.AddInstanceIds(instanceId);
   request.SetDryRun(true);

   Aws::EC2::Model::StopInstancesOutcome dryRunOutcome =
ec2Client.StopInstances(request);
   if (dryRunOutcome.IsSuccess()) {
       std::cerr
               << "Failed dry run to stop instance. A dry run should trigger an
error."
               << std::endl;
       return false;
   } else if (dryRunOutcome.GetError().GetErrorType() !=
              Aws::EC2::EC2Errors::DRY_RUN_OPERATION) {
       std::cout << "Failed dry run to stop instance " << instanceId << ": "
                 << dryRunOutcome.GetError().GetMessage() << std::endl;
       return false;
   }

   request.SetDryRun(false);
   Aws::EC2::Model::StopInstancesOutcome outcome = ec2Client.StopInstances(request);
   if (!outcome.IsSuccess()) {
       std::cout << "Failed to stop instance " << instanceId << ": " <<
                 outcome.GetError().GetMessage() << std::endl;
   } else {
       std::cout << "Successfully stopped instance " << instanceId <<
                 std::endl;
   }
```

See the complete example.

Reboot an Instance

To reboot an Amazon EC2 instance, call the EC2Client's `RebootInstances` function, providing it with a RebootInstancesRequest containing the ID of the instance to reboot.

Includes

```
#include <aws/ec2/EC2Client.h>
#include <aws/ec2/model/RebootInstancesRequest.h>
#include <iostream>
```

Code

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::RebootInstancesRequest request;
    request.AddInstanceIds(instanceId);
    request.SetDryRun(true);

    Aws::EC2::Model::RebootInstancesOutcome dry_run_outcome =
ec2Client.RebootInstances(request);
    if (dry_run_outcome.IsSuccess()) {
        std::cerr
                << "Failed dry run to reboot on instance. A dry run should trigger an
error."
                <<
                std::endl;
        return false;
    } else if (dry_run_outcome.GetError().GetErrorType()
               != Aws::EC2::EC2Errors::DRY_RUN_OPERATION) {
        std::cout << "Failed dry run to reboot instance " << instanceId << ": "
                  << dry_run_outcome.GetError().GetMessage() << std::endl;
        return false;
    }

    request.SetDryRun(false);
    Aws::EC2::Model::RebootInstancesOutcome outcome =
ec2Client.RebootInstances(request);
    if (!outcome.IsSuccess()) {
        std::cout << "Failed to reboot instance " << instanceId << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    } else {
        std::cout << "Successfully rebooted instance " << instanceId <<
```

```
                  std::endl;
    }
```

See the complete example.

Describe Instances

To list your instances, create a DescribeInstancesRequest and call the EC2Client's `DescribeInstances` function. It will return a DescribeInstancesResponse object that you can use to list the Amazon EC2 instances for your AWS account and AWS Region.

Instances are grouped by *reservation*. Each reservation corresponds to the call to `StartInstances` that launched the instance. To list your instances, you must first call the `DescribeInstancesResponse` class' `GetReservations` function, and then call `getInstances` on each returned Reservation object.

Includes

```
#include <aws/ec2/EC2Client.h>
#include <aws/ec2/model/DescribeInstancesRequest.h>
#include <aws/ec2/model/DescribeInstancesResponse.h>
#include <iomanip>
#include <iostream>
```

Code

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::DescribeInstancesRequest request;
    bool header = false;
    bool done = false;
    while (!done) {
        Aws::EC2::Model::DescribeInstancesOutcome outcome =
 ec2Client.DescribeInstances(request);
        if (outcome.IsSuccess()) {
            if (!header) {
                std::cout << std::left <<
                          std::setw(48) << "Name" <<
                          std::setw(20) << "ID" <<
                          std::setw(25) << "Ami" <<
                          std::setw(15) << "Type" <<
                          std::setw(15) << "State" <<
                          std::setw(15) << "Monitoring" << std::endl;
                header = true;
```

```
            }

            const std::vector<Aws::EC2::Model::Reservation> &reservations =
                    outcome.GetResult().GetReservations();

            for (const auto &reservation: reservations) {
                const std::vector<Aws::EC2::Model::Instance> &instances =
                        reservation.GetInstances();
                for (const auto &instance: instances) {
                    Aws::String instanceStateString =

Aws::EC2::Model::InstanceStateNameMapper::GetNameForInstanceStateName(
                                    instance.GetState().GetName());

                    Aws::String typeString =

Aws::EC2::Model::InstanceTypeMapper::GetNameForInstanceType(
                                    instance.GetInstanceType());

                    Aws::String monitorString =

Aws::EC2::Model::MonitoringStateMapper::GetNameForMonitoringState(
                                    instance.GetMonitoring().GetState());
                    Aws::String name = "Unknown";

                    const std::vector<Aws::EC2::Model::Tag> &tags = instance.GetTags();
                    auto nameIter = std::find_if(tags.cbegin(), tags.cend(),
                                                 [](const Aws::EC2::Model::Tag &tag) {
                                                     return tag.GetKey() == "Name";
                                                 });
                    if (nameIter != tags.cend()) {
                        name = nameIter->GetValue();
                    }
                    std::cout <<
                              std::setw(48) << name <<
                              std::setw(20) << instance.GetInstanceId() <<
                              std::setw(25) << instance.GetImageId() <<
                              std::setw(15) << typeString <<
                              std::setw(15) << instanceStateString <<
                              std::setw(15) << monitorString << std::endl;
                }
            }

            if (!outcome.GetResult().GetNextToken().empty()) {
```

```
                request.SetNextToken(outcome.GetResult().GetNextToken());
            } else {
                done = true;
            }
        } else {
            std::cerr << "Failed to describe EC2 instances:" <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }
```

Results are paged; you can get further results by passing the value returned from the result object's `GetNextToken` function to your original request object's `SetNextToken` function, then using the same request object in your next call to `DescribeInstances`.

See the complete example.

Enable Instance Monitoring

You can monitor various aspects of your Amazon EC2 instances, such as CPU and network utilization, available memory, and disk space remaining. To learn more about instance monitoring, see Monitoring Amazon EC2 in the Amazon EC2 User Guide.

To start monitoring an instance, you must create a MonitorInstancesRequest with the ID of the instance to monitor, and pass it to the EC2Client's `MonitorInstances` function.

Includes

```
#include <aws/ec2/EC2Client.h>
#include <aws/ec2/model/MonitorInstancesRequest.h>
#include <aws/ec2/model/UnmonitorInstancesRequest.h>
#include <iostream>
```

Code

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::MonitorInstancesRequest request;
    request.AddInstanceIds(instanceId);
    request.SetDryRun(true);

    Aws::EC2::Model::MonitorInstancesOutcome dryRunOutcome =
  ec2Client.MonitorInstances(request);
```

```
    if (dryRunOutcome.IsSuccess()) {
        std::cerr
                << "Failed dry run to enable monitoring on instance. A dry run should
trigger an error."
                <<
                std::endl;
        return false;
    } else if (dryRunOutcome.GetError().GetErrorType()
               != Aws::EC2::EC2Errors::DRY_RUN_OPERATION) {
        std::cerr << "Failed dry run to enable monitoring on instance " <<
                  instanceId << ": " << dryRunOutcome.GetError().GetMessage() <<
                  std::endl;
        return false;
    }

    request.SetDryRun(false);
    Aws::EC2::Model::MonitorInstancesOutcome monitorInstancesOutcome =
ec2Client.MonitorInstances(request);
    if (!monitorInstancesOutcome.IsSuccess()) {
        std::cerr << "Failed to enable monitoring on instance " <<
                  instanceId << ": " <<
                  monitorInstancesOutcome.GetError().GetMessage() << std::endl;
    } else {
        std::cout << "Successfully enabled monitoring on instance " <<
                  instanceId << std::endl;
    }
```

See the complete example.

Disable Instance Monitoring

To stop monitoring an instance, create an UnmonitorInstancesRequest with the ID of the instance to stop monitoring, and pass it to the EC2Client's `UnmonitorInstances` function.

Includes

```
#include <aws/ec2/EC2Client.h>
#include <aws/ec2/model/MonitorInstancesRequest.h>
#include <aws/ec2/model/UnmonitorInstancesRequest.h>
#include <iostream>
```

Code

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::UnmonitorInstancesRequest unrequest;
    unrequest.AddInstanceIds(instanceId);
    unrequest.SetDryRun(true);

    Aws::EC2::Model::UnmonitorInstancesOutcome dryRunOutcome =
ec2Client.UnmonitorInstances(unrequest);
    if (dryRunOutcome.IsSuccess()) {
        std::cerr
                << "Failed dry run to disable monitoring on instance. A dry run should
trigger an error."
                <<
                std::endl;
        return false;
    } else if (dryRunOutcome.GetError().GetErrorType() !=
               Aws::EC2::EC2Errors::DRY_RUN_OPERATION) {
        std::cout << "Failed dry run to disable monitoring on instance " <<
                  instanceId << ": " << dryRunOutcome.GetError().GetMessage() <<
                  std::endl;
        return false;
    }

    unrequest.SetDryRun(false);
    Aws::EC2::Model::UnmonitorInstancesOutcome unmonitorInstancesOutcome =
ec2Client.UnmonitorInstances(unrequest);
    if (!unmonitorInstancesOutcome.IsSuccess()) {
        std::cout << "Failed to disable monitoring on instance " << instanceId
                  << ": " << unmonitorInstancesOutcome.GetError().GetMessage() <<
                  std::endl;
    } else {
        std::cout << "Successfully disable monitoring on instance " <<
                  instanceId << std::endl;
    }
```

See the complete example.

More Information

- RunInstances in the Amazon EC2 API Reference
- DescribeInstances in the Amazon EC2 API Reference
- StartInstances in the Amazon EC2 API Reference
- StopInstances in the Amazon EC2 API Reference

- RebootInstances in the Amazon EC2 API Reference
- DescribeInstances in the Amazon EC2 API Reference
- MonitorInstances in the Amazon EC2 API Reference
- UnmonitorInstances in the Amazon EC2 API Reference

Using Elastic IP Addresses in Amazon EC2

Prerequisites

Before you begin, we recommend you read Getting started using the AWS SDK for C++.

Download the example code and build the solution as described in Getting started on code examples.

To run the examples, the user profile your code uses to make the requests must have proper permissions in AWS (for the service and the action). For more information, see Providing AWS credentials.

Allocate an Elastic IP Address

To use an Elastic IP address, you first allocate one to your account, and then associate it with your instance or a network interface.

To allocate an Elastic IP address, call the EC2Client's `AllocateAddress` function with an AllocateAddressRequest object containing the network type (classic EC2 or VPC).

> **Warning**
>
> We are retiring EC2-Classic on August 15, 2022. We recommend that you migrate from EC2-Classic to a VPC. For more information, see **Migrate from EC2-Classic to a VPC** in the the Amazon EC2 User Guide for Linux Instances or the Amazon EC2 User Guide for Windows Instances. Also see the blog post EC2-Classic Networking is Retiring – Here's How to Prepare.

The AllocateAddressResponse class in the response object contains an allocation ID that you can use to associate the address with an instance, by passing the allocation ID and instance ID in a AssociateAddressRequest to the EC2Client's `AssociateAddress` function.

Includes

```
#include <aws/ec2/EC2Client.h>
#include <aws/ec2/model/AllocateAddressRequest.h>
#include <aws/ec2/model/AssociateAddressRequest.h>
#include <iostream>
```

Code

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::AllocateAddressRequest request;
    request.SetDomain(Aws::EC2::Model::DomainType::vpc);

    const Aws::EC2::Model::AllocateAddressOutcome outcome =
            ec2Client.AllocateAddress(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Failed to allocate Elastic IP address:" <<
                  outcome.GetError().GetMessage() << std::endl;
        return false;
    }
    const Aws::EC2::Model::AllocateAddressResponse &response = outcome.GetResult();
    allocationID = response.GetAllocationId();
    publicIPAddress = response.GetPublicIp();


    Aws::EC2::Model::AssociateAddressRequest associate_request;
    associate_request.SetInstanceId(instanceId);
    associate_request.SetAllocationId(allocationID);

    const Aws::EC2::Model::AssociateAddressOutcome associate_outcome =
            ec2Client.AssociateAddress(associate_request);
    if (!associate_outcome.IsSuccess()) {
        std::cerr << "Failed to associate Elastic IP address " << allocationID
                  << " with instance " << instanceId << ":" <<
                  associate_outcome.GetError().GetMessage() << std::endl;
        return false;
    }

    std::cout << "Successfully associated Elastic IP address " << allocationID
              << " with instance " << instanceId << std::endl;
```

See the complete example.

Describe Elastic IP Addresses

To list the Elastic IP addresses assigned to your account, call the EC2Client's `DescribeAddresses` function. It returns an outcome object that contains a DescribeAddressesResponse which you can use to get a list of Address objects that represent the Elastic IP addresses on your account.

Includes

```
#include <aws/ec2/EC2Client.h>
#include <aws/ec2/model/DescribeAddressesRequest.h>
#include <aws/ec2/model/DescribeAddressesResponse.h>
#include <iomanip>
#include <iostream>
```

Code

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::DescribeAddressesRequest request;
    Aws::EC2::Model::DescribeAddressesOutcome outcome =
ec2Client.DescribeAddresses(request);
    if (outcome.IsSuccess()) {
        std::cout << std::left << std::setw(20) << "InstanceId" <<
                  std::setw(15) << "Public IP" << std::setw(10) << "Domain" <<
                  std::setw(30) << "Allocation ID" << std::setw(25) <<
                  "NIC ID" << std::endl;

        const Aws::Vector<Aws::EC2::Model::Address> &addresses =
outcome.GetResult().GetAddresses();
        for (const auto &address: addresses) {
            Aws::String domainString =
                    Aws::EC2::Model::DomainTypeMapper::GetNameForDomainType(
                            address.GetDomain());

            std::cout << std::left << std::setw(20) <<
                      address.GetInstanceId() << std::setw(15) <<
                      address.GetPublicIp() << std::setw(10) << domainString <<
                      std::setw(30) << address.GetAllocationId() << std::setw(25)
                      << address.GetNetworkInterfaceId() << std::endl;
        }
    } else {
        std::cerr << "Failed to describe Elastic IP addresses:" <<
                  outcome.GetError().GetMessage() << std::endl;
```

```
    }
```

See the complete example.

Release an Elastic IP Address

To release an Elastic IP address, call the EC2Client's `ReleaseAddress` function, passing it a ReleaseAddressRequest containing the allocation ID of the Elastic IP address you want to release.

Includes

```
#include <aws/ec2/EC2Client.h>
#include <aws/ec2/model/ReleaseAddressRequest.h>
#include <iostream>
```

Code

```
    Aws::EC2::EC2Client ec2(clientConfiguration);

    Aws::EC2::Model::ReleaseAddressRequest request;
    request.SetAllocationId(allocationID);

    Aws::EC2::Model::ReleaseAddressOutcome outcome = ec2.ReleaseAddress(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Failed to release Elastic IP address " <<
                  allocationID << ":" << outcome.GetError().GetMessage() <<
                  std::endl;
    } else {
        std::cout << "Successfully released Elastic IP address " <<
                  allocationID << std::endl;
    }
```

After you release an Elastic IP address, it is released to the AWS IP address pool and might be unavailable to you afterward. Be sure to update your DNS records and any servers or devices that communicate with the address. If you attempt to release an Elastic IP address that you already released, you'll get an *AuthFailure* error if the address is already allocated to another AWS account.

If you are using a *default VPC*, then releasing an Elastic IP address automatically disassociates it from any instance that it's associated with. To disassociate an Elastic IP address without releasing it, use the EC2Client's `DisassociateAddress` function.

If you are using a non-default VPC, you *must* use `DisassociateAddress` to disassociate the Elastic IP address before you try to release it. Otherwise, Amazon EC2 returns an error (*InvalidIPAddress.InUse*).

See the complete example.

More Information

- Elastic IP Addresses in the Amazon EC2 User Guide
- AllocateAddress in the Amazon EC2 API Reference
- DescribeAddresses in the Amazon EC2 API Reference
- ReleaseAddress in the Amazon EC2 API Reference

Using Regions and Availability Zones for Amazon EC2

Prerequisites

Before you begin, we recommend you read Getting started using the AWS SDK for C++.

Download the example code and build the solution as described in Getting started on code examples.

To run the examples, the user profile your code uses to make the requests must have proper permissions in AWS (for the service and the action). For more information, see Providing AWS credentials.

Describe Regions

To list the AWS Regions available to your AWS account, call the EC2Client's `DescribeRegions` function with a DescribeRegionsRequest.

You will receive a DescribeRegionsResponse in the outcome object. Call its `GetRegions` function to get a list of Region objects that represent each Region.

Includes

```
#include <aws/ec2/EC2Client.h>
#include <aws/ec2/model/DescribeRegionsRequest.h>
```

Code

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::DescribeRegionsRequest request;
    Aws::EC2::Model::DescribeRegionsOutcome outcome =
ec2Client.DescribeRegions(request);
    if (outcome.IsSuccess()) {
        std::cout << std::left <<
                  std::setw(32) << "RegionName" <<
                  std::setw(64) << "Endpoint" << std::endl;

        const auto &regions = outcome.GetResult().GetRegions();
        for (const auto &region: regions) {
            std::cout << std::left <<
                      std::setw(32) << region.GetRegionName() <<
                      std::setw(64) << region.GetEndpoint() << std::endl;
        }
    } else {
        std::cerr << "Failed to describe regions:" <<
                  outcome.GetError().GetMessage() << std::endl;
    }
```

See the complete example.

Describe Availability Zones

To list each availability zone available to your account, call the EC2Client's `DescribeAvailabilityZones` function with a DescribeAvailabilityZonesRequest.

You will receive a DescribeAvailabilityZonesResponse in the outcome object. Call its `GetAvailabilityZones` function to get a list of AvailabilityZone objects that represent each availability zone.

Includes

```
#include <aws/ec2/model/DescribeAvailabilityZonesRequest.h>
```

Code

```
    Aws::EC2::Model::DescribeAvailabilityZonesRequest request;
```

```
   Aws::EC2::Model::DescribeAvailabilityZonesOutcome outcome =
ec2Client.DescribeAvailabilityZones(request);

   if (outcome.IsSuccess()) {
       std::cout << std::left <<
                 std::setw(32) << "ZoneName" <<
                 std::setw(20) << "State" <<
                 std::setw(32) << "Region" << std::endl;

       const auto &zones =
               outcome.GetResult().GetAvailabilityZones();

       for (const auto &zone: zones) {
           Aws::String stateString =

Aws::EC2::Model::AvailabilityZoneStateMapper::GetNameForAvailabilityZoneState(
                           zone.GetState());
           std::cout << std::left <<
                     std::setw(32) << zone.GetZoneName() <<
                     std::setw(20) << stateString <<
                     std::setw(32) << zone.GetRegionName() << std::endl;
       }
   } else {
       std::cerr << "Failed to describe availability zones:" <<
                 outcome.GetError().GetMessage() << std::endl;

   }
```

See the complete example.

More Information

- Regions and Availability Zones in the Amazon EC2 User Guide
- DescribeRegions in the Amazon EC2 API Reference
- DescribeAvailabilityZones in the Amazon EC2 API Reference

Working with Amazon EC2 Key Pairs

Prerequisites

Before you begin, we recommend you read Getting started using the AWS SDK for C++.

Download the example code and build the solution as described in Getting started on code examples.

To run the examples, the user profile your code uses to make the requests must have proper permissions in AWS (for the service and the action). For more information, see Providing AWS credentials.

Create a Key Pair

To create a key pair, call the EC2Client's `CreateKeyPair` function with a CreateKeyPairRequest that contains the key's name.

Includes

```
#include <aws/ec2/EC2Client.h>
#include <aws/ec2/model/CreateKeyPairRequest.h>
#include <iostream>
#include <fstream>
```

Code

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::CreateKeyPairRequest request;
    request.SetKeyName(keyPairName);

    Aws::EC2::Model::CreateKeyPairOutcome outcome = ec2Client.CreateKeyPair(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Failed to create key pair - "  << keyPairName << ". " <<
                  outcome.GetError().GetMessage() << std::endl;
    } else {
        std::cout << "Successfully created key pair named " <<
                  keyPairName << std::endl;
        if (!keyFilePath.empty()) {
            std::ofstream keyFile(keyFilePath.c_str());
            keyFile << outcome.GetResult().GetKeyMaterial();
            keyFile.close();
            std::cout << "Keys written to the file " <<
                      keyFilePath << std::endl;
        }

    }
```

See the complete example.

Describe Key Pairs

To list your key pairs or to get information about them, call the EC2Client's `DescribeKeyPairs` function with a DescribeKeyPairsRequest.

You will receive a DescribeKeyPairsResponse that you can use to access the list of key pairs by calling its `GetKeyPairs` function, which returns a list of KeyPairInfo objects.

Includes

```
#include <aws/ec2/EC2Client.h>
#include <aws/ec2/model/DescribeKeyPairsRequest.h>
#include <aws/ec2/model/DescribeKeyPairsResponse.h>
#include <iomanip>
#include <iostream>
```

Code

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::DescribeKeyPairsRequest request;

    Aws::EC2::Model::DescribeKeyPairsOutcome outcome =
ec2Client.DescribeKeyPairs(request);
    if (outcome.IsSuccess()) {
        std::cout << std::left <<
                  std::setw(32) << "Name" <<
                  std::setw(64) << "Fingerprint" << std::endl;

        const std::vector<Aws::EC2::Model::KeyPairInfo> &key_pairs =
                outcome.GetResult().GetKeyPairs();
        for (const auto &key_pair: key_pairs) {
            std::cout << std::left <<
                      std::setw(32) << key_pair.GetKeyName() <<
                      std::setw(64) << key_pair.GetKeyFingerprint() << std::endl;
        }
    } else {
        std::cerr << "Failed to describe key pairs:" <<
                  outcome.GetError().GetMessage() << std::endl;
    }
```

See the complete example.

Delete a Key Pair

To delete a key pair, call the EC2Client's `DeleteKeyPair` function, passing it a DeleteKeyPairRequest that contains the name of the key pair to delete.

Includes

```
#include <aws/ec2/EC2Client.h>
#include <aws/ec2/model/DeleteKeyPairRequest.h>
#include <iostream>
```

Code

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::DeleteKeyPairRequest request;

    request.SetKeyName(keyPairName);
    const Aws::EC2::Model::DeleteKeyPairOutcome outcome = ec2Client.DeleteKeyPair(
            request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Failed to delete key pair " << keyPairName <<
                  ":" << outcome.GetError().GetMessage() << std::endl;
    } else {
        std::cout << "Successfully deleted key pair named " << keyPairName <<
                  std::endl;
    }
```

See the complete example.

More Information

- Amazon EC2 Key Pairs in the Amazon EC2 User Guide
- CreateKeyPair in the Amazon EC2 API Reference
- DescribeKeyPairs in the Amazon EC2 API Reference
- DeleteKeyPair in the Amazon EC2 API Reference

Working with Security Groups in Amazon EC2

Prerequisites

Before you begin, we recommend you read Getting started using the AWS SDK for C++.

Download the example code and build the solution as described in Getting started on code examples.

To run the examples, the user profile your code uses to make the requests must have proper permissions in AWS (for the service and the action). For more information, see Providing AWS credentials.

Create a Security Group

To create a security group, call the EC2Client's `CreateSecurityGroup` function with a CreateSecurityGroupRequest that contains the key's name.

Includes

```
#include <aws/ec2/EC2Client.h>
#include <aws/ec2/model/CreateSecurityGroupRequest.h>
```

Code

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::CreateSecurityGroupRequest request;

    request.SetGroupName(groupName);
    request.SetDescription(description);
    request.SetVpcId(vpcID);

    const Aws::EC2::Model::CreateSecurityGroupOutcome outcome =
            ec2Client.CreateSecurityGroup(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Failed to create security group:" <<
                  outcome.GetError().GetMessage() << std::endl;
        return false;
    }

    std::cout << "Successfully created security group named " << groupName <<
```

```
            std::endl;
```

See the complete example.

Configure a Security Group

A security group can control both inbound (ingress) and outbound (egress) traffic to your Amazon EC2 instances.

To add ingress rules to your security group, use the EC2Client's `AuthorizeSecurityGroupIngress` function, providing the name of the security group and the access rules (IpPermission) you want to assign to it within an AuthorizeSecurityGroupIngressRequest object. The following example shows how to add IP permissions to a security group.

Includes

```
#include <aws/ec2/model/AuthorizeSecurityGroupIngressRequest.h>
```

Code

```
   Aws::EC2::Model::AuthorizeSecurityGroupIngressRequest
authorizeSecurityGroupIngressRequest;
   authorizeSecurityGroupIngressRequest.SetGroupId(groupID);
```

```
   Aws::String ingressIPRange = "203.0.113.0/24";  // Configure this for your allowed
IP range.
   Aws::EC2::Model::IpRange ip_range;
   ip_range.SetCidrIp(ingressIPRange);

   Aws::EC2::Model::IpPermission permission1;
   permission1.SetIpProtocol("tcp");
   permission1.SetToPort(80);
   permission1.SetFromPort(80);
   permission1.AddIpRanges(ip_range);

   authorize_request.AddIpPermissions(permission1);

   Aws::EC2::Model::IpPermission permission2;
   permission2.SetIpProtocol("tcp");
   permission2.SetToPort(22);
```

```
    permission2.SetFromPort(22);
    permission2.AddIpRanges(ip_range);

    authorize_request.AddIpPermissions(permission2);
```

```
   Aws::EC2::Model::AuthorizeSecurityGroupIngressOutcome
authorizeSecurityGroupIngressOutcome =

ec2Client.AuthorizeSecurityGroupIngress(authorizeSecurityGroupIngressRequest);

   if (authorizeSecurityGroupIngressOutcome.IsSuccess()) {
       std::cout << "Successfully authorized security group ingress." << std::endl;
   } else {
       std::cerr << "Error authorizing security group ingress: "
                 << authorizeSecurityGroupIngressOutcome.GetError().GetMessage() <<
std::endl;
   }
```

To add an egress rule to the security group, provide similar data in an AuthorizeSecurityGroupEgressRequest to the EC2Client's `AuthorizeSecurityGroupEgress` function.

See the complete example.

Describe Security Groups

To describe your security groups or get information about them, call the EC2Client's `DescribeSecurityGroups` function with a DescribeSecurityGroupsRequest.

You will receive a DescribeSecurityGroupsResponse in the outcome object that you can use to access the list of security groups by calling its `GetSecurityGroups` function, which returns a list of SecurityGroup objects.

Includes

```
#include <aws/ec2/EC2Client.h>
#include <aws/ec2/model/DescribeSecurityGroupsRequest.h>
#include <aws/ec2/model/DescribeSecurityGroupsResponse.h>
#include <iomanip>
#include <iostream>
```

Code

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::DescribeSecurityGroupsRequest request;

    if (!groupID.empty()) {
        request.AddGroupIds(groupID);
    }

    Aws::String nextToken;
    do {
        if (!nextToken.empty()) {
            request.SetNextToken(nextToken);
        }

        Aws::EC2::Model::DescribeSecurityGroupsOutcome outcome =
ec2Client.DescribeSecurityGroups(request);
        if (outcome.IsSuccess()) {
            std::cout << std::left <<
                      std::setw(32) << "Name" <<
                      std::setw(30) << "GroupId" <<
                      std::setw(30) << "VpcId" <<
                      std::setw(64) << "Description" << std::endl;

            const std::vector<Aws::EC2::Model::SecurityGroup> &securityGroups =
                    outcome.GetResult().GetSecurityGroups();

            for (const auto &securityGroup: securityGroups) {
                std::cout << std::left <<
                          std::setw(32) << securityGroup.GetGroupName() <<
                          std::setw(30) << securityGroup.GetGroupId() <<
                          std::setw(30) << securityGroup.GetVpcId() <<
                          std::setw(64) << securityGroup.GetDescription() <<
                          std::endl;
            }
        } else {
            std::cerr << "Failed to describe security groups:" <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }

        nextToken = outcome.GetResult().GetNextToken();
    } while (!nextToken.empty());
```

See the complete example.

Delete a Security Group

To delete a security group, call the EC2Client's `DeleteSecurityGroup` function, passing it a DeleteSecurityGroupRequest that contains the ID of the security group to delete.

Includes

```
#include <aws/ec2/EC2Client.h>
#include <aws/ec2/model/DeleteSecurityGroupRequest.h>
#include <iostream>
```

Code

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::DeleteSecurityGroupRequest request;

    request.SetGroupId(securityGroupID);
    Aws::EC2::Model::DeleteSecurityGroupOutcome outcome =
ec2Client.DeleteSecurityGroup(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Failed to delete security group " << securityGroupID <<
                  ":" << outcome.GetError().GetMessage() << std::endl;
    } else {
        std::cout << "Successfully deleted security group " << securityGroupID <<
                  std::endl;
    }
```

See the complete example.

More Information

- Amazon EC2 Security Groups in the Amazon EC2 User Guide
- Authorizing Inbound Traffic for Your Linux Instances in the Amazon EC2 User Guide
- CreateSecurityGroup in the Amazon EC2 API Reference
- DescribeSecurityGroups in the Amazon EC2 API Reference
- DeleteSecurityGroup in the Amazon EC2 API Reference
- AuthorizeSecurityGroupIngress in the Amazon EC2 API Reference

Amazon S3 code examples using the AWS SDK for C++

Amazon S3 is object storage built to store and retrieve any amount of data from anywhere. There are multiple classes provided by the AWS SDK for C++ to interface with Amazon S3.

> **Note**
>
> Only the code that is necessary to demonstrate certain techniques is supplied in this Guide, but the complete example code is available on GitHub. On GitHub you can download a single source file or you can clone the repository locally to get, build, and run all examples.

- `S3Client` class

  The `S3Client` library is a fully-featured Amazon S3 interface.

  The `list_buckets_disabling_dns_cache.cpp` example in this set is catered specifically to work with CURL on Linux/Mac (though can be modified to work on Windows). If you are on Windows, delete the file `list_buckets_disabling_dns_cache.cpp` before building the project because it relies on the curl HttpClient of Linux.

  The example code utilizing the `S3Client` is in the `s3` folder on Github. See the Readme on Github for a full list of functions demonstrated by this example set.

  Portions of the `s3` example set are covered in additional detail in this guide:

  - Creating, listing, and deleting buckets
  - Operations on objects – Uploading and downloading data objects
  - Managing Amazon S3 Access Permissions
  - Managing Access to Amazon S3 Buckets Using Bucket Policies
  - Configuring an Amazon S3 Bucket as a Website
- `S3CrtClient` class

  The `S3CrtClient` was added in version 1.9 of the SDK. `S3CrtClient` provides high throughput for Amazon S3 GET (download) and PUT (upload) operations. The `S3CrtClient` is implemented on the top of the AWS Common Runtime (CRT) libraries.

  The example code utilizing the `S3CrtClient` is in the `s3-crt` folder on Github. See the Readme on Github for a full list of functions demonstrated by this example set.

- Using `S3CrtClient` for Amazon S3 operations
- `TransferManager` class

  `TransferManager` is a fully managed service that enables the transfer of files over the File Transfer Protocol (FTP), File Transfer Protocol over SSL (FTPS), or Secure Shell (SSH) File Transfer Protocol (SFTP) directly into and out of Amazon S3.

  The example code utilizing the `TransferManager` is in the `transfer-manager` folder on Github. See the Readme on Github for a full list of functions demonstrated by this example set.

  - Using TransferManager for Amazon S3 operations

Creating, listing, and deleting buckets

Every *object* or file in Amazon Simple Storage Service (Amazon S3) is contained in a *bucket*, which represents a folder of objects. Each bucket has a name that is globally unique within AWS. For more information, see Working with Amazon S3 Buckets in the Amazon Simple Storage Service User Guide.

Prerequisites

Before you begin, we recommend you read Getting started using the AWS SDK for C++.

Download the example code and build the solution as described in Getting started on code examples.

To run the examples, the user profile your code uses to make the requests must have proper permissions in AWS (for the service and the action). For more information, see Providing AWS credentials.

List buckets

To run the `list_buckets` example, at a command prompt, navigate to the folder where your build system creates your build executables. Run the executable like `run_list_buckets` (your full executable filename will differ based on your operating system). The output lists your account's buckets if you have any, or it displays an empty list if you don't have any buckets.

In `list_buckets.cpp`, there are two methods.

- `main()` calls `ListBuckets()`.
- `ListBuckets()` uses the SDK to query your buckets.

The `S3Client` object calls the SDK's `ListBuckets()` method. If successful, the method returns a `ListBucketOutcome` object, which contains a `ListBucketResult` object. The `ListBucketResult` object calls the `GetBuckets()` method to get a list of `Bucket` objects that contain information about each Amazon S3 bucket in your account.

Code

```
bool AwsDoc::S3::listBuckets(const Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client client(clientConfig);

    auto outcome = client.ListBuckets();

    bool result = true;
    if (!outcome.IsSuccess()) {
        std::cerr << "Failed with error: " << outcome.GetError() << std::endl;
        result = false;
    } else {
        std::cout << "Found " << outcome.GetResult().GetBuckets().size() << " buckets
\n";
        for (auto &&b: outcome.GetResult().GetBuckets()) {
            std::cout << b.GetName() << std::endl;
        }
    }

    return result;
}
```

See the complete list_buckets example on Github.

Create a bucket

To run the `create_bucket` example, at a command prompt, navigate to the folder where your build system creates your build executables. Run the executable like `run_create_bucket` (your full executable filename will differ based on your operating system). The code creates an empty bucket under your account and then displays the success or failure of the request.

In `create_bucket.cpp`, there are two methods.

- `main()` calls `CreateBucket()`. In `main()`, you need to change the AWS Region to the Region of your account by using the `enum`. You can view the Region of your account by logging into the AWS Management Console, and locating the Region in the upper right-hand corner.

- `CreateBucket()` uses the SDK to create a bucket.

The `S3Client` object calls the SDK's `CreateBucket()` method, passing in a `CreateBucketRequest` with the bucket's name. By default, buckets are created in the *us-east-1* (N. Virginia) Region. If your Region is not *us-east-1* then the code sets up a bucket constraint to ensure the bucket is created in your Region.

Code

```
bool AwsDoc::S3::createBucket(const Aws::String &bucketName,
                              const Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client client(clientConfig);
    Aws::S3::Model::CreateBucketRequest request;
    request.SetBucket(bucketName);

    if (clientConfig.region != "us-east-1") {
        Aws::S3::Model::CreateBucketConfiguration createBucketConfig;
        createBucketConfig.SetLocationConstraint(

 Aws::S3::Model::BucketLocationConstraintMapper::GetBucketLocationConstraintForName(
                        clientConfig.region));
        request.SetCreateBucketConfiguration(createBucketConfig);
    }

    Aws::S3::Model::CreateBucketOutcome outcome = client.CreateBucket(request);
    if (!outcome.IsSuccess()) {
        auto err = outcome.GetError();
        std::cerr << "Error: createBucket: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() << std::endl;
    } else {
        std::cout << "Created bucket " << bucketName <<
                  " in the specified AWS Region." << std::endl;
    }

    return outcome.IsSuccess();
}
```

See the complete create_buckets example on Github.

Delete a bucket

To run the `delete_bucket` example, at a command prompt, navigate to the folder where your build system creates your build executables. Run the executable like `run_delete_bucket` (your full executable filename will differ based on your operating system). The code deletes the specified bucket in your account and then displays the success or failure of the request.

In `delete_bucket.cpp` there are two methods.

- `main()` calls `DeleteBucket()`. In `main()`, you need to change the AWS Region to the Region of your account by using the `enum`. You also need to change the `bucket_name` to the name of the bucket to delete.
- `DeleteBucket()` uses the SDK to delete the bucket.

The `S3Client` object uses the SDK's `DeleteBucket()` method, passing in a `DeleteBucketRequest` object with the name of the bucket to delete. The bucket must be empty to be successful.

Code

```
bool AwsDoc::S3::deleteBucket(const Aws::String &bucketName,
                              const Aws::S3::S3ClientConfiguration &clientConfig) {

    Aws::S3::S3Client client(clientConfig);

    Aws::S3::Model::DeleteBucketRequest request;
    request.SetBucket(bucketName);

    Aws::S3::Model::DeleteBucketOutcome outcome =
            client.DeleteBucket(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: deleteBucket: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() << std::endl;
    } else {
        std::cout << "The bucket was deleted" << std::endl;
    }

    return outcome.IsSuccess();
}
```

See the complete delete_bucket example on Github.

Operations on objects

An Amazon S3 object represents a *file*, which is a collection of data. Every object must reside within a bucket.

Prerequisites

Before you begin, we recommend you read Getting started using the AWS SDK for C++.

Download the example code and build the solution as described in Getting started on code examples.

To run the examples, the user profile your code uses to make the requests must have proper permissions in AWS (for the service and the action). For more information, see Providing AWS credentials.

Upload a file to a bucket

Use the `S3Client` object `PutObject` function, supplying it with a bucket name, key name, and file to upload. `Aws::FStream` is used to upload the contents of the local file to the bucket. The bucket must exist or an error will result.

For an example on uploading objects asynchronously, see Asynchronous programming using the AWS SDK for C++

Code

```
bool AwsDoc::S3::putObject(const Aws::String &bucketName,
                           const Aws::String &fileName,
                           const Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client s3Client(clientConfig);

    Aws::S3::Model::PutObjectRequest request;
    request.SetBucket(bucketName);
    //We are using the name of the file as the key for the object in the bucket.
    //However, this is just a string and can be set according to your retrieval needs.
    request.SetKey(fileName);

    std::shared_ptr<Aws::IOStream> inputData =
            Aws::MakeShared<Aws::FStream>("SampleAllocationTag",
                                          fileName.c_str(),
                                          std::ios_base::in | std::ios_base::binary);
```

```
    if (!*inputData) {
        std::cerr << "Error unable to read file " << fileName << std::endl;
        return false;
    }

    request.SetBody(inputData);

    Aws::S3::Model::PutObjectOutcome outcome =
            s3Client.PutObject(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: putObject: " <<
                  outcome.GetError().GetMessage() << std::endl;
    } else {
        std::cout << "Added object '" << fileName << "' to bucket '"
                  << bucketName << "'.";
    }

    return outcome.IsSuccess();
}
```

See the complete example on Github.

Upload a string to a bucket

Use the `S3Client` object `PutObject` function, supplying it with a bucket name, key name, and file to upload. The bucket must exist or an error will result. This example differs from the previous one by using `Aws::StringStream` to upload an in-memory string data object directly to a bucket.

For an example on uploading objects asynchronously, see Asynchronous programming using the AWS SDK for C++

Code

```
bool AwsDoc::S3::putObjectBuffer(const Aws::String &bucketName,
                                 const Aws::String &objectName,
                                 const std::string &objectContent,
                                 const Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client s3Client(clientConfig);

    Aws::S3::Model::PutObjectRequest request;
    request.SetBucket(bucketName);
```

```
    request.SetKey(objectName);

    const std::shared_ptr<Aws::IOStream> inputData =
            Aws::MakeShared<Aws::StringStream>("");
    *inputData << objectContent.c_str();

    request.SetBody(inputData);

    Aws::S3::Model::PutObjectOutcome outcome = s3Client.PutObject(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: putObjectBuffer: " <<
                  outcome.GetError().GetMessage() << std::endl;
    } else {
        std::cout << "Success: Object '" << objectName << "' with content '"
                  << objectContent << "' uploaded to bucket '" << bucketName << "'.";
    }

    return outcome.IsSuccess();
}
```

See the complete example on Github.

List objects

To get a list of objects within a bucket, use the `S3Client` object `ListObjects` function. Supply it with a `ListObjectsRequest` that you set with the name of a bucket to list the contents of.

The `ListObjects` function returns a `ListObjectsOutcome` object that you can use to get a list of objects in the form of `Object` instances.

Code

```
bool AwsDoc::S3::listObjects(const Aws::String &bucketName,
                             Aws::Vector<Aws::String> &keysResult,
                             const Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client s3Client(clientConfig);

    Aws::S3::Model::ListObjectsV2Request request;
    request.WithBucket(bucketName);

    Aws::String continuationToken; // Used for pagination.
    Aws::Vector<Aws::S3::Model::Object> allObjects;
```

```
    do {
        if (!continuationToken.empty()) {
            request.SetContinuationToken(continuationToken);
        }

        auto outcome = s3Client.ListObjectsV2(request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Error: listObjects: " <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        } else {
            Aws::Vector<Aws::S3::Model::Object> objects =
                    outcome.GetResult().GetContents();

            allObjects.insert(allObjects.end(), objects.begin(), objects.end());
            continuationToken = outcome.GetResult().GetNextContinuationToken();
        }
    } while (!continuationToken.empty());

    std::cout << allObjects.size() << " object(s) found:" << std::endl;

    for (const auto &object: allObjects) {
        std::cout << "  " << object.GetKey() << std::endl;
        keysResult.push_back(object.GetKey());
    }

    return true;
}
```

See the complete example on Github.

Download an object

Use the `S3Client` object `GetObject` function, passing it a `GetObjectRequest` that you set with the name of a bucket and the object key to download. `GetObject` returns a `GetObjectOutcome` object that consists of a `GetObjectResult` and a `S3Error`. `GetObjectResult` can be used to access the S3 object's data.

The following example downloads an object from Amazon S3. The object contents are stored in a local variable and the first line of the contents is output to the console.

Code

```
bool AwsDoc::S3::getObject(const Aws::String &objectKey,
                           const Aws::String &fromBucket,
                           const Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client client(clientConfig);

    Aws::S3::Model::GetObjectRequest request;
    request.SetBucket(fromBucket);
    request.SetKey(objectKey);

    Aws::S3::Model::GetObjectOutcome outcome =
            client.GetObject(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: getObject: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() << std::endl;
    } else {
        std::cout << "Successfully retrieved '" << objectKey << "' from '"
                  << fromBucket << "'." << std::endl;
    }

    return outcome.IsSuccess();
}
```

See the complete example on Github.

Delete an object

Use the `S3Client` object's `DeleteObject` function, passing it a `DeleteObjectRequest` that you set with the name of a bucket and object to download. *The specified bucket and object key must exist or an error will result.*

Code

```
bool AwsDoc::S3::deleteObject(const Aws::String &objectKey,
                              const Aws::String &fromBucket,
                              const Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client client(clientConfig);
    Aws::S3::Model::DeleteObjectRequest request;

    request.WithKey(objectKey)
            .WithBucket(fromBucket);
```

```
    Aws::S3::Model::DeleteObjectOutcome outcome =
            client.DeleteObject(request);

    if (!outcome.IsSuccess()) {
        auto err = outcome.GetError();
        std::cerr << "Error: deleteObject: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() << std::endl;
    } else {
        std::cout << "Successfully deleted the object." << std::endl;
    }

    return outcome.IsSuccess();
}
```

See the complete example on Github.

Managing Amazon S3 Access Permissions

Access permissions for an Amazon S3 bucket or object are defined in an access control list (ACL). The ACL specifies the owner of the bucket/object and a list of grants. Each grant specifies a user (or grantee) and the user's permissions to access the bucket/object, such as READ or WRITE access.

Prerequisites

Before you begin, we recommend you read Getting started using the AWS SDK for C++.

Download the example code and build the solution as described in Getting started on code examples.

To run the examples, the user profile your code uses to make the requests must have proper permissions in AWS (for the service and the action). For more information, see Providing AWS credentials.

Manage an Object's Access Control List

The access control list for an object can be retrieved by calling the `S3Client` method `GetObjectAcl`. The method accepts the names of the object and its bucket. The return value includes the ACL's `Owner` and list of `Grants`.

```
bool AwsDoc::S3::getObjectAcl(const Aws::String &bucketName,
                              const Aws::String &objectKey,
                              const Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client s3Client(clientConfig);
```

```
    Aws::S3::Model::GetObjectAclRequest request;
    request.SetBucket(bucketName);
    request.SetKey(objectKey);

    Aws::S3::Model::GetObjectAclOutcome outcome =
            s3Client.GetObjectAcl(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: getObjectAcl: "
                  << err.GetExceptionName() << ": " << err.GetMessage() << std::endl;
    } else {
        Aws::Vector<Aws::S3::Model::Grant> grants =
                outcome.GetResult().GetGrants();

        for (auto it = grants.begin(); it != grants.end(); it++) {
            std::cout << "For object " << objectKey << ": "
                      << std::endl << std::endl;

            Aws::S3::Model::Grant grant = *it;
            Aws::S3::Model::Grantee grantee = grant.GetGrantee();

            if (grantee.TypeHasBeenSet()) {
                std::cout << "Type:          "
                          << getGranteeTypeString(grantee.GetType()) << std::endl;
            }

            if (grantee.DisplayNameHasBeenSet()) {
                std::cout << "Display name:  "
                          << grantee.GetDisplayName() << std::endl;
            }

            if (grantee.EmailAddressHasBeenSet()) {
                std::cout << "Email address: "
                          << grantee.GetEmailAddress() << std::endl;
            }

            if (grantee.IDHasBeenSet()) {
                std::cout << "ID:            "
                          << grantee.GetID() << std::endl;
            }

            if (grantee.URIHasBeenSet()) {
```

```
                std::cout << "URI:           "
                          << grantee.GetURI() << std::endl;
            }

            std::cout << "Permission:    " <<
                      getPermissionString(grant.GetPermission()) <<
                      std::endl << std::endl;
        }
    }

    return outcome.IsSuccess();
}

//! Routine which converts a built-in type enumeration to a human-readable string.
/*!
 \param type: Type enumeration.
 \return String: Human-readable string
*/
Aws::String getGranteeTypeString(const Aws::S3::Model::Type &type) {
    switch (type) {
        case Aws::S3::Model::Type::AmazonCustomerByEmail:
            return "Email address of an AWS account";
        case Aws::S3::Model::Type::CanonicalUser:
            return "Canonical user ID of an AWS account";
        case Aws::S3::Model::Type::Group:
            return "Predefined Amazon S3 group";
        case Aws::S3::Model::Type::NOT_SET:
            return "Not set";
        default:
            return "Type unknown";
    }
}

//! Routine which converts a built-in type enumeration to a human-readable string.
/*!
 \param permission: Permission enumeration.
 \return String: Human-readable string
*/
Aws::String getPermissionString(const Aws::S3::Model::Permission &permission) {
    switch (permission) {
        case Aws::S3::Model::Permission::FULL_CONTROL:
            return "Can read this object's data and its metadata, "
                   "and read/write this object's permissions";
        case Aws::S3::Model::Permission::NOT_SET:
```

```
            return "Permission not set";
        case Aws::S3::Model::Permission::READ:
            return "Can read this object's data and its metadata";
        case Aws::S3::Model::Permission::READ_ACP:
            return "Can read this object's permissions";
            // case Aws::S3::Model::Permission::WRITE // Not applicable.
        case Aws::S3::Model::Permission::WRITE_ACP:
            return "Can write this object's permissions";
        default:
            return "Permission unknown";
    }
}
```

The ACL can be modified by either creating a new ACL or changing the grants specified in the current ACL. The updated ACL becomes the new current ACL by passing it to the `PutObjectAcl` method.

The following code uses the ACL retrieved by `GetObjectAcl` and adds a new grant to it. The user or grantee is given READ permission for the object. The modified ACL is passed to `PutObjectAcl`, making it the new current ACL.

```
bool AwsDoc::S3::putObjectAcl(const Aws::String &bucketName, const Aws::String
 &objectKey, const Aws::String &ownerID,
                               const Aws::String &granteePermission, const Aws::String
 &granteeType,
                               const Aws::String &granteeID, const Aws::String
 &granteeEmailAddress,
                               const Aws::String &granteeURI, const
 Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client s3Client(clientConfig);

    Aws::S3::Model::Owner owner;
    owner.SetID(ownerID);

    Aws::S3::Model::Grantee grantee;
    grantee.SetType(setGranteeType(granteeType));

    if (!granteeEmailAddress.empty()) {
        grantee.SetEmailAddress(granteeEmailAddress);
    }

    if (!granteeID.empty()) {
```

```
        grantee.SetID(granteeID);
    }

    if (!granteeURI.empty()) {
        grantee.SetURI(granteeURI);
    }

    Aws::S3::Model::Grant grant;
    grant.SetGrantee(grantee);
    grant.SetPermission(setGranteePermission(granteePermission));

    Aws::Vector<Aws::S3::Model::Grant> grants;
    grants.push_back(grant);

    Aws::S3::Model::AccessControlPolicy acp;
    acp.SetOwner(owner);
    acp.SetGrants(grants);

    Aws::S3::Model::PutObjectAclRequest request;
    request.SetAccessControlPolicy(acp);
    request.SetBucket(bucketName);
    request.SetKey(objectKey);

    Aws::S3::Model::PutObjectAclOutcome outcome =
            s3Client.PutObjectAcl(request);

    if (!outcome.IsSuccess()) {
        auto error = outcome.GetError();
        std::cerr << "Error: putObjectAcl: " << error.GetExceptionName()
                  << " - " << error.GetMessage() << std::endl;
    } else {
        std::cout << "Successfully added an ACL to the object '" << objectKey
                  << "' in the bucket '" << bucketName << "'." << std::endl;
    }

    return outcome.IsSuccess();
}

//! Routine which converts a human-readable string to a built-in type enumeration.
/*!
 \param access: Human readable string.
 \return Permission: Permission enumeration.
*/
Aws::S3::Model::Permission setGranteePermission(const Aws::String &access) {
```

```
    if (access == "FULL_CONTROL")
        return Aws::S3::Model::Permission::FULL_CONTROL;
    if (access == "WRITE")
        return Aws::S3::Model::Permission::WRITE;
    if (access == "READ")
        return Aws::S3::Model::Permission::READ;
    if (access == "WRITE_ACP")
        return Aws::S3::Model::Permission::WRITE_ACP;
    if (access == "READ_ACP")
        return Aws::S3::Model::Permission::READ_ACP;
    return Aws::S3::Model::Permission::NOT_SET;
}

//! Routine which converts a human-readable string to a built-in type enumeration.
/*!
 \param type: Human readable string.
 \return Type: Type enumeration.
*/
Aws::S3::Model::Type setGranteeType(const Aws::String &type) {
    if (type == "Amazon customer by email")
        return Aws::S3::Model::Type::AmazonCustomerByEmail;
    if (type == "Canonical user")
        return Aws::S3::Model::Type::CanonicalUser;
    if (type == "Group")
        return Aws::S3::Model::Type::Group;
    return Aws::S3::Model::Type::NOT_SET;
}
```

See the complete example on Github.

Manage a Bucket's Access Control List

In most cases, the preferred method for setting the access permissions of a bucket is to define a bucket policy. However, buckets also support access control lists for users who wish to use them.

Management of an access control list for a bucket is identical to that used for an object. The `GetBucketAcl` method retrieves a bucket's current ACL and `PutBucketAcl` applies a new ACL to the bucket.

The following code demonstrates getting and setting a bucket ACL.

```
//! Routine which demonstrates setting the ACL for an S3 bucket.
/*!
  \param bucketName: Name of a bucket.
  \param ownerID: The canonical ID of the bucket owner.
   See https://docs.aws.amazon.com/AmazonS3/latest/userguide/finding-canonical-user-
id.html for more information.
  \param granteePermission: The access level to enable for the grantee.
  \param granteeType: The type of grantee.
  \param granteeID: The canonical ID of the grantee.
  \param granteeEmailAddress: The email address associated with the grantee's AWS
 account.
  \param granteeURI: The URI of a built-in access group.
  \param clientConfig: Aws client configuration.
  \return bool: Function succeeded.
*/

bool AwsDoc::S3::getPutBucketAcl(const Aws::String &bucketName,
                                 const Aws::String &ownerID,
                                 const Aws::String &granteePermission,
                                 const Aws::String &granteeType,
                                 const Aws::String &granteeID,
                                 const Aws::String &granteeEmailAddress,
                                 const Aws::String &granteeURI,
                                 const Aws::S3::S3ClientConfiguration &clientConfig) {
    bool result = ::putBucketAcl(bucketName, ownerID, granteePermission, granteeType,
                                 granteeID,
                                 granteeEmailAddress,
                                 granteeURI,
                                 clientConfig);
    if (result) {
        result = ::getBucketAcl(bucketName, clientConfig);
    }

    return result;
}

//! Routine which demonstrates setting the ACL for an S3 bucket.
/*!
  \param bucketName: Name of from bucket.
  \param ownerID: The canonical ID of the bucket owner.
   See https://docs.aws.amazon.com/AmazonS3/latest/userguide/finding-canonical-user-
id.html for more information.
  \param granteePermission: The access level to enable for the grantee.
  \param granteeType: The type of grantee.
```

```
  \param granteeID: The canonical ID of the grantee.
  \param granteeEmailAddress: The email address associated with the grantee's AWS
 account.
  \param granteeURI: The URI of a built-in access group.
  \param clientConfig: Aws client configuration.
  \return bool: Function succeeded.
*/

bool putBucketAcl(const Aws::String &bucketName,
                  const Aws::String &ownerID,
                  const Aws::String &granteePermission,
                  const Aws::String &granteeType,
                  const Aws::String &granteeID,
                  const Aws::String &granteeEmailAddress,
                  const Aws::String &granteeURI,
                  const Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client s3Client(clientConfig);

    Aws::S3::Model::Owner owner;
    owner.SetID(ownerID);

    Aws::S3::Model::Grantee grantee;
    grantee.SetType(setGranteeType(granteeType));

    if (!granteeEmailAddress.empty()) {
        grantee.SetEmailAddress(granteeEmailAddress);
    }

    if (!granteeID.empty()) {
        grantee.SetID(granteeID);
    }

    if (!granteeURI.empty()) {
        grantee.SetURI(granteeURI);
    }

    Aws::S3::Model::Grant grant;
    grant.SetGrantee(grantee);
    grant.SetPermission(setGranteePermission(granteePermission));

    Aws::Vector<Aws::S3::Model::Grant> grants;
    grants.push_back(grant);

    Aws::S3::Model::AccessControlPolicy acp;
```

```
    acp.SetOwner(owner);
    acp.SetGrants(grants);

    Aws::S3::Model::PutBucketAclRequest request;
    request.SetAccessControlPolicy(acp);
    request.SetBucket(bucketName);

    Aws::S3::Model::PutBucketAclOutcome outcome =
            s3Client.PutBucketAcl(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &error = outcome.GetError();

        std::cerr << "Error: putBucketAcl: " << error.GetExceptionName()
                  << " - " << error.GetMessage() << std::endl;
    } else {
        std::cout << "Successfully added an ACL to the bucket '" << bucketName
                  << "'." << std::endl;
    }

    return outcome.IsSuccess();
}

//! Routine which demonstrates getting the ACL for an S3 bucket.
/*!
  \param bucketName: Name of the s3 bucket.
  \param clientConfig: Aws client configuration.
  \return bool: Function succeeded.
*/
bool getBucketAcl(const Aws::String &bucketName,
                  const Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client s3Client(clientConfig);

    Aws::S3::Model::GetBucketAclRequest request;
    request.SetBucket(bucketName);

    Aws::S3::Model::GetBucketAclOutcome outcome =
            s3Client.GetBucketAcl(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: getBucketAcl: "
                  << err.GetExceptionName() << ": " << err.GetMessage() << std::endl;
    } else {
```

```
        const Aws::Vector<Aws::S3::Model::Grant> &grants =
                outcome.GetResult().GetGrants();

        for (const Aws::S3::Model::Grant &grant: grants) {
            const Aws::S3::Model::Grantee &grantee = grant.GetGrantee();

            std::cout << "For bucket " << bucketName << ": "
                      << std::endl << std::endl;

            if (grantee.TypeHasBeenSet()) {
                std::cout << "Type:          "
                          << getGranteeTypeString(grantee.GetType()) << std::endl;
            }

            if (grantee.DisplayNameHasBeenSet()) {
                std::cout << "Display name:  "
                          << grantee.GetDisplayName() << std::endl;
            }

            if (grantee.EmailAddressHasBeenSet()) {
                std::cout << "Email address: "
                          << grantee.GetEmailAddress() << std::endl;
            }

            if (grantee.IDHasBeenSet()) {
                std::cout << "ID:            "
                          << grantee.GetID() << std::endl;
            }

            if (grantee.URIHasBeenSet()) {
                std::cout << "URI:           "
                          << grantee.GetURI() << std::endl;
            }

            std::cout << "Permission:    " <<
                      getPermissionString(grant.GetPermission()) <<
                      std::endl << std::endl;
        }
    }

    return outcome.IsSuccess();
}

//! Routine which converts a built-in type enumeration to a human-readable string.
```

```
/*!
 \param permission: Permission enumeration.
 \return String: Human-readable string.
*/

Aws::String getPermissionString(const Aws::S3::Model::Permission &permission) {
    switch (permission) {
        case Aws::S3::Model::Permission::FULL_CONTROL:
            return "Can list objects in this bucket, create/overwrite/delete "
                   "objects in this bucket, and read/write this "
                   "bucket's permissions";
        case Aws::S3::Model::Permission::NOT_SET:
            return "Permission not set";
        case Aws::S3::Model::Permission::READ:
            return "Can list objects in this bucket";
        case Aws::S3::Model::Permission::READ_ACP:
            return "Can read this bucket's permissions";
        case Aws::S3::Model::Permission::WRITE:
            return "Can create, overwrite, and delete objects in this bucket";
        case Aws::S3::Model::Permission::WRITE_ACP:
            return "Can write this bucket's permissions";
        default:
            return "Permission unknown";
    }
}

//! Routine which converts a human-readable string to a built-in type enumeration
/*!
 \param access: Human readable string.
 \return Permission: Permission enumeration.
*/
Aws::S3::Model::Permission setGranteePermission(const Aws::String &access) {
    if (access == "FULL_CONTROL")
        return Aws::S3::Model::Permission::FULL_CONTROL;
    if (access == "WRITE")
        return Aws::S3::Model::Permission::WRITE;
    if (access == "READ")
        return Aws::S3::Model::Permission::READ;
    if (access == "WRITE_ACP")
        return Aws::S3::Model::Permission::WRITE_ACP;
    if (access == "READ_ACP")
        return Aws::S3::Model::Permission::READ_ACP;
    return Aws::S3::Model::Permission::NOT_SET;
}
```

```
//! Routine which converts a built-in type enumeration to a human-readable string.
/*!
 \param type: Type enumeration.
 \return bool: Human-readable string.
*/
Aws::String getGranteeTypeString(const Aws::S3::Model::Type &type) {
    switch (type) {
        case Aws::S3::Model::Type::AmazonCustomerByEmail:
            return "Email address of an AWS account";
        case Aws::S3::Model::Type::CanonicalUser:
            return "Canonical user ID of an AWS account";
        case Aws::S3::Model::Type::Group:
            return "Predefined Amazon S3 group";
        case Aws::S3::Model::Type::NOT_SET:
            return "Not set";
        default:
            return "Type unknown";
    }
}

Aws::S3::Model::Type setGranteeType(const Aws::String &type) {
    if (type == "Amazon customer by email")
        return Aws::S3::Model::Type::AmazonCustomerByEmail;
    if (type == "Canonical user")
        return Aws::S3::Model::Type::CanonicalUser;
    if (type == "Group")
        return Aws::S3::Model::Type::Group;
    return Aws::S3::Model::Type::NOT_SET;
}
```

See the complete example on Github.

Managing Access to Amazon S3 Buckets Using Bucket Policies

You can set, get, or delete a *bucket policy* to manage access to your Amazon S3 buckets.

Prerequisites

Before you begin, we recommend you read Getting started using the AWS SDK for C++.

Download the example code and build the solution as described in Getting started on code examples.

To run the examples, the user profile your code uses to make the requests must have proper permissions in AWS (for the service and the action). For more information, see Providing AWS credentials.

Set a Bucket Policy

You can set the bucket policy for a particular S3 bucket by calling the `S3Client`'s `PutBucketPolicy` function and providing it with the bucket name and policy's JSON representation in a PutBucketPolicyRequest.

Code

```
//! Build a policy JSON string.
/*!
  \param userArn: Aws user Amazon Resource Name (ARN).
      For more information, see https://docs.aws.amazon.com/IAM/latest/UserGuide/
reference_identifiers.html#identifiers-arns.
  \param bucketName: Name of a bucket.
  \return String: Policy as JSON string.
*/

Aws::String getPolicyString(const Aws::String &userArn,
                            const Aws::String &bucketName) {
    return
            "{\n"
            "   \"Version\":\"2012-10-17\",\n"
            "   \"Statement\":[\n"
            "       {\n"
            "           \"Sid\": \"1\",\n"
            "           \"Effect\": \"Allow\",\n"
            "           \"Principal\": {\n"
            "               \"AWS\": \""
            + userArn +
            "\"\n""           },\n"
            "           \"Action\": [ \"s3:getObject\" ],\n"
            "           \"Resource\": [ \"arn:aws:s3:::"
            + bucketName +
            "/*\" ]\n"
            "       }\n"
            "   ]\n"
            "}";
}
```

```
bool AwsDoc::S3::putBucketPolicy(const Aws::String &bucketName,
                                 const Aws::String &policyBody,
                                 const Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client s3Client(clientConfig);

    std::shared_ptr<Aws::StringStream> request_body =
            Aws::MakeShared<Aws::StringStream>("");
    *request_body << policyBody;

    Aws::S3::Model::PutBucketPolicyRequest request;
    request.SetBucket(bucketName);
    request.SetBody(request_body);

    Aws::S3::Model::PutBucketPolicyOutcome outcome =
            s3Client.PutBucketPolicy(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: putBucketPolicy: "
                  << outcome.GetError().GetMessage() << std::endl;
    } else {
        std::cout << "Set the following policy body for the bucket '" <<
                  bucketName << "':" << std::endl << std::endl;
        std::cout << policyBody << std::endl;
    }

    return outcome.IsSuccess();
}
```

Note

The Aws::Utils::Json::JsonValue utility class can be used to help you construct valid JSON objects to pass to `PutBucketPolicy`.

See the complete example on Github.

Get a Bucket Policy

To retrieve the policy for an Amazon S3 bucket, call the `S3Client`'s `GetBucketPolicy` function, passing it the name of the bucket in a GetBucketPolicyRequest.

Code

```
bool AwsDoc::S3::getBucketPolicy(const Aws::String &bucketName,
                                 const Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client s3Client(clientConfig);

    Aws::S3::Model::GetBucketPolicyRequest request;
    request.SetBucket(bucketName);

    Aws::S3::Model::GetBucketPolicyOutcome outcome =
            s3Client.GetBucketPolicy(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: getBucketPolicy: "
                  << err.GetExceptionName() << ": " << err.GetMessage() << std::endl;
    } else {
        Aws::StringStream policy_stream;
        Aws::String line;

        outcome.GetResult().GetPolicy() >> line;
        policy_stream << line;

        std::cout << "Retrieve the policy for bucket '" << bucketName << "':\n\n" <<
                  policy_stream.str() << std::endl;
    }

    return outcome.IsSuccess();
}
```

See the complete example on Github.

Delete a Bucket Policy

To delete a bucket policy, call the `S3Client`'s `DeleteBucketPolicy` function, providing it with the bucket name in a DeleteBucketPolicyRequest.

Code

```
bool AwsDoc::S3::deleteBucketPolicy(const Aws::String &bucketName,
                                    const Aws::S3::S3ClientConfiguration &clientConfig)
 {
    Aws::S3::S3Client client(clientConfig);
```

```
    Aws::S3::Model::DeleteBucketPolicyRequest request;
    request.SetBucket(bucketName);

    Aws::S3::Model::DeleteBucketPolicyOutcome outcome =
 client.DeleteBucketPolicy(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: deleteBucketPolicy: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() << std::endl;
    } else {
        std::cout << "Policy was deleted from the bucket." << std::endl;
    }

    return outcome.IsSuccess();
}
```

This function succeeds even if the bucket doesn't already have a policy. If you specify a bucket name that doesn't exist or if you don't have access to the bucket, an `AmazonServiceException` is thrown.

See the complete example on Github.

More Info

- PutBucketPolicy in the Amazon Simple Storage Service API Reference
- GetBucketPolicy in the Amazon Simple Storage Service API Reference
- DeleteBucketPolicy in the Amazon Simple Storage Service API Reference
- Access Policy Language Overview in the Amazon Simple Storage Service User Guide
- Bucket Policy Examples in the Amazon Simple Storage Service User Guide

Configuring an Amazon S3 Bucket as a Website

You can configure an Amazon S3 bucket to behave as a website. To do this, you need to set its website configuration.

Prerequisites

Before you begin, we recommend you read Getting started using the AWS SDK for C++.

Download the example code and build the solution as described in Getting started on code examples.

To run the examples, the user profile your code uses to make the requests must have proper permissions in AWS (for the service and the action). For more information, see Providing AWS credentials.

Set a Bucket's Website Configuration

To set an Amazon S3 bucket's website configuration, call the `S3Client`'s `PutBucketWebsite` function with a PutBucketWebsiteRequest object containing the bucket name and its website configuration, provided in a WebsiteConfiguration object.

Setting an index document is *required*; all other parameters are optional.

Code

```
bool AwsDoc::S3::putWebsiteConfig(const Aws::String &bucketName,
                                  const Aws::String &indexPage, const Aws::String
 &errorPage,
                                  const Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client client(clientConfig);

    Aws::S3::Model::IndexDocument indexDocument;
    indexDocument.SetSuffix(indexPage);

    Aws::S3::Model::ErrorDocument errorDocument;
    errorDocument.SetKey(errorPage);

    Aws::S3::Model::WebsiteConfiguration websiteConfiguration;
    websiteConfiguration.SetIndexDocument(indexDocument);
    websiteConfiguration.SetErrorDocument(errorDocument);

    Aws::S3::Model::PutBucketWebsiteRequest request;
    request.SetBucket(bucketName);
    request.SetWebsiteConfiguration(websiteConfiguration);

    Aws::S3::Model::PutBucketWebsiteOutcome outcome =
            client.PutBucketWebsite(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: PutBucketWebsite: "
                  << outcome.GetError().GetMessage() << std::endl;
```

```
    } else {
        std::cout << "Success: Set website configuration for bucket '"
                  << bucketName << "'." << std::endl;
    }

    return outcome.IsSuccess();
}
```

> **Note**
>
> Setting a website configuration does not modify the access permissions for your bucket. To make your files visible on the web, you will also need to set a *bucket policy* that allows public read access to the files in the bucket. For more information, see Managing Access to Amazon S3 Buckets Using Bucket Policies.

See the complete example on Github.

Get a Bucket's Website Configuration

To get an Amazon S3 bucket's website configuration, call the `S3Client`'s `GetBucketWebsite` function with a GetBucketWebsiteRequest containing the name of the bucket to retrieve the configuration for.

The configuration will be returned as a GetBucketWebsiteResult object within the outcome object. If there is no website configuration for the bucket, then `null` will be returned.

Code

```
bool AwsDoc::S3::getWebsiteConfig(const Aws::String &bucketName,
                                  const Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client s3Client(clientConfig);

    Aws::S3::Model::GetBucketWebsiteRequest request;
    request.SetBucket(bucketName);

    Aws::S3::Model::GetBucketWebsiteOutcome outcome =
            s3Client.GetBucketWebsite(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
```

```
        std::cerr << "Error: GetBucketWebsite: "
                  << err.GetMessage() << std::endl;
    } else {
        Aws::S3::Model::GetBucketWebsiteResult websiteResult = outcome.GetResult();

        std::cout << "Success: GetBucketWebsite: "
                  << std::endl << std::endl
                  << "For bucket '" << bucketName << "':"
                  << std::endl
                  << "Index page : "
                  << websiteResult.GetIndexDocument().GetSuffix()
                  << std::endl
                  << "Error page: "
                  << websiteResult.GetErrorDocument().GetKey()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

See the complete example on Github.

Delete a Bucket's Website Configuration

To delete an Amazon S3 bucket's website configuration, call the `S3Client`'s `DeleteBucketWebsite` function with a DeleteBucketWebsiteRequest: containing the name of the bucket to delete the configuration from.

Code

```
bool AwsDoc::S3::deleteBucketWebsite(const Aws::String &bucketName,
                                     const Aws::S3::S3ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client client(clientConfig);
    Aws::S3::Model::DeleteBucketWebsiteRequest request;
    request.SetBucket(bucketName);

    Aws::S3::Model::DeleteBucketWebsiteOutcome outcome =
            client.DeleteBucketWebsite(request);

    if (!outcome.IsSuccess()) {
        auto err = outcome.GetError();
```

```
        std::cerr << "Error: deleteBucketWebsite: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() << std::endl;
    } else {
        std::cout << "Website configuration was removed." << std::endl;
    }

    return outcome.IsSuccess();
}
```

See the complete example on Github.

More Information

- PUT Bucket website in the Amazon Simple Storage Service API Reference
- GET Bucket website in the Amazon Simple Storage Service API Reference
- DELETE Bucket website in the Amazon Simple Storage Service API Reference

Using TransferManager for Amazon S3 operations

You can use the AWS SDK for C++ `TransferManager` class to reliably transfer files from the local environment to Amazon S3 and to copy objects from one Amazon S3 location to another. `TransferManager` can get the progress of a transfer and pause or resume uploads and downloads.

> **Note**
>
> To avoid being charged for incomplete or partial uploads, we recommend that you enable the AbortIncompleteMultipartUpload lifecycle rule on your Amazon S3 buckets.
> This rule directs Amazon S3 to abort multipart uploads that don't complete within a specified number of days after being initiated. When the set time limit is exceeded, Amazon S3 aborts the upload and then deletes the incomplete upload data.
> For more information, see Setting lifecycle configuration on a bucket in the Amazon S3 User Guide.

Prerequisites

Before you begin, we recommend you read Getting started using the AWS SDK for C++.

Download the example code and build the solution as described in Getting started on code examples.

To run the examples, the user profile your code uses to make the requests must have proper permissions in AWS (for the service and the action). For more information, see Providing AWS credentials.

Upload and download of object using `TransferManager`

This example demonstrates how `TransferManager` transfers large object in memory. `UploadFile` and `DownloadFile` methods are both called asynchronously and return a `TransferHandle` to manage the status of your request. If the object uploaded is larger than `bufferSize` then a multipart upload will be performed. The `bufferSize` defaults to 5MB, but this can be configured via `TransferManagerConfiguration`.

```
        auto s3_client = Aws::MakeShared<Aws::S3::S3Client>("S3Client");
        auto executor =
Aws::MakeShared<Aws::Utils::Threading::PooledThreadExecutor>("executor", 25);
        Aws::Transfer::TransferManagerConfiguration transfer_config(executor.get());
        transfer_config.s3Client = s3_client;

        // Create buffer to hold data received by the data stream.
        Aws::Utils::Array<unsigned char> buffer(BUFFER_SIZE);

        // The local variable 'streamBuffer' is captured by reference in a lambda.
        // It must persist until all downloading by the 'transfer_manager' is complete.
        Stream::PreallocatedStreamBuf streamBuffer(buffer.GetUnderlyingData(),
buffer.GetLength());

        auto transfer_manager =
Aws::Transfer::TransferManager::Create(transfer_config);

        auto uploadHandle = transfer_manager->UploadFile(LOCAL_FILE, BUCKET, KEY,
"text/plain", Aws::Map<Aws::String, Aws::String>());
        uploadHandle->WaitUntilFinished();
        bool success = uploadHandle->GetStatus() ==
Transfer::TransferStatus::COMPLETED;

        if (!success)
        {
            auto err = uploadHandle->GetLastError();
            std::cout << "File upload failed:  "<< err.GetMessage() << std::endl;
        }
```

```
        else
        {
            std::cout << "File upload finished." << std::endl;

            auto downloadHandle = transfer_manager->DownloadFile(BUCKET,
                KEY,
                [&]() { //Define a lambda expression for the callback method parameter
to stream back the data.
                    return Aws::New<MyUnderlyingStream>("TestTag", &streamBuffer);
                });
            downloadHandle->WaitUntilFinished();// Block calling thread until download
is complete.
            auto downStat = downloadHandle->GetStatus();
            if (downStat != Transfer::TransferStatus::COMPLETED)
            {
                auto err = downloadHandle->GetLastError();
                std::cout << "File download failed:  " << err.GetMessage() <<
std::endl;
            }
            std::cout << "File download to memory finished."  << std::endl;
```

See the complete example on Github.

Using `S3CrtClient` for Amazon S3 operations

The `S3CrtClient` class is available in version 1.9 of the AWS SDK for C++ and improves the throughput of uploading and downloading large data files to and from Amazon S3. For more information on the improvements of this release, see Improving Amazon S3 Throughput with AWS SDK for C++ v1.9

The `S3CrtClient` is implemented on the top of the AWS Common Runtime (CRT) libraries.

> **Note**
>
> To avoid being charged for incomplete or partial uploads, we recommend that you enable the AbortIncompleteMultipartUpload lifecycle rule on your Amazon S3 buckets.
> This rule directs Amazon S3 to abort multipart uploads that don't complete within a specified number of days after being initiated. When the set time limit is exceeded, Amazon S3 aborts the upload and then deletes the incomplete upload data.
> For more information, see Setting lifecycle configuration on a bucket in the Amazon S3 User Guide.

Prerequisites

Before you begin, we recommend you read Getting started using the AWS SDK for C++.

Download the example code and build the solution as described in Getting started on code examples.

To run the examples, the user profile your code uses to make the requests must have proper permissions in AWS (for the service and the action). For more information, see Providing AWS credentials.

Upload and download of object using `S3CrtClient`

This example demonstrates how to use the `S3CrtClient`. The example creates a bucket, uploads an object, downloads the object, then deletes the file and the bucket. A PUT operation turns into a multipart upload. A GET operation turns into multiple "ranged" GET requests. For more information on multipart uploads, see Uploading and copying objects using multipart upload in the Amazon S3 User Guide.

The provided data file, `ny.json`, gets uploaded as a multipart upload in this example. This can be confirmed by viewing the debug logs after a successful run of the program.

If the upload fails, an `AbortMultipartUpload` is issued in the underlying CRT library to clean up any already-uploaded parts. However, not all failures can be handled internally (such as a network cable being unplugged). It is recommended to create a lifecycle rule on your Amazon S3 bucket to ensure partially uploaded data does not linger on your account (partially uploaded data is still billable). To find out how to set up a lifecycle rule, see Discovering and Deleting Incomplete Multipart Uploads to Lower Amazon S3 Costs.

Using the debug log to explore multipart upload details

1. In `main()`, note that there are "TODO" comments with instructions for updating the code.
    a. For `file_name`: From the link provided in the code comment download sample data file `ny.json`, or use a large data file of your own.
    b. For `region`: Update the `region` variable, using the enum, to the AWS Region of your account. To find your Region of your account, log into the AWS Management Console, and locate the Region in the upper right-hand corner.
2. Build the example.

3. Copy the file specified by variable `file_name` to your executable folder and run the `s3-crt-demo` executable.
4. In your executable folder, find the most recent `.log` file.
5. Open the log file, select **search**, and enter **`partNumber`**.
6. The log contains entries similar to the following, where the `partNumber` and `uploadId` are specified for each portion of the uploaded file:

   ```
   PUT /my-object
   partNumber=1&uploadId=gsk8vDbmnlA5EseDo._LDEgq22Qmt0SeuszYxMsZ9ABt503VqDIFOP8
   content-length:8388608 host:my-bucketasdfasdf.s3.us-
   east-2.amazonaws.com x-amz-content-sha256:UNSIGNED-PAYLOAD
   ```

   and

   ```
   PUT /my-object
   partNumber=2&uploadId=gsk8vDbmnlA5EseDo._LDEgq22Qmt0SeuszYxMsZ9ABt503VqDIFOP8
   content-length:8388608 host:my-bucketasdfasdf.s3.us-
   east-2.amazonaws.com x-amz-content-sha256:UNSIGNED-PAYLOAD
   ```

See the complete example on Github.

Amazon SQS code examples using the AWS SDK for C++

Amazon Simple Queue Service (Amazon SQS) is a fully managed message queuing service that makes it easy to decouple and scale microservices, distributed systems, and serverless applications. You can use the following examples to program Amazon SQS using the AWS SDK for C++.

> **Note**
>
> Only the code that is necessary to demonstrate certain techniques is supplied in this Guide, but the complete example code is available on GitHub. On GitHub you can download a single source file or you can clone the repository locally to get, build, and run all examples.

Topics

- Working with Amazon SQS Message Queues
- Sending, Receiving, and Deleting Amazon SQS Messages

- Enabling Long Polling for Amazon SQS Message Queues
- Setting Visibility Timeout in Amazon SQS
- Using Dead Letter Queues in Amazon SQS

Working with Amazon SQS Message Queues

A *message queue* is the logical container you use to send messages reliably in Amazon SQS. There are two types of queues: *standard* and *first-in, first-out* (FIFO). To learn more about queues and the differences between these types, see the Amazon Simple Queue Service Developer Guide.

These C++ examples show you how to use the AWS SDK for C++ to create, list, delete, and get the URL of an Amazon SQS queue.

Prerequisites

Before you begin, we recommend you read Getting started using the AWS SDK for C++.

Download the example code and build the solution as described in Getting started on code examples.

To run the examples, the user profile your code uses to make the requests must have proper permissions in AWS (for the service and the action). For more information, see Providing AWS credentials.

Create a Queue

Use the SQSClient class `CreateQueue` member function, and provide it with a CreateQueueRequest object that describes the queue parameters.

Includes

```
#include <aws/core/Aws.h>
#include <aws/sqs/SQSClient.h>
#include <aws/sqs/model/CreateQueueRequest.h>
#include <iostream>
```

Code

```
    Aws::SQS::SQSClient sqsClient(clientConfiguration);
```

```
    Aws::SQS::Model::CreateQueueRequest request;
    request.SetQueueName(queueName);

    const Aws::SQS::Model::CreateQueueOutcome outcome = sqsClient.CreateQueue(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully created queue " << queueName << " with a queue URL "
                  << outcome.GetResult().GetQueueUrl() << "." << std::endl;
    }
    else {
        std::cerr << "Error creating queue " << queueName << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
```

See the complete example.

List Queues

To list Amazon SQS queues for your account, call the SQSClient class `ListQueues` member function, and pass it a ListQueuesRequest object.

Includes

```
#include <aws/core/Aws.h>
#include <aws/sqs/SQSClient.h>
#include <aws/sqs/model/ListQueuesRequest.h>
#include <iostream>
```

Code

```
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::ListQueuesRequest listQueuesRequest;

    Aws::String nextToken; // Used for pagination.
    Aws::Vector<Aws::String> allQueueUrls;

    do {
        if (!nextToken.empty()) {
            listQueuesRequest.SetNextToken(nextToken);
        }
        const Aws::SQS::Model::ListQueuesOutcome outcome = sqsClient.ListQueues(
                listQueuesRequest);
        if (outcome.IsSuccess()) {
```

```
            const Aws::Vector<Aws::String> &queueUrls =
outcome.GetResult().GetQueueUrls();
            allQueueUrls.insert(allQueueUrls.end(),
                                queueUrls.begin(),
                                queueUrls.end());

            nextToken = outcome.GetResult().GetNextToken();
        }
        else {
            std::cerr << "Error listing queues: " <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }

    } while (!nextToken.empty());

    std::cout << allQueueUrls.size() << " Amazon SQS queue(s) found." << std::endl;
    for (const auto &iter: allQueueUrls) {
        std::cout << " " << iter << std::endl;
    }
```

See the complete example.

Get the Queue's URL

To get the URL for an existing Amazon SQS queue, call the SQSClient class `GetQueueUrl` member function.

Includes

```
#include <aws/core/Aws.h>
#include <aws/sqs/SQSClient.h>
#include <aws/sqs/model/GetQueueUrlRequest.h>
#include <iostream>
```

Code

```
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::GetQueueUrlRequest request;
    request.SetQueueName(queueName);

    const Aws::SQS::Model::GetQueueUrlOutcome outcome = sqsClient.GetQueueUrl(request);
```

```
    if (outcome.IsSuccess()) {
        std::cout << "Queue " << queueName << " has url " <<
                  outcome.GetResult().GetQueueUrl() << std::endl;
    }
    else {
        std::cerr << "Error getting url for queue " << queueName << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
```

See the complete example.

Delete a Queue

Provide the URL to the SQSClient class `DeleteQueue` member function.

Includes

```
#include <aws/core/Aws.h>
#include <aws/core/client/DefaultRetryStrategy.h>
#include <aws/sqs/SQSClient.h>
#include <aws/sqs/model/DeleteQueueRequest.h>
#include <iostream>
```

Code

```
    Aws::SQS::Model::DeleteQueueRequest request;
    request.SetQueueUrl(queueURL);

    const Aws::SQS::Model::DeleteQueueOutcome outcome = sqsClient.DeleteQueue(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted queue with url " << queueURL <<
                  std::endl;
    }
    else {
        std::cerr << "Error deleting queue " << queueURL << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
```

See the complete example.

More Info

- How Amazon SQS Queues Work in the Amazon Simple Queue Service Developer Guide

- CreateQueue in the Amazon Simple Queue Service API Reference
- GetQueueUrl in the Amazon Simple Queue Service API Reference
- ListQueues in the Amazon Simple Queue Service API Reference
- DeleteQueues in the Amazon Simple Queue Service API Reference

Sending, Receiving, and Deleting Amazon SQS Messages

Messages are always delivered using an SQS queue. These C++ examples show you how to use the AWS SDK for C++ to send, receive, and delete Amazon SQS messages from SQS queues.

Prerequisites

Before you begin, we recommend you read Getting started using the AWS SDK for C++.

Download the example code and build the solution as described in Getting started on code examples.

To run the examples, the user profile your code uses to make the requests must have proper permissions in AWS (for the service and the action). For more information, see Providing AWS credentials.

Send a Message

You can add a single message to an Amazon SQS queue by calling the SQSClient class `SendMessage` member function. You provide `SendMessage` with a SendMessageRequest object containing the queue's URL, the message body, and an optional delay value (in seconds).

Includes

```
#include <aws/core/Aws.h>
#include <aws/sqs/SQSClient.h>
#include <aws/sqs/model/SendMessageRequest.h>
#include <iostream>
```

Code

```
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::SendMessageRequest request;
    request.SetQueueUrl(queueUrl);
```

```
    request.SetMessageBody(messageBody);

    const Aws::SQS::Model::SendMessageOutcome outcome = sqsClient.SendMessage(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully sent message to " << queueUrl <<
                  std::endl;
    }
    else {
        std::cerr << "Error sending message to " << queueUrl << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
```

See the complete example.

Receive Messages

Retrieve any messages that are currently in the queue by calling the SQSClient class `ReceiveMessage` member function, passing it the queue's URL. Messages are returned as a list of Message objects.

Includes

```
#include <aws/core/Aws.h>
#include <aws/sqs/SQSClient.h>
#include <aws/sqs/model/ReceiveMessageRequest.h>
#include <iostream>
```

Code

```
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::ReceiveMessageRequest request;
    request.SetQueueUrl(queueUrl);
    request.SetMaxNumberOfMessages(1);

    const Aws::SQS::Model::ReceiveMessageOutcome outcome = sqsClient.ReceiveMessage(
            request);
    if (outcome.IsSuccess()) {

        const Aws::Vector<Aws::SQS::Model::Message> &messages =
                outcome.GetResult().GetMessages();
        if (!messages.empty()) {
```

```
            const Aws::SQS::Model::Message &message = messages[0];
            std::cout << "Received message:" << std::endl;
            std::cout << "  MessageId: " << message.GetMessageId() << std::endl;
            std::cout << "  ReceiptHandle: " << message.GetReceiptHandle() <<
 std::endl;
            std::cout << "  Body: " << message.GetBody() << std::endl << std::endl;
        }
        else {
            std::cout << "No messages received from queue " << queueUrl <<
                      std::endl;

        }
    }
    else {
        std::cerr << "Error receiving message from queue " << queueUrl << ": "
                  << outcome.GetError().GetMessage() << std::endl;
    }
```

See the complete example.

Delete Messages after Receipt

After receiving a message and processing its contents, delete the message from the queue by sending the message's receipt handle and the queue URL to the SQSClient class `DeleteMessage` member function.

Includes

```
#include <aws/core/Aws.h>
#include <aws/sqs/SQSClient.h>
#include <aws/sqs/model/DeleteMessageRequest.h>
#include <iostream>
```

Code

```
    Aws::SQS::Model::DeleteMessageRequest request;
    request.SetQueueUrl(queueUrl);
    request.SetReceiptHandle(messageReceiptHandle);

    const Aws::SQS::Model::DeleteMessageOutcome outcome = sqsClient.DeleteMessage(
            request);
    if (outcome.IsSuccess()) {
```

```
        std::cout << "Successfully deleted message from queue " << queueUrl
                  << std::endl;
    }
    else {
        std::cerr << "Error deleting message from queue " << queueUrl << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
```

See the complete example.

More Info

- How Amazon SQS Queues Work in the Amazon Simple Queue Service Developer Guide
- SendMessage in the Amazon Simple Queue Service API Reference
- SendMessageBatch in the Amazon Simple Queue Service API Reference
- ReceiveMessage in the Amazon Simple Queue Service API Reference
- DeleteMessage in the Amazon Simple Queue Service API Reference

Enabling Long Polling for Amazon SQS Message Queues

Amazon SQS uses *short polling* by default, querying only a subset of the servers—based on a weighted random distribution—to determine whether any messages are available for inclusion in the response.

Long polling helps reduce your cost of using Amazon SQS by reducing the number of empty responses when there are no messages available to return in reply to a ReceiveMessage request sent to an Amazon SQS queue and eliminating false empty responses. You can set a long polling frequency from *1–20 seconds*.

Prerequisites

Before you begin, we recommend you read Getting started using the AWS SDK for C++.

Download the example code and build the solution as described in Getting started on code examples.

To run the examples, the user profile your code uses to make the requests must have proper permissions in AWS (for the service and the action). For more information, see Providing AWS credentials.

Enable Long Polling when Creating a Queue

To enable long polling when creating an Amazon SQS queue, set the `ReceiveMessageWaitTimeSeconds` attribute on the CreateQueueRequest object before calling the SQSClient class' `CreateQueue` member function.

Includes

```
#include <aws/core/Aws.h>
#include <aws/sqs/SQSClient.h>
#include <aws/sqs/model/CreateQueueRequest.h>
#include <iostream>
```

Code

```
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::CreateQueueRequest request;
    request.SetQueueName(queueName);
    request.AddAttributes(
            Aws::SQS::Model::QueueAttributeName::ReceiveMessageWaitTimeSeconds,
            pollTimeSeconds);

    const Aws::SQS::Model::CreateQueueOutcome outcome = sqsClient.CreateQueue(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully created queue " << queueName <<
                  std::endl;
    }
    else {
        std::cout << "Error creating queue " << queueName << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
```

See the complete example.

Enable Long Polling on an Existing Queue

In addition to enabling long polling when creating a queue, you can also enable it on an existing queue by setting `ReceiveMessageWaitTimeSeconds` on the SetQueueAttributesRequest before calling the SQSClient class' `SetQueueAttributes` member function.

Includes

```
#include <aws/core/Aws.h>
#include <aws/sqs/SQSClient.h>
#include <aws/sqs/model/SetQueueAttributesRequest.h>
#include <iostream>
```

Code

```
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::SetQueueAttributesRequest request;
    request.SetQueueUrl(queueURL);
    request.AddAttributes(
            Aws::SQS::Model::QueueAttributeName::ReceiveMessageWaitTimeSeconds,
            pollTimeSeconds);

    const Aws::SQS::Model::SetQueueAttributesOutcome outcome =
sqsClient.SetQueueAttributes(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully updated long polling time for queue " <<
                  queueURL << " to " << pollTimeSeconds << std::endl;
    }
    else {
        std::cout << "Error updating long polling time for queue " <<
                  queueURL << ": " << outcome.GetError().GetMessage() <<
                  std::endl;
    }
```

See the complete example.

Enable Long Polling on Message Receipt

You can enable long polling when receiving a message by setting the wait time in seconds on the ReceiveMessageRequest that you supply to the SQSClient class' ReceiveMessage member function.

> **Note**
>
> You should make sure that the AWS client's request timeout is larger than the maximum long poll time (20s) so that your `ReceiveMessage` requests don't time out while waiting for the next poll event!

Includes

```
#include <aws/core/Aws.h>
#include <aws/sqs/SQSClient.h>
#include <aws/sqs/model/ReceiveMessageRequest.h>
```

Code

```
    Aws::SQS::SQSClient sqsClient(customConfiguration);

    Aws::SQS::Model::ReceiveMessageRequest request;
    request.SetQueueUrl(queueUrl);
    request.SetMaxNumberOfMessages(1);
    request.SetWaitTimeSeconds(waitTimeSeconds);

    auto outcome = sqsClient.ReceiveMessage(request);
    if (outcome.IsSuccess()) {
        const auto &messages = outcome.GetResult().GetMessages();
        if (messages.empty()) {
            std::cout << "No messages received from queue " << queueUrl <<
                      std::endl;
        }
        else {
            const auto &message = messages[0];
            std::cout << "Received message:" << std::endl;
            std::cout << "  MessageId: " << message.GetMessageId() << std::endl;
            std::cout << "  ReceiptHandle: " << message.GetReceiptHandle() <<
std::endl;
            std::cout << "  Body: " << message.GetBody() << std::endl << std::endl;
        }
    }
    else {
        std::cout << "Error receiving message from queue " << queueUrl << ": "
                  << outcome.GetError().GetMessage() << std::endl;
    }
```

See the complete example.

More Info

- Amazon SQS Long Polling in the Amazon Simple Queue Service Developer Guide
- CreateQueue in the Amazon Simple Queue Service API Reference

- ReceiveMessage in the Amazon Simple Queue Service API Reference
- SetQueueAttributes in the Amazon Simple Queue Service API Reference

Setting Visibility Timeout in Amazon SQS

When a message is received in Amazon SQS, it remains on the queue until it's deleted in order to ensure receipt. A message that was received, but not deleted, will be available in subsequent requests after a given *visibility timeout* to help prevent the message from being received more than once before it can be processed and deleted.

When using standard queues, visibility timeout isn't a guarantee against receiving a message twice. If you are using a standard queue, be sure that your code can handle the case where the same message has been delivered more than once.

Prerequisites

Before you begin, we recommend you read Getting started using the AWS SDK for C++.

Download the example code and build the solution as described in Getting started on code examples.

To run the examples, the user profile your code uses to make the requests must have proper permissions in AWS (for the service and the action). For more information, see Providing AWS credentials.

Set the Message Visibility Timeout upon Message Receipt

When you have received a message, you can modify its visibility timeout by passing its receipt handle in a ChangeMessageVisibilityRequest that you pass to the SQSClient class' `ChangeMessageVisibility` member function.

Includes

```
#include <aws/core/Aws.h>
#include <aws/sqs/SQSClient.h>
#include <aws/sqs/model/ChangeMessageVisibilityRequest.h>
#include <aws/sqs/model/ReceiveMessageRequest.h>
#include <iostream>
```

Code

```
    Aws::SQS::Model::ChangeMessageVisibilityRequest request;
    request.SetQueueUrl(queue_url);
    request.SetReceiptHandle(messageReceiptHandle);
    request.SetVisibilityTimeout(visibilityTimeoutSeconds);

    auto outcome = sqsClient.ChangeMessageVisibility(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully changed visibility of message " <<
                  messageReceiptHandle << " from queue " << queue_url << std::endl;
    }
    else {
        std::cout << "Error changing visibility of message from queue "
                  << queue_url << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
```

See the complete example.

More Info

- Visibility Timeout in the Amazon Simple Queue Service Developer Guide
- SetQueueAttributes in the Amazon Simple Queue Service API Reference
- GetQueueAttributes in the Amazon Simple Queue Service API Reference
- ReceiveMessage in the Amazon Simple Queue Service API Reference
- ChangeMessageVisibility in the Amazon Simple Queue Service API Reference
- ChangeMessageVisibilityBatch in the Amazon Simple Queue Service API Reference

Using Dead Letter Queues in Amazon SQS

Amazon SQS provides support for *dead letter queues*. A dead letter queue is a queue that other queues can target for messages that can't be processed successfully. You can set aside and isolate these messages in the dead letter queue to determine why their processing did not succeed.

To create a dead letter queue, you must first create a *redrive policy*, and then set the policy in the queue's attributes.

> **Important**
>
> A dead letter queue must be the same type of queue (FIFO or standard) that the source queue is. It must also be created using the same AWS account and AWS Region as the source queue.

Prerequisites

Before you begin, we recommend you read Getting started using the AWS SDK for C++.

Download the example code and build the solution as described in Getting started on code examples.

To run the examples, the user profile your code uses to make the requests must have proper permissions in AWS (for the service and the action). For more information, see Providing AWS credentials.

Create a Redrive Policy

A redrive policy is specified in JSON. To create it, you can use the JSON utility class provided with the AWS SDK for C++.

Here is an example function that creates a redrive policy by providing it with the ARN of your dead letter queue and the maximum number of times the message can be received and not processed before it's sent to the dead letter queue.

Includes

```
#include <aws/core/Aws.h>
#include <aws/core/utils/json/JsonSerializer.h>
```

Code

```
Aws::String MakeRedrivePolicy(const Aws::String &queueArn, int maxReceiveCount) {
    Aws::Utils::Json::JsonValue redrive_arn_entry;
    redrive_arn_entry.AsString(queueArn);

    Aws::Utils::Json::JsonValue max_msg_entry;
    max_msg_entry.AsInteger(maxReceiveCount);
```

```
    Aws::Utils::Json::JsonValue policy_map;
    policy_map.WithObject("deadLetterTargetArn", redrive_arn_entry);
    policy_map.WithObject("maxReceiveCount", max_msg_entry);

    return policy_map.View().WriteReadable();
}
```

See the complete example.

Set the Redrive Policy on your Source Queue

To finish setting up your dead letter queue, call the SQSClient class' `SetQueueAttributes` member function with a SetQueueAttributesRequest object for which you've set the `RedrivePolicy` attribute with your JSON redrive policy.

Includes

```
#include <aws/sqs/SQSClient.h>
#include <aws/sqs/model/SetQueueAttributesRequest.h>
#include <iostream>
```

Code

```
    Aws::SQS::Model::SetQueueAttributesRequest request;
    request.SetQueueUrl(srcQueueUrl);
    request.AddAttributes(
            Aws::SQS::Model::QueueAttributeName::RedrivePolicy,
            redrivePolicy);

    const Aws::SQS::Model::SetQueueAttributesOutcome outcome =
            sqsClient.SetQueueAttributes(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully set dead letter queue for queue  " <<
                  srcQueueUrl << " to " << deadLetterQueueARN << std::endl;
    }
    else {
        std::cerr << "Error setting dead letter queue for queue " <<
                  srcQueueUrl << ": " << outcome.GetError().GetMessage() <<
                  std::endl;
    }
```

See the complete example.

More Info

- Using Amazon SQS Dead Letter Queues in the Amazon Simple Queue Service Developer Guide
- SetQueueAttributes in the Amazon Simple Queue Service API Reference

SDK for C++ code examples

The code examples in this topic show you how to use the AWS SDK for C++ with AWS.

Basics are code examples that show you how to perform the essential operations within a service.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Scenarios are code examples that show you how to accomplish specific tasks by calling multiple functions within a service or combined with other AWS services.

Some services contain additional example categories that show how to leverage libraries or functions specific to the service.

Services

- ACM examples using SDK for C++
- API Gateway examples using SDK for C++
- Aurora examples using SDK for C++
- Auto Scaling examples using SDK for C++
- CloudTrail examples using SDK for C++
- CloudWatch examples using SDK for C++
- CloudWatch Logs examples using SDK for C++
- CodeBuild examples using SDK for C++
- Amazon Cognito Identity Provider examples using SDK for C++
- DynamoDB examples using SDK for C++
- Amazon EC2 examples using SDK for C++
- EventBridge examples using SDK for C++
- AWS Glue examples using SDK for C++
- HealthImaging examples using SDK for C++
- IAM examples using SDK for C++
- AWS IoT examples using SDK for C++

- AWS IoT data examples using SDK for C++
- Lambda examples using SDK for C++
- MediaConvert examples using SDK for C++
- Amazon RDS examples using SDK for C++
- Amazon RDS Data Service examples using SDK for C++
- Amazon Rekognition examples using SDK for C++
- Amazon S3 examples using SDK for C++
- Secrets Manager examples using SDK for C++
- Amazon SES examples using SDK for C++
- Amazon SNS examples using SDK for C++
- Amazon SQS examples using SDK for C++
- AWS STS examples using SDK for C++
- Amazon Transcribe Streaming examples using SDK for C++

ACM examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with ACM.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Actions

Actions

`AddTagsToCertificate`

The following code example shows how to use `AddTagsToCertificate`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Add tags to an AWS Certificate Manager (ACM) certificate.
/*!
  \param certificateArn: The Amazon Resource Name (ARN) of a certificate.
  \param tagKey: The key for the tag.
  \param tagValue: The value for the tag.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::ACM::addTagsToCertificate(const Aws::String &certificateArn,
                                       const Aws::String &tagKey,
                                       const Aws::String &tagValue,
                                       const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::ACM::ACMClient acmClient(clientConfiguration);

    Aws::ACM::Model::AddTagsToCertificateRequest request;
    Aws::Vector<Aws::ACM::Model::Tag> tags;
    Aws::ACM::Model::Tag tag;

    tag.WithKey(tagKey).WithValue(tagValue);
    tags.push_back(tag);

    request.WithCertificateArn(certificateArn).WithTags(tags);

    Aws::ACM::Model::AddTagsToCertificateOutcome outcome =
            acmClient.AddTagsToCertificate(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: addTagsToCertificate: " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Success: Tag with key '" << tagKey <<
                  "' and value '" << tagValue <<
```

```
                "' added to certificate with ARN '" <<
                certificateArn << "'." << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see AddTagsToCertificate in *AWS SDK for C++ API Reference*.

`DeleteCertificate`

The following code example shows how to use `DeleteCertificate`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Delete an AWS Certificate Manager (ACM) certificate.
/*!
  \param certificateArn: The Amazon Resource Name (ARN) of a certificate.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::ACM::deleteCertificate(const Aws::String &certificateArn,
                                    const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::ACM::ACMClient acmClient(clientConfiguration);

    Aws::ACM::Model::DeleteCertificateRequest request;
    request.WithCertificateArn(certificateArn);

    Aws::ACM::Model::DeleteCertificateOutcome outcome =
            acmClient.DeleteCertificate(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: DeleteCertificate: " <<
                  outcome.GetError().GetMessage() << std::endl;
```

```
    }
    else {
        std::cout << "Success: The certificate with the ARN '" <<
                  certificateArn << "' is deleted." << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DeleteCertificate in *AWS SDK for C++ API Reference*.

`DescribeCertificate`

The following code example shows how to use `DescribeCertificate`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Describe an AWS Certificate Manager (ACM) certificate.
/*!
  \param certificateArn: The Amazon Resource Name (ARN) of a certificate.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::ACM::describeCertificate(const Aws::String &certificateArn,
                                      const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::ACM::ACMClient acm_client(clientConfiguration);

    Aws::ACM::Model::DescribeCertificateRequest request;
    request.WithCertificateArn(certificateArn);

    Aws::ACM::Model::DescribeCertificateOutcome outcome =
            acm_client.DescribeCertificate(request);

    if (!outcome.IsSuccess()) {
```

```
        std::cerr << "Error: DescribeCertificate: " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        Aws::ACM::Model::CertificateDetail certificate =
                outcome.GetResult().GetCertificate();

        std::cout << "Success: Information about certificate "
                     "with ARN '" << certificateArn << "':" << std::endl <<
std::endl;

        std::cout << "ARN:                 " << certificate.GetCertificateArn()
                  << std::endl;
        std::cout << "Authority ARN:       " <<
                  certificate.GetCertificateAuthorityArn() << std::endl;
        std::cout << "Created at (GMT):    " <<
                  certificate.GetCreatedAt().ToGmtString(
                          Aws::Utils::DateFormat::ISO_8601)
                  << std::endl;
        std::cout << "Domain name:         " << certificate.GetDomainName()
                  << std::endl;

        Aws::Vector<Aws::ACM::Model::DomainValidation> options =
                certificate.GetDomainValidationOptions();

        if (!options.empty()) {
            std::cout << std::endl << "Domain validation information: "
                      << std::endl << std::endl;

            for (auto &validation: options) {
                std::cout << "  Domain name:              " <<
                          validation.GetDomainName() << std::endl;

                const Aws::ACM::Model::ResourceRecord &record =
                        validation.GetResourceRecord();

                std::cout << "  Resource record name:     " <<
                          record.GetName() << std::endl;

                Aws::ACM::Model::RecordType recordType = record.GetType();
                Aws::String type;

                switch (recordType) {
                    case Aws::ACM::Model::RecordType::CNAME:
```

```
                type = "CNAME";
                break;
            case Aws::ACM::Model::RecordType::NOT_SET:
                type = "Not set";
                break;
            default:
                type = "Cannot determine.";
                break;
        }

        std::cout << "  Resource record type:     " << type <<
                  std::endl;

        std::cout << "  Resource record value:    " <<
                  record.GetValue() << std::endl;

        std::cout << "  Validation domain:        " <<
                  validation.GetValidationDomain() << std::endl;

        Aws::Vector<Aws::String> emails =
                validation.GetValidationEmails();

        if (!emails.empty()) {
            std::cout << "  Validation emails:" << std::endl <<
                      std::endl;

            for (auto &email: emails) {
                std::cout << "    " << email << std::endl;
            }

            std::cout << std::endl;
        }

        Aws::ACM::Model::ValidationMethod validationMethod =
                validation.GetValidationMethod();
        Aws::String method;

        switch (validationMethod) {
            case Aws::ACM::Model::ValidationMethod::DNS:
                method = "DNS";
                break;
            case Aws::ACM::Model::ValidationMethod::EMAIL:
                method = "Email";
                break;
```

```
                case Aws::ACM::Model::ValidationMethod::NOT_SET:
                    method = "Not set";
                    break;
                default:
                    method = "Cannot determine";
            }

            std::cout << "  Validation method:        " <<
                      method << std::endl;

            Aws::ACM::Model::DomainStatus domainStatus =
                    validation.GetValidationStatus();
            Aws::String status;

            switch (domainStatus) {
                case Aws::ACM::Model::DomainStatus::FAILED:
                    status = "Failed";
                    break;
                case Aws::ACM::Model::DomainStatus::NOT_SET:
                    status = "Not set";
                    break;
                case Aws::ACM::Model::DomainStatus::PENDING_VALIDATION:
                    status = "Pending validation";
                    break;
                case Aws::ACM::Model::DomainStatus::SUCCESS:
                    status = "Success";
                    break;
                default:
                    status = "Cannot determine";
            }

            std::cout << "  Domain validation status: " << status <<
                      std::endl << std::endl;

        }
    }

    Aws::Vector<Aws::ACM::Model::ExtendedKeyUsage> usages =
            certificate.GetExtendedKeyUsages();

    if (!usages.empty()) {
        std::cout << std::endl << "Extended key usages:" <<
                  std::endl << std::endl;
```

```
            for (auto &usage: usages) {
                Aws::ACM::Model::ExtendedKeyUsageName usageName =
                        usage.GetName();
                Aws::String name;

                switch (usageName) {
                    case Aws::ACM::Model::ExtendedKeyUsageName::ANY:
                        name = "Any";
                        break;
                    case Aws::ACM::Model::ExtendedKeyUsageName::CODE_SIGNING:
                        name = "Code signing";
                        break;
                    case Aws::ACM::Model::ExtendedKeyUsageName::CUSTOM:
                        name = "Custom";
                        break;
                    case Aws::ACM::Model::ExtendedKeyUsageName::EMAIL_PROTECTION:
                        name = "Email protection";
                        break;
                    case Aws::ACM::Model::ExtendedKeyUsageName::IPSEC_END_SYSTEM:
                        name = "IPSEC end system";
                        break;
                    case Aws::ACM::Model::ExtendedKeyUsageName::IPSEC_TUNNEL:
                        name = "IPSEC tunnel";
                        break;
                    case Aws::ACM::Model::ExtendedKeyUsageName::IPSEC_USER:
                        name = "IPSEC user";
                        break;
                    case Aws::ACM::Model::ExtendedKeyUsageName::NONE:
                        name = "None";
                        break;
                    case Aws::ACM::Model::ExtendedKeyUsageName::NOT_SET:
                        name = "Not set";
                        break;
                    case Aws::ACM::Model::ExtendedKeyUsageName::OCSP_SIGNING:
                        name = "OCSP signing";
                        break;
                    case Aws::ACM::Model::ExtendedKeyUsageName::TIME_STAMPING:
                        name = "Time stamping";
                        break;
                    case
    Aws::ACM::Model::ExtendedKeyUsageName::TLS_WEB_CLIENT_AUTHENTICATION:
                        name = "TLS web client authentication";
                        break;
```

```
                    case
Aws::ACM::Model::ExtendedKeyUsageName::TLS_WEB_SERVER_AUTHENTICATION:
                        name = "TLS web server authentication";
                        break;
                    default:
                        name = "Cannot determine";
                }

                std::cout << "  Name: " << name << std::endl;
                std::cout << "  OID:  " << usage.GetOID() <<
                          std::endl << std::endl;
            }

            std::cout << std::endl;
        }

        Aws::ACM::Model::CertificateStatus certificateStatus =
                certificate.GetStatus();
        Aws::String status;

        switch (certificateStatus) {
            case Aws::ACM::Model::CertificateStatus::EXPIRED:
                status = "Expired";
                break;
            case Aws::ACM::Model::CertificateStatus::FAILED:
                status = "Failed";
                break;
            case Aws::ACM::Model::CertificateStatus::INACTIVE:
                status = "Inactive";
                break;
            case Aws::ACM::Model::CertificateStatus::ISSUED:
                status = "Issued";
                break;
            case Aws::ACM::Model::CertificateStatus::NOT_SET:
                status = "Not set";
                break;
            case Aws::ACM::Model::CertificateStatus::PENDING_VALIDATION:
                status = "Pending validation";
                break;
            case Aws::ACM::Model::CertificateStatus::REVOKED:
                status = "Revoked";
                break;
            case Aws::ACM::Model::CertificateStatus::VALIDATION_TIMED_OUT:
                status = "Validation timed out";
```

```
                break;
            default:
                status = "Cannot determine";
        }

        std::cout << "Status:              " << status << std::endl;

        if (certificate.GetStatus() ==
            Aws::ACM::Model::CertificateStatus::FAILED) {
            Aws::ACM::Model::FailureReason failureReason =
                    certificate.GetFailureReason();
            Aws::String reason;

            switch (failureReason) {
                case
Aws::ACM::Model::FailureReason::ADDITIONAL_VERIFICATION_REQUIRED:
                    reason = "Additional verification required";
                    break;
                case Aws::ACM::Model::FailureReason::CAA_ERROR:
                    reason = "CAA error";
                    break;
                case Aws::ACM::Model::FailureReason::DOMAIN_NOT_ALLOWED:
                    reason = "Domain not allowed";
                    break;
                case Aws::ACM::Model::FailureReason::DOMAIN_VALIDATION_DENIED:
                    reason = "Domain validation denied";
                    break;
                case Aws::ACM::Model::FailureReason::INVALID_PUBLIC_DOMAIN:
                    reason = "Invalid public domain";
                    break;
                case Aws::ACM::Model::FailureReason::NOT_SET:
                    reason = "Not set";
                    break;
                case Aws::ACM::Model::FailureReason::NO_AVAILABLE_CONTACTS:
                    reason = "No available contacts";
                    break;
                case Aws::ACM::Model::FailureReason::OTHER:
                    reason = "Other";
                    break;
                case Aws::ACM::Model::FailureReason::PCA_ACCESS_DENIED:
                    reason = "PCA access denied";
                    break;
                case Aws::ACM::Model::FailureReason::PCA_INVALID_ARGS:
                    reason = "PCA invalid args";
```

```
                    break;
                case Aws::ACM::Model::FailureReason::PCA_INVALID_ARN:
                    reason = "PCA invalid ARN";
                    break;
                case Aws::ACM::Model::FailureReason::PCA_INVALID_DURATION:
                    reason = "PCA invalid duration";
                    break;
                case Aws::ACM::Model::FailureReason::PCA_INVALID_STATE:
                    reason = "PCA invalid state";
                    break;
                case Aws::ACM::Model::FailureReason::PCA_LIMIT_EXCEEDED:
                    reason = "PCA limit exceeded";
                    break;
                case
Aws::ACM::Model::FailureReason::PCA_NAME_CONSTRAINTS_VALIDATION:
                    reason = "PCA name constraints validation";
                    break;
                case Aws::ACM::Model::FailureReason::PCA_REQUEST_FAILED:
                    reason = "PCA request failed";
                    break;
                case Aws::ACM::Model::FailureReason::PCA_RESOURCE_NOT_FOUND:
                    reason = "PCA resource not found";
                    break;
                default:
                    reason = "Cannot determine";
            }

            std::cout << "Failure reason:      " << reason << std::endl;
        }

        if (certificate.GetStatus() == Aws::ACM::Model::CertificateStatus::REVOKED)
{
            std::cout << "Revoked at (GMT):    " <<
                      certificate.GetRevokedAt().ToGmtString(
                              Aws::Utils::DateFormat::ISO_8601)
                      << std::endl;

            Aws::ACM::Model::RevocationReason revocationReason =
                    certificate.GetRevocationReason();
            Aws::String reason;

            switch (revocationReason) {
                case Aws::ACM::Model::RevocationReason::AFFILIATION_CHANGED:
                    reason = "Affiliation changed";
```

```
                    break;
                case Aws::ACM::Model::RevocationReason::A_A_COMPROMISE:
                    reason = "AA compromise";
                    break;
                case Aws::ACM::Model::RevocationReason::CA_COMPROMISE:
                    reason = "CA compromise";
                    break;
                case Aws::ACM::Model::RevocationReason::CERTIFICATE_HOLD:
                    reason = "Certificate hold";
                    break;
                case Aws::ACM::Model::RevocationReason::CESSATION_OF_OPERATION:
                    reason = "Cessation of operation";
                    break;
                case Aws::ACM::Model::RevocationReason::KEY_COMPROMISE:
                    reason = "Key compromise";
                    break;
                case Aws::ACM::Model::RevocationReason::NOT_SET:
                    reason = "Not set";
                    break;
                case Aws::ACM::Model::RevocationReason::PRIVILEGE_WITHDRAWN:
                    reason = "Privilege withdrawn";
                    break;
                case Aws::ACM::Model::RevocationReason::REMOVE_FROM_CRL:
                    reason = "Revoke from CRL";
                    break;
                case Aws::ACM::Model::RevocationReason::SUPERCEDED:
                    reason = "Superceded";
                    break;
                case Aws::ACM::Model::RevocationReason::UNSPECIFIED:
                    reason = "Unspecified";
                    break;
                default:
                    reason = "Cannot determine";
            }

            std::cout << "Revocation reason:   " << reason << std::endl;
        }

        if (certificate.GetType() == Aws::ACM::Model::CertificateType::IMPORTED) {
            std::cout << "Imported at (GMT):   " <<
                      certificate.GetImportedAt().ToGmtString(
                              Aws::Utils::DateFormat::ISO_8601)
                      << std::endl;
        }
```

```
        Aws::Vector<Aws::String> inUseBys = certificate.GetInUseBy();

        if (!inUseBys.empty()) {
            std::cout << std::endl << "In use by:" << std::endl << std::endl;

            for (auto &in_use_by: inUseBys) {
                std::cout << "  " << in_use_by << std::endl;
            }

            std::cout << std::endl;
        }

        if (certificate.GetType() == Aws::ACM::Model::CertificateType::AMAZON_ISSUED
&&
            certificate.GetStatus() == Aws::ACM::Model::CertificateStatus::ISSUED) {
            std::cout << "Issued at (GMT):     " <<
                      certificate.GetIssuedAt().ToGmtString(
                              Aws::Utils::DateFormat::ISO_8601)
                      << std::endl;
        }

        std::cout << "Issuer:              " << certificate.GetIssuer() <<
                  std::endl;

        Aws::ACM::Model::KeyAlgorithm keyAlgorithm =
                certificate.GetKeyAlgorithm();
        Aws::String algorithm;

        switch (keyAlgorithm) {
            case Aws::ACM::Model::KeyAlgorithm::EC_prime256v1:
                algorithm = "P-256 (secp256r1, prime256v1)";
                break;
            case Aws::ACM::Model::KeyAlgorithm::EC_secp384r1:
                algorithm = "P-384 (secp384r1)";
                break;
            case Aws::ACM::Model::KeyAlgorithm::EC_secp521r1:
                algorithm = "P-521 (secp521r1)";
                break;
            case Aws::ACM::Model::KeyAlgorithm::NOT_SET:
                algorithm = "Not set";
                break;
            case Aws::ACM::Model::KeyAlgorithm::RSA_1024:
                algorithm = "RSA 1024";
```

```
                break;
            case Aws::ACM::Model::KeyAlgorithm::RSA_2048:
                algorithm = "RSA 2048";
                break;
            case Aws::ACM::Model::KeyAlgorithm::RSA_4096:
                algorithm = "RSA 4096";
                break;
            default:
                algorithm = "Cannot determine";
        }

        std::cout << "Key algorithm:       " << algorithm << std::endl;

        if (certificate.GetStatus() == Aws::ACM::Model::CertificateStatus::ISSUED) {
            std::cout << "Not valid after (GMT): " <<
                      certificate.GetNotAfter().ToGmtString(
                              Aws::Utils::DateFormat::ISO_8601)
                      << std::endl;
            std::cout << "Not valid before (GMT): " <<
                      certificate.GetNotBefore().ToGmtString(
                              Aws::Utils::DateFormat::ISO_8601)
                      << std::endl;
        }

        Aws::ACM::Model::CertificateTransparencyLoggingPreference loggingPreference
=

certificate.GetOptions().GetCertificateTransparencyLoggingPreference();
        Aws::String preference;

        switch (loggingPreference) {
            case
Aws::ACM::Model::CertificateTransparencyLoggingPreference::DISABLED:
                preference = "Disabled";
                break;
            case Aws::ACM::Model::CertificateTransparencyLoggingPreference::ENABLED:
                preference = "Enabled";
                break;
            case Aws::ACM::Model::CertificateTransparencyLoggingPreference::NOT_SET:
                preference = "Not set";
                break;
            default:
                preference = "Cannot determine";
        }
```

```
        std::cout << "Logging preference:  " << preference << std::endl;

        std::cout << "Serial:              " << certificate.GetSerial() <<
                  std::endl;
        std::cout << "Signature algorithm: "
                  << certificate.GetSignatureAlgorithm() << std::endl;
        std::cout << "Subject:             " << certificate.GetSubject() <<
                  std::endl;

        Aws::ACM::Model::CertificateType certificateType = certificate.GetType();
        Aws::String type;

        switch (certificateType) {
            case Aws::ACM::Model::CertificateType::AMAZON_ISSUED:
                type = "Amazon issued";
                break;
            case Aws::ACM::Model::CertificateType::IMPORTED:
                type = "Imported";
                break;
            case Aws::ACM::Model::CertificateType::NOT_SET:
                type = "Not set";
                break;
            case Aws::ACM::Model::CertificateType::PRIVATE_:
                type = "Private";
                break;
            default:
                type = "Cannot determine";
        }

        std::cout << "Type:                " << type << std::endl;

        Aws::Vector<Aws::String> altNames =
                certificate.GetSubjectAlternativeNames();

        if (!altNames.empty()) {
            std::cout << std::endl << "Alternative names:" <<
                      std::endl << std::endl;

            for (auto &alt_name: altNames) {
                std::cout << "  " << alt_name << std::endl;
            }

            std::cout << std::endl;
```

```
        }
    }

    return outcome.IsSuccess();
}
```

- For API details, see DescribeCertificate in *AWS SDK for C++ API Reference*.

`ExportCertificate`

The following code example shows how to use `ExportCertificate`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Export an AWS Certificate Manager (ACM)  certificate.
/*!
  \param certificateArn: The Amazon Resource Name (ARN) of a certificate.
  \param passphrase: A passphrase to decrypt the exported certificate.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::ACM::exportCertificate(const Aws::String &certificateArn,
                                    const Aws::String &passphrase,
                                    const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::ACM::ACMClient acm_client(clientConfiguration);

    Aws::ACM::Model::ExportCertificateRequest request;
    Aws::Utils::CryptoBuffer cryptoBuffer(
            reinterpret_cast<const unsigned char *>(passphrase.c_str()),
            passphrase.length());
    request.WithCertificateArn(certificateArn).WithPassphrase(cryptoBuffer);

    Aws::ACM::Model::ExportCertificateOutcome outcome =
```

```
            acm_client.ExportCertificate(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: ExportCertificate: " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Success: Information about certificate with ARN '"
                  << certificateArn << "':" << std::endl << std::endl;

        auto result = outcome.GetResult();

        std::cout << "Certificate:       " << std::endl << std::endl <<
                  result.GetCertificate() << std::endl << std::endl;
        std::cout << "Certificate chain: " << std::endl << std::endl <<
                  result.GetCertificateChain() << std::endl << std::endl;
        std::cout << "Private key:       " << std::endl << std::endl <<
                  result.GetPrivateKey() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see ExportCertificate in *AWS SDK for C++ API Reference*.

`GetCertificate`

The following code example shows how to use `GetCertificate`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Get an AWS Certificate Manager (ACM) certificate.
/*!
  \param certificateArn: The Amazon Resource Name (ARN) of a certificate.
```

```
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::ACM::getCertificate(const Aws::String &certificateArn,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::ACM::ACMClient acmClient(clientConfiguration);

    Aws::ACM::Model::GetCertificateRequest request;
    request.WithCertificateArn(certificateArn);

    Aws::ACM::Model::GetCertificateOutcome outcome =
            acmClient.GetCertificate(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: GetCertificate: " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Success: Information about certificate with ARN '"
                  << certificateArn << "':" << std::endl << std::endl;

        auto result = outcome.GetResult();

        std::cout << "Certificate: " << std::endl << std::endl <<
                  result.GetCertificate() << std::endl;
        std::cout << "Certificate chain: " << std::endl << std::endl <<
                  result.GetCertificateChain() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see GetCertificate in *AWS SDK for C++ API Reference*.

`ImportCertificate`

The following code example shows how to use `ImportCertificate`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Import an AWS Certificate Manager (ACM) certificate.
/*!
  \param certificateFile: Path to certificate to import.
  \param privateKeyFile: Path to file containing a private key.
  \param certificateChainFile: Path to file containing a PEM encoded certificate
 chain.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::ACM::importCertificate(const Aws::String &certificateFile,
                                    const Aws::String &privateKeyFile,
                                    const Aws::String &certificateChainFile,
                                    const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    std::ifstream certificateInStream(certificateFile.c_str());
    if (!certificateInStream) {
        std::cerr << "Error: The certificate file '" << certificateFile <<
                  "' does not exist." << std::endl;

        return false;
    }

    std::ifstream privateKeyInstream(privateKeyFile.c_str());
    if (!privateKeyInstream) {
        std::cerr << "Error: The private key file '" << privateKeyFile <<
                  "' does not exist." << std::endl;

        return false;
    }

    std::ifstream certificateChainInStream(certificateChainFile.c_str());
    if (!certificateChainInStream) {
        std::cerr << "Error: The certificate chain file '"
                  << certificateChainFile << "' does not exist." << std::endl;
```

```
        return false;
    }

    Aws::String certificate;
    certificate.assign(std::istreambuf_iterator<char>(certificateInStream),
                       std::istreambuf_iterator<char>());

    Aws::String privateKey;
    privateKey.assign(std::istreambuf_iterator<char>(privateKeyInstream),
                      std::istreambuf_iterator<char>());

    Aws::String certificateChain;

certificateChain.assign(std::istreambuf_iterator<char>(certificateChainInStream),
                            std::istreambuf_iterator<char>());

    Aws::ACM::ACMClient acmClient(clientConfiguration);

    Aws::ACM::Model::ImportCertificateRequest request;

    request.WithCertificate(Aws::Utils::ByteBuffer((unsigned char *)
                                                           certificate.c_str(),
                                                   certificate.size()))
            .WithPrivateKey(Aws::Utils::ByteBuffer((unsigned char *)
                                                           privateKey.c_str(),
                                                   privateKey.size()))
            .WithCertificateChain(Aws::Utils::ByteBuffer((unsigned char *)

certificateChain.c_str(),
                                                         certificateChain.size()));

    Aws::ACM::Model::ImportCertificateOutcome outcome =
            acmClient.ImportCertificate(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: ImportCertificate: " <<
                  outcome.GetError().GetMessage() << std::endl;

        return false;
    }
    else {
        std::cout << "Success: Certificate associated with ARN '" <<
                  outcome.GetResult().GetCertificateArn() << "' imported."
```

```
                  << std::endl;

        return true;
    }
}
```

- For API details, see ImportCertificate in *AWS SDK for C++ API Reference*.

`ListCertificates`

The following code example shows how to use `ListCertificates`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! List the AWS Certificate Manager (ACM) certificates in an account.
/*!
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::ACM::listCertificates(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::ACM::ACMClient acmClient(clientConfiguration);

    Aws::ACM::Model::ListCertificatesRequest request;
    Aws::Vector<Aws::ACM::Model::CertificateSummary> allCertificates;
    Aws::String nextToken;
    do {
        if (!nextToken.empty()) {
            request.SetNextToken(nextToken);
        }

        Aws::ACM::Model::ListCertificatesOutcome outcome =
                acmClient.ListCertificates(request);
```

```
        if (!outcome.IsSuccess()) {
            std::cerr << "Error: ListCertificates: " <<
                      outcome.GetError().GetMessage() << std::endl;

            return false;
        }
        else {
            const Aws::ACM::Model::ListCertificatesResult &result =
 outcome.GetResult();

            const Aws::Vector<Aws::ACM::Model::CertificateSummary> &certificates =
                    result.GetCertificateSummaryList();
            allCertificates.insert(allCertificates.end(), certificates.begin(),
                                   certificates.end());

            nextToken = result.GetNextToken();
        }
    } while (!nextToken.empty());

    if (!allCertificates.empty()) {
        for (const Aws::ACM::Model::CertificateSummary &certificate:
 allCertificates) {
            std::cout << "Certificate ARN: " <<
                      certificate.GetCertificateArn() << std::endl;
            std::cout << "Domain name:     " <<
                      certificate.GetDomainName() << std::endl << std::endl;
        }
    }
    else {
        std::cout << "No available certificates found in account."
                  << std::endl;
    }

    return true;
}
```

- For API details, see ListCertificates in *AWS SDK for C++ API Reference*.

`ListTagsForCertificate`

The following code example shows how to use `ListTagsForCertificate`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! List the tags for an AWS Certificate Manager (ACM) certificate.
/*!
  \param certificateArn: The Amazon Resource Name (ARN) of a certificate.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::ACM::listTagsForCertificate(const Aws::String &certificateArn,
                                         const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::ACM::ACMClient acm_client(clientConfiguration);

    Aws::ACM::Model::ListTagsForCertificateRequest request;
    request.WithCertificateArn(certificateArn);

    Aws::ACM::Model::ListTagsForCertificateOutcome outcome =
            acm_client.ListTagsForCertificate(request);

    if (!outcome.IsSuccess()) {
        std::cout << "Error: ListTagsForCertificate: " <<
                  outcome.GetError().GetMessage() << std::endl;

        return false;
    }
    else {
        std::cout << "Success: Information about tags for "
                     "certificate with ARN '"
                  << certificateArn << "':" << std::endl << std::endl;

        auto result = outcome.GetResult();

        Aws::Vector<Aws::ACM::Model::Tag> tags =
                result.GetTags();

        if (tags.size() > 0) {
```

```
            for (const Aws::ACM::Model::Tag &tag: tags) {
                std::cout << "Key:   " << tag.GetKey() << std::endl;
                std::cout << "Value: " << tag.GetValue()
                          << std::endl << std::endl;
            }
        }
        else {
            std::cout << "No tags found." << std::endl;
        }

        return true;
    }
}
```

- For API details, see ListTagsForCertificate in *AWS SDK for C++ API Reference*.

`RemoveTagsFromCertificate`

The following code example shows how to use `RemoveTagsFromCertificate`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Remove a tag from an ACM certificate.
/*!
  \param certificateArn: The Amazon Resource Name (ARN) of a certificate.
  \param tagKey: The key for the tag.
  \param tagValue: The value for the tag.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::ACM::removeTagsFromCertificate(const Aws::String &certificateArn,
                                            const Aws::String &tagKey,
                                            const Aws::String &tagValue,
                                            const Aws::Client::ClientConfiguration
 &clientConfiguration) {
```

```
    Aws::ACM::ACMClient acmClient(clientConfiguration);

    Aws::Vector<Aws::ACM::Model::Tag> tags;

    Aws::ACM::Model::Tag tag;
    tag.SetKey(tagKey);

    tags.push_back(tag);

    Aws::ACM::Model::RemoveTagsFromCertificateRequest request;
    request.WithCertificateArn(certificateArn)
            .WithTags(tags);

    Aws::ACM::Model::RemoveTagsFromCertificateOutcome outcome =
            acmClient.RemoveTagsFromCertificate(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: RemoveTagFromCertificate: " <<
                  outcome.GetError().GetMessage() << std::endl;

        return false;
    }
    else {
        std::cout << "Success: Tag with key '" << tagKey << "' removed from "
                  << "certificate with ARN '" << certificateArn << "'." <<
 std::endl;

        return true;
    }
}
```

- For API details, see RemoveTagsFromCertificate in *AWS SDK for C++ API Reference*.

`RenewCertificate`

The following code example shows how to use `RenewCertificate`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Renew an AWS Certificate Manager (ACM) certificate.
/*!
  \param certificateArn: The Amazon Resource Name (ARN) of a certificate.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::ACM::renewCertificate(const Aws::String &certificateArn,
                                   const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::ACM::ACMClient acmClient(clientConfiguration);

    Aws::ACM::Model::RenewCertificateRequest request;
    request.SetCertificateArn(certificateArn);

    Aws::ACM::Model::RenewCertificateOutcome outcome =
            acmClient.RenewCertificate(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: RenewCertificate: " <<
                  outcome.GetError().GetMessage() << std::endl;

        return false;
    }
    else {
        std::cout << "Success: Renewed certificate with ARN '"
                  << certificateArn << "'." << std::endl;

        return true;
    }
}
```

- For API details, see RenewCertificate in *AWS SDK for C++ API Reference*.

`RequestCertificate`

The following code example shows how to use `RequestCertificate`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Request an AWS Certificate Manager (ACM) certificate.
/*!
  \param domainName: A fully qualified domain name.
  \param idempotencyToken: Customer chosen string for idempotency.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::ACM::requestCertificate(const Aws::String &domainName,
                                     const Aws::String &idempotencyToken,
                                     const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::ACM::ACMClient acmClient(clientConfiguration);

    Aws::ACM::Model::RequestCertificateRequest request;
    request.WithDomainName(domainName)
            .WithIdempotencyToken(idempotencyToken);

    Aws::ACM::Model::RequestCertificateOutcome outcome =
            acmClient.RequestCertificate(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "RequestCertificate error: " <<
                  outcome.GetError().GetMessage() << std::endl;

        return false;
    }
    else {
        std::cout << "Success: The newly requested certificate's "
                     "ARN is '" <<
                  outcome.GetResult().GetCertificateArn() <<
                  "'." << std::endl;
```

```
        return true;
    }
}
```

- For API details, see RequestCertificate in *AWS SDK for C++ API Reference*.

`ResendValidationEmail`

The following code example shows how to use `ResendValidationEmail`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Resend the email that requests domain ownership validation.
/*!
  \param certificateArn: The Amazon Resource Name (ARN) of a certificate.
  \param domainName: A fully qualified domain name.
  \param validationDomain: The base validation domain that will act as the suffix
                           of the email addresses.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::ACM::resendValidationEmail(const Aws::String &certificateArn,
                                        const Aws::String &domainName,
                                        const Aws::String &validationDomain,
                                        const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::ACM::ACMClient acmClient(clientConfiguration);

    Aws::ACM::Model::ResendValidationEmailRequest request;
    request.WithCertificateArn(certificateArn)
            .WithDomain(domainName)
            .WithValidationDomain(validationDomain);

    Aws::ACM::Model::ResendValidationEmailOutcome outcome =
```

```
            acmClient.ResendValidationEmail(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "ResendValidationEmail error: " <<
                  outcome.GetError().GetMessage() << std::endl;

        return false;
    }
    else {
        std::cout << "Success: The validation email has been resent."
                  << std::endl;

        return true;
    }
}
```

- For API details, see ResendValidationEmail in *AWS SDK for C++ API Reference*.

`UpdateCertificateOptions`

The following code example shows how to use `UpdateCertificateOptions`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Update an AWS Certificate Manager (ACM) certificate option.
/*!
  \param certificateArn: The Amazon Resource Name (ARN) of a certificate.
  \param loggingEnabled: Boolean specifying logging enabled.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::ACM::updateCertificateOption(const Aws::String &certificateArn,
                                          bool loggingEnabled,
                                          const Aws::Client::ClientConfiguration
 &clientConfiguration) {
```

```
    Aws::ACM::ACMClient acmClient(clientConfiguration);

    Aws::ACM::Model::UpdateCertificateOptionsRequest request;
    request.SetCertificateArn(certificateArn);

    Aws::ACM::Model::CertificateOptions options;

    if (loggingEnabled) {
        options.SetCertificateTransparencyLoggingPreference(
                Aws::ACM::Model::CertificateTransparencyLoggingPreference::ENABLED);
    }
    else {
        options.SetCertificateTransparencyLoggingPreference(

 Aws::ACM::Model::CertificateTransparencyLoggingPreference::DISABLED);
    }

    request.SetOptions(options);

    Aws::ACM::Model::UpdateCertificateOptionsOutcome outcome =
            acmClient.UpdateCertificateOptions(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "UpdateCertificateOption error: " <<
                  outcome.GetError().GetMessage() << std::endl;

        return false;
    }
    else {
        std::cout << "Success: The option '"
                  << (loggingEnabled ? "enabled" : "disabled") << "' has been set
 for "
                                                                 "the certificate
 with the ARN '"
                  << certificateArn << "'."
                  << std::endl;

        return true;
    }
}
```

- For API details, see [UpdateCertificateOptions](#) in *AWS SDK for C++ API Reference*.

API Gateway examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with API Gateway.

Scenarios are code examples that show you how to accomplish specific tasks by calling multiple functions within a service or combined with other AWS services.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Scenarios

Scenarios

Create a serverless application to manage photos

The following code example shows how to create a serverless application that lets users manage photos using labels.

SDK for C++

Shows how to develop a photo asset management application that detects labels in images using Amazon Rekognition and stores them for later retrieval.

For complete source code and instructions on how to set up and run, see the full example on GitHub.

For a deep dive into the origin of this example see the post on AWS Community.

Services used in this example

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3

- Amazon SNS

Aurora examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with Aurora.

Basics are code examples that show you how to perform the essential operations within a service.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Scenarios are code examples that show you how to accomplish specific tasks by calling multiple functions within a service or combined with other AWS services.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Get started
- Basics
- Actions
- Scenarios

Get started

Hello Aurora

The following code example shows how to get started using Aurora.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Code for the CMakeLists.txt CMake file.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS rds)

# Set this project's name.
project("hello_aurora")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD AND AWSSDK_INSTALL_AS_SHARED_LIBS)
     # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

     # set(BIN_SUB_DIR "/Debug") # If you are building from the command line, you
 may need to uncomment this
                                 # and set the proper subdirectory to the
 executables' location.

     AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_aurora.cpp)
```

```
target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Code for the hello_aurora.cpp source file.

```
#include <aws/core/Aws.h>
#include <aws/rds/RDSClient.h>
#include <aws/rds/model/DescribeDBClustersRequest.h>
#include <iostream>

/*
 *  A "Hello Aurora" starter application which initializes an Amazon Relational
 Database Service (Amazon RDS) client
 *  and describes the Amazon Aurora (Aurora) clusters.
 *
 *  main function
 *
 *  Usage: 'hello_aurora'
 *
 */
int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::RDS::RDSClient rdsClient(clientConfig);

        Aws::String marker; // Used for pagination.
        std::vector<Aws::String> clusterIds;
        do {
            Aws::RDS::Model::DescribeDBClustersRequest request;

            Aws::RDS::Model::DescribeDBClustersOutcome outcome =
                    rdsClient.DescribeDBClusters(request);

            if (outcome.IsSuccess()) {
```

```
                for (auto &cluster: outcome.GetResult().GetDBClusters()) {
                    clusterIds.push_back(cluster.GetDBClusterIdentifier());
                }
                marker = outcome.GetResult().GetMarker();
            } else {
                result = 1;
                std::cerr << "Error with Aurora::GDescribeDBClusters. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                break;
            }
        } while (!marker.empty());

        std::cout << clusterIds.size() << " Aurora clusters found." << std::endl;
        for (auto &clusterId: clusterIds) {
            std::cout << "  clusterId " << clusterId << std::endl;
        }
    }

    Aws::ShutdownAPI(options); // Should only be called once.
    return 0;
}
```

- For API details, see DescribeDBClusters in *AWS SDK for C++ API Reference*.

Basics

Learn the basics

The following code example shows how to:

- Create a custom Aurora DB cluster parameter group and set parameter values.
- Create a DB cluster that uses the parameter group.
- Create a DB instance that contains a database.
- Take a snapshot of the DB cluster, then clean up resources.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Routine which creates an Amazon Aurora DB cluster and demonstrates several
 operations
//! on that cluster.
/*!
 \sa gettingStartedWithDBClusters()
 \param clientConfiguration: AWS client configuration.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::gettingStartedWithDBClusters(
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::RDS::RDSClient client(clientConfig);

    printAsterisksLine();
    std::cout << "Welcome to the Amazon Relational Database Service (Amazon Aurora)"
              << std::endl;
    std::cout << "get started with DB clusters demo." << std::endl;
    printAsterisksLine();

    std::cout << "Checking for an existing DB cluster parameter group named '" <<
              CLUSTER_PARAMETER_GROUP_NAME << "'." << std::endl;
    Aws::String dbParameterGroupFamily("Undefined");
    bool parameterGroupFound = true;
    {
        // 1. Check if the DB cluster parameter group already exists.
        Aws::RDS::Model::DescribeDBClusterParameterGroupsRequest request;
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);

        Aws::RDS::Model::DescribeDBClusterParameterGroupsOutcome outcome =
                client.DescribeDBClusterParameterGroups(request);
```

```
        if (outcome.IsSuccess()) {
            std::cout << "DB cluster parameter group named '" <<
                      CLUSTER_PARAMETER_GROUP_NAME << "' already exists." <<
std::endl;
            dbParameterGroupFamily =
outcome.GetResult().GetDBClusterParameterGroups()[0].GetDBParameterGroupFamily();
        }
        else if (outcome.GetError().GetErrorType() ==
                 Aws::RDS::RDSErrors::D_B_PARAMETER_GROUP_NOT_FOUND_FAULT) {
            std::cout << "DB cluster parameter group named '" <<
                      CLUSTER_PARAMETER_GROUP_NAME << "' does not exist." <<
std::endl;
            parameterGroupFound = false;
        }
        else {
            std::cerr << "Error with Aurora::DescribeDBClusterParameterGroups. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }

    if (!parameterGroupFound) {
        Aws::Vector<Aws::RDS::Model::DBEngineVersion> engineVersions;

        // 2. Get available parameter group families for the specified engine.
        if (!getDBEngineVersions(DB_ENGINE, NO_PARAMETER_GROUP_FAMILY,
                                 engineVersions, client)) {
            return false;
        }

        std::cout << "Getting available parameter group families for " << DB_ENGINE
                  << "."
                  << std::endl;
        std::vector<Aws::String> families;
        for (const Aws::RDS::Model::DBEngineVersion &version: engineVersions) {
            Aws::String family = version.GetDBParameterGroupFamily();
            if (std::find(families.begin(), families.end(), family) ==
                families.end()) {
                families.push_back(family);
                std::cout << "  " << families.size() << ": " << family << std::endl;
            }
        }
```

```
        int choice = askQuestionForIntRange("Which family do you want to use? ", 1,
                                            static_cast<int>(families.size()));
        dbParameterGroupFamily = families[choice - 1];
    }
    if (!parameterGroupFound) {
        // 3.  Create a DB cluster parameter group.
        Aws::RDS::Model::CreateDBClusterParameterGroupRequest request;
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);
        request.SetDBParameterGroupFamily(dbParameterGroupFamily);
        request.SetDescription("Example cluster parameter group.");

        Aws::RDS::Model::CreateDBClusterParameterGroupOutcome outcome =
                client.CreateDBClusterParameterGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB cluster parameter group was successfully created."
                      << std::endl;
        }
        else {
            std::cerr << "Error with Aurora::CreateDBClusterParameterGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }

    printAsterisksLine();
    std::cout << "Let's set some parameter values in your cluster parameter group."
              << std::endl;

    Aws::Vector<Aws::RDS::Model::Parameter> autoIncrementParameters;
    // 4.  Get the parameters in the DB cluster parameter group.
    if (!getDBClusterParameters(CLUSTER_PARAMETER_GROUP_NAME, AUTO_INCREMENT_PREFIX,
                                NO_SOURCE,
                                autoIncrementParameters,
                                client)) {
        cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, "", "", client);
        return false;
    }

    Aws::Vector<Aws::RDS::Model::Parameter> updateParameters;

    for (Aws::RDS::Model::Parameter &autoIncParameter: autoIncrementParameters) {
        if (autoIncParameter.GetIsModifiable() &&
```

```
            (autoIncParameter.GetDataType() == "integer")) {
            std::cout << "The " << autoIncParameter.GetParameterName()
                      << " is described as: " <<
                      autoIncParameter.GetDescription() << "." << std::endl;
            if (autoIncParameter.ParameterValueHasBeenSet()) {
                std::cout << "The current value is "
                          << autoIncParameter.GetParameterValue()
                          << "." << std::endl;
            }
            std::vector<int> splitValues = splitToInts(
                    autoIncParameter.GetAllowedValues(), '-');
            if (splitValues.size() == 2) {
                int newValue = askQuestionForIntRange(
                        Aws::String("Enter a new value between ") +
                        autoIncParameter.GetAllowedValues() + ": ",
                        splitValues[0], splitValues[1]);
                autoIncParameter.SetParameterValue(std::to_string(newValue));
                updateParameters.push_back(autoIncParameter);

            }
            else {
                std::cerr << "Error parsing " << autoIncParameter.GetAllowedValues()
                          << std::endl;
            }
        }
    }

    {
        // 5.  Modify the auto increment parameters in the DB cluster parameter
group.
        Aws::RDS::Model::ModifyDBClusterParameterGroupRequest request;
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);
        request.SetParameters(updateParameters);

        Aws::RDS::Model::ModifyDBClusterParameterGroupOutcome outcome =
                client.ModifyDBClusterParameterGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB cluster parameter group was successfully modified."
                      << std::endl;
        }
        else {
            std::cerr << "Error with Aurora::ModifyDBClusterParameterGroup. "
                      << outcome.GetError().GetMessage()
```

```
                    << std::endl;
        }
    }

    std::cout
            << "You can get a list of parameters you've set by specifying a source
of 'user'."
            << std::endl;

    Aws::Vector<Aws::RDS::Model::Parameter> userParameters;
    // 6.  Display the modified parameters in the DB cluster parameter group.
    if (!getDBClusterParameters(CLUSTER_PARAMETER_GROUP_NAME, NO_NAME_PREFIX,
"user",
                                userParameters,
                                client)) {
        cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, "", "", client);
        return false;
    }

    for (const auto &userParameter: userParameters) {
        std::cout << "  " << userParameter.GetParameterName() << ", " <<
                  userParameter.GetDescription() << ", parameter value - "
                  << userParameter.GetParameterValue() << std::endl;
    }

    printAsterisksLine();
    std::cout << "Checking for an existing DB Cluster." << std::endl;

    Aws::RDS::Model::DBCluster dbCluster;
    // 7.  Check if the DB cluster already exists.
    if (!describeDBCluster(DB_CLUSTER_IDENTIFIER, dbCluster, client)) {
        cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, "", "", client);
        return false;
    }

    Aws::String engineVersionName;
    Aws::String engineName;
    if (dbCluster.DBClusterIdentifierHasBeenSet()) {
        std::cout << "The DB cluster already exists." << std::endl;
        engineVersionName = dbCluster.GetEngineVersion();
        engineName = dbCluster.GetEngine();

    }
    else {
```

```
        std::cout << "Let's create a DB cluster." << std::endl;
        const Aws::String administratorName = askQuestion(
                "Enter an administrator username for the database: ");
        const Aws::String administratorPassword = askQuestion(
                "Enter a password for the administrator (at least 8 characters): ");
        Aws::Vector<Aws::RDS::Model::DBEngineVersion> engineVersions;

        // 8.  Get a list of engine versions for the parameter group family.
        if (!getDBEngineVersions(DB_ENGINE, dbParameterGroupFamily, engineVersions,
                                 client)) {
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, "", "", client);
            return false;
        }

        std::cout << "The available engines for your parameter group family are:"
                  << std::endl;

        int index = 1;
        for (const Aws::RDS::Model::DBEngineVersion &engineVersion: engineVersions)
{
            std::cout << "   " << index << ": " << engineVersion.GetEngineVersion()
                      << std::endl;
            ++index;
        }
        int choice = askQuestionForIntRange("Which engine do you want to use? ", 1,

static_cast<int>(engineVersions.size()));
        const Aws::RDS::Model::DBEngineVersion engineVersion = engineVersions[choice
-
                                                                               1];

        engineName = engineVersion.GetEngine();
        engineVersionName = engineVersion.GetEngineVersion();
        std::cout << "Creating a DB cluster named '" << DB_CLUSTER_IDENTIFIER
                  << "' and database '" << DB_NAME << "'.\n"
                  << "The DB cluster is configured to use your custom cluster
parameter group '"
                  << CLUSTER_PARAMETER_GROUP_NAME << "', and \n"
                  << "selected engine version " << engineVersion.GetEngineVersion()
                  << ".\nThis typically takes several minutes." << std::endl;

        Aws::RDS::Model::CreateDBClusterRequest request;
        request.SetDBClusterIdentifier(DB_CLUSTER_IDENTIFIER);
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);
```

```
        request.SetEngine(engineName);
        request.SetEngineVersion(engineVersionName);
        request.SetMasterUsername(administratorName);
        request.SetMasterUserPassword(administratorPassword);

        Aws::RDS::Model::CreateDBClusterOutcome outcome =
                client.CreateDBCluster(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB cluster creation has started."
                      << std::endl;
        }
        else {
            std::cerr << "Error with Aurora::CreateDBCluster. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, "", "", client);
            return false;
        }
    }

    std::cout << "Waiting for the DB cluster to become available." << std::endl;

    int counter = 0;
    // 11. Wait for the DB cluster to become available.
    do {
        std::this_thread::sleep_for(std::chrono::seconds(1));
        ++counter;
        if (counter > 900) {
            std::cerr << "Wait for cluster to become available timed out ofter "
                      << counter
                      << " seconds." << std::endl;
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                             DB_CLUSTER_IDENTIFIER, "", client);
            return false;
        }

        dbCluster = Aws::RDS::Model::DBCluster();
        if (!describeDBCluster(DB_CLUSTER_IDENTIFIER, dbCluster, client)) {
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                             DB_CLUSTER_IDENTIFIER, "", client);
            return false;
        }
```

```
        if ((counter % 20) == 0) {
            std::cout << "Current DB cluster status is '"
                      << dbCluster.GetStatus()
                      << "' after " << counter << " seconds." << std::endl;
        }
    } while (dbCluster.GetStatus() != "available");

    if (dbCluster.GetStatus() == "available") {
        std::cout << "The DB cluster has been created." << std::endl;
    }

    printAsterisksLine();
    Aws::RDS::Model::DBInstance dbInstance;
    // 11.  Check if the DB instance already exists.
    if (!describeDBInstance(DB_INSTANCE_IDENTIFIER, dbInstance, client)) {
        cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, DB_CLUSTER_IDENTIFIER, "",
                         client);
        return false;
    }

    if (dbInstance.DbInstancePortHasBeenSet()) {
        std::cout << "The DB instance already exists." << std::endl;
    }
    else {
        std::cout << "Let's create a DB instance." << std::endl;

        Aws::String dbInstanceClass;
        // 12.  Get a list of instance classes.
        if (!chooseDBInstanceClass(engineName,
                                   engineVersionName,
                                   dbInstanceClass,
                                   client)) {
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, DB_CLUSTER_IDENTIFIER,
"",
                             client);
            return false;
        }

        std::cout << "Creating a DB instance named '" << DB_INSTANCE_IDENTIFIER
                  << "' with selected DB instance class '" << dbInstanceClass
                  << "'.\nThis typically takes several minutes." << std::endl;

        // 13. Create a DB instance.
        Aws::RDS::Model::CreateDBInstanceRequest request;
```

```
        request.SetDBInstanceIdentifier(DB_INSTANCE_IDENTIFIER);
        request.SetDBClusterIdentifier(DB_CLUSTER_IDENTIFIER);
        request.SetEngine(engineName);
        request.SetDBInstanceClass(dbInstanceClass);

        Aws::RDS::Model::CreateDBInstanceOutcome outcome =
                client.CreateDBInstance(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB instance creation has started."
                      << std::endl;
        }
        else {
            std::cerr << "Error with RDS::CreateDBInstance. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, DB_CLUSTER_IDENTIFIER,
""",
                             client);
            return false;
        }
    }

    std::cout << "Waiting for the DB instance to become available." << std::endl;

    counter = 0;
    // 14. Wait for the DB instance to become available.
    do {
        std::this_thread::sleep_for(std::chrono::seconds(1));
        ++counter;
        if (counter > 900) {
            std::cerr << "Wait for instance to become available timed out ofter "
                      << counter
                      << " seconds." << std::endl;
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                             DB_CLUSTER_IDENTIFIER, DB_INSTANCE_IDENTIFIER, client);
            return false;
        }

        dbInstance = Aws::RDS::Model::DBInstance();
        if (!describeDBInstance(DB_INSTANCE_IDENTIFIER, dbInstance, client)) {
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                             DB_CLUSTER_IDENTIFIER, DB_INSTANCE_IDENTIFIER, client);
            return false;
```

```
        }

        if ((counter % 20) == 0) {
            std::cout << "Current DB instance status is '"
                      << dbInstance.GetDBInstanceStatus()
                      << "' after " << counter << " seconds." << std::endl;
        }
    } while (dbInstance.GetDBInstanceStatus() != "available");

    if (dbInstance.GetDBInstanceStatus() == "available") {
        std::cout << "The DB instance has been created." << std::endl;
    }

    // 15. Display the connection string that can be used to connect a 'mysql' shell
to the database.
    displayConnection(dbCluster);

    printAsterisksLine();

    if (askYesNoQuestion(
            "Do you want to create a snapshot of your DB cluster (y/n)? ")) {
        Aws::String snapshotID(DB_CLUSTER_IDENTIFIER + "-" +
                               Aws::String(Aws::Utils::UUID::RandomUUID()));
        {
            std::cout << "Creating a snapshot named " << snapshotID << "." <<
std::endl;
            std::cout << "This typically takes a few minutes." << std::endl;

            // 16. Create a snapshot of the DB cluster. (CreateDBClusterSnapshot)
            Aws::RDS::Model::CreateDBClusterSnapshotRequest request;
            request.SetDBClusterIdentifier(DB_CLUSTER_IDENTIFIER);
            request.SetDBClusterSnapshotIdentifier(snapshotID);

            Aws::RDS::Model::CreateDBClusterSnapshotOutcome outcome =
                    client.CreateDBClusterSnapshot(request);

            if (outcome.IsSuccess()) {
                std::cout << "Snapshot creation has started."
                          << std::endl;
            }
            else {
                std::cerr << "Error with Aurora::CreateDBClusterSnapshot. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
```

```
                cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                                 DB_CLUSTER_IDENTIFIER, DB_INSTANCE_IDENTIFIER,
client);
                return false;
            }
        }

        std::cout << "Waiting for the snapshot to become available." << std::endl;

        Aws::RDS::Model::DBClusterSnapshot snapshot;
        counter = 0;
        do {
            std::this_thread::sleep_for(std::chrono::seconds(1));
            ++counter;
            if (counter > 600) {
                std::cerr << "Wait for snapshot to be available timed out ofter "
                          << counter
                          << " seconds." << std::endl;
                cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                                 DB_CLUSTER_IDENTIFIER, DB_INSTANCE_IDENTIFIER,
client);
                return false;
            }

            // 17. Wait for the snapshot to become available.
            Aws::RDS::Model::DescribeDBClusterSnapshotsRequest request;
            request.SetDBClusterSnapshotIdentifier(snapshotID);

            Aws::RDS::Model::DescribeDBClusterSnapshotsOutcome outcome =
                    client.DescribeDBClusterSnapshots(request);

            if (outcome.IsSuccess()) {
                snapshot = outcome.GetResult().GetDBClusterSnapshots()[0];
            }
            else {
                std::cerr << "Error with Aurora::DescribeDBClusterSnapshots. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                                 DB_CLUSTER_IDENTIFIER, DB_INSTANCE_IDENTIFIER,
client);
                return false;
            }
```

```
            if ((counter % 20) == 0) {
                std::cout << "Current snapshot status is '"
                          << snapshot.GetStatus()
                          << "' after " << counter << " seconds." << std::endl;
            }
        } while (snapshot.GetStatus() != "available");

        if (snapshot.GetStatus() != "available") {
            std::cout << "A snapshot has been created." << std::endl;
        }
    }

    printAsterisksLine();

    bool result = true;
    if (askYesNoQuestion(
            "Do you want to delete the DB cluster, DB instance, and parameter group
 (y/n)? ")) {
        result = cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                                  DB_CLUSTER_IDENTIFIER, DB_INSTANCE_IDENTIFIER,
                                  client);
    }

    return result;
}

//! Routine which gets a DB cluster description.
/*!
 \sa describeDBCluster()
 \param dbClusterIdentifier: A DB cluster identifier.
 \param clusterResult: The 'DBCluster' object containing the description.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::describeDBCluster(const Aws::String &dbClusterIdentifier,
                                       Aws::RDS::Model::DBCluster &clusterResult,
                                       const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBClustersRequest request;
    request.SetDBClusterIdentifier(dbClusterIdentifier);

    Aws::RDS::Model::DescribeDBClustersOutcome outcome =
            client.DescribeDBClusters(request);

    bool result = true;
```

```
    if (outcome.IsSuccess()) {
        clusterResult = outcome.GetResult().GetDBClusters()[0];
    }
    else if (outcome.GetError().GetErrorType() !=
             Aws::RDS::RDSErrors::D_B_CLUSTER_NOT_FOUND_FAULT) {
        result = false;
        std::cerr << "Error with Aurora::GDescribeDBClusters. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
        // This example does not log an error if the DB cluster does not exist.
        // Instead, clusterResult is set to empty.
    else {
        clusterResult = Aws::RDS::Model::DBCluster();
    }

    return result;

}


//! Routine which gets DB parameters using the 'DescribeDBClusterParameters' api.
/*!
 \sa getDBCLusterParameters()
 \param parameterGroupName: The name of the cluster parameter group.
 \param namePrefix: Prefix string to filter results by parameter name.
 \param source: A source such as 'user', ignored if empty.
 \param parametersResult: Vector of 'Parameter' objects returned by the routine.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::getDBCLusterParameters(const Aws::String &parameterGroupName,
                                            const Aws::String &namePrefix,
                                            const Aws::String &source,
                                            Aws::Vector<Aws::RDS::Model::Parameter>
 &parametersResult,
                                            const Aws::RDS::RDSClient &client) {
    Aws::String marker; // The marker is used for pagination.
    do {
        Aws::RDS::Model::DescribeDBClusterParametersRequest request;
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);
        if (!marker.empty()) {
            request.SetMarker(marker);
        }
```

```
        if (!source.empty()) {
            request.SetSource(source);
        }

        Aws::RDS::Model::DescribeDBClusterParametersOutcome outcome =
                client.DescribeDBClusterParameters(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::RDS::Model::Parameter> &parameters =
                    outcome.GetResult().GetParameters();
            for (const Aws::RDS::Model::Parameter &parameter: parameters) {
                if (!namePrefix.empty()) {
                    if (parameter.GetParameterName().find(namePrefix) == 0) {
                        parametersResult.push_back(parameter);
                    }
                }
                else {
                    parametersResult.push_back(parameter);
                }
            }

            marker = outcome.GetResult().GetMarker();
        }
        else {
            std::cerr << "Error with Aurora::DescribeDBClusterParameters. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (!marker.empty());

    return true;
}


//! Routine which gets available DB engine versions for an engine name and
//! an optional parameter group family.
/*!
 \sa getDBEngineVersions()
 \param engineName: A DB engine name.
 \param parameterGroupFamily: A parameter group family name, ignored if empty.
 \param engineVersionsResult: Vector of 'DBEngineVersion' objects returned by the
 routine.
 \param client: 'RDSClient' instance.
```

```
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::getDBEngineVersions(const Aws::String &engineName,
                                         const Aws::String &parameterGroupFamily,

 Aws::Vector<Aws::RDS::Model::DBEngineVersion> &engineVersionsResult,
                                         const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBEngineVersionsRequest request;
    request.SetEngine(engineName);
    if (!parameterGroupFamily.empty()) {
        request.SetDBParameterGroupFamily(parameterGroupFamily);
    }

    engineVersionsResult.clear();
    Aws::String marker; // The marker is used for pagination.
    do {
        if (!marker.empty()) {
            request.SetMarker(marker);
        }

        Aws::RDS::Model::DescribeDBEngineVersionsOutcome outcome =
                client.DescribeDBEngineVersions(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::RDS::Model::DBEngineVersion> &engineVersions =
                    outcome.GetResult().GetDBEngineVersions();

            engineVersionsResult.insert(engineVersionsResult.end(),
                                        engineVersions.begin(),
 engineVersions.end());
            marker  = outcome.GetResult().GetMarker();
        }
        else {
            std::cerr << "Error with Aurora::DescribeDBEngineVersionsRequest. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
    } while (!marker.empty());

    return true;
}


//! Routine which gets a DB instance description.
```

```
/*!
 \sa describeDBCluster()
 \param dbInstanceIdentifier: A DB instance identifier.
 \param instanceResult: The 'DBInstance' object containing the description.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::describeDBInstance(const Aws::String &dbInstanceIdentifier,
                                        Aws::RDS::Model::DBInstance &instanceResult,
                                        const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBInstancesRequest request;
    request.SetDBInstanceIdentifier(dbInstanceIdentifier);

    Aws::RDS::Model::DescribeDBInstancesOutcome outcome =
            client.DescribeDBInstances(request);

    bool result = true;
    if (outcome.IsSuccess()) {
        instanceResult = outcome.GetResult().GetDBInstances()[0];
    }
    else if (outcome.GetError().GetErrorType() !=
             Aws::RDS::RDSErrors::D_B_INSTANCE_NOT_FOUND_FAULT) {
        result = false;
        std::cerr << "Error with Aurora::DescribeDBInstances. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
        // This example does not log an error if the DB instance does not exist.
        // Instead, instanceResult is set to empty.
    else {
        instanceResult = Aws::RDS::Model::DBInstance();
    }

    return result;
}


//! Routine which gets available DB instance classes, displays the list
//! to the user, and returns the user selection.
/*!
 \sa chooseDBInstanceClass()
 \param engineName: The DB engine name.
 \param engineVersion: The DB engine version.
 \param dbInstanceClass: String for DB instance class chosen by the user.
```

```
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::chooseDBInstanceClass(const Aws::String &engine,
                                           const Aws::String &engineVersion,
                                           Aws::String &dbInstanceClass,
                                           const Aws::RDS::RDSClient &client) {
    std::vector<Aws::String> instanceClasses;
    Aws::String marker; // The marker is used for pagination.
    do {
        Aws::RDS::Model::DescribeOrderableDBInstanceOptionsRequest request;
        request.SetEngine(engine);
        request.SetEngineVersion(engineVersion);
        if (!marker.empty()) {
            request.SetMarker(marker);
        }

        Aws::RDS::Model::DescribeOrderableDBInstanceOptionsOutcome outcome =
                client.DescribeOrderableDBInstanceOptions(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::RDS::Model::OrderableDBInstanceOption> &options =
                    outcome.GetResult().GetOrderableDBInstanceOptions();
            for (const Aws::RDS::Model::OrderableDBInstanceOption &option: options)
 {
                const Aws::String &instanceClass = option.GetDBInstanceClass();
                if (std::find(instanceClasses.begin(), instanceClasses.end(),
                              instanceClass) == instanceClasses.end()) {
                    instanceClasses.push_back(instanceClass);
                }
            }
            marker = outcome.GetResult().GetMarker();
        }
        else {
            std::cerr << "Error with Aurora::DescribeOrderableDBInstanceOptions. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (!marker.empty());

    std::cout << "The available DB instance classes for your database engine are:"
              << std::endl;
    for (int i = 0; i < instanceClasses.size(); ++i) {
```

```
        std::cout << "   " << i + 1 << ": " << instanceClasses[i] << std::endl;
    }

    int choice = askQuestionForIntRange(
            "Which DB instance class do you want to use? ",
            1, static_cast<int>(instanceClasses.size()));
    dbInstanceClass = instanceClasses[choice - 1];
    return true;
}

//! Routine which deletes resources created by the scenario.
/*!
\sa cleanUpResources()
\param parameterGroupName: A parameter group name, this may be empty.
\param dbInstanceIdentifier: A DB instance identifier, this may be empty.
\param client: 'RDSClient' instance.
\return bool: Successful completion.
*/
bool AwsDoc::Aurora::cleanUpResources(const Aws::String &parameterGroupName,
                                      const Aws::String &dbClusterIdentifier,
                                      const Aws::String &dbInstanceIdentifier,
                                      const Aws::RDS::RDSClient &client) {
    bool result = true;
    bool instanceDeleting = false;
    bool clusterDeleting = false;
    if (!dbInstanceIdentifier.empty()) {
        {
            // 18. Delete the DB instance.
            Aws::RDS::Model::DeleteDBInstanceRequest request;
            request.SetDBInstanceIdentifier(dbInstanceIdentifier);
            request.SetSkipFinalSnapshot(true);
            request.SetDeleteAutomatedBackups(true);

            Aws::RDS::Model::DeleteDBInstanceOutcome outcome =
                    client.DeleteDBInstance(request);

            if (outcome.IsSuccess()) {
                std::cout << "DB instance deletion has started."
                          << std::endl;
                instanceDeleting = true;
                std::cout
                        << "Waiting for DB instance to delete before deleting the
 parameter group."
                        << std::endl;
```

```
            }
            else {
                std::cerr << "Error with Aurora::DeleteDBInstance. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
        }
    }

    if (!dbClusterIdentifier.empty()) {
        {
            // 19. Delete the DB cluster.
            Aws::RDS::Model::DeleteDBClusterRequest request;
            request.SetDBClusterIdentifier(dbClusterIdentifier);
            request.SetSkipFinalSnapshot(true);

            Aws::RDS::Model::DeleteDBClusterOutcome outcome =
                    client.DeleteDBCluster(request);

            if (outcome.IsSuccess()) {
                std::cout << "DB cluster deletion has started."
                          << std::endl;
                clusterDeleting = true;
                std::cout
                        << "Waiting for DB cluster to delete before deleting the
parameter group."
                        << std::endl;
                std::cout << "This may take a while." << std::endl;
            }
            else {
                std::cerr << "Error with Aurora::DeleteDBCluster. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
        }
    }
    int counter = 0;

    while (clusterDeleting || instanceDeleting) {
        // 20. Wait for the DB cluster and instance to be deleted.
        std::this_thread::sleep_for(std::chrono::seconds(1));
        ++counter;
```

```
        if (counter > 800) {
            std::cerr << "Wait for instance to delete timed out ofter " << counter
                      << " seconds." << std::endl;
            return false;
        }

        Aws::RDS::Model::DBInstance dbInstance = Aws::RDS::Model::DBInstance();
        if (instanceDeleting) {
            if (!describeDBInstance(dbInstanceIdentifier, dbInstance, client)) {
                return false;
            }
            instanceDeleting = dbInstance.DBInstanceIdentifierHasBeenSet();
        }

        Aws::RDS::Model::DBCluster dbCluster = Aws::RDS::Model::DBCluster();
        if (clusterDeleting) {
            if (!describeDBCluster(dbClusterIdentifier, dbCluster, client)) {
                return false;
            }

            clusterDeleting = dbCluster.DBClusterIdentifierHasBeenSet();
        }

        if ((counter % 20) == 0) {
            if (instanceDeleting) {
                std::cout << "Current DB instance status is '"
                          << dbInstance.GetDBInstanceStatus() << "." << std::endl;
            }

            if (clusterDeleting) {
                std::cout << "Current DB cluster status is '"
                          << dbCluster.GetStatus() << "." << std::endl;
            }
        }
    }

    if (!parameterGroupName.empty()) {
        // 21. Delete the DB cluster parameter group.
        Aws::RDS::Model::DeleteDBClusterParameterGroupRequest request;
        request.SetDBClusterParameterGroupName(parameterGroupName);

        Aws::RDS::Model::DeleteDBClusterParameterGroupOutcome outcome =
                client.DeleteDBClusterParameterGroup(request);
```

```
        if (outcome.IsSuccess()) {
            std::cout << "The DB parameter group was successfully deleted."
                      << std::endl;
        }
        else {
            std::cerr << "Error with Aurora::DeleteDBClusterParameterGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
        }
    }

    return result;
}
```

- For API details, see the following topics in *AWS SDK for C++ API Reference*.
  - CreateDBCluster
  - CreateDBClusterParameterGroup
  - CreateDBClusterSnapshot
  - CreateDBInstance
  - DeleteDBCluster
  - DeleteDBClusterParameterGroup
  - DeleteDBInstance
  - DescribeDBClusterParameterGroups
  - DescribeDBClusterParameters
  - DescribeDBClusterSnapshots
  - DescribeDBClusters
  - DescribeDBEngineVersions
  - DescribeDBInstances
  - DescribeOrderableDBInstanceOptions
  - ModifyDBClusterParameterGroup

Actions

`CreateDBCluster`

The following code example shows how to use `CreateDBCluster`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
    Aws::Client::ClientConfiguration clientConfig;
    // Optional: Set to the AWS Region (overrides config file).
    // clientConfig.region = "us-east-1";

Aws::RDS::RDSClient client(clientConfig);

    Aws::RDS::Model::CreateDBClusterRequest request;
    request.SetDBClusterIdentifier(DB_CLUSTER_IDENTIFIER);
    request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);
    request.SetEngine(engineName);
    request.SetEngineVersion(engineVersionName);
    request.SetMasterUsername(administratorName);
    request.SetMasterUserPassword(administratorPassword);

    Aws::RDS::Model::CreateDBClusterOutcome outcome =
            client.CreateDBCluster(request);

    if (outcome.IsSuccess()) {
        std::cout << "The DB cluster creation has started."
                  << std::endl;
    }
    else {
        std::cerr << "Error with Aurora::CreateDBCluster. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
        cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, "", "", client);
        return false;
    }
```

- For API details, see CreateDBCluster in *AWS SDK for C++ API Reference*.

`CreateDBClusterParameterGroup`

The following code example shows how to use `CreateDBClusterParameterGroup`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
    Aws::Client::ClientConfiguration clientConfig;
    // Optional: Set to the AWS Region (overrides config file).
    // clientConfig.region = "us-east-1";

Aws::RDS::RDSClient client(clientConfig);

    Aws::RDS::Model::CreateDBClusterParameterGroupRequest request;
    request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);
    request.SetDBParameterGroupFamily(dbParameterGroupFamily);
    request.SetDescription("Example cluster parameter group.");

    Aws::RDS::Model::CreateDBClusterParameterGroupOutcome outcome =
            client.CreateDBClusterParameterGroup(request);

    if (outcome.IsSuccess()) {
        std::cout << "The DB cluster parameter group was successfully created."
                  << std::endl;
    }
    else {
        std::cerr << "Error with Aurora::CreateDBClusterParameterGroup. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
        return false;
    }
```

- For API details, see CreateDBClusterParameterGroup in *AWS SDK for C++ API Reference*.

`CreateDBClusterSnapshot`

The following code example shows how to use `CreateDBClusterSnapshot`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

            Aws::RDS::Model::CreateDBClusterSnapshotRequest request;
            request.SetDBClusterIdentifier(DB_CLUSTER_IDENTIFIER);
            request.SetDBClusterSnapshotIdentifier(snapshotID);

            Aws::RDS::Model::CreateDBClusterSnapshotOutcome outcome =
                    client.CreateDBClusterSnapshot(request);

            if (outcome.IsSuccess()) {
                std::cout << "Snapshot creation has started."
                          << std::endl;
            }
            else {
                std::cerr << "Error with Aurora::CreateDBClusterSnapshot. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                                 DB_CLUSTER_IDENTIFIER, DB_INSTANCE_IDENTIFIER,
client);
                return false;
            }
```

- For API details, see CreateDBClusterSnapshot in *AWS SDK for C++ API Reference*.

`CreateDBInstance`

The following code example shows how to use `CreateDBInstance`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

        Aws::RDS::Model::CreateDBInstanceRequest request;
        request.SetDBInstanceIdentifier(DB_INSTANCE_IDENTIFIER);
        request.SetDBClusterIdentifier(DB_CLUSTER_IDENTIFIER);
        request.SetEngine(engineName);
        request.SetDBInstanceClass(dbInstanceClass);

        Aws::RDS::Model::CreateDBInstanceOutcome outcome =
                client.CreateDBInstance(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB instance creation has started."
                      << std::endl;
        }
        else {
            std::cerr << "Error with RDS::CreateDBInstance. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME, DB_CLUSTER_IDENTIFIER,
"",
                             client);
            return false;
        }
```

- For API details, see CreateDBInstance in *AWS SDK for C++ API Reference*.

`DeleteDBCluster`

The following code example shows how to use `DeleteDBCluster`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

            Aws::RDS::Model::DeleteDBClusterRequest request;
            request.SetDBClusterIdentifier(dbClusterIdentifier);
            request.SetSkipFinalSnapshot(true);

            Aws::RDS::Model::DeleteDBClusterOutcome outcome =
                    client.DeleteDBCluster(request);

            if (outcome.IsSuccess()) {
                std::cout << "DB cluster deletion has started."
                          << std::endl;
                clusterDeleting = true;
                std::cout
                        << "Waiting for DB cluster to delete before deleting the
parameter group."
                        << std::endl;
                std::cout << "This may take a while." << std::endl;
            }
            else {
                std::cerr << "Error with Aurora::DeleteDBCluster. "
```

```
                        << outcome.GetError().GetMessage()
                        << std::endl;
                result = false;
            }
```

- For API details, see DeleteDBCluster in *AWS SDK for C++ API Reference*.

`DeleteDBClusterParameterGroup`

The following code example shows how to use `DeleteDBClusterParameterGroup`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
    Aws::Client::ClientConfiguration clientConfig;
    // Optional: Set to the AWS Region (overrides config file).
    // clientConfig.region = "us-east-1";

Aws::RDS::RDSClient client(clientConfig);

    Aws::RDS::Model::DeleteDBClusterParameterGroupRequest request;
    request.SetDBClusterParameterGroupName(parameterGroupName);

    Aws::RDS::Model::DeleteDBClusterParameterGroupOutcome outcome =
            client.DeleteDBClusterParameterGroup(request);

    if (outcome.IsSuccess()) {
        std::cout << "The DB parameter group was successfully deleted."
                  << std::endl;
    }
    else {
        std::cerr << "Error with Aurora::DeleteDBClusterParameterGroup. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
        result = false;
```

```
        }
```

- For API details, see DeleteDBClusterParameterGroup in *AWS SDK for C++ API Reference*.

`DeleteDBInstance`

The following code example shows how to use `DeleteDBInstance`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

            Aws::RDS::Model::DeleteDBInstanceRequest request;
            request.SetDBInstanceIdentifier(dbInstanceIdentifier);
            request.SetSkipFinalSnapshot(true);
            request.SetDeleteAutomatedBackups(true);

            Aws::RDS::Model::DeleteDBInstanceOutcome outcome =
                    client.DeleteDBInstance(request);

            if (outcome.IsSuccess()) {
                std::cout << "DB instance deletion has started."
                          << std::endl;
                instanceDeleting = true;
                std::cout
                        << "Waiting for DB instance to delete before deleting the
parameter group."
                        << std::endl;
            }
            else {
                std::cerr << "Error with Aurora::DeleteDBInstance. "
```

```
                        << outcome.GetError().GetMessage()
                        << std::endl;
                result = false;
            }
```

- For API details, see DeleteDBInstance in *AWS SDK for C++ API Reference*.

`DescribeDBClusterParameterGroups`

The following code example shows how to use `DescribeDBClusterParameterGroups`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

        Aws::RDS::Model::DescribeDBClusterParameterGroupsRequest request;
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);

        Aws::RDS::Model::DescribeDBClusterParameterGroupsOutcome outcome =
                client.DescribeDBClusterParameterGroups(request);

        if (outcome.IsSuccess()) {
            std::cout << "DB cluster parameter group named '" <<
                      CLUSTER_PARAMETER_GROUP_NAME << "' already exists." <<
std::endl;
            dbParameterGroupFamily =
outcome.GetResult().GetDBClusterParameterGroups()[0].GetDBParameterGroupFamily();
        }

        else {
            std::cerr << "Error with Aurora::DescribeDBClusterParameterGroups. "
```

```
                    << outcome.GetError().GetMessage()
                    << std::endl;
            return false;
        }
```

- For API details, see DescribeDBClusterParameterGroups in *AWS SDK for C++ API Reference*.

`DescribeDBClusterParameters`

The following code example shows how to use `DescribeDBClusterParameters`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);


//! Routine which gets DB parameters using the 'DescribeDBClusterParameters' api.
/*!
 \sa getDBClusterParameters()
 \param parameterGroupName: The name of the cluster parameter group.
 \param namePrefix: Prefix string to filter results by parameter name.
 \param source: A source such as 'user', ignored if empty.
 \param parametersResult: Vector of 'Parameter' objects returned by the routine.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::getDBClusterParameters(const Aws::String &parameterGroupName,
                                            const Aws::String &namePrefix,
                                            const Aws::String &source,
                                            Aws::Vector<Aws::RDS::Model::Parameter>
 &parametersResult,
```

```
                                                const Aws::RDS::RDSClient &client) {
    Aws::String marker; // The marker is used for pagination.
    do {
        Aws::RDS::Model::DescribeDBClusterParametersRequest request;
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);
        if (!marker.empty()) {
            request.SetMarker(marker);
        }
        if (!source.empty()) {
            request.SetSource(source);
        }

        Aws::RDS::Model::DescribeDBClusterParametersOutcome outcome =
                client.DescribeDBClusterParameters(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::RDS::Model::Parameter> &parameters =
                    outcome.GetResult().GetParameters();
            for (const Aws::RDS::Model::Parameter &parameter: parameters) {
                if (!namePrefix.empty()) {
                    if (parameter.GetParameterName().find(namePrefix) == 0) {
                        parametersResult.push_back(parameter);
                    }
                }
                else {
                    parametersResult.push_back(parameter);
                }
            }

            marker = outcome.GetResult().GetMarker();
        }
        else {
            std::cerr << "Error with Aurora::DescribeDBClusterParameters. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (!marker.empty());

    return true;
}
```

- For API details, see DescribeDBClusterParameters in *AWS SDK for C++ API Reference*.

`DescribeDBClusterSnapshots`

The following code example shows how to use `DescribeDBClusterSnapshots`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

            Aws::RDS::Model::DescribeDBClusterSnapshotsRequest request;
            request.SetDBClusterSnapshotIdentifier(snapshotID);

            Aws::RDS::Model::DescribeDBClusterSnapshotsOutcome outcome =
                    client.DescribeDBClusterSnapshots(request);

            if (outcome.IsSuccess()) {
                snapshot = outcome.GetResult().GetDBClusterSnapshots()[0];
            }
            else {
                std::cerr << "Error with Aurora::DescribeDBClusterSnapshots. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUpResources(CLUSTER_PARAMETER_GROUP_NAME,
                                 DB_CLUSTER_IDENTIFIER, DB_INSTANCE_IDENTIFIER,
client);
                return false;
            }
```

- For API details, see DescribeDBClusterSnapshots in *AWS SDK for C++ API Reference*.

`DescribeDBClusters`

The following code example shows how to use `DescribeDBClusters`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

//! Routine which gets a DB cluster description.
/*!
 \sa describeDBCluster()
 \param dbClusterIdentifier: A DB cluster identifier.
 \param clusterResult: The 'DBCluster' object containing the description.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::describeDBCluster(const Aws::String &dbClusterIdentifier,
                                       Aws::RDS::Model::DBCluster &clusterResult,
                                       const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBClustersRequest request;
    request.SetDBClusterIdentifier(dbClusterIdentifier);

    Aws::RDS::Model::DescribeDBClustersOutcome outcome =
            client.DescribeDBClusters(request);

    bool result = true;
    if (outcome.IsSuccess()) {
        clusterResult = outcome.GetResult().GetDBClusters()[0];
    }
    else if (outcome.GetError().GetErrorType() !=
             Aws::RDS::RDSErrors::D_B_CLUSTER_NOT_FOUND_FAULT) {
        result = false;
        std::cerr << "Error with Aurora::GDescribeDBClusters. "
```

```
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
        // This example does not log an error if the DB cluster does not exist.
        // Instead, clusterResult is set to empty.
    else {
        clusterResult = Aws::RDS::Model::DBCluster();
    }

    return result;

}
```

- For API details, see DescribeDBClusters in *AWS SDK for C++ API Reference*.

`DescribeDBEngineVersions`

The following code example shows how to use `DescribeDBEngineVersions`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);


//! Routine which gets available DB engine versions for an engine name and
//! an optional parameter group family.
/*!
 \sa getDBEngineVersions()
 \param engineName: A DB engine name.
 \param parameterGroupFamily: A parameter group family name, ignored if empty.
```

```
 \param engineVersionsResult: Vector of 'DBEngineVersion' objects returned by the
 routine.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::getDBEngineVersions(const Aws::String &engineName,
                                         const Aws::String &parameterGroupFamily,

 Aws::Vector<Aws::RDS::Model::DBEngineVersion> &engineVersionsResult,
                                         const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBEngineVersionsRequest request;
    request.SetEngine(engineName);
    if (!parameterGroupFamily.empty()) {
        request.SetDBParameterGroupFamily(parameterGroupFamily);
    }

    engineVersionsResult.clear();
    Aws::String marker; // The marker is used for pagination.
    do {
        if (!marker.empty()) {
            request.SetMarker(marker);
        }

        Aws::RDS::Model::DescribeDBEngineVersionsOutcome outcome =
                client.DescribeDBEngineVersions(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::RDS::Model::DBEngineVersion> &engineVersions =
                    outcome.GetResult().GetDBEngineVersions();

            engineVersionsResult.insert(engineVersionsResult.end(),
                                        engineVersions.begin(),
 engineVersions.end());
            marker  = outcome.GetResult().GetMarker();
        }
        else {
            std::cerr << "Error with Aurora::DescribeDBEngineVersionsRequest. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
    } while (!marker.empty());

    return true;
}
```

- For API details, see DescribeDBEngineVersions in *AWS SDK for C++ API Reference*.

`DescribeDBInstances`

The following code example shows how to use `DescribeDBInstances`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);


//! Routine which gets a DB instance description.
/*!
 \sa describeDBCluster()
 \param dbInstanceIdentifier: A DB instance identifier.
 \param instanceResult: The 'DBInstance' object containing the description.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::describeDBInstance(const Aws::String &dbInstanceIdentifier,
                                        Aws::RDS::Model::DBInstance &instanceResult,
                                        const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBInstancesRequest request;
    request.SetDBInstanceIdentifier(dbInstanceIdentifier);

    Aws::RDS::Model::DescribeDBInstancesOutcome outcome =
            client.DescribeDBInstances(request);

    bool result = true;
    if (outcome.IsSuccess()) {
```

```
        instanceResult = outcome.GetResult().GetDBInstances()[0];
    }
    else if (outcome.GetError().GetErrorType() !=
             Aws::RDS::RDSErrors::D_B_INSTANCE_NOT_FOUND_FAULT) {
        result = false;
        std::cerr << "Error with Aurora::DescribeDBInstances. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
        // This example does not log an error if the DB instance does not exist.
        // Instead, instanceResult is set to empty.
    else {
        instanceResult = Aws::RDS::Model::DBInstance();
    }

    return result;
}
```

- For API details, see DescribeDBInstances in *AWS SDK for C++ API Reference*.

`DescribeOrderableDBInstanceOptions`

The following code example shows how to use `DescribeOrderableDBInstanceOptions`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);


//! Routine which gets available DB instance classes, displays the list
//! to the user, and returns the user selection.
```

```
/*!
 \sa chooseDBInstanceClass()
 \param engineName: The DB engine name.
 \param engineVersion: The DB engine version.
 \param dbInstanceClass: String for DB instance class chosen by the user.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::Aurora::chooseDBInstanceClass(const Aws::String &engine,
                                           const Aws::String &engineVersion,
                                           Aws::String &dbInstanceClass,
                                           const Aws::RDS::RDSClient &client) {
    std::vector<Aws::String> instanceClasses;
    Aws::String marker; // The marker is used for pagination.
    do {
        Aws::RDS::Model::DescribeOrderableDBInstanceOptionsRequest request;
        request.SetEngine(engine);
        request.SetEngineVersion(engineVersion);
        if (!marker.empty()) {
            request.SetMarker(marker);
        }

        Aws::RDS::Model::DescribeOrderableDBInstanceOptionsOutcome outcome =
                client.DescribeOrderableDBInstanceOptions(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::RDS::Model::OrderableDBInstanceOption> &options =
                    outcome.GetResult().GetOrderableDBInstanceOptions();
            for (const Aws::RDS::Model::OrderableDBInstanceOption &option: options)
 {
                const Aws::String &instanceClass = option.GetDBInstanceClass();
                if (std::find(instanceClasses.begin(), instanceClasses.end(),
                              instanceClass) == instanceClasses.end()) {
                    instanceClasses.push_back(instanceClass);
                }
            }
            marker = outcome.GetResult().GetMarker();
        }
        else {
            std::cerr << "Error with Aurora::DescribeOrderableDBInstanceOptions. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
```

```
    } while (!marker.empty());

    std::cout << "The available DB instance classes for your database engine are:"
              << std::endl;
    for (int i = 0; i < instanceClasses.size(); ++i) {
        std::cout << "   " << i + 1 << ": " << instanceClasses[i] << std::endl;
    }

    int choice = askQuestionForIntRange(
            "Which DB instance class do you want to use? ",
            1, static_cast<int>(instanceClasses.size()));
    dbInstanceClass = instanceClasses[choice - 1];
    return true;
}
```

- For API details, see DescribeOrderableDBInstanceOptions in *AWS SDK for C++ API Reference*.

`ModifyDBClusterParameterGroup`

The following code example shows how to use `ModifyDBClusterParameterGroup`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

        Aws::RDS::Model::ModifyDBClusterParameterGroupRequest request;
        request.SetDBClusterParameterGroupName(CLUSTER_PARAMETER_GROUP_NAME);
        request.SetParameters(updateParameters);

        Aws::RDS::Model::ModifyDBClusterParameterGroupOutcome outcome =
```

```
            client.ModifyDBClusterParameterGroup(request);

    if (outcome.IsSuccess()) {
        std::cout << "The DB cluster parameter group was successfully modified."
                  << std::endl;
    }
    else {
        std::cerr << "Error with Aurora::ModifyDBClusterParameterGroup. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
```

- For API details, see ModifyDBClusterParameterGroup in *AWS SDK for C++ API Reference*.

Scenarios

Create an Aurora Serverless work item tracker

The following code example shows how to create a web application that tracks work items in an Amazon Aurora Serverless database and uses Amazon Simple Email Service (Amazon SES) to send reports.

SDK for C++

Shows how to create a web application that tracks and reports on work items stored in an Amazon Aurora Serverless database.

For complete source code and instructions on how to set up a C++ REST API that queries Amazon Aurora Serverless data and for use by a React application, see the full example on GitHub.

Services used in this example

- Aurora
- Amazon RDS
- Amazon RDS Data Service
- Amazon SES

Auto Scaling examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with Auto Scaling.

Basics are code examples that show you how to perform the essential operations within a service.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Get started
- Basics
- Actions

Get started

Hello Auto Scaling

The following code example shows how to get started using Auto Scaling.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Code for the CMakeLists.txt CMake file.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS autoscaling)
```

```
# Set this project's name.
project("hello_autoscaling")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD AND AWSSDK_INSTALL_AS_SHARED_LIBS)
     # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

     # set(BIN_SUB_DIR "/Debug") # If you are building from the command line, you
 may need to uncomment this
                                     # and set the proper subdirectory to the
 executables' location.

     AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_autoscaling.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Code for the hello_autoscaling.cpp source file.

```
#include <aws/core/Aws.h>
```

```
#include <aws/autoscaling/AutoScalingClient.h>
#include <aws/autoscaling/model/DescribeAutoScalingGroupsRequest.h>
#include <iostream>

/*
 *  A "Hello Autoscaling" starter application which initializes an Amazon EC2 Auto
 Scaling client and describes the
 *  Amazon EC2 Auto Scaling groups.
 *
 *  main function
 *
 *  Usage: 'hello_autoscaling'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::AutoScaling::AutoScalingClient autoscalingClient(clientConfig);

        std::vector<Aws::String> groupNames;
        Aws::String nextToken; // Used for pagination.

        do {

            Aws::AutoScaling::Model::DescribeAutoScalingGroupsRequest request;
            if (!nextToken.empty()) {
                request.SetNextToken(nextToken);
            }

            Aws::AutoScaling::Model::DescribeAutoScalingGroupsOutcome outcome =
                    autoscalingClient.DescribeAutoScalingGroups(request);

            if (outcome.IsSuccess()) {
                const Aws::Vector<Aws::AutoScaling::Model::AutoScalingGroup>
 &autoScalingGroups =
```

```
                        outcome.GetResult().GetAutoScalingGroups();
                for (auto &group: autoScalingGroups) {
                    groupNames.push_back(group.GetAutoScalingGroupName());
                }
                nextToken = outcome.GetResult().GetNextToken();
            } else {
                std::cerr << "Error with AutoScaling::DescribeAutoScalingGroups. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = 1;
                break;
            }
        } while (!nextToken.empty());

        std::cout << "Found " << groupNames.size() << " AutoScaling groups." <<
 std::endl;
        for (auto &groupName: groupNames) {
            std::cout << "AutoScaling group: " << groupName << std::endl;
        }

    }


    Aws::ShutdownAPI(options); // Should only be called once.
    return result;
}
```

- For API details, see DescribeAutoScalingGroups in *AWS SDK for C++ API Reference*.

Basics

Learn the basics

The following code example shows how to:

- Create an Amazon EC2 Auto Scaling group with a launch template and Availability Zones, and get information about running instances.
- Enable Amazon CloudWatch metrics collection.
- Update the group's desired capacity and wait for an instance to start.
- Terminate an instance in the group.

- List scaling activities that occur in response to user requests and capacity changes.
- Get statistics for CloudWatch metrics, then clean up resources.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Routine which demonstrates using an Auto Scaling group
//! to manage Amazon EC2 instances.
/*!
  \sa groupsAndInstancesScenario()
  \param clientConfig: AWS client configuration.
  \return bool: Successful completion.
 */
bool AwsDoc::AutoScaling::groupsAndInstancesScenario(
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::String templateName;
    Aws::EC2::EC2Client ec2Client(clientConfig);

    std::cout << std::setfill('*') << std::setw(ASTERISK_FILL_WIDTH) << " "
              << std::endl;
    std::cout
            << "Welcome to the Amazon Elastic Compute Cloud (Amazon EC2) Auto
 Scaling "
            << "demo for managing groups and instances." << std::endl;
    std::cout << std::setfill('*') << std::setw(ASTERISK_FILL_WIDTH) << " \n"
              << std::endl;

    std::cout << "This example requires an EC2 launch template." << std::endl;
    if (askYesNoQuestion(
            "Would you like to use an existing EC2 launch template (y/n)?  ")) {

        // 1. Specify the name of an existing EC2 launch template.
        templateName = askQuestion(
                "Enter the name of the existing EC2 launch template.  ");

        Aws::EC2::Model::DescribeLaunchTemplatesRequest request;
```

```
        request.AddLaunchTemplateNames(templateName);
        Aws::EC2::Model::DescribeLaunchTemplatesOutcome outcome =
                ec2Client.DescribeLaunchTemplates(request);

        if (outcome.IsSuccess()) {
            std::cout << "Validated the EC2 launch template '" << templateName
                      << "' exists by calling DescribeLaunchTemplate." << std::endl;
        }
        else {
            std::cerr << "Error validating the existence of the launch template. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
    }
    else { // 2.  Or create a new EC2 launch template.
        templateName = askQuestion("Enter the name for a new EC2 launch template:
");

        Aws::EC2::Model::CreateLaunchTemplateRequest request;
        request.SetLaunchTemplateName(templateName);

        Aws::EC2::Model::RequestLaunchTemplateData requestLaunchTemplateData;

requestLaunchTemplateData.SetInstanceType(EC2_LAUNCH_TEMPLATE_INSTANCE_TYPE);
        requestLaunchTemplateData.SetImageId(EC2_LAUNCH_TEMPLATE_IMAGE_ID);

        request.SetLaunchTemplateData(requestLaunchTemplateData);

        Aws::EC2::Model::CreateLaunchTemplateOutcome outcome =
                ec2Client.CreateLaunchTemplate(request);

        if (outcome.IsSuccess()) {
            std::cout << "The EC2 launch template '" << templateName << " was
created."
                      << std::endl;
        }
        else if (outcome.GetError().GetExceptionName() ==
                 "InvalidLaunchTemplateName.AlreadyExistsException") {
            std::cout << "The EC2 template '" << templateName << "' already exists"
                      << std::endl;
        }
        else {
            std::cerr << "Error with EC2::CreateLaunchTemplate. "
                      << outcome.GetError().GetMessage()
```

```
                    << std::endl;
        }
    }
    Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);
    std::cout << "Let's create an Auto Scaling group." << std::endl;
    Aws::String groupName = askQuestion(
            "Enter a name for the Auto Scaling group:  ");
    // 3. Retrieve a list of EC2 Availability Zones.
    Aws::Vector<Aws::EC2::Model::AvailabilityZone> availabilityZones;
    {
        Aws::EC2::Model::DescribeAvailabilityZonesRequest request;

        Aws::EC2::Model::DescribeAvailabilityZonesOutcome outcome =
                ec2Client.DescribeAvailabilityZones(request);

        if (outcome.IsSuccess()) {
            std::cout
                    << "EC2 instances can be created in the following Availability
Zones:"
                    << std::endl;

            availabilityZones = outcome.GetResult().GetAvailabilityZones();
            for (size_t i = 0; i < availabilityZones.size(); ++i) {
                std::cout << "   " << i + 1 << ".  "
                          << availabilityZones[i].GetZoneName() << std::endl;
            }
        }
        else {
            std::cerr << "Error with EC2::DescribeAvailabilityZones. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanupResources("", templateName, autoScalingClient, ec2Client);
            return false;
        }
    }

    int availabilityZoneChoice = askQuestionForIntRange(
            "Choose an Availability Zone:  ", 1,
            static_cast<int>(availabilityZones.size()));
    // 4. Create an Auto Scaling group with the specified Availability Zone.
    {
        Aws::AutoScaling::Model::CreateAutoScalingGroupRequest request;
        request.SetAutoScalingGroupName(groupName);
        Aws::Vector<Aws::String> availabilityGroupZones;
```

```
        availabilityGroupZones.push_back(
                availabilityZones[availabilityZoneChoice - 1].GetZoneName());
        request.SetAvailabilityZones(availabilityGroupZones);
        request.SetMaxSize(1);
        request.SetMinSize(1);

        Aws::AutoScaling::Model::LaunchTemplateSpecification
launchTemplateSpecification;
        launchTemplateSpecification.SetLaunchTemplateName(templateName);
        request.SetLaunchTemplate(launchTemplateSpecification);

        Aws::AutoScaling::Model::CreateAutoScalingGroupOutcome outcome =
                autoScalingClient.CreateAutoScalingGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "Created Auto Scaling group '" << groupName << "'..."
                      << std::endl;
        }
        else if (outcome.GetError().GetErrorType() ==
                 Aws::AutoScaling::AutoScalingErrors::ALREADY_EXISTS_FAULT) {
            std::cout << "Auto Scaling group '" << groupName << "' already exists."
                      << std::endl;
        }
        else {
            std::cerr << "Error with AutoScaling::CreateAutoScalingGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanupResources("", templateName, autoScalingClient, ec2Client);
            return false;
        }
    }

    Aws::Vector<Aws::AutoScaling::Model::AutoScalingGroup> autoScalingGroups;
    if (AwsDoc::AutoScaling::describeGroup(groupName, autoScalingGroups,
                                           autoScalingClient)) {
        std::cout << "Here is the Auto Scaling group description." << std::endl;
        if (!autoScalingGroups.empty()) {
            logAutoScalingGroupInfo(autoScalingGroups);
        }
    }
    else {
        cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
        return false;
    }
```

```
   std::cout
           << "Waiting for the EC2 instance in the Auto Scaling group to become
active..."
           << std::endl;
   if (!waitForInstances(groupName, autoScalingGroups, autoScalingClient)) {
       cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
       return false;
   }

   bool enableMetrics = askYesNoQuestion(
           "Do you want to collect metrics about the A"
           "Auto Scaling group during this demo (y/n)?  ");
   // 7. Optionally enable metrics collection for the Auto Scaling group.
   if (enableMetrics) {
       Aws::AutoScaling::Model::EnableMetricsCollectionRequest request;
       request.SetAutoScalingGroupName(groupName);

       request.AddMetrics("GroupMinSize");
       request.AddMetrics("GroupMaxSize");
       request.AddMetrics("GroupDesiredCapacity");
       request.AddMetrics("GroupInServiceInstances");
       request.AddMetrics("GroupTotalInstances");
       request.SetGranularity("1Minute");

       Aws::AutoScaling::Model::EnableMetricsCollectionOutcome outcome =
               autoScalingClient.EnableMetricsCollection(request);
       if (outcome.IsSuccess()) {
           std::cout << "Auto Scaling metrics have been enabled."
                     << std::endl;
       }
       else {
           std::cerr << "Error with AutoScaling::EnableMetricsCollection. "
                     << outcome.GetError().GetMessage()
                     << std::endl;
           cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
           return false;
       }
   }

   std::cout << "Let's update the maximum number of EC2 instances in '" <<
groupName <<
             "' from 1 to 3." << std::endl;
   askQuestion("Press enter to continue:  ", alwaysTrueTest);
```

```
    // 8. Update the Auto Scaling group, setting a new maximum size.
    {
        Aws::AutoScaling::Model::UpdateAutoScalingGroupRequest request;
        request.SetAutoScalingGroupName(groupName);
        request.SetMaxSize(3);

        Aws::AutoScaling::Model::UpdateAutoScalingGroupOutcome outcome =
                autoScalingClient.UpdateAutoScalingGroup(request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Error with AutoScaling::UpdateAutoScalingGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
            return false;
        }
    }

    if (AwsDoc::AutoScaling::describeGroup(groupName, autoScalingGroups,
                                           autoScalingClient)) {
        if (!autoScalingGroups.empty()) {
            const auto &instances = autoScalingGroups[0].GetInstances();
            std::cout
                    << "The group still has one running EC2 instance, but it can
have up to 3.\n"
                    << std::endl;
            logAutoScalingGroupInfo(autoScalingGroups);
        }
        else {
            std::cerr
                    << "No EC2 launch groups were retrieved from DescribeGroup
request."
                    << std::endl;
            cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
            return false;
        }
    }

    std::cout << "\n" << std::setfill('*') << std::setw(ASTERISK_FILL_WIDTH) << "\n"
              << std::endl;
    std::cout << "Let's update the desired capacity in '" << groupName <<
              "' from 1 to 2." << std::endl;
    askQuestion("Press enter to continue:  ", alwaysTrueTest);
    //  9. Update the Auto Scaling group, setting a new desired capacity.
```

```
    {
        Aws::AutoScaling::Model::SetDesiredCapacityRequest request;
        request.SetAutoScalingGroupName(groupName);
        request.SetDesiredCapacity(2);

        Aws::AutoScaling::Model::SetDesiredCapacityOutcome outcome =
                autoScalingClient.SetDesiredCapacity(request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Error with AutoScaling::SetDesiredCapacityRequest. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
            return false;
        }
    }

    if (AwsDoc::AutoScaling::describeGroup(groupName, autoScalingGroups,
                                           autoScalingClient)) {
        if (!autoScalingGroups.empty()) {
            std::cout
                    << "Here is the current state of the group." << std::endl;
            logAutoScalingGroupInfo(autoScalingGroups);
        }
        else {
            std::cerr
                    << "No EC2 launch groups were retrieved from DescribeGroup
request."
                    << std::endl;
            cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
            return false;
        }
    }

    std::cout << "Waiting for the new EC2 instance to start..." << std::endl;
    waitForInstances(groupName, autoScalingGroups, autoScalingClient);

    std::cout << "\n" << std::setfill('*') << std::setw(ASTERISK_FILL_WIDTH) << "\n"
              << std::endl;

    std::cout << "Let's terminate one of the EC2 instances in " << groupName << "."
              << std::endl;
    std::cout << "Because the desired capacity is 2, another EC2 instance will start
"
```

```
              << "to replace the terminated EC2 instance."
              << std::endl;
   std::cout << "The currently running EC2 instances are:" << std::endl;

   if (autoScalingGroups.empty()) {
       std::cerr << "Error describing groups. No groups returned." << std::endl;
       cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
       return false;
   }

   int instanceNumber = 1;
   Aws::Vector<Aws::String> instanceIDs = instancesToInstanceIDs(
           autoScalingGroups[0].GetInstances());
   for (const Aws::String &instanceID: instanceIDs) {
       std::cout << "   " << instanceNumber << ". " << instanceID << std::endl;
       ++instanceNumber;
   }

   instanceNumber = askQuestionForIntRange("Which EC2 instance do you want to stop?
",
                                           1,
                                           static_cast<int>(instanceIDs.size()));

   // 10. Terminate an EC2 instance in the Auto Scaling group.
   {
       Aws::AutoScaling::Model::TerminateInstanceInAutoScalingGroupRequest request;
       request.SetInstanceId(instanceIDs[instanceNumber - 1]);
       request.SetShouldDecrementDesiredCapacity(false);

       Aws::AutoScaling::Model::TerminateInstanceInAutoScalingGroupOutcome outcome
=
               autoScalingClient.TerminateInstanceInAutoScalingGroup(request);

       if (outcome.IsSuccess()) {
           std::cout << "Waiting for EC2 instance with ID '"
                     << instanceIDs[instanceNumber - 1] << "' to terminate..."
                     << std::endl;
       }
       else {
           std::cerr << "Error with
AutoScaling::TerminateInstanceInAutoScalingGroup. "
                     << outcome.GetError().GetMessage()
                     << std::endl;
           cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
```

```
            return false;
        }
    }

    waitForInstances(groupName, autoScalingGroups, autoScalingClient);

    std::cout << "\n" << std::setfill('*') << std::setw(ASTERISK_FILL_WIDTH) << "\n"
              << std::endl;
    std::cout << "Let's get a report of scaling activities for EC2 launch group '"
              << groupName << "'."
              << std::endl;
    askQuestion("Press enter to continue:  ", alwaysTrueTest);
    // 11. Get a description of activities for the Auto Scaling group.
    {
        Aws::AutoScaling::Model::DescribeScalingActivitiesRequest request;
        request.SetAutoScalingGroupName(groupName);

        Aws::Vector<Aws::AutoScaling::Model::Activity> allActivities;
        Aws::String nextToken; // Used for pagination;
        do {
            if (!nextToken.empty()) {
                request.SetNextToken(nextToken);
            }
            Aws::AutoScaling::Model::DescribeScalingActivitiesOutcome outcome =
                    autoScalingClient.DescribeScalingActivities(request);

            if (outcome.IsSuccess()) {
                const Aws::Vector<Aws::AutoScaling::Model::Activity> &activities =
                        outcome.GetResult().GetActivities();
                allActivities.insert(allActivities.end(), activities.begin(),
activities.end());
                nextToken  = outcome.GetResult().GetNextToken();
            }
            else {
                std::cerr << "Error with AutoScaling::DescribeScalingActivities. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanupResources(groupName, templateName, autoScalingClient,
ec2Client);
                return false;
            }
        } while (!nextToken.empty());

        std::cout << "Found " << allActivities.size() << " activities."
```

```
                  << std::endl;
        std::cout << "Activities are ordered with the most recent first."
                  << std::endl;
        for (const Aws::AutoScaling::Model::Activity &activity: allActivities) {
            std::cout << activity.GetDescription() << std::endl;
            std::cout << activity.GetDetails() << std::endl;
        }
    }

    if (enableMetrics) {
        if (!logAutoScalingMetrics(groupName, clientConfig)) {
            cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
            return false;
        }
    }

    std::cout << "Let's  clean up." << std::endl;
    askQuestion("Press enter to continue:  ", alwaysTrueTest);

    // 13. Disable metrics collection if enabled.
    if (enableMetrics) {
        Aws::AutoScaling::Model::DisableMetricsCollectionRequest request;
        request.SetAutoScalingGroupName(groupName);

        Aws::AutoScaling::Model::DisableMetricsCollectionOutcome outcome =
                autoScalingClient.DisableMetricsCollection(request);

        if (outcome.IsSuccess()) {
            std::cout << "Metrics collection has been disabled." << std::endl;
        }
        else {
            std::cerr << "Error with AutoScaling::DisableMetricsCollection. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
            return false;
        }
    }

    return cleanupResources(groupName, templateName, autoScalingClient, ec2Client);
}

//! Routine which waits for EC2 instances in an Auto Scaling group to
//! complete startup or shutdown.
```

```
/*!
 \sa waitForInstances()
 \param groupName: An Auto Scaling group name.
 \param autoScalingGroups: Vector to receive 'AutoScalingGroup' records.
 \param client: 'AutoScalingClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::AutoScaling::waitForInstances(const Aws::String &groupName,

 Aws::Vector<Aws::AutoScaling::Model::AutoScalingGroup> &autoScalingGroups,
                                            const Aws::AutoScaling::AutoScalingClient
 &client) {
    bool ready = false;
    const std::vector<Aws::String> READY_STATES = {"InService", "Terminated"};

    int count = 0;
    int desiredCapacity = 0;
    std::this_thread::sleep_for(std::chrono::seconds(4));
    while (!ready) {
        if (WAIT_FOR_INSTANCES_TIMEOUT < count) {
            std::cerr << "Wait for instance timed out." << std::endl;
            return false;
        }

        std::this_thread::sleep_for(std::chrono::seconds(1));
        ++count;
        if (!describeGroup(groupName, autoScalingGroups, client)) {
            return false;
        }
        Aws::Vector<Aws::String> instanceIDs;
        if (!autoScalingGroups.empty()) {
            instanceIDs =
 instancesToInstanceIDs(autoScalingGroups[0].GetInstances());
            desiredCapacity = autoScalingGroups[0].GetDesiredCapacity();
        }

        if (instanceIDs.empty()) {
            if (desiredCapacity == 0) {
                break;
            }
            else {
                if ((count % 5) == 0) {
                    std::cout << "No instance IDs returned for group." << std::endl;
                }
```

```
                continue;
            }
        }

        // 6.  Check lifecycle state of the instances using
 DescribeAutoScalingInstances.
        Aws::AutoScaling::Model::DescribeAutoScalingInstancesRequest request;
        request.SetInstanceIds(instanceIDs);

        Aws::AutoScaling::Model::DescribeAutoScalingInstancesOutcome outcome =
                client.DescribeAutoScalingInstances(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::AutoScaling::Model::AutoScalingInstanceDetails>
 &instancesDetails =
                    outcome.GetResult().GetAutoScalingInstances();
            ready = instancesDetails.size() >= desiredCapacity;
            for (const Aws::AutoScaling::Model::AutoScalingInstanceDetails &details:
 instancesDetails) {
                if (!stringInVector(details.GetLifecycleState(), READY_STATES)) {
                    ready = false;
                    break;
                }
            }
            // Log the status while waiting.
            if (((count % 5) == 1) || ready) {
                logInstancesLifecycleState(instancesDetails);
            }
        }
        else {
            std::cerr << "Error with AutoScaling::DescribeAutoScalingInstances. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }

    if (!describeGroup(groupName, autoScalingGroups, client)) {
        return false;
    }

    return true;
}
```

```
//! Routine to cleanup resources created in 'groupsAndInstancesScenario'.
/*!
 \sa cleanupResources()
 \param groupName: Optional Auto Scaling group name.
 \param templateName: Optional EC2 launch template name.
 \param autoScalingClient: 'AutoScalingClient' instance.
 \param ec2Client: 'EC2Client' instance.
\return bool: Successful completion.
 */
bool AwsDoc::AutoScaling::cleanupResources(const Aws::String &groupName,
                                           const Aws::String &templateName,
                                           const Aws::AutoScaling::AutoScalingClient
 &autoScalingClient,
                                           const Aws::EC2::EC2Client &ec2Client) {
    bool result = true;

    // 14. Delete the Auto Scaling group.
    if (!groupName.empty() &&
        (askYesNoQuestion(
                Aws::String("Delete the Auto Scaling group '") + groupName +
                "'  (y/n)?"))) {
        {
            Aws::AutoScaling::Model::UpdateAutoScalingGroupRequest request;
            request.SetAutoScalingGroupName(groupName);
            request.SetMinSize(0);
            request.SetDesiredCapacity(0);

            Aws::AutoScaling::Model::UpdateAutoScalingGroupOutcome outcome =
                    autoScalingClient.UpdateAutoScalingGroup(request);

            if (outcome.IsSuccess()) {
                std::cout
                        << "The minimum size and desired capacity of the Auto
 Scaling group "
                        << "was set to zero before terminating the instances."
                        << std::endl;
            }
            else {
                std::cerr << "Error with AutoScaling::UpdateAutoScalingGroup. "
                          << outcome.GetError().GetMessage() << std::endl;
                result = false;
            }
        }
```

```
        Aws::Vector<Aws::AutoScaling::Model::AutoScalingGroup> autoScalingGroups;
        if (AwsDoc::AutoScaling::describeGroup(groupName, autoScalingGroups,
                                               autoScalingClient)) {
            if (!autoScalingGroups.empty()) {
                Aws::Vector<Aws::String> instanceIDs = instancesToInstanceIDs(
                        autoScalingGroups[0].GetInstances());
                for (const Aws::String &instanceID: instanceIDs) {

Aws::AutoScaling::Model::TerminateInstanceInAutoScalingGroupRequest request;
                    request.SetInstanceId(instanceID);
                    request.SetShouldDecrementDesiredCapacity(true);


Aws::AutoScaling::Model::TerminateInstanceInAutoScalingGroupOutcome outcome =
                            autoScalingClient.TerminateInstanceInAutoScalingGroup(
                                    request);

                    if (outcome.IsSuccess()) {
                        std::cout << "Initiating termination of EC2 instance '"
                                  << instanceID << "'." << std::endl;
                    }
                    else {
                        std::cerr
                                << "Error with
AutoScaling::TerminateInstanceInAutoScalingGroup. "
                                << outcome.GetError().GetMessage() << std::endl;
                        result = false;
                    }
                }
            }

            std::cout
                    << "Waiting for the EC2 instances to terminate before deleting
the "
                    << "Auto Scaling group..." << std::endl;
            waitForInstances(groupName, autoScalingGroups, autoScalingClient);
        }

        {
            Aws::AutoScaling::Model::DeleteAutoScalingGroupRequest request;
            request.SetAutoScalingGroupName(groupName);

            Aws::AutoScaling::Model::DeleteAutoScalingGroupOutcome outcome =
```

```
                    autoScalingClient.DeleteAutoScalingGroup(request);

            if (outcome.IsSuccess()) {
                std::cout << "Auto Scaling group '" << groupName << "' was deleted."
                          << std::endl;
            }
            else {
                std::cerr << "Error with AutoScaling::DeleteAutoScalingGroup. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
        }
    }

    // 15. Delete the EC2 launch template.
    if (!templateName.empty() && (askYesNoQuestion(
            Aws::String("Delete the EC2 launch template '") + templateName +
            "' (y/n)?"))) {
        Aws::EC2::Model::DeleteLaunchTemplateRequest request;
        request.SetLaunchTemplateName(templateName);

        Aws::EC2::Model::DeleteLaunchTemplateOutcome outcome =
                ec2Client.DeleteLaunchTemplate(request);

        if (outcome.IsSuccess()) {
            std::cout << "EC2 launch template '" << templateName << "' was deleted."
                      << std::endl;
        }
        else {
            std::cerr << "Error with EC2::DeleteLaunchTemplate. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
        }
    }

    return result;
}

//! Routine which retrieves Auto Scaling group descriptions.
/*!
 \sa describeGroup()
 \param groupName: An Auto Scaling group name.
```

```
 \param autoScalingGroups: Vector to receive 'AutoScalingGroup' records.
 \param client: 'AutoScalingClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::AutoScaling::describeGroup(const Aws::String &groupName,

 Aws::Vector<Aws::AutoScaling::Model::AutoScalingGroup> &autoScalingGroup,
                                         const Aws::AutoScaling::AutoScalingClient
 &client) {
    // 5. Retrieve a description of the Auto Scaling group.
    Aws::AutoScaling::Model::DescribeAutoScalingGroupsRequest request;
    Aws::Vector<Aws::String> groupNames;
    groupNames.push_back(groupName);
    request.SetAutoScalingGroupNames(groupNames);

    Aws::AutoScaling::Model::DescribeAutoScalingGroupsOutcome outcome =
            client.DescribeAutoScalingGroups(request);

    if (outcome.IsSuccess()) {
        autoScalingGroup = outcome.GetResult().GetAutoScalingGroups();
    }
    else {
        std::cerr << "Error with AutoScaling::DescribeAutoScalingGroups. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see the following topics in *AWS SDK for C++ API Reference*.
  - CreateAutoScalingGroup
  - DeleteAutoScalingGroup
  - DescribeAutoScalingGroups
  - DescribeAutoScalingInstances
  - DescribeScalingActivities
  - DisableMetricsCollection
  - EnableMetricsCollection
  - SetDesiredCapacity

- TerminateInstanceInAutoScalingGroup
- UpdateAutoScalingGroup

Actions

`CreateAutoScalingGroup`

The following code example shows how to use `CreateAutoScalingGroup`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

        Aws::AutoScaling::Model::CreateAutoScalingGroupRequest request;
        request.SetAutoScalingGroupName(groupName);
        Aws::Vector<Aws::String> availabilityGroupZones;
        availabilityGroupZones.push_back(
                availabilityZones[availabilityZoneChoice - 1].GetZoneName());
        request.SetAvailabilityZones(availabilityGroupZones);
        request.SetMaxSize(1);
        request.SetMinSize(1);

        Aws::AutoScaling::Model::LaunchTemplateSpecification
launchTemplateSpecification;
        launchTemplateSpecification.SetLaunchTemplateName(templateName);
        request.SetLaunchTemplate(launchTemplateSpecification);

        Aws::AutoScaling::Model::CreateAutoScalingGroupOutcome outcome =
                autoScalingClient.CreateAutoScalingGroup(request);

        if (outcome.IsSuccess()) {
```

```
            std::cout << "Created Auto Scaling group '" << groupName << "'..."
                      << std::endl;
        }
        else if (outcome.GetError().GetErrorType() ==
                 Aws::AutoScaling::AutoScalingErrors::ALREADY_EXISTS_FAULT) {
            std::cout << "Auto Scaling group '" << groupName << "' already exists."
                      << std::endl;
        }
        else {
            std::cerr << "Error with AutoScaling::CreateAutoScalingGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

        }
```

- For API details, see CreateAutoScalingGroup in *AWS SDK for C++ API Reference*.

`DeleteAutoScalingGroup`

The following code example shows how to use `DeleteAutoScalingGroup`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
    Aws::Client::ClientConfiguration clientConfig;
    // Optional: Set to the AWS Region (overrides config file).
    // clientConfig.region = "us-east-1";

Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

        Aws::AutoScaling::Model::DeleteAutoScalingGroupRequest request;
        request.SetAutoScalingGroupName(groupName);

        Aws::AutoScaling::Model::DeleteAutoScalingGroupOutcome outcome =
                autoScalingClient.DeleteAutoScalingGroup(request);
```

```
            if (outcome.IsSuccess()) {
                std::cout << "Auto Scaling group '" << groupName << "' was deleted."
                          << std::endl;
            }
            else {
                std::cerr << "Error with AutoScaling::DeleteAutoScalingGroup. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
        }
```

- For API details, see DeleteAutoScalingGroup in *AWS SDK for C++ API Reference*.

`DescribeAutoScalingGroups`

The following code example shows how to use `DescribeAutoScalingGroups`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
    Aws::Client::ClientConfiguration clientConfig;
    // Optional: Set to the AWS Region (overrides config file).
    // clientConfig.region = "us-east-1";

Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

Aws::AutoScaling::Model::DescribeAutoScalingGroupsRequest request;
Aws::Vector<Aws::String> groupNames;
groupNames.push_back(groupName);
request.SetAutoScalingGroupNames(groupNames);

Aws::AutoScaling::Model::DescribeAutoScalingGroupsOutcome outcome =
        client.DescribeAutoScalingGroups(request);

if (outcome.IsSuccess()) {
```

```
        autoScalingGroup = outcome.GetResult().GetAutoScalingGroups();
    }
    else {
        std::cerr << "Error with AutoScaling::DescribeAutoScalingGroups. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
```

- For API details, see DescribeAutoScalingGroups in *AWS SDK for C++ API Reference*.

`DescribeAutoScalingInstances`

The following code example shows how to use `DescribeAutoScalingInstances`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

        Aws::AutoScaling::Model::DescribeAutoScalingInstancesRequest request;
        request.SetInstanceIds(instanceIDs);

        Aws::AutoScaling::Model::DescribeAutoScalingInstancesOutcome outcome =
                client.DescribeAutoScalingInstances(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::AutoScaling::Model::AutoScalingInstanceDetails>
&instancesDetails =
                    outcome.GetResult().GetAutoScalingInstances();

        }
        else {
```

```
            std::cerr << "Error with AutoScaling::DescribeAutoScalingInstances. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
```

- For API details, see DescribeAutoScalingInstances in *AWS SDK for C++ API Reference*.

`DescribeScalingActivities`

The following code example shows how to use `DescribeScalingActivities`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
    Aws::Client::ClientConfiguration clientConfig;
    // Optional: Set to the AWS Region (overrides config file).
    // clientConfig.region = "us-east-1";

Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

    Aws::AutoScaling::Model::DescribeScalingActivitiesRequest request;
    request.SetAutoScalingGroupName(groupName);

    Aws::Vector<Aws::AutoScaling::Model::Activity> allActivities;
    Aws::String nextToken; // Used for pagination;
    do {
        if (!nextToken.empty()) {
            request.SetNextToken(nextToken);
        }
        Aws::AutoScaling::Model::DescribeScalingActivitiesOutcome outcome =
                autoScalingClient.DescribeScalingActivities(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::AutoScaling::Model::Activity> &activities =
                    outcome.GetResult().GetActivities();
```

```
                allActivities.insert(allActivities.end(), activities.begin(),
activities.end());
                nextToken  = outcome.GetResult().GetNextToken();
            }
            else {
                std::cerr << "Error with AutoScaling::DescribeScalingActivities. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

            }
        } while (!nextToken.empty());

        std::cout << "Found " << allActivities.size() << " activities."
                  << std::endl;
        std::cout << "Activities are ordered with the most recent first."
                  << std::endl;
        for (const Aws::AutoScaling::Model::Activity &activity: allActivities) {
            std::cout << activity.GetDescription() << std::endl;
            std::cout << activity.GetDetails() << std::endl;
        }
```

- For API details, see DescribeScalingActivities in *AWS SDK for C++ API Reference*.

`DisableMetricsCollection`

The following code example shows how to use `DisableMetricsCollection`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);
```

```
        Aws::AutoScaling::Model::DisableMetricsCollectionRequest request;
        request.SetAutoScalingGroupName(groupName);

        Aws::AutoScaling::Model::DisableMetricsCollectionOutcome outcome =
                autoScalingClient.DisableMetricsCollection(request);

        if (outcome.IsSuccess()) {
            std::cout << "Metrics collection has been disabled." << std::endl;
        }
        else {
            std::cerr << "Error with AutoScaling::DisableMetricsCollection. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

        }
```

- For API details, see DisableMetricsCollection in *AWS SDK for C++ API Reference*.

`EnableMetricsCollection`

The following code example shows how to use `EnableMetricsCollection`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

        Aws::AutoScaling::Model::EnableMetricsCollectionRequest request;
        request.SetAutoScalingGroupName(groupName);

        request.AddMetrics("GroupMinSize");
        request.AddMetrics("GroupMaxSize");
```

```
        request.AddMetrics("GroupDesiredCapacity");
        request.AddMetrics("GroupInServiceInstances");
        request.AddMetrics("GroupTotalInstances");
        request.SetGranularity("1Minute");

        Aws::AutoScaling::Model::EnableMetricsCollectionOutcome outcome =
                autoScalingClient.EnableMetricsCollection(request);
        if (outcome.IsSuccess()) {
            std::cout << "Auto Scaling metrics have been enabled."
                      << std::endl;
        }
        else {
            std::cerr << "Error with AutoScaling::EnableMetricsCollection. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

        }
```

- For API details, see EnableMetricsCollection in *AWS SDK for C++ API Reference*.

`SetDesiredCapacity`

The following code example shows how to use `SetDesiredCapacity`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
    Aws::Client::ClientConfiguration clientConfig;
    // Optional: Set to the AWS Region (overrides config file).
    // clientConfig.region = "us-east-1";

Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

    Aws::AutoScaling::Model::SetDesiredCapacityRequest request;
    request.SetAutoScalingGroupName(groupName);
    request.SetDesiredCapacity(2);
```

```
        Aws::AutoScaling::Model::SetDesiredCapacityOutcome outcome =
                autoScalingClient.SetDesiredCapacity(request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Error with AutoScaling::SetDesiredCapacityRequest. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

        }
```

- For API details, see SetDesiredCapacity in *AWS SDK for C++ API Reference*.

`TerminateInstanceInAutoScalingGroup`

The following code example shows how to use `TerminateInstanceInAutoScalingGroup`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

        Aws::AutoScaling::Model::TerminateInstanceInAutoScalingGroupRequest request;
        request.SetInstanceId(instanceIDs[instanceNumber - 1]);
        request.SetShouldDecrementDesiredCapacity(false);

        Aws::AutoScaling::Model::TerminateInstanceInAutoScalingGroupOutcome outcome
=
                autoScalingClient.TerminateInstanceInAutoScalingGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "Waiting for EC2 instance with ID '"
```

```
                    << instanceIDs[instanceNumber - 1] << "' to terminate..."
                    << std::endl;
        }
        else {
            std::cerr << "Error with
AutoScaling::TerminateInstanceInAutoScalingGroup. "
                    << outcome.GetError().GetMessage()
                    << std::endl;

        }
```

- For API details, see TerminateInstanceInAutoScalingGroup in *AWS SDK for C++ API Reference*.

`UpdateAutoScalingGroup`

The following code example shows how to use `UpdateAutoScalingGroup`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::AutoScaling::AutoScalingClient autoScalingClient(clientConfig);

        Aws::AutoScaling::Model::UpdateAutoScalingGroupRequest request;
        request.SetAutoScalingGroupName(groupName);
        request.SetMaxSize(3);

        Aws::AutoScaling::Model::UpdateAutoScalingGroupOutcome outcome =
                autoScalingClient.UpdateAutoScalingGroup(request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Error with AutoScaling::UpdateAutoScalingGroup. "
                    << outcome.GetError().GetMessage()
```

```
                    << std::endl;

        }
```

- For API details, see UpdateAutoScalingGroup in *AWS SDK for C++ API Reference*.

CloudTrail examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with CloudTrail.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Actions

Actions

`CreateTrail`

The following code example shows how to use `CreateTrail`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
// Routine which creates an AWS CloudTrail trail.
/*!
  \param trailName: The name of the CloudTrail trail.
  \param bucketName: The Amazon S3 bucket designate for publishing logs.
```

```
  \param clientConfig: Aws client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::CloudTrail::createTrail(const Aws::String trailName,
                                     const Aws::String bucketName,
                                     const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::CloudTrail::CloudTrailClient trailClient(clientConfig);
    Aws::CloudTrail::Model::CreateTrailRequest request;
    request.SetName(trailName);
    request.SetS3BucketName(bucketName);

    Aws::CloudTrail::Model::CreateTrailOutcome outcome = trailClient.CreateTrail(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully created trail " << trailName << std::endl;
    }
    else {
        std::cerr << "Failed to create trail " << trailName <<
                  ": " << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see CreateTrail in *AWS SDK for C++ API Reference*.

`DeleteTrail`

The following code example shows how to use `DeleteTrail`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
// Routine which deletes an AWS CloudTrail trail.
/*!
```

```
  \param trailName: The name of the CloudTrail trail.
  \param clientConfig: Aws client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::CloudTrail::deleteTrail(const Aws::String trailName,
                                     const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::CloudTrail::CloudTrailClient trailClient(clientConfig);

    Aws::CloudTrail::Model::DeleteTrailRequest request;
    request.SetName(trailName);

    auto outcome = trailClient.DeleteTrail(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted trail " << trailName << std::endl;
    }
    else {
        std::cerr << "Error deleting trail " << trailName << " " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DeleteTrail in *AWS SDK for C++ API Reference*.

`DescribeTrail`

The following code example shows how to use `DescribeTrail`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
// Routine which describes the AWS CloudTrail trails in an account.
/*!
  \param clientConfig: Aws client configuration.
```

```
  \return bool: Function succeeded.
*/

bool AwsDoc::CloudTrail::describeTrails(
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::CloudTrail::CloudTrailClient cloudTrailClient(clientConfig);
    Aws::CloudTrail::Model::DescribeTrailsRequest request;

    auto outcome = cloudTrailClient.DescribeTrails(request);
    if (outcome.IsSuccess()) {
        const Aws::Vector<Aws::CloudTrail::Model::Trail> &trails =
 outcome.GetResult().GetTrailList();
        std::cout << trails.size() << " trail(s) found." << std::endl;
        for (const Aws::CloudTrail::Model::Trail &trail: trails) {
            std::cout << trail.GetName() << std::endl;
        }
    }
    else {
        std::cerr << "Failed to describe trails." << outcome.GetError().GetMessage()
                  << std::endl;
    }
    return outcome.IsSuccess();
}
```

- For API details, see DescribeTrail in *AWS SDK for C++ API Reference*.

`LookupEvents`

The following code example shows how to use `LookupEvents`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
// Routine which looks up events captured by AWS CloudTrail.
/*!
  \param clientConfig: Aws client configuration.
```

```
  \return bool: Function succeeded.
*/
bool AwsDoc::CloudTrail::lookupEvents(
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::CloudTrail::CloudTrailClient cloudtrail(clientConfig);

    Aws::String nextToken; // Used for pagination.
    Aws::Vector<Aws::CloudTrail::Model::Event> allEvents;

    Aws::CloudTrail::Model::LookupEventsRequest request;

    size_t count = 0;
    do {
        if (!nextToken.empty()) {
            request.SetNextToken(nextToken);
        }

        Aws::CloudTrail::Model::LookupEventsOutcome outcome =
 cloudtrail.LookupEvents(
                request);
        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::CloudTrail::Model::Event> &events =
 outcome.GetResult().GetEvents();
            count += events.size();
            allEvents.insert(allEvents.end(), events.begin(), events.end());
            nextToken = outcome.GetResult().GetNextToken();
        }
        else {
            std::cerr << "Error: " << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    } while (!nextToken.empty() && count <= 50); // Limit to 50 events.

    std::cout << "Found " << allEvents.size() << " event(s)." << std::endl;

    for (auto &event: allEvents) {
        std::cout << "Event name: " << event.GetEventName() << std::endl;
        std::cout << "Event source: " << event.GetEventSource() << std::endl;
        std::cout << "Event id: " << event.GetEventId() << std::endl;
        std::cout << "Resources: " << std::endl;
        for (auto &resource: event.GetResources()) {
            std::cout << "  " << resource.GetResourceName() << std::endl;
        }
    }
```

```
    return true;
}
```

- For API details, see LookupEvents in *AWS SDK for C++ API Reference*.

CloudWatch examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with CloudWatch.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Actions

Actions

`DeleteAlarms`

The following code example shows how to use `DeleteAlarms`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Include the required files.

```
#include <aws/core/Aws.h>
#include <aws/monitoring/CloudWatchClient.h>
```

```
#include <aws/monitoring/model/DeleteAlarmsRequest.h>
#include <iostream>
```

Delete the alarm.

```
        Aws::CloudWatch::CloudWatchClient cw;
        Aws::CloudWatch::Model::DeleteAlarmsRequest request;
        request.AddAlarmNames(alarm_name);

        auto outcome = cw.DeleteAlarms(request);
        if (!outcome.IsSuccess())
        {
            std::cout << "Failed to delete CloudWatch alarm:" <<
                outcome.GetError().GetMessage() << std::endl;
        }
        else
        {
            std::cout << "Successfully deleted CloudWatch alarm " << alarm_name
                << std::endl;
        }
```

- For API details, see DeleteAlarms in *AWS SDK for C++ API Reference*.

`DescribeAlarmsForMetric`

The following code example shows how to use `DescribeAlarmsForMetric`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Include the required files.

```
#include <aws/core/Aws.h>
#include <aws/monitoring/CloudWatchClient.h>
```

```
#include <aws/monitoring/model/DescribeAlarmsRequest.h>
#include <aws/monitoring/model/DescribeAlarmsResult.h>
#include <iomanip>
#include <iostream>
```

Describe the alarms.

```
        Aws::CloudWatch::CloudWatchClient cw;
        Aws::CloudWatch::Model::DescribeAlarmsRequest request;
        request.SetMaxRecords(1);

        bool done = false;
        bool header = false;
        while (!done)
        {
            auto outcome = cw.DescribeAlarms(request);
            if (!outcome.IsSuccess())
            {
                std::cout << "Failed to describe CloudWatch alarms:" <<
                    outcome.GetError().GetMessage() << std::endl;
                break;
            }

            if (!header)
            {
                std::cout << std::left <<
                    std::setw(32) << "Name" <<
                    std::setw(64) << "Arn" <<
                    std::setw(64) << "Description" <<
                    std::setw(20) << "LastUpdated" <<
                    std::endl;
                header = true;
            }

            const auto &alarms = outcome.GetResult().GetMetricAlarms();
            for (const auto &alarm : alarms)
            {
                std::cout << std::left <<
                    std::setw(32) << alarm.GetAlarmName() <<
                    std::setw(64) << alarm.GetAlarmArn() <<
                    std::setw(64) << alarm.GetAlarmDescription() <<
                    std::setw(20) <<
```

```
                    alarm.GetAlarmConfigurationUpdatedTimestamp().ToGmtString(
                        SIMPLE_DATE_FORMAT_STR) <<
                    std::endl;
            }

            const auto &next_token = outcome.GetResult().GetNextToken();
            request.SetNextToken(next_token);
            done = next_token.empty();
        }
```

- For API details, see DescribeAlarmsForMetric in *AWS SDK for C++ API Reference*.

`DisableAlarmActions`

The following code example shows how to use `DisableAlarmActions`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Include the required files.

```
#include <aws/core/Aws.h>
#include <aws/monitoring/CloudWatchClient.h>
#include <aws/monitoring/model/DisableAlarmActionsRequest.h>
#include <iostream>
```

Disable the alarm actions.

```
        Aws::CloudWatch::CloudWatchClient cw;

        Aws::CloudWatch::Model::DisableAlarmActionsRequest
 disableAlarmActionsRequest;
        disableAlarmActionsRequest.AddAlarmNames(alarm_name);
```

```
        auto disableAlarmActionsOutcome =
cw.DisableAlarmActions(disableAlarmActionsRequest);
        if (!disableAlarmActionsOutcome.IsSuccess())
        {
            std::cout << "Failed to disable actions for alarm " << alarm_name <<
                ": " << disableAlarmActionsOutcome.GetError().GetMessage() <<
                std::endl;
        }
        else
        {
            std::cout << "Successfully disabled actions for alarm " <<
                alarm_name << std::endl;
        }
```

- For API details, see DisableAlarmActions in *AWS SDK for C++ API Reference*.

`EnableAlarmActions`

The following code example shows how to use `EnableAlarmActions`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Include the required files.

```
#include <aws/core/Aws.h>
#include <aws/monitoring/CloudWatchClient.h>
#include <aws/monitoring/model/EnableAlarmActionsRequest.h>
#include <aws/monitoring/model/PutMetricAlarmRequest.h>
#include <iostream>
```

Enable the alarm actions.

```
    Aws::CloudWatch::CloudWatchClient cw;
```

```
    Aws::CloudWatch::Model::PutMetricAlarmRequest request;
    request.SetAlarmName(alarm_name);
    request.SetComparisonOperator(
        Aws::CloudWatch::Model::ComparisonOperator::GreaterThanThreshold);
    request.SetEvaluationPeriods(1);
    request.SetMetricName("CPUUtilization");
    request.SetNamespace("AWS/EC2");
    request.SetPeriod(60);
    request.SetStatistic(Aws::CloudWatch::Model::Statistic::Average);
    request.SetThreshold(70.0);
    request.SetActionsEnabled(false);
    request.SetAlarmDescription("Alarm when server CPU exceeds 70%");
    request.SetUnit(Aws::CloudWatch::Model::StandardUnit::Seconds);
    request.AddAlarmActions(actionArn);

    Aws::CloudWatch::Model::Dimension dimension;
    dimension.SetName("InstanceId");
    dimension.SetValue(instanceId);
    request.AddDimensions(dimension);

    auto outcome = cw.PutMetricAlarm(request);
    if (!outcome.IsSuccess())
    {
        std::cout << "Failed to create CloudWatch alarm:" <<
            outcome.GetError().GetMessage() << std::endl;
        return;
    }

    Aws::CloudWatch::Model::EnableAlarmActionsRequest enable_request;
    enable_request.AddAlarmNames(alarm_name);

    auto enable_outcome = cw.EnableAlarmActions(enable_request);
    if (!enable_outcome.IsSuccess())
    {
        std::cout << "Failed to enable alarm actions:" <<
            enable_outcome.GetError().GetMessage() << std::endl;
        return;
    }

    std::cout << "Successfully created alarm " << alarm_name <<
        " and enabled actions on it." << std::endl;
```

- For API details, see EnableAlarmActions in *AWS SDK for C++ API Reference*.

`ListMetrics`

The following code example shows how to use `ListMetrics`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Include the required files.

```
#include <aws/core/Aws.h>
#include <aws/monitoring/CloudWatchClient.h>
#include <aws/monitoring/model/ListMetricsRequest.h>
#include <aws/monitoring/model/ListMetricsResult.h>
#include <iomanip>
#include <iostream>
```

List the metrics.

```
        Aws::CloudWatch::CloudWatchClient cw;
        Aws::CloudWatch::Model::ListMetricsRequest request;

        if (argc > 1)
        {
            request.SetMetricName(argv[1]);
        }

        if (argc > 2)
        {
            request.SetNamespace(argv[2]);
        }

        bool done = false;
        bool header = false;
        while (!done)
        {
            auto outcome = cw.ListMetrics(request);
```

```
            if (!outcome.IsSuccess())
            {
                std::cout << "Failed to list CloudWatch metrics:" <<
                    outcome.GetError().GetMessage() << std::endl;
                break;
            }

            if (!header)
            {
                std::cout << std::left << std::setw(48) << "MetricName" <<
                    std::setw(32) << "Namespace" << "DimensionNameValuePairs" <<
                    std::endl;
                header = true;
            }

            const auto &metrics = outcome.GetResult().GetMetrics();
            for (const auto &metric : metrics)
            {
                std::cout << std::left << std::setw(48) <<
                    metric.GetMetricName() << std::setw(32) <<
                    metric.GetNamespace();
                const auto &dimensions = metric.GetDimensions();
                for (auto iter = dimensions.cbegin();
                    iter != dimensions.cend(); ++iter)
                {
                    const auto &dimkv = *iter;
                    std::cout << dimkv.GetName() << " = " << dimkv.GetValue();
                    if (iter + 1 != dimensions.cend())
                    {
                        std::cout << ", ";
                    }
                }
                std::cout << std::endl;
            }

            const auto &next_token = outcome.GetResult().GetNextToken();
            request.SetNextToken(next_token);
            done = next_token.empty();
        }
```

- For API details, see ListMetrics in *AWS SDK for C++ API Reference*.

`PutMetricAlarm`

The following code example shows how to use `PutMetricAlarm`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Include the required files.

```
#include <aws/core/Aws.h>
#include <aws/monitoring/CloudWatchClient.h>
#include <aws/monitoring/model/PutMetricAlarmRequest.h>
#include <iostream>
```

Create the alarm to watch the metric.

```
        Aws::CloudWatch::CloudWatchClient cw;
        Aws::CloudWatch::Model::PutMetricAlarmRequest request;
        request.SetAlarmName(alarm_name);
        request.SetComparisonOperator(
            Aws::CloudWatch::Model::ComparisonOperator::GreaterThanThreshold);
        request.SetEvaluationPeriods(1);
        request.SetMetricName("CPUUtilization");
        request.SetNamespace("AWS/EC2");
        request.SetPeriod(60);
        request.SetStatistic(Aws::CloudWatch::Model::Statistic::Average);
        request.SetThreshold(70.0);
        request.SetActionsEnabled(false);
        request.SetAlarmDescription("Alarm when server CPU exceeds 70%");
        request.SetUnit(Aws::CloudWatch::Model::StandardUnit::Seconds);

        Aws::CloudWatch::Model::Dimension dimension;
        dimension.SetName("InstanceId");
        dimension.SetValue(instanceId);

        request.AddDimensions(dimension);
```

```
        auto outcome = cw.PutMetricAlarm(request);
        if (!outcome.IsSuccess())
        {
            std::cout << "Failed to create CloudWatch alarm:" <<
                outcome.GetError().GetMessage() << std::endl;
        }
        else
        {
            std::cout << "Successfully created CloudWatch alarm " << alarm_name
                << std::endl;
        }
```

- For API details, see PutMetricAlarm in *AWS SDK for C++ API Reference*.

`PutMetricData`

The following code example shows how to use `PutMetricData`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Include the required files.

```
#include <aws/core/Aws.h>
#include <aws/monitoring/CloudWatchClient.h>
#include <aws/monitoring/model/PutMetricDataRequest.h>
#include <iostream>
```

Put data into the metric.

```
        Aws::CloudWatch::CloudWatchClient cw;
```

```
        Aws::CloudWatch::Model::Dimension dimension;
        dimension.SetName("UNIQUE_PAGES");
        dimension.SetValue("URLS");

        Aws::CloudWatch::Model::MetricDatum datum;
        datum.SetMetricName("PAGES_VISITED");
        datum.SetUnit(Aws::CloudWatch::Model::StandardUnit::None);
        datum.SetValue(data_point);
        datum.AddDimensions(dimension);

        Aws::CloudWatch::Model::PutMetricDataRequest request;
        request.SetNamespace("SITE/TRAFFIC");
        request.AddMetricData(datum);

        auto outcome = cw.PutMetricData(request);
        if (!outcome.IsSuccess())
        {
            std::cout << "Failed to put sample metric data:" <<
                outcome.GetError().GetMessage() << std::endl;
        }
        else
        {
            std::cout << "Successfully put sample metric data" << std::endl;
        }
```

- For API details, see PutMetricData in *AWS SDK for C++ API Reference*.

CloudWatch Logs examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with CloudWatch Logs.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Actions

Actions

`DeleteSubscriptionFilter`

The following code example shows how to use `DeleteSubscriptionFilter`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Include the required files.

```
#include <aws/core/Aws.h>
#include <aws/core/utils/Outcome.h>
#include <aws/logs/CloudWatchLogsClient.h>
#include <aws/logs/model/DeleteSubscriptionFilterRequest.h>
#include <iostream>
```

Delete the subscription filter.

```
        Aws::CloudWatchLogs::CloudWatchLogsClient cwl;
        Aws::CloudWatchLogs::Model::DeleteSubscriptionFilterRequest request;
        request.SetFilterName(filter_name);
        request.SetLogGroupName(log_group);

        auto outcome = cwl.DeleteSubscriptionFilter(request);
        if (!outcome.IsSuccess()) {
            std::cout << "Failed to delete CloudWatch log subscription filter "
                << filter_name << ": " << outcome.GetError().GetMessage() <<
                std::endl;
        } else {
            std::cout << "Successfully deleted CloudWatch logs subscription " <<
                "filter " << filter_name << std::endl;
        }
```

- For API details, see DeleteSubscriptionFilter in *AWS SDK for C++ API Reference*.

`DescribeSubscriptionFilters`

The following code example shows how to use `DescribeSubscriptionFilters`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Include the required files.

```
#include <aws/core/Aws.h>
#include <aws/core/utils/Outcome.h>
#include <aws/logs/CloudWatchLogsClient.h>
#include <aws/logs/model/DescribeSubscriptionFiltersRequest.h>
#include <aws/logs/model/DescribeSubscriptionFiltersResult.h>
#include <iostream>
#include <iomanip>
```

List the subscription filters.

```
        Aws::CloudWatchLogs::CloudWatchLogsClient cwl;
        Aws::CloudWatchLogs::Model::DescribeSubscriptionFiltersRequest request;
        request.SetLogGroupName(log_group);
        request.SetLimit(1);

        bool done = false;
        bool header = false;
        while (!done) {
            auto outcome = cwl.DescribeSubscriptionFilters(
                    request);
            if (!outcome.IsSuccess()) {
                std::cout << "Failed to describe CloudWatch subscription filters "
                    << "for log group " << log_group << ": " <<
                    outcome.GetError().GetMessage() << std::endl;
                break;
```

```
            }

            if (!header) {
                std::cout << std::left << std::setw(32) << "Name" <<
                    std::setw(64) << "FilterPattern" << std::setw(64) <<
                    "DestinationArn" << std::endl;
                header = true;
            }

            const auto &filters = outcome.GetResult().GetSubscriptionFilters();
            for (const auto &filter : filters) {
                std::cout << std::left << std::setw(32) <<
                    filter.GetFilterName() << std::setw(64) <<
                    filter.GetFilterPattern() << std::setw(64) <<
                    filter.GetDestinationArn() << std::endl;
            }

            const auto &next_token = outcome.GetResult().GetNextToken();
            request.SetNextToken(next_token);
            done = next_token.empty();
        }
```

- For API details, see DescribeSubscriptionFilters in *AWS SDK for C++ API Reference*.

`PutSubscriptionFilter`

The following code example shows how to use `PutSubscriptionFilter`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Include the required files.

```
#include <aws/core/Aws.h>
#include <aws/logs/CloudWatchLogsClient.h>
#include <aws/logs/model/PutSubscriptionFilterRequest.h>
```

```
#include <aws/core/utils/Outcome.h>
#include <iostream>
```

Create the subscription filter.

```
        Aws::CloudWatchLogs::CloudWatchLogsClient cwl;
        Aws::CloudWatchLogs::Model::PutSubscriptionFilterRequest request;
        request.SetFilterName(filter_name);
        request.SetFilterPattern(filter_pattern);
        request.SetLogGroupName(log_group);
        request.SetDestinationArn(dest_arn);
        auto outcome = cwl.PutSubscriptionFilter(request);
        if (!outcome.IsSuccess())
        {
            std::cout << "Failed to create CloudWatch logs subscription filter "
                << filter_name << ": " << outcome.GetError().GetMessage() <<
                std::endl;
        }
        else
        {
            std::cout << "Successfully created CloudWatch logs subscription " <<
                "filter " << filter_name << std::endl;
        }
```

- For API details, see PutSubscriptionFilter in *AWS SDK for C++ API Reference*.

CodeBuild examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with CodeBuild.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Actions

Actions

`ListBuilds`

The following code example shows how to use `ListBuilds`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! List the CodeBuild builds.
/*!
  \param sortType: 'SortOrderType' type.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::CodeBuild::listBuilds(Aws::CodeBuild::Model::SortOrderType sortType,
                                   const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::CodeBuild::CodeBuildClient codeBuildClient(clientConfiguration);

    Aws::CodeBuild::Model::ListBuildsRequest listBuildsRequest;
    listBuildsRequest.SetSortOrder(sortType);

    Aws::String nextToken; // Used for pagination.

    do {
        if (!nextToken.empty()) {
            listBuildsRequest.SetNextToken(nextToken);
        }

        Aws::CodeBuild::Model::ListBuildsOutcome listBuildsOutcome =
 codeBuildClient.ListBuilds(
                listBuildsRequest);

        if (listBuildsOutcome.IsSuccess()) {
            const Aws::Vector<Aws::String> &ids =
 listBuildsOutcome.GetResult().GetIds();
```

```
            if (!ids.empty()) {

                std::cout << "Information about each build:" << std::endl;
                Aws::CodeBuild::Model::BatchGetBuildsRequest getBuildsRequest;
                getBuildsRequest.SetIds(listBuildsOutcome.GetResult().GetIds());
                Aws::CodeBuild::Model::BatchGetBuildsOutcome getBuildsOutcome =
 codeBuildClient.BatchGetBuilds(
                        getBuildsRequest);

                if (getBuildsOutcome.IsSuccess()) {
                    const Aws::Vector<Aws::CodeBuild::Model::Build> &builds =
 getBuildsOutcome.GetResult().GetBuilds();
                    std::cout << builds.size() << " build(s) found." << std::endl;
                    for (auto val: builds) {
                        std::cout << val.GetId() << std::endl;
                    }
                } else {
                    std::cerr << "Error getting builds"
                              << getBuildsOutcome.GetError().GetMessage() <<
 std::endl;
                    return false;
                }
            } else {
                std::cout << "No builds found." << std::endl;
            }

            // Get the next token for pagination.

            nextToken = listBuildsOutcome.GetResult().GetNextToken();
        } else {
            std::cerr << "Error listing builds"
                      << listBuildsOutcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }

    } while (!nextToken.

            empty()

            );

    return true;
}
```

- For API details, see ListBuilds in *AWS SDK for C++ API Reference*.

`ListProjects`

The following code example shows how to use `ListProjects`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! List the CodeBuild projects.
/*!
  \param sortType: 'SortOrderType' type.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::CodeBuild::listProjects(Aws::CodeBuild::Model::SortOrderType sortType,
                                     const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::CodeBuild::CodeBuildClient codeBuildClient(clientConfiguration);

    Aws::CodeBuild::Model::ListProjectsRequest listProjectsRequest;
    listProjectsRequest.SetSortOrder(sortType);

    Aws::String nextToken; // Next token for pagination.
    Aws::Vector<Aws::String> allProjects;

    do {
        if (!nextToken.empty()) {
            listProjectsRequest.SetNextToken(nextToken);
        }

        Aws::CodeBuild::Model::ListProjectsOutcome outcome =
 codeBuildClient.ListProjects(
                listProjectsRequest);
```

```
        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::String> &projects =
 outcome.GetResult().GetProjects();
            allProjects.insert(allProjects.end(), projects.begin(), projects.end());
            nextToken = outcome.GetResult().GetNextToken();
        }

        else {
            std::cerr << "Error listing projects" << outcome.GetError().GetMessage()
                      << std::endl;
        }

    } while (!nextToken.empty());

    std::cout << allProjects.size() << " project(s) found." << std::endl;
    for (auto project: allProjects) {
        std::cout << project << std::endl;
    }

    return true;
}
```

- For API details, see ListProjects in *AWS SDK for C++ API Reference*.

`StartBuild`

The following code example shows how to use `StartBuild`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Start an AWS CodeBuild project build.
/*!
  \param projectName: A CodeBuild project name.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
```

```
 */
bool AwsDoc::CodeBuild::startBuild(const Aws::String &projectName,
                                   const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::CodeBuild::CodeBuildClient codeBuildClient(clientConfiguration);

    Aws::CodeBuild::Model::StartBuildRequest startBuildRequest;
    startBuildRequest.SetProjectName(projectName);

    Aws::CodeBuild::Model::StartBuildOutcome outcome = codeBuildClient.StartBuild(
            startBuildRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully started build" << std::endl;
        std::cout << "Build ID: " << outcome.GetResult().GetBuild().GetId()
                  << std::endl;
    }

    else {
        std::cerr << "Error starting build" << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see StartBuild in *AWS SDK for C++ API Reference*.

Amazon Cognito Identity Provider examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with Amazon Cognito Identity Provider.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Scenarios are code examples that show you how to accomplish specific tasks by calling multiple functions within a service or combined with other AWS services.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Get started
- Actions
- Scenarios

Get started

Hello Amazon Cognito

The following code example shows how to get started using Amazon Cognito.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Code for the CMakeLists.txt CMake file.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS cognito-idp)

# Set this project's name.
project("hello_cognito")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
```

```
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD AND AWSSDK_INSTALL_AS_SHARED_LIBS)
     # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

     # set(BIN_SUB_DIR "/Debug") # If you are building from the command line, you
 may need to uncomment this
                                 # and set the proper subdirectory to the
 executables' location.

     AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_cognito.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Code for the hello_cognito.cpp source file.

```
#include <aws/core/Aws.h>
#include <aws/cognito-idp/CognitoIdentityProviderClient.h>
#include <aws/cognito-idp/model/ListUserPoolsRequest.h>
#include <iostream>

/*
 *  A "Hello Cognito" starter application which initializes an Amazon Cognito client
 and lists the Amazon Cognito
 *  user pools.
 *
 *  main function
 *
 *  Usage: 'hello_cognito'
```

```
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
 cognitoClient(clientConfig);

        Aws::String nextToken; // Used for pagination.
        std::vector<Aws::String> userPools;

        do {
            Aws::CognitoIdentityProvider::Model::ListUserPoolsRequest
 listUserPoolsRequest;
            if (!nextToken.empty()) {
                listUserPoolsRequest.SetNextToken(nextToken);
            }

            Aws::CognitoIdentityProvider::Model::ListUserPoolsOutcome
 listUserPoolsOutcome =
                    cognitoClient.ListUserPools(listUserPoolsRequest);

            if (listUserPoolsOutcome.IsSuccess()) {
                for (auto &userPool:
 listUserPoolsOutcome.GetResult().GetUserPools()) {

                    userPools.push_back(userPool.GetName());
                }

                nextToken = listUserPoolsOutcome.GetResult().GetNextToken();
            } else {
                std::cerr << "ListUserPools error: " <<
 listUserPoolsOutcome.GetError().GetMessage() << std::endl;
                result = 1;
                break;
```

```
            }


        } while (!nextToken.empty());
        std::cout << userPools.size() << " user pools found." << std::endl;
        for (auto &userPool: userPools) {
            std::cout << "   user pool: " << userPool << std::endl;
        }
    }

    Aws::ShutdownAPI(options); // Should only be called once.
    return result;
}
```

- For API details, see ListUserPools in *AWS SDK for C++ API Reference*.

Actions

`AdminGetUser`

The following code example shows how to use `AdminGetUser`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
client(clientConfig);

    Aws::CognitoIdentityProvider::Model::AdminGetUserRequest request;
    request.SetUsername(userName);
    request.SetUserPoolId(userPoolID);
```

```
   Aws::CognitoIdentityProvider::Model::AdminGetUserOutcome outcome =
           client.AdminGetUser(request);

   if (outcome.IsSuccess()) {
       std::cout << "The status for " << userName << " is " <<

Aws::CognitoIdentityProvider::Model::UserStatusTypeMapper::GetNameForUserStatusType(
                        outcome.GetResult().GetUserStatus()) << std::endl;
       std::cout << "Enabled is " << outcome.GetResult().GetEnabled() << std::endl;
   }
   else {
       std::cerr << "Error with CognitoIdentityProvider::AdminGetUser. "
                 << outcome.GetError().GetMessage()
                 << std::endl;
   }
```

- For API details, see AdminGetUser in *AWS SDK for C++ API Reference*.

`AdminInitiateAuth`

The following code example shows how to use `AdminInitiateAuth`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
       Aws::Client::ClientConfiguration clientConfig;
       // Optional: Set to the AWS Region (overrides config file).
       // clientConfig.region = "us-east-1";

   Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
client(clientConfig);

   Aws::CognitoIdentityProvider::Model::AdminInitiateAuthRequest request;
   request.SetClientId(clientID);
   request.SetUserPoolId(userPoolID);
```

```
    request.AddAuthParameters("USERNAME", userName);
    request.AddAuthParameters("PASSWORD", password);
    request.SetAuthFlow(

Aws::CognitoIdentityProvider::Model::AuthFlowType::ADMIN_USER_PASSWORD_AUTH);


    Aws::CognitoIdentityProvider::Model::AdminInitiateAuthOutcome outcome =
            client.AdminInitiateAuth(request);

    if (outcome.IsSuccess()) {
        std::cout << "Call to AdminInitiateAuth was successful." << std::endl;
        sessionResult = outcome.GetResult().GetSession();
    }
    else {
        std::cerr << "Error with CognitoIdentityProvider::AdminInitiateAuth. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
```

- For API details, see AdminInitiateAuth in *AWS SDK for C++ API Reference*.

`AdminRespondToAuthChallenge`

The following code example shows how to use `AdminRespondToAuthChallenge`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
client(clientConfig);
```

```
        Aws::CognitoIdentityProvider::Model::AdminRespondToAuthChallengeRequest
request;
        request.AddChallengeResponses("USERNAME", userName);
        request.AddChallengeResponses("SOFTWARE_TOKEN_MFA_CODE", mfaCode);
        request.SetChallengeName(

Aws::CognitoIdentityProvider::Model::ChallengeNameType::SOFTWARE_TOKEN_MFA);
        request.SetClientId(clientID);
        request.SetUserPoolId(userPoolID);
        request.SetSession(session);

        Aws::CognitoIdentityProvider::Model::AdminRespondToAuthChallengeOutcome
outcome =
                client.AdminRespondToAuthChallenge(request);

        if (outcome.IsSuccess()) {
            std::cout << "Here is the response to the challenge.\n" <<

outcome.GetResult().GetAuthenticationResult().Jsonize().View().WriteReadable()
                      << std::endl;

            accessToken =
outcome.GetResult().GetAuthenticationResult().GetAccessToken();
        }
        else {
            std::cerr << "Error with
CognitoIdentityProvider::AdminRespondToAuthChallenge. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
```

- For API details, see AdminRespondToAuthChallenge in *AWS SDK for C++ API Reference*.

`AssociateSoftwareToken`

The following code example shows how to use `AssociateSoftwareToken`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
 client(clientConfig);

        Aws::CognitoIdentityProvider::Model::AssociateSoftwareTokenRequest request;
        request.SetSession(session);

        Aws::CognitoIdentityProvider::Model::AssociateSoftwareTokenOutcome outcome =
                client.AssociateSoftwareToken(request);

        if (outcome.IsSuccess()) {
            std::cout
                    << "Enter this setup key into an authenticator app, for example
 Google Authenticator."
                    << std::endl;
            std::cout << "Setup key: " << outcome.GetResult().GetSecretCode()
                      << std::endl;
#ifdef USING_QR
            printAsterisksLine();
            std::cout << "\nOr scan the QR code in the file '" << QR_CODE_PATH <<
 "."
                      << std::endl;

            saveQRCode(std::string("otpauth://totp/") + userName + "?secret=" +
                       outcome.GetResult().GetSecretCode());
#endif // USING_QR
            session = outcome.GetResult().GetSession();
        }
        else {
            std::cerr << "Error with
 CognitoIdentityProvider::AssociateSoftwareToken. "
```

```
                    << outcome.GetError().GetMessage()
                    << std::endl;
            return false;
        }
```

- For API details, see AssociateSoftwareToken in *AWS SDK for C++ API Reference*.

`ConfirmSignUp`

The following code example shows how to use `ConfirmSignUp`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
client(clientConfig);

        Aws::CognitoIdentityProvider::Model::ConfirmSignUpRequest request;
        request.SetClientId(clientID);
        request.SetConfirmationCode(confirmationCode);
        request.SetUsername(userName);

        Aws::CognitoIdentityProvider::Model::ConfirmSignUpOutcome outcome =
                client.ConfirmSignUp(request);

        if (outcome.IsSuccess()) {
            std::cout << "ConfirmSignup was Successful."
                      << std::endl;
        }
        else {
            std::cerr << "Error with CognitoIdentityProvider::ConfirmSignUp. "
```

```
                    << outcome.GetError().GetMessage()
                    << std::endl;
            return false;
        }
```

- For API details, see ConfirmSignUp in *AWS SDK for C++ API Reference*.

`DeleteUser`

The following code example shows how to use `DeleteUser`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
client(clientConfig);

        Aws::CognitoIdentityProvider::Model::DeleteUserRequest request;
        request.SetAccessToken(accessToken);

        Aws::CognitoIdentityProvider::Model::DeleteUserOutcome outcome =
                client.DeleteUser(request);

        if (outcome.IsSuccess()) {
            std::cout << "The user " << userName << " was deleted."
                    << std::endl;
        }
        else {
            std::cerr << "Error with CognitoIdentityProvider::DeleteUser. "
                    << outcome.GetError().GetMessage()
                    << std::endl;
        }
```

- For API details, see DeleteUser in *AWS SDK for C++ API Reference*.

`ResendConfirmationCode`

The following code example shows how to use `ResendConfirmationCode`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
client(clientConfig);

        Aws::CognitoIdentityProvider::Model::ResendConfirmationCodeRequest request;
        request.SetUsername(userName);
        request.SetClientId(clientID);

        Aws::CognitoIdentityProvider::Model::ResendConfirmationCodeOutcome outcome =
                client.ResendConfirmationCode(request);

        if (outcome.IsSuccess()) {
            std::cout
                    << "CognitoIdentityProvider::ResendConfirmationCode was
successful."
                    << std::endl;
        }
        else {
            std::cerr << "Error with
CognitoIdentityProvider::ResendConfirmationCode. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
```

```
        }
```

- For API details, see ResendConfirmationCode in *AWS SDK for C++ API Reference*.

`SignUp`

The following code example shows how to use `SignUp`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
       Aws::Client::ClientConfiguration clientConfig;
       // Optional: Set to the AWS Region (overrides config file).
       // clientConfig.region = "us-east-1";

   Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
client(clientConfig);

       Aws::CognitoIdentityProvider::Model::SignUpRequest request;
       request.AddUserAttributes(
               Aws::CognitoIdentityProvider::Model::AttributeType().WithName(
                       "email").WithValue(email));
       request.SetUsername(userName);
       request.SetPassword(password);
       request.SetClientId(clientID);
       Aws::CognitoIdentityProvider::Model::SignUpOutcome outcome =
               client.SignUp(request);

       if (outcome.IsSuccess()) {
           std::cout << "The signup request for " << userName << " was successful."
                     << std::endl;
       }
       else if (outcome.GetError().GetErrorType() ==

Aws::CognitoIdentityProvider::CognitoIdentityProviderErrors::USERNAME_EXISTS) {
           std::cout
```

```
                    << "The username already exists. Please enter a different
username."
                    << std::endl;
            userExists = true;
        }
        else {
            std::cerr << "Error with CognitoIdentityProvider::SignUpRequest. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
```

- For API details, see SignUp in *AWS SDK for C++ API Reference*.

`VerifySoftwareToken`

The following code example shows how to use `VerifySoftwareToken`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
client(clientConfig);

        Aws::CognitoIdentityProvider::Model::VerifySoftwareTokenRequest request;
        request.SetUserCode(userCode);
        request.SetSession(session);

        Aws::CognitoIdentityProvider::Model::VerifySoftwareTokenOutcome outcome =
                client.VerifySoftwareToken(request);

        if (outcome.IsSuccess()) {
```

```
            std::cout << "Verification of the code was successful."
                      << std::endl;
            session = outcome.GetResult().GetSession();
        }
        else {
            std::cerr << "Error with CognitoIdentityProvider::VerifySoftwareToken. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
```

- For API details, see VerifySoftwareToken in *AWS SDK for C++ API Reference*.

Scenarios

Sign up a user with a user pool that requires MFA

The following code example shows how to:

- Sign up and confirm a user with a username, password, and email address.
- Set up multi-factor authentication by associating an MFA application with the user.
- Sign in by using a password and an MFA code.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Scenario that adds a user to an Amazon Cognito user pool.
/*!
  \sa gettingStartedWithUserPools()
  \param clientID: Client ID associated with an Amazon Cognito user pool.
```

```
  \param userPoolID: An Amazon Cognito user pool ID.
  \param clientConfig: Aws client configuration.
  \return bool: Successful completion.
 */
bool AwsDoc::Cognito::gettingStartedWithUserPools(const Aws::String &clientID,
                                                  const Aws::String &userPoolID,
                                                  const
 Aws::Client::ClientConfiguration &clientConfig) {
    printAsterisksLine();
    std::cout
            << "Welcome to the Amazon Cognito example scenario."
            << std::endl;
    printAsterisksLine();

    std::cout
            << "This scenario will add a user to an Amazon Cognito user pool."
            << std::endl;
    const Aws::String userName = askQuestion("Enter a new username: ");
    const Aws::String password = askQuestion("Enter a new password: ");
    const Aws::String email = askQuestion("Enter a valid email for the user: ");

    std::cout << "Signing up " << userName << std::endl;

    Aws::CognitoIdentityProvider::CognitoIdentityProviderClient
 client(clientConfig);
    bool userExists = false;
    do {
        // 1. Add a user with a username, password, and email address.
        Aws::CognitoIdentityProvider::Model::SignUpRequest request;
        request.AddUserAttributes(
                Aws::CognitoIdentityProvider::Model::AttributeType().WithName(
                        "email").WithValue(email));
        request.SetUsername(userName);
        request.SetPassword(password);
        request.SetClientId(clientID);
        Aws::CognitoIdentityProvider::Model::SignUpOutcome outcome =
                client.SignUp(request);

        if (outcome.IsSuccess()) {
            std::cout << "The signup request for " << userName << " was successful."
                      << std::endl;
        }
        else if (outcome.GetError().GetErrorType() ==
```

```
Aws::CognitoIdentityProvider::CognitoIdentityProviderErrors::USERNAME_EXISTS) {
            std::cout
                    << "The username already exists. Please enter a different
username."
                    << std::endl;
            userExists = true;
        }
        else {
            std::cerr << "Error with CognitoIdentityProvider::SignUpRequest. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (userExists);

    printAsterisksLine();
    std::cout << "Retrieving status of " << userName << " in the user pool."
              << std::endl;
    // 2. Confirm that the user was added to the user pool.
    if (!checkAdminUserStatus(userName, userPoolID, client)) {
        return false;
    }

    std::cout << "A confirmation code was sent to " << email << "." << std::endl;

    bool resend = askYesNoQuestion("Would you like to send a new code? (y/n) ");
    if (resend) {
        // Request a resend of the confirmation code to the email address.
(ResendConfirmationCode)
        Aws::CognitoIdentityProvider::Model::ResendConfirmationCodeRequest request;
        request.SetUsername(userName);
        request.SetClientId(clientID);

        Aws::CognitoIdentityProvider::Model::ResendConfirmationCodeOutcome outcome =
                client.ResendConfirmationCode(request);

        if (outcome.IsSuccess()) {
            std::cout
                    << "CognitoIdentityProvider::ResendConfirmationCode was
successful."
                    << std::endl;
        }
        else {
```

```
            std::cerr << "Error with
CognitoIdentityProvider::ResendConfirmationCode. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }

    printAsterisksLine();

    {
        // 4. Send the confirmation code that's received in the email.
(ConfirmSignUp)
        const Aws::String confirmationCode = askQuestion(
                "Enter the confirmation code that was emailed: ");
        Aws::CognitoIdentityProvider::Model::ConfirmSignUpRequest request;
        request.SetClientId(clientID);
        request.SetConfirmationCode(confirmationCode);
        request.SetUsername(userName);

        Aws::CognitoIdentityProvider::Model::ConfirmSignUpOutcome outcome =
                client.ConfirmSignUp(request);

        if (outcome.IsSuccess()) {
            std::cout << "ConfirmSignup was Successful."
                      << std::endl;
        }
        else {
            std::cerr << "Error with CognitoIdentityProvider::ConfirmSignUp. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }

    std::cout << "Rechecking the status of " << userName << " in the user pool."
              << std::endl;
    if (!checkAdminUserStatus(userName, userPoolID, client)) {
        return false;
    }

    printAsterisksLine();

    std::cout << "Initiating authorization using the username and password."
```

```
              << std::endl;

    Aws::String session;
    // 5. Initiate authorization with username and password. (AdminInitiateAuth)
    if (!adminInitiateAuthorization(clientID, userPoolID,  userName, password,
 session, client)) {
        return false;
    }

    printAsterisksLine();

    std::cout
            << "Starting setup of time-based one-time password (TOTP) multi-factor
 authentication (MFA)."
            << std::endl;

    {
        // 6. Request a setup key for one-time password (TOTP)
        //    multi-factor authentication (MFA). (AssociateSoftwareToken)
        Aws::CognitoIdentityProvider::Model::AssociateSoftwareTokenRequest request;
        request.SetSession(session);

        Aws::CognitoIdentityProvider::Model::AssociateSoftwareTokenOutcome outcome =
                client.AssociateSoftwareToken(request);

        if (outcome.IsSuccess()) {
            std::cout
                    << "Enter this setup key into an authenticator app, for example
 Google Authenticator."
                    << std::endl;
            std::cout << "Setup key: " << outcome.GetResult().GetSecretCode()
                      << std::endl;
#ifdef USING_QR
            printAsterisksLine();
            std::cout << "\nOr scan the QR code in the file '" << QR_CODE_PATH <<
 "."
                      << std::endl;

            saveQRCode(std::string("otpauth://totp/") + userName + "?secret=" +
                       outcome.GetResult().GetSecretCode());
#endif // USING_QR
            session = outcome.GetResult().GetSession();
        }
        else {
```

```
            std::cerr << "Error with
CognitoIdentityProvider::AssociateSoftwareToken. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }
    askQuestion("Type enter to continue...", alwaysTrueTest);

    printAsterisksLine();

    {
        Aws::String userCode = askQuestion(
                "Enter the 6 digit code displayed in the authenticator app: ");

        //  7. Send the MFA code copied from an authenticator app.
(VerifySoftwareToken)
        Aws::CognitoIdentityProvider::Model::VerifySoftwareTokenRequest request;
        request.SetUserCode(userCode);
        request.SetSession(session);

        Aws::CognitoIdentityProvider::Model::VerifySoftwareTokenOutcome outcome =
                client.VerifySoftwareToken(request);

        if (outcome.IsSuccess()) {
            std::cout << "Verification of the code was successful."
                      << std::endl;
            session = outcome.GetResult().GetSession();
        }
        else {
            std::cerr << "Error with CognitoIdentityProvider::VerifySoftwareToken. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }

    printAsterisksLine();
    std::cout << "You have completed the MFA authentication setup." << std::endl;
    std::cout << "Now, sign in." << std::endl;

    // 8. Initiate authorization again with username and password.
(AdminInitiateAuth)
```

```
   if (!adminInitiateAuthorization(clientID, userPoolID, userName, password,
session, client)) {
       return false;
   }

   Aws::String accessToken;
   {
       Aws::String mfaCode = askQuestion(
               "Re-enter the 6 digit code displayed in the authenticator app: ");

       // 9. Send a new MFA code copied from an authenticator app.
(AdminRespondToAuthChallenge)
       Aws::CognitoIdentityProvider::Model::AdminRespondToAuthChallengeRequest
request;
       request.AddChallengeResponses("USERNAME", userName);
       request.AddChallengeResponses("SOFTWARE_TOKEN_MFA_CODE", mfaCode);
       request.SetChallengeName(

Aws::CognitoIdentityProvider::Model::ChallengeNameType::SOFTWARE_TOKEN_MFA);
       request.SetClientId(clientID);
       request.SetUserPoolId(userPoolID);
       request.SetSession(session);

       Aws::CognitoIdentityProvider::Model::AdminRespondToAuthChallengeOutcome
outcome =
               client.AdminRespondToAuthChallenge(request);

       if (outcome.IsSuccess()) {
           std::cout << "Here is the response to the challenge.\n" <<

outcome.GetResult().GetAuthenticationResult().Jsonize().View().WriteReadable()
                     << std::endl;

           accessToken =
outcome.GetResult().GetAuthenticationResult().GetAccessToken();
       }
       else {
           std::cerr << "Error with
CognitoIdentityProvider::AdminRespondToAuthChallenge. "
                     << outcome.GetError().GetMessage()
                     << std::endl;
           return false;
       }
```

```
        std::cout << "You have successfully added a user to Amazon Cognito."
                  << std::endl;
    }

    if (askYesNoQuestion("Would you like to delete the user that you just added? (y/
n) ")) {
        // 10. Delete the user that you just added. (DeleteUser)
        Aws::CognitoIdentityProvider::Model::DeleteUserRequest request;
        request.SetAccessToken(accessToken);

        Aws::CognitoIdentityProvider::Model::DeleteUserOutcome outcome =
                client.DeleteUser(request);

        if (outcome.IsSuccess()) {
            std::cout << "The user " << userName << " was deleted."
                      << std::endl;
        }
        else {
            std::cerr << "Error with CognitoIdentityProvider::DeleteUser. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
    }

    return true;
}

//! Routine which checks the user status in an Amazon Cognito user pool.
/*!
 \sa checkAdminUserStatus()
 \param userName: A username.
 \param userPoolID: An Amazon Cognito user pool ID.
 \return bool: Successful completion.
 */
bool AwsDoc::Cognito::checkAdminUserStatus(const Aws::String &userName,
                                           const Aws::String &userPoolID,
                                           const
 Aws::CognitoIdentityProvider::CognitoIdentityProviderClient &client) {
    Aws::CognitoIdentityProvider::Model::AdminGetUserRequest request;
    request.SetUsername(userName);
    request.SetUserPoolId(userPoolID);

    Aws::CognitoIdentityProvider::Model::AdminGetUserOutcome outcome =
            client.AdminGetUser(request);
```

```
    if (outcome.IsSuccess()) {
        std::cout << "The status for " << userName << " is " <<

 Aws::CognitoIdentityProvider::Model::UserStatusTypeMapper::GetNameForUserStatusType(
                          outcome.GetResult().GetUserStatus()) << std::endl;
        std::cout << "Enabled is " << outcome.GetResult().GetEnabled() << std::endl;
    }
    else {
        std::cerr << "Error with CognitoIdentityProvider::AdminGetUser. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}

//! Routine which starts authorization of an Amazon Cognito user.
//! This routine requires administrator credentials.
/*!
 \sa adminInitiateAuthorization()
 \param clientID: Client ID of tracked device.
 \param userPoolID: An Amazon Cognito user pool ID.
 \param userName: A username.
 \param password: A password.
 \param sessionResult: String to receive a session token.
 \return bool: Successful completion.
 */
bool AwsDoc::Cognito::adminInitiateAuthorization(const Aws::String &clientID,
                                                 const Aws::String &userPoolID,
                                                 const Aws::String &userName,
                                                 const Aws::String &password,
                                                 Aws::String &sessionResult,
                                                 const
 Aws::CognitoIdentityProvider::CognitoIdentityProviderClient &client) {
    Aws::CognitoIdentityProvider::Model::AdminInitiateAuthRequest request;
    request.SetClientId(clientID);
    request.SetUserPoolId(userPoolID);
    request.AddAuthParameters("USERNAME", userName);
    request.AddAuthParameters("PASSWORD", password);
    request.SetAuthFlow(

 Aws::CognitoIdentityProvider::Model::AuthFlowType::ADMIN_USER_PASSWORD_AUTH);
```

```
    Aws::CognitoIdentityProvider::Model::AdminInitiateAuthOutcome outcome =
            client.AdminInitiateAuth(request);

    if (outcome.IsSuccess()) {
        std::cout << "Call to AdminInitiateAuth was successful." << std::endl;
        sessionResult = outcome.GetResult().GetSession();
    }
    else {
        std::cerr << "Error with CognitoIdentityProvider::AdminInitiateAuth. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see the following topics in *AWS SDK for C++ API Reference*.
  - AdminGetUser
  - AdminInitiateAuth
  - AdminRespondToAuthChallenge
  - AssociateSoftwareToken
  - ConfirmDevice
  - ConfirmSignUp
  - InitiateAuth
  - ListUsers
  - ResendConfirmationCode
  - RespondToAuthChallenge
  - SignUp
  - VerifySoftwareToken

DynamoDB examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with DynamoDB.

Basics are code examples that show you how to perform the essential operations within a service.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Scenarios are code examples that show you how to accomplish specific tasks by calling multiple functions within a service or combined with other AWS services.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Get started
- Basics
- Actions
- Scenarios

Get started

Hello DynamoDB

The following code example shows how to get started using DynamoDB.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Code for the CMakeLists.txt CMake file.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS dynamodb)
```

```
# Set this project's name.
project("hello_dynamodb")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD AND AWSSDK_INSTALL_AS_SHARED_LIBS)
     # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

     # set(BIN_SUB_DIR "/Debug") # if you are building from the command line you may
 need to uncomment this
                                     # and set the proper subdirectory to the
 executables' location.

     AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_dynamodb.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Code for the hello_dynamodb.cpp source file.

```
#include <aws/core/Aws.h>
```

```
#include <aws/dynamodb/DynamoDBClient.h>
#include <aws/dynamodb/model/ListTablesRequest.h>
#include <iostream>

/*
 *  A "Hello DynamoDB" starter application which initializes an Amazon DynamoDB
 (DynamoDB) client and lists the
 *  DynamoDB tables.
 *
 *  main function
 *
 *  Usage: 'hello_dynamodb'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.

    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::DynamoDB::DynamoDBClient dynamodbClient(clientConfig);
        Aws::DynamoDB::Model::ListTablesRequest listTablesRequest;
        listTablesRequest.SetLimit(50);
        do {
            const Aws::DynamoDB::Model::ListTablesOutcome &outcome =
 dynamodbClient.ListTables(
                    listTablesRequest);
            if (!outcome.IsSuccess()) {
                std::cout << "Error: " << outcome.GetError().GetMessage() <<
 std::endl;
                result = 1;
                break;
            }

            for (const auto &tableName: outcome.GetResult().GetTableNames()) {
                std::cout << tableName << std::endl;
            }
```

```
            listTablesRequest.SetExclusiveStartTableName(
                    outcome.GetResult().GetLastEvaluatedTableName());

        } while (!listTablesRequest.GetExclusiveStartTableName().empty());
    }


    Aws::ShutdownAPI(options); // Should only be called once.
    return result;
}
```

- For API details, see ListTables in *AWS SDK for C++ API Reference*.

Basics

Learn the basics

The following code example shows how to:

- Create a table that can hold movie data.
- Put, get, and update a single movie in the table.
- Write movie data to the table from a sample JSON file.
- Query for movies that were released in a given year.
- Scan for movies that were released in a range of years.
- Delete a movie from the table, then delete the table.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
    {
        Aws::Client::ClientConfiguration clientConfig;
```

```
        //  1. Create a table with partition: year (N) and sort: title (S).
 (CreateTable)
        if (AwsDoc::DynamoDB::createMoviesDynamoDBTable(clientConfig)) {

            AwsDoc::DynamoDB::dynamodbGettingStartedScenario(clientConfig);

            // 9. Delete the table. (DeleteTable)
            AwsDoc::DynamoDB::deleteMoviesDynamoDBTable(clientConfig);
        }
    }

//! Scenario to modify and query a DynamoDB table.
/*!
  \sa dynamodbGettingStartedScenario()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::DynamoDB::dynamodbGettingStartedScenario(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    std::cout << std::setfill('*') << std::setw(ASTERISK_FILL_WIDTH) << " "
              << std::endl;
    std::cout << "Welcome to the Amazon DynamoDB getting started demo." <<
 std::endl;
    std::cout << std::setfill('*') << std::setw(ASTERISK_FILL_WIDTH) << " "
              << std::endl;

    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    // 2. Add a new movie.
    Aws::String title;
    float rating;
    int year;
    Aws::String plot;
    {
        title = askQuestion(
                "Enter the title of a movie you want to add to the table: ");
        year = askQuestionForInt("What year was it released? ");
        rating = askQuestionForFloatRange("On a scale of 1 - 10, how do you rate it?
 ",
                                          1, 10);
        plot = askQuestion("Summarize the plot for me: ");

        Aws::DynamoDB::Model::PutItemRequest putItemRequest;
        putItemRequest.SetTableName(MOVIE_TABLE_NAME);
```

```
        putItemRequest.AddItem(YEAR_KEY,
                               Aws::DynamoDB::Model::AttributeValue().SetN(year));
        putItemRequest.AddItem(TITLE_KEY,
                               Aws::DynamoDB::Model::AttributeValue().SetS(title));

        // Create attribute for the info map.
        Aws::DynamoDB::Model::AttributeValue infoMapAttribute;

        std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> ratingAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
                ALLOCATION_TAG.c_str());
        ratingAttribute->SetN(rating);
        infoMapAttribute.AddMEntry(RATING_KEY, ratingAttribute);

        std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> plotAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
                ALLOCATION_TAG.c_str());
        plotAttribute->SetS(plot);
        infoMapAttribute.AddMEntry(PLOT_KEY, plotAttribute);

        putItemRequest.AddItem(INFO_KEY, infoMapAttribute);

        Aws::DynamoDB::Model::PutItemOutcome outcome = dynamoClient.PutItem(
                putItemRequest);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to add an item: " <<
outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }

    std::cout << "\nAdded '" << title << "' to '" << MOVIE_TABLE_NAME << "'."
              << std::endl;

    // 3. Update the rating and plot of the movie by using an update expression.
    {
        rating = askQuestionForFloatRange(
                Aws::String("\nLet's update your movie.\nYou rated it  ") +
                std::to_string(rating)
                + ", what new rating would you give it? ", 1, 10);
        plot = askQuestion(Aws::String("You summarized the plot as '") + plot +
                           "'.\nWhat would you say now? ");
```

```
       Aws::DynamoDB::Model::UpdateItemRequest request;
       request.SetTableName(MOVIE_TABLE_NAME);
       request.AddKey(TITLE_KEY,
Aws::DynamoDB::Model::AttributeValue().SetS(title));
       request.AddKey(YEAR_KEY, Aws::DynamoDB::Model::AttributeValue().SetN(year));
       std::stringstream expressionStream;
       expressionStream << "set " << INFO_KEY << "." << RATING_KEY << " =:r, "
                        << INFO_KEY << "." << PLOT_KEY << " =:p";
       request.SetUpdateExpression(expressionStream.str());
       request.SetExpressionAttributeValues({
                                                {":r",
Aws::DynamoDB::Model::AttributeValue().SetN(
                                                        rating)},
                                                {":p",
Aws::DynamoDB::Model::AttributeValue().SetS(
                                                        plot)}
                                            });

       request.SetReturnValues(Aws::DynamoDB::Model::ReturnValue::UPDATED_NEW);

       const Aws::DynamoDB::Model::UpdateItemOutcome &result =
dynamoClient.UpdateItem(
               request);
       if (!result.IsSuccess()) {
           std::cerr << "Error updating movie " + result.GetError().GetMessage()
                     << std::endl;
           return false;
       }
   }

   std::cout << "\nUpdated '" << title << "' with new attributes:" << std::endl;

   // 4. Put 250 movies in the table from moviedata.json.
   {
       std::cout << "Adding movies from a json file to the database." << std::endl;
       const size_t MAX_SIZE_FOR_BATCH_WRITE = 25;
       const size_t MOVIES_TO_WRITE = 10 * MAX_SIZE_FOR_BATCH_WRITE;
       Aws::String jsonString = getMovieJSON();
       if (!jsonString.empty()) {
           Aws::Utils::Json::JsonValue json(jsonString);
           Aws::Utils::Array<Aws::Utils::Json::JsonView> movieJsons =
json.View().AsArray();
           Aws::Vector<Aws::DynamoDB::Model::WriteRequest> writeRequests;
```

```
            // To add movies with a cross-section of years, use an appropriate
increment
            // value for iterating through the database.
            size_t increment = movieJsons.GetLength() / MOVIES_TO_WRITE;
            for (size_t i = 0; i < movieJsons.GetLength(); i += increment) {
                writeRequests.push_back(Aws::DynamoDB::Model::WriteRequest());
                Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue> putItems
= movieJsonViewToAttributeMap(
                        movieJsons[i]);
                Aws::DynamoDB::Model::PutRequest putRequest;
                putRequest.SetItem(putItems);
                writeRequests.back().SetPutRequest(putRequest);
                if (writeRequests.size() == MAX_SIZE_FOR_BATCH_WRITE) {
                    Aws::DynamoDB::Model::BatchWriteItemRequest request;
                    request.AddRequestItems(MOVIE_TABLE_NAME, writeRequests);
                    const Aws::DynamoDB::Model::BatchWriteItemOutcome &outcome =
dynamoClient.BatchWriteItem(
                            request);
                    if (!outcome.IsSuccess()) {
                        std::cerr << "Unable to batch write movie data: "
                                  << outcome.GetError().GetMessage()
                                  << std::endl;
                        writeRequests.clear();
                        break;
                    }
                    else {
                        std::cout << "Added batch of " << writeRequests.size()
                                  << " movies to the database."
                                  << std::endl;
                    }
                    writeRequests.clear();
                }
            }
        }
    }

    std::cout << std::setfill('*') << std::setw(ASTERISK_FILL_WIDTH) << " "
              << std::endl;

    // 5. Get a movie by Key (partition + sort).
    {
        Aws::String titleToGet("King Kong");
        Aws::String answer = askQuestion(Aws::String(
```

```
                "Let's move on...Would you like to get info about '" + titleToGet +
                "'? (y/n) "));
        if (answer == "y") {
            Aws::DynamoDB::Model::GetItemRequest request;
            request.SetTableName(MOVIE_TABLE_NAME);
            request.AddKey(TITLE_KEY,
                           Aws::DynamoDB::Model::AttributeValue().SetS(titleToGet));
            request.AddKey(YEAR_KEY,
Aws::DynamoDB::Model::AttributeValue().SetN(1933));

            const Aws::DynamoDB::Model::GetItemOutcome &result =
dynamoClient.GetItem(
                    request);
            if (!result.IsSuccess()) {
                std::cerr << "Error " << result.GetError().GetMessage();
            }
            else {
                const Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
&item = result.GetResult().GetItem();
                if (!item.empty()) {
                    std::cout << "\nHere's what I found:" << std::endl;
                    printMovieInfo(item);
                }
                else {
                    std::cout << "\nThe movie was not found in the database."
                              << std::endl;
                }
            }
        }
    }

    // 6. Use Query with a key condition expression to return all movies
    //    released in a given year.
    Aws::String doAgain = "n";
    do {
        Aws::DynamoDB::Model::QueryRequest req;

        req.SetTableName(MOVIE_TABLE_NAME);

        // "year" is a DynamoDB reserved keyword and must be replaced with an
        // expression attribute name.
        req.SetKeyConditionExpression("#dynobase_year = :valueToMatch");
        req.SetExpressionAttributeNames({{"#dynobase_year", YEAR_KEY}});
```

```
        int yearToMatch = askQuestionForIntRange(
                "\nLet's get a list of movies released in"
                " a given year. Enter a year between 1972 and 2018 ",
                1972, 2018);
        Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue> attributeValues;
        attributeValues.emplace(":valueToMatch",
                                Aws::DynamoDB::Model::AttributeValue().SetN(
                                        yearToMatch));
        req.SetExpressionAttributeValues(attributeValues);

        const Aws::DynamoDB::Model::QueryOutcome &result = dynamoClient.Query(req);
        if (result.IsSuccess()) {
            const Aws::Vector<Aws::Map<Aws::String,
Aws::DynamoDB::Model::AttributeValue>> &items = result.GetResult().GetItems();
            if (!items.empty()) {
                std::cout << "\nThere were " << items.size()
                          << " movies in the database from "
                          << yearToMatch << "." << std::endl;
                for (const auto &item: items) {
                    printMovieInfo(item);
                }
                doAgain = "n";
            }
            else {
                std::cout << "\nNo movies from " << yearToMatch
                          << " were found in the database"
                          << std::endl;
                doAgain = askQuestion(Aws::String("Try another year? (y/n) "));
            }
        }
        else {
            std::cerr << "Failed to Query items: " << result.GetError().GetMessage()
                      << std::endl;
        }

    } while (doAgain == "y");

    //  7. Use Scan to return movies released within a range of years.
    //     Show how to paginate data using ExclusiveStartKey. (Scan +
FilterExpression)
    {
        int startYear = askQuestionForIntRange("\nNow let's scan a range of years "
                                               "for movies in the database. Enter a
start year: ",
```

```
                                                1972, 2018);
        int endYear = askQuestionForIntRange("\nEnter an end year: ",
                                             startYear, 2018);
        Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
exclusiveStartKey;
        do {
            Aws::DynamoDB::Model::ScanRequest scanRequest;
            scanRequest.SetTableName(MOVIE_TABLE_NAME);
            scanRequest.SetFilterExpression(
                    "#dynobase_year >= :startYear AND #dynobase_year <= :endYear");
            scanRequest.SetExpressionAttributeNames({{"#dynobase_year", YEAR_KEY}});

            Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
attributeValues;
            attributeValues.emplace(":startYear",
                                    Aws::DynamoDB::Model::AttributeValue().SetN(
                                            startYear));
            attributeValues.emplace(":endYear",
                                    Aws::DynamoDB::Model::AttributeValue().SetN(
                                            endYear));
            scanRequest.SetExpressionAttributeValues(attributeValues);

            if (!exclusiveStartKey.empty()) {
                scanRequest.SetExclusiveStartKey(exclusiveStartKey);
            }

            const Aws::DynamoDB::Model::ScanOutcome &result = dynamoClient.Scan(
                    scanRequest);
            if (result.IsSuccess()) {
                const Aws::Vector<Aws::Map<Aws::String,
Aws::DynamoDB::Model::AttributeValue>> &items = result.GetResult().GetItems();
                if (!items.empty()) {
                    std::stringstream stringStream;
                    stringStream << "\nFound " << items.size() << " movies in one
scan."
                                 << " How many would you like to see? ";
                    size_t count = askQuestionForInt(stringStream.str());
                    for (size_t i = 0; i < count && i < items.size(); ++i) {
                        printMovieInfo(items[i]);
                    }
                }
                else {
                    std::cout << "\nNo movies in the database between " << startYear
<<
```

```
                                " and " << endYear << "." << std::endl;
                    }

                    exclusiveStartKey = result.GetResult().GetLastEvaluatedKey();
                    if (!exclusiveStartKey.empty()) {
                        std::cout << "Not all movies were retrieved. Scanning for more."
                                  << std::endl;
                    }
                    else {
                        std::cout << "All movies were retrieved with this scan."
                                  << std::endl;
                    }
                }
                else {
                    std::cerr << "Failed to Scan movies: "
                              << result.GetError().GetMessage() << std::endl;
                }
            } while (!exclusiveStartKey.empty());
        }

        // 8. Delete a movie. (DeleteItem)
        {
            std::stringstream stringStream;
            stringStream << "\nWould you like to delete the movie " << title
                         << " from the database? (y/n) ";
            Aws::String answer = askQuestion(stringStream.str());
            if (answer == "y") {
                Aws::DynamoDB::Model::DeleteItemRequest request;
                request.AddKey(YEAR_KEY,
    Aws::DynamoDB::Model::AttributeValue().SetN(year));
                request.AddKey(TITLE_KEY,
                               Aws::DynamoDB::Model::AttributeValue().SetS(title));
                request.SetTableName(MOVIE_TABLE_NAME);

                const Aws::DynamoDB::Model::DeleteItemOutcome &result =
    dynamoClient.DeleteItem(
                        request);
                if (result.IsSuccess()) {
                    std::cout << "\nRemoved \"" << title << "\" from the database."
                              << std::endl;
                }
                else {
                    std::cerr << "Failed to delete the movie: "
                              << result.GetError().GetMessage()
```

```
                            << std::endl;
                }
            }
        }

        return true;
}

//! Routine to convert a JsonView object to an attribute map.
/*!
  \sa movieJsonViewToAttributeMap()
  \param jsonView: Json view object.
  \return map: Map that can be used in a DynamoDB request.
 */
Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
AwsDoc::DynamoDB::movieJsonViewToAttributeMap(
        const Aws::Utils::Json::JsonView &jsonView) {
    Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue> result;

    if (jsonView.KeyExists(YEAR_KEY)) {
        result[YEAR_KEY].SetN(jsonView.GetInteger(YEAR_KEY));
    }
    if (jsonView.KeyExists(TITLE_KEY)) {
        result[TITLE_KEY].SetS(jsonView.GetString(TITLE_KEY));
    }
    if (jsonView.KeyExists(INFO_KEY)) {
        Aws::Map<Aws::String, const
 std::shared_ptr<Aws::DynamoDB::Model::AttributeValue>> infoMap;
        Aws::Utils::Json::JsonView infoView = jsonView.GetObject(INFO_KEY);
        if (infoView.KeyExists(RATING_KEY)) {
            std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> attributeValue =
 std::make_shared<Aws::DynamoDB::Model::AttributeValue>();
            attributeValue->SetN(infoView.GetDouble(RATING_KEY));
            infoMap.emplace(std::make_pair(RATING_KEY, attributeValue));
        }
        if (infoView.KeyExists(PLOT_KEY)) {
            std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> attributeValue =
 std::make_shared<Aws::DynamoDB::Model::AttributeValue>();
            attributeValue->SetS(infoView.GetString(PLOT_KEY));
            infoMap.emplace(std::make_pair(PLOT_KEY, attributeValue));
        }

        result[INFO_KEY].SetM(infoMap);
    }
```

```
    return result;
}

//! Create a DynamoDB table to be used in sample code scenarios.
/*!
  \sa createMoviesDynamoDBTable()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::createMoviesDynamoDBTable(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    bool movieTableAlreadyExisted = false;

    {
        Aws::DynamoDB::Model::CreateTableRequest request;

        Aws::DynamoDB::Model::AttributeDefinition yearAttributeDefinition;
        yearAttributeDefinition.SetAttributeName(YEAR_KEY);
        yearAttributeDefinition.SetAttributeType(
                Aws::DynamoDB::Model::ScalarAttributeType::N);
        request.AddAttributeDefinitions(yearAttributeDefinition);

        Aws::DynamoDB::Model::AttributeDefinition titleAttributeDefinition;
        yearAttributeDefinition.SetAttributeName(TITLE_KEY);
        yearAttributeDefinition.SetAttributeType(
                Aws::DynamoDB::Model::ScalarAttributeType::S);
        request.AddAttributeDefinitions(yearAttributeDefinition);

        Aws::DynamoDB::Model::KeySchemaElement yearKeySchema;
        yearKeySchema.WithAttributeName(YEAR_KEY).WithKeyType(
                Aws::DynamoDB::Model::KeyType::HASH);
        request.AddKeySchema(yearKeySchema);

        Aws::DynamoDB::Model::KeySchemaElement titleKeySchema;
        yearKeySchema.WithAttributeName(TITLE_KEY).WithKeyType(
                Aws::DynamoDB::Model::KeyType::RANGE);
        request.AddKeySchema(yearKeySchema);

        Aws::DynamoDB::Model::ProvisionedThroughput throughput;
        throughput.WithReadCapacityUnits(
                PROVISIONED_THROUGHPUT_UNITS).WithWriteCapacityUnits(
```

```
                PROVISIONED_THROUGHPUT_UNITS);
        request.SetProvisionedThroughput(throughput);
        request.SetTableName(MOVIE_TABLE_NAME);

        std::cout << "Creating table '" << MOVIE_TABLE_NAME << "'..." << std::endl;
        const Aws::DynamoDB::Model::CreateTableOutcome &result =
 dynamoClient.CreateTable(
                request);
        if (!result.IsSuccess()) {
            if (result.GetError().GetErrorType() ==
                Aws::DynamoDB::DynamoDBErrors::RESOURCE_IN_USE) {
                std::cout << "Table already exists." << std::endl;
                movieTableAlreadyExisted = true;
            }
            else {
                std::cerr << "Failed to create table: "
                          << result.GetError().GetMessage();
                return false;
            }
        }
    }

    // Wait for table to become active.
    if (!movieTableAlreadyExisted) {
        std::cout << "Waiting for table '" << MOVIE_TABLE_NAME
                  << "' to become active...." << std::endl;
        if (!AwsDoc::DynamoDB::waitTableActive(MOVIE_TABLE_NAME,
 clientConfiguration)) {
            return false;
        }
        std::cout << "Table '" << MOVIE_TABLE_NAME << "' created and active."
                  << std::endl;
    }

    return true;
}

//! Delete the DynamoDB table used for sample code scenarios.
/*!
  \sa deleteMoviesDynamoDBTable()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::deleteMoviesDynamoDBTable(
```

```
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::DeleteTableRequest request;
    request.SetTableName(MOVIE_TABLE_NAME);

    const Aws::DynamoDB::Model::DeleteTableOutcome &result =
 dynamoClient.DeleteTable(
           request);
    if (result.IsSuccess()) {
        std::cout << "Your table \""
                  << result.GetResult().GetTableDescription().GetTableName()
                  << " was deleted.\n";
    }
    else {
        std::cerr << "Failed to delete table: " << result.GetError().GetMessage()
                  << std::endl;
    }

    return result.IsSuccess();
}

//! Query a newly created DynamoDB table until it is active.
/*!
  \sa waitTableActive()
  \param waitTableActive: The DynamoDB table's name.
  \param dynamoClient: A DynamoDB client.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::waitTableActive(const Aws::String &tableName,
                                       const Aws::DynamoDB::DynamoDBClient
 &dynamoClient) {

    // Repeatedly call DescribeTable until table is ACTIVE.
    const int MAX_QUERIES = 20;
    Aws::DynamoDB::Model::DescribeTableRequest request;
    request.SetTableName(tableName);

    int count = 0;
    while (count < MAX_QUERIES) {
        const Aws::DynamoDB::Model::DescribeTableOutcome &result =
 dynamoClient.DescribeTable(
                request);
        if (result.IsSuccess()) {
```

```
            Aws::DynamoDB::Model::TableStatus status =
 result.GetResult().GetTable().GetTableStatus();

            if (Aws::DynamoDB::Model::TableStatus::ACTIVE != status) {
                std::this_thread::sleep_for(std::chrono::seconds(1));
            }
            else {
                return true;
            }
        }
        else {
            std::cerr << "Error DynamoDB::waitTableActive "
                      << result.GetError().GetMessage() << std::endl;
            return false;
        }
        count++;
    }
    return false;
}
```

- For API details, see the following topics in *AWS SDK for C++ API Reference*.
  - BatchWriteItem
  - CreateTable
  - DeleteItem
  - DeleteTable
  - DescribeTable
  - GetItem
  - PutItem
  - Query
  - Scan
  - UpdateItem

Actions

`BatchExecuteStatement`

The following code example shows how to use `BatchExecuteStatement`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Use batches of INSERT statements to add items.

```
    // 2. Add multiple movies using "Insert" statements. (BatchExecuteStatement)
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    std::vector<Aws::String> titles;
    std::vector<float> ratings;
    std::vector<int> years;
    std::vector<Aws::String> plots;
    Aws::String doAgain = "n";
    do {
        Aws::String aTitle = askQuestion(
                "Enter the title of a movie you want to add to the table: ");
        titles.push_back(aTitle);
        int aYear = askQuestionForInt("What year was it released? ");
        years.push_back(aYear);
        float aRating = askQuestionForFloatRange(
                "On a scale of 1 - 10, how do you rate it? ",
                1, 10);
        ratings.push_back(aRating);
        Aws::String aPlot = askQuestion("Summarize the plot for me: ");
        plots.push_back(aPlot);

        doAgain = askQuestion(Aws::String("Would you like to add more movies? (y/n)
"));
    } while (doAgain == "y");

    std::cout << "Adding " << titles.size()
              << (titles.size() == 1 ? " movie " : " movies ")
              << "to the table using a batch \"INSERT\" statement." << std::endl;

    {
        Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
                titles.size());
```

```
        std::stringstream sqlStream;
        sqlStream << "INSERT INTO \"" << MOVIE_TABLE_NAME << "\" VALUE {'"
                  << TITLE_KEY << "': ?, '" << YEAR_KEY << "': ?, '"
                  << INFO_KEY << "': ?}";

        std::string sql(sqlStream.str());

        for (size_t i = 0; i < statements.size(); ++i) {
            statements[i].SetStatement(sql);

            Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));

attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));

            // Create attribute for the info map.
            Aws::DynamoDB::Model::AttributeValue infoMapAttribute;

            std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> ratingAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
                    ALLOCATION_TAG.c_str());
            ratingAttribute->SetN(ratings[i]);
            infoMapAttribute.AddMEntry(RATING_KEY, ratingAttribute);

            std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> plotAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
                    ALLOCATION_TAG.c_str());
            plotAttribute->SetS(plots[i]);
            infoMapAttribute.AddMEntry(PLOT_KEY, plotAttribute);
            attributes.push_back(infoMapAttribute);
            statements[i].SetParameters(attributes);
        }

        Aws::DynamoDB::Model::BatchExecuteStatementRequest request;

        request.SetStatements(statements);

        Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
dynamoClient.BatchExecuteStatement(
                request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to add the movies: " <<
outcome.GetError().GetMessage()
```

```
                    << std::endl;
            return false;
        }
    }
```

Use batches of SELECT statements to get items.

```
    // 3. Get the data for multiple movies using "Select" statements.
(BatchExecuteStatement)
    {
        Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
                titles.size());
        std::stringstream sqlStream;
        sqlStream << "SELECT * FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        std::string sql(sqlStream.str());

        for (size_t i = 0; i < statements.size(); ++i) {
            statements[i].SetStatement(sql);
            Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));

attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));
            statements[i].SetParameters(attributes);
        }

        Aws::DynamoDB::Model::BatchExecuteStatementRequest request;

        request.SetStatements(statements);

        Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
dynamoClient.BatchExecuteStatement(
                request);
        if (outcome.IsSuccess()) {
            const Aws::DynamoDB::Model::BatchExecuteStatementResult &result =
outcome.GetResult();

            const Aws::Vector<Aws::DynamoDB::Model::BatchStatementResponse>
&responses = result.GetResponses();
```

```
            for (const Aws::DynamoDB::Model::BatchStatementResponse &response:
responses) {
                const Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
&item = response.GetItem();

                printMovieInfo(item);
            }
        }
        else {
            std::cerr << "Failed to retrieve the movie information: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }
```

Use batches of UPDATE statements to update items.

```
    // 4. Update the data for multiple movies using "Update" statements.
(BatchExecuteStatement)

    for (size_t i = 0; i < titles.size(); ++i) {
        ratings[i] = askQuestionForFloatRange(
                Aws::String("\nLet's update your the movie, \"") + titles[i] +
                ".\nYou rated it  " + std::to_string(ratings[i])
                + ", what new rating would you give it? ", 1, 10);
    }

    std::cout << "Updating the movie with a batch \"UPDATE\" statement." <<
std::endl;

    {
        Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
                titles.size());

        std::stringstream sqlStream;
        sqlStream << "UPDATE \"" << MOVIE_TABLE_NAME << "\" SET "
                  << INFO_KEY << "." << RATING_KEY << "=? WHERE "
                  << TITLE_KEY << "=? AND " << YEAR_KEY << "=?";


        std::string sql(sqlStream.str());
```

```
        for (size_t i = 0; i < statements.size(); ++i) {
            statements[i].SetStatement(sql);

            Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetN(ratings[i]));
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));

attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));
            statements[i].SetParameters(attributes);
        }

        Aws::DynamoDB::Model::BatchExecuteStatementRequest request;

        request.SetStatements(statements);
        Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
dynamoClient.BatchExecuteStatement(
                request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to update movie information: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }
```

Use batches of DELETE statements to delete items.

```
    // 6. Delete multiple movies using "Delete" statements. (BatchExecuteStatement)
    {
        Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
                titles.size());
        std::stringstream sqlStream;
        sqlStream << "DELETE FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        std::string sql(sqlStream.str());

        for (size_t i = 0; i < statements.size(); ++i) {
            statements[i].SetStatement(sql);
            Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
            attributes.push_back(
```

```
                    Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));

attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));
            statements[i].SetParameters(attributes);
        }

        Aws::DynamoDB::Model::BatchExecuteStatementRequest request;

        request.SetStatements(statements);

        Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
dynamoClient.BatchExecuteStatement(
                request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to delete the movies: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }
```

- For API details, see BatchExecuteStatement in *AWS SDK for C++ API Reference*.

`BatchGetItem`

The following code example shows how to use `BatchGetItem`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Batch get items from different Amazon DynamoDB tables.
/*!
  \sa batchGetItem()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
```

```
bool AwsDoc::DynamoDB::batchGetItem(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::BatchGetItemRequest request;

    // Table1: Forum.
    Aws::String table1Name = "Forum";
    Aws::DynamoDB::Model::KeysAndAttributes table1KeysAndAttributes;

    // Table1: Projection expression.
    table1KeysAndAttributes.SetProjectionExpression("#n, Category, Messages, #v");

    // Table1: Expression attribute names.
    Aws::Http::HeaderValueCollection headerValueCollection;
    headerValueCollection.emplace("#n", "Name");
    headerValueCollection.emplace("#v", "Views");
    table1KeysAndAttributes.SetExpressionAttributeNames(headerValueCollection);

    // Table1: Set key name, type, and value to search.
    std::vector<Aws::String> nameValues = {"Amazon DynamoDB", "Amazon S3"};
    for (const Aws::String &name: nameValues) {
        Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue> keys;
        Aws::DynamoDB::Model::AttributeValue key;
        key.SetS(name);
        keys.emplace("Name", key);
        table1KeysAndAttributes.AddKeys(keys);
    }

    Aws::Map<Aws::String, Aws::DynamoDB::Model::KeysAndAttributes> requestItems;
    requestItems.emplace(table1Name, table1KeysAndAttributes);

    // Table2: ProductCatalog.
    Aws::String table2Name = "ProductCatalog";
    Aws::DynamoDB::Model::KeysAndAttributes table2KeysAndAttributes;
    table2KeysAndAttributes.SetProjectionExpression("Title, Price, Color");

    // Table2: Set key name, type, and value to search.
    std::vector<Aws::String> idValues = {"102", "103", "201"};
    for (const Aws::String &id: idValues) {
        Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue> keys;
        Aws::DynamoDB::Model::AttributeValue key;
        key.SetN(id);
        keys.emplace("Id", key);
```

```
        table2KeysAndAttributes.AddKeys(keys);
    }

    requestItems.emplace(table2Name, table2KeysAndAttributes);

    bool result = true;
    do {  // Use a do loop to handle pagination.
        request.SetRequestItems(requestItems);
        const Aws::DynamoDB::Model::BatchGetItemOutcome &outcome =
dynamoClient.BatchGetItem(
                request);

        if (outcome.IsSuccess()) {
            for (const auto &responsesMapEntry: outcome.GetResult().GetResponses())
{
                Aws::String tableName = responsesMapEntry.first;
                const Aws::Vector<Aws::Map<Aws::String,
Aws::DynamoDB::Model::AttributeValue>> &tableResults = responsesMapEntry.second;
                std::cout << "Retrieved " << tableResults.size()
                          << " responses for table '" << tableName << "'.\n"
                          << std::endl;
                if (tableName == "Forum") {

                    std::cout << "Name | Category | Message | Views" << std::endl;
                    for (const Aws::Map<Aws::String,
Aws::DynamoDB::Model::AttributeValue> &item: tableResults) {
                        std::cout << item.at("Name").GetS() << " | ";
                        std::cout << item.at("Category").GetS() << " | ";
                        std::cout << (item.count("Message") == 0 ? "" : item.at(
                                "Messages").GetN()) << " | ";
                        std::cout << (item.count("Views") == 0 ? "" : item.at(
                                "Views").GetN()) << std::endl;
                    }
                }
                else {
                    std::cout << "Title | Price | Color" << std::endl;
                    for (const Aws::Map<Aws::String,
Aws::DynamoDB::Model::AttributeValue> &item: tableResults) {
                        std::cout << item.at("Title").GetS() << " | ";
                        std::cout << (item.count("Price") == 0 ? "" : item.at(
                                "Price").GetN());
                        if (item.count("Color")) {
                            std::cout << " | ";
```

```
                            for (const
 std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> &listItem: item.at(
                                    "Color").GetL())
                                std::cout << listItem->GetS() << " ";
                        }
                        std::cout << std::endl;
                    }
                }
                std::cout << std::endl;
            }

            // If necessary, repeat request for remaining items.
            requestItems = outcome.GetResult().GetUnprocessedKeys();
        }
        else {
            std::cerr << "Batch get item failed: " <<
 outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
            break;
        }
    } while (!requestItems.empty());

    return result;
}
```

- For API details, see BatchGetItem in *AWS SDK for C++ API Reference*.

`BatchWriteItem`

The following code example shows how to use `BatchWriteItem`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Batch write items from a JSON file.
```

```
/*!
  \sa batchWriteItem()
  \param jsonFilePath: JSON file path.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */

/*
 * The input for this routine is a JSON file that you can download from the
 following URL:
 * https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/SampleData.html.
 *
 * The JSON data uses the BatchWriteItem API request syntax. The JSON strings are
 * converted to AttributeValue objects. These AttributeValue objects will then
 generate
 * JSON strings when constructing the BatchWriteItem request, essentially outputting
 * their input.
 *
 * This is perhaps an artificial example, but it demonstrates the APIs.
 */

bool AwsDoc::DynamoDB::batchWriteItem(const Aws::String &jsonFilePath,
                                      const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    std::ifstream fileStream(jsonFilePath);

    if (!fileStream) {
        std::cerr << "Error: could not open file '" << jsonFilePath << "'."
                  << std::endl;
    }

    std::stringstream stringStream;
    stringStream << fileStream.rdbuf();
    Aws::Utils::Json::JsonValue jsonValue(stringStream);

    Aws::DynamoDB::Model::BatchWriteItemRequest batchWriteItemRequest;
    Aws::Map<Aws::String, Aws::Utils::Json::JsonView> level1Map =
 jsonValue.View().GetAllObjects();
    for (const auto &level1Entry: level1Map) {
        const Aws::Utils::Json::JsonView &entriesView = level1Entry.second;
        const Aws::String &tableName = level1Entry.first;
        // The JSON entries at this level are as follows:
        //  key - table name
        //  value - list of request objects
```

```
        if (!entriesView.IsListType()) {
            std::cerr << "Error: JSON file entry '"
                      << tableName << "' is not a list." << std::endl;
            continue;
        }

        Aws::Utils::Array<Aws::Utils::Json::JsonView> entries =
 entriesView.AsArray();

        Aws::Vector<Aws::DynamoDB::Model::WriteRequest> writeRequests;
        if (AwsDoc::DynamoDB::addWriteRequests(tableName, entries,
                                               writeRequests)) {
            batchWriteItemRequest.AddRequestItems(tableName, writeRequests);
        }
    }

    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::BatchWriteItemOutcome outcome =
 dynamoClient.BatchWriteItem(
            batchWriteItemRequest);

    if (outcome.IsSuccess()) {
        std::cout << "DynamoDB::BatchWriteItem was successful." << std::endl;
    }
    else {
        std::cerr << "Error with DynamoDB::BatchWriteItem. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
        return false;
    }

    return outcome.IsSuccess();
}

//! Convert requests in JSON format to a vector of WriteRequest objects.
/*!
  \sa addWriteRequests()
  \param tableName: Name of the table for the write operations.
  \param requestsJson: Request data in JSON format.
  \param writeRequests: Vector to receive the WriteRequest objects.
  \return bool: Function succeeded.
 */
bool AwsDoc::DynamoDB::addWriteRequests(const Aws::String &tableName,
```

```
                                        const
Aws::Utils::Array<Aws::Utils::Json::JsonView> &requestsJson,

Aws::Vector<Aws::DynamoDB::Model::WriteRequest> &writeRequests) {
   for (size_t i = 0; i < requestsJson.GetLength(); ++i) {
       const Aws::Utils::Json::JsonView &requestsEntry = requestsJson[i];
       if (!requestsEntry.IsObject()) {
           std::cerr << "Error: incorrect requestsEntry type "
                     << requestsEntry.WriteReadable() << std::endl;
           return false;
       }

       Aws::Map<Aws::String, Aws::Utils::Json::JsonView> requestsMap =
requestsEntry.GetAllObjects();

       for (const auto &request: requestsMap) {
           const Aws::String &requestType = request.first;
           const Aws::Utils::Json::JsonView &requestJsonView = request.second;

           if (requestType == "PutRequest") {
               if (!requestJsonView.ValueExists("Item")) {
                   std::cerr << "Error: item key missing for requests "
                             << requestJsonView.WriteReadable() << std::endl;
                   return false;
               }
               Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
attributes;
               if (!getAttributeObjectsMap(requestJsonView.GetObject("Item"),
                                           attributes)) {
                   std::cerr << "Error getting attributes "
                             << requestJsonView.WriteReadable() << std::endl;
                   return false;
               }

               Aws::DynamoDB::Model::PutRequest putRequest;
               putRequest.SetItem(attributes);
               writeRequests.push_back(
                       Aws::DynamoDB::Model::WriteRequest().WithPutRequest(
                               putRequest));
           }
           else {
               std::cerr << "Error: unimplemented request type '" << requestType
                         << "'." << std::endl;
           }
```

```
        }
    }

    return true;
}

//! Generate a map of AttributeValue objects from JSON records.
/*!
  \sa getAttributeObjectsMap()
  \param jsonView: JSONView of attribute records.
  \param writeRequests: Map to receive the AttributeValue objects.
  \return bool: Function succeeded.
 */
bool
AwsDoc::DynamoDB::getAttributeObjectsMap(const Aws::Utils::Json::JsonView &jsonView,
                                         Aws::Map<Aws::String,
 Aws::DynamoDB::Model::AttributeValue> &attributes) {
    Aws::Map<Aws::String, Aws::Utils::Json::JsonView> objectsMap =
 jsonView.GetAllObjects();
    for (const auto &entry: objectsMap) {
        const Aws::String &attributeKey = entry.first;
        const Aws::Utils::Json::JsonView &attributeJsonView = entry.second;

        if (!attributeJsonView.IsObject()) {
            std::cerr << "Error: attribute not an object "
                      << attributeJsonView.WriteReadable() << std::endl;
            return false;
        }

        attributes.emplace(attributeKey,
                           Aws::DynamoDB::Model::AttributeValue(attributeJsonView));
    }

    return true;
}
```

- For API details, see BatchWriteItem in *AWS SDK for C++ API Reference*.

`CreateTable`

The following code example shows how to use `CreateTable`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Create an Amazon DynamoDB table.
/*!
  \sa createTable()
  \param tableName: Name for the DynamoDB table.
  \param primaryKey: Primary key for the DynamoDB table.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::DynamoDB::createTable(const Aws::String &tableName,
                                   const Aws::String &primaryKey,
                                   const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    std::cout << "Creating table " << tableName <<
              " with a simple primary key: \"" << primaryKey << "\"." << std::endl;

    Aws::DynamoDB::Model::CreateTableRequest request;

    Aws::DynamoDB::Model::AttributeDefinition hashKey;
    hashKey.SetAttributeName(primaryKey);
    hashKey.SetAttributeType(Aws::DynamoDB::Model::ScalarAttributeType::S);
    request.AddAttributeDefinitions(hashKey);

    Aws::DynamoDB::Model::KeySchemaElement keySchemaElement;
    keySchemaElement.WithAttributeName(primaryKey).WithKeyType(
            Aws::DynamoDB::Model::KeyType::HASH);
    request.AddKeySchema(keySchemaElement);

    Aws::DynamoDB::Model::ProvisionedThroughput throughput;
    throughput.WithReadCapacityUnits(5).WithWriteCapacityUnits(5);
    request.SetProvisionedThroughput(throughput);
    request.SetTableName(tableName);
```

```
    const Aws::DynamoDB::Model::CreateTableOutcome &outcome =
 dynamoClient.CreateTable(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Table \""
                  << outcome.GetResult().GetTableDescription().GetTableName() <<
                  " created!" << std::endl;
    }
    else {
        std::cerr << "Failed to create table: " << outcome.GetError().GetMessage()
                  << std::endl;
        return false;
    }

    return waitTableActive(tableName, dynamoClient);
}
```

Code that waits for the table to become active.

```
//! Query a newly created DynamoDB table until it is active.
/*!
  \sa waitTableActive()
  \param waitTableActive: The DynamoDB table's name.
  \param dynamoClient: A DynamoDB client.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::waitTableActive(const Aws::String &tableName,
                                       const Aws::DynamoDB::DynamoDBClient
 &dynamoClient) {

    // Repeatedly call DescribeTable until table is ACTIVE.
    const int MAX_QUERIES = 20;
    Aws::DynamoDB::Model::DescribeTableRequest request;
    request.SetTableName(tableName);

    int count = 0;
    while (count < MAX_QUERIES) {
        const Aws::DynamoDB::Model::DescribeTableOutcome &result =
 dynamoClient.DescribeTable(
                request);
        if (result.IsSuccess()) {
```

```
            Aws::DynamoDB::Model::TableStatus status =
 result.GetResult().GetTable().GetTableStatus();

            if (Aws::DynamoDB::Model::TableStatus::ACTIVE != status) {
                std::this_thread::sleep_for(std::chrono::seconds(1));
            }
            else {
                return true;
            }
        }
        else {
            std::cerr << "Error DynamoDB::waitTableActive "
                      << result.GetError().GetMessage() << std::endl;
            return false;
        }
        count++;
    }
    return false;
}
```

- For API details, see CreateTable in *AWS SDK for C++ API Reference*.

`DeleteItem`

The following code example shows how to use `DeleteItem`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Delete an item from an Amazon DynamoDB table.
/*!
  \sa deleteItem()
  \param tableName: The table name.
  \param partitionKey: The partition key.
  \param partitionValue: The value for the partition key.
```

```
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */

bool AwsDoc::DynamoDB::deleteItem(const Aws::String &tableName,
                                  const Aws::String &partitionKey,
                                  const Aws::String &partitionValue,
                                  const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::DeleteItemRequest request;

    request.AddKey(partitionKey,
                   Aws::DynamoDB::Model::AttributeValue().SetS(partitionValue));
    request.SetTableName(tableName);

    const Aws::DynamoDB::Model::DeleteItemOutcome &outcome =
 dynamoClient.DeleteItem(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Item \"" << partitionValue << "\" deleted!" << std::endl;
    }
    else {
        std::cerr << "Failed to delete item: " << outcome.GetError().GetMessage()
                  << std::endl;
        return false;
    }

    return waitTableActive(tableName, dynamoClient);
}
```

Code that waits for the table to become active.

```
//! Query a newly created DynamoDB table until it is active.
/*!
  \sa waitTableActive()
  \param waitTableActive: The DynamoDB table's name.
  \param dynamoClient: A DynamoDB client.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::waitTableActive(const Aws::String &tableName,
```

```
                                        const Aws::DynamoDB::DynamoDBClient
 &dynamoClient) {

    // Repeatedly call DescribeTable until table is ACTIVE.
    const int MAX_QUERIES = 20;
    Aws::DynamoDB::Model::DescribeTableRequest request;
    request.SetTableName(tableName);

    int count = 0;
    while (count < MAX_QUERIES) {
        const Aws::DynamoDB::Model::DescribeTableOutcome &result =
 dynamoClient.DescribeTable(
                request);
        if (result.IsSuccess()) {
            Aws::DynamoDB::Model::TableStatus status =
 result.GetResult().GetTable().GetTableStatus();

            if (Aws::DynamoDB::Model::TableStatus::ACTIVE != status) {
                std::this_thread::sleep_for(std::chrono::seconds(1));
            }
            else {
                return true;
            }
        }
        else {
            std::cerr << "Error DynamoDB::waitTableActive "
                      << result.GetError().GetMessage() << std::endl;
            return false;
        }
        count++;
    }
    return false;
}
```

- For API details, see DeleteItem in *AWS SDK for C++ API Reference*.

`DeleteTable`

The following code example shows how to use `DeleteTable`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Delete an Amazon DynamoDB table.
/*!
  \sa deleteTable()
  \param tableName: The DynamoDB table name.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::deleteTable(const Aws::String &tableName,
                                   const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::DeleteTableRequest request;
    request.SetTableName(tableName);

    const Aws::DynamoDB::Model::DeleteTableOutcome &result =
 dynamoClient.DeleteTable(
            request);
    if (result.IsSuccess()) {
        std::cout << "Your table \""
                  << result.GetResult().GetTableDescription().GetTableName()
                  << " was deleted.\n";
    }
    else {
        std::cerr << "Failed to delete table: " << result.GetError().GetMessage()
                  << std::endl;
    }

    return result.IsSuccess();
}
```

- For API details, see DeleteTable in *AWS SDK for C++ API Reference*.

`DescribeTable`

The following code example shows how to use `DescribeTable`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Describe an Amazon DynamoDB table.
/*!
  \sa describeTable()
  \param tableName: The DynamoDB table name.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::describeTable(const Aws::String &tableName,
                                     const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::DescribeTableRequest request;
    request.SetTableName(tableName);

    const Aws::DynamoDB::Model::DescribeTableOutcome &outcome =
 dynamoClient.DescribeTable(
            request);

    if (outcome.IsSuccess()) {
        const Aws::DynamoDB::Model::TableDescription &td =
 outcome.GetResult().GetTable();
        std::cout << "Table name  : " << td.GetTableName() << std::endl;
        std::cout << "Table ARN   : " << td.GetTableArn() << std::endl;
        std::cout << "Status      : "
                  << Aws::DynamoDB::Model::TableStatusMapper::GetNameForTableStatus(
                         td.GetTableStatus()) << std::endl;
        std::cout << "Item count  : " << td.GetItemCount() << std::endl;
        std::cout << "Size (bytes): " << td.GetTableSizeBytes() << std::endl;
```

```
        const Aws::DynamoDB::Model::ProvisionedThroughputDescription &ptd =
 td.GetProvisionedThroughput();
        std::cout << "Throughput" << std::endl;
        std::cout << "  Read Capacity : " << ptd.GetReadCapacityUnits() <<
 std::endl;
        std::cout << "  Write Capacity: " << ptd.GetWriteCapacityUnits() <<
 std::endl;

        const Aws::Vector<Aws::DynamoDB::Model::AttributeDefinition> &ad =
 td.GetAttributeDefinitions();
        std::cout << "Attributes" << std::endl;
        for (const auto &a: ad)
            std::cout << "  " << a.GetAttributeName() << " (" <<

 Aws::DynamoDB::Model::ScalarAttributeTypeMapper::GetNameForScalarAttributeType(
                              a.GetAttributeType()) <<
                     ")" << std::endl;
    }
    else {
        std::cerr << "Failed to describe table: " <<
 outcome.GetError().GetMessage();
    }

    return outcome.IsSuccess();
}
```

- For API details, see DescribeTable in *AWS SDK for C++ API Reference*.

`ExecuteStatement`

The following code example shows how to use `ExecuteStatement`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Use an INSERT statement to add an item.

```
   Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

   // 2. Add a new movie using an "Insert" statement. (ExecuteStatement)
   Aws::String title;
   float rating;
   int year;
   Aws::String plot;
   {
       title = askQuestion(
               "Enter the title of a movie you want to add to the table: ");
       year = askQuestionForInt("What year was it released? ");
       rating = askQuestionForFloatRange("On a scale of 1 - 10, how do you rate it?
",
                                         1, 10);
       plot = askQuestion("Summarize the plot for me: ");

       Aws::DynamoDB::Model::ExecuteStatementRequest request;
       std::stringstream sqlStream;
       sqlStream << "INSERT INTO \"" << MOVIE_TABLE_NAME << "\" VALUE {'"
                 << TITLE_KEY << "': ?, '" << YEAR_KEY << "': ?, '"
                 << INFO_KEY << "': ?}";

       request.SetStatement(sqlStream.str());

       // Create the parameter attributes.
       Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
       attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
       attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));

       Aws::DynamoDB::Model::AttributeValue infoMapAttribute;

       std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> ratingAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
               ALLOCATION_TAG.c_str());
       ratingAttribute->SetN(rating);
       infoMapAttribute.AddMEntry(RATING_KEY, ratingAttribute);

       std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> plotAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
               ALLOCATION_TAG.c_str());
       plotAttribute->SetS(plot);
       infoMapAttribute.AddMEntry(PLOT_KEY, plotAttribute);
       attributes.push_back(infoMapAttribute);
```

```
        request.SetParameters(attributes);

        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
dynamoClient.ExecuteStatement(
                request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to add a movie: " <<
outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }
```

Use a SELECT statement to get an item.

```
    //  3. Get the data for the movie using a "Select" statement. (ExecuteStatement)
    {
        Aws::DynamoDB::Model::ExecuteStatementRequest request;
        std::stringstream sqlStream;
        sqlStream << "SELECT * FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        request.SetStatement(sqlStream.str());

        Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));
        request.SetParameters(attributes);

        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
dynamoClient.ExecuteStatement(
                request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to retrieve movie information: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
        else {
            // Print the retrieved movie information.
```

```
            const Aws::DynamoDB::Model::ExecuteStatementResult &result =
outcome.GetResult();

            const Aws::Vector<Aws::Map<Aws::String,
Aws::DynamoDB::Model::AttributeValue>> &items = result.GetItems();

            if (items.size() == 1) {
                printMovieInfo(items[0]);
            }
            else {
                std::cerr << "Error: " << items.size() << " movies were retrieved. "
                          << " There should be only one movie." << std::endl;
            }
        }
    }
```

Use an UPDATE statement to update an item.

```
    //  4. Update the data for the movie using an "Update" statement.
(ExecuteStatement)
    {
        rating = askQuestionForFloatRange(
                Aws::String("\nLet's update your movie.\nYou rated it  ") +
                std::to_string(rating)
                + ", what new rating would you give it? ", 1, 10);

        Aws::DynamoDB::Model::ExecuteStatementRequest request;
        std::stringstream sqlStream;
        sqlStream << "UPDATE \"" << MOVIE_TABLE_NAME << "\" SET "
                  << INFO_KEY << "." << RATING_KEY << "=? WHERE "
                  << TITLE_KEY << "=? AND " << YEAR_KEY << "=?";

        request.SetStatement(sqlStream.str());

        Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(rating));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));

        request.SetParameters(attributes);
```

```
        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
dynamoClient.ExecuteStatement(
                request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to update a movie: "
                      << outcome.GetError().GetMessage();
            return false;
        }
    }
```

Use a DELETE statement to delete an item.

```
    // 6. Delete the movie using a "Delete" statement. (ExecuteStatement)
    {
        Aws::DynamoDB::Model::ExecuteStatementRequest request;
        std::stringstream sqlStream;
        sqlStream << "DELETE FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        request.SetStatement(sqlStream.str());

        Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));
        request.SetParameters(attributes);

        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
dynamoClient.ExecuteStatement(
                request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to delete the movie: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }
```

- For API details, see ExecuteStatement in *AWS SDK for C++ API Reference*.

`GetItem`

The following code example shows how to use `GetItem`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Get an item from an Amazon DynamoDB table.
/*!
  \sa getItem()
  \param tableName: The table name.
  \param partitionKey: The partition key.
  \param partitionValue: The value for the partition key.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */

bool AwsDoc::DynamoDB::getItem(const Aws::String &tableName,
                               const Aws::String &partitionKey,
                               const Aws::String &partitionValue,
                               const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);
    Aws::DynamoDB::Model::GetItemRequest request;

    // Set up the request.
    request.SetTableName(tableName);
    request.AddKey(partitionKey,
                   Aws::DynamoDB::Model::AttributeValue().SetS(partitionValue));

    // Retrieve the item's fields and values.
    const Aws::DynamoDB::Model::GetItemOutcome &outcome =
 dynamoClient.GetItem(request);
    if (outcome.IsSuccess()) {
        // Reference the retrieved fields/values.
        const Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue> &item =
 outcome.GetResult().GetItem();
        if (!item.empty()) {
```

```
            // Output each retrieved field and its value.
            for (const auto &i: item)
                std::cout << "Values: " << i.first << ": " << i.second.GetS()
                          << std::endl;
        }
        else {
            std::cout << "No item found with the key " << partitionKey << std::endl;
        }
    }
    else {
        std::cerr << "Failed to get item: " << outcome.GetError().GetMessage();
    }

    return outcome.IsSuccess();
}
```

- For API details, see GetItem in *AWS SDK for C++ API Reference*.

`ListTables`

The following code example shows how to use `ListTables`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! List the Amazon DynamoDB tables for the current AWS account.
/*!
  \sa listTables()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */

bool AwsDoc::DynamoDB::listTables(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);
```

```
    Aws::DynamoDB::Model::ListTablesRequest listTablesRequest;
    listTablesRequest.SetLimit(50);
    do {
        const Aws::DynamoDB::Model::ListTablesOutcome &outcome =
 dynamoClient.ListTables(
                listTablesRequest);
        if (!outcome.IsSuccess()) {
            std::cout << "Error: " << outcome.GetError().GetMessage() << std::endl;
            return false;
        }

        for (const auto &tableName: outcome.GetResult().GetTableNames())
            std::cout << tableName << std::endl;
        listTablesRequest.SetExclusiveStartTableName(
                outcome.GetResult().GetLastEvaluatedTableName());

    } while (!listTablesRequest.GetExclusiveStartTableName().empty());

    return true;
}
```

- For API details, see ListTables in *AWS SDK for C++ API Reference*.

`PutItem`

The following code example shows how to use `PutItem`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Put an item in an Amazon DynamoDB table.
/*!
  \sa putItem()
  \param tableName: The table name.
  \param artistKey: The artist key. This is the partition key for the table.
  \param artistValue: The artist value.
```

```
  \param albumTitleKey: The album title key.
  \param albumTitleValue: The album title value.
  \param awardsKey: The awards key.
  \param awardsValue: The awards value.
  \param songTitleKey: The song title key.
  \param songTitleValue: The song title value.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::DynamoDB::putItem(const Aws::String &tableName,
                               const Aws::String &artistKey,
                               const Aws::String &artistValue,
                               const Aws::String &albumTitleKey,
                               const Aws::String &albumTitleValue,
                               const Aws::String &awardsKey,
                               const Aws::String &awardsValue,
                               const Aws::String &songTitleKey,
                               const Aws::String &songTitleValue,
                               const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::PutItemRequest putItemRequest;
    putItemRequest.SetTableName(tableName);

    putItemRequest.AddItem(artistKey, Aws::DynamoDB::Model::AttributeValue().SetS(
            artistValue)); // This is the hash key.
    putItemRequest.AddItem(albumTitleKey,
 Aws::DynamoDB::Model::AttributeValue().SetS(
            albumTitleValue));
    putItemRequest.AddItem(awardsKey,

 Aws::DynamoDB::Model::AttributeValue().SetS(awardsValue));
    putItemRequest.AddItem(songTitleKey,

 Aws::DynamoDB::Model::AttributeValue().SetS(songTitleValue));

    const Aws::DynamoDB::Model::PutItemOutcome outcome = dynamoClient.PutItem(
            putItemRequest);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully added Item!" << std::endl;
    }
    else {
        std::cerr << outcome.GetError().GetMessage() << std::endl;
```

```
        return false;
    }

    return waitTableActive(tableName, dynamoClient);
}
```

Code that waits for the table to become active.

```
//! Query a newly created DynamoDB table until it is active.
/*!
  \sa waitTableActive()
  \param waitTableActive: The DynamoDB table's name.
  \param dynamoClient: A DynamoDB client.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::waitTableActive(const Aws::String &tableName,
                                       const Aws::DynamoDB::DynamoDBClient
 &dynamoClient) {

    // Repeatedly call DescribeTable until table is ACTIVE.
    const int MAX_QUERIES = 20;
    Aws::DynamoDB::Model::DescribeTableRequest request;
    request.SetTableName(tableName);

    int count = 0;
    while (count < MAX_QUERIES) {
        const Aws::DynamoDB::Model::DescribeTableOutcome &result =
 dynamoClient.DescribeTable(
                request);
        if (result.IsSuccess()) {
            Aws::DynamoDB::Model::TableStatus status =
 result.GetResult().GetTable().GetTableStatus();

            if (Aws::DynamoDB::Model::TableStatus::ACTIVE != status) {
                std::this_thread::sleep_for(std::chrono::seconds(1));
            }
            else {
                return true;
            }
        }
        else {
```

```
            std::cerr << "Error DynamoDB::waitTableActive "
                      << result.GetError().GetMessage() << std::endl;
            return false;
        }
        count++;
    }
    return false;
}
```

- For API details, see PutItem in *AWS SDK for C++ API Reference*.

`Query`

The following code example shows how to use `Query`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Perform a query on an Amazon DynamoDB Table and retrieve items.
/*!
  \sa queryItem()
  \param tableName: The table name.
  \param partitionKey: The partition key.
  \param partitionValue: The value for the partition key.
  \param projectionExpression: The projections expression, which is ignored if
 empty.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
  */

/*
 * The partition key attribute is searched with the specified value. By default, all
 fields and values
 * contained in the item are returned. If an optional projection expression is
 * specified on the command line, only the specified fields and values are
 * returned.
```

```
 */

bool AwsDoc::DynamoDB::queryItems(const Aws::String &tableName,
                                  const Aws::String &partitionKey,
                                  const Aws::String &partitionValue,
                                  const Aws::String &projectionExpression,
                                  const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);
    Aws::DynamoDB::Model::QueryRequest request;

    request.SetTableName(tableName);

    if (!projectionExpression.empty()) {
        request.SetProjectionExpression(projectionExpression);
    }

    // Set query key condition expression.
    request.SetKeyConditionExpression(partitionKey + "= :valueToMatch");

    // Set Expression AttributeValues.
    Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue> attributeValues;
    attributeValues.emplace(":valueToMatch", partitionValue);

    request.SetExpressionAttributeValues(attributeValues);

    bool result = true;

    // "exclusiveStartKey" is used for pagination.
    Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue> exclusiveStartKey;
    do {
        if (!exclusiveStartKey.empty()) {
            request.SetExclusiveStartKey(exclusiveStartKey);
            exclusiveStartKey.clear();
        }
        // Perform Query operation.
        const Aws::DynamoDB::Model::QueryOutcome &outcome =
 dynamoClient.Query(request);
        if (outcome.IsSuccess()) {
            // Reference the retrieved items.
            const Aws::Vector<Aws::Map<Aws::String,
 Aws::DynamoDB::Model::AttributeValue>> &items = outcome.GetResult().GetItems();
            if (!items.empty()) {
```

```
                std::cout << "Number of items retrieved from Query: " <<
 items.size()
                          << std::endl;
                // Iterate each item and print.
                for (const auto &item: items) {
                    std::cout
                            <<
 "*************************************************"
                            << std::endl;
                    // Output each retrieved field and its value.
                    for (const auto &i: item)
                        std::cout << i.first << ": " << i.second.GetS() <<
 std::endl;
                }
            }
            else {
                std::cout << "No item found in table: " << tableName << std::endl;
            }

            exclusiveStartKey = outcome.GetResult().GetLastEvaluatedKey();
        }
        else {
            std::cerr << "Failed to Query items: " <<
 outcome.GetError().GetMessage();
            result = false;
            break;
        }
    } while (!exclusiveStartKey.empty());

    return result;
}
```

- For API details, see Query in *AWS SDK for C++ API Reference*.

Scan

The following code example shows how to use `Scan`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Scan an Amazon DynamoDB table.
/*!
  \sa scanTable()
  \param tableName: Name for the DynamoDB table.
  \param projectionExpression: An optional projection expression, ignored if empty.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */

bool AwsDoc::DynamoDB::scanTable(const Aws::String &tableName,
                                 const Aws::String &projectionExpression,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);
    Aws::DynamoDB::Model::ScanRequest request;
    request.SetTableName(tableName);

    if (!projectionExpression.empty())
        request.SetProjectionExpression(projectionExpression);

    Aws::Vector<Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>>
 all_items;
    Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
 last_evaluated_key; // Used for pagination;
    do {
        if (!last_evaluated_key.empty()) {
            request.SetExclusiveStartKey(last_evaluated_key);
        }
        const Aws::DynamoDB::Model::ScanOutcome &outcome =
 dynamoClient.Scan(request);
        if (outcome.IsSuccess()) {
            // Reference the retrieved items.
            const Aws::Vector<Aws::Map<Aws::String,
 Aws::DynamoDB::Model::AttributeValue>> &items = outcome.GetResult().GetItems();
```

```
            all_items.insert(all_items.end(), items.begin(), items.end());

            last_evaluated_key = outcome.GetResult().GetLastEvaluatedKey();
        }
        else {
            std::cerr << "Failed to Scan items: " << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }

    } while (!last_evaluated_key.empty());

    if (!all_items.empty()) {
        std::cout << "Number of items retrieved from scan: " << all_items.size()
                  << std::endl;
        // Iterate each item and print.
        for (const Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
 &itemMap: all_items) {
            std::cout << "*************************************************"
                      << std::endl;
            // Output each retrieved field and its value.
            for (const auto &itemEntry: itemMap)
                std::cout << itemEntry.first << ": " << itemEntry.second.GetS()
                          << std::endl;
        }
    }

    else {
        std::cout << "No items found in table: " << tableName << std::endl;
    }

    return true;
}
```

- For API details, see Scan in *AWS SDK for C++ API Reference*.

`UpdateItem`

The following code example shows how to use `UpdateItem`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Update an Amazon DynamoDB table item.
/*!
  \sa updateItem()
  \param tableName: The table name.
  \param partitionKey: The partition key.
  \param partitionValue: The value for the partition key.
  \param attributeKey: The key for the attribute to be updated.
  \param attributeValue: The value for the attribute to be updated.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
  */

/*
 *  The example code only sets/updates an attribute value. It processes
 *  the attribute value as a string, even if the value could be interpreted
 *  as a number. Also, the example code does not remove an existing attribute
 *  from the key value.
 */

bool AwsDoc::DynamoDB::updateItem(const Aws::String &tableName,
                                  const Aws::String &partitionKey,
                                  const Aws::String &partitionValue,
                                  const Aws::String &attributeKey,
                                  const Aws::String &attributeValue,
                                  const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    // *** Define UpdateItem request arguments.
    // Define TableName argument.
    Aws::DynamoDB::Model::UpdateItemRequest request;
    request.SetTableName(tableName);

    // Define KeyName argument.
```

```
    Aws::DynamoDB::Model::AttributeValue attribValue;
    attribValue.SetS(partitionValue);
    request.AddKey(partitionKey, attribValue);

    // Construct the SET update expression argument.
    Aws::String update_expression("SET #a = :valueA");
    request.SetUpdateExpression(update_expression);

    // Construct attribute name argument.
    Aws::Map<Aws::String, Aws::String> expressionAttributeNames;
    expressionAttributeNames["#a"] = attributeKey;
    request.SetExpressionAttributeNames(expressionAttributeNames);

    // Construct attribute value argument.
    Aws::DynamoDB::Model::AttributeValue attributeUpdatedValue;
    attributeUpdatedValue.SetS(attributeValue);
    Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
 expressionAttributeValues;
    expressionAttributeValues[":valueA"] = attributeUpdatedValue;
    request.SetExpressionAttributeValues(expressionAttributeValues);

    // Update the item.
    const Aws::DynamoDB::Model::UpdateItemOutcome &outcome =
 dynamoClient.UpdateItem(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Item was updated" << std::endl;
    } else {
        std::cerr << outcome.GetError().GetMessage() << std::endl;
        return false;
    }

    return waitTableActive(tableName, dynamoClient);
}
```

Code that waits for the table to become active.

```
//! Query a newly created DynamoDB table until it is active.
/*!
  \sa waitTableActive()
  \param waitTableActive: The DynamoDB table's name.
  \param dynamoClient: A DynamoDB client.
```

```
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::waitTableActive(const Aws::String &tableName,
                                       const Aws::DynamoDB::DynamoDBClient
 &dynamoClient) {

    // Repeatedly call DescribeTable until table is ACTIVE.
    const int MAX_QUERIES = 20;
    Aws::DynamoDB::Model::DescribeTableRequest request;
    request.SetTableName(tableName);

    int count = 0;
    while (count < MAX_QUERIES) {
        const Aws::DynamoDB::Model::DescribeTableOutcome &result =
 dynamoClient.DescribeTable(
                request);
        if (result.IsSuccess()) {
            Aws::DynamoDB::Model::TableStatus status =
 result.GetResult().GetTable().GetTableStatus();

            if (Aws::DynamoDB::Model::TableStatus::ACTIVE != status) {
                std::this_thread::sleep_for(std::chrono::seconds(1));
            }
            else {
                return true;
            }
        }
        else {
            std::cerr << "Error DynamoDB::waitTableActive "
                      << result.GetError().GetMessage() << std::endl;
            return false;
        }
        count++;
    }
    return false;
}
```

- For API details, see UpdateItem in *AWS SDK for C++ API Reference*.

`UpdateTable`

The following code example shows how to use `UpdateTable`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Update a DynamoDB table.
/*!
  \sa updateTable()
  \param tableName: Name for the DynamoDB table.
  \param readCapacity: Provisioned read capacity.
  \param writeCapacity: Provisioned write capacity.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::DynamoDB::updateTable(const Aws::String &tableName,
                                   long long readCapacity, long long writeCapacity,
                                   const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    std::cout << "Updating " << tableName << " with new provisioned throughput
 values"
              << std::endl;
    std::cout << "Read capacity : " << readCapacity << std::endl;
    std::cout << "Write capacity: " << writeCapacity << std::endl;

    Aws::DynamoDB::Model::UpdateTableRequest request;
    Aws::DynamoDB::Model::ProvisionedThroughput provisionedThroughput;

 provisionedThroughput.WithReadCapacityUnits(readCapacity).WithWriteCapacityUnits(
            writeCapacity);

 request.WithProvisionedThroughput(provisionedThroughput).WithTableName(tableName);

    const Aws::DynamoDB::Model::UpdateTableOutcome &outcome =
 dynamoClient.UpdateTable(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully updated the table." << std::endl;
```

```
    } else {
        const Aws::DynamoDB::DynamoDBError &error = outcome.GetError();
        if (error.GetErrorType() == Aws::DynamoDB::DynamoDBErrors::VALIDATION &&
            error.GetMessage().find("The provisioned throughput for the table will
 not change") != std::string::npos) {
            std::cout << "The provisioned throughput for the table will not change."
 << std::endl;
        } else {
            std::cerr << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }

    return waitTableActive(tableName, dynamoClient);
}
```

Code that waits for the table to become active.

```
//! Query a newly created DynamoDB table until it is active.
/*!
  \sa waitTableActive()
  \param waitTableActive: The DynamoDB table's name.
  \param dynamoClient: A DynamoDB client.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::waitTableActive(const Aws::String &tableName,
                                       const Aws::DynamoDB::DynamoDBClient
 &dynamoClient) {

    // Repeatedly call DescribeTable until table is ACTIVE.
    const int MAX_QUERIES = 20;
    Aws::DynamoDB::Model::DescribeTableRequest request;
    request.SetTableName(tableName);

    int count = 0;
    while (count < MAX_QUERIES) {
        const Aws::DynamoDB::Model::DescribeTableOutcome &result =
 dynamoClient.DescribeTable(
                request);
        if (result.IsSuccess()) {
            Aws::DynamoDB::Model::TableStatus status =
 result.GetResult().GetTable().GetTableStatus();
```

```
            if (Aws::DynamoDB::Model::TableStatus::ACTIVE != status) {
                std::this_thread::sleep_for(std::chrono::seconds(1));
            }
            else {
                return true;
            }
        }
        else {
            std::cerr << "Error DynamoDB::waitTableActive "
                      << result.GetError().GetMessage() << std::endl;
            return false;
        }
        count++;
    }
    return false;
}
```

- For API details, see UpdateTable in *AWS SDK for C++ API Reference*.

Scenarios

Create a serverless application to manage photos

The following code example shows how to create a serverless application that lets users manage photos using labels.

SDK for C++

Shows how to develop a photo asset management application that detects labels in images using Amazon Rekognition and stores them for later retrieval.

For complete source code and instructions on how to set up and run, see the full example on GitHub.

For a deep dive into the origin of this example see the post on AWS Community.

Services used in this example

- API Gateway
- DynamoDB

- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Query a table by using batches of PartiQL statements

The following code example shows how to:

- Get a batch of items by running multiple SELECT statements.
- Add a batch of items by running multiple INSERT statements.
- Update a batch of items by running multiple UPDATE statements.
- Delete a batch of items by running multiple DELETE statements.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        //  1. Create a table. (CreateTable)
        if (AwsDoc::DynamoDB::createMoviesDynamoDBTable(clientConfig)) {

            AwsDoc::DynamoDB::partiqlBatchExecuteScenario(clientConfig);

            // 7. Delete the table. (DeleteTable)
            AwsDoc::DynamoDB::deleteMoviesDynamoDBTable(clientConfig);
        }

//! Scenario to modify and query a DynamoDB table using PartiQL batch statements.
/*!
  \sa partiqlBatchExecuteScenario()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
```

```
bool AwsDoc::DynamoDB::partiqlBatchExecuteScenario(
        const Aws::Client::ClientConfiguration &clientConfiguration) {

    // 2. Add multiple movies using "Insert" statements. (BatchExecuteStatement)
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    std::vector<Aws::String> titles;
    std::vector<float> ratings;
    std::vector<int> years;
    std::vector<Aws::String> plots;
    Aws::String doAgain = "n";
    do {
        Aws::String aTitle = askQuestion(
                "Enter the title of a movie you want to add to the table: ");
        titles.push_back(aTitle);
        int aYear = askQuestionForInt("What year was it released? ");
        years.push_back(aYear);
        float aRating = askQuestionForFloatRange(
                "On a scale of 1 - 10, how do you rate it? ",
                1, 10);
        ratings.push_back(aRating);
        Aws::String aPlot = askQuestion("Summarize the plot for me: ");
        plots.push_back(aPlot);

        doAgain = askQuestion(Aws::String("Would you like to add more movies? (y/n)
 "));
    } while (doAgain == "y");

    std::cout << "Adding " << titles.size()
              << (titles.size() == 1 ? " movie " : " movies ")
              << "to the table using a batch \"INSERT\" statement." << std::endl;

    {
        Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
                titles.size());

        std::stringstream sqlStream;
        sqlStream << "INSERT INTO \"" << MOVIE_TABLE_NAME << "\" VALUE {'"
                  << TITLE_KEY << "': ?, '" << YEAR_KEY << "': ?, '"
                  << INFO_KEY << "': ?}";

        std::string sql(sqlStream.str());

        for (size_t i = 0; i < statements.size(); ++i) {
```

```
            statements[i].SetStatement(sql);

            Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));

attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));

            // Create attribute for the info map.
            Aws::DynamoDB::Model::AttributeValue infoMapAttribute;

            std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> ratingAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
                    ALLOCATION_TAG.c_str());
            ratingAttribute->SetN(ratings[i]);
            infoMapAttribute.AddMEntry(RATING_KEY, ratingAttribute);

            std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> plotAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
                    ALLOCATION_TAG.c_str());
            plotAttribute->SetS(plots[i]);
            infoMapAttribute.AddMEntry(PLOT_KEY, plotAttribute);
            attributes.push_back(infoMapAttribute);
            statements[i].SetParameters(attributes);
        }

        Aws::DynamoDB::Model::BatchExecuteStatementRequest request;

        request.SetStatements(statements);

        Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
dynamoClient.BatchExecuteStatement(
                request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to add the movies: " <<
outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }

    std::cout << "Retrieving the movie data with a batch \"SELECT\" statement."
              << std::endl;
```

```
   // 3. Get the data for multiple movies using "Select" statements.
(BatchExecuteStatement)
   {
       Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
               titles.size());
       std::stringstream sqlStream;
       sqlStream << "SELECT * FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                 << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

       std::string sql(sqlStream.str());

       for (size_t i = 0; i < statements.size(); ++i) {
           statements[i].SetStatement(sql);
           Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
           attributes.push_back(
                   Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));

attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));
           statements[i].SetParameters(attributes);
       }

       Aws::DynamoDB::Model::BatchExecuteStatementRequest request;

       request.SetStatements(statements);

       Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
dynamoClient.BatchExecuteStatement(
               request);
       if (outcome.IsSuccess()) {
           const Aws::DynamoDB::Model::BatchExecuteStatementResult &result =
outcome.GetResult();

           const Aws::Vector<Aws::DynamoDB::Model::BatchStatementResponse>
&responses = result.GetResponses();

           for (const Aws::DynamoDB::Model::BatchStatementResponse &response:
responses) {
               const Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
&item = response.GetItem();

               printMovieInfo(item);
           }
       }
       else {
```

```
            std::cerr << "Failed to retrieve the movie information: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }

    // 4. Update the data for multiple movies using "Update" statements.
(BatchExecuteStatement)

    for (size_t i = 0; i < titles.size(); ++i) {
        ratings[i] = askQuestionForFloatRange(
                Aws::String("\nLet's update your the movie, \"") + titles[i] +
                ".\nYou rated it  " + std::to_string(ratings[i])
                + ", what new rating would you give it? ", 1, 10);
    }

    std::cout << "Updating the movie with a batch \"UPDATE\" statement." <<
std::endl;

    {
        Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
                titles.size());

        std::stringstream sqlStream;
        sqlStream << "UPDATE \"" << MOVIE_TABLE_NAME << "\" SET "
                  << INFO_KEY << "." << RATING_KEY << "=? WHERE "
                  << TITLE_KEY << "=? AND " << YEAR_KEY << "=?";


        std::string sql(sqlStream.str());

        for (size_t i = 0; i < statements.size(); ++i) {
            statements[i].SetStatement(sql);

            Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetN(ratings[i]));
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));

attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));
            statements[i].SetParameters(attributes);
        }
```

```
        Aws::DynamoDB::Model::BatchExecuteStatementRequest request;

        request.SetStatements(statements);
        Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
dynamoClient.BatchExecuteStatement(
                request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to update movie information: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }

    std::cout << "Retrieving the updated movie data with a batch \"SELECT\"
statement."
              << std::endl;

    // 5. Get the updated data for multiple movies using "Select" statements.
(BatchExecuteStatement)
    {
        Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
                titles.size());
        std::stringstream sqlStream;
        sqlStream << "SELECT * FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        std::string sql(sqlStream.str());

        for (size_t i = 0; i < statements.size(); ++i) {
            statements[i].SetStatement(sql);
            Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));

attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));
            statements[i].SetParameters(attributes);
        }

        Aws::DynamoDB::Model::BatchExecuteStatementRequest request;

        request.SetStatements(statements);

        Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
dynamoClient.BatchExecuteStatement(
```

```
                request);
        if (outcome.IsSuccess()) {
            const Aws::DynamoDB::Model::BatchExecuteStatementResult &result =
outcome.GetResult();

            const Aws::Vector<Aws::DynamoDB::Model::BatchStatementResponse>
&responses = result.GetResponses();

            for (const Aws::DynamoDB::Model::BatchStatementResponse &response:
responses) {
                const Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>
&item = response.GetItem();

                printMovieInfo(item);
            }
        }
        else {
            std::cerr << "Failed to retrieve the movies information: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }

    std::cout << "Deleting the movie data with a batch \"DELETE\" statement."
              << std::endl;

    // 6. Delete multiple movies using "Delete" statements. (BatchExecuteStatement)
    {
        Aws::Vector<Aws::DynamoDB::Model::BatchStatementRequest> statements(
                titles.size());
        std::stringstream sqlStream;
        sqlStream << "DELETE FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        std::string sql(sqlStream.str());

        for (size_t i = 0; i < statements.size(); ++i) {
            statements[i].SetStatement(sql);
            Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
            attributes.push_back(
                    Aws::DynamoDB::Model::AttributeValue().SetS(titles[i]));

attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(years[i]));
            statements[i].SetParameters(attributes);
```

```
        }

        Aws::DynamoDB::Model::BatchExecuteStatementRequest request;

        request.SetStatements(statements);

        Aws::DynamoDB::Model::BatchExecuteStatementOutcome outcome =
 dynamoClient.BatchExecuteStatement(
                request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to delete the movies: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }

    return true;
}

//! Create a DynamoDB table to be used in sample code scenarios.
/*!
  \sa createMoviesDynamoDBTable()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::createMoviesDynamoDBTable(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    bool movieTableAlreadyExisted = false;

    {
        Aws::DynamoDB::Model::CreateTableRequest request;

        Aws::DynamoDB::Model::AttributeDefinition yearAttributeDefinition;
        yearAttributeDefinition.SetAttributeName(YEAR_KEY);
        yearAttributeDefinition.SetAttributeType(
                Aws::DynamoDB::Model::ScalarAttributeType::N);
        request.AddAttributeDefinitions(yearAttributeDefinition);

        Aws::DynamoDB::Model::AttributeDefinition titleAttributeDefinition;
        yearAttributeDefinition.SetAttributeName(TITLE_KEY);
        yearAttributeDefinition.SetAttributeType(
```

```
                Aws::DynamoDB::Model::ScalarAttributeType::S);
        request.AddAttributeDefinitions(yearAttributeDefinition);

        Aws::DynamoDB::Model::KeySchemaElement yearKeySchema;
        yearKeySchema.WithAttributeName(YEAR_KEY).WithKeyType(
                Aws::DynamoDB::Model::KeyType::HASH);
        request.AddKeySchema(yearKeySchema);

        Aws::DynamoDB::Model::KeySchemaElement titleKeySchema;
        yearKeySchema.WithAttributeName(TITLE_KEY).WithKeyType(
                Aws::DynamoDB::Model::KeyType::RANGE);
        request.AddKeySchema(yearKeySchema);

        Aws::DynamoDB::Model::ProvisionedThroughput throughput;
        throughput.WithReadCapacityUnits(
                PROVISIONED_THROUGHPUT_UNITS).WithWriteCapacityUnits(
                PROVISIONED_THROUGHPUT_UNITS);
        request.SetProvisionedThroughput(throughput);
        request.SetTableName(MOVIE_TABLE_NAME);

        std::cout << "Creating table '" << MOVIE_TABLE_NAME << "'..." << std::endl;
        const Aws::DynamoDB::Model::CreateTableOutcome &result =
dynamoClient.CreateTable(
                request);
        if (!result.IsSuccess()) {
            if (result.GetError().GetErrorType() ==
                Aws::DynamoDB::DynamoDBErrors::RESOURCE_IN_USE) {
                std::cout << "Table already exists." << std::endl;
                movieTableAlreadyExisted = true;
            }
            else {
                std::cerr << "Failed to create table: "
                          << result.GetError().GetMessage();
                return false;
            }
        }
    }

    // Wait for table to become active.
    if (!movieTableAlreadyExisted) {
        std::cout << "Waiting for table '" << MOVIE_TABLE_NAME
                  << "' to become active...." << std::endl;
        if (!AwsDoc::DynamoDB::waitTableActive(MOVIE_TABLE_NAME,
clientConfiguration)) {
```

```
            return false;
        }
        std::cout << "Table '" << MOVIE_TABLE_NAME << "' created and active."
                  << std::endl;
    }

    return true;
}

//! Delete the DynamoDB table used for sample code scenarios.
/*!
  \sa deleteMoviesDynamoDBTable()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::deleteMoviesDynamoDBTable(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::DeleteTableRequest request;
    request.SetTableName(MOVIE_TABLE_NAME);

    const Aws::DynamoDB::Model::DeleteTableOutcome &result =
 dynamoClient.DeleteTable(
            request);
    if (result.IsSuccess()) {
        std::cout << "Your table \""
                  << result.GetResult().GetTableDescription().GetTableName()
                  << " was deleted.\n";
    }
    else {
        std::cerr << "Failed to delete table: " << result.GetError().GetMessage()
                  << std::endl;
    }

    return result.IsSuccess();
}

//! Query a newly created DynamoDB table until it is active.
/*!
  \sa waitTableActive()
  \param waitTableActive: The DynamoDB table's name.
  \param dynamoClient: A DynamoDB client.
  \return bool: Function succeeded.
```

```
*/
bool AwsDoc::DynamoDB::waitTableActive(const Aws::String &tableName,
                                       const Aws::DynamoDB::DynamoDBClient
 &dynamoClient) {

    // Repeatedly call DescribeTable until table is ACTIVE.
    const int MAX_QUERIES = 20;
    Aws::DynamoDB::Model::DescribeTableRequest request;
    request.SetTableName(tableName);

    int count = 0;
    while (count < MAX_QUERIES) {
        const Aws::DynamoDB::Model::DescribeTableOutcome &result =
 dynamoClient.DescribeTable(
                request);
        if (result.IsSuccess()) {
            Aws::DynamoDB::Model::TableStatus status =
 result.GetResult().GetTable().GetTableStatus();

            if (Aws::DynamoDB::Model::TableStatus::ACTIVE != status) {
                std::this_thread::sleep_for(std::chrono::seconds(1));
            }
            else {
                return true;
            }
        }
        else {
            std::cerr << "Error DynamoDB::waitTableActive "
                      << result.GetError().GetMessage() << std::endl;
            return false;
        }
        count++;
    }
    return false;
}
```

- For API details, see BatchExecuteStatement in *AWS SDK for C++ API Reference*.

Query a table using PartiQL

The following code example shows how to:

- Get an item by running a SELECT statement.
- Add an item by running an INSERT statement.
- Update an item by running an UPDATE statement.
- Delete an item by running a DELETE statement.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        //  1. Create a table. (CreateTable)
        if (AwsDoc::DynamoDB::createMoviesDynamoDBTable(clientConfig)) {

            AwsDoc::DynamoDB::partiqlExecuteScenario(clientConfig);

            // 7. Delete the table. (DeleteTable)
            AwsDoc::DynamoDB::deleteMoviesDynamoDBTable(clientConfig);
        }

//! Scenario to modify and query a DynamoDB table using single PartiQL statements.
/*!
  \sa partiqlExecuteScenario()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool
AwsDoc::DynamoDB::partiqlExecuteScenario(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    // 2. Add a new movie using an "Insert" statement. (ExecuteStatement)
    Aws::String title;
    float rating;
    int year;
    Aws::String plot;
    {
        title = askQuestion(
```

```
                "Enter the title of a movie you want to add to the table: ");
        year = askQuestionForInt("What year was it released? ");
        rating = askQuestionForFloatRange("On a scale of 1 - 10, how do you rate it?
",
                                          1, 10);
        plot = askQuestion("Summarize the plot for me: ");

        Aws::DynamoDB::Model::ExecuteStatementRequest request;
        std::stringstream sqlStream;
        sqlStream << "INSERT INTO \"" << MOVIE_TABLE_NAME << "\" VALUE {'"
                  << TITLE_KEY << "': ?, '" << YEAR_KEY << "': ?, '"
                  << INFO_KEY << "': ?}";

        request.SetStatement(sqlStream.str());

        // Create the parameter attributes.
        Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));

        Aws::DynamoDB::Model::AttributeValue infoMapAttribute;

        std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> ratingAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
                ALLOCATION_TAG.c_str());
        ratingAttribute->SetN(rating);
        infoMapAttribute.AddMEntry(RATING_KEY, ratingAttribute);

        std::shared_ptr<Aws::DynamoDB::Model::AttributeValue> plotAttribute =
Aws::MakeShared<Aws::DynamoDB::Model::AttributeValue>(
                ALLOCATION_TAG.c_str());
        plotAttribute->SetS(plot);
        infoMapAttribute.AddMEntry(PLOT_KEY, plotAttribute);
        attributes.push_back(infoMapAttribute);
        request.SetParameters(attributes);

        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
dynamoClient.ExecuteStatement(
                request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to add a movie: " <<
outcome.GetError().GetMessage()
                      << std::endl;
```

```
            return false;
        }
    }

    std::cout << "\nAdded '" << title << "' to '" << MOVIE_TABLE_NAME << "'."
              << std::endl;

    //  3. Get the data for the movie using a "Select" statement. (ExecuteStatement)
    {
        Aws::DynamoDB::Model::ExecuteStatementRequest request;
        std::stringstream sqlStream;
        sqlStream << "SELECT * FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        request.SetStatement(sqlStream.str());

        Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));
        request.SetParameters(attributes);

        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
dynamoClient.ExecuteStatement(
                request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to retrieve movie information: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
        else {
            // Print the retrieved movie information.
            const Aws::DynamoDB::Model::ExecuteStatementResult &result =
outcome.GetResult();

            const Aws::Vector<Aws::Map<Aws::String,
Aws::DynamoDB::Model::AttributeValue>> &items = result.GetItems();

            if (items.size() == 1) {
                printMovieInfo(items[0]);
            }
            else {
                std::cerr << "Error: " << items.size() << " movies were retrieved. "
                          << " There should be only one movie." << std::endl;
```

```
            }
        }
    }

    //  4. Update the data for the movie using an "Update" statement.
(ExecuteStatement)
    {
        rating = askQuestionForFloatRange(
                Aws::String("\nLet's update your movie.\nYou rated it  ") +
                std::to_string(rating)
                + ", what new rating would you give it? ", 1, 10);

        Aws::DynamoDB::Model::ExecuteStatementRequest request;
        std::stringstream sqlStream;
        sqlStream << "UPDATE \"" << MOVIE_TABLE_NAME << "\" SET "
                  << INFO_KEY << "." << RATING_KEY << "=? WHERE "
                  << TITLE_KEY << "=? AND " << YEAR_KEY << "=?";

        request.SetStatement(sqlStream.str());

        Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(rating));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));

        request.SetParameters(attributes);

        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
dynamoClient.ExecuteStatement(
                request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to update a movie: "
                      << outcome.GetError().GetMessage();
            return false;
        }
    }

    std::cout << "\nUpdated '" << title << "' with new attributes:" << std::endl;

    //  5. Get the updated data for the movie using a "Select" statement.
(ExecuteStatement)
    {
        Aws::DynamoDB::Model::ExecuteStatementRequest request;
```

```
        std::stringstream sqlStream;
        sqlStream << "SELECT * FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";

        request.SetStatement(sqlStream.str());

        Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));
        request.SetParameters(attributes);

        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
dynamoClient.ExecuteStatement(
                request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to retrieve the movie information: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
        else {
            const Aws::DynamoDB::Model::ExecuteStatementResult &result =
outcome.GetResult();

            const Aws::Vector<Aws::Map<Aws::String,
Aws::DynamoDB::Model::AttributeValue>> &items = result.GetItems();

            if (items.size() == 1) {
                printMovieInfo(items[0]);
            }
            else {
                std::cerr << "Error: " << items.size() << " movies were retrieved. "
                          << " There should be only one movie." << std::endl;
            }
        }
    }

    std::cout << "Deleting the movie" << std::endl;

    // 6. Delete the movie using a "Delete" statement. (ExecuteStatement)
    {
        Aws::DynamoDB::Model::ExecuteStatementRequest request;
        std::stringstream sqlStream;
        sqlStream << "DELETE FROM  \"" << MOVIE_TABLE_NAME << "\" WHERE "
                  << TITLE_KEY << "=? and " << YEAR_KEY << "=?";
```

```
        request.SetStatement(sqlStream.str());

        Aws::Vector<Aws::DynamoDB::Model::AttributeValue> attributes;
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetS(title));
        attributes.push_back(Aws::DynamoDB::Model::AttributeValue().SetN(year));
        request.SetParameters(attributes);

        Aws::DynamoDB::Model::ExecuteStatementOutcome outcome =
 dynamoClient.ExecuteStatement(
                request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to delete the movie: "
                      << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    }

    std::cout << "Movie successfully deleted." << std::endl;
    return true;
}

//! Create a DynamoDB table to be used in sample code scenarios.
/*!
  \sa createMoviesDynamoDBTable()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::createMoviesDynamoDBTable(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    bool movieTableAlreadyExisted = false;

    {
        Aws::DynamoDB::Model::CreateTableRequest request;

        Aws::DynamoDB::Model::AttributeDefinition yearAttributeDefinition;
        yearAttributeDefinition.SetAttributeName(YEAR_KEY);
        yearAttributeDefinition.SetAttributeType(
                Aws::DynamoDB::Model::ScalarAttributeType::N);
        request.AddAttributeDefinitions(yearAttributeDefinition);

        Aws::DynamoDB::Model::AttributeDefinition titleAttributeDefinition;
```

```
        yearAttributeDefinition.SetAttributeName(TITLE_KEY);
        yearAttributeDefinition.SetAttributeType(
                Aws::DynamoDB::Model::ScalarAttributeType::S);
        request.AddAttributeDefinitions(yearAttributeDefinition);

        Aws::DynamoDB::Model::KeySchemaElement yearKeySchema;
        yearKeySchema.WithAttributeName(YEAR_KEY).WithKeyType(
                Aws::DynamoDB::Model::KeyType::HASH);
        request.AddKeySchema(yearKeySchema);

        Aws::DynamoDB::Model::KeySchemaElement titleKeySchema;
        yearKeySchema.WithAttributeName(TITLE_KEY).WithKeyType(
                Aws::DynamoDB::Model::KeyType::RANGE);
        request.AddKeySchema(yearKeySchema);

        Aws::DynamoDB::Model::ProvisionedThroughput throughput;
        throughput.WithReadCapacityUnits(
                PROVISIONED_THROUGHPUT_UNITS).WithWriteCapacityUnits(
                PROVISIONED_THROUGHPUT_UNITS);
        request.SetProvisionedThroughput(throughput);
        request.SetTableName(MOVIE_TABLE_NAME);

        std::cout << "Creating table '" << MOVIE_TABLE_NAME << "'..." << std::endl;
        const Aws::DynamoDB::Model::CreateTableOutcome &result =
dynamoClient.CreateTable(
                request);
        if (!result.IsSuccess()) {
            if (result.GetError().GetErrorType() ==
                Aws::DynamoDB::DynamoDBErrors::RESOURCE_IN_USE) {
                std::cout << "Table already exists." << std::endl;
                movieTableAlreadyExisted = true;
            }
            else {
                std::cerr << "Failed to create table: "
                          << result.GetError().GetMessage();
                return false;
            }
        }
    }

    // Wait for table to become active.
    if (!movieTableAlreadyExisted) {
        std::cout << "Waiting for table '" << MOVIE_TABLE_NAME
                  << "' to become active...." << std::endl;
```

```
        if (!AwsDoc::DynamoDB::waitTableActive(MOVIE_TABLE_NAME,
 clientConfiguration)) {
            return false;
        }
        std::cout << "Table '" << MOVIE_TABLE_NAME << "' created and active."
                  << std::endl;
    }

    return true;
}

//! Delete the DynamoDB table used for sample code scenarios.
/*!
  \sa deleteMoviesDynamoDBTable()
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::deleteMoviesDynamoDBTable(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfiguration);

    Aws::DynamoDB::Model::DeleteTableRequest request;
    request.SetTableName(MOVIE_TABLE_NAME);

    const Aws::DynamoDB::Model::DeleteTableOutcome &result =
 dynamoClient.DeleteTable(
            request);
    if (result.IsSuccess()) {
        std::cout << "Your table \""
                  << result.GetResult().GetTableDescription().GetTableName()
                  << " was deleted.\n";
    }
    else {
        std::cerr << "Failed to delete table: " << result.GetError().GetMessage()
                  << std::endl;
    }

    return result.IsSuccess();
}

//! Query a newly created DynamoDB table until it is active.
/*!
  \sa waitTableActive()
  \param waitTableActive: The DynamoDB table's name.
```

```
  \param dynamoClient: A DynamoDB client.
  \return bool: Function succeeded.
*/
bool AwsDoc::DynamoDB::waitTableActive(const Aws::String &tableName,
                                       const Aws::DynamoDB::DynamoDBClient
 &dynamoClient) {

    // Repeatedly call DescribeTable until table is ACTIVE.
    const int MAX_QUERIES = 20;
    Aws::DynamoDB::Model::DescribeTableRequest request;
    request.SetTableName(tableName);

    int count = 0;
    while (count < MAX_QUERIES) {
        const Aws::DynamoDB::Model::DescribeTableOutcome &result =
 dynamoClient.DescribeTable(
                request);
        if (result.IsSuccess()) {
            Aws::DynamoDB::Model::TableStatus status =
 result.GetResult().GetTable().GetTableStatus();

            if (Aws::DynamoDB::Model::TableStatus::ACTIVE != status) {
                std::this_thread::sleep_for(std::chrono::seconds(1));
            }
            else {
                return true;
            }
        }
        else {
            std::cerr << "Error DynamoDB::waitTableActive "
                      << result.GetError().GetMessage() << std::endl;
            return false;
        }
        count++;
    }
    return false;
}
```

- For API details, see ExecuteStatement in *AWS SDK for C++ API Reference*.

Amazon EC2 examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with Amazon EC2.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Get started
- Actions

Get started

Hello Amazon EC2

The following code example shows how to get started using Amazon EC2.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Code for the CMakeLists.txt CMake file.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS ec2)

# Set this project's name.
project("hello_ec2")
```

```
# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD AND AWSSDK_INSTALL_AS_SHARED_LIBS)
     # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

     # set(BIN_SUB_DIR "/Debug") # If you are building from the command line, you
 may need to uncomment this
                                     # and set the proper subdirectory to the
 executables' location.

     AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_ec2.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Code for the hello_ec2.cpp source file.

```
#include <aws/core/Aws.h>
#include <aws/ec2/EC2Client.h>
#include <aws/ec2/model/DescribeInstancesRequest.h>
```

```
#include <iomanip>
#include <iostream>

/*
 *  A "Hello EC2" starter application which initializes an Amazon Elastic Compute
 Cloud (Amazon EC2) client and describes
 *  the Amazon EC2 instances.
 *
 *  main function
 *
 *  Usage: 'hello_ec2'
 *
 */

int main(int argc, char **argv) {
    (void)argc;
    (void)argv;

    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::EC2::EC2Client ec2Client(clientConfig);
        Aws::EC2::Model::DescribeInstancesRequest request;
        bool header = false;
        bool done = false;
        while (!done) {
            Aws::EC2::Model::DescribeInstancesOutcome outcome =
 ec2Client.DescribeInstances(request);
            if (outcome.IsSuccess()) {
                if (!header) {
                    std::cout << std::left <<
                              std::setw(48) << "Name" <<
                              std::setw(20) << "ID" <<
                              std::setw(25) << "Ami" <<
                              std::setw(15) << "Type" <<
                              std::setw(15) << "State" <<
                              std::setw(15) << "Monitoring" << std::endl;
```

```
                    header = true;
                }

                const std::vector<Aws::EC2::Model::Reservation> &reservations =
                        outcome.GetResult().GetReservations();

                for (const auto &reservation: reservations) {
                    const std::vector<Aws::EC2::Model::Instance> &instances =
                            reservation.GetInstances();
                    for (const auto &instance: instances) {
                        Aws::String instanceStateString =

Aws::EC2::Model::InstanceStateNameMapper::GetNameForInstanceStateName(
                                        instance.GetState().GetName());

                        Aws::String typeString =

Aws::EC2::Model::InstanceTypeMapper::GetNameForInstanceType(
                                        instance.GetInstanceType());

                        Aws::String monitorString =

Aws::EC2::Model::MonitoringStateMapper::GetNameForMonitoringState(
                                        instance.GetMonitoring().GetState());
                        Aws::String name = "Unknown";

                        const std::vector<Aws::EC2::Model::Tag> &tags =
instance.GetTags();
                        auto nameIter = std::find_if(tags.cbegin(), tags.cend(),
                                                     [](const Aws::EC2::Model::Tag
&tag) {
                                                         return tag.GetKey() ==
"Name";
                                                     });
                        if (nameIter != tags.cend()) {
                            name = nameIter->GetValue();
                        }
                        std::cout <<
                                  std::setw(48) << name <<
                                  std::setw(20) << instance.GetInstanceId() <<
                                  std::setw(25) << instance.GetImageId() <<
                                  std::setw(15) << typeString <<
                                  std::setw(15) << instanceStateString <<
                                  std::setw(15) << monitorString << std::endl;
```

```
                    }
                }

                if (!outcome.GetResult().GetNextToken().empty()) {
                    request.SetNextToken(outcome.GetResult().GetNextToken());
                } else {
                    done = true;
                }
            } else {
                std::cerr << "Failed to describe EC2 instances:" <<
                          outcome.GetError().GetMessage() << std::endl;
                result = 1;
                break;
            }
        }
    }


    Aws::ShutdownAPI(options); // Should only be called once.
    return result;
}
```

- For API details, see DescribeSecurityGroups in *AWS SDK for C++ API Reference*.

Actions

`AllocateAddress`

The following code example shows how to use `AllocateAddress`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Allocate an Elastic IP address and associate it with an Amazon Elastic Compute
 Cloud
```

```
//! (Amazon EC2) instance.
/*!
  \param instanceID: An EC2 instance ID.
  \param[out] publicIPAddress: String to return the public IP address.
  \param[out] allocationID: String to return the allocation ID.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::EC2::allocateAndAssociateAddress(const Aws::String &instanceId,
 Aws::String &publicIPAddress,
                                               Aws::String &allocationID,
                                               const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::AllocateAddressRequest request;
    request.SetDomain(Aws::EC2::Model::DomainType::vpc);

    const Aws::EC2::Model::AllocateAddressOutcome outcome =
            ec2Client.AllocateAddress(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Failed to allocate Elastic IP address:" <<
                  outcome.GetError().GetMessage() << std::endl;
        return false;
    }
    const Aws::EC2::Model::AllocateAddressResponse &response = outcome.GetResult();
    allocationID = response.GetAllocationId();
    publicIPAddress = response.GetPublicIp();


    return true;
}
```

- For API details, see AllocateAddress in *AWS SDK for C++ API Reference*.

`AssociateAddress`

The following code example shows how to use `AssociateAddress`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

//! Associate an Elastic IP address with an EC2 instance.
/*!
  \param instanceId: An EC2 instance ID.
  \param allocationId: An Elastic IP allocation ID.
  \param[out] associationID: String to receive the association ID.
  \param clientConfiguration: AWS client configuration.
  \return bool: True if the address was associated with the instance; otherwise,
 false.
 */
bool AwsDoc::EC2::associateAddress(const Aws::String &instanceId, const Aws::String
 &allocationId,
                                   Aws::String &associationID,
                                   const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::AssociateAddressRequest request;
    request.SetInstanceId(instanceId);
    request.SetAllocationId(allocationId);

    Aws::EC2::Model::AssociateAddressOutcome outcome =
 ec2Client.AssociateAddress(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Failed to associate address " << allocationId <<
                  " with instance " << instanceId << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    } else {
        std::cout << "Successfully associated address " << allocationId <<
                  " with instance " << instanceId << std::endl;
        associationID = outcome.GetResult().GetAssociationId();
    }
```

```
    return outcome.IsSuccess();
}
```

- For API details, see AssociateAddress in *AWS SDK for C++ API Reference*.

`AuthorizeSecurityGroupIngress`

The following code example shows how to use `AuthorizeSecurityGroupIngress`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Authorize ingress to an Amazon Elastic Compute Cloud (Amazon EC2) group.
/*!
  \param groupID: The EC2 group ID.
  \param clientConfiguration: The ClientConfiguration object.
  \return bool: True if the operation was successful, false otherwise.
 */
bool
AwsDoc::EC2::authorizeSecurityGroupIngress(const Aws::String &groupID,
                                           const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::AuthorizeSecurityGroupIngressRequest
 authorizeSecurityGroupIngressRequest;
    authorizeSecurityGroupIngressRequest.SetGroupId(groupID);
    buildSampleIngressRule(authorizeSecurityGroupIngressRequest);

    Aws::EC2::Model::AuthorizeSecurityGroupIngressOutcome
 authorizeSecurityGroupIngressOutcome =

 ec2Client.AuthorizeSecurityGroupIngress(authorizeSecurityGroupIngressRequest);

    if (authorizeSecurityGroupIngressOutcome.IsSuccess()) {
        std::cout << "Successfully authorized security group ingress." << std::endl;
```

```
    } else {
        std::cerr << "Error authorizing security group ingress: "
                  << authorizeSecurityGroupIngressOutcome.GetError().GetMessage() <<
 std::endl;
    }

    return authorizeSecurityGroupIngressOutcome.IsSuccess();
}
```

Utility function to build an ingress rule.

```
//! Build a sample ingress rule.
/*!
  \param authorize_request: An 'AuthorizeSecurityGroupIngressRequest' instance.
  \return void:
 */
void buildSampleIngressRule(
        Aws::EC2::Model::AuthorizeSecurityGroupIngressRequest &authorize_request) {
    Aws::String ingressIPRange = "203.0.113.0/24";  // Configure this for your
 allowed IP range.
    Aws::EC2::Model::IpRange ip_range;
    ip_range.SetCidrIp(ingressIPRange);

    Aws::EC2::Model::IpPermission permission1;
    permission1.SetIpProtocol("tcp");
    permission1.SetToPort(80);
    permission1.SetFromPort(80);
    permission1.AddIpRanges(ip_range);

    authorize_request.AddIpPermissions(permission1);

    Aws::EC2::Model::IpPermission permission2;
    permission2.SetIpProtocol("tcp");
    permission2.SetToPort(22);
    permission2.SetFromPort(22);
    permission2.AddIpRanges(ip_range);

    authorize_request.AddIpPermissions(permission2);
}
```

- For API details, see AuthorizeSecurityGroupIngress in *AWS SDK for C++ API Reference*.

`CreateKeyPair`

The following code example shows how to use `CreateKeyPair`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Create an Amazon Elastic Compute Cloud (Amazon EC2) instance key pair.
/*!
  \param keyPairName: A name for a key pair.
  \param keyFilePath: File path where the credentials are stored. Ignored if it is
 an empty string;
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::EC2::createKeyPair(const Aws::String &keyPairName, const Aws::String
 &keyFilePath,
                                const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::CreateKeyPairRequest request;
    request.SetKeyName(keyPairName);

    Aws::EC2::Model::CreateKeyPairOutcome outcome =
 ec2Client.CreateKeyPair(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Failed to create key pair - "  << keyPairName << ". " <<
                  outcome.GetError().GetMessage() << std::endl;
    } else {
        std::cout << "Successfully created key pair named " <<
                  keyPairName << std::endl;
        if (!keyFilePath.empty()) {
            std::ofstream keyFile(keyFilePath.c_str());
            keyFile << outcome.GetResult().GetKeyMaterial();
            keyFile.close();
            std::cout << "Keys written to the file " <<
                      keyFilePath << std::endl;
        }
```

```
    }

    return outcome.IsSuccess();

}
```

- For API details, see CreateKeyPair in *AWS SDK for C++ API Reference*.

`CreateSecurityGroup`

The following code example shows how to use `CreateSecurityGroup`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Create a security group.
/*!
  \param groupName: A security group name.
  \param description: A description.
  \param vpcID: A virtual private cloud (VPC) ID.
  \param[out] groupIDResult: A string to receive the group ID.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::EC2::createSecurityGroup(const Aws::String &groupName,
                                      const Aws::String &description,
                                      const Aws::String &vpcID,
                                      Aws::String &groupIDResult,
                                      const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::CreateSecurityGroupRequest request;

    request.SetGroupName(groupName);
```

```
    request.SetDescription(description);
    request.SetVpcId(vpcID);

    const Aws::EC2::Model::CreateSecurityGroupOutcome outcome =
            ec2Client.CreateSecurityGroup(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Failed to create security group:" <<
                  outcome.GetError().GetMessage() << std::endl;
        return false;
    }

    std::cout << "Successfully created security group named " << groupName <<
              std::endl;


    groupIDResult = outcome.GetResult().GetGroupId();

    return true;
}
```

- For API details, see CreateSecurityGroup in *AWS SDK for C++ API Reference*.

`CreateTags`

The following code example shows how to use `CreateTags`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Add or overwrite only the specified tags for the specified Amazon Elastic
 Compute Cloud (Amazon EC2) resource or resources.
/*!
  \param resources: The resources for the tags.
  \param tags: Vector of tags.
  \param clientConfiguration: AWS client configuration.
```

```
  \return bool: Function succeeded.
 */
bool AwsDoc::EC2::createTags(const Aws::Vector<Aws::String> &resources,
                             const Aws::Vector<Aws::EC2::Model::Tag> &tags,
                             const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::CreateTagsRequest createTagsRequest;
    createTagsRequest.SetResources(resources);
    createTagsRequest.SetTags(tags);

    Aws::EC2::Model::CreateTagsOutcome outcome =
 ec2Client.CreateTags(createTagsRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully created tags for resources" << std::endl;
    } else {
        std::cerr << "Failed to create tags for resources, " <<
 outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see CreateTags in *AWS SDK for C++ API Reference*.

`DeleteKeyPair`

The following code example shows how to use `DeleteKeyPair`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Delete an Amazon Elastic Compute Cloud (Amazon EC2) instance key pair.
/*!
```

```
  \param keyPairName: A name for a key pair.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */

bool AwsDoc::EC2::deleteKeyPair(const Aws::String &keyPairName,
                                const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::DeleteKeyPairRequest request;

    request.SetKeyName(keyPairName);
    const Aws::EC2::Model::DeleteKeyPairOutcome outcome = ec2Client.DeleteKeyPair(
            request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Failed to delete key pair " << keyPairName <<
                  ":" << outcome.GetError().GetMessage() << std::endl;
    } else {
        std::cout << "Successfully deleted key pair named " << keyPairName <<
                  std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DeleteKeyPair in *AWS SDK for C++ API Reference*.

`DeleteSecurityGroup`

The following code example shows how to use `DeleteSecurityGroup`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Delete a security group.
```

```
/*!
  \param securityGroupID: A security group ID.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::EC2::deleteSecurityGroup(const Aws::String &securityGroupID,
                                      const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::DeleteSecurityGroupRequest request;

    request.SetGroupId(securityGroupID);
    Aws::EC2::Model::DeleteSecurityGroupOutcome outcome =
 ec2Client.DeleteSecurityGroup(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Failed to delete security group " << securityGroupID <<
                  ":" << outcome.GetError().GetMessage() << std::endl;
    } else {
        std::cout << "Successfully deleted security group " << securityGroupID <<
                  std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DeleteSecurityGroup in *AWS SDK for C++ API Reference*.

`DescribeAddresses`

The following code example shows how to use `DescribeAddresses`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Describe all Elastic IP addresses.
```

```
/*!
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::EC2::describeAddresses(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::DescribeAddressesRequest request;
    Aws::EC2::Model::DescribeAddressesOutcome outcome =
 ec2Client.DescribeAddresses(request);
    if (outcome.IsSuccess()) {
        std::cout << std::left << std::setw(20) << "InstanceId" <<
                  std::setw(15) << "Public IP" << std::setw(10) << "Domain" <<
                  std::setw(30) << "Allocation ID" << std::setw(25) <<
                  "NIC ID" << std::endl;

        const Aws::Vector<Aws::EC2::Model::Address> &addresses =
 outcome.GetResult().GetAddresses();
        for (const auto &address: addresses) {
            Aws::String domainString =
                    Aws::EC2::Model::DomainTypeMapper::GetNameForDomainType(
                            address.GetDomain());

            std::cout << std::left << std::setw(20) <<
                      address.GetInstanceId() << std::setw(15) <<
                      address.GetPublicIp() << std::setw(10) << domainString <<
                      std::setw(30) << address.GetAllocationId() << std::setw(25)
                      << address.GetNetworkInterfaceId() << std::endl;
        }
    } else {
        std::cerr << "Failed to describe Elastic IP addresses:" <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DescribeAddresses in *AWS SDK for C++ API Reference*.

`DescribeAvailabilityZones`

The following code example shows how to use `DescribeAvailabilityZones`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! DescribeAvailabilityZones
/*!
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
*/
int AwsDoc::EC2::describeAvailabilityZones(const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::DescribeAvailabilityZonesRequest request;
    Aws::EC2::Model::DescribeAvailabilityZonesOutcome outcome =
 ec2Client.DescribeAvailabilityZones(request);

    if (outcome.IsSuccess()) {
        std::cout << std::left <<
                  std::setw(32) << "ZoneName" <<
                  std::setw(20) << "State" <<
                  std::setw(32) << "Region" << std::endl;

        const auto &zones =
                outcome.GetResult().GetAvailabilityZones();

        for (const auto &zone: zones) {
            Aws::String stateString =

 Aws::EC2::Model::AvailabilityZoneStateMapper::GetNameForAvailabilityZoneState(
                            zone.GetState());
            std::cout << std::left <<
                      std::setw(32) << zone.GetZoneName() <<
                      std::setw(20) << stateString <<
                      std::setw(32) << zone.GetRegionName() << std::endl;
        }
    } else {
        std::cerr << "Failed to describe availability zones:" <<
```

```
                  outcome.GetError().GetMessage() << std::endl;

    }

    return outcome.IsSuccess();
}
```

- For API details, see DescribeAvailabilityZones in *AWS SDK for C++ API Reference*.

`DescribeInstances`

The following code example shows how to use `DescribeInstances`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Describe all Amazon Elastic Compute Cloud (Amazon EC2) instances associated with
 an account.
/*!
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::EC2::describeInstances(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::DescribeInstancesRequest request;
    bool header = false;
    bool done = false;
    while (!done) {
        Aws::EC2::Model::DescribeInstancesOutcome outcome =
 ec2Client.DescribeInstances(request);
        if (outcome.IsSuccess()) {
            if (!header) {
                std::cout << std::left <<
                          std::setw(48) << "Name" <<
                          std::setw(20) << "ID" <<
```

```
                        std::setw(25) << "Ami" <<
                        std::setw(15) << "Type" <<
                        std::setw(15) << "State" <<
                        std::setw(15) << "Monitoring" << std::endl;
                header = true;
            }

            const std::vector<Aws::EC2::Model::Reservation> &reservations =
                    outcome.GetResult().GetReservations();

            for (const auto &reservation: reservations) {
                const std::vector<Aws::EC2::Model::Instance> &instances =
                        reservation.GetInstances();
                for (const auto &instance: instances) {
                    Aws::String instanceStateString =

Aws::EC2::Model::InstanceStateNameMapper::GetNameForInstanceStateName(
                                    instance.GetState().GetName());

                    Aws::String typeString =

Aws::EC2::Model::InstanceTypeMapper::GetNameForInstanceType(
                                    instance.GetInstanceType());

                    Aws::String monitorString =

Aws::EC2::Model::MonitoringStateMapper::GetNameForMonitoringState(
                                    instance.GetMonitoring().GetState());
                    Aws::String name = "Unknown";

                    const std::vector<Aws::EC2::Model::Tag> &tags =
instance.GetTags();
                    auto nameIter = std::find_if(tags.cbegin(), tags.cend(),
                                                 [](const Aws::EC2::Model::Tag &tag)
{
                                                     return tag.GetKey() == "Name";
                                                 });
                    if (nameIter != tags.cend()) {
                        name = nameIter->GetValue();
                    }
                    std::cout <<
                              std::setw(48) << name <<
                              std::setw(20) << instance.GetInstanceId() <<
                              std::setw(25) << instance.GetImageId() <<
```

```
                                std::setw(15) << typeString <<
                                std::setw(15) << instanceStateString <<
                                std::setw(15) << monitorString << std::endl;
                    }
                }

                if (!outcome.GetResult().GetNextToken().empty()) {
                    request.SetNextToken(outcome.GetResult().GetNextToken());
                } else {
                    done = true;
                }
            } else {
                std::cerr << "Failed to describe EC2 instances:" <<
                          outcome.GetError().GetMessage() << std::endl;
                return false;
            }
        }

        return true;
}
```

- For API details, see DescribeInstances in *AWS SDK for C++ API Reference*.

`DescribeKeyPairs`

The following code example shows how to use `DescribeKeyPairs`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Describe all Amazon Elastic Compute Cloud (Amazon EC2) instance key pairs.
/*!
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::EC2::describeKeyPairs(
```

```
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::DescribeKeyPairsRequest request;

    Aws::EC2::Model::DescribeKeyPairsOutcome outcome =
 ec2Client.DescribeKeyPairs(request);
    if (outcome.IsSuccess()) {
        std::cout << std::left <<
                  std::setw(32) << "Name" <<
                  std::setw(64) << "Fingerprint" << std::endl;

        const std::vector<Aws::EC2::Model::KeyPairInfo> &key_pairs =
                outcome.GetResult().GetKeyPairs();
        for (const auto &key_pair: key_pairs) {
            std::cout << std::left <<
                      std::setw(32) << key_pair.GetKeyName() <<
                      std::setw(64) << key_pair.GetKeyFingerprint() << std::endl;
        }
    } else {
        std::cerr << "Failed to describe key pairs:" <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DescribeKeyPairs in *AWS SDK for C++ API Reference*.

`DescribeRegions`

The following code example shows how to use `DescribeRegions`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Describe all Amazon Elastic Compute Cloud (Amazon EC2) Regions.
```

```
/*!
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::EC2::describeRegions(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::DescribeRegionsRequest request;
    Aws::EC2::Model::DescribeRegionsOutcome outcome =
 ec2Client.DescribeRegions(request);
    if (outcome.IsSuccess()) {
        std::cout << std::left <<
                  std::setw(32) << "RegionName" <<
                  std::setw(64) << "Endpoint" << std::endl;

        const auto &regions = outcome.GetResult().GetRegions();
        for (const auto &region: regions) {
            std::cout << std::left <<
                      std::setw(32) << region.GetRegionName() <<
                      std::setw(64) << region.GetEndpoint() << std::endl;
        }
    } else {
        std::cerr << "Failed to describe regions:" <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    std::cout << std::endl;

    return outcome.IsSuccess();

}
```

- For API details, see DescribeRegions in *AWS SDK for C++ API Reference*.

`DescribeSecurityGroups`

The following code example shows how to use `DescribeSecurityGroups`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Describe all Amazon Elastic Compute Cloud (Amazon EC2) security groups, or a
 specific group.
/*!
  \param groupID: A group ID, ignored if empty.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::EC2::describeSecurityGroups(const Aws::String &groupID,
                                         const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::DescribeSecurityGroupsRequest request;

    if (!groupID.empty()) {
        request.AddGroupIds(groupID);
    }

    Aws::String nextToken;
    do {
        if (!nextToken.empty()) {
            request.SetNextToken(nextToken);
        }

        Aws::EC2::Model::DescribeSecurityGroupsOutcome outcome =
 ec2Client.DescribeSecurityGroups(request);
        if (outcome.IsSuccess()) {
            std::cout << std::left <<
                      std::setw(32) << "Name" <<
                      std::setw(30) << "GroupId" <<
                      std::setw(30) << "VpcId" <<
                      std::setw(64) << "Description" << std::endl;

            const std::vector<Aws::EC2::Model::SecurityGroup> &securityGroups =
                    outcome.GetResult().GetSecurityGroups();
```

```
            for (const auto &securityGroup: securityGroups) {
                std::cout << std::left <<
                          std::setw(32) << securityGroup.GetGroupName() <<
                          std::setw(30) << securityGroup.GetGroupId() <<
                          std::setw(30) << securityGroup.GetVpcId() <<
                          std::setw(64) << securityGroup.GetDescription() <<
                          std::endl;
            }
        } else {
            std::cerr << "Failed to describe security groups:" <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }

        nextToken = outcome.GetResult().GetNextToken();
    } while (!nextToken.empty());

    return true;
}
```

- For API details, see DescribeSecurityGroups in *AWS SDK for C++ API Reference*.

`MonitorInstances`

The following code example shows how to use `MonitorInstances`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Enable detailed monitoring for an Amazon Elastic Compute Cloud (Amazon EC2)
 instance.
/*!
  \param instanceId: An EC2 instance ID.
  \param clientConfiguration: AWS client configuration.
```

```
  \return bool: Function succeeded.
 */
bool AwsDoc::EC2::enableMonitoring(const Aws::String &instanceId,
                                   const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::MonitorInstancesRequest request;
    request.AddInstanceIds(instanceId);
    request.SetDryRun(true);

    Aws::EC2::Model::MonitorInstancesOutcome dryRunOutcome =
 ec2Client.MonitorInstances(request);
    if (dryRunOutcome.IsSuccess()) {
        std::cerr
                << "Failed dry run to enable monitoring on instance. A dry run
 should trigger an error."
                <<
                std::endl;
        return false;
    } else if (dryRunOutcome.GetError().GetErrorType()
               != Aws::EC2::EC2Errors::DRY_RUN_OPERATION) {
        std::cerr << "Failed dry run to enable monitoring on instance " <<
                  instanceId << ": " << dryRunOutcome.GetError().GetMessage() <<
                  std::endl;
        return false;
    }

    request.SetDryRun(false);
    Aws::EC2::Model::MonitorInstancesOutcome monitorInstancesOutcome =
 ec2Client.MonitorInstances(request);
    if (!monitorInstancesOutcome.IsSuccess()) {
        std::cerr << "Failed to enable monitoring on instance " <<
                  instanceId << ": " <<
                  monitorInstancesOutcome.GetError().GetMessage() << std::endl;
    } else {
        std::cout << "Successfully enabled monitoring on instance " <<
                  instanceId << std::endl;
    }

    return monitorInstancesOutcome.IsSuccess();
}
```

- For API details, see MonitorInstances in *AWS SDK for C++ API Reference*.

`RebootInstances`

The following code example shows how to use `RebootInstances`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Reboot an Amazon Elastic Compute Cloud (Amazon EC2) instance.
/*!
  \param instanceID: An EC2 instance ID.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::EC2::rebootInstance(const Aws::String &instanceId,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::RebootInstancesRequest request;
    request.AddInstanceIds(instanceId);
    request.SetDryRun(true);

    Aws::EC2::Model::RebootInstancesOutcome dry_run_outcome =
 ec2Client.RebootInstances(request);
    if (dry_run_outcome.IsSuccess()) {
        std::cerr
                << "Failed dry run to reboot on instance. A dry run should trigger
 an error."
                <<
                std::endl;
        return false;
    } else if (dry_run_outcome.GetError().GetErrorType()
               != Aws::EC2::EC2Errors::DRY_RUN_OPERATION) {
        std::cout << "Failed dry run to reboot instance " << instanceId << ": "
                  << dry_run_outcome.GetError().GetMessage() << std::endl;
        return false;
    }
```

```
    request.SetDryRun(false);
    Aws::EC2::Model::RebootInstancesOutcome outcome =
 ec2Client.RebootInstances(request);
    if (!outcome.IsSuccess()) {
        std::cout << "Failed to reboot instance " << instanceId << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    } else {
        std::cout << "Successfully rebooted instance " << instanceId <<
                  std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see RebootInstances in *AWS SDK for C++ API Reference*.

`ReleaseAddress`

The following code example shows how to use `ReleaseAddress`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Release an Elastic IP address.
/*!
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::EC2::releaseAddress(const Aws::String &allocationID,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::EC2::EC2Client ec2(clientConfiguration);

    Aws::EC2::Model::ReleaseAddressRequest request;
    request.SetAllocationId(allocationID);
```

```
    Aws::EC2::Model::ReleaseAddressOutcome outcome = ec2.ReleaseAddress(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Failed to release Elastic IP address " <<
                  allocationID << ":" << outcome.GetError().GetMessage() <<
                  std::endl;
    } else {
        std::cout << "Successfully released Elastic IP address " <<
                  allocationID << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see ReleaseAddress in *AWS SDK for C++ API Reference*.

`RunInstances`

The following code example shows how to use `RunInstances`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Launch an Amazon Elastic Compute Cloud (Amazon EC2) instance.
/*!
  \param instanceName: A name for the EC2 instance.
  \param amiId: An Amazon Machine Image (AMI) identifier.
  \param[out] instanceID: String to return the instance ID.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::EC2::runInstance(const Aws::String &instanceName,
                              const Aws::String &amiId,
                              Aws::String &instanceID,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
```

```
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::RunInstancesRequest runRequest;
    runRequest.SetImageId(amiId);
    runRequest.SetInstanceType(Aws::EC2::Model::InstanceType::t1_micro);
    runRequest.SetMinCount(1);
    runRequest.SetMaxCount(1);

    Aws::EC2::Model::RunInstancesOutcome runOutcome = ec2Client.RunInstances(
            runRequest);
    if (!runOutcome.IsSuccess()) {
        std::cerr << "Failed to launch EC2 instance " << instanceName <<
                  " based on ami " << amiId << ":" <<
                  runOutcome.GetError().GetMessage() << std::endl;
        return false;
    }

    const Aws::Vector<Aws::EC2::Model::Instance> &instances =
 runOutcome.GetResult().GetInstances();
    if (instances.empty()) {
        std::cerr << "Failed to launch EC2 instance " << instanceName <<
                  " based on ami " << amiId << ":" <<
                  runOutcome.GetError().GetMessage() << std::endl;
        return false;
    }

    instanceID = instances[0].GetInstanceId();

    return true;
}
```

- For API details, see RunInstances in *AWS SDK for C++ API Reference*.

`StartInstances`

The following code example shows how to use `StartInstances`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Start an Amazon Elastic Compute Cloud (Amazon EC2) instance.
/*!
  \param instanceID: An EC2 instance ID.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::EC2::startInstance(const Aws::String &instanceId,
                                const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::StartInstancesRequest startRequest;
    startRequest.AddInstanceIds(instanceId);
    startRequest.SetDryRun(true);

    Aws::EC2::Model::StartInstancesOutcome dryRunOutcome =
 ec2Client.StartInstances(startRequest);
    if (dryRunOutcome.IsSuccess()) {
        std::cerr
                << "Failed dry run to start instance. A dry run should trigger an
 error."
                << std::endl;
        return false;
    } else if (dryRunOutcome.GetError().GetErrorType() !=
               Aws::EC2::EC2Errors::DRY_RUN_OPERATION) {
        std::cout << "Failed dry run to start instance " << instanceId << ": "
                  << dryRunOutcome.GetError().GetMessage() << std::endl;
        return false;
    }

    startRequest.SetDryRun(false);
    Aws::EC2::Model::StartInstancesOutcome startInstancesOutcome =
 ec2Client.StartInstances(startRequest);
```

```
    if (!startInstancesOutcome.IsSuccess()) {
        std::cout << "Failed to start instance " << instanceId << ": " <<
                  startInstancesOutcome.GetError().GetMessage() << std::endl;
    } else {
        std::cout << "Successfully started instance " << instanceId <<
                  std::endl;
    }

    return startInstancesOutcome.IsSuccess();
}
```

- For API details, see StartInstances in *AWS SDK for C++ API Reference*.

`StopInstances`

The following code example shows how to use `StopInstances`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Stop an EC2 instance.
/*!
  \param instanceID: An EC2 instance ID.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::EC2::stopInstance(const Aws::String &instanceId,
                               const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::StopInstancesRequest request;
    request.AddInstanceIds(instanceId);
    request.SetDryRun(true);

    Aws::EC2::Model::StopInstancesOutcome dryRunOutcome =
 ec2Client.StopInstances(request);
```

```
    if (dryRunOutcome.IsSuccess()) {
        std::cerr
                << "Failed dry run to stop instance. A dry run should trigger an
 error."
                << std::endl;
        return false;
    } else if (dryRunOutcome.GetError().GetErrorType() !=
               Aws::EC2::EC2Errors::DRY_RUN_OPERATION) {
        std::cout << "Failed dry run to stop instance " << instanceId << ": "
                  << dryRunOutcome.GetError().GetMessage() << std::endl;
        return false;
    }

    request.SetDryRun(false);
    Aws::EC2::Model::StopInstancesOutcome outcome =
 ec2Client.StopInstances(request);
    if (!outcome.IsSuccess()) {
        std::cout << "Failed to stop instance " << instanceId << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    } else {
        std::cout << "Successfully stopped instance " << instanceId <<
                  std::endl;
    }

    return outcome.IsSuccess();
}

void PrintUsage() {
    std::cout << "Usage: run_start_stop_instance <instance_id> <start|stop>" <<
              std::endl;
}
```

- For API details, see StopInstances in *AWS SDK for C++ API Reference*.

`TerminateInstances`

The following code example shows how to use `TerminateInstances`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Terminate an Amazon Elastic Compute Cloud (Amazon EC2) instance.
/*!
  \param instanceID: An EC2 instance ID.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::EC2::terminateInstances(const Aws::String &instanceID,
                                     const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::EC2::EC2Client ec2Client(clientConfiguration);

    Aws::EC2::Model::TerminateInstancesRequest request;
    request.SetInstanceIds({instanceID});

    Aws::EC2::Model::TerminateInstancesOutcome outcome =
            ec2Client.TerminateInstances(request);
    if (outcome.IsSuccess()) {
        std::cout << "Ec2 instance '" << instanceID <<
                  "' was terminated." << std::endl;
    } else {
        std::cerr << "Failed to terminate ec2 instance " << instanceID <<
                  ", " <<
                  outcome.GetError().GetMessage() << std::endl;
        return false;
    }

    return outcome.IsSuccess();
}
```

- For API details, see TerminateInstances in *AWS SDK for C++ API Reference*.

`UnmonitorInstances`

The following code example shows how to use `UnmonitorInstances`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Disable monitoring for an EC2 instance.
/*!
  \param instanceId: An EC2 instance ID.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::EC2::disableMonitoring(const Aws::String &instanceId,
                                    const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::EC2::EC2Client ec2Client(clientConfiguration);
    Aws::EC2::Model::UnmonitorInstancesRequest unrequest;
    unrequest.AddInstanceIds(instanceId);
    unrequest.SetDryRun(true);

    Aws::EC2::Model::UnmonitorInstancesOutcome dryRunOutcome =
 ec2Client.UnmonitorInstances(unrequest);
    if (dryRunOutcome.IsSuccess()) {
        std::cerr
                << "Failed dry run to disable monitoring on instance. A dry run
 should trigger an error."
                <<
                std::endl;
        return false;
    } else if (dryRunOutcome.GetError().GetErrorType() !=
               Aws::EC2::EC2Errors::DRY_RUN_OPERATION) {
        std::cout << "Failed dry run to disable monitoring on instance " <<
                  instanceId << ": " << dryRunOutcome.GetError().GetMessage() <<
                  std::endl;
        return false;
    }
```

```
    unrequest.SetDryRun(false);
    Aws::EC2::Model::UnmonitorInstancesOutcome unmonitorInstancesOutcome =
 ec2Client.UnmonitorInstances(unrequest);
    if (!unmonitorInstancesOutcome.IsSuccess()) {
        std::cout << "Failed to disable monitoring on instance " << instanceId
                  << ": " << unmonitorInstancesOutcome.GetError().GetMessage() <<
                  std::endl;
    } else {
        std::cout << "Successfully disable monitoring on instance " <<
                  instanceId << std::endl;
    }

    return unmonitorInstancesOutcome.IsSuccess();
}
```

- For API details, see UnmonitorInstances in *AWS SDK for C++ API Reference*.

EventBridge examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with EventBridge.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Actions

Actions

`PutEvents`

The following code example shows how to use `PutEvents`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Include the required files.

```
#include <aws/core/Aws.h>
#include <aws/events/EventBridgeClient.h>
#include <aws/events/model/PutEventsRequest.h>
#include <aws/events/model/PutEventsResult.h>
#include <aws/core/utils/Outcome.h>
#include <iostream>
```

Send the event.

```
        Aws::CloudWatchEvents::EventBridgeClient cwe;

        Aws::CloudWatchEvents::Model::PutEventsRequestEntry event_entry;
        event_entry.SetDetail(MakeDetails(event_key, event_value));
        event_entry.SetDetailType("sampleSubmitted");
        event_entry.AddResources(resource_arn);
        event_entry.SetSource("aws-sdk-cpp-cloudwatch-example");

        Aws::CloudWatchEvents::Model::PutEventsRequest request;
        request.AddEntries(event_entry);

        auto outcome = cwe.PutEvents(request);
        if (!outcome.IsSuccess())
        {
            std::cout << "Failed to post CloudWatch event: " <<
                outcome.GetError().GetMessage() << std::endl;
        }
        else
        {
            std::cout << "Successfully posted CloudWatch event" << std::endl;
        }
```

- For API details, see PutEvents in *AWS SDK for C++ API Reference*.

`PutRule`

The following code example shows how to use `PutRule`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Include the required files.

```
#include <aws/core/Aws.h>
#include <aws/events/EventBridgeClient.h>
#include <aws/events/model/PutRuleRequest.h>
#include <aws/events/model/PutRuleResult.h>
#include <aws/core/utils/Outcome.h>
#include <iostream>
```

Create the rule.

```
        Aws::CloudWatchEvents::EventBridgeClient cwe;
        Aws::CloudWatchEvents::Model::PutRuleRequest request;
        request.SetName(rule_name);
        request.SetRoleArn(role_arn);
        request.SetScheduleExpression("rate(5 minutes)");
        request.SetState(Aws::CloudWatchEvents::Model::RuleState::ENABLED);

        auto outcome = cwe.PutRule(request);
        if (!outcome.IsSuccess())
        {
            std::cout << "Failed to create CloudWatch events rule " <<
                rule_name << ": " << outcome.GetError().GetMessage() <<
                std::endl;
        }
        else
```

```
        {
            std::cout << "Successfully created CloudWatch events rule " <<
                rule_name << " with resulting Arn " <<
                outcome.GetResult().GetRuleArn() << std::endl;
        }
```

- For API details, see PutRule in *AWS SDK for C++ API Reference*.

`PutTargets`

The following code example shows how to use `PutTargets`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Include the required files.

```
#include <aws/core/Aws.h>
#include <aws/events/EventBridgeClient.h>
#include <aws/events/model/PutTargetsRequest.h>
#include <aws/events/model/PutTargetsResult.h>
#include <aws/core/utils/Outcome.h>
#include <iostream>
```

Add the target.

```
        Aws::CloudWatchEvents::EventBridgeClient cwe;

        Aws::CloudWatchEvents::Model::Target target;
        target.SetArn(lambda_arn);
        target.SetId(target_id);

        Aws::CloudWatchEvents::Model::PutTargetsRequest request;
```

```
        request.SetRule(rule_name);
        request.AddTargets(target);

        auto putTargetsOutcome = cwe.PutTargets(request);
        if (!putTargetsOutcome.IsSuccess())
        {
            std::cout << "Failed to create CloudWatch events target for rule "
                << rule_name << ": " <<
                putTargetsOutcome.GetError().GetMessage() << std::endl;
        }
        else
        {
            std::cout <<
                "Successfully created CloudWatch events target for rule "
                << rule_name << std::endl;
        }
```

- For API details, see PutTargets in *AWS SDK for C++ API Reference*.

AWS Glue examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with AWS Glue.

Basics are code examples that show you how to perform the essential operations within a service.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Get started
- Basics
- Actions

Get started

Hello AWS Glue

The following code example shows how to get started using AWS Glue.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Code for the CMakeLists.txt CMake file.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS glue)

# Set this project's name.
project("hello_glue")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})
```

```
if (WINDOWS_BUILD AND AWSSDK_INSTALL_AS_SHARED_LIBS)
     # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

     # set(BIN_SUB_DIR "/Debug") # if you are building from the command line you may
 need to uncomment this
                                     # and set the proper subdirectory to the
 executables' location.

     AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_glue.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Code for the hello_glue.cpp source file.

```
#include <aws/core/Aws.h>
#include <aws/glue/GlueClient.h>
#include <aws/glue/model/ListJobsRequest.h>
#include <iostream>

/*
 *  A "Hello Glue" starter application which initializes an AWS Glue client and
 lists the
 *  AWS Glue job definitions.
 *
 *  main function
 *
 *  Usage: 'hello_glue'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
```

```
    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::Glue::GlueClient glueClient(clientConfig);

        std::vector<Aws::String> jobs;

        Aws::String nextToken;  // Used for pagination.
        do {
            Aws::Glue::Model::ListJobsRequest listJobsRequest;
            if (!nextToken.empty()) {
                listJobsRequest.SetNextToken(nextToken);
            }

            Aws::Glue::Model::ListJobsOutcome listRunsOutcome = glueClient.ListJobs(
                    listJobsRequest);

            if (listRunsOutcome.IsSuccess()) {
                const std::vector<Aws::String> &jobNames =
 listRunsOutcome.GetResult().GetJobNames();
                jobs.insert(jobs.end(), jobNames.begin(), jobNames.end());

                nextToken = listRunsOutcome.GetResult().GetNextToken();
            } else {
                std::cerr << "Error listing jobs. "
                          << listRunsOutcome.GetError().GetMessage()
                          << std::endl;
                result = 1;
                break;
            }
        } while (!nextToken.empty());

        std::cout << "Your account has " << jobs.size() << " jobs."
                  << std::endl;
        for (size_t i = 0; i < jobs.size(); ++i) {
            std::cout << "   " << i + 1 << ". " << jobs[i] << std::endl;
        }
    }
    Aws::ShutdownAPI(options); // Should only be called once.
    return result;
}
```

- For API details, see ListJobs in *AWS SDK for C++ API Reference*.

Basics

Learn the basics

The following code example shows how to:

- Create a crawler that crawls a public Amazon S3 bucket and generates a database of CSV-formatted metadata.
- List information about databases and tables in your AWS Glue Data Catalog.
- Create a job to extract CSV data from the S3 bucket, transform the data, and load JSON-formatted output into another S3 bucket.
- List information about job runs, view transformed data, and clean up resources.

For more information, see Tutorial: Getting started with AWS Glue Studio.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Scenario which demonstrates using AWS Glue to add a crawler and run a job.
/*!
 \\sa runGettingStartedWithGlueScenario()
 \param bucketName: An S3 bucket created in the setup.
 \param roleName: An AWS Identity and Access Management (IAM) role created in the
 setup.
 \param clientConfig: AWS client configuration.
 \return bool: Successful completion.
 */

bool AwsDoc::Glue::runGettingStartedWithGlueScenario(const Aws::String &bucketName,
                                                     const Aws::String &roleName,
```

```
                                                        const
Aws::Client::ClientConfiguration &clientConfig) {
   Aws::Glue::GlueClient client(clientConfig);

   Aws::String roleArn;
   if (!getRoleArn(roleName, roleArn, clientConfig)) {
       std::cerr << "Error getting role ARN for role." << std::endl;
       return false;
   }

   // 1. Upload the job script to the S3 bucket.
   {
       std::cout << "Uploading the job script '"
                 << AwsDoc::Glue::PYTHON_SCRIPT
                 << "'." << std::endl;

       if (!AwsDoc::Glue::uploadFile(bucketName,
                                     AwsDoc::Glue::PYTHON_SCRIPT_PATH,
                                     AwsDoc::Glue::PYTHON_SCRIPT,
                                     clientConfig)) {
           std::cerr << "Error uploading the job file." << std::endl;
           return false;
       }
   }

   // 2. Create a crawler.
   {
       Aws::Glue::Model::S3Target s3Target;
       s3Target.SetPath("s3://crawler-public-us-east-1/flight/2016/csv");
       Aws::Glue::Model::CrawlerTargets crawlerTargets;
       crawlerTargets.AddS3Targets(s3Target);

       Aws::Glue::Model::CreateCrawlerRequest request;
       request.SetTargets(crawlerTargets);
       request.SetName(CRAWLER_NAME);
       request.SetDatabaseName(CRAWLER_DATABASE_NAME);
       request.SetTablePrefix(CRAWLER_DATABASE_PREFIX);
       request.SetRole(roleArn);

       Aws::Glue::Model::CreateCrawlerOutcome outcome =
client.CreateCrawler(request);

       if (outcome.IsSuccess()) {
           std::cout << "Successfully created the crawler." << std::endl;
```

```
        }
        else {
            std::cerr << "Error creating a crawler. " <<
outcome.GetError().GetMessage()
                      << std::endl;
            deleteAssets("", CRAWLER_DATABASE_NAME, "", bucketName, clientConfig);
            return false;
        }
    }

    // 3. Get a crawler.
    {
        Aws::Glue::Model::GetCrawlerRequest request;
        request.SetName(CRAWLER_NAME);

        Aws::Glue::Model::GetCrawlerOutcome outcome = client.GetCrawler(request);

        if (outcome.IsSuccess()) {
            Aws::Glue::Model::CrawlerState crawlerState =
outcome.GetResult().GetCrawler().GetState();
            std::cout << "Retrieved crawler with state " <<
                      Aws::Glue::Model::CrawlerStateMapper::GetNameForCrawlerState(
                              crawlerState)
                      << "." << std::endl;
        }
        else {
            std::cerr << "Error retrieving a crawler.  "
                      << outcome.GetError().GetMessage() << std::endl;
            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                         clientConfig);
            return false;
        }
    }

    // 4. Start a crawler.
    {
        Aws::Glue::Model::StartCrawlerRequest request;
        request.SetName(CRAWLER_NAME);

        Aws::Glue::Model::StartCrawlerOutcome outcome =
client.StartCrawler(request);


        if (outcome.IsSuccess() || (Aws::Glue::GlueErrors::CRAWLER_RUNNING ==
```

```
                                    outcome.GetError().GetErrorType())) {
            if (!outcome.IsSuccess()) {
                std::cout << "Crawler was already started." << std::endl;
            }
            else {
                std::cout << "Successfully started crawler." << std::endl;
            }

            std::cout << "This may take a while to run." << std::endl;

            Aws::Glue::Model::CrawlerState crawlerState =
Aws::Glue::Model::CrawlerState::NOT_SET;
            int iterations = 0;
            while (Aws::Glue::Model::CrawlerState::READY != crawlerState) {
                std::this_thread::sleep_for(std::chrono::seconds(1));
                ++iterations;
                if ((iterations % 10) == 0) { // Log status every 10 seconds.
                    std::cout << "Crawler status " <<

Aws::Glue::Model::CrawlerStateMapper::GetNameForCrawlerState(
                                      crawlerState)
                              << ". After " << iterations
                              << " seconds elapsed."
                              << std::endl;
                }
                Aws::Glue::Model::GetCrawlerRequest getCrawlerRequest;
                getCrawlerRequest.SetName(CRAWLER_NAME);

                Aws::Glue::Model::GetCrawlerOutcome getCrawlerOutcome =
client.GetCrawler(
                        getCrawlerRequest);

                if (getCrawlerOutcome.IsSuccess()) {
                    crawlerState =
getCrawlerOutcome.GetResult().GetCrawler().GetState();
                }
                else {
                    std::cerr << "Error getting crawler.  "
                              << getCrawlerOutcome.GetError().GetMessage() <<
std::endl;
                    break;
                }
            }
```

```
            if (Aws::Glue::Model::CrawlerState::READY == crawlerState) {
                std::cout << "Crawler finished running after " << iterations
                          << " seconds."
                          << std::endl;
            }
        }
        else {
            std::cerr << "Error starting a crawler.  "
                      << outcome.GetError().GetMessage()
                      << std::endl;

            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                         clientConfig);
            return false;
        }
    }

    // 5. Get a database.
    {
        Aws::Glue::Model::GetDatabaseRequest request;
        request.SetName(CRAWLER_DATABASE_NAME);

        Aws::Glue::Model::GetDatabaseOutcome outcome = client.GetDatabase(request);

        if (outcome.IsSuccess()) {
            const Aws::Glue::Model::Database &database =
outcome.GetResult().GetDatabase();

            std::cout << "Successfully retrieve the database\n" <<
                      database.Jsonize().View().WriteReadable() << "'." <<
std::endl;
        }
        else {
            std::cerr << "Error getting the database.  "
                      << outcome.GetError().GetMessage() << std::endl;
            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                         clientConfig);
            return false;
        }
    }

    // 6. Get tables.
    Aws::String tableName;
    {
```

```
        Aws::Glue::Model::GetTablesRequest request;
        request.SetDatabaseName(CRAWLER_DATABASE_NAME);
        std::vector<Aws::Glue::Model::Table> all_tables;
        Aws::String nextToken; // Used for pagination.
        do {
            Aws::Glue::Model::GetTablesOutcome outcome = client.GetTables(request);

            if (outcome.IsSuccess()) {
                const std::vector<Aws::Glue::Model::Table> &tables =
outcome.GetResult().GetTableList();
                all_tables.insert(all_tables.end(), tables.begin(), tables.end());
                nextToken = outcome.GetResult().GetNextToken();
            }
            else {
                std::cerr << "Error getting the tables. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                             clientConfig);
                return false;
            }
        } while (!nextToken.empty());

        std::cout << "The database contains " << all_tables.size()
                  << (all_tables.size() == 1 ?
                      " table." : "tables.") << std::endl;
        std::cout << "Here is a list of the tables in the database.";
        for (size_t index = 0; index < all_tables.size(); ++index) {
            std::cout << "    " << index + 1 << ":  " << all_tables[index].GetName()
                      << std::endl;
        }

        if (!all_tables.empty()) {
            int tableIndex = askQuestionForIntRange(
                    "Enter an index to display the database detail ",
                    1, static_cast<int>(all_tables.size()));
            std::cout << all_tables[tableIndex - 1].Jsonize().View().WriteReadable()
                      << std::endl;

            tableName = all_tables[tableIndex - 1].GetName();
        }
    }

    // 7. Create a job.
```

```
    {
        Aws::Glue::Model::CreateJobRequest request;
        request.SetName(JOB_NAME);
        request.SetRole(roleArn);
        request.SetGlueVersion(GLUE_VERSION);

        Aws::Glue::Model::JobCommand command;
        command.SetName(JOB_COMMAND_NAME);
        command.SetPythonVersion(JOB_PYTHON_VERSION);
        command.SetScriptLocation(
                Aws::String("s3://") + bucketName + "/" + PYTHON_SCRIPT);
        request.SetCommand(command);

        Aws::Glue::Model::CreateJobOutcome outcome = client.CreateJob(request);

        if (outcome.IsSuccess()) {
            std::cout << "Successfully created the job." << std::endl;
        }
        else {
            std::cerr << "Error creating the job. " <<
outcome.GetError().GetMessage()
                      << std::endl;
            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                         clientConfig);
            return false;
        }
    }

    // 8. Start a job run.
    {
        Aws::Glue::Model::StartJobRunRequest request;
        request.SetJobName(JOB_NAME);

        Aws::Map<Aws::String, Aws::String> arguments;
        arguments["--input_database"] = CRAWLER_DATABASE_NAME;
        arguments["--input_table"] = tableName;
        arguments["--output_bucket_url"] = Aws::String("s3://") + bucketName + "/";
        request.SetArguments(arguments);

        Aws::Glue::Model::StartJobRunOutcome outcome = client.StartJobRun(request);

        if (outcome.IsSuccess()) {
            std::cout << "Successfully started the job." << std::endl;
```

```
            Aws::String jobRunId = outcome.GetResult().GetJobRunId();

            int iterator = 0;
            bool done = false;
            while (!done) {
                ++iterator;
                std::this_thread::sleep_for(std::chrono::seconds(1));
                Aws::Glue::Model::GetJobRunRequest jobRunRequest;
                jobRunRequest.SetJobName(JOB_NAME);
                jobRunRequest.SetRunId(jobRunId);

                Aws::Glue::Model::GetJobRunOutcome jobRunOutcome = client.GetJobRun(
                        jobRunRequest);

                if (jobRunOutcome.IsSuccess()) {
                    const Aws::Glue::Model::JobRun &jobRun =
jobRunOutcome.GetResult().GetJobRun();
                    Aws::Glue::Model::JobRunState jobRunState =
jobRun.GetJobRunState();

                    if ((jobRunState == Aws::Glue::Model::JobRunState::STOPPED) ||
                        (jobRunState == Aws::Glue::Model::JobRunState::FAILED) ||
                        (jobRunState == Aws::Glue::Model::JobRunState::TIMEOUT)) {
                        std::cerr << "Error running job. "
                                  << jobRun.GetErrorMessage()
                                  << std::endl;
                        deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, JOB_NAME,
                                     bucketName,
                                     clientConfig);
                        return false;
                    }
                    else if (jobRunState ==
                             Aws::Glue::Model::JobRunState::SUCCEEDED) {
                        std::cout << "Job run succeeded after  " << iterator <<
                                  " seconds elapsed." << std::endl;
                        done = true;
                    }
                    else if ((iterator % 10) == 0) { // Log status every 10 seconds.
                        std::cout << "Job run status " <<

Aws::Glue::Model::JobRunStateMapper::GetNameForJobRunState(
                                          jobRunState) <<
                                  ". " << iterator <<
                                  " seconds elapsed." << std::endl;
```

```
                    }
                }
                else {
                    std::cerr << "Error retrieving job run state. "
                              << jobRunOutcome.GetError().GetMessage()
                              << std::endl;
                    deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, JOB_NAME,
                                 bucketName, clientConfig);
                    return false;
                }
            }
        }
        else {
            std::cerr << "Error starting a job. " << outcome.GetError().GetMessage()
                      << std::endl;
            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, JOB_NAME, bucketName,
                         clientConfig);
            return false;
        }
    }

    // 9. List the output data stored in the S3 bucket.
    {
        Aws::S3::S3Client s3Client;
        Aws::S3::Model::ListObjectsV2Request request;
        request.SetBucket(bucketName);
        request.SetPrefix(OUTPUT_FILE_PREFIX);

        Aws::String continuationToken; // Used for pagination.
        std::vector<Aws::S3::Model::Object> allObjects;
        do {
            if (!continuationToken.empty()) {
                request.SetContinuationToken(continuationToken);
            }
            Aws::S3::Model::ListObjectsV2Outcome outcome = s3Client.ListObjectsV2(
                    request);

            if (outcome.IsSuccess()) {
                const std::vector<Aws::S3::Model::Object> &objects =
                        outcome.GetResult().GetContents();
                allObjects.insert(allObjects.end(), objects.begin(), objects.end());
                continuationToken = outcome.GetResult().GetNextContinuationToken();
            }
            else {
```

```
                std::cerr << "Error listing objects. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                break;
            }
        } while (!continuationToken.empty());

        std::cout << "Data from your job is in " << allObjects.size() <<
                  " files in the S3 bucket, " << bucketName << "." << std::endl;

        for (size_t i = 0; i < allObjects.size(); ++i) {
            std::cout << "    " << i + 1 << ". " << allObjects[i].GetKey()
                      << std::endl;
        }

        int objectIndex = askQuestionForIntRange(
                std::string(
                        "Enter the number of a block to download it and see the
first ") +
                std::to_string(LINES_OF_RUN_FILE_TO_DISPLAY) +
                " lines of JSON output in the block: ", 1,
                static_cast<int>(allObjects.size()));

        Aws::String objectKey = allObjects[objectIndex - 1].GetKey();

        std::stringstream stringStream;
        if (getObjectFromBucket(bucketName, objectKey, stringStream,
                                clientConfig)) {
            for (int i = 0; i < LINES_OF_RUN_FILE_TO_DISPLAY && stringStream; ++i) {
                std::string line;
                std::getline(stringStream, line);
                std::cout << "    " << line << std::endl;
            }
        }
        else {
            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, JOB_NAME, bucketName,
                         clientConfig);
            return false;
        }
    }

    // 10. List all the jobs.
    Aws::String jobName;
    {
```

```
        Aws::Glue::Model::ListJobsRequest listJobsRequest;

        Aws::String nextToken;
        std::vector<Aws::String> allJobNames;

        do {
            if (!nextToken.empty()) {
                listJobsRequest.SetNextToken(nextToken);
            }
            Aws::Glue::Model::ListJobsOutcome listRunsOutcome = client.ListJobs(
                    listJobsRequest);

            if (listRunsOutcome.IsSuccess()) {
                const std::vector<Aws::String> &jobNames =
listRunsOutcome.GetResult().GetJobNames();
                allJobNames.insert(allJobNames.end(), jobNames.begin(),
jobNames.end());
                nextToken = listRunsOutcome.GetResult().GetNextToken();
            }
            else {
                std::cerr << "Error listing jobs. "
                          << listRunsOutcome.GetError().GetMessage()
                          << std::endl;
            }
        } while (!nextToken.empty());
        std::cout << "Your account has " << allJobNames.size() << " jobs."
                  << std::endl;
        for (size_t i = 0; i < allJobNames.size(); ++i) {
            std::cout << "   " << i + 1 << ". " << allJobNames[i] << std::endl;
        }
        int jobIndex = askQuestionForIntRange(
                Aws::String("Enter a number between 1 and ") +
                std::to_string(allJobNames.size()) +
                " to see the list of runs for a job: ",
                1, static_cast<int>(allJobNames.size()));

        jobName = allJobNames[jobIndex - 1];
    }

    // 11. Get the job runs for a job.
    Aws::String jobRunID;
    if (!jobName.empty()) {
        Aws::Glue::Model::GetJobRunsRequest getJobRunsRequest;
        getJobRunsRequest.SetJobName(jobName);
```

```
        Aws::String nextToken; // Used for pagination.
        std::vector<Aws::Glue::Model::JobRun> allJobRuns;
        do {
            if (!nextToken.empty()) {
                getJobRunsRequest.SetNextToken(nextToken);
            }
            Aws::Glue::Model::GetJobRunsOutcome jobRunsOutcome = client.GetJobRuns(
                    getJobRunsRequest);

            if (jobRunsOutcome.IsSuccess()) {
                const std::vector<Aws::Glue::Model::JobRun> &jobRuns =
jobRunsOutcome.GetResult().GetJobRuns();
                allJobRuns.insert(allJobRuns.end(), jobRuns.begin(), jobRuns.end());

                nextToken = jobRunsOutcome.GetResult().GetNextToken();
            }
            else {
                std::cerr << "Error getting job runs. "
                          << jobRunsOutcome.GetError().GetMessage()
                          << std::endl;
                break;
            }
        } while (!nextToken.empty());

        std::cout << "There are " << allJobRuns.size() << " runs in the job '"
                  <<
                  jobName << "'." << std::endl;

        for (size_t i = 0; i < allJobRuns.size(); ++i) {
            std::cout << "   " << i + 1 << ". " << allJobRuns[i].GetJobName()
                      << std::endl;
        }

        int runIndex = askQuestionForIntRange(
                Aws::String("Enter a number between 1 and ") +
                std::to_string(allJobRuns.size()) +
                " to see details for a run: ",
                1, static_cast<int>(allJobRuns.size()));
        jobRunID = allJobRuns[runIndex - 1].GetId();
    }

    // 12. Get a single job run.
    if (!jobRunID.empty()) {
```

```
        Aws::Glue::Model::GetJobRunRequest jobRunRequest;
        jobRunRequest.SetJobName(jobName);
        jobRunRequest.SetRunId(jobRunID);

        Aws::Glue::Model::GetJobRunOutcome jobRunOutcome = client.GetJobRun(
                jobRunRequest);

        if (jobRunOutcome.IsSuccess()) {
            std::cout << "Displaying the job run JSON description." << std::endl;
            std::cout
                    <<
 jobRunOutcome.GetResult().GetJobRun().Jsonize().View().WriteReadable()
                    << std::endl;
        }
        else {
            std::cerr << "Error get a job run. "
                      << jobRunOutcome.GetError().GetMessage()
                      << std::endl;
        }
    }

    return deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, JOB_NAME, bucketName,
                        clientConfig);
}

//! Cleanup routine to delete created assets.
/*!
 \\sa deleteAssets()
 \param crawler: Name of an AWS Glue crawler.
 \param database: The name of an AWS Glue database.
 \param job: The name of an AWS Glue job.
 \param bucketName: The name of an S3 bucket.
 \param clientConfig: AWS client configuration.
 \return bool: Successful completion.
 */
bool AwsDoc::Glue::deleteAssets(const Aws::String &crawler, const Aws::String
 &database,
                                const Aws::String &job, const Aws::String
 &bucketName,
                                const Aws::Client::ClientConfiguration
 &clientConfig) {
    const Aws::Glue::GlueClient client(clientConfig);
    bool result = true;
```

```
   // 13. Delete a job.
   if (!job.empty()) {
       Aws::Glue::Model::DeleteJobRequest request;
       request.SetJobName(job);

       Aws::Glue::Model::DeleteJobOutcome outcome = client.DeleteJob(request);


       if (outcome.IsSuccess()) {
           std::cout << "Successfully deleted the job." << std::endl;
       }
       else {
           std::cerr << "Error deleting the job. " <<
outcome.GetError().GetMessage()
                     << std::endl;
           result = false;
       }
   }

   // 14. Delete a database.
   if (!database.empty()) {
       Aws::Glue::Model::DeleteDatabaseRequest request;
       request.SetName(database);

       Aws::Glue::Model::DeleteDatabaseOutcome outcome = client.DeleteDatabase(
               request);

       if (outcome.IsSuccess()) {
           std::cout << "Successfully deleted the database." << std::endl;
       }
       else {
           std::cerr << "Error deleting database. " <<
outcome.GetError().GetMessage()
                     << std::endl;
           result = false;
       }
   }

   // 15. Delete a crawler.
   if (!crawler.empty()) {
       Aws::Glue::Model::DeleteCrawlerRequest request;
       request.SetName(crawler);
```

```
        Aws::Glue::Model::DeleteCrawlerOutcome outcome =
 client.DeleteCrawler(request);

        if (outcome.IsSuccess()) {
            std::cout << "Successfully deleted the crawler." << std::endl;
        }
        else {
            std::cerr << "Error deleting the crawler. "
                      << outcome.GetError().GetMessage() << std::endl;
            result = false;
        }
    }

    // 16. Delete the job script and run data from the S3 bucket.
    result &= AwsDoc::Glue::deleteAllObjectsInS3Bucket(bucketName,
                                                       clientConfig);
    return result;
}

//! Routine which uploads a file to an S3 bucket.
/*!
 \\sa uploadFile()
 \param bucketName: An S3 bucket created in the setup.
 \param filePath: The path of the file to upload.
 \param fileName The name for the uploaded file.
 \param clientConfig: AWS client configuration.
 \return bool: Successful completion.
 */
bool
AwsDoc::Glue::uploadFile(const Aws::String &bucketName,
                         const Aws::String &filePath,
                         const Aws::String &fileName,
                         const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::S3::S3Client s3_client(clientConfig);

    Aws::S3::Model::PutObjectRequest request;
    request.SetBucket(bucketName);
    request.SetKey(fileName);

    std::shared_ptr<Aws::IOStream> inputData =
            Aws::MakeShared<Aws::FStream>("SampleAllocationTag",
                                          filePath.c_str(),
                                          std::ios_base::in |
 std::ios_base::binary);
```

```
    if (!*inputData) {
        std::cerr << "Error unable to read file " << filePath << std::endl;
        return false;
    }

    request.SetBody(inputData);

    Aws::S3::Model::PutObjectOutcome outcome =
            s3_client.PutObject(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: PutObject: " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Added object '" << filePath << "' to bucket '"
                  << bucketName << "'." << std::endl;
    }

    return outcome.IsSuccess();
}

//! Routine which deletes all objects in an S3 bucket.
/*!
 \\sa deleteAllObjectsInS3Bucket()
 \param bucketName: The S3 bucket name.
 \param clientConfig: AWS client configuration.
 \return bool: Successful completion.
 */
bool AwsDoc::Glue::deleteAllObjectsInS3Bucket(const Aws::String &bucketName,
                                              const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client client(clientConfig);
    Aws::S3::Model::ListObjectsV2Request listObjectsRequest;
    listObjectsRequest.SetBucket(bucketName);

    Aws::String continuationToken; // Used for pagination.
    bool result = true;
    do {
        if (!continuationToken.empty()) {
            listObjectsRequest.SetContinuationToken(continuationToken);
        }
```

```
       Aws::S3::Model::ListObjectsV2Outcome listObjectsOutcome =
client.ListObjectsV2(
               listObjectsRequest);

       if (listObjectsOutcome.IsSuccess()) {
           const std::vector<Aws::S3::Model::Object> &objects =
listObjectsOutcome.GetResult().GetContents();
           if (!objects.empty()) {
               Aws::S3::Model::DeleteObjectsRequest deleteObjectsRequest;
               deleteObjectsRequest.SetBucket(bucketName);

               std::vector<Aws::S3::Model::ObjectIdentifier> objectIdentifiers;
               for (const Aws::S3::Model::Object &object: objects) {
                   objectIdentifiers.push_back(
                           Aws::S3::Model::ObjectIdentifier().WithKey(
                                   object.GetKey()));
               }
               Aws::S3::Model::Delete objectsDelete;
               objectsDelete.SetObjects(objectIdentifiers);
               objectsDelete.SetQuiet(true);
               deleteObjectsRequest.SetDelete(objectsDelete);

               Aws::S3::Model::DeleteObjectsOutcome deleteObjectsOutcome =
                       client.DeleteObjects(deleteObjectsRequest);

               if (!deleteObjectsOutcome.IsSuccess()) {
                   std::cerr << "Error deleting objects. " <<
                             deleteObjectsOutcome.GetError().GetMessage() <<
std::endl;
                   result = false;
                   break;
               }
               else {
                   std::cout << "Successfully deleted the objects." << std::endl;

               }
           }
           else {
               std::cout << "No objects to delete in '" << bucketName << "'."
                         << std::endl;
           }

           continuationToken =
listObjectsOutcome.GetResult().GetNextContinuationToken();
```

```
        }
        else {
            std::cerr << "Error listing objects. "
                      << listObjectsOutcome.GetError().GetMessage() << std::endl;
            result = false;
            break;
        }
    } while (!continuationToken.empty());

    return result;
}

//! Routine which retrieves an object from an S3 bucket.
/*!
 \\sa getObjectFromBucket()
 \param bucketName: The S3 bucket name.
 \param objectKey: The object's name.
 \param objectStream: A stream to receive the retrieved data.
 \param clientConfig: AWS client configuration.
 \return bool: Successful completion.
 */
bool AwsDoc::Glue::getObjectFromBucket(const Aws::String &bucketName,
                                       const Aws::String &objectKey,
                                       std::ostream &objectStream,
                                       const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client client(clientConfig);
    Aws::S3::Model::GetObjectRequest request;
    request.SetBucket(bucketName);
    request.SetKey(objectKey);

    Aws::S3::Model::GetObjectOutcome outcome = client.GetObject(request);


    if (outcome.IsSuccess()) {
        std::cout << "Successfully retrieved '" << objectKey << "'." << std::endl;
        auto &body = outcome.GetResult().GetBody();
        objectStream << body.rdbuf();
    }
    else {
        std::cerr << "Error retrieving object. " << outcome.GetError().GetMessage()
                  << std::endl;
    }
```

```
    return outcome.IsSuccess();
}
```

- For API details, see the following topics in *AWS SDK for C++ API Reference*.
  - CreateCrawler
  - CreateJob
  - DeleteCrawler
  - DeleteDatabase
  - DeleteJob
  - DeleteTable
  - GetCrawler
  - GetDatabase
  - GetDatabases
  - GetJob
  - GetJobRun
  - GetJobRuns
  - GetTables
  - ListJobs
  - StartCrawler
  - StartJobRun

Actions

`CreateCrawler`

The following code example shows how to use `CreateCrawler`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
       Aws::Client::ClientConfiguration clientConfig;
       // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
       // clientConfig.region = "us-east-1";

   Aws::Glue::GlueClient client(clientConfig);

       Aws::Glue::Model::S3Target s3Target;
       s3Target.SetPath("s3://crawler-public-us-east-1/flight/2016/csv");
       Aws::Glue::Model::CrawlerTargets crawlerTargets;
       crawlerTargets.AddS3Targets(s3Target);

       Aws::Glue::Model::CreateCrawlerRequest request;
       request.SetTargets(crawlerTargets);
       request.SetName(CRAWLER_NAME);
       request.SetDatabaseName(CRAWLER_DATABASE_NAME);
       request.SetTablePrefix(CRAWLER_DATABASE_PREFIX);
       request.SetRole(roleArn);

       Aws::Glue::Model::CreateCrawlerOutcome outcome =
client.CreateCrawler(request);

       if (outcome.IsSuccess()) {
           std::cout << "Successfully created the crawler." << std::endl;
       }
       else {
           std::cerr << "Error creating a crawler. " <<
outcome.GetError().GetMessage()
                     << std::endl;
           deleteAssets("", CRAWLER_DATABASE_NAME, "", bucketName, clientConfig);
           return false;
       }
```

- For API details, see CreateCrawler in *AWS SDK for C++ API Reference*.

`CreateJob`

The following code example shows how to use `CreateJob`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::CreateJobRequest request;
        request.SetName(JOB_NAME);
        request.SetRole(roleArn);
        request.SetGlueVersion(GLUE_VERSION);

        Aws::Glue::Model::JobCommand command;
        command.SetName(JOB_COMMAND_NAME);
        command.SetPythonVersion(JOB_PYTHON_VERSION);
        command.SetScriptLocation(
                Aws::String("s3://") + bucketName + "/" + PYTHON_SCRIPT);
        request.SetCommand(command);

        Aws::Glue::Model::CreateJobOutcome outcome = client.CreateJob(request);

        if (outcome.IsSuccess()) {
            std::cout << "Successfully created the job." << std::endl;
        }
        else {
            std::cerr << "Error creating the job. " <<
outcome.GetError().GetMessage()
                      << std::endl;
```

```
            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                         clientConfig);
            return false;
        }
```

- For API details, see CreateJob in *AWS SDK for C++ API Reference*.

`DeleteCrawler`

The following code example shows how to use `DeleteCrawler`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::DeleteCrawlerRequest request;
        request.SetName(crawler);

        Aws::Glue::Model::DeleteCrawlerOutcome outcome =
client.DeleteCrawler(request);

        if (outcome.IsSuccess()) {
            std::cout << "Successfully deleted the crawler." << std::endl;
        }
        else {
            std::cerr << "Error deleting the crawler. "
                      << outcome.GetError().GetMessage() << std::endl;
            result = false;
        }
```

- For API details, see DeleteCrawler in *AWS SDK for C++ API Reference*.

`DeleteDatabase`

The following code example shows how to use `DeleteDatabase`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
       Aws::Client::ClientConfiguration clientConfig;
       // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
       // clientConfig.region = "us-east-1";

   Aws::Glue::GlueClient client(clientConfig);

       Aws::Glue::Model::DeleteDatabaseRequest request;
       request.SetName(database);

       Aws::Glue::Model::DeleteDatabaseOutcome outcome = client.DeleteDatabase(
               request);

       if (outcome.IsSuccess()) {
           std::cout << "Successfully deleted the database." << std::endl;
       }
       else {
           std::cerr << "Error deleting database. " <<
outcome.GetError().GetMessage()
                     << std::endl;
           result = false;
       }
```

- For API details, see DeleteDatabase in *AWS SDK for C++ API Reference*.

`DeleteJob`

The following code example shows how to use `DeleteJob`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
       Aws::Client::ClientConfiguration clientConfig;
       // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
       // clientConfig.region = "us-east-1";

   Aws::Glue::GlueClient client(clientConfig);

       Aws::Glue::Model::DeleteJobRequest request;
       request.SetJobName(job);

       Aws::Glue::Model::DeleteJobOutcome outcome = client.DeleteJob(request);


       if (outcome.IsSuccess()) {
           std::cout << "Successfully deleted the job." << std::endl;
       }
       else {
           std::cerr << "Error deleting the job. " <<
outcome.GetError().GetMessage()
                     << std::endl;
           result = false;
       }
```

- For API details, see DeleteJob in *AWS SDK for C++ API Reference*.

`GetCrawler`

The following code example shows how to use `GetCrawler`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
       Aws::Client::ClientConfiguration clientConfig;
       // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
       // clientConfig.region = "us-east-1";

   Aws::Glue::GlueClient client(clientConfig);

       Aws::Glue::Model::GetCrawlerRequest request;
       request.SetName(CRAWLER_NAME);

       Aws::Glue::Model::GetCrawlerOutcome outcome = client.GetCrawler(request);

       if (outcome.IsSuccess()) {
           Aws::Glue::Model::CrawlerState crawlerState =
outcome.GetResult().GetCrawler().GetState();
           std::cout << "Retrieved crawler with state " <<
                     Aws::Glue::Model::CrawlerStateMapper::GetNameForCrawlerState(
                             crawlerState)
                     << "." << std::endl;
       }
       else {
           std::cerr << "Error retrieving a crawler.  "
                     << outcome.GetError().GetMessage() << std::endl;
           deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                        clientConfig);
           return false;
       }
```

- For API details, see GetCrawler in *AWS SDK for C++ API Reference*.

`GetDatabase`

The following code example shows how to use `GetDatabase`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
       Aws::Client::ClientConfiguration clientConfig;
       // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
       // clientConfig.region = "us-east-1";

   Aws::Glue::GlueClient client(clientConfig);

       Aws::Glue::Model::GetDatabaseRequest request;
       request.SetName(CRAWLER_DATABASE_NAME);

       Aws::Glue::Model::GetDatabaseOutcome outcome = client.GetDatabase(request);

       if (outcome.IsSuccess()) {
           const Aws::Glue::Model::Database &database =
outcome.GetResult().GetDatabase();

           std::cout << "Successfully retrieve the database\n" <<
                     database.Jsonize().View().WriteReadable() << "'." <<
std::endl;
       }
       else {
           std::cerr << "Error getting the database.  "
                     << outcome.GetError().GetMessage() << std::endl;
           deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                        clientConfig);
           return false;
       }
```

- For API details, see GetDatabase in *AWS SDK for C++ API Reference*.

`GetJobRun`

The following code example shows how to use `GetJobRun`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
       Aws::Client::ClientConfiguration clientConfig;
       // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
       // clientConfig.region = "us-east-1";

   Aws::Glue::GlueClient client(clientConfig);

       Aws::Glue::Model::GetJobRunRequest jobRunRequest;
       jobRunRequest.SetJobName(jobName);
       jobRunRequest.SetRunId(jobRunID);

       Aws::Glue::Model::GetJobRunOutcome jobRunOutcome = client.GetJobRun(
               jobRunRequest);

       if (jobRunOutcome.IsSuccess()) {
           std::cout << "Displaying the job run JSON description." << std::endl;
           std::cout
                   <<
jobRunOutcome.GetResult().GetJobRun().Jsonize().View().WriteReadable()
                   << std::endl;
       }
       else {
           std::cerr << "Error get a job run. "
                     << jobRunOutcome.GetError().GetMessage()
                     << std::endl;
       }
```

- For API details, see GetJobRun in *AWS SDK for C++ API Reference*.

`GetJobRuns`

The following code example shows how to use `GetJobRuns`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::GetJobRunsRequest getJobRunsRequest;
        getJobRunsRequest.SetJobName(jobName);

        Aws::String nextToken; // Used for pagination.
        std::vector<Aws::Glue::Model::JobRun> allJobRuns;
        do {
            if (!nextToken.empty()) {
                getJobRunsRequest.SetNextToken(nextToken);
            }
            Aws::Glue::Model::GetJobRunsOutcome jobRunsOutcome = client.GetJobRuns(
                    getJobRunsRequest);

            if (jobRunsOutcome.IsSuccess()) {
                const std::vector<Aws::Glue::Model::JobRun> &jobRuns =
jobRunsOutcome.GetResult().GetJobRuns();
                allJobRuns.insert(allJobRuns.end(), jobRuns.begin(), jobRuns.end());

                nextToken = jobRunsOutcome.GetResult().GetNextToken();
            }
            else {
                std::cerr << "Error getting job runs. "
                          << jobRunsOutcome.GetError().GetMessage()
                          << std::endl;
                break;
```

```
            }
        } while (!nextToken.empty());
```

- For API details, see GetJobRuns in *AWS SDK for C++ API Reference*.

`GetTables`

The following code example shows how to use `GetTables`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
       Aws::Client::ClientConfiguration clientConfig;
       // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
       // clientConfig.region = "us-east-1";

   Aws::Glue::GlueClient client(clientConfig);

       Aws::Glue::Model::GetTablesRequest request;
       request.SetDatabaseName(CRAWLER_DATABASE_NAME);
       std::vector<Aws::Glue::Model::Table> all_tables;
       Aws::String nextToken; // Used for pagination.
       do {
           Aws::Glue::Model::GetTablesOutcome outcome = client.GetTables(request);

           if (outcome.IsSuccess()) {
               const std::vector<Aws::Glue::Model::Table> &tables =
outcome.GetResult().GetTableList();
               all_tables.insert(all_tables.end(), tables.begin(), tables.end());
               nextToken = outcome.GetResult().GetNextToken();
           }
           else {
               std::cerr << "Error getting the tables. "
                         << outcome.GetError().GetMessage()
                         << std::endl;
```

```
            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                         clientConfig);
            return false;
        }
    } while (!nextToken.empty());

    std::cout << "The database contains " << all_tables.size()
              << (all_tables.size() == 1 ?
                  " table." : "tables.") << std::endl;
    std::cout << "Here is a list of the tables in the database.";
    for (size_t index = 0; index < all_tables.size(); ++index) {
        std::cout << "    " << index + 1 << ":  " << all_tables[index].GetName()
                  << std::endl;
    }

    if (!all_tables.empty()) {
        int tableIndex = askQuestionForIntRange(
                "Enter an index to display the database detail ",
                1, static_cast<int>(all_tables.size()));
        std::cout << all_tables[tableIndex - 1].Jsonize().View().WriteReadable()
                  << std::endl;

        tableName = all_tables[tableIndex - 1].GetName();
    }
```

- For API details, see GetTables in *AWS SDK for C++ API Reference*.

`ListJobs`

The following code example shows how to use `ListJobs`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
    Aws::Client::ClientConfiguration clientConfig;
```

```
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::ListJobsRequest listJobsRequest;

        Aws::String nextToken;
        std::vector<Aws::String> allJobNames;

        do {
            if (!nextToken.empty()) {
                listJobsRequest.SetNextToken(nextToken);
            }
            Aws::Glue::Model::ListJobsOutcome listRunsOutcome = client.ListJobs(
                    listJobsRequest);

            if (listRunsOutcome.IsSuccess()) {
                const std::vector<Aws::String> &jobNames =
listRunsOutcome.GetResult().GetJobNames();
                allJobNames.insert(allJobNames.end(), jobNames.begin(),
jobNames.end());
                nextToken = listRunsOutcome.GetResult().GetNextToken();
            }
            else {
                std::cerr << "Error listing jobs. "
                          << listRunsOutcome.GetError().GetMessage()
                          << std::endl;
            }
        } while (!nextToken.empty());
```

- For API details, see ListJobs in *AWS SDK for C++ API Reference*.

`StartCrawler`

The following code example shows how to use `StartCrawler`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
       Aws::Client::ClientConfiguration clientConfig;
       // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
       // clientConfig.region = "us-east-1";

   Aws::Glue::GlueClient client(clientConfig);

       Aws::Glue::Model::StartCrawlerRequest request;
       request.SetName(CRAWLER_NAME);

       Aws::Glue::Model::StartCrawlerOutcome outcome =
client.StartCrawler(request);


       if (outcome.IsSuccess() || (Aws::Glue::GlueErrors::CRAWLER_RUNNING ==
                                   outcome.GetError().GetErrorType())) {
           if (!outcome.IsSuccess()) {
               std::cout << "Crawler was already started." << std::endl;
           }
           else {
               std::cout << "Successfully started crawler." << std::endl;
           }

           std::cout << "This may take a while to run." << std::endl;

           Aws::Glue::Model::CrawlerState crawlerState =
Aws::Glue::Model::CrawlerState::NOT_SET;
           int iterations = 0;
           while (Aws::Glue::Model::CrawlerState::READY != crawlerState) {
               std::this_thread::sleep_for(std::chrono::seconds(1));
               ++iterations;
               if ((iterations % 10) == 0) { // Log status every 10 seconds.
                   std::cout << "Crawler status " <<
```

```
Aws::Glue::Model::CrawlerStateMapper::GetNameForCrawlerState(
                                    crawlerState)
                            << ". After " << iterations
                            << " seconds elapsed."
                            << std::endl;
                }
                Aws::Glue::Model::GetCrawlerRequest getCrawlerRequest;
                getCrawlerRequest.SetName(CRAWLER_NAME);

                Aws::Glue::Model::GetCrawlerOutcome getCrawlerOutcome =
client.GetCrawler(
                        getCrawlerRequest);

                if (getCrawlerOutcome.IsSuccess()) {
                    crawlerState =
getCrawlerOutcome.GetResult().GetCrawler().GetState();
                }
                else {
                    std::cerr << "Error getting crawler.  "
                              << getCrawlerOutcome.GetError().GetMessage() <<
std::endl;
                    break;
                }
            }

            if (Aws::Glue::Model::CrawlerState::READY == crawlerState) {
                std::cout << "Crawler finished running after " << iterations
                          << " seconds."
                          << std::endl;
            }
        }
        else {
            std::cerr << "Error starting a crawler.  "
                      << outcome.GetError().GetMessage()
                      << std::endl;

            deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, "", bucketName,
                         clientConfig);
            return false;
        }
```

- For API details, see StartCrawler in *AWS SDK for C++ API Reference*.

`StartJobRun`

The following code example shows how to use `StartJobRun`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Glue::GlueClient client(clientConfig);

        Aws::Glue::Model::StartJobRunRequest request;
        request.SetJobName(JOB_NAME);

        Aws::Map<Aws::String, Aws::String> arguments;
        arguments["--input_database"] = CRAWLER_DATABASE_NAME;
        arguments["--input_table"] = tableName;
        arguments["--output_bucket_url"] = Aws::String("s3://") + bucketName + "/";
        request.SetArguments(arguments);

        Aws::Glue::Model::StartJobRunOutcome outcome = client.StartJobRun(request);

        if (outcome.IsSuccess()) {
            std::cout << "Successfully started the job." << std::endl;

            Aws::String jobRunId = outcome.GetResult().GetJobRunId();

            int iterator = 0;
            bool done = false;
            while (!done) {
                ++iterator;
                std::this_thread::sleep_for(std::chrono::seconds(1));
                Aws::Glue::Model::GetJobRunRequest jobRunRequest;
                jobRunRequest.SetJobName(JOB_NAME);
                jobRunRequest.SetRunId(jobRunId);
```

```
                Aws::Glue::Model::GetJobRunOutcome jobRunOutcome = client.GetJobRun(
                        jobRunRequest);

                if (jobRunOutcome.IsSuccess()) {
                    const Aws::Glue::Model::JobRun &jobRun =
jobRunOutcome.GetResult().GetJobRun();
                    Aws::Glue::Model::JobRunState jobRunState =
jobRun.GetJobRunState();

                    if ((jobRunState == Aws::Glue::Model::JobRunState::STOPPED) ||
                        (jobRunState == Aws::Glue::Model::JobRunState::FAILED) ||
                        (jobRunState == Aws::Glue::Model::JobRunState::TIMEOUT)) {
                        std::cerr << "Error running job. "
                                  << jobRun.GetErrorMessage()
                                  << std::endl;
                        deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, JOB_NAME,
                                     bucketName,
                                     clientConfig);
                        return false;
                    }
                    else if (jobRunState ==
                             Aws::Glue::Model::JobRunState::SUCCEEDED) {
                        std::cout << "Job run succeeded after  " << iterator <<
                                  " seconds elapsed." << std::endl;
                        done = true;
                    }
                    else if ((iterator % 10) == 0) { // Log status every 10 seconds.
                        std::cout << "Job run status " <<

Aws::Glue::Model::JobRunStateMapper::GetNameForJobRunState(
                                         jobRunState) <<
                                  ". " << iterator <<
                                  " seconds elapsed." << std::endl;
                    }
                }
                else {
                    std::cerr << "Error retrieving job run state. "
                              << jobRunOutcome.GetError().GetMessage()
                              << std::endl;
                    deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, JOB_NAME,
                                 bucketName, clientConfig);
                    return false;
                }
```

```
        }
    }
    else {
        std::cerr << "Error starting a job. " << outcome.GetError().GetMessage()
                  << std::endl;
        deleteAssets(CRAWLER_NAME, CRAWLER_DATABASE_NAME, JOB_NAME, bucketName,
                     clientConfig);
        return false;
    }
```

- For API details, see StartJobRun in *AWS SDK for C++ API Reference*.

HealthImaging examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with HealthImaging.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Scenarios are code examples that show you how to accomplish specific tasks by calling multiple functions within a service or combined with other AWS services.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Get started
- Actions
- Scenarios

Get started

Hello HealthImaging

The following code example shows how to get started using HealthImaging.

SDK for C++

Code for the CMakeLists.txt CMake file.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS medical-imaging)

# Set this project's name.
project("hello_health-imaging")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD AND AWSSDK_INSTALL_AS_SHARED_LIBS)
    # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

    # set(BIN_SUB_DIR "/Debug") # If you are building from the command line, you may
 need to uncomment this
    # and set the proper subdirectory to the executable location.

    AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_health_imaging.cpp)
```

```
target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Code for the hello_health_imaging.cpp source file.

```
#include <aws/core/Aws.h>
#include <aws/medical-imaging/MedicalImagingClient.h>
#include <aws/medical-imaging/model/ListDatastoresRequest.h>

#include <iostream>

/*
 *  A "Hello HealthImaging" starter application which initializes an AWS
 HealthImaging (HealthImaging) client
 *  and lists the HealthImaging data stores in the current account.
 *
 *  main function
 *
 *  Usage: 'hello_health-imaging'
 *
 */
#include <aws/core/auth/AWSCredentialsProviderChain.h>
#include <aws/core/platform/Environment.h>

int main(int argc, char **argv) {
    (void) argc;
    (void) argv;
    Aws::SDKOptions options;
    //   Optional: change the log level for debugging.
    //   options.loggingOptions.logLevel = Aws::Utils::Logging::LogLevel::Debug;

    Aws::InitAPI(options); // Should only be called once.
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::MedicalImaging::MedicalImagingClient
 medicalImagingClient(clientConfig);
        Aws::MedicalImaging::Model::ListDatastoresRequest listDatastoresRequest;
```

```
        Aws::Vector<Aws::MedicalImaging::Model::DatastoreSummary>
 allDataStoreSummaries;
        Aws::String nextToken; // Used for paginated results.
        do {
            if (!nextToken.empty()) {
                listDatastoresRequest.SetNextToken(nextToken);
            }
            Aws::MedicalImaging::Model::ListDatastoresOutcome listDatastoresOutcome
 =
                    medicalImagingClient.ListDatastores(listDatastoresRequest);
            if (listDatastoresOutcome.IsSuccess()) {
                const Aws::Vector<Aws::MedicalImaging::Model::DatastoreSummary>
 &dataStoreSummaries =
                        listDatastoresOutcome.GetResult().GetDatastoreSummaries();
                allDataStoreSummaries.insert(allDataStoreSummaries.cend(),
                                             dataStoreSummaries.cbegin(),
                                             dataStoreSummaries.cend());
                nextToken = listDatastoresOutcome.GetResult().GetNextToken();
            }
            else {
                std::cerr << "ListDatastores error: "
                          << listDatastoresOutcome.GetError().GetMessage() <<
 std::endl;
                break;
            }
        } while (!nextToken.empty());

        std::cout << allDataStoreSummaries.size() << " HealthImaging data "
                  << ((allDataStoreSummaries.size() == 1) ?
                      "store was retrieved." : "stores were retrieved.") <<
 std::endl;

        for (auto const &dataStoreSummary: allDataStoreSummaries) {
            std::cout << "  Datastore: " << dataStoreSummary.GetDatastoreName()
                      << std::endl;
            std::cout << "  Datastore ID: " << dataStoreSummary.GetDatastoreId()
                      << std::endl;
        }
    }

    Aws::ShutdownAPI(options); // Should only be called once.
    return 0;
}
```

- For API details, see ListDatastores in *AWS SDK for C++ API Reference*.

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Actions

`DeleteImageSet`

The following code example shows how to use `DeleteImageSet`.

SDK for C++

```
//! Routine which deletes an AWS HealthImaging image set.
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param imageSetID: The image set ID.
  \param clientConfig: Aws client configuration.
  \return bool: Function succeeded.
  */
bool AwsDoc::Medical_Imaging::deleteImageSet(
        const Aws::String &dataStoreID, const Aws::String &imageSetID,
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::MedicalImaging::MedicalImagingClient client(clientConfig);
    Aws::MedicalImaging::Model::DeleteImageSetRequest request;
    request.SetDatastoreId(dataStoreID);
    request.SetImageSetId(imageSetID);
    Aws::MedicalImaging::Model::DeleteImageSetOutcome outcome =
 client.DeleteImageSet(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted image set " << imageSetID
                  << " from data store " << dataStoreID << std::endl;
    }
    else {
        std::cerr << "Error deleting image set " << imageSetID << " from data store
 "
```

```
                  << dataStoreID << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DeleteImageSet in *AWS SDK for C++ API Reference*.

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

`GetDICOMImportJob`

The following code example shows how to use `GetDICOMImportJob`.

SDK for C++

```
//! Routine which gets a HealthImaging DICOM import job's properties.
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param importJobID: The DICOM import job ID
  \param clientConfig: Aws client configuration.
  \return GetDICOMImportJobOutcome: The import job outcome.
*/
Aws::MedicalImaging::Model::GetDICOMImportJobOutcome
AwsDoc::Medical_Imaging::getDICOMImportJob(const Aws::String &dataStoreID,
                                           const Aws::String &importJobID,
                                           const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::MedicalImaging::MedicalImagingClient client(clientConfig);
    Aws::MedicalImaging::Model::GetDICOMImportJobRequest request;
    request.SetDatastoreId(dataStoreID);
    request.SetJobId(importJobID);
    Aws::MedicalImaging::Model::GetDICOMImportJobOutcome outcome =
 client.GetDICOMImportJob(
            request);
    if (!outcome.IsSuccess()) {
```

```
        std::cerr << "GetDICOMImportJob error: "
                  << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome;
}
```

- For API details, see GetDICOMImportJob in *AWS SDK for C++ API Reference*.

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

`GetImageFrame`

The following code example shows how to use `GetImageFrame`.

SDK for C++

```
//! Routine which downloads an AWS HealthImaging image frame.
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param imageSetID: The image set ID.
  \param frameID: The image frame ID.
  \param jphFile: File to store the downloaded frame.
  \param clientConfig: Aws client configuration.
  \return bool: Function succeeded.
*/
bool AwsDoc::Medical_Imaging::getImageFrame(const Aws::String &dataStoreID,
                                            const Aws::String &imageSetID,
                                            const Aws::String &frameID,
                                            const Aws::String &jphFile,
                                            const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::MedicalImaging::MedicalImagingClient client(clientConfig);

    Aws::MedicalImaging::Model::GetImageFrameRequest request;
    request.SetDatastoreId(dataStoreID);
    request.SetImageSetId(imageSetID);
```

```
    Aws::MedicalImaging::Model::ImageFrameInformation imageFrameInformation;
    imageFrameInformation.SetImageFrameId(frameID);
    request.SetImageFrameInformation(imageFrameInformation);

    Aws::MedicalImaging::Model::GetImageFrameOutcome outcome = client.GetImageFrame(
            request);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully retrieved image frame." << std::endl;
        auto &buffer = outcome.GetResult().GetImageFrameBlob();

        std::ofstream outfile(jphFile, std::ios::binary);
        outfile << buffer.rdbuf();
    }
    else {
        std::cout << "Error retrieving image frame." <<
 outcome.GetError().GetMessage()
                  << std::endl;

    }

    return outcome.IsSuccess();
}
```

- For API details, see GetImageFrame in *AWS SDK for C++ API Reference*.

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

`GetImageSetMetadata`

The following code example shows how to use `GetImageSetMetadata`.

SDK for C++

Utility function to get image set metadata.

```
//! Routine which gets a HealthImaging image set's metadata.
```

```
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param imageSetID: The HealthImaging image set ID.
  \param versionID: The HealthImaging image set version ID, ignored if empty.
  \param outputFilePath: The path where the metadata will be stored as gzipped json.
  \param clientConfig: Aws client configuration.
  \\return bool: Function succeeded.
*/
bool AwsDoc::Medical_Imaging::getImageSetMetadata(const Aws::String &dataStoreID,
                                                  const Aws::String &imageSetID,
                                                  const Aws::String &versionID,
                                                  const Aws::String &outputFilePath,
                                                  const
 Aws::Client::ClientConfiguration &clientConfig) {
    Aws::MedicalImaging::Model::GetImageSetMetadataRequest request;
    request.SetDatastoreId(dataStoreID);
    request.SetImageSetId(imageSetID);
    if (!versionID.empty()) {
        request.SetVersionId(versionID);
    }
    Aws::MedicalImaging::MedicalImagingClient client(clientConfig);
    Aws::MedicalImaging::Model::GetImageSetMetadataOutcome outcome =
 client.GetImageSetMetadata(
            request);
    if (outcome.IsSuccess()) {
        std::ofstream file(outputFilePath, std::ios::binary);
        auto &metadata = outcome.GetResult().GetImageSetMetadataBlob();
        file << metadata.rdbuf();
    }
    else {
        std::cerr << "Failed to get image set metadata: "
                  << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

Get image set metadata without version.

```
        if (AwsDoc::Medical_Imaging::getImageSetMetadata(dataStoreID, imageSetID,
 "", outputFilePath, clientConfig))
        {
```

```
            std::cout << "Successfully retrieved image set metadata." << std::endl;
            std::cout << "Metadata stored in: " << outputFilePath << std::endl;
        }
```

Get image set metadata with version.

```
        if (AwsDoc::Medical_Imaging::getImageSetMetadata(dataStoreID, imageSetID,
 versionID, outputFilePath, clientConfig))
        {
            std::cout << "Successfully retrieved image set metadata." << std::endl;
            std::cout << "Metadata stored in: " << outputFilePath << std::endl;
        }
```

- For API details, see GetImageSetMetadata in *AWS SDK for C++ API Reference*.

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

`SearchImageSets`

The following code example shows how to use `SearchImageSets`.

SDK for C++

The utility function for searching image sets.

```
//! Routine which searches for image sets based on defined input attributes.
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param searchCriteria: A search criteria instance.
  \param imageSetResults: Vector to receive the image set IDs.
  \param clientConfig: Aws client configuration.
  \return bool: Function succeeded.
  */
bool AwsDoc::Medical_Imaging::searchImageSets(const Aws::String &dataStoreID,
                                              const
 Aws::MedicalImaging::Model::SearchCriteria &searchCriteria,
```

```
                                                Aws::Vector<Aws::String>
 &imageSetResults,
                                                const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::MedicalImaging::MedicalImagingClient client(clientConfig);
    Aws::MedicalImaging::Model::SearchImageSetsRequest request;
    request.SetDatastoreId(dataStoreID);
    request.SetSearchCriteria(searchCriteria);

    Aws::String nextToken; // Used for paginated results.
    bool result = true;
    do {
        if (!nextToken.empty()) {
            request.SetNextToken(nextToken);
        }

        Aws::MedicalImaging::Model::SearchImageSetsOutcome outcome =
 client.SearchImageSets(
                request);
        if (outcome.IsSuccess()) {
            for (auto &imageSetMetadataSummary:
 outcome.GetResult().GetImageSetsMetadataSummaries()) {
                imageSetResults.push_back(imageSetMetadataSummary.GetImageSetId());
            }

            nextToken = outcome.GetResult().GetNextToken();
        }
        else {
            std::cout << "Error: " << outcome.GetError().GetMessage() << std::endl;
            result = false;
        }
    } while (!nextToken.empty());

    return result;
}
```

Use case #1: EQUAL operator.

```
        Aws::Vector<Aws::String> imageIDsForPatientID;
        Aws::MedicalImaging::Model::SearchCriteria searchCriteriaEqualsPatientID;
        Aws::Vector<Aws::MedicalImaging::Model::SearchFilter> patientIDSearchFilters
 = {
```

```
 Aws::MedicalImaging::Model::SearchFilter().WithOperator(Aws::MedicalImaging::Model::Operato

 .WithValues({Aws::MedicalImaging::Model::SearchByAttributeValue().WithDICOMPatientId(patien
        };

        searchCriteriaEqualsPatientID.SetFilters(patientIDSearchFilters);
        bool result = AwsDoc::Medical_Imaging::searchImageSets(dataStoreID,

 searchCriteriaEqualsPatientID,
                                                                imageIDsForPatientID,
                                                                clientConfig);
        if (result) {
            std::cout << imageIDsForPatientID.size() << " image sets found for the
 patient with ID '"
            <<  patientID << "'." << std::endl;
            for (auto &imageSetResult : imageIDsForPatientID) {
                std::cout << "  Image set with ID '" << imageSetResult << std::endl;
            }
        }
```

Use case #2: BETWEEN operator using DICOMStudyDate and DICOMStudyTime.

```
         Aws::MedicalImaging::Model::SearchByAttributeValue useCase2StartDate;

 useCase2StartDate.SetDICOMStudyDateAndTime(Aws::MedicalImaging::Model::DICOMStudyDateAndTim
        .WithDICOMStudyDate("19990101")
        .WithDICOMStudyTime("000000.000"));

        Aws::MedicalImaging::Model::SearchByAttributeValue useCase2EndDate;

 useCase2EndDate.SetDICOMStudyDateAndTime(Aws::MedicalImaging::Model::DICOMStudyDateAndTime(

 .WithDICOMStudyDate(Aws::Utils::DateTime(std::chrono::system_clock::now()).ToLocalTimeStrin
%m%d"))
        .WithDICOMStudyTime("000000.000"));

        Aws::MedicalImaging::Model::SearchFilter useCase2SearchFilter;
        useCase2SearchFilter.SetValues({useCase2StartDate, useCase2EndDate});

 useCase2SearchFilter.SetOperator(Aws::MedicalImaging::Model::Operator::BETWEEN);
```

```
        Aws::MedicalImaging::Model::SearchCriteria useCase2SearchCriteria;
        useCase2SearchCriteria.SetFilters({useCase2SearchFilter});

        Aws::Vector<Aws::String> usesCase2Results;
        result = AwsDoc::Medical_Imaging::searchImageSets(dataStoreID,
                                                          useCase2SearchCriteria,
                                                          usesCase2Results,
                                                          clientConfig);
        if (result) {
            std::cout << usesCase2Results.size() << " image sets found for between
1999/01/01 and present."
                      <<  std::endl;
            for (auto &imageSetResult : usesCase2Results) {
                std::cout << "  Image set with ID '" << imageSetResult << std::endl;
            }
        }
```

Use case #3: BETWEEN operator using createdAt. Time studies were previously persisted.

```
        Aws::MedicalImaging::Model::SearchByAttributeValue useCase3StartDate;

useCase3StartDate.SetCreatedAt(Aws::Utils::DateTime("20231130T000000000Z",Aws::Utils::DateF

        Aws::MedicalImaging::Model::SearchByAttributeValue useCase3EndDate;

useCase3EndDate.SetCreatedAt(Aws::Utils::DateTime(std::chrono::system_clock::now()));

        Aws::MedicalImaging::Model::SearchFilter useCase3SearchFilter;
        useCase3SearchFilter.SetValues({useCase3StartDate, useCase3EndDate});

useCase3SearchFilter.SetOperator(Aws::MedicalImaging::Model::Operator::BETWEEN);

        Aws::MedicalImaging::Model::SearchCriteria useCase3SearchCriteria;
        useCase3SearchCriteria.SetFilters({useCase3SearchFilter});

        Aws::Vector<Aws::String> usesCase3Results;
        result = AwsDoc::Medical_Imaging::searchImageSets(dataStoreID,
                                                          useCase3SearchCriteria,
                                                          usesCase3Results,
                                                          clientConfig);
        if (result) {
```

```
            std::cout << usesCase3Results.size() << " image sets found for created
between 2023/11/30 and present."
                      <<  std::endl;
            for (auto &imageSetResult : usesCase3Results) {
                std::cout << "  Image set with ID '" << imageSetResult << std::endl;
            }
        }
```

Use case #4: EQUAL operator on DICOMSeriesInstanceUID and BETWEEN on updatedAt and sort response in ASC order on updatedAt field.

```
        Aws::MedicalImaging::Model::SearchByAttributeValue useCase4StartDate;

useCase4StartDate.SetUpdatedAt(Aws::Utils::DateTime("20231130T000000000Z",Aws::Utils::DateF

        Aws::MedicalImaging::Model::SearchByAttributeValue useCase4EndDate;

useCase4EndDate.SetUpdatedAt(Aws::Utils::DateTime(std::chrono::system_clock::now()));

        Aws::MedicalImaging::Model::SearchFilter useCase4SearchFilterBetween;
        useCase4SearchFilterBetween.SetValues({useCase4StartDate, useCase4EndDate});

useCase4SearchFilterBetween.SetOperator(Aws::MedicalImaging::Model::Operator::BETWEEN);

        Aws::MedicalImaging::Model::SearchByAttributeValue seriesInstanceUID;
        seriesInstanceUID.SetDICOMSeriesInstanceUID(dicomSeriesInstanceUID);

        Aws::MedicalImaging::Model::SearchFilter useCase4SearchFilterEqual;
        useCase4SearchFilterEqual.SetValues({seriesInstanceUID});

useCase4SearchFilterEqual.SetOperator(Aws::MedicalImaging::Model::Operator::EQUAL);

        Aws::MedicalImaging::Model::SearchCriteria useCase4SearchCriteria;
        useCase4SearchCriteria.SetFilters({useCase4SearchFilterBetween,
useCase4SearchFilterEqual});

        Aws::MedicalImaging::Model::Sort useCase4Sort;
        useCase4Sort.SetSortField(Aws::MedicalImaging::Model::SortField::updatedAt);
        useCase4Sort.SetSortOrder(Aws::MedicalImaging::Model::SortOrder::ASC);

        useCase4SearchCriteria.SetSort(useCase4Sort);
```

```
        Aws::Vector<Aws::String> usesCase4Results;
        result = AwsDoc::Medical_Imaging::searchImageSets(dataStoreID,
                                                          useCase4SearchCriteria,
                                                          usesCase4Results,
                                                          clientConfig);
        if (result) {
            std::cout << usesCase4Results.size() << " image sets found for EQUAL
 operator "
            << "on DICOMSeriesInstanceUID and BETWEEN on updatedAt and sort response
\n"
            <<  "in ASC order on updatedAt field." <<  std::endl;
            for (auto &imageSetResult : usesCase4Results) {
                std::cout << "  Image set with ID '" << imageSetResult << std::endl;
            }
        }
```

- For API details, see SearchImageSets in *AWS SDK for C++ API Reference*.

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

`StartDICOMImportJob`

The following code example shows how to use `StartDICOMImportJob`.

SDK for C++

```
//! Routine which starts a HealthImaging import job.
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param inputBucketName: The name of the Amazon S3 bucket containing the DICOM
 files.
  \param inputDirectory: The directory in the S3 bucket containing the DICOM files.
  \param outputBucketName: The name of the S3 bucket for the output.
  \param outputDirectory: The directory in the S3 bucket to store the output.
  \param roleArn: The ARN of the IAM role with permissions for the import.
  \param importJobId: A string to receive the import job ID.
  \param clientConfig: Aws client configuration.
  \return bool: Function succeeded.
```

```
  */
bool AwsDoc::Medical_Imaging::startDICOMImportJob(
        const Aws::String &dataStoreID, const Aws::String &inputBucketName,
        const Aws::String &inputDirectory, const Aws::String &outputBucketName,
        const Aws::String &outputDirectory, const Aws::String &roleArn,
        Aws::String &importJobId,
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::MedicalImaging::MedicalImagingClient medicalImagingClient(clientConfig);
    Aws::String inputURI = "s3://" + inputBucketName + "/" + inputDirectory + "/";
    Aws::String outputURI = "s3://" + outputBucketName + "/" + outputDirectory +
 "/";
    Aws::MedicalImaging::Model::StartDICOMImportJobRequest
 startDICOMImportJobRequest;
    startDICOMImportJobRequest.SetDatastoreId(dataStoreID);
    startDICOMImportJobRequest.SetDataAccessRoleArn(roleArn);
    startDICOMImportJobRequest.SetInputS3Uri(inputURI);
    startDICOMImportJobRequest.SetOutputS3Uri(outputURI);

    Aws::MedicalImaging::Model::StartDICOMImportJobOutcome
 startDICOMImportJobOutcome = medicalImagingClient.StartDICOMImportJob(
            startDICOMImportJobRequest);

    if (startDICOMImportJobOutcome.IsSuccess()) {
        importJobId = startDICOMImportJobOutcome.GetResult().GetJobId();
    }
    else {
        std::cerr << "Failed to start DICOM import job because "
                  << startDICOMImportJobOutcome.GetError().GetMessage() <<
 std::endl;
    }

    return startDICOMImportJobOutcome.IsSuccess();
}
```

- For API details, see StartDICOMImportJob in *AWS SDK for C++ API Reference*.

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Scenarios

Get started with image sets and image frames

The following code example shows how to import DICOM files and download image frames in HealthImaging.

The implementation is structured as a command-line application.

- Set up resources for a DICOM import.
- Import DICOM files into a data store.
- Retrieve the image set IDs for the import job.
- Retrieve the image frame IDs for the image sets.
- Download, decode and verify the image frames.
- Clean up resources.

SDK for C++

Create an CloudFormation stack with the necessary resources.

```
    Aws::String inputBucketName;
    Aws::String outputBucketName;
    Aws::String dataStoreId;
    Aws::String roleArn;
    Aws::String stackName;

    if (askYesNoQuestion(
            "Would you like to let this workflow create the resources for you? (y/n)
")) {
        stackName = askQuestion(
                "Enter a name for the AWS CloudFormation stack to create. ");
        Aws::String dataStoreName = askQuestion(
                "Enter a name for the HealthImaging datastore to create. ");

        Aws::Map<Aws::String, Aws::String> outputs = createCloudFormationStack(
                stackName,
                dataStoreName,
                clientConfiguration);
```

```
       if (!retrieveOutputs(outputs, dataStoreId, inputBucketName,
outputBucketName,
                            roleArn)) {
           return false;
       }

       std::cout << "The following resources have been created." << std::endl;
       std::cout << "A HealthImaging datastore with ID: " << dataStoreId << "."
                 << std::endl;
       std::cout << "An Amazon S3 input bucket named: " << inputBucketName << "."
                 << std::endl;
       std::cout << "An Amazon S3 output bucket named: " << outputBucketName << "."
                 << std::endl;
       std::cout << "An IAM role with the ARN: " << roleArn << "." << std::endl;
       askQuestion("Enter return to continue.", alwaysTrueTest);
   }
   else {
       std::cout << "You have chosen to use preexisting resources:" << std::endl;
       dataStoreId = askQuestion(
               "Enter the data store ID of the HealthImaging datastore you wish to
use: ");
       inputBucketName = askQuestion(
               "Enter the name of the S3 input bucket you wish to use: ");
       outputBucketName = askQuestion(
               "Enter the name of the S3 output bucket you wish to use: ");
       roleArn = askQuestion(
               "Enter the ARN for the IAM role with the proper permissions to
import a DICOM series: ");
   }
```

Copy DICOM files to the Amazon S3 import bucket.

```
   std::cout
           << "This workflow uses DICOM files from the National Cancer Institute
Imaging Data\n"
           << "Commons (IDC) Collections." << std::endl;
   std::cout << "Here is the link to their website." << std::endl;
   std::cout << "https://registry.opendata.aws/nci-imaging-data-commons/" <<
std::endl;
   std::cout << "We will use DICOM files stored in an S3 bucket managed by the
IDC."
             << std::endl;
```

```
    std::cout
            << "First one of the DICOM folders in the IDC collection must be copied
 to your\n"
               "input S3 bucket."
            << std::endl;
    std::cout << "You have the choice of one of the following "
              << IDC_ImageChoices.size() << " folders to copy." << std::endl;

    int index = 1;
    for (auto &idcChoice: IDC_ImageChoices) {
        std::cout << index << " - " << idcChoice.mDescription << std::endl;
        index++;
    }
    int choice = askQuestionForIntRange("Choose DICOM files to import: ", 1, 4);

    Aws::String fromDirectory = IDC_ImageChoices[choice - 1].mDirectory;
    Aws::String inputDirectory = "input";

    std::cout << "The files in the directory '" << fromDirectory << "' in the bucket
 '"
              << IDC_S3_BucketName << "' will be copied " << std::endl;
    std::cout << "to the folder '" << inputDirectory << "/" << fromDirectory
              << "' in the bucket '" << inputBucketName << "'." << std::endl;
    askQuestion("Enter return to start the copy.", alwaysTrueTest);

    if (!AwsDoc::Medical_Imaging::copySeriesBetweenBuckets(
            IDC_S3_BucketName,
            fromDirectory,
            inputBucketName,
            inputDirectory, clientConfiguration)) {
        std::cerr << "This workflow will exit because of an error." << std::endl;
        cleanup(stackName, dataStoreId, clientConfiguration);
        return false;
    }
```

Import the DICOM files to the Amazon S3 data store.

```
bool AwsDoc::Medical_Imaging::startDicomImport(const Aws::String &dataStoreID,
                                               const Aws::String &inputBucketName,
                                               const Aws::String &inputDirectory,
                                               const Aws::String &outputBucketName,
                                               const Aws::String &outputDirectory,
```

```
                                                const Aws::String &roleArn,
                                                Aws::String &importJobId,
                                                const
 Aws::Client::ClientConfiguration &clientConfiguration) {
    bool result = false;
    if (startDICOMImportJob(dataStoreID, inputBucketName, inputDirectory,
                            outputBucketName, outputDirectory, roleArn, importJobId,
                            clientConfiguration)) {
        std::cout << "DICOM import job started with job ID " << importJobId << "."
                  << std::endl;
        result = waitImportJobCompleted(dataStoreID, importJobId,
 clientConfiguration);
        if (result) {
            std::cout << "DICOM import job completed." << std::endl;

        }
    }

    return result;
}

//! Routine which starts a HealthImaging import job.
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param inputBucketName: The name of the Amazon S3 bucket containing the DICOM
 files.
  \param inputDirectory: The directory in the S3 bucket containing the DICOM files.
  \param outputBucketName: The name of the S3 bucket for the output.
  \param outputDirectory: The directory in the S3 bucket to store the output.
  \param roleArn: The ARN of the IAM role with permissions for the import.
  \param importJobId: A string to receive the import job ID.
  \param clientConfig: Aws client configuration.
  \return bool: Function succeeded.
  */
bool AwsDoc::Medical_Imaging::startDICOMImportJob(
        const Aws::String &dataStoreID, const Aws::String &inputBucketName,
        const Aws::String &inputDirectory, const Aws::String &outputBucketName,
        const Aws::String &outputDirectory, const Aws::String &roleArn,
        Aws::String &importJobId,
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::MedicalImaging::MedicalImagingClient medicalImagingClient(clientConfig);
    Aws::String inputURI = "s3://" + inputBucketName + "/" + inputDirectory + "/";
    Aws::String outputURI = "s3://" + outputBucketName + "/" + outputDirectory +
 "/";
```

```
    Aws::MedicalImaging::Model::StartDICOMImportJobRequest
 startDICOMImportJobRequest;
    startDICOMImportJobRequest.SetDatastoreId(dataStoreID);
    startDICOMImportJobRequest.SetDataAccessRoleArn(roleArn);
    startDICOMImportJobRequest.SetInputS3Uri(inputURI);
    startDICOMImportJobRequest.SetOutputS3Uri(outputURI);

    Aws::MedicalImaging::Model::StartDICOMImportJobOutcome
 startDICOMImportJobOutcome = medicalImagingClient.StartDICOMImportJob(
            startDICOMImportJobRequest);

    if (startDICOMImportJobOutcome.IsSuccess()) {
        importJobId = startDICOMImportJobOutcome.GetResult().GetJobId();
    }
    else {
        std::cerr << "Failed to start DICOM import job because "
                  << startDICOMImportJobOutcome.GetError().GetMessage() <<
 std::endl;
    }

    return startDICOMImportJobOutcome.IsSuccess();
}


//! Routine which waits for a DICOM import job to complete.
/*!
 * @param dataStoreID: The HealthImaging data store ID.
 * @param importJobId: The import job ID.
 * @param clientConfiguration : Aws client configuration.
 * @return  bool: Function succeeded.
 */
bool AwsDoc::Medical_Imaging::waitImportJobCompleted(const Aws::String &datastoreID,
                                                     const Aws::String &importJobId,
                                                     const
 Aws::Client::ClientConfiguration &clientConfiguration) {

    Aws::MedicalImaging::Model::JobStatus jobStatus =
 Aws::MedicalImaging::Model::JobStatus::IN_PROGRESS;
    while (jobStatus == Aws::MedicalImaging::Model::JobStatus::IN_PROGRESS) {
        std::this_thread::sleep_for(std::chrono::seconds(1));

        Aws::MedicalImaging::Model::GetDICOMImportJobOutcome
 getDicomImportJobOutcome = getDICOMImportJob(
                datastoreID, importJobId,
```

```
                clientConfiguration);

        if (getDicomImportJobOutcome.IsSuccess()) {
            jobStatus =
 getDicomImportJobOutcome.GetResult().GetJobProperties().GetJobStatus();

            std::cout << "DICOM import job status: " <<

 Aws::MedicalImaging::Model::JobStatusMapper::GetNameForJobStatus(
                              jobStatus) << std::endl;
        }
        else {
            std::cerr << "Failed to get import job status because "
                      << getDicomImportJobOutcome.GetError().GetMessage() <<
 std::endl;
            return false;
        }
    }

    return jobStatus == Aws::MedicalImaging::Model::JobStatus::COMPLETED;
}

//! Routine which gets a HealthImaging DICOM import job's properties.
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param importJobID: The DICOM import job ID
  \param clientConfig: Aws client configuration.
  \return GetDICOMImportJobOutcome: The import job outcome.
*/
Aws::MedicalImaging::Model::GetDICOMImportJobOutcome
AwsDoc::Medical_Imaging::getDICOMImportJob(const Aws::String &dataStoreID,
                                           const Aws::String &importJobID,
                                           const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::MedicalImaging::MedicalImagingClient client(clientConfig);
    Aws::MedicalImaging::Model::GetDICOMImportJobRequest request;
    request.SetDatastoreId(dataStoreID);
    request.SetJobId(importJobID);
    Aws::MedicalImaging::Model::GetDICOMImportJobOutcome outcome =
 client.GetDICOMImportJob(
            request);
    if (!outcome.IsSuccess()) {
        std::cerr << "GetDICOMImportJob error: "
                  << outcome.GetError().GetMessage() << std::endl;
```

```
    }

    return outcome;
}
```

Get image sets created by the DICOM import job.

```
bool
AwsDoc::Medical_Imaging::getImageSetsForDicomImportJob(const Aws::String
 &datastoreID,
                                                       const Aws::String
 &importJobId,
                                                       Aws::Vector<Aws::String>
 &imageSets,
                                                       const
 Aws::Client::ClientConfiguration &clientConfiguration) {
   Aws::MedicalImaging::Model::GetDICOMImportJobOutcome getDicomImportJobOutcome =
 getDICOMImportJob(
           datastoreID, importJobId, clientConfiguration);
   bool result = false;
   if (getDicomImportJobOutcome.IsSuccess()) {
       auto outputURI =
 getDicomImportJobOutcome.GetResult().GetJobProperties().GetOutputS3Uri();
       Aws::Http::URI uri(outputURI);
       const Aws::String &bucket = uri.GetAuthority();
       Aws::String key = uri.GetPath();

       Aws::S3::S3Client s3Client(clientConfiguration);
       Aws::S3::Model::GetObjectRequest objectRequest;
       objectRequest.SetBucket(bucket);
       objectRequest.SetKey(key + "/" + IMPORT_JOB_MANIFEST_FILE_NAME);

       auto getObjectOutcome = s3Client.GetObject(objectRequest);
       if (getObjectOutcome.IsSuccess()) {
           auto &data = getObjectOutcome.GetResult().GetBody();

           std::stringstream stringStream;
           stringStream << data.rdbuf();

           try {
               // Use JMESPath to extract the image set IDs.
               // https://jmespath.org/specification.html
```

```
                std::string jmesPathExpression =
 "jobSummary.imageSetsSummary[].imageSetId";
                jsoncons::json doc = jsoncons::json::parse(stringStream.str());

                jsoncons::json imageSetsJson = jsoncons::jmespath::search(doc,

 jmesPathExpression);\
                for (auto &imageSet: imageSetsJson.array_range()) {
                    imageSets.push_back(imageSet.as_string());
                }

                result = true;
            }
            catch (const std::exception &e) {
                std::cerr << e.what() << '\n';
            }

        }
        else {
            std::cerr << "Failed to get object because "
                      << getObjectOutcome.GetError().GetMessage() << std::endl;
        }

    }
    else {
        std::cerr << "Failed to get import job status because "
                  << getDicomImportJobOutcome.GetError().GetMessage() << std::endl;
    }

    return result;
}
```

Get image frame information for image sets.

```
bool AwsDoc::Medical_Imaging::getImageFramesForImageSet(const Aws::String
 &dataStoreID,
                                                        const Aws::String
 &imageSetID,
                                                        const Aws::String
 &outDirectory,
                                                        Aws::Vector<ImageFrameInfo>
 &imageFrames,
```

```
                                                        const
Aws::Client::ClientConfiguration &clientConfiguration) {
   Aws::String fileName = outDirectory + "/" + imageSetID + "_metadata.json.gzip";
   bool result = false;
   if (getImageSetMetadata(dataStoreID, imageSetID, "", // Empty string for version
ID.
                           fileName, clientConfiguration)) {
       try {
           std::string metadataGZip;
           {
               std::ifstream inFileStream(fileName.c_str(), std::ios::binary);
               if (!inFileStream) {
                   throw std::runtime_error("Failed to open file " + fileName);
               }

               std::stringstream stringStream;
               stringStream << inFileStream.rdbuf();
               metadataGZip = stringStream.str();
           }
           std::string metadataJson = gzip::decompress(metadataGZip.data(),
                                                       metadataGZip.size());
           // Use JMESPath to extract the image set IDs.
           // https://jmespath.org/specification.html
           jsoncons::json doc = jsoncons::json::parse(metadataJson);
           std::string jmesPathExpression = "Study.Series.*.Instances[].*[]";
           jsoncons::json instances = jsoncons::jmespath::search(doc,

jmesPathExpression);
           for (auto &instance: instances.array_range()) {
               jmesPathExpression = "DICOM.RescaleSlope";
               std::string rescaleSlope = jsoncons::jmespath::search(instance,

jmesPathExpression).to_string();
               jmesPathExpression = "DICOM.RescaleIntercept";
               std::string rescaleIntercept = jsoncons::jmespath::search(instance,

jmesPathExpression).to_string();

               jmesPathExpression = "ImageFrames[][]";
               jsoncons::json imageFramesJson =
jsoncons::jmespath::search(instance,

jmesPathExpression);
```

```
                for (auto &imageFrame: imageFramesJson.array_range()) {
                    ImageFrameInfo imageFrameIDs;
                    imageFrameIDs.mImageSetId = imageSetID;
                    imageFrameIDs.mImageFrameId = imageFrame.find(
                            "ID")->value().as_string();
                    imageFrameIDs.mRescaleIntercept = rescaleIntercept;
                    imageFrameIDs.mRescaleSlope = rescaleSlope;
                    imageFrameIDs.MinPixelValue = imageFrame.find(
                            "MinPixelValue")->value().as_string();
                    imageFrameIDs.MaxPixelValue = imageFrame.find(
                            "MaxPixelValue")->value().as_string();

                    jmesPathExpression =
 "max_by(PixelDataChecksumFromBaseToFullResolution, &Width).Checksum";
                    jsoncons::json checksumJson =
 jsoncons::jmespath::search(imageFrame,

 jmesPathExpression);
                    imageFrameIDs.mFullResolutionChecksum =
 checksumJson.as_integer<uint32_t>();

                    imageFrames.emplace_back(imageFrameIDs);
                }
            }

            result = true;
        }
        catch (const std::exception &e) {
            std::cerr << "getImageFramesForImageSet failed because " << e.what()
                      << std::endl;
        }
    }

    return result;
}

//! Routine which gets a HealthImaging image set's metadata.
/*!
  \param dataStoreID: The HealthImaging data store ID.
  \param imageSetID: The HealthImaging image set ID.
  \param versionID: The HealthImaging image set version ID, ignored if empty.
  \param outputFilePath: The path where the metadata will be stored as gzipped json.
  \param clientConfig: Aws client configuration.
  \\return bool: Function succeeded.
```

```
*/
bool AwsDoc::Medical_Imaging::getImageSetMetadata(const Aws::String &dataStoreID,
                                                  const Aws::String &imageSetID,
                                                  const Aws::String &versionID,
                                                  const Aws::String &outputFilePath,
                                                  const
 Aws::Client::ClientConfiguration &clientConfig) {
    Aws::MedicalImaging::Model::GetImageSetMetadataRequest request;
    request.SetDatastoreId(dataStoreID);
    request.SetImageSetId(imageSetID);
    if (!versionID.empty()) {
        request.SetVersionId(versionID);
    }
    Aws::MedicalImaging::MedicalImagingClient client(clientConfig);
    Aws::MedicalImaging::Model::GetImageSetMetadataOutcome outcome =
 client.GetImageSetMetadata(
            request);
    if (outcome.IsSuccess()) {
        std::ofstream file(outputFilePath, std::ios::binary);
        auto &metadata = outcome.GetResult().GetImageSetMetadataBlob();
        file << metadata.rdbuf();
    }
    else {
        std::cerr << "Failed to get image set metadata: "
                  << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

Download, decode and verify image frames.

```
bool AwsDoc::Medical_Imaging::downloadDecodeAndCheckImageFrames(
        const Aws::String &dataStoreID,
        const Aws::Vector<ImageFrameInfo> &imageFrames,
        const Aws::String &outDirectory,
        const Aws::Client::ClientConfiguration &clientConfiguration) {

    Aws::Client::ClientConfiguration clientConfiguration1(clientConfiguration);
    clientConfiguration1.executor =
 Aws::MakeShared<Aws::Utils::Threading::PooledThreadExecutor>(
            "executor", 25);
```

```
    Aws::MedicalImaging::MedicalImagingClient medicalImagingClient(
            clientConfiguration1);

    Aws::Utils::Threading::Semaphore semaphore(0, 1);
    std::atomic<size_t> count(imageFrames.size());

    bool result = true;
    for (auto &imageFrame: imageFrames) {
        Aws::MedicalImaging::Model::GetImageFrameRequest getImageFrameRequest;
        getImageFrameRequest.SetDatastoreId(dataStoreID);
        getImageFrameRequest.SetImageSetId(imageFrame.mImageSetId);

        Aws::MedicalImaging::Model::ImageFrameInformation imageFrameInformation;
        imageFrameInformation.SetImageFrameId(imageFrame.mImageFrameId);
        getImageFrameRequest.SetImageFrameInformation(imageFrameInformation);

        auto getImageFrameAsyncLambda = [&semaphore, &result, &count, imageFrame,
outDirectory](
                const Aws::MedicalImaging::MedicalImagingClient *client,
                const Aws::MedicalImaging::Model::GetImageFrameRequest &request,
                Aws::MedicalImaging::Model::GetImageFrameOutcome outcome,
                const std::shared_ptr<const Aws::Client::AsyncCallerContext>
&context) {

                if (!handleGetImageFrameResult(outcome, outDirectory, imageFrame)) {
                    std::cerr << "Failed to download and convert image frame: "
                              << imageFrame.mImageFrameId << " from image set: "
                              << imageFrame.mImageSetId << std::endl;
                    result = false;
                }

                count--;
                if (count <= 0) {

                    semaphore.ReleaseAll();
                }
        }; // End of 'getImageFrameAsyncLambda' lambda.

        medicalImagingClient.GetImageFrameAsync(getImageFrameRequest,
                                                getImageFrameAsyncLambda);
    }

    if (count > 0) {
        semaphore.WaitOne();
```

```
    }

    if (result) {
        std::cout << imageFrames.size() << " image files were downloaded."
                  << std::endl;
    }

    return result;
}

bool AwsDoc::Medical_Imaging::decodeJPHFileAndValidateWithChecksum(
        const Aws::String &jphFile,
        uint32_t crc32Checksum) {
    opj_image_t *outputImage = jphImageToOpjBitmap(jphFile);
    if (!outputImage) {
        return false;
    }

    bool result = true;
    if (!verifyChecksumForImage(outputImage, crc32Checksum)) {
        std::cerr << "The checksum for the image does not match the expected value."
                  << std::endl;
        std::cerr << "File :" << jphFile << std::endl;
        result = false;
    }

    opj_image_destroy(outputImage);

    return result;
}

opj_image *
AwsDoc::Medical_Imaging::jphImageToOpjBitmap(const Aws::String &jphFile) {
    opj_stream_t *inFileStream = nullptr;
    opj_codec_t *decompressorCodec = nullptr;
    opj_image_t *outputImage = nullptr;
    try {
        std::shared_ptr<opj_dparameters> decodeParameters =
 std::make_shared<opj_dparameters>();
        memset(decodeParameters.get(), 0, sizeof(opj_dparameters));

        opj_set_default_decoder_parameters(decodeParameters.get());

        decodeParameters->decod_format = 1; // JP2 image format.
```

```
        decodeParameters->cod_format = 2; // BMP image format.

        std::strncpy(decodeParameters->infile, jphFile.c_str(),
                     OPJ_PATH_LEN);

        inFileStream = opj_stream_create_default_file_stream(
                decodeParameters->infile, true);
        if (!inFileStream) {
            throw std::runtime_error(
                    "Unable to create input file stream for file '" + jphFile +
"'.");
        }

        decompressorCodec = opj_create_decompress(OPJ_CODEC_JP2);
        if (!decompressorCodec) {
            throw std::runtime_error("Failed to create decompression codec.");
        }

        int decodeMessageLevel = 1;
        if (!setupCodecLogging(decompressorCodec, &decodeMessageLevel)) {
            std::cerr << "Failed to setup codec logging." << std::endl;
        }

        if (!opj_setup_decoder(decompressorCodec, decodeParameters.get())) {
            throw std::runtime_error("Failed to setup decompression codec.");
        }
        if (!opj_codec_set_threads(decompressorCodec, 4)) {
            throw std::runtime_error("Failed to set decompression codec threads.");
        }

        if (!opj_read_header(inFileStream, decompressorCodec, &outputImage)) {
            throw std::runtime_error("Failed to read header.");
        }

        if (!opj_decode(decompressorCodec, inFileStream,
                        outputImage)) {
            throw std::runtime_error("Failed to decode.");
        }

        if (DEBUGGING) {
            std::cout << "image width : " << outputImage->x1 - outputImage->x0
                      << std::endl;
            std::cout << "image height : " << outputImage->y1 - outputImage->y0
                      << std::endl;
```

```
            std::cout << "number of channels: " << outputImage->numcomps
                      << std::endl;
            std::cout << "colorspace : " << outputImage->color_space << std::endl;
        }

    } catch (const std::exception &e) {
        std::cerr << e.what() << std::endl;
        if (outputImage) {
            opj_image_destroy(outputImage);
            outputImage = nullptr;
        }
    }
    if (inFileStream) {
        opj_stream_destroy(inFileStream);
    }
    if (decompressorCodec) {
        opj_destroy_codec(decompressorCodec);
    }

    return outputImage;
}

//! Template function which converts a planar image bitmap to an interleaved image
 bitmap and
//! then verifies the checksum of the bitmap.
/*!
 * @param image: The OpenJPEG image struct.
 * @param crc32Checksum: The CRC32 checksum.
 * @return  bool: Function succeeded.
 */
template<class myType>
bool verifyChecksumForImageForType(opj_image_t *image, uint32_t crc32Checksum) {
    uint32_t width = image->x1 - image->x0;
    uint32_t height = image->y1 - image->y0;
    uint32_t numOfChannels = image->numcomps;

    // Buffer for interleaved bitmap.
    std::vector<myType> buffer(width * height * numOfChannels);

    // Convert planar bitmap to interleaved bitmap.
    for (uint32_t channel = 0; channel < numOfChannels; channel++) {
        for (uint32_t row = 0; row < height; row++) {
            uint32_t fromRowStart = row / image->comps[channel].dy * width /
                                    image->comps[channel].dx;
```

```
            uint32_t toIndex = (row * width) * numOfChannels + channel;

            for (uint32_t col = 0; col < width; col++) {
                uint32_t fromIndex = fromRowStart + col / image->comps[channel].dx;

                buffer[toIndex] = static_cast<myType>(image-
>comps[channel].data[fromIndex]);

                toIndex += numOfChannels;
            }
        }
    }

    // Verify checksum.
    boost::crc_32_type crc32;
    crc32.process_bytes(reinterpret_cast<char *>(buffer.data()),
                        buffer.size() * sizeof(myType));

    bool result = crc32.checksum() == crc32Checksum;
    if (!result) {
        std::cerr << "verifyChecksumForImage, checksum mismatch, expected - "
                  << crc32Checksum << ", actual - " << crc32.checksum()
                  << std::endl;
    }

    return result;
}

//! Routine which verifies the checksum of an OpenJPEG image struct.
/*!
 * @param image: The OpenJPEG image struct.
 * @param crc32Checksum: The CRC32 checksum.
 * @return  bool: Function succeeded.
 */
bool AwsDoc::Medical_Imaging::verifyChecksumForImage(opj_image_t *image,
                                                     uint32_t crc32Checksum) {
    uint32_t channels = image->numcomps;
    bool result = false;
    if (0 < channels) {
        // Assume the precision is the same for all channels.
        uint32_t precision = image->comps[0].prec;
        bool signedData = image->comps[0].sgnd;
        uint32_t bytes = (precision + 7) / 8;
```

```
        if (signedData) {
            switch (bytes) {
                case 1 :
                    result = verifyChecksumForImageForType<int8_t>(image,
                                                                   crc32Checksum);
                    break;
                case 2 :
                    result = verifyChecksumForImageForType<int16_t>(image,
                                                                    crc32Checksum);
                    break;
                case 4 :
                    result = verifyChecksumForImageForType<int32_t>(image,
                                                                    crc32Checksum);
                    break;
                default:
                    std::cerr
                            << "verifyChecksumForImage, unsupported data type,
signed bytes - "
                            << bytes << std::endl;
                    break;
            }
        }
        else {
            switch (bytes) {
                case 1 :
                    result = verifyChecksumForImageForType<uint8_t>(image,
                                                                    crc32Checksum);
                    break;
                case 2 :
                    result = verifyChecksumForImageForType<uint16_t>(image,
                                                                     crc32Checksum);
                    break;
                case 4 :
                    result = verifyChecksumForImageForType<uint32_t>(image,
                                                                     crc32Checksum);
                    break;
                default:
                    std::cerr
                            << "verifyChecksumForImage, unsupported data type,
unsigned bytes - "
                            << bytes << std::endl;
                    break;
            }
        }
```

```
        if (!result) {
            std::cerr << "verifyChecksumForImage, error bytes " << bytes
                      << " signed "
                      << signedData << std::endl;
        }
    }
    else {
        std::cerr << "'verifyChecksumForImage', no channels in the image."
                  << std::endl;
    }
    return result;
}
```

Clean up resources.

```
bool AwsDoc::Medical_Imaging::cleanup(const Aws::String &stackName,
                                      const Aws::String &dataStoreId,
                                      const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    bool result = true;

    if (!stackName.empty() && askYesNoQuestion(
            "Would you like to delete the stack " + stackName + "? (y/n)")) {
        std::cout << "Deleting the image sets in the stack." << std::endl;
        result &= emptyDatastore(dataStoreId, clientConfiguration);
        printAsterisksLine();
        std::cout << "Deleting the stack." << std::endl;
        result &= deleteStack(stackName, clientConfiguration);
    }
    return result;
}

bool AwsDoc::Medical_Imaging::emptyDatastore(const Aws::String &datastoreID,
                                             const Aws::Client::ClientConfiguration
 &clientConfiguration) {

    Aws::MedicalImaging::Model::SearchCriteria emptyCriteria;
    Aws::Vector<Aws::String> imageSetIDs;
    bool result = false;
    if (searchImageSets(datastoreID, emptyCriteria, imageSetIDs,
                        clientConfiguration)) {
```

```
        result = true;
        for (auto &imageSetID: imageSetIDs) {
            result &= deleteImageSet(datastoreID, imageSetID, clientConfiguration);
        }
    }

    return result;
}
```

- For API details, see the following topics in *AWS SDK for C++ API Reference*.
  - DeleteImageSet
  - GetDICOMImportJob
  - GetImageFrame
  - GetImageSetMetadata
  - SearchImageSets
  - StartDICOMImportJob

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

IAM examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with IAM.

Basics are code examples that show you how to perform the essential operations within a service.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Get started

- Basics
- Actions

Get started

Hello IAM

The following code example shows how to get started using IAM.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Code for the CMakeLists.txt CMake file.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS iam)

# Set this project's name.
project("hello_iam")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()
```

```
# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD AND AWSSDK_INSTALL_AS_SHARED_LIBS)
    # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

    # set(BIN_SUB_DIR "/Debug") # if you are building from the command line you may
 need to uncomment this
    # and set the proper subdirectory to the executables' location.

    AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_iam.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Code for the iam.cpp source file.

```
#include <aws/core/Aws.h>
#include <aws/iam/IAMClient.h>
#include <aws/iam/model/ListPoliciesRequest.h>
#include <iostream>
#include <iomanip>

/*
 *  A "Hello IAM" starter application which initializes an AWS Identity and Access
 Management (IAM) client
 *  and lists the IAM policies.
 *
 *  main function
 *
 *  Usage: 'hello_iam'
 *
 */

int main(int argc, char **argv) {
```

```
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
    {
        const Aws::String DATE_FORMAT("%Y-%m-%d");
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::IAM::IAMClient iamClient(clientConfig);
        Aws::IAM::Model::ListPoliciesRequest request;

        bool done = false;
        bool header = false;
        while (!done) {
            auto outcome = iamClient.ListPolicies(request);
            if (!outcome.IsSuccess()) {
                std::cerr << "Failed to list iam policies: " <<
                          outcome.GetError().GetMessage() << std::endl;
                result = 1;
                break;
            }

            if (!header) {
                std::cout << std::left << std::setw(55) << "Name" <<
                          std::setw(30) << "ID" << std::setw(80) << "Arn" <<
                          std::setw(64) << "Description" << std::setw(12) <<
                          "CreateDate" << std::endl;
                header = true;
            }

            const auto &policies = outcome.GetResult().GetPolicies();
            for (const auto &policy: policies) {
                std::cout << std::left << std::setw(55) <<
                          policy.GetPolicyName() << std::setw(30) <<
                          policy.GetPolicyId() << std::setw(80) << policy.GetArn()
 <<
                          std::setw(64) << policy.GetDescription() << std::setw(12)
 <<
                          policy.GetCreateDate().ToGmtString(DATE_FORMAT.c_str()) <<
                          std::endl;
            }
```

```
            if (outcome.GetResult().GetIsTruncated()) {
                request.SetMarker(outcome.GetResult().GetMarker());
            } else {
                done = true;
            }
        }
    }


    Aws::ShutdownAPI(options); // Should only be called once.
    return result;
}
```

- For API details, see ListPolicies in *AWS SDK for C++ API Reference*.

Basics

Learn the basics

The following code example shows how to create a user and assume a role.

> **Warning**
>
> To avoid security risks, don't use IAM users for authentication when developing purpose-built software or working with real data. Instead, use federation with an identity provider such as AWS IAM Identity Center.

- Create a user with no permissions.
- Create a role that grants permission to list Amazon S3 buckets for the account.
- Add a policy to let the user assume the role.
- Assume the role and list S3 buckets using temporary credentials, then clean up resources.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
namespace AwsDoc {
    namespace IAM {

        //! Cleanup by deleting created entities.
        /*!
          \sa DeleteCreatedEntities
          \param client: IAM client.
          \param role: IAM role.
          \param user: IAM user.
          \param policy: IAM policy.
        */
        static bool DeleteCreatedEntities(const Aws::IAM::IAMClient &client,
                                          const Aws::IAM::Model::Role &role,
                                          const Aws::IAM::Model::User &user,
                                          const Aws::IAM::Model::Policy &policy);
    }

    static const int LIST_BUCKETS_WAIT_SEC = 20;

    static const char ALLOCATION_TAG[] = "example_code";
}

//! Scenario to create an IAM user, create an IAM role, and apply the role to the
 user.
// "IAM access" permissions are needed to run this code.
// "STS assume role" permissions are needed to run this code. (Note: It might be
 necessary to
//    create a custom policy).
/*!
  \sa iamCreateUserAssumeRoleScenario
  \param clientConfig: Aws client configuration.
  \return bool: Successful completion.
*/
bool AwsDoc::IAM::iamCreateUserAssumeRoleScenario(
```

```
        const Aws::Client::ClientConfiguration &clientConfig) {

    Aws::IAM::IAMClient client(clientConfig);
    Aws::IAM::Model::User user;
    Aws::IAM::Model::Role role;
    Aws::IAM::Model::Policy policy;

    // 1. Create a user.
    {
        Aws::IAM::Model::CreateUserRequest request;
        Aws::String uuid = Aws::Utils::UUID::RandomUUID();
        Aws::String userName = "iam-demo-user-" +
                               Aws::Utils::StringUtils::ToLower(uuid.c_str());
        request.SetUserName(userName);

        Aws::IAM::Model::CreateUserOutcome outcome = client.CreateUser(request);
        if (!outcome.IsSuccess()) {
            std::cout << "Error creating IAM user " << userName << ":" <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }
        else {
            std::cout << "Successfully created IAM user " << userName << std::endl;
        }

        user = outcome.GetResult().GetUser();
    }

    // 2. Create a role.
    {
        // Get the IAM user for the current client in order to access its ARN.
        Aws::String iamUserArn;
        {
            Aws::IAM::Model::GetUserRequest request;
            Aws::IAM::Model::GetUserOutcome outcome = client.GetUser(request);
            if (!outcome.IsSuccess()) {
                std::cerr << "Error getting Iam user. " <<
                          outcome.GetError().GetMessage() << std::endl;

                DeleteCreatedEntities(client, role, user, policy);
                return false;
            }
            else {
                std::cout << "Successfully retrieved Iam user "
```

```
                    << outcome.GetResult().GetUser().GetUserName()
                    << std::endl;
        }

        iamUserArn = outcome.GetResult().GetUser().GetArn();
    }

    Aws::IAM::Model::CreateRoleRequest request;

    Aws::String uuid = Aws::Utils::UUID::RandomUUID();
    Aws::String roleName = "iam-demo-role-" +
                           Aws::Utils::StringUtils::ToLower(uuid.c_str());
    request.SetRoleName(roleName);

    // Build policy document for role.
    Aws::Utils::Document jsonStatement;
    jsonStatement.WithString("Effect", "Allow");

    Aws::Utils::Document jsonPrincipal;
    jsonPrincipal.WithString("AWS", iamUserArn);
    jsonStatement.WithObject("Principal", jsonPrincipal);
    jsonStatement.WithString("Action", "sts:AssumeRole");
    jsonStatement.WithObject("Condition", Aws::Utils::Document());

    Aws::Utils::Document policyDocument;
    policyDocument.WithString("Version", "2012-10-17");

    Aws::Utils::Array<Aws::Utils::Document> statements(1);
    statements[0] = jsonStatement;
    policyDocument.WithArray("Statement", statements);

    std::cout << "Setting policy for role\n   "
              << policyDocument.View().WriteCompact() << std::endl;

    // Set role policy document as JSON string.
    request.SetAssumeRolePolicyDocument(policyDocument.View().WriteCompact());

    Aws::IAM::Model::CreateRoleOutcome outcome = client.CreateRole(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Error creating role. " <<
                  outcome.GetError().GetMessage() << std::endl;

        DeleteCreatedEntities(client, role, user, policy);
        return false;
```

```
        }
        else {
            std::cout << "Successfully created a role with name " << roleName
                      << std::endl;
        }

        role = outcome.GetResult().GetRole();
    }

    // 3. Create an IAM policy.
    {
        Aws::IAM::Model::CreatePolicyRequest request;
        Aws::String uuid = Aws::Utils::UUID::RandomUUID();
        Aws::String policyName = "iam-demo-policy-" +
                                 Aws::Utils::StringUtils::ToLower(uuid.c_str());
        request.SetPolicyName(policyName);

        // Build IAM policy document.
        Aws::Utils::Document jsonStatement;
        jsonStatement.WithString("Effect", "Allow");
        jsonStatement.WithString("Action", "s3:ListAllMyBuckets");
        jsonStatement.WithString("Resource", "arn:aws:s3:::*");

        Aws::Utils::Document policyDocument;
        policyDocument.WithString("Version", "2012-10-17");

        Aws::Utils::Array<Aws::Utils::Document> statements(1);
        statements[0] = jsonStatement;
        policyDocument.WithArray("Statement", statements);

        std::cout << "Creating a policy.\n   " <<
policyDocument.View().WriteCompact()
                  << std::endl;

        // Set IAM policy document as JSON string.
        request.SetPolicyDocument(policyDocument.View().WriteCompact());

        Aws::IAM::Model::CreatePolicyOutcome outcome = client.CreatePolicy(request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Error creating policy. " <<
                      outcome.GetError().GetMessage() << std::endl;

            DeleteCreatedEntities(client, role, user, policy);
            return false;
```

```
        }
        else {
            std::cout << "Successfully created a policy with name, " << policyName
<<
                      "." << std::endl;
        }

        policy = outcome.GetResult().GetPolicy();
    }

    // 4. Assume the new role using the AWS Security Token Service (STS).
    Aws::STS::Model::Credentials credentials;
    {
        Aws::STS::STSClient stsClient(clientConfig);

        Aws::STS::Model::AssumeRoleRequest request;
        request.SetRoleArn(role.GetArn());
        Aws::String uuid = Aws::Utils::UUID::RandomUUID();
        Aws::String roleSessionName = "iam-demo-role-session-" +

Aws::Utils::StringUtils::ToLower(uuid.c_str());
        request.SetRoleSessionName(roleSessionName);

        Aws::STS::Model::AssumeRoleOutcome assumeRoleOutcome;

        // Repeatedly call AssumeRole, because there is often a delay
        // before the role is available to be assumed.
        // Repeat at most 20 times when access is denied.
        int count = 0;
        while (true) {
            assumeRoleOutcome = stsClient.AssumeRole(request);
            if (!assumeRoleOutcome.IsSuccess()) {
                if (count > 20 ||
                    assumeRoleOutcome.GetError().GetErrorType() !=
                    Aws::STS::STSErrors::ACCESS_DENIED) {
                    std::cerr << "Error assuming role after 20 tries. " <<
                              assumeRoleOutcome.GetError().GetMessage() <<
std::endl;

                    DeleteCreatedEntities(client, role, user, policy);
                    return false;
                }
                std::this_thread::sleep_for(std::chrono::seconds(1));
            }
```

```
            else {
                std::cout << "Successfully assumed the role after " << count
                          << " seconds." << std::endl;
                break;
            }
            count++;
        }

        credentials = assumeRoleOutcome.GetResult().GetCredentials();
    }


    // 5. List objects in the bucket (This should fail).
    {
        Aws::S3::S3Client s3Client(
                Aws::Auth::AWSCredentials(credentials.GetAccessKeyId(),
                                          credentials.GetSecretAccessKey(),
                                          credentials.GetSessionToken()),
                Aws::MakeShared<Aws::S3::S3EndpointProvider>(ALLOCATION_TAG),
                clientConfig);
        Aws::S3::Model::ListBucketsOutcome listBucketsOutcome =
s3Client.ListBuckets();
        if (!listBucketsOutcome.IsSuccess()) {
            if (listBucketsOutcome.GetError().GetErrorType() !=
                Aws::S3::S3Errors::ACCESS_DENIED) {
                std::cerr << "Could not lists buckets. " <<
                          listBucketsOutcome.GetError().GetMessage() << std::endl;
            }
            else {
                std::cout
                        << "Access to list buckets denied because privileges have
not been applied."
                        << std::endl;
            }
        }
        else {
            std::cerr
                    << "Successfully retrieved bucket lists when this should not
happen."
                    << std::endl;
        }
    }

    // 6. Attach the policy to the role.
```

```
    {
        Aws::IAM::Model::AttachRolePolicyRequest request;
        request.SetRoleName(role.GetRoleName());
        request.WithPolicyArn(policy.GetArn());

        Aws::IAM::Model::AttachRolePolicyOutcome outcome = client.AttachRolePolicy(
                request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Error creating policy. " <<
                      outcome.GetError().GetMessage() << std::endl;

            DeleteCreatedEntities(client, role, user, policy);
            return false;
        }
        else {
            std::cout << "Successfully attached the policy with name, "
                      << policy.GetPolicyName() <<
                      ", to the role, " << role.GetRoleName() << "." << std::endl;
        }
    }

    int count = 0;
    // 7. List objects in the bucket (this should succeed).
    // Repeatedly call ListBuckets, because there is often a delay
    // before the policy with ListBucket permissions has been applied to the role.
    // Repeat at most LIST_BUCKETS_WAIT_SEC times when access is denied.
    while (true) {
        Aws::S3::S3Client s3Client(
                Aws::Auth::AWSCredentials(credentials.GetAccessKeyId(),
                                          credentials.GetSecretAccessKey(),
                                          credentials.GetSessionToken()),
                Aws::MakeShared<Aws::S3::S3EndpointProvider>(ALLOCATION_TAG),
                clientConfig);
        Aws::S3::Model::ListBucketsOutcome listBucketsOutcome =
s3Client.ListBuckets();
        if (!listBucketsOutcome.IsSuccess()) {
            if ((count > LIST_BUCKETS_WAIT_SEC) ||
                listBucketsOutcome.GetError().GetErrorType() !=
                Aws::S3::S3Errors::ACCESS_DENIED) {
                std::cerr << "Could not lists buckets after " <<
LIST_BUCKETS_WAIT_SEC << " seconds. " <<
                          listBucketsOutcome.GetError().GetMessage() << std::endl;
                DeleteCreatedEntities(client, role, user, policy);
                return false;
```

```
            }

            std::this_thread::sleep_for(std::chrono::seconds(1));
        }
        else {

            std::cout << "Successfully retrieved bucket lists after " << count
                      << " seconds." << std::endl;
            break;
        }
        count++;
    }

    // 8. Delete all the created resources.
    return DeleteCreatedEntities(client, role, user, policy);
}

bool AwsDoc::IAM::DeleteCreatedEntities(const Aws::IAM::IAMClient &client,
                                        const Aws::IAM::Model::Role &role,
                                        const Aws::IAM::Model::User &user,
                                        const Aws::IAM::Model::Policy &policy) {
    bool result = true;
    if (policy.ArnHasBeenSet()) {
        // Detach the policy from the role.
        {
            Aws::IAM::Model::DetachRolePolicyRequest request;
            request.SetPolicyArn(policy.GetArn());
            request.SetRoleName(role.GetRoleName());

            Aws::IAM::Model::DetachRolePolicyOutcome outcome =
 client.DetachRolePolicy(
                    request);
            if (!outcome.IsSuccess()) {
                std::cerr << "Error Detaching policy from roles. " <<
                          outcome.GetError().GetMessage() << std::endl;
                result = false;
            }
            else {
                std::cout << "Successfully detached the policy with arn "
                          << policy.GetArn()
                          << " from role " << role.GetRoleName() << "." <<
 std::endl;
            }
        }
```

```
        // Delete the policy.
        {
            Aws::IAM::Model::DeletePolicyRequest request;
            request.WithPolicyArn(policy.GetArn());

            Aws::IAM::Model::DeletePolicyOutcome outcome =
client.DeletePolicy(request);
            if (!outcome.IsSuccess()) {
                std::cerr << "Error deleting policy. " <<
                          outcome.GetError().GetMessage() << std::endl;
                result = false;
            }
            else {
                std::cout << "Successfully deleted the policy with arn "
                          << policy.GetArn() << std::endl;
            }
        }

    }

    if (role.RoleIdHasBeenSet()) {
        // Delete the role.
        Aws::IAM::Model::DeleteRoleRequest request;
        request.SetRoleName(role.GetRoleName());

        Aws::IAM::Model::DeleteRoleOutcome outcome = client.DeleteRole(request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Error deleting role. " <<
                      outcome.GetError().GetMessage() << std::endl;
            result = false;
        }
        else {
            std::cout << "Successfully deleted the role with name "
                      << role.GetRoleName() << std::endl;
        }
    }

    if (user.ArnHasBeenSet()) {
        // Delete the user.
        Aws::IAM::Model::DeleteUserRequest request;
        request.WithUserName(user.GetUserName());

        Aws::IAM::Model::DeleteUserOutcome outcome = client.DeleteUser(request);
```

```
        if (!outcome.IsSuccess()) {
            std::cerr << "Error deleting user. " <<
                      outcome.GetError().GetMessage() << std::endl;
            result = false;
        }
        else {
            std::cout << "Successfully deleted the user with name "
                      << user.GetUserName() << std::endl;
        }
    }

    return result;
}
```

- For API details, see the following topics in *AWS SDK for C++ API Reference*.
  - AttachRolePolicy
  - CreateAccessKey
  - CreatePolicy
  - CreateRole
  - CreateUser
  - DeleteAccessKey
  - DeletePolicy
  - DeleteRole
  - DeleteUser
  - DeleteUserPolicy
  - DetachRolePolicy
  - PutUserPolicy

Actions

`AttachRolePolicy`

The following code example shows how to use `AttachRolePolicy`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::IAM::attachRolePolicy(const Aws::String &roleName,
                                   const Aws::String &policyArn,
                                   const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);

    Aws::IAM::Model::ListAttachedRolePoliciesRequest list_request;
    list_request.SetRoleName(roleName);

    bool done = false;
    while (!done) {
        auto list_outcome = iam.ListAttachedRolePolicies(list_request);
        if (!list_outcome.IsSuccess()) {
            std::cerr << "Failed to list attached policies of role " <<
                      roleName << ": " << list_outcome.GetError().GetMessage() <<
                      std::endl;
            return false;
        }

        const auto &policies = list_outcome.GetResult().GetAttachedPolicies();
        if (std::any_of(policies.cbegin(), policies.cend(),
                        [=](const Aws::IAM::Model::AttachedPolicy &policy) {
                                return policy.GetPolicyArn() == policyArn;
                        })) {
            std::cout << "Policy " << policyArn <<
                      " is already attached to role " << roleName << std::endl;
            return true;
        }

        done = !list_outcome.GetResult().GetIsTruncated();
        list_request.SetMarker(list_outcome.GetResult().GetMarker());
    }

    Aws::IAM::Model::AttachRolePolicyRequest request;
```

```
    request.SetRoleName(roleName);
    request.SetPolicyArn(policyArn);

    Aws::IAM::Model::AttachRolePolicyOutcome outcome =
 iam.AttachRolePolicy(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Failed to attach policy " << policyArn << " to role " <<
                  roleName << ": " << outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully attached policy " << policyArn << " to role " <<
                  roleName << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see AttachRolePolicy in *AWS SDK for C++ API Reference*.

`CreateAccessKey`

The following code example shows how to use `CreateAccessKey`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
Aws::String AwsDoc::IAM::createAccessKey(const Aws::String &userName,
                                         const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);

    Aws::IAM::Model::CreateAccessKeyRequest request;
    request.SetUserName(userName);

    Aws::String result;
```

```
    Aws::IAM::Model::CreateAccessKeyOutcome outcome = iam.CreateAccessKey(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Error creating access key for IAM user " << userName
                  << ":" << outcome.GetError().GetMessage() << std::endl;
    }
    else {
        const auto &accessKey = outcome.GetResult().GetAccessKey();
        std::cout << "Successfully created access key for IAM user " <<
                  userName << std::endl << "  aws_access_key_id = " <<
                  accessKey.GetAccessKeyId() << std::endl <<
                  " aws_secret_access_key = " << accessKey.GetSecretAccessKey() <<
                  std::endl;
        result = accessKey.GetAccessKeyId();
    }

    return result;
}
```

- For API details, see CreateAccessKey in *AWS SDK for C++ API Reference*.

`CreateAccountAlias`

The following code example shows how to use `CreateAccountAlias`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::IAM::createAccountAlias(const Aws::String &aliasName,
                                     const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::CreateAccountAliasRequest request;
    request.SetAccountAlias(aliasName);

    Aws::IAM::Model::CreateAccountAliasOutcome outcome = iam.CreateAccountAlias(
```

```
            request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Error creating account alias " << aliasName << ": "
                  << outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully created account alias " << aliasName <<
                  std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see CreateAccountAlias in *AWS SDK for C++ API Reference*.

`CreatePolicy`

The following code example shows how to use `CreatePolicy`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
Aws::String AwsDoc::IAM::createPolicy(const Aws::String &policyName,
                                      const Aws::String &rsrcArn,
                                      const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);

    Aws::IAM::Model::CreatePolicyRequest request;
    request.SetPolicyName(policyName);
    request.SetPolicyDocument(BuildSamplePolicyDocument(rsrcArn));

    Aws::IAM::Model::CreatePolicyOutcome outcome = iam.CreatePolicy(request);
    Aws::String result;
    if (!outcome.IsSuccess()) {
        std::cerr << "Error creating policy " << policyName << ": " <<
```

```
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        result = outcome.GetResult().GetPolicy().GetArn();
        std::cout << "Successfully created policy " << policyName <<
                  std::endl;
    }

    return result;
}

Aws::String AwsDoc::IAM::BuildSamplePolicyDocument(const Aws::String &rsrc_arn) {
    std::stringstream stringStream;
    stringStream << "{"
                 << "  \"Version\": \"2012-10-17\","
                 << "  \"Statement\": ["
                 << "    {"
                 << "        \"Effect\": \"Allow\","
                 << "        \"Action\": \"logs:CreateLogGroup\","
                 << "        \"Resource\": \""
                 << rsrc_arn
                 << "\""
                 << "    },"
                 << "    {"
                 << "        \"Effect\": \"Allow\","
                 << "        \"Action\": ["
                 << "            \"dynamodb:DeleteItem\","
                 << "            \"dynamodb:GetItem\","
                 << "            \"dynamodb:PutItem\","
                 << "            \"dynamodb:Scan\","
                 << "            \"dynamodb:UpdateItem\""
                 << "       ],"
                 << "       \"Resource\": \""
                 << rsrc_arn
                 << "\""
                 << "    }"
                 << "   ]"
                 << "}";

    return stringStream.str();
}
```

- For API details, see CreatePolicy in *AWS SDK for C++ API Reference*.

`CreateRole`

The following code example shows how to use `CreateRole`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::IAM::createIamRole(
        const Aws::String &roleName,
        const Aws::String &policy,
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::IAM::IAMClient client(clientConfig);
    Aws::IAM::Model::CreateRoleRequest request;

    request.SetRoleName(roleName);
    request.SetAssumeRolePolicyDocument(policy);

    Aws::IAM::Model::CreateRoleOutcome outcome = client.CreateRole(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Error creating role. " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        const Aws::IAM::Model::Role iamRole = outcome.GetResult().GetRole();
        std::cout << "Created role " << iamRole.GetRoleName() << "\n";
        std::cout << "ID: " << iamRole.GetRoleId() << "\n";
        std::cout << "ARN: " << iamRole.GetArn() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see CreateRole in *AWS SDK for C++ API Reference*.

`CreateUser`

The following code example shows how to use `CreateUser`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
Aws::IAM::IAMClient iam(clientConfig);

Aws::IAM::Model::CreateUserRequest create_request;
create_request.SetUserName(userName);

auto create_outcome = iam.CreateUser(create_request);
if (!create_outcome.IsSuccess()) {
    std::cerr << "Error creating IAM user " << userName << ":" <<
              create_outcome.GetError().GetMessage() << std::endl;
}
else {
    std::cout << "Successfully created IAM user " << userName << std::endl;
}

return create_outcome.IsSuccess();
```

- For API details, see CreateUser in *AWS SDK for C++ API Reference*.

`DeleteAccessKey`

The following code example shows how to use `DeleteAccessKey`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::IAM::deleteAccessKey(const Aws::String &userName,
                                  const Aws::String &accessKeyID,
                                  const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);

    Aws::IAM::Model::DeleteAccessKeyRequest request;
    request.SetUserName(userName);
    request.SetAccessKeyId(accessKeyID);

    auto outcome = iam.DeleteAccessKey(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error deleting access key " << accessKeyID << " from user "
                  << userName << ": " << outcome.GetError().GetMessage() <<
                  std::endl;
    }
    else {
        std::cout << "Successfully deleted access key " << accessKeyID
                  << " for IAM user " << userName << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DeleteAccessKey in *AWS SDK for C++ API Reference*.

`DeleteAccountAlias`

The following code example shows how to use `DeleteAccountAlias`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::IAM::deleteAccountAlias(const Aws::String &accountAlias,
                                     const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);

    Aws::IAM::Model::DeleteAccountAliasRequest request;
    request.SetAccountAlias(accountAlias);

    const auto outcome = iam.DeleteAccountAlias(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Error deleting account alias " << accountAlias << ": "
                  << outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully deleted account alias " << accountAlias <<
                  std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DeleteAccountAlias in *AWS SDK for C++ API Reference*.

`DeletePolicy`

The following code example shows how to use `DeletePolicy`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::IAM::deletePolicy(const Aws::String &policyArn,
                               const Aws::Client::ClientConfiguration &clientConfig)
 {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::DeletePolicyRequest request;
    request.SetPolicyArn(policyArn);

    auto outcome = iam.DeletePolicy(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Error deleting policy with arn " << policyArn << ": "
                  << outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully deleted policy with arn " << policyArn
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DeletePolicy in *AWS SDK for C++ API Reference*.

`DeleteServerCertificate`

The following code example shows how to use `DeleteServerCertificate`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::IAM::deleteServerCertificate(const Aws::String &certificateName,
                                          const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::DeleteServerCertificateRequest request;
    request.SetServerCertificateName(certificateName);

    const auto outcome = iam.DeleteServerCertificate(request);
    bool result = true;
    if (!outcome.IsSuccess()) {
        if (outcome.GetError().GetErrorType() !=
 Aws::IAM::IAMErrors::NO_SUCH_ENTITY) {
            std::cerr << "Error deleting server certificate " << certificateName <<
                      ": " << outcome.GetError().GetMessage() << std::endl;
            result = false;
        }
        else {
            std::cout << "Certificate '" << certificateName
                      << "' not found." << std::endl;
        }
    }
    else {
        std::cout << "Successfully deleted server certificate " << certificateName
                  << std::endl;
    }

    return result;
}
```

- For API details, see DeleteServerCertificate in *AWS SDK for C++ API Reference*.

`DeleteUser`

The following code example shows how to use `DeleteUser`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
Aws::IAM::IAMClient iam(clientConfig);

Aws::IAM::Model::DeleteUserRequest request;
request.SetUserName(userName);
auto outcome = iam.DeleteUser(request);
if (!outcome.IsSuccess()) {
    std::cerr << "Error deleting IAM user " << userName << ": " <<
              outcome.GetError().GetMessage() << std::endl;;
}
else {
    std::cout << "Successfully deleted IAM user " << userName << std::endl;
}

return outcome.IsSuccess();
```

- For API details, see DeleteUser in *AWS SDK for C++ API Reference*.

`DetachRolePolicy`

The following code example shows how to use `DetachRolePolicy`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
    Aws::IAM::IAMClient iam(clientConfig);

    Aws::IAM::Model::DetachRolePolicyRequest detachRequest;
    detachRequest.SetRoleName(roleName);
    detachRequest.SetPolicyArn(policyArn);

    auto detachOutcome = iam.DetachRolePolicy(detachRequest);
    if (!detachOutcome.IsSuccess()) {
        std::cerr << "Failed to detach policy " << policyArn << " from role "
                  << roleName << ": " << detachOutcome.GetError().GetMessage() <<
                  std::endl;
    }
    else {
        std::cout << "Successfully detached policy " << policyArn << " from role "
                  << roleName << std::endl;
    }

    return detachOutcome.IsSuccess();
```

- For API details, see DetachRolePolicy in *AWS SDK for C++ API Reference*.

`GetAccessKeyLastUsed`

The following code example shows how to use `GetAccessKeyLastUsed`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::IAM::accessKeyLastUsed(const Aws::String &secretKeyID,
                                    const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::GetAccessKeyLastUsedRequest request;

    request.SetAccessKeyId(secretKeyID);
```

```
    Aws::IAM::Model::GetAccessKeyLastUsedOutcome outcome = iam.GetAccessKeyLastUsed(
            request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error querying last used time for access key " <<
                  secretKeyID << ":" << outcome.GetError().GetMessage() <<
 std::endl;
    }
    else {
        Aws::String lastUsedTimeString =
                outcome.GetResult()
                        .GetAccessKeyLastUsed()
                        .GetLastUsedDate()
                        .ToGmtString(Aws::Utils::DateFormat::ISO_8601);
        std::cout << "Access key " << secretKeyID << " last used at time " <<
                  lastUsedTimeString << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see GetAccessKeyLastUsed in *AWS SDK for C++ API Reference*.

`GetPolicy`

The following code example shows how to use `GetPolicy`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::IAM::getPolicy(const Aws::String &policyArn,
                            const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::GetPolicyRequest request;
    request.SetPolicyArn(policyArn);
```

```
    auto outcome = iam.GetPolicy(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Error getting policy " << policyArn << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        const auto &policy = outcome.GetResult().GetPolicy();
        std::cout << "Name: " << policy.GetPolicyName() << std::endl <<
                  "ID: " << policy.GetPolicyId() << std::endl << "Arn: " <<
                  policy.GetArn() << std::endl << "Description: " <<
                  policy.GetDescription() << std::endl << "CreateDate: " <<

 policy.GetCreateDate().ToGmtString(Aws::Utils::DateFormat::ISO_8601)
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see GetPolicy in *AWS SDK for C++ API Reference*.

`GetServerCertificate`

The following code example shows how to use `GetServerCertificate`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::IAM::getServerCertificate(const Aws::String &certificateName,
                                       const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::GetServerCertificateRequest request;
    request.SetServerCertificateName(certificateName);
```

```
    auto outcome = iam.GetServerCertificate(request);
    bool result = true;
    if (!outcome.IsSuccess()) {
        if (outcome.GetError().GetErrorType() !=
 Aws::IAM::IAMErrors::NO_SUCH_ENTITY) {
            std::cerr << "Error getting server certificate " << certificateName <<
                      ": " << outcome.GetError().GetMessage() << std::endl;
            result = false;
        }
        else {
            std::cout << "Certificate '" << certificateName
                      << "' not found." << std::endl;
        }
    }
    else {
        const auto &certificate = outcome.GetResult().GetServerCertificate();
        std::cout << "Name: " <<

 certificate.GetServerCertificateMetadata().GetServerCertificateName()
                  << std::endl << "Body: " << certificate.GetCertificateBody() <<
                  std::endl << "Chain: " << certificate.GetCertificateChain() <<
                  std::endl;
    }

    return result;
}
```

- For API details, see GetServerCertificate in *AWS SDK for C++ API Reference*.

`ListAccessKeys`

The following code example shows how to use `ListAccessKeys`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::IAM::listAccessKeys(const Aws::String &userName,
                                 const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::ListAccessKeysRequest request;
    request.SetUserName(userName);

    bool done = false;
    bool header = false;
    while (!done) {
        auto outcome = iam.ListAccessKeys(request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to list access keys for user " << userName
                      << ": " << outcome.GetError().GetMessage() << std::endl;
            return false;
        }

        if (!header) {
            std::cout << std::left << std::setw(32) << "UserName" <<
                      std::setw(30) << "KeyID" << std::setw(20) << "Status" <<
                      std::setw(20) << "CreateDate" << std::endl;
            header = true;
        }

        const auto &keys = outcome.GetResult().GetAccessKeyMetadata();
        const Aws::String DATE_FORMAT = "%Y-%m-%d";

        for (const auto &key: keys) {
            Aws::String statusString =
                    Aws::IAM::Model::StatusTypeMapper::GetNameForStatusType(
                            key.GetStatus());
            std::cout << std::left << std::setw(32) << key.GetUserName() <<
                      std::setw(30) << key.GetAccessKeyId() << std::setw(20) <<
                      statusString << std::setw(20) <<
                      key.GetCreateDate().ToGmtString(DATE_FORMAT.c_str()) <<
 std::endl;
        }

        if (outcome.GetResult().GetIsTruncated()) {
            request.SetMarker(outcome.GetResult().GetMarker());
        }
        else {
            done = true;
```

```
        }
    }

    return true;
}
```

- For API details, see ListAccessKeys in *AWS SDK for C++ API Reference*.

`ListAccountAliases`

The following code example shows how to use `ListAccountAliases`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool
AwsDoc::IAM::listAccountAliases(const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::ListAccountAliasesRequest request;

    bool done = false;
    bool header = false;
    while (!done) {
        auto outcome = iam.ListAccountAliases(request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to list account aliases: " <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }

        const auto &aliases = outcome.GetResult().GetAccountAliases();
        if (!header) {
            if (aliases.size() == 0) {
                std::cout << "Account has no aliases" << std::endl;
```

```
                break;
            }
            std::cout << std::left << std::setw(32) << "Alias" << std::endl;
            header = true;
        }

        for (const auto &alias: aliases) {
            std::cout << std::left << std::setw(32) << alias << std::endl;
        }

        if (outcome.GetResult().GetIsTruncated()) {
            request.SetMarker(outcome.GetResult().GetMarker());
        }
        else {
            done = true;
        }
    }

    return true;
}
```

- For API details, see ListAccountAliases in *AWS SDK for C++ API Reference*.

`ListPolicies`

The following code example shows how to use `ListPolicies`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::IAM::listPolicies(const Aws::Client::ClientConfiguration &clientConfig)
 {
    const Aws::String DATE_FORMAT("%Y-%m-%d");
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::ListPoliciesRequest request;
```

```
    bool done = false;
    bool header = false;
    while (!done) {
        auto outcome = iam.ListPolicies(request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to list iam policies: " <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }

        if (!header) {
            std::cout << std::left << std::setw(55) << "Name" <<
                      std::setw(30) << "ID" << std::setw(80) << "Arn" <<
                      std::setw(64) << "Description" << std::setw(12) <<
                      "CreateDate" << std::endl;
            header = true;
        }

        const auto &policies = outcome.GetResult().GetPolicies();
        for (const auto &policy: policies) {
            std::cout << std::left << std::setw(55) <<
                      policy.GetPolicyName() << std::setw(30) <<
                      policy.GetPolicyId() << std::setw(80) << policy.GetArn() <<
                      std::setw(64) << policy.GetDescription() << std::setw(12) <<
                      policy.GetCreateDate().ToGmtString(DATE_FORMAT.c_str()) <<
                      std::endl;
        }

        if (outcome.GetResult().GetIsTruncated()) {
            request.SetMarker(outcome.GetResult().GetMarker());
        }
        else {
            done = true;
        }
    }

    return true;
}
```

- For API details, see ListPolicies in *AWS SDK for C++ API Reference*.

`ListServerCertificates`

The following code example shows how to use `ListServerCertificates`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::IAM::listServerCertificates(
        const Aws::Client::ClientConfiguration &clientConfig) {
    const Aws::String DATE_FORMAT = "%Y-%m-%d";

    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::ListServerCertificatesRequest request;

    bool done = false;
    bool header = false;
    while (!done) {
        auto outcome = iam.ListServerCertificates(request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to list server certificates: " <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }

        if (!header) {
            std::cout << std::left << std::setw(55) << "Name" <<
                      std::setw(30) << "ID" << std::setw(80) << "Arn" <<
                      std::setw(14) << "UploadDate" << std::setw(14) <<
                      "ExpirationDate" << std::endl;
            header = true;
        }

        const auto &certificates =
                outcome.GetResult().GetServerCertificateMetadataList();

        for (const auto &certificate: certificates) {
            std::cout << std::left << std::setw(55) <<
                      certificate.GetServerCertificateName() << std::setw(30) <<
```

```
                        certificate.GetServerCertificateId() << std::setw(80) <<
                        certificate.GetArn() << std::setw(14) <<
                        certificate.GetUploadDate().ToGmtString(DATE_FORMAT.c_str())
 <<
                        std::setw(14) <<
                        certificate.GetExpiration().ToGmtString(DATE_FORMAT.c_str())
 <<
                        std::endl;
        }

        if (outcome.GetResult().GetIsTruncated()) {
            request.SetMarker(outcome.GetResult().GetMarker());
        }
        else {
            done = true;
        }
    }

    return true;
}
```

- For API details, see ListServerCertificates in *AWS SDK for C++ API Reference*.

`ListUsers`

The following code example shows how to use `ListUsers`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::IAM::listUsers(const Aws::Client::ClientConfiguration &clientConfig) {
    const Aws::String DATE_FORMAT = "%Y-%m-%d";
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::ListUsersRequest request;
```

```
    bool done = false;
    bool header = false;
    while (!done) {
        auto outcome = iam.ListUsers(request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Failed to list iam users:" <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }

        if (!header) {
            std::cout << std::left << std::setw(32) << "Name" <<
                      std::setw(30) << "ID" << std::setw(64) << "Arn" <<
                      std::setw(20) << "CreateDate" << std::endl;
            header = true;
        }

        const auto &users = outcome.GetResult().GetUsers();
        for (const auto &user: users) {
            std::cout << std::left << std::setw(32) << user.GetUserName() <<
                      std::setw(30) << user.GetUserId() << std::setw(64) <<
                      user.GetArn() << std::setw(20) <<
                      user.GetCreateDate().ToGmtString(DATE_FORMAT.c_str())
                      << std::endl;
        }

        if (outcome.GetResult().GetIsTruncated()) {
            request.SetMarker(outcome.GetResult().GetMarker());
        }
        else {
            done = true;
        }
    }

    return true;
}
```

- For API details, see ListUsers in *AWS SDK for C++ API Reference*.

`PutRolePolicy`

The following code example shows how to use `PutRolePolicy`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::IAM::putRolePolicy(
        const Aws::String &roleName,
        const Aws::String &policyName,
        const Aws::String &policyDocument,
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::IAM::IAMClient iamClient(clientConfig);
    Aws::IAM::Model::PutRolePolicyRequest request;

    request.SetRoleName(roleName);
    request.SetPolicyName(policyName);
    request.SetPolicyDocument(policyDocument);

    Aws::IAM::Model::PutRolePolicyOutcome outcome =
 iamClient.PutRolePolicy(request);
    if (!outcome.IsSuccess()) {
        std::cerr << "Error putting policy on role. " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Successfully put the role policy." << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see PutRolePolicy in *AWS SDK for C++ API Reference*.

`UpdateAccessKey`

The following code example shows how to use `UpdateAccessKey`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::IAM::updateAccessKey(const Aws::String &userName,
                                  const Aws::String &accessKeyID,
                                  Aws::IAM::Model::StatusType status,
                                  const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::UpdateAccessKeyRequest request;
    request.SetUserName(userName);
    request.SetAccessKeyId(accessKeyID);
    request.SetStatus(status);

    auto outcome = iam.UpdateAccessKey(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully updated status of access key "
                  << accessKeyID << " for user " << userName << std::endl;
    }
    else {
        std::cerr << "Error updated status of access key " << accessKeyID <<
                  " for user " << userName << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see UpdateAccessKey in *AWS SDK for C++ API Reference*.

`UpdateServerCertificate`

The following code example shows how to use `UpdateServerCertificate`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::IAM::updateServerCertificate(const Aws::String &currentCertificateName,
                                          const Aws::String &newCertificateName,
                                          const Aws::Client::ClientConfiguration
 &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);
    Aws::IAM::Model::UpdateServerCertificateRequest request;
    request.SetServerCertificateName(currentCertificateName);
    request.SetNewServerCertificateName(newCertificateName);

    auto outcome = iam.UpdateServerCertificate(request);
    bool result = true;
    if (outcome.IsSuccess()) {
        std::cout << "Server certificate " << currentCertificateName
                  << " successfully renamed as " << newCertificateName
                  << std::endl;
    }
    else {
        if (outcome.GetError().GetErrorType() !=
 Aws::IAM::IAMErrors::NO_SUCH_ENTITY) {
            std::cerr << "Error changing name of server certificate " <<
                      currentCertificateName << " to " << newCertificateName << ":"
 <<
                      outcome.GetError().GetMessage() << std::endl;
            result = false;
        }
        else {
            std::cout << "Certificate '" << currentCertificateName
                      << "' not found." << std::endl;
        }
    }

    return result;
}
```

- For API details, see UpdateServerCertificate in *AWS SDK for C++ API Reference*.

`UpdateUser`

The following code example shows how to use `UpdateUser`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::IAM::updateUser(const Aws::String &currentUserName,
                             const Aws::String &newUserName,
                             const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::IAM::IAMClient iam(clientConfig);

    Aws::IAM::Model::UpdateUserRequest request;
    request.SetUserName(currentUserName);
    request.SetNewUserName(newUserName);

    auto outcome = iam.UpdateUser(request);
    if (outcome.IsSuccess()) {
        std::cout << "IAM user " << currentUserName <<
                  " successfully updated with new user name " << newUserName <<
                  std::endl;
    }
    else {
        std::cerr << "Error updating user name for IAM user " << currentUserName <<
                  ":" << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see UpdateUser in *AWS SDK for C++ API Reference*.

AWS IoT examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with AWS IoT.

Basics are code examples that show you how to perform the essential operations within a service.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Get started
- Basics
- Actions

Get started

Hello AWS IoT

The following code example shows how to get started using AWS IoT.

SDK for C++

Code for the CMakeLists.txt CMake file.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS iot)

# Set this project's name.
project("hello_iot")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)
```

```
# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD AND AWSSDK_INSTALL_AS_SHARED_LIBS)
    # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

    # set(BIN_SUB_DIR "/Debug") # If you are building from the command line, you may
 need to uncomment this
    # and set the proper subdirectory to the executables' location.

    AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_iot.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Code for the hello_iot.cpp source file.

```
#include <aws/core/Aws.h>
#include <aws/iot/IoTClient.h>
#include <aws/iot/model/ListThingsRequest.h>
#include <iostream>

/*
 *  A "Hello IoT" starter application which initializes an AWS IoT client and
 *  lists the AWS IoT topics in the current account.
```

```
 *
 *  main function
 *
 *  Usage: 'hello_iot'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    //  Optional: change the log level for debugging.
    //  options.loggingOptions.logLevel = Aws::Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::IoT::IoTClient iotClient(clientConfig);
        // List the things in the current account.
        Aws::IoT::Model::ListThingsRequest listThingsRequest;

        Aws::String nextToken; // Used for pagination.
        Aws::Vector<Aws::IoT::Model::ThingAttribute> allThings;

        do {
            if (!nextToken.empty()) {
                listThingsRequest.SetNextToken(nextToken);
            }

            Aws::IoT::Model::ListThingsOutcome listThingsOutcome =
 iotClient.ListThings(
                    listThingsRequest);
            if (listThingsOutcome.IsSuccess()) {
                const Aws::Vector<Aws::IoT::Model::ThingAttribute> &things =
 listThingsOutcome.GetResult().GetThings();
                allThings.insert(allThings.end(), things.begin(), things.end());
                nextToken = listThingsOutcome.GetResult().GetNextToken();
            }
            else {
                std::cerr << "List things failed"
                          << listThingsOutcome.GetError().GetMessage() << std::endl;
                break;
            }
        } while (!nextToken.empty());
```

```
        std::cout << allThings.size() << " thing(s) found." << std::endl;
        for (auto const &thing: allThings) {
            std::cout << thing.GetThingName() << std::endl;
        }
    }

    Aws::ShutdownAPI(options); // Should only be called once.
    return 0;
}
```

- For API details, see listThings in *AWS SDK for C++ API Reference*.

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Basics

Learn the basics

The following code example shows how to:

- Create an AWS IoT Thing.
- Generate a device certificate.
- Update an AWS IoT Thing with Attributes.
- Return a unique endpoint.
- List your AWS IoT certificates.
- Update an AWS IoT shadow.
- Write out state information.
- Creates a rule.
- List your rules.
- Search things using the Thing name.
- Delete an AWS IoT Thing.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Create an AWS IoT thing.

```
    Aws::String thingName = askQuestion("Enter a thing name: ");

    if (!createThing(thingName, clientConfiguration)) {
        std::cerr << "Exiting because createThing failed." << std::endl;
        cleanup("", "", "", "", "", false, clientConfiguration);
        return false;
    }
```

```
//! Create an AWS IoT thing.
/*!
  \param thingName: The name for the thing.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::createThing(const Aws::String &thingName,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::IoT::IoTClient iotClient(clientConfiguration);
    Aws::IoT::Model::CreateThingRequest createThingRequest;
    createThingRequest.SetThingName(thingName);

    Aws::IoT::Model::CreateThingOutcome outcome = iotClient.CreateThing(
            createThingRequest);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully created thing " << thingName << std::endl;
    }
    else {
        std::cerr << "Failed to create thing " << thingName << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
```

```
    return outcome.IsSuccess();
}
```

Generate and attach a device certificate.

```
    Aws::String certificateARN;
    Aws::String certificateID;
    if (askYesNoQuestion("Would you like to create a certificate for your thing? (y/
n) ")) {
        Aws::String outputFolder;
        if (askYesNoQuestion(
                "Would you like to save the certificate and keys to file? (y/n) "))
 {
            outputFolder = std::filesystem::current_path();
            outputFolder += "/device_keys_and_certificates";

            std::filesystem::create_directories(outputFolder);

            std::cout << "The certificate and keys will be saved to the folder: "
                      << outputFolder << std::endl;
        }

        if (!createKeysAndCertificate(outputFolder, certificateARN, certificateID,
                                      clientConfiguration)) {
            std::cerr << "Exiting because createKeysAndCertificate failed."
                      << std::endl;
            cleanup(thingName, "", "", "", "", false, clientConfiguration);
            return false;
        }

        std::cout << "\nNext, the certificate will be attached to the thing.\n"
                  << std::endl;
        if (!attachThingPrincipal(certificateARN, thingName, clientConfiguration)) {
            std::cerr << "Exiting because attachThingPrincipal failed." <<
 std::endl;
            cleanup(thingName, certificateARN, certificateID, "", "",
                    false,
                    clientConfiguration);
            return false;
        }
    }
```

```
//! Create keys and certificate for an Aws IoT device.
//! This routine will save certificates and keys to an output folder, if provided.
/*!
  \param outputFolder: Location for storing output in files, ignored when string is
 empty.
  \param certificateARNResult: A string to receive the ARN of the created
 certificate.
  \param certificateID: A string to receive the ID of the created certificate.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::createKeysAndCertificate(const Aws::String &outputFolder,
                                           Aws::String &certificateARNResult,
                                           Aws::String &certificateID,
                                           const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::IoT::IoTClient client(clientConfiguration);
    Aws::IoT::Model::CreateKeysAndCertificateRequest
 createKeysAndCertificateRequest;

    Aws::IoT::Model::CreateKeysAndCertificateOutcome outcome =
            client.CreateKeysAndCertificate(createKeysAndCertificateRequest);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully created a certificate and keys" << std::endl;
        certificateARNResult = outcome.GetResult().GetCertificateArn();
        certificateID = outcome.GetResult().GetCertificateId();
        std::cout << "Certificate ARN: " << certificateARNResult << ", certificate
 ID: "
                  << certificateID << std::endl;

        if (!outputFolder.empty()) {
            std::cout << "Writing certificate and keys to the folder '" <<
 outputFolder
                      << "'." << std::endl;
            std::cout << "Be sure these files are stored securely." << std::endl;

            Aws::String certificateFilePath = outputFolder + "/certificate.pem.crt";
            std::ofstream certificateFile(certificateFilePath);
            if (!certificateFile.is_open()) {
                std::cerr << "Error opening certificate file, '" <<
 certificateFilePath
                          << "'."
                          << std::endl;
```

```
                return false;
            }
            certificateFile << outcome.GetResult().GetCertificatePem();
            certificateFile.close();

            const Aws::IoT::Model::KeyPair &keyPair =
 outcome.GetResult().GetKeyPair();

            Aws::String privateKeyFilePath = outputFolder + "/private.pem.key";
            std::ofstream privateKeyFile(privateKeyFilePath);
            if (!privateKeyFile.is_open()) {
                std::cerr << "Error opening private key file, '" <<
 privateKeyFilePath
                          << "'."
                          << std::endl;
                return false;
            }
            privateKeyFile << keyPair.GetPrivateKey();
            privateKeyFile.close();

            Aws::String publicKeyFilePath = outputFolder + "/public.pem.key";
            std::ofstream publicKeyFile(publicKeyFilePath);
            if (!publicKeyFile.is_open()) {
                std::cerr << "Error opening public key file, '" << publicKeyFilePath
                          << "'."
                          << std::endl;
                return false;
            }
            publicKeyFile << keyPair.GetPublicKey();
        }
    }
    else {
        std::cerr << "Error creating keys and certificate: "
                  << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}

//! Attach a principal to an AWS IoT thing.
/*!
  \param principal: A principal to attach.
  \param thingName: The name for the thing.
  \param clientConfiguration: AWS client configuration.
```

```
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::attachThingPrincipal(const Aws::String &principal,
                                       const Aws::String &thingName,
                                       const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::IoT::IoTClient client(clientConfiguration);
    Aws::IoT::Model::AttachThingPrincipalRequest request;
    request.SetPrincipal(principal);
    request.SetThingName(thingName);
    Aws::IoT::Model::AttachThingPrincipalOutcome outcome =
 client.AttachThingPrincipal(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully attached principal to thing." << std::endl;
    }
    else {
        std::cerr << "Failed to attach principal to thing." <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

Perform various operations on the AWS IoT thing.

```
    if (!updateThing(thingName, { {"location", "Office"}, {"firmwareVersion",
 "v2.0"} }, clientConfiguration)) {
        std::cerr << "Exiting because updateThing failed." << std::endl;
        cleanup(thingName, certificateARN, certificateID, "", "", false,
                clientConfiguration);
        return false;
    }

    printAsterisksLine();

    std::cout << "Now an endpoint will be retrieved for your account.\n" <<
 std::endl;
    std::cout << "An IoT Endpoint refers to a specific URL or Uniform Resource
 Locator that serves as the entry point\n"
    << "for communication between IoT devices and the AWS IoT service." <<
 std::endl;
```

```
    askQuestion("Press Enter to continue:", alwaysTrueTest);

    Aws::String endpoint;
    if (!describeEndpoint(endpoint, clientConfiguration)) {
        std::cerr << "Exiting because getEndpoint failed." << std::endl;
        cleanup(thingName, certificateARN, certificateID, "", "", false,
                clientConfiguration);
        return false;
    }
    std::cout <<"Your endpoint is " << endpoint << "." << std::endl;
    printAsterisksLine();

    std::cout << "Now the certificates in your account will be listed." <<
 std::endl;
    askQuestion("Press Enter to continue:", alwaysTrueTest);

    if (!listCertificates(clientConfiguration)) {
        std::cerr << "Exiting because listCertificates failed." << std::endl;
        cleanup(thingName, certificateARN, certificateID, "", "", false,
                clientConfiguration);
        return false;
    }

    printAsterisksLine();

    std::cout << "Now the shadow for the thing will be updated.\n" << std::endl;
    std::cout << "A thing shadow refers to a feature that enables you to create a
 virtual representation, or \"shadow,\"\n"
    << "of a physical device or thing. The thing shadow allows you to synchronize
 and control the state of a device between\n"
    << "the cloud and the device itself. and the AWS IoT service. For example, you
 can write and retrieve JSON data from a thing shadow." << std::endl;
    askQuestion("Press Enter to continue:", alwaysTrueTest);

    if (!updateThingShadow(thingName, R"({"state":{"reported":
{"temperature":25,"humidity":50}}})", clientConfiguration)) {
        std::cerr << "Exiting because updateThingShadow failed." << std::endl;
        cleanup(thingName, certificateARN, certificateID, "", "", false,
                clientConfiguration);
        return false;
    }

    printAsterisksLine();
```

```
   std::cout << "Now, the state information for the shadow will be retrieved.\n" <<
std::endl;
   askQuestion("Press Enter to continue:", alwaysTrueTest);

   Aws::String shadowState;
   if (!getThingShadow(thingName, shadowState, clientConfiguration)) {
       std::cerr << "Exiting because getThingShadow failed." << std::endl;
       cleanup(thingName, certificateARN, certificateID, "", "", false,
               clientConfiguration);
       return false;
   }
   std::cout << "The retrieved shadow state is: " << shadowState << std::endl;

   printAsterisksLine();

   std::cout << "A rule with now be added to to the thing.\n" << std::endl;
   std::cout << "Any user who has permission to create rules will be able to access
data processed by the rule." << std::endl;
   std::cout << "In this case, the rule will use an Simple Notification Service
(SNS) topic and an IAM rule." << std::endl;
   std::cout << "These resources will be created using a CloudFormation template."
<< std::endl;
   std::cout << "Stack creation may take a few minutes." << std::endl;

   askQuestion("Press Enter to continue: ", alwaysTrueTest);
   Aws::Map<Aws::String, Aws::String> outputs
=createCloudFormationStack(STACK_NAME,clientConfiguration);
   if (outputs.empty()) {
       std::cerr << "Exiting because createCloudFormationStack failed." <<
std::endl;
       cleanup(thingName, certificateARN, certificateID, "", "", false,
               clientConfiguration);
       return false;
   }

   // Retrieve the topic ARN and role ARN from the CloudFormation stack outputs.
   auto topicArnIter = outputs.find(SNS_TOPIC_ARN_OUTPUT);
   auto roleArnIter = outputs.find(ROLE_ARN_OUTPUT);
   if ((topicArnIter == outputs.end()) || (roleArnIter == outputs.end())) {
       std::cerr << "Exiting because output '" << SNS_TOPIC_ARN_OUTPUT <<
       "' or '" << ROLE_ARN_OUTPUT << "'not found in the CloudFormation stack."  <<
std::endl;
       cleanup(thingName, certificateARN, certificateID, STACK_NAME, "",
```

```
                false,
                clientConfiguration);
        return false;
    }

    Aws::String topicArn = topicArnIter->second;
    Aws::String roleArn = roleArnIter->second;
    Aws::String sqlStatement = "SELECT * FROM '";
    sqlStatement += MQTT_MESSAGE_TOPIC_FILTER;
    sqlStatement += "'";

    printAsterisksLine();

    std::cout << "Now a rule will be created.\n" << std::endl;
    std::cout << "Rules are an administrator-level action. Any user who has
 permission\n"
                << "to create rules will be able to access data processed by the
 rule." << std::endl;
    std::cout << "In this case, the rule will use an SNS topic" << std::endl;
    std::cout << "and the following SQL statement '" << sqlStatement << "'." <<
 std::endl;
    std::cout << "For more information on IoT SQL, see https://docs.aws.amazon.com/
iot/latest/developerguide/iot-sql-reference.html" << std::endl;
    Aws::String ruleName = askQuestion("Enter a rule name: ");
    if (!createTopicRule(ruleName, topicArn, sqlStatement, roleArn,
 clientConfiguration)) {
        std::cerr << "Exiting because createRule failed." << std::endl;
        cleanup(thingName, certificateARN, certificateID, STACK_NAME, "",
                false,
                clientConfiguration);
        return false;
    }

    printAsterisksLine();

    std::cout << "Now your rules will be listed.\n" << std::endl;
    askQuestion("Press Enter to continue: ", alwaysTrueTest);
    if (!listTopicRules(clientConfiguration)) {
        std::cerr << "Exiting because listRules failed." << std::endl;
        cleanup(thingName, certificateARN, certificateID, STACK_NAME, ruleName,
                false,
                clientConfiguration);
        return false;
    }
```

```
    printAsterisksLine();
    Aws::String queryString = "thingName:" + thingName;
    std::cout << "Now the AWS IoT fleet index will be queried with the query\n'"
    << queryString << "'.\n" << std::endl;
    std::cout << "For query information, see https://docs.aws.amazon.com/iot/latest/
developerguide/query-syntax.html" << std::endl;

    std::cout << "For this query to work, thing indexing must be enabled in your
 account.\n"
    << "This can be done with the awscli command line by calling 'aws iot update-
indexing-configuration'\n"
       << "or it can be done programmatically." << std::endl;
    std::cout << "For more information, see https://docs.aws.amazon.com/iot/latest/
developerguide/managing-index.html" << std::endl;
    if (askYesNoQuestion("Do you want to enable thing indexing in your account? (y/
n) "))
    {
        Aws::IoT::Model::ThingIndexingConfiguration thingIndexingConfiguration;

 thingIndexingConfiguration.SetThingIndexingMode(Aws::IoT::Model::ThingIndexingMode::REGISTR

 thingIndexingConfiguration.SetThingConnectivityIndexingMode(Aws::IoT::Model::ThingConnectiv
        // The ThingGroupIndexingConfiguration object is ignored if not set.
        Aws::IoT::Model::ThingGroupIndexingConfiguration
 thingGroupIndexingConfiguration;
        if (!updateIndexingConfiguration(thingIndexingConfiguration,
 thingGroupIndexingConfiguration, clientConfiguration)) {
            std::cerr << "Exiting because updateIndexingConfiguration failed." <<
 std::endl;
            cleanup(thingName, certificateARN, certificateID, STACK_NAME,
                    ruleName, false,
                    clientConfiguration);
            return false;
        }
    }

    if (!searchIndex(queryString, clientConfiguration)) {

        std::cerr << "Exiting because searchIndex failed." << std::endl;
        cleanup(thingName, certificateARN, certificateID, STACK_NAME, ruleName,
                false,
                clientConfiguration);
        return false;
```

```
    }
```

```
//! Update an AWS IoT thing with attributes.
/*!
  \param thingName: The name for the thing.
  \param attributeMap: A map of key/value attributes/
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::updateThing(const Aws::String &thingName,
                              const std::map<Aws::String, Aws::String>
 &attributeMap,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::IoT::IoTClient iotClient(clientConfiguration);
    Aws::IoT::Model::UpdateThingRequest request;
    request.SetThingName(thingName);
    Aws::IoT::Model::AttributePayload attributePayload;
    for (const auto &attribute: attributeMap) {
        attributePayload.AddAttributes(attribute.first, attribute.second);
    }
    request.SetAttributePayload(attributePayload);

    Aws::IoT::Model::UpdateThingOutcome outcome = iotClient.UpdateThing(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully updated thing " << thingName << std::endl;
    }
    else {
        std::cerr << "Failed to update thing " << thingName << ":" <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}

//! Describe the endpoint specific to the AWS account making the call.
/*!
  \param endpointResult: String to receive the endpoint result.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::describeEndpoint(Aws::String &endpointResult,
```

```
                                    const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::String endpoint;
    Aws::IoT::IoTClient iotClient(clientConfiguration);
    Aws::IoT::Model::DescribeEndpointRequest describeEndpointRequest;
    describeEndpointRequest.SetEndpointType(
            "iot:Data-ATS"); // Recommended endpoint type.

    Aws::IoT::Model::DescribeEndpointOutcome outcome = iotClient.DescribeEndpoint(
            describeEndpointRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully described endpoint." << std::endl;
        endpointResult = outcome.GetResult().GetEndpointAddress();
    }
    else {
        std::cerr << "Error describing endpoint" << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}

//! List certificates registered in the AWS account making the call.
/*!
   \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::listCertificates(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::IoT::IoTClient iotClient(clientConfiguration);
    Aws::IoT::Model::ListCertificatesRequest request;

    Aws::Vector<Aws::IoT::Model::Certificate> allCertificates;
    Aws::String marker; // Used to paginate results.
    do {
        if (!marker.empty()) {
            request.SetMarker(marker);
        }

        Aws::IoT::Model::ListCertificatesOutcome outcome =
 iotClient.ListCertificates(
                request);
```

```
        if (outcome.IsSuccess()) {
            const Aws::IoT::Model::ListCertificatesResult &result =
 outcome.GetResult();
            marker = result.GetNextMarker();
            allCertificates.insert(allCertificates.end(),
                                   result.GetCertificates().begin(),
                                   result.GetCertificates().end());
        }
        else {
            std::cerr << "Error: " << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    } while (!marker.empty());

    std::cout << allCertificates.size() << " certificate(s) found." << std::endl;

    for (auto &certificate: allCertificates) {
        std::cout << "Certificate ID: " << certificate.GetCertificateId() <<
 std::endl;
        std::cout << "Certificate ARN: " << certificate.GetCertificateArn()
                  << std::endl;
        std::cout << std::endl;
    }

    return true;
}

//! Update the shadow of an AWS IoT thing.
/*!
  \param thingName: The name for the thing.
  \param document: The state information, in JSON format.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::updateThingShadow(const Aws::String &thingName,
                                    const Aws::String &document,
                                    const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::IoTDataPlane::IoTDataPlaneClient iotDataPlaneClient(clientConfiguration);
    Aws::IoTDataPlane::Model::UpdateThingShadowRequest updateThingShadowRequest;
    updateThingShadowRequest.SetThingName(thingName);
    std::shared_ptr<std::stringstream> streamBuf =
 std::make_shared<std::stringstream>(
            document);
```

```
    updateThingShadowRequest.SetBody(streamBuf);
    Aws::IoTDataPlane::Model::UpdateThingShadowOutcome outcome =
 iotDataPlaneClient.UpdateThingShadow(
            updateThingShadowRequest);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully updated thing shadow." << std::endl;
    }
    else {
        std::cerr << "Error while updating thing shadow."
                  << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}

//! Get the shadow of an AWS IoT thing.
/*!
  \param thingName: The name for the thing.
  \param documentResult: String to receive the state information, in JSON format.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::getThingShadow(const Aws::String &thingName,
                                 Aws::String &documentResult,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::IoTDataPlane::IoTDataPlaneClient iotClient(clientConfiguration);
    Aws::IoTDataPlane::Model::GetThingShadowRequest request;
    request.SetThingName(thingName);
    auto outcome = iotClient.GetThingShadow(request);
    if (outcome.IsSuccess()) {
        std::stringstream ss;
        ss << outcome.GetResult().GetPayload().rdbuf();
        documentResult = ss.str();
    }
    else {
        std::cerr << "Error getting thing shadow: " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}

//! Create an AWS IoT rule with an SNS topic as the target.
```

```
/*!
  \param ruleName: The name for the rule.
  \param snsTopic: The SNS topic ARN for the action.
  \param sql: The SQL statement used to query the topic.
  \param roleARN: The IAM role ARN for the action.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool
AwsDoc::IoT::createTopicRule(const Aws::String &ruleName,
                             const Aws::String &snsTopicARN, const Aws::String &sql,
                             const Aws::String &roleARN,
                             const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::IoT::IoTClient iotClient(clientConfiguration);

    Aws::IoT::Model::CreateTopicRuleRequest request;
    request.SetRuleName(ruleName);

    Aws::IoT::Model::SnsAction snsAction;
    snsAction.SetTargetArn(snsTopicARN);
    snsAction.SetRoleArn(roleARN);

    Aws::IoT::Model::Action action;
    action.SetSns(snsAction);

    Aws::IoT::Model::TopicRulePayload topicRulePayload;
    topicRulePayload.SetSql(sql);
    topicRulePayload.SetActions({action});

    request.SetTopicRulePayload(topicRulePayload);
    auto outcome = iotClient.CreateTopicRule(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully created topic rule " << ruleName << "." <<
 std::endl;
    }
    else {
        std::cerr << "Error creating topic rule " << ruleName << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    return outcome.IsSuccess();
}

//! Lists the AWS IoT topic rules.
```

```
/*!
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::listTopicRules(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::IoT::IoTClient iotClient(clientConfiguration);
    Aws::IoT::Model::ListTopicRulesRequest request;

    Aws::Vector<Aws::IoT::Model::TopicRuleListItem> allRules;
    Aws::String nextToken; // Used for pagination.
    do {
        if (!nextToken.empty()) {
            request.SetNextToken(nextToken);
        }

        Aws::IoT::Model::ListTopicRulesOutcome outcome = iotClient.ListTopicRules(
                request);

        if (outcome.IsSuccess()) {
            const Aws::IoT::Model::ListTopicRulesResult &result =
 outcome.GetResult();
            allRules.insert(allRules.end(),
                            result.GetRules().cbegin(),
                            result.GetRules().cend());

            nextToken = result.GetNextToken();
        }
        else {
            std::cerr << "ListTopicRules error: " <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }

    } while (!nextToken.empty());

    std::cout << "ListTopicRules: " << allRules.size() << " rule(s) found."
              << std::endl;
    for (auto &rule: allRules) {
        std::cout << "  Rule name: " << rule.GetRuleName() << ", rule ARN: "
                  << rule.GetRuleArn() << "." << std::endl;
    }

    return true;
```

```
}

//! Query the AWS IoT fleet index.
//! For query information, see https://docs.aws.amazon.com/iot/latest/
developerguide/query-syntax.html
/*!
  \param: query: The query string.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::searchIndex(const Aws::String &query,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::IoT::IoTClient iotClient(clientConfiguration);

    Aws::IoT::Model::SearchIndexRequest request;
    request.SetQueryString(query);

    Aws::Vector<Aws::IoT::Model::ThingDocument> allThingDocuments;
    Aws::String nextToken; // Used for pagination.
    do {
        if (!nextToken.empty()) {
            request.SetNextToken(nextToken);
        }

        Aws::IoT::Model::SearchIndexOutcome outcome =
 iotClient.SearchIndex(request);

        if (outcome.IsSuccess()) {
            const Aws::IoT::Model::SearchIndexResult &result = outcome.GetResult();
            allThingDocuments.insert(allThingDocuments.end(),
                                     result.GetThings().cbegin(),
                                     result.GetThings().cend());
            nextToken = result.GetNextToken();

        }
        else {
            std::cerr << "Error in SearchIndex: " << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (!nextToken.empty());
```

```
    std::cout << allThingDocuments.size() << " thing document(s) found." <<
 std::endl;
    for (const auto thingDocument: allThingDocuments) {
        std::cout << "  Thing name: " << thingDocument.GetThingName() << "."
                  << std::endl;
    }
    return true;
}
```

Clean up resources.

```
bool
AwsDoc::IoT::cleanup(const Aws::String &thingName, const Aws::String
 &certificateARN,
                     const Aws::String &certificateID, const Aws::String &stackName,
                     const Aws::String &ruleName, bool askForConfirmation,
                     const Aws::Client::ClientConfiguration &clientConfiguration) {
    bool result = true;

    if (!ruleName.empty() && (!askForConfirmation ||
                              askYesNoQuestion("Delete the rule '" + ruleName +
                                               "'? (y/n) "))) {
        result &= deleteTopicRule(ruleName, clientConfiguration);
    }

    Aws::CloudFormation::CloudFormationClient
 cloudFormationClient(clientConfiguration);

    if (!stackName.empty() && (!askForConfirmation ||
                               askYesNoQuestion(
                                       "Delete the CloudFormation stack '" +
 stackName +
                                       "'? (y/n) "))) {
        result &= deleteStack(stackName, clientConfiguration);
    }

    if (!certificateARN.empty() && (!askForConfirmation ||
                                    askYesNoQuestion("Delete the certificate '" +
                                                     certificateARN + "'? (y/n) ")))
 {
        result &= detachThingPrincipal(certificateARN, thingName,
 clientConfiguration);
```

```
        result &= deleteCertificate(certificateID, clientConfiguration);
    }

    if (!thingName.empty() && (!askForConfirmation ||
                               askYesNoQuestion("Delete the thing '" + thingName +
                                                "'? (y/n) "))) {
        result &= deleteThing(thingName, clientConfiguration);
    }

    return result;
}
```

```
//! Detach a principal from an AWS IoT thing.
/*!
  \param principal: A principal to detach.
  \param thingName: The name for the thing.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::detachThingPrincipal(const Aws::String &principal,
                                       const Aws::String &thingName,
                                       const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::IoT::IoTClient iotClient(clientConfiguration);

    Aws::IoT::Model::DetachThingPrincipalRequest detachThingPrincipalRequest;
    detachThingPrincipalRequest.SetThingName(thingName);
    detachThingPrincipalRequest.SetPrincipal(principal);

    Aws::IoT::Model::DetachThingPrincipalOutcome outcome =
 iotClient.DetachThingPrincipal(
            detachThingPrincipalRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully detached principal " << principal << " from thing
 "
                  << thingName << std::endl;
    }
    else {
        std::cerr << "Failed to detach principal " << principal << " from thing "
                  << thingName << ": "
                  << outcome.GetError().GetMessage() << std::endl;
```

```
    }

    return outcome.IsSuccess();
}

//! Delete a certificate.
/*!
  \param certificateID: The ID of a certificate.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::deleteCertificate(const Aws::String &certificateID,
                                    const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::IoT::IoTClient iotClient(clientConfiguration);

    Aws::IoT::Model::DeleteCertificateRequest request;
    request.SetCertificateId(certificateID);

    Aws::IoT::Model::DeleteCertificateOutcome outcome = iotClient.DeleteCertificate(
            request);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted certificate " << certificateID <<
 std::endl;
    }
    else {
        std::cerr << "Error deleting certificate " << certificateID << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}

//! Delete an AWS IoT rule.
/*!
  \param ruleName: The name for the rule.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::deleteTopicRule(const Aws::String &ruleName,
                                  const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::IoT::IoTClient iotClient(clientConfiguration);
```

```
    Aws::IoT::Model::DeleteTopicRuleRequest request;
    request.SetRuleName(ruleName);

    Aws::IoT::Model::DeleteTopicRuleOutcome outcome = iotClient.DeleteTopicRule(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted rule " << ruleName << std::endl;
    }
    else {
        std::cerr << "Failed to delete rule " << ruleName <<
                  ": " << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}

//! Delete an AWS IoT thing.
/*!
  \param thingName: The name for the thing.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::deleteThing(const Aws::String &thingName,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::IoT::IoTClient iotClient(clientConfiguration);
    Aws::IoT::Model::DeleteThingRequest request;
    request.SetThingName(thingName);
    const auto outcome = iotClient.DeleteThing(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted thing " << thingName << std::endl;
    }
    else {
        std::cerr << "Error deleting thing " << thingName << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

Actions

`AttachThingPrincipal`

The following code example shows how to use `AttachThingPrincipal`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Attach a principal to an AWS IoT thing.
/*!
  \param principal: A principal to attach.
  \param thingName: The name for the thing.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::attachThingPrincipal(const Aws::String &principal,
                                       const Aws::String &thingName,
                                       const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::IoT::IoTClient client(clientConfiguration);
    Aws::IoT::Model::AttachThingPrincipalRequest request;
    request.SetPrincipal(principal);
    request.SetThingName(thingName);
    Aws::IoT::Model::AttachThingPrincipalOutcome outcome =
 client.AttachThingPrincipal(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully attached principal to thing." << std::endl;
    }
    else {
        std::cerr << "Failed to attach principal to thing." <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see AttachThingPrincipal in *AWS SDK for C++ API Reference*.

`CreateKeysAndCertificate`

The following code example shows how to use `CreateKeysAndCertificate`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Create keys and certificate for an Aws IoT device.
//! This routine will save certificates and keys to an output folder, if provided.
/*!
  \param outputFolder: Location for storing output in files, ignored when string is
 empty.
  \param certificateARNResult: A string to receive the ARN of the created
 certificate.
  \param certificateID: A string to receive the ID of the created certificate.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::createKeysAndCertificate(const Aws::String &outputFolder,
                                           Aws::String &certificateARNResult,
                                           Aws::String &certificateID,
                                           const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::IoT::IoTClient client(clientConfiguration);
    Aws::IoT::Model::CreateKeysAndCertificateRequest
 createKeysAndCertificateRequest;

    Aws::IoT::Model::CreateKeysAndCertificateOutcome outcome =
            client.CreateKeysAndCertificate(createKeysAndCertificateRequest);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully created a certificate and keys" << std::endl;
        certificateARNResult = outcome.GetResult().GetCertificateArn();
        certificateID = outcome.GetResult().GetCertificateId();
```

```
        std::cout << "Certificate ARN: " << certificateARNResult << ", certificate
ID: "
                  << certificateID << std::endl;

        if (!outputFolder.empty()) {
            std::cout << "Writing certificate and keys to the folder '" <<
outputFolder
                      << "'." << std::endl;
            std::cout << "Be sure these files are stored securely." << std::endl;

            Aws::String certificateFilePath = outputFolder + "/certificate.pem.crt";
            std::ofstream certificateFile(certificateFilePath);
            if (!certificateFile.is_open()) {
                std::cerr << "Error opening certificate file, '" <<
certificateFilePath
                          << "'."
                          << std::endl;
                return false;
            }
            certificateFile << outcome.GetResult().GetCertificatePem();
            certificateFile.close();

            const Aws::IoT::Model::KeyPair &keyPair =
outcome.GetResult().GetKeyPair();

            Aws::String privateKeyFilePath = outputFolder + "/private.pem.key";
            std::ofstream privateKeyFile(privateKeyFilePath);
            if (!privateKeyFile.is_open()) {
                std::cerr << "Error opening private key file, '" <<
privateKeyFilePath
                          << "'."
                          << std::endl;
                return false;
            }
            privateKeyFile << keyPair.GetPrivateKey();
            privateKeyFile.close();

            Aws::String publicKeyFilePath = outputFolder + "/public.pem.key";
            std::ofstream publicKeyFile(publicKeyFilePath);
            if (!publicKeyFile.is_open()) {
                std::cerr << "Error opening public key file, '" << publicKeyFilePath
                          << "'."
                          << std::endl;
                return false;
```

```
            }
            publicKeyFile << keyPair.GetPublicKey();
        }
    }
    else {
        std::cerr << "Error creating keys and certificate: "
                  << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see CreateKeysAndCertificate in *AWS SDK for C++ API Reference*.

`CreateThing`

The following code example shows how to use `CreateThing`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Create an AWS IoT thing.
/*!
  \param thingName: The name for the thing.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::createThing(const Aws::String &thingName,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::IoT::IoTClient iotClient(clientConfiguration);
    Aws::IoT::Model::CreateThingRequest createThingRequest;
    createThingRequest.SetThingName(thingName);

    Aws::IoT::Model::CreateThingOutcome outcome = iotClient.CreateThing(
            createThingRequest);
```

```
    if (outcome.IsSuccess()) {
        std::cout << "Successfully created thing " << thingName << std::endl;
    }
    else {
        std::cerr << "Failed to create thing " << thingName << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see CreateThing in *AWS SDK for C++ API Reference*.

`CreateTopicRule`

The following code example shows how to use `CreateTopicRule`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Create an AWS IoT rule with an SNS topic as the target.
/*!
  \param ruleName: The name for the rule.
  \param snsTopic: The SNS topic ARN for the action.
  \param sql: The SQL statement used to query the topic.
  \param roleARN: The IAM role ARN for the action.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool
AwsDoc::IoT::createTopicRule(const Aws::String &ruleName,
                             const Aws::String &snsTopicARN, const Aws::String &sql,
                             const Aws::String &roleARN,
                             const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::IoT::IoTClient iotClient(clientConfiguration);
```

```
    Aws::IoT::Model::CreateTopicRuleRequest request;
    request.SetRuleName(ruleName);

    Aws::IoT::Model::SnsAction snsAction;
    snsAction.SetTargetArn(snsTopicARN);
    snsAction.SetRoleArn(roleARN);

    Aws::IoT::Model::Action action;
    action.SetSns(snsAction);

    Aws::IoT::Model::TopicRulePayload topicRulePayload;
    topicRulePayload.SetSql(sql);
    topicRulePayload.SetActions({action});

    request.SetTopicRulePayload(topicRulePayload);
    auto outcome = iotClient.CreateTopicRule(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully created topic rule " << ruleName << "." <<
 std::endl;
    }
    else {
        std::cerr << "Error creating topic rule " << ruleName << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    return outcome.IsSuccess();
}
```

- For API details, see CreateTopicRule in *AWS SDK for C++ API Reference*.

`DeleteCertificate`

The following code example shows how to use `DeleteCertificate`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Delete a certificate.
/*!
  \param certificateID: The ID of a certificate.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::deleteCertificate(const Aws::String &certificateID,
                                    const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::IoT::IoTClient iotClient(clientConfiguration);

    Aws::IoT::Model::DeleteCertificateRequest request;
    request.SetCertificateId(certificateID);

    Aws::IoT::Model::DeleteCertificateOutcome outcome = iotClient.DeleteCertificate(
            request);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted certificate " << certificateID <<
 std::endl;
    }
    else {
        std::cerr << "Error deleting certificate " << certificateID << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DeleteCertificate in *AWS SDK for C++ API Reference*.

`DeleteThing`

The following code example shows how to use `DeleteThing`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Delete an AWS IoT thing.
/*!
  \param thingName: The name for the thing.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::deleteThing(const Aws::String &thingName,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::IoT::IoTClient iotClient(clientConfiguration);
    Aws::IoT::Model::DeleteThingRequest request;
    request.SetThingName(thingName);
    const auto outcome = iotClient.DeleteThing(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted thing " << thingName << std::endl;
    }
    else {
        std::cerr << "Error deleting thing " << thingName << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DeleteThing in *AWS SDK for C++ API Reference*.

`DeleteTopicRule`

The following code example shows how to use `DeleteTopicRule`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Delete an AWS IoT rule.
/*!
  \param ruleName: The name for the rule.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::deleteTopicRule(const Aws::String &ruleName,
                                  const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::IoT::IoTClient iotClient(clientConfiguration);
    Aws::IoT::Model::DeleteTopicRuleRequest request;
    request.SetRuleName(ruleName);

    Aws::IoT::Model::DeleteTopicRuleOutcome outcome = iotClient.DeleteTopicRule(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted rule " << ruleName << std::endl;
    }
    else {
        std::cerr << "Failed to delete rule " << ruleName <<
                  ": " << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DeleteTopicRule in *AWS SDK for C++ API Reference*.

`DescribeEndpoint`

The following code example shows how to use `DescribeEndpoint`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Describe the endpoint specific to the AWS account making the call.
/*!
  \param endpointResult: String to receive the endpoint result.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::describeEndpoint(Aws::String &endpointResult,
                                   const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::String endpoint;
    Aws::IoT::IoTClient iotClient(clientConfiguration);
    Aws::IoT::Model::DescribeEndpointRequest describeEndpointRequest;
    describeEndpointRequest.SetEndpointType(
            "iot:Data-ATS"); // Recommended endpoint type.

    Aws::IoT::Model::DescribeEndpointOutcome outcome = iotClient.DescribeEndpoint(
            describeEndpointRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully described endpoint." << std::endl;
        endpointResult = outcome.GetResult().GetEndpointAddress();
    }
    else {
        std::cerr << "Error describing endpoint" << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DescribeEndpoint in *AWS SDK for C++ API Reference*.

`DescribeThing`

The following code example shows how to use `DescribeThing`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Describe an AWS IoT thing.
/*!
  \param thingName: The name for the thing.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::describeThing(const Aws::String &thingName,
                                const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::IoT::IoTClient iotClient(clientConfiguration);

    Aws::IoT::Model::DescribeThingRequest request;
    request.SetThingName(thingName);

    Aws::IoT::Model::DescribeThingOutcome outcome =
 iotClient.DescribeThing(request);

    if (outcome.IsSuccess()) {
        const Aws::IoT::Model::DescribeThingResult &result = outcome.GetResult();
        std::cout << "Retrieved thing '" << result.GetThingName() << "'" <<
 std::endl;
        std::cout << "thingArn: " << result.GetThingArn() << std::endl;
        std::cout << result.GetAttributes().size() << " attribute(s) retrieved"
                  << std::endl;
        for (const auto &attribute: result.GetAttributes()) {
            std::cout << "  attribute: " << attribute.first << "=" <<
 attribute.second
                      << std::endl;
        }
    }
    else {
```

```
        std::cerr << "Error describing thing " << thingName << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DescribeThing in *AWS SDK for C++ API Reference*.

`DetachThingPrincipal`

The following code example shows how to use `DetachThingPrincipal`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Detach a principal from an AWS IoT thing.
/*!
  \param principal: A principal to detach.
  \param thingName: The name for the thing.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::detachThingPrincipal(const Aws::String &principal,
                                       const Aws::String &thingName,
                                       const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::IoT::IoTClient iotClient(clientConfiguration);

    Aws::IoT::Model::DetachThingPrincipalRequest detachThingPrincipalRequest;
    detachThingPrincipalRequest.SetThingName(thingName);
    detachThingPrincipalRequest.SetPrincipal(principal);

    Aws::IoT::Model::DetachThingPrincipalOutcome outcome =
 iotClient.DetachThingPrincipal(
            detachThingPrincipalRequest);
```

```
    if (outcome.IsSuccess()) {
        std::cout << "Successfully detached principal " << principal << " from thing
 "
                  << thingName << std::endl;
    }
    else {
        std::cerr << "Failed to detach principal " << principal << " from thing "
                  << thingName << ": "
                  << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DetachThingPrincipal in *AWS SDK for C++ API Reference*.

`ListCertificates`

The following code example shows how to use `ListCertificates`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! List certificates registered in the AWS account making the call.
/*!
   \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::listCertificates(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::IoT::IoTClient iotClient(clientConfiguration);
    Aws::IoT::Model::ListCertificatesRequest request;

    Aws::Vector<Aws::IoT::Model::Certificate> allCertificates;
```

```
    Aws::String marker; // Used to paginate results.
    do {
        if (!marker.empty()) {
            request.SetMarker(marker);
        }

        Aws::IoT::Model::ListCertificatesOutcome outcome =
 iotClient.ListCertificates(
                request);

        if (outcome.IsSuccess()) {
            const Aws::IoT::Model::ListCertificatesResult &result =
 outcome.GetResult();
            marker = result.GetNextMarker();
            allCertificates.insert(allCertificates.end(),
                                   result.GetCertificates().begin(),
                                   result.GetCertificates().end());
        }
        else {
            std::cerr << "Error: " << outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    } while (!marker.empty());

    std::cout << allCertificates.size() << " certificate(s) found." << std::endl;

    for (auto &certificate: allCertificates) {
        std::cout << "Certificate ID: " << certificate.GetCertificateId() <<
 std::endl;
        std::cout << "Certificate ARN: " << certificate.GetCertificateArn()
                  << std::endl;
        std::cout << std::endl;
    }

    return true;
}
```

- For API details, see ListCertificates in *AWS SDK for C++ API Reference*.

`SearchIndex`

The following code example shows how to use `SearchIndex`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Query the AWS IoT fleet index.
//! For query information, see https://docs.aws.amazon.com/iot/latest/
developerguide/query-syntax.html
/*!
  \param: query: The query string.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::searchIndex(const Aws::String &query,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::IoT::IoTClient iotClient(clientConfiguration);

    Aws::IoT::Model::SearchIndexRequest request;
    request.SetQueryString(query);

    Aws::Vector<Aws::IoT::Model::ThingDocument> allThingDocuments;
    Aws::String nextToken; // Used for pagination.
    do {
        if (!nextToken.empty()) {
            request.SetNextToken(nextToken);
        }

        Aws::IoT::Model::SearchIndexOutcome outcome =
 iotClient.SearchIndex(request);

        if (outcome.IsSuccess()) {
            const Aws::IoT::Model::SearchIndexResult &result = outcome.GetResult();
            allThingDocuments.insert(allThingDocuments.end(),
                                     result.GetThings().cbegin(),
                                     result.GetThings().cend());
            nextToken = result.GetNextToken();

        }
```

```
        else {
            std::cerr << "Error in SearchIndex: " << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (!nextToken.empty());

    std::cout << allThingDocuments.size() << " thing document(s) found." <<
 std::endl;
    for (const auto thingDocument: allThingDocuments) {
        std::cout << "  Thing name: " << thingDocument.GetThingName() << "."
                  << std::endl;
    }
    return true;
}
```

- For API details, see SearchIndex in *AWS SDK for C++ API Reference*.

`UpdateIndexingConfiguration`

The following code example shows how to use `UpdateIndexingConfiguration`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Update the indexing configuration.
/*!
  \param thingIndexingConfiguration: A ThingIndexingConfiguration object which is
 ignored if not set.
  \param thingGroupIndexingConfiguration: A ThingGroupIndexingConfiguration object
 which is ignored if not set.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::updateIndexingConfiguration(
```

```
        const Aws::IoT::Model::ThingIndexingConfiguration
 &thingIndexingConfiguration,
        const Aws::IoT::Model::ThingGroupIndexingConfiguration
 &thingGroupIndexingConfiguration,
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::IoT::IoTClient iotClient(clientConfiguration);

    Aws::IoT::Model::UpdateIndexingConfigurationRequest request;

    if (thingIndexingConfiguration.ThingIndexingModeHasBeenSet()) {
        request.SetThingIndexingConfiguration(thingIndexingConfiguration);
    }

    if (thingGroupIndexingConfiguration.ThingGroupIndexingModeHasBeenSet()) {
        request.SetThingGroupIndexingConfiguration(thingGroupIndexingConfiguration);
    }

    Aws::IoT::Model::UpdateIndexingConfigurationOutcome outcome =
 iotClient.UpdateIndexingConfiguration(
            request);

    if (outcome.IsSuccess()) {
        std::cout << "UpdateIndexingConfiguration succeeded." << std::endl;
    }
    else {
        std::cerr << "UpdateIndexingConfiguration failed."
                  << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see [UpdateIndexingConfiguration](#) in *AWS SDK for C++ API Reference*.

`UpdateThing`

The following code example shows how to use `UpdateThing`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Update an AWS IoT thing with attributes.
/*!
  \param thingName: The name for the thing.
  \param attributeMap: A map of key/value attributes/
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::updateThing(const Aws::String &thingName,
                              const std::map<Aws::String, Aws::String>
 &attributeMap,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::IoT::IoTClient iotClient(clientConfiguration);
    Aws::IoT::Model::UpdateThingRequest request;
    request.SetThingName(thingName);
    Aws::IoT::Model::AttributePayload attributePayload;
    for (const auto &attribute: attributeMap) {
        attributePayload.AddAttributes(attribute.first, attribute.second);
    }
    request.SetAttributePayload(attributePayload);

    Aws::IoT::Model::UpdateThingOutcome outcome = iotClient.UpdateThing(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully updated thing " << thingName << std::endl;
    }
    else {
        std::cerr << "Failed to update thing " << thingName << ":" <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see UpdateThing in *AWS SDK for C++ API Reference*.

AWS IoT data examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with AWS IoT data.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Actions

Actions

`GetThingShadow`

The following code example shows how to use `GetThingShadow`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Get the shadow of an AWS IoT thing.
/*!
  \param thingName: The name for the thing.
  \param documentResult: String to receive the state information, in JSON format.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::getThingShadow(const Aws::String &thingName,
                                 Aws::String &documentResult,
```

```
                                    const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::IoTDataPlane::IoTDataPlaneClient iotClient(clientConfiguration);
    Aws::IoTDataPlane::Model::GetThingShadowRequest request;
    request.SetThingName(thingName);
    auto outcome = iotClient.GetThingShadow(request);
    if (outcome.IsSuccess()) {
        std::stringstream ss;
        ss << outcome.GetResult().GetPayload().rdbuf();
        documentResult = ss.str();
    }
    else {
        std::cerr << "Error getting thing shadow: " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see GetThingShadow in *AWS SDK for C++ API Reference*.

`UpdateThingShadow`

The following code example shows how to use `UpdateThingShadow`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Update the shadow of an AWS IoT thing.
/*!
  \param thingName: The name for the thing.
  \param document: The state information, in JSON format.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::IoT::updateThingShadow(const Aws::String &thingName,
```

```
                                    const Aws::String &document,
                                    const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::IoTDataPlane::IoTDataPlaneClient iotDataPlaneClient(clientConfiguration);
    Aws::IoTDataPlane::Model::UpdateThingShadowRequest updateThingShadowRequest;
    updateThingShadowRequest.SetThingName(thingName);
    std::shared_ptr<std::stringstream> streamBuf =
 std::make_shared<std::stringstream>(
            document);
    updateThingShadowRequest.SetBody(streamBuf);
    Aws::IoTDataPlane::Model::UpdateThingShadowOutcome outcome =
 iotDataPlaneClient.UpdateThingShadow(
            updateThingShadowRequest);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully updated thing shadow." << std::endl;
    }
    else {
        std::cerr << "Error while updating thing shadow."
                  << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see UpdateThingShadow in *AWS SDK for C++ API Reference*.

Lambda examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with Lambda.

Basics are code examples that show you how to perform the essential operations within a service.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Scenarios are code examples that show you how to accomplish specific tasks by calling multiple functions within a service or combined with other AWS services.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Get started
- Basics
- Actions
- Scenarios

Get started

Hello Lambda

The following code example shows how to get started using Lambda.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Code for the CMakeLists.txt CMake file.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS lambda)

# Set this project's name.
project("hello_lambda")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
```

```
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD AND AWSSDK_INSTALL_AS_SHARED_LIBS)
     # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

     # set(BIN_SUB_DIR "/Debug") # if you are building from the command line you may
 need to uncomment this
                                     # and set the proper subdirectory to the
 executables' location.

     AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_lambda.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Code for the hello_lambda.cpp source file.

```
#include <aws/core/Aws.h>
#include <aws/lambda/LambdaClient.h>
#include <aws/lambda/model/ListFunctionsRequest.h>
#include <iostream>

/*
 *  A "Hello Lambda" starter application which initializes an AWS Lambda (Lambda)
 client and lists the Lambda functions.
 *
 *  main function
 *
 *  Usage: 'hello_lambda'
 *
```

```
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::Lambda::LambdaClient lambdaClient(clientConfig);
        std::vector<Aws::String> functions;
        Aws::String marker; // Used for pagination.

        do {
            Aws::Lambda::Model::ListFunctionsRequest request;
            if (!marker.empty()) {
                request.SetMarker(marker);
            }

            Aws::Lambda::Model::ListFunctionsOutcome outcome =
 lambdaClient.ListFunctions(
                    request);

            if (outcome.IsSuccess()) {
                const Aws::Lambda::Model::ListFunctionsResult &listFunctionsResult =
 outcome.GetResult();
                std::cout << listFunctionsResult.GetFunctions().size()
                          << " lambda functions were retrieved." << std::endl;

                for (const Aws::Lambda::Model::FunctionConfiguration
 &functionConfiguration: listFunctionsResult.GetFunctions()) {
                    functions.push_back(functionConfiguration.GetFunctionName());
                    std::cout << functions.size() << "  "
                              << functionConfiguration.GetDescription() <<
 std::endl;
                    std::cout << "   "
                              <<
 Aws::Lambda::Model::RuntimeMapper::GetNameForRuntime(
                                      functionConfiguration.GetRuntime()) << ": "
                              << functionConfiguration.GetHandler()
```

```
                                << std::endl;
                    }
                    marker = listFunctionsResult.GetNextMarker();
                } else {
                    std::cerr << "Error with Lambda::ListFunctions. "
                              << outcome.GetError().GetMessage()
                              << std::endl;
                    result = 1;
                    break;
                }
            } while (!marker.empty());
        }


        Aws::ShutdownAPI(options); // Should only be called once.
        return result;
    }
```

- For API details, see ListFunctions in *AWS SDK for C++ API Reference*.

Basics

Learn the basics

The following code example shows how to:

- Create an IAM role and Lambda function, then upload handler code.
- Invoke the function with a single parameter and get results.
- Update the function code and configure with an environment variable.
- Invoke the function with new parameters and get results. Display the returned execution log.
- List the functions for your account, then clean up resources.

For more information, see Create a Lambda function with the console.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Get started with functions scenario.
/*!
 \param clientConfig: AWS client configuration.
 \return bool: Successful completion.
 */
bool AwsDoc::Lambda::getStartedWithFunctionsScenario(
        const Aws::Client::ClientConfiguration &clientConfig) {

    Aws::Lambda::LambdaClient client(clientConfig);

    // 1. Create an AWS Identity and Access Management (IAM) role for Lambda
 function.
    Aws::String roleArn;
    if (!getIamRoleArn(roleArn, clientConfig)) {
        return false;
    }

    // 2. Create a Lambda function.
    int seconds = 0;
    do {
        Aws::Lambda::Model::CreateFunctionRequest request;
        request.SetFunctionName(LAMBDA_NAME);
        request.SetDescription(LAMBDA_DESCRIPTION); // Optional.
#if USE_CPP_LAMBDA_FUNCTION
        request.SetRuntime(Aws::Lambda::Model::Runtime::provided_al2);
        request.SetTimeout(15);
        request.SetMemorySize(128);

        // Assume the AWS Lambda function was built in Docker with same architecture
        // as this code.
#if  defined(__x86_64__)
        request.SetArchitectures({Aws::Lambda::Model::Architecture::x86_64});
#elif defined(__aarch64__)
        request.SetArchitectures({Aws::Lambda::Model::Architecture::arm64});
```

```
#else
#error "Unimplemented architecture"
#endif // defined(architecture)
#else
        request.SetRuntime(Aws::Lambda::Model::Runtime::python3_9);
#endif
        request.SetRole(roleArn);
        request.SetHandler(LAMBDA_HANDLER_NAME);
        request.SetPublish(true);
        Aws::Lambda::Model::FunctionCode code;
        std::ifstream ifstream(INCREMENT_LAMBDA_CODE.c_str(),
                               std::ios_base::in | std::ios_base::binary);
        if (!ifstream.is_open()) {
            std::cerr << "Error opening file " << INCREMENT_LAMBDA_CODE << "." <<
 std::endl;

#if USE_CPP_LAMBDA_FUNCTION
            std::cerr
                    << "The cpp Lambda function must be built following the
 instructions in the cpp_lambda/README.md file. "
                    << std::endl;
#endif
            deleteIamRole(clientConfig);
            return false;
        }

        Aws::StringStream buffer;
        buffer << ifstream.rdbuf();

        code.SetZipFile(Aws::Utils::ByteBuffer((unsigned char *)
 buffer.str().c_str(),
                                               buffer.str().length()));
        request.SetCode(code);

        Aws::Lambda::Model::CreateFunctionOutcome outcome = client.CreateFunction(
                request);

        if (outcome.IsSuccess()) {
            std::cout << "The lambda function was successfully created. " << seconds
                      << " seconds elapsed." << std::endl;
            break;
        }
        else if (outcome.GetError().GetErrorType() ==
                 Aws::Lambda::LambdaErrors::INVALID_PARAMETER_VALUE &&
```

```
                outcome.GetError().GetMessage().find("role") >= 0) {
            if ((seconds % 5) == 0) { // Log status every 10 seconds.
                std::cout
                        << "Waiting for the IAM role to become available as a
CreateFunction parameter. "
                        << seconds
                        << " seconds elapsed." << std::endl;

                std::cout << outcome.GetError().GetMessage() << std::endl;
            }
        }
        else {
            std::cerr << "Error with CreateFunction. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            deleteIamRole(clientConfig);
            return false;
        }
        ++seconds;
        std::this_thread::sleep_for(std::chrono::seconds(1));
    } while (60 > seconds);

    std::cout << "The current Lambda function increments 1 by an input." <<
std::endl;

    // 3.  Invoke the Lambda function.
    {
        int increment = askQuestionForInt("Enter an increment integer: ");

        Aws::Lambda::Model::InvokeResult invokeResult;
        Aws::Utils::Json::JsonValue jsonPayload;
        jsonPayload.WithString("action", "increment");
        jsonPayload.WithInteger("number", increment);
        if (invokeLambdaFunction(jsonPayload, Aws::Lambda::Model::LogType::Tail,
                                 invokeResult, client)) {
            Aws::Utils::Json::JsonValue jsonValue(invokeResult.GetPayload());
            Aws::Map<Aws::String, Aws::Utils::Json::JsonView> values =
                    jsonValue.View().GetAllObjects();
            auto iter = values.find("result");
            if (iter != values.end() && iter->second.IsIntegerType()) {
                {
                    std::cout << INCREMENT_RESUlT_PREFIX
                              << iter->second.AsInteger() << std::endl;
                }
```

```
            }
            else {
                std::cout << "There was an error in execution. Here is the log."
                          << std::endl;
                Aws::Utils::ByteBuffer buffer =
 Aws::Utils::HashingUtils::Base64Decode(
                        invokeResult.GetLogResult());
                std::cout << "With log " << buffer.GetUnderlyingData() << std::endl;
            }
        }
    }

    std::cout
            << "The Lambda function will now be updated with new code. Press return
 to continue, ";
    Aws::String answer;
    std::getline(std::cin, answer);

    // 4.  Update the Lambda function code.
    {
        Aws::Lambda::Model::UpdateFunctionCodeRequest request;
        request.SetFunctionName(LAMBDA_NAME);
        std::ifstream ifstream(CALCULATOR_LAMBDA_CODE.c_str(),
                               std::ios_base::in | std::ios_base::binary);
        if (!ifstream.is_open()) {
            std::cerr << "Error opening file " << INCREMENT_LAMBDA_CODE << "." <<
 std::endl;

#if USE_CPP_LAMBDA_FUNCTION
            std::cerr
                    << "The cpp Lambda function must be built following the
 instructions in the cpp_lambda/README.md file. "
                    << std::endl;
#endif
            deleteLambdaFunction(client);
            deleteIamRole(clientConfig);
            return false;
        }

        Aws::StringStream buffer;
        buffer << ifstream.rdbuf();
        request.SetZipFile(
                Aws::Utils::ByteBuffer((unsigned char *) buffer.str().c_str(),
                                       buffer.str().length()));
```

```
        request.SetPublish(true);

        Aws::Lambda::Model::UpdateFunctionCodeOutcome outcome =
client.UpdateFunctionCode(
                request);

        if (outcome.IsSuccess()) {
            std::cout << "The lambda code was successfully updated." << std::endl;
        }
        else {
            std::cerr << "Error with Lambda::UpdateFunctionCode. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
    }

    std::cout
            << "This function uses an environment variable to control the logging
level."
            << std::endl;
    std::cout
            << "UpdateFunctionConfiguration will be used to set the LOG_LEVEL to
DEBUG."
            << std::endl;
    seconds = 0;

    // 5.  Update the Lambda function configuration.
    do {
        ++seconds;
        std::this_thread::sleep_for(std::chrono::seconds(1));
        Aws::Lambda::Model::UpdateFunctionConfigurationRequest request;
        request.SetFunctionName(LAMBDA_NAME);
        Aws::Lambda::Model::Environment environment;
        environment.AddVariables("LOG_LEVEL", "DEBUG");
        request.SetEnvironment(environment);

        Aws::Lambda::Model::UpdateFunctionConfigurationOutcome outcome =
client.UpdateFunctionConfiguration(
                request);

        if (outcome.IsSuccess()) {
            std::cout << "The lambda configuration was successfully updated."
                      << std::endl;
            break;
```

```
        }

            // RESOURCE_IN_USE: function code update not completed.
        else if (outcome.GetError().GetErrorType() !=
                 Aws::Lambda::LambdaErrors::RESOURCE_IN_USE) {
            if ((seconds % 10) == 0) { // Log status every 10 seconds.
                std::cout << "Lambda function update in progress . After " <<
seconds
                          << " seconds elapsed." << std::endl;
            }
        }
        else {
            std::cerr << "Error with Lambda::UpdateFunctionConfiguration. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }

    } while (0 < seconds);

    if (0 > seconds) {
        std::cerr << "Function failed to become active." << std::endl;
    }
    else {
        std::cout << "Updated function active after " << seconds << " seconds."
                  << std::endl;
    }

    std::cout
            << "\nThe new code applies an arithmetic operator to two variables, x an
y."
            << std::endl;
    std::vector<Aws::String> operators = {"plus", "minus", "times", "divided-by"};
    for (size_t i = 0; i < operators.size(); ++i) {
        std::cout << "   " << i + 1 << " " << operators[i] << std::endl;
    }

    // 6.  Invoke the updated Lambda function.
    do {
        int operatorIndex = askQuestionForIntRange("Select an operator index 1 - 4
", 1,
                                                   4);
        int x = askQuestionForInt("Enter an integer for the x value ");
        int y = askQuestionForInt("Enter an integer for the y value ");
```

```
        Aws::Utils::Json::JsonValue calculateJsonPayload;
        calculateJsonPayload.WithString("action", operators[operatorIndex - 1]);
        calculateJsonPayload.WithInteger("x", x);
        calculateJsonPayload.WithInteger("y", y);
        Aws::Lambda::Model::InvokeResult calculatedResult;
        if (invokeLambdaFunction(calculateJsonPayload,
                                 Aws::Lambda::Model::LogType::Tail,
                                 calculatedResult, client)) {
            Aws::Utils::Json::JsonValue jsonValue(calculatedResult.GetPayload());
            Aws::Map<Aws::String, Aws::Utils::Json::JsonView> values =
                    jsonValue.View().GetAllObjects();
            auto iter = values.find("result");
            if (iter != values.end() && iter->second.IsIntegerType()) {
                std::cout << ARITHMETIC_RESULT_PREFIX << x << " "
                          << operators[operatorIndex - 1] << " "
                          << y << " is " << iter->second.AsInteger() << std::endl;
            }
            else if (iter != values.end() && iter->second.IsFloatingPointType()) {
                std::cout << ARITHMETIC_RESULT_PREFIX << x << " "
                          << operators[operatorIndex - 1] << " "
                          << y << " is " << iter->second.AsDouble() << std::endl;
            }
            else {
                std::cout << "There was an error in execution. Here is the log."
                          << std::endl;
                Aws::Utils::ByteBuffer buffer =
Aws::Utils::HashingUtils::Base64Decode(
                        calculatedResult.GetLogResult());
                std::cout << "With log " << buffer.GetUnderlyingData() << std::endl;
            }
        }

        answer = askQuestion("Would you like to try another operation? (y/n) ");
    } while (answer == "y");

    std::cout
            << "A list of the lambda functions will be retrieved. Press return to
continue, ";
    std::getline(std::cin, answer);

    // 7.  List the Lambda functions.

    std::vector<Aws::String> functions;
    Aws::String marker;
```

```
   do {
       Aws::Lambda::Model::ListFunctionsRequest request;
       if (!marker.empty()) {
           request.SetMarker(marker);
       }

       Aws::Lambda::Model::ListFunctionsOutcome outcome = client.ListFunctions(
               request);

       if (outcome.IsSuccess()) {
           const Aws::Lambda::Model::ListFunctionsResult &result =
outcome.GetResult();
           std::cout << result.GetFunctions().size()
                     << " lambda functions were retrieved." << std::endl;

           for (const Aws::Lambda::Model::FunctionConfiguration
&functionConfiguration: result.GetFunctions()) {
               functions.push_back(functionConfiguration.GetFunctionName());
               std::cout << functions.size() << "  "
                         << functionConfiguration.GetDescription() << std::endl;
               std::cout << "   "
                         << Aws::Lambda::Model::RuntimeMapper::GetNameForRuntime(
                                 functionConfiguration.GetRuntime()) << ": "
                         << functionConfiguration.GetHandler()
                         << std::endl;
           }
           marker = result.GetNextMarker();
       }
       else {
           std::cerr << "Error with Lambda::ListFunctions. "
                     << outcome.GetError().GetMessage()
                     << std::endl;
       }
   } while (!marker.empty());

   // 8.  Get a Lambda function.
   if (!functions.empty()) {
       std::stringstream question;
       question << "Choose a function to retrieve between 1 and " <<
functions.size()
                << " ";
       int functionIndex = askQuestionForIntRange(question.str(), 1,
```

```
 static_cast<int>(functions.size()));

        Aws::String functionName = functions[functionIndex - 1];

        Aws::Lambda::Model::GetFunctionRequest request;
        request.SetFunctionName(functionName);

        Aws::Lambda::Model::GetFunctionOutcome outcome =
 client.GetFunction(request);

        if (outcome.IsSuccess()) {
            std::cout << "Function retrieve.\n" <<

 outcome.GetResult().GetConfiguration().Jsonize().View().WriteReadable()
                      << std::endl;
        }
        else {
            std::cerr << "Error with Lambda::GetFunction. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
    }

    std::cout << "The resources will be deleted. Press return to continue, ";
    std::getline(std::cin, answer);

    // 9.  Delete the Lambda function.
    bool result = deleteLambdaFunction(client);

    // 10. Delete the IAM role.
    return result && deleteIamRole(clientConfig);
}

//! Routine which invokes a Lambda function and returns the result.
/*!
 \param jsonPayload: Payload for invoke function.
 \param logType: Log type setting for invoke function.
 \param invokeResult: InvokeResult object to receive the result.
 \param client: Lambda client.
 \return bool: Successful completion.
 */
bool
AwsDoc::Lambda::invokeLambdaFunction(const Aws::Utils::Json::JsonValue &jsonPayload,
```

```
                                    Aws::Lambda::Model::LogType logType,
                                    Aws::Lambda::Model::InvokeResult &invokeResult,
                                    const Aws::Lambda::LambdaClient &client) {
   int seconds = 0;
   bool result = false;
   /*
    * In this example, the Invoke function can be called before recently created
resources are
    * available.  The Invoke function is called repeatedly until the resources are
    * available.
    */
   do {
       Aws::Lambda::Model::InvokeRequest request;
       request.SetFunctionName(LAMBDA_NAME);
       request.SetLogType(logType);
       std::shared_ptr<Aws::IOStream> payload = Aws::MakeShared<Aws::StringStream>(
               "FunctionTest");
       *payload << jsonPayload.View().WriteReadable();
       request.SetBody(payload);
       request.SetContentType("application/json");
       Aws::Lambda::Model::InvokeOutcome outcome = client.Invoke(request);

       if (outcome.IsSuccess()) {
           invokeResult = std::move(outcome.GetResult());
           result = true;
           break;
       }

           // ACCESS_DENIED: because the role is not available yet.
           // RESOURCE_CONFLICT: because the Lambda function is being created or
updated.
       else if ((outcome.GetError().GetErrorType() ==
                 Aws::Lambda::LambdaErrors::ACCESS_DENIED) ||
                (outcome.GetError().GetErrorType() ==
                 Aws::Lambda::LambdaErrors::RESOURCE_CONFLICT)) {
           if ((seconds % 5) == 0) { // Log status every 10 seconds.
               std::cout << "Waiting for the invoke api to be available, status "
<<
                         ((outcome.GetError().GetErrorType() ==
                           Aws::Lambda::LambdaErrors::ACCESS_DENIED ?
                           "ACCESS_DENIED" : "RESOURCE_CONFLICT")) << ". " <<
seconds
                         << " seconds elapsed." << std::endl;
           }
```

```
        }
        else {
            std::cerr << "Error with Lambda::InvokeRequest. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            break;
        }
        ++seconds;
        std::this_thread::sleep_for(std::chrono::seconds(1));
    } while (seconds < 60);

    return result;
}
```

- For API details, see the following topics in *AWS SDK for C++ API Reference*.
  - CreateFunction
  - DeleteFunction
  - GetFunction
  - Invoke
  - ListFunctions
  - UpdateFunctionCode
  - UpdateFunctionConfiguration

Actions

`CreateFunction`

The following code example shows how to use `CreateFunction`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
 (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Lambda::LambdaClient client(clientConfig);

        Aws::Lambda::Model::CreateFunctionRequest request;
        request.SetFunctionName(LAMBDA_NAME);
        request.SetDescription(LAMBDA_DESCRIPTION); // Optional.
#if USE_CPP_LAMBDA_FUNCTION
        request.SetRuntime(Aws::Lambda::Model::Runtime::provided_al2);
        request.SetTimeout(15);
        request.SetMemorySize(128);

        // Assume the AWS Lambda function was built in Docker with same architecture
        // as this code.
#if  defined(__x86_64__)
        request.SetArchitectures({Aws::Lambda::Model::Architecture::x86_64});
#elif defined(__aarch64__)
        request.SetArchitectures({Aws::Lambda::Model::Architecture::arm64});
#else
#error "Unimplemented architecture"
#endif // defined(architecture)
#else
        request.SetRuntime(Aws::Lambda::Model::Runtime::python3_9);
#endif
        request.SetRole(roleArn);
        request.SetHandler(LAMBDA_HANDLER_NAME);
        request.SetPublish(true);
        Aws::Lambda::Model::FunctionCode code;
        std::ifstream ifstream(INCREMENT_LAMBDA_CODE.c_str(),
                               std::ios_base::in | std::ios_base::binary);
        if (!ifstream.is_open()) {
            std::cerr << "Error opening file " << INCREMENT_LAMBDA_CODE << "." <<
 std::endl;

#if USE_CPP_LAMBDA_FUNCTION
            std::cerr
                    << "The cpp Lambda function must be built following the
 instructions in the cpp_lambda/README.md file. "
                    << std::endl;
#endif
```

```
            deleteIamRole(clientConfig);
            return false;
        }

        Aws::StringStream buffer;
        buffer << ifstream.rdbuf();

        code.SetZipFile(Aws::Utils::ByteBuffer((unsigned char *)
buffer.str().c_str(),
                                               buffer.str().length()));
        request.SetCode(code);

        Aws::Lambda::Model::CreateFunctionOutcome outcome = client.CreateFunction(
                request);

        if (outcome.IsSuccess()) {
            std::cout << "The lambda function was successfully created. " << seconds
                      << " seconds elapsed." << std::endl;
            break;
        }

        else {
            std::cerr << "Error with CreateFunction. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            deleteIamRole(clientConfig);
            return false;
        }
```

- For API details, see CreateFunction in *AWS SDK for C++ API Reference*.

`DeleteFunction`

The following code example shows how to use `DeleteFunction`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Lambda::LambdaClient client(clientConfig);

    Aws::Lambda::Model::DeleteFunctionRequest request;
    request.SetFunctionName(LAMBDA_NAME);

    Aws::Lambda::Model::DeleteFunctionOutcome outcome = client.DeleteFunction(
            request);

    if (outcome.IsSuccess()) {
        std::cout << "The lambda function was successfully deleted." << std::endl;
    }
    else {
        std::cerr << "Error with Lambda::DeleteFunction. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
```

- For API details, see DeleteFunction in *AWS SDK for C++ API Reference*.

`GetFunction`

The following code example shows how to use `GetFunction`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";
```

```
   Aws::Lambda::LambdaClient client(clientConfig);

       Aws::Lambda::Model::GetFunctionRequest request;
       request.SetFunctionName(functionName);

       Aws::Lambda::Model::GetFunctionOutcome outcome =
client.GetFunction(request);

       if (outcome.IsSuccess()) {
           std::cout << "Function retrieve.\n" <<

outcome.GetResult().GetConfiguration().Jsonize().View().WriteReadable()
                     << std::endl;
       }
       else {
           std::cerr << "Error with Lambda::GetFunction. "
                     << outcome.GetError().GetMessage()
                     << std::endl;
       }
```

- For API details, see GetFunction in *AWS SDK for C++ API Reference*.

Invoke

The following code example shows how to use `Invoke`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
       Aws::Client::ClientConfiguration clientConfig;
       // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
       // clientConfig.region = "us-east-1";

   Aws::Lambda::LambdaClient client(clientConfig);
```

```
        Aws::Lambda::Model::InvokeRequest request;
        request.SetFunctionName(LAMBDA_NAME);
        request.SetLogType(logType);
        std::shared_ptr<Aws::IOStream> payload = Aws::MakeShared<Aws::StringStream>(
                "FunctionTest");
        *payload << jsonPayload.View().WriteReadable();
        request.SetBody(payload);
        request.SetContentType("application/json");
        Aws::Lambda::Model::InvokeOutcome outcome = client.Invoke(request);

        if (outcome.IsSuccess()) {
            invokeResult = std::move(outcome.GetResult());
            result = true;
            break;
        }

        else {
            std::cerr << "Error with Lambda::InvokeRequest. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            break;
        }
```

- For API details, see Invoke in *AWS SDK for C++ API Reference*.

`ListFunctions`

The following code example shows how to use `ListFunctions`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
```

```
        // clientConfig.region = "us-east-1";

    Aws::Lambda::LambdaClient client(clientConfig);

    std::vector<Aws::String> functions;
    Aws::String marker;

    do {
        Aws::Lambda::Model::ListFunctionsRequest request;
        if (!marker.empty()) {
            request.SetMarker(marker);
        }

        Aws::Lambda::Model::ListFunctionsOutcome outcome = client.ListFunctions(
                request);

        if (outcome.IsSuccess()) {
            const Aws::Lambda::Model::ListFunctionsResult &result =
outcome.GetResult();
            std::cout << result.GetFunctions().size()
                      << " lambda functions were retrieved." << std::endl;

            for (const Aws::Lambda::Model::FunctionConfiguration
&functionConfiguration: result.GetFunctions()) {
                functions.push_back(functionConfiguration.GetFunctionName());
                std::cout << functions.size() << "  "
                          << functionConfiguration.GetDescription() << std::endl;
                std::cout << "   "
                          << Aws::Lambda::Model::RuntimeMapper::GetNameForRuntime(
                                  functionConfiguration.GetRuntime()) << ": "
                          << functionConfiguration.GetHandler()
                          << std::endl;
            }
            marker = result.GetNextMarker();
        }
        else {
            std::cerr << "Error with Lambda::ListFunctions. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
    } while (!marker.empty());
```

- For API details, see ListFunctions in *AWS SDK for C++ API Reference*.

`UpdateFunctionCode`

The following code example shows how to use `UpdateFunctionCode`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
 (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Lambda::LambdaClient client(clientConfig);

        Aws::Lambda::Model::UpdateFunctionCodeRequest request;
        request.SetFunctionName(LAMBDA_NAME);
        std::ifstream ifstream(CALCULATOR_LAMBDA_CODE.c_str(),
                               std::ios_base::in | std::ios_base::binary);
        if (!ifstream.is_open()) {
            std::cerr << "Error opening file " << INCREMENT_LAMBDA_CODE << "." <<
 std::endl;

#if USE_CPP_LAMBDA_FUNCTION
            std::cerr
                    << "The cpp Lambda function must be built following the
 instructions in the cpp_lambda/README.md file. "
                    << std::endl;
#endif
            deleteLambdaFunction(client);
            deleteIamRole(clientConfig);
            return false;
        }

        Aws::StringStream buffer;
        buffer << ifstream.rdbuf();
        request.SetZipFile(
                Aws::Utils::ByteBuffer((unsigned char *) buffer.str().c_str(),
                                       buffer.str().length()));
```

```
        request.SetPublish(true);

        Aws::Lambda::Model::UpdateFunctionCodeOutcome outcome =
client.UpdateFunctionCode(
                request);

        if (outcome.IsSuccess()) {
            std::cout << "The lambda code was successfully updated." << std::endl;
        }
        else {
            std::cerr << "Error with Lambda::UpdateFunctionCode. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
```

- For API details, see [UpdateFunctionCode](#) in *AWS SDK for C++ API Reference*.

`UpdateFunctionConfiguration`

The following code example shows how to use `UpdateFunctionConfiguration`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region in which the bucket was created
(overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::Lambda::LambdaClient client(clientConfig);

        Aws::Lambda::Model::UpdateFunctionConfigurationRequest request;
        request.SetFunctionName(LAMBDA_NAME);
        Aws::Lambda::Model::Environment environment;
        environment.AddVariables("LOG_LEVEL", "DEBUG");
        request.SetEnvironment(environment);
```

```
        Aws::Lambda::Model::UpdateFunctionConfigurationOutcome outcome =
client.UpdateFunctionConfiguration(
                request);

        if (outcome.IsSuccess()) {
            std::cout << "The lambda configuration was successfully updated."
                      << std::endl;
            break;
        }

        else {
            std::cerr << "Error with Lambda::UpdateFunctionConfiguration. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
```

- For API details, see UpdateFunctionConfiguration in *AWS SDK for C++ API Reference*.

Scenarios

Create a serverless application to manage photos

The following code example shows how to create a serverless application that lets users manage photos using labels.

SDK for C++

Shows how to develop a photo asset management application that detects labels in images using Amazon Rekognition and stores them for later retrieval.

For complete source code and instructions on how to set up and run, see the full example on GitHub.

For a deep dive into the origin of this example see the post on AWS Community.

Services used in this example

- API Gateway
- DynamoDB
- Lambda

- Amazon Rekognition
- Amazon S3
- Amazon SNS

MediaConvert examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with MediaConvert.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Actions

Actions

`CreateJob`

The following code example shows how to use `CreateJob`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Create an AWS Elemental MediaConvert job.
/*!
  \param mediaConvertRole: An Amazon Resource Name (ARN) for the AWS Identity and
                           Access Management (IAM) role for the job.
  \param fileInput: A URI to an input file that is stored in Amazon Simple Storage
 Service
                    (Amazon S3) or on an HTTP(S) server.
```

```
  \param fileOutput: A URI for an Amazon S3 output location and the output file name
 base.
  \param jobSettingsFile: An optional JSON settings file.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */

bool AwsDoc::MediaConvert::createJob(const Aws::String &mediaConvertRole,
                                     const Aws::String &fileInput,
                                     const Aws::String &fileOutput,
                                     const Aws::String &jobSettingsFile,
                                     const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::MediaConvert::Model::CreateJobRequest createJobRequest;

    createJobRequest.SetRole(mediaConvertRole);
    Aws::Http::HeaderValueCollection hvc;
    hvc.emplace("Customer", "Amazon");
    createJobRequest.SetUserMetadata(hvc);

    if (!jobSettingsFile.empty()) // Use a JSON file for the job settings.
    {
        std::ifstream jobSettingsStream(jobSettingsFile, std::ios::ate);
        if (!jobSettingsStream) {
            std::cerr << "Unable to open the job template file." << std::endl;
            return false;
        }
        std::vector<char> buffer(jobSettingsStream.tellg());
        jobSettingsStream.seekg(0);
        jobSettingsStream.read(buffer.data(), buffer.size());
        std::string jobSettingsJSON(buffer.data(), buffer.size());
        size_t pos = jobSettingsJSON.find(INPUT_FILE_PLACEHOLDER);
        if (pos != std::string::npos) {
            jobSettingsJSON.replace(pos, strlen(INPUT_FILE_PLACEHOLDER), fileInput);
        }

        pos = jobSettingsJSON.find(OUTPUT_FILE_PLACEHOLDER);
        if (pos != std::string::npos) {
            jobSettingsJSON.replace(pos, strlen(OUTPUT_FILE_PLACEHOLDER),
 fileOutput);
        }
        Aws::Utils::Json::JsonValue jsonValue(jobSettingsJSON);
        Aws::MediaConvert::Model::JobSettings jobSettings(jsonValue);
```

```
        createJobRequest.SetSettings(jobSettings);
    }
    else { // Configure the job settings programmatically.
        Aws::MediaConvert::Model::JobSettings jobSettings;
        jobSettings.SetAdAvailOffset(0);
        Aws::MediaConvert::Model::TimecodeConfig timecodeConfig;

timecodeConfig.SetSource(Aws::MediaConvert::Model::TimecodeSource::EMBEDDED);
        jobSettings.SetTimecodeConfig(timecodeConfig);

        // Configure the output group.
        Aws::MediaConvert::Model::OutputGroup outputGroup;
        outputGroup.SetName("File Group");
        Aws::MediaConvert::Model::OutputGroupSettings outputGroupSettings;
        outputGroupSettings.SetType(
                Aws::MediaConvert::Model::OutputGroupType::FILE_GROUP_SETTINGS);
        Aws::MediaConvert::Model::FileGroupSettings fileGroupSettings;
        fileGroupSettings.SetDestination(fileOutput);
        outputGroupSettings.SetFileGroupSettings(fileGroupSettings);
        outputGroup.SetOutputGroupSettings(outputGroupSettings);

        Aws::MediaConvert::Model::Output output;
        output.SetNameModifier("_1");

        Aws::MediaConvert::Model::VideoDescription videoDescription;
        videoDescription.SetScalingBehavior(
                Aws::MediaConvert::Model::ScalingBehavior::DEFAULT);
        videoDescription.SetTimecodeInsertion(
                Aws::MediaConvert::Model::VideoTimecodeInsertion::DISABLED);
        videoDescription.SetAntiAlias(Aws::MediaConvert::Model::AntiAlias::ENABLED);
        videoDescription.SetSharpness(50);

videoDescription.SetAfdSignaling(Aws::MediaConvert::Model::AfdSignaling::NONE);
        videoDescription.SetDropFrameTimecode(
                Aws::MediaConvert::Model::DropFrameTimecode::ENABLED);

videoDescription.SetRespondToAfd(Aws::MediaConvert::Model::RespondToAfd::NONE);
        videoDescription.SetColorMetadata(
                Aws::MediaConvert::Model::ColorMetadata::INSERT);

        Aws::MediaConvert::Model::VideoCodecSettings videoCodecSettings;
        videoCodecSettings.SetCodec(Aws::MediaConvert::Model::VideoCodec::H_264);
        Aws::MediaConvert::Model::H264Settings h264Settings;
        h264Settings.SetNumberReferenceFrames(3);
```

```
        h264Settings.SetSyntax(Aws::MediaConvert::Model::H264Syntax::DEFAULT);
        h264Settings.SetSoftness(0);
        h264Settings.SetGopClosedCadence(1);
        h264Settings.SetGopSize(90);
        h264Settings.SetSlices(1);
        h264Settings.SetGopBReference(
                Aws::MediaConvert::Model::H264GopBReference::DISABLED);
        h264Settings.SetSlowPal(Aws::MediaConvert::Model::H264SlowPal::DISABLED);
        h264Settings.SetSpatialAdaptiveQuantization(
                Aws::MediaConvert::Model::H264SpatialAdaptiveQuantization::ENABLED);
        h264Settings.SetTemporalAdaptiveQuantization(

Aws::MediaConvert::Model::H264TemporalAdaptiveQuantization::ENABLED);
        h264Settings.SetFlickerAdaptiveQuantization(

Aws::MediaConvert::Model::H264FlickerAdaptiveQuantization::DISABLED);
        h264Settings.SetEntropyEncoding(
                Aws::MediaConvert::Model::H264EntropyEncoding::CABAC);
        h264Settings.SetBitrate(5000000);
        h264Settings.SetFramerateControl(
                Aws::MediaConvert::Model::H264FramerateControl::SPECIFIED);
        h264Settings.SetRateControlMode(
                Aws::MediaConvert::Model::H264RateControlMode::CBR);

h264Settings.SetCodecProfile(Aws::MediaConvert::Model::H264CodecProfile::MAIN);
        h264Settings.SetTelecine(Aws::MediaConvert::Model::H264Telecine::NONE);
        h264Settings.SetMinIInterval(0);
        h264Settings.SetAdaptiveQuantization(
                Aws::MediaConvert::Model::H264AdaptiveQuantization::HIGH);
        h264Settings.SetCodecLevel(Aws::MediaConvert::Model::H264CodecLevel::AUTO);
        h264Settings.SetFieldEncoding(
                Aws::MediaConvert::Model::H264FieldEncoding::PAFF);
        h264Settings.SetSceneChangeDetect(
                Aws::MediaConvert::Model::H264SceneChangeDetect::ENABLED);
        h264Settings.SetQualityTuningLevel(
                Aws::MediaConvert::Model::H264QualityTuningLevel::SINGLE_PASS);
        h264Settings.SetFramerateConversionAlgorithm(

Aws::MediaConvert::Model::H264FramerateConversionAlgorithm::DUPLICATE_DROP);
        h264Settings.SetUnregisteredSeiTimecode(
                Aws::MediaConvert::Model::H264UnregisteredSeiTimecode::DISABLED);
        h264Settings.SetGopSizeUnits(
                Aws::MediaConvert::Model::H264GopSizeUnits::FRAMES);
```

```
h264Settings.SetParControl(Aws::MediaConvert::Model::H264ParControl::SPECIFIED);
        h264Settings.SetNumberBFramesBetweenReferenceFrames(2);

h264Settings.SetRepeatPps(Aws::MediaConvert::Model::H264RepeatPps::DISABLED);
        h264Settings.SetFramerateNumerator(30);
        h264Settings.SetFramerateDenominator(1);
        h264Settings.SetParNumerator(1);
        h264Settings.SetParDenominator(1);
        videoCodecSettings.SetH264Settings(h264Settings);
        videoDescription.SetCodecSettings(videoCodecSettings);
        output.SetVideoDescription(videoDescription);

        Aws::MediaConvert::Model::AudioDescription audioDescription;
        audioDescription.SetLanguageCodeControl(
                Aws::MediaConvert::Model::AudioLanguageCodeControl::FOLLOW_INPUT);
        audioDescription.SetAudioSourceName(AUDIO_SOURCE_NAME);
        Aws::MediaConvert::Model::AudioCodecSettings audioCodecSettings;
        audioCodecSettings.SetCodec(Aws::MediaConvert::Model::AudioCodec::AAC);
        Aws::MediaConvert::Model::AacSettings aacSettings;
        aacSettings.SetAudioDescriptionBroadcasterMix(

Aws::MediaConvert::Model::AacAudioDescriptionBroadcasterMix::NORMAL);
        aacSettings.SetRateControlMode(
                Aws::MediaConvert::Model::AacRateControlMode::CBR);
        aacSettings.SetCodecProfile(Aws::MediaConvert::Model::AacCodecProfile::LC);
        aacSettings.SetCodingMode(
                Aws::MediaConvert::Model::AacCodingMode::CODING_MODE_2_0);
        aacSettings.SetRawFormat(Aws::MediaConvert::Model::AacRawFormat::NONE);
        aacSettings.SetSampleRate(48000);

aacSettings.SetSpecification(Aws::MediaConvert::Model::AacSpecification::MPEG4);
        aacSettings.SetBitrate(64000);
        audioCodecSettings.SetAacSettings(aacSettings);
        audioDescription.SetCodecSettings(audioCodecSettings);
        Aws::Vector<Aws::MediaConvert::Model::AudioDescription> audioDescriptions;
        audioDescriptions.emplace_back(audioDescription);
        output.SetAudioDescriptions(audioDescriptions);

        Aws::MediaConvert::Model::ContainerSettings mp4container;
        mp4container.SetContainer(Aws::MediaConvert::Model::ContainerType::MP4);
        Aws::MediaConvert::Model::Mp4Settings mp4Settings;
        mp4Settings.SetCslgAtom(Aws::MediaConvert::Model::Mp4CslgAtom::INCLUDE);
```

```
mp4Settings.SetFreeSpaceBox(Aws::MediaConvert::Model::Mp4FreeSpaceBox::EXCLUDE);
        mp4Settings.SetMoovPlacement(
                Aws::MediaConvert::Model::Mp4MoovPlacement::PROGRESSIVE_DOWNLOAD);
        mp4container.SetMp4Settings(mp4Settings);
        output.SetContainerSettings(mp4container);

        outputGroup.AddOutputs(output);
        jobSettings.AddOutputGroups(outputGroup);

        // Configure inputs.
        Aws::MediaConvert::Model::Input input;
        input.SetFilterEnable(Aws::MediaConvert::Model::InputFilterEnable::AUTO);
        input.SetPsiControl(Aws::MediaConvert::Model::InputPsiControl::USE_PSI);
        input.SetFilterStrength(0);

input.SetDeblockFilter(Aws::MediaConvert::Model::InputDeblockFilter::DISABLED);

input.SetDenoiseFilter(Aws::MediaConvert::Model::InputDenoiseFilter::DISABLED);
        input.SetTimecodeSource(
                Aws::MediaConvert::Model::InputTimecodeSource::EMBEDDED);
        input.SetFileInput(fileInput);

        Aws::MediaConvert::Model::AudioSelector audioSelector;
        audioSelector.SetOffset(0);
        audioSelector.SetDefaultSelection(
                Aws::MediaConvert::Model::AudioDefaultSelection::NOT_DEFAULT);
        audioSelector.SetProgramSelection(1);
        audioSelector.SetSelectorType(
                Aws::MediaConvert::Model::AudioSelectorType::TRACK);
        audioSelector.AddTracks(1);
        input.AddAudioSelectors(AUDIO_SOURCE_NAME, audioSelector);

        Aws::MediaConvert::Model::VideoSelector videoSelector;
        videoSelector.SetColorSpace(Aws::MediaConvert::Model::ColorSpace::FOLLOW);
        input.SetVideoSelector(videoSelector);

        jobSettings.AddInputs(input);

        createJobRequest.SetSettings(jobSettings);
    }

    Aws::MediaConvert::MediaConvertClient client(clientConfiguration);
    Aws::MediaConvert::Model::CreateJobOutcome outcome = client.CreateJob(
```

```
            createJobRequest);
    if (outcome.IsSuccess()) {
        std::cout << "Job successfully created with ID - "
                  << outcome.GetResult().GetJob().GetId() << std::endl;
    }
    else {
        std::cerr << "Error CreateJob - " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see CreateJob in *AWS SDK for C++ API Reference*.

`GetJob`

The following code example shows how to use `GetJob`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Retrieve the information for a specific completed transcoding job.
/*!
  \param jobID: A job ID.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::MediaConvert::getJob(const Aws::String &jobID,
                                  const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::MediaConvert::MediaConvertClient client(clientConfiguration);

    Aws::MediaConvert::Model::GetJobRequest request;
    request.SetId(jobID);
```

```
    const Aws::MediaConvert::Model::GetJobOutcome outcome = client.GetJob(
            request);
    if (outcome.IsSuccess()) {
        std::cout << outcome.GetResult().GetJob().Jsonize().View().WriteReadable()
                  << std::endl;
    }
    else {
        std::cerr << "DescribeEndpoints error - " << outcome.GetError().GetMessage()
                  << std::endl;
    }


    return outcome.IsSuccess();
}
```

- For API details, see GetJob in *AWS SDK for C++ API Reference*.

`ListJobs`

The following code example shows how to use `ListJobs`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Retrieve a list of created jobs.
/*!
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::MediaConvert::listJobs(
        const Aws::Client::ClientConfiguration &clientConfiguration) {

    Aws::MediaConvert::MediaConvertClient client(clientConfiguration);

    bool result = true;
```

```
    Aws::String nextToken; // Used to handle paginated results.
    do {
        Aws::MediaConvert::Model::ListJobsRequest request;
        if (!nextToken.empty()) {
            request.SetNextToken(nextToken);
        }
        const Aws::MediaConvert::Model::ListJobsOutcome outcome = client.ListJobs(
                request);
        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::MediaConvert::Model::Job> &jobs =
                    outcome.GetResult().GetJobs();
            std::cout << jobs.size() << " jobs retrieved." << std::endl;
            for (const Aws::MediaConvert::Model::Job &job: jobs) {
                std::cout << "  " << job.Jsonize().View().WriteReadable() <<
 std::endl;
            }

            nextToken = outcome.GetResult().GetNextToken();
        }
        else {
            std::cerr << "DescribeEndpoints error - " <<
 outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
            break;

        }
    } while (!nextToken.empty());


    return result;
}
```

- For API details, see ListJobs in *AWS SDK for C++ API Reference*.

Amazon RDS examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with Amazon RDS.

Basics are code examples that show you how to perform the essential operations within a service.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Scenarios are code examples that show you how to accomplish specific tasks by calling multiple functions within a service or combined with other AWS services.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Get started
- Basics
- Actions
- Scenarios

Get started

Hello Amazon RDS

The following code example shows how to get started using Amazon RDS.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Code for the CMakeLists.txt CMake file.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS rds)

# Set this project's name.
project("hello_rds")
```

```
# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD AND AWSSDK_INSTALL_AS_SHARED_LIBS)
     # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

     # set(BIN_SUB_DIR "/Debug") # If you are building from the command line, you
 may need to uncomment this
                                     # and set the proper subdirectory to the
 executables' location.

     AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_rds.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Code for the hello_rds.cpp source file.

```
#include <aws/core/Aws.h>
#include <aws/rds/RDSClient.h>
#include <aws/rds/model/DescribeDBInstancesRequest.h>
```

```
#include <iostream>

/*
 *  A "Hello Rds" starter application which initializes an Amazon Relational
 Database Service (Amazon RDS) client and
 *  describes the Amazon RDS instances.
 *
 *  main function
 *
 *  Usage: 'hello_rds'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::RDS::RDSClient rdsClient(clientConfig);
        Aws::String marker;
        std::vector<Aws::String> instanceDBIDs;

        do {
            Aws::RDS::Model::DescribeDBInstancesRequest request;

            if (!marker.empty()) {
                request.SetMarker(marker);
            }

            Aws::RDS::Model::DescribeDBInstancesOutcome outcome =
                    rdsClient.DescribeDBInstances(request);

            if (outcome.IsSuccess()) {
                for (auto &instance: outcome.GetResult().GetDBInstances()) {
                    instanceDBIDs.push_back(instance.GetDBInstanceIdentifier());
                }
                marker = outcome.GetResult().GetMarker();
            } else {
```

```
                result = 1;
                std::cerr << "Error with RDS::DescribeDBInstances. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                break;
            }
        } while (!marker.empty());

        std::cout << instanceDBIDs.size() << " RDS instances found." << std::endl;
        for (auto &instanceDBID: instanceDBIDs) {
            std::cout << "   Instance: " << instanceDBID << std::endl;
        }
    }

    Aws::ShutdownAPI(options); // Should only be called once.
    return result;
}
```

- For API details, see DescribeDBInstances in *AWS SDK for C++ API Reference*.

Basics

Learn the basics

The following code example shows how to:

- Create a custom DB parameter group and set parameter values.
- Create a DB instance that's configured to use the parameter group. The DB instance also contains a database.
- Take a snapshot of the instance.
- Delete the instance and parameter group.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Routine which creates an Amazon RDS instance and demonstrates several operations
//! on that instance.
/*!
 \sa gettingStartedWithDBInstances()
 \param clientConfiguration: AWS client configuration.
 \return bool: Successful completion.
 */
bool AwsDoc::RDS::gettingStartedWithDBInstances(
        const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::RDS::RDSClient client(clientConfig);

    printAsterisksLine();
    std::cout << "Welcome to the Amazon Relational Database Service (Amazon RDS)"
              << std::endl;
    std::cout << "get started with DB instances demo." << std::endl;
    printAsterisksLine();

    std::cout << "Checking for an existing DB parameter group named '" <<
              PARAMETER_GROUP_NAME << "'." << std::endl;
    Aws::String dbParameterGroupFamily("Undefined");
    bool parameterGroupFound = true;
    {
        // 1. Check if the DB parameter group already exists.
        Aws::RDS::Model::DescribeDBParameterGroupsRequest request;
        request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);

        Aws::RDS::Model::DescribeDBParameterGroupsOutcome outcome =
                client.DescribeDBParameterGroups(request);

        if (outcome.IsSuccess()) {
            std::cout << "DB parameter group named '" <<
                      PARAMETER_GROUP_NAME << "' already exists." << std::endl;
            dbParameterGroupFamily = outcome.GetResult().GetDBParameterGroups()
[0].GetDBParameterGroupFamily();
        }
        else if (outcome.GetError().GetErrorType() ==
                 Aws::RDS::RDSErrors::D_B_PARAMETER_GROUP_NOT_FOUND_FAULT) {
            std::cout << "DB parameter group named '" <<
                      PARAMETER_GROUP_NAME << "' does not exist." << std::endl;
```

```
            parameterGroupFound = false;
        }
        else {
            std::cerr << "Error with RDS::DescribeDBParameterGroups. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }

    if (!parameterGroupFound) {
        Aws::Vector<Aws::RDS::Model::DBEngineVersion> engineVersions;

        // 2. Get available engine versions for the specified engine.
        if (!getDBEngineVersions(DB_ENGINE, NO_PARAMETER_GROUP_FAMILY,
                                 engineVersions, client)) {
            return false;
        }

        std::cout << "Getting available database engine versions for " << DB_ENGINE
                  << "."
                  << std::endl;
        std::vector<Aws::String> families;
        for (const Aws::RDS::Model::DBEngineVersion &version: engineVersions) {
            Aws::String family = version.GetDBParameterGroupFamily();
            if (std::find(families.begin(), families.end(), family) ==
                families.end()) {
                families.push_back(family);
                std::cout << "  " << families.size() << ": " << family << std::endl;
            }
        }

        int choice = askQuestionForIntRange("Which family do you want to use? ", 1,
                                            static_cast<int>(families.size()));
        dbParameterGroupFamily = families[choice - 1];
    }
    if (!parameterGroupFound) {
        // 3.  Create a DB parameter group.
        Aws::RDS::Model::CreateDBParameterGroupRequest request;
        request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);
        request.SetDBParameterGroupFamily(dbParameterGroupFamily);
        request.SetDescription("Example parameter group.");

        Aws::RDS::Model::CreateDBParameterGroupOutcome outcome =
```

```
                client.CreateDBParameterGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB parameter group was successfully created."
                      << std::endl;
        }
        else {
            std::cerr << "Error with RDS::CreateDBParameterGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    }

    printAsterisksLine();
    std::cout << "Let's set some parameter values in your parameter group."
              << std::endl;

    Aws::String marker;
    Aws::Vector<Aws::RDS::Model::Parameter> autoIncrementParameters;
    // 4.  Get the parameters in the DB parameter group.
    if (!getDBParameters(PARAMETER_GROUP_NAME, AUTO_INCREMENT_PREFIX, NO_SOURCE,
                         autoIncrementParameters,
                         client)) {
        cleanUpResources(PARAMETER_GROUP_NAME, "", client);
        return false;
    }

    Aws::Vector<Aws::RDS::Model::Parameter> updateParameters;

    for (Aws::RDS::Model::Parameter &autoIncParameter: autoIncrementParameters) {
        if (autoIncParameter.GetIsModifiable() &&
            (autoIncParameter.GetDataType() == "integer")) {
            std::cout << "The " << autoIncParameter.GetParameterName()
                      << " is described as: " <<
                      autoIncParameter.GetDescription() << "." << std::endl;
            if (autoIncParameter.ParameterValueHasBeenSet()) {
                std::cout << "The current value is "
                          << autoIncParameter.GetParameterValue()
                          << "." << std::endl;
            }
            std::vector<int> splitValues = splitToInts(
                    autoIncParameter.GetAllowedValues(), '-');
            if (splitValues.size() == 2) {
```

```
                int newValue = askQuestionForIntRange(
                        Aws::String("Enter a new value in the range ") +
                        autoIncParameter.GetAllowedValues() + ": ",
                        splitValues[0], splitValues[1]);
                autoIncParameter.SetParameterValue(std::to_string(newValue));
                updateParameters.push_back(autoIncParameter);

            }
            else {
                std::cerr << "Error parsing " << autoIncParameter.GetAllowedValues()
                          << std::endl;
            }
        }
    }

    {
        // 5.  Modify the auto increment parameters in the group.
        Aws::RDS::Model::ModifyDBParameterGroupRequest request;
        request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);
        request.SetParameters(updateParameters);

        Aws::RDS::Model::ModifyDBParameterGroupOutcome outcome =
                client.ModifyDBParameterGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB parameter group was successfully modified."
                      << std::endl;
        }
        else {
            std::cerr << "Error with RDS::ModifyDBParameterGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
        }
    }

    std::cout
            << "You can get a list of parameters you've set by specifying a source
of 'user'."
            << std::endl;

    Aws::Vector<Aws::RDS::Model::Parameter> userParameters;
    // 6.  Display the modified parameters in the group.
    if (!getDBParameters(PARAMETER_GROUP_NAME, NO_NAME_PREFIX, "user",
userParameters,
```

```
                        client)) {
        cleanUpResources(PARAMETER_GROUP_NAME, "", client);
        return false;
    }

    for (const auto &userParameter: userParameters) {
        std::cout << "  " << userParameter.GetParameterName() << ", " <<
                  userParameter.GetDescription() << ", parameter value - "
                  << userParameter.GetParameterValue() << std::endl;
    }

    printAsterisksLine();
    std::cout << "Checking for an existing DB instance." << std::endl;

    Aws::RDS::Model::DBInstance dbInstance;
    // 7.  Check if the DB instance already exists.
    if (!describeDBInstance(DB_INSTANCE_IDENTIFIER, dbInstance, client)) {
        cleanUpResources(PARAMETER_GROUP_NAME, "", client);
        return false;
    }

    if (dbInstance.DbInstancePortHasBeenSet()) {
        std::cout << "The DB instance already exists." << std::endl;
    }
    else {
        std::cout << "Let's create a DB instance." << std::endl;
        const Aws::String administratorName = askQuestion(
                "Enter an administrator username for the database: ");
        const Aws::String administratorPassword = askQuestion(
                "Enter a password for the administrator (at least 8 characters): ");
        Aws::Vector<Aws::RDS::Model::DBEngineVersion> engineVersions;

        // 8.  Get a list of available engine versions.
        if (!getDBEngineVersions(DB_ENGINE, dbParameterGroupFamily, engineVersions,
                                 client)) {
            cleanUpResources(PARAMETER_GROUP_NAME, "", client);
            return false;
        }

        std::cout << "The available engines for your parameter group are:" <<
std::endl;

        int index = 1;
```

```
        for (const Aws::RDS::Model::DBEngineVersion &engineVersion: engineVersions)
{
            std::cout << "  " << index << ": " << engineVersion.GetEngineVersion()
                      << std::endl;
            ++index;
        }
        int choice = askQuestionForIntRange("Which engine do you want to use? ", 1,

static_cast<int>(engineVersions.size()));
        const Aws::RDS::Model::DBEngineVersion engineVersion = engineVersions[choice
-
                                                                               1];

        Aws::String dbInstanceClass;
        // 9.  Get a list of micro instance classes.
        if (!chooseMicroDBInstanceClass(engineVersion.GetEngine(),
                                        engineVersion.GetEngineVersion(),
                                        dbInstanceClass,
                                        client)) {
            cleanUpResources(PARAMETER_GROUP_NAME, "", client);
            return false;
        }

        std::cout << "Creating a DB instance named '" << DB_INSTANCE_IDENTIFIER
                  << "' and database '" << DB_NAME << "'.\n"
                  << "The DB instance is configured to use your custom parameter
group '"
                  << PARAMETER_GROUP_NAME << "',\n"
                  << "selected engine version " << engineVersion.GetEngineVersion()
                  << ",\n"
                  << "selected DB instance class '" << dbInstanceClass << "',"
                  << " and " << DB_ALLOCATED_STORAGE << " GiB of " <<
DB_STORAGE_TYPE
                  << " storage.\nThis typically takes several minutes." <<
std::endl;

        Aws::RDS::Model::CreateDBInstanceRequest request;
        request.SetDBName(DB_NAME);
        request.SetDBInstanceIdentifier(DB_INSTANCE_IDENTIFIER);
        request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);
        request.SetEngine(engineVersion.GetEngine());
        request.SetEngineVersion(engineVersion.GetEngineVersion());
        request.SetDBInstanceClass(dbInstanceClass);
        request.SetStorageType(DB_STORAGE_TYPE);
```

```
        request.SetAllocatedStorage(DB_ALLOCATED_STORAGE);
        request.SetMasterUsername(administratorName);
        request.SetMasterUserPassword(administratorPassword);

        Aws::RDS::Model::CreateDBInstanceOutcome outcome =
                client.CreateDBInstance(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB instance creation has started."
                      << std::endl;
        }
        else {
            std::cerr << "Error with RDS::CreateDBInstance. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            cleanUpResources(PARAMETER_GROUP_NAME, "", client);
            return false;
        }
    }

    std::cout << "Waiting for the DB instance to become available." << std::endl;

    int counter = 0;
    // 11. Wait for the DB instance to become available.
    do {
        std::this_thread::sleep_for(std::chrono::seconds(1));
        ++counter;
        if (counter > 900) {
            std::cerr << "Wait for instance to become available timed out ofter "
                      << counter
                      << " seconds." << std::endl;
            cleanUpResources(PARAMETER_GROUP_NAME, DB_INSTANCE_IDENTIFIER, client);
            return false;
        }

        dbInstance = Aws::RDS::Model::DBInstance();
        if (!describeDBInstance(DB_INSTANCE_IDENTIFIER, dbInstance, client)) {
            cleanUpResources(PARAMETER_GROUP_NAME, DB_INSTANCE_IDENTIFIER, client);
            return false;
        }

        if ((counter % 20) == 0) {
            std::cout << "Current DB instance status is '"
                      << dbInstance.GetDBInstanceStatus()
```

```
                    << "' after " << counter << " seconds." << std::endl;
        }
    } while (dbInstance.GetDBInstanceStatus() != "available");

    if (dbInstance.GetDBInstanceStatus() == "available") {
        std::cout << "The DB instance has been created." << std::endl;
    }

    printAsterisksLine();

    // 12. Display the connection string that can be used to connect a 'mysql' shell
to the database.
    displayConnection(dbInstance);

    printAsterisksLine();

    if (askYesNoQuestion(
            "Do you want to create a snapshot of your DB instance (y/n)? ")) {
        Aws::String snapshotID(DB_INSTANCE_IDENTIFIER + "-" +
                               Aws::String(Aws::Utils::UUID::RandomUUID()));
        {
            std::cout << "Creating a snapshot named " << snapshotID << "." <<
std::endl;
            std::cout << "This typically takes a few minutes." << std::endl;

            // 13. Create a snapshot of the DB instance.
            Aws::RDS::Model::CreateDBSnapshotRequest request;
            request.SetDBInstanceIdentifier(DB_INSTANCE_IDENTIFIER);
            request.SetDBSnapshotIdentifier(snapshotID);

            Aws::RDS::Model::CreateDBSnapshotOutcome outcome =
                    client.CreateDBSnapshot(request);

            if (outcome.IsSuccess()) {
                std::cout << "Snapshot creation has started."
                          << std::endl;
            }
            else {
                std::cerr << "Error with RDS::CreateDBSnapshot. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUpResources(PARAMETER_GROUP_NAME, DB_INSTANCE_IDENTIFIER,
client);
                return false;
```

```
            }
        }

        std::cout << "Waiting for snapshot to become available." << std::endl;

        Aws::RDS::Model::DBSnapshot snapshot;
        counter = 0;
        do {
            std::this_thread::sleep_for(std::chrono::seconds(1));
            ++counter;
            if (counter > 600) {
                std::cerr << "Wait for snapshot to be available timed out ofter "
                          << counter
                          << " seconds." << std::endl;
                cleanUpResources(PARAMETER_GROUP_NAME, DB_INSTANCE_IDENTIFIER,
client);
                return false;
            }

            // 14. Wait for the snapshot to become available.
            Aws::RDS::Model::DescribeDBSnapshotsRequest request;
            request.SetDBSnapshotIdentifier(snapshotID);

            Aws::RDS::Model::DescribeDBSnapshotsOutcome outcome =
                    client.DescribeDBSnapshots(request);

            if (outcome.IsSuccess()) {
                snapshot = outcome.GetResult().GetDBSnapshots()[0];
            }
            else {
                std::cerr << "Error with RDS::DescribeDBSnapshots. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUpResources(PARAMETER_GROUP_NAME, DB_INSTANCE_IDENTIFIER,
client);
                return false;
            }

            if ((counter % 20) == 0) {
                std::cout << "Current snapshot status is '"
                          << snapshot.GetStatus()
                          << "' after " << counter << " seconds." << std::endl;
            }
        } while (snapshot.GetStatus() != "available");
```

```
        if (snapshot.GetStatus() != "available") {
            std::cout << "A snapshot has been created." << std::endl;
        }
    }

    printAsterisksLine();

    bool result = true;
    if (askYesNoQuestion(
            "Do you want to delete the DB instance and parameter group (y/n)? ")) {
        result = cleanUpResources(PARAMETER_GROUP_NAME, DB_INSTANCE_IDENTIFIER,
 client);
    }

    return result;
}


//! Routine which gets DB parameters using the 'DescribeDBParameters' api.
/*!
 \sa getDBParameters()
 \param parameterGroupName: The name of the parameter group.
 \param namePrefix: Prefix string to filter results by parameter name.
 \param source: A source such as 'user', ignored if empty.
 \param parametersResult: Vector of 'Parameter' objects returned by the routine.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::RDS::getDBParameters(const Aws::String &parameterGroupName,
                                  const Aws::String &namePrefix,
                                  const Aws::String &source,
                                  Aws::Vector<Aws::RDS::Model::Parameter>
 &parametersResult,
                                  const Aws::RDS::RDSClient &client) {
    Aws::String marker;
    do {
        Aws::RDS::Model::DescribeDBParametersRequest request;
        request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);
        if (!marker.empty()) {
            request.SetMarker(marker);
        }
        if (!source.empty()) {
            request.SetSource(source);
```

```
        }

        Aws::RDS::Model::DescribeDBParametersOutcome outcome =
                client.DescribeDBParameters(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::RDS::Model::Parameter> &parameters =
                    outcome.GetResult().GetParameters();
            for (const Aws::RDS::Model::Parameter &parameter: parameters) {
                if (!namePrefix.empty()) {
                    if (parameter.GetParameterName().find(namePrefix) == 0) {
                        parametersResult.push_back(parameter);
                    }
                }
                else {
                    parametersResult.push_back(parameter);
                }
            }

            marker = outcome.GetResult().GetMarker();
        }
        else {
            std::cerr << "Error with RDS::DescribeDBParameters. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (!marker.empty());

    return true;
}


//! Routine which gets available DB engine versions for an engine name and
//! an optional parameter group family.
/*!
 \sa getDBEngineVersions()
 \param engineName: A DB engine name.
 \param parameterGroupFamily: A parameter group family name, ignored if empty.
 \param engineVersionsResult: Vector of 'DBEngineVersion' objects returned by the
 routine.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
```

```
bool AwsDoc::RDS::getDBEngineVersions(const Aws::String &engineName,
                                      const Aws::String &parameterGroupFamily,
                                      Aws::Vector<Aws::RDS::Model::DBEngineVersion>
 &engineVersionsResult,
                                      const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBEngineVersionsRequest request;
    request.SetEngine(engineName);
    if (!parameterGroupFamily.empty()) {
        request.SetDBParameterGroupFamily(parameterGroupFamily);
    }

    engineVersionsResult.clear();
    Aws::String marker; // Used for pagination.

    do {
        if (!marker.empty()) {
            request.SetMarker(marker);
        }


        Aws::RDS::Model::DescribeDBEngineVersionsOutcome outcome =
                client.DescribeDBEngineVersions(request);

        if (outcome.IsSuccess()) {
            auto &engineVersions = outcome.GetResult().GetDBEngineVersions();
            engineVersionsResult.insert(engineVersionsResult.end(),
 engineVersions.begin(),
                                        engineVersions.end());
            marker = outcome.GetResult().GetMarker();
        }
        else {
            std::cerr << "Error with RDS::DescribeDBEngineVersionsRequest. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }

    } while (!marker.empty());


    return true;
}
```

```
//! Routine which gets a DB instance description.
/*!
 \sa describeDBInstance()
 \param dbInstanceIdentifier: A DB instance identifier.
 \param instanceResult: The 'DBInstance' object containing the description.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::RDS::describeDBInstance(const Aws::String &dbInstanceIdentifier,
                                     Aws::RDS::Model::DBInstance &instanceResult,
                                     const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBInstancesRequest request;
    request.SetDBInstanceIdentifier(dbInstanceIdentifier);

    Aws::RDS::Model::DescribeDBInstancesOutcome outcome =
            client.DescribeDBInstances(request);

    bool result = true;
    if (outcome.IsSuccess()) {
        instanceResult = outcome.GetResult().GetDBInstances()[0];
    }
    else if (outcome.GetError().GetErrorType() !=
             Aws::RDS::RDSErrors::D_B_INSTANCE_NOT_FOUND_FAULT) {
        result = false;
        std::cerr << "Error with RDS::DescribeDBInstances. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
        // This example does not log an error if the DB instance does not exist.
        // Instead, instanceResult is set to empty.
    else {
        instanceResult = Aws::RDS::Model::DBInstance();
    }

    return result;
}


//! Routine which gets available 'micro' DB instance classes, displays the list
//! to the user, and returns the user selection.
/*!
 \sa chooseMicroDBInstanceClass()
 \param engineName: The DB engine name.
 \param engineVersion: The DB engine version.
```

```
 \param dbInstanceClass: String for DB instance class chosen by the user.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::RDS::chooseMicroDBInstanceClass(const Aws::String &engine,
                                             const Aws::String &engineVersion,
                                             Aws::String &dbInstanceClass,
                                             const Aws::RDS::RDSClient &client) {
    std::vector<Aws::String> instanceClasses;
    Aws::String marker;
    do {
        Aws::RDS::Model::DescribeOrderableDBInstanceOptionsRequest request;
        request.SetEngine(engine);
        request.SetEngineVersion(engineVersion);
        if (!marker.empty()) {
            request.SetMarker(marker);
        }

        Aws::RDS::Model::DescribeOrderableDBInstanceOptionsOutcome outcome =
                client.DescribeOrderableDBInstanceOptions(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::RDS::Model::OrderableDBInstanceOption> &options =
                    outcome.GetResult().GetOrderableDBInstanceOptions();
            for (const Aws::RDS::Model::OrderableDBInstanceOption &option: options)
 {
                const Aws::String &instanceClass = option.GetDBInstanceClass();
                if (instanceClass.find("micro") != std::string::npos) {
                    if (std::find(instanceClasses.begin(), instanceClasses.end(),
                                  instanceClass) ==
                        instanceClasses.end()) {
                        instanceClasses.push_back(instanceClass);
                    }
                }
            }
            marker = outcome.GetResult().GetMarker();
        }
        else {
            std::cerr << "Error with RDS::DescribeOrderableDBInstanceOptions. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (!marker.empty());
```

```
    std::cout << "The available micro DB instance classes for your database engine
 are:"
              << std::endl;
    for (int i = 0; i < instanceClasses.size(); ++i) {
        std::cout << "   " << i + 1 << ": " << instanceClasses[i] << std::endl;
    }

    int choice = askQuestionForIntRange(
            "Which micro DB instance class do you want to use? ",
            1, static_cast<int>(instanceClasses.size()));
    dbInstanceClass = instanceClasses[choice - 1];
    return true;
}

//! Routine which deletes resources created by the scenario.
/*!
\sa cleanUpResources()
\param parameterGroupName: A parameter group name, this may be empty.
\param dbInstanceIdentifier: A DB instance identifier, this may be empty.
\param client: 'RDSClient' instance.
\return bool: Successful completion.
*/
bool AwsDoc::RDS::cleanUpResources(const Aws::String &parameterGroupName,
                                   const Aws::String &dbInstanceIdentifier,
                                   const Aws::RDS::RDSClient &client) {
    bool result = true;
    if (!dbInstanceIdentifier.empty()) {
        {
            // 15. Delete the DB instance.
            Aws::RDS::Model::DeleteDBInstanceRequest request;
            request.SetDBInstanceIdentifier(dbInstanceIdentifier);
            request.SetSkipFinalSnapshot(true);
            request.SetDeleteAutomatedBackups(true);

            Aws::RDS::Model::DeleteDBInstanceOutcome outcome =
                    client.DeleteDBInstance(request);

            if (outcome.IsSuccess()) {
                std::cout << "DB instance deletion has started."
                          << std::endl;
            }
            else {
                std::cerr << "Error with RDS::DeleteDBInstance. "
```

```
                        << outcome.GetError().GetMessage()
                        << std::endl;
                result = false;
            }
        }

        std::cout
                << "Waiting for DB instance to delete before deleting the parameter
group."
                << std::endl;
        std::cout << "This may take a while." << std::endl;

        int counter = 0;
        Aws::RDS::Model::DBInstance dbInstance;
        do {
            std::this_thread::sleep_for(std::chrono::seconds(1));
            ++counter;
            if (counter > 800) {
                std::cerr << "Wait for instance to delete timed out ofter " <<
counter
                        << " seconds." << std::endl;
                return false;
            }

            dbInstance = Aws::RDS::Model::DBInstance();
            // 16. Wait for the DB instance to be deleted.
            if (!describeDBInstance(dbInstanceIdentifier, dbInstance, client)) {
                return false;
            }

            if (dbInstance.DBInstanceIdentifierHasBeenSet() && (counter % 20) == 0)
{
                std::cout << "Current DB instance status is '"
                        << dbInstance.GetDBInstanceStatus()
                        << "' after " << counter << " seconds." << std::endl;
            }
        } while (dbInstance.DBInstanceIdentifierHasBeenSet());
    }

    if (!parameterGroupName.empty()) {
        // 17. Delete the parameter group.
        Aws::RDS::Model::DeleteDBParameterGroupRequest request;
        request.SetDBParameterGroupName(parameterGroupName);
```

```
        Aws::RDS::Model::DeleteDBParameterGroupOutcome outcome =
                client.DeleteDBParameterGroup(request);

        if (outcome.IsSuccess()) {
            std::cout << "The DB parameter group was successfully deleted."
                      << std::endl;
        }
        else {
            std::cerr << "Error with RDS::DeleteDBParameterGroup. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
        }
    }

    return result;
}
```

- For API details, see the following topics in *AWS SDK for C++ API Reference*.
  - CreateDBInstance
  - CreateDBParameterGroup
  - CreateDBSnapshot
  - DeleteDBInstance
  - DeleteDBParameterGroup
  - DescribeDBEngineVersions
  - DescribeDBInstances
  - DescribeDBParameterGroups
  - DescribeDBParameters
  - DescribeDBSnapshots
  - DescribeOrderableDBInstanceOptions
  - ModifyDBParameterGroup

Actions

`CreateDBInstance`

The following code example shows how to use `CreateDBInstance`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
    Aws::Client::ClientConfiguration clientConfig;
    // Optional: Set to the AWS Region (overrides config file).
    // clientConfig.region = "us-east-1";

Aws::RDS::RDSClient client(clientConfig);

    Aws::RDS::Model::CreateDBInstanceRequest request;
    request.SetDBName(DB_NAME);
    request.SetDBInstanceIdentifier(DB_INSTANCE_IDENTIFIER);
    request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);
    request.SetEngine(engineVersion.GetEngine());
    request.SetEngineVersion(engineVersion.GetEngineVersion());
    request.SetDBInstanceClass(dbInstanceClass);
    request.SetStorageType(DB_STORAGE_TYPE);
    request.SetAllocatedStorage(DB_ALLOCATED_STORAGE);
    request.SetMasterUsername(administratorName);
    request.SetMasterUserPassword(administratorPassword);

    Aws::RDS::Model::CreateDBInstanceOutcome outcome =
            client.CreateDBInstance(request);

    if (outcome.IsSuccess()) {
        std::cout << "The DB instance creation has started."
                  << std::endl;
    }
    else {
        std::cerr << "Error with RDS::CreateDBInstance. "
                  << outcome.GetError().GetMessage()
```

```
                  << std::endl;
        cleanUpResources(PARAMETER_GROUP_NAME, "", client);
        return false;
    }
```

- For API details, see CreateDBInstance in *AWS SDK for C++ API Reference*.

`CreateDBParameterGroup`

The following code example shows how to use `CreateDBParameterGroup`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
    Aws::Client::ClientConfiguration clientConfig;
    // Optional: Set to the AWS Region (overrides config file).
    // clientConfig.region = "us-east-1";

Aws::RDS::RDSClient client(clientConfig);

    Aws::RDS::Model::CreateDBParameterGroupRequest request;
    request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);
    request.SetDBParameterGroupFamily(dbParameterGroupFamily);
    request.SetDescription("Example parameter group.");

    Aws::RDS::Model::CreateDBParameterGroupOutcome outcome =
            client.CreateDBParameterGroup(request);

    if (outcome.IsSuccess()) {
        std::cout << "The DB parameter group was successfully created."
                  << std::endl;
    }
    else {
        std::cerr << "Error with RDS::CreateDBParameterGroup. "
                  << outcome.GetError().GetMessage()
```

```
                    << std::endl;
            return false;
        }
```

- For API details, see CreateDBParameterGroup in *AWS SDK for C++ API Reference*.

`CreateDBSnapshot`

The following code example shows how to use `CreateDBSnapshot`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

            Aws::RDS::Model::CreateDBSnapshotRequest request;
            request.SetDBInstanceIdentifier(DB_INSTANCE_IDENTIFIER);
            request.SetDBSnapshotIdentifier(snapshotID);

            Aws::RDS::Model::CreateDBSnapshotOutcome outcome =
                    client.CreateDBSnapshot(request);

            if (outcome.IsSuccess()) {
                std::cout << "Snapshot creation has started."
                          << std::endl;
            }
            else {
                std::cerr << "Error with RDS::CreateDBSnapshot. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUpResources(PARAMETER_GROUP_NAME, DB_INSTANCE_IDENTIFIER,
client);
```

```
            return false;
        }
```

- For API details, see CreateDBSnapshot in *AWS SDK for C++ API Reference*.

`DeleteDBInstance`

The following code example shows how to use `DeleteDBInstance`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
    Aws::Client::ClientConfiguration clientConfig;
    // Optional: Set to the AWS Region (overrides config file).
    // clientConfig.region = "us-east-1";

Aws::RDS::RDSClient client(clientConfig);

        Aws::RDS::Model::DeleteDBInstanceRequest request;
        request.SetDBInstanceIdentifier(dbInstanceIdentifier);
        request.SetSkipFinalSnapshot(true);
        request.SetDeleteAutomatedBackups(true);

        Aws::RDS::Model::DeleteDBInstanceOutcome outcome =
                client.DeleteDBInstance(request);

        if (outcome.IsSuccess()) {
            std::cout << "DB instance deletion has started."
                      << std::endl;
        }
        else {
            std::cerr << "Error with RDS::DeleteDBInstance. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
        }
```

- For API details, see DeleteDBInstance in *AWS SDK for C++ API Reference*.

`DeleteDBParameterGroup`

The following code example shows how to use `DeleteDBParameterGroup`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
    Aws::Client::ClientConfiguration clientConfig;
    // Optional: Set to the AWS Region (overrides config file).
    // clientConfig.region = "us-east-1";

Aws::RDS::RDSClient client(clientConfig);

    Aws::RDS::Model::DeleteDBParameterGroupRequest request;
    request.SetDBParameterGroupName(parameterGroupName);

    Aws::RDS::Model::DeleteDBParameterGroupOutcome outcome =
            client.DeleteDBParameterGroup(request);

    if (outcome.IsSuccess()) {
        std::cout << "The DB parameter group was successfully deleted."
                  << std::endl;
    }
    else {
        std::cerr << "Error with RDS::DeleteDBParameterGroup. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
        result = false;
    }
```

- For API details, see DeleteDBParameterGroup in *AWS SDK for C++ API Reference*.

`DescribeDBEngineVersions`

The following code example shows how to use `DescribeDBEngineVersions`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);


//! Routine which gets available DB engine versions for an engine name and
//! an optional parameter group family.
/*!
 \sa getDBEngineVersions()
 \param engineName: A DB engine name.
 \param parameterGroupFamily: A parameter group family name, ignored if empty.
 \param engineVersionsResult: Vector of 'DBEngineVersion' objects returned by the
 routine.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::RDS::getDBEngineVersions(const Aws::String &engineName,
                                      const Aws::String &parameterGroupFamily,
                                      Aws::Vector<Aws::RDS::Model::DBEngineVersion>
 &engineVersionsResult,
                                      const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBEngineVersionsRequest request;
    request.SetEngine(engineName);
    if (!parameterGroupFamily.empty()) {
        request.SetDBParameterGroupFamily(parameterGroupFamily);
    }

    engineVersionsResult.clear();
    Aws::String marker; // Used for pagination.
```

```
    do {
        if (!marker.empty()) {
            request.SetMarker(marker);
        }


        Aws::RDS::Model::DescribeDBEngineVersionsOutcome outcome =
                client.DescribeDBEngineVersions(request);

        if (outcome.IsSuccess()) {
            auto &engineVersions = outcome.GetResult().GetDBEngineVersions();
            engineVersionsResult.insert(engineVersionsResult.end(),
 engineVersions.begin(),
                                        engineVersions.end());
            marker = outcome.GetResult().GetMarker();
        }
        else {
            std::cerr << "Error with RDS::DescribeDBEngineVersionsRequest. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }

    } while (!marker.empty());


    return true;
}
```

- For API details, see DescribeDBEngineVersions in *AWS SDK for C++ API Reference*.

`DescribeDBInstances`

The following code example shows how to use `DescribeDBInstances`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);


//! Routine which gets a DB instance description.
/*!
 \sa describeDBInstance()
 \param dbInstanceIdentifier: A DB instance identifier.
 \param instanceResult: The 'DBInstance' object containing the description.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::RDS::describeDBInstance(const Aws::String &dbInstanceIdentifier,
                                     Aws::RDS::Model::DBInstance &instanceResult,
                                     const Aws::RDS::RDSClient &client) {
    Aws::RDS::Model::DescribeDBInstancesRequest request;
    request.SetDBInstanceIdentifier(dbInstanceIdentifier);

    Aws::RDS::Model::DescribeDBInstancesOutcome outcome =
            client.DescribeDBInstances(request);

    bool result = true;
    if (outcome.IsSuccess()) {
        instanceResult = outcome.GetResult().GetDBInstances()[0];
    }
    else if (outcome.GetError().GetErrorType() !=
             Aws::RDS::RDSErrors::D_B_INSTANCE_NOT_FOUND_FAULT) {
        result = false;
        std::cerr << "Error with RDS::DescribeDBInstances. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
```

```
    }
        // This example does not log an error if the DB instance does not exist.
        // Instead, instanceResult is set to empty.
    else {
        instanceResult = Aws::RDS::Model::DBInstance();
    }

    return result;
}
```

- For API details, see DescribeDBInstances in *AWS SDK for C++ API Reference*.

`DescribeDBParameterGroups`

The following code example shows how to use `DescribeDBParameterGroups`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

        Aws::RDS::Model::DescribeDBParameterGroupsRequest request;
        request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);

        Aws::RDS::Model::DescribeDBParameterGroupsOutcome outcome =
                client.DescribeDBParameterGroups(request);

        if (outcome.IsSuccess()) {
            std::cout << "DB parameter group named '" <<
                      PARAMETER_GROUP_NAME << "' already exists." << std::endl;
            dbParameterGroupFamily = outcome.GetResult().GetDBParameterGroups()
[0].GetDBParameterGroupFamily();
```

```
        }

        else {
            std::cerr << "Error with RDS::DescribeDBParameterGroups. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
```

- For API details, see DescribeDBParameterGroups in *AWS SDK for C++ API Reference*.

`DescribeDBParameters`

The following code example shows how to use `DescribeDBParameters`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);


//! Routine which gets DB parameters using the 'DescribeDBParameters' api.
/*!
 \sa getDBParameters()
 \param parameterGroupName: The name of the parameter group.
 \param namePrefix: Prefix string to filter results by parameter name.
 \param source: A source such as 'user', ignored if empty.
 \param parametersResult: Vector of 'Parameter' objects returned by the routine.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::RDS::getDBParameters(const Aws::String &parameterGroupName,
```

```
                                const Aws::String &namePrefix,
                                const Aws::String &source,
                                Aws::Vector<Aws::RDS::Model::Parameter>
&parametersResult,
                                const Aws::RDS::RDSClient &client) {
   Aws::String marker;
   do {
       Aws::RDS::Model::DescribeDBParametersRequest request;
       request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);
       if (!marker.empty()) {
           request.SetMarker(marker);
       }
       if (!source.empty()) {
           request.SetSource(source);
       }

       Aws::RDS::Model::DescribeDBParametersOutcome outcome =
               client.DescribeDBParameters(request);

       if (outcome.IsSuccess()) {
           const Aws::Vector<Aws::RDS::Model::Parameter> &parameters =
                   outcome.GetResult().GetParameters();
           for (const Aws::RDS::Model::Parameter &parameter: parameters) {
               if (!namePrefix.empty()) {
                   if (parameter.GetParameterName().find(namePrefix) == 0) {
                       parametersResult.push_back(parameter);
                   }
               }
               else {
                   parametersResult.push_back(parameter);
               }
           }

           marker = outcome.GetResult().GetMarker();
       }
       else {
           std::cerr << "Error with RDS::DescribeDBParameters. "
                     << outcome.GetError().GetMessage()
                     << std::endl;
           return false;
       }
   } while (!marker.empty());

   return true;
```

```
}
```

- For API details, see DescribeDBParameters in *AWS SDK for C++ API Reference*.

`DescribeDBSnapshots`

The following code example shows how to use `DescribeDBSnapshots`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);

            Aws::RDS::Model::DescribeDBSnapshotsRequest request;
            request.SetDBSnapshotIdentifier(snapshotID);

            Aws::RDS::Model::DescribeDBSnapshotsOutcome outcome =
                    client.DescribeDBSnapshots(request);

            if (outcome.IsSuccess()) {
                snapshot = outcome.GetResult().GetDBSnapshots()[0];
            }
            else {
                std::cerr << "Error with RDS::DescribeDBSnapshots. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUpResources(PARAMETER_GROUP_NAME, DB_INSTANCE_IDENTIFIER,
client);
                return false;
            }
```

- For API details, see DescribeDBSnapshots in *AWS SDK for C++ API Reference*.

`DescribeOrderableDBInstanceOptions`

The following code example shows how to use `DescribeOrderableDBInstanceOptions`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::RDS::RDSClient client(clientConfig);


//! Routine which gets available 'micro' DB instance classes, displays the list
//! to the user, and returns the user selection.
/*!
 \sa chooseMicroDBInstanceClass()
 \param engineName: The DB engine name.
 \param engineVersion: The DB engine version.
 \param dbInstanceClass: String for DB instance class chosen by the user.
 \param client: 'RDSClient' instance.
 \return bool: Successful completion.
 */
bool AwsDoc::RDS::chooseMicroDBInstanceClass(const Aws::String &engine,
                                             const Aws::String &engineVersion,
                                             Aws::String &dbInstanceClass,
                                             const Aws::RDS::RDSClient &client) {
    std::vector<Aws::String> instanceClasses;
    Aws::String marker;
    do {
        Aws::RDS::Model::DescribeOrderableDBInstanceOptionsRequest request;
        request.SetEngine(engine);
        request.SetEngineVersion(engineVersion);
        if (!marker.empty()) {
```

```
            request.SetMarker(marker);
        }

        Aws::RDS::Model::DescribeOrderableDBInstanceOptionsOutcome outcome =
                client.DescribeOrderableDBInstanceOptions(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::RDS::Model::OrderableDBInstanceOption> &options =
                    outcome.GetResult().GetOrderableDBInstanceOptions();
            for (const Aws::RDS::Model::OrderableDBInstanceOption &option: options)
 {
                const Aws::String &instanceClass = option.GetDBInstanceClass();
                if (instanceClass.find("micro") != std::string::npos) {
                    if (std::find(instanceClasses.begin(), instanceClasses.end(),
                                  instanceClass) ==
                        instanceClasses.end()) {
                        instanceClasses.push_back(instanceClass);
                    }
                }
            }
            marker = outcome.GetResult().GetMarker();
        }
        else {
            std::cerr << "Error with RDS::DescribeOrderableDBInstanceOptions. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (!marker.empty());

    std::cout << "The available micro DB instance classes for your database engine
 are:"
              << std::endl;
    for (int i = 0; i < instanceClasses.size(); ++i) {
        std::cout << "   " << i + 1 << ": " << instanceClasses[i] << std::endl;
    }

    int choice = askQuestionForIntRange(
            "Which micro DB instance class do you want to use? ",
            1, static_cast<int>(instanceClasses.size()));
    dbInstanceClass = instanceClasses[choice - 1];
    return true;
}
```

- For API details, see DescribeOrderableDBInstanceOptions in *AWS SDK for C++ API Reference*.

`ModifyDBParameterGroup`

The following code example shows how to use `ModifyDBParameterGroup`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
    Aws::Client::ClientConfiguration clientConfig;
    // Optional: Set to the AWS Region (overrides config file).
    // clientConfig.region = "us-east-1";

Aws::RDS::RDSClient client(clientConfig);

    Aws::RDS::Model::ModifyDBParameterGroupRequest request;
    request.SetDBParameterGroupName(PARAMETER_GROUP_NAME);
    request.SetParameters(updateParameters);

    Aws::RDS::Model::ModifyDBParameterGroupOutcome outcome =
            client.ModifyDBParameterGroup(request);

    if (outcome.IsSuccess()) {
        std::cout << "The DB parameter group was successfully modified."
                  << std::endl;
    }
    else {
        std::cerr << "Error with RDS::ModifyDBParameterGroup. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
```

- For API details, see ModifyDBParameterGroup in *AWS SDK for C++ API Reference*.

Scenarios

Create an Aurora Serverless work item tracker

The following code example shows how to create a web application that tracks work items in an Amazon Aurora Serverless database and uses Amazon Simple Email Service (Amazon SES) to send reports.

SDK for C++

Shows how to create a web application that tracks and reports on work items stored in an Amazon Aurora Serverless database.

For complete source code and instructions on how to set up a C++ REST API that queries Amazon Aurora Serverless data and for use by a React application, see the full example on GitHub.

Services used in this example

- Aurora
- Amazon RDS
- Amazon RDS Data Service
- Amazon SES

Amazon RDS Data Service examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with Amazon RDS Data Service.

Scenarios are code examples that show you how to accomplish specific tasks by calling multiple functions within a service or combined with other AWS services.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Scenarios

Scenarios

Create an Aurora Serverless work item tracker

The following code example shows how to create a web application that tracks work items in an Amazon Aurora Serverless database and uses Amazon Simple Email Service (Amazon SES) to send reports.

SDK for C++

Shows how to create a web application that tracks and reports on work items stored in an Amazon Aurora Serverless database.

For complete source code and instructions on how to set up a C++ REST API that queries Amazon Aurora Serverless data and for use by a React application, see the full example on GitHub.

Services used in this example

- Aurora
- Amazon RDS
- Amazon RDS Data Service
- Amazon SES

Amazon Rekognition examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with Amazon Rekognition.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Scenarios are code examples that show you how to accomplish specific tasks by calling multiple functions within a service or combined with other AWS services.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Get started

- Actions
- Scenarios

Get started

Hello Amazon Rekognition

The following code example shows how to get started using Amazon Rekognition.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Code for the CMakeLists.txt CMake file.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS rekognition)

# Set this project's name.
project("hello_rekognition")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()
```

```
# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD AND AWSSDK_INSTALL_AS_SHARED_LIBS)
     # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

     # set(BIN_SUB_DIR "/Debug") # If you are building from the command line, you
 may need to uncomment this
                                     # and set the proper subdirectory to the
 executables' location.

     AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_rekognition.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Code for the hello_rekognition.cpp source file.

```
#include <aws/core/Aws.h>
#include <aws/rekognition/RekognitionClient.h>
#include <aws/rekognition/model/ListCollectionsRequest.h>
#include <iostream>

/*
 *  A "Hello Rekognition" starter application which initializes an Amazon
 Rekognition client and
 *  lists the Amazon Rekognition collections in the current account and region.
 *
 *  main function
 *
 *  Usage: 'hello_rekognition'
 *
 */

int main(int argc, char **argv) {
```

```
    Aws::SDKOptions options;
    //  Optional: change the log level for debugging.
    //  options.loggingOptions.logLevel = Aws::Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::Rekognition::RekognitionClient rekognitionClient(clientConfig);
        Aws::Rekognition::Model::ListCollectionsRequest request;
        Aws::Rekognition::Model::ListCollectionsOutcome outcome =
                rekognitionClient.ListCollections(request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::String>& collectionsIds =
 outcome.GetResult().GetCollectionIds();
            if (!collectionsIds.empty()) {
                std::cout << "collectionsIds: " << std::endl;
                for (auto &collectionId : collectionsIds) {
                    std::cout << "- " << collectionId << std::endl;
                }
            } else {
                std::cout << "No collections found" << std::endl;
            }
        } else {
            std::cerr << "Error with ListCollections: " << outcome.GetError()
                      << std::endl;
        }
    }


    Aws::ShutdownAPI(options); // Should only be called once.
    return 0;
}
```

- For API details, see ListCollections in *AWS SDK for C++ API Reference*.

Actions

`DetectLabels`

The following code example shows how to use `DetectLabels`.

For more information, see Detecting labels in an image.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Detect instances of real-world entities within an image by using Amazon
 Rekognition
/*!
  \param imageBucket: The Amazon Simple Storage Service (Amazon S3) bucket
 containing an image.
  \param imageKey: The Amazon S3 key of an image object.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::Rekognition::detectLabels(const Aws::String &imageBucket,
                                       const Aws::String &imageKey,
                                       const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::Rekognition::RekognitionClient rekognitionClient(clientConfiguration);

    Aws::Rekognition::Model::DetectLabelsRequest request;
    Aws::Rekognition::Model::S3Object s3Object;
    s3Object.SetBucket(imageBucket);
    s3Object.SetName(imageKey);

    Aws::Rekognition::Model::Image image;
    image.SetS3Object(s3Object);

    request.SetImage(image);
```

```
    const Aws::Rekognition::Model::DetectLabelsOutcome outcome =
 rekognitionClient.DetectLabels(request);

    if (outcome.IsSuccess()) {
        const Aws::Vector<Aws::Rekognition::Model::Label> &labels =
 outcome.GetResult().GetLabels();
        if (labels.empty()) {
            std::cout << "No labels detected" << std::endl;
        } else {
            for (const Aws::Rekognition::Model::Label &label: labels) {
                std::cout << label.GetName() << ": " << label.GetConfidence() <<
 std::endl;
            }
        }
    } else {
        std::cerr << "Error while detecting labels: '"
                  << outcome.GetError().GetMessage()
                  << "'" << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DetectLabels in *AWS SDK for C++ API Reference*.

Scenarios

Create a serverless application to manage photos

The following code example shows how to create a serverless application that lets users manage photos using labels.

SDK for C++

Shows how to develop a photo asset management application that detects labels in images using Amazon Rekognition and stores them for later retrieval.

For complete source code and instructions on how to set up and run, see the full example on GitHub.

For a deep dive into the origin of this example see the post on AWS Community.

Services used in this example

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Amazon S3 examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with Amazon S3.

Basics are code examples that show you how to perform the essential operations within a service.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Scenarios are code examples that show you how to accomplish specific tasks by calling multiple functions within a service or combined with other AWS services.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Get started
- Basics
- Actions
- Scenarios

Get started

Hello Amazon S3

The following code example shows how to get started using Amazon S3.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Code for the CMakeLists.txt CMake file.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS s3)

# Set this project's name.
project("hello_s3")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD AND AWSSDK_INSTALL_AS_SHARED_LIBS)
    # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

    # set(BIN_SUB_DIR "/Debug") # if you are building from the command line you may
 need to uncomment this
    # and set the proper subdirectory to the executables' location.
```

```
    AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_s3.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Code for the hello_s3.cpp source file.

```
#include <aws/core/Aws.h>
#include <aws/s3/S3Client.h>
#include <iostream>
#include <aws/core/auth/AWSCredentialsProviderChain.h>
using namespace Aws;
using namespace Aws::Auth;

/*
 *  A "Hello S3" starter application which initializes an Amazon Simple Storage
 Service (Amazon S3) client
 *  and lists the Amazon S3 buckets in the selected region.
 *
 *  main function
 *
 *  Usage: 'hello_s3'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    int result = 0;
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";
```

```
        // You don't normally have to test that you are authenticated. But the S3
 service permits anonymous requests, thus the s3Client will return "success" and 0
 buckets even if you are unauthenticated, which can be confusing to a new user.
        auto provider = Aws::MakeShared<DefaultAWSCredentialsProviderChain>("alloc-
tag");
        auto creds = provider->GetAWSCredentials();
        if (creds.IsEmpty()) {
            std::cerr << "Failed authentication" << std::endl;
        }

        Aws::S3::S3Client s3Client(clientConfig);
        auto outcome = s3Client.ListBuckets();

        if (!outcome.IsSuccess()) {
            std::cerr << "Failed with error: " << outcome.GetError() << std::endl;
            result = 1;
        } else {
            std::cout << "Found " << outcome.GetResult().GetBuckets().size()
                      << " buckets\n";
            for (auto &bucket: outcome.GetResult().GetBuckets()) {
                std::cout << bucket.GetName() << std::endl;
            }
        }
    }

    Aws::ShutdownAPI(options); // Should only be called once.
    return result;
}
```

- For API details, see ListBuckets in *AWS SDK for C++ API Reference*.

Basics

Learn the basics

The following code example shows how to:

- Create a bucket and upload a file to it.
- Download an object from a bucket.
- Copy an object to a subfolder in a bucket.

- List the objects in a bucket.
- Delete the bucket objects and the bucket.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
#include <iostream>
#include <aws/core/Aws.h>
#include <aws/s3/S3Client.h>
#include <aws/s3/model/CopyObjectRequest.h>
#include <aws/s3/model/CreateBucketRequest.h>
#include <aws/s3/model/DeleteBucketRequest.h>
#include <aws/s3/model/DeleteObjectRequest.h>
#include <aws/s3/model/GetObjectRequest.h>
#include <aws/s3/model/ListObjectsV2Request.h>
#include <aws/s3/model/PutObjectRequest.h>
#include <aws/s3/model/BucketLocationConstraint.h>
#include <aws/s3/model/CreateBucketConfiguration.h>
#include <aws/core/utils/UUID.h>
#include <aws/core/utils/StringUtils.h>
#include <aws/core/utils/memory/stl/AWSAllocator.h>
#include <fstream>
#include "s3_examples.h"

namespace AwsDoc {
    namespace S3 {

        //! Delete an S3 bucket.
        /*!
          \param bucketName: The S3 bucket's name.
          \param client: An S3 client.
          \return bool: Function succeeded.
        */
        static bool
        deleteBucket(const Aws::String &bucketName, Aws::S3::S3Client &client);
```

```
        //! Delete an object in an S3 bucket.
        /*!
          \param bucketName: The S3 bucket's name.
          \param key: The key for the object in the S3 bucket.
          \param client: An S3 client.
          \return bool: Function succeeded.
         */
        static bool
        deleteObjectFromBucket(const Aws::String &bucketName, const Aws::String
 &key,
                               Aws::S3::S3Client &client);
    }
}


//! Scenario to create, copy, and delete S3 buckets and objects.
/*!
  \param bucketNamePrefix: A prefix for a bucket name.
  \param uploadFilePath: Path to file to upload to an Amazon S3 bucket.
  \param saveFilePath: Path for saving a downloaded S3 object.
  \param clientConfig: Aws client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::S3::S3_GettingStartedScenario(const Aws::String &bucketNamePrefix,
        const Aws::String &uploadFilePath,
                                           const Aws::String &saveFilePath,
                                           const Aws::Client::ClientConfiguration
 &clientConfig) {

    Aws::S3::S3Client client(clientConfig);

    // Create a unique bucket name which is only temporary and will be deleted.
    // Format: <bucketNamePrefix> + "-" + lowercase UUID.
    Aws::String uuid = Aws::Utils::UUID::RandomUUID();
    Aws::String bucketName = bucketNamePrefix +
                             Aws::Utils::StringUtils::ToLower(uuid.c_str());

    // 1. Create a bucket.
    {
        Aws::S3::Model::CreateBucketRequest request;
        request.SetBucket(bucketName);

        if (clientConfig.region != Aws::Region::US_EAST_1) {
            Aws::S3::Model::CreateBucketConfiguration createBucketConfiguration;
```

```
            createBucketConfiguration.WithLocationConstraint(

Aws::S3::Model::BucketLocationConstraintMapper::GetBucketLocationConstraintForName(
                            clientConfig.region));
            request.WithCreateBucketConfiguration(createBucketConfiguration);
        }

        Aws::S3::Model::CreateBucketOutcome outcome = client.CreateBucket(request);

        if (!outcome.IsSuccess()) {
            const Aws::S3::S3Error &err = outcome.GetError();
            std::cerr << "Error: createBucket: " <<
                      err.GetExceptionName() << ": " << err.GetMessage() <<
std::endl;
            return false;
        } else {
            std::cout << "Created the bucket, '" << bucketName <<
                      "', in the region, '" << clientConfig.region << "'." <<
std::endl;
        }
    }

    // 2. Upload a local file to the bucket.
    Aws::String key = "key-for-test";
    {
        Aws::S3::Model::PutObjectRequest request;
        request.SetBucket(bucketName);
        request.SetKey(key);

        std::shared_ptr<Aws::FStream> input_data =
                Aws::MakeShared<Aws::FStream>("SampleAllocationTag",
                                              uploadFilePath,
                                              std::ios_base::in |
                                              std::ios_base::binary);

        if (!input_data->is_open()) {
            std::cerr << "Error: unable to open file, '" << uploadFilePath << "'."
                      << std::endl;
            AwsDoc::S3::deleteBucket(bucketName, client);
            return false;
        }

        request.SetBody(input_data);
```

```
        Aws::S3::Model::PutObjectOutcome outcome =
                client.PutObject(request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Error: putObject: " <<
                      outcome.GetError().GetMessage() << std::endl;
            AwsDoc::S3::deleteObjectFromBucket(bucketName, key, client);
            AwsDoc::S3::deleteBucket(bucketName, client);
            return false;
        } else {
            std::cout << "Added the object with the key, '" << key
                      << "', to the bucket, '"
                      << bucketName << "'." << std::endl;
        }
    }

    // 3. Download the object to a local file.
    {
        Aws::S3::Model::GetObjectRequest request;
        request.SetBucket(bucketName);
        request.SetKey(key);

        Aws::S3::Model::GetObjectOutcome outcome =
                client.GetObject(request);

        if (!outcome.IsSuccess()) {
            const Aws::S3::S3Error &err = outcome.GetError();
            std::cerr << "Error: getObject: " <<
                      err.GetExceptionName() << ": " << err.GetMessage() <<
std::endl;
        } else {
            std::cout << "Downloaded the object with the key, '" << key
                      << "', in the bucket, '"
                      << bucketName << "'." << std::endl;

            Aws::IOStream &ioStream = outcome.GetResultWithOwnership().
                    GetBody();
            Aws::OFStream outStream(saveFilePath,
                                    std::ios_base::out | std::ios_base::binary);
            if (!outStream.is_open()) {
                std::cout << "Error: unable to open file, '" << saveFilePath << "'."
                          << std::endl;
            } else {
                outStream << ioStream.rdbuf();
```

```
                std::cout << "Wrote the downloaded object to the file '"
                          << saveFilePath << "'." << std::endl;
            }
        }
    }

    // 4. Copy the object to a different "folder" in the bucket.
    Aws::String copiedToKey = "test-folder/" + key;
    {
        Aws::S3::Model::CopyObjectRequest request;
        request.WithBucket(bucketName)
                .WithKey(copiedToKey)
                .WithCopySource(bucketName + "/" + key);

        Aws::S3::Model::CopyObjectOutcome outcome =
                client.CopyObject(request);
        if (!outcome.IsSuccess()) {
            std::cerr << "Error: copyObject: " <<
                      outcome.GetError().GetMessage() << std::endl;
        } else {
            std::cout << "Copied the object with the key, '" << key
                      << "', to the key, '" << copiedToKey
                      << ", in the bucket, '" << bucketName << "'." << std::endl;
        }
    }

    // 5. List objects in the bucket.
    {
        Aws::S3::Model::ListObjectsV2Request request;
        request.WithBucket(bucketName);

        Aws::String continuationToken;
        Aws::Vector<Aws::S3::Model::Object> allObjects;

        do {
            if (!continuationToken.empty()) {
                request.SetContinuationToken(continuationToken);
            }
            Aws::S3::Model::ListObjectsV2Outcome outcome = client.ListObjectsV2(
                    request);

            if (!outcome.IsSuccess()) {
                std::cerr << "Error: ListObjects: " <<
                          outcome.GetError().GetMessage() << std::endl;
```

```
                break;
            } else {
                Aws::Vector<Aws::S3::Model::Object> objects =
                        outcome.GetResult().GetContents();
                allObjects.insert(allObjects.end(), objects.begin(), objects.end());
                continuationToken = outcome.GetResult().GetContinuationToken();
            }
        } while (!continuationToken.empty());

        std::cout << allObjects.size() << " objects in the bucket, '" << bucketName
                  << "':" << std::endl;

        for (Aws::S3::Model::Object &object: allObjects) {
            std::cout << "     '" << object.GetKey() << "'" << std::endl;
        }
    }

    // 6. Delete all objects in the bucket.
    // All objects in the bucket must be deleted before deleting the bucket.
    AwsDoc::S3::deleteObjectFromBucket(bucketName, copiedToKey, client);
    AwsDoc::S3::deleteObjectFromBucket(bucketName, key, client);

    // 7. Delete the bucket.
    return AwsDoc::S3::deleteBucket(bucketName, client);
}

bool AwsDoc::S3::deleteObjectFromBucket(const Aws::String &bucketName,
                                        const Aws::String &key,
                                        Aws::S3::S3Client &client) {
    Aws::S3::Model::DeleteObjectRequest request;
    request.SetBucket(bucketName);
    request.SetKey(key);

    Aws::S3::Model::DeleteObjectOutcome outcome =
            client.DeleteObject(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: deleteObject: " <<
                  outcome.GetError().GetMessage() << std::endl;
    } else {
        std::cout << "Deleted the object with the key, '" << key
                  << "', from the bucket, '"
                  << bucketName << "'." << std::endl;
    }
```

```
    return outcome.IsSuccess();
}

bool
AwsDoc::S3::deleteBucket(const Aws::String &bucketName, Aws::S3::S3Client &client) {
    Aws::S3::Model::DeleteBucketRequest request;
    request.SetBucket(bucketName);

    Aws::S3::Model::DeleteBucketOutcome outcome =
            client.DeleteBucket(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: deleteBucket: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() << std::endl;
    } else {
        std::cout << "Deleted the bucket, '" << bucketName << "'." << std::endl;
    }
    return outcome.IsSuccess();
}
```

- For API details, see the following topics in *AWS SDK for C++ API Reference*.
  - CopyObject
  - CreateBucket
  - DeleteBucket
  - DeleteObjects
  - GetObject
  - ListObjectsV2
  - PutObject

Actions

`AbortMultipartUpload`

The following code example shows how to use `AbortMultipartUpload`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Abort a multipart upload to an S3 bucket.
/*!
    \param bucket: The name of the S3 bucket where the object will be uploaded.
    \param key: The unique identifier (key) for the object within the S3 bucket.
    \param uploadID: An upload ID string.
    \param client: The S3 client instance used to perform the upload operation.
    \return bool: Function succeeded.
*/

bool AwsDoc::S3::abortMultipartUpload(const Aws::String &bucket,
                                      const Aws::String &key,
                                      const Aws::String &uploadID,
                                      const Aws::S3::S3Client &client) {
    Aws::S3::Model::AbortMultipartUploadRequest request;
    request.SetBucket(bucket);
    request.SetKey(key);
    request.SetUploadId(uploadID);

    Aws::S3::Model::AbortMultipartUploadOutcome outcome =
            client.AbortMultipartUpload(request);

    if (outcome.IsSuccess()) {
        std::cout << "Multipart upload aborted." << std::endl;
    } else {
        std::cerr << "Error aborting multipart upload: " <<
 outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see AbortMultipartUpload in *AWS SDK for C++ API Reference*.

`CompleteMultipartUpload`

The following code example shows how to use `CompleteMultipartUpload`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Complete a multipart upload to an S3 bucket.
/*!
    \param bucket: The name of the S3 bucket where the object will be uploaded.
    \param key: The unique identifier (key) for the object within the S3 bucket.
    \param uploadID: An upload ID string.
    \param parts: A vector of CompleteParts.
    \param client: The S3 client instance used to perform the upload operation.
    \return CompleteMultipartUploadOutcome: The request outcome.
*/
Aws::S3::Model::CompleteMultipartUploadOutcome
 AwsDoc::S3::completeMultipartUpload(const Aws::String &bucket,

 const Aws::String &key,

 const Aws::String &uploadID,

 const Aws::Vector<Aws::S3::Model::CompletedPart> &parts,

 const Aws::S3::S3Client &client) {
    Aws::S3::Model::CompletedMultipartUpload completedMultipartUpload;
    completedMultipartUpload.SetParts(parts);

    Aws::S3::Model::CompleteMultipartUploadRequest request;
    request.SetBucket(bucket);
    request.SetKey(key);
    request.SetUploadId(uploadID);
    request.SetMultipartUpload(completedMultipartUpload);

    Aws::S3::Model::CompleteMultipartUploadOutcome outcome =
            client.CompleteMultipartUpload(request);
```

```
    if (!outcome.IsSuccess()) {
        std::cerr << "Error completing multipart upload: " <<
 outcome.GetError().GetMessage() << std::endl;
    }
    return outcome;
}
```

- For API details, see CompleteMultipartUpload in *AWS SDK for C++ API Reference*.

`CopyObject`

The following code example shows how to use `CopyObject`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::S3::copyObject(const Aws::String &objectKey, const Aws::String
 &fromBucket, const Aws::String &toBucket,
                            const Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client client(clientConfig);
    Aws::S3::Model::CopyObjectRequest request;

    request.WithCopySource(fromBucket + "/" + objectKey)
            .WithKey(objectKey)
            .WithBucket(toBucket);

    Aws::S3::Model::CopyObjectOutcome outcome = client.CopyObject(request);
    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: copyObject: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() << std::endl;

    } else {
        std::cout << "Successfully copied " << objectKey << " from " << fromBucket
 <<
                  " to " << toBucket << "." << std::endl;
```

```
    }

    return outcome.IsSuccess();
}
```

- For API details, see CopyObject in *AWS SDK for C++ API Reference*.

`CreateBucket`

The following code example shows how to use `CreateBucket`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::S3::createBucket(const Aws::String &bucketName,
                              const Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client client(clientConfig);
    Aws::S3::Model::CreateBucketRequest request;
    request.SetBucket(bucketName);

    if (clientConfig.region != "us-east-1") {
        Aws::S3::Model::CreateBucketConfiguration createBucketConfig;
        createBucketConfig.SetLocationConstraint(

 Aws::S3::Model::BucketLocationConstraintMapper::GetBucketLocationConstraintForName(
                        clientConfig.region));
        request.SetCreateBucketConfiguration(createBucketConfig);
    }

    Aws::S3::Model::CreateBucketOutcome outcome = client.CreateBucket(request);
    if (!outcome.IsSuccess()) {
        auto err = outcome.GetError();
        std::cerr << "Error: createBucket: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() << std::endl;
    } else {
        std::cout << "Created bucket " << bucketName <<
```

```
                  " in the specified AWS Region." << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see CreateBucket in *AWS SDK for C++ API Reference*.

`CreateMultipartUpload`

The following code example shows how to use `CreateMultipartUpload`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Create a multipart upload.
/*!
    \param bucket: The name of the S3 bucket where the object will be uploaded.
    \param key: The unique identifier (key) for the object within the S3 bucket.
    \param client: The S3 client instance used to perform the upload operation.
    \return Aws::String: Upload ID or empty string if failed.
*/
Aws::String
AwsDoc::S3::createMultipartUpload(const Aws::String &bucket, const Aws::String &key,
                                  Aws::S3::Model::ChecksumAlgorithm
 checksumAlgorithm,
                                  const Aws::S3::S3Client &client) {
    Aws::S3::Model::CreateMultipartUploadRequest request;
    request.SetBucket(bucket);
    request.SetKey(key);

    if (checksumAlgorithm != Aws::S3::Model::ChecksumAlgorithm::NOT_SET) {
        request.SetChecksumAlgorithm(checksumAlgorithm);
    }
```

```
    Aws::S3::Model::CreateMultipartUploadOutcome outcome =
            client.CreateMultipartUpload(request);

    Aws::String uploadID;
    if (outcome.IsSuccess()) {
        uploadID = outcome.GetResult().GetUploadId();
    } else {
        std::cerr << "Error creating multipart upload: " <<
 outcome.GetError().GetMessage() << std::endl;
    }

    return uploadID;
}
```

- For API details, see CreateMultipartUpload in *AWS SDK for C++ API Reference*.

`DeleteBucket`

The following code example shows how to use `DeleteBucket`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::S3::deleteBucket(const Aws::String &bucketName,
                              const Aws::S3::S3ClientConfiguration &clientConfig) {

    Aws::S3::S3Client client(clientConfig);

    Aws::S3::Model::DeleteBucketRequest request;
    request.SetBucket(bucketName);

    Aws::S3::Model::DeleteBucketOutcome outcome =
            client.DeleteBucket(request);

    if (!outcome.IsSuccess()) {
```

```
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: deleteBucket: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() << std::endl;
    } else {
        std::cout << "The bucket was deleted" << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DeleteBucket in *AWS SDK for C++ API Reference*.

`DeleteBucketPolicy`

The following code example shows how to use `DeleteBucketPolicy`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::S3::deleteBucketPolicy(const Aws::String &bucketName,
                                    const Aws::S3::S3ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client client(clientConfig);

    Aws::S3::Model::DeleteBucketPolicyRequest request;
    request.SetBucket(bucketName);

    Aws::S3::Model::DeleteBucketPolicyOutcome outcome =
 client.DeleteBucketPolicy(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: deleteBucketPolicy: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() << std::endl;
    } else {
```

```
        std::cout << "Policy was deleted from the bucket." << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DeleteBucketPolicy in *AWS SDK for C++ API Reference*.

`DeleteBucketWebsite`

The following code example shows how to use `DeleteBucketWebsite`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::S3::deleteBucketWebsite(const Aws::String &bucketName,
                                     const Aws::S3::S3ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client client(clientConfig);
    Aws::S3::Model::DeleteBucketWebsiteRequest request;
    request.SetBucket(bucketName);

    Aws::S3::Model::DeleteBucketWebsiteOutcome outcome =
            client.DeleteBucketWebsite(request);

    if (!outcome.IsSuccess()) {
        auto err = outcome.GetError();
        std::cerr << "Error: deleteBucketWebsite: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() << std::endl;
    } else {
        std::cout << "Website configuration was removed." << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DeleteBucketWebsite in *AWS SDK for C++ API Reference*.

`DeleteObject`

The following code example shows how to use `DeleteObject`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::S3::deleteObject(const Aws::String &objectKey,
                              const Aws::String &fromBucket,
                              const Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client client(clientConfig);
    Aws::S3::Model::DeleteObjectRequest request;

    request.WithKey(objectKey)
            .WithBucket(fromBucket);

    Aws::S3::Model::DeleteObjectOutcome outcome =
            client.DeleteObject(request);

    if (!outcome.IsSuccess()) {
        auto err = outcome.GetError();
        std::cerr << "Error: deleteObject: " <<
                  err.GetExceptionName() << ": " << err.GetMessage() << std::endl;
    } else {
        std::cout << "Successfully deleted the object." << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DeleteObject in *AWS SDK for C++ API Reference*.

`DeleteObjects`

The following code example shows how to use `DeleteObjects`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::S3::deleteObjects(const std::vector<Aws::String> &objectKeys,
                               const Aws::String &fromBucket,
                               const Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client client(clientConfig);
    Aws::S3::Model::DeleteObjectsRequest request;

    Aws::S3::Model::Delete deleteObject;
    for (const Aws::String &objectKey: objectKeys) {

 deleteObject.AddObjects(Aws::S3::Model::ObjectIdentifier().WithKey(objectKey));
    }

    request.SetDelete(deleteObject);
    request.SetBucket(fromBucket);

    Aws::S3::Model::DeleteObjectsOutcome outcome =
            client.DeleteObjects(request);

    if (!outcome.IsSuccess()) {
        auto err = outcome.GetError();
        std::cerr << "Error deleting objects. " <<
                  err.GetExceptionName() << ": " << err.GetMessage() << std::endl;
    } else {
        std::cout << "Successfully deleted the objects.";
        for (size_t i = 0; i < objectKeys.size(); ++i) {
            std::cout << objectKeys[i];
            if (i < objectKeys.size() - 1) {
                std::cout << ", ";
            }
        }
```

```
        std::cout << " from bucket " << fromBucket << "." << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DeleteObjects in *AWS SDK for C++ API Reference*.

`GetBucketAcl`

The following code example shows how to use `GetBucketAcl`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::S3::getBucketAcl(const Aws::String &bucketName,
                              const Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client s3Client(clientConfig);

    Aws::S3::Model::GetBucketAclRequest request;
    request.SetBucket(bucketName);

    Aws::S3::Model::GetBucketAclOutcome outcome =
            s3Client.GetBucketAcl(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: getBucketAcl: "
                  << err.GetExceptionName() << ": " << err.GetMessage() <<
 std::endl;
    } else {
        Aws::Vector<Aws::S3::Model::Grant> grants =
                outcome.GetResult().GetGrants();

        for (auto it = grants.begin(); it != grants.end(); it++) {
            Aws::S3::Model::Grant grant = *it;
```

```
            Aws::S3::Model::Grantee grantee = grant.GetGrantee();

            std::cout << "For bucket " << bucketName << ": "
                      << std::endl << std::endl;

            if (grantee.TypeHasBeenSet()) {
                std::cout << "Type:          "
                          << getGranteeTypeString(grantee.GetType()) << std::endl;
            }

            if (grantee.DisplayNameHasBeenSet()) {
                std::cout << "Display name:  "
                          << grantee.GetDisplayName() << std::endl;
            }

            if (grantee.EmailAddressHasBeenSet()) {
                std::cout << "Email address: "
                          << grantee.GetEmailAddress() << std::endl;
            }

            if (grantee.IDHasBeenSet()) {
                std::cout << "ID:            "
                          << grantee.GetID() << std::endl;
            }

            if (grantee.URIHasBeenSet()) {
                std::cout << "URI:           "
                          << grantee.GetURI() << std::endl;
            }

            std::cout << "Permission:    " <<
                      getPermissionString(grant.GetPermission()) <<
                      std::endl << std::endl;
        }
    }

    return outcome.IsSuccess();
}

//! Routine which converts a built-in type enumeration to a human-readable string.
/*!
 \param type: Type enumeration.
 \return String: Human-readable string.
*/
```

```
Aws::String getGranteeTypeString(const Aws::S3::Model::Type &type) {
    switch (type) {
        case Aws::S3::Model::Type::AmazonCustomerByEmail:
            return "Email address of an AWS account";
        case Aws::S3::Model::Type::CanonicalUser:
            return "Canonical user ID of an AWS account";
        case Aws::S3::Model::Type::Group:
            return "Predefined Amazon S3 group";
        case Aws::S3::Model::Type::NOT_SET:
            return "Not set";
        default:
            return "Type unknown";
    }
}

//! Routine which converts a built-in type enumeration to a human-readable string.
/*!
 \param permission: Permission enumeration.
 \return String: Human-readable string.
*/

Aws::String getPermissionString(const Aws::S3::Model::Permission &permission) {
    switch (permission) {
        case Aws::S3::Model::Permission::FULL_CONTROL:
            return "Can list objects in this bucket, create/overwrite/delete "
                   "objects in this bucket, and read/write this "
                   "bucket's permissions";
        case Aws::S3::Model::Permission::NOT_SET:
            return "Permission not set";
        case Aws::S3::Model::Permission::READ:
            return "Can list objects in this bucket";
        case Aws::S3::Model::Permission::READ_ACP:
            return "Can read this bucket's permissions";
        case Aws::S3::Model::Permission::WRITE:
            return "Can create, overwrite, and delete objects in this bucket";
        case Aws::S3::Model::Permission::WRITE_ACP:
            return "Can write this bucket's permissions";
        default:
            return "Permission unknown";
    }

    return "Permission unknown";
}
```

- For API details, see GetBucketAcl in *AWS SDK for C++ API Reference*.

`GetBucketPolicy`

The following code example shows how to use `GetBucketPolicy`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::S3::getBucketPolicy(const Aws::String &bucketName,
                                 const Aws::S3::S3ClientConfiguration &clientConfig)
 {
    Aws::S3::S3Client s3Client(clientConfig);

    Aws::S3::Model::GetBucketPolicyRequest request;
    request.SetBucket(bucketName);

    Aws::S3::Model::GetBucketPolicyOutcome outcome =
            s3Client.GetBucketPolicy(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: getBucketPolicy: "
                  << err.GetExceptionName() << ": " << err.GetMessage() <<
 std::endl;
    } else {
        Aws::StringStream policy_stream;
        Aws::String line;

        outcome.GetResult().GetPolicy() >> line;
        policy_stream << line;

        std::cout << "Retrieve the policy for bucket '" << bucketName << "':\n\n" <<
                  policy_stream.str() << std::endl;
```

```
    }

    return outcome.IsSuccess();
}
```

- For API details, see GetBucketPolicy in *AWS SDK for C++ API Reference*.

`GetBucketWebsite`

The following code example shows how to use `GetBucketWebsite`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::S3::getWebsiteConfig(const Aws::String &bucketName,
                                  const Aws::S3::S3ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client s3Client(clientConfig);

    Aws::S3::Model::GetBucketWebsiteRequest request;
    request.SetBucket(bucketName);

    Aws::S3::Model::GetBucketWebsiteOutcome outcome =
            s3Client.GetBucketWebsite(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();

        std::cerr << "Error: GetBucketWebsite: "
                  << err.GetMessage() << std::endl;
    } else {
        Aws::S3::Model::GetBucketWebsiteResult websiteResult = outcome.GetResult();

        std::cout << "Success: GetBucketWebsite: "
                  << std::endl << std::endl
                  << "For bucket '" << bucketName << "':"
```

```
                  << std::endl
                  << "Index page : "
                  << websiteResult.GetIndexDocument().GetSuffix()
                  << std::endl
                  << "Error page: "
                  << websiteResult.GetErrorDocument().GetKey()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see GetBucketWebsite in *AWS SDK for C++ API Reference*.

`GetObject`

The following code example shows how to use `GetObject`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::S3::getObject(const Aws::String &objectKey,
                           const Aws::String &fromBucket,
                           const Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client client(clientConfig);

    Aws::S3::Model::GetObjectRequest request;
    request.SetBucket(fromBucket);
    request.SetKey(objectKey);

    Aws::S3::Model::GetObjectOutcome outcome =
            client.GetObject(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: getObject: " <<
```

```
                  err.GetExceptionName() << ": " << err.GetMessage() << std::endl;
    } else {
        std::cout << "Successfully retrieved '" << objectKey << "' from '"
                  << fromBucket << "'." << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see GetObject in *AWS SDK for C++ API Reference*.

`GetObjectAcl`

The following code example shows how to use `GetObjectAcl`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::S3::getObjectAcl(const Aws::String &bucketName,
                              const Aws::String &objectKey,
                              const Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client s3Client(clientConfig);

    Aws::S3::Model::GetObjectAclRequest request;
    request.SetBucket(bucketName);
    request.SetKey(objectKey);

    Aws::S3::Model::GetObjectAclOutcome outcome =
            s3Client.GetObjectAcl(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &err = outcome.GetError();
        std::cerr << "Error: getObjectAcl: "
                  << err.GetExceptionName() << ": " << err.GetMessage() <<
 std::endl;
    } else {
```

```
        Aws::Vector<Aws::S3::Model::Grant> grants =
                outcome.GetResult().GetGrants();

        for (auto it = grants.begin(); it != grants.end(); it++) {
            std::cout << "For object " << objectKey << ": "
                      << std::endl << std::endl;

            Aws::S3::Model::Grant grant = *it;
            Aws::S3::Model::Grantee grantee = grant.GetGrantee();

            if (grantee.TypeHasBeenSet()) {
                std::cout << "Type:          "
                          << getGranteeTypeString(grantee.GetType()) << std::endl;
            }

            if (grantee.DisplayNameHasBeenSet()) {
                std::cout << "Display name:  "
                          << grantee.GetDisplayName() << std::endl;
            }

            if (grantee.EmailAddressHasBeenSet()) {
                std::cout << "Email address: "
                          << grantee.GetEmailAddress() << std::endl;
            }

            if (grantee.IDHasBeenSet()) {
                std::cout << "ID:            "
                          << grantee.GetID() << std::endl;
            }

            if (grantee.URIHasBeenSet()) {
                std::cout << "URI:           "
                          << grantee.GetURI() << std::endl;
            }

            std::cout << "Permission:    " <<
                      getPermissionString(grant.GetPermission()) <<
                      std::endl << std::endl;
        }
    }

    return outcome.IsSuccess();
}
```

```
//! Routine which converts a built-in type enumeration to a human-readable string.
/*!
 \param type: Type enumeration.
 \return String: Human-readable string
*/
Aws::String getGranteeTypeString(const Aws::S3::Model::Type &type) {
    switch (type) {
        case Aws::S3::Model::Type::AmazonCustomerByEmail:
            return "Email address of an AWS account";
        case Aws::S3::Model::Type::CanonicalUser:
            return "Canonical user ID of an AWS account";
        case Aws::S3::Model::Type::Group:
            return "Predefined Amazon S3 group";
        case Aws::S3::Model::Type::NOT_SET:
            return "Not set";
        default:
            return "Type unknown";
    }
}

//! Routine which converts a built-in type enumeration to a human-readable string.
/*!
 \param permission: Permission enumeration.
 \return String: Human-readable string
*/
Aws::String getPermissionString(const Aws::S3::Model::Permission &permission) {
    switch (permission) {
        case Aws::S3::Model::Permission::FULL_CONTROL:
            return "Can read this object's data and its metadata, "
                   "and read/write this object's permissions";
        case Aws::S3::Model::Permission::NOT_SET:
            return "Permission not set";
        case Aws::S3::Model::Permission::READ:
            return "Can read this object's data and its metadata";
        case Aws::S3::Model::Permission::READ_ACP:
            return "Can read this object's permissions";
            // case Aws::S3::Model::Permission::WRITE // Not applicable.
        case Aws::S3::Model::Permission::WRITE_ACP:
            return "Can write this object's permissions";
        default:
            return "Permission unknown";
    }
}
```

- For API details, see GetObjectAcl in *AWS SDK for C++ API Reference*.

`GetObjectAttributes`

The following code example shows how to use `GetObjectAttributes`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
// ! Routine which retrieves the hash value of an object stored in an S3 bucket.
/*!
   \param bucket: The name of the S3 bucket where the object is stored.
   \param key: The unique identifier (key) of the object within the S3 bucket.
   \param hashMethod: The hashing algorithm used to calculate the hash value of the
 object.
   \param[out] hashData: The retrieved hash.
   \param[out] partHashes: The part hashes if available.
   \param client: The S3 client instance used to retrieve the object.
   \return bool: Function succeeded.
*/
bool AwsDoc::S3::retrieveObjectHash(const Aws::String &bucket, const Aws::String
 &key,
                                    AwsDoc::S3::HASH_METHOD hashMethod,
                                    Aws::String &hashData,
                                    std::vector<Aws::String> *partHashes,
                                    const Aws::S3::S3Client &client) {
    Aws::S3::Model::GetObjectAttributesRequest request;
    request.SetBucket(bucket);
    request.SetKey(key);

    if (hashMethod == MD5) {
        Aws::Vector<Aws::S3::Model::ObjectAttributes> attributes;
        attributes.push_back(Aws::S3::Model::ObjectAttributes::ETag);
        request.SetObjectAttributes(attributes);
```

```
        Aws::S3::Model::GetObjectAttributesOutcome outcome =
 client.GetObjectAttributes(
                request);
        if (outcome.IsSuccess()) {
            const Aws::S3::Model::GetObjectAttributesResult &result =
 outcome.GetResult();
            hashData = result.GetETag();
        } else {
            std::cerr << "Error retrieving object etag attributes." <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    } else { // hashMethod != MD5
        Aws::Vector<Aws::S3::Model::ObjectAttributes> attributes;
        attributes.push_back(Aws::S3::Model::ObjectAttributes::Checksum);
        request.SetObjectAttributes(attributes);

        Aws::S3::Model::GetObjectAttributesOutcome outcome =
 client.GetObjectAttributes(
                request);
        if (outcome.IsSuccess()) {
            const Aws::S3::Model::GetObjectAttributesResult &result =
 outcome.GetResult();
            switch (hashMethod) {
                case AwsDoc::S3::DEFAULT: // NOLINT(*-branch-clone)
                    break;  // Default is not supported.
#pragma clang diagnostic push
#pragma ide diagnostic ignored "UnreachableCode"
                case AwsDoc::S3::MD5:
                    break;  // MD5 is not supported.
#pragma clang diagnostic pop
                case AwsDoc::S3::SHA1:
                    hashData = result.GetChecksum().GetChecksumSHA1();
                    break;
                case AwsDoc::S3::SHA256:
                    hashData = result.GetChecksum().GetChecksumSHA256();
                    break;
                case AwsDoc::S3::CRC32:
                    hashData = result.GetChecksum().GetChecksumCRC32();
                    break;
                case AwsDoc::S3::CRC32C:
                    hashData = result.GetChecksum().GetChecksumCRC32C();
                    break;
                default:
```

```
                    std::cerr << "Unknown hash method." << std::endl;
                    return false;
            }
        } else {
            std::cerr << "Error retrieving object checksum attributes." <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }

        if (nullptr != partHashes) {
            attributes.clear();
            attributes.push_back(Aws::S3::Model::ObjectAttributes::ObjectParts);
            request.SetObjectAttributes(attributes);
            outcome = client.GetObjectAttributes(request);
            if (outcome.IsSuccess()) {
                const Aws::S3::Model::GetObjectAttributesResult &result =
outcome.GetResult();
                const Aws::Vector<Aws::S3::Model::ObjectPart> parts =
result.GetObjectParts().GetParts();
                for (const Aws::S3::Model::ObjectPart &part: parts) {
                    switch (hashMethod) {
                        case AwsDoc::S3::DEFAULT: // Default is not supported.
NOLINT(*-branch-clone)
                            break;
                        case AwsDoc::S3::MD5: // MD5 is not supported.
                            break;
                        case AwsDoc::S3::SHA1:
                            partHashes->push_back(part.GetChecksumSHA1());
                            break;
                        case AwsDoc::S3::SHA256:
                            partHashes->push_back(part.GetChecksumSHA256());
                            break;
                        case AwsDoc::S3::CRC32:
                            partHashes->push_back(part.GetChecksumCRC32());
                            break;
                        case AwsDoc::S3::CRC32C:
                            partHashes->push_back(part.GetChecksumCRC32C());
                            break;
                        default:
                            std::cerr << "Unknown hash method." << std::endl;
                            return false;
                    }
                }
            } else {
```

```
                std::cerr << "Error retrieving object attributes for object parts."
 <<
                          outcome.GetError().GetMessage() << std::endl;
                return false;
            }
        }
    }

    return true;
}
```

- For API details, see GetObjectAttributes in *AWS SDK for C++ API Reference*.

`ListBuckets`

The following code example shows how to use `ListBuckets`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::S3::listBuckets(const Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client client(clientConfig);

    auto outcome = client.ListBuckets();

    bool result = true;
    if (!outcome.IsSuccess()) {
        std::cerr << "Failed with error: " << outcome.GetError() << std::endl;
        result = false;
    } else {
        std::cout << "Found " << outcome.GetResult().GetBuckets().size() << "
 buckets\n";
        for (auto &&b: outcome.GetResult().GetBuckets()) {
            std::cout << b.GetName() << std::endl;
        }
    }
```

```
    return result;
}
```

- For API details, see ListBuckets in *AWS SDK for C++ API Reference*.

`ListObjectsV2`

The following code example shows how to use `ListObjectsV2`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::S3::listObjects(const Aws::String &bucketName,
                             Aws::Vector<Aws::String> &keysResult,
                             const Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client s3Client(clientConfig);

    Aws::S3::Model::ListObjectsV2Request request;
    request.WithBucket(bucketName);

    Aws::String continuationToken; // Used for pagination.
    Aws::Vector<Aws::S3::Model::Object> allObjects;

    do {
        if (!continuationToken.empty()) {
            request.SetContinuationToken(continuationToken);
        }

        auto outcome = s3Client.ListObjectsV2(request);

        if (!outcome.IsSuccess()) {
            std::cerr << "Error: listObjects: " <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        } else {
```

```
            Aws::Vector<Aws::S3::Model::Object> objects =
                    outcome.GetResult().GetContents();

            allObjects.insert(allObjects.end(), objects.begin(), objects.end());
            continuationToken = outcome.GetResult().GetNextContinuationToken();
        }
    } while (!continuationToken.empty());

    std::cout << allObjects.size() << " object(s) found:" << std::endl;

    for (const auto &object: allObjects) {
        std::cout << "  " << object.GetKey() << std::endl;
        keysResult.push_back(object.GetKey());
    }

    return true;
}
```

- For API details, see ListObjectsV2 in *AWS SDK for C++ API Reference*.

`PutBucketAcl`

The following code example shows how to use `PutBucketAcl`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::S3::putBucketAcl(const Aws::String &bucketName, const Aws::String
 &ownerID,
                              const Aws::String &granteePermission,
                              const Aws::String &granteeType, const Aws::String
 &granteeID,
                              const Aws::String &granteeEmailAddress,
                              const Aws::String &granteeURI, const
 Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client s3Client(clientConfig);
```

```
    Aws::S3::Model::Owner owner;
    owner.SetID(ownerID);

    Aws::S3::Model::Grantee grantee;
    grantee.SetType(setGranteeType(granteeType));

    if (!granteeEmailAddress.empty()) {
        grantee.SetEmailAddress(granteeEmailAddress);
    }

    if (!granteeID.empty()) {
        grantee.SetID(granteeID);
    }

    if (!granteeURI.empty()) {
        grantee.SetURI(granteeURI);
    }

    Aws::S3::Model::Grant grant;
    grant.SetGrantee(grantee);
    grant.SetPermission(setGranteePermission(granteePermission));

    Aws::Vector<Aws::S3::Model::Grant> grants;
    grants.push_back(grant);

    Aws::S3::Model::AccessControlPolicy acp;
    acp.SetOwner(owner);
    acp.SetGrants(grants);

    Aws::S3::Model::PutBucketAclRequest request;
    request.SetAccessControlPolicy(acp);
    request.SetBucket(bucketName);

    Aws::S3::Model::PutBucketAclOutcome outcome =
            s3Client.PutBucketAcl(request);

    if (!outcome.IsSuccess()) {
        const Aws::S3::S3Error &error = outcome.GetError();

        std::cerr << "Error: putBucketAcl: " << error.GetExceptionName()
                  << " - " << error.GetMessage() << std::endl;
    } else {
        std::cout << "Successfully added an ACL to the bucket '" << bucketName
```

```
                  << "'." << std::endl;
    }

    return outcome.IsSuccess();
}

//! Routine which converts a human-readable string to a built-in type enumeration.
/*!
 \param access: Human readable string.
 \return Permission: A Permission enum.
*/

Aws::S3::Model::Permission setGranteePermission(const Aws::String &access) {
    if (access == "FULL_CONTROL")
        return Aws::S3::Model::Permission::FULL_CONTROL;
    if (access == "WRITE")
        return Aws::S3::Model::Permission::WRITE;
    if (access == "READ")
        return Aws::S3::Model::Permission::READ;
    if (access == "WRITE_ACP")
        return Aws::S3::Model::Permission::WRITE_ACP;
    if (access == "READ_ACP")
        return Aws::S3::Model::Permission::READ_ACP;
    return Aws::S3::Model::Permission::NOT_SET;
}

//! Routine which converts a human-readable string to a built-in type enumeration.
/*!
 \param type: Human readable string.
 \return Type: Type enumeration
*/

Aws::S3::Model::Type setGranteeType(const Aws::String &type) {
    if (type == "Amazon customer by email")
        return Aws::S3::Model::Type::AmazonCustomerByEmail;
    if (type == "Canonical user")
        return Aws::S3::Model::Type::CanonicalUser;
    if (type == "Group")
        return Aws::S3::Model::Type::Group;
    return Aws::S3::Model::Type::NOT_SET;
}
```

- For API details, see PutBucketAcl in *AWS SDK for C++ API Reference*.

`PutBucketPolicy`

The following code example shows how to use `PutBucketPolicy`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::S3::putBucketPolicy(const Aws::String &bucketName,
                                 const Aws::String &policyBody,
                                 const Aws::S3::S3ClientConfiguration &clientConfig)
 {
    Aws::S3::S3Client s3Client(clientConfig);

    std::shared_ptr<Aws::StringStream> request_body =
            Aws::MakeShared<Aws::StringStream>("");
    *request_body << policyBody;

    Aws::S3::Model::PutBucketPolicyRequest request;
    request.SetBucket(bucketName);
    request.SetBody(request_body);

    Aws::S3::Model::PutBucketPolicyOutcome outcome =
            s3Client.PutBucketPolicy(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: putBucketPolicy: "
                  << outcome.GetError().GetMessage() << std::endl;
    } else {
        std::cout << "Set the following policy body for the bucket '" <<
                  bucketName << "':" << std::endl << std::endl;
        std::cout << policyBody << std::endl;
    }

    return outcome.IsSuccess();
}


//! Build a policy JSON string.
```

```
/*!
  \param userArn: Aws user Amazon Resource Name (ARN).
      For more information, see https://docs.aws.amazon.com/IAM/latest/UserGuide/
reference_identifiers.html#identifiers-arns.
  \param bucketName: Name of a bucket.
  \return String: Policy as JSON string.
*/

Aws::String getPolicyString(const Aws::String &userArn,
                            const Aws::String &bucketName) {
    return
            "{\n"
            "   \"Version\":\"2012-10-17\",\n"
            "   \"Statement\":[\n"
            "       {\n"
            "           \"Sid\": \"1\",\n"
            "           \"Effect\": \"Allow\",\n"
            "           \"Principal\": {\n"
            "               \"AWS\": \""
            + userArn +
            "\"\n""           },\n"
            "           \"Action\": [ \"s3:getObject\" ],\n"
            "           \"Resource\": [ \"arn:aws:s3:::"
            + bucketName +
            "/*\" ]\n"
            "       }\n"
            "   ]\n"
            "}";
}
```

- For API details, see PutBucketPolicy in *AWS SDK for C++ API Reference*.

`PutBucketWebsite`

The following code example shows how to use `PutBucketWebsite`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::S3::putWebsiteConfig(const Aws::String &bucketName,
                                  const Aws::String &indexPage, const Aws::String
 &errorPage,
                                  const Aws::S3::S3ClientConfiguration
 &clientConfig) {
    Aws::S3::S3Client client(clientConfig);

    Aws::S3::Model::IndexDocument indexDocument;
    indexDocument.SetSuffix(indexPage);

    Aws::S3::Model::ErrorDocument errorDocument;
    errorDocument.SetKey(errorPage);

    Aws::S3::Model::WebsiteConfiguration websiteConfiguration;
    websiteConfiguration.SetIndexDocument(indexDocument);
    websiteConfiguration.SetErrorDocument(errorDocument);

    Aws::S3::Model::PutBucketWebsiteRequest request;
    request.SetBucket(bucketName);
    request.SetWebsiteConfiguration(websiteConfiguration);

    Aws::S3::Model::PutBucketWebsiteOutcome outcome =
            client.PutBucketWebsite(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: PutBucketWebsite: "
                  << outcome.GetError().GetMessage() << std::endl;
    } else {
        std::cout << "Success: Set website configuration for bucket '"
                  << bucketName << "'." << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see PutBucketWebsite in *AWS SDK for C++ API Reference*.

`PutObject`

The following code example shows how to use `PutObject`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::S3::putObject(const Aws::String &bucketName,
                           const Aws::String &fileName,
                           const Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client s3Client(clientConfig);

    Aws::S3::Model::PutObjectRequest request;
    request.SetBucket(bucketName);
    //We are using the name of the file as the key for the object in the bucket.
    //However, this is just a string and can be set according to your retrieval
 needs.
    request.SetKey(fileName);

    std::shared_ptr<Aws::IOStream> inputData =
            Aws::MakeShared<Aws::FStream>("SampleAllocationTag",
                                          fileName.c_str(),
                                          std::ios_base::in |
 std::ios_base::binary);

    if (!*inputData) {
        std::cerr << "Error unable to read file " << fileName << std::endl;
        return false;
    }

    request.SetBody(inputData);

    Aws::S3::Model::PutObjectOutcome outcome =
```

```
            s3Client.PutObject(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error: putObject: " <<
                  outcome.GetError().GetMessage() << std::endl;
    } else {
        std::cout << "Added object '" << fileName << "' to bucket '"
                  << bucketName << "'.";
    }

    return outcome.IsSuccess();
}
```

- For API details, see PutObject in *AWS SDK for C++ API Reference*.

`PutObjectAcl`

The following code example shows how to use `PutObjectAcl`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::S3::putObjectAcl(const Aws::String &bucketName, const Aws::String
 &objectKey, const Aws::String &ownerID,
                              const Aws::String &granteePermission, const
 Aws::String &granteeType,
                              const Aws::String &granteeID, const Aws::String
 &granteeEmailAddress,
                              const Aws::String &granteeURI, const
 Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client s3Client(clientConfig);

    Aws::S3::Model::Owner owner;
    owner.SetID(ownerID);

    Aws::S3::Model::Grantee grantee;
```

```
    grantee.SetType(setGranteeType(granteeType));

    if (!granteeEmailAddress.empty()) {
        grantee.SetEmailAddress(granteeEmailAddress);
    }

    if (!granteeID.empty()) {
        grantee.SetID(granteeID);
    }

    if (!granteeURI.empty()) {
        grantee.SetURI(granteeURI);
    }

    Aws::S3::Model::Grant grant;
    grant.SetGrantee(grantee);
    grant.SetPermission(setGranteePermission(granteePermission));

    Aws::Vector<Aws::S3::Model::Grant> grants;
    grants.push_back(grant);

    Aws::S3::Model::AccessControlPolicy acp;
    acp.SetOwner(owner);
    acp.SetGrants(grants);

    Aws::S3::Model::PutObjectAclRequest request;
    request.SetAccessControlPolicy(acp);
    request.SetBucket(bucketName);
    request.SetKey(objectKey);

    Aws::S3::Model::PutObjectAclOutcome outcome =
            s3Client.PutObjectAcl(request);

    if (!outcome.IsSuccess()) {
        auto error = outcome.GetError();
        std::cerr << "Error: putObjectAcl: " << error.GetExceptionName()
                  << " - " << error.GetMessage() << std::endl;
    } else {
        std::cout << "Successfully added an ACL to the object '" << objectKey
                  << "' in the bucket '" << bucketName << "'." << std::endl;
    }

    return outcome.IsSuccess();
}
```

```
//! Routine which converts a human-readable string to a built-in type enumeration.
/*!
 \param access: Human readable string.
 \return Permission: Permission enumeration.
*/
Aws::S3::Model::Permission setGranteePermission(const Aws::String &access) {
    if (access == "FULL_CONTROL")
        return Aws::S3::Model::Permission::FULL_CONTROL;
    if (access == "WRITE")
        return Aws::S3::Model::Permission::WRITE;
    if (access == "READ")
        return Aws::S3::Model::Permission::READ;
    if (access == "WRITE_ACP")
        return Aws::S3::Model::Permission::WRITE_ACP;
    if (access == "READ_ACP")
        return Aws::S3::Model::Permission::READ_ACP;
    return Aws::S3::Model::Permission::NOT_SET;
}

//! Routine which converts a human-readable string to a built-in type enumeration.
/*!
 \param type: Human readable string.
 \return Type: Type enumeration.
*/
Aws::S3::Model::Type setGranteeType(const Aws::String &type) {
    if (type == "Amazon customer by email")
        return Aws::S3::Model::Type::AmazonCustomerByEmail;
    if (type == "Canonical user")
        return Aws::S3::Model::Type::CanonicalUser;
    if (type == "Group")
        return Aws::S3::Model::Type::Group;
    return Aws::S3::Model::Type::NOT_SET;
}
```

- For API details, see PutObjectAcl in *AWS SDK for C++ API Reference*.

`UploadPart`

The following code example shows how to use `UploadPart`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Upload a part to an S3 bucket.
/*!
    \param bucket: The name of the S3 bucket where the object will be uploaded.
    \param key: The unique identifier (key) for the object within the S3 bucket.
    \param uploadID: An upload ID string.
    \param partNumber:
    \param checksumAlgorithm: Checksum algorithm, ignored when NOT_SET.
    \param calculatedHash: A data integrity hash to set, depending on the checksum
 algorithm,
                           ignored when it is an empty string.
    \param body: An shared_ptr IOStream of the data to be uploaded.
    \param client: The S3 client instance used to perform the upload operation.
    \return UploadPartOutcome: The outcome.
*/

Aws::S3::Model::UploadPartOutcome AwsDoc::S3::uploadPart(const Aws::String &bucket,
                                                         const Aws::String &key,
                                                         const Aws::String
 &uploadID,
                                                         int partNumber,

 Aws::S3::Model::ChecksumAlgorithm checksumAlgorithm,
                                                         const Aws::String
 &calculatedHash,
                                                         const
 std::shared_ptr<Aws::IOStream> &body,
                                                         const Aws::S3::S3Client
 &client) {
    Aws::S3::Model::UploadPartRequest request;
    request.SetBucket(bucket);
    request.SetKey(key);
    request.SetUploadId(uploadID);
    request.SetPartNumber(partNumber);
    if (checksumAlgorithm != Aws::S3::Model::ChecksumAlgorithm::NOT_SET) {
```

```
        request.SetChecksumAlgorithm(checksumAlgorithm);
    }
    request.SetBody(body);

    if (!calculatedHash.empty()) {
        switch (checksumAlgorithm) {
            case Aws::S3::Model::ChecksumAlgorithm::NOT_SET:
                request.SetContentMD5(calculatedHash);
                break;
            case Aws::S3::Model::ChecksumAlgorithm::CRC32:
                request.SetChecksumCRC32(calculatedHash);
                break;
            case Aws::S3::Model::ChecksumAlgorithm::CRC32C:
                request.SetChecksumCRC32C(calculatedHash);
                break;
            case Aws::S3::Model::ChecksumAlgorithm::SHA1:
                request.SetChecksumSHA1(calculatedHash);
                break;
            case Aws::S3::Model::ChecksumAlgorithm::SHA256:
                request.SetChecksumSHA256(calculatedHash);
                break;
        }
    }

    return client.UploadPart(request);
}
```

- For API details, see UploadPart in *AWS SDK for C++ API Reference*.

Scenarios

Create a presigned URL

The following code example shows how to create a presigned URL for Amazon S3 and upload an object.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Generate a pre-signed URL to download an object.

```
//! Routine which demonstrates creating a pre-signed URL to download an object from
 an
//! Amazon Simple Storage Service (Amazon S3) bucket.
/*!
  \param bucketName: Name of the bucket.
  \param key: Name of an object key.
  \param expirationSeconds: Expiration in seconds for pre-signed URL.
  \param clientConfig: Aws client configuration.
  \return Aws::String: A pre-signed URL.
*/
Aws::String AwsDoc::S3::generatePreSignedGetObjectUrl(const Aws::String &bucketName,
                                                      const Aws::String &key,
                                                      uint64_t expirationSeconds,
                                                      const
 Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client client(clientConfig);
    return client.GeneratePresignedUrl(bucketName, key,
 Aws::Http::HttpMethod::HTTP_GET,
                                       expirationSeconds);
}
```

Download using libcurl.

```
static size_t myCurlWriteBack(char *buffer, size_t size, size_t nitems, void
 *userdata) {
    Aws::StringStream *str = (Aws::StringStream *) userdata;

    if (nitems > 0) {
        str->write(buffer, size * nitems);
    }
    return size * nitems;
```

```
}

//! Utility routine to test getObject with a pre-signed URL.
/*!
  \param presignedURL: A pre-signed URL to get an object from a bucket.
  \param resultString: A string to hold the result.
  \return bool: Function succeeded.
*/
bool AwsDoc::S3::getObjectWithPresignedObjectUrl(const Aws::String &presignedURL,
                                                 Aws::String &resultString) {
    CURL *curl = curl_easy_init();
    CURLcode result;

    std::stringstream outWriteString;

    result = curl_easy_setopt(curl, CURLOPT_WRITEDATA, &outWriteString);

    if (result != CURLE_OK) {
        std::cerr << "Failed to set CURLOPT_WRITEDATA " << std::endl;
        return false;
    }

    result = curl_easy_setopt(curl, CURLOPT_WRITEFUNCTION, myCurlWriteBack);

    if (result != CURLE_OK) {
        std::cerr << "Failed to set CURLOPT_WRITEFUNCTION" << std::endl;
        return false;
    }

    result = curl_easy_setopt(curl, CURLOPT_URL, presignedURL.c_str());

    if (result != CURLE_OK) {
        std::cerr << "Failed to set CURLOPT_URL" << std::endl;
        return false;
    }

    result = curl_easy_perform(curl);

    if (result != CURLE_OK) {
        std::cerr << "Failed to perform CURL request" << std::endl;
        return false;
    }

    resultString = outWriteString.str();
```

```
    if (resultString.find("<?xml") == 0) {
        std::cerr << "Failed to get object, response:\n" << resultString <<
 std::endl;
        return false;
    }

    return true;
}
```

Generate a pre-signed URL to upload an object.

```
//! Routine which demonstrates creating a pre-signed URL to upload an object to an
//! Amazon Simple Storage Service (Amazon S3) bucket.
/*!
  \param bucketName: Name of the bucket.
  \param key: Name of an object key.
  \param clientConfig: Aws client configuration.
  \return Aws::String: A pre-signed URL.
*/
Aws::String AwsDoc::S3::generatePreSignedPutObjectUrl(const Aws::String &bucketName,
                                                      const Aws::String &key,
                                                      uint64_t expirationSeconds,
                                                      const
 Aws::S3::S3ClientConfiguration &clientConfig) {
    Aws::S3::S3Client client(clientConfig);
    return client.GeneratePresignedUrl(bucketName, key,
 Aws::Http::HttpMethod::HTTP_PUT,
                                       expirationSeconds);
}
```

Upload using libcurl.

```
static size_t myCurlReadBack(char *buffer, size_t size, size_t nitems, void
 *userdata) {
    Aws::StringStream *str = (Aws::StringStream *) userdata;

    str->read(buffer, size * nitems);

    return str->gcount();
}
```

```
static size_t myCurlWriteBack(char *buffer, size_t size, size_t nitems, void
 *userdata) {
    Aws::StringStream *str = (Aws::StringStream *) userdata;

    if (nitems > 0) {
        str->write(buffer, size * nitems);
    }
    return size * nitems;
}

//! Utility routine to test putObject with a pre-signed URL.
/*!
  \param presignedURL: A pre-signed URL to put an object in a bucket.
  \param data: Body of the putObject request.
  \return bool: Function succeeded.
*/
bool AwsDoc::S3::PutStringWithPresignedObjectURL(const Aws::String &presignedURL,
                                                 const Aws::String &data) {
    CURL *curl = curl_easy_init();
    CURLcode result;

    Aws::StringStream readStringStream;
    readStringStream << data;
    result = curl_easy_setopt(curl, CURLOPT_READFUNCTION, myCurlReadBack);

    if (result != CURLE_OK) {
        std::cerr << "Failed to set CURLOPT_READFUNCTION" << std::endl;
        return false;
    }

    result = curl_easy_setopt(curl, CURLOPT_READDATA, &readStringStream);
    if (result != CURLE_OK) {
        std::cerr << "Failed to set CURLOPT_READDATA" << std::endl;
        return false;
    }

    result = curl_easy_setopt(curl, CURLOPT_INFILESIZE_LARGE,
                              (curl_off_t) data.size());

    if (result != CURLE_OK) {
        std::cerr << "Failed to set CURLOPT_INFILESIZE_LARGE" << std::endl;
        return false;
    }
```

```
    result = curl_easy_setopt(curl, CURLOPT_WRITEFUNCTION, myCurlWriteBack);

    if (result != CURLE_OK) {
        std::cerr << "Failed to set CURLOPT_WRITEFUNCTION" << std::endl;
        return false;
    }

    std::stringstream outWriteString;

    result = curl_easy_setopt(curl, CURLOPT_WRITEDATA, &outWriteString);

    if (result != CURLE_OK) {
        std::cerr << "Failed to set CURLOPT_WRITEDATA " << std::endl;
        return false;
    }

    result = curl_easy_setopt(curl, CURLOPT_URL, presignedURL.c_str());

    if (result != CURLE_OK) {
        std::cerr << "Failed to set CURLOPT_URL" << std::endl;
        return false;
    }

    result = curl_easy_setopt(curl, CURLOPT_UPLOAD, 1L);

    if (result != CURLE_OK) {
        std::cerr << "Failed to set CURLOPT_PUT" << std::endl;
        return false;
    }

    result = curl_easy_perform(curl);

    if (result != CURLE_OK) {
        std::cerr << "Failed to perform CURL request" << std::endl;
        return false;
    }

    std::string outString = outWriteString.str();
    if (outString.empty()) {
        std::cout << "Successfully put object." << std::endl;
        return true;
    } else {
        std::cout << "A server error was encountered, output:\n" << outString
```

```
                  << std::endl;
        return false;
    }
}
```

Create a serverless application to manage photos

The following code example shows how to create a serverless application that lets users manage photos using labels.

SDK for C++

Shows how to develop a photo asset management application that detects labels in images using Amazon Rekognition and stores them for later retrieval.

For complete source code and instructions on how to set up and run, see the full example on GitHub.

For a deep dive into the origin of this example see the post on AWS Community.

Services used in this example

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Work with Amazon S3 object integrity

The following code example shows how to work with S3 object integrity features.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Run an interactive scenario demonstrating Amazon S3 object integrity features.

```
//! Routine which runs the S3 object integrity workflow.
/*!
   \param clientConfig: Aws client configuration.
   \return bool: Function succeeded.
*/
bool AwsDoc::S3::s3ObjectIntegrityWorkflow(
        const Aws::S3::S3ClientConfiguration &clientConfiguration) {

    /*
     * Create a large file to be used for multipart uploads.
     */
    if (!createLargeFileIfNotExists()) {
        std::cerr << "Workflow exiting because large file creation failed." <<
 std::endl;
        return false;
    }

    Aws::String bucketName = TEST_BUCKET_PREFIX;
    bucketName += Aws::Utils::UUID::RandomUUID();
    bucketName = Aws::Utils::StringUtils::ToLower(bucketName.c_str());

    bucketName.resize(std::min(bucketName.size(), MAX_BUCKET_NAME_LENGTH));

    introductoryExplanations(bucketName);

    if (!AwsDoc::S3::createBucket(bucketName, clientConfiguration)) {
        std::cerr << "Workflow exiting because bucket creation failed." <<
 std::endl;
        return false;
    }

    Aws::S3::S3ClientConfiguration s3ClientConfiguration(clientConfiguration);
```

```
   std::shared_ptr<Aws::S3::S3Client> client =
Aws::MakeShared<Aws::S3::S3Client>("S3Client", s3ClientConfiguration);

   printAsterisksLine();
   std::cout << "Choose from one of the following checksum algorithms."
             << std::endl;

   for (HASH_METHOD hashMethod = DEFAULT; hashMethod <= SHA256; ++hashMethod) {
       std::cout << "  " << hashMethod << " - " << stringForHashMethod(hashMethod)
                 << std::endl;
   }

   HASH_METHOD chosenHashMethod = askQuestionForIntRange("Enter an index: ",
DEFAULT,
                                                         SHA256);


   gUseCalculatedChecksum = !askYesNoQuestion(
           "Let the SDK calculate the checksum for you? (y/n) ");

   printAsterisksLine();

   std::cout << "The workflow will now upload a file using PutObject."
             << std::endl;
   std::cout << "Object integrity will be verified using the "
             << stringForHashMethod(chosenHashMethod) << " algorithm."
             << std::endl;
   if (gUseCalculatedChecksum) {
       std::cout
               << "A checksum computed by this workflow will be used for object
integrity verification,"
               << std::endl;
       std::cout << "except for the TransferManager upload." << std::endl;
   } else {
       std::cout
               << "A checksum computed by the SDK will be used for object integrity
verification."
               << std::endl;
   }

   pressEnterToContinue();
   printAsterisksLine();

   std::shared_ptr<Aws::IOStream> inputData =
```

```
        Aws::MakeShared<Aws::FStream>("SampleAllocationTag",
                                      TEST_FILE,
                                      std::ios_base::in |
                                      std::ios_base::binary);

    if (!*inputData) {
        std::cerr << "Error unable to read file " << TEST_FILE << std::endl;
        cleanUp(bucketName, clientConfiguration);
        return false;
    }

    Hasher hasher;
    HASH_METHOD putObjectHashMethod = chosenHashMethod;
    if (putObjectHashMethod == DEFAULT) {
        putObjectHashMethod = MD5; // MD5 is the default hash method for PutObject.

        std::cout << "The default checksum algorithm for PutObject is "
                  << stringForHashMethod(putObjectHashMethod)
                  << std::endl;
    }

    // Demonstrate in code how the hash is computed.
    if (!hasher.calculateObjectHash(*inputData, putObjectHashMethod)) {
        std::cerr << "Error calculating hash for file " << TEST_FILE << std::endl;
        cleanUp(bucketName, clientConfiguration);
        return false;
    }
    Aws::String key = stringForHashMethod(putObjectHashMethod);
    key += "_";
    key += TEST_FILE_KEY;
    Aws::String localHash = hasher.getBase64HashString();

    // Upload the object with PutObject
    if (!putObjectWithHash(bucketName, key, localHash, putObjectHashMethod,
                           inputData, chosenHashMethod == DEFAULT,
                           *client)) {
        std::cerr << "Error putting file " << TEST_FILE << " to bucket "
                  << bucketName << " with key " << key << std::endl;
        cleanUp(bucketName, clientConfiguration);
        return false;
    }

    Aws::String retrievedHash;
    if (!retrieveObjectHash(bucketName, key,
```

```
                            putObjectHashMethod, retrievedHash,
                            nullptr, *client)) {
        std::cerr << "Error getting file " << TEST_FILE << " from bucket "
                  << bucketName << " with key " << key << std::endl;
        cleanUp(bucketName, clientConfiguration);
        return false;
    }

    explainPutObjectResults();
    verifyHashingResults(retrievedHash, hasher,
                         "PutObject upload", putObjectHashMethod);


    printAsterisksLine();
    pressEnterToContinue();

    key = "tr_";
    key += stringForHashMethod(chosenHashMethod) + "_" + MULTI_PART_TEST_FILE;

    introductoryTransferManagerUploadExplanations(key);

    HASH_METHOD transferManagerHashMethod = chosenHashMethod;
    if (transferManagerHashMethod == DEFAULT) {
        transferManagerHashMethod = CRC32;  // The default hash method for the
TransferManager is CRC32.

        std::cout << "The default checksum algorithm for TransferManager is "
                  << stringForHashMethod(transferManagerHashMethod)
                  << std::endl;
    }

    // Upload the large file using the transfer manager.
    if (!doTransferManagerUpload(bucketName, key, transferManagerHashMethod,
chosenHashMethod == DEFAULT,
                                 client)) {
        std::cerr << "Exiting because of an error in doTransferManagerUpload." <<
std::endl;
        cleanUp(bucketName, clientConfiguration);
        return false;
    }

    std::vector<Aws::String> retrievedTransferManagerPartHashes;
    Aws::String retrievedTransferManagerFinalHash;
```

```
   // Retrieve all the hashes for the TransferManager upload.
   if (!retrieveObjectHash(bucketName, key,
                           transferManagerHashMethod,
                           retrievedTransferManagerFinalHash,
                           &retrievedTransferManagerPartHashes, *client)) {
       std::cerr << "Exiting because of an error in retrieveObjectHash for
TransferManager." << std::endl;
       cleanUp(bucketName, clientConfiguration);
       return false;
   }

   AwsDoc::S3::Hasher locallyCalculatedFinalHash;
   std::vector<Aws::String> locallyCalculatedPartHashes;

   // Calculate the hashes locally to demonstrate how TransferManager hashes are
computed.
   if (!calculatePartHashesForFile(transferManagerHashMethod, MULTI_PART_TEST_FILE,
                                   UPLOAD_BUFFER_SIZE,
                                   locallyCalculatedFinalHash,
                                   locallyCalculatedPartHashes)) {
       std::cerr << "Exiting because of an error in calculatePartHashesForFile." <<
std::endl;
       cleanUp(bucketName, clientConfiguration);
       return false;
   }

   verifyHashingResults(retrievedTransferManagerFinalHash,
                        locallyCalculatedFinalHash, "TransferManager upload",
                        transferManagerHashMethod,
                        retrievedTransferManagerPartHashes,
                        locallyCalculatedPartHashes);

   printAsterisksLine();

   key = "mp_";
   key += stringForHashMethod(chosenHashMethod) + "_" + MULTI_PART_TEST_FILE;

   multiPartUploadExplanations(key, chosenHashMethod);

   pressEnterToContinue();

   std::shared_ptr<Aws::IOStream> largeFileInputData =
           Aws::MakeShared<Aws::FStream>("SampleAllocationTag",
                                         MULTI_PART_TEST_FILE,
```

```
                                        std::ios_base::in |
                                        std::ios_base::binary);

    if (!largeFileInputData->good()) {
        std::cerr << "Error unable to read file " << TEST_FILE << std::endl;
        cleanUp(bucketName, clientConfiguration);
        return false;
    }

    HASH_METHOD multipartUploadHashMethod = chosenHashMethod;
    if (multipartUploadHashMethod == DEFAULT) {
        multipartUploadHashMethod = MD5;  // The default hash method for multipart
uploads is MD5.

        std::cout << "The default checksum algorithm for multipart upload is "
                  << stringForHashMethod(putObjectHashMethod)
                  << std::endl;
    }

    AwsDoc::S3::Hasher hashData;
    std::vector<Aws::String> partHashes;

    if (!doMultipartUpload(bucketName, key,
                           multipartUploadHashMethod,
                           largeFileInputData, chosenHashMethod == DEFAULT,
                           hashData,
                           partHashes,
                           *client)) {
        std::cerr << "Exiting because of an error in doMultipartUpload." <<
std::endl;
        cleanUp(bucketName, clientConfiguration);
        return false;
    }

    std::cout << "Finished multipart upload of with hash method " <<
              stringForHashMethod(multipartUploadHashMethod) << std::endl;

    std::cout << "Now we will retrieve the checksums from the server." << std::endl;

    retrievedHash.clear();
    std::vector<Aws::String> retrievedPartHashes;
    if (!retrieveObjectHash(bucketName, key,
                            multipartUploadHashMethod,
                            retrievedHash, &retrievedPartHashes, *client)) {
```

```
        std::cerr << "Exiting because of an error in retrieveObjectHash for
 multipart." << std::endl;
        cleanUp(bucketName, clientConfiguration);
        return false;
    }

    verifyHashingResults(retrievedHash, hashData, "MultiPart upload",
                         multipartUploadHashMethod,
                         retrievedPartHashes, partHashes);

    printAsterisksLine();

    if (askYesNoQuestion("Would you like to delete the resources created in this
 workflow? (y/n)")) {
        return cleanUp(bucketName, clientConfiguration);
    } else {
        std::cout << "The bucket " << bucketName << " was not deleted." <<
 std::endl;
        return true;
    }
}

//! Routine which uploads an object to an S3 bucket with different object integrity
 hashing methods.
/*!
   \param bucket: The name of the S3 bucket where the object will be uploaded.
   \param key: The unique identifier (key) for the object within the S3 bucket.
   \param hashData: The hash value that will be associated with the uploaded object.
   \param hashMethod: The hashing algorithm to use when calculating the hash value.
   \param body: The data content of the object being uploaded.
   \param useDefaultHashMethod: A flag indicating whether to use the default hash
 method or the one specified in the hashMethod parameter.
   \param client: The S3 client instance used to perform the upload operation.
   \return bool: Function succeeded.
*/
bool AwsDoc::S3::putObjectWithHash(const Aws::String &bucket, const Aws::String
 &key,
                                   const Aws::String &hashData,
                                   AwsDoc::S3::HASH_METHOD hashMethod,
                                   const std::shared_ptr<Aws::IOStream> &body,
                                   bool useDefaultHashMethod,
                                   const Aws::S3::S3Client &client) {
    Aws::S3::Model::PutObjectRequest request;
    request.SetBucket(bucket);
```

```
    request.SetKey(key);
    if (!useDefaultHashMethod) {
        if (hashMethod != MD5) {

 request.SetChecksumAlgorithm(getChecksumAlgorithmForHashMethod(hashMethod));
        }
    }

    if (gUseCalculatedChecksum) {
        switch (hashMethod) {
            case AwsDoc::S3::MD5:
                request.SetContentMD5(hashData);
                break;
            case AwsDoc::S3::SHA1:
                request.SetChecksumSHA1(hashData);
                break;
            case AwsDoc::S3::SHA256:
                request.SetChecksumSHA256(hashData);
                break;
            case AwsDoc::S3::CRC32:
                request.SetChecksumCRC32(hashData);
                break;
            case AwsDoc::S3::CRC32C:
                request.SetChecksumCRC32C(hashData);
                break;
            default:
                std::cerr << "Unknown hash method." << std::endl;
                return false;
        }
    }
    request.SetBody(body);
    Aws::S3::Model::PutObjectOutcome outcome = client.PutObject(request);
    body->seekg(0, body->beg);
    if (outcome.IsSuccess()) {
        std::cout << "Object successfully uploaded." << std::endl;
    } else {
        std::cerr << "Error uploading object." <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    return outcome.IsSuccess();
}


// ! Routine which retrieves the hash value of an object stored in an S3 bucket.
```

```
/*!
   \param bucket: The name of the S3 bucket where the object is stored.
   \param key: The unique identifier (key) of the object within the S3 bucket.
   \param hashMethod: The hashing algorithm used to calculate the hash value of the
 object.
   \param[out] hashData: The retrieved hash.
   \param[out] partHashes: The part hashes if available.
   \param client: The S3 client instance used to retrieve the object.
   \return bool: Function succeeded.
*/
bool AwsDoc::S3::retrieveObjectHash(const Aws::String &bucket, const Aws::String
 &key,
                                    AwsDoc::S3::HASH_METHOD hashMethod,
                                    Aws::String &hashData,
                                    std::vector<Aws::String> *partHashes,
                                    const Aws::S3::S3Client &client) {
    Aws::S3::Model::GetObjectAttributesRequest request;
    request.SetBucket(bucket);
    request.SetKey(key);

    if (hashMethod == MD5) {
        Aws::Vector<Aws::S3::Model::ObjectAttributes> attributes;
        attributes.push_back(Aws::S3::Model::ObjectAttributes::ETag);
        request.SetObjectAttributes(attributes);

        Aws::S3::Model::GetObjectAttributesOutcome outcome =
 client.GetObjectAttributes(
                request);
        if (outcome.IsSuccess()) {
            const Aws::S3::Model::GetObjectAttributesResult &result =
 outcome.GetResult();
            hashData = result.GetETag();
        } else {
            std::cerr << "Error retrieving object etag attributes." <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }
    } else { // hashMethod != MD5
        Aws::Vector<Aws::S3::Model::ObjectAttributes> attributes;
        attributes.push_back(Aws::S3::Model::ObjectAttributes::Checksum);
        request.SetObjectAttributes(attributes);

        Aws::S3::Model::GetObjectAttributesOutcome outcome =
 client.GetObjectAttributes(
```

```
                request);
        if (outcome.IsSuccess()) {
            const Aws::S3::Model::GetObjectAttributesResult &result =
 outcome.GetResult();
            switch (hashMethod) {
                case AwsDoc::S3::DEFAULT: // NOLINT(*-branch-clone)
                    break;  // Default is not supported.
#pragma clang diagnostic push
#pragma ide diagnostic ignored "UnreachableCode"
                case AwsDoc::S3::MD5:
                    break;  // MD5 is not supported.
#pragma clang diagnostic pop
                case AwsDoc::S3::SHA1:
                    hashData = result.GetChecksum().GetChecksumSHA1();
                    break;
                case AwsDoc::S3::SHA256:
                    hashData = result.GetChecksum().GetChecksumSHA256();
                    break;
                case AwsDoc::S3::CRC32:
                    hashData = result.GetChecksum().GetChecksumCRC32();
                    break;
                case AwsDoc::S3::CRC32C:
                    hashData = result.GetChecksum().GetChecksumCRC32C();
                    break;
                default:
                    std::cerr << "Unknown hash method." << std::endl;
                    return false;
            }
        } else {
            std::cerr << "Error retrieving object checksum attributes." <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }

        if (nullptr != partHashes) {
            attributes.clear();
            attributes.push_back(Aws::S3::Model::ObjectAttributes::ObjectParts);
            request.SetObjectAttributes(attributes);
            outcome = client.GetObjectAttributes(request);
            if (outcome.IsSuccess()) {
                const Aws::S3::Model::GetObjectAttributesResult &result =
 outcome.GetResult();
                const Aws::Vector<Aws::S3::Model::ObjectPart> parts =
 result.GetObjectParts().GetParts();
```

```
                for (const Aws::S3::Model::ObjectPart &part: parts) {
                    switch (hashMethod) {
                        case AwsDoc::S3::DEFAULT: // Default is not supported.
 NOLINT(*-branch-clone)
                            break;
                        case AwsDoc::S3::MD5: // MD5 is not supported.
                            break;
                        case AwsDoc::S3::SHA1:
                            partHashes->push_back(part.GetChecksumSHA1());
                            break;
                        case AwsDoc::S3::SHA256:
                            partHashes->push_back(part.GetChecksumSHA256());
                            break;
                        case AwsDoc::S3::CRC32:
                            partHashes->push_back(part.GetChecksumCRC32());
                            break;
                        case AwsDoc::S3::CRC32C:
                            partHashes->push_back(part.GetChecksumCRC32C());
                            break;
                        default:
                            std::cerr << "Unknown hash method." << std::endl;
                            return false;
                    }
                }
            } else {
                std::cerr << "Error retrieving object attributes for object parts."
 <<
                          outcome.GetError().GetMessage() << std::endl;
                return false;
            }
        }
    }

    return true;
}

//! Verifies the hashing results between the retrieved and local hashes.
/*!
 \param retrievedHash The hash value retrieved from the remote source.
 \param localHash The hash value calculated locally.
 \param uploadtype The type of upload (e.g., "multipart", "single-part").
 \param hashMethod The hashing method used (e.g., MD5, SHA-256).
 \param retrievedPartHashes (Optional) The list of hashes for the individual parts
 retrieved from the remote source.
```

```
 \param localPartHashes (Optional) The list of hashes for the individual parts
 calculated locally.
 */
void AwsDoc::S3::verifyHashingResults(const Aws::String &retrievedHash,
                                      const Hasher &localHash,
                                      const Aws::String &uploadtype,
                                      HASH_METHOD hashMethod,
                                      const std::vector<Aws::String>
 &retrievedPartHashes,
                                      const std::vector<Aws::String>
 &localPartHashes) {
    std::cout << "For " << uploadtype << " retrieved hash is " << retrievedHash <<
 std::endl;
    if (!retrievedPartHashes.empty()) {
        std::cout << retrievedPartHashes.size() << " part hash(es) were also
 retrieved."
                  << std::endl;
        for (auto &retrievedPartHash: retrievedPartHashes) {
            std::cout << "  Part hash " << retrievedPartHash << std::endl;
        }
    }
    Aws::String hashString;
    if (hashMethod == MD5) {
        hashString = localHash.getHexHashString();
        if (!localPartHashes.empty()) {
            hashString += "-" + std::to_string(localPartHashes.size());
        }
    } else {
        hashString = localHash.getBase64HashString();
    }

    bool allMatch = true;
    if (hashString != retrievedHash) {
        std::cerr << "For " << uploadtype << ", the main hashes do not match" <<
 std::endl;
        std::cerr << "Local hash- '" << hashString << "'" << std::endl;
        std::cerr << "Remote hash - '" << retrievedHash << "'" << std::endl;
        allMatch = false;
    }

    if (hashMethod != MD5) {
        if (localPartHashes.size() != retrievedPartHashes.size()) {
            std::cerr << "For " << uploadtype << ", the number of part hashes do not
 match" << std::endl;
```

```
            std::cerr << "Local number of hashes- '" << localPartHashes.size() <<
 "'"
                      << std::endl;
            std::cerr << "Remote number of hashes - '"
                      << retrievedPartHashes.size()
                      << "'" << std::endl;
        }

        for (int i = 0; i < localPartHashes.size(); ++i) {
            if (localPartHashes[i] != retrievedPartHashes[i]) {
                std::cerr << "For " << uploadtype << ", the part hashes do not match
 for part " << i + 1
                          << "." << std::endl;
                std::cerr << "Local hash- '" << localPartHashes[i] << "'"
                          << std::endl;
                std::cerr << "Remote hash - '" << retrievedPartHashes[i] << "'"
                          << std::endl;
                allMatch = false;
            }
        }
    }

    if (allMatch) {
        std::cout << "For " << uploadtype << ", locally and remotely calculated
 hashes all match!" << std::endl;
    }

}

static void transferManagerErrorCallback(const Aws::Transfer::TransferManager *,
                                         const std::shared_ptr<const
 Aws::Transfer::TransferHandle> &,
                                         const
 Aws::Client::AWSError<Aws::S3::S3Errors> &err) {
    std::cerr << "Error during transfer: '" << err.GetMessage() << "'" << std::endl;
}

static void transferManagerStatusCallback(const Aws::Transfer::TransferManager *,
                                          const std::shared_ptr<const
 Aws::Transfer::TransferHandle> &handle) {
    if (handle->GetStatus() == Aws::Transfer::TransferStatus::IN_PROGRESS) {
        std::cout << "Bytes transferred: " << handle->GetBytesTransferred() <<
 std::endl;
    }
```

```
}

//! Routine which uploads an object to an S3 bucket using the AWS C++ SDK's Transfer
 Manager.
/*!
   \param bucket: The name of the S3 bucket where the object will be uploaded.
   \param key: The unique identifier (key) for the object within the S3 bucket.
   \param hashMethod: The hashing algorithm to use when calculating the hash value.
   \param useDefaultHashMethod: A flag indicating whether to use the default hash
 method or the one specified in the hashMethod parameter.
   \param client: The S3 client instance used to perform the upload operation.
   \return bool: Function succeeded.
*/
bool
AwsDoc::S3::doTransferManagerUpload(const Aws::String &bucket, const Aws::String
 &key,
                                    AwsDoc::S3::HASH_METHOD hashMethod,
                                    bool useDefaultHashMethod,
                                    const std::shared_ptr<Aws::S3::S3Client>
 &client) {
    std::shared_ptr<Aws::Utils::Threading::PooledThreadExecutor> executor =
 Aws::MakeShared<Aws::Utils::Threading::PooledThreadExecutor>(
            "executor", 25);
    Aws::Transfer::TransferManagerConfiguration transfer_config(executor.get());
    transfer_config.s3Client = client;
    transfer_config.bufferSize = UPLOAD_BUFFER_SIZE;
    if (!useDefaultHashMethod) {
        if (hashMethod == MD5) {
            transfer_config.computeContentMD5 = true;
        } else {
            transfer_config.checksumAlgorithm = getChecksumAlgorithmForHashMethod(
                    hashMethod);
        }
    }
    transfer_config.errorCallback = transferManagerErrorCallback;
    transfer_config.transferStatusUpdatedCallback = transferManagerStatusCallback;

    std::shared_ptr<Aws::Transfer::TransferManager> transfer_manager =
 Aws::Transfer::TransferManager::Create(
            transfer_config);

    std::cout << "Uploading the file..." << std::endl;
    std::shared_ptr<Aws::Transfer::TransferHandle> uploadHandle = transfer_manager-
>UploadFile(MULTI_PART_TEST_FILE,
```

```
            bucket, key,

            "text/plain",

            Aws::Map<Aws::String, Aws::String>());
    uploadHandle->WaitUntilFinished();
    bool success =
            uploadHandle->GetStatus() == Aws::Transfer::TransferStatus::COMPLETED;
    if (!success) {
        Aws::Client::AWSError<Aws::S3::S3Errors> err = uploadHandle->GetLastError();
        std::cerr << "File upload failed:  " << err.GetMessage() << std::endl;
    }

    return success;
}

//! Routine which calculates the hash values for each part of a file being uploaded
 to an S3 bucket.
/*!
   \param hashMethod: The hashing algorithm to use when calculating the hash values.
   \param fileName: The path to the file for which the part hashes will be
 calculated.
   \param bufferSize: The size of the buffer to use when reading the file.
   \param[out] hashDataResult: The Hasher object that will store the concatenated
 hash value.
   \param[out] partHashes: The vector that will store the calculated hash values for
 each part of the file.
   \return bool: Function succeeded.
*/
bool AwsDoc::S3::calculatePartHashesForFile(AwsDoc::S3::HASH_METHOD hashMethod,
                                            const Aws::String &fileName,
                                            size_t bufferSize,
                                            AwsDoc::S3::Hasher &hashDataResult,
                                            std::vector<Aws::String> &partHashes) {
    std::ifstream fileStream(fileName.c_str(), std::ifstream::binary);
    fileStream.seekg(0, std::ifstream::end);
    size_t objectSize = fileStream.tellg();
    fileStream.seekg(0, std::ifstream::beg);
    std::vector<unsigned char> totalHashBuffer;
    size_t uploadedBytes = 0;


    while (uploadedBytes < objectSize) {
```

```
        std::vector<unsigned char> buffer(bufferSize);
        std::streamsize bytesToRead =
 static_cast<std::streamsize>(std::min(buffer.size(), objectSize - uploadedBytes));
        fileStream.read((char *) buffer.data(), bytesToRead);
        Aws::Utils::Stream::PreallocatedStreamBuf
 preallocatedStreamBuf(buffer.data(),

 bytesToRead);
        std::shared_ptr<Aws::IOStream> body =
                Aws::MakeShared<Aws::IOStream>("SampleAllocationTag",
                                               &preallocatedStreamBuf);
        Hasher hasher;
        if (!hasher.calculateObjectHash(*body, hashMethod)) {
            std::cerr << "Error calculating hash." << std::endl;
            return false;
        }
        Aws::String base64HashString = hasher.getBase64HashString();
        partHashes.push_back(base64HashString);

        Aws::Utils::ByteBuffer hashBuffer = hasher.getByteBufferHash();

        totalHashBuffer.insert(totalHashBuffer.end(),
 hashBuffer.GetUnderlyingData(),
                               hashBuffer.GetUnderlyingData() +
 hashBuffer.GetLength());

        uploadedBytes += bytesToRead;
    }

    return hashDataResult.calculateObjectHash(totalHashBuffer, hashMethod);
}

//! Create a multipart upload.
/*!
    \param bucket: The name of the S3 bucket where the object will be uploaded.
    \param key: The unique identifier (key) for the object within the S3 bucket.
    \param client: The S3 client instance used to perform the upload operation.
    \return Aws::String: Upload ID or empty string if failed.
*/
Aws::String
AwsDoc::S3::createMultipartUpload(const Aws::String &bucket, const Aws::String &key,
                                  Aws::S3::Model::ChecksumAlgorithm
 checksumAlgorithm,
                                  const Aws::S3::S3Client &client) {
```

```
    Aws::S3::Model::CreateMultipartUploadRequest request;
    request.SetBucket(bucket);
    request.SetKey(key);

    if (checksumAlgorithm != Aws::S3::Model::ChecksumAlgorithm::NOT_SET) {
        request.SetChecksumAlgorithm(checksumAlgorithm);
    }

    Aws::S3::Model::CreateMultipartUploadOutcome outcome =
            client.CreateMultipartUpload(request);

    Aws::String uploadID;
    if (outcome.IsSuccess()) {
        uploadID = outcome.GetResult().GetUploadId();
    } else {
        std::cerr << "Error creating multipart upload: " <<
 outcome.GetError().GetMessage() << std::endl;
    }

    return uploadID;
}

//! Upload a part to an S3 bucket.
/*!
    \param bucket: The name of the S3 bucket where the object will be uploaded.
    \param key: The unique identifier (key) for the object within the S3 bucket.
    \param uploadID: An upload ID string.
    \param partNumber:
    \param checksumAlgorithm: Checksum algorithm, ignored when NOT_SET.
    \param calculatedHash: A data integrity hash to set, depending on the checksum
 algorithm,
                           ignored when it is an empty string.
    \param body: An shared_ptr IOStream of the data to be uploaded.
    \param client: The S3 client instance used to perform the upload operation.
    \return UploadPartOutcome: The outcome.
*/

Aws::S3::Model::UploadPartOutcome AwsDoc::S3::uploadPart(const Aws::String &bucket,
                                                         const Aws::String &key,
                                                         const Aws::String
 &uploadID,
                                                         int partNumber,

 Aws::S3::Model::ChecksumAlgorithm checksumAlgorithm,
```

```
                                                        const Aws::String
 &calculatedHash,
                                                        const
 std::shared_ptr<Aws::IOStream> &body,
                                                        const Aws::S3::S3Client
 &client) {
    Aws::S3::Model::UploadPartRequest request;
    request.SetBucket(bucket);
    request.SetKey(key);
    request.SetUploadId(uploadID);
    request.SetPartNumber(partNumber);
    if (checksumAlgorithm != Aws::S3::Model::ChecksumAlgorithm::NOT_SET) {
        request.SetChecksumAlgorithm(checksumAlgorithm);
    }
    request.SetBody(body);

    if (!calculatedHash.empty()) {
        switch (checksumAlgorithm) {
            case Aws::S3::Model::ChecksumAlgorithm::NOT_SET:
                request.SetContentMD5(calculatedHash);
                break;
            case Aws::S3::Model::ChecksumAlgorithm::CRC32:
                request.SetChecksumCRC32(calculatedHash);
                break;
            case Aws::S3::Model::ChecksumAlgorithm::CRC32C:
                request.SetChecksumCRC32C(calculatedHash);
                break;
            case Aws::S3::Model::ChecksumAlgorithm::SHA1:
                request.SetChecksumSHA1(calculatedHash);
                break;
            case Aws::S3::Model::ChecksumAlgorithm::SHA256:
                request.SetChecksumSHA256(calculatedHash);
                break;
        }
    }

    return client.UploadPart(request);
}

//! Abort a multipart upload to an S3 bucket.
/*!
    \param bucket: The name of the S3 bucket where the object will be uploaded.
    \param key: The unique identifier (key) for the object within the S3 bucket.
    \param uploadID: An upload ID string.
```

```
    \param client: The S3 client instance used to perform the upload operation.
    \return bool: Function succeeded.
*/

bool AwsDoc::S3::abortMultipartUpload(const Aws::String &bucket,
                                      const Aws::String &key,
                                      const Aws::String &uploadID,
                                      const Aws::S3::S3Client &client) {
    Aws::S3::Model::AbortMultipartUploadRequest request;
    request.SetBucket(bucket);
    request.SetKey(key);
    request.SetUploadId(uploadID);

    Aws::S3::Model::AbortMultipartUploadOutcome outcome =
            client.AbortMultipartUpload(request);

    if (outcome.IsSuccess()) {
        std::cout << "Multipart upload aborted." << std::endl;
    } else {
        std::cerr << "Error aborting multipart upload: " <<
 outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}

//! Complete a multipart upload to an S3 bucket.
/*!
    \param bucket: The name of the S3 bucket where the object will be uploaded.
    \param key: The unique identifier (key) for the object within the S3 bucket.
    \param uploadID: An upload ID string.
    \param parts: A vector of CompleteParts.
    \param client: The S3 client instance used to perform the upload operation.
    \return CompleteMultipartUploadOutcome: The request outcome.
*/
Aws::S3::Model::CompleteMultipartUploadOutcome
 AwsDoc::S3::completeMultipartUpload(const Aws::String &bucket,

 const Aws::String &key,

 const Aws::String &uploadID,

 const Aws::Vector<Aws::S3::Model::CompletedPart> &parts,
```

```
 const Aws::S3::S3Client &client) {
    Aws::S3::Model::CompletedMultipartUpload completedMultipartUpload;
    completedMultipartUpload.SetParts(parts);

    Aws::S3::Model::CompleteMultipartUploadRequest request;
    request.SetBucket(bucket);
    request.SetKey(key);
    request.SetUploadId(uploadID);
    request.SetMultipartUpload(completedMultipartUpload);

    Aws::S3::Model::CompleteMultipartUploadOutcome outcome =
            client.CompleteMultipartUpload(request);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error completing multipart upload: " <<
 outcome.GetError().GetMessage() << std::endl;
    }
    return outcome;
}

//! Routine which performs a multi-part upload.
/*!
    \param bucket: The name of the S3 bucket where the object will be uploaded.
    \param key: The unique identifier (key) for the object within the S3 bucket.
    \param hashMethod: The hashing algorithm to use when calculating the hash value.
    \param ioStream: An IOStream for the data to be uploaded.
    \param useDefaultHashMethod: A flag indicating whether to use the default hash
 method or the one specified in the hashMethod parameter.
    \param[out] hashDataResult: The Hasher object that will store the concatenated
 hash value.
    \param[out] partHashes: The vector that will store the calculated hash values
 for each part of the file.
    \param client: The S3 client instance used to perform the upload operation.
    \return bool: Function succeeded.
*/
bool AwsDoc::S3::doMultipartUpload(const Aws::String &bucket,
                                   const Aws::String &key,
                                   AwsDoc::S3::HASH_METHOD hashMethod,
                                   const std::shared_ptr<Aws::IOStream> &ioStream,
                                   bool useDefaultHashMethod,
                                   AwsDoc::S3::Hasher &hashDataResult,
                                   std::vector<Aws::String> &partHashes,
                                   const Aws::S3::S3Client &client) {
```

```
   // Get object size.
   ioStream->seekg(0, ioStream->end);
   size_t objectSize = ioStream->tellg();
   ioStream->seekg(0, ioStream->beg);

   Aws::S3::Model::ChecksumAlgorithm checksumAlgorithm =
Aws::S3::Model::ChecksumAlgorithm::NOT_SET;
   if (!useDefaultHashMethod) {
       if (hashMethod != MD5) {
           checksumAlgorithm = getChecksumAlgorithmForHashMethod(hashMethod);
       }
   }
   Aws::String uploadID = createMultipartUpload(bucket, key, checksumAlgorithm,
client);
   if (uploadID.empty()) {
       return false;
   }

   std::vector<unsigned char> totalHashBuffer;
   bool uploadSucceeded = true;
   std::streamsize uploadedBytes = 0;
   int partNumber = 1;
   Aws::Vector<Aws::S3::Model::CompletedPart> parts;
   while (uploadedBytes < objectSize) {
       std::cout << "Uploading part " << partNumber << "." << std::endl;

       std::vector<unsigned char> buffer(UPLOAD_BUFFER_SIZE);
       std::streamsize bytesToRead =
static_cast<std::streamsize>(std::min(buffer.size(),

objectSize - uploadedBytes));
       ioStream->read((char *) buffer.data(), bytesToRead);
       Aws::Utils::Stream::PreallocatedStreamBuf
preallocatedStreamBuf(buffer.data(),

bytesToRead);
       std::shared_ptr<Aws::IOStream> body =
               Aws::MakeShared<Aws::IOStream>("SampleAllocationTag",
                                              &preallocatedStreamBuf);

       Hasher hasher;
       if (!hasher.calculateObjectHash(*body, hashMethod)) {
           std::cerr << "Error calculating hash." << std::endl;
           uploadSucceeded = false;
```

```
            break;
        }

        Aws::String base64HashString = hasher.getBase64HashString();
        partHashes.push_back(base64HashString);

        Aws::Utils::ByteBuffer hashBuffer = hasher.getByteBufferHash();

        totalHashBuffer.insert(totalHashBuffer.end(),
hashBuffer.GetUnderlyingData(),
                               hashBuffer.GetUnderlyingData() +
hashBuffer.GetLength());

        Aws::String calculatedHash;
        if (gUseCalculatedChecksum) {
            calculatedHash = base64HashString;
        }
        Aws::S3::Model::UploadPartOutcome uploadPartOutcome = uploadPart(bucket,
key, uploadID, partNumber,

checksumAlgorithm, base64HashString, body,
                                                                        client);
        if (uploadPartOutcome.IsSuccess()) {
            const Aws::S3::Model::UploadPartResult &uploadPartResult =
uploadPartOutcome.GetResult();
            Aws::S3::Model::CompletedPart completedPart;
            completedPart.SetETag(uploadPartResult.GetETag());
            completedPart.SetPartNumber(partNumber);
            switch (hashMethod) {
                case AwsDoc::S3::MD5:
                    break; // Do nothing.
                case AwsDoc::S3::SHA1:

completedPart.SetChecksumSHA1(uploadPartResult.GetChecksumSHA1());
                    break;
                case AwsDoc::S3::SHA256:

completedPart.SetChecksumSHA256(uploadPartResult.GetChecksumSHA256());
                    break;
                case AwsDoc::S3::CRC32:

completedPart.SetChecksumCRC32(uploadPartResult.GetChecksumCRC32());
                    break;
                case AwsDoc::S3::CRC32C:
```

```
completedPart.SetChecksumCRC32C(uploadPartResult.GetChecksumCRC32C());
                    break;
                default:
                    std::cerr << "Unhandled hash method for completedPart." <<
std::endl;
                    break;
            }

            parts.push_back(completedPart);
        } else {
            std::cerr << "Error uploading part. " <<
                      uploadPartOutcome.GetError().GetMessage() << std::endl;
            uploadSucceeded = false;
            break;
        }

        uploadedBytes += bytesToRead;
        partNumber++;
    }

    if (!uploadSucceeded) {
        abortMultipartUpload(bucket, key, uploadID, client);
        return false;
    } else {

        Aws::S3::Model::CompleteMultipartUploadOutcome
completeMultipartUploadOutcome = completeMultipartUpload(bucket,

                             key,

                             uploadID,

                             parts,

                             client);

        if (completeMultipartUploadOutcome.IsSuccess()) {
            std::cout << "Multipart upload completed." << std::endl;
            if (!hashDataResult.calculateObjectHash(totalHashBuffer, hashMethod)) {
                std::cerr << "Error calculating hash." << std::endl;
                return false;
            }
        } else {
```

```
            std::cerr << "Error completing multipart upload." <<
                      completeMultipartUploadOutcome.GetError().GetMessage()
                      << std::endl;
        }

        return completeMultipartUploadOutcome.IsSuccess();
    }
}

//! Routine which retrieves the string for a HASH_METHOD constant.
/*!
    \param: hashMethod: A HASH_METHOD constant.
    \return: String: A string description of the hash method.
*/
Aws::String AwsDoc::S3::stringForHashMethod(AwsDoc::S3::HASH_METHOD hashMethod) {
    switch (hashMethod) {
        case AwsDoc::S3::DEFAULT:
            return "Default";
        case AwsDoc::S3::MD5:
            return "MD5";
        case AwsDoc::S3::SHA1:
            return "SHA1";
        case AwsDoc::S3::SHA256:
            return "SHA256";
        case AwsDoc::S3::CRC32:
            return "CRC32";
        case AwsDoc::S3::CRC32C:
            return "CRC32C";
        default:
            return "Unknown";
    }
}

//! Routine that returns the ChecksumAlgorithm for a HASH_METHOD constant.
/*!
    \param: hashMethod: A HASH_METHOD constant.
    \return: ChecksumAlgorithm: The ChecksumAlgorithm enum.
*/
Aws::S3::Model::ChecksumAlgorithm
AwsDoc::S3::getChecksumAlgorithmForHashMethod(AwsDoc::S3::HASH_METHOD hashMethod) {
    Aws::S3::Model::ChecksumAlgorithm result =
 Aws::S3::Model::ChecksumAlgorithm::NOT_SET;
    switch (hashMethod) {
        case AwsDoc::S3::DEFAULT:
```

```
            std::cerr << "getChecksumAlgorithmForHashMethod- DEFAULT is not valid."
 << std::endl;
            break;  // Default is not supported.
        case AwsDoc::S3::MD5:
            break; // Ignore MD5.
        case AwsDoc::S3::SHA1:
            result = Aws::S3::Model::ChecksumAlgorithm::SHA1;
            break;
        case AwsDoc::S3::SHA256:
            result = Aws::S3::Model::ChecksumAlgorithm::SHA256;
            break;
        case AwsDoc::S3::CRC32:
            result = Aws::S3::Model::ChecksumAlgorithm::CRC32;
            break;
        case AwsDoc::S3::CRC32C:
            result = Aws::S3::Model::ChecksumAlgorithm::CRC32C;
            break;
        default:
            std::cerr << "Unknown hash method." << std::endl;
            break;

    }

    return result;
}

//! Routine which cleans up after the example is complete.
/*!
    \param bucket: The name of the S3 bucket where the object was uploaded.
    \param clientConfiguration: The client configuration for the S3 client.
    \return bool: Function succeeded.
*/
bool AwsDoc::S3::cleanUp(const Aws::String &bucketName,
                         const Aws::S3::S3ClientConfiguration &clientConfiguration)
 {

    Aws::Vector<Aws::String> keysResult;
    bool result = true;
    if (AwsDoc::S3::listObjects(bucketName, keysResult, clientConfiguration)) {
        if (!keysResult.empty()) {
            result = AwsDoc::S3::deleteObjects(keysResult, bucketName,
                                               clientConfiguration);
        }
    } else {
```

```
        result = false;
    }

    return result && AwsDoc::S3::deleteBucket(bucketName, clientConfiguration);
}

//! Console interaction introducing the workflow.
/*!
  \param bucketName: The name of the S3 bucket to use.
*/
void AwsDoc::S3::introductoryExplanations(const Aws::String &bucketName) {

    std::cout
            << "Welcome to the Amazon Simple Storage Service (Amazon S3) object
 integrity workflow."
            << std::endl;
    printAsterisksLine();
    std::cout
            << "This workflow demonstrates how Amazon S3 uses checksum values to
 verify the integrity of data\n";
    std::cout << "uploaded to Amazon S3 buckets" << std::endl;
    std::cout
            << "The AWS SDK for C++ automatically handles checksums.\n";
    std::cout
            << "By default it calculates a checksum that is uploaded with an object.
\n"
            << "The default checksum algorithm for PutObject and MultiPart upload is
 an MD5 hash.\n"
            << "The default checksum algorithm for TransferManager uploads is a
 CRC32 checksum."
            << std::endl;
    std::cout
            << "You can override the default behavior, requiring one of the
 following checksums,\n";
    std::cout << "MD5, CRC32, CRC32C, SHA-1 or SHA-256." << std::endl;
    std::cout << "You can also set the checksum hash value, instead of letting the
 SDK calculate the value."
              << std::endl;
    std::cout
            << "For more information, see https://docs.aws.amazon.com/AmazonS3/
latest/userguide/checking-object-integrity.html."
            << std::endl;

    std::cout
```

```
            << "This workflow will locally compute checksums for files uploaded to
 an Amazon S3 bucket,\n";
    std::cout << "even when the SDK also computes the checksum." << std::endl;
    std::cout
            << "This is done to provide demonstration code for how the checksums are
 calculated."
            << std::endl;
    std::cout << "A bucket named '" << bucketName << "' will be created for the
 object uploads."
              << std::endl;
}

//! Console interaction which explains the PutObject results.
/*!
*/
void AwsDoc::S3::explainPutObjectResults() {

    std::cout << "The upload was successful.\n";
    std::cout << "If the checksums had not matched, the upload would have failed."
              << std::endl;
    std::cout
            << "The checksums calculated by the server have been retrieved using the
 GetObjectAttributes."
            << std::endl;
    std::cout
            << "The locally calculated checksums have been verified against the
 retrieved checksums."
            << std::endl;
}

//! Console interaction explaining transfer manager uploads.
/*!
  \param objectKey: The key for the object being uploaded.
*/
void AwsDoc::S3::introductoryTransferManagerUploadExplanations(
        const Aws::String &objectKey) {
    std::cout
            << "Now the workflow will demonstrate object integrity for
 TransferManager multi-part uploads."
            << std::endl;
    std::cout
            << "The AWS C++ SDK has a TransferManager class which simplifies
 multipart uploads."
            << std::endl;
```

```
    std::cout
            << "The following code lets the TransferManager handle much of the
 checksum configuration."
            << std::endl;

    std::cout << "An object with the key '" << objectKey
              << " will be uploaded by the TransferManager using a "
              << BUFFER_SIZE_IN_MEGABYTES << " MB buffer." << std::endl;
    if (gUseCalculatedChecksum) {
        std::cout << "For TransferManager uploads, this demo always lets the SDK
 calculate the hash value."
                  << std::endl;
    }

    pressEnterToContinue();
    printAsterisksLine();
}

//! Console interaction explaining multi-part uploads.
/*!
  \param objectKey: The key for the object being uploaded.
  \param chosenHashMethod: The hash method selected by the user.
*/
void AwsDoc::S3::multiPartUploadExplanations(const Aws::String &objectKey,
                                             HASH_METHOD chosenHashMethod) {
    std::cout
            << "Now we will provide an in-depth demonstration of multi-part
 uploading by calling the multi-part upload APIs directly."
            << std::endl;
    std::cout << "These are the same APIs used by the TransferManager when uploading
 large files."
              << std::endl;
    std::cout
            << "In the following code, the checksums are also calculated locally and
 then compared."
            << std::endl;
    std::cout
            << "For multi-part uploads, a checksum is uploaded with each part. The
 final checksum is a concatenation of"
            << std::endl;
    std::cout << "the checksums for each part." << std::endl;
    std::cout
            << "This is explained in the user guide, https://docs.aws.amazon.com/
AmazonS3/latest/userguide/checking-object-integrity.html,\""
```

```
            << " in the section \"Using part-level checksums for multipart uploads
\"." << std::endl;

    std::cout << "Starting multipart upload of with hash method " <<
              stringForHashMethod(chosenHashMethod) << " uploading to with object
 key\n"
              << "'" << objectKey << "'," << std::endl;

}

//! Create a large file for doing multi-part uploads.
/*!
*/
bool AwsDoc::S3::createLargeFileIfNotExists() {
    // Generate a large file by writing this source file multiple times to a new
 file.
    if (std::filesystem::exists(MULTI_PART_TEST_FILE)) {
        return true;
    }

    std::ofstream newFile(MULTI_PART_TEST_FILE, std::ios::out

                                                | std::ios::binary);

    if (!newFile) {
        std::cerr << "createLargeFileIfNotExists- Error creating file " <<
 MULTI_PART_TEST_FILE <<
                  std::endl;
        return false;
    }

    std::ifstream input(TEST_FILE, std::ios::in

                                   | std::ios::binary);
    if (!input) {
        std::cerr << "Error opening file " << TEST_FILE <<
                  std::endl;
        return false;
    }
    std::stringstream buffer;
    buffer << input.rdbuf();

    input.close();
```

```
    while (newFile.tellp() < LARGE_FILE_SIZE && !newFile.bad()) {
        buffer.seekg(std::stringstream::beg);
        newFile << buffer.rdbuf();
    }

    newFile.close();

    return true;
}
```

- For API details, see the following topics in *AWS SDK for C++ API Reference*.
  - AbortMultipartUpload
  - CompleteMultipartUpload
  - CreateMultipartUpload
  - DeleteObject
  - GetObjectAttributes
  - PutObject
  - UploadPart

Secrets Manager examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with Secrets Manager.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Actions

Actions

`GetSecretValue`

The following code example shows how to use `GetSecretValue`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Retrieve an AWS Secrets Manager encrypted secret.
/*!
  \param secretID: The ID for the secret.
  \return bool: Function succeeded.
 */
bool AwsDoc::SecretsManager::getSecretValue(const Aws::String &secretID,
                                            const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SecretsManager::SecretsManagerClient
 secretsManagerClient(clientConfiguration);

    Aws::SecretsManager::Model::GetSecretValueRequest request;
    request.SetSecretId(secretID);

    Aws::SecretsManager::Model::GetSecretValueOutcome getSecretValueOutcome =
 secretsManagerClient.GetSecretValue(
            request);
    if (getSecretValueOutcome.IsSuccess()) {
        std::cout << "Secret is: "
                  << getSecretValueOutcome.GetResult().GetSecretString() <<
 std::endl;
    }
    else {
        std::cerr << "Failed with Error: " << getSecretValueOutcome.GetError()
                  << std::endl;
    }

    return getSecretValueOutcome.IsSuccess();
```

```
}
```

- For API details, see GetSecretValue in *AWS SDK for C++ API Reference*.

Amazon SES examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with Amazon SES.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Scenarios are code examples that show you how to accomplish specific tasks by calling multiple functions within a service or combined with other AWS services.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Actions
- Scenarios

Actions

`CreateReceiptFilter`

The following code example shows how to use `CreateReceiptFilter`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Create an Amazon Simple Email Service (Amazon SES) receipt filter..
```

```
/*!
  \param receiptFilterName: The name for the receipt filter.
  \param cidr: IP address or IP address range in Classless Inter-Domain Routing
 (CIDR) notation.
  \param policy: Block or allow enum of type ReceiptFilterPolicy.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::createReceiptFilter(const Aws::String &receiptFilterName,
                                      const Aws::String &cidr,
                                      Aws::SES::Model::ReceiptFilterPolicy policy,
                                      const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);
    Aws::SES::Model::CreateReceiptFilterRequest createReceiptFilterRequest;
    Aws::SES::Model::ReceiptFilter receiptFilter;
    Aws::SES::Model::ReceiptIpFilter receiptIpFilter;
    receiptIpFilter.SetCidr(cidr);
    receiptIpFilter.SetPolicy(policy);
    receiptFilter.SetName(receiptFilterName);
    receiptFilter.SetIpFilter(receiptIpFilter);
    createReceiptFilterRequest.SetFilter(receiptFilter);
    Aws::SES::Model::CreateReceiptFilterOutcome createReceiptFilterOutcome =
 sesClient.CreateReceiptFilter(
            createReceiptFilterRequest);
    if (createReceiptFilterOutcome.IsSuccess()) {
        std::cout << "Successfully created receipt filter." << std::endl;
    }
    else {
        std::cerr << "Error creating receipt filter: " <<
                  createReceiptFilterOutcome.GetError().GetMessage() << std::endl;
    }

    return createReceiptFilterOutcome.IsSuccess();
}
```

- For API details, see CreateReceiptFilter in *AWS SDK for C++ API Reference*.

`CreateReceiptRule`

The following code example shows how to use `CreateReceiptRule`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Create an Amazon Simple Email Service (Amazon SES) receipt rule.
/*!
  \param receiptRuleName: The name for the receipt rule.
  \param s3BucketName: The name of the S3 bucket for incoming mail.
  \param s3ObjectKeyPrefix: The prefix for the objects in the S3 bucket.
  \param ruleSetName: The name of the rule set where the receipt rule is added.
  \param recipients: Aws::Vector of recipients.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::createReceiptRule(const Aws::String &receiptRuleName,
                                    const Aws::String &s3BucketName,
                                    const Aws::String &s3ObjectKeyPrefix,
                                    const Aws::String &ruleSetName,
                                    const Aws::Vector<Aws::String> &recipients,
                                    const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::CreateReceiptRuleRequest createReceiptRuleRequest;

    Aws::SES::Model::S3Action s3Action;
    s3Action.SetBucketName(s3BucketName);
    s3Action.SetObjectKeyPrefix(s3ObjectKeyPrefix);

    Aws::SES::Model::ReceiptAction receiptAction;
    receiptAction.SetS3Action(s3Action);

    Aws::SES::Model::ReceiptRule receiptRule;
    receiptRule.SetName(receiptRuleName);
    receiptRule.WithRecipients(recipients);

    Aws::Vector<Aws::SES::Model::ReceiptAction> receiptActionList;
    receiptActionList.emplace_back(receiptAction);
```

```
    receiptRule.SetActions(receiptActionList);

    createReceiptRuleRequest.SetRuleSetName(ruleSetName);
    createReceiptRuleRequest.SetRule(receiptRule);

    auto outcome = sesClient.CreateReceiptRule(createReceiptRuleRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully created receipt rule." << std::endl;
    }
    else {
        std::cerr << "Error creating receipt rule. " <<
 outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see CreateReceiptRule in *AWS SDK for C++ API Reference*.

`CreateReceiptRuleSet`

The following code example shows how to use `CreateReceiptRuleSet`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Create an Amazon Simple Email Service (Amazon SES) receipt rule set.
/*!
  \param ruleSetName: The name of the rule set.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
```

```
bool AwsDoc::SES::createReceiptRuleSet(const Aws::String &ruleSetName,
                                       const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::CreateReceiptRuleSetRequest createReceiptRuleSetRequest;

    createReceiptRuleSetRequest.SetRuleSetName(ruleSetName);

    Aws::SES::Model::CreateReceiptRuleSetOutcome outcome =
 sesClient.CreateReceiptRuleSet(
            createReceiptRuleSetRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully created receipt rule set." << std::endl;
    }
    else {
        std::cerr << "Error creating receipt rule set. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see CreateReceiptRuleSet in *AWS SDK for C++ API Reference*.

`CreateTemplate`

The following code example shows how to use `CreateTemplate`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Create an Amazon Simple Email Service (Amazon SES) template.
```

```
/*!
  \param templateName: The name of the template.
  \param htmlPart: The HTML body of the email.
  \param subjectPart: The subject line of the email.
  \param textPart: The plain text version of the email.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::createTemplate(const Aws::String &templateName,
                                 const Aws::String &htmlPart,
                                 const Aws::String &subjectPart,
                                 const Aws::String &textPart,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::CreateTemplateRequest createTemplateRequest;
    Aws::SES::Model::Template aTemplate;

    aTemplate.SetTemplateName(templateName);
    aTemplate.SetHtmlPart(htmlPart);
    aTemplate.SetSubjectPart(subjectPart);
    aTemplate.SetTextPart(textPart);

    createTemplateRequest.SetTemplate(aTemplate);

    Aws::SES::Model::CreateTemplateOutcome outcome = sesClient.CreateTemplate(
            createTemplateRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully created template." << templateName << "."
                  << std::endl;
    }
    else {
        std::cerr << "Error creating template. " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see CreateTemplate in *AWS SDK for C++ API Reference*.

`DeleteIdentity`

The following code example shows how to use `DeleteIdentity`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Delete the specified identity (an email address or a domain).
/*!
  \param identity: The identity to delete.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::deleteIdentity(const Aws::String &identity,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::DeleteIdentityRequest deleteIdentityRequest;

    deleteIdentityRequest.SetIdentity(identity);

    Aws::SES::Model::DeleteIdentityOutcome outcome = sesClient.DeleteIdentity(
            deleteIdentityRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted identity." << std::endl;
    }
    else {
        std::cerr << "Error deleting identity. " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DeleteIdentity in *AWS SDK for C++ API Reference*.

`DeleteReceiptFilter`

The following code example shows how to use `DeleteReceiptFilter`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Delete an Amazon Simple Email Service (Amazon SES) receipt filter.
/*!
  \param receiptFilterName: The name for the receipt filter.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::deleteReceiptFilter(const Aws::String &receiptFilterName,
                                      const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::DeleteReceiptFilterRequest deleteReceiptFilterRequest;

    deleteReceiptFilterRequest.SetFilterName(receiptFilterName);

    Aws::SES::Model::DeleteReceiptFilterOutcome outcome =
 sesClient.DeleteReceiptFilter(
            deleteReceiptFilterRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted receipt filter." << std::endl;
    }
    else {
        std::cerr << "Error deleting receipt filter. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }
```

```
    return outcome.IsSuccess();
}
```

- For API details, see DeleteReceiptFilter in *AWS SDK for C++ API Reference*.

`DeleteReceiptRule`

The following code example shows how to use `DeleteReceiptRule`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Delete an Amazon Simple Email Service (Amazon SES) receipt rule.
/*!
  \param receiptRuleName: The name for the receipt rule.
  \param receiptRuleSetName: The name for the receipt rule set.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::deleteReceiptRule(const Aws::String &receiptRuleName,
                                    const Aws::String &receiptRuleSetName,
                                    const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::DeleteReceiptRuleRequest deleteReceiptRuleRequest;

    deleteReceiptRuleRequest.SetRuleName(receiptRuleName);
    deleteReceiptRuleRequest.SetRuleSetName(receiptRuleSetName);

    Aws::SES::Model::DeleteReceiptRuleOutcome outcome = sesClient.DeleteReceiptRule(
            deleteReceiptRuleRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted receipt rule." << std::endl;
    }
```

```
    else {
        std::cout << "Error deleting receipt rule. " <<
 outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DeleteReceiptRule in *AWS SDK for C++ API Reference*.

`DeleteReceiptRuleSet`

The following code example shows how to use `DeleteReceiptRuleSet`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Delete an Amazon Simple Email Service (Amazon SES) receipt rule set.
/*!
  \param receiptRuleSetName: The name for the receipt rule set.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::deleteReceiptRuleSet(const Aws::String &receiptRuleSetName,
                                       const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::DeleteReceiptRuleSetRequest deleteReceiptRuleSetRequest;

    deleteReceiptRuleSetRequest.SetRuleSetName(receiptRuleSetName);

    Aws::SES::Model::DeleteReceiptRuleSetOutcome outcome =
 sesClient.DeleteReceiptRuleSet(
```

```
            deleteReceiptRuleSetRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted receipt rule set." << std::endl;
    }

    else {
        std::cerr << "Error deleting receipt rule set. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DeleteReceiptRuleSet in *AWS SDK for C++ API Reference*.

`DeleteTemplate`

The following code example shows how to use `DeleteTemplate`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Delete an Amazon Simple Email Service (Amazon SES) template.
/*!
  \param templateName: The name for the template.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::deleteTemplate(const Aws::String &templateName,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::DeleteTemplateRequest deleteTemplateRequest;
```

```
    deleteTemplateRequest.SetTemplateName(templateName);

    Aws::SES::Model::DeleteTemplateOutcome outcome = sesClient.DeleteTemplate(
            deleteTemplateRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted template." << std::endl;
    }
    else {
        std::cerr << "Error deleting template. " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DeleteTemplate in *AWS SDK for C++ API Reference*.

`GetTemplate`

The following code example shows how to use `GetTemplate`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Get a template's attributes.
/*!
  \param templateName: The name for the template.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::getTemplate(const Aws::String &templateName,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
```

```
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::GetTemplateRequest getTemplateRequest;

    getTemplateRequest.SetTemplateName(templateName);

    Aws::SES::Model::GetTemplateOutcome outcome = sesClient.GetTemplate(
            getTemplateRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully got template." << std::endl;
    }

    else {
        std::cerr << "Error getting template. " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see GetTemplate in *AWS SDK for C++ API Reference*.

`ListIdentities`

The following code example shows how to use `ListIdentities`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! List the identities associated with this account.
/*!
  \param identityType: The identity type enum. "NOT_SET" is a valid option.
  \param identities; A vector to receive the retrieved identities.
  \param clientConfiguration: AWS client configuration.
```

```
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::listIdentities(Aws::SES::Model::IdentityType identityType,
                                 Aws::Vector<Aws::String> &identities,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::ListIdentitiesRequest listIdentitiesRequest;

    if (identityType != Aws::SES::Model::IdentityType::NOT_SET) {
        listIdentitiesRequest.SetIdentityType(identityType);
    }

    Aws::String nextToken; // Used for paginated results.
    do {
        if (!nextToken.empty()) {
            listIdentitiesRequest.SetNextToken(nextToken);
        }
        Aws::SES::Model::ListIdentitiesOutcome outcome = sesClient.ListIdentities(
                listIdentitiesRequest);

        if (outcome.IsSuccess()) {
            const auto &retrievedIdentities = outcome.GetResult().GetIdentities();
            if (!retrievedIdentities.empty()) {
                identities.insert(identities.cend(), retrievedIdentities.cbegin(),
                                  retrievedIdentities.cend());
            }
            nextToken = outcome.GetResult().GetNextToken();
        }
        else {
            std::cout << "Error listing identities. " <<
 outcome.GetError().GetMessage()
                      << std::endl;
            return false;
        }
    } while (!nextToken.empty());

    return true;
}
```

- For API details, see ListIdentities in *AWS SDK for C++ API Reference*.

`ListReceiptFilters`

The following code example shows how to use `ListReceiptFilters`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! List the receipt filters associated with this account.
/*!
  \param filters; A vector of "ReceiptFilter" to receive the retrieved filters.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool
AwsDoc::SES::listReceiptFilters(Aws::Vector<Aws::SES::Model::ReceiptFilter>
 &filters,
                                const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);
    Aws::SES::Model::ListReceiptFiltersRequest listReceiptFiltersRequest;

    Aws::SES::Model::ListReceiptFiltersOutcome outcome =
 sesClient.ListReceiptFilters(
            listReceiptFiltersRequest);
    if (outcome.IsSuccess()) {
        auto &retrievedFilters = outcome.GetResult().GetFilters();
        if (!retrievedFilters.empty()) {
            filters.insert(filters.cend(), retrievedFilters.cbegin(),
                           retrievedFilters.cend());
        }
    }
    else {
        std::cerr << "Error retrieving IP address filters: "
                  << outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see ListReceiptFilters in *AWS SDK for C++ API Reference*.

`SendEmail`

The following code example shows how to use `SendEmail`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Send an email to a list of recipients.
/*!
  \param recipients; Vector of recipient email addresses.
  \param subject: Email subject.
  \param htmlBody: Email body as HTML. At least one body data is required.
  \param textBody: Email body as plain text. At least one body data is required.
  \param senderEmailAddress: Email address of sender. Ignored if empty string.
  \param ccAddresses: Vector of cc addresses. Ignored if empty.
  \param replyToAddress: Reply to email address. Ignored if empty string.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::sendEmail(const Aws::Vector<Aws::String> &recipients,
                            const Aws::String &subject,
                            const Aws::String &htmlBody,
                            const Aws::String &textBody,
                            const Aws::String &senderEmailAddress,
                            const Aws::Vector<Aws::String> &ccAddresses,
                            const Aws::String &replyToAddress,
                            const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::Destination destination;
    if (!ccAddresses.empty()) {
        destination.WithCcAddresses(ccAddresses);
```

```
    }
    if (!recipients.empty()) {
        destination.WithToAddresses(recipients);
    }

    Aws::SES::Model::Body message_body;
    if (!htmlBody.empty()) {
        message_body.SetHtml(
                Aws::SES::Model::Content().WithCharset("UTF-8").WithData(htmlBody));
    }

    if (!textBody.empty()) {
        message_body.SetText(
                Aws::SES::Model::Content().WithCharset("UTF-8").WithData(textBody));
    }

    Aws::SES::Model::Message message;
    message.SetBody(message_body);
    message.SetSubject(
            Aws::SES::Model::Content().WithCharset("UTF-8").WithData(subject));

    Aws::SES::Model::SendEmailRequest sendEmailRequest;
    sendEmailRequest.SetDestination(destination);
    sendEmailRequest.SetMessage(message);
    if (!senderEmailAddress.empty()) {
        sendEmailRequest.SetSource(senderEmailAddress);
    }
    if (!replyToAddress.empty()) {
        sendEmailRequest.AddReplyToAddresses(replyToAddress);
    }

    auto outcome = sesClient.SendEmail(sendEmailRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully sent message with ID "
                  << outcome.GetResult().GetMessageId()
                  << "." << std::endl;
    }
    else {
        std::cerr << "Error sending message. " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
```

```
}
```

- For API details, see SendEmail in *AWS SDK for C++ API Reference*.

`SendTemplatedEmail`

The following code example shows how to use `SendTemplatedEmail`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Send a templated email to a list of recipients.
/*!
  \param recipients; Vector of recipient email addresses.
  \param templateName: The name of the template to use.
  \param templateData: Map of key-value pairs for replacing text in template.
  \param senderEmailAddress: Email address of sender. Ignored if empty string.
  \param ccAddresses: Vector of cc addresses. Ignored if empty.
  \param replyToAddress: Reply to email address. Ignored if empty string.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::sendTemplatedEmail(const Aws::Vector<Aws::String> &recipients,
                                     const Aws::String &templateName,
                                     const Aws::Map<Aws::String, Aws::String>
 &templateData,
                                     const Aws::String &senderEmailAddress,
                                     const Aws::Vector<Aws::String> &ccAddresses,
                                     const Aws::String &replyToAddress,
                                     const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::Destination destination;
    if (!ccAddresses.empty()) {
        destination.WithCcAddresses(ccAddresses);
```

```
    }
    if (!recipients.empty()) {
        destination.WithToAddresses(recipients);
    }

    Aws::SES::Model::SendTemplatedEmailRequest sendTemplatedEmailRequest;
    sendTemplatedEmailRequest.SetDestination(destination);
    sendTemplatedEmailRequest.SetTemplate(templateName);

    std::ostringstream templateDataStream;
    templateDataStream << "{";
    size_t dataCount = 0;
    for (auto &pair: templateData) {
        templateDataStream << "\"" << pair.first << "\":\"" << pair.second << "\"";
        dataCount++;
        if (dataCount < templateData.size()) {
            templateDataStream << ",";
        }
    }
    templateDataStream << "}";

    sendTemplatedEmailRequest.SetTemplateData(templateDataStream.str());

    if (!senderEmailAddress.empty()) {
        sendTemplatedEmailRequest.SetSource(senderEmailAddress);
    }
    if (!replyToAddress.empty()) {
        sendTemplatedEmailRequest.AddReplyToAddresses(replyToAddress);
    }

    auto outcome = sesClient.SendTemplatedEmail(sendTemplatedEmailRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully sent templated message with ID "
                  << outcome.GetResult().GetMessageId()
                  << "." << std::endl;
    }
    else {
        std::cerr << "Error sending templated message. "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
```

```
}
```

- For API details, see SendTemplatedEmail in *AWS SDK for C++ API Reference*.

`UpdateTemplate`

The following code example shows how to use `UpdateTemplate`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Update an Amazon Simple Email Service (Amazon SES) template.
/*!
  \param templateName: The name of the template.
  \param htmlPart: The HTML body of the email.
  \param subjectPart: The subject line of the email.
  \param textPart: The plain text version of the email.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::updateTemplate(const Aws::String &templateName,
                                 const Aws::String &htmlPart,
                                 const Aws::String &subjectPart,
                                 const Aws::String &textPart,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SES::SESClient sesClient(clientConfiguration);

    Aws::SES::Model::Template templateValues;

    templateValues.SetTemplateName(templateName);
    templateValues.SetSubjectPart(subjectPart);
    templateValues.SetHtmlPart(htmlPart);
    templateValues.SetTextPart(textPart);

    Aws::SES::Model::UpdateTemplateRequest updateTemplateRequest;
```

```
    updateTemplateRequest.SetTemplate(templateValues);

    Aws::SES::Model::UpdateTemplateOutcome outcome =
 sesClient.UpdateTemplate(updateTemplateRequest);

    if (outcome.IsSuccess()) {
        std::cout << "Successfully updated template." << std::endl;
    } else {
        std::cerr << "Error updating template. " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see UpdateTemplate in *AWS SDK for C++ API Reference*.

`VerifyEmailIdentity`

The following code example shows how to use `VerifyEmailIdentity`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Add an email address to the list of identities associated with this account and
//! initiate verification.
/*!
  \param emailAddress; The email address to add.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SES::verifyEmailIdentity(const Aws::String &emailAddress,
                          const Aws::Client::ClientConfiguration
 &clientConfiguration)
{
    Aws::SES::SESClient sesClient(clientConfiguration);
```

```
    Aws::SES::Model::VerifyEmailIdentityRequest verifyEmailIdentityRequest;

    verifyEmailIdentityRequest.SetEmailAddress(emailAddress);

    Aws::SES::Model::VerifyEmailIdentityOutcome outcome =
 sesClient.VerifyEmailIdentity(verifyEmailIdentityRequest);

    if (outcome.IsSuccess())
    {
        std::cout << "Email verification initiated." << std::endl;
    }

    else
    {
        std::cerr << "Error initiating email verification. " <<
 outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see VerifyEmailIdentity in *AWS SDK for C++ API Reference*.

Scenarios

Create an Aurora Serverless work item tracker

The following code example shows how to create a web application that tracks work items in an Amazon Aurora Serverless database and uses Amazon Simple Email Service (Amazon SES) to send reports.

SDK for C++

Shows how to create a web application that tracks and reports on work items stored in an Amazon Aurora Serverless database.

For complete source code and instructions on how to set up a C++ REST API that queries Amazon Aurora Serverless data and for use by a React application, see the full example on GitHub.

Services used in this example

- Aurora
- Amazon RDS
- Amazon RDS Data Service
- Amazon SES

Amazon SNS examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with Amazon SNS.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Scenarios are code examples that show you how to accomplish specific tasks by calling multiple functions within a service or combined with other AWS services.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Get started
- Actions
- Scenarios

Get started

Hello Amazon SNS

The following code example shows how to get started using Amazon SNS.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Code for the CMakeLists.txt CMake file.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS sns)

# Set this project's name.
project("hello_sns")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if (WINDOWS_BUILD AND AWSSDK_INSTALL_AS_SHARED_LIBS)
    # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

    # set(BIN_SUB_DIR "/Debug") # If you are building from the command line you may
 need to uncomment this
    # and set the proper subdirectory to the executables' location.

    AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif ()

add_executable(${PROJECT_NAME}
        hello_sns.cpp)

target_link_libraries(${PROJECT_NAME}
```

```
        ${AWSSDK_LINK_LIBRARIES})
```

Code for the hello_sns.cpp source file.

```
#include <aws/core/Aws.h>
#include <aws/sns/SNSClient.h>
#include <aws/sns/model/ListTopicsRequest.h>
#include <iostream>

/*
 *  A "Hello SNS" starter application which initializes an Amazon Simple
 Notification
 *  Service (Amazon SNS) client and lists the SNS topics in the current account.
 *
 *  main function
 *
 *  Usage: 'hello_sns'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::SNS::SNSClient snsClient(clientConfig);

        Aws::Vector<Aws::SNS::Model::Topic> allTopics;
        Aws::String nextToken; // Next token is used to handle a paginated response.
        do {
            Aws::SNS::Model::ListTopicsRequest request;

            if (!nextToken.empty()) {
                request.SetNextToken(nextToken);
            }

            const Aws::SNS::Model::ListTopicsOutcome outcome = snsClient.ListTopics(
```

```
                    request);

            if (outcome.IsSuccess()) {
                const Aws::Vector<Aws::SNS::Model::Topic> &paginatedTopics =
                        outcome.GetResult().GetTopics();
                if (!paginatedTopics.empty()) {
                    allTopics.insert(allTopics.cend(), paginatedTopics.cbegin(),
                                     paginatedTopics.cend());
                }
            }
            else {
                std::cerr << "Error listing topics " <<
 outcome.GetError().GetMessage()
                          << std::endl;
                return 1;
            }

            nextToken = outcome.GetResult().GetNextToken();
        } while (!nextToken.empty());

        std::cout << "Hello Amazon SNS! You have " << allTopics.size() << " topic"
                  << (allTopics.size() == 1 ? "" : "s") << " in your account."
                  << std::endl;

        if (!allTopics.empty()) {
            std::cout << "Here are your topic ARNs." << std::endl;
            for (const Aws::SNS::Model::Topic &topic: allTopics) {
                std::cout << "  * " << topic.GetTopicArn() << std::endl;
            }
        }
    }


    Aws::ShutdownAPI(options); // Should only be called once.
    return 0;
}
```

- For API details, see ListTopics in *AWS SDK for C++ API Reference*.

Actions

`CreateTopic`

The following code example shows how to use `CreateTopic`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Create an Amazon Simple Notification Service (Amazon SNS) topic.
/*!
  \param topicName: An Amazon SNS topic name.
  \param topicARNResult: String to return the Amazon Resource Name (ARN) for the
 topic.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::createTopic(const Aws::String &topicName,
                              Aws::String &topicARNResult,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::CreateTopicRequest request;
    request.SetName(topicName);

    const Aws::SNS::Model::CreateTopicOutcome outcome =
 snsClient.CreateTopic(request);

    if (outcome.IsSuccess()) {
        topicARNResult = outcome.GetResult().GetTopicArn();
        std::cout << "Successfully created an Amazon SNS topic " << topicName
                  << " with topic ARN '" << topicARNResult
                  << "'." << std::endl;

    }
    else {
```

```
        std::cerr << "Error creating topic " << topicName << ":" <<
                  outcome.GetError().GetMessage() << std::endl;
        topicARNResult.clear();
    }

    return outcome.IsSuccess();
}
```

- For API details, see CreateTopic in *AWS SDK for C++ API Reference*.

`DeleteTopic`

The following code example shows how to use `DeleteTopic`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Delete an Amazon Simple Notification Service (Amazon SNS) topic.
/*!
  \param topicARN: The Amazon Resource Name (ARN) for an Amazon SNS topic.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::deleteTopic(const Aws::String &topicARN,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::DeleteTopicRequest request;
    request.SetTopicArn(topicARN);

    const Aws::SNS::Model::DeleteTopicOutcome outcome =
 snsClient.DeleteTopic(request);

    if (outcome.IsSuccess()) {
```

```
        std::cout << "Successfully deleted the Amazon SNS topic " << topicARN <<
 std::endl;
    }
    else {
        std::cerr << "Error deleting topic " << topicARN << ":" <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DeleteTopic in *AWS SDK for C++ API Reference*.

`GetSMSAttributes`

The following code example shows how to use `GetSMSAttributes`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Retrieve the default settings for sending SMS messages from your AWS account by
 using
//! Amazon Simple Notification Service (Amazon SNS).
/*!
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool
AwsDoc::SNS::getSMSType(const Aws::Client::ClientConfiguration &clientConfiguration)
 {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::GetSMSAttributesRequest request;
    //Set the request to only retrieve the DefaultSMSType setting.
    //Without the following line, GetSMSAttributes would retrieve all settings.
    request.AddAttributes("DefaultSMSType");
```

```
    const Aws::SNS::Model::GetSMSAttributesOutcome outcome =
snsClient.GetSMSAttributes(
            request);

    if (outcome.IsSuccess()) {
        const Aws::Map<Aws::String, Aws::String> attributes =
                outcome.GetResult().GetAttributes();
        if (!attributes.empty()) {
            for (auto const &att: attributes) {
                std::cout << att.first << ":  " << att.second << std::endl;
            }
        }
        else {
            std::cout
                    << "AwsDoc::SNS::getSMSType - an empty map of attributes was
retrieved."
                    << std::endl;
        }
    }
    else {
        std::cerr << "Error while getting SMS Type: '"
                  << outcome.GetError().GetMessage()
                  << "'" << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see GetSMSAttributes in *AWS SDK for C++ API Reference*.

`GetTopicAttributes`

The following code example shows how to use `GetTopicAttributes`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Retrieve the properties of an Amazon Simple Notification Service (Amazon SNS)
 topic.
/*!
  \param topicARN: The Amazon Resource Name (ARN) for an Amazon SNS topic.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::getTopicAttributes(const Aws::String &topicARN,
                                     const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);
    Aws::SNS::Model::GetTopicAttributesRequest request;
    request.SetTopicArn(topicARN);

    const Aws::SNS::Model::GetTopicAttributesOutcome outcome =
 snsClient.GetTopicAttributes(
            request);

    if (outcome.IsSuccess()) {
        std::cout << "Topic Attributes:" << std::endl;
        for (auto const &attribute: outcome.GetResult().GetAttributes()) {
            std::cout << "  * " << attribute.first << " : " << attribute.second
                      << std::endl;
        }
    }
    else {
        std::cerr << "Error while getting Topic attributes "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see GetTopicAttributes in *AWS SDK for C++ API Reference*.

`ListSubscriptions`

The following code example shows how to use `ListSubscriptions`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Retrieve a list of Amazon Simple Notification Service (Amazon SNS)
 subscriptions.
/*!
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::listSubscriptions(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::String nextToken; // Next token is used to handle a paginated response.
    bool result = true;
    Aws::Vector<Aws::SNS::Model::Subscription> subscriptions;
    do {
        Aws::SNS::Model::ListSubscriptionsRequest request;

        if (!nextToken.empty()) {
            request.SetNextToken(nextToken);
        }

        const Aws::SNS::Model::ListSubscriptionsOutcome outcome =
 snsClient.ListSubscriptions(
                request);

        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::SNS::Model::Subscription> &newSubscriptions =
                    outcome.GetResult().GetSubscriptions();
            subscriptions.insert(subscriptions.cend(), newSubscriptions.begin(),
                                 newSubscriptions.end());
        }
        else {
            std::cerr << "Error listing subscriptions "
                      << outcome.GetError().GetMessage()
                      <<
```

```
                        std::endl;
            result = false;
            break;
        }

        nextToken = outcome.GetResult().GetNextToken();
    } while (!nextToken.empty());

    if (result) {
        if (subscriptions.empty()) {
            std::cout << "No subscriptions found" << std::endl;
        }
        else {
            std::cout << "Subscriptions list:" << std::endl;
            for (auto const &subscription: subscriptions) {
                std::cout << "  * " << subscription.GetSubscriptionArn() <<
 std::endl;
            }
        }
    }
    return result;
}
```

- For API details, see ListSubscriptions in *AWS SDK for C++ API Reference*.

`ListTopics`

The following code example shows how to use `ListTopics`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Retrieve a list of Amazon Simple Notification Service (Amazon SNS) topics.
/*!
  \param clientConfiguration: AWS client configuration.
```

```
  \return bool: Function succeeded.
 */
bool
AwsDoc::SNS::listTopics(const Aws::Client::ClientConfiguration &clientConfiguration)
 {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::String nextToken; // Next token is used to handle a paginated response.
    bool result = true;
    do {
        Aws::SNS::Model::ListTopicsRequest request;

        if (!nextToken.empty()) {
            request.SetNextToken(nextToken);
        }

        const Aws::SNS::Model::ListTopicsOutcome outcome = snsClient.ListTopics(
                request);

        if (outcome.IsSuccess()) {
            std::cout << "Topics list:" << std::endl;
            for (auto const &topic: outcome.GetResult().GetTopics()) {
                std::cout << "  * " << topic.GetTopicArn() << std::endl;
            }
        }
        else {
            std::cerr << "Error listing topics " << outcome.GetError().GetMessage()
 <<
                      std::endl;
            result = false;
            break;
        }

        nextToken = outcome.GetResult().GetNextToken();
    } while (!nextToken.empty());

    return result;
}
```

- For API details, see ListTopics in *AWS SDK for C++ API Reference*.

`Publish`

The following code example shows how to use `Publish`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Send a message to an Amazon Simple Notification Service (Amazon SNS) topic.
/*!
  \param message: The message to publish.
  \param topicARN: The Amazon Resource Name (ARN) for an Amazon SNS topic.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::publishToTopic(const Aws::String &message,
                                 const Aws::String &topicARN,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::PublishRequest request;
    request.SetMessage(message);
    request.SetTopicArn(topicARN);

    const Aws::SNS::Model::PublishOutcome outcome = snsClient.Publish(request);

    if (outcome.IsSuccess()) {
        std::cout << "Message published successfully with id '"
                  << outcome.GetResult().GetMessageId() << "'." << std::endl;
    }
    else {
        std::cerr << "Error while publishing message "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

Publish a message with an attribute.

```
       static const Aws::String TONE_ATTRIBUTE("tone");
       static const Aws::Vector<Aws::String> TONES = {"cheerful", "funny",
"serious",
                                                      "sincere"};

       Aws::Client::ClientConfiguration clientConfig;
       // Optional: Set to the AWS Region (overrides config file).
       // clientConfig.region = "us-east-1";

   Aws::SNS::SNSClient snsClient(clientConfiguration);

       Aws::SNS::Model::PublishRequest request;
       request.SetTopicArn(topicARN);
       Aws::String message = askQuestion("Enter a message text to publish.  ");
       request.SetMessage(message);

       if (filteringMessages && askYesNoQuestion(
               "Add an attribute to this message? (y/n) ")) {
           for (size_t i = 0; i < TONES.size(); ++i) {
               std::cout << "  " << (i + 1) << ". " << TONES[i] << std::endl;
           }
           int selection = askQuestionForIntRange(
                   "Enter a number for an attribute. ",
                   1, static_cast<int>(TONES.size()));
           Aws::SNS::Model::MessageAttributeValue messageAttributeValue;
           messageAttributeValue.SetDataType("String");
           messageAttributeValue.SetStringValue(TONES[selection - 1]);
           request.AddMessageAttributes(TONE_ATTRIBUTE, messageAttributeValue);
       }

       Aws::SNS::Model::PublishOutcome outcome = snsClient.Publish(request);

       if (outcome.IsSuccess()) {
           std::cout << "Your message was successfully published." << std::endl;
       }
       else {
           std::cerr << "Error with TopicsAndQueues::Publish. "
                     << outcome.GetError().GetMessage()
                     << std::endl;
```

```
            cleanUp(topicARN,
                    queueURLS,
                    subscriptionARNS,
                    snsClient,
                    sqsClient);

            return false;
        }
```

- For API details, see Publish in *AWS SDK for C++ API Reference*.

`SetSMSAttributes`

The following code example shows how to use `SetSMSAttributes`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

How to use Amazon SNS to set the DefaultSMSType attribute.

```
//! Set the default settings for sending SMS messages.
/*!
  \param smsType: The type of SMS message that you will send by default.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::setSMSType(const Aws::String &smsType,
                             const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::SetSMSAttributesRequest request;
    request.AddAttributes("DefaultSMSType", smsType);
```

```
    const Aws::SNS::Model::SetSMSAttributesOutcome outcome =
 snsClient.SetSMSAttributes(
            request);

    if (outcome.IsSuccess()) {
        std::cout << "SMS Type set successfully " << std::endl;
    }
    else {
        std::cerr << "Error while setting SMS Type: '"
                  << outcome.GetError().GetMessage()
                  << "'" << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see SetSMSAttributes in *AWS SDK for C++ API Reference*.

`Subscribe`

The following code example shows how to use `Subscribe`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Subscribe an email address to a topic.

```
//! Subscribe to an Amazon Simple Notification Service (Amazon SNS) topic with
 delivery to an email address.
/*!
  \param topicARN: An SNS topic Amazon Resource Name (ARN).
  \param emailAddress: An email address.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::subscribeEmail(const Aws::String &topicARN,
```

```
                                const Aws::String &emailAddress,
                                const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::SubscribeRequest request;
    request.SetTopicArn(topicARN);
    request.SetProtocol("email");
    request.SetEndpoint(emailAddress);

    const Aws::SNS::Model::SubscribeOutcome outcome = snsClient.Subscribe(request);

    if (outcome.IsSuccess()) {
        std::cout << "Subscribed successfully." << std::endl;
        std::cout << "Subscription ARN '" <<
 outcome.GetResult().GetSubscriptionArn()
                  << "'." << std::endl;
    }
    else {
        std::cerr << "Error while subscribing " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

Subscribe a mobile application to a topic.

```
//! Subscribe to an Amazon Simple Notification Service (Amazon SNS) topic with
 delivery to a mobile app.
/*!
  \param topicARN: The Amazon Resource Name (ARN) for an Amazon SNS topic.
  \param endpointARN: The ARN for a mobile app or device endpoint.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool
AwsDoc::SNS::subscribeApp(const Aws::String &topicARN,
                          const Aws::String &endpointARN,
                          const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);
```

```
    Aws::SNS::Model::SubscribeRequest request;
    request.SetTopicArn(topicARN);
    request.SetProtocol("application");
    request.SetEndpoint(endpointARN);

    const Aws::SNS::Model::SubscribeOutcome outcome = snsClient.Subscribe(request);

    if (outcome.IsSuccess()) {
        std::cout << "Subscribed successfully." << std::endl;
        std::cout << "Subscription ARN '" <<
 outcome.GetResult().GetSubscriptionArn()
                  << "'." << std::endl;
    }
    else {
        std::cerr << "Error while subscribing " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

Subscribe a Lambda function to a topic.

```
//! Subscribe to an Amazon Simple Notification Service (Amazon SNS) topic with
 delivery to an AWS Lambda function.
/*!
  \param topicARN: The Amazon Resource Name (ARN) for an Amazon SNS topic.
  \param lambdaFunctionARN: The ARN for an AWS Lambda function.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::subscribeLambda(const Aws::String &topicARN,
                                  const Aws::String &lambdaFunctionARN,
                                  const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::SubscribeRequest request;
    request.SetTopicArn(topicARN);
    request.SetProtocol("lambda");
```

```
    request.SetEndpoint(lambdaFunctionARN);

    const Aws::SNS::Model::SubscribeOutcome outcome = snsClient.Subscribe(request);

    if (outcome.IsSuccess()) {
        std::cout << "Subscribed successfully." << std::endl;
        std::cout << "Subscription ARN '" <<
 outcome.GetResult().GetSubscriptionArn()
                  << "'." << std::endl;
    }
    else {
        std::cerr << "Error while subscribing " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

Subscribe an SQS queue to a topic.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::SNS::SNSClient snsClient(clientConfiguration);

            Aws::SNS::Model::SubscribeRequest request;
            request.SetTopicArn(topicARN);
            request.SetProtocol("sqs");
            request.SetEndpoint(queueARN);

            Aws::SNS::Model::SubscribeOutcome outcome =
 snsClient.Subscribe(request);

            if (outcome.IsSuccess()) {
                Aws::String subscriptionARN =
 outcome.GetResult().GetSubscriptionArn();
                std::cout << "The queue '" << queueName
                          << "' has been subscribed to the topic '"
                          << "'" << topicName << "'" << std::endl;
                std::cout << "with the subscription ARN '" << subscriptionARN << "."
                          << std::endl;
```

```
            subscriptionARNS.push_back(subscriptionARN);
        }
        else {
            std::cerr << "Error with TopicsAndQueues::Subscribe. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

            cleanUp(topicARN,
                    queueURLS,
                    subscriptionARNS,
                    snsClient,
                    sqsClient);

            return false;
        }
```

Subscribe with a filter to a topic.

```
       static const Aws::String TONE_ATTRIBUTE("tone");
       static const Aws::Vector<Aws::String> TONES = {"cheerful", "funny",
"serious",
                                                      "sincere"};

       Aws::Client::ClientConfiguration clientConfig;
       // Optional: Set to the AWS Region (overrides config file).
       // clientConfig.region = "us-east-1";

   Aws::SNS::SNSClient snsClient(clientConfiguration);

           Aws::SNS::Model::SubscribeRequest request;
           request.SetTopicArn(topicARN);
           request.SetProtocol("sqs");
           request.SetEndpoint(queueARN);
           if (isFifoTopic) {
               if (first) {
                   std::cout << "Subscriptions to a FIFO topic can have filters."
                             << std::endl;
                   std::cout
                           << "If you add a filter to this subscription, then only
the filtered messages "
                           << "will be received in the queue." << std::endl;
                   std::cout << "For information about message filtering, "
```

```
                                << "see https://docs.aws.amazon.com/sns/latest/dg/sns-
message-filtering.html"
                                << std::endl;
                    std::cout << "For this example, you can filter messages by a \""
                                << TONE_ATTRIBUTE << "\" attribute." << std::endl;
                }

                std::ostringstream ostringstream;
                ostringstream << "Filter messages for \"" << queueName
                              << "\"'s subscription to the topic \""
                              << topicName << "\"?  (y/n)";

                // Add filter if user answers yes.
                if (askYesNoQuestion(ostringstream.str())) {
                    Aws::String jsonPolicy = getFilterPolicyFromUser();
                    if (!jsonPolicy.empty()) {
                        filteringMessages = true;

                        std::cout << "This is the filter policy for this
 subscription."
                                  << std::endl;
                        std::cout << jsonPolicy << std::endl;

                        request.AddAttributes("FilterPolicy", jsonPolicy);
                    }
                    else {
                        std::cout
                                << "Because you did not select any attributes, no
 filter "
                                << "will be added to this subscription." <<
 std::endl;
                    }
                }
            }  // if (isFifoTopic)
            Aws::SNS::Model::SubscribeOutcome outcome =
 snsClient.Subscribe(request);

            if (outcome.IsSuccess()) {
                Aws::String subscriptionARN =
 outcome.GetResult().GetSubscriptionArn();
                std::cout << "The queue '" << queueName
                          << "' has been subscribed to the topic '"
                          << "'" << topicName << "'" << std::endl;
                std::cout << "with the subscription ARN '" << subscriptionARN << "."
```

```
                          << std::endl;
                subscriptionARNS.push_back(subscriptionARN);
            }
            else {
                std::cerr << "Error with TopicsAndQueues::Subscribe. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }

//! Routine that lets the user select attributes for a subscription filter policy.
/*!
 \sa getFilterPolicyFromUser()
 \return Aws::String: The filter policy as JSON.
 */
Aws::String AwsDoc::TopicsAndQueues::getFilterPolicyFromUser() {
    std::cout
            << "You can filter messages by one or more of the following \""
            << TONE_ATTRIBUTE << "\" attributes." << std::endl;

    std::vector<Aws::String> filterSelections;
    int selection;
    do {
        for (size_t j = 0; j < TONES.size(); ++j) {
            std::cout << "  " << (j + 1) << ". " << TONES[j]
                      << std::endl;
        }
        selection = askQuestionForIntRange(
                "Enter a number (or enter zero to stop adding more). ",
                0, static_cast<int>(TONES.size()));

        if (selection != 0) {
            const Aws::String &selectedTone(TONES[selection - 1]);
            // Add the tone to the selection if it is not already added.
            if (std::find(filterSelections.begin(),
                          filterSelections.end(),
                          selectedTone)
```

```
                == filterSelections.end()) {
                filterSelections.push_back(selectedTone);
            }
        }
    } while (selection != 0);

    Aws::String result;
    if (!filterSelections.empty()) {
        std::ostringstream jsonPolicyStream;
        jsonPolicyStream << "{ \"" << TONE_ATTRIBUTE << "\": [";


        for (size_t j = 0; j < filterSelections.size(); ++j) {
            jsonPolicyStream << "\"" << filterSelections[j] << "\"";
            if (j < filterSelections.size() - 1) {
                jsonPolicyStream << ",";
            }
        }
        jsonPolicyStream << "] }";

        result = jsonPolicyStream.str();
    }

    return result;
}
```

- For API details, see Subscribe in *AWS SDK for C++ API Reference*.

`Unsubscribe`

The following code example shows how to use `Unsubscribe`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
//! Delete a subscription to an Amazon Simple Notification Service (Amazon SNS)
 topic.
/*!
  \param subscriptionARN: The Amazon Resource Name (ARN) for an Amazon SNS topic
 subscription.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::unsubscribe(const Aws::String &subscriptionARN,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::UnsubscribeRequest request;
    request.SetSubscriptionArn(subscriptionARN);

    const Aws::SNS::Model::UnsubscribeOutcome outcome =
 snsClient.Unsubscribe(request);

    if (outcome.IsSuccess()) {
        std::cout << "Unsubscribed successfully " << std::endl;
    }
    else {
        std::cerr << "Error while unsubscribing " << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see Unsubscribe in *AWS SDK for C++ API Reference*.

Scenarios

Create a serverless application to manage photos

The following code example shows how to create a serverless application that lets users manage photos using labels.

SDK for C++

Shows how to develop a photo asset management application that detects labels in images using Amazon Rekognition and stores them for later retrieval.

For complete source code and instructions on how to set up and run, see the full example on GitHub.

For a deep dive into the origin of this example see the post on AWS Community.

Services used in this example

- API Gateway
- DynamoDB
- Lambda
- Amazon Rekognition
- Amazon S3
- Amazon SNS

Publish an SMS text message

The following code example shows how to publish SMS messages using Amazon SNS.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
/**
 * Publish SMS: use Amazon Simple Notification Service (Amazon SNS) to send an SMS
 text message to a phone number.
 * Note: This requires additional AWS configuration prior to running example.
 *
 *  NOTE: When you start using Amazon SNS to send SMS messages, your AWS account is
 in the SMS sandbox and you can only
 *  use verified destination phone numbers. See https://docs.aws.amazon.com/sns/
latest/dg/sns-sms-sandbox.html.
```

```
 *  NOTE: If destination is in the US, you also have an additional restriction that
 you have use a dedicated
 *  origination ID (phone number). You can request an origination number using
 Amazon Pinpoint for a fee.
 *  See https://aws.amazon.com/blogs/compute/provisioning-and-using-10dlc-
origination-numbers-with-amazon-sns/
 *  for more information.
 *
 *  <phone_number_value> input parameter uses E.164 format.
 *  For example, in United States, this input value should be of the form:
 +12223334444
 */

//! Send an SMS text message to a phone number.
/*!
  \param message: The message to publish.
  \param phoneNumber: The phone number of the recipient in E.164 format.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SNS::publishSms(const Aws::String &message,
                             const Aws::String &phoneNumber,
                             const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SNS::SNSClient snsClient(clientConfiguration);

    Aws::SNS::Model::PublishRequest request;
    request.SetMessage(message);
    request.SetPhoneNumber(phoneNumber);

    const Aws::SNS::Model::PublishOutcome outcome = snsClient.Publish(request);

    if (outcome.IsSuccess()) {
        std::cout << "Message published successfully with message id, '"
                  << outcome.GetResult().GetMessageId() << "'."
                  << std::endl;
    }
    else {
        std::cerr << "Error while publishing message "
                  << outcome.GetError().GetMessage()
                  << std::endl;
    }

    return outcome.IsSuccess();
```

```
}
```

- For API details, see Publish in *AWS SDK for C++ API Reference*.

Publish messages to queues

The following code example shows how to:

- Create topic (FIFO or non-FIFO).
- Subscribe several queues to the topic with an option to apply a filter.
- Publish messages to the topic.
- Poll the queues for messages received.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Workflow for messaging with topics and queues using Amazon SNS and Amazon SQS.
/*!
 \param clientConfig Aws client configuration.
 \return bool: Successful completion.
 */
bool AwsDoc::TopicsAndQueues::messagingWithTopicsAndQueues(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    std::cout << "Welcome to messaging with topics and queues." << std::endl;
    printAsterisksLine();
    std::cout << "In this workflow, you will create an SNS topic and subscribe "
              << NUMBER_OF_QUEUES <<
              " SQS queues to the topic." << std::endl;
    std::cout
```

```
            << "You can select from several options for configuring the topic and
 the subscriptions for the "
            << NUMBER_OF_QUEUES << " queues." << std::endl;
    std::cout << "You can then post to the topic and see the results in the queues."
              << std::endl;

    Aws::SNS::SNSClient snsClient(clientConfiguration);

    printAsterisksLine();

    std::cout << "SNS topics can be configured as FIFO (First-In-First-Out)."
              << std::endl;
    std::cout
            << "FIFO topics deliver messages in order and support deduplication and
 message filtering."
            << std::endl;
    bool isFifoTopic = askYesNoQuestion(
            "Would you like to work with FIFO topics? (y/n) ");

    bool contentBasedDeduplication = false;
    Aws::String topicName;
    if (isFifoTopic) {
        printAsterisksLine();
        std::cout << "Because you have chosen a FIFO topic, deduplication is
 supported."
                  << std::endl;
        std::cout
                << "Deduplication IDs are either set in the message or automatically
 generated "
                << "from content using a hash function." << std::endl;
        std::cout
                << "If a message is successfully published to an SNS FIFO topic, any
 message "
                << "published and determined to have the same deduplication ID, "
                << std::endl;
        std::cout
                << "within the five-minute deduplication interval, is accepted but
 not delivered."
                << std::endl;
        std::cout
                << "For more information about deduplication, "
                << "see https://docs.aws.amazon.com/sns/latest/dg/fifo-message-
dedup.html."
                << std::endl;
```

```
        contentBasedDeduplication = askYesNoQuestion(
                "Use content-based deduplication instead of entering a deduplication
ID? (y/n) ");
    }

    printAsterisksLine();

    Aws::SQS::SQSClient sqsClient(clientConfiguration);
    Aws::Vector<Aws::String> queueURLS;
    Aws::Vector<Aws::String> subscriptionARNS;

    Aws::String topicARN;
    {
        topicName = askQuestion("Enter a name for your SNS topic. ");

        // 1.  Create an Amazon SNS topic, either FIFO or non-FIFO.
        Aws::SNS::Model::CreateTopicRequest request;

        if (isFifoTopic) {
            request.AddAttributes("FifoTopic", "true");
            if (contentBasedDeduplication) {
                request.AddAttributes("ContentBasedDeduplication", "true");
            }
            topicName = topicName + FIFO_SUFFIX;

            std::cout
                    << "Because you have selected a FIFO topic, '.fifo' must be
appended to the topic name."
                    << std::endl;
        }

        request.SetName(topicName);

        Aws::SNS::Model::CreateTopicOutcome outcome =
snsClient.CreateTopic(request);

        if (outcome.IsSuccess()) {
            topicARN = outcome.GetResult().GetTopicArn();
            std::cout << "Your new topic with the name '" << topicName
                      << "' and the topic Amazon Resource Name (ARN) " << std::endl;
            std::cout << "'" << topicARN << "' has been created." << std::endl;

        }
        else {
```

```
            std::cerr << "Error with TopicsAndQueues::CreateTopic. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

            cleanUp(topicARN,
                    queueURLS,
                    subscriptionARNS,
                    snsClient,
                    sqsClient);

            return false;
        }
    }

    printAsterisksLine();

    std::cout << "Now you will create " << NUMBER_OF_QUEUES
              << " SQS queues to subscribe to the topic." << std::endl;
    Aws::Vector<Aws::String> queueNames;
    bool filteringMessages = false;
    bool first = true;
    for (int i = 1; i <= NUMBER_OF_QUEUES; ++i) {
        Aws::String queueURL;
        Aws::String queueName;
        {
            printAsterisksLine();
            std::ostringstream ostringstream;
            ostringstream << "Enter a name for " << (first ? "an" : "the next")
                          << " SQS queue. ";
            queueName = askQuestion(ostringstream.str());

            // 2.  Create an SQS queue.
            Aws::SQS::Model::CreateQueueRequest request;
            if (isFifoTopic) {

request.AddAttributes(Aws::SQS::Model::QueueAttributeName::FifoQueue,
                                      "true");
                queueName = queueName + FIFO_SUFFIX;

                if (first) // Only explain this once.
                {
                    std::cout
                            << "Because you are creating a FIFO SQS queue, '.fifo'
must "
```

```
                        << "be appended to the queue name." << std::endl;
            }
        }

        request.SetQueueName(queueName);
        queueNames.push_back(queueName);

        Aws::SQS::Model::CreateQueueOutcome outcome =
                sqsClient.CreateQueue(request);

        if (outcome.IsSuccess()) {
            queueURL = outcome.GetResult().GetQueueUrl();
            std::cout << "Your new SQS queue with the name '" << queueName
                      << "' and the queue URL " << std::endl;
            std::cout << "'" << queueURL << "' has been created." << std::endl;
        }
        else {
            std::cerr << "Error with SQS::CreateQueue. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

            cleanUp(topicARN,
                    queueURLS,
                    subscriptionARNS,
                    snsClient,
                    sqsClient);

            return false;
        }
    }
    queueURLS.push_back(queueURL);

    if (first) // Only explain this once.
    {
        std::cout
                << "The queue URL is used to retrieve the queue ARN, which is "
                << "used to create a subscription." << std::endl;
    }

    Aws::String queueARN;
    {
        // 3.  Get the SQS queue ARN attribute.
        Aws::SQS::Model::GetQueueAttributesRequest request;
        request.SetQueueUrl(queueURL);
```

```
request.AddAttributeNames(Aws::SQS::Model::QueueAttributeName::QueueArn);

            Aws::SQS::Model::GetQueueAttributesOutcome outcome =
                    sqsClient.GetQueueAttributes(request);

            if (outcome.IsSuccess()) {
                const Aws::Map<Aws::SQS::Model::QueueAttributeName, Aws::String>
&attributes =
                        outcome.GetResult().GetAttributes();
                const auto &iter = attributes.find(
                        Aws::SQS::Model::QueueAttributeName::QueueArn);
                if (iter != attributes.end()) {
                    queueARN = iter->second;
                    std::cout << "The queue ARN '" << queueARN
                              << "' has been retrieved."
                              << std::endl;
                }
                else {
                    std::cerr
                            << "Error ARN attribute not returned by
GetQueueAttribute."
                            << std::endl;

                    cleanUp(topicARN,
                            queueURLS,
                            subscriptionARNS,
                            snsClient,
                            sqsClient);

                    return false;
                }
            }
            else {
                std::cerr << "Error with SQS::GetQueueAttributes. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);
```

```
                return false;
            }
        }

        if (first) {
            std::cout
                    << "An IAM policy must be attached to an SQS queue, enabling it
to receive "
                       "messages from an SNS topic." << std::endl;
        }

        {
            // 4.  Set the SQS queue policy attribute with a policy enabling the
receipt of SNS messages.
            Aws::SQS::Model::SetQueueAttributesRequest request;
            request.SetQueueUrl(queueURL);
            Aws::String policy = createPolicyForQueue(queueARN, topicARN);
            request.AddAttributes(Aws::SQS::Model::QueueAttributeName::Policy,
                                  policy);

            Aws::SQS::Model::SetQueueAttributesOutcome outcome =
                    sqsClient.SetQueueAttributes(request);

            if (outcome.IsSuccess()) {
                std::cout << "The attributes for the queue '" << queueName
                          << "' were successfully updated." << std::endl;
            }
            else {
                std::cerr << "Error with SQS::SetQueueAttributes. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }

        printAsterisksLine();
```

```
        {
            // 5.  Subscribe the SQS queue to the SNS topic.
            Aws::SNS::Model::SubscribeRequest request;
            request.SetTopicArn(topicARN);
            request.SetProtocol("sqs");
            request.SetEndpoint(queueARN);
            if (isFifoTopic) {
                if (first) {
                    std::cout << "Subscriptions to a FIFO topic can have filters."
                              << std::endl;
                    std::cout
                            << "If you add a filter to this subscription, then only
 the filtered messages "
                            << "will be received in the queue." << std::endl;
                    std::cout << "For information about message filtering, "
                              << "see https://docs.aws.amazon.com/sns/latest/dg/sns-
message-filtering.html"
                              << std::endl;
                    std::cout << "For this example, you can filter messages by a \""
                              << TONE_ATTRIBUTE << "\" attribute." << std::endl;
                }

                std::ostringstream ostringstream;
                ostringstream << "Filter messages for \"" << queueName
                              << "\"'s subscription to the topic \""
                              << topicName << "\"?  (y/n)";

                // Add filter if user answers yes.
                if (askYesNoQuestion(ostringstream.str())) {
                    Aws::String jsonPolicy = getFilterPolicyFromUser();
                    if (!jsonPolicy.empty()) {
                        filteringMessages = true;

                        std::cout << "This is the filter policy for this
 subscription."
                                  << std::endl;
                        std::cout << jsonPolicy << std::endl;

                        request.AddAttributes("FilterPolicy", jsonPolicy);
                    }
                    else {
                        std::cout
                                << "Because you did not select any attributes, no
 filter "
```

```
                                << "will be added to this subscription." <<
std::endl;
                    }
                }
            }  // if (isFifoTopic)
            Aws::SNS::Model::SubscribeOutcome outcome =
snsClient.Subscribe(request);

            if (outcome.IsSuccess()) {
                Aws::String subscriptionARN =
outcome.GetResult().GetSubscriptionArn();
                std::cout << "The queue '" << queueName
                          << "' has been subscribed to the topic '"
                          << "'" << topicName << "'" << std::endl;
                std::cout << "with the subscription ARN '" << subscriptionARN << "."
                          << std::endl;
                subscriptionARNS.push_back(subscriptionARN);
            }
            else {
                std::cerr << "Error with TopicsAndQueues::Subscribe. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }

        first = false;
    }

    first = true;
    do {
        printAsterisksLine();

        // 6.  Publish a message to the SNS topic.
        Aws::SNS::Model::PublishRequest request;
        request.SetTopicArn(topicARN);
        Aws::String message = askQuestion("Enter a message text to publish.  ");
```

```
        request.SetMessage(message);
        if (isFifoTopic) {
            if (first) {
                std::cout
                        << "Because you are using a FIFO topic, you must set a
message group ID."
                        << std::endl;
                std::cout
                        << "All messages within the same group will be received in
the "
                        << "order they were published." << std::endl;
            }
            Aws::String messageGroupID = askQuestion(
                    "Enter a message group ID for this message. ");
            request.SetMessageGroupId(messageGroupID);
            if (!contentBasedDeduplication) {
                if (first) {
                    std::cout
                            << "Because you are not using content-based
deduplication, "
                            << "you must enter a deduplication ID." << std::endl;
                }
                Aws::String deduplicationID = askQuestion(
                        "Enter a deduplication ID for this message. ");
                request.SetMessageDeduplicationId(deduplicationID);
            }
        }

        if (filteringMessages && askYesNoQuestion(
                "Add an attribute to this message? (y/n) ")) {
            for (size_t i = 0; i < TONES.size(); ++i) {
                std::cout << "  " << (i + 1) << ". " << TONES[i] << std::endl;
            }
            int selection = askQuestionForIntRange(
                    "Enter a number for an attribute. ",
                    1, static_cast<int>(TONES.size()));
            Aws::SNS::Model::MessageAttributeValue messageAttributeValue;
            messageAttributeValue.SetDataType("String");
            messageAttributeValue.SetStringValue(TONES[selection - 1]);
            request.AddMessageAttributes(TONE_ATTRIBUTE, messageAttributeValue);
        }

        Aws::SNS::Model::PublishOutcome outcome = snsClient.Publish(request);
```

```
        if (outcome.IsSuccess()) {
            std::cout << "Your message was successfully published." << std::endl;
        }
        else {
            std::cerr << "Error with TopicsAndQueues::Publish. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

            cleanUp(topicARN,
                    queueURLS,
                    subscriptionARNS,
                    snsClient,
                    sqsClient);

            return false;
        }

        first = false;
    } while (askYesNoQuestion("Post another message? (y/n) "));

    printAsterisksLine();

    std::cout << "Now the SQS queue will be polled to retrieve the messages."
              << std::endl;
    askQuestion("Press any key to continue...", alwaysTrueTest);

    for (size_t i = 0; i < queueURLS.size(); ++i) {
        // 7.  Poll an SQS queue for its messages.
        std::vector<Aws::String> messages;
        std::vector<Aws::String> receiptHandles;
        while (true) {
            Aws::SQS::Model::ReceiveMessageRequest request;
            request.SetMaxNumberOfMessages(10);
            request.SetQueueUrl(queueURLS[i]);

            // Setting WaitTimeSeconds to non-zero enables long polling.
            // For information about long polling, see
            // https://docs.aws.amazon.com/AWSSimpleQueueService/latest/
SQSDeveloperGuide/sqs-short-and-long-polling.html
            request.SetWaitTimeSeconds(1);
            Aws::SQS::Model::ReceiveMessageOutcome outcome =
                    sqsClient.ReceiveMessage(request);

            if (outcome.IsSuccess()) {
```

```
                const Aws::Vector<Aws::SQS::Model::Message> &newMessages =
outcome.GetResult().GetMessages();
                if (newMessages.empty()) {
                    break;
                }
                else {
                    for (const Aws::SQS::Model::Message &message: newMessages) {
                        messages.push_back(message.GetBody());
                        receiptHandles.push_back(message.GetReceiptHandle());
                    }
                }
            }
            else {
                std::cerr << "Error with SQS::ReceiveMessage. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }

        printAsterisksLine();

        if (messages.empty()) {
            std::cout << "No messages were ";
        }
        else if (messages.size() == 1) {
            std::cout << "One message was ";
        }
        else {
            std::cout << messages.size() << " messages were ";
        }
        std::cout << "received by the queue '" << queueNames[i]
                  << "'." << std::endl;
        for (const Aws::String &message: messages) {
            std::cout << "  Message : '" << message << "'."
                      << std::endl;
        }
```

```
        // 8.  Delete a batch of messages from an SQS queue.
        if (!receiptHandles.empty()) {
            Aws::SQS::Model::DeleteMessageBatchRequest request;
            request.SetQueueUrl(queueURLS[i]);
            int id = 1; // Ids must be unique within a batch delete request.
            for (const Aws::String &receiptHandle: receiptHandles) {
                Aws::SQS::Model::DeleteMessageBatchRequestEntry entry;
                entry.SetId(std::to_string(id));
                ++id;
                entry.SetReceiptHandle(receiptHandle);
                request.AddEntries(entry);
            }

            Aws::SQS::Model::DeleteMessageBatchOutcome outcome =
                    sqsClient.DeleteMessageBatch(request);

            if (outcome.IsSuccess()) {
                std::cout << "The batch deletion of messages was successful."
                          << std::endl;
            }
            else {
                std::cerr << "Error with SQS::DeleteMessageBatch. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }
    }

    return cleanUp(topicARN,
                   queueURLS,
                   subscriptionARNS,
                   snsClient,
                   sqsClient,
                   true); // askUser
}
```

```
bool AwsDoc::TopicsAndQueues::cleanUp(const Aws::String &topicARN,
                                      const Aws::Vector<Aws::String> &queueURLS,
                                      const Aws::Vector<Aws::String>
 &subscriptionARNS,
                                      const Aws::SNS::SNSClient &snsClient,
                                      const Aws::SQS::SQSClient &sqsClient,
                                      bool askUser) {
    bool result = true;
    printAsterisksLine();
    if (!queueURLS.empty() && askUser &&
        askYesNoQuestion("Delete the SQS queues? (y/n) ")) {

        for (const auto &queueURL: queueURLS) {
            // 9.  Delete an SQS queue.
            Aws::SQS::Model::DeleteQueueRequest request;
            request.SetQueueUrl(queueURL);

            Aws::SQS::Model::DeleteQueueOutcome outcome =
                    sqsClient.DeleteQueue(request);

            if (outcome.IsSuccess()) {
                std::cout << "The queue with URL '" << queueURL
                          << "' was successfully deleted." << std::endl;
            }
            else {
                std::cerr << "Error with SQS::DeleteQueue. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
        }

        for (const auto &subscriptionARN: subscriptionARNS) {
            // 10. Unsubscribe an SNS subscription.
            Aws::SNS::Model::UnsubscribeRequest request;
            request.SetSubscriptionArn(subscriptionARN);

            Aws::SNS::Model::UnsubscribeOutcome outcome =
                    snsClient.Unsubscribe(request);

            if (outcome.IsSuccess()) {
                std::cout << "Unsubscribe of subscription ARN '" << subscriptionARN
                          << "' was successful." << std::endl;
```

```
            }
            else {
                std::cerr << "Error with TopicsAndQueues::Unsubscribe. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
        }
    }

    printAsterisksLine();
    if (!topicARN.empty() && askUser &&
        askYesNoQuestion("Delete the SNS topic? (y/n) ")) {

        // 11. Delete an SNS topic.
        Aws::SNS::Model::DeleteTopicRequest request;
        request.SetTopicArn(topicARN);

        Aws::SNS::Model::DeleteTopicOutcome outcome =
 snsClient.DeleteTopic(request);

        if (outcome.IsSuccess()) {
            std::cout << "The topic with ARN '" << topicARN
                      << "' was successfully deleted." << std::endl;
        }
        else {
            std::cerr << "Error with TopicsAndQueues::DeleteTopicRequest. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
        }
    }

    return result;
}

//! Create an IAM policy that gives an SQS queue permission to receive messages from
 an SNS topic.
/*!
 \sa createPolicyForQueue()
 \param queueARN: The SQS queue Amazon Resource Name (ARN).
 \param topicARN: The SNS topic ARN.
 \return Aws::String: The policy as JSON.
 */
```

```
Aws::String AwsDoc::TopicsAndQueues::createPolicyForQueue(const Aws::String
 &queueARN,
                                                           const Aws::String
 &topicARN) {
    std::ostringstream policyStream;
    policyStream << R"({
        "Statement": [
        {
            "Effect": "Allow",
                    "Principal": {
                "Service": "sns.amazonaws.com"
            },
            "Action": "sqs:SendMessage",
                    "Resource": ")" << queueARN << R"(",
                    "Condition": {
                "ArnEquals": {
                    "aws:SourceArn": ")" << topicARN << R"("
                }
            }
        }
        ]
    })";

    return policyStream.str();
}
```

- For API details, see the following topics in *AWS SDK for C++ API Reference*.
  - CreateQueue
  - CreateTopic
  - DeleteMessageBatch
  - DeleteQueue
  - DeleteTopic
  - GetQueueAttributes
  - Publish
  - ReceiveMessage
  - SetQueueAttributes
  - Subscribe
  - Unsubscribe

Amazon SQS examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with Amazon SQS.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Scenarios are code examples that show you how to accomplish specific tasks by calling multiple functions within a service or combined with other AWS services.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Get started
- Actions
- Scenarios

Get started

Hello Amazon SQS

The following code example shows how to get started using Amazon SQS.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

Code for the CMakeLists.txt CMake file.

```
# Set the minimum required version of CMake for this project.
cmake_minimum_required(VERSION 3.13)

# Set the AWS service components used by this project.
set(SERVICE_COMPONENTS sqs)
```

```
# Set this project's name.
project("hello_sqs")

# Set the C++ standard to use to build this target.
# At least C++ 11 is required for the AWS SDK for C++.
set(CMAKE_CXX_STANDARD 11)

# Use the MSVC variable to determine if this is a Windows build.
set(WINDOWS_BUILD ${MSVC})

if (WINDOWS_BUILD) # Set the location where CMake can find the installed libraries
 for the AWS SDK.
    string(REPLACE ";" "/aws-cpp-sdk-all;" SYSTEM_MODULE_PATH
 "${CMAKE_SYSTEM_PREFIX_PATH}/aws-cpp-sdk-all")
    list(APPEND CMAKE_PREFIX_PATH ${SYSTEM_MODULE_PATH})
endif ()

# Find the AWS SDK for C++ package.
find_package(AWSSDK REQUIRED COMPONENTS ${SERVICE_COMPONENTS})

if(WINDOWS_BUILD AND AWSSDK_INSTALL_AS_SHARED_LIBS)
    # Copy relevant AWS SDK for C++ libraries into the current binary directory for
 running and debugging.

    # set(BIN_SUB_DIR "/Debug") # If you are building from the command line you may
 need to uncomment this
    # and set the proper subdirectory to the executables' location.

    AWSSDK_CPY_DYN_LIBS(SERVICE_COMPONENTS ""
 ${CMAKE_CURRENT_BINARY_DIR}${BIN_SUB_DIR})
endif()

add_executable(${PROJECT_NAME}
        hello_sqs.cpp)

target_link_libraries(${PROJECT_NAME}
        ${AWSSDK_LINK_LIBRARIES})
```

Code for the hello_sqs.cpp source file.

```
#include <aws/core/Aws.h>
```

```
#include <aws/sqs/SQSClient.h>
#include <aws/sqs/model/ListQueuesRequest.h>
#include <iostream>

/*
 *  A "Hello SQS" starter application that initializes an Amazon Simple Queue
 Service
 *  (Amazon SQS) client and lists the SQS queues in the current account.
 *
 *  main function
 *
 *  Usage: 'hello_sqs'
 *
 */

int main(int argc, char **argv) {
    Aws::SDKOptions options;
    // Optionally change the log level for debugging.
//   options.loggingOptions.logLevel = Utils::Logging::LogLevel::Debug;
    Aws::InitAPI(options); // Should only be called once.
    {
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

        Aws::SQS::SQSClient sqsClient(clientConfig);

        Aws::Vector<Aws::String> allQueueUrls;
        Aws::String nextToken; // Next token is used to handle a paginated response.
        do {
            Aws::SQS::Model::ListQueuesRequest request;

            Aws::SQS::Model::ListQueuesOutcome outcome =
 sqsClient.ListQueues(request);

            if (outcome.IsSuccess()) {
                const Aws::Vector<Aws::String> &pageOfQueueUrls =
 outcome.GetResult().GetQueueUrls();
                if (!pageOfQueueUrls.empty()) {
                    allQueueUrls.insert(allQueueUrls.cend(),
 pageOfQueueUrls.cbegin(),
                                        pageOfQueueUrls.cend());
                }
            }
```

```
            else {
                std::cerr << "Error with SQS::ListQueues. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                break;
            }
            nextToken = outcome.GetResult().GetNextToken();
        } while (!nextToken.empty());


        std::cout << "Hello Amazon SQS! You have " << allQueueUrls.size() << "
 queue"
                  << (allQueueUrls.size() == 1 ? "" : "s") << " in your account."
                  << std::endl;

        if (!allQueueUrls.empty()) {
            std::cout << "Here are your queue URLs." << std::endl;
            for (const Aws::String &queueUrl: allQueueUrls) {
                std::cout << "  * " << queueUrl << std::endl;
            }
        }
    }

    Aws::ShutdownAPI(options); // Should only be called once.
    return 0;
}
```

- For API details, see ListQueues in *AWS SDK for C++ API Reference*.

Actions

`ChangeMessageVisibility`

The following code example shows how to use `ChangeMessageVisibility`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Changes the visibility timeout of a message in an Amazon Simple Queue Service
//! (Amazon SQS) queue.
/*!
  \param queueUrl: An Amazon SQS queue URL.
  \param messageReceiptHandle: A message receipt handle.
  \param visibilityTimeoutSeconds: Visibility timeout in seconds.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::changeMessageVisibility(
        const Aws::String &queue_url,
        const Aws::String &messageReceiptHandle,
        int visibilityTimeoutSeconds,
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::ChangeMessageVisibilityRequest request;
    request.SetQueueUrl(queue_url);
    request.SetReceiptHandle(messageReceiptHandle);
    request.SetVisibilityTimeout(visibilityTimeoutSeconds);

    auto outcome = sqsClient.ChangeMessageVisibility(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully changed visibility of message " <<
                  messageReceiptHandle << " from queue " << queue_url << std::endl;
    }
    else {
        std::cout << "Error changing visibility of message from queue "
                  << queue_url << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
```

```
    }

    return outcome.IsSuccess();
}
```

- For API details, see ChangeMessageVisibility in *AWS SDK for C++ API Reference*.

`CreateQueue`

The following code example shows how to use `CreateQueue`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Create an Amazon Simple Queue Service (Amazon SQS) queue.
/*!
  \param queueName: An Amazon SQS queue name.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::createQueue(const Aws::String &queueName,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::CreateQueueRequest request;
    request.SetQueueName(queueName);

    const Aws::SQS::Model::CreateQueueOutcome outcome =
 sqsClient.CreateQueue(request);
    if (outcome.IsSuccess()) {
```

```
        std::cout << "Successfully created queue " << queueName << " with a queue
 URL "
                  << outcome.GetResult().GetQueueUrl() << "." << std::endl;
    }
    else {
        std::cerr << "Error creating queue " << queueName << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see CreateQueue in *AWS SDK for C++ API Reference*.

`DeleteMessage`

The following code example shows how to use `DeleteMessage`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Delete a message from an Amazon Simple Queue Service (Amazon SQS) queue.
/*!
  \param queueUrl: An Amazon SQS queue URL.
  \param messageReceiptHandle: A message receipt handle.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::deleteMessage(const Aws::String &queueUrl,
                                const Aws::String &messageReceiptHandle,
                                const Aws::Client::ClientConfiguration
 &clientConfiguration) {
```

```
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::DeleteMessageRequest request;
    request.SetQueueUrl(queueUrl);
    request.SetReceiptHandle(messageReceiptHandle);

    const Aws::SQS::Model::DeleteMessageOutcome outcome = sqsClient.DeleteMessage(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted message from queue " << queueUrl
                  << std::endl;
    }
    else {
        std::cerr << "Error deleting message from queue " << queueUrl << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see DeleteMessage in *AWS SDK for C++ API Reference*.

`DeleteMessageBatch`

The following code example shows how to use `DeleteMessageBatch`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::SQS::SQSClient sqsClient(clientConfiguration);
```

```
            Aws::SQS::Model::DeleteMessageBatchRequest request;
            request.SetQueueUrl(queueURLS[i]);
            int id = 1; // Ids must be unique within a batch delete request.
            for (const Aws::String &receiptHandle: receiptHandles) {
                Aws::SQS::Model::DeleteMessageBatchRequestEntry entry;
                entry.SetId(std::to_string(id));
                ++id;
                entry.SetReceiptHandle(receiptHandle);
                request.AddEntries(entry);
            }

            Aws::SQS::Model::DeleteMessageBatchOutcome outcome =
                    sqsClient.DeleteMessageBatch(request);

            if (outcome.IsSuccess()) {
                std::cout << "The batch deletion of messages was successful."
                          << std::endl;
            }
            else {
                std::cerr << "Error with SQS::DeleteMessageBatch. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
```

- For API details, see DeleteMessageBatch in *AWS SDK for C++ API Reference*.

`DeleteQueue`

The following code example shows how to use `DeleteQueue`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Delete an Amazon Simple Queue Service (Amazon SQS) queue.
/*!
  \param queueURL: An Amazon SQS queue URL.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::deleteQueue(const Aws::String &queueURL,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);
    Aws::SQS::Model::DeleteQueueRequest request;
    request.SetQueueUrl(queueURL);

    const Aws::SQS::Model::DeleteQueueOutcome outcome =
 sqsClient.DeleteQueue(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully deleted queue with url " << queueURL <<
                  std::endl;
    }
    else {
        std::cerr << "Error deleting queue " << queueURL << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    return outcome.IsSuccess();
}
```

- For API details, see DeleteQueue in *AWS SDK for C++ API Reference*.

`GetQueueAttributes`

The following code example shows how to use `GetQueueAttributes`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

    Aws::SQS::SQSClient sqsClient(clientConfiguration);

            Aws::SQS::Model::GetQueueAttributesRequest request;
            request.SetQueueUrl(queueURL);

request.AddAttributeNames(Aws::SQS::Model::QueueAttributeName::QueueArn);

            Aws::SQS::Model::GetQueueAttributesOutcome outcome =
                    sqsClient.GetQueueAttributes(request);

            if (outcome.IsSuccess()) {
                const Aws::Map<Aws::SQS::Model::QueueAttributeName, Aws::String>
&attributes =
                        outcome.GetResult().GetAttributes();
                const auto &iter = attributes.find(
                        Aws::SQS::Model::QueueAttributeName::QueueArn);
                if (iter != attributes.end()) {
                    queueARN = iter->second;
                    std::cout << "The queue ARN '" << queueARN
                              << "' has been retrieved."
                              << std::endl;
                }

            }
            else {
                std::cerr << "Error with SQS::GetQueueAttributes. "
                          << outcome.GetError().GetMessage()
```

```
                          << std::endl;


            }
```

- For API details, see GetQueueAttributes in *AWS SDK for C++ API Reference*.

`GetQueueUrl`

The following code example shows how to use `GetQueueUrl`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Get the URL for an Amazon Simple Queue Service (Amazon SQS) queue.
/*!
  \param queueName: An Amazon SQS queue name.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::getQueueUrl(const Aws::String &queueName,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::GetQueueUrlRequest request;
    request.SetQueueName(queueName);

    const Aws::SQS::Model::GetQueueUrlOutcome outcome =
 sqsClient.GetQueueUrl(request);
    if (outcome.IsSuccess()) {
```

```
        std::cout << "Queue " << queueName << " has url " <<
                  outcome.GetResult().GetQueueUrl() << std::endl;
    }
    else {
        std::cerr << "Error getting url for queue " << queueName << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see GetQueueUrl in *AWS SDK for C++ API Reference*.

`ListQueues`

The following code example shows how to use `ListQueues`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! List the Amazon Simple Queue Service (Amazon SQS) queues within an AWS account.
/*!
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool
AwsDoc::SQS::listQueues(const Aws::Client::ClientConfiguration &clientConfiguration)
 {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::ListQueuesRequest listQueuesRequest;
```

```
    Aws::String nextToken; // Used for pagination.
    Aws::Vector<Aws::String> allQueueUrls;

    do {
        if (!nextToken.empty()) {
            listQueuesRequest.SetNextToken(nextToken);
        }
        const Aws::SQS::Model::ListQueuesOutcome outcome = sqsClient.ListQueues(
                listQueuesRequest);
        if (outcome.IsSuccess()) {
            const Aws::Vector<Aws::String> &queueUrls =
 outcome.GetResult().GetQueueUrls();
            allQueueUrls.insert(allQueueUrls.end(),
                                queueUrls.begin(),
                                queueUrls.end());

            nextToken = outcome.GetResult().GetNextToken();
        }
        else {
            std::cerr << "Error listing queues: " <<
                      outcome.GetError().GetMessage() << std::endl;
            return false;
        }

    } while (!nextToken.empty());

    std::cout << allQueueUrls.size() << " Amazon SQS queue(s) found." << std::endl;
    for (const auto &iter: allQueueUrls) {
        std::cout << " " << iter << std::endl;
    }

    return true;
}
```

- For API details, see ListQueues in *AWS SDK for C++ API Reference*.

`ReceiveMessage`

The following code example shows how to use `ReceiveMessage`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Receive a message from an Amazon Simple Queue Service (Amazon SQS) queue.
/*!
  \param queueUrl: An Amazon SQS queue URL.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::receiveMessage(const Aws::String &queueUrl,
                                 const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::ReceiveMessageRequest request;
    request.SetQueueUrl(queueUrl);
    request.SetMaxNumberOfMessages(1);

    const Aws::SQS::Model::ReceiveMessageOutcome outcome = sqsClient.ReceiveMessage(
            request);
    if (outcome.IsSuccess()) {

        const Aws::Vector<Aws::SQS::Model::Message> &messages =
                outcome.GetResult().GetMessages();
        if (!messages.empty()) {
            const Aws::SQS::Model::Message &message = messages[0];
            std::cout << "Received message:" << std::endl;
            std::cout << "  MessageId: " << message.GetMessageId() << std::endl;
            std::cout << "  ReceiptHandle: " << message.GetReceiptHandle() <<
 std::endl;
            std::cout << "  Body: " << message.GetBody() << std::endl << std::endl;
        }
        else {
```

```
            std::cout << "No messages received from queue " << queueUrl <<
                      std::endl;

        }
    }
    else {
        std::cerr << "Error receiving message from queue " << queueUrl << ": "
                  << outcome.GetError().GetMessage() << std::endl;
    }
    return outcome.IsSuccess();
}
```

- For API details, see ReceiveMessage in *AWS SDK for C++ API Reference*.

SendMessage

The following code example shows how to use SendMessage.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Send a message to an Amazon Simple Queue Service (Amazon SQS) queue.
/*!
  \param queueUrl: An Amazon SQS queue URL.
  \param messageBody: A message body.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::sendMessage(const Aws::String &queueUrl,
                              const Aws::String &messageBody,
                              const Aws::Client::ClientConfiguration
 &clientConfiguration) {
```

```
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::SendMessageRequest request;
    request.SetQueueUrl(queueUrl);
    request.SetMessageBody(messageBody);

    const Aws::SQS::Model::SendMessageOutcome outcome =
 sqsClient.SendMessage(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully sent message to " << queueUrl <<
                  std::endl;
    }
    else {
        std::cerr << "Error sending message to " << queueUrl << ": " <<
                  outcome.GetError().GetMessage() << std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see SendMessage in *AWS SDK for C++ API Reference*.

`SetQueueAttributes`

The following code example shows how to use `SetQueueAttributes`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Set the value for an attribute in an Amazon Simple Queue Service (Amazon SQS)
 queue.
```

```
/*!
  \param queueUrl: An Amazon SQS queue URL.
  \param attributeName: An attribute name enum.
  \param attribute: The attribute value as a string.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::setQueueAttributes(const Aws::String &queueURL,
                                     Aws::SQS::Model::QueueAttributeName
 attributeName,
                                     const Aws::String &attribute,
                                     const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::SetQueueAttributesRequest request;
    request.SetQueueUrl(queueURL);
    request.AddAttributes(
            attributeName,
            attribute);

    const Aws::SQS::Model::SetQueueAttributesOutcome outcome =
 sqsClient.SetQueueAttributes(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully set the attribute  " <<

 Aws::SQS::Model::QueueAttributeNameMapper::GetNameForQueueAttributeName(
                        attributeName)
                << " with value " << attribute << " in queue " <<
                queueURL << "." << std::endl;
    }
    else {
        std::cout << "Error setting attribute for  queue " <<
                  queueURL << ": " << outcome.GetError().GetMessage() <<
                  std::endl;
    }

    return outcome.IsSuccess();
}
```

Configure a dead-letter queue.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Connect an Amazon Simple Queue Service (Amazon SQS) queue to an associated
//! dead-letter queue.
/*!
  \param srcQueueUrl: An Amazon SQS queue URL.
  \param deadLetterQueueARN: The Amazon Resource Name (ARN) of an Amazon SQS dead-
letter queue.
  \param maxReceiveCount: The max receive count of a message before it is sent to
 the dead-letter queue.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::setDeadLetterQueue(const Aws::String &srcQueueUrl,
                                     const Aws::String &deadLetterQueueARN,
                                     int maxReceiveCount,
                                     const Aws::Client::ClientConfiguration
 &clientConfiguration) {
    Aws::String redrivePolicy = MakeRedrivePolicy(deadLetterQueueARN,
 maxReceiveCount);

    Aws::SQS::SQSClient sqsClient(clientConfiguration);

    Aws::SQS::Model::SetQueueAttributesRequest request;
    request.SetQueueUrl(srcQueueUrl);
    request.AddAttributes(
            Aws::SQS::Model::QueueAttributeName::RedrivePolicy,
            redrivePolicy);

    const Aws::SQS::Model::SetQueueAttributesOutcome outcome =
            sqsClient.SetQueueAttributes(request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully set dead letter queue for queue  " <<
                  srcQueueUrl << " to " << deadLetterQueueARN << std::endl;
    }
    else {
        std::cerr << "Error setting dead letter queue for queue " <<
                  srcQueueUrl << ": " << outcome.GetError().GetMessage() <<
                  std::endl;
    }
```

```
    return outcome.IsSuccess();
}

//! Make a redrive policy for a dead-letter queue.
/*!
  \param queueArn: An Amazon SQS ARN for the dead-letter queue.
  \param maxReceiveCount: The max receive count of a message before it is sent to
 the dead-letter queue.
  \return Aws::String: Policy as JSON string.
 */
Aws::String MakeRedrivePolicy(const Aws::String &queueArn, int maxReceiveCount) {
    Aws::Utils::Json::JsonValue redrive_arn_entry;
    redrive_arn_entry.AsString(queueArn);

    Aws::Utils::Json::JsonValue max_msg_entry;
    max_msg_entry.AsInteger(maxReceiveCount);

    Aws::Utils::Json::JsonValue policy_map;
    policy_map.WithObject("deadLetterTargetArn", redrive_arn_entry);
    policy_map.WithObject("maxReceiveCount", max_msg_entry);

    return policy_map.View().WriteReadable();
}
```

Configure an Amazon SQS queue to use long polling.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Set the wait time for an Amazon Simple Queue Service (Amazon SQS) queue poll.
/*!
  \param queueUrl: An Amazon SQS queue URL.
  \param pollTimeSeconds: The receive message wait time in seconds.
  \param clientConfiguration: AWS client configuration.
  \return bool: Function succeeded.
 */
bool AwsDoc::SQS::setQueueLongPollingAttribute(const Aws::String &queueURL,
                                               const Aws::String &pollTimeSeconds,
                                               const
 Aws::Client::ClientConfiguration &clientConfiguration) {
    Aws::SQS::SQSClient sqsClient(clientConfiguration);
```

```
    Aws::SQS::Model::SetQueueAttributesRequest request;
    request.SetQueueUrl(queueURL);
    request.AddAttributes(
            Aws::SQS::Model::QueueAttributeName::ReceiveMessageWaitTimeSeconds,
            pollTimeSeconds);

    const Aws::SQS::Model::SetQueueAttributesOutcome outcome =
 sqsClient.SetQueueAttributes(
            request);
    if (outcome.IsSuccess()) {
        std::cout << "Successfully updated long polling time for queue " <<
                  queueURL << " to " << pollTimeSeconds << std::endl;
    }
    else {
        std::cout << "Error updating long polling time for queue " <<
                  queueURL << ": " << outcome.GetError().GetMessage() <<
                  std::endl;
    }

    return outcome.IsSuccess();
}
```

- For API details, see SetQueueAttributes in *AWS SDK for C++ API Reference*.

Scenarios

Publish messages to queues

The following code example shows how to:

- Create topic (FIFO or non-FIFO).
- Subscribe several queues to the topic with an option to apply a filter.
- Publish messages to the topic.
- Poll the queues for messages received.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
        Aws::Client::ClientConfiguration clientConfig;
        // Optional: Set to the AWS Region (overrides config file).
        // clientConfig.region = "us-east-1";

//! Workflow for messaging with topics and queues using Amazon SNS and Amazon SQS.
/*!
 \param clientConfig Aws client configuration.
 \return bool: Successful completion.
 */
bool AwsDoc::TopicsAndQueues::messagingWithTopicsAndQueues(
        const Aws::Client::ClientConfiguration &clientConfiguration) {
    std::cout << "Welcome to messaging with topics and queues." << std::endl;
    printAsterisksLine();
    std::cout << "In this workflow, you will create an SNS topic and subscribe "
              << NUMBER_OF_QUEUES <<
              " SQS queues to the topic." << std::endl;
    std::cout
            << "You can select from several options for configuring the topic and
 the subscriptions for the "
            << NUMBER_OF_QUEUES << " queues." << std::endl;
    std::cout << "You can then post to the topic and see the results in the queues."
              << std::endl;

    Aws::SNS::SNSClient snsClient(clientConfiguration);

    printAsterisksLine();

    std::cout << "SNS topics can be configured as FIFO (First-In-First-Out)."
              << std::endl;
    std::cout
            << "FIFO topics deliver messages in order and support deduplication and
 message filtering."
            << std::endl;
    bool isFifoTopic = askYesNoQuestion(
```

```
            "Would you like to work with FIFO topics? (y/n) ");

    bool contentBasedDeduplication = false;
    Aws::String topicName;
    if (isFifoTopic) {
        printAsterisksLine();
        std::cout << "Because you have chosen a FIFO topic, deduplication is
 supported."
                  << std::endl;
        std::cout
                << "Deduplication IDs are either set in the message or automatically
 generated "
                << "from content using a hash function." << std::endl;
        std::cout
                << "If a message is successfully published to an SNS FIFO topic, any
 message "
                << "published and determined to have the same deduplication ID, "
                << std::endl;
        std::cout
                << "within the five-minute deduplication interval, is accepted but
 not delivered."
                << std::endl;
        std::cout
                << "For more information about deduplication, "
                << "see https://docs.aws.amazon.com/sns/latest/dg/fifo-message-
dedup.html."
                << std::endl;
        contentBasedDeduplication = askYesNoQuestion(
                "Use content-based deduplication instead of entering a deduplication
 ID? (y/n) ");
    }

    printAsterisksLine();

    Aws::SQS::SQSClient sqsClient(clientConfiguration);
    Aws::Vector<Aws::String> queueURLS;
    Aws::Vector<Aws::String> subscriptionARNS;

    Aws::String topicARN;
    {
        topicName = askQuestion("Enter a name for your SNS topic. ");

        // 1.  Create an Amazon SNS topic, either FIFO or non-FIFO.
        Aws::SNS::Model::CreateTopicRequest request;
```

```
        if (isFifoTopic) {
            request.AddAttributes("FifoTopic", "true");
            if (contentBasedDeduplication) {
                request.AddAttributes("ContentBasedDeduplication", "true");
            }
            topicName = topicName + FIFO_SUFFIX;

            std::cout
                    << "Because you have selected a FIFO topic, '.fifo' must be
appended to the topic name."
                    << std::endl;
        }

        request.SetName(topicName);

        Aws::SNS::Model::CreateTopicOutcome outcome =
snsClient.CreateTopic(request);

        if (outcome.IsSuccess()) {
            topicARN = outcome.GetResult().GetTopicArn();
            std::cout << "Your new topic with the name '" << topicName
                      << "' and the topic Amazon Resource Name (ARN) " << std::endl;
            std::cout << "'" << topicARN << "' has been created." << std::endl;

        }
        else {
            std::cerr << "Error with TopicsAndQueues::CreateTopic. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

            cleanUp(topicARN,
                    queueURLS,
                    subscriptionARNS,
                    snsClient,
                    sqsClient);

            return false;
        }
    }

    printAsterisksLine();

    std::cout << "Now you will create " << NUMBER_OF_QUEUES
```

```
              << " SQS queues to subscribe to the topic." << std::endl;
    Aws::Vector<Aws::String> queueNames;
    bool filteringMessages = false;
    bool first = true;
    for (int i = 1; i <= NUMBER_OF_QUEUES; ++i) {
        Aws::String queueURL;
        Aws::String queueName;
        {
            printAsterisksLine();
            std::ostringstream ostringstream;
            ostringstream << "Enter a name for " << (first ? "an" : "the next")
                          << " SQS queue. ";
            queueName = askQuestion(ostringstream.str());

            // 2.  Create an SQS queue.
            Aws::SQS::Model::CreateQueueRequest request;
            if (isFifoTopic) {

request.AddAttributes(Aws::SQS::Model::QueueAttributeName::FifoQueue,
                                      "true");
                queueName = queueName + FIFO_SUFFIX;

                if (first) // Only explain this once.
                {
                    std::cout
                            << "Because you are creating a FIFO SQS queue, '.fifo'
must "
                            << "be appended to the queue name." << std::endl;
                }
            }

            request.SetQueueName(queueName);
            queueNames.push_back(queueName);

            Aws::SQS::Model::CreateQueueOutcome outcome =
                    sqsClient.CreateQueue(request);

            if (outcome.IsSuccess()) {
                queueURL = outcome.GetResult().GetQueueUrl();
                std::cout << "Your new SQS queue with the name '" << queueName
                          << "' and the queue URL " << std::endl;
                std::cout << "'" << queueURL << "' has been created." << std::endl;
            }
            else {
```

```
                std::cerr << "Error with SQS::CreateQueue. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }
        queueURLS.push_back(queueURL);

        if (first) // Only explain this once.
        {
            std::cout
                    << "The queue URL is used to retrieve the queue ARN, which is "
                    << "used to create a subscription." << std::endl;
        }

        Aws::String queueARN;
        {
            // 3.  Get the SQS queue ARN attribute.
            Aws::SQS::Model::GetQueueAttributesRequest request;
            request.SetQueueUrl(queueURL);

request.AddAttributeNames(Aws::SQS::Model::QueueAttributeName::QueueArn);

            Aws::SQS::Model::GetQueueAttributesOutcome outcome =
                    sqsClient.GetQueueAttributes(request);

            if (outcome.IsSuccess()) {
                const Aws::Map<Aws::SQS::Model::QueueAttributeName, Aws::String>
&attributes =
                        outcome.GetResult().GetAttributes();
                const auto &iter = attributes.find(
                        Aws::SQS::Model::QueueAttributeName::QueueArn);
                if (iter != attributes.end()) {
                    queueARN = iter->second;
                    std::cout << "The queue ARN '" << queueARN
                              << "' has been retrieved."
                              << std::endl;
```

```
                }
                else {
                    std::cerr
                            << "Error ARN attribute not returned by
GetQueueAttribute."
                            << std::endl;

                    cleanUp(topicARN,
                            queueURLS,
                            subscriptionARNS,
                            snsClient,
                            sqsClient);

                    return false;
                }
            }
            else {
                std::cerr << "Error with SQS::GetQueueAttributes. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }

        if (first) {
            std::cout
                    << "An IAM policy must be attached to an SQS queue, enabling it
to receive "
                       "messages from an SNS topic." << std::endl;
        }

        {
            // 4.  Set the SQS queue policy attribute with a policy enabling the
receipt of SNS messages.
            Aws::SQS::Model::SetQueueAttributesRequest request;
            request.SetQueueUrl(queueURL);
            Aws::String policy = createPolicyForQueue(queueARN, topicARN);
```

```
            request.AddAttributes(Aws::SQS::Model::QueueAttributeName::Policy,
                                  policy);

            Aws::SQS::Model::SetQueueAttributesOutcome outcome =
                    sqsClient.SetQueueAttributes(request);

            if (outcome.IsSuccess()) {
                std::cout << "The attributes for the queue '" << queueName
                          << "' were successfully updated." << std::endl;
            }
            else {
                std::cerr << "Error with SQS::SetQueueAttributes. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }

        printAsterisksLine();

        {
            // 5.  Subscribe the SQS queue to the SNS topic.
            Aws::SNS::Model::SubscribeRequest request;
            request.SetTopicArn(topicARN);
            request.SetProtocol("sqs");
            request.SetEndpoint(queueARN);
            if (isFifoTopic) {
                if (first) {
                    std::cout << "Subscriptions to a FIFO topic can have filters."
                              << std::endl;
                    std::cout
                            << "If you add a filter to this subscription, then only
 the filtered messages "
                            << "will be received in the queue." << std::endl;
                    std::cout << "For information about message filtering, "
                              << "see https://docs.aws.amazon.com/sns/latest/dg/sns-
message-filtering.html"
```

```
                            << std::endl;
                    std::cout << "For this example, you can filter messages by a \""
                            << TONE_ATTRIBUTE << "\" attribute." << std::endl;
                }

                std::ostringstream ostringstream;
                ostringstream << "Filter messages for \"" << queueName
                            << "\"'s subscription to the topic \""
                            << topicName << "\"?  (y/n)";

                // Add filter if user answers yes.
                if (askYesNoQuestion(ostringstream.str())) {
                    Aws::String jsonPolicy = getFilterPolicyFromUser();
                    if (!jsonPolicy.empty()) {
                        filteringMessages = true;

                        std::cout << "This is the filter policy for this
subscription."
                                  << std::endl;
                        std::cout << jsonPolicy << std::endl;

                        request.AddAttributes("FilterPolicy", jsonPolicy);
                    }
                    else {
                        std::cout
                                << "Because you did not select any attributes, no
filter "
                                << "will be added to this subscription." <<
std::endl;
                    }
                }
            }  // if (isFifoTopic)
            Aws::SNS::Model::SubscribeOutcome outcome =
snsClient.Subscribe(request);

            if (outcome.IsSuccess()) {
                Aws::String subscriptionARN =
outcome.GetResult().GetSubscriptionArn();
                std::cout << "The queue '" << queueName
                          << "' has been subscribed to the topic '"
                          << "'" << topicName << "'" << std::endl;
                std::cout << "with the subscription ARN '" << subscriptionARN << "."
                          << std::endl;
                subscriptionARNS.push_back(subscriptionARN);
```

```
            }
            else {
                std::cerr << "Error with TopicsAndQueues::Subscribe. "
                          << outcome.GetError().GetMessage()
                          << std::endl;

                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }

        first = false;
    }

    first = true;
    do {
        printAsterisksLine();

        // 6.  Publish a message to the SNS topic.
        Aws::SNS::Model::PublishRequest request;
        request.SetTopicArn(topicARN);
        Aws::String message = askQuestion("Enter a message text to publish.  ");
        request.SetMessage(message);
        if (isFifoTopic) {
            if (first) {
                std::cout
                        << "Because you are using a FIFO topic, you must set a
message group ID."
                        << std::endl;
                std::cout
                        << "All messages within the same group will be received in
the "
                        << "order they were published." << std::endl;
            }
            Aws::String messageGroupID = askQuestion(
                    "Enter a message group ID for this message. ");
            request.SetMessageGroupId(messageGroupID);
            if (!contentBasedDeduplication) {
                if (first) {
```

```
                    std::cout
                            << "Because you are not using content-based
deduplication, "
                            << "you must enter a deduplication ID." << std::endl;
                }
                Aws::String deduplicationID = askQuestion(
                        "Enter a deduplication ID for this message. ");
                request.SetMessageDeduplicationId(deduplicationID);
            }
        }

        if (filteringMessages && askYesNoQuestion(
                "Add an attribute to this message? (y/n) ")) {
            for (size_t i = 0; i < TONES.size(); ++i) {
                std::cout << "  " << (i + 1) << ". " << TONES[i] << std::endl;
            }
            int selection = askQuestionForIntRange(
                    "Enter a number for an attribute. ",
                    1, static_cast<int>(TONES.size()));
            Aws::SNS::Model::MessageAttributeValue messageAttributeValue;
            messageAttributeValue.SetDataType("String");
            messageAttributeValue.SetStringValue(TONES[selection - 1]);
            request.AddMessageAttributes(TONE_ATTRIBUTE, messageAttributeValue);
        }

        Aws::SNS::Model::PublishOutcome outcome = snsClient.Publish(request);

        if (outcome.IsSuccess()) {
            std::cout << "Your message was successfully published." << std::endl;
        }
        else {
            std::cerr << "Error with TopicsAndQueues::Publish. "
                      << outcome.GetError().GetMessage()
                      << std::endl;

            cleanUp(topicARN,
                    queueURLS,
                    subscriptionARNS,
                    snsClient,
                    sqsClient);

            return false;
        }
```

```
        first = false;
    } while (askYesNoQuestion("Post another message? (y/n) "));

    printAsterisksLine();

    std::cout << "Now the SQS queue will be polled to retrieve the messages."
              << std::endl;
    askQuestion("Press any key to continue...", alwaysTrueTest);

    for (size_t i = 0; i < queueURLS.size(); ++i) {
        // 7.  Poll an SQS queue for its messages.
        std::vector<Aws::String> messages;
        std::vector<Aws::String> receiptHandles;
        while (true) {
            Aws::SQS::Model::ReceiveMessageRequest request;
            request.SetMaxNumberOfMessages(10);
            request.SetQueueUrl(queueURLS[i]);

            // Setting WaitTimeSeconds to non-zero enables long polling.
            // For information about long polling, see
            // https://docs.aws.amazon.com/AWSSimpleQueueService/latest/
SQSDeveloperGuide/sqs-short-and-long-polling.html
            request.SetWaitTimeSeconds(1);
            Aws::SQS::Model::ReceiveMessageOutcome outcome =
                    sqsClient.ReceiveMessage(request);

            if (outcome.IsSuccess()) {
                const Aws::Vector<Aws::SQS::Model::Message> &newMessages =
 outcome.GetResult().GetMessages();
                if (newMessages.empty()) {
                    break;
                }
                else {
                    for (const Aws::SQS::Model::Message &message: newMessages) {
                        messages.push_back(message.GetBody());
                        receiptHandles.push_back(message.GetReceiptHandle());
                    }
                }
            }
            else {
                std::cerr << "Error with SQS::ReceiveMessage. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
```

```
                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }

        printAsterisksLine();

        if (messages.empty()) {
            std::cout << "No messages were ";
        }
        else if (messages.size() == 1) {
            std::cout << "One message was ";
        }
        else {
            std::cout << messages.size() << " messages were ";
        }
        std::cout << "received by the queue '" << queueNames[i]
                  << "'." << std::endl;
        for (const Aws::String &message: messages) {
            std::cout << "  Message : '" << message << "'."
                      << std::endl;
        }

        // 8.  Delete a batch of messages from an SQS queue.
        if (!receiptHandles.empty()) {
            Aws::SQS::Model::DeleteMessageBatchRequest request;
            request.SetQueueUrl(queueURLS[i]);
            int id = 1; // Ids must be unique within a batch delete request.
            for (const Aws::String &receiptHandle: receiptHandles) {
                Aws::SQS::Model::DeleteMessageBatchRequestEntry entry;
                entry.SetId(std::to_string(id));
                ++id;
                entry.SetReceiptHandle(receiptHandle);
                request.AddEntries(entry);
            }

            Aws::SQS::Model::DeleteMessageBatchOutcome outcome =
                    sqsClient.DeleteMessageBatch(request);
```

```
            if (outcome.IsSuccess()) {
                std::cout << "The batch deletion of messages was successful."
                          << std::endl;
            }
            else {
                std::cerr << "Error with SQS::DeleteMessageBatch. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                cleanUp(topicARN,
                        queueURLS,
                        subscriptionARNS,
                        snsClient,
                        sqsClient);

                return false;
            }
        }
    }

    return cleanUp(topicARN,
                   queueURLS,
                   subscriptionARNS,
                   snsClient,
                   sqsClient,
                   true); // askUser
}


bool AwsDoc::TopicsAndQueues::cleanUp(const Aws::String &topicARN,
                                      const Aws::Vector<Aws::String> &queueURLS,
                                      const Aws::Vector<Aws::String>
 &subscriptionARNS,
                                      const Aws::SNS::SNSClient &snsClient,
                                      const Aws::SQS::SQSClient &sqsClient,
                                      bool askUser) {
    bool result = true;
    printAsterisksLine();
    if (!queueURLS.empty() && askUser &&
        askYesNoQuestion("Delete the SQS queues? (y/n) ")) {

        for (const auto &queueURL: queueURLS) {
            // 9.  Delete an SQS queue.
            Aws::SQS::Model::DeleteQueueRequest request;
            request.SetQueueUrl(queueURL);
```

```
            Aws::SQS::Model::DeleteQueueOutcome outcome =
                    sqsClient.DeleteQueue(request);

            if (outcome.IsSuccess()) {
                std::cout << "The queue with URL '" << queueURL
                          << "' was successfully deleted." << std::endl;
            }
            else {
                std::cerr << "Error with SQS::DeleteQueue. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
        }

        for (const auto &subscriptionARN: subscriptionARNS) {
            // 10. Unsubscribe an SNS subscription.
            Aws::SNS::Model::UnsubscribeRequest request;
            request.SetSubscriptionArn(subscriptionARN);

            Aws::SNS::Model::UnsubscribeOutcome outcome =
                    snsClient.Unsubscribe(request);

            if (outcome.IsSuccess()) {
                std::cout << "Unsubscribe of subscription ARN '" << subscriptionARN
                          << "' was successful." << std::endl;
            }
            else {
                std::cerr << "Error with TopicsAndQueues::Unsubscribe. "
                          << outcome.GetError().GetMessage()
                          << std::endl;
                result = false;
            }
        }
    }

    printAsterisksLine();
    if (!topicARN.empty() && askUser &&
        askYesNoQuestion("Delete the SNS topic? (y/n) ")) {

        // 11. Delete an SNS topic.
        Aws::SNS::Model::DeleteTopicRequest request;
        request.SetTopicArn(topicARN);
```

```
        Aws::SNS::Model::DeleteTopicOutcome outcome =
 snsClient.DeleteTopic(request);

        if (outcome.IsSuccess()) {
            std::cout << "The topic with ARN '" << topicARN
                      << "' was successfully deleted." << std::endl;
        }
        else {
            std::cerr << "Error with TopicsAndQueues::DeleteTopicRequest. "
                      << outcome.GetError().GetMessage()
                      << std::endl;
            result = false;
        }
    }

    return result;
}

//! Create an IAM policy that gives an SQS queue permission to receive messages from
 an SNS topic.
/*!
 \sa createPolicyForQueue()
 \param queueARN: The SQS queue Amazon Resource Name (ARN).
 \param topicARN: The SNS topic ARN.
 \return Aws::String: The policy as JSON.
 */
Aws::String AwsDoc::TopicsAndQueues::createPolicyForQueue(const Aws::String
 &queueARN,
                                                           const Aws::String
 &topicARN) {
    std::ostringstream policyStream;
    policyStream << R"({
        "Statement": [
        {
            "Effect": "Allow",
                    "Principal": {
                "Service": "sns.amazonaws.com"
            },
            "Action": "sqs:SendMessage",
                    "Resource": ")" << queueARN << R"(",
                    "Condition": {
                "ArnEquals": {
                    "aws:SourceArn": ")" << topicARN << R"("
```

```
                }
            }
        }
        ]
    })";

    return policyStream.str();
}
```

- For API details, see the following topics in *AWS SDK for C++ API Reference*.
  - CreateQueue
  - CreateTopic
  - DeleteMessageBatch
  - DeleteQueue
  - DeleteTopic
  - GetQueueAttributes
  - Publish
  - ReceiveMessage
  - SetQueueAttributes
  - Subscribe
  - Unsubscribe

AWS STS examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with AWS STS.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Actions

Actions

`AssumeRole`

The following code example shows how to use `AssumeRole`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
bool AwsDoc::STS::assumeRole(const Aws::String &roleArn,
                             const Aws::String &roleSessionName,
                             const Aws::String &externalId,
                             Aws::Auth::AWSCredentials &credentials,
                             const Aws::Client::ClientConfiguration &clientConfig) {
    Aws::STS::STSClient sts(clientConfig);
    Aws::STS::Model::AssumeRoleRequest sts_req;

    sts_req.SetRoleArn(roleArn);
    sts_req.SetRoleSessionName(roleSessionName);
    sts_req.SetExternalId(externalId);

    const Aws::STS::Model::AssumeRoleOutcome outcome = sts.AssumeRole(sts_req);

    if (!outcome.IsSuccess()) {
        std::cerr << "Error assuming IAM role. " <<
                  outcome.GetError().GetMessage() << std::endl;
    }
    else {
        std::cout << "Credentials successfully retrieved." << std::endl;
        const Aws::STS::Model::AssumeRoleResult result = outcome.GetResult();
        const Aws::STS::Model::Credentials &temp_credentials =
 result.GetCredentials();

        // Store temporary credentials in return argument.
        // Note: The credentials object returned by assumeRole differs
        // from the AWSCredentials object used in most situations.
        credentials.SetAWSAccessKeyId(temp_credentials.GetAccessKeyId());
```

```
        credentials.SetAWSSecretKey(temp_credentials.GetSecretAccessKey());
        credentials.SetSessionToken(temp_credentials.GetSessionToken());
    }

    return outcome.IsSuccess();
}
```

- For API details, see AssumeRole in *AWS SDK for C++ API Reference*.

Amazon Transcribe Streaming examples using SDK for C++

The following code examples show you how to perform actions and implement common scenarios by using the AWS SDK for C++ with Amazon Transcribe Streaming.

Actions are code excerpts from larger programs and must be run in context. While actions show you how to call individual service functions, you can see actions in context in their related scenarios.

Scenarios are code examples that show you how to accomplish specific tasks by calling multiple functions within a service or combined with other AWS services.

Each example includes a link to the complete source code, where you can find instructions on how to set up and run the code in context.

Topics

- Actions
- Scenarios

Actions

`StartStreamTranscription`

The following code example shows how to use `StartStreamTranscription`.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
int main() {
    Aws::SDKOptions options;

    Aws::InitAPI(options);
    {
        //TODO(User): Set to the region of your AWS account.
        const Aws::String region = Aws::Region::US_WEST_2;

        //Load a profile that has been granted AmazonTranscribeFullAccess AWS
 managed permission policy.
        Aws::Client::ClientConfiguration config;
#ifdef _WIN32
        // ATTENTION: On Windows with the AWS C++ SDK, this example only runs if the
 SDK is built
        // with the curl library.
        // For more information, see the accompanying ReadMe.
        // For more information, see "Building the SDK for Windows with curl".
        // https://docs.aws.amazon.com/sdk-for-cpp/v1/developer-guide/setup-
windows.html
        //TODO(User): Update to the location of your .crt file.
        config.caFile = "C:/curl/bin/curl-ca-bundle.crt";
#endif
        config.region = region;

        TranscribeStreamingServiceClient client(config);
        StartStreamTranscriptionHandler handler;
        handler.SetOnErrorCallback(
                [](const Aws::Client::AWSError<TranscribeStreamingServiceErrors>
 &error) {
                        std::cerr << "ERROR: " + error.GetMessage() << std::endl;
                });
        //SetTranscriptEventCallback called for every 'chunk' of file transcripted.
        // Partial results are returned in real time.
        handler.SetTranscriptEventCallback([](const TranscriptEvent &ev) {
```

```
                for (auto &&r: ev.GetTranscript().GetResults()) {
                    if (r.GetIsPartial()) {
                        std::cout << "[partial] ";
                    }
                    else {
                        std::cout << "[Final] ";
                    }
                    for (auto &&alt: r.GetAlternatives()) {
                        std::cout << alt.GetTranscript() << std::endl;
                    }
                }
        });

        StartStreamTranscriptionRequest request;
        request.SetMediaSampleRateHertz(SAMPLE_RATE);
        request.SetLanguageCode(LanguageCode::en_US);
        request.SetMediaEncoding(
                MediaEncoding::pcm); // wav and aiff files are PCM formats.
        request.SetEventStreamHandler(handler);

        auto OnStreamReady = [](AudioStream &stream) {
                Aws::FStream file(FILE_NAME, std::ios_base::in |
std::ios_base::binary);
                if (!file.is_open()) {
                    std::cerr << "Failed to open " << FILE_NAME << '\n';
                }
                std::array<char, BUFFER_SIZE> buf;
                int i = 0;
                while (file) {
                    file.read(&buf[0], buf.size());

                    if (!file)
                        std::cout << "File: only " << file.gcount() << " could be
read"
                                  << std::endl;

                    Aws::Vector<unsigned char> bits{buf.begin(), buf.end()};
                    AudioEvent event(std::move(bits));
                    if (!stream) {
                        std::cerr << "Failed to create a stream" << std::endl;
                        break;
                    }
                    //The std::basic_istream::gcount() is used to count the
characters in the given string. It returns
```

```
                    //the number of characters extracted by the last read()
 operation.
                    if (file.gcount() > 0) {
                        if (!stream.WriteAudioEvent(event)) {
                            std::cerr << "Failed to write an audio event" <<
 std::endl;
                            break;
                        }
                    }
                    else {
                        break;
                    }
                    std::this_thread::sleep_for(std::chrono::milliseconds(
                            25)); // Slow down because we are streaming from a file.
                }
                if (!stream.WriteAudioEvent(
                        AudioEvent())) {
                    // Per the spec, we have to send an empty event (an event
 without a payload) at the end.
                    std::cerr << "Failed to send an empty frame" << std::endl;
                }
                else {
                    std::cout << "Successfully sent the empty frame" << std::endl;
                }
                stream.flush();
                stream.Close();
        };

        Aws::Utils::Threading::Semaphore signaling(0 /*initialCount*/, 1 /
*maxCount*/);
        auto OnResponseCallback = [&signaling](
                const TranscribeStreamingServiceClient * /*unused*/,
                const Model::StartStreamTranscriptionRequest & /*unused*/,
                const Model::StartStreamTranscriptionOutcome &outcome,
                const std::shared_ptr<const Aws::Client::AsyncCallerContext> & /
*unused*/) {

                if (!outcome.IsSuccess()) {
                    std::cerr << "Transcribe streaming error "
                              << outcome.GetError().GetMessage() << std::endl;
                }

                signaling.Release();
        };
```

```
        std::cout << "Starting..." << std::endl;
        client.StartStreamTranscriptionAsync(request, OnStreamReady,
 OnResponseCallback,
                                             nullptr /*context*/);
        signaling.WaitOne(); // Prevent the application from exiting until we're
 done.
        std::cout << "Done" << std::endl;
    }

    Aws::ShutdownAPI(options);

    return 0;
}
```

- For API details, see StartStreamTranscription in *AWS SDK for C++ API Reference*.

Scenarios

Transcribe an audio file

The following code example shows how to generate a transcription of a source audio file using Amazon Transcribe streaming.

SDK for C++

> **Note**
>
> There's more on GitHub. Find the complete example and learn how to set up and run in the AWS Code Examples Repository.

```
int main() {
    Aws::SDKOptions options;

    Aws::InitAPI(options);
    {
        //TODO(User): Set to the region of your AWS account.
        const Aws::String region = Aws::Region::US_WEST_2;
```

```
        //Load a profile that has been granted AmazonTranscribeFullAccess AWS
 managed permission policy.
        Aws::Client::ClientConfiguration config;
#ifdef _WIN32
        // ATTENTION: On Windows with the AWS C++ SDK, this example only runs if the
 SDK is built
        // with the curl library.
        // For more information, see the accompanying ReadMe.
        // For more information, see "Building the SDK for Windows with curl".
        // https://docs.aws.amazon.com/sdk-for-cpp/v1/developer-guide/setup-
windows.html
        //TODO(User): Update to the location of your .crt file.
        config.caFile = "C:/curl/bin/curl-ca-bundle.crt";
#endif
        config.region = region;

        TranscribeStreamingServiceClient client(config);
        StartStreamTranscriptionHandler handler;
        handler.SetOnErrorCallback(
                [](const Aws::Client::AWSError<TranscribeStreamingServiceErrors>
 &error) {
                        std::cerr << "ERROR: " + error.GetMessage() << std::endl;
                });
        //SetTranscriptEventCallback called for every 'chunk' of file transcripted.
        // Partial results are returned in real time.
        handler.SetTranscriptEventCallback([](const TranscriptEvent &ev) {
                for (auto &&r: ev.GetTranscript().GetResults()) {
                    if (r.GetIsPartial()) {
                        std::cout << "[partial] ";
                    }
                    else {
                        std::cout << "[Final] ";
                    }
                    for (auto &&alt: r.GetAlternatives()) {
                        std::cout << alt.GetTranscript() << std::endl;
                    }
                }
        });

        StartStreamTranscriptionRequest request;
        request.SetMediaSampleRateHertz(SAMPLE_RATE);
        request.SetLanguageCode(LanguageCode::en_US);
        request.SetMediaEncoding(
                MediaEncoding::pcm); // wav and aiff files are PCM formats.
```

```
        request.SetEventStreamHandler(handler);

        auto OnStreamReady = [](AudioStream &stream) {
                Aws::FStream file(FILE_NAME, std::ios_base::in |
std::ios_base::binary);
                if (!file.is_open()) {
                    std::cerr << "Failed to open " << FILE_NAME << '\n';
                }
                std::array<char, BUFFER_SIZE> buf;
                int i = 0;
                while (file) {
                    file.read(&buf[0], buf.size());

                    if (!file)
                        std::cout << "File: only " << file.gcount() << " could be
read"
                                  << std::endl;

                    Aws::Vector<unsigned char> bits{buf.begin(), buf.end()};
                    AudioEvent event(std::move(bits));
                    if (!stream) {
                        std::cerr << "Failed to create a stream" << std::endl;
                        break;
                    }
                    //The std::basic_istream::gcount() is used to count the
characters in the given string. It returns
                    //the number of characters extracted by the last read()
operation.
                    if (file.gcount() > 0) {
                        if (!stream.WriteAudioEvent(event)) {
                            std::cerr << "Failed to write an audio event" <<
std::endl;
                            break;
                        }
                    }
                    else {
                        break;
                    }
                    std::this_thread::sleep_for(std::chrono::milliseconds(
                            25)); // Slow down because we are streaming from a file.
                }
                if (!stream.WriteAudioEvent(
                        AudioEvent())) {
```

```
                    // Per the spec, we have to send an empty event (an event
 without a payload) at the end.
                    std::cerr << "Failed to send an empty frame" << std::endl;
                }
                else {
                    std::cout << "Successfully sent the empty frame" << std::endl;
                }
                stream.flush();
                stream.Close();
        };

        Aws::Utils::Threading::Semaphore signaling(0 /*initialCount*/, 1 /
*maxCount*/);
        auto OnResponseCallback = [&signaling](
                const TranscribeStreamingServiceClient * /*unused*/,
                const Model::StartStreamTranscriptionRequest & /*unused*/,
                const Model::StartStreamTranscriptionOutcome &outcome,
                const std::shared_ptr<const Aws::Client::AsyncCallerContext> & /
*unused*/) {

                if (!outcome.IsSuccess()) {
                    std::cerr << "Transcribe streaming error "
                              << outcome.GetError().GetMessage() << std::endl;
                }

                signaling.Release();
        };

        std::cout << "Starting..." << std::endl;
        client.StartStreamTranscriptionAsync(request, OnStreamReady,
 OnResponseCallback,
                                             nullptr /*context*/);
        signaling.WaitOne(); // Prevent the application from exiting until we're
 done.
        std::cout << "Done" << std::endl;
    }

    Aws::ShutdownAPI(options);

    return 0;
}
```

- For API details, see StartStreamTranscription in *AWS SDK for C++ API Reference*.

Security for AWS SDK for C++

Cloud security at Amazon Web Services (AWS) is the highest priority. As an AWS customer, you benefit from a data center and network architecture that is built to meet the requirements of the most security-sensitive organizations. Security is a shared responsibility between AWS and you. The Shared Responsibility Model describes this as Security of the Cloud and Security in the Cloud.

Security of the Cloud – AWS is responsible for protecting the infrastructure that runs all of the services offered in the AWS Cloud and providing you with services that you can use securely. Our security responsibility is the highest priority at AWS, and the effectiveness of our security is regularly tested and verified by third-party auditors as part of the AWS Compliance Programs.

Security in the Cloud – Your responsibility is determined by the AWS service you are using, and other factors including the sensitivity of your data, your organization's requirements, and applicable laws and regulations.

This AWS product or service follows the shared responsibility model through the specific Amazon Web Services (AWS) services it supports. For AWS service security information, see the AWS service security documentation page and AWS services that are in scope of AWS compliance efforts by compliance program.

Topics

- Data Protection in AWS SDK for C++
- Identity and Access Management
- Compliance Validation for this AWS Product or Service
- Resilience for this AWS Product or Service
- Infrastructure Security for this AWS Product or Service
- Enforcing a minimum TLS version in the AWS SDK for C++
- Amazon S3 Encryption Client Migration (V1 to V2)
- Amazon S3 Encryption Client Migration (V2 to V3)

Data Protection in AWS SDK for C++

The AWS shared responsibility model applies to data protection in AWS SDK for C++. As described in this model, AWS is responsible for protecting the global infrastructure that runs all of the

AWS Cloud. You are responsible for maintaining control over your content that is hosted on this infrastructure. You are also responsible for the security configuration and management tasks for the AWS services that you use. For more information about data privacy, see the Data Privacy FAQ. For information about data protection in Europe, see the AWS Shared Responsibility Model and GDPR blog post on the *AWS Security Blog*.

For data protection purposes, we recommend that you protect AWS account credentials and set up individual users with AWS IAM Identity Center or AWS Identity and Access Management (IAM). That way, each user is given only the permissions necessary to fulfill their job duties. We also recommend that you secure your data in the following ways:

- Use multi-factor authentication (MFA) with each account.
- Use SSL/TLS to communicate with AWS resources. We require TLS 1.2 and recommend TLS 1.3.
- Set up API and user activity logging with AWS CloudTrail. For information about using CloudTrail trails to capture AWS activities, see Working with CloudTrail trails in the *AWS CloudTrail User Guide*.
- Use AWS encryption solutions, along with all default security controls within AWS services.
- Use advanced managed security services such as Amazon Macie, which assists in discovering and securing sensitive data that is stored in Amazon S3.
- If you require FIPS 140-3 validated cryptographic modules when accessing AWS through a command line interface or an API, use a FIPS endpoint. For more information about the available FIPS endpoints, see Federal Information Processing Standard (FIPS) 140-3.

We strongly recommend that you never put confidential or sensitive information, such as your customers' email addresses, into tags or free-form text fields such as a **Name** field. This includes when you work with SDK for C++ or other AWS services using the console, API, AWS CLI, or AWS SDKs. Any data that you enter into tags or free-form text fields used for names may be used for billing or diagnostic logs. If you provide a URL to an external server, we strongly recommend that you do not include credentials information in the URL to validate your request to that server.

Identity and Access Management

AWS Identity and Access Management (IAM) is an AWS service that helps an administrator securely control access to AWS resources. IAM administrators control who can be *authenticated* (signed in) and *authorized* (have permissions) to use AWS resources. IAM is an AWS service that you can use with no additional charge.

Topics

- Audience
- Authenticating with identities
- Managing access using policies
- How AWS services work with IAM
- Troubleshooting AWS identity and access

Audience

How you use AWS Identity and Access Management (IAM) differs, depending on the work that you do in AWS.

Service user – If you use AWS services to do your job, then your administrator provides you with the credentials and permissions that you need. As you use more AWS features to do your work, you might need additional permissions. Understanding how access is managed can help you request the right permissions from your administrator. If you cannot access a feature in AWS, see Troubleshooting AWS identity and access or the user guide of the AWS service you are using.

Service administrator – If you're in charge of AWS resources at your company, you probably have full access to AWS. It's your job to determine which AWS features and resources your service users should access. You must then submit requests to your IAM administrator to change the permissions of your service users. Review the information on this page to understand the basic concepts of IAM. To learn more about how your company can use IAM with AWS, see the user guide of the AWS service you are using.

IAM administrator – If you're an IAM administrator, you might want to learn details about how you can write policies to manage access to AWS. To view example AWS identity-based policies that you can use in IAM, see the user guide of the AWS service you are using.

Authenticating with identities

Authentication is how you sign in to AWS using your identity credentials. You must be authenticated as the AWS account root user, an IAM user, or by assuming an IAM role.

You can sign in as a federated identity using credentials from an identity source like AWS IAM Identity Center (IAM Identity Center), single sign-on authentication, or Google/Facebook

credentials. For more information about signing in, see How to sign in to your AWS account in the *AWS Sign-In User Guide*.

For programmatic access, AWS provides an SDK and CLI to cryptographically sign requests. For more information, see AWS Signature Version 4 for API requests in the *IAM User Guide*.

AWS account root user

When you create an AWS account, you begin with one sign-in identity called the AWS account *root user* that has complete access to all AWS services and resources. We strongly recommend that you don't use the root user for everyday tasks. For tasks that require root user credentials, see Tasks that require root user credentials in the *IAM User Guide*.

Federated identity

As a best practice, require human users to use federation with an identity provider to access AWS services using temporary credentials.

A *federated identity* is a user from your enterprise directory, web identity provider, or Directory Service that accesses AWS services using credentials from an identity source. Federated identities assume roles that provide temporary credentials.

For centralized access management, we recommend AWS IAM Identity Center. For more information, see What is IAM Identity Center? in the *AWS IAM Identity Center User Guide*.

IAM users and groups

An *IAM user* is an identity with specific permissions for a single person or application. We recommend using temporary credentials instead of IAM users with long-term credentials. For more information, see Require human users to use federation with an identity provider to access AWS using temporary credentials in the *IAM User Guide*.

An *IAM group* specifies a collection of IAM users and makes permissions easier to manage for large sets of users. For more information, see Use cases for IAM users in the *IAM User Guide*.

IAM roles

An *IAM role* is an identity with specific permissions that provides temporary credentials. You can assume a role by switching from a user to an IAM role (console) or by calling an AWS CLI or AWS API operation. For more information, see Methods to assume a role in the *IAM User Guide*.

IAM roles are useful for federated user access, temporary IAM user permissions, cross-account access, cross-service access, and applications running on Amazon EC2. For more information, see Cross account resource access in IAM in the *IAM User Guide*.

Managing access using policies

You control access in AWS by creating policies and attaching them to AWS identities or resources. A policy defines permissions when associated with an identity or resource. AWS evaluates these policies when a principal makes a request. Most policies are stored in AWS as JSON documents. For more information about JSON policy documents, see Overview of JSON policies in the *IAM User Guide*.

Using policies, administrators specify who has access to what by defining which **principal** can perform **actions** on what **resources**, and under what **conditions**.

By default, users and roles have no permissions. An IAM administrator creates IAM policies and adds them to roles, which users can then assume. IAM policies define permissions regardless of the method used to perform the operation.

Identity-based policies

Identity-based policies are JSON permissions policy documents that you attach to an identity (user, group, or role). These policies control what actions identities can perform, on which resources, and under what conditions. To learn how to create an identity-based policy, see Define custom IAM permissions with customer managed policies in the *IAM User Guide*.

Identity-based policies can be *inline policies* (embedded directly into a single identity) or *managed policies* (standalone policies attached to multiple identities). To learn how to choose between managed and inline policies, see Choose between managed policies and inline policies in the *IAM User Guide*.

Resource-based policies

Resource-based policies are JSON policy documents that you attach to a resource. Examples include IAM *role trust policies* and Amazon S3 *bucket policies*. In services that support resource-based policies, service administrators can use them to control access to a specific resource. You must specify a principal in a resource-based policy.

Resource-based policies are inline policies that are located in that service. You can't use AWS managed policies from IAM in a resource-based policy.

Access control lists (ACLs)

Access control lists (ACLs) control which principals (account members, users, or roles) have permissions to access a resource. ACLs are similar to resource-based policies, although they do not use the JSON policy document format.

Amazon S3, AWS WAF, and Amazon VPC are examples of services that support ACLs. To learn more about ACLs, see Access control list (ACL) overview in the *Amazon Simple Storage Service Developer Guide*.

Other policy types

AWS supports additional policy types that can set the maximum permissions granted by more common policy types:

- **Permissions boundaries** – Set the maximum permissions that an identity-based policy can grant to an IAM entity. For more information, see Permissions boundaries for IAM entities in the *IAM User Guide*.
- **Service control policies (SCPs)** – Specify the maximum permissions for an organization or organizational unit in AWS Organizations. For more information, see Service control policies in the *AWS Organizations User Guide*.
- **Resource control policies (RCPs)** – Set the maximum available permissions for resources in your accounts. For more information, see Resource control policies (RCPs) in the *AWS Organizations User Guide*.
- **Session policies** – Advanced policies passed as a parameter when creating a temporary session for a role or federated user. For more information, see Session policies in the *IAM User Guide*.

Multiple policy types

When multiple types of policies apply to a request, the resulting permissions are more complicated to understand. To learn how AWS determines whether to allow a request when multiple policy types are involved, see Policy evaluation logic in the *IAM User Guide*.

How AWS services work with IAM

To get a high-level view of how AWS services work with most IAM features, see AWS services that work with IAM in the *IAM User Guide*.

To learn how to use a specific AWS service with IAM, see the security section of the relevant service's User Guide.

Troubleshooting AWS identity and access

Use the following information to help you diagnose and fix common issues that you might encounter when working with AWS and IAM.

Topics

- I am not authorized to perform an action in AWS
- I am not authorized to perform iam:PassRole
- I want to allow people outside of my AWS account to access my AWS resources

I am not authorized to perform an action in AWS

If you receive an error that you're not authorized to perform an action, your policies must be updated to allow you to perform the action.

The following example error occurs when the `mateojackson` IAM user tries to use the console to view details about a fictional *`my-example-widget`* resource but doesn't have the fictional `awes:`*`GetWidget`* permissions.

```
User: arn:aws:iam::123456789012:user/mateojackson is not authorized to perform:
 awes:GetWidget on resource: my-example-widget
```

In this case, the policy for the `mateojackson` user must be updated to allow access to the *`my-example-widget`* resource by using the `awes:`*`GetWidget`* action.

If you need help, contact your AWS administrator. Your administrator is the person who provided you with your sign-in credentials.

I am not authorized to perform iam:PassRole

If you receive an error that you're not authorized to perform the `iam:PassRole` action, your policies must be updated to allow you to pass a role to AWS.

Some AWS services allow you to pass an existing role to that service instead of creating a new service role or service-linked role. To do this, you must have permissions to pass the role to the service.

The following example error occurs when an IAM user named `marymajor` tries to use the console to perform an action in AWS. However, the action requires the service to have permissions that are granted by a service role. Mary does not have permissions to pass the role to the service.

```
User: arn:aws:iam::123456789012:user/marymajor is not authorized to perform:
 iam:PassRole
```

In this case, Mary's policies must be updated to allow her to perform the `iam:PassRole` action.

If you need help, contact your AWS administrator. Your administrator is the person who provided you with your sign-in credentials.

I want to allow people outside of my AWS account to access my AWS resources

You can create a role that users in other accounts or people outside of your organization can use to access your resources. You can specify who is trusted to assume the role. For services that support resource-based policies or access control lists (ACLs), you can use those policies to grant people access to your resources.

To learn more, consult the following:

- To learn whether AWS supports these features, see How AWS services work with IAM.
- To learn how to provide access to your resources across AWS accounts that you own, see Providing access to an IAM user in another AWS account that you own in the *IAM User Guide*.
- To learn how to provide access to your resources to third-party AWS accounts, see Providing access to AWS accounts owned by third parties in the *IAM User Guide*.
- To learn how to provide access through identity federation, see Providing access to externally authenticated users (identity federation) in the *IAM User Guide*.
- To learn the difference between using roles and resource-based policies for cross-account access, see Cross account resource access in IAM in the *IAM User Guide*.

Compliance Validation for this AWS Product or Service

To learn whether an AWS service is within the scope of specific compliance programs, see AWS services in Scope by Compliance Program and choose the compliance program that you are interested in. For general information, see AWS Compliance Programs.

You can download third-party audit reports using AWS Artifact. For more information, see Downloading Reports in AWS Artifact.

Your compliance responsibility when using AWS services is determined by the sensitivity of your data, your company's compliance objectives, and applicable laws and regulations. For more information about your compliance responsibility when using AWS services, see AWS Security Documentation.

This AWS product or service follows the shared responsibility model through the specific Amazon Web Services (AWS) services it supports. For AWS service security information, see the AWS service security documentation page and AWS services that are in scope of AWS compliance efforts by compliance program.

Resilience for this AWS Product or Service

The AWS global infrastructure is built around AWS Regions and Availability Zones.

AWS Regions provide multiple physically separated and isolated Availability Zones, which are connected with low-latency, high-throughput, and highly redundant networking.

With Availability Zones, you can design and operate applications and databases that automatically fail over between zones without interruption. Availability Zones are more highly available, fault tolerant, and scalable than traditional single or multiple data center infrastructures.

For more information about AWS Regions and Availability Zones, see AWS Global Infrastructure.

This AWS product or service follows the shared responsibility model through the specific Amazon Web Services (AWS) services it supports. For AWS service security information, see the AWS service security documentation page and AWS services that are in scope of AWS compliance efforts by compliance program.

Infrastructure Security for this AWS Product or Service

This AWS product or service uses managed services, and therefore is protected by the AWS global network security. For information about AWS security services and how AWS protects infrastructure, see AWS Cloud Security. To design your AWS environment using the best practices for infrastructure security, see Infrastructure Protection in *Security Pillar AWS Well-Architected Framework*.

You use AWS published API calls to access this AWS Product or Service through the network. Clients must support the following:

- Transport Layer Security (TLS). We require TLS 1.2 and recommend TLS 1.3.
- Cipher suites with perfect forward secrecy (PFS) such as DHE (Ephemeral Diffie-Hellman) or ECDHE (Elliptic Curve Ephemeral Diffie-Hellman). Most modern systems such as Java 7 and later support these modes.

Additionally, requests must be signed by using an access key ID and a secret access key that is associated with an IAM principal. Or you can use the AWS Security Token Service (AWS STS) to generate temporary security credentials to sign requests.

This AWS product or service follows the shared responsibility model through the specific Amazon Web Services (AWS) services it supports. For AWS service security information, see the AWS service security documentation page and AWS services that are in scope of AWS compliance efforts by compliance program.

Enforcing a minimum TLS version in the AWS SDK for C++

To increase security when communicating with AWS services, you should configure SDK for C++ to use TLS 1.2 or later. We recommend using TLS 1.3.

The AWS SDK for C++ is a cross-platform library. You can build and run your application on the platforms you want. Different platforms might depend on different underlying HTTP clients.

By default, macOS, Linux, Android and other non-Windows platforms use libcurl. If the libcurl version is later than 7.34.0, TLS 1.0 is the minimum version used by the underlying HTTP clients.

For Windows, the default library is WinHttp. Windows decides the actual protocol to use among the TLS 1.0, TLS 1.1, TLS 1.2, and TLS 1.3 protocols available. WinINet and IXMLHttpRequest2 are the other two options that are available on Windows. You can configure your application to replace the default library during CMake and at runtime. For these two HTTP clients, Windows also decides the secure protocol.

The AWS SDK for C++ also provides the flexibility to override the default HTTP clients. For example, you can enforce libcurl or use whatever HTTP clients you want by using a custom HTTP client factory. So to use TLS 1.2 as the minimum version, you must be aware of the HTTP client library you're using.

Enforce specific TLS version with libcurl on all platforms

This section assumes that the AWS SDK for C++ is using libcurl as a dependency for HTTP protocol support. To explicitly specify the TLS version, you will need a minimum libcurl version of 7.34.0. In addition, you might need to modify the source code of the AWS SDK for C++ and then rebuild it.

The following procedure shows you how to perform these tasks.

To enforce TLS 1.2 with libcurl

1. Verify that your installation of libcurl is at least version 7.34.0.
2. Download the source code for the AWS SDK for C++ from GitHub.
3. Open `aws-cpp-sdk-core/source/http/curl/CurlHttpClient.cpp` and find the following lines of code.

```
#if LIBCURL_VERSION_MAJOR >= 7
#if LIBCURL_VERSION_MINOR >= 34
curl_easy_setopt(connectionHandle, CURLOPT_SSLVERSION, CURL_SSLVERSION_TLSv1);
#endif //LIBCURL_VERSION_MINOR
#endif //LIBCURL_VERSION_MAJOR
```

4. If necessary, change the last parameter in the function call as follows.

```
#if LIBCURL_VERSION_MAJOR >= 7
#if LIBCURL_VERSION_MINOR >= 34
curl_easy_setopt(connectionHandle, CURLOPT_SSLVERSION, CURL_SSLVERSION_TLSv1_2);
#endif //LIBCURL_VERSION_MINOR
#endif //LIBCURL_VERSION_MAJOR
```

5. If you performed the preceding code changes, build and install the AWS SDK for C++ according to the instructions at https://github.com/aws/aws-sdk-cpp#building-the-sdk.
6. For the service client in your application, enable `verifySSL` in its client configuration, if this option isn't already enabled.

To enforce TLS 1.3 with libcurl

To enforce TLS 1.3, follow the steps in the preceding section setting the `CURL_SSLVERSION_TLSv1_3` option instead of `CURL_SSLVERSION_TLSv1_2`.

Enforce specific TLS version on Windows

The following procedures show you how to enforce TLS 1.2 or TLS 1.3 with WinHttp, WinINet, or IXMLHTTPRequest2.

Prerequisite: Determine Windows TLS support

- Determine the TLS protocol version support available for your system as described at https://docs.microsoft.com/en-us/windows/win32/secauthn/protocols-in-tls-ssl–schannel-ssp-.
- If you're running on Windows 7 SP1 or Windows Server 2008 R2 SP1, you need to ensure that TLS 1.2 support is enabled in the registry, as described at https://docs.microsoft.com/en-us/windows-server/security/tls/tls-registry-settings#tls-12. If you're running an earlier distribution, you must upgrade your operating system.

To enforce TLS 1.2 or TLS 1.3 with WinHttp

WinHttp provides an API to explicitly set the acceptable secure protocols. However, to make this configurable at runtime, you need to modify the source code of the AWS SDK for C++ and then rebuild it.

1. Download the source code for the AWS SDK for C++ from GitHub.
2. Open `aws-cpp-sdk-core/source/http/windows/WinHttpSyncHttpClient.cpp` and find the following lines of code.

```
#if defined(WINHTTP_FLAG_SECURE_PROTOCOL_TLS1_3)
    DWORD flags = WINHTTP_FLAG_SECURE_PROTOCOL_TLS1 |
 WINHTTP_FLAG_SECURE_PROTOCOL_TLS1_1 |
            WINHTTP_FLAG_SECURE_PROTOCOL_TLS1_2 |
 WINHTTP_FLAG_SECURE_PROTOCOL_TLS1_3;
#else
    DWORD flags = WINHTTP_FLAG_SECURE_PROTOCOL_TLS1 |
 WINHTTP_FLAG_SECURE_PROTOCOL_TLS1_1 | WINHTTP_FLAG_SECURE_PROTOCOL_TLS1_2;
#endif

if (!WinHttpSetOption(GetOpenHandle(), WINHTTP_OPTION_SECURE_PROTOCOLS, &flags,
 sizeof(flags)))
{
    AWS_LOGSTREAM_FATAL(GetLogTag(), "Failed setting secure crypto protocols with
 error code: " << GetLastError());
```

```
}
```

The `WINHTTP_FLAG_SECURE_PROTOCOL_TLS1_3` option flag is defined if TLS 1.3 is present on the current build system. For more information, see WINHTTP_OPTION_SECURE_PROTOCOLS and TLS protocol version support on the Microsoft website.

3. Choose one of the following:

   - **To enforce TLS 1.2:**

     Under the `#else` directive, change the value of the `flags` variable, as follows.

     ```
     DWORD flags = WINHTTP_FLAG_SECURE_PROTOCOL_TLS1_2;
     ```

   - **To enforce TLS 1.3:**

     Under the `#if defined(WINHTTP_FLAG_SECURE_PROTOCOL_TLS1_3)` directive, change the value of the `flags` variable, as follows.

     ```
     DWORD flags = WINHTTP_FLAG_SECURE_PROTOCOL_TLS1_3;
     ```

4. If you performed the preceding code changes, build and install the AWS SDK for C++ according to the instructions at https://github.com/aws/aws-sdk-cpp#building-the-sdk.
5. For the service client in your application, enable `verifySSL` in its client configuration, if this option isn't already enabled.

To enforce TLS 1.2 with WinINet and IXMLHTTPRequest2

There is no API to specify the secure protocol for the WinINet and IXMLHTTPRequest2 libraries. So the AWS SDK for C++ uses the default for the operating system. You can update the Windows registry to enforce the use of TLS 1.2, as shown in the following procedure. Be advised, however, that the result is a global change that impacts all applications that depend on Schannel.

1. Open Registry Editor and go to `Computer\HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Control\SecurityProviders\SCHANNEL\Protocols`.
2. If they don't already exist, create the following subkeys: `TLS 1.0,`, `TLS 1.1`, and `TLS 1.2`.
3. Under each of the subkeys, create a `Client` subkey and a `Server` subkey.
4. Create the following keys and values.

```
Key name                           Key type   Value
--------                           ---------  -----
TLS 1.0\Client\DisabledByDefault   DWORD      0
TLS 1.1\Client\DisabledByDefault   DWORD      0
TLS 1.2\Client\DisabledByDefault   DWORD      0
TLS 1.0\Client\Enabled             DWORD      0
TLS 1.1\Client\Enabled             DWORD      0
TLS 1.2\Client\Enabled             DWORD      1
```

Notice that `TLS 1.2\Client\Enabled` is the only key that's set to 1. Setting this key to 1 enforces TLS 1.2 as the only acceptable secure protocol.

To enforce TLS 1.3 with WinINet and IXMLHTTPRequest2

There is no API to specify the secure protocol for the WinINet and IXMLHTTPRequest2 libraries. So the AWS SDK for C++ uses the default for the operating system. You can update the Windows registry to enforce the use of TLS 1.3, as shown in the following procedure. Be advised, however, that the result is a global change that impacts all applications that depend on Schannel.

1. Open Registry Editor and go to `Computer\HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Control\SecurityProviders\SCHANNEL\Protocols`.
2. If they don't already exist, create the following subkeys: `TLS 1.0,`, `TLS 1.1`, `TLS 1.2` and `TLS 1.3`.
3. Under each of the subkeys, create a `Client` subkey and a `Server` subkey.
4. Create the following keys and values.

```
Key name                           Key type   Value
--------                           ---------  -----
TLS 1.0\Client\DisabledByDefault   DWORD      0
TLS 1.1\Client\DisabledByDefault   DWORD      0
TLS 1.2\Client\DisabledByDefault   DWORD      0
TLS 1.3\Client\DisabledByDefault   DWORD      0
TLS 1.0\Client\Enabled             DWORD      0
TLS 1.1\Client\Enabled             DWORD      0
TLS 1.2\Client\Enabled             DWORD      0
TLS 1.3\Client\Enabled             DWORD      1
```

Notice that `TLS 1.3\Client\Enabled` is the only key that's set to 1. Setting this key to 1 enforces TLS 1.3 as the only acceptable secure protocol.

Amazon S3 Encryption Client Migration (V1 to V2)

> **Note**
>
> If you are using V2 of the Amazon S3 encryption client and want to migrate to V3, see Amazon S3 Encryption Client Migration (V2 to V3).

This topic shows how to migrate your applications from Version 1 (V1) of the Amazon Simple Storage Service (Amazon S3) encryption client to Version 2 (V2) and ensure application availability throughout the migration process.

Migration Overview

This migration happens in two phases:

1. **Update existing clients to read new formats.** First, deploy an updated version of the AWS SDK for C++ to your application. This allows existing V1 encryption clients to decrypt objects written by the new V2 clients. If your application uses multiple AWS SDKs, you must upgrade each SDK separately.

2. **Migrate encryption and decryption clients to V2.** Once all of your V1 encryption clients can read new formats, you can migrate your existing encryption and decryption clients to their respective V2 versions.

Update Existing Clients to Read New Formats

You must first update your existing clients to the latest SDK release. After completing this step, your application's V1 clients will be able to decrypt objects encrypted by V2 encryption clients without updating your application's code base.

Build and Install the Latest Version of the AWS SDK for C++

Applications Consuming the SDK from Source

If you build and install the AWS SDK for C++ from source, download or clone the SDK source from aws/aws-sdk-cpp on GitHub . Then repeat your normal build and install steps.

If you are upgrading AWS SDK for C++ from a version earlier than 1.8.x, see this CHANGELOG for breaking changes introduced in each major version. For more information about how to build and install the AWS SDK for C++, see Getting the AWS SDK for C++ from source code.

Applications Consuming the SDK from Vcpkg

If your application uses Vcpkg to track SDK updates, simply use your existing Vcpkg upgrade method to upgrade the SDK to the latest version. Keep in mind, there is a delay between when a version is released and when it is available through a package manager. The most recent version is always available through installing from source.

You can run the following command to upgrade package `aws-sdk-cpp`:

```
vcpkg upgrade aws-sdk-cpp
```

And verify the version of package `aws-sdk-cpp`:

```
vcpkg list aws-sdk-cpp
```

The version should be at least 1.8.24.

For more information on using Vcpkg with the AWS SDK for C++, see Getting the AWS SDK for C++ from a package manager.

Build, Install, and Deploy Your Applications

If your application is statically linking against the AWS SDK for C++, code changes are not required in your application, but you must build your application again to consume the latest SDK changes. This step is not necessary for dynamic linking.

After upgrading your application's dependency version and verifying application functionality, proceed to deploying your application to your fleet. Once application deployment is complete, you can proceed with the next phase for migrating your application to use the V2 encryption and decryption clients.

Migrate Encryption and Decryption Clients to V2

The following steps show you how to successfully migrate your code from V1 to V2 of the Amazon S3 encryption client. Since code changes are required, you will need to rebuild your application regardless of whether it's statically or dynamically linking against the AWS SDK for C++.

Using New Encryption Materials

With V2 Amazon S3 encryption clients and the V2 crypto configuration, the following encryption materials have been deprecated:

- `SimpleEncryptionMaterials`
- `KMSEncryptionMaterials`

They have been replaced with the following secure encryption materials:

- `SimpleEncryptionMaterialsWithGCMAAD`
- `KMSWithContextEncryptionMaterials`

The following code changes are required to construct a V2 S3 encryption client:

- **If you are using `KMSEncryptionMaterials` when creating an S3 encryption client:**
  - When creating a V2 S3 encryption client, replace `KMSEncryptionMaterials` with `KMSWithContextEncryptionMaterials` and specify it in the V2 crypto configuration.
  - When putting an object with V2 Amazon S3 encryption clients, you must explicitly provide a string-string context map as the KMS context for encrypting the CEK. This might be an empty map.
- **If you are using `SimpleEncryptionMaterials` when creating an S3 encryption client:**
  - When creating a V2 Amazon S3 encryption client, replace `SimpleEncryptionMaterials` with `SimpleEncryptionMaterialsWithGCMAAD` and specify it in the V2 crypto configuration.
  - When putting an object with V2 Amazon S3 encryption clients, you must explicitly provide an empty string-string context map, otherwise the SDK will return an error.

Example: Using the KMS/KMSWithContext Key Wrap Algorithm

Pre-migration (KMS key wrap)

```
auto materials = Aws::MakeShared<KMSEncryptionMaterials>("s3Encryption",
 CUSTOMER_MASTER_KEY_ID);
CryptoConfiguration cryptoConfig;
S3EncryptionClient encryptionClient(materials, cryptoConfig);
// Code snippet here to setup the putObjectRequest object.
encryptionClient.PutObject(putObjectRequest);
```

Post-migration (KMSWithContext key wrap)

```
auto materials = Aws::MakeShared<KMSWithContextEncryptionMaterials>("s3EncryptionV2",
 CUSTOMER_MASTER_KEY_ID);
CryptoConfigurationV2 cryptoConfig(materials);
S3EncryptionClientV2 encryptionClient(cryptoConfig);
// Code snippet here to setup the putObjectRequest object.
Aws::Map<Aws::String, Aws::String> kmsContextMap;
kmsContextMap.emplace("client", "aws-sdk-cpp");
kmsContextMap.emplace("version", "1.8.0");
encryptionClient.PutObject(putObjectRequest, kmsContextMap /* could be empty as well
 */);
```

Example: Using the AES/AES-GCM Key Wrap Algorithm

Pre-migration (AES key wrap)

```
auto materials = Aws::MakeShared<SimpleEncryptionMaterials>("s3Encryption",
 HashingUtils::Base64Decode(AES_MASTER_KEY_BASE64));
CryptoConfiguration cryptoConfig;
S3EncryptionClient encryptionClient(materials, cryptoConfig);
// Code snippet here to setup the putObjectRequest object.
encryptionClient.PutObject(putObjectRequest);
```

Post-migration (AES-GCM key wrap)

```
auto materials = Aws::MakeShared<SimpleEncryptionMaterialsWithGCMAAD>("s3EncryptionV2",
 HashingUtils::Base64Decode(AES_MASTER_KEY_BASE64));
CryptoConfigurationV2 cryptoConfig(materials);
S3EncryptionClientV2 encryptionClient(cryptoConfig);
// Code snippet here to setup the putObjectRequest object.
encryptionClient.PutObject(putObjectRequest, {} /* must be an empty map */);
```

Additional Examples

The following examples demonstrate how to address specific use cases related to a migration from V1 to V2.

Decrypt Objects Encrypted by Legacy Amazon S3 Encryption Clients

By default, you can't use the V2 Amazon S3 encryption client to decrypt objects that were encrypted with deprecated key wrap algorithms or deprecated content crypto schemas.

The following key wrap algorithms have been deprecated:

- `KMS`
- `AES_KEY_WRAP`

And the following content crypto schemas have been deprecated:

- `CBC`
- `CTR`

If you're using legacy Amazon S3 encryption clients in the AWS SDK for C++ to encrypt the objects, you're likely using the deprecated methods if:

- You used `SimpleEncryptionMaterials` or `KMSEncryptionMaterials`.
- You used `ENCRYPTION_ONLY` as `Crypto Mode` in your crypto configuration.

To use the V2 Amazon S3 encryption client to decrypt objects that were encrypted by deprecated key wrap algorithms or deprecated content crypto schemas, you must override the default value of `SecurityProfile` in the V2 crypto configuration from `V2` to `V2_AND_LEGACY`.

Example

Pre-migration

```
auto materials = Aws::MakeShared<KMSEncryptionMaterials>("s3Encryption",
 CUSTOMER_MASTER_KEY_ID);
CryptoConfiguration cryptoConfig;
S3EncryptionClient encryptionClient(materials, cryptoConfig);
```

```
// Code snippet here to setup the getObjectRequest object.
encryptionClient.GetObject(getObjectRequest);
```

Post-migration

```
auto materials = Aws::MakeShared<KMSWithContextEncryptionMaterials>("s3EncryptionV2",
 CUSTOMER_MASTER_KEY_ID);
CryptoConfigurationV2 cryptoConfig(materials);
cryptoConfig.SetSecurityProfile(SecurityProfile::V2_AND_LEGACY);
S3EncryptionClientV2 encryptionClient(cryptoConfig);
// Code snippet here to setup the getObjectRequest object.
encryptionClient.GetObject(getObjectRequest);
```

Decrypt Objects with Range

With legacy Amazon S3 encryption clients, you can specify a range of bytes to receive when decrypting an S3 object. In the V2 Amazon S3 encryption client, this feature is `DISABLED` by default. Therefore you have to override the default value of `RangeGetMode` from `DISABLED` to `ALL` in the V2 crypto configuration.

Example

Pre-migration

```
auto materials = Aws::MakeShared<KMSEncryptionMaterials>("s3Encryption",
 CUSTOMER_MASTER_KEY_ID);
CryptoConfiguration cryptoConfig;
S3EncryptionClient encryptionClient(materials, cryptoConfig);
// Code snippet here to setup the getObjectRequest object.
getObjectRequest.WithRange("bytes=38-75");
encryptionClient.GetObject(getObjectRequest);
```

Post-migration

```
auto materials = Aws::MakeShared<KMSWithContextEncryptionMaterials>("s3EncryptionV2",
 CUSTOMER_MASTER_KEY_ID);
CryptoConfigurationV2 cryptoConfig(materials);
cryptoConfig.SetUnAuthenticatedRangeGet(RangeGetMode::ALL);
S3EncryptionClientV2 encryptionClient(cryptoConfig);
// Code snippet here to setup the getObjectRequest object.
getObjectRequest.WithRange("bytes=38-75");
```

```
encryptionClient.GetObject(getObjectRequest);
```

Decrypt Objects with any CMK

When decrypting objects that were encrypted with `KMSWithContextEncryptionMaterials`, V2 Amazon S3 encryption clients are capable of letting KMS to find the proper CMK by providing an empty master key. This feature is `DISABLED` by default. You have to configure it explicitly by calling `SetKMSDecryptWithAnyCMK(true)` for your KMS encryption materials.

Example

Pre-migration

```
auto materials = Aws::MakeShared<KMSEncryptionMaterials>("s3Encryption", ""/* provide
 an empty KMS Master Key*/);
CryptoConfiguration cryptoConfig;
S3EncryptionClient encryptionClient(materials, cryptoConfig);
// Code snippet here to setup the getObjectRequest object.
encryptionClient.GetObject(getObjectRequest);
```

Post-migration

```
auto materials = Aws::MakeShared<KMSWithContextEncryptionMaterials>("s3EncryptionV2",
 ""/* provide an empty KMS Master Key*/);
materials.SetKMSDecryptWithAnyCMK(true);
CryptoConfigurationV2 cryptoConfig(materials);
S3EncryptionClientV2 encryptionClient(cryptoConfig);
// Code snippet here to setup the getObjectRequest object.
encryptionClient.GetObject(getObjectRequest);
```

For complete code for all of these migration scenarios, see the Amazon S3 Encryption example on Github.

Amazon S3 Encryption Client Migration (V2 to V3)

> **Note**
>
> If you are using V1 of the Amazon S3 encryption client, you must first migrate to V2 before migrating to V3. See Amazon S3 Encryption Client Migration (V1 to V2).

This topic shows how to migrate your applications from Version 2 (V2) to Version 3 (V3) of the Amazon Simple Storage Service (Amazon S3) encryption client and ensure application availability throughout the migration process. V3 introduces the `ALG_AES_256_GCM_HKDF_SHA512_COMMIT_KEY` algorithm and Commitment Policies to enhance security by protecting against data key tampering in Instruction Files.

Migration Overview

This migration happens in two phases:

1. **Update existing clients to read new formats.** First, deploy an updated version of the AWS SDK for C++ to your application. This allows existing V2 encryption clients to decrypt objects written by the new V3 clients. If your application uses multiple AWS SDKs, you must upgrade each SDK separately.

2. **Migrate encryption and decryption clients to V3.** Once all of your V2 encryption clients can read new formats, you can migrate your existing encryption and decryption clients to their respective V3 versions.

Understanding V3 Concepts

Version 3 of the Amazon S3 encryption client introduces new security features that enhance protection against data key tampering. Understanding these concepts is essential for a successful migration.

Commitment Policy

Commitment Policies control how the encryption client handles key commitment during encryption and decryption operations. V3 provides three policy options to support different migration scenarios and security requirements:

`FORBID_ENCRYPT_ALLOW_DECRYPT`

Encryption behavior: Encrypts objects without key commitment, using the same algorithms as V2.

Decryption behavior: Allows decryption of objects encrypted with and without key commitment.

Security implications: This policy does not enforce key commitment and may allow tampering with the encrypted data key in Instruction Files. Use this policy only during the initial migration phase when you need V2 clients to read newly encrypted objects.

Version compatibility: Objects encrypted with this policy can be read by all V2 and V3 implementations.

`REQUIRE_ENCRYPT_ALLOW_DECRYPT` (Default)

Encryption behavior: Encrypts objects with key commitment using the `ALG_AES_256_GCM_HKDF_SHA512_COMMIT_KEY` algorithm.

Decryption behavior: Allows decryption of both objects encrypted with key commitment and objects encrypted without key commitment.

Security implications: This policy provides strong security for newly encrypted objects while maintaining backward compatibility for reading older objects. This is the recommended policy for most migration scenarios.

Version compatibility: Objects encrypted with this policy can only be read by V3 and the latest V2 implementations. V2 clients cannot decrypt these objects. However, V3 clients using this policy can still decrypt objects encrypted by V2 clients.

`REQUIRE_ENCRYPT_REQUIRE_DECRYPT`

Encryption behavior: Encrypts objects with key commitment using the `ALG_AES_256_GCM_HKDF_SHA512_COMMIT_KEY` algorithm.

Decryption behavior: Only allows decryption of objects encrypted with key commitment. Rejects objects encrypted without key commitment.

Security implications: This policy provides the highest level of security by enforcing key commitment for all operations. Use this policy only after all objects have been re-encrypted with key commitment and you no longer need to read legacy V1 or V2 encrypted objects.

Version compatibility: Objects encrypted with this policy can only be read by V3 and the latest V2 implementations. Additionally, clients using this policy cannot decrypt objects encrypted by V1 or V2 clients.

Migration considerations: During migration, start with `FORBID_ENCRYPT_ALLOW_DECRYPT` if you need V2 clients to read new objects, then move to `REQUIRE_ENCRYPT_ALLOW_DECRYPT` once all

clients are upgraded to V3. Finally, consider `REQUIRE_ENCRYPT_REQUIRE_DECRYPT` only after all legacy objects have been re-encrypted.

ALG_AES_256_GCM_HKDF_SHA512_COMMIT_KEY Algorithm

The `ALG_AES_256_GCM_HKDF_SHA512_COMMIT_KEY` algorithm is a new encryption algorithm introduced in V3 that provides enhanced security for encrypted data keys stored in Instruction Files.

Instruction File impact: The `ALG_AES_256_GCM_HKDF_SHA512_COMMIT_KEY` algorithm only impacts Instruction Files, which are separate S3 objects that store encryption metadata including the encrypted data key. Objects that store encryption metadata in object metadata (the default storage method) are not affected by this algorithm change.

Protection against tampering: The `ALG_AES_256_GCM_HKDF_SHA512_COMMIT_KEY` algorithm protects against data key tampering by cryptographically binding the encrypted data key to the encryption context. This prevents attackers from substituting a different encrypted data key in the Instruction File, which could potentially lead to decryption with an unintended key.

Version compatibility: Objects encrypted with the `ALG_AES_256_GCM_HKDF_SHA512_COMMIT_KEY` algorithm can only be decrypted by V3 implementations and the latest V2 transition versions of the SDK that include V3 decryption support.

> **Warning**
>
> **Important:** Before enabling encryption with the `ALG_AES_256_GCM_HKDF_SHA512_COMMIT_KEY` algorithm (by using `REQUIRE_ENCRYPT_ALLOW_DECRYPT` or `REQUIRE_ENCRYPT_REQUIRE_DECRYPT` commitment policies), you must ensure that all clients that will read these objects have been upgraded to V3 or the latest V2 transition version that supports V3 decryption. Failure to upgrade all readers first will result in decryption failures for newly encrypted objects.

Update Existing Clients to Read New Formats

You must first update your existing clients to the latest SDK release. After completing this step, your application's V2 clients will be able to decrypt objects encrypted by V3 encryption clients without updating your application's code base.

Build and Install the Latest Version of the AWS SDK for C++

Applications Consuming the SDK from Source

If you build and install the AWS SDK for C++ from source, download or clone the SDK source from `aws/aws-sdk-cpp` on GitHub . Then repeat your normal build and install steps.

If you are upgrading AWS SDK for C++ from a version earlier than 1.11.x, see this CHANGELOG for breaking changes introduced in each major version. For more information about how to build and install the AWS SDK for C++, see Getting the AWS SDK for C++ from source code.

Applications Consuming the SDK from Vcpkg

If your application uses Vcpkg to track SDK updates, simply use your existing Vcpkg upgrade method to upgrade the SDK to the latest version. Keep in mind, there is a delay between when a version is released and when it is available through a package manager. The most recent version is always available through installing from source.

You can run the following command to upgrade package `aws-sdk-cpp`:

```
vcpkg upgrade aws-sdk-cpp
```

And verify the version of package `aws-sdk-cpp`:

```
vcpkg list aws-sdk-cpp
```

The version should be at least 1.11.x to support decryption of V3-encrypted objects.

For more information on using Vcpkg with the AWS SDK for C++, see Getting the AWS SDK for C++ from a package manager.

Build, Install, and Deploy Your Applications

If your application is statically linking against the AWS SDK for C++, code changes are not required in your application, but you must build your application again to consume the latest SDK changes. This step is not necessary for dynamic linking.

After upgrading your application's dependency version and verifying application functionality, proceed to deploying your application to your fleet. Once application deployment is complete, you can proceed with the next phase for migrating your application to use the V3 encryption and decryption clients.

Migrate Encryption and Decryption Clients to V3

The following steps show you how to successfully migrate your code from V2 to V3 of the Amazon S3 encryption client. Since code changes are required, you will need to rebuild your application regardless of whether it's statically or dynamically linking against the AWS SDK for C++.

Using V3 Encryption Clients

V3 introduces the `S3EncryptionClientV3` class and `CryptoConfigurationV3` to replace the V2 equivalents. The key differences in V3 are:

- V3 uses `KMSWithContextEncryptionMaterials` (same as V2) but requires explicit configuration in `CryptoConfigurationV3`.
- All `PutObject` operations require an encryption context map (can be empty).
- V3 introduces Commitment Policies to control encryption and decryption behavior.
- By default, V3 encrypts with key commitment using the `ALG_AES_256_GCM_HKDF_SHA512_COMMIT_KEY` algorithm.
- The legacy algorithm decryption configuration API changes from `config.SetSecurityProfile(SecurityProfile::V2_AND_LEGACY);` to `config.AllowLegacy();`.

Example: Migrating from V2 to V3 with KMS Encryption

Pre-migration (V2)

```
// Create encryption materials
```

```
auto materials = Aws::MakeShared<KMSWithContextEncryptionMaterials>("s3EncryptionV2",
 CUSTOMER_MASTER_KEY_ID);

// Create V2 crypto configuration
CryptoConfigurationV2 cryptoConfig(materials);

// Create V2 encryption client
S3EncryptionClientV2 encryptionClient(cryptoConfig);

// Put object with encryption context
Aws::Map<Aws::String, Aws::String> encryptionContext;
encryptionContext.emplace("client", "aws-sdk-cpp");
encryptionContext.emplace("version", "1.11.0");

PutObjectRequest putObjectRequest;
putObjectRequest.SetBucket(BUCKET_NAME);
putObjectRequest.SetKey(OBJECT_KEY);
// Set object body...

auto putOutcome = encryptionClient.PutObject(putObjectRequest, encryptionContext);

// Get object with encryption context
GetObjectRequest getObjectRequest;
getObjectRequest.SetBucket(BUCKET_NAME);
getObjectRequest.SetKey(OBJECT_KEY);

auto getOutcome = encryptionClient.GetObject(getObjectRequest, encryptionContext);
```

During migration (V3 with backward compatibility)

```
// Create encryption materials
auto materials = Aws::MakeShared<KMSWithContextEncryptionMaterials>("s3EncryptionV3",
 CUSTOMER_MASTER_KEY_ID);

// Create V3 crypto configuration with materials
CryptoConfigurationV3 cryptoConfig(materials);

// Set commitment policy to maintain compatibility with V2 encrypted objects
// This allows V3 clients to decrypt objects encrypted by the V2 client
cryptoConfig.SetCommitmentPolicy(CommitmentPolicy::REQUIRE_ENCRYPT_ALLOW_DECRYPT);

// Create V3 encryption client
S3EncryptionClientV3 encryptionClient(cryptoConfig);
```

```
// Put object with encryption context
Aws::Map<Aws::String, Aws::String> encryptionContext;
encryptionContext.emplace("client", "aws-sdk-cpp");
encryptionContext.emplace("version", "1.11.0");

PutObjectRequest putObjectRequest;
putObjectRequest.SetBucket(BUCKET_NAME);
putObjectRequest.SetKey(OBJECT_KEY);
// Set object body...

auto putOutcome = encryptionClient.PutObject(putObjectRequest, encryptionContext);

// Get object with encryption context
GetObjectRequest getObjectRequest;
getObjectRequest.SetBucket(BUCKET_NAME);
getObjectRequest.SetKey(OBJECT_KEY);

auto getOutcome = encryptionClient.GetObject(getObjectRequest, encryptionContext);
```

Post-migration (V3 with key commitment)

```
// Create encryption materials
auto materials = Aws::MakeShared<KMSWithContextEncryptionMaterials>("s3EncryptionV3",
 CUSTOMER_MASTER_KEY_ID);

// Create V3 crypto configuration with materials
CryptoConfigurationV3 cryptoConfig(materials);

// Use the default commitment policy (REQUIRE_ENCRYPT_REQUIRE_DECRYPT)
// This encrypts with key commitment and does not decrypt V2 objects
// cryptoConfig.SetCommitmentPolicy(CommitmentPolicy::REQUIRE_ENCRYPT_ALLOW_DECRYPT);

// Create V3 encryption client
S3EncryptionClientV3 encryptionClient(cryptoConfig);

// Put object with encryption context
Aws::Map<Aws::String, Aws::String> encryptionContext;
encryptionContext.emplace("client", "aws-sdk-cpp");
encryptionContext.emplace("version", "1.11.0");

PutObjectRequest putObjectRequest;
putObjectRequest.SetBucket(BUCKET_NAME);
```

```
putObjectRequest.SetKey(OBJECT_KEY);
// Set object body...

auto putOutcome = encryptionClient.PutObject(putObjectRequest, encryptionContext);

// Get object with encryption context
GetObjectRequest getObjectRequest;
getObjectRequest.SetBucket(BUCKET_NAME);
getObjectRequest.SetKey(OBJECT_KEY);

auto getOutcome = encryptionClient.GetObject(getObjectRequest, encryptionContext);
```

Additional Examples

This section provides additional examples for configuring V3 encryption client options to support various migration scenarios and requirements.

Enabling Legacy Support

V3 clients can decrypt objects encrypted by V2 clients only when using the `REQUIRE_ENCRYPT_ALLOW_DECRYPT` or `FORBID_ENCRYPT_ALLOW_DECRYPT` commitment policies. However, if you need to decrypt objects encrypted by V1 clients, you must explicitly enable legacy support using the `AllowLegacy()` method.

When to use legacy support:

- You have objects in S3 that were encrypted using V1 of the S3 Encryption Client.
- You need to read these V1-encrypted objects with your V3 client during the migration process.
- You are using the `REQUIRE_ENCRYPT_ALLOW_DECRYPT` or `FORBID_ENCRYPT_ALLOW_DECRYPT` commitment policy.

> **⚠ Warning**
>
> Legacy support should only be enabled temporarily during migration. Once all V1 objects have been re-encrypted with V2 or V3, disable legacy support to ensure maximum security.

Example: Enabling Legacy Support

```
// Create encryption materials
```

```
auto materials = Aws::MakeShared<KMSWithContextEncryptionMaterials>("s3EncryptionV3",
 CUSTOMER_MASTER_KEY_ID);

// Create V3 crypto configuration
CryptoConfigurationV3 cryptoConfig(materials);

// Enable legacy support to read V1 encrypted objects
cryptoConfig.AllowLegacy();

// Set commitment policy (default is REQUIRE_ENCRYPT_REQUIRE_DECRYPT but we need to
 allow decryption)
cryptoConfig.SetCommitmentPolicy(CommitmentPolicy::REQUIRE_ENCRYPT_ALLOW_DECRYPT);

// Create V3 encryption client with legacy support enabled
S3EncryptionClientV3 encryptionClient(cryptoConfig);

// Now you can decrypt objects encrypted by V1, V2, and V3 clients
GetObjectRequest getObjectRequest;
getObjectRequest.SetBucket(BUCKET_NAME);
getObjectRequest.SetKey(LEGACY_OBJECT_KEY);

Aws::Map<Aws::String, Aws::String> encryptionContext;
auto getOutcome = encryptionClient.GetObject(getObjectRequest, encryptionContext);
```

Configuring Storage Method

The S3 Encryption Client can store encryption metadata in two ways: as object metadata (the default) or in a separate Instruction File. You can configure the storage method using the `SetStorageMethod()` method on `CryptoConfigurationV3`.

Storage method options:

`METADATA` (Default)

Encryption metadata is stored in the object's metadata headers. This is the most common and convenient method as all encryption information is stored with the object itself.

When to use: Use this method for most scenarios. It simplifies object management since encryption metadata travels with the object.

`INSTRUCTION_FILE`

Encryption metadata is stored in a separate S3 object (the Instruction File) with the suffix `.instruction`.

When to use: Use this method when object metadata size is a concern or when you need to separate encryption metadata from the encrypted object. Note that using Instruction Files requires managing two S3 objects (the encrypted object and its instruction file) instead of one.

Example: Configuring Storage Method

```
// Create encryption materials
auto materials = Aws::MakeShared<KMSWithContextEncryptionMaterials>("s3EncryptionV3",
 CUSTOMER_MASTER_KEY_ID);

// Create V3 crypto configuration
CryptoConfigurationV3 cryptoConfig(materials);

// Option 1: Use metadata storage (default, can be omitted)
cryptoConfig.SetStorageMethod(StorageMethod::METADATA);

// Option 2: Use instruction file storage
cryptoConfig.SetStorageMethod(StorageMethod::INSTRUCTION_FILE);

// Create V3 encryption client with the configured storage method
S3EncryptionClientV3 encryptionClient(cryptoConfig);

// Put object - encryption metadata will be stored according to the configured method
Aws::Map<Aws::String, Aws::String> encryptionContext;
encryptionContext.emplace("client", "aws-sdk-cpp");

PutObjectRequest putObjectRequest;
putObjectRequest.SetBucket(BUCKET_NAME);
putObjectRequest.SetKey(OBJECT_KEY);
// Set object body...

auto putOutcome = encryptionClient.PutObject(putObjectRequest, encryptionContext);

// If using INSTRUCTION_FILE, a separate object with key "OBJECT_KEY.instruction" will
 be created
```

Note

When using the `INSTRUCTION_FILE` storage method, remember that deleting the encrypted object does not automatically delete the instruction file. You must manage both objects separately.

Document history for the AWS SDK for C++ Developer Guide

This topic lists important changes to the AWS SDK for C++ Developer Guide. For notification about updates to this documentation, you can subscribe to an RSS feed.

Change	Description	Date
Client configuration options	Updated listing of client configuration variables.	September 8, 2025
Updates to memory management and table of contents	Updated memory management parameters to latest. Standardized table of contents to be more consisten t across AWS SDKs.	March 14, 2025
Amazon S3 Encryption Client V3 Migration	Added information about migrating from V2 to V3 of the Amazon S3 encryption client.	December 2, 2024
Custom libcrypto	Added content for custom libcrypto usage. Removed CMake maximum limitatio n. Updated available CMake parameters.	February 20, 2024
Table of contents	Updated table of contents to make code examples more accessible.	June 1, 2023
IAM best practices updates	Updated guide to align with the IAM best practices . For more information, see Security best practices in IAM.	March 1, 2023

Removing nuget	Removing mention of nuget as a viable package manager option because the latest version available is too old.	December 2, 2022
Updates to Getting Started	Updated vcpkg content to clearly communicate that is not supported by AWS and is an external option. Updated instructions on building the SDK for Windows with curl.	October 18, 2022
Updates to `ClientConfiguration`	Updated the structure of the `ClientConfiguration` to accurately reflect latest API.	September 22, 2022
Improvements to Getting Started	Improved clarity of getting started instructions for building the SDK on Windows and Linux.	June 24, 2022
Windows curl Support	Added notes about building the SDK for Windows with curl.	June 15, 2022
Retiring EC2-Classic	Added notes about retiring EC2-Classic.	April 13, 2022
Enabling SDK Metrics	Removed information about enabling SDK metrics, which has been deprecated.	January 20, 2022
Working with AWS services	Included lists of the code examples that are available on GitHub in the Code Examples repository.	January 11, 2022

Improvements	Improvements to Getting started section, Code examples section, and general standardization.	June 9, 2021
Version update	Reflected the update to general release version of SDK to 1.9.	April 20, 2021
Getting started using the AWS SDK for C++	Updated section with new organization and details.	March 17, 2021
Amazon S3 Encryption Client Migration	Added information about how to migrate your applications from V1 to V2 of the Amazon S3 encryption client.	August 7, 2020
Security Content	Added security content.	February 6, 2020
Creating, listing, and deleting buckets	Updated the Amazon S3 `CreateBucket` example to support AWS Regions.	June 20, 2019
Build instructions	Updated the SDK build instructions.	April 16, 2019
Asynchronous methods	Added new section.	April 16, 2019
Service Client Classes	Various updates.	April 5, 2019
Managing Amazon S3 Access Permissions	Various updates.	April 3, 2019
Updates for building and for configuration variables	Updated the instructions for building the SDK. Updated the available AWS Client Configuration variables.	March 1, 2019

vcpkg C++ package manager	Updated the instructions for setting up the *vcpkg* C++ package manager.	January 19, 2019